

# The L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> Sources

Johannes Braams  
David Carlisle  
Alan Jeffrey  
Leslie Lamport  
Frank Mittelbach  
Chris Rowley  
Rainer Schöpf

2025-11-01 Patch level -4

This file is maintained by the L<sup>A</sup>T<sub>E</sub>X Project team.  
Bug reports can be opened (category `latex`) at  
<https://latex-project.org/bugs.html>.

## Contents

<b>01</b>	<b>ltdirchk.dtx</b>	<b>1</b>
<b>1</b>	<b>L<sup>A</sup>T<sub>E</sub>X System Dependent Initializations</b>	<b>1</b>
<b>2</b>	<b>Initialization</b>	<b>2</b>
2.1	INITEX . . . . .	3
2.2	Some bits of 2e . . . . .	4
<b>3</b>	<b>texsys.cfg</b>	<b>5</b>
3.1	texsys.cfg . . . . .	5
3.2	UNIX (web2c) . . . . .	6
3.3	UNIX (other) . . . . .	7
3.4	MSDOS (emtex) . . . . .	7
3.5	MSDOS (other) . . . . .	7
3.6	VMS (DECUS T <sub>E</sub> X, PD VMS 3.6) . . . . .	7
3.7	VMS (???) . . . . .	7
3.8	MACINTOSH (OzT <sub>E</sub> X 1.6) . . . . .	8
3.9	MACINTOSH (other) . . . . .	8
3.10	FAKE EXAMPLE . . . . .	8
<b>4</b>	<b>Setting \@currdir</b>	<b>9</b>
<b>5</b>	<b>Setting \input@path</b>	<b>10</b>

<b>6</b>	<b>Filename Parsing</b>	<b>11</b>
<b>7</b>	<b>T<sub>E</sub>X Versions</b>	<b>13</b>
<b>8</b>	<b>ltxcheck.tex</b>	<b>13</b>
<b>02</b>	<b>lplain.dtx</b>	<b>14</b>
<b>1</b>	<b>Plain T<sub>E</sub>X</b>	<b>14</b>
<b>03</b>	<b>ltvers.dtx</b>	<b>35</b>
<b>1</b>	<b>Version Identification</b>	<b>35</b>
1.1	Declaring an all-new module . . . . .	38
<b>04</b>	<b>lualatex.dtx</b>	<b>40</b>
<b>1</b>	<b>Overview</b>	<b>40</b>
<b>2</b>	<b>Core T<sub>E</sub>X functionality</b>	<b>40</b>
<b>3</b>	<b>Plain T<sub>E</sub>X interface</b>	<b>41</b>
<b>4</b>	<b>Lua functionality</b>	<b>41</b>
4.1	Allocators in Lua . . . . .	41
4.2	Lua access to T <sub>E</sub> X register numbers . . . . .	42
4.3	Module utilities . . . . .	43
4.4	Callback management . . . . .	43
<b>5</b>	<b>Implementation</b>	<b>44</b>
5.1	Minimum LuaT <sub>E</sub> X version . . . . .	44
5.2	Older L <sup>A</sup> T <sub>E</sub> X/Plain T <sub>E</sub> X setup . . . . .	45
5.2.1	Fixes to <code>etex.src/etex.sty</code> . . . . .	45
5.2.2	luatex specific settings . . . . .	46
5.3	Attributes . . . . .	47
5.4	Category code tables . . . . .	47
5.5	Named Lua functions . . . . .	49
5.6	Custom whatsits . . . . .	49
5.7	Lua bytecode registers . . . . .	50
5.8	Lua chunk registers . . . . .	50
5.9	Lua loader . . . . .	50
5.10	Lua module preliminaries . . . . .	52
5.11	Lua module utilities . . . . .	52
5.11.1	Module tracking . . . . .	52
5.11.2	Module messages . . . . .	53
5.12	Accessing register numbers from Lua . . . . .	54
5.13	Attribute allocation . . . . .	55
5.14	Custom whatsit allocation . . . . .	56

5.15	Bytecode register allocation	56
5.16	Lua chunk name allocation	56
5.17	Lua function allocation	57
5.18	Lua callback management	57
5.18.1	Housekeeping	57
5.18.2	Handlers	62
5.18.3	Public functions for callback management	65
<b>05</b>	<b>ltxexpl.dtx</b>	<b>71</b>
<b>1</b>	<b>expl3-dependent code</b>	<b>71</b>
1.1	Loader	71
1.2	Using expl3 code	74
<b>2</b>	<b>Document-level command names for expl3 functions</b>	<b>75</b>
<b>06</b>	<b>ltxdefns.dtx</b>	<b>78</b>
<b>1</b>	<b>Definitions</b>	<b>78</b>
1.1	Initex initializations	78
1.2	Saved versions of TeX primitives	78
1.3	Command definitions	79
1.4	Robust commands and protect	89
1.5	Acting on robust commands	96
1.5.1	Copying robust commands	98
1.5.2	Showing robust commands	101
1.5.3	Commands defined with <code>\DeclareRobustCommand</code>	101
1.5.4	Commands defined with <code>\newcommand</code> (with optional argument)	103
1.5.5	Showing environments	105
1.6	Internal defining commands	106
<b>2</b>	<b>Discretionary Hyphenation</b>	<b>110</b>
<b>07</b>	<b>ltxcmd.dtx</b>	<b>113</b>
<b>1</b>	<b>Creating document commands</b>	<b>113</b>
1.1	Variables and constants	113
1.2	Declaring commands and environments	117
1.3	Structure of xparse commands	123
1.4	Normalizing the argument specifications	127
1.5	Preparing the signature: general mechanism	136
1.6	Setting up a standard signature	137
1.7	Setting up expandable types	142
1.7.1	Copying a command and its internal structure	145
1.7.2	Showing the definition of a command	151
1.8	Grabbing arguments	157
1.9	Grabbing arguments expandably	174
1.10	Argument processors	180

1.11	Conversion to key-value form	182
1.12	Utilities	185
1.13	Access to the argument specification	189
1.14	Messages	189
1.15	User functions	195
<b>08</b>	<b>lthooks.dtx</b>	<b>201</b>
<b>1</b>	<b>Introduction</b>	<b>201</b>
<b>2</b>	<b>Package writer interface</b>	<b>201</b>
2.1	L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> interfaces	201
2.1.1	Declaring hooks	201
2.1.2	Special declarations for generic hooks	202
2.1.3	Using hooks in code	203
2.1.4	Updating code for hooks	204
2.1.5	Hook names and default labels	207
2.1.6	The <code>top-level</code> label	209
2.1.7	Defining relations between hook code	209
2.1.8	Querying hooks	211
2.1.9	Displaying hook code	212
2.1.10	Debugging hook code	213
2.2	L3 programming layer ( <code>expl3</code> ) interfaces	213
2.3	On the order of hook code execution	216
2.4	The use of “reversed” hooks	218
2.5	Difference between “normal” and “one-time” hooks	219
2.6	Generic hooks provided by packages	219
2.7	Hooks with arguments	220
2.8	Private L <sup>A</sup> T <sub>E</sub> X kernel hooks	222
2.9	Legacy L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> interfaces	222
<b>3</b>	<b>L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> commands and environments augmented by hooks</b>	<b>223</b>
3.1	Generic hooks	223
3.1.1	Generic hooks for all environments	224
3.1.2	Generic hooks for commands	225
3.1.3	Generic hooks provided by file loading operations	225
3.2	Hooks provided by <code>\begin{document}</code>	226
3.3	Hooks provided by <code>\end{document}</code>	226
3.4	Hooks provided by <code>\shipout</code> operations	228
3.5	Hooks provided for paragraphs	228
3.6	Hooks provided in NFSS commands	228
3.7	Hook provided by the mark mechanism	229

<b>4</b>	<b>The Implementation</b>	<b>229</b>
4.1	Debugging	229
4.2	Borrowing from internals of other kernel modules	230
4.3	Declarations	230
4.4	Providing new hooks	232
4.4.1	The data structures of a hook	232
4.4.2	On the existence of hooks	233
4.4.3	Setting hooks up	234
4.4.4	Disabling and providing hooks	240
4.5	Parsing a label	242
4.6	Adding or removing hook code	246
4.7	Setting rules for hooks code	267
4.8	Specifying code for next invocation	289
4.9	Using the hook	291
4.10	Querying a hook	297
4.11	Messages	301
4.12	L <sup>A</sup> T <sub>ε</sub> X package interface commands	304
4.13	Deprecated that needs cleanup at some point	307
4.14	Internal commands needed elsewhere	309
<b>09</b>	<b>ltcmdhooks.dtx</b>	<b>311</b>
<b>1</b>	<b>Introduction</b>	<b>311</b>
<b>2</b>	<b>Restrictions and Operational details</b>	<b>312</b>
2.1	Patching	313
2.1.1	Timing	313
2.2	Commands that look ahead	313
<b>3</b>	<b>Package Author Interface</b>	<b>314</b>
3.1	Arguments and redefining commands	315
<b>4</b>	<b>The Implementation</b>	<b>315</b>
4.1	Execution plan	315
4.2	Variables	316
4.3	Variants	317
4.4	Patching or delaying	317
4.5	Patching commands	319
4.5.1	Patching by expansion and redefinition	320
4.5.2	Patching by retokenization	328
4.6	Messages	335
<b>10</b>	<b>ltsockets.dtx</b>	<b>337</b>
<b>1</b>	<b>Introduction</b>	<b>337</b>

<b>2</b>	<b>Configuration of the transformation process</b>	<b>337</b>
2.1	The template mechanism . . . . .	337
2.2	The hook mechanism . . . . .	338
2.3	The socket mechanism . . . . .	338
2.3.1	Examples . . . . .	340
2.3.2	Details and semantics . . . . .	341
2.3.3	Command syntax . . . . .	343
2.3.4	Rationale for error handling . . . . .	345
<b>3</b>	<b>The Implementation</b>	<b>345</b>
3.1	Debugging the socket structures . . . . .	345
3.2	The L3 layer commands . . . . .	346
3.3	Error messages . . . . .	350
3.4	The L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> interface commands . . . . .	350
<b>11</b>	<b>lttemplates.dtx</b>	<b>352</b>
<b>1</b>	<b>Introduction</b>	<b>352</b>
<b>2</b>	<b>What is a document?</b>	<b>352</b>
<b>3</b>	<b>Types, templates, and instances</b>	<b>353</b>
<b>4</b>	<b>Template types</b>	<b>353</b>
<b>5</b>	<b>Templates</b>	<b>353</b>
<b>6</b>	<b>Multiple choices</b>	<b>357</b>
<b>7</b>	<b>Instances</b>	<b>358</b>
<b>8</b>	<b>Document interface</b>	<b>359</b>
<b>9</b>	<b>Changing existing definitions</b>	<b>360</b>
9.1	Expanding the values of keys . . . . .	360
<b>10</b>	<b>Getting information about templates and instances</b>	<b>361</b>
<b>11</b>	<b>The implementation</b>	<b>361</b>
11.1	Variables and constants . . . . .	362
11.2	Testing existence and validity . . . . .	364
11.3	Saving and recovering property lists . . . . .	365
11.4	Creating new template types . . . . .	367
11.5	Design part of template declaration . . . . .	368
11.5.1	Storing values . . . . .	371
11.6	Implementation part of template declaration . . . . .	372
11.7	Editing template defaults . . . . .	377
11.8	Creating instances of templates . . . . .	379
11.9	Using templates directly . . . . .	382
11.10	Assigning values to variables . . . . .	382
11.11	Using instances . . . . .	385

11.12	Assignment manipulation . . . . .	386
11.13	Showing templates and instances . . . . .	386
11.14	Messages . . . . .	387
11.15	User functions . . . . .	391
<b>12</b>	<b>ltdll.dtx</b>	<b>394</b>
<b>1</b>	<b>Counters</b>	<b>394</b>
<b>13</b>	<b>ltdl.dtx</b>	<b>396</b>
<b>1</b>	<b>Program control structure</b>	<b>396</b>
<b>14</b>	<b>ltderr.dtx</b>	<b>400</b>
<b>1</b>	<b>Error handling and tracing</b>	<b>400</b>
1.1	General commands . . . . .	400
1.2	Specific errors . . . . .	406
1.3	Tracing . . . . .	410
<b>15</b>	<b>ltdpar.dtx</b>	<b>411</b>
<b>1</b>	<b>Paragraphs</b>	<b>411</b>
1.1	Implementation . . . . .	411
<b>16</b>	<b>ltdpara.dtx</b>	<b>413</b>
<b>1</b>	<b>Introduction</b>	<b>413</b>
1.1	The default processing done by the engine . . . . .	413
<b>2</b>	<b>The new mechanism implemented for L<sup>A</sup>T<sub>E</sub>X</b>	<b>415</b>
2.1	The provided hooks . . . . .	416
2.2	Altered and newly provided commands . . . . .	417
2.3	Examples . . . . .	418
2.3.1	Testing the mechanism . . . . .	418
2.3.2	Mark the first paragraph of each <code>itemize</code> . . . . .	420
2.4	Some technical notes . . . . .	420
2.4.1	Glue items between paragraphs (found with <code>fancypar</code> ) . . . . .	420
<b>3</b>	<b>The Implementation</b>	<b>421</b>
3.1	Providing hooks for paragraphs . . . . .	421
3.2	The error messages . . . . .	428
<b>17</b>	<b>ltdmeta.dtx</b>	<b>430</b>

<b>1</b>	<b>Introduction</b>	<b>430</b>
1.1	<code>\DocumentMetadata</code> . . . . .	430
<b>2</b>	<b>The Implementation</b>	<b>430</b>
<b>18</b>	<b>ltspace.dtx</b>	<b>433</b>
<b>1</b>	<b>Spacing</b>	<b>433</b>
1.1	User Commands . . . . .	433
1.2	Chris' comments . . . . .	433
1.3	Some immediate actions . . . . .	435
1.4	The code . . . . .	436
1.5	Vertical spacing . . . . .	443
1.6	Horizontal space (and breaks) . . . . .	449
<b>19</b>	<b>ltlogos.dtx</b>	<b>453</b>
<b>1</b>	<b>Logos</b>	<b>453</b>
<b>20</b>	<b>ltfiles.dtx</b>	<b>454</b>
<b>1</b>	<b>File Handling</b>	<b>454</b>
1.1	Safe Input Macros . . . . .	468
1.2	Listing files . . . . .	475
<b>21</b>	<b>ltoutenc.dtx</b>	<b>478</b>
<b>1</b>	<b>Font encodings</b>	<b>478</b>
1.1	Removing encoding-specific commands . . . . .	480
1.2	The order of declarations . . . . .	481
1.3	Docstrip modules . . . . .	481
1.4	Definitions for the kernel . . . . .	482
1.4.1	Declaration commands . . . . .	482
1.4.2	Hyphenation . . . . .	490
1.4.3	Miscellania . . . . .	491
1.4.4	Default encodings . . . . .	491
1.4.5	Math material . . . . .	493
1.5	Definitions for the OT1 encoding . . . . .	494
1.6	Definitions for the T1 encoding . . . . .	497
1.7	Definitions for the OMS encoding . . . . .	503
1.8	Definitions for the OML encoding . . . . .	503
1.9	Definitions for the OT4 encoding . . . . .	503
1.10	Definitions for the TS1 encoding . . . . .	506
1.11	Definitions for the TU encoding . . . . .	510
<b>2</b>	<b>Package files</b>	<b>521</b>
2.1	The fontenc package . . . . .	521

<b>22</b>	<b>ltcounts.dtx</b>	<b>525</b>
<b>1</b>	<b>Counters and Lengths</b>	<b>525</b>
1.1	Document command and environment counter macros . . . . .	525
<b>23</b>	<b>ltnlength.dtx</b>	<b>536</b>
<b>1</b>	<b>Lengths</b>	<b>536</b>
<b>24</b>	<b>ltfssbas.dtx</b>	<b>538</b>
<b>1</b>	<b>Preliminary macros</b>	<b>538</b>
<b>2</b>	<b>Macros for setting up the tables</b>	<b>539</b>
<b>3</b>	<b>Selecting a new font</b>	<b>548</b>
3.1	Macros for the user . . . . .	548
3.2	Macros for loading fonts . . . . .	554
<b>4</b>	<b>Assigning math fonts to <i>versions</i></b>	<b>561</b>
<b>25</b>	<b>ltfssaxes.dtx</b>	<b>568</b>
<b>1</b>	<b>Changing the font series</b>	<b>568</b>
1.1	The series lookup table . . . . .	568
1.2	Mapping rules for series changes . . . . .	569
1.3	Changing to a new series . . . . .	623
<b>2</b>	<b>Changing the shape</b>	<b>627</b>
2.1	Mapping rules for shape combinations . . . . .	629
2.2	Changing to a new shape . . . . .	633
<b>3</b>	<b>Make sure we win ...</b>	<b>635</b>
<b>26</b>	<b>ltfssstrc.dtx</b>	<b>638</b>
<b>1</b>	<b>Introduction</b>	<b>638</b>
<b>2</b>	<b>A driver for this document</b>	<b>638</b>
<b>3</b>	<b>The Implementation</b>	<b>639</b>
<b>4</b>	<b>Handling Options</b>	<b>639</b>

<b>5</b>	<b>Macros common to fam.tex and tracefmt.sty</b>	<b>641</b>
5.1	General font loading . . . . .	641
5.2	Math fonts setup . . . . .	647
5.2.1	Outline of algorithm for math font sizes . . . . .	647
5.2.2	Code for math font size setting . . . . .	648
5.2.3	Other code for math . . . . .	649
<b>6</b>	<b>Scaled font extraction</b>	<b>652</b>
6.1	Sizefunctions . . . . .	660
<b>27</b>	<b>lffscmp.dtx</b>	<b>664</b>
<b>28</b>	<b>lffsdcl.dtx</b>	<b>669</b>
<b>1</b>	<b>Interface Commands</b>	<b>669</b>
<b>29</b>	<b>lffssini.dtx</b>	<b>702</b>
<b>1</b>	<b>NFSS Initialization</b>	<b>702</b>
1.1	Providing math <i>versions</i> . . . . .	702
<b>2</b>	<b>Custom series settings for main document families</b>	<b>703</b>
<b>3</b>	<b>Supporting nested emphasis</b>	<b>722</b>
3.1	Legacy . . . . .	725
3.2	Miscellaneous . . . . .	726
<b>30</b>	<b>fontdef.dtx</b>	<b>732</b>
<b>1</b>	<b>Introduction</b>	<b>732</b>
<b>2</b>	<b>Customization</b>	<b>732</b>
<b>3</b>	<b>The docstrip modules</b>	<b>733</b>
<b>4</b>	<b>A driver for this document</b>	<b>733</b>
<b>5</b>	<b>The fonttext.ltx file</b>	<b>733</b>
5.1	Encodings . . . . .	734
5.2	Defaults . . . . .	736

<b>6</b>	<b>The fontmath.ltx file</b>	<b>738</b>
6.1	The font encodings used . . . . .	738
6.1.1	Symbolfont and Alphabet declarations . . . . .	739
6.2	Math font sizes . . . . .	739
6.3	The math symbol assignments . . . . .	740
6.3.1	The letters . . . . .	740
6.3.2	The digits . . . . .	741
6.3.3	Punctuation, brace, etc. keys . . . . .	741
6.3.4	Delimitercodes for characters . . . . .	742
6.4	Symbols accessed via control sequences . . . . .	742
6.4.1	Greek letters . . . . .	742
6.4.2	Ordinary symbols . . . . .	743
6.4.3	Large Operators . . . . .	744
6.4.4	Binary symbols . . . . .	744
6.4.5	Relations . . . . .	745
6.4.6	Arrows . . . . .	747
6.4.7	Punctuation symbols . . . . .	747
6.4.8	Math accents . . . . .	748
6.4.9	Radicals . . . . .	748
6.4.10	Over and under something, etc . . . . .	748
6.4.11	Delimiters . . . . .	749
6.5	Math versions of text commands . . . . .	750
6.6	Other special functions and parameters . . . . .	751
6.6.1	Biggggg . . . . .	751
6.6.2	The log-like functions . . . . .	751
6.6.3	Parameters . . . . .	751
<b>7</b>	<b>Default cfg files</b>	<b>751</b>
<b>31</b>	<b>preload.dtx</b>	<b>753</b>
<b>1</b>	<b>Overview</b>	<b>753</b>
<b>2</b>	<b>Customization</b>	<b>753</b>
<b>3</b>	<b>Module switches for the DOCSTRIP program</b>	<b>753</b>
<b>4</b>	<b>A driver for this document</b>	<b>754</b>
<b>5</b>	<b>The code</b>	<b>754</b>
<b>32</b>	<b>lftntcmd.dtx</b>	<b>756</b>
<b>1</b>	<b>Introduction</b>	<b>756</b>
<b>2</b>	<b>The implementation</b>	<b>758</b>
<b>3</b>	<b>Initialization</b>	<b>764</b>

<b>33</b>	<b>ltxtextcomp.dtx</b>	<b>765</b>
<b>1</b>	<b>Sub-encodings</b>	<b>767</b>
1.1	Unavailable in sub-encoding 1 and higher (drop symbols not working in Latin Modern) . . . . .	769
1.2	Unavailable in sub-encoding 2 (majority of new OTF fonts via autotinst) and higher . . . . .	769
1.3	Unavailable in sub-encoding 3 and higher . . . . .	772
1.4	Unavailable in sub-encoding 4 and higher . . . . .	772
1.5	Unavailable in sub-encoding 5 (most older PS fonts) and higher . . . .	773
1.6	Unavailable in sub-encoding 6 and higher . . . . .	773
1.7	Unavailable in sub-encoding 7 and higher . . . . .	773
1.8	Unavailable in sub-encoding 8 and higher . . . . .	773
1.9	Unavailable in Sub-encoding 9 (most missing) . . . . .	774
<b>2</b>	<b>Unicode engine specials</b>	<b>774</b>
<b>3</b>	<b>Font family sub-encodings setup</b>	<b>775</b>
<b>4</b>	<b>Legacy symbol support for lists and footnote symbols</b>	<b>779</b>
<b>5</b>	<b>The textcomp package</b>	<b>784</b>
5.1	The old textcomp package code . . . . .	785
5.1.1	Supporting oldstyle digits . . . . .	794
5.1.2	Subset encoding defaults . . . . .	794
<b>6</b>	<b>The checkencodingssubset.tex file</b>	<b>796</b>
<b>34</b>	<b>ltxpageno.dtx</b>	<b>805</b>
<b>1</b>	<b>Page Numbering</b>	<b>805</b>
<b>35</b>	<b>ltxref.dtx</b>	<b>806</b>
<b>1</b>	<b>Cross Referencing</b>	<b>806</b>
1.1	Cross Referencing . . . . .	806
<b>36</b>	<b>ltxproperties.dtx</b>	<b>814</b>
<b>1</b>	<b>Introduction</b>	<b>814</b>
<b>2</b>	<b>Design discussion</b>	<b>814</b>
<b>3</b>	<b>Handling unknown labels and properties</b>	<b>815</b>
<b>4</b>	<b>Rerun messages</b>	<b>815</b>
<b>5</b>	<b>Open points</b>	<b>815</b>

<b>6</b>	<b>Code interfaces</b>	<b>815</b>
<b>7</b>	<b>Auxiliary file interfaces</b>	<b>817</b>
<b>8</b>	<b>L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interface</b>	<b>817</b>
<b>9</b>	<b>Pre-declared properties</b>	<b>818</b>
<b>10</b>	<b>The Implementation</b>	<b>819</b>
10.1	Reference commands . . . . .	821
10.2	Tests and warnings . . . . .	823
10.3	Predeclared properties . . . . .	825
10.4	Messages . . . . .	827
<b>37</b>	<b>ltmiscen.dtx</b>	<b>828</b>
<b>1</b>	<b>Miscellaneous Environments</b>	<b>828</b>
1.1	Environments . . . . .	828
1.2	Center, Flushright, Flushleft . . . . .	842
1.3	Verbatim . . . . .	845
<b>38</b>	<b>ltmath.dtx</b>	<b>853</b>
<b>1</b>	<b>Math setup</b>	<b>853</b>
1.1	Math commands based on plain T <sub>E</sub> X . . . . .	853
1.1.1	The log-like functions . . . . .	853
1.1.2	Biggggg . . . . .	854
1.1.3	The UNSORTED Rest . . . . .	854
1.2	Math Environments . . . . .	861
1.3	External options to the standard document classes . . . . .	868
1.3.1	Left equation numbering . . . . .	868
1.3.2	Flush left equations . . . . .	868
<b>39</b>	<b>ltlists.dtx</b>	<b>871</b>
<b>1</b>	<b>List, and related environments</b>	<b>871</b>
1.1	List and Trivlist . . . . .	872
1.2	Vertical Spacing (skips) . . . . .	873
1.3	Penalties . . . . .	873
1.4	Horizontal Spacing (dimens) . . . . .	873
1.5	Default Values . . . . .	873
1.6	Itemize and Enumerate . . . . .	886
<b>40</b>	<b>ltboxes.dtx</b>	<b>889</b>
<b>1</b>	<b>L<sup>A</sup>T<sub>E</sub>X Box commands</b>	<b>889</b>
1.1	Some low-level constructs . . . . .	907

<b>41</b>	<b>lttab.dtx</b>	<b>908</b>
<b>1</b>	<b>Tabbing, Tabular and Array Environments</b>	<b>908</b>
1.1	tabbing . . . . .	908
1.2	array and tabular environments . . . . .	917
<b>42</b>	<b>ltpictur.dtx</b>	<b>933</b>
<b>1</b>	<b>Picture Mode</b>	<b>933</b>
1.1	Curves . . . . .	960
<b>43</b>	<b>ltthm.dtx</b>	<b>965</b>
<b>1</b>	<b>Theorem Environments</b>	<b>965</b>
<b>44</b>	<b>ltsect.dtx</b>	<b>969</b>
<b>1</b>	<b>Sectioning Commands</b>	<b>969</b>
1.1	The Title . . . . .	969
1.2	Sectioning . . . . .	970
1.2.1	Initializations . . . . .	977
1.3	Table of Contents etc. . . . .	977
1.3.1	Convention . . . . .	977
1.3.2	Commands . . . . .	977
<b>45</b>	<b>ltfloat.dtx</b>	<b>983</b>
<b>1</b>	<b>Floats</b>	<b>983</b>
1.1	Floating Environments . . . . .	983
1.2	Footnotes . . . . .	997
<b>46</b>	<b>ltxglo.dtx</b>	<b>1006</b>
<b>1</b>	<b>Index and Glossary Generation</b>	<b>1006</b>
<b>47</b>	<b>ltbibl.dtx</b>	<b>1009</b>
<b>1</b>	<b>Bibliography Generation</b>	<b>1009</b>
1.1	Default definitions . . . . .	1013
<b>48</b>	<b>ltmarks.dtx</b>	<b>1014</b>
<b>1</b>	<b>Introduction</b>	<b>1014</b>

<b>2</b>	<b>Design-level and code-level interfaces</b>	<b>1015</b>
2.1	Use cases for conditionals . . . . .	1017
2.2	Understanding regions . . . . .	1017
2.3	Debugging mark code . . . . .	1019
<b>3</b>	<b>Application examples</b>	<b>1019</b>
<b>4</b>	<b>Legacy L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interface</b>	<b>1019</b>
4.1	Legacy design-level and document-level interfaces . . . . .	1020
4.2	Legacy interface extensions . . . . .	1020
<b>5</b>	<b>Notes on the mechanism</b>	<b>1021</b>
<b>6</b>	<b>Public interfaces for packages such as multicol</b>	<b>1022</b>
<b>7</b>	<b>Internal functions for the standard output routine of L<sup>A</sup>T<sub>E</sub>X</b>	<b>1023</b>
<b>8</b>	<b>The Implementation</b>	<b>1024</b>
8.1	Allocating new mark classes . . . . .	1024
8.2	Updating mark structures . . . . .	1026
8.3	Placing and retrieving marks . . . . .	1034
8.4	Comparing mark values . . . . .	1036
8.5	Messages . . . . .	1037
8.6	Debugging the mark structures . . . . .	1037
8.7	Designer-level interfaces . . . . .	1039
<b>9</b>	<b>L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> integration</b>	<b>1040</b>
9.1	Core L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> integration . . . . .	1040
9.2	Other L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> output routines . . . . .	1043
9.3	Rollback information . . . . .	1044
<b>49</b>	<b>ltpage.dtx</b>	<b>1045</b>
<b>1</b>	<b>Page styles and related commands</b>	<b>1045</b>
1.1	Page Style Commands . . . . .	1045
1.2	How a page style makes running heads and feet . . . . .	1045
1.3	marking conventions . . . . .	1045
<b>50</b>	<b>ltxclass.dtx</b>	<b>1050</b>
<b>1</b>	<b>Introduction</b>	<b>1050</b>
<b>2</b>	<b>User interface</b>	<b>1050</b>
2.1	Option processing . . . . .	1051

<b>3</b>	<b>Class and Package interface</b>	<b>1052</b>
3.1	Class name and version . . . . .	1052
3.2	Package name and version . . . . .	1052
3.3	Requiring other packages . . . . .	1052
3.4	Declaring new options . . . . .	1054
3.5	Safe Input Macros . . . . .	1054
<b>4</b>	<b>Implementation</b>	<b>1054</b>
4.1	Hooks . . . . .	1084
4.2	Providing shipment . . . . .	1086
<b>5</b>	<b>Package/class rollback mechanism</b>	<b>1094</b>
<b>6</b>	<b>After Preamble</b>	<b>1103</b>
<b>51</b>	<b>ltkeys.dtx</b>	<b>1104</b>
<b>1</b>	<b>Creating and using keyval options</b>	<b>1104</b>
1.1	Implementation of ltkeys . . . . .	1106
1.2	Key properties . . . . .	1106
1.3	Main mechanism . . . . .	1107
1.4	The document interfaces . . . . .	1112
1.5	Option usage scope . . . . .	1113
1.6	General key setting . . . . .	1114
<b>52</b>	<b>ltfilehook.dtx</b>	<b>1115</b>
<b>1</b>	<b>Introduction</b>	<b>1115</b>
1.1	Provided hooks . . . . .	1115
1.2	General hooks for file reading . . . . .	1115
1.3	Hooks for package and class files . . . . .	1116
1.4	Hooks for <code>\include</code> files . . . . .	1117
1.5	High-level interfaces for <code>L<sup>A</sup>T<sub>E</sub>X</code> . . . . .	1118
1.6	Kernel, class, and package interfaces for <code>L<sup>A</sup>T<sub>E</sub>X</code> . . . . .	1119
1.7	A sample package for structuring the log output . . . . .	1119
<b>2</b>	<b>The Implementation</b>	<b>1120</b>
2.1	Document and package-level commands . . . . .	1120
2.2	<code>expl3</code> helpers . . . . .	1121
2.3	Declaring the file-related hooks . . . . .	1124
2.4	Patching <code>L<sup>A</sup>T<sub>E</sub>X</code> 's <code>\InputIfFileExists</code> command . . . . .	1124
2.5	Declaring a file substitution . . . . .	1126
2.6	Selecting a file ( <code>\set@curr@file</code> ) . . . . .	1128
2.7	Replacing a file and detecting loops . . . . .	1131
2.7.1	The Tortoise and Hare algorithm . . . . .	1132
2.8	Preventing a package from loading . . . . .	1134
2.9	High-level interfaces for <code>L<sup>A</sup>T<sub>E</sub>X</code> . . . . .	1135
2.10	Internal commands needed elsewhere . . . . .	1135

<b>3</b>	<b>A sample package for structuring the log output</b>	<b>1136</b>
<b>4</b>	<b>Package emulations</b>	<b>1137</b>
4.1	Package atveryend emulation . . . . .	1137
<b>53</b>	<b>ltshipout.dtx</b>	<b>1139</b>
<b>1</b>	<b>Introduction</b>	<b>1139</b>
1.1	Overloading the <code>\shipout</code> primitive . . . . .	1139
1.2	Provided hooks . . . . .	1140
1.3	Legacy L <sup>A</sup> T <sub>E</sub> X commands . . . . .	1142
1.4	Special commands for use inside the hooks . . . . .	1143
1.5	Provided LuaT <sub>E</sub> X callbacks . . . . .	1143
1.6	Information counters . . . . .	1144
1.7	Debugging shipout code . . . . .	1144
<b>2</b>	<b>Emulating commands from other packages</b>	<b>1145</b>
2.1	Emulating atbegshi . . . . .	1145
2.2	Emulating everyshi . . . . .	1146
2.3	Emulating atenddvi . . . . .	1146
2.4	Emulating everypage . . . . .	1146
<b>3</b>	<b>The Implementation</b>	<b>1147</b>
3.1	Debugging . . . . .	1147
3.2	Handling the end of job hook . . . . .	1159
<b>4</b>	<b>Legacy L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interfaces</b>	<b>1162</b>
<b>5</b>	<b>Internal commands needed elsewhere</b>	<b>1163</b>
<b>6</b>	<b>Package emulation for compatibility</b>	<b>1165</b>
6.1	Package atenddvi emulation . . . . .	1165
6.2	Package atbegshi emulation . . . . .	1166
6.3	Package everyshi emulation . . . . .	1167
<b>54</b>	<b>ltoutput.dtx</b>	<b>1168</b>
<b>1</b>	<b>Output Routine and float handling</b>	<b>1168</b>
1.1	Historical notes on the algorithm and commands . . . . .	1168
1.2	Core definitions . . . . .	1178
1.2.1	Definition of float boxes . . . . .	1178
1.2.2	Page layout parameters . . . . .	1179
1.2.3	Internal registers . . . . .	1181
1.2.4	Page break commands . . . . .	1181

<b>2</b>	<b>The L<sup>A</sup>T<sub>E</sub>X output routine</b>	<b>1186</b>
2.1	Hooks and replaceable code blocks . . . . .	1186
2.1.1	Output routine hooks . . . . .	1186
2.1.2	Replaceable code blocks (sockets) . . . . .	1186
2.1.3	Tagging sockets . . . . .	1188
2.1.4	Output routine commands . . . . .	1189
2.2	The output routine configuration components . . . . .	1200
2.2.1	Dealing with floats . . . . .	1214
2.2.2	Kludgeins . . . . .	1243
2.2.3	Float control . . . . .	1245
2.2.4	Float placement parameters . . . . .	1259
<b>55</b>	<b>ltagging.dtx</b>	<b>1263</b>
<b>1</b>	<b>General support for tagged output</b>	<b>1263</b>
<b>2</b>	<b>Implementation</b>	<b>1265</b>
2.1	Math collection . . . . .	1266
2.2	Tagging sockets . . . . .	1266
2.3	Generic sockets . . . . .	1266
2.3.1	Tagging support for paragraph setup . . . . .	1267
2.3.2	Tagging socket for targets . . . . .	1269
2.3.3	Tagging Sockets for lists and blocks . . . . .	1270
2.3.4	Tagging sockets for headings . . . . .	1270
2.3.5	Tagging sockets for toc . . . . .	1271
2.3.6	Tagging support for marginpar . . . . .	1271
2.3.7	Tagging support for table/tabular packages . . . . .	1271
2.3.8	Tagging Support for floats . . . . .	1272
2.4	Tagging support for output routines . . . . .	1273
2.5	Tagging support for math . . . . .	1273
2.5.1	General sockets . . . . .	1273
2.5.2	Sockets specific for luamml . . . . .	1274
2.6	MathML intent attributes . . . . .	1275
2.7	Symbolic structure names . . . . .	1276
<b>3</b>	<b>For lttab.dtx parked here for now</b>	<b>1276</b>
3.1	Variables for row, column and span counting . . . . .	1276
3.2	Tracing/debugging . . . . .	1277
3.3	Interface commands . . . . .	1277
<b>56</b>	<b>lthyphen.dtx</b>	<b>1282</b>
<b>57</b>	<b>ltfinal.dtx</b>	<b>1284</b>

<b>1</b>	<b>Final settings</b>	<b>1284</b>
1.1	Debugging . . . . .	1284
1.2	Typesetting parameters . . . . .	1284
1.3	Lccodes for hyphenation . . . . .	1288
1.4	Hyphenation . . . . .	1290
1.5	Font loading . . . . .	1291
1.6	Input encoding . . . . .	1292
1.7	Lccodes and uccodes . . . . .	1297
1.8	Case changing . . . . .	1298
1.9	Automatic insertion of <code>\par</code> tokens . . . . .	1300
1.10	Applying Patch files . . . . .	1301
1.11	Freeing Memory . . . . .	1302
1.12	Initialise file list . . . . .	1302
1.13	Preparation for supporting PDF in backends . . . . .	1303
1.14	Do some temporary work for pre-release . . . . .	1303
1.15	Some last minute initializations . . . . .	1303
1.16	Dumping the format . . . . .	1303
	 <b>Change History</b>	 <b>1304</b>
	 <b>Index</b>	 <b>1388</b>

## File 01

# ltdirchk.dtx

## 1 L<sup>A</sup>T<sub>E</sub>X System Dependent Initializations

This file implements the semi-automatic determination of various system dependent parts of the initialization. The actual definitions may be placed in a file `texsys.cfg`. Thus for operating systems for which the tests here do not result in acceptable settings, a ‘hand written’ `texsys.cfg` may be produced.

The macros that must be defined are:

`\@currdir`     `\@currdir{filename}<space>` should expand to a form of the filename that uniquely refers to the ‘current directory’ if this is possible. (The expansion should also end with a space.) on UNIX, this is `\def\@currdir{./}`. For more exotic operating systems you may want to make `\@currdir` a macro with arguments delimited by `.` and/or `<space>`. If the operating system has no concept of directory structure, this macro should be defined to be empty.

`\input@path`     If the primitive `\openin` searches the same directories as the primitive `\input`, then it is possible to tell (using `\ifeof`) whether a file exists before trying to input it. For systems like this, `\input@path` should be left undefined.

If `\openin` does not ‘follow’ `\input` then `\input@path` must be defined to be a list of directories to search for input files. The format for each directory is as for `\@currdir`, normally just a prefix is required, but it may be a macro with space-delimited argument. That is, if `<dir>` is an entry in the input path, T<sub>E</sub>X will try to load the expansion of `<dir><filename><space>`

So either `<dir>` should be defined as a macro with argument delimited by space, or it should just expand to a directory name, including the final directory separator, so that it may be concatenated with the `<filename>`. This means that for UNIX-like syntax, each `<dir>` should end with a slash, `/`.

`\input@path` should expand to a list of such directories, each in a `{}` group.

`\filename@parse`     After a call of the form: `\filename@parse{<filename>}`, the three macros `\filename@area`, `\filename@base` and `\filename@ext` should be defined to be the ‘area’ (or directory), basename and extension respectively. If there was no extension specified in `<filename>`, `\filename@ext` should be `\let` to `\relax` (so this case may be tested with `\@ifundefined{filename@ext}` and, perhaps a default extension substituted).

Normally one would not need to define this macro in `texsys.cfg` as the automatic tests can supply parsers that work with UNIX and VMS and Macintosh syntax, as well as a basic parser that will cover many other cases. However some operating systems may need a ‘hand produced’ parser in which case it should be defined in this file.

The UNIX parser also works for most MSDOS T<sub>E</sub>X versions. Currently if the UNIX, VMS or Macintosh parser is not used, `\filename@parse` is defined to always return an empty area, and to split the argument into basename and extension at the first ‘.’ that occurs in the name. Parsers for other formats may be defined in `texsys.cfg`, in which case they will be used in preference to the default definitions.

`\@TeXversion`     `\@TeXversion` is now set automatically by the initialization tests in this file. You should not need to set it in `texsys.cfg`, however the following documentation is left for information. L<sup>A</sup>T<sub>E</sub>X does not set this variable exactly, the automatic tests set it to:

2 for any version,  $v$ ,  $v < 3.0$

3 for any version,  $v$ ,  $3.0 \leq v \leq 3.14$

`<undefined>` otherwise.

However these values are accurate enough for L<sup>A</sup>T<sub>E</sub>X to take appropriate action for these old T<sub>E</sub>Xs.

If your T<sub>E</sub>X is older than version 3.141, then you should define `\@TeXversion` (using `\def`) to be the version number. If you do not do this<sup>1</sup>, L<sup>A</sup>T<sub>E</sub>X will not work around a bug in old T<sub>E</sub>X versions, and so error messages will appear in a very strange format, with `^^J` appearing instead of line breaks:

```
LaTeX Error: \rubbish undefined.^^J^^JSee the LaTeX manual or LaTeX=
Companion
for explanation.^^JType  H <return>  for immediate help.
...

.3 \renewcommand{\rubbish}
      {}
```

However if you put `\def\@TeXversion{3.14}` in `texsys.cfg` the following format will be used:

```
LaTeX Error: \rubbish undefined.

ee the LaTeX manual or LaTeX Companion for explanation.
ype  H <return>  for immediate help.
.
...

.3 \renewcommand{\rubbish}
      {}
```

Note that this has an extra line ! . which does not appear in error messages that use the default settings with a current version of T<sub>E</sub>X, but this should not cause any confusion we hope.

## 2 Initialization

As this file is read at a very early stage, some definitions that are normally considered to be part of the format must be made here.

Most such definitions are repeated later in the “right” place, usually (but not always) with different implementations. To be able to spot this more easily if you look into the file `latex.ltx` (which is stripped of comments) we add some comment lines to that effect that survive the stripping process by `docstrip`.

```
1 <*dircheck>
2 %% ---- START temporary definitions for bootstrapping; later overwritten ----
3 </dircheck>
```

---

<sup>1</sup>Actually if your T<sub>E</sub>X is really old, version 2, L<sup>A</sup>T<sub>E</sub>X can detect this, and sets `\@TeXversion` to 2 if it is not set in the `cfg` file.

## 2.1 INITEX

```

4 <*dircheck>
5 <*initex>
6 <initex>\ifnum\catcode'\{=1
7 <initex> \errmessage
8 <initex> {LaTeX must be made using an initex with no format preloaded}
9 <initex>\fi
10 \catcode'\{=1
11 \catcode'\}=2

```

If LuaTeX is in use the extensions and other new primitives have to be activated: this is done as early as possible. Older versions of LuaTeX do not hide the primitives: a version check is not needed as the version itself will be missing in the case where action is needed!

```

12 \ifx\directlua\undefined
13 \else
14 \ifx\luatexversion\undefined

```

Enable e-TeX/pdfTeX/Umath primitives with their natural names

```

15 \directlua{tex.enableprimitives("",%
16 tex.extraprimitives('etex', 'pdftex', 'umath'))}

```

In current formats enable primitives with unprefix names. the `latexrelease` guards allow the primitives to be defined with a `\luatex` prefix if older formats are specified.

The unprefix forms are *not* undefined for improved compatibility with external packages when rolling back the format.

```

17 </initex>
18 </dircheck>
19 <*initex, latexrelease>
20 <latexrelease>\ifx\directlua\undefined\else
21 <latexrelease>\IncludeInRelease{2015/10/01}{\luatexluafunction}
22 <latexrelease> {LuaTeX (prefixed names)}%
23 \directlua{tex.enableprimitives("",%
24 tex.extraprimitives("omega", "aleph", "luatex"))}
25 <latexrelease>\EndIncludeInRelease
26 <latexrelease>\IncludeInRelease{0000/00/00}{\luatexluafunction}
27 <latexrelease> {LuaTeX (prefixed names)}%
28 <latexrelease>\directlua{
29 <latexrelease> tex.enableprimitives(
30 <latexrelease> "luatex",
31 <latexrelease> tex.extraprimitives("core","omega", "aleph", "luatex")
32 <latexrelease> )
33 <latexrelease>}
34 <latexrelease>\EndIncludeInRelease
35 <latexrelease>\fi
36 </initex, latexrelease>
37 <*dircheck>
38 <*initex>
39 \fi
40 \fi

```

A test can now be made for eTeX.

```

41 <initex>\ifx\eTeXversion\undefined
42 <initex> \errmessage
43 <initex> {LaTeX requires e-TeX}
44 <initex> \expandafter\endinput

```

```

45 <initex>\fi
    That distraction over, back to the basics of a format.
46 \catcode'\#=6
47 \catcode'\^=7
48 \chardef\active=13
49 \catcode'\@=11
50 \countdef\count@=255
51 \let\bgroup={ \let\egroup=}
52 \ifx\@input\undefined\let\@input\input\fi
53 \ifx\@end\undefined\let\@end\end\fi
54 \chardef\@inputcheck0
55 \chardef\sixt@n=16
56 \newlinechar'\^^J
57 \def\typeout{\immediate\write17}
58 \def\dospecials{\do\ \do\\\do\{\do\}\do\$\do\&%
59 \do\#\do\^\do\_ \do\%\do\~\do\^^I}
60 \def\@makeoother#1{\catcode'#1=12\relax}
61 \def\space{ }
62 \def\@tempswafalse{\let\if@tempswa\iffalse}
63 \def\@tempswatrue{\let\if@tempswa\iftrue}
64 \let\if@tempswa\iffalse
65 \def\loop#1\repeat{\def\iterate{#1\relax\expandafter\iterate\fi}%
66 \iterate \let\iterate\relax}
67 \let\repeat\fi
68 </initex>

```

## 2.2 Some bits of 2e

```

69 <*2kernel>
70 \def\two@digits#1{\ifnum#1<10 0\fi\number#1}
71 \long\def\@firstoftwo#1#2{#1}
72 \long\def\@secondoftwo#1#2{#2}

```

This is a special version of \ProvidesFile for initex use.

```

73 \def\ProvidesFile#1{%
74 \begingroup
75 \catcode'\ 10 %
76 \ifnum \endlinechar<256 %
77 \ifnum \endlinechar>\m@ne
78 \catcode\endlinechar 10 %
79 \fi
80 \fi
81 \@makeoother\/%
82 \@ifnextchar[{\@providesfile{#1}}{\@providesfile{#1}[]}]
83 \def\@providesfile#1[#2]{%
84 \wlog{File: #1 #2}%
85 \@addtofilelist{ #2}%
86 \endgroup}
87 \long\def\@addtofilelist#1{}
88 \def\@empty{}
89 \catcode'\%=12
90 \def\@percentchar{%}
91 \catcode'\%=14
92 \let\@currdir\@undefined
93 \let\input@path\@undefined

```

```

94 \let\filename@parse\@undefined

\strip@prefix

```

```

95 \def\strip@prefix#1>{}
96 </2ekernel>

```

(End of definition for \strip@prefix.)

### 3 texsys.cfg

As mentioned above, any site specific definitions required to describe the filename handling must be entered into a file `texsys.cfg`. If `texsys.cfg` can not be located by `\openin`, we write a default version out. The default version only contains comments, so we do not actually input the file in that case. The automatic tests later will, hopefully, correctly define the required macros.

The tricky code below checks to see if `texsys.cfg` exists. If it does not, all the text in this file between `START` and `END` is copied verbatim to a new file `texsys.cfg`. If `texsys.cfg` is found, then it is simply input. This is only done when this file is being used unstripped.

```

97 <*docstrip>
98 \openin15=texsys.cfg
99 \ifeof15
100 \typeout{** Writing a default texsys.cfg}
101 \immediate\openout15=texsys.cfg
102 \begingroup
103 \catcode'\^M\active%
104 \let^M\par%
105 \def\reserved@a#1^M{%
106   \def\reserved@b{#1}%
107   \ifx\reserved@b\reserved@c\endgroup\else%
108     \immediate\write15{#1}%
109     \expandafter\reserved@a{fi}%
110 \def\reserved@d#1START^M{\let\do\makeother\dospecials\reserved@a}%
111 \catcode'\%=12
112 \def\reserved@c{END}
113 \reserved@d

```

START

#### 3.1 texsys.cfg

This file contains the site specific definitions of the four macros

`\@currdir`, `\input@path`, `\filename@parse` and `\@TeXversion`.

As distributed it only contains comments, however this ‘empty’ file will work on many systems because of the automatic tests built into `ltdirchk.dtx`. You *are* allowed to edit this file to add definitions of these macros appropriate to your system.

The macros that must be defined are:

`\@currdir`      `\@currdir{filename}<space>` should expand to a form of the filename that uniquely refers to the ‘current directory’ if this is possible. (The expansion should also end with a space.) on UNIX, this is `\def\@currdir{./}`. For more exotic operating systems you may want to make `\@currdir` a macro with arguments delimited by `.` and/or `<space>`. If

the operating system has no concept of directory structure, this macro should be defined to be empty.

`\input@path` If the primitive `\openin` searches the same directories as the primitive `\input`, then it is possible to tell (using `\ifeof`) whether a file exists before trying to input it. For systems like this, `\input@path` should be left undefined.

If `\openin` does not ‘follow’ `\input` then `\input@path` must be defined to be a list of directories to search for input files. The format for each directory is as for `\@currdir`, normally just a prefix is required, but it may be a macro with space-delimited argument. That is, if `<dir>` is an entry in the input path, `TeX` will try to load the expansion of

`<dir><filename><space>`

So either `<dir>` should be defined as a macro with argument delimited by space, or it should just expand to a directory name, including the final directory separator, so that it may be concatenated with the `<filename>`. This means that for UNIX-like syntax, each `<dir>` should end with a slash, `/`. One exception to this rule is that the input path should *always* contain the empty directory `{}` as this will allow ‘full pathnames’ to be used, and the ‘current directory’ to be searched.

`\input@path` should expand to a list of such directories, each in a `{}` group.

`\filename@parse` After a call of the form: `\filename@parse{<filename>}`, the three macros `\filename@area`, `\filename@base`, `\filename@ext` should be defined to be the ‘area’ (or directory), basename and extension respectively. If there was no extension specified in `<filename>`, `\filename@ext` should be `\let` to `\relax` (so this case may be tested with `\@ifundefined{filename@ext}` and, perhaps a default extension substituted).

Normally one would not need to define this macro in `texsys.cfg` as the automatic tests can supply parsers that work with UNIX and VMS syntax, as well as a basic parser that will cover many other cases. However some operating systems may need a ‘hand produced’ parser in which case it should be defined in this file.

The UNIX parser also works for most MSDOS `TeX` versions. Currently if the UNIX or VMS parser is not used, `\filename@parse` is defined to always return an empty area, and to split the argument into basename and extension at the first ‘.’ that occurs in the name. Parsers for other formats may be defined in `texsys.cfg`, in which case they will be used in preference to the default definitions.

`\@TeXversion` You should not need to set this macro in `texsys.cfg`. `LaTeX` tests to set this automatically. See the comments in the opening section of `ltdirchk.dtx`.

The following sections give examples of definitions which might work on various systems. These are currently mainly untested as I only have access to a few systems, all of which do not need this file as the automatic tests work. All the code is commented out.

## 3.2 UNIX (web2c)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

114 `%\def\@currdir{./}`

115 `%\let\input@path\@undefined`

### 3.3 UNIX (other)

Apparently some commercial UNIX implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever directories are used at your site): note that the directory names should end with `/`.

```
116 % \def\currdir{./}
117 % \def\input@path{%
118 %   {/usr/local/lib/tex/inputs/distrib/}%
119 %   {/usr/local/lib/tex/inputs/contrib/}%
120 %   {/usr/local/lib/tex/inputs/local/}%
121 % }
```

### 3.4 MSDOS (emtex)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
122 % \def\currdir{./}
123 % \let\input@path\undefined
```

### 3.5 MSDOS (other)

Some PC implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever directories are used at your site): note that the directory names should end with `/`. This assumes the implementation uses UNIX style `/` as the directory separator.

```
124 % \def\currdir{./}
125 % \def\input@path{%
126 %   {c:/tex/inputs/distrib/}%
127 %   {c:/tex/inputs/contrib/}%
128 %   {c:/tex/inputs/local/}%
129 % }
```

### 3.6 VMS (DECUS T<sub>E</sub>X, PD VMS 3.6)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
130 % \def\currdir{[] }
131 % \let\input@path\undefined
```

### 3.7 VMS (???)

Some VMS implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following:

```
132 % \def\currdir{[] }
133 % \def\input@path{%
134 %   {tex_inputs:}%
135 %   {SOMEDISK:[SOME.TEX.DIRECTORY]}%
136 % }
```

### 3.8 MACINTOSH (OzTeX 1.6)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
137 % \def\@currdir{:}
138 % \let\input@path\@undefined
```

### 3.9 MACINTOSH (other)

Some Macintosh implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever folders are used on your machine): note that the directory names should end with `:`, and they should contain *no* spaces.

```
139 % \def\@currdir{:}
140 % \def\input@path{%
141 %   {Hard-Disk:Applications:TeX:TeX-inputs:}%
142 %   {Hard-Disk:Applications:TeX:My-inputs:}%
143 % }
```

### 3.10 FAKE EXAMPLE

This example is for an operating system that has filenames of the form `<area>name`. For maximum compatibility with macro sets, you want `name.ext` to be mapped to `<ext>name`, and `<area>name.ext` to be mapped to `<area.ext>name`. `\input` does this mapping automatically, but `\openin` does not, and does not look in the same places as `\input`. `<>name` is the desired ‘current directory’ syntax.

the following code would possibly work:

```
144 % \def\@dir#1#2 {%
145 %   \@d@r{#1}#2..\@nil}
146 % \def\@d@r#1#2.#3.#4\@nil{%
147 %   <\ifx\@dir#1\@dir\else#1\ifx\@dir#3\@dir\else.\fi\fi#3>#2 }
148 %
149 % \def\@currdir{\@dir{}}
150 % \def\input@path{%
151 %   {\@dir{area.one}}}%
152 %   {\@dir{area.two}}}%
153 % }
```

END

```
154 \immediate\closeout15
```

If `texsys.cfg` did exist, then input it.

```
155 \else
156 \typeout{** Using the existing texsys.cfg}
157 \closein15
158 \input texsys.cfg
159 \fi
160 </docstrip>
```

If the stripped version of this file is being used (in `latex2e.ltx`) then `texsys.cfg` should be there, so just input it.

```
161 <dircheck>\input texsys.cfg
```

## 4 Setting \@currdir

`\@currdir` This is a local definition of `\IfFileExists`. It tries to relocate `texsys.aux`. If it succeeds, then the `\@currdir` syntax has been determined. If all the tests fail then `\@currdir` will be set to `\@empty`, and `ltxcheck` will warn of this when it checks the format.

```
162 \begingroup
163 \count@ \time
164 \divide \count@ 60
165 \count2 = - \count@
166 \multiply \count2 60
167 \advance \count2 \time
```

The current date and time stamp.

```
168 \edef \today {%
\today 169 \the \year / \two@digits {\the \month} / \two@digits {\the \day} : %
170 \two@digits {\the \count@} : \two@digits {\the \count2}}
```

Create a file `texsys.aux` (hopefully in the current directory), then try to locate it again.

```
171 \immediate \openout15 = texsys.aux
172 \immediate \write15 {\today ^^J}
173 \immediate \closeout15 %
```

`#1` is the file to try, `#2` is what to do on success, `#3` on failure. Note that this definition is overwritten later on again!

```
174 \def \IfFileExists #1#2#3 {%
175 \openin \@inputcheck #1 %
176 \ifeof \@inputcheck
177 #3 \relax
178 \else
179 \read \@inputcheck to \reserved@a
180 \ifx \reserved@a \today
181 \typeout {#1 found} #2 \relax
182 \else
183 \typeout {BAD: old file \reserved@a (should be \today)} %
184 #3 \relax
185 \fi
186 \fi
187 \closein \@inputcheck}
188 \endlinechar = -1
```

If `\@currdir` has not been pre-defined in `texsys.cfg` then test for UNIX, VMS and Oz-TeX-Mac. syntax.

```
189 \ifx \@currdir \@undefined
190 \IfFileExists {./texsys.aux} {\gdef \@currdir {./}} %
191 {\IfFileExists {} {texsys.aux} {\gdef \@currdir {}}} %
192 {\IfFileExists {:texsys.aux} {\gdef \@currdir {:}} {}} %
```

If it is still undefined at this point, all the above tests failed. Earlier versions interactively prompted for a definition at this point, but it seems impossible to reliably obtain information from users at this point in the installation. This version of the file produces

a format with no user-interaction. Later if the format is not suitable for the system, `texsys.cfg` may be edited and the format re-made.

```

193 \ifx\@currdir\undefined
194 \global\let\@currdir\empty
195 \typeout{^^J^^J%
196     !! No syntax for the current directory could be found^^J%
197 }%
198 \fi

```

Otherwise `\@currdir` was defined in `texsys.cfg`. In this case check that the syntax specified works on this system. (In case a complete L<sup>A</sup>T<sub>E</sub>X system has been copied from one system to another.) If the test fails, give up. The installer should remove or correct the offending `texsys.cfg` and try again.

```

199 \else
200 \IfFileExists{\@currdir texsys.aux}{\}%
201 \edef\reserved@a{\errhelp{%
202     texsys.cfg specifies the current directory syntax to be^^J%
203     \meaning\@currdir^^J%
204     but this does not work on this system.^^J%
205     Remove texsys.cfg and restart.}}\reserved@a
206 \errmessage{Bad texsys.cfg file: \noexpand\@currdir}\@@end}

```

The version of `\@currdir` in `texsys.cfg` looks OK.

```

207 \fi

208 \immediate\closeout15 %
209 \endgroup

210 \typeout{^^J^^J%
211     \noexpand\@currdir set to:
212     \expandafter\strip@prefix\meaning\@currdir.^^J%
213 }

```

*(End of definition for \@currdir, \IfFileExists, and \today.)*

Stop here if the file is being used unstripped.

```

214 <docstrip>
215 \relax\endinput
216 </docstrip>

```

## 5 Setting `\input@path`

Earlier versions of this file attempted to automatically test whether `\input@path` was required, and interactively prompt for a path if necessary. This was not found to be very reliable. The first-time installer of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> can not be expected to have enough information to supply the correct information to the prompts. Now the interaction is omitted. After the format is made the installer can attempt to run the test document `ltxcheck.tex` through L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. This will check, among other things, whether `texsys.cfg` will need to be edited and the format remade.

`\input@path` Now set up the `\input@path`.

`\input@path` should either be undefined, or a list of directories as described in the introduction.

```

217 \typeout{^^J%

```

```

218     Assuming \noexpand\openin and \noexpand\input^^J%
219     \ifx\input@path\@undefined
\input@path has not been pre-defined.
220         have the same search path.^^J%
221     \else
\input@path has been defined in texsys.cfg.
222         have different search paths.^^J%
223         LaTeX will use the path specified by \noexpand\input@path:^^J%
224     \fi
225 }

(End of definition for \input@path.)

```

## 6 Filename Parsing

`\filename@parse` Split a filename into its components.

```

226 \ifx\filename@parse\@undefined
227     \def\reserved@a{.}\ifx\@currdir\reserved@a
\filename@parse was not specified in texsys.cfg, but \@currdir looks like UNIX...
228     \typeout{^^JDefining UNIX/DOS style filename parser.^^J}
229     \def\filename@parse#1{%
230         \let\filename@area\@empty
231         \expandafter\filename@path#1/\}

Search for the last /.
232     \def\filename@path#1/#2\{%
233         \ifx\#2\%
234             \def\reserved@a{\filename@simple#1.\}%
235         \else
236             \edef\filename@area{\filename@area#1/}%
237             \def\reserved@a{\filename@path#2\}%
238         \fi
239         \reserved@a}

240 \else\def\reserved@a{[]}\ifx\@currdir\reserved@a
\filename@parse was not specified in texsys.cfg, but \@currdir looks like VMS...
241     \typeout{^^JDefining VMS style filename parser.^^J}
242     \def\filename@parse#1{%
243         \let\filename@area\@empty
244         \expandafter\filename@path#1]\}

Search for the last ].
245     \def\filename@path#1]\#2\{%
246         \ifx\#2\%
247             \def\reserved@a{\filename@simple#1.\}%
248         \else
249             \edef\filename@area{\filename@area#1]}\%
250             \def\reserved@a{\filename@path#2]\}%
251         \fi
252         \reserved@a}

253 \else\def\reserved@a{:}\ifx\@currdir\reserved@a

```

\filename@parse was not specified in texsys.cfg, but \@currdir looks like Macintosh...

```

254 \typeout{^^JDefining Mac style filename parser.^^J}
255 \def\filename@parse#1{%
256   \let\filename@area\@empty
257   \expandafter\filename@path#1:\}

```

Search for the last :.

```

258 \def\filename@path#1:#2\{%
259   \ifx\#2\%
260     \def\reserved@a{\filename@simple#1.\}%
261   \else
262     \edef\filename@area{\filename@area#1:}%
263     \def\reserved@a{\filename@path#2\}%
264   \fi
265   \reserved@a}
266 \else

```

\filename@parse was not specified in texsys.cfg. So just make a simple parser that always sets \filename@area to empty.

```

267 \typeout{^^JDefining generic filename parser.^^J}
268 \def\filename@parse#1{%
269   \let\filename@area\@empty
270   \expandafter\filename@simple#1.\}
271 \fi\fi\fi

```

\filename@simple is used by all three versions. Finally we can split off the extension.

```

272 </dircheck>
273 <*dircheck, latexrelease>
274 <latexrelease> \IncludeInRelease{2019/10/01}{\filename@simple}
275 <latexrelease> {Final dot for extension}%
276 \def\filename@simple#1.#2\{%
277   \ifx\#2\%
278     \let\filename@ext\relax
279     \edef\filename@base{#1}%
280   \else
281     \filename@dots{#1}#2\%
282   \fi}
283 \def\filename@dots#1#2.#3\{%
284   \ifx\#3\%
285     \def\filename@ext{#2}%
286     \edef\filename@base{#1}%
287   \else
288     \filename@dots{#1.#2}#3\%
289   \fi}
290 <latexrelease> \EndIncludeInRelease
291 <latexrelease> \IncludeInRelease{0000/00/00}{\filename@simple}
292 <latexrelease> {Final dot for extension}%
293 <latexrelease> \def\filename@simple#1.#2\{%
294 <latexrelease>   \ifx\#2\%
295 <latexrelease>     \let\filename@ext\relax
296 <latexrelease>   \else
297 <latexrelease>     \edef\filename@ext{\filename@dot#2\}%

```

```

298 <latexrelease>      \fi
299 <latexrelease>      \edef\filename@base{#1}}
300 <latexrelease>\EndIncludeInRelease
301 </dircheck,latexrelease>
302 <*dircheck>

      Remove a final dot, added earlier.
303   \def\filename@dot#1.\{#1}

304   \else

Otherwise, \filename@parse was specified in texsys.cfg.
305   \typeout{^^J^^J%
306     \noexpand\filename@parse was defined in texsys.cfg:^^J%
307     \expandafter\strip@prefix\meaning\filename@parse.^^J%
308   }
309   \fi

(End of definition for \filename@parse.)

```

## 7 T<sub>E</sub>X Versions

`\@TeXversion` T<sub>E</sub>X versions older than 3.141 require `\@TeXversion` to be set. This can be determined automatically due to a trick suggested by Bernd Raichle. Actually this will not always get the correct version number, e.g., T<sub>E</sub>X3.14 would be detected as T<sub>E</sub>X3, but L<sup>A</sup>T<sub>E</sub>X only needs to take account of T<sub>E</sub>X's older than 3, or between 3 and 3.14.

```

310 \ifx\@TeXversion\@undefined
311   \ifx\@undefined\inputlineno
312     \def\@TeXversion{2}
313   \else
314     {\catcode'\^^J=\active
315      \def\reserved@a#1#2\@{\if#1\string^3\fi}
316      \edef\reserved@a{\expandafter\reserved@a\string^^J\@}
317      \ifx\reserved@a\@empty\else\gdef\@TeXversion{3}\fi}
318   \fi
319 \fi

(End of definition for \@TeXversion.)

320 %% ---- END temporary definitions for bootstrapping ----
321 </dircheck>

```

## 8 ltxcheck.tex

After the format has been made, and `article.cls` moved with the other files to the ‘standard input directory’ as specified in `install.txt`, the format may be checked by running the file `ltxcheck.tex`.

## File 02

# lplain.dtx

## 1 Plain T<sub>E</sub>X

L<sup>A</sup>T<sub>E</sub>X includes almost all of the functionality of Knuth's original 'Basic Macros' That is, the plain T<sub>E</sub>X format described in Appendix B of the T<sub>E</sub>XBook. However, some of the user commands are not much use so, in order to save memory, we may remove them from the kernel into a package. Here is a list of the commands that may be removed (PROBABLY NOT COMPLETE).

```
\magstep      \magstephalf
\mathhexbox
\vglue        \vgl@
\hglue        \hgl@
```

This file is by now very small as most of it has been moved to more appropriate kernel files: it may disappear completely one day.

L<sup>A</sup>T<sub>E</sub>X font definitions are done using NFSS2 so none of PLAIN's font definitions are in L<sup>A</sup>T<sub>E</sub>X.

L<sup>A</sup>T<sub>E</sub>X has its own tabbing environment, so PLAIN's is disabled.

L<sup>A</sup>T<sub>E</sub>X uses its own output routine, so most of the plain one was removed.

```
1 (*2kernel)
2 \catcode'\{=1 % left brace is begin-group character
3 \catcode'\}=2 % right brace is end-group character
4 \catcode'\$=3 % dollar sign is math shift
5 \catcode'\&=4 % ampersand is alignment tab
6 \catcode'\#=6 % hash mark is macro parameter character
7 \catcode'\^=7 % circumflex and uparrow are for superscripts
8 \catcode'\_ =8 % underline and downarrow are for subscripts
9 \catcode'\^~I=10 % ascii tab is a blank space
10 \chardef\active=13 \catcode'\~=\active % tilde is active
11 \catcode'\^~L=\active \def^~L{\par}% ascii form-feed is \par
12 \message{catcodes,}
```

We had to define the \catcodes right away, before the message line, since \message uses the { and } characters. When INITEX (the T<sub>E</sub>X initializer) starts up, it has defined the following \catcode values:

```
\catcode'\^~@=9 %  ascii null is ignored
\catcode'\^~M=5 %  ascii return is end-line
\catcode'\ =0 %    backslash is TeX escape character
\catcode'\%=14 %   percent sign is comment character
\catcode'\ =10 %   ascii space is blank space
\catcode'\^~?=15 %  ascii delete is invalid
\catcode'\A=11 ... \catcode'\Z=11 % uppercase letters
\catcode'\a=11 ... \catcode'\z=11 % lowercase letters
all others are type 12 (other)
```

Here is a list of the characters that have been specially catcoded:

```
13 \def\dospecials{\do\ \do\\\do\{\do\}\do\$ \do\&%
14 \do\# \do\^ \do\_ \do\% \do\~ \do\^~I}
```

(not counting ascii null, linefeed, formfeed, return, delete) Each symbol in the list is preceded by , which can be defined if you want to do something to every item in the list.

We make @ signs act like letters, temporarily, to avoid conflict between user names and internal control sequences of plain format.

```
15 \catcode'\@=11
```

To make the plain macros more efficient in time and space, several constant values are declared here as control sequences. If they were changed, anything could happen; so they are private symbols.

`\@ne` Small constants are defined using `\chardef`.

```
\tw@ 16 \chardef\@ne=1
\thr@@ 17 \chardef\tw@=2
\sixt@@n 18 \chardef\thr@@=3
\@cclv 19 \chardef\sixt@@n=16
20 \chardef\@cclv=255
```

*(End of definition for \@ne and others.)*

`\@ccclvi` Constants above 255 defined using `\mathchardef`.

```
\@m 21 \mathchardef\@ccclvi=256
\@M 22 \mathchardef\@m=1000
\@MM 23 \mathchardef\@M=10000
24 \mathchardef\@MM=20000
```

*(End of definition for \@ccclvi and others.)*

Allocation of registers

Here are macros for the automatic allocation of `\count`, `\box`, `\dimen`, `\skip`, `\muskip`, and `\toks` registers, as well as `\read` and `\write` stream numbers, `\fam` codes, `\language` codes, and `\insert` numbers.

```
25 \message{registers,}
```

When a register is used only temporarily, it need not be allocated; grouping can be used, making the value previously in the register return after the close of the group. The main use of these macros is for registers that are defined by one macro and used by others, possibly at different nesting levels. All such registers should be defined through these macros; otherwise conflicts may occur, especially when two or more macro packages are being used at the same time.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

The following counters are reserved:

- 0 to 9 page numbering
- 10 count allocation
- 11 dimen allocation
- 12 skip allocation
- 13 muskip allocation
- 14 box allocation
- 15 toks allocation
- 16 read file allocation
- 17 write file allocation
- 18 math family allocation
- 19 language allocation
- 20 insert allocation
- 21 the most recently allocated number

22 constant -1

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

New counters are allocated starting with 23, 24, etc. Other registers are allocated starting with 10. This leaves 0 through 9 for the user to play with safely, except that counts 0 to 9 are considered to be the page and subpage numbers (since they are displayed during output). In this scheme, `\count 10` always contains the number of the highest-numbered counter that has been allocated, `\count 14` the highest-numbered box, etc. Inserts are given numbers 254, 253, etc., since they require a `\count`, `\dimen`, `\skip`, and `\box` all with the same number; `\count 20` contains the lowest-numbered insert that has been allocated. Of course, `\box255` is reserved for `\output`; `\count255`, `\dimen255`, and `\skip255` can be used freely.

It is recommended that macro designers always use `\global` assignments with respect to registers numbered

1, 3, 5, 7, 9,

and always non-`\global` assignments with respect to registers

0, 2, 4, 6, 8, 255.

This will prevent “save stack buildup” that might otherwise occur.

```
26 \count10=22 % allocates \count registers 23, 24, ...
27 \count11=9 % allocates \dimen registers 10, 11, ...
28 \count12=9 % allocates \skip registers 10, 11, ...
29 \count13=9 % allocates \muskip registers 10, 11, ...
30 \count14=9 % allocates \box registers 10, 11, ...
31 \count15=9 % allocates \toks registers 10, 11, ...
32 \count16=-1 % allocates input streams 0, 1, ...
33 \count17=-1 % allocates output streams 0, 1, ...
34 \count18=3 % allocates math families 4, 5, ...
35 \count19=0 % allocates \language codes 1, 2, ...
36 \count20=255 % allocates insertions 254, 253, ...
```

`\insc@unt` The insertion counter and most recent allocation.

```
\allocationnumber
37 \countdef\insc@unt=20
38 \countdef\allocationnumber=21
```

*(End of definition for \insc@unt and \allocationnumber.)*

`\m@ne` The constant  $-1$ .

```
39 \countdef\m@ne=22 \m@ne=-1
```

*(End of definition for \m@ne.)*

`\wlog` Write on log file (only)

```
40 \def\wlog{\immediate\write\m@ne}
```

*(End of definition for \wlog.)*

`\count@` Here are abbreviations for the names of scratch registers that don’t need to be allocated.

```
\dimen@
41 \countdef\count@=255
```

```
\dimen@i
42 \dimendef\dimen@=0
```

```
\dimen@ii
43 \dimendef\dimen@i=1 % global only
```

```
\skip@
44 \dimendef\dimen@ii=2
```

```
\toks@
45 \skipdef\skip@=0
```

```
46 \toksdef\toks@=0
```

(End of definition for \count@ and others.)

\newcount Now, we define \newcount, \newbox, etc. so that you can say \newcount\foo and \foo  
 \newdimen will be defined (with \countdef) to be the next counter.  
 \newskip To find out which counter \foo is, you can look at \allocationnumber.  
 \newmuskip Since there's no \boxdef command, \chardef is used to define a \newbox,  
 \newbox \newinsert, \newfam, and so on.  
 \newtoks L<sup>A</sup>T<sub>E</sub>X change: remove \outer from \newcount and \newdimen (FMi) This is nec-  
 \newread essary to use \newcount inside \if... later on. Also remove from \newskip, \newbox  
 \newwrite \newwrite and \newfam (DPC) to save later redefinition. Rolling back the allocation  
 \newfam routine runs us into trouble nowadays as the kernel itself will use up all of the standard  
 \newlanguage pool. So we pretend we've always used the full range: this is needed for roll forward.

```

47 \def\newcount {\e@alloc\count \countdef {\count10}\insc@unt\float@count}
48 \def\newdimen {\e@alloc\dimen \dimendef {\count11}\insc@unt\float@count}
49 \def\newskip {\e@alloc\skip \skipdef {\count12}\insc@unt\float@count}
50 \def\newmuskip
51 {\e@alloc\muskip\muskipdef{\count13}\m@ne\e@alloc@top}

```

For compatibility use \chardef in the classical range.

```

52 \def\newbox {\e@alloc\box
53 {\ifnum\allocationnumber<\@ccclvi
54 \expandafter\chardef
55 \else
56 \expandafter\e@alloc@chardef
57 \fi}
58 {\count14}\insc@unt\float@count}
59 \def\newtoks {\e@alloc\toks \toksdef{\count15}\m@ne\e@alloc@top}
60 \def\newread {\e@alloc\read \chardef{\count16}\m@ne\sixt@@n}

```

Skip \write18 due to its traditional use as a shell-escape.

```

61 \ifx\directlua@\undefined
62 \def\newwrite {\e@alloc\write \chardef{\count17}\m@ne\sixt@@n}
63 \else
64 \def\newwrite {\e@alloc\write
65 {\ifnum\allocationnumber=18
66 \advance\count17\@ne
67 \allocationnumber\count17 %
68 \fi
69 \global\chardef}%
70 {\count17}%
71 \m@ne
72 {128}}
73 \fi
74 \def\new@mathgroup
75 {\e@alloc\mathgroup\chardef{\count18}\m@ne\e@mathgroup@top}
76 \let\newfam\new@mathgroup
77 \ifx\directlua@\undefined
78 \def\newlanguage {\e@alloc\language \chardef{\count19}\m@ne\@ccclvi}
79 \else
80 \def\newlanguage {\e@alloc\language \chardef{\count19}\m@ne{16384}}
81 \fi

```

(End of definition for \newcount and others.)

`\e@alloc@chardef` The upper limit of extended registers, which leaves this number (eg `\dimen32767`) always unallocated by these macros. cf traditional `\dimen255`.

```

82 \ifx\directlua\undefined
83   \mathchardef\e@alloc@top=32767
84   \let\e@alloc@chardef\mathchardef
85 \else

```

luatex has  $2^{16}$  registers.

```

86   \chardef\e@alloc@top=65535
87   \let\e@alloc@chardef\chardef
88 \fi

```

*(End of definition for \e@alloc@chardef and \e@alloc@top.)*

`\e@mathgroup@top` The upper limit of extended math groups (`\fam`) 16 in classic T<sub>E</sub>X and e-T<sub>E</sub>X, but 256 in Unicode TeX variants.

```

89 \ifx\Umathcode\undefined

```

classic and e tex have 16 fam (0–15).

```

90   \chardef\e@mathgroup@top=16
91 \else

```

xetex and luatex have 256 fam (0–255).

```

92   \chardef\e@mathgroup@top=256
93 \fi

```

*(End of definition for \e@mathgroup@top.)*

`\e@alloc` A modified version of `\alloc@` that takes the count register rather than just the final digit of its number (assuming `\count1x`). It also has an extra argument to give the top of the extended range.

```

      #1 #2      #3    #4    #5      #6
      \e@alloc type defcmd current top extended-top newname

```

Note that if just a single allocation range is required (not omitting a range up to 255 for inserts) then `-1` should be used for the first upper bound argument, `#4`.

```

94 \def\e@alloc#1#2#3#4#5#6{%
95   \global\advance#3\@ne
96   \e@ch@ck{#3}{#4}{#5}#1%
97   \allocationnumber#3\relax
98   \global#2#6\allocationnumber
99   \wlog{\string#6=\string#1\the\allocationnumber}}%

```

*(End of definition for \e@alloc.)*

`\e@ch@ck` Extended check command. If the first range is exceeded, bump to 256 (or 266 for counts) and try again, testing the extended range.

Allocate matching registers from the top of the extended range and add to `\@freelist`.

```

\extrafloats
100 \gdef\e@ch@ck#1#2#3#4{%
101   \ifnum#1<#2\else

```

If we've reached the classical top limit, bump to 256 or 266 for counts (count 256–265 are reserved by the allocation system).

```

102 \ifnum#1=#2\relax
103 \global#1@cclvi
104 \ifx\count#4\global\advance#1 10 \fi
105 \fi

```

Check we are below the extended limit.

```

106 \ifnum#1<#3\relax
107 \else
108 \errmessage{No room for a new \string#4}%
109 \fi
110 \fi}%
111 \let\float@count\e@alloc@top

```

`\extrafloats`

```

112 \ifx\numexpr\@undefined
In classic TeX use \newinsert to allocate float boxes.
113 \def\extrafloats#1{%
114 \count@#1\relax
115 \ifnum\count@>\z@
116 \newinsert\reserved@a
117 \global\expandafter\chardef
118 \csname bx@\the\allocationnumber\endcsname\allocationnumber
119 \@cons\@freelist{\csname bx@\the\allocationnumber\endcsname}%
120 \advance\count@\m@ne
121 \expandafter\extrafloats
122 \expandafter\count@
123 \fi
124 }%
125 \else

```

In e-text take float boxes from the top of the extended range.

```

126 \def\extrafloats#1{%
127 \ifnum#1>\z@
128 \count@\numexpr\float@count-1\relax
129 \ifnum\count@<266 \ch@ck0@m@ne\insert\fi
130 \ch@ck0\count@\count
131 \ch@ck1\count@\dimen
132 \ch@ck2\count@\skip
133 \ch@ck4\count@\box
134 \global\e@alloc@chardef\float@count\count@
135 \global\expandafter\e@alloc@chardef
136 \csname bx@\the\float@count\endcsname\float@count
137 \@cons\@freelist{\csname bx@\the\float@count\endcsname}%
138 \expandafter\extrafloats\expandafter{\the\numexpr#1-1\expandafter}%
139 \fi}%
140 \fi

```

*(End of definition for `\e@ch@ck`, `\extrafloats`, and `\extrafloats`.)*

`\alloc@` Since `\e@alloc` was added in 2015, `\@alloc` has not been used, but was left as some legacy code calls it. However the original definition gives spurious errors once the “classic” registers run out, so it is now defined to call `\e@alloc` internally.

```
141 \def\alloc@#1#2#3#4{\e@alloc#2#3{\count1#1}#4\float@count}
```

*(End of definition for \alloc@.)*

`\newinsert` The highest register allowed with `\insert`.

```
142 \ifx\directlua\@undefined
143   \chardef\e@insert@top255
144 \else
145   \chardef\e@insert@top\e@alloc@top
146 \fi
```

If the classic registers are exhausted, take an insert from the free float list and use `\extrafloats` to add a new float to that list.

```
147 \def\newinsert#1{%
148   \@tempswafalse
149   \global\advance\insc@unt\m@ne
150   \ifnum\count10<\insc@unt
151   \ifnum\count11<\insc@unt
152   \ifnum\count12<\insc@unt
153   \ifnum\count14<\insc@unt
154     \@tempswatrue
155   \fi\fi\fi\fi
156   \if@tempswa
157     \allocationnumber\insc@unt
158   \else
159     \global\advance\insc@unt\@ne
160     \extrafloats\@ne
161     \@next\@currbox\@freelist
162     {\ifnum\@currbox<\e@insert@top
163       \allocationnumber\@currbox
164     \else
165       \ch@ck0\m@ne\insert
166     \fi}%
167     {\ch@ck0\m@ne\insert}%
168   \fi
169   \global\chardef#1\allocationnumber
170   \wlog{\string#1=\string\insert\the\allocationnumber}%
171 }
```

*(End of definition for \newinsert.)*

`\ch@ck`

```
172 \gdef\ch@ck#1#2#3{%
173   \ifnum\count1#1<#2\else
174     \errmessage{No room for a new #3}%
175   \fi}
```

*(End of definition for \ch@ck.)*

`\newhelp`

```
176 \def\newhelp#1#2{\newtoks#1#1\expandafter{\csname#2\endcsname}}
```

(End of definition for `\newhelp`.)

`\@inputcheck` Allocate read stream for testing and output stream that is never open and thus writes to the terminal.  
`\@unused`

```

177 \newread\@inputcheck
178 \newwrite\@unused

```

(End of definition for `\@inputcheck` and `\@unused`.)

`\maxdimen` Here are some examples of allocation.  
`\hideskip`

```

179 \newdimen\maxdimen \maxdimen=16383.99999pt % the largest legal <dimen>
180 \newskip\hideskip \hideskip=-1000pt plus 1fill % negative but can grow

```

(End of definition for `\maxdimen` and `\hideskip`.)

`\p@`  
`\z@`

```

181 \newdimen\p@ \p@=1pt % this saves macro space and time
182 \newdimen\z@ \z@=0pt % can be used both for 0pt and 0
183 \newskip\z@skip \z@skip=0pt plus 0pt minus 0pt
184 \newbox\voidb@x % permanently void box register

```

(End of definition for `\p@` and others.)

Assign initial values to T<sub>E</sub>X's parameters

```

185 \message{parameters,}

```

All of T<sub>E</sub>X's numeric parameters are listed here, but the code is commented out if no special value needs to be set. INITEX makes all parameters zero except where noted.

```

186 \pretolerance=100
187 \tolerance=200 % INITEX sets this to 10000
188 \hbadness=1000
189 \vbadness=1000
190 \linepenalty=10
191 \hyphenpenalty=50
192 \exhyphenpenalty=50
193 \binoppenalty=700
194 \relpenalty=500
195 \clubpenalty=150
196 \widowpenalty=150
197 \displaywidowpenalty=50
198 \brokenpenalty=100
199 \predisplaypenalty=10000
200 % \postdisplaypenalty=0
201 % \interlinepenalty=0
202 % \floatingpenalty=0, set during \insert
203 % \outputpenalty=0, set before TeX enters \output
204 \doublehyphendemerits=10000
205 \finalhyphendemerits=5000
206 \adjdemerits=10000

```

```

207 % \looseness=0, cleared by TeX after each paragraph
208 % \pausing=0
209 % \holdinginserts=0
210 % \tracingonline=0
211 % \tracingmacros=0
212 % \tracingstats=0
213 % \tracingparagraphs=0
214 % \tracingpages=0
215 % \tracingoutput=0

```

In the past L<sup>A</sup>T<sub>E</sub>X used the default value of 1 for `\tracinglostchars` because this was the best it could do. This way one would at least get a warning in the `.log` file. e-T<sub>E</sub>X improved on that and supported a value of 2 to show the warning on the terminal, so we could have changed the default when we made the e-T<sub>E</sub>X extensions required—however, we overlooked that opportunity. In 2021 this parameter was improved on again and now also accepts the value 3 (error on the terminal). This made us realize that we should change the default. Using 3 would really be the best, but for compatibility reasons we only use 2. For recent LuaT<sub>E</sub>X releases, we set 4: this is offset by 2 from the e-T<sub>E</sub>X value as otherwise LuaT<sub>E</sub>X only issues a warning for text in a box when the box is used, not saved. (Accepting values of 4 and 5 was updated in the T<sub>E</sub>X Live 2025 release.)

```

216 \tracinglostchars=2
217 \ifdefined\luatexversion
218   \ifnum\luatexversion>120
219     \tracinglostchars=4
220   \fi
221 \fi
222 % \tracingcommands=0
223 % \tracingrestores=0

```

`\tracingstacklevels` For LuaT<sub>E</sub>X, the `\tracingstacklevels` functionality was implemented as a callback, so here we just define the count register to hold the value of the parameter.

```

224 </2ekernel>
225 <*2ekernel | latexrelease>
226 <latexrelease> \IncludeInRelease{2021/06/01}{\tracingstacklevels}%
227 <latexrelease> {tracingstacklevels}%
228 \ifx\directlua\@undefined
229   % \tracingstacklevels=0 % added in 2021
230 \else
231   \newcount\tracingstacklevels
232   % Code for \tracingstacklevels defined in ltfinal.dtx
233 \fi
234 <latexrelease> \EndIncludeInRelease
235 <latexrelease>
236 <latexrelease> \IncludeInRelease{0000/00/00}{\tracingstacklevels}%
237 <latexrelease> {tracingstacklevels}%
238 <latexrelease> \ifx\directlua\@undefined
239 <latexrelease> \else
240 <latexrelease> \let\tracingstacklevels\@undefined
241 <latexrelease> \fi
242 <latexrelease> \EndIncludeInRelease
243 </2ekernel | latexrelease>
244 <*2ekernel>

```

(End of definition for \tracingstacklevels.)

```
245 \uchyph=1
246 % \lefthyphenmin=2 \righthyphenmin=3 set below
247 % \globaldefs=0
248 % \maxdeadcycles=25 % INITEX does this
249 % \hangafter=1 % INITEX does this, also TeX after each paragraph
250 % \fam=0
251 % \mag=1000 % INITEX does this
252 % \escapechar='\ % INITEX does this
253 \defaultthyphenchar='\-
254 \defaultskewchar=-1
255 % \endlinechar='\^M % INITEX does this
256 % \newlinechar=-1 \LaTeX\ sets this in ltdefs.dtx.
257 \delimiterfactor=901
258 % \time=now % TeX does this at beginning of job
259 % \day=now % TeX does this at beginning of job
260 % \month=now % TeX does this at beginning of job
261 % \year=now % TeX does this at beginning of job
```

In L<sup>A</sup>T<sub>E</sub>X we don't want box information in the transcript unless we do a full tracing.

```
262 \showboxbreadth=-1
263 \showboxdepth=-1
264 \errorcontextlines=-1
265 \hfuzz=0.1pt
266 \vfuzz=0.1pt
267 \overfullrule=5pt
268 \maxdepth=4pt
269 \splitmaxdepth=\maxdimen
270 \boxmaxdepth=\maxdimen
271 % \lineskiplimit=0pt, changed by \normalbaselines
272 \delimitershortfall=5pt
273 \nulldelimiterspace=1.2pt
274 \scriptspace=0.5pt
275 % \mathsurround=0pt
276 % \predisplaysize=0pt, set before TeX enters $$
277 % \displaywidth=0pt, set before TeX enters $$
278 % \displayindent=0pt, set before TeX enters $$
279 \parindent=20pt
280 % \hangindent=0pt, zeroed by TeX after each paragraph
281 % \hoffset=0pt
282 % \voffset=0pt
283 %
284 % \baselineskip=0pt, changed by \normalbaselines
285 % \lineskip=0pt, changed by \normalbaselines
286 \parskip=0pt plus 1pt
287 \abovedisplayskip=12pt plus 3pt minus 9pt
288 \abovedisplayshortskip=0pt plus 3pt
289 \belowdisplayskip=12pt plus 3pt minus 9pt
290 \belowdisplayshortskip=7pt plus 3pt minus 4pt
```

```

291 % \leftskip=0pt
292 % \rightskip=0pt

293 \topskip=10pt
294 \splittopskip=10pt

295 % \tabskip=0pt
296 % \spaceskip=0pt
297 % \xspaceskip=0pt

298 \parfillskip=0pt plus 1fil

\normalbaselineskip We also define special registers that function like parameters:
\normallineskip 299 \newskip\normalbaselineskip \normalbaselineskip=12pt
\normallineskiplimit 300 \newskip\normallineskip \normallineskip=1pt
301 \newdimen\normallineskiplimit \normallineskiplimit=0pt

(End of definition for \normalbaselineskip, \normallineskip, and \normallineskiplimit.)

\interfootlinepenalty
302 \newcount\interfootnotelinepenalty \interfootnotelinepenalty=100

(End of definition for \interfootlinepenalty.)
Definitions for preloaded fonts

\nmagstephalf
\nmagstep 303 \def\nmagstephalf{1095 }
304 \def\nmagstep#1{\ifcase#1 \@m\or 1200\or 1440\or 1728\or
305 2074\or 2488\fi\relax}

(End of definition for \magstephalf and \magstep.)
Macros for setting ordinary text

\nfrenchspacing
\nonfrenchspacing 306 \def\nfrenchspacing{\sfcode'\.\@m \sfcode'\?\@m \sfcode'\!\@m
307 \sfcode'\:\@m \sfcode'\;\@m \sfcode'\,\@m}
308 \def\nonfrenchspacing{\sfcode'\.3000\sfcode'\?3000\sfcode'\!3000%
309 \sfcode'\:2000\sfcode'\;1500\sfcode'\,1250 }

(End of definition for \frenchspacing and \nonfrenchspacing.)

\normalbaselines
310 \def\normalbaselines{\lineskip\normallineskip
311 \baselineskip\normalbaselineskip \lineskiplimit\normallineskiplimit}

(End of definition for \normalbaselines.)

\M Save a bit of space by using \let here.
\I 312 \def\^M{\ } % control <return> = control <space>
313 \let\^I\^M % same for <tab>

(End of definition for \M and \I.)

\lq
\rq 314 \def\lq{' }
315 \def\rq{' }

```

```

        (End of definition for \lq and \rq.)

\lbrack
\rbrack 316 \def\lbrack{[}
        317 \def\rbrack{]}

        (End of definition for \lbrack and \rbrack.)

\aa  These are not from plain.tex but they are similar to other commands found here and
\AA  nowhere else, being alternate input forms for characters.
        318 \def \aa {\r a}
        319 \def \AA {\r A}

        (End of definition for \aa and \AA.)

\endgraf
\endline 320 \let\endgraf=\par
        321 \let\endline=\cr

        (End of definition for \endgraf and \endline. These functions are documented on page 417.)

\space
        322 \def\space{ }

        (End of definition for \space.)

\empty  This probably ought to go altogether, but let it to the LATEX version to save space.
        323 \let\empty\@empty

        (End of definition for \empty.)

\null
        324 \def\null{\hbox{}}

        (End of definition for \null.)

\bgroup
\egroup 325 \let\bgroup={
        326 \let\egroup=}

        (End of definition for \bgroup and \egroup.)

\obeylines  In \obeylines, we say \let^M=\obeyedline instead of \def^M{\obeyedline} since
\obeyspaces this allows, for example, \let\obeyedline=\cr \obeylines \halign{...

        This is essentially a plain TEX trick and in its original version where you had to use
        to use \let\par=\cr not really a safe idea in LATEX. If anybody used this trick this now
        breaks (and one needs to use \obeyedline instead).

        327 </2ekernel>
        328 <*2ekernel | latexrelease>
        329 <latexrelease>\IncludeInRelease{2022/06/01}{\obeylines}%
        330 <latexrelease> {Add a redirection to obeylines and obeyspaces}%

```

If the active `^^M` escapes, e.g., into a `\write` (which is effectively in a different context) then we don't want the definition from `\obeylines` but rather a simple `\par` (in fact even the primitive one, not the L<sup>A</sup>T<sub>E</sub>X version `\para_end`: which is only defined later).

```
331 \begingroup
332 \catcode'\^^M=\active % these lines must end with %
333 \gdef\obeylines{\catcode'\^^M\active%
334 \let^^M\obeyedline%
```

The next line ending the definition is rather curious and it took me awhile to understand why rollback fails. The problem is the following: if `latexrelease` is used, then blocks of `\IncludeInRelease ... \EndIncludeInRelease` are bypassed at high speed by grabbing each as a delimited argument. However, in that case `^^M` is seen not as code but as line ending characters and in that mode T<sub>E</sub>X discards everything from that point onwards to the real end of the line so it works like a comment — pretty strange really (and I think due to the fact that the original pascal compiler could have some garbage showing up after the normal line ending character. Thus we really have to make sure that any closing braces is not one the same line as an `^^M`, because otherwise it would get dropped and we end with unbalanced braces and never see the `\EndIncludeInRelease` — weird. In other places it doesn't matter because we aren't using the incomplete result.

```
335 }%
336 \global\let^^M\par % this is in case ^^M appears in a \write
337 \endgroup
```

The `\obeyedline` expands by default to `\par` with whatever definition `\par` has when it is executed. It can, however, be redefined (before calling `\obeylines`!) to achieve some special effects. If you want to alter this definition when already in the scope of `\obeylines`, it has no effect (because `\let` is used above). In that case simply make another call to `\obeylines` immediately. As you are in a restricted scope all that happens is that your redefinition is applied.

For the default definition we have to use `\def` not `\let` because the meaning of `\par` can change and we want to use the one that is current when `\obeylines` act.

There is a small subtlety here: in an `\edef` the active `^^M` stayed put (because it was equal to the primitive `\par`), now `\obeyedline` expands and you get what it contains, i.e., in that case `\par`, into the `\edef` or `\mark` unless we use `\protected` on it.

```
338 \protected\gdef\obeyedline{\par}
```

The definition of `\obeyspaces` is changed in the same way and now executes `\obeyedspace` for each active space.

```
\obeyedspace 339 \global\let\obeyedspace\space

340 \begingroup
341 \catcode'\ =\active%
342 \gdef\obeyspaces{\catcode'\ \active\let =\obeyedspace}%
```

An active space elsewhere generates `\space` by default (for example in a `\write`).

```
343 \global\let =\space%
344 \endgroup

345 </2ekernel | latexrelease>
346 <latexrelease>\EndIncludeInRelease
347 <latexrelease>\IncludeInRelease{0000/00/00}{\obeylines}%
348 <latexrelease> {Add a redirection to obeylines and obeyspaces}%
349 <latexrelease>
```

From 2019 onwards the commands are made robust (somewhat later in the kernel sources). So if we roll back they are robust, so when redefining them we have get rid of the robust payload first. Otherwise that is seen by the later rollback below, which then installs a fragile version of the new definition on top of the one we roll back to here, sigh. `\kernel@make@fragile` also changes its definition (later own) so this is done directly.

```
350 <latexrelease>\expandafter\let\csname obeylines \endcsname \@undefined
351 <latexrelease>\expandafter\let\csname obeyspace \endcsname \@undefined
352 <latexrelease>
353 <latexrelease>\begingroup
354 <latexrelease>\catcode'\^M=\active % these lines must end with %
355 <latexrelease> \gdef\obeylines{\catcode'\^M\active \let^M\par %
```

Closing brace on a separate line (see comment above).

```
356 <latexrelease> }%
```

Another pitfall: if we do a rollback `\par` is no longer the primitive, so the roll back definition needs `\let` to what is new the primitive.

```
357 <latexrelease> \global\let^M\RawParEnd % this is in case ^M appears in a \write
358 <latexrelease>\endgroup
359 <latexrelease>\def\obeyspaces{\catcode'\ \active}
360 <latexrelease>
361 <latexrelease>\let\obeyedline\@undefined
362 <latexrelease>\let\obeyedspace\@undefined
363 <latexrelease>\EndIncludeInRelease
364 <*2ekernel>
```

*(End of definition for \obeylines and others.)*

`\loop` We use Kabelschacht's method of doing loops, see TUB 8#2 (1987). (unless that breaks something :-). It turned out to need an extra `\relax`: see pr/642 (`\loop` could do one iteration too much in certain cases).

```
365 \long\def \loop #1\repeat{%
366   \def\iterate{#1\relax % Extra \relax
367     \expandafter\iterate\fi
368   }%
369   \iterate
370   \let\iterate\relax
371 }
```

This setting of `\repeat` is needed to make `\loop...\if...\repeat` skippable within another `\if....`

```
372 \let\repeat=\fi
```

*(End of definition for \loop, \iterate, and \repeat.)*

L<sup>A</sup>T<sub>E</sub>X defines `\smallskip`, etc. in `ltspace.dtx`.

```
\nointerlineskip
\offinterlineskip
373 \def\nointerlineskip{\prevdepth-\@m\p@}
374 \def\offinterlineskip{\baselineskip-\@m\p@
375   \lineskip\z@ \lineskiplimit\maxdimen}
```

*(End of definition for \nointerlineskip and \offinterlineskip.)*

```

\vglue
\hglue 376 \def\vglue{\afterassignment\vgl@\skip@=}
377 \def\vgl@{\par \dimen@\prevdepth \hrule \@height\z@
378 \nobreak\vskip\skip@ \prevdepth\dimen@}
379 \def\hglue{\afterassignment\hgl@\skip@=}
380 \def\hgl@{\leavevmode \count@\spacefactor \vrule \@width\z@
381 \nobreak\hskip\skip@ \spacefactor\count@}

(End of definition for \vglue and \hglue.)
LATEX defines ~ in ltdefs.dtx.

\slash This generates a / acting a bit like - but still allows hyphenation in the word part
preceding it (but not after).
382 \def\slash{/\penalty\exhyphenpenalty}

(End of definition for \slash.)

\break
\nobreak 383 \def\break{\penalty-\@M}
\allowbreak 384 \def\nobreak{\penalty \@M}
385 \def\allowbreak{\penalty \z@}

(End of definition for \break, \nobreak, and \allowbreak.)

\filbreak
\goodbreak 386 \def\filbreak{\par\vfil\penalty-200\vfilneg}
387 \def\goodbreak{\par\penalty-500 }

(End of definition for \filbreak and \goodbreak.)

\eject Define \eject as in plain TEX but define \supereject only in the compatibility file.
388 \def\eject{\par\break}

(End of definition for \eject.)

\removelastskip
389 \def\removelastskip{\ifdim\lastskip=\z@\else\vskip-\lastskip\fi}

(End of definition for \removelastskip.)

\smallbreak
\medbreak 390 \def\smallbreak{\par\ifdim\lastskip<\smallskipamount
\removelastskip\penalty-50\smallskip\fi}
\bigbreak 391 \def\medbreak{\par\ifdim\lastskip<\medskipamount
\removelastskip\penalty-100\medskip\fi}
392 \def\bigbreak{\par\ifdim\lastskip<\bigskipamount
\removelastskip\penalty-200\bigskip\fi}
393
394
395

(End of definition for \smallbreak, \medbreak, and \bigbreak.)

\m@th
396 \def\m@th{\mathsurround\z@}

(End of definition for \m@th.)

```

`\underbar` Due to L<sup>A</sup>T<sub>E</sub>X's redefinition of `\underline` plain T<sub>E</sub>X's `\underbar` can be done in a simpler fashion (but do we need it at all?).

```

397 \def\underbar#1{\underline{\sbox\tw@{#1}\dp\tw@z@box\tw@}}

```

(End of definition for `\underbar`.)

`\strutbox` L<sup>A</sup>T<sub>E</sub>X sets `\strutbox` in `\set@fontsize`.

```

\strut
398 \newbox\strutbox
399 \def\strut{\relax\ifmmode\copy\strutbox\else\unhcopy\strutbox\fi}

```

(End of definition for `\strutbox` and `\strut`.)

`\hidewidth` For alignment entries that can stick out.

```

400 \def\hidewidth{\hskip\hideskip}

```

(End of definition for `\hidewidth`.)

`\narrower`

```

401 \def\narrower{%
402   \advance\leftskip\parindent
403   \advance\rightskip\parindent}

```

(End of definition for `\narrower`.)

L<sup>A</sup>T<sub>E</sub>X defines `\ae` and similar commands elsewhere.

```

404 \chardef\%= '\%
405 \chardef\&= '\&
406 \chardef\#= '\#

```

Most text commands are actually encoding specific and therefore defined later, so commented out or removed from this file.

`\leavevmode` begins a paragraph, if necessary

```

407 \def\leavevmode{\unhbox\voidb@x}

```

(End of definition for `\leavevmode`.)

`\mathhexbox`

```

408 \def\mathhexbox#1#2#3{\mbox{$\m@th \mathchar"#1#2#3$}}

```

(End of definition for `\mathhexbox`.)

`\ialign`

```

409 \def\ialign{\everycr{}\tabskipz@skip\halign} % initialized \halign

```

(End of definition for `\ialign`.)

`\oalign`

```

\o@lign
410 \def\oalign#1{\leavevmode\vtop{\baselineskipz@skip \lineskip.25ex%
\oalign
411   \ialign{##\crrc#1\crrc}}}
412 \def\o@lign{\lineskiplimitz@ \oalign}
413 \def\oalign{\lineskiplimit-\maxdimen \oalign}

```

(End of definition for `\oalign`, `\o@lign`, and `\oalign`.)

`\sh@ft` The definition of this macro in plain.tex was improved in about 1997; but as a result its usage was changed and its new definition is not appropriate for L<sup>A</sup>T<sub>E</sub>X.

Since the version given here has been in use by L<sup>A</sup>T<sub>E</sub>X for many years it does not seem prudent to remove it now. As far as we can tell it has only been used to define `\b` and `\d` but this cannot be certain.

```
414 \def\sh@ft#1{\dimen@.00#1ex\multiply\dimen@\fontdimen1\font
415 \kern-.0156\dimen@} % compensate for slant in lowered accents
```

*(End of definition for \sh@ft.)*

`\ltx@sh@ft` This is the L<sup>A</sup>T<sub>E</sub>X version of the second incarnation of the plain macro `\sh@ft`, which takes a dimension as its argument. It shifts a pseudo-accent horizontally by an amount proportional to the product of its argument and the slant-per-point (`fontdimen 1`).

```
416 \def\ltx@sh@ft #1{%
417 \dimen@ #1%
418 \kern \strip@pt
419 \fontdimen1\font \dimen@
420 } % kern by #1 times the current slant
```

*(End of definition for \ltx@sh@ft.)*

L<sup>A</sup>T<sub>E</sub>X change: the text commands such as `\d`, `\b`, `\c`, `\copyright`, `\TeX` are now defined elsewhere.

L<sup>A</sup>T<sub>E</sub>X change: Make `\t` work in a moving argument. Now defined elsewhere.

`\hrulefill` L<sup>A</sup>T<sub>E</sub>X change: `\kern\z@` added to end of `\hrulefill` and `\dotfill` to make them work  
`\dotfill` in ‘tabular’ and ‘array’ environments. (Change made 24 July 1987). L<sup>A</sup>T<sub>E</sub>X change:  
`\leavevmode` added at beginning of `\dotfill` and `\hrulefill` so that they work as expected in vertical mode.

```
421 \def\hrulefill{\leavevmode\leaders\hrule\hfill\kern\z@}
```

The box in `\dotfill` originally contained (in plain.tex):

```
\mkern 1.5mu .\mkern 1.5mu;
```

the width of .44em differs from this by .04pt which is probably an acceptable difference within leaders.

```
422 \def\dotfill{%
423 \leavevmode
424 \cleaders \hb@xt@ .44em{\hss.\hss}\hfill
425 \kern\z@}
```

*(End of definition for \hrulefill and \dotfill.)*

INITEX sets `\sfcode x=1000` for all x, except that `\sfcode X=999` for uppercase letters. The following changes are needed:

```
426 \sfcode'\)=0 \sfcode'\ '=0 \sfcode'\]=0
```

The `\nonfrenchspacing` macro will make further changes to `\sfcode` values.

Definitions related to output

`\magnification` doesn’t work in L<sup>A</sup>T<sub>E</sub>X.

```
def\magnification{\afterassignment\m@g\count@}
def\m@g{\mag\count@
\hsize6.5truein\vsiz8.9truein\dimen\footins8truein}
```

`\showoverfull` The following commands are used in debugging:

```
427 \def\showoverfull{\tracingonline\@ne}
```

(End of definition for \showoverfull.)

\showoutput  
\loggingoutput

```
428 \gdef\loggingoutput{\tracingoutput\@ne
429   \showboxbreadth\maxdimen\showboxdepth\maxdimen\errorstopmode}
430 \gdef\showoutput{\loggingoutput\showoverfull}
431 \endkernel
```

(End of definition for \showoutput and \loggingoutput.)

\tracingall  
\loggingall

```
432 \<latexrelease>\IncludeInRelease{2021/06/01}{\loggingall}
433 \<latexrelease>          {\tracingstacklevels and \tracinglostchars=3}%
434 \*2ekernel | latexrelease)
435 \edef\loggingall{%
436   \tracingstats\tw@
437   \tracingpages\@ne
438   \tracingparagraphs\@ne
439   \tracinggroups\@ne
440   \tracingifs\@ne
441   \tracingscantokens\@ne
442   \tracingnesting\@ne
443   \errorcontextlines\maxdimen
444   \ifdefined\tracingstacklevels \tracingstacklevels\maxdimen \fi
445   \noexpand \loggingoutput
446   \tracingmacros\tw@
447   \tracingcommands\thr@@
448   \tracingrestores\@ne
449   \tracingassigns\@ne
450 }%
451 \def\tracingall{\showoverfull\loggingall}
452 \endkernel | latexrelease)
453 \<latexrelease>\EndIncludeInRelease
454 \<latexrelease>
455 \<latexrelease>\IncludeInRelease{2015/01/01}{\loggingall}{etex tracing}%
456 \<latexrelease>\ifx\tracingscantokens\@undefined
457 \<latexrelease>\gdef\loggingall{%
458   \<latexrelease> \tracingstats\tw@
459   \<latexrelease> \tracingpages\@ne
460   \<latexrelease> \tracinglostchars\@ne
461   \<latexrelease> \tracingparagraphs\@ne
462   \<latexrelease> \errorcontextlines\maxdimen
463   \<latexrelease> \loggingoutput
464   \<latexrelease> \tracingmacros\tw@
465   \<latexrelease> \tracingcommands\tw@
466   \<latexrelease> \tracingrestores\@ne
467   \<latexrelease> }%
468 \<latexrelease>\else
469 \<latexrelease>\gdef\loggingall{%
470   \<latexrelease> \tracingstats\tw@
471   \<latexrelease> \tracingpages\@ne
472   \<latexrelease> \tracinglostchars\tw@
473   \<latexrelease> \tracingparagraphs\@ne
474   \<latexrelease> \tracinggroups\@ne
```

```

475 <latexrelease> \tracingifs\@ne
476 <latexrelease> \tracingscantokens\@ne
477 <latexrelease> \tracingnesting\@ne
478 <latexrelease> \errorcontextlines\maxdimen
479 <latexrelease> \loggingoutput
480 <latexrelease> \tracingmacros\tw@
481 <latexrelease> \tracingcommands\thr@@
482 <latexrelease> \tracingrestores\@ne
483 <latexrelease> \tracingassigns\@ne
484 <latexrelease>}%
485 <latexrelease>\fi
486 <latexrelease>\gdef\tracingall{\showoverfull\loggingall}
487 <latexrelease>\EndIncludeInRelease
488 <latexrelease>
489 <latexrelease>\IncludeInRelease{0000/00/00}{\loggingall}{etex tracing}%
490 <latexrelease>\gdef\loggingall{\tracingcommands\tw@\tracingstats\tw@
491 <latexrelease> \tracingpages\@ne\tracinglostchars\@ne
492 <latexrelease> \tracingmacros\tw@\tracingparagraphs\@ne\tracingrestores\@ne
493 <latexrelease> \errorcontextlines\maxdimen\loggingoutput}
494 <latexrelease> \gdef\tracingall{\loggingall\showoverfull}
495 <latexrelease>\EndIncludeInRelease

```

*(End of definition for \tracingall and \loggingall.)*

**\tracingnone**

```

496 <latexrelease>\IncludeInRelease{2015/01/01}{\tracingnone}%
497 <latexrelease> \turn off etex tracing}%
498 <*2ekernel | latexrelease>
499 \edef\tracingnone{%
500   \tracingassigns\z@
501   \tracingrestores\z@
502   \tracingonline\z@
503   \tracingcommands\z@
504   \showboxdepth\m@ne
505   \showboxbreadth\m@ne
506   \tracingoutput\z@
507   \errorcontextlines\m@ne
508   \ifdefined\tracingstacklevels \tracingstacklevels\z@ \fi
509   \tracingnesting\z@
510   \tracingscantokens\z@
511   \tracingifs\z@
512   \tracinggroups\z@
513   \tracingparagraphs\z@
514   \tracingmacros\z@
515   \tracingpages\z@
516   \tracingstats\z@
517 }%
518 </2ekernel | latexrelease>
519 <latexrelease>\EndIncludeInRelease
520 <latexrelease>
521 <latexrelease>\IncludeInRelease{2015/01/01}{\tracingnone}%
522 <latexrelease> \turn off etex tracing}%
523 <latexrelease>\ifx\tracingscantokens\@undefined
524 <latexrelease>\def\tracingnone{%

```

```

525 <latexrelease> \tracingonline\z@
526 <latexrelease> \tracingcommands\z@
527 <latexrelease> \showboxdepth\m@ne
528 <latexrelease> \showboxbreadth\m@ne
529 <latexrelease> \tracingoutput\z@
530 <latexrelease> \errorcontextlines\m@ne
531 <latexrelease> \tracingrestores\z@
532 <latexrelease> \tracingparagraphs\z@
533 <latexrelease> \tracingmacros\z@
534 <latexrelease> \tracinglostchars\@ne
535 <latexrelease> \tracingpages\z@
536 <latexrelease> \tracingstats\z@
537 <latexrelease>}%
538 <latexrelease>\else
539 <latexrelease>\def\tracingnone{%
540 <latexrelease> \tracingassigns\z@
541 <latexrelease> \tracingrestores\z@
542 <latexrelease> \tracingonline\z@
543 <latexrelease> \tracingcommands\z@
544 <latexrelease> \showboxdepth\m@ne
545 <latexrelease> \showboxbreadth\m@ne
546 <latexrelease> \tracingoutput\z@
547 <latexrelease> \errorcontextlines\m@ne
548 <latexrelease> \tracingnesting\z@
549 <latexrelease> \tracingscantokens\z@
550 <latexrelease> \tracingifs\z@
551 <latexrelease> \tracinggroups\z@
552 <latexrelease> \tracingparagraphs\z@
553 <latexrelease> \tracingmacros\z@
554 <latexrelease> \tracinglostchars\@ne
555 <latexrelease> \tracingpages\z@
556 <latexrelease> \tracingstats\z@
557 <latexrelease>}%
558 <latexrelease>\fi
559 <latexrelease>\EndIncludeInRelease
560 <latexrelease>
561 <latexrelease>\IncludeInRelease{0000/00/00}{\tracingnone}%
562 <latexrelease> {turn off etex tracing}%
563 <latexrelease>\let\tracingnone\@undefined
564 <latexrelease>\EndIncludeInRelease

```

(End of definition for \tracingnone.)

\hideoutput

```

565 <*2ekernel | latexrelease>
566 <latexrelease>\IncludeInRelease{2015/01/01}{\hideoutput}%
567 <latexrelease> {hide output from tracing}%
568 \def\hideoutput{%
569 \tracingoutput\z@
570 \showboxbreadth\m@ne
571 \showboxdepth\m@ne
572 \tracingonline\m@ne
573 }%
574 <latexrelease>\EndIncludeInRelease

```

```

575 <latexrelease>
576 <latexrelease> \IncludeInRelease{0000/00/00}{\hideoutput}%
577 <latexrelease> {hide output from tracing}%
578 <latexrelease> \let\hideoutput\@undefined
579 <latexrelease> \EndIncludeInRelease
580 </2ekernel | latexrelease>

(End of definition for \hideoutput.)
    LATEX change: \showhyphens Defined later.
    Punctuation affects the spacing.

581 <*2ekernel>
582 \nonfrenchspacing
583 </2ekernel>

```

## File 03

# ltvers.dtx

## 1 Version Identification

First we identify the date and version number of this release of L<sup>A</sup>T<sub>E</sub>X, and set `\everyjob` so that it is printed at the start of every L<sup>A</sup>T<sub>E</sub>X run.

`\fmtname` A `\patch@level` of 0 or higher denotes an official public release. A negative value indicates a candidate release that is not distributed.

`\fmtversion`

`\latexreleaseversion` If we put code updates into the kernel that are supposed to go into the next release we set the `\patch@level` to -1 and the `\fmtversion` / `\latexreleaseversion` to the dated of the next release (guessed, the real value is not so important and will get corrected when we make the release official).

`\patch@level`

If the `\patch@level` is already at -1 we do nothing here and use the `\fmtversion` date for any new `\IncludeInRelease` line when we add further code.

Finally, if we do make a public release we either just set the `\patch@level` to zero (if our initial guess was good) or we also change the date and then have to additionally change to that date on all the `\IncludeInRelease` statements that used the “guessed” date.

```
1 <*2ekernel>
2 \def\fmtname{LaTeX2e}
3 \edef\fmtversion
4 </2ekernel>
5 <latexrelease>\edef\latexreleaseversion
6 <*2ekernel| latexrelease>
7 {2025-11-01}
8 </2ekernel| latexrelease>
9 <*2ekernel>
10 \def\patch@level{-4}
```

For more fine grain control there is the possibility to name the current development branch. This is only used when the `\patch@level` is negative (i.e., a pre-release format) and is intended to help us internally when we locally install a format out of some development branch.

```
\development@branch@name 11 \edef\development@branch@name{develop \the\year-\the\month-\the\day}
```

*(End of definition for `\fmtname` and others.)*

Check that the format being made is not too old. The error message complains about ‘more than 5 years’ but in fact the error is not triggered until 65 months.

This code is currently not activated as we don’t know if we already got to the last official 2e version (due to staff shortage or due to a successor (think positive:-)).

```
12 \iffalse
13 \def\reserved@a#1/#2/#3\@nil{%
14   \count@ \year
15   \advance\count@-#1\relax
16   \multiply\count@ by 12\relax
17   \advance\count@\month
18   \advance\count@-#2\relax}
19 \expandafter\reserved@a\fmtversion\@nil
```

\count@ is now the age of this file in months. Take a generous definition of ‘year’ so this message is not generated too often.

```

68     \fi
69     \fi
70 \</2ekernel>

\IncludeInRelease
\EndIncludeInRelease
\@IncludeInRelease
\@IncludeInRelease
\@gobble@IncludeInRelease
\@check@IncludeInRelease

71 \<2ekernel>\let\@currname\@empty
72 \<*2ekernel | latexrelease>
73 \<latexrelease>\newif\if@includeinrelease
74 \<latexrelease>\@includeinreleasefalse
75 \def\IncludeInRelease#1{%
76   \if@includeinrelease
77     \PackageError{latexrelease}{mis-matched IncludeInRelease}%
78       {There is an \string\EndIncludeRelease\space missing}%
79   \@includeinreleasefalse
80   \fi
81   \ifnum0%
82     \ifx\new@moduledate\@empty\else 1\fi
83     \ifnum \expandafter\@parse@version#1//00\@nil=0 1\fi
84     =11
85     \expandafter\@firstoftwo
86   \else
87     \expandafter\@secondoftwo
88   \fi
89   {\finish@module@release{#1}}%
90   {\kernel@ifnextchar[%
91     {\@IncludeInRelease{#1}}
92     {\@IncludeInRelease{#1}[#1]}}}%
93 \def\finish@module@release#1#2#3{%
94   \toks@{[#1] #3}%
95   \begingroup
96     \edef\x{\detokenize\expandafter{\new@modulename}}%
97     \edef\y{\detokenize{#2}}%
98   \expandafter\endgroup
99   \ifx\x\y \else
100     \@latex@error{\noexpand\IncludeInRelease dated #1 in a module is not
101       allowed.\MessageBreak Use a date at least equal to \new@moduledate
102       \space for complete rollback}\@ehd
103   \fi
104   \ifnum\expandafter\@parse@version\new@moduledate//00\@nil
105     >\expandafter\@parse@version\fmtversion//00\@nil
106     \GenericInfo{ }\{Applying: \the\toks@\}%
107   \else
108     \GenericInfo{ }\{Skipping: \the\toks@\}%
109     \expandafter\gobble@finish@module@release
110   \fi}
111 \long\def\gobble@finish@module@release#1\EndModuleRelease{%
112   \EndModuleRelease}

    If a specific date has not been specified in latexrelease use ‘#1’.
113 \def\@IncludeInRelease#1[#2]{\@IncludeInRelease{#2}}
114 \def\@IncludeInRelease#1#2#3{%
115   \toks@{[#1] #3}%
116   \expandafter\ifx\curname\string#2+\@currname+IIR\endcurname\relax

```

If we roll back and the first patch already match then applying that is actually reapplying what is already in the format, i.e., it is useless and possibly allocating new registers. However, it makes the logic simpler so this is the way it is for now. In theory we could always jump over the first patch because that is only really needed for rolling forward. So maybe one day ...

```

117 \ifnum\expandafter\@parse@version#1//00\@nil
118 >\expandafter\@parse@version\fmtversion//00\@nil
119 \GenericInfo{}\{Skipping: \the\toks@}%
120 \expandafter\expandafter\expandafter\@gobble@IncludeInRelease
121 \else
122 \GenericInfo{}\{Applying: \the\toks@}%
123 \@includeinreleasetrue
124 \expandafter\let\csname\string#2+\@currname+IIR\endcsname\@empty
125 \fi
126 \else
127 \GenericInfo{}\{Already applied: \the\toks@}%
128 \expandafter\@gobble@IncludeInRelease
129 \fi
130 }

131 \def\EndIncludeInRelease{%
132 \if@includeinrelease
133 \@includeinreleasefalse
134 \else
135 \PackageError{latexrelease}{mis-matched EndIncludeInRelease}{}%
136 \fi
137 \if@skipping@module
138 \expandafter\new@module@skip
139 \fi}

140 \long\def\@gobble@IncludeInRelease#1\EndIncludeInRelease{%
141 \@includeinreleasefalse
142 \@check@IncludeInRelease#1\IncludeInRelease\@check@IncludeInRelease
143 \@end@check@IncludeInRelease}

144 \long\def\@check@IncludeInRelease#1\IncludeInRelease
145 #2#3\@end@check@IncludeInRelease{%
146 \ifx\@check@IncludeInRelease#2\else
147 \PackageError{latexrelease}{skipped IncludeInRelease for tag \string#2}{}%
148 \fi
149 \if@skipping@module
150 \expandafter\new@module@skip
151 \fi}

```

(End of definition for `\IncludeInRelease` and others.)

## 1.1 Declaring an all-new module

```

\if@skipping@module \NewModuleRelease
\EndModuleRelease \new@module@skip
\new@modulename
\new@moduledate
152 \let\if@skipping@module\iffalse
153 \def\@skipping@moduletrue{\let\if@skipping@module\iftrue}
154 \def\@skipping@modulefalse{\let\if@skipping@module\iffalse}

```

When we have a whole new module, we can't roll back to a date where such module exists, otherwise hundreds of "command already defined" errors will pop up. But we can't skip it altogether either, because the module might have changes we still want applied, so a more detailed cherry-picking of code chunks have to be done.

```

155 \let\new@modulename\@empty
156 \let\new@moduledate\@empty
157 \def\NewModuleRelease#1#2#3{%
158   \ifx\new@modulename\@empty \else
159     \@latex@error{Nested \noexpand\NewModuleRelease forbidden.}\@ehd \fi
160   \edef\new@moduledate{#1}%
161   \edef\new@modulename{#2}%
162   \GenericInfo{}{BEGIN module: \new@modulename\space (\new@moduledate)}%
163   \GenericInfo{}{ \@spaces\@spaces\@spaces\space#3\@gobble}%
164   \ifnum\sourceLaTeXdate<%
165     \expandafter\@parse@version\new@moduledate//00\@nil\relax
166     \ifnum\expandafter\@parse@version\fmtversion//00\@nil<%
167       \expandafter\@parse@version\new@moduledate//00\@nil\relax
168       \GenericInfo{}{Skipping module \new@modulename}%
169       \expandafter\expandafter
170       \expandafter\gobble@finish@module@release
171     \else
172       \GenericInfo{}{Applying module \new@modulename}
173       \@skipping@modulefalse
174     \fi
175   \else
176     \GenericInfo{}{Skipping module \new@modulename}
177     \@skipping@moduletrue
178     \expandafter\new@module@skip
179   \fi}
180 \long\def\new@module@skip#1\IncludeInRelease{%
181 \long\def\reserved@a##1\EndModuleRelease{}%
182 \ifrelax\detokenize\expandafter{\reserved@a#1{}}\EndModuleRelease}\relax
183 \else
184   \@latex@error{Missing mandatory \string\IncludeInRelease{0000/00/00}}\@ehc
185   \expandafter\@secondoftwo
186 \fi
187 \@gobble
188   {\@expandtwoargs\IncludeInRelease
189     {0000/00/00}{\new@modulename}%
190     {ERROR! Emergency recovery}%
191     #1}%
192 \IncludeInRelease}
193 \def\EndModuleRelease{%
194   \ifx\new@modulename\@empty
195     \@latex@error{Extra \string\EndModuleRelease.}\@eha
196   \else
197     \GenericInfo{}{END module: \new@modulename\space (\new@moduledate)}%
198     \let\new@modulename\@empty
199     \let\new@moduledate\@empty
200     \@skipping@modulefalse
201   \fi}

```

(End of definition for \if@skipping@module and others.)

```

202 </2ekernel | latexrelease>

```

## File 04

# ltxuatex.dtx

## 1 Overview

LuaTeX adds a number of engine-specific functions to TeX. Several of these require set up that is best done in the kernel or need related support functions. This file provides *basic* support for LuaTeX at the L<sup>A</sup>TeX 2<sub>ε</sub> kernel level plus as a loadable file which can be used with plain TeX and L<sup>A</sup>TeX.

This file contains code for both TeX (to be stored as part of the format) and Lua (to be loaded at the start of each job). In the Lua code, the kernel uses the namespace `luatexbase`.

The following `\count` registers are used here for register allocation:

```
\e@alloc@attribute@count Attributes (default 258)
\e@alloc@ccodetable@count Category code tables (default 259)
\e@alloc@luafunction@count Lua functions (default 260)
  \e@alloc@whatsit@count User whatsits (default 261)
  \e@alloc@bytecode@count Lua bytecodes (default 262)
  \e@alloc@luachunk@count Lua chunks (default 263)
```

(`\count 256` is used for `\newmarks` allocation and `\count 257` is used for `\newXeTeXintercharclass` with XeTeX, with code defined in `ltxfinal.dtx`). With any L<sup>A</sup>TeX 2<sub>ε</sub> kernel from 2015 onward these registers are part of the block in the extended area reserved by the kernel (prior to 2015 the L<sup>A</sup>TeX 2<sub>ε</sub> kernel did not provide any functionality for the extended allocation area).

## 2 Core TeX functionality

The commands defined here are defined for possible inclusion in a future L<sup>A</sup>TeX format, however also extracted to the file `ltxuatex.tex` which may be used with older L<sup>A</sup>TeX formats, and with plain TeX.

```
\newattribute \newattribute{<attribute>}
  Defines a named \attribute, indexed from 1 (i.e. \attribute0 is never defined). Attributes initially have the marker value -7FFFFFFF ('unset') set by the engine.
\newcatcodetable \newcatcodetable{<catcodetable>}
  Defines a named \catcodetable, indexed from 1 (\catcodetable0 is never assigned). A new catcode table will be populated with exactly those values assigned by IniTeX (as described in the LuaTeX manual).
\newluafunction \newluafunction{<function>}
  Defines a named \luafunction, indexed from 1. (Lua indexes tables from 1 so \luafunction0 is not available).
\newluacmd \newluacmd{<function>}
  Like \newluafunction, but defines the command using \luadef instead of just assigning an integer.
```

<code>\newprotectedluacmd</code>	<code>\newluaundef{&lt;function&gt;}</code>	Like <code>\newluacmd</code> , but the defined command is not expandable.
<code>\newwhatsit</code>	<code>\newwhatsit{&lt;whatsit&gt;}</code>	Defines a custom <code>\whatsit</code> , indexed from 1.
<code>\newluabytecode</code>	<code>\newluabytecode{&lt;bytecode&gt;}</code>	Allocates a number for Lua bytecode register, indexed from 1.
<code>\newluachunkname</code>	<code>newluachunkname{&lt;chunkname&gt;}</code>	Allocates a number for Lua chunk register, indexed from 1. Also enters the name of the register (without backslash) into the <code>lua.name</code> table to be used in stack traces.
<code>\catcodetable@initex</code>	Predefined category code tables with the obvious assignments. Note that the <code>latex</code> and	
<code>\catcodetable@string</code>	<code>atletter</code> tables set the full Unicode range to the codes predefined by the kernel.	
<code>\catcodetable@latex</code>	<code>\setattribute{&lt;attribute&gt;}{&lt;value&gt;}</code>	
<code>\catcodetable@atletter</code>	<code>\unsetattribute{&lt;attribute&gt;}</code>	
<code>\setattribute</code>	Set and unset attributes in a manner analogous to <code>\setlength</code> . Note that attributes	
<code>\unsetattribute</code>	take a marker value when unset so this operation is distinct from setting the value to zero.	

### 3 Plain T<sub>E</sub>X interface

The `ltluatex` interface may be used with plain T<sub>E</sub>X using `\input{ltluatex}`. This inputs `ltluatex.tex` which inputs `etex.src` (or `etex.sty` if used with L<sup>A</sup>T<sub>E</sub>X) if it is not already input, and then defines some internal commands to allow the `ltluatex` interface to be defined.

The `luatexbase` package interface may also be used in plain T<sub>E</sub>X, as before, by inputting the package `\input luatexbase.sty`. The new version of `luatexbase` is based on this `ltluatex` code but implements a compatibility layer providing the interface of the original package.

## 4 Lua functionality

### 4.1 Allocators in Lua

<code>new_attribute</code>	<code>luatexbase.new_attribute(&lt;attribute&gt;)</code>	Returns an allocation number for the <code>&lt;attribute&gt;</code> , indexed from 1. The attribute will be initialised with the marker value <code>-"7FFFFFFF</code> ('unset'). The attribute allocation sequence is shared with the T <sub>E</sub> X code but this function does <i>not</i> define a token using <code>\attributedef</code> . The attribute name is recorded in the <code>attributes</code> table. A metatable is provided so that the table syntax can be used consistently for attributes declared in T <sub>E</sub> X or Lua.
<code>new_whatsit</code>	<code>luatexbase.new_whatsit(&lt;whatsit&gt;)</code>	Returns an allocation number for the custom <code>&lt;whatsit&gt;</code> , indexed from 1.
<code>new_bytecode</code>	<code>luatexbase.new_bytecode(&lt;bytecode&gt;)</code>	Returns an allocation number for a bytecode register, indexed from 1. The optional <code>&lt;name&gt;</code> argument is just used for logging.
<code>new_chunkname</code>	<code>luatexbase.new_chunkname(&lt;chunkname&gt;)</code>	Returns an allocation number for a Lua chunk name for use with <code>\directlua</code> and <code>\latelua</code> , indexed from 1. The number is returned and also <code>&lt;name&gt;</code> argument is added to the <code>lua.name</code> array at that index.
<code>new_luafunction</code>	<code>luatexbase.new_luafunction(&lt;functionname&gt;)</code>	

Returns an allocation number for a lua function for use with `\luafunction`, `\lateluafunction`, and `\luadef`, indexed from 1. The optional `<functionname>` argument is just used for logging.

These functions all require access to a named T<sub>E</sub>X count register to manage their allocations. The standard names are those defined above for access from T<sub>E</sub>X, e.g. `\e@alloc@attribute@count`, but these can be adjusted by defining the variable `<type>_count_name` before loading `ltluatex.lua`, for example

```
local attribute_count_name = "attributetracker"
require("ltluatex")
```

would use a T<sub>E</sub>X `\count` (`\countdef`'d token) called `attributetracker` in place of `\e@alloc@attribute@count`.

## 4.2 Lua access to T<sub>E</sub>X register numbers

`registernumber` `luatexbase.registernumber(<name>)`

Sometimes (notably in the case of Lua attributes) it is necessary to access a register *by number* that has been allocated by T<sub>E</sub>X. This package provides a function to look up the relevant number using LuaT<sub>E</sub>X's internal tables. After for example `\newattribute\myattrib, \myattrib` would be defined by (say) `\myattrib=\attribute15`. `luatexbase.registernumber("myattrib")` would then return the register number, 15 in this case. If the string passed as argument does not correspond to a token defined by `\attributedef`, `\countdef` or similar commands, the Lua value `false` is returned.

As an example, consider the input:

```
\newcommand\test[1]{%
\typeout{#1: \expandafter\meaning\csname#1\endcsname^^J
\space\space\space\space
\directlua{tex.write(luatexbase.registernumber("#1") or "bad input")}}%
}

\test{undefinedrubbish}

\test{space}

\test{hbox}

\test{@MM}

\test{@tempdima}
\test{@tempdimb}

\test{strutbox}

\test{sixt@@n}

\attributedef\myattr=12
\myattr=200
\test{myattr}
```

If the demonstration code is processed with Lua $\text{\LaTeX}$  then the following would be produced in the log and terminal output.

```
undefinedrubbish: \relax
      bad input
space: macro:->
      bad input
hbox: \hbox
      bad input
@MM: \mathchar"4E20
      20000
@tempdima: \dimen14
      14
@tempdimb: \dimen15
      15
strutbox: \char"B
      11
sixt@@n: \char"10
      16
myattr: \attribute12
      12
```

Notice how undefined commands, or commands unrelated to registers do not produce an error, just return `false` and so print `bad input` here. Note also that commands defined by `\newbox` work and return the number of the box register even though the actual command holding this number is a `\chardef` defined token (there is no `\boxdef`).

### 4.3 Module utilities

`provides_module` `luatexbase.provides_module( $\langle info \rangle$ )`

This function is used by modules to identify themselves; the `info` should be a table containing information about the module. The required field `name` must contain the name of the module. It is recommended to provide a field `date` in the usual  $\text{\LaTeX}$  format `yyyy/mm/dd`. Optional fields `version` (a string) and `description` may be used if present. This information will be recorded in the log. Other fields are ignored. If the `version` begins with a digit, a `v` will be added at the start in the log.

`module_info` `luatexbase.module_info( $\langle module \rangle$ ,  $\langle text \rangle$ )`

`module_warning` `luatexbase.module_warning( $\langle module \rangle$ ,  $\langle text \rangle$ )`

`module_error` `luatexbase.module_error( $\langle module \rangle$ ,  $\langle text \rangle$ )`

These functions are similar to  $\text{\LaTeX}$ 's `\PackageError`, `\PackageWarning` and `\PackageInfo` in the way they format the output. No automatic line breaking is done, you may still use `\n` as usual for that, and the name of the package will be prepended to each output line.

Note that `luatexbase.module_error` raises an actual Lua error with `error()`, which currently means a call stack will be dumped. While this may not look pretty, at least it provides useful information for tracking the error down.

### 4.4 Callback management

`add_to_callback` `luatexbase.add_to_callback( $\langle callback \rangle$ ,  $\langle function \rangle$ ,  $\langle description \rangle$ )` Registers the  $\langle function \rangle$  into the  $\langle callback \rangle$  with a textual  $\langle description \rangle$  of the function. Functions are inserted into the callback in the order loaded.

**remove\_from\_callback** `luatexbase.remove_from_callback(<callback>, <description>)` Removes the callback function with *<description>* from the *<callback>*. The removed function and its description are returned as the results of this function.

**in\_callback** `luatexbase.in_callback(<callback>, <description>)` Checks if the *<description>* matches one of the functions added to the list for the *<callback>*, returning a boolean value.

**disable\_callback** `luatexbase.disable_callback(<callback>)` Sets the *<callback>* to `false` as described in the LuaTeX manual for the underlying `callback.register` built-in. Callbacks will only be set to false (and thus be skipped entirely) if there are no functions registered using the callback.

**callback\_descriptions** A list of the descriptions of functions registered to the specified callback is returned. {} is returned if there are no functions registered.

**create\_callback** `luatexbase.create_callback(<name>, <type>, <default>)` Defines a user defined callback. The last argument is a default function or `false`.

**call\_callback** `luatexbase.call_callback(<name>, ...)` Calls a user defined callback with the supplied arguments.

**declare\_callback\_rule** `luatexbase.declare_callback_rule(<name>, <first>, <relation>, <second>)` Adds an ordering constraint between two callback functions for callback *<name>*.  
The kind of constraint added depends on *<relation>*:

**before** The callback function with description *<first>* will be executed before the function with description *<second>*.

**after** The callback function with description *<first>* will be executed after the function with description *<second>*.

**incompatible-warning** When both a callback function with description *<first>* and with description *<second>* is registered, then a warning is printed when the callback is executed.

**incompatible-error** When both a callback function with description *<first>* and with description *<second>* is registered, then an error is printed when the callback is executed.

**unrelated** Any previously declared callback rule between *<first>* and *<second>* gets disabled.

Every call to `declare_callback_rule` with a specific callback *<name>* and descriptions *<first>* and *<second>* overwrites all previous calls with same callback and descriptions.

The callback functions do not have to be registered yet when the functions is called. Only the constraints for which both callback descriptions refer to callbacks registered at the time the callback is called will have an effect.

## 5 Implementation

```

1 <*2ekernel | tex | latexrelease>
2 <2ekernel | latexrelease> \ifx\directlua\@undefined\else

```

### 5.1 Minimum LuaTeX version

LuaTeX has changed a lot over time. In the kernel support for ancient versions is not provided: trying to build a format with a very old binary therefore gives some information

in the log and loading stops. The cut-off selected here relates to the tree-searching behaviour of `require()`: from version 0.60, LuaTeX will correctly find Lua files in the `texmf` tree without ‘help’.

```

3 <latexrelease>\IncludeInRelease{2015/10/01}
4 <latexrelease>          {\newluafunction}{LuaTeX}%
5 \ifnum\luatexversion<60 %
6   \wlog{*****}
7   \wlog{* LuaTeX version too old for ltuatex support *}
8   \wlog{*****}
9   \expandafter\endinput
10 \fi

```

Two simple L<sup>A</sup>T<sub>E</sub>X macros from `ltdefns.dtx` have to be defined here because `ltdefns.dtx` is not loaded yet when `ltluatex.dtx` is executed.

```

11 \long\def\@gobble#1{}
12 \long\def\@firstofone#1{#1}

```

## 5.2 Older L<sup>A</sup>T<sub>E</sub>X/Plain T<sub>E</sub>X setup

```

13 <*tex>

```

Older L<sup>A</sup>T<sub>E</sub>X formats don’t have the primitives with ‘native’ names: sort that out. If they already exist this will still be safe.

```

14 \directlua{tex.enableprimitives("",tex.extraprimitives("luatex"))}
15 \ifx\@alloc\@undefined

```

In pre-2014 L<sup>A</sup>T<sub>E</sub>X, or plain T<sub>E</sub>X, load `etex.{sty,src}`.

```

16 \ifx\documentclass\@undefined
17   \ifx\loccount\@undefined
18     \input{etex.src}%
19   \fi
20   \catcode'\@=11 %
21   \outer\expandafter\def\csname newfam\endcsname
22     {\alloc@8\fam\chardef\et@xmaxfam}
23 \else
24   \RequirePackage{etex}
25   \expandafter\def\csname newfam\endcsname
26     {\alloc@8\fam\chardef\et@xmaxfam}
27   \expandafter\let\expandafter\new@mathgroup\csname newfam\endcsname
28 \fi

```

### 5.2.1 Fixes to `etex.src/etex.sty`

These could and probably should be made directly in an update to `etex.src` which already has some LuaTeX-specific code, but does not define the correct range for LuaTeX.

2015-07-13 higher range in `luatex`.

```

29 \edef \et@xmaxregs {\ifx\directlua\@undefined 32768\else 65536\fi}

```

`luatex/xetex` also allow more math fam.

```

30 \edef \et@xmaxfam {\ifx\Umathcode\@undefined\sixt@@n\else@cclvi\fi}
31 \count 270=\et@xmaxregs % locally allocates \count registers
32 \count 271=\et@xmaxregs % ditto for \dimen registers
33 \count 272=\et@xmaxregs % ditto for \skip registers
34 \count 273=\et@xmaxregs % ditto for \muskip registers
35 \count 274=\et@xmaxregs % ditto for \box registers

```

```

36 \count 275=\et@xmaxregs % ditto for \toks registers
37 \count 276=\et@xmaxregs % ditto for \marks classes
    and 256 or 16 fam. (Done above due to plain/LATEX differences in luatex.)
38 % \outer\def\newfam{\alloc@8\fam\chardef\et@xmaxfam}
    End of proposed changes to etex.src

```

### 5.2.2 luatex specific settings

Switch to global cf `luatex.sty` to leave room for inserts not really needed for `luatex` but possibly most compatible with existing use.

```

39 \expandafter\let\csname newcount\expandafter\expandafter\endcsname
    \csname globcount\endcsname
40
41 \expandafter\let\csname newdimen\expandafter\expandafter\endcsname
    \csname globdimen\endcsname
42
43 \expandafter\let\csname newskip\expandafter\expandafter\endcsname
    \csname globskip\endcsname
44
45 \expandafter\let\csname newbox\expandafter\expandafter\endcsname
    \csname globbox\endcsname
46

```

Define `\e@alloc` as in L<sup>A</sup>T<sub>E</sub>X (the existing macros in `etex.src` are hard to extend to further register types as they assume specific 26x and 27x count range). For compatibility the existing register allocation is not changed.

```

47 \chardef\e@alloc@top=65535
48 \let\e@alloc\chardef\chardef
49 \def\e@alloc#1#2#3#4#5#6{%
50   \global\advance#3\@ne
51   \e@ch@ck{#3}{#4}{#5}#1%
52   \allocationnumber#3\relax
53   \global#2#6\allocationnumber
54   \wlog{\string#6=\string#1\the\allocationnumber}}%
55 \gdef\e@ch@ck#1#2#3#4{%
56   \ifnum#1<#2\else
57     \ifnum#1=#2\relax
58       #1\@ccclvi
59       \ifx\count#4\advance#1 10 \fi
60     \fi
61     \ifnum#1<#3\relax
62     \else
63       \errmessage{No room for a new \string#4}%
64     \fi
65   \fi}%

```

Fix up allocations not to clash with `etex.src`.

```

66 \expandafter\csname newcount\endcsname\e@alloc@attribute@count
67 \expandafter\csname newcount\endcsname\e@alloc@ccodetable@count
68 \expandafter\csname newcount\endcsname\e@alloc@luafunction@count
69 \expandafter\csname newcount\endcsname\e@alloc@whatsit@count
70 \expandafter\csname newcount\endcsname\e@alloc@bytecode@count
71 \expandafter\csname newcount\endcsname\e@alloc@luachunk@count

```

End of conditional setup for plain T<sub>E</sub>X / old L<sup>A</sup>T<sub>E</sub>X.

```

72 \fi
73 </tex>

```

## 5.3 Attributes

`\newattribute` As is generally the case for the LuaTeX registers we start here from 1. Notably, some code assumes that `\attribute0` is never used so this is important in this case.

```

74 \ifx\@alloc@attribute@count\@undefined
75   \countdef\@alloc@attribute@count=258
76   \@alloc@attribute@count=\z@
77 \fi
78 \def\newattribute#1{%
79   \@alloc@attribute@attributedef
80   \@alloc@attribute@count\m@ne\@alloc@top#1%
81 }
```

*(End of definition for \newattribute.)*

`\setattribute` Handy utilities.

```

\unsetattribute 82 \def\setattribute#1#2{#1=\numexpr#2\relax}
83 \def\unsetattribute#1{#1=-"7FFFFFFF\relax}
```

*(End of definition for \setattribute and \unsetattribute.)*

## 5.4 Category code tables

`\newcatcodetable` Category code tables are allocated with a limit half of that used by LuaTeX for everything else. At the end of allocation there needs to be an initialization step. Table 0 is already taken (it's the global one for current use) so the allocation starts at 1.

```

84 \ifx\@alloc@ccodetable@count\@undefined
85   \countdef\@alloc@ccodetable@count=259
86   \@alloc@ccodetable@count=\z@
87 \fi
88 \def\newcatcodetable#1{%
89   \@alloc@catcodetable\chardef
90   \@alloc@ccodetable@count\m@ne{"8000}#1%
91   \initcatcodetable\allocationnumber
92 }
```

*(End of definition for \newcatcodetable.)*

`\catcodetable@initex` Save a small set of standard tables. The Unicode data is read here in using a parser simplified from that in `load-unicode-data`: only the nature of letters needs to be detected.

`\catcodetable@string`

`\catcodetable@latex`

`\catcodetable@atletter`

```

93 \newcatcodetable\catcodetable@initex
94 \newcatcodetable\catcodetable@string
95 \begingroup
96   \def\setrangecatcode#1#2#3{%
97     \ifnum#1>#2 %
98       \expandafter\@gobble
99     \else
100      \expandafter\@firstofone
101    \fi
102    {%
103      \catcode#1=#3 %
104      \expandafter\setrangecatcode\expandafter
105        {\number\numexpr#1 + 1\relax}{#2}{#3}
106    }%
```

```

107 }
108 \@firstofone{%
109   \catcodetable\catcodetable@initex
110   \catcode0=12 %
111   \catcode13=12 %
112   \catcode37=12 %
113   \setrangecatcode{65}{90}{12}%
114   \setrangecatcode{97}{122}{12}%
115   \catcode92=12 %
116   \catcode127=12 %
117   \savecatcodetable\catcodetable@string
118   \endgroup
119 }%
120 \newcatcodetable\catcodetable@latex
121 \newcatcodetable\catcodetable@atletter
122 \beginingroup
123   \def\parseunicodedataI#1;#2;#3;#4\relax{%
124     \parseunicodedataII#1;#3;#2 First>\relax
125   }%
126   \def\parseunicodedataII#1;#2;#3 First>#4\relax{%
127     \ifx\relax#4\relax
128       \expandafter\parseunicodedataIII
129     \else
130       \expandafter\parseunicodedataIV
131     \fi
132     {#1}#2\relax%
133   }%
134   \def\parseunicodedataIII#1#2#3\relax{%
135     \ifnum 0%
136       \if L#21\fi
137       \if M#21\fi
138       >0 %
139       \catcode"#1=11 %
140     \fi
141   }%
142   \def\parseunicodedataIV#1#2#3\relax{%
143     \read\unicoderead to \unicodedataline
144     \if L#2%
145       \count0="#1 %
146       \expandafter\parseunicodedataV\unicodedataline\relax
147     \fi
148   }%
149   \def\parseunicodedataV#1;#2\relax{%
150     \loop
151       \unless\ifnum\count0>"#1 %
152       \catcode\count0=11 %
153       \advance\count0 by 1 %
154     \repeat
155   }%
156   \def\storedpar{\par}%
157   \chardef\unicoderead=\numexpr\count16 + 1\relax
158   \openin\unicoderead=UnicodeData.txt %
159   \loop\unless\ifeof\unicoderead %
160     \read\unicoderead to \unicodedataline

```

```

161 \unless\ifx\unicodedataline\storedpar
162 \expandafter\parseunicodedataI\unicodedataline\relax
163 \fi
164 \repeat
165 \closein\unicoderead
166 \@firstofone{%
167 \catcode64=12 %
168 \savecatcodetable\catcodetable@latex
169 \catcode64=11 %
170 \savecatcodetable\catcodetable@atletter
171 }
172 \endgroup

```

(End of definition for \catcodetable@initex and others.)

## 5.5 Named Lua functions

`\newluafunction` Much the same story for allocating LuaTeX functions except here they are just numbers so they are allocated in the same way as boxes. Lua indexes from 1 so once again slot 0 is skipped.

```

173 \ifx\e@alloc@luafunction@count\@undefined
174 \countdef\e@alloc@luafunction@count=260
175 \e@alloc@luafunction@count=\z@
176 \fi
177 \def\newluafunction{%
178 \e@alloc@luafunction\e@alloc@chardef
179 \e@alloc@luafunction@count\m@ne\e@alloc@top
180 }

```

(End of definition for \newluafunction.)

`\newluacmd` Additionally two variants are provided to make the passed control sequence call the function directly.

`\newprotectedluacmd`

```

181 \def\newluacmd{%
182 \e@alloc@luafunction\luadef
183 \e@alloc@luafunction@count\m@ne\e@alloc@top
184 }
185 \def\newprotectedluacmd{%
186 \e@alloc@luafunction{\protected\luadef}
187 \e@alloc@luafunction@count\m@ne\e@alloc@top
188 }

```

(End of definition for \newluacmd and \newprotectedluacmd.)

## 5.6 Custom whatsits

`\newwhatsit` These are only settable from Lua but for consistency are definable here.

```

189 \ifx\e@alloc@whatsit@count\@undefined
190 \countdef\e@alloc@whatsit@count=261
191 \e@alloc@whatsit@count=\z@
192 \fi
193 \def\newwhatsit#1{%
194 \e@alloc@whatsit\e@alloc@chardef
195 \e@alloc@whatsit@count\m@ne\e@alloc@top#1%
196 }

```

(End of definition for `\newwhatsit`.)

## 5.7 Lua bytecode registers

`\newluabytocode` These are only settable from Lua but for consistency are definable here.

```

197 \ifx\@alloc@bytecode@count\@undefined
198   \countdef\@alloc@bytecode@count=262
199   \@alloc@bytecode@count=\z@
200 \fi
201 \def\newluabytocode#1{%
202   \@alloc@luabytocode\@alloc@chardef
203   \@alloc@bytecode@count\m@ne\@alloc@top#1%
204 }
```

(End of definition for `\newluabytocode`.)

## 5.8 Lua chunk registers

`\newluachunkname` As for bytecode registers, but in addition we need to add a string to the `lua.name` table to use in stack tracing. We use the name of the command passed to the allocator, with no backslash.

```

205 \ifx\@alloc@luachunk@count\@undefined
206   \countdef\@alloc@luachunk@count=263
207   \@alloc@luachunk@count=\z@
208 \fi
209 \def\newluachunkname#1{%
210   \@alloc@luachunk\@alloc@chardef
211   \@alloc@luachunk@count\m@ne\@alloc@top#1%
212   {\escapechar\m@ne
213    \directlua{lua.name[\the\allocationnumber]="\string#1"}}%
214 }
```

(End of definition for `\newluachunkname`.)

## 5.9 Lua loader

Lua code loaded in the format often has to be loaded again at the beginning of every job, so we define a helper which allows us to avoid duplicated code:

```

215 \def\now@and@everyjob#1{%
216   \everyjob\expandafter{\the\everyjob
217     #1%
218   }%
219   #1%
220 }
```

Load the Lua code at the start of every job. For the conversion of  $\TeX$  into numbers at the Lua side we need some known registers: for convenience we use a set of systematic names, which means using a group around the Lua loader.

```

221 <2ekernel>\now@and@everyjob{%
222   \begingroup
223     \attributedef\attributezero=0 %
224     \chardef      \charzero      =0 %
```

Note name change required on older luatex, for hash table access.

```

225 \countdef \CountZero =0 %
226 \dimendef \dimenzero =0 %
227 \mathchardef \mathcharzero =0 %
228 \muskipdef \muskipzero =0 %
229 \skipdef \skipzero =0 %
230 \toksdef \tokszero =0 %
231 \directlua{require("ltnatex")}
232 \endgroup
233 <2ekernel>}
234 <latexrelease>\EndIncludeInRelease

235 <latexrelease>\IncludeInRelease{0000/00/00}
236 <latexrelease> {\newluafunction}{LuaTeX}%
237 <latexrelease>\let\@alloc@attribute@count\@undefined
238 <latexrelease>\let\newattribute\@undefined
239 <latexrelease>\let\setattribute\@undefined
240 <latexrelease>\let\unsetattribute\@undefined
241 <latexrelease>\let\@alloc@ccodetable@count\@undefined
242 <latexrelease>\let\newcatcodetable\@undefined
243 <latexrelease>\let\catcodetable@initex\@undefined
244 <latexrelease>\let\catcodetable@string\@undefined
245 <latexrelease>\let\catcodetable@latex\@undefined
246 <latexrelease>\let\catcodetable@atletter\@undefined
247 <latexrelease>\let\@alloc@luafunction@count\@undefined
248 <latexrelease>\let\newluafunction\@undefined
249 <latexrelease>\let\@alloc@luafunction@count\@undefined
250 <latexrelease>\let\newwhatsit\@undefined
251 <latexrelease>\let\@alloc@whatsit@count\@undefined
252 <latexrelease>\let\newluabytecode\@undefined
253 <latexrelease>\let\@alloc@bytecode@count\@undefined
254 <latexrelease>\let\newluachunkname\@undefined
255 <latexrelease>\let\@alloc@luachunk@count\@undefined
256 <latexrelease>\directlua{luatexbase.uninstall()}
257 <latexrelease>\EndIncludeInRelease

```

In \everyjob, if luaotfload is available, load it and switch to TU.

```

258 <latexrelease>\IncludeInRelease{2017/01/01}%
259 <latexrelease> {\fontencoding}{TU in everyjob}%
260 <latexrelease>\fontencoding{TU}\let\encodingdefault\fontencoding
261 <latexrelease>\ifx\directlua\@undefined\else
262 <2ekernel>\everyjob\expandafter{%
263 <2ekernel> \the\everyjob
264 <*2ekernel, latexrelease>
265 \directlua{%
266 if xpcall(function ()%
267 require('luaotfload-main')%
268 end, texio.write_nl) then %
269 local _void = luaotfload.main ()%
270 else %
271 texio.write_nl('Error in luaotfload: reverting to OT1')%
272 tex.print('\string\def\string\encodingdefault{OT1}')%
273 end %
274 }%

```

```

275 \let\fontencoding\encodingdefault
276 \expandafter\let\csname ver@luaotfload.sty\endcsname\fmtversion
277 </2ekernel, latexrelease>
278 <latexrelease>\fi
279 <2ekernel> }
280 <latexrelease>\EndIncludeInRelease
281 <latexrelease>\IncludeInRelease{0000/00/00}%
282 <latexrelease>{\fontencoding}{TU in everyjob}%
283 <latexrelease>\fontencoding{OT1}\let\encodingdefault\fontencoding
284 <latexrelease>\EndIncludeInRelease

285 <2ekernel | latexrelease>\fi
286 </2ekernel | tex | latexrelease>

```

## 5.10 Lua module preliminaries

```

287 <*lua>

```

Some set up for the Lua module which is needed for all of the Lua functionality added here.

**luatexbase** Set up the table for the returned functions. This is used to expose all of the public functions.

```

288 luatexbase = luatexbase or { }
289 local luatexbase = luatexbase

```

*(End of definition for luatexbase.)*

Some Lua best practice: use local versions of functions where possible.

```

290 local string_gsub = string.gsub
291 local tex_count = tex.count
292 local tex_setcount = tex.setcount
293 local texio_write_nl = texio.write_nl
294 local flush_list = node.flush_list

295 local luatexbase_warning
296 local luatexbase_error

```

## 5.11 Lua module utilities

### 5.11.1 Module tracking

**modules** To allow tracking of module usage, a structure is provided to store information and to return it.

```

297 local modules = modules or { }

```

*(End of definition for modules.)*

**provides\_module** Local function to write to the log.

```

298 local function luatexbase_log(text)
299   texio_write_nl("log", text)
300 end

```

Modelled on `\ProvidesPackage`, we store much the same information but with a little more structure.

```

301 local function provides_module(info)
302   if not (info and info.name) then
303     luatexbase_error("Missing module name for provides_module")
304   end
305   local function spaced(text)
306     return text and (" " .. text) or ""
307   end
308   luatexbase_log(
309     "Lua module: " .. info.name
310     .. spaced(info.date)
311     .. spaced(info.version and string_gsub(info.version or "", "^(%d)", "v%1"))
312     .. spaced(info.description)
313   )
314   modules[info.name] = info
315 end
316 luatexbase.provides_module = provides_module

```

*(End of definition for provides\_module.)*

### 5.11.2 Module messages

There are various warnings and errors that need to be given. For warnings we can get exactly the same formatting as from `TEX`. For errors we have to make some changes. Here we give the text of the error in the `LATEX` format then force an error from Lua to halt the run. Splitting the message text is done using `\n` which takes the place of `\MessageBreak`.

First an auxiliary for the formatting: this measures up the message leader so we always get the correct indent.

```

317 local function msg_format(mod, msg_type, text)
318   local leader = ""
319   local cont
320   local first_head
321   if mod == "LaTeX" then
322     cont = string_gsub(leader, ".", " ")
323     first_head = leader .. "LaTeX: "
324   else
325     first_head = leader .. "Module " .. msg_type
326     cont = "(" .. mod .. ")"
327     .. string_gsub(first_head, ".", " ")
328     first_head = leader .. "Module " .. mod .. " " .. msg_type .. ":"
329   end
330   if msg_type == "Error" then
331     first_head = "\n" .. first_head
332   end
333   if string.sub(text, -1) ~= "\n" then
334     text = text .. " "
335   end
336   return first_head .. " "
337     .. string_gsub(
338       text
339       .. "on input line "

```

```

340         .. tex.inputlineno, "\n", "\n" .. cont .. " "
341     )
342     .. "\n"
343 end

module_info Write messages.
module_warning 344 local function module_info(mod, text)
module_error 345     texio_write_nl("log", msg_format(mod, "Info", text))
346 end
347 luatexbase.module_info = module_info
348 local function module_warning(mod, text)
349     texio_write_nl("term and log", msg_format(mod, "Warning", text))
350 end
351 luatexbase.module_warning = module_warning
352 local function module_error(mod, text)
353     error(msg_format(mod, "Error", text))
354 end
355 luatexbase.module_error = module_error

(End of definition for module_info, module_warning, and module_error.)
    Dedicated versions for the rest of the code here.

356 function luatexbase_warning(text)
357     module_warning("luatexbase", text)
358 end
359 function luatexbase_error(text)
360     module_error("luatexbase", text)
361 end

```

## 5.12 Accessing register numbers from Lua

Collect up the data from the T<sub>E</sub>X level into a Lua table: from version 0.80, LuaT<sub>E</sub>X makes that easy.

```

362 local luaregisterbasetable = { }
363 local registermap = {
364     attributezero = "assign_attr"    ,
365     charzero      = "char_given"     ,
366     CountZero     = "assign_int"     ,
367     dimenzero     = "assign_dimen"   ,
368     mathcharzero  = "math_given"     ,
369     muskipzero    = "assign_mu_skip" ,
370     skipzero      = "assign_skip"    ,
371     tokszero      = "assign_toks"    ,
372 }
373 local createtoken
374 if tex.luatexversion > 81 then
375     createtoken = token.create
376 elseif tex.luatexversion > 79 then
377     createtoken = newtoken.create
378 end
379 local hashtokens = tex.hashtokens()
380 local luatexversion = tex.luatexversion
381 for i,j in pairs (registermap) do
382     if luatexversion < 80 then

```

```

383     luaregisterbasetable[hashtokens[i][1]] =
384         hashtokens[i][2]
385     else
386         luaregisterbasetable[j] = createtoken(i).mode
387     end
388 end

```

**registernumber** Working out the correct return value can be done in two ways. For older LuaTeX releases it has to be extracted from the `hashtokens`. On the other hand, newer LuaTeX's have `newtoken`, and whilst `.mode` isn't currently documented, Hans Hagen pointed to this approach so we should be OK.

```

389 local registernumber
390 if luatexversion < 80 then
391     function registernumber(name)
392         local nt = hashtokens[name]
393         if(nt and luaregisterbasetable[nt[1]]) then
394             return nt[2] - luaregisterbasetable[nt[1]]
395         else
396             return false
397         end
398     end
399 else
400     function registernumber(name)
401         local nt = createtoken(name)
402         if(luaregisterbasetable[nt.cmdname]) then
403             return nt.mode - luaregisterbasetable[nt.cmdname]
404         else
405             return false
406         end
407     end
408 end
409 luatexbase.registernumber = registernumber

```

*(End of definition for registernumber.)*

## 5.13 Attribute allocation

**new\_attribute** As attributes are used for Lua manipulations its useful to be able to assign from this end.

```

410 local attributes=setmetatable(
411     {},
412     {
413         __index = function(t,key)
414             return registernumber(key) or nil
415         end}
416 )
417 luatexbase.attributes = attributes
418 local attribute_count_name =
419     attribute_count_name or "e@alloc@attribute@count"
420 local function new_attribute(name)
421     tex_setcount("global", attribute_count_name,
422                 tex_count[attribute_count_name] + 1)
423     if tex_count[attribute_count_name] > 65534 then
424         luatexbase_error("No room for a new \\attribute")

```

```

425     end
426     attributes[name]= tex_count[attribute_count_name]
427     luatexbase_log("Lua-only attribute " .. name .. " = " ..
428                   tex_count[attribute_count_name])
429     return tex_count[attribute_count_name]
430 end
431 luatexbase.new_attribute = new_attribute

```

*(End of definition for new\_attribute.)*

## 5.14 Custom whatsit allocation

**new\_whatsit** Much the same as for attribute allocation in Lua.

```

432 local whatsit_count_name = whatsit_count_name or "e@alloc@whatsit@count"
433 local function new_whatsit(name)
434     tex_setcount("global", whatsit_count_name,
435                 tex_count[whatsit_count_name] + 1)
436     if tex_count[whatsit_count_name] > 65534 then
437         luatexbase_error("No room for a new custom whatsit")
438     end
439     luatexbase_log("Custom whatsit " .. (name or "") .. " = " ..
440                 tex_count[whatsit_count_name])
441     return tex_count[whatsit_count_name]
442 end
443 luatexbase.new_whatsit = new_whatsit

```

*(End of definition for new\_whatsit.)*

## 5.15 Bytecode register allocation

**new\_bytecode** Much the same as for attribute allocation in Lua. The optional *<name>* argument is used in the log if given.

```

444 local bytecode_count_name =
445     bytecode_count_name or "e@alloc@bytecode@count"
446 local function new_bytecode(name)
447     tex_setcount("global", bytecode_count_name,
448                 tex_count[bytecode_count_name] + 1)
449     if tex_count[bytecode_count_name] > 65534 then
450         luatexbase_error("No room for a new bytecode register")
451     end
452     luatexbase_log("Lua bytecode " .. (name or "") .. " = " ..
453                 tex_count[bytecode_count_name])
454     return tex_count[bytecode_count_name]
455 end
456 luatexbase.new_bytecode = new_bytecode

```

*(End of definition for new\_bytecode.)*

## 5.16 Lua chunk name allocation

**new\_chunkname** As for bytecode registers but also store the name in the lua.name table.

```

457 local chunkname_count_name =
458     chunkname_count_name or "e@alloc@luachunk@count"
459 local function new_chunkname(name)

```

```

460 tex_setcount("global", chunkname_count_name,
461             tex_count[chunkname_count_name] + 1)
462 local chunkname_count = tex_count[chunkname_count_name]
463 chunkname_count = chunkname_count + 1
464 if chunkname_count > 65534 then
465     luatexbase_error("No room for a new chunkname")
466 end
467 lua.name[chunkname_count]=name
468 luatexbase_log("Lua chunkname " .. (name or "") .. " = " ..
469             chunkname_count .. "\n")
470 return chunkname_count
471 end
472 luatexbase.new_chunkname = new_chunkname

```

*(End of definition for new\_chunkname.)*

## 5.17 Lua function allocation

**new\_luafunction** Much the same as for attribute allocation in Lua. The optional *<name>* argument is used in the log if given.

```

473 local luafunction_count_name =
474             luafunction_count_name or "e@alloc@luafunction@count"
475 local function new_luafunction(name)
476     tex_setcount("global", luafunction_count_name,
477             math.max(
478                 #(lua.get_functions_table()),
479                 tex_count[luafunction_count_name])
480             + 1)
481     lua.get_functions_table()[tex_count[luafunction_count_name]] = false
482     if tex_count[luafunction_count_name] > 65534 then
483         luatexbase_error("No room for a new luafunction register")
484     end
485     luatexbase_log("Lua function " .. (name or "") .. " = " ..
486             tex_count[luafunction_count_name])
487     return tex_count[luafunction_count_name]
488 end
489 luatexbase.new_luafunction = new_luafunction

```

*(End of definition for new\_luafunction.)*

## 5.18 Lua callback management

The native mechanism for callbacks in LuaTeX allows only one per function. That is extremely restrictive and so a mechanism is needed to add and remove callbacks from the appropriate hooks.

### 5.18.1 Housekeeping

The main table: keys are callback names, and values are the associated lists of functions. More precisely, the entries in the list are tables holding the actual function as **func** and the identifying description as **description**. Only callbacks with a non-empty list of functions have an entry in this list.

Actually there are two tables: `realcallbacklist` directly contains the entries as described above while `callbacklist` only directly contains the already sorted entries. Other entries can be queried through `callbacklist` too which triggers a resort.

Additionally `callbackrules` describes the ordering constraints: It contains two element tables with the descriptions of the constrained callback implementations. It can additionally contain a `type` entry indicating the kind of rule. A missing value indicates a normal ordering constraint.

```

490 local realcallbacklist = {}
491 local callbackrules = {}
492 local callbacklist = setmetatable({}, {
493   __index = function(t, name)
494     local list = realcallbacklist[name]
495     local rules = callbackrules[name]
496     if list and rules then
497       local meta = {}
498       for i, entry in ipairs(list) do
499         local t = {value = entry, count = 0, pos = i}
500         meta[entry.description], list[i] = t, t
501       end
502       local count = #list
503       local pos = count
504       for i, rule in ipairs(rules) do
505         local rule = rules[i]
506         local pre, post = meta[rule[1]], meta[rule[2]]
507         if pre and post then
508           if rule.type then
509             if not rule.hidden then
510               assert(rule.type == 'incompatible-warning' and luatexbase_warning
511                 or rule.type == 'incompatible-error' and luatexbase_error)(
512                 "Incompatible functions \"" .. rule[1] .. "\" and \"" .. rule[2]
513                 .. "\" specified for callback \"" .. name .. "\".")
514               rule.hidden = true
515             end
516           else
517             local post_count = post.count
518             post.count = post_count+1
519             if post_count == 0 then
520               local post_pos = post.pos
521               if post_pos ~= pos then
522                 local new_post_pos = list[pos]
523                 new_post_pos.pos = post_pos
524                 list[post_pos] = new_post_pos
525               end
526               list[pos] = nil
527               pos = pos - 1
528             end
529             pre[#pre+1] = post
530           end
531         end
532       end
533       for i=1, count do -- The actual sort begins
534         local current = list[i]
535         if current then

```

```

536     meta[current.value.description] = nil
537   for j, cur in ipairs(current) do
538     local count = cur.count
539     if count == 1 then
540       pos = pos + 1
541       list[pos] = cur
542     else
543       cur.count = count - 1
544     end
545   end
546   list[i] = current.value
547 else
548   -- Cycle occurred. TODO: Show cycle for debugging
549   -- list[i] = ...
550   local remaining = {}
551   for name, entry in next, meta do
552     local value = entry.value
553     list[#list + 1] = entry.value
554     remaining[#remaining + 1] = name
555   end
556   table.sort(remaining)
557   local first_name = remaining[1]
558   for j, name in ipairs(remaining) do
559     local entry = meta[name]
560     list[i + j - 1] = entry.value
561     for _, post_entry in ipairs(entry) do
562       local post_name = post_entry.value.description
563       if not remaining[post_name] then
564         remaining[post_name] = name
565       end
566     end
567   end
568   local cycle = {first_name}
569   local index = 1
570   local last_name = first_name
571   repeat
572     cycle[last_name] = index
573     last_name = remaining[last_name]
574     index = index + 1
575     cycle[index] = last_name
576   until cycle[last_name]
577   local length = index - cycle[last_name] + 1
578   table.move(cycle, cycle[last_name], index, 1)
579   for i=2, length//2 do
580     cycle[i], cycle[length + 1 - i] = cycle[length + 1 - i], cycle[i]
581   end
582   error('Cycle occurred at ' .. table.concat(cycle, ' -> ', 1, length))
583 end
584 end
585 end
586 realcallbacklist[name] = list
587 t[name] = list
588 return list
589 end

```

```
590 })
```

Numerical codes for callback types, and name-to-value association (the table keys are strings, the values are numbers).

```
591 local list, data, exclusive, simple, reverselist = 1, 2, 3, 4, 5
592 local types = {
593   list      = list,
594   data      = data,
595   exclusive = exclusive,
596   simple    = simple,
597   reverselist = reverselist,
598 }
```

Now, list all predefined callbacks with their current type, based on the LuaTeX manual version 1.01. A full list of the currently-available callbacks can be obtained using

```
\directlua{
  for i,_ in pairs(callback.list()) do
    texio.write_nl("- " .. i)
  end
}
\bye
```

in plain LuaTeX. (Some undocumented callbacks are omitted as they are to be removed.)

```
599 local callbacktypes = callbacktypes or {
```

Section 8.2: file discovery callbacks.

```
600   find_read_file      = exclusive,
601   find_write_file     = exclusive,
602   find_font_file      = data,
603   find_output_file    = data,
604   find_format_file    = data,
605   find_vf_file        = data,
606   find_map_file       = data,
607   find_enc_file       = data,
608   find_pk_file        = data,
609   find_data_file      = data,
610   find_opentype_file  = data,
611   find_truetype_file  = data,
612   find_type1_file     = data,
613   find_image_file     = data,

614   open_read_file      = exclusive,
615   read_font_file      = exclusive,
616   read_vf_file        = exclusive,
617   read_map_file       = exclusive,
618   read_enc_file       = exclusive,
619   read_pk_file        = exclusive,
620   read_data_file      = exclusive,
621   read_truetype_file  = exclusive,
622   read_type1_file     = exclusive,
623   read_opentype_file  = exclusive,
```

Not currently used by luatex but included for completeness. may be used by a font handler.

```

624 find_cidmap_file    = data,
625 read_cidmap_file    = exclusive,

```

Section 8.3: data processing callbacks.

```

626 process_input_buffer = data,
627 process_output_buffer = data,
628 process_jobname      = data,

```

Section 8.4: node list processing callbacks.

```

629 contribute_filter    = simple,
630 buildpage_filter     = simple,
631 build_page_insert    = exclusive,
632 pre_linebreak_filter = list,
633 linebreak_filter      = exclusive,
634 append_to_vlist_filter = exclusive,
635 post_linebreak_filter = reverselist,
636 hpack_filter          = list,
637 vpack_filter          = list,
638 hpack_quality         = exclusive,
639 vpack_quality         = exclusive,
640 pre_output_filter     = list,
641 process_rule          = exclusive,
642 hyphenate             = simple,
643 ligaturing            = simple,
644 kerning               = simple,
645 insert_local_par      = simple,
646 % mlist_to_hlist      = exclusive,
647 new_graf              = exclusive,

```

Section 8.5: information reporting callbacks.

```

648 pre_dump              = simple,
649 start_run             = simple,
650 stop_run              = simple,
651 start_page_number     = simple,
652 stop_page_number      = simple,
653 show_error_hook       = simple,
654 show_warning_message  = simple,
655 show_error_message    = simple,
656 show_lua_error_hook   = simple,
657 start_file            = simple,
658 stop_file             = simple,
659 call_edit             = simple,
660 finish_synctex        = simple,
661 wrapup_run            = simple,

```

Section 8.6: PDF-related callbacks.

```

662 finish_pdffile        = data,
663 finish_pdfpage        = data,
664 page_objnum_provider  = data,
665 page_order_index      = data,
666 process_pdf_image_content = data,

```

Section 8.7: font-related callbacks.

```

667 define_font           = exclusive,
668 glyph_info            = exclusive,
669 glyph_not_found       = exclusive,

```

```

670 glyph_stream_provider      = exclusive,
671 make_extensible            = exclusive,
672 font_descriptor_objnum_provider = exclusive,
673 input_level_string          = exclusive,
674 provide_charproc_data       = exclusive,
675 }
676 luatexbase.callbacktypes=callbacktypes

```

Sometimes multiple callbacks correspond to a single underlying engine level callback. Then the engine level callback should be registered as long as at least one of these callbacks is in use. This is implemented though a shared table which counts how many of the involved callbacks are currently in use. The engine level callback is registered iff this count is not 0.

We add `mlist_to_hlist` directly to the list to demonstrate this, but the handler gets added later when it is actually defined.

All callbacks in this list are treated as user defined callbacks.

```

677 local shared_callbacks = {
678   mlist_to_hlist = {
679     callback = "mlist_to_hlist",
680     count = 0,
681     handler = nil,
682   },
683 }
684 shared_callbacks.pre_mlist_to_hlist_filter = shared_callbacks.mlist_to_hlist
685 shared_callbacks.post_mlist_to_hlist_filter = shared_callbacks.mlist_to_hlist

```

`callback.register` Save the original function for registering callbacks and prevent the original being used. The original is saved in a place that remains available so other more sophisticated code can override the approach taken by the kernel if desired.

```

686 local callback_register = callback_register or callback.register
687 function callback.register()
688   luatexbase_error("Attempt to use callback.register() directly\n")
689 end

```

*(End of definition for `callback.register`.)*

### 5.18.2 Handlers

The handler function is registered into the callback when the first function is added to this callback's list. Then, when the callback is called, the handler takes care of running all functions in the list. When the last function is removed from the callback's list, the handler is unregistered.

More precisely, the functions below are used to generate a specialized function (closure) for a given callback, which is the actual handler.

The way the functions are combined together depends on the type of the callback. There are currently 4 types of callback, depending on the calling convention of the functions the callback can hold:

**simple** is for functions that don't return anything: they are called in order, all with the same argument;

**data** is for functions receiving a piece of data of any type except node list head (and possibly other arguments) and returning it (possibly modified): the functions are called in order, and each is passed the return value of the previous (and the other arguments untouched, if any). The return value is that of the last function;

**list** is a specialized variant of *data* for functions filtering node lists. Such functions are called with a node list head as the first argument and may return either the head of a modified node list, or the boolean values **true** or **false**. The functions are chained the same way as for *data* except for the following cases. If a function returns **false**, then **false** is immediately returned and the following functions are *not* called. If a function returns **true**, then the same head is passed to the next function. If all functions return **true**, then the original head is returned, otherwise the return value of the last function not returning **true** is used.

**reverselist** is a specialized variant of *list* which executes functions in inverse order.

**exclusive** is for functions with more complex signatures; functions in this type of callback are *not* combined: An error is raised if a second callback is registered.

Handler for **data** callbacks.

```
690 local function data_handler(name)
691   return function(data, ...)
692     for _,i in ipairs(callbacklist[name]) do
693       data = i.func(data,...)
694     end
695     return data
696   end
697 end
```

Default for user-defined **data** callbacks without explicit default.

```
698 local function data_handler_default(value)
699   return value
700 end
```

Handler for **exclusive** callbacks. We can assume `callbacklist[name]` is not empty: otherwise, the function wouldn't be registered in the callback any more.

```
701 local function exclusive_handler(name)
702   return function(...)
703     return callbacklist[name][1].func(...)
704   end
705 end
```

Handler for **list** callbacks.

```
706 local function list_handler(name)
707   return function(head, ...)
708     local ret
709     for _,i in ipairs(callbacklist[name]) do
710       ret = i.func(head, ...)
711       if ret == false then
712         luatexbase_warning(
713           "Function '" .. i.description .. "' returned false\n"
714           .. "in callback '" .. name .. "'")
715       )
716       return false
717     end
```

```

718     if ret ~= true then
719         head = ret
720     end
721 end
722 return head
723 end
724 end

```

Default for user-defined `list` and `reverselist` callbacks without explicit default.

```

725 local function list_handler_default(head)
726 return head
727 end

```

Handler for `reverselist` callbacks.

```

728 local function reverselist_handler(name)
729 return function(head, ...)
730     local ret
731     local callbacks = callbacklist[name]
732     for i = #callbacks, 1, -1 do
733         local cb = callbacks[i]
734         ret = cb.func(head, ...)
735         if ret == false then
736             luatexbase_warning(
737                 "Function '" .. cb.description .. "' returned false\n"
738                 .. "in callback '" .. name .. "'")
739         )
740         return false
741     end
742     if ret ~= true then
743         head = ret
744     end
745 end
746 return head
747 end
748 end

```

Handler for `simple` callbacks.

```

749 local function simple_handler(name)
750 return function(...)
751     for _,i in ipairs(callbacklist[name]) do
752         i.func(...)
753     end
754 end
755 end

```

Default for user-defined `simple` callbacks without explicit default.

```

756 local function simple_handler_default()
757 end

```

Keep a handlers table for indexed access and a table with the corresponding default functions.

```

758 local handlers = {
759     [data] = data_handler,
760     [exclusive] = exclusive_handler,
761     [list] = list_handler,
762     [reverselist] = reverselist_handler,

```

```

763 [simple]      = simple_handler,
764 }
765 local defaults = {
766 [data]       = data_handler_default,
767 [exclusive]  = nil,
768 [list]       = list_handler_default,
769 [reverselist] = list_handler_default,
770 [simple]      = simple_handler_default,
771 }

```

### 5.18.3 Public functions for callback management

Defining user callbacks perhaps should be in package code, but impacts on `add_to_callback`. If a default function is not required, it may be declared as `false`. First we need a list of user callbacks.

```

772 local user_callbacks_defaults = {}

```

`create_callback` The allocator itself.

```

773 local function create_callback(name, ctype, default)
774   local ctype_id = types[ctype]
775   if not name or name == ""
776   or not ctype_id
777   then
778     luatexbase_error("Unable to create callback:\n" ..
779                       "valid callback name and type required")
780   end
781   if callbacktypes[name] then
782     luatexbase_error("Unable to create callback '" .. name ..
783                       "':\ncallback is already defined")
784   end
785   default = default or defaults[ctype_id]
786   if not default then
787     luatexbase_error("Unable to create callback '" .. name ..
788                       "':\ndefault is required for '" .. ctype ..
789                       "' callbacks")
790   elseif type (default) ~= "function" then
791     luatexbase_error("Unable to create callback '" .. name ..
792                       "':\ndefault is not a function")
793   end
794   user_callbacks_defaults[name] = default
795   callbacktypes[name] = ctype_id
796 end
797 luatexbase.create_callback = create_callback

```

*(End of definition for create\_callback.)*

`call_callback` Call a user defined callback. First check arguments.

```

798 local function call_callback(name,...)
799   if not name or name == "" then
800     luatexbase_error("Unable to create callback:\n" ..
801                       "valid callback name required")
802   end
803   if user_callbacks_defaults[name] == nil then
804     luatexbase_error("Unable to call callback '" .. name

```

```

805         .. ":\unknown or empty")
806     end
807     local l = callbacklist[name]
808     local f
809     if not l then
810         f = user_callbacks_defaults[name]
811     else
812         f = handlers[callbacktypes[name]](name)
813     end
814     return f(...)
815 end
816 luatexbase.call_callback=call_callback

```

(End of definition for call\_callback.)

**add\_to\_callback** Add a function to a callback. First check arguments.

```

817 local function add_to_callback(name, func, description)
818     if not name or name == "" then
819         luatexbase_error("Unable to register callback:\n" ..
820             "valid callback name required")
821     end
822     if not callbacktypes[name] or
823         type(func) ~= "function" or
824         not description or
825         description == "" then
826         luatexbase_error(
827             "Unable to register callback.\n\n"
828             .. "Correct usage:\n"
829             .. "add_to_callback(<callback>, <function>, <description>)"
830         )
831     end

```

Then test if this callback is already in use. If not, initialise its list and register the proper handler.

```

832     local l = realcallbacklist[name]
833     if l == nil then
834         l = { }
835         realcallbacklist[name] = l

```

Handle count for shared engine callbacks.

```

836     local shared = shared_callbacks[name]
837     if shared then
838         shared.count = shared.count + 1
839         if shared.count == 1 then
840             callback_register(shared.callback, shared.handler)
841         end

```

If it is not a user defined callback use the primitive callback register.

```

842     elseif user_callbacks_defaults[name] == nil then
843         callback_register(name, handlers[callbacktypes[name]](name))
844     end
845 end

```

Actually register the function and give an error if more than one **exclusive** one is registered.

```

846     local f = {

```

```

847     func          = func,
848     description = description,
849   }
850   if callbacktypes[name] == exclusive then
851     if #l == 1 then
852       luatexbase_error(
853         "Cannot add second callback to exclusive function\n'" ..
854         name .. "'"")
855     end
856   end
857   table.insert(l, f)
858   callbacklist[name] = nil

```

Keep user informed.

```

859   luatexbase_log(
860     "Inserting '" .. description .. "' in '" .. name .. "'"")
861   )
862 end
863 luatexbase.add_to_callback = add_to_callback

```

*(End of definition for add\_to\_callback.)*

**declare\_callback\_rule** Add an ordering constraint between two callback implementations

```

864 local function declare_callback_rule(name, desc1, relation, desc2)
865   if not callbacktypes[name] or
866     not desc1 or not desc2 or
867     desc1 == "" or desc2 == "" then
868     luatexbase_error(
869       "Unable to create ordering constraint. "
870       .. "Correct usage:\n"
871       .. "declare_callback_rule(<callback>, <description_a>, <description_b>)"
872     )
873   end
874   if relation == 'before' then
875     relation = nil
876   elseif relation == 'after' then
877     desc2, desc1 = desc1, desc2
878     relation = nil
879   elseif relation == 'incompatible-warning' or relation == 'incompatible-error' then
880   elseif relation == 'unrelated' then
881   else
882     luatexbase_error(
883       "Unknown relation type in declare_callback_rule"
884     )
885   end
886   callbacklist[name] = nil
887   local rules = callbackrules[name]
888   if rules then
889     for i, rule in ipairs(rules) do
890       if rule[1] == desc1 and rule[2] == desc2 or rule[1] == desc2 and rule[2] == desc1 then
891         if relation == 'unrelated' then
892           table.remove(rules, i)
893         else
894           rule[1], rule[2], rule.type = desc1, desc2, relation
895         end
896       end
897     end
898   end

```

```

896         return
897     end
898 end
899 if relation ~= 'unrelated' then
900     rules[#rules + 1] = {desc1, desc2, type = relation}
901 end
902 elseif relation ~= 'unrelated' then
903     callbackrules[name] = {{desc1, desc2, type = relation}}
904 end
905 end
906 luatexbase.declare_callback_rule = declare_callback_rule

```

(End of definition for declare\_callback\_rule.)

**remove\_from\_callback** Remove a function from a callback. First check arguments.

```

907 local function remove_from_callback(name, description)
908     if not name or name == "" then
909         luatexbase_error("Unable to remove function from callback:\n" ..
910             "valid callback name required")
911     end
912     if not callbacktypes[name] or
913         not description or
914         description == "" then
915         luatexbase_error(
916             "Unable to remove function from callback.\n\n"
917             .. "Correct usage:\n"
918             .. "remove_from_callback(<callback>, <description>)"
919         )
920     end
921     local l = realcallbacklist[name]
922     if not l then
923         luatexbase_error(
924             "No callback list for '" .. name .. "'\n")
925     end

```

Loop over the callback's function list until we find a matching entry. Remove it and check if the list is empty: if so, unregister the callback handler.

```

926     local index = false
927     for i,j in ipairs(l) do
928         if j.description == description then
929             index = i
930             break
931         end
932     end
933     if not index then
934         luatexbase_error(
935             "No callback '" .. description .. "' registered for '" ..
936             name .. "'\n")
937     end
938     local cb = l[index]
939     table.remove(l, index)
940     luatexbase_log(
941         "Removing '" .. description .. "' from '" .. name .. "'."
942     )
943     if #l == 0 then

```

```

944     realcallbacklist[name] = nil
945     callbacklist[name] = nil
946     local shared = shared_callbacks[name]
947     if shared then
948         shared.count = shared.count - 1
949         if shared.count == 0 then
950             callback_register(shared.callback, nil)
951         end
952     elseif user_callbacks_defaults[name] == nil then
953         callback_register(name, nil)
954     end
955 end
956 return cb.func,cb.description
957 end
958 luatexbase.remove_from_callback = remove_from_callback

```

*(End of definition for remove\_from\_callback.)*

**in\_callback** Look for a function description in a callback.

```

959 local function in_callback(name, description)
960     if not name
961         or name == ""
962         or not realcallbacklist[name]
963         or not callbacktypes[name]
964         or not description then
965         return false
966     end
967     for _, i in pairs(realcallbacklist[name]) do
968         if i.description == description then
969             return true
970         end
971     end
972     return false
973 end
974 luatexbase.in_callback = in_callback

```

*(End of definition for in\_callback.)*

**disable\_callback** As we subvert the engine interface we need to provide a way to access this functionality.

```

975 local function disable_callback(name)
976     if(realcallbacklist[name] == nil) then
977         callback_register(name, false)
978     else
979         luatexbase_error("Callback list for " .. name .. " not empty")
980     end
981 end
982 luatexbase.disable_callback = disable_callback

```

*(End of definition for disable\_callback.)*

**callback\_descriptions** List the descriptions of functions registered for the given callback. This will sort the list if necessary.

```

983 local function callback_descriptions (name)
984     local d = {}
985     if not name

```

```

986     or name == ""
987     or not realcallbacklist[name]
988     or not callbacktypes[name]
989     then
990         return d
991     else
992     for k, i in pairs(callbacklist[name]) do
993         d[k]= i.description
994     end
995     end
996     return d
997 end
998 luatexbase.callback_descriptions =callback_descriptions

```

(End of definition for callback\_descriptions.)

**uninstall** Unlike at the TeX level, we have to provide a back-out mechanism here at the same time as the rest of the code. This is not meant for use by anything other than latexrelease: as such this is *deliberately* not documented for users!

```

999 local function uninstall()
1000     module_info(
1001         "luatexbase",
1002         "Uninstalling kernel luatexbase code"
1003     )
1004     callback.register = callback_register
1005     luatexbase = nil
1006 end
1007 luatexbase.uninstall = uninstall

```

(End of definition for uninstall.)

**mlist\_to\_hlist** To emulate these callbacks, the “real” mlist\_to\_hlist is replaced by a wrapper calling the wrappers before and after.

```

1008 create_callback('pre_mlist_to_hlist_filter', 'list')
1009 create_callback('mlist_to_hlist', 'exclusive', node.mlist_to_hlist)
1010 create_callback('post_mlist_to_hlist_filter', 'reverselist')
1011 function shared_callbacks.mlist_to_hlist.handler(head, display_type, need_penalties)
1012     local current = call_callback("pre_mlist_to_hlist_filter", head, display_type, need_penalties)
1013     if current == false then
1014         flush_list(head)
1015         return nil
1016     end
1017     current = call_callback("mlist_to_hlist", current, display_type, need_penalties)
1018     local post = call_callback("post_mlist_to_hlist_filter", current, display_type, need_penalties)
1019     if post == false then
1020         flush_list(current)
1021         return nil
1022     end
1023     return post
1024 end

```

(End of definition for mlist\_to\_hlist.)

```

1025 </lua>

```

Reset the catcode of @.

```

1026 <tex>\catcode'\@=\etacatcode\relax

```

# File 05

## ltxexpl.dtx

### 1 expl3-dependent code

#### 1.1 Loader

```
\@kernel@after@enddocument
\@kernel@before@enddocument@afterlastpage
\@kernel@after@enddocument@afterlastpage
```

These three kernel hooks are used by the shipout code. They are defined early (i.e., here) because the lthooks code adds material to them.

```
1 <*2ekernel | latexrelease>
2 <latexrelease> \IncludeInRelease{2020/10/01}%
3 <latexrelease> {kernel@enddocument hooks}{Define several kernel hooks}
```

We initialize these kernel hooks only when they do not already exist. Otherwise they would be set to \@empty on rollback, which would be wrong because code that has been added to them may still have to be executed in the rollback situation. Instead code that writes to them needs to handle the rollback as needed. It is likely that we have to change that approach in the future, but for now it should do. (It is enough to test only for the existence of one hook, as all got added at the same time.)

```
4 \ifx\@kernel@after@enddocument\undefined
5   \let \@kernel@after@enddocument \@empty
6   \let \@kernel@after@enddocument@afterlastpage \@empty
```

For the similar reasons we also define those that are used in \document because they too get material added to in early modules.

```
\@kernel@before@begindocument
\@kernel@after@begindocument
```

```
7   \let \@kernel@before@begindocument \@empty
8   \let \@kernel@after@begindocument \@empty
9 \fi
```

This one actually came later so we need to have a separate check, but otherwise we don't bother with a separate rollback.

```
10 \ifx\@kernel@before@enddocument@afterlastpage\undefined
11   \let \@kernel@before@enddocument@afterlastpage \@empty
12 \fi
13 <latexrelease> \EndIncludeInRelease
14 <latexrelease> \IncludeInRelease{0000/00/00}%
15 <latexrelease> {kernel@enddocument hooks}{Define several kernel hooks}
16 <latexrelease> \let\@kernel@after@enddocument\undefined
17 <latexrelease> \let\@kernel@before@enddocument@afterlastpage\undefined
18 <latexrelease> \let\@kernel@after@enddocument@afterlastpage\undefined
19 <latexrelease> \let\@kernel@before@begindocument\undefined
20 <latexrelease> \let\@kernel@after@begindocument\undefined
21 </2ekernel | latexrelease>
22 <latexrelease> \EndIncludeInRelease
```

(End of definition for \@kernel@after@enddocument and others.)

First define some blank commands, so that in case something goes wrong while loading expl3, we won't get strange Undefined control sequence errors.

```
23 <*2ekernel | latexrelease>
24 <latexrelease> \IncludeInRelease{2020/10/01}%
25 <latexrelease> {\@expl@sys@load@backend@}{Roll forward support}%
```

```

26 \def\reserved@a#1{\ifdefined#1\else\def#1{}\fi}
27 \reserved@a\@expl@sys@load@backend@@
28 \reserved@a\@expl@push@filename@@
29 \reserved@a\@expl@push@filename@aux@@
30 \reserved@a\@expl@pop@filename@@
31 \<latexrelease>\EndIncludeInRelease
32 \</2ekernel | latexrelease>

```

Create a hook for last-minute expl3 material.

```

33 \<2ekernel>
34 \def\@expl@finalise@setup@@{}
35 \</2ekernel>

```

Now define some basics to support loading expl3. These macros can be defined here safely, because they are redefined later on by the kernel, so we define simpler versions just to suit our needs.

```

36 \<2ekernel>
37 \long\def\@gobble#1{}
38 \long\def\@firstofone#1{#1}
39 \long\def\@firstoftwo#1#2{#1}
40 \long\def\@secondoftwo#1#2{#2}
41 \long\def\IfFileExists#1{%
42   \openin\@inputcheck"#1" %
43   \ifeof\@inputcheck
44     \expandafter\@secondoftwo
45   \else
46     \closein\@inputcheck
47     \expandafter\@firstoftwo
48   \fi}
49 \long\def\@ifnextchar#1#2#3{%
50   \let\reserved@d=#1%
51   \def\reserved@a{#2}%
52   \def\reserved@b{#3}%
53   \futurelet\@let@token\@ifnch}
54 \def\@ifnch{%
55   \ifx\@let@token\reserved@d
56     \expandafter\reserved@a
57   \else
58     \expandafter\reserved@b
59   \fi}
60 \</2ekernel>

```

If we are doing a rollback with a format containing expl3 we aren't reloading it as that creates havoc. This may need a refined version!

```

61 \<2ekernel | latexrelease>
62 \<latexrelease>\IncludeInRelease{2020/10/01}%
63 \<latexrelease>{expl3}{Pre-load expl3}%
64 \expandafter\ifx\csname tex\string _let:D\endcsname\relax
65   \expandafter\@firstofone
66 \else
67   \GenericInfo{}\{Skipping: expl3 code already part of the format}%
68 \<2ekernel> \expandafter\endinput
69 \<latexrelease> \expandafter\@gobble
70 \fi

```

Check for the required primitive/engine support and the existence of a loader.

```

71  {%
72    \IfFileExists{expl3.ltx}
73    {%
74      \ifnum0%
75        \ifdefined\pdffilesize 1\fi
76        \ifdefined\filesize 1\fi
77        \ifdefined\luatexversion\ifnum\luatexversion>94 1\fi\fi
78        \ifdefined\kanjiskip 1\fi
79        >0 %
80        \expandafter\@firstofone
81      \else

```

In 2ekernel mode, an error is fatal and building the format is aborted. Use `\batchmode \read -1 to \tokenlist`, which errors with

! Emergency stop. (cannot \read from terminal in nonstop modes)

and aborts the T<sub>E</sub>X run. In latexrelease mode, raise an error and do nothing. Both ways, the error message shows the minimum expl3 engine requirements.

```

82 <2ekernel>          \def~{ }\def\MessageBreak{^^J~~~~~}%
83 <2ekernel>          \errmessage{LaTeX Error:
84 <latexrelease>      \@latex@error{%
85                    LaTeX requires the e-TeX primitives and additional\MessageBreak
86                    functionality available in the engines:\MessageBreak
87                    - pdfTeX v1.40\MessageBreak
88                    - XeTeX v0.99992\MessageBreak
89                    - LuaTeX v0.95\MessageBreak
90                    - e-(u)pTeX mid-2012\MessageBreak
91                    or later%
92 <latexrelease>      } \@ehd \expandafter\@gobble
93 <2ekernel>          }\batchmode \read -1 to \reserved@a
94                  \fi
95                }
96                {%
97 <*2ekernel>
98                \errmessage{LaTeX requires expl3}%
99                \batchmode \read -1 to \reserved@a
100 </2ekernel>

```

We do not support a roll forward across 2019. You need to start with 2019 if you want to get to 2020 or beyond.

```

101 <*latexrelease>
102       \@latex@warning@no@line
103       {You need a format that already contains a recent\MessageBreak
104       expl3 as part of the kernel, e.g. at least a kernel\MessageBreak
105       from 2019 to roll forward to that date!\MessageBreak
106       --- I'm giving up!\MessageBreak\MessageBreak
107       Note that manually loading the expl3 package\MessageBreak
108       from your distribution is not enough}%
109       \batchmode \read -1 to \reserved@a
110 </latexrelease>
111       }%
112       {\input expl3.ltx }%
113   }

```

```

114 <latexrelease>\EndIncludeInRelease
115 <latexrelease>

```

To support roll-forward for the case where xparse is fully integrated into the kernel, we do not need to repeat the complex test above as we can simply look for the marker command.

```

116 <latexrelease>\IncludeInRelease{2020/02/02}%
117 <latexrelease>          {expl3}{Pre-load expl3}%
118 <latexrelease>\IfFileExists{expl3.ltx}
119 <latexrelease>  {%
120 <latexrelease>    \ifnum0%
121 <latexrelease>      \ifdefined\pdffilesize 1\fi
122 <latexrelease>      \ifdefined\filesize 1\fi
123 <latexrelease>      \ifdefined\luatexversion\ifnum\luatexversion>94 1\fi\fi
124 <latexrelease>      >0 %
125 <latexrelease>    \else
126 <latexrelease>      \message{Skipping expl3-dependent extensions}
127 <latexrelease>      \expandafter\@gobbletwo
128 <latexrelease>    \fi
129 <latexrelease>  }
130 <latexrelease>  {%
131 <latexrelease>    \message{Skipping expl3-dependent extensions}%
132 <latexrelease>    \@gobbletwo
133 <latexrelease>  }%
134 <latexrelease>\input{expl3.ltx}
135 <latexrelease>\EndIncludeInRelease

```

Now in `latexrelease` mode, redefine a few commands to avoid “already defined” errors.

```

136 <latexrelease>\@ifundefined{ExplSyntaxOff}{\{\}\latexrelease@postltxpl}

```

## 1.2 Using expl3 code

In order to ease the implementation of some new features in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> we may (temporarily) use some coding based on the `expl3`-code. Such macros will eventually vanish and may be changed unannounced. They are there for internal use in the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> kernel and are not meant to be used in third-party packages. These macros will always have the `@expl@` prefix in their name.

The rest of the name matches the `expl3` name but with all underscores replaced by `@s` and the `:` replaced by `@@`, e.g.,

```
\cs_new_eq:NN \@expl@tl@trim@spaces@apply@@nN \tl_trim_spaces_apply:nN
```

if that `expl3` command is needed in places that are others coded in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> conventions.

In this file, each release of LaTeX adds an `\IncludeInRelease` block, in which the macros copied for that release were defined. In case a rollback is requested, the entire block is changed.

Each macro copied has a `\changes` entry to explain when and why it was copied, so that further to that may spot it easily.

Here `\cs_gset_eq:NN` is used, instead of the `new` variant because if different releases use that same name for different purposes, each can copy the macro without worrying about redefinitions.

```

137 <latexrelease>\IncludeInRelease{2020/10/01}{\@expl@cs@to@str@@N}%
138 <latexrelease>          {expl3 macros added for the 2020-10-01 release}%

```

The expl3 activation needs to be inside the release guards as otherwise rolling forward is broken in old kernels that do not have expl3 loaded.

```

139 \ExplSyntaxOn

140 \cs_gset_eq:NN \@expl@cs@to@str@N \cs_to_str:N
141 \cs_gset_eq:NN \@expl@str@if@eq@nnTF \str_if_eq:nnTF

142 \cs_gset_eq:NN \@expl@cs@prefix@spec@N \cs_prefix_spec:N
143 \cs_if_exist:NTF \cs_parameter_spec:N
144 { \cs_gset_eq:NN \@expl@cs@parameter@spec@N \cs_parameter_spec:N }
145 { \cs_gset_eq:NN \@expl@cs@parameter@spec@N \cs_argument_spec:N }
146 \cs_gset_eq:NN \_kernel_cs_parameter_spec:N \@expl@cs@parameter@spec@N
147 \cs_gset_eq:NN \@expl@cs@replacement@spec@N \cs_replacement_spec:N

148 \cs_gset_eq:NN \@expl@str@map@function@NN \str_map_function:NN
149 \cs_gset_eq:NN \@expl@char@generate@nn \char_generate:nn

150 \ExplSyntaxOff

```

Here we can't assume that expl3 is available. It will be if we roll back but if this code is executed rolling forward it needs to be pure 2e.

```

151 \<latexrelease>\EndIncludeInRelease
152 \<latexrelease>\IncludeInRelease{0000/00/00}{\@expl@cs@to@str@N}%
153 \<latexrelease>{expl3 macros added for the 2020-10-01 release}%
154 \<latexrelease>\let \@expl@cs@to@str@N \undefined
155 \<latexrelease>\let \@expl@str@if@eq@nnTF \undefined
156 \<latexrelease>\let \@expl@cs@prefix@spec@N \undefined
157 \<latexrelease>\let \@expl@cs@parameter@spec@N \undefined
158 \<latexrelease>\let \@expl@cs@replacement@spec@N \undefined
159 \<latexrelease>\let \@expl@str@map@function@NN \undefined
160 \<latexrelease>\EndIncludeInRelease
161 \</2ekernel|latexrelease>

```

## 2 Document-level command names for expl3 functions

Current home for L3 programming layer functions that we make directly available at the document level. This section may need to be moved later (after `\NewDocumentCommand` is defined in case we want to use that in the setup).

`\fpeval` The expandable command `\fpeval` takes as its argument a floating point expression and produces a result using the normal rules of mathematics. As this command is expandable it can be used where T<sub>E</sub>X requires a number and for example within a low-level `\edef` operation to give a purely numerical result. See `usrguide3` for further explanation.

`\inteval` The expandable command `\inteval` takes as its argument an integer expression and produces a result using the normal rules of mathematics. The operations recognised are `\dimeval` `\skipeval` `+`, `-`, `*` and `/` plus parentheses. Division occurs with *rounding*, and ties are rounded away from zero. As this command is expandable it can be used where T<sub>E</sub>X requires a number and for example within a low-level `\edef` operation to give a purely numerical result. See `usrguide3` for further explanation. `\dimeval` and `\skipeval` are similar, but generate fixed and rubber length values, respectively.

`\fpeval` A document level wrapper around the code level function for floating point calculations.

`\interval`

`\dimeval` 162 `<*2ekernel | latexrelease>`

`\skipeval` 163 `<latexrelease>\IncludeInRelease{2022/06/01}%`  
164 `<latexrelease> {\fpeval}{fp and int calculations}%`  
165 `\ExplSyntaxOn`  
166 `\cs_new_eq:NN \fpeval \fp_eval:n`

And a few more, this time wrappers around the eTeX primitives.

167 `\cs_new_eq:NN \interval \int_eval:n`

168 `\cs_new_eq:NN \dimeval \dim_eval:n`  
169 `\cs_new_eq:NN \skipeval \skip_eval:n`  
170 `\ExplSyntaxOff`

*(End of definition for \fpeval and others.)*

171 `</2ekernel | latexrelease>`  
172 `<latexrelease>\EndIncludeInRelease`  
173 `<latexrelease>\IncludeInRelease{0000/00/00}%`  
174 `<latexrelease> {\fpeval}{fp and int calculations}%`  
175 `<latexrelease>`  
176 `<latexrelease>\let\fpeval\@undefined`  
177 `<latexrelease>\let\interval\@undefined`  
178 `<latexrelease>\let\dimeval\@undefined`  
179 `<latexrelease>\let\skipeval\@undefined`  
180 `<latexrelease>\EndIncludeInRelease`

`\UseName` When declaring new commands with `\NewDocumentCommand` or `\NewCommandCopy`

`\ExpandArgs` or similar, it is sometimes necessary to “construct” the csname. As a general mechanism the L3 programming layer has `\exp_args:N...` for this, but there is no mechanism for it if `\ExplSyntaxOn` is not active. We therefore offer a few of these commands also with CamelCase names.

`\UseName` A document wrapper for changing arguments to cs names for use with `\NewDocumentCommand`

`\ExpandArgs` and similar functions.

181 `<*2ekernel | latexrelease>`  
182 `<latexrelease>\IncludeInRelease{2022/06/01}%`  
183 `<latexrelease> {\ExpandArgs}{Some pre-expansion commands}%`  
184 `\ExplSyntaxOn`  
185 `\cs_new_eq:NN \UseName \use:c`

186 `\cs_new:Npn \ExpandArgs #1`  
187 `{`  
188 `\cs_if_exist_use:cF { exp_args:N #1 }`  
189 `{ \msg_expandable_error:nnn { kernel } { unknown-arg-expansion } {#1} }`  
190 `}`  
191 `\msg_new:nnn { kernel } { unknown-arg-expansion }`  
192 `{ Unknown-arg-expansion-“#1” }`  
193 `\ExplSyntaxOff`

*(End of definition for \UseName and \ExpandArgs.)*

194 `</2ekernel | latexrelease>`  
195 `<latexrelease>\EndIncludeInRelease`  
196 `<latexrelease>\IncludeInRelease{0000/00/00}%`  
197 `<latexrelease> {\ExpandArgs}{Some pre-expansion commands}%`

```

198 <latexrelease>
199 <latexrelease>\let\UserName\@undefined
200 <latexrelease>\let\ExpandArgs\@undefined
201 <latexrelease>\EndIncludeInRelease

\IfExplAtLeastTF      A pretty simple set of wrappers. \IfExplAtLeastTF was already introduced in 2023
\IfExplAtLeastT      but since we pretend that these commands were always there, even in rollback, things
\IfExplAtLeastF      can be kept simple and we just alter the rollback date.

\IfExplAtLeastTF

202 <*2ekernel | latexrelease>
203 <latexrelease>\IncludeInRelease{2025/06/01}%
204 <latexrelease>          {\IfExplAtLeastTF}{Test for expl3 date}%
205 \def\IfExplAtLeastTF{\@ifl@t@r\ExplLoaderFileDate}
206 \def\IfExplAtLeastT#1#2{\IfExplAtLeastTF{#1}{#2}\@firstofone\@gobble}
207 \def\IfExplAtLeastF#1{\IfExplAtLeastTF{#1}{}}

(End of definition for \IfExplAtLeastTF.)
    We make sure the commands are always available.

208 </2ekernel | latexrelease>
209 <latexrelease>\EndIncludeInRelease
210 <latexrelease>\IncludeInRelease{0000/00/00}%
211 <latexrelease>          {\IfExplAtLeastTF}{Test for expl3 date}%
212 <latexrelease>
213 <latexrelease>\def\IfExplAtLeastTF{\@ifl@t@r\ExplLoaderFileDate}
214 <latexrelease>\def\IfExplAtLeastT#1#2{\IfExplAtLeastTF{#1}{#2}\@firstofone\@gobble}
215 <latexrelease>\def\IfExplAtLeastF#1{\IfExplAtLeastTF{#1}{}}
216 <latexrelease>\EndIncludeInRelease

\expandableinput

217 <*2ekernel | latexrelease>
218 <latexrelease>\IncludeInRelease{2025/06/01}%
219 <latexrelease>          {\expandableinput}{Expandable input}%
220 \ExplSyntaxOn
221 \cs_new_eq:NN \expandableinput \file_input_raw:n
222 \ExplSyntaxOff

(End of definition for \expandableinput.)

223 </2ekernel | latexrelease>
224 <latexrelease>\EndIncludeInRelease
225 <latexrelease>\IncludeInRelease{0000/00/00}%
226 <latexrelease>          {\expandableinput}{Expandable input}%
227 <latexrelease>
228 <latexrelease>\let\expandableinput\@undefined
229 <latexrelease>\EndIncludeInRelease

```

# File 06

## ltdefns.dtx

### 1 Definitions

This section contains commands used in defining other macros.

```
1 <*2ekernel>
```

#### 1.1 Initex initializations

`\two@digits` Prefix a number less than 10 with ‘0’.

```
2 \def\two@digits#1{\ifnum#1<10 0\fi\number#1}
```

*(End of definition for \two@digits.)*

`\typeout` Display something on the terminal.

```
3 </2ekernel>
4 <*2ekernel | latexrelease>
5 <latexrelease> \IncludeInRelease{2020/10/01}%
6 <latexrelease> { \typeout}{Allow "par" in \typeout}%
7 \protected\long\def\typeout#1{\begingroup
8   \set@display@protect
9   \def\par{^^J^^J}%
10  \immediate\write\@unused{#1}\endgroup}
11 </2ekernel | latexrelease>
12 <latexrelease> \EndIncludeInRelease
13 <latexrelease> \IncludeInRelease{0000/00/00}%
14 <latexrelease> { \typeout}{Allow "par" in \typeout}%
15 <latexrelease>
16 <latexrelease> \def\typeout#1{\begingroup\set@display@protect
17 <latexrelease> \immediate\write\@unused{#1}\endgroup}
18 <latexrelease> \EndIncludeInRelease
19 <*2ekernel>
```

*(End of definition for \typeout.)*

`\newlinechar` A char to be used as new-line in output to files.

```
20 \newlinechar‘^^J
```

*(End of definition for \newlinechar.)*

#### 1.2 Saved versions of TeX primitives

The TeX primitive `\foo` is saved as `\@@foo`. The following primitives are handled in this way:

`\@@par`

```
21 \let\@@par=\par
22 %\let\@@input=\input      %%% moved earlier
23 %\let\@@end=\end          %%%
```

*(End of definition for \@@par.)*

`\@@hyph` Save original primitive definition.

```

24 \let\@@hyph=\-

```

(End of definition for `\@@hyph`.)

`\@@italiccorr` Save the original italic correction.

```

25 \let\@@italiccorr=\/

```

(End of definition for `\@@italiccorr`.)

`\@height` The following definitions save token space. E.g., using `\@height` instead of `height` saves

`\@depth` 5 tokens at the cost in time of one macro expansion.

```

\@width 26 \def\@height{height} \def\@depth{depth} \def\@width{width}
\@minus 27 \def\@minus{minus}
\@plus 28 \def\@plus{plus}

```

The next one is another 100 tokens worth.

```

29 \def\hb@xt@{\hbox to}

```

(End of definition for `\@height` and others.)

```

30 \message{hacks,}

```

`\hb@xt@`

### 1.3 Command definitions

This section defines the following commands:

`\@namedef` `{\NAME}`  
Expands to `\def\NAME`, except name can contain any characters.

`\@nameuse` `{\NAME}`  
Expands to `\NAME`.

`\@ifnextchar` `X{\YES}{\NO}`  
Expands to `\YES` if next character is an ‘X’, and to `\NO` otherwise. (Uses `\reserved@a-`  
`\reserved@c`.) NOTE: GOBBLES ANY SPACE FOLLOWING IT.

`\@ifstar` `{\YES}{\NO}`  
Gobbles following spaces and then tests if next the character is a ‘\*’. If it is, then it  
gobbles the ‘\*’ and expands to `\YES`, otherwise it expands to `\NO`.

`\@dblarg` `{\CMD}{\ARG}`  
Expands to `\{\CMD\}[\ARG]{\ARG}`. Use `\@dblarg\CS` when `\CS` takes arguments  
`[ARG1]{ARG2}`, where default is `ARG1 = ARG2`.

`\@ifundefined` `{\NAME}{\YES}{\NO}`  
: If `\NAME` is undefined then it executes `\YES`, otherwise it executes `\NO`. More precisely,  
true if `\NAME` either undefined or = `\relax`.

`\@ifdefinable` `\NAME{\YES}` Executes `\YES` if the user is allowed to define `\NAME`, otherwise it  
gives an error. The user can define `\NAME` if `\@ifundefined{\NAME}` is true, ‘`NAME`’ ≠  
‘`relax`’ and the first three letters of ‘`NAME`’ are not ‘`end`’, and if `\endNAME` is not defined.

`\newcommand` `*{\FOO}[\i]{\TEXT}`  
User command to define `\FOO` to be a macro with `i` arguments (`i = 0` if missing) having  
the definition `\TEXT`. Produces an error if `\FOO` already defined.

Normally the command is defined to be `\long` (ie it may take multiple paragraphs  
in its argument). In the star-form, the command is not defined as `\long` and a blank line  
in any argument to the command would generate an error.

`\renewcommand` `*{\FOO}[\i]{\TEXT}`

Same as `\newcommand`, except it checks if `\F00` already defined.

`\newenvironment`       $\star{\langle FOO\rangle}[\langle i\rangle]{\langle DEF1\rangle}{\langle DEF2\rangle}$   
equivalent to:  
`\newcommand{\F00}[i]{DEF1} \def{\endF00}{DEF2}`  
(or the appropriate star forms).

`\renewenvironment`      Obvious companion to `\newenvironment`.

`\@cons`                  : See description of `\output` routine.

`\@car`                  `\@car T1 T2 ... Tn\@nil == T1` (unexpanded)

`\@cdr`                  `\@cdr T1 T2 ... Tn\@nil == T2 ... Tn` (unexpanded)

`\typeout`                 $\{\langle message\rangle\}$   
Produces a warning message on the terminal.

`\typein`                 $\{\langle message\rangle\}$   
Types message, asks the user to type in a command, then executes it

`\typein`                 $[\langle\backslash CS\rangle]{\langle MSG\rangle}$   
Same as above, except defines `\CS` to be the input instead of executing it.

`\typein`

```

31 \def\typein{%
32   \let\@typein\relax
33   \@testopt\@xtypein\@typein}

34 \ifx\directlua\@undefined

35 \def\@xtypein[#1]#2{%
36   \typeout{#2}%
37   \advance\endlinechar\@M
38   \read\@inputcheck to#1%
39   \advance\endlinechar-\@M
40   \@typein}%

41 \else

42 \def\@xtypein[#1]#2{%
43   \typeout{#2}%
44   \begingroup \endlinechar\m@ne
45   \read\@inputcheck to#1%
46   \expandafter\endgroup
47   \expandafter\def\expandafter#1\expandafter{#1}%
48   \@typein}%

49 \fi

```

(End of definition for `\typein`.)

`\@namedef`

```

50 \def\@namedef#1{\expandafter\def\csname #1\endcsname}

```

(End of definition for `\@namedef`.)

`\@nameuse`

```

51 \def\@nameuse#1{\csname #1\endcsname}

```

(End of definition for `\@nameuse`.)

```

\@cons
52 \def\@cons#1#2{\begingroup\let\@elt\relax\xdef#1{#1\@elt #2}\endgroup}

(End of definition for \@cons.)

\@car
\@cdr
53 \def\@car#1#2\@nil{#1}
54 \def\@cdr#1#2\@nil{#2}

(End of definition for \@car and \@cdr.)

\@carcube \@carcube T1 ... Tn\@nil = T1 T2 T3 ,  $n > 3$ 
55 \</2ekernel>
56 \<latexrelease>\IncludeInRelease{2020/10/01}{\@carcube}{Make \@carcube long}%
57 \<*2ekernel | latexrelease>
58 \long\def\@carcube#1#2#3#4\@nil{#1#2#3}
59 \</2ekernel | latexrelease>
60 \<latexrelease>\EndIncludeInRelease
61 %
62 \<latexrelease>\IncludeInRelease{0000/00/00}{\@carcube}{Undo: Make \@carcube long}%
63 \<latexrelease>\def\@carcube#1#2#3#4\@nil{#1#2#3}
64 \<latexrelease>\EndIncludeInRelease
65 \<*2ekernel>

(End of definition for \@carcube.)

\@onlypreamble This macro adds its argument to the list of commands stored in \@preamblecmds
\@preamblecmds to be disabled after \begin{document}. These commands are redefined to generate
\@notprerr at this point.
66 \def\@preamblecmds{}
67 \def\@onlypreamble#1{%
68   \expandafter\gdef\expandafter\@preamblecmds\expandafter{%
69     \@preamblecmds\do#1}}
70 \@onlypreamble\@onlypreamble
71 \@onlypreamble\@preamblecmds

(End of definition for \@onlypreamble and \@preamblecmds.)

\@star@or@long Look ahead for a *. If present reset \l@ngrel@x so that the next definition, #1, will be
non-long.
72 \</2ekernel>
73 \<*2ekernel | latexrelease>
74 \<latexrelease>\IncludeInRelease{2025/11/01}%
75 \<latexrelease> {\@star@or@long}{Macros without args are short}%
76 \def\@star@or@long#1{%

By default commands defined with \newcommand and friends are not \protected so
\pr@tectedrel@x is set to \relax.
77 \let\pr@tectedrel@x\relax
78 \@ifstar
79 {\let\l@ngrel@x\relax#1}%
80 {\let\l@ngrel@x\long#1}}

```

```

81 </2ekernel | latexrelease>
82 <latexrelease>\EndIncludeInRelease
83 <latexrelease>\IncludeInRelease{0000/00/00}%
84 <latexrelease>    {\@star@or@long}{Macros without args are short}%
85 <latexrelease>
86 <latexrelease>\def\@star@or@long#1{%
87 <latexrelease>    \ifstar
88 <latexrelease>        {\let\l@ngrel@x\relax#1}%
89 <latexrelease>        {\let\l@ngrel@x\long#1}}
90 <latexrelease>
91 <latexrelease>\EndIncludeInRelease
92 <*2ekernel>

```

*(End of definition for \@star@or@long.)*

**\l@ngrel@x** This is either `\relax` or `\long` depending on whether the `*`-form of a definition command is being executed.

```
93 \let\l@ngrel@x\relax
```

*(End of definition for \l@ngrel@x.)*

**\pr@tectedrel@x** Same for the protection status.

```
94 \let\pr@tectedrel@x\relax
```

*(End of definition for \pr@tectedrel@x.)*

**\newcommand** User level `\newcommand`.

```
95 \def\newcommand{\@star@or@long\new@command}
```

**\new@command**

```
96 \def\new@command#1{%
97     \testopt{\@newcommand#1}0}
```

*(End of definition for \newcommand and \new@command.)*

**\@newcommand** Handling arguments for `\newcommand`.

```

\@argdef 98 \def\@newcommand#1[#2]{%
\@xargdef 99     \kernel@ifnextchar [{\@xargdef#1[#2]}%
100         {\@argdef#1[#2]}}

```

Define `#1` if it is definable.

Both here and in `\@xargdef` the replacement text is absorbed as an argument because if we are not allowed to make the definition we have to get rid of it completely.

```

101 \long\def\@argdef#1[#2]#3{%
102     \@ifdefinable #1{\@yargdef#1\@ne{#2}{#3}}

```

Handle the second optional argument.

```

103 \long\def\@xargdef#1[#2] [#3]#4{%
104     \@ifdefinable#1{%

```

Define the actual command to be:

```
\def\foo{\@protected@testopt\foo\\foo{default}}
```

where `\\foo` is a csname generated from applying `\csname` and `\string` to `\foo`, ie the actual name contains a backslash and therefore can't clash easily with existing command names. "Default" is the contents of the second optional argument of `(re)newcommand`.

```
105 \expandafter\def\expandafter#1\expandafter{%
106     \expandafter
107     \@protected@testopt
108     \expandafter
109     #1%
110     \csname\string#1\endcsname
111     {#3}}%
```

Now we define the internal macro ie `\\foo` which is supposed to pick up all arguments (optional and mandatory).

```
112 \expandafter\@yargdef
113 \csname\string#1\endcsname
114 \tw@
115 {#2}%
116 {#4}}}
```

(End of definition for `\@newcommand`, `\@argdef`, and `\@xargdef`.)

**`\@testopt`** This macro encapsulates the most common call to `\@ifnextchar`, saving several tokens each time it is used in the definition of a command with an optional argument. **#1** The code to execute in the case that there is a `[` need not be a single token but can be any sequence of commands that 'expects' to be followed by `[`. If this command were only used in `\newcommand` definitions then **#1** would be a single token and the braces could be omitted from `{#1}` in the definition below, saving a bit of memory.

```
117 \long\def\@testopt#1#2{%
118     \kernel@ifnextchar[#{1}{#1[{#2}]}}}
```

(End of definition for `\@testopt`.)

**`\@protected@testopt`** Robust version of `\@testopt`. The extra argument (**#1**) must be a single token. If protection is needed the call expands to `\protect` applied to this token, and the 2nd and 3rd arguments are discarded (by `\@x@protect`). Otherwise `\@testopt` is called on the 2nd and 3rd arguments.

This method of making commands robust avoids the need for using up two csnames per command, the price is the extra expansion time for the `\ifx` test.

```
119 \def\@protected@testopt#1{%
120     \ifx\protect\@typeset@protect
121     \expandafter\@testopt
122     \else
123     \@x@protect#1%
124     \fi}
```

(End of definition for `\@protected@testopt`.)

**`\@yargdef`** These generate a primitive argument specification, from a L<sup>A</sup>T<sub>E</sub>X [*digit*] form; in fact *digit* can be anything such that `\number <digit>` is single digit.

**`\@yargdef`** Reorganised slightly so that `\renewcommand{\reserved@a}[1]{foo}` works. I am not sure this is worth it, as a following `\newcommand` would over-write the definition of `\reserved@a`.

Recall that L<sup>A</sup>T<sub>E</sub>X2.09 goes into an infinite loop with  
`\renewcommand[1]{\@tempa}{foo}`  
(DPC 6 October 93).

Reorganised again (DPC 1999). Rather than make a loop to construct the argument spec by counting, just extract the required argument spec by using a delimited argument (delimited by the digit). This is faster and uses less tokens. The coding is slightly odd to preserve the old interface (using `#2 = \tw@` as the flag to surround the first argument with `[]`). But the new method did not allow for the number of arguments `#3` not being given as an explicit digit; hence (further expansion of this argument and use of) `\number` was added later in 1999.

It is not clear why these are still `\long`.

```

125 \long \def \@yargdef #1#2#3{%
126   \ifx#2\tw@
127     \def\reserved@b##1{####1}%
128   \else
129     \let\reserved@b\@gobble
130   \fi
131   \expandafter
132     \@yargd@f \expandafter{\number #3}#1%
133 }

134 </2ekernel>
135 <*2ekernel | latexrelease>
136 <latexrelease>\IncludeInRelease{2025/11/01}%
137 <latexrelease>  {\@yargd@f}{Macros without args are short}%
138 <latexrelease>
139 \long \def \@yargd@f#1#2{%
140   \def \reserved@a ##1#1##2##{%
141     \expandafter\def\expandafter#2\reserved@b ##1#1%
142   }%

```

If the command needs to be `\protected` then `\pr@tectedrel@x` has the appropriate value at this point.

```

143   \pr@tectedrel@x

```

If the command has no arguments then we don't want to to be `\long` (even if `\l@ngrel@x` has been set to `\long`).

```

144   \ifnum#1>\z@ \l@ngrel@x \fi
145   \reserved@a 0##1##2##3##4##5##6##7##8##9###1%
146 }

147 </2ekernel | latexrelease>
148 <latexrelease>\EndIncludeInRelease
149 <latexrelease>\IncludeInRelease{0000/00/00}%
150 <latexrelease>  {\@yargd@f}{Macros without args are short}%
151 <latexrelease>
152 <latexrelease>\long \def \@yargd@f#1#2{%
153 <latexrelease>  \def \reserved@a ##1#1##2##{%
154 <latexrelease>    \expandafter\def\expandafter#2\reserved@b ##1#1%
155 <latexrelease>  }%
156 <latexrelease>  \l@ngrel@x \reserved@a 0##1##2##3##4##5##6##7##8##9###1%
157 <latexrelease>}
158 <latexrelease>
159 <latexrelease>\EndIncludeInRelease
160 <*2ekernel>

```

(End of definition for \@yargdef and \@yargdef.)

**\@reargdef**

```
161 \long\def\@reargdef#1[#2]{%
162   \@yargdef#1\@ne{#2}}
```

(End of definition for \@reargdef.)

**\renewcommand** Check the command name is already used. If not give an error message. Then temporarily disable \@ifdefinable then call \newcommand. (Previous version \let#1=\relax but this does not work too well if #1 is \@tempa-e.)

```
163 \def\renewcommand{\@star@or@long\renew@command}
```

**\renew@command**

```
164 \def\renew@command#1{%
165   \begingroup
166   \escapechar\m@ne\xdef\@gtempa{\expandafter\string\@car#1?\@nil}}%
167   \endgroup
168   \expandafter\@ifundefined\@gtempa
169   {\@latex@error{Command \string#1 undefined}\@ehc}%
170   \relax
171   \let\@ifdefinable\@rc@ifdefinable
172   \new@command#1}
```

(End of definition for \renewcommand and \renew@command.)

**\@ifdefinable** Test if user is allowed to define a command.

**\@@ifdefinable**

**\@rc@ifdefinable**

```
173 \long\def\@ifdefinable #1#2{%
174   \edef\reserved@a{\expandafter\@gobble\string #1}%
175   \@ifundefined\reserved@a
176   {\edef\reserved@b{\expandafter\@carcube \reserved@a xxx\@nil}}%
177   \ifx \reserved@b\@qend \@notdefinable\else
178   \ifx \reserved@a\@qrelax \@notdefinable\else
179   #2%
180   \fi
181   \fi}%
182   \@notdefinable}
```

Saved definition of \@ifdefinable.

```
183 \let\@@ifdefinable\@ifdefinable
```

Version of \@ifdefinable for use with \renewcommand. Does not do the check this time, but restores the normal definition.

```
184 \long\def\@rc@ifdefinable#1#2{%
185   \let\@ifdefinable\@@ifdefinable
186   #2}
```

(End of definition for \@ifdefinable, \@@ifdefinable, and \@rc@ifdefinable.)

**\newenvironment**

Define a new user environment. #1 is the environment name. #2# Grabs all the tokens up to the first {. These will be any optional arguments. They are not parsed at this point, but are just passed to \@newenv which will eventually call \newcommand. Any optional arguments will then be parsed by \newcommand as it defines the command that executes the ‘begin code’ of the environment.

This #2# trick removed with version 1.2i as it fails if a { occurs in the optional argument. Now use \@ifnextchar directly.

```

187 \def\newenvironment{\@star@or@long\new@environment}

\new@environment 188 \def\new@environment#1{%
189   \@testopt{\@newenva#1}0}

190 \def\@newenva#1[#2]{%
\@newenva 191   \kernel@ifnextchar [{\@newenvb#1[#2]}{\@newenv{#1}{[#2]}}}]

192 \def\@newenvb#1[#2][#3]{\@newenv{#1}{[#2][#3]}}
\@newenvb
(End of definition for \newenvironment and others.)

\renewenvironment Redefine an environment. For \renewenvironment disable \@ifdefinable and then call
\newenvironment. It is OK to \let the argument to \relax here as there should not
be a @temp... environment.
193 \def\renewenvironment{\@star@or@long\renew@environment}

\renew@environment 194 \def\renew@environment#1{%
195   \@ifundefined{#1}%
196     {\@latex@error{Environment #1 undefined}\@ehc
197     }\relax
198   \expandafter\let\csname#1\endcsname\relax
199   \expandafter\let\csname end#1\endcsname\relax
200   \new@environment{#1}}

(End of definition for \renewenvironment and \renew@environment.)

\@newenv The internal version of \newenvironment.
Call \newcommand to define the <begin-code> for the environment. \def is used for
the <end-code> as it does not take arguments. (but may contain \pars)
Make sure that an attempt to define a ‘graf’ or ‘group’ environment fails by tem-
porarily letting the undefined \... (begin code) to the definition of \end... and as a
result we get an error if that has a definition.
201 \long\def\@newenv#1#2#3#4{%
202   \@ifundefined{#1}%
203     {\expandafter\let\csname#1\expandafter\endcsname
204       \csname end#1\endcsname}%
205     \relax
206   \expandafter\new@command
207     \csname #1\endcsname#2{#3}%
208     \l@ngrel@x\expandafter\def\csname end#1\endcsname{#4}}

(End of definition for \@newenv.)

```

`\newif` And here's a different sort of allocation: For example, `\newif\ifffoo` creates `\footrue`, `\foofalse` to go with `\ifffoo`.

```
209 \def\newif#1{%
210   \count@\escapechar \escapechar\m@ne
211   \let#1\iffalse
212   \@if#1\iftrue
213   \@if#1\iffalse
214   \escapechar\count@}
```

```
\@if 215 \def\@if#1#2{%
216   \expandafter\def\csname\expandafter\@gobbletwo\string#1%
217   \expandafter\@gobbletwo\string#2\endcsname
218   {\let#1#2}}
```

(End of definition for `\newif` and `\@if`.)

`\providecommand` `\providecommand` takes the same arguments as `\newcommand`, but discards them if #1 is already defined. Otherwise it just acts like `\newcommand`. This implementation currently leaves any discarded definition in `\reserved@a` (and possibly `\reserved@a`) this wastes a bit of space, but it will be reclaimed as soon as these scratch macros are redefined.

```
219 \def\providecommand{\@star@or@long\provide@command}
```

```
\provide@command 220 \def\provide@command#1{%
221   \begingroup
222   \escapechar\m@ne\xdef\@gtempa{\expandafter\string\@car#1?\@nil}}%
223   \endgroup
224   \expandafter\@ifundefined\@gtempa
225   {\def\reserved@a{\new@command#1}}%
226   {\def\reserved@a{\renew@command\reserved@a}}%
227   \reserved@a}%
```

(End of definition for `\providecommand` and `\provide@command`.)

`\CheckCommand` `\CheckCommand` takes the same arguments as `\newcommand`. If the command already exists, with the same definition, then nothing happens, otherwise a warning is issued. Useful for checking the current state before a macro package starts redefining things. Currently two macros are considered to have the same definition if they are the same except for different default arguments. That is, if the old definition was: `\newcommand\xxx[2][a]{(#1)(#2)}` then `\CheckCommand\xxx[2][b]{(#1)(#2)}` would *not* generate a warning, but, for instance `\CheckCommand\xxx[2]{(#1)(#2)}` would.

```
228 \def\CheckCommand{\@star@or@long\check@command}
```

`\CheckCommand` is only available in the preamble part of the document.

```
229 \@onlypreamble\CheckCommand
```

```
\check@command 230 \def\check@command#1#2#{\@check@c#1{#2}}
231 \@onlypreamble\check@command
```

(End of definition for `\CheckCommand` and `\check@command`.)

`\@check@c` `\CheckCommand` itself just grabs all the arguments we need, without actually looking for [ optional argument forms. Now define `\reserved@a`. If `\reserved@a` is then defined, compare it with the “`\#1`” otherwise compare `\reserved@a` with `\#1`.

```
232 \long\def\@check@c#1#2#3{%
233   \expandafter\let\csname\string\reserved@a\endcsname\relax
234   \renewcommand\reserved@a#2{#3}%
235   \@ifundefined{\string\reserved@a}%
236     {\@check@eq#1\reserved@a}%
237     {\expandafter\@check@eq
238       \csname\string#1\expandafter\endcsname
239       \csname\string\reserved@a\endcsname}}
240 \@onlypreamble\@check@c
```

*(End of definition for \@check@c.)*

`\@check@eq` Complain if `\#1` and `\#2` are not `\ifx` equal.

```
241 \def\@check@eq#1#2{%
242   \ifx#1#2\else
243     \@latex@warning@no@line
244       {Command \noexpand#1 has
245        changed.\MessageBreak
246        Check if current package is valid}%
247   \fi}
248 \@onlypreamble\@check@eq
```

*(End of definition for \@check@eq.)*

`\@gobble` The `\@gobble` macro is used to get rid of its argument.

```
\@gobbletwo 249 \long\def \@gobble #1{}
\@gobblethree 250 \long\def \@gobbletwo #1#2{}
\@gobblefour 251 \long\def \@gobblethree #1#2#3{}
252 \long\def \@gobblefour #1#2#3#4{}
```

*(End of definition for \@gobble and others.)*

There are also `\@gobble@om`, `\@gobble@som`, `\@gobble@with@sphack@om`, and `\@gobble@with@sphack@som`. They accept an optional and a mandatory argument, possibly preceded by a star. In all cases the expansion is empty or just manipulates the spaces around the command. Used to disable commands such as `\index` or `\label` in certain situations. Since they are defined with `\DeclareDocumentCommand`, which is not yet available at this point, the actual definition happens in `ltsect.dtx`.

`\@firstofone` Some argument-grabbers.

```
\@firstoftwo 253 \long\def\@firstofone#1{#1}
\@secondoftwo 254 \long\def\@firstoftwo#1#2{#1}
255 \long\def\@secondoftwo#1#2{#2}
```

`\@iden` is another name for `\@firstofone` for compatibility reasons.

```
256 \let\@iden\@firstofone
```

`\@iden` *(End of definition for \@firstofone and others.)*

`\@thirdofthree` Another grabber now used in the encoding specific section.

```
257 \long\def\@thirdofthree#1#2#3{#3}
```

(End of definition for \@thirdofthree.)

`\@expandtwoargs` A macro to totally expand two arguments to another macro

```
258 </2ekernel>
259 <latexrelease>\IncludeInRelease{2022/11/01}%
260 <latexrelease>      {\@expandtwoargs}{protected edef}%
261 <*2ekernel | latexrelease>
262 \def\@expandtwoargs#1#2#3{%
263 \protected@edef\reserved@a{\noexpand#1{#2}{#3}}\reserved@a}
264 </2ekernel | latexrelease>
265 <latexrelease>\EndIncludeInRelease
266 <latexrelease>\IncludeInRelease{00/00/00}%
267 <latexrelease>      {\@expandtwoargs}{protected edef}%
268 <latexrelease>\def\@expandtwoargs#1#2#3{%
269 <latexrelease>\edef\reserved@a{\noexpand#1{#2}{#3}}\reserved@a}
270 <latexrelease>\EndIncludeInRelease
271 <*2ekernel>
```

(End of definition for \@expandtwoargs.)

`\@backslashchar` A category code 12 backslash.

```
272 \edef\@backslashchar{\expandafter\@gobble\string\\}
```

(End of definition for \@backslashchar.)

## 1.4 Robust commands and protect

Fragile and robust commands are one of the thornier issues in L<sup>A</sup>T<sub>E</sub>X's commands. Whilst typesetting documents, L<sup>A</sup>T<sub>E</sub>X makes use of many of T<sub>E</sub>X's features, such as arithmetic, defining macros, and setting variables. However, there are (at least) three different occasions when these commands are not safe. These are called 'moving arguments' by L<sup>A</sup>T<sub>E</sub>X, and consist of:

- writing information to a file, such as indexes or tables of contents.
- writing information to the screen.
- inside an `\edef`, `\message`, `\mark`, or other command which evaluates its argument fully.

The method L<sup>A</sup>T<sub>E</sub>X uses for making fragile commands robust is to precede them with `\protect`. This can have one of four possible values:

- `\relax`, for normal typesetting. So `\protect\foo` will execute `\foo`.
- `\string`, for writing to the screen. So `\protect\foo` will write `\foo`.
- `\noexpand`, for writing to a file. So `\protect\foo` will write `\foo` followed by a space.
- `\@unexpandable@protect`, for writing a moving argument to a file. So `\protect\foo` will write `\protect\foo` followed by a space. This value is also used inside `\edefs`, `\marks` and other commands which evaluate their arguments fully. More precisely, whenever the content of an `\edef` or `\xdef` etc. can contain arbitrary user input not under the direct control of the programmer, one should use `\protected@edef` instead of `\edef`, etc., so that `\protect` has a suitable definition and the user input will not break if it contains fragile commands.

`\@unexpandable@protect`

```
273 \def\@unexpandable@protect{\noexpand\protect\noexpand}
```

(End of definition for \@unexpandable@protect.)

```
\DeclareRobustCommand
\declare@robustcommand
\declare@robustcommand@auxi
\declare@robustcommand@auxii
\declare@robustcommand@auxiii
```

This is a package-writers command, which has the same syntax as `\newcommand`, but which declares a protected command. It does this by having

```
\DeclareRobustCommand\foo
define \foo to be \protect\foo<space>,
and then use \newcommand\foo<space>.
```

Since the internal command is `\foo<space>`, when it is written to an auxiliary file, it will appear as `\foo`.

We have to be a bit cleverer if we're defining a short command, such as `\_`, in order to make sure that the auxiliary file does not include a space after the command, since `\_ a` and `\_a` aren't the same. In this case we define `\_` to be:

```
\x@protect\_ \protect\_<space>
```

which expands to:

```
\ifx\protect\@typeset@protect\else
\x@protect@\_
\fi
\protect\_<space>
```

Then if `\protect` is `\@typeset@protect` (normally `\relax`) then we just perform `\_<space>`, and otherwise `\x@protect@` gobbles everything up and expands to `\protect\_`. None of that works with an active char (as we have only one character token to play with), so we resort to using the engine mechanism there. (The braces in passing `#1` there are defensive in case someone has passed more than one token!)

*Note:* setting `\protect` to any value other than `\relax` whilst in 'typesetting' mode will cause commands to go into an infinite loop! In particular, setting `\protect` to `\@empty` will cause `\_` to loop forever. It will also break lots of other things, such as protected `\ifmmodes` inside `\haligns`. If you really have to do such a thing, then please set `\@typeset@protect` to be `\@empty` as well. (This is what the code for `\patterns` does, for example.)

More fun with `\expandafter` and `\csname`.

```
274 \def\DeclareRobustCommand{\@star@or@long\declare@robustcommand}
275 \def\declare@robustcommand#1{%
276   \ifx\@undefined#1\else\ifx\relax#1\else
277     \@latex@info{Redefining \string#1}%
278     \fi\fi
279   \ifcat\noexpand~\noexpand#1%
280     \expandafter\declare@robustcommand@auxi
281   \else
282     \expandafter\declare@robustcommand@auxiii
283   \fi
284   {#1}%
285 }
```

For active chars, we cannot use an auxiliary so have to ‘pack’ everything we need in one definition. To allow for use in file names, etc., we need `\ifincsname` in the definition, so we use two steps to grab that. We also take advantage of the need for an extra auxiliary to do some expansion to give us the string we will want.

```

286 \protected\long\def\declare@robustcommand@auxi#1#2#{%
287   \expandafter\declare@robustcommand@auxii\expandafter{\string#1}#1{#2}%
288 }

289 \</2ekernel>
290 \<*2ekernel | latexrelease>
291 \<latexrelease>\IncludeInRelease{2025/11/01}%
292 \<latexrelease>    {\declare@robustcommand@auxii}{Macros without args are short}%
293 \protected\long\def\declare@robustcommand@auxii#1#2#3#4{%

```

Here we want a `\protected` command.

```

294   \let\pr@tectedrel@x\protected
295   \let\@ifdefinable\@rc@ifdefinable
296   \new@command#2#3{%
297     \ifincsname
298     \expandafter\@firstoftwo
299     \else
300     \expandafter\@secondoftwo
301     \fi
302     {#1}{#4}%
303   }%
304 }

305 \</2ekernel | latexrelease>
306 \<latexrelease>\EndIncludeInRelease
307 \<latexrelease>\IncludeInRelease{0000/00/00}%
308 \<latexrelease>    {\declare@robustcommand@auxii}{Macros without args are short}%
309 \<latexrelease>
310 \<latexrelease>\protected\long\def\declare@robustcommand@auxii#1#2#3#4{%
311 \<latexrelease>   \ifx\l@ngrel@x\relax
312 \<latexrelease>     \let\l@ngrel@x\protected
313 \<latexrelease>   \else
314 \<latexrelease>     \def\l@ngrel@x{\protected\long}%
315 \<latexrelease>   \fi
316 \<latexrelease>   \let\@ifdefinable\@rc@ifdefinable
317 \<latexrelease>   \new@command#2#3{%
318 \<latexrelease>     \ifincsname
319 \<latexrelease>     \expandafter\@firstoftwo
320 \<latexrelease>     \else
321 \<latexrelease>     \expandafter\@secondoftwo
322 \<latexrelease>     \fi
323 \<latexrelease>     {#1}{#4}%
324 \<latexrelease>   }%
325 \<latexrelease> }
326 \<latexrelease>
327 \<latexrelease>\EndIncludeInRelease
328 \<*2ekernel>

329 \protected\def\declare@robustcommand@auxiii#1{%
330   \edef\reserved@a{\string#1}%
331   \def\reserved@b{#1}%
332   \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%

```

```

333 \edef#1{%
334     \ifx\reserved@a\reserved@b
335         \noexpand\x@protect
336         \noexpand#1%
337     \fi
338     \noexpand\protect
339     \expandafter\noexpand\csname
340         \expandafter\@gobble\string#1 \endcsname
341 }%
342 \let\@ifdefinable\@rc@ifdefinable
343 \expandafter\new@command\csname
344     \expandafter\@gobble\string#1 \endcsname
345 }

```

```

346 \def\x@protect#1{%
347     \ifx\protect\@typeset@protect\else
348         \x@protect#1%
349     \fi
350 }
351 \def\@x@protect#1\fi#2#3{%
352     \fi\protect#1%
353 }

```

(End of definition for `\DeclareRobustCommand` and others.)

`\@typeset@protect` We set `\@typeset@protect` to `\relax` rather than `\@empty` to make sure that the protection mechanism stops the look-ahead and expansion performed at the start of `\halign` cells.

```
354 \let\@typeset@protect\relax
```

(End of definition for `\@typeset@protect`.)

`\set@display@protect` These macros set `\protect` appropriately for typesetting or displaying.

```

\set@typeset@protect 355 \def\set@display@protect{\let\protect\string}
356 \def\set@typeset@protect{\let\protect\@typeset@protect}

```

(End of definition for `\set@display@protect` and `\set@typeset@protect`.)

`\protected@edef` The commands `\protected@edef` and `\protected@xdef` perform ‘safe’ `\edefs` and `\xdefs`, saving and restoring `\protect` appropriately. For cases where restoring `\protect` doesn’t matter, there’s an ‘unsafe’ `\unrestored@protected@xdef`, useful if you know what you’re doing!

`\protected@xdef`  
`\unrestored@protected@xdef`  
`\restore@protect`

```

357 \def\protected@edef{%
358     \let\@protect\protect
359     \let\protect\@unexpandable@protect
360     \afterassignment\restore@protect
361     \edef
362 }
363 \def\protected@xdef{%
364     \let\@protect\protect
365     \let\protect\@unexpandable@protect
366     \afterassignment\restore@protect
367     \xdef

```

```

368 }
369 \def\unrestored@protected@xdef{%
370   \let\protect\@unexpandable@protect
371   \xdef
372 }
373 \def\restore@protect{\let\protect\@protect}

```

(End of definition for \protected@edef and others.)

**\protect** The normal meaning of \protect

```

374 \set@typeset@protect

```

(End of definition for \protect.)

**\MakeRobust** This macro makes an existing fragile macro robust, but only if it hasn't been robust in the past, i.e., it checks for the existence of the macro `\<name>` and if that exists it assumes that `\<name>` is already robust. In that case either undefine the inner macro first or use `\DeclareRobustCommand` to define it in a robust way directly. We could probably test the top-level definition to have the right kind of structure, but this is somewhat problematical as we then have to distinguish between `\long` macros and others and also take into account that sometimes the top-level is deliberately done manually (like with `\begin`).

The macro firstly checks if the control sequence in question exists at all.

```

375 \</2ekernel>
376 \<latexrelease>\IncludeInRelease{2020/10/01}{\MakeRobust}{\MakeRobust}%
377 \<*2ekernel | latexrelease>
378 \def\MakeRobust#1{%
379   \count@=\escapechar
380   \escapechar='\\
381   \@ifundefined{\expandafter\@gobble\string#1}{%
382     \@latex@error{Command '\string#1' undefined.%
383     \MessageBreak There is nothing here to make robust}%
384     \@eha
385   }%

```

Then we check if the macro is already robust. We do this by testing if the internal name for a robust macro is defined, namely `\foo`. If it is already defined do nothing, otherwise set `\foo` equal to `\foo` and redefine `\foo` so that it acts like a macro defined with `\DeclareRobustCommand`. We use `\@kernel@rename@newcommand` to copy `\foo` over to `\foo`, including a possible default optional argument.

```

386   {%
387     \@ifundefined{\expandafter\@gobble\string#1\space}%
388     {%
389       \expandafter\@kernel@rename@newcommand
390       \csname\expandafter\@gobble\string#1\space\endcsname
391       #1%
392       \edef\reserved@a{\string#1}%
393       \def\reserved@b{#1}%
394       \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
395       \xdef#1{%
396         \ifx\reserved@a\reserved@b
397           \noexpand\x@protect\noexpand#1%
398         \fi
399         \noexpand\protect\expandafter\noexpand

```

```

400     \csname\expandafter\@gobble\string#1\space\endcsname}%
401   }%
402   {\@latex@info{Command '\string#1' is already robust}}%
403 }%
404 \escapechar=\count@
405 }%

```

This macro renames a command, possibly with an optional argument (defined with `\newcommand`) from #2 to #1, by renaming the internal macro `\\#2` to `\\#1` and defining `\\#1` appropriately, then undefining `\\#2` and `\\#2`. The `\afterassignment` trick is to make both definitions in `\@copy@newcommand` global (which are local by default).

In case the macro was defined with `\newcommand` and an optional argument, to replicate exactly the behaviour of `\DeclareRobustCommand` we have to move also the internal `\\foo` to `\\foo_`. In that case, #1 will be a parameterless macro (`\robust@command@chk@safe` checks that), and `\@if@newcommand` will return true (both defined below in this file). If so, we can use `\@copy@newcommand` rather than plain `\let` to copy the command over. `\@kernel@rename@newcommand` does this test and carries out the renaming.

```

406 \def\@kernel@rename@newcommand#1#2{%
407   \robust@command@chk@safe#2%
408   {\@if@newcommand#2%
409     {\afterassignment\global
410       \global\@copy@newcommand#1#2%
411       \global\let#2\@undefined
412       \global\expandafter\let\csname\string#2\endcsname\@undefined}%
413     {\global\let#1=#2}}%
414   {\global\let#1=#2}}

415 \</2ekernel|latexrelease>
416 \<latexrelease>\EndIncludeInRelease
417 %
418 \<latexrelease>\IncludeInRelease{2019/10/01}{\MakeRobust}{\MakeRobust}%
419 \<latexrelease>\def\MakeRobust#1{%
420 \<latexrelease>   \@ifundefined{\expandafter\@gobble\string#1}{%
421 \<latexrelease>     \@latex@error{The control sequence '\string#1' is undefined!%
422 \<latexrelease>       \MessageBreak There is nothing here to make robust}%
423 \<latexrelease>     \@eha
424 \<latexrelease>   }%
425 \<latexrelease>   {%
426 \<latexrelease>     \@ifundefined{\expandafter\@gobble\string#1\space}%
427 \<latexrelease>     {%
428 \<latexrelease>       \global\expandafter\let\csname
429 \<latexrelease>         \expandafter\@gobble\string#1\space\endcsname=#1%
430 \<latexrelease>       \edef\reserved@a{\string#1}%
431 \<latexrelease>       \def\reserved@b{#1}%
432 \<latexrelease>       \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
433 \<latexrelease>       \xdef#1{%
434 \<latexrelease>         \ifx\reserved@a\reserved@b
435 \<latexrelease>           \noexpand\x@protect\noexpand#1%
436 \<latexrelease>         \fi
437 \<latexrelease>         \noexpand\protect\expandafter\noexpand
438 \<latexrelease>         \csname\expandafter\@gobble\string#1\space\endcsname}%
439 \<latexrelease>       }%

```

```

440 <latexrelease>    {\@latex@info{The control sequence ‘\string#1’ is already robust}}}%
441 <latexrelease>    }%
442 <latexrelease>}%
443 <latexrelease>\let\@kernel@rename@newcommand\@undefined
444 <latexrelease>\EndIncludeInRelease
445 %
446 <latexrelease>\IncludeInRelease{2015/01/01}{\MakeRobust}{\MakeRobust}%
447 <latexrelease>\def\MakeRobust#1{%
448 <latexrelease>    \ifundefined{\expandafter\@gobble\string#1}{%
449 <latexrelease>        \@latex@error{The control sequence ‘\string#1’ is undefined!%
450 <latexrelease>        \MessageBreak There is nothing here to make robust}%
451 <latexrelease>        \@eha
452 <latexrelease>    }%
453 <latexrelease>    {%
454 <latexrelease>        \ifundefined{\expandafter\@gobble\string#1\space}%
455 <latexrelease>        {%
456 <latexrelease>            \expandafter\let\csname
457 <latexrelease>            \expandafter\@gobble\string#1\space\endcsname=#1%
458 <latexrelease>            \edef\reserved@a{\string#1}%
459 <latexrelease>            \def\reserved@b{#1}%
460 <latexrelease>            \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
461 <latexrelease>            \edef#1{%
462 <latexrelease>                \ifx\reserved@a\reserved@b
463 <latexrelease>                    \noexpand\x@protect\noexpand#1%
464 <latexrelease>                \fi
465 <latexrelease>                \noexpand\protect\expandafter\noexpand
466 <latexrelease>                \csname\expandafter\@gobble\string#1\space\endcsname}%
467 <latexrelease>            }%
468 <latexrelease>        {\@latex@info{The control sequence ‘\string#1’ is already robust}}}%
469 <latexrelease>    }%
470 <latexrelease>}%
471 <latexrelease>\let\@kernel@rename@newcommand\@undefined
472 <latexrelease>\EndIncludeInRelease
473 %
474 <latexrelease>\IncludeInRelease{0000/00/00}{\MakeRobust}{\MakeRobust}%
475 <latexrelease>\let\MakeRobust\@undefined
476 <latexrelease>\let\@kernel@rename@newcommand\@undefined
477 <latexrelease>\EndIncludeInRelease
478 <*2ekernel>

```

*(End of definition for \MakeRobust and \@kernel@rename@newcommand.)*

**\kernel@make@fragile** The opposite of **\MakeRobust** except that it doesn't do many checks as it is internal to the kernel. Why does one want such a thing? Only for compatibility reasons if **latexrelease** requests a rollback of the kernel. For this reason we pretend that this command existed in all earlier versions of L<sup>A</sup>T<sub>E</sub>X i.e., we are not rolling it back since we need it precisely then. But we have to get it into the **latexrelease** file so that a roll forward is possible too.

```

479 </2ekernel>
480 <*2ekernel | latexrelease>
481 <latexrelease>\IncludeInRelease{2020/10/01}%
482 <latexrelease>    {\kernel@make@fragile}{Undo robustness}%
483 <def\kernel@make@fragile#1{%
484     \ifundefined{\expandafter\@gobble\string#1\space}%

```

If not robust do nothing.

```

485     {}%
Otherwise copy \foo_ back to \foo. Then use \@kernel@rename@newcommand to check
and copy \\foo_ back to \\foo in case the command has an optional argument. If so,
also undefine \\foo_, and at the end undefine \foo_.
486     {%
487         \global\expandafter\let\expandafter #1\csname
488             \expandafter@gobble\string#1\space\endcsname
489         \expandafter\@kernel@rename@newcommand
490         \csname\expandafter@gobble\string#1\expandafter\endcsname
491         \csname\expandafter@gobble\string#1\space\endcsname
492         \global\expandafter\let\csname
493         \expandafter@gobble\string#1\space\endcsname\undefined
494     }%
495 }
496 \<latexrelease>\EndIncludeInRelease
497 %
498 \<latexrelease>\IncludeInRelease{0000/00/00}%
499 \<latexrelease>          {\kernel@make@fragile}{Undo robustness}%
500 \<latexrelease>\def\kernel@make@fragile#1{%
501 \<latexrelease>  \@ifundefined{\expandafter@gobble\string#1\space}%
502 \<latexrelease>    {}%
503 \<latexrelease>    {%
504 \<latexrelease>      \global\expandafter\let\expandafter #1\csname
505 \<latexrelease>      \expandafter@gobble\string#1\space\endcsname
506 \<latexrelease>      \global\expandafter\let\csname
507 \<latexrelease>      \expandafter@gobble\string#1\space\endcsname\undefined
508 \<latexrelease>    }%
509 \<latexrelease>}
510 \<latexrelease>\EndIncludeInRelease
511 \</2ekernel | latexrelease>
512 \<*2ekernel>

```

(End of definition for \kernel@make@fragile.)

## 1.5 Acting on robust commands

```

513 \</2ekernel>
514 \<latexrelease>\IncludeInRelease{2020-10-01}{\robust@command@act}
515 \<latexrelease>  {Add \robust@command@act}%
516 \<*2ekernel | latexrelease>

```

With most document level commands being robust now there is more of a requirement to have a standard way of aliasing (or copying) a command to a new name, for example to save an original definition before changing a command. `\DeclareCommandCopy` is analogous to  $\text{\TeX}$ 's `\let`, except that it copes with the different types of robust commands defined by  $\text{\LaTeX}$ 's mechanisms.

A couple of “types of robustness” are defined by the  $\text{\LaTeX} 2_\epsilon$  kernel, namely robust commands defined with `\DeclareRobustCommand` and commands with optional arguments defined with `\newcommand`. However there are other types of robust commands that are frequently used, which are not defined in the  $\text{\LaTeX} 2_\epsilon$  kernel, like commands defined with `xparse`'s `\NewDocumentCommand` and `etoolbox`'s `\newrobustcmd`.

In this section we will define a generic extensible machinery to act on robust commands. This code will then be used to test if a command is robust, considered the different types of robustness, and then either copy that definition, if `\DeclareCommandCopy` (or similar) is used, or show the definition of the command, if `\ShowCommand` is used.

`\robust@command@act` The looping machinery is generic and knows nothing about what is to be done for each case. The syntax of the main macro `\robust@command@act` is:

```
\robust@command@act⟨action-list⟩⟨robust-cmd⟩
⟨fallback-action⟩⟨act-arg⟩
```

`⟨action-list⟩` is a token list of the form:

```
{⟨if-type-1⟩ ⟨act-type-1⟩}
{⟨if-type-2⟩ ⟨act-type-2⟩}
...
```

`\robust@command@act` will iterate over the `⟨action-list⟩`, evaluating each `⟨if-type-n⟩` `⟨robust-cmd⟩` `{⟨true⟩}{⟨false⟩}`. If the `⟨if-type-n⟩` conditional returns `⟨true⟩`, then `⟨act-type-n⟩⟨act-arg⟩` is executed, and the loop ends. If the conditional returns `⟨false⟩`, then `⟨if-type-n + 1⟩` is executed in the same way, until either one of the conditionals return `⟨true⟩`, or the end of the `⟨action-list⟩` is reached. If the end is reached, then `⟨fallback-action⟩⟨act-arg⟩` is executed before `\robust@command@act` exits.

`\robust@command@act` will start by using `\robust@command@act@chk@args` to check if the `⟨robust-cmd⟩` (#2) is a parameterless (possibly `\protected`) macro. If it is not, the command is not a robust command: these always start with a parameterless user-level macro; in that case, `\robust@command@act@end` is used to short-circuit the process and do the `⟨fallback-action⟩` (#3). This first test is necessary because later on we need to be able to expand the `⟨robust-cmd⟩` without the risk of it Breaking Badly, and as a bonus, this speeds up the process in case we used `\NewCommandCopy` in a “normal” macro.

```
517 \long\def\robust@command@act#1#2#3#4{%
518   \robust@command@chk@safe#2%
519   {\expandafter\robust@command@act@loop
520    \expandafter#2%
521    #1{\@nnil\@nnil}%
522    \robust@command@act@end}%
523   {\robust@command@act@end}%
524   {#3}{#4}}%
```

If `\robust@command@act@chk@args` branched to false, then `\robust@command@act@loop` will loop over the list of items in the `⟨action-list⟩` (#1), and process each item as described earlier. If the `⟨if-type-n⟩` command expands to `⟨true⟩` then `\robust@command@act@do` is used to execute `⟨act-type-n⟩` on the `⟨act-arg⟩`, otherwise the loop resumes with the next item.

```
525 \long\def\robust@command@act@loop#1#2{\robust@command@act@loop@aux#1#2}
526 \long\def\robust@command@act@loop@aux#1#2#3{%
527   \ifx\@nnil#2%
528   \else
529     #2{#1}%
530     {\robust@command@act@do{#3}}%
531     {\expandafter\robust@command@act@loop\expandafter#1}%
532   \fi}
```

```

533 \long\def\robust@command@act@do#1%
534   \fi#2%
535   \robust@command@act@end#3#4{%
536   \fi
537   #1#4}

```

If the end is reached and no action was taken, then do  $\langle fallback-action \rangle \langle act-arg \rangle$ .

```

\robust@command@act@end 538 \long\def\robust@command@act@end#1#2{#1#2}

```

```

\robust@command@chk@safe 539 \long\def\robust@command@chk@safe#1{%
\robust@command@act@chk@args 540   \begingroup
541   \escapechar='\\
542   \expandafter\endgroup\expandafter
543   \robust@command@act@chk@args\meaning#1:->\@nil}
544 \def\robust@command@act@chk@args#1:->#2\@nil{%
545   \@expl@str@if@eq@nnTF{#1}{macro}%
546   {\@firstoftwo}%
547   {\@expl@str@if@eq@nnTF{#1}{\protected macro}%
548   {\@firstoftwo}%
549   {\@secondoftwo}}}

550 </2ekernel | latexrelease>
551 <latexrelease>\EndIncludeInRelease
552 <latexrelease>\IncludeInRelease{0000-00-00}{\robust@command@act}
553 <latexrelease> {Add \robust@command@act}%
554 <latexrelease>\let\robust@command@act\@undefined
555 <latexrelease>\let\robust@command@act@loop\@undefined
556 <latexrelease>\let\robust@command@act@loop@aux\@undefined
557 <latexrelease>\let\robust@command@act@do\@undefined
558 <latexrelease>\let\robust@command@act@end\@undefined
559 <latexrelease>\let\robust@command@chk@safe\@undefined
560 <latexrelease>\let\robust@command@act@chk@args\@undefined
561 <latexrelease>\EndIncludeInRelease
562 <*2ekernel>

```

(End of definition for `\robust@command@act` and others.)

### 1.5.1 Copying robust commands

```

563 </2ekernel>
564 <latexrelease>\IncludeInRelease{2020-10-01}{\DeclareCommandCopy}
565 <latexrelease> {Add \NewCommandCopy, \RenewCommandCopy, and \DeclareCommandCopy}%
566 <*2ekernel | latexrelease>

```

`\NewCommandCopy` `\NewCommandCopy` starts by checking if `#1` is already defined, and raises an error if so, otherwise the definition is carried out. `\RenewCommandCopy` does (almost) the opposite. `\DeclareCommandCopy` If the command is *not* defined, then an error is raised. But the definition is carried out anyhow, so the behaviour is consistent with `\renewcommand`.

A `\ProvideCommandCopy` isn't defined because it's not reasonably useful. `\provide...` commands mean “define this if there's no other definition”, but copying a command (usually) implies that the command being copied is defined, so `\ProvideCommandCopy` doesn't make a lot of sense. But more importantly, the most common use case of copying a command is to redefine it later, while preserving the old definition, as in:

```

\ProvideCommandCopy \A \B
\renewcommand \B { ... \A ... }

```

then, if \A is already defined the first line is skipped, and in this case \B won't work as expected.

The three versions call the internal `\declare@commandcopy` with the proper action. `\@firstofone` will carry out the copy. The only case when the copy is not made is the `<false>` case for `\NewCommandCopy`, in which the command already exists and the definition is aborted.

```

567 \def\NewCommandCopy{%
568   \declare@commandcopy
569     {\@firstofone}%
570     {\@firstoftwo\@notdefinable}}
571 \def\RenewCommandCopy{%
572   \declare@commandcopy
573     {\@latexerror{Command \backslashchar\reserved@a\space undefined}\@ehc
574     \@firstofone}%
575     {\@firstofone}}
576 \def\DeclareCommandCopy{%
577   \declare@commandcopy
578     {\@firstofone}%
579     {\@firstofone}}

```

Start by checking if the command is already defined. The proper action is taken by each specific command above. If all's good, then `\robust@command@act` is called with the proper arguments as described earlier, with `\@declarecommandcopylisthook` as the `<action-list>` and `\declare@commandcopy@let` as the `<fallback-action>`.

```

\declare@commandcopy
\declare@commandcopy@do
580 \long\def\declare@commandcopy#1#2#3#4{%
581   \edef\reserved@a{\@expl@cs@to@str@N#3}%
582   \@ifundefined\reserved@a{#1}{#2}%
583     {\declare@commandcopy@do{#3}{#4}}
584 \long\def\declare@commandcopy@do#1#2{%
585   \robust@command@act
586     \@declarecommandcopylisthook#2%
587     \declare@commandcopy@let{#1#2}}

```

The initial definition of `\@declarecommandcopylisthook` contains the tests for the two types of robust command in the kernel.

```

\@declarecommandcopylisthook
588 \def\@declarecommandcopylisthook{%
589   {\@if@DeclareRobustCommand \@copy@DeclareRobustCommand}%
590   {\@if@newcommand \@copy@newcommand}}

```

The initial definition of `\@declarecommandcopylisthook` contains the tests for the two types of robust command in the kernel.

```

591 \long\def\declare@commandcopy@let#1#2{\let#1=#2\relax}
\declare@commandcopy@let

```

Now the rollback code.

```

592 </2ekernel | latexrelease>
593 <latexrelease>\EndIncludeInRelease
594 <latexrelease>\IncludeInRelease{0000-00-00}{\DeclareCommandCopy}
595 <latexrelease> {Undefine \NewCommandCopy, \RenewCommandCopy, and \DeclareCommandCopy}%
596 <latexrelease>\let\NewCommandCopy\@undefined

```

```

597 <latexrelease>\let\RenewCommandCopy\@undefined
598 <latexrelease>\let\DeclareCommandCopy\@undefined
599 <latexrelease>\let\declare@commandcopy\@undefined
600 <latexrelease>\let\@declarecommandcopylisthook\@undefined
601 <latexrelease>\let\declare@commandcopy\let\@undefined
602 <latexrelease>\EndIncludeInRelease
603 <*2ekernel>

(End of definition for \NewCommandCopy and others.)

604 </2ekernel>
605 <latexrelease>\IncludeInRelease{2023-06-01}{\DeclareEnvironmentCopy}
606 <latexrelease> {Add \NewEnvironmentCopy, \RenewEnvironmentCopy, and \DeclareEnvironmentCopy}%
607 <*2ekernel | latexrelease>

```

`\NewEnvironmentCopy` If `\#1` or `\end#1` already exist one gets an error message talking about the problematical command (not the environment). The remainder of the  $\text{\LaTeX}$  run is probably badly broken and it is unlikely that continuing it gives reasonable results.

```

608 \def\NewEnvironmentCopy{%
609   \declare@environmentcopy
610     {\@firstofone}%
611     {\@firstoftwo\@notdefinable}}
612 \def\RenewEnvironmentCopy{%
613   \declare@environmentcopy
614     {\@latex@error{Environment \reserved@a\space undefined}\@ehc
615     \@firstofone}%
616     {\@firstofone}}
617 \def\DeclareEnvironmentCopy{%
618   \declare@environmentcopy
619     {\@firstofone}%
620     {\@firstofone}}
621 \long\def\declare@environmentcopy#1#2#3#4{%
622   \edef\reserved@a{\@ifundefined{#3}{end#3}{#3}}%
623   \@ifundefined\reserved@a
624     {\def\reserved@a{#3}#1}%
625     {\def\reserved@a{#3}#2}%
626     {\ExpandArgs{cc}\declare@commandcopy@do{#3}{#4}%
627     \ExpandArgs{cc}\declare@commandcopy@do{end#3}{end#4}}}

```

Now the rollback code.

```

628 </2ekernel | latexrelease>
629 <latexrelease>\EndIncludeInRelease
630 <latexrelease>\IncludeInRelease{0000-00-00}{\DeclareEnvironmentCopy}
631 <latexrelease> {Undefine \NewEnvironmentCopy, \RenewEnvironmentCopy, and \DeclareEnvironmentCopy}
632 <latexrelease>\let\NewEnvironmentCopy\@undefined
633 <latexrelease>\let\RenewEnvironmentCopy\@undefined
634 <latexrelease>\let\DeclareEnvironmentCopy\@undefined
635 <latexrelease>\EndIncludeInRelease
636 <*2ekernel>

```

(End of definition for `\NewEnvironmentCopy`, `\RenewEnvironmentCopy`, and `\DeclareEnvironmentCopy`.)

## 1.5.2 Showing robust commands

`\ShowCommand` Most of the machinery defined for `\NewCommandCopy` can be used to show the definition of a robust command, in a similar fashion to `\texdef`. The difference is that after the command is detected to have a given type of robustness, rather than making a copy, we use a separate routine to show its definition.

With all the machinery in place, `\ShowCommand` itself is quite simple: we use `\robust@command@act` to iterate through the `\@showcommandlisthook` list, and if nothing is found, fallback to `\show`.

```

637 </2ekernel>
638 <latexrelease>\IncludeInRelease{2020-10-01}{\ShowCommand}%
639 <latexrelease> {Add \ShowCommand}%
640 <*2ekernel | latexrelease>

641 \long\def\ShowCommand#1{%
642   \robust@command@act
643   \@showcommandlisthook#1%
644   \show#1}

```

`\@showcommandlisthook` The initial definition of `\@showcommandlisthook` contains the same tests as used for copying, but `\@show@...` commands instead of `\@copy@...`. Same as before, it is initialized to cope with `\DeclareRobustCommand` and `\newcommand` with optional arguments.

```

645 \def\@showcommandlisthook{%
646   {\@if@DeclareRobustCommand \@show@DeclareRobustCommand}%
647   {\@if@newcommand \@show@newcommand}}

```

Now the rollback code.

```

648 </2ekernel | latexrelease>
649 <latexrelease>\EndIncludeInRelease
650 <latexrelease>\IncludeInRelease{0000-00-00}{\ShowCommand}
651 <latexrelease> {Undefine \ShowCommand}%
652 <latexrelease>\let\ShowCommand\@undefined
653 <latexrelease>\let\@showcommandlisthook\@undefined
654 <latexrelease>\EndIncludeInRelease
655 <*2ekernel>

```

*(End of definition for \ShowCommand and \@showcommandlisthook.)*

```

656 </2ekernel>
657 <latexrelease>\IncludeInRelease{2020-10-01}{\@if@DeclareRobustCommand}
658 <latexrelease> {Add \@if@DeclareRobustCommand, \@if@newcommand,
659 <latexrelease>       \@copy@DeclareRobustCommand, \@copy@newcommand,
660 <latexrelease>       \@show@DeclareRobustCommand, \@show@newcommand}%
661 <*2ekernel | latexrelease>

```

## 1.5.3 Commands defined with \DeclareRobustCommand

`\@if@DeclareRobustCommand` Now that we provided a generic way to copy one macro to another, we need to define a way to check if a command is one of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s robust types. These tests are heavily based on Heiko's `\LetLtxMacro`, but chopped into separate macros.

The command `\@if@DeclareRobustCommand` checks if a command `\cmd` was defined by `\DeclareRobustCommand`. The test returns true if the expansion of `\cmd` is exactly `\protect\cmd_`.

```

662 \long\def\@if@DeclareRobustCommand#1{%

```

```

663 \begingroup
664 \escapechar='\\
665 \edef\reserved@a{\string#1}%
666 \edef\reserved@b{\detokenize{#1}}%
667 \xdef\@gtempa{%
668     \ifx\reserved@a\reserved@b
669         \noexpand\x@protect
670         \noexpand#1%
671     \fi
672     \noexpand\protect
673     \expandafter\noexpand\csname\@expl@cs@to@str@@N#1 \endcsname}%
674 \endgroup
675 \ifx\@gtempa#1\relax
676     \expandafter\@firstoftwo
677 \else
678     \expandafter\@secondoftwo
679 \fi}

```

If a command was defined by `\DeclareRobustCommand` (that is, `\@if@DeclareRobustCommand` returns true), then to make a copy of `\cmd` into `\foo` we define the latter such that it expands to `\protect\foo`, then make `\foo` equal to `\cmd`.

There is one detail we need to take care of: if a command was defined with `\DeclareRobustCommand` it may still have an optional argument, in which case there is one more macro layer before the actual definition of the command. We use `\@if@newcommand` to check that and `\@copy@newcommand` to do the copying.

```

680 \long\def\@copy@DeclareRobustCommand#1#2{%
681     \begingroup
682     \escapechar='\\
683     \edef\reserved@a{\string#1}%
684     \edef\reserved@b{\detokenize{#1}}%
685     \edef\reserved@a{%
686     \endgroup
687     \def\noexpand#1{%
688         \ifx\reserved@a\reserved@b
689             \noexpand\x@protect
690             \noexpand#1%
691         \fi
692         \noexpand\protect
693         \expandafter\noexpand\csname\@expl@cs@to@str@@N#1 \endcsname}%
694     \noexpand\copy@kernel@robust@command
695     \expandafter\noexpand\csname\@expl@cs@to@str@@N#1 \endcsname
696     \expandafter\noexpand\csname\@expl@cs@to@str@@N#2 \endcsname}%
697     \reserved@a}
698 \long\def\copy@kernel@robust@command#1#2{%
699     \robust@command@chk@safe#2%
700     {\@if@newcommand#2%
701         {\@copy@newcommand}%
702         {\declare@commandcopy@let}}
703     {\declare@commandcopy@let}%
704     #1#2}

```

Showing the command is pretty simple. This command prints the top-level expansion as  $\TeX$ 's `\show` would, but with robust macro: rather than just `macro:`, then

```

\@show@DeclareRobustCommand
\show@kernel@robust@command
\@show@macro

```

a blank line and then `\show` the inner command. For a macro defined with, say, `\DeclareRobustCommand\foo[1]{bar}`, it will print:

```
> \foo=robust macro:
->\protect \foo .

> \foo =\long macro:
#1->bar.
```

If the inner command is defined with an optional argument, then `\@show@newcommand` is also used.

The value of `\escapechar` is deliberately not enforced, so `\ShowCommand` behaves more like `\show`.

```
705 \long\def\@show@DeclareRobustCommand#1{%
706   \typeout{> \string#1=robust macro:}%
707   \typeout{->\@expl@cs@replacement@spec@@N#1.^~J}%
708   \expandafter\show@kernel@robust@command
709     \csname\@expl@cs@to@str@@N#1 \endcsname}
710 \long\def\show@kernel@robust@command#1{%
711   \robust@command@chk@safe#1%
712     {\@if@newcommand#1%
713       {\@show@newcommand}%
714       {\@show@macro}}%
715     {\@show@macro}%
716   #1}
717 \let\@show@macro\show
```

(End of definition for `\@if@DeclareRobustCommand` and others.)

#### 1.5.4 Commands defined with `\newcommand` (with optional argument)

`\@if@newcommand` A command `\cmd` (or `\cmdL`, if it was defined with `\DeclareRobustCommand`) with an optional argument will expand to `\@protected@testopt\cmd\cmd{<opt>}`. To check that we look at the first three tokens in the expansion of `\cmd`, and return true or false accordingly.

This test *requires* that the command be a parameterless macro, otherwise it will not work (and probably break). This is ensured with `\robust@command@chk@safe` before calling `\@if@newcommand`.

```
718 \long\def\@if@newcommand#1{%
719   \edef\reserved@a{%
720     \noexpand\@protected@testopt
721     \noexpand#1%
722     \expandafter\noexpand\csname\@backslashchar\@expl@cs@to@str@@N#1\endcsname}%
723   \edef\reserved@b{%
724     \unexpanded\expandafter\expandafter\expandafter
725       {\expandafter\@carcube#1{-}{-}{-}\@nil}}%
726   \ifx\reserved@a\reserved@b
727     \expandafter\@firstoftwo
728   \else
729     \expandafter\@secondoftwo
730   \fi}
```

Then, if a command `\cmd` takes an optional argument, we copy it to `\foo` by defining the latter to expand to `\@protected@testopt\foo\foo{<opt>}`.

```
\@copy@newcommand
731 \long\def\@copy@newcommand#1#2{%
732   \edef#1{\noexpand\@protected@testopt
733     \noexpand#1%
734     \expandafter\noexpand\csname\@backslashchar\@expl@cs@to@str@@N#1\endcsname
735     \unexpanded\expandafter\expandafter\expandafter
736       {\expandafter\@gobblethree#2}}%
737   \expandafter
738   \let\csname\@backslashchar\@expl@cs@to@str@@N#1\expandafter\endcsname
739     \csname\@backslashchar\@expl@cs@to@str@@N#2\endcsname}
```

`\@show@newcommand`  
`\@show@newcommand@aux`

A command being `\shown` here is guaranteed to have an optional argument. Start by showing the top-level expansion of the command (using `\typeout` to avoid TeX asking for interaction and extra context lines), then call `\@show@newcommand@aux` with the internal command, which contains the actual definition, and with the expansion of the command to extract the default value of the optional argument.

```
740 \long\def\@show@newcommand#1{%
741   \typeout{> \string#1=robust macro:}%
742   \typeout{->\@expl@cs@replacement@spec@@N#1.^^J}%
743   \expandafter\@show@newcommand@aux
744     \csname\@backslashchar\@expl@cs@to@str@@N#1\expandafter\endcsname
745     \expandafter{#1}\@show@tokens}
```

For a macro defined with, say, `\newcommand\foo[1][opt]{bar}`, it will print:

```
> \foo=robust macro:
->\@protected@testopt \foo \foo {opt}.

> \foo=\long macro:
> default #1=opt.
[#1]->bar.
```

If the command was defined with `\DeclareRobustCommand`, then another pair of lines show the top-level expansion `\protect_\foo_`.

```
746 \long\def\@show@newcommand@aux#1#2#3{%
747   \typeout{> \string#1=\@expl@cs@prefix@spec@@N#1macro:}%
748   #3{default \string##1=\expandafter\detokenize\@gobblethree#2.^^J%
749     \@expl@cs@parameter@spec@@N#1->\@expl@cs@replacement@spec@@N#1}}
```

This macro prints the contents of the token list (macro) `#1` using `\showtokens`. The `\expandafter` gymnastics ensures that `\showtokens` itself, and the internals of this macro aren't showed in the context lines.

```
\@show@tokens
750 \long\def\@show@tokens#1{%
751   \edef\reserved@a{#1}%
752   \showtokens\expandafter
753     \expandafter\expandafter{\expandafter\reserved@a}}
```

Now the rollback code.

```
754 </2ekernel | latexrelease>
755 <latexrelease>\EndIncludeInRelease
756 <latexrelease>\IncludeInRelease{0000-00-00}{\@if@DeclareRobustCommand}
757 <latexrelease> {Undefine \@if@DeclareRobustCommand, \@if@newcommand,
```

```

758 <latexrelease> \copy@DeclareRobustCommand, \copy@newcommand,
759 <latexrelease> \show@DeclareRobustCommand, \show@newcommand}%
760 <latexrelease>\let\@if@DeclareRobustCommand\@undefined
761 <latexrelease>\let\@copy@DeclareRobustCommand\@undefined
762 <latexrelease>\let\@show@DeclareRobustCommand\@undefined
763 <latexrelease>\let\@if@newcommand\@undefined
764 <latexrelease>\let\@copy@newcommand\@undefined
765 <latexrelease>\let\@show@newcommand\@undefined
766 %
767 <latexrelease>\let\copy@kernel@robust@command\@undefined
768 <latexrelease>\let\show@kernel@robust@command\@undefined
769 <latexrelease>\let\@show@newcommand@aux\@undefined
770 <latexrelease>\EndIncludeInRelease
771 <*2ekernel>

```

(End of definition for \@if@newcommand and others.)

### 1.5.5 Showing environments

\ShowEnvironment

```

772 </2ekernel>
773 <latexrelease>\IncludeInRelease{2023-06-01}{\ShowEnvironment}
774 <latexrelease> {Add \ShowEnvironment}%
775 <*2ekernel | latexrelease>

```

\ShowEnvironment is quite similar to \ShowCommand. We will pass the environment `<env>` around as the macro `\env`, because `\robust@command@act` expects a single token.

```

776 \def\ShowEnvironment#1{%
777   \expandafter\@show@environment\csname #1\endcsname}
778 \long\def\@show@environment#1{%
779   \robust@command@act
780   \@show@environmentlisthook#1%
781   \@show@normalenv#1}

```

This is similar to `\@showcommandlisthook`, but uses the dedicated versions for environments.

```

782 \def\@show@environmentlisthook{%
783   {\@if@DeclareRobustCommand \show@DeclareRobustCommand@env}%
784   {\@if@newcommand \show@newcommand@env}}

```

These are similar to the command versions below, except they say “environment” and call `\@show@environment@end` to print the `\end` part.

\show@newcommand@env  
\show@DeclareRobustCommand@env

```

785 \long\def\@show@newcommand@env#1{%
786   \@show@environment@begin#1%
787   \expandafter\@show@newcommand@aux
788   \csname\@backslashchar\@expl@cs@to@str@@N#1\expandafter\endcsname
789   \expandafter{#1}\@show@typeout
790   \@show@environment@end#1}
791 \long\def\@show@DeclareRobustCommand@env#1{%
792   \@show@environment@begin#1%
793   \begingroup
794   \let\@show@tokens\@show@typeout
795   \let\@show@macro\@show@nonstop
796   \expandafter\show@kernel@robust@command

```

```

797 \csname\@expl@cs@to@str@N#1 \endcsname
798 \endgroup
799 \@show@environment@end#1}
800 \long\def\@show@environment@begin#1{%
801 \typeout{> \string\begin{\@expl@cs@to@str@N#1}=environment:}%
802 \typeout{\@expl@cs@parameter@spec@N#1->%
803 \@expl@cs@replacement@spec@N#1.^^J}}

```

A “normal” environment is straightforward. `\@show@environment@end` needs to check if the `\end` part is defined and show it accordingly, otherwise the output would show gibberish.

`\@show@normalenv`  
`\@show@environment@end`

```

804 \long\def\@show@normalenv#1{%
805 \show@environment@begin#1%
806 \show@environment@end#1}
807 \long\def\@show@environment@end#1{%
808 \expandafter\@show@environment@end@aux
809 \csname end\@expl@cs@to@str@N#1\endcsname#1}
810 \long\def\@show@environment@end@aux#1#2{%
811 \@show@tokens{\string\end{\@expl@cs@to@str@N#2}%
812 \ifx\relax#1=undefined%
813 \else:^^J\@expl@cs@parameter@spec@N#1->%
814 \@expl@cs@replacement@spec@N#1%
815 \fi}}

```

And here some auxiliaries:

`\@show@nonstop`  
`\@show@typeout`

`\@show@nonstop` same output as `\show`, but doesn’t stop for interaction;  
`\@show@typeout` same output as `\showtokens`, but doesn’t stop for interaction.

```

816 \def\@show@nonstop#1{%
817 \typeout{> \string#1=\@expl@cs@prefix@spec@N#1macro:^^J%
818 \@expl@cs@parameter@spec@N#1->\@expl@cs@replacement@spec@N#1.}}
819 \def\@show@typeout#1{\typeout{> #1.^^J}}

```

Now the rollback code.

```

820 </2ekernel | latexrelease>
821 <latexrelease>\EndIncludeInRelease
822 <latexrelease>\IncludeInRelease{0000-00-00}{\ShowEnvironment}
823 <latexrelease> {Undefine \ShowEnvironment}%
824 <latexrelease>\let\ShowEnvironment\@undefined
825 <latexrelease>\EndIncludeInRelease
826 <*2ekernel>

```

*(End of definition for \ShowEnvironment and others.)*

## 1.6 Internal defining commands

These commands are used internally to define other L<sup>A</sup>T<sub>E</sub>X commands.

`\@ifundefined` Check if first arg is undefined or `\relax` and execute second or third arg depending,

```

827 </2ekernel>
828 <latexrelease>\IncludeInRelease{2018-04-01}{\@ifundefined}
829 <latexrelease>\Leave commands undefined in \@ifundefined}%
830 <*2ekernel | latexrelease>

```

Version using `\ifcsname` to avoid defining undefined tokens to `\relax`. Defined here to simplify using unmatched `\fi`.

```

831 \def\@ifundefined#1{%
832   \ifcsname#1\endcsname\@ifundefin@d@i\else\@ifundefin@d@ii\fi{#1}}
833 \long\def\@ifundefin@d@i#1\fi#2{\fi
834   \expandafter\ifx\csname #2\endcsname\relax
835     \@ifundefin@d@ii
836   \fi
837   \@secondoftwo}
838 \long\def\@ifundefin@d@ii\fi#1#2#3{\fi #2}

```

Now test of engine.

```
839 \ifx\numexpr\@undefined
```

Classic version (should not be needed as etex is assumed).

```

840 \def\@ifundefined#1{%
841   \expandafter\ifx\csname#1\endcsname\relax
842     \expandafter\@firstoftwo
843   \else
844     \expandafter\@secondoftwo
845   \fi}
846 \else\ifx\directlua\@undefined

```

Use the `\ifcsname` defined above.

```
847 \else
```

Optimised version for LuaTeX, using `\lastnamedcs`

```

848 \def\@ifundefined#1{%
849   \ifcsname#1\endcsname
850     \expandafter\ifx\lastnamedcs\relax\else\@ifundefin@d@i\fi
851   \fi
852   \@firstoftwo}
853 \long\def\@ifundefin@d@i#1#2#3#4#5{#1#2#5}
854 \fi
855 \fi
856 </2ekernel | latexrelease>
857 <latexrelease>\EndIncludeInRelease
858 <latexrelease>\IncludeInRelease{0000-00-00}{\@ifundefined}
859 <latexrelease>\Leave commands undefined in \@ifundefined}%
860 <latexrelease>\def\@ifundefined#1{%
861 <latexrelease>   \expandafter\ifx\csname#1\endcsname\relax
862 <latexrelease>     \expandafter\@firstoftwo
863 <latexrelease>   \else
864 <latexrelease>     \expandafter\@secondoftwo
865 <latexrelease>   \fi}
866 <latexrelease>\EndIncludeInRelease
867 <*2ekernel>

```

*(End of definition for \@ifundefined.)*

`\@qend` The following define `\@qend` and `\@qrelax` to be the strings ‘end’ and ‘relax’ with the characters `\catcoded 12`.

```

868 \edef\@qend{\expandafter\@cdr\string\end\@nil}
869 \edef\@qrelax{\expandafter\@cdr\string\relax\@nil}

```

(End of definition for \@qend and \@qrelax.)

**\@ifnextchar** \@ifnextchar peeks at the following character and compares it with its first argument. If both are the same it executes its second argument, otherwise its third.

```
870 \long\def\@ifnextchar#1#2#3{%  
871   \let\reserved@d=#1%  
872   \def\reserved@a{#2}%  
873   \def\reserved@b{#3}%  
874   \futurelet\@let@token\@ifnch}
```

(End of definition for \@ifnextchar.)

**\kernel@ifnextchar** This macro is the kernel version of \@ifnextchar which is used in a couple of places to prevent the AMS variant from being used since in some places this produced chaos. For example, if an `fd` file is loaded in a random place then the optional argument to `\ProvidesFile` could get printed there instead of being written only in the log file. This happened when there was a space or a newline between the mandatory and optional arguments! It should really be fixed in the `amsmath` package one day, but...

Note that there may be other places in the kernel where this version should be used rather than the original, but variable, version.

```
875 \let\kernel@ifnextchar\@ifnextchar
```

(End of definition for \kernel@ifnextchar.)

**\@ifnch** \@ifnch is a tricky macro to skip any space tokens that may appear before the character in question. If it encounters a space token, it calls `xifnch`.

```
876 \def\@ifnch{%  
877   \ifx\@let@token\@sptoken  
878     \let\reserved@c\@xifnch  
879   \else  
880     \ifx\@let@token\reserved@d  
881       \let\reserved@c\reserved@a  
882     \else  
883       \let\reserved@c\reserved@b  
884     \fi  
885   \fi  
886   \reserved@c}
```

(End of definition for \@ifnch.)

**\@sptoken** The following code makes \@sptoken a space token. It is important here that the control sequence `\:` consists of a non-letter only, so that the following whitespace is significant. Together with the fact that the equal sign in a `\let` may be followed by only one optional space the desired effect is achieved. NOTE: the following hacking must precede the definition of `\:` as math medium space.

```
887 \def\:{\let\@sptoken= } \: % this makes \@sptoken a space token
```

(End of definition for \@sptoken.)

**\@xifnch** In the following definition of \@xifnch, `\:` is again used to get a space token as delimiter into the definition.

```
888 \def\:{\@xifnch} \expandafter\def\:{ {\futurelet\@let@token\@ifnch}}
```

(End of definition for \@xifnch.)

`\@ifstar` The new implementation below avoids passing the `<true code>` Through one more `\def` than the `<false code>`, which previously meant that `#` had to be written as `####` in one argument, but `##` in the other. The `*` is gobbled by `\@firstoftwo`.

```
889 \def\@ifstar#1{\@ifnextchar *{\@firstoftwo{#1}}}
```

(End of definition for `\@ifstar`.)

`\@dblarg`

```
\@xdblarg 890 \long\def\@dblarg#1{\kernel@ifnextchar[{\#1}{\@xdblarg{#1}}}
```

```
891 \long\def\@xdblarg#1#2{\#1[\#2]{\#2}}
```

(End of definition for `\@dblarg` and `\@xdblarg`.)

`\@sanitize` The command `\@sanitize` changes the catcode of all special characters except for braces to ‘other’. It can be used for commands like `\index` that want to write their arguments verbatim. Needless to say, this command should only be executed within a group, or chaos will ensue.

```
892 \def\@sanitize{\@makeother\ \@makeother\\\@makeother$\@makeother\&%
```

```
893 \@makeother\#\@makeother\^\@makeother\_ \@makeother%\@makeother\~}
```

(End of definition for `\@sanitize`.)

`\@onelevel@sanitize` This makes the whole “meaning” of `#1` (its one-level expansion) into catcode 12 tokens: it could be used in `\DeclareRobustCommand`.

If it is to be used on default float specifiers, this should be done when they are defined.

```
894 \def \@onelevel@sanitize #1{%
895   \edef #1{\expandafter\strip@prefix
896     \meaning #1}%
897 }
```

(End of definition for `\@onelevel@sanitize`.)

`\string@makeletter` Iterates through a string, turning each alphabetic character into a catcode-11 token (partly undoes a `\detokenize`). Useful for `\ifx`-based string comparisons where `\detokenize`-ing the other string would break too much code.

The macro uses `expl3`’s `\@expl@str@map@function@NN` to iterate on the string (without losing spaces) and applies `\string@makeletter` on each character. The latter checks if character is between `a–z` or `A–Z`, and uses `\@alpha` or `\@Alpha` to get the corresponding catcode-11 token. Other tokens are passed through unchanged.

```
898 </2ekernel>
899 <latexrelease>\IncludeInRelease{2020/10/01}{\string@makeletter}
900 <latexrelease> {Add \string@makeletter}%
901 <*2ekernel|latexrelease>
902 \def\string@makeletter#1{%
903   \@expl@str@map@function@NN#1\string@makeletter}
904 \def\@string@makeletter#1{%
905   \@char@if@alpha{#1}%
906   {\@expl@char@generate@nn{‘#1’}{11}}%
907   {#1}}
908 \def\@char@if@alpha#1{%
909   \ifnum0\ifnum‘#1<‘A 1\fi\ifnum‘#1>‘z 1\fi
910   \if\ifnum‘#1>‘Z \@fi\ifnum‘#1<‘a \@fi01\fi>0
```

```

911     \expandafter\@secondoftwo
912     \else
913     \expandafter\@firstoftwo
914     \fi}
915 </2ekernel | latexrelease>
916 <latexrelease>\EndIncludeInRelease
917 %
918 <latexrelease>\IncludeInRelease{0000/00/00}{\string@makeletter}
919 <latexrelease> {Undefine \string@makeletter}%
920 <latexrelease>\let\string@makeletter\@undefined
921 <latexrelease>\let\@string@makeletter\@undefined
922 <latexrelease>\let\char@if@alph\@undefined
923 <latexrelease>\EndIncludeInRelease
924 <*2ekernel>

(End of definition for \string@makeletter, \@string@makeletter, and \char@if@alph.)

```

```

\makeatletter Make internal control sequences accessible or inaccessible.
\makeatother
925 \DeclareRobustCommand\makeatletter{\catcode'\@11\relax}
926 \DeclareRobustCommand\makeatother{\catcode'\@12\relax}

(End of definition for \makeatletter and \makeatother.)

```

## 2 Discretionary Hyphenation

```

\@dischyph
\@dischyph

```

Moved here to be after the definition of `\DeclareRobustCommand`.

The primitive `\-` command adds a discretionary hyphen using the current font's `\hyphenchar`. Monospace fonts are usually declared with `\hyphenchar` set to `-1` to suppress hyphenation.

$\text{\LaTeX}$ , from  $\text{\LaTeX}$ 2.09 in 1986 defined `\-` by

```

\def\-\{\discretionary{-}{-}{-}

```

The following comment was added when these commands were first set up, 19 April 1986:

the `\-` command is redefined to allow it to work in the `\ttfamily` type style, where automatic hyphenation is suppressed by setting `\hyphenchar` to `-1`. The original primitive  $\text{\TeX}$  definition is saved as `\@@hyph` just in case anyone needs it.

$\text{\LaTeX}$ 2 $\epsilon$ , between 1993 and 2017, had a comment at this point saying that the definition “would probably change” because the definition always uses `-`. The definition used below was given in comments at this point during time.

In 2017 we finally enabled this definition by default, with the older  $\text{\LaTeX}$  definition accessible via `latexrelease` as usual.

In  $\text{\LuaLaTeX}$  the primitive definition of `\-` is used directly because its use of extended hyphenation parameters means that `\-` works correctly even with `\hyphenchar` set to `-1`. This change makes `\-` under  $\text{\LuaLaTeX}$  compatible with language specific hyphenation characters.

Temporary definition of `\@latex@info`, final definition is later.

```

927 \def\@latex@info#1{}

```

```

928 </2ekernel>
929 <latexrelease>\IncludeInRelease{2020/10/01}{\-\-}{Use primitive \- in Lua\LaTeX}%
930 <*2ekernel | latexrelease>
931 \ifx\directlua\undefined
932   \DeclareRobustCommand{\-\-}{%
933     \discretionary{%
934       \char \ifnum\hyphenchar\font<\z@
935         \defaultthyphenchar
936       \else
937         \hyphenchar\font
938       \fi
939     }{}{}%
940   }
941 \else
942   \let\-\- \@@hyph
943 \fi
944 </2ekernel | latexrelease>
945 <latexrelease>\EndIncludeInRelease
946 <latexrelease>\IncludeInRelease{2017/04/15}{\-\-}{Use \hyphenchar in \-\-}%
947 <latexrelease>\DeclareRobustCommand{\-\-}{%
948 <latexrelease>   \discretionary{%
949 <latexrelease>     \char \ifnum\hyphenchar\font<\z@
950 <latexrelease>       \defaultthyphenchar
951 <latexrelease>     \else
952 <latexrelease>       \hyphenchar\font
953 <latexrelease>     \fi
954 <latexrelease>     }{}{}%
955 <latexrelease> }
956 <latexrelease>\EndIncludeInRelease
957 <latexrelease>\IncludeInRelease{0000/00/00}{\-\-}{Use \hyphenchar in \-\-}%
958 <latexrelease>\def\-\-{\discretionary{\-\-}{}{}}
959 <latexrelease>\EndIncludeInRelease

960 <*2ekernel | latexrelease>
961 \let\@dischyph=\-
962 </2ekernel | latexrelease>
963 <*2ekernel>

(End of definition for \- and \@dischyph.)
  Delayed from ltvers.dtx

964 \newif\if@includeinrelease
965 \@includeinreleasefalse

  Delayed from ltplain.dtx

966 </2ekernel>
967 <*2ekernel | latexrelease>
968 <latexrelease>\IncludeInRelease{2019/10/01}%
969 <latexrelease>   {\allowbreak}{Make various commands robust}%
970 \MakeRobust\allowbreak
971 \MakeRobust\bigbreak
972 \MakeRobust\break
973 \MakeRobust\dotfill
974 \MakeRobust\frenchspacing
975 \MakeRobust\goodbreak
976 \MakeRobust\hrulefill

```

```

977 \MakeRobust\medbreak
978 \MakeRobust\nobreak
979 \MakeRobust\nonfrenchspacing
980 \MakeRobust\obeylines
981 \MakeRobust\obeyspaces
982 \MakeRobust\slash
983 \MakeRobust\smallbreak
984 \MakeRobust\strut
985 \MakeRobust\underbar
986 </2ekernel | latexrelease>
987 <latexrelease>\EndIncludeInRelease
988 <latexrelease>\IncludeInRelease{0000/00/00}%
989 <latexrelease>                {\allowbreak}{Make various commands robust}%
990 <latexrelease>
991 <latexrelease>\kernel@make@fragile\allowbreak
992 <latexrelease>\kernel@make@fragile\bigbreak
993 <latexrelease>\kernel@make@fragile\break
994 <latexrelease>\kernel@make@fragile\dotfill
995 <latexrelease>\kernel@make@fragile\frenchspacing
996 <latexrelease>\kernel@make@fragile\goodbreak
997 <latexrelease>\kernel@make@fragile\hrulefill
998 <latexrelease>\kernel@make@fragile\medbreak
999 <latexrelease>\kernel@make@fragile\nobreak
1000 <latexrelease>\kernel@make@fragile\nonfrenchspacing
1001 <latexrelease>\kernel@make@fragile\obeylines
1002 <latexrelease>\kernel@make@fragile\obeyspaces
1003 <latexrelease>\kernel@make@fragile\slash
1004 <latexrelease>\kernel@make@fragile\smallbreak
1005 <latexrelease>\kernel@make@fragile\strut
1006 <latexrelease>\kernel@make@fragile\underbar
1007 <latexrelease>
1008 <latexrelease>\EndIncludeInRelease
1009 <*2ekernel>

```

`\g@addto@macro` Globally add to the end of a macro. This macro is used by the kernel to add to its internal hooks.

```

1010 \long\def\g@addto@macro#1#2{%
1011   \begingroup
1012     \toks@\expandafter{#1#2}%
1013     \xdef#1{the\toks@}%
1014   \endgroup}

```

*(End of definition for \g@addto@macro.)*

```

1015 </2ekernel>

```

## File 07

# ltxcmd.dtx

## 1 Creating document commands

Document commands should be created using the tools provided by this module: `\NewDocumentCommand`, etc., in almost all cases. This allows clean separation of document-level syntax from code-level interfaces. Users have a need to create new document commands, and as such a significant amount of documentation for `ltxcmd` is provided as part of `usrguide3`. Here, additional material aimed at programmers is provided

```
1 <@@=cmd>
2 <*2ekernel>
3 \message{document commands,}
4 </2ekernel>
```

`ltxcmd` code contains an `^^@` character, which usually has catcode 15, so `\IncludeInRelease` will break when this code is being skipped, so we'll save the catcode of `^^@` to restore later:

```
5 <*2ekernel | latexrelease>
6 <latexrelease>\edef\@latexrelease@catcode@null{\the\catcode'\^^@ }
7 <latexrelease>\catcode'\^^@=12
8 \ExplSyntaxOn
9 <latexrelease>\NewModuleRelease{2020/10/01}{ltxcmd}
10 <latexrelease>{Document~command~parser}%
11 \cs_generate_variant:Nn \tl_head:n { e }
```

### 1.1 Variables and constants

---

<code>\l__cmd_arg_spec_tl</code>	Holds the argument specification after normalization of shorthands.
----------------------------------	---

---

```
12 \tl_new:N \l__cmd_arg_spec_tl
```

---

<code>\l__cmd_args_tl</code>	Token list variable for grabbed arguments.
------------------------------	--

---

```
13 \tl_new:N \l__cmd_args_tl
```

---

<code>\l__cmd_args_i_tl</code> <code>\l__cmd_args_ii_tl</code>	Hold the modified arguments when dealing with default values or processors.
---	---

---

```
14 \tl_new:N \l__cmd_args_i_tl
15 \tl_new:N \l__cmd_args_ii_tl
```

---

<code>\l__cmd_current_arg_int</code>	The number of the current argument being set up: this is used to make sure there are at most 9 arguments, then for creating the expandable auxiliary functions and knowing how many arguments the code function should take.
--------------------------------------	--

---

```
16 \int_new:N \l__cmd_current_arg_int
```

---

\l\_\_cmd\_total\_args\_int The total number of arguments found during normalization: this is required where special action is needed for the penultimate argument.

17 \int\_new:N \l\_\_cmd\_total\_args\_int

---

\l\_\_cmd\_last\_mandatory\_arg\_int

Needed to allow handling of verbatim catcodes at the end of the setup.

18 \int\_new:N \l\_\_cmd\_last\_mandatory\_arg\_int

---

\l\_\_cmd\_defaults\_bool The boolean indicates whether there are any argument with default value other than  
\l\_\_cmd\_defaults\_tl -NoValue-; the token list holds the code to determine these default values in terms of other arguments.

19 \bool\_new:N \l\_\_cmd\_defaults\_bool

20 \tl\_new:N \l\_\_cmd\_defaults\_tl

---

\l\_\_cmd\_environment\_bool

Generating environments uses the same mechanism as generating functions. However, full processing of arguments is always needed for environments, and so the function-generating code needs to know this. This variable is also used at run time to give correct error messages.

21 \bool\_new:N \l\_\_cmd\_environment\_bool

---

\l\_\_cmd\_environment\_str

Name of the environment, used at definition time and at run time.

22 \str\_new:N \l\_\_cmd\_environment\_str

---

\l\_\_cmd\_expandable\_bool

Used to indicate if an expandable command is begin generated, as this affects both the acceptable argument types and how they are implemented.

23 \bool\_new:N \l\_\_cmd\_expandable\_bool

---

\l\_\_cmd\_expandable\_aux\_name\_tl

Used to create pretty-printing names for the auxiliaries: although the immediate definition does not vary, the full expansion does and so it does not count as a constant.

24 \tl\_new:N \l\_\_cmd\_expandable\_aux\_name\_tl

25 \tl\_set:Nn \l\_\_cmd\_expandable\_aux\_name\_tl

26 {

27 \l\_\_cmd\_function\_tl \c\_space\_tl

28 ( arg~ \int\_use:N \l\_\_cmd\_current\_arg\_int )

29 }

---

\g\_\_cmd\_grabber\_int

Used (in exceptional cases) to get unique names for grabbers used by expandable commands.

30 \int\_new:N \g\_\_cmd\_grabber\_int

\l\_\_cmd\_fn\_tl For passing the pre-formed name of the auxiliary to be used as the parsing function.

31 \tl\_new:N \l\_\_cmd\_fn\_tl

\l\_\_cmd\_fn\_code\_tl For passing the pre-formed name of the auxiliary that contains the actual code.

32 \tl\_new:N \l\_\_cmd\_fn\_code\_tl

\l\_\_cmd\_function\_tl Holds the control sequence name of the function currently being defined: used to avoid passing this as an argument and to avoid repeated use of \cs\_to\_str:N.

33 \tl\_new:N \l\_\_cmd\_function\_tl

\l\_\_cmd\_grab\_expandably\_bool

When defining a non-expandable command, indicates whether the arguments can all safely be grabbed by expandable grabbers. This is to support abuses of xparse that use protected functions inside csname constructions.

34 \bool\_new:N \l\_\_cmd\_grab\_expandably\_bool

\l\_\_cmd\_obey\_spaces\_bool For trailing optionals.

35 \bool\_new:N \l\_\_cmd\_obey\_spaces\_bool

\l\_\_cmd\_last\_delimiters\_tl Holds the delimiters (first tokens) of all optional arguments since the previous mandatory argument, to warn about cases where it would be impossible to omit optional arguments completely because the following mandatory argument has the same delimiter as one of the optional arguments.

36 \tl\_new:N \l\_\_cmd\_last\_delimiters\_tl

\l\_\_cmd\_long\_bool Used to indicate that an argument is long, on a per-argument basis.

37 \bool\_new:N \l\_\_cmd\_long\_bool

\l\_\_cmd\_suppress\_strip\_bool

Used to indicate that an a pair of braces should not be stripped from an optional argument.

38 \bool\_new:N \l\_\_cmd\_suppress\_strip\_bool

\l\_\_cmd\_m\_args\_int The number of m arguments: if this is the same as the total number of arguments, then a short-cut can be taken in the creation of the grabber code.

39 \int\_new:N \l\_\_cmd\_m\_args\_int

---

\l\_\_cmd\_prefixed\_bool When preparing the signature of non-expandable commands, indicates that the current argument is affected by a processor or by + (namely is long).

40 \bool\_new:N \l\_\_cmd\_prefixed\_bool

---

\l\_\_cmd\_process\_all\_tl  
\l\_\_cmd\_process\_one\_tl  
\l\_\_cmd\_process\_some\_bool When preparing the signature, the processors that will be applied to a given argument are collected in \l\_\_cmd\_process\_one\_tl, while \l\_\_cmd\_process\_all\_tl contains processors for all arguments. The boolean indicates whether there are any processors (to bypass the whole endeavour otherwise).

41 \tl\_new:N \l\_\_cmd\_process\_all\_tl  
 42 \tl\_new:N \l\_\_cmd\_process\_one\_tl  
 43 \bool\_new:N \l\_\_cmd\_process\_some\_bool

---

\l\_\_cmd\_saved\_args\_tl Stores \l\_\_cmd\_args\_tl to deal with space-trimming of b-type arguments.

44 \tl\_new:N \l\_\_cmd\_saved\_args\_tl

---

\l\_\_cmd\_signature\_tl Used when constructing the signature (code for argument grabbing) to hold what will become the implementation of the main function. When arguments are grabbed (at point of use of the command/environment), it also stores the code for grabbing the remaining arguments.

45 \tl\_new:N \l\_\_cmd\_signature\_tl

---

\l\_\_cmd\_some\_obey\_spaces\_bool  
\l\_\_cmd\_some\_long\_bool  
\l\_\_cmd\_some\_short\_bool

These flags are set while normalizing the argument specification. The `obey_spaces` one is used to detect when ! is used on an argument that is not a trailing optional argument. The other two are used to check whether all short arguments appear before long arguments: this is needed to grab arguments expandably. As soon as the first long argument is seen (other than t-type, whose long status is ignored) the `some_long` flag is set. The `some_short` flag is used for expandable commands, to know whether to define a short auxiliary too.

46 \bool\_new:N \l\_\_cmd\_some\_obey\_spaces\_bool  
 47 \bool\_new:N \l\_\_cmd\_some\_long\_bool  
 48 \bool\_new:N \l\_\_cmd\_some\_short\_bool

---

\l\_\_cmd\_final\_verb\_bool Needed to establish whether optional arguments should be collected “verbatim safe”.

49 \bool\_new:N \l\_\_cmd\_final\_verb\_bool

---

```

\q__cmd_recursion_tail
\q__cmd_recursion_stop
\__cmd_use_i_delimit_by_q_recursion_stop:nw

```

Quarks and functions for internal processing.

```

50 \quark_new:N \q__cmd_recursion_tail
51 \quark_new:N \q__cmd_recursion_stop
52 \__kernel_quark_new_test:N \__cmd_if_recursion_tail_stop_do:Nn

```

(End of definition for \\_\_cmd\_if\_recursion\_tail\_stop\_do:Nn and  
\\_\_cmd\_use\_i\_delimit\_by\_q\_recursion\_stop:nw.)

---

```

\l__cmd_tmp_prop
\l__cmd_tmptl
\l__cmd_tmptl

```

Scratch space.

```

53 \prop_new:N \l__cmd_tmp_prop
54 \tl_new:N \l__cmd_tmptl
55 \tl_new:N \l__cmd_tmptl
56 \cs_new_eq:NN \__cmd_tmp:w ?

```

(End of definition for \\_\_cmd\_tmp:w.)

With `xparse`, information about commands being (re)defined was switched off by default, unless the `log-declarations` package option was used, so here we'll switch that off as well.

```

57 \msg_redirect_module:nnn { cmd } { info } { none }

```

Also add `cmd` to the LaTeX messages.

```

58 \prop_gput:Nnn \g_msg_module_type_prop { cmd } { LaTeX }

```

## 1.2 Declaring commands and environments

```

\__cmd_declare_cmd:Nnn
\__cmd_declare_expandable_cmd:Nnn
\__cmd_declare_cmd_aux:Nnn
\__cmd_declare_cmd_internal:Nnn

```

The main functions for creating commands set the appropriate flag then use the same internal code to do the definition.

```

59 \cs_new_protected:Npn \__cmd_declare_cmd:Nnn
60 {
61   \bool_set_false:N \l__cmd_expandable_bool
62   \__cmd_declare_cmd_aux:Nnn
63 }
64 \cs_new_protected:Npn \__cmd_declare_expandable_cmd:Nnn
65 {
66   \bool_set_true:N \l__cmd_expandable_bool
67   \__cmd_declare_cmd_aux:Nnn
68 }

```

The first stage is to log information, both for the user in the log and for programmatic use in a property list of all declared commands.

```

69 \cs_new_protected:Npn \__cmd_declare_cmd_aux:Nnn #1#2#3
70 {
71   \cs_if_exist:NTF #1
72   {
73     \msg_info:nnxx { cmd } { redefine }
74     { \token_to_str:N #1 } { \tl_to_str:n {#2} }
75   }
76   {
77     \bool_lazy_or:nnT
78     { \cs_if_exist_p:c { \cs_to_str:N #1 ~ code } }

```

```

79         { \cs_if_exist_p:c { \cs_to_str:N #1 ~ defaults } }
80     {
81         \msg_warning:nnx { cmd } { unsupported-let }
82         { \token_to_str:N #1 }
83     }
84     \msg_info:nnxx { cmd } { define-command }
85     { \token_to_str:N #1 } { \tl_to_str:n {#2} }
86 }
87 \bool_set_false:N \l__cmd_environment_bool
88 \__cmd_declare_cmd_internal:Nnnn #1 {#2} {#3} { }
89 }

```

At definition time, the variable `\l__cmd_fn_tl` is only used for error messages. The real business of defining a document command starts with setting up the appropriate name, then normalizing the argument specification to get rid of shorthands.

```

90 \cs_new_protected:Npn \__cmd_declare_cmd_internal:Nnnn #1#2#3#4
91 {
92     \tl_set:Nx \l__cmd_function_tl { \cs_to_str:N #1 }
93     \__cmd_normalize_arg_spec:n {#2}
94     \exp_args:No \__cmd_prepare_signature:n \l__cmd_arg_spec_tl
95     \__cmd_declare_cmd_code:Nnn #1 {#2} {#3}
96     #4
97     \__cmd_break_point:n {#2}
98 }

```

*(End of definition for `\__cmd_declare_cmd:Nnn` and others.)*

`\__cmd_break_point:n` A marker used to escape from creating a definition if necessary.

```

99 \cs_new_eq:NN \__cmd_break_point:n \use_none:n

```

*(End of definition for `\__cmd_break_point:n`.)*

`\__cmd_all_m_check:n` A quick loop to check for all (+)m-type arguments.

```

\__cmd_all_m_check_aux:n
100 \cs_new:Npn \__cmd_all_m_check:n #1
101 { \tl_map_function:nN {#1} \__cmd_all_m_check_aux:n }
102 \cs_new:Npn \__cmd_all_m_check_aux:n #1
103 {
104     \str_if_eq:nnF {#1} { m }
105     {
106         \str_if_eq:nnF {#1} { + }
107         { X }
108     }
109 }

```

*(End of definition for `\__cmd_all_m_check:n` and `\__cmd_all_m_check_aux:n`.)*

`\__cmd_declare_cmd_code:Nnn` At this stage we can check for a short-cut possibility: if the argument specification is made up of just (+)m tokens, and if all arguments are either short or long, then we can produce an optimized document command. This only applies to document commands, not creation of environments (which are more complex).

```

\__cmd_declare_cmd_optimized:Nnn
\__cmd_declare_cmd_code_aux:Nnn
\__cmd_declare_cmd_code_expandable:Nnn
\__cmd_start_optimized:

```

```

110 \cs_new_protected:Npn \__cmd_declare_cmd_code:Nnn #1#2
111 {
112     \bool_lazy_any:nTF
113     {
114         { \l__cmd_environment_bool }

```

```

115     {
116         \bool_lazy_and_p:nn
117         { \l__cmd_some_short_bool }
118         { \l__cmd_some_long_bool }
119     }
120     { ! \tl_if_blank_p:e { \__cmd_all_m_check:n {#2} } }
121 }
122 {
123     \tl_set:Nx \l__cmd_fn_tl
124     { \exp_not:c { \l__cmd_function_tl \c_space_tl } }
125     \bool_if:NTF \l__cmd_grab_expandably_bool
126     { \__cmd_declare_cmd_code_expandable:Nnn }
127     { \__cmd_declare_cmd_code_aux:Nnn }
128 }
129 { \__cmd_declare_cmd_optimized:Nnn }
130 #1 {#2}
131 }

```

The optimized version of commands just has to worry about whether to make them protected or long. The commands start with an expandable marker so that other parts of the kernel know these are set up by `ltxcmd`. We need the two layers of redirection so that the `code` internal function has the same form as it would for any other document command. Optimization means that there is no `\group_align_safe_begin:` before grabbing the arguments, so anything involving `&` tokens will not work. However, this is really only intended for making optional argument processing safe anyway, so in practice should not be an issue.

```

132 \cs_new_protected:Npn \__cmd_declare_cmd_optimized:Nnn #1#2#3
133 {
134     \bool_if:NTF \l__cmd_expandable_bool
135     { \cs_set_nopar:Npe }
136     { \cs_set_protected_nopar:Npe }
137     #1
138     {
139         \exp_not:N \__cmd_start_optimized:
140         \exp_not:c { \l__cmd_function_tl \c_space_tl code }
141     }
142     \exp_args:Ncc \cs_generate_from_arg_count:NNnn
143     { \l__cmd_function_tl \c_space_tl code }
144     {
145         cs_set
146         \bool_if:NF \l__cmd_expandable_bool { _protected }
147         \bool_if:NF \l__cmd_some_long_bool { _nopar }
148         :Npn
149     }
150     \l__cmd_current_arg_int
151     {#3}
152 }
153 \cs_new:Npn \__cmd_start_optimized: { }

```

Standard functions call `\__cmd_start:nNNnnn`, which receives the argument specification, an auxiliary used for grabbing arguments, an auxiliary containing the code, and then the signature, default arguments, and processors.

```

154 \cs_new_protected:Npn \__cmd_declare_cmd_code_aux:Nnn #1#2#3
155 {

```

```

156 \cs_generate_from_arg_count:cNnn
157 { \l__cmd_function_tl \c_space_tl code }
158 \cs_set_protected:Npn \l__cmd_current_arg_int {#3}
159 \cs_set_protected_nopar:Npx #1
160 {
161   \bool_if:NTF \l__cmd_environment_bool
162   {
163     \__cmd_start_env:nnnnn { \exp_not:n {#2} }
164     { \l__cmd_environment_str }
165   }
166   {
167     \__cmd_start:nNNnnn { \exp_not:n {#2} }
168     \exp_not:c { \l__cmd_function_tl \c_space_tl }
169     \exp_not:c { \l__cmd_function_tl \c_space_tl code }
170   }
171   { \exp_not:o \l__cmd_signature_tl }
172   {
173     \bool_if:NT \l__cmd_defaults_bool
174     { \exp_not:o \l__cmd_defaults_tl }
175   }
176   {
177     \bool_if:NT \l__cmd_process_some_bool
178     { \exp_not:o \l__cmd_process_all_tl }
179   }
180 }
181 }

```

Expandable functions and functions whose arguments can be grabbed expandably call `\__cmd_start_expandable:nNNNNn`, which receives the argument specification, four auxiliaries (two for grabbing arguments, one for the code, and one for default arguments), and finally the signature. Non-expandable functions that take this branch should nevertheless be protected, as well as their `code` function. They will only be expanded in contexts such as constructing a `csname`. The two grabbers (named after the function with one or two spaces) are needed when there are both short and long arguments; otherwise the same grabber is included twice in the definition. If all arguments are long or all are short the (only) grabber is defined correspondingly to be long/short. Otherwise two grabbers are defined, one long, one short.

```

182 \cs_new_protected:Npn \__cmd_declare_cmd_code_expandable:Nnn #1#2#3
183 {
184   \exp_args:Ncc \cs_generate_from_arg_count:NNnn
185   { \l__cmd_function_tl \c_space_tl code }
186   { cs_set \bool_if:NF \l__cmd_expandable_bool { _protected } :Npn }
187   \l__cmd_current_arg_int {#3}
188   \bool_if:NT \l__cmd_defaults_bool
189   {
190     \use:x
191     {
192       \cs_generate_from_arg_count:cNnn
193       { \l__cmd_function_tl \c_space_tl defaults }
194       \cs_set:Npn \l__cmd_current_arg_int
195       { \exp_not:o \l__cmd_defaults_tl }
196     }
197   }
198   \bool_if:NTF \l__cmd_expandable_bool

```

```

199 { \cs_set_nopar:Npx } { \cs_set_protected_nopar:Npx } #1
200 {
201   \exp_not:N \l__cmd_start_expandable:nNNNNn
202   { \exp_not:n {#2} }
203   \exp_not:c { \l__cmd_function_tl \c_space_tl }
204   \exp_not:c
205   {
206     \l__cmd_function_tl \c_space_tl
207     \bool_if:NT \l__cmd_some_short_bool
208     { \bool_if:NT \l__cmd_some_long_bool { \c_space_tl } }
209   }
210   \exp_not:c { \l__cmd_function_tl \c_space_tl code }
211   \bool_if:NTF \l__cmd_defaults_bool
212   { \exp_not:c { \l__cmd_function_tl \c_space_tl defaults } }
213   { ? }
214   { \exp_not:o \l__cmd_signature_tl }
215 }
216 \bool_if:NTF \l__cmd_some_long_bool
217 {
218   \bool_if:NT \l__cmd_some_short_bool
219   {
220     \cs_set_nopar:cpx { \l__cmd_function_tl \c_space_tl \c_space_tl }
221     ##1##2 { ##1 {##2} }
222   }
223   \cs_set:cpx
224 }
225 { \cs_set_nopar:cpx }
226 { \l__cmd_function_tl \c_space_tl } ##1##2 { ##1 {##2} }
227 }

```

(End of definition for \l\_\_cmd\_declare\_cmd\_code:Nnn and others.)

```

\__cmd_declare_env:nnnn
\__cmd_declare_env:ennn
\__cmd_declare_env_internal:nnnn
\__cmd_set_environment_end:n

```

The lead-off to creating an environment is much the same as that for creating a command: issue the appropriate message, store the argument specification then hand off to an internal function.

```

228 <latexrelease> \IncludeInRelease{2024/11/01}{\__cmd_declare_env:nnnn}%
229 <latexrelease> {Use~space-trimmed-envname-directly}
230 \cs_new_protected:Npn \__cmd_declare_env:nnnn #1#2
231 {
232   \str_set:Nn \l__cmd_environment_str {#1}
233   \cs_if_exist:CTF { #1 }
234   { \msg_info:nnnn { cmd } { redefine-env } { #1 } { #2 } }
235   { \msg_info:nnnn { cmd } { define-env } { #1 } { #2 } }
236   \bool_set_false:N \l__cmd_expandable_bool
237   \bool_set_true:N \l__cmd_environment_bool
238   \__cmd_declare_env_internal:nnnn {#1} {#2}
239 }
240 \cs_generate_variant:Nn \__cmd_declare_env:nnnn { e }
241 <latexrelease> \EndIncludeInRelease
242 <latexrelease> \IncludeInRelease{2024/06/01}{\__cmd_declare_env:nnnn}%
243 <latexrelease> {Use~space-trimmed-envname-directly}
244 <latexrelease> \cs_new_protected:Npn \__cmd_declare_env:nnnn #1#2
245 <latexrelease> {
246 <latexrelease>   \str_set:Nx \l__cmd_environment_str {#1}

```

```

247 \latexrelease \str_set:Nx \l__cmd_environment_str
248 \latexrelease { \tl_trim_spaces:o { \l__cmd_environment_str } }
249 \latexrelease \cs_if_exist:cTF { \l__cmd_environment_str }
250 \latexrelease {
251 \latexrelease \msg_info:nnxx { cmd } { redefine-env }
252 \latexrelease { \l__cmd_environment_str } { \tl_to_str:n {#2} }
253 \latexrelease }
254 \latexrelease {
255 \latexrelease \msg_info:nnxx { cmd } { define-env }
256 \latexrelease { \l__cmd_environment_str } { \tl_to_str:n {#2} }
257 \latexrelease }
258 \latexrelease \bool_set_false:N \l__cmd_expandable_bool
259 \latexrelease \bool_set_true:N \l__cmd_environment_bool
260 \latexrelease \exp_args:NV \__cmd_declare_env_internal:nnnn
261 \latexrelease \l__cmd_environment_str {#2}
262 \latexrelease }
263 \latexrelease
264 \latexrelease \EndIncludeInRelease

```

Creating a document environment requires a few more steps than creating a single command. In order to pass the arguments of the command to the end of the function, it is necessary to store the grabbed arguments. To do that, the function used at the end of the environment has to be redefined to contain the appropriate information. To minimize the amount of expansion at point of use, the code here is expanded now as well as when used. The last argument of `\__cmd_declare_cmd_internal:Nnnn` is only run if the definition succeeded. In package mode this ensures that the original definition of the environment is not changed if the definition fails for any reason. This also avoids an error when defining the `end_au_x` function when the user asks for more than 9 arguments.

```

265 \cs_new_protected:Npn \__cmd_declare_env_internal:nnnn #1#2#3#4
266 {
267 \exp_args:Nc \__cmd_declare_cmd_internal:Nnnn { environment~ #1 } {#2}
268 {#3}
269 {
270 \cs_set_nopar:cpx { environment~ #1 ~end }
271 { \exp_not:c { environment~ #1 ~end~aux } }
272 \cs_generate_from_arg_count:cNnn
273 { environment~ #1 ~end~aux~ } \cs_set:Npn
274 \l__cmd_current_arg_int {#4}
275 \cs_set_eq:cc {#1} { environment~ #1 }
276 \cs_set_eq:cc { end #1 } { environment~ #1 ~end }
277 }
278 }
279 \cs_new_protected:Npn \__cmd_set_environment_end:n #1
280 {
281 \cs_set_nopar:cpx { environment~ #1 ~end~aux }
282 {
283 \exp_not:c { environment~ #1 ~end~aux~ }
284 \exp_not:o \l__cmd_args_tl
285 }
286 }

```

(End of definition for `\__cmd_declare_env:nnnn`, `\__cmd_declare_env_internal:nnnn`, and `\__cmd_set_environment_end:n`.)

### 1.3 Structure of xparse commands

`\__cmd_start_env:nnnnn`  
`\__cmd_start:nNNnnn`

For error messages that occur during run-time when getting arguments of environments it is necessary to keep track of the environment name. We begin non-expandable commands with a token equal to `\scan_stop:`, whose name gives a reasonable error message if the command is used inside a csname and protects against f-expansion. This is useless for environments since `\begin` is already not expandable. Both the command and environment codes start with `\group_align_safe_begin:`, then `\__cmd_run_code:` (used by both) does `\group_align_safe_end:`, so that delimited arguments may be grabbed in alignments if they contain an alignment tab token (see latex3/latex3/issues/839).

```

287 \cs_new_protected:Npn \__cmd_start_env:nnnnn #1#2
288 {
289   \conditionally@traceoff
290   \group_align_safe_begin:
291   \str_set:Nn \l__cmd_environment_str {#2}
292   \bool_set_true:N \l__cmd_environment_bool
293   \__cmd_start_aux:ccnnnn
294   { environment~ \l__cmd_environment_str \c_space_tl }
295   { environment~ \l__cmd_environment_str \c_space_tl code }
296   {#1}
297 }
298 \cs_new_protected:Npx \__cmd_start:nNNnnn #1#2#3
299 {
300   \exp_not:c { xparse~function~is~not~expandable }
301   \exp_not:N \conditionally@traceoff
302   \exp_not:N \group_align_safe_begin:
303   \exp_not:n { \bool_set_false:N \l__cmd_environment_bool }
304   \exp_not:N \__cmd_start_aux:NNnnnn
305   #2 #3 {#1}
306 }
```

*(End of definition for \\_\_cmd\_start\_env:nnnnn and \\_\_cmd\_start:nNNnnn.)*

`\__cmd_start_aux:NNnnnn`  
`\__cmd_start_aux:ccnnnn`

This sets up a few variables to minimize the boilerplate code included in all xparse-defined commands. It then runs the grabbers #4. Again, the argument specification #1 is only for diagnostics.

```

307 \cs_new_protected:Npn \__cmd_start_aux:NNnnnn #1#2#3#4#5#6
308 {
309   \tl_clear:N \l__cmd_args_tl
310   \tl_set:Nn \l__cmd_fn_tl {#1}
311   \tl_set:Nn \l__cmd_fn_code_tl {#2}
312   \tl_set:Nn \l__cmd_defaults_tl {#5}
313   \tl_set:Nn \l__cmd_process_all_tl {#6}
314   #4
315   \__cmd_run_code:
316 }
317 \cs_generate_variant:Nn \__cmd_start_aux:NNnnnn { cc }
```

*(End of definition for \\_\_cmd\_start\_aux:NNnnnn.)*

`\__cmd_run_code:`

After arguments are grabbed, this function is responsible for inserting default values, running processors, and finally doing `\group_align_safe_end:` as promised, and running the code.

```

318 \cs_new_protected:Npn \__cmd_run_code:
```

```

319 {
320   \tl_if_empty:NF \l__cmd_defaults_tl { \__cmd_defaults: }
321   \tl_if_empty:NF \l__cmd_process_all_tl { \__cmd_args_process: }
322   \bool_if:NT \l__cmd_environment_bool
323     { \exp_args:No \__cmd_set_environment_end:n \l__cmd_environment_str }
324   \group_align_safe_end:
325   \conditionally@traceon
326   \exp_after:wN \l__cmd_fn_code_tl \l__cmd_args_tl
327 }

```

(End of definition for \\_\_cmd\_run\_code:.)

\\_\_cmd\_defaults: First construct \\_\_cmd\_tmp:w (see below) that will receive the arguments found so far and determine default values for any missing argument. Then call it repeatedly until the set of arguments stabilizes. Since that could lead to an infinite loop we only call it up to nine times, the maximal number needed for stabilization if there is a chain of arguments that depend on each other. If that fails to stabilize raise an error.

```

\__cmd_defaults_def:nn
\__cmd_defaults_def:nnn
\__cmd_defaults_aux:
\__cmd_defaults_error:w
328 \cs_new_protected:Npn \__cmd_defaults:
329 {
330   \__cmd_defaults_def:
331   \tl_set_eq:NN \l__cmd_args_i_tl \l__cmd_args_tl
332   \__cmd_defaults_aux: \__cmd_defaults_aux: \__cmd_defaults_aux:
333   \__cmd_defaults_aux: \__cmd_defaults_aux: \__cmd_defaults_aux:
334   \__cmd_defaults_aux: \__cmd_defaults_aux: \__cmd_defaults_aux:
335   \__cmd_defaults_error:w
336   \q_recursion_stop
337   \tl_set_eq:NN \l__cmd_args_tl \l__cmd_args_i_tl
338 }
339 \cs_new_protected:Npn \__cmd_defaults_aux:
340 {
341   \tl_set:Nx \l__cmd_args_ii_tl
342     { \exp_after:wN \__cmd_tmp:w \l__cmd_args_i_tl }
343   \tl_if_eq:NNT \l__cmd_args_ii_tl \l__cmd_args_i_tl
344     { \use_none_delimit_by_q_recursion_stop:w }
345   \tl_set_eq:NN \l__cmd_args_i_tl \l__cmd_args_ii_tl
346 }
347 \cs_new_protected:Npn \__cmd_defaults_error:w \q_recursion_stop
348 {
349   \msg_error:nnx { cmd } { default-loop }
350   { \__cmd_environment_or_command: }
351 }

```

To construct \\_\_cmd\_tmp:w, first go through the arguments found and the corresponding defaults, building a token list with `{#⟨arg number⟩}` for arguments found in the input (whose default will not be used) and otherwise `{\exp_not:n{⟨default⟩}}` for arguments whose default will be used.

```

352 \cs_new_protected:Npn \__cmd_defaults_def:
353 {
354   \tl_clear:N \l__cmd_tmpa_tl
355   \int_zero:N \l__cmd_current_arg_int
356   \__cmd_tl_mapthread_function:NNN \l__cmd_args_tl \l__cmd_defaults_tl
357     \__cmd_defaults_def:nn
358   \cs_generate_from_arg_count:NNno \__cmd_tmp:w \cs_set:Npn
359     \l__cmd_current_arg_int \l__cmd_tmpa_tl

```

```

360 }
361 \cs_generate_variant:Nn \cs_generate_from_arg_count:NNnn { NNno }
362 \cs_new_protected:Npn \__cmd_defaults_def:nn
363 {
364   \int_incr:N \l__cmd_current_arg_int
365   \exp_args:NV \__cmd_defaults_def:nnn \l__cmd_current_arg_int
366 }
367 \cs_new_protected:Npn \__cmd_defaults_def:nnn #1#2#3
368 {
369   \tl_put_right:Nx \l__cmd_tmpa_tl
370   {
371     {
372       \exp_not:N \exp_not:n
373       {
374         \tl_if_novalue:nTF {#2}
375         { \exp_not:o {#3} }
376         { \exp_not:n { ## #1 } }
377       }
378     }
379   }
380 }

```

(End of definition for \\_\_cmd\_defaults: and others.)

\\_\_cmd\_args\_process: Loop through arguments (stored in \l\_\_cmd\_args\_tl) and the corresponding processors (in \l\_\_cmd\_process\_all\_tl) simultaneously, apply all processors for each argument and store the result back into \l\_\_cmd\_args\_tl. To allow processors to depend on other arguments, for every processor define a temporary auxiliary that receives all arguments \l\_\_cmd\_args\_tl.

```

381 \cs_new_protected:Npn \__cmd_args_process:
382 {
383   \tl_clear:N \l__cmd_args_ii_tl
384   \__cmd_tl_mapthread_function:NNN
385   \l__cmd_args_tl
386   \l__cmd_process_all_tl
387   \__cmd_args_process_loop:nn
388   \tl_set_eq:NN \l__cmd_args_tl \l__cmd_args_ii_tl
389 }
390 \cs_new_protected:Npn \__cmd_args_process_loop:nn #1#2
391 {
392   \tl_set:Nn \ProcessedArgument {#1}
393   \tl_if_novalue:nF {#1}
394   { \tl_map_function:nN {#2} \__cmd_args_process_aux:n }
395   \tl_put_right:No \l__cmd_args_ii_tl
396   { \exp_after:wN { \ProcessedArgument } }
397 }
398 \cs_new_protected:Npn \__cmd_args_process_aux:n #1
399 {
400   \cs_generate_from_arg_count:NNnn \__cmd_tmp:w \cs_set:Npn
401   { \tl_count:N \l__cmd_args_tl } {#1}
402   \exp_args:NNNo \exp_after:wN \__cmd_tmp:w \l__cmd_args_tl
403   { \ProcessedArgument }
404 }

```

(End of definition for `\__cmd_args_process:`, `\__cmd_args_process_loop:nn`, and `\__cmd_args_process_aux:n`.)

`\__cmd_start_expandable:nnNNNn`

This is called for all expandable commands. #6 is the signature, responsible for grabbing arguments. #5 is used to determine default values (or is ? if there are none). #4 is the code to run. #2 and #3 are functions (named after the command) that grab a single argument in the input stream (#3 is short). The argument specification #1 is only used by diagnostic functions. Same as for the non-expandable version, this starts with `\group_align_safe_begin:`, which expands to nothing, so may be safely used in an expandable context.

```
405 \cs_new:Npn \__cmd_start_expandable:nnNNNn #1#2#3#4#5#6
406 {
407   \group_align_safe_begin:
408   #6 \__cmd_end_expandable:NNw #5 #4 \q__cmd #2#3
409 }
```

(End of definition for `\__cmd_start_expandable:nnNNNn`.)

`\__cmd_end_expandable:NNw`  
`\__cmd_end_expandable_aux:w`  
`\__cmd_end_expandable_aux:nnNNN`  
`\__cmd_end_expandable_defaults:nnnNNn`  
`\__cmd_end_expandable_defaults:nnw`  
`\__cmd_end_expandable_defaults:nnw`

Followed by a function #1 to determine default values (or ? if there are no defaults), the code #2, arguments that have been grabbed, then `\q__cmd` and two generic grabbers. The idea to find default values is similar to the non-expandable case but we cannot define an auxiliary function, so at every step in the loop we need to go through all arguments searching for which ones started out as `-NoValue-` and replacing these by the newly computed values. In fact we need to keep track of three versions of all arguments: the original version, the previous version with default values, and the currently built version (first argument of `\__cmd_end_expandable_defaults:nnnNNn`).

```
410 \cs_new:Npn \__cmd_end_expandable:NNw #1#2
411 { \__cmd_end_expandable_aux:w #1#2 \prg_do_nothing: }
412 \cs_new:Npn \__cmd_end_expandable_aux:w #1#2#3 \q__cmd
413 { \exp_args:No \__cmd_end_expandable_aux:nnNNN {#3} #1 #2 }
414 \cs_new:Npn \__cmd_end_expandable_aux:nnNNN #1#2#3#4#5
415 {
416   \token_if_eq_charcode:NNT ? #2 { \exp_after:wN \use_iv:nnnn }
417   \__cmd_end_expandable_defaults:nnnNNn {#1} { } {#1} #2#3
418   { } { } { } { } { } { } { } { } { } { } { } { } { }
419   {
420     \msg_expandable_error:nnf { cmd } { default-loop }
421     { \exp_args:Nf \tl_trim_spaces:n { \token_to_str:N #4 } }
422     \use_iv:nnnn
423   }
424   \q_stop
425 }
426 \cs_new:Npn \__cmd_end_expandable_defaults:nnnNNn #1#2#3#4#5#6
427 {
428   #6
429   \str_if_eq:nnTF {#1} {#2}
430   { \use_i_delimit_by_q_stop:nw { \group_align_safe_end: #5 #1 } }
431   {
432     \exp_args:No \__cmd_tl_mapthread_function:nnN
433     { #4 #1 } {#3}
434     \__cmd_end_expandable_defaults:nnw
435     \__cmd_end_expandable_defaults:nnnNNn { } {#1} {#3} #4 #5
436   }
```

```

437 }
438 \cs_new:Npn \__cmd_end_expandable_defaults:nnw #1#2
439 {
440   \tl_if_novalue:nTF {#2}
441     { \exp_args:No \__cmd_end_expandable_defaults:nw {#1} }
442     { \__cmd_end_expandable_defaults:nw {#2} }
443 }
444 \cs_new:Npn \__cmd_end_expandable_defaults:nw
445   #1#2 \__cmd_end_expandable_defaults:nnnNNn #3
446   { #2 \__cmd_end_expandable_defaults:nnnNNn { #3 {#1} } }

```

*(End of definition for \\_\_cmd\_end\_expandable:NNw and others.)*

## 1.4 Normalizing the argument specifications

The goal here is to expand aliases and check that the argument specification is valid before the main parsing run. If it is not valid the entire set up is abandoned to avoid any strange internal errors. A function is provided for each argument type that will grab any extra data items and call the loop function after performing the following checks and tasks.

- Check that each argument has the correct number of data items associated with it, and that where a single character is required, one has actually been supplied.
- Check that processors and the markers +, ! and = are followed by an argument for which they make sense, and are not redundant.
- Check the absence of forbidden types for expandable commands, namely G/v always, and l/u after optional arguments (xparse may have inserted braces due to a failed search for an optional argument).
- Check that no optional argument is followed by a mandatory argument with the same delimiter, as otherwise the optional argument could never be omitted.
- Keep track in \l\_\_cmd\_some\_long\_bool and \l\_\_cmd\_some\_short\_bool of whether the command has some long/short arguments.
- Keep track in \l\_\_cmd\_grab\_expandably\_bool of whether all arguments are m/l/u type and short arguments appear before long ones, in which case they can be grabbed expandably just as safely as they could be grabbed nonexpandably. Regardless of that, arguments of expandable commands will be grabbed expandably and arguments of environments will not (because the list of arguments built by non-expandable grabbing is used to pass them to the end-environment code).

Further checks happen at the end of the loop:

- that there are at most 9 arguments;
- that an expandable command does not end with an optional argument (this case is detected by using the fact that \l\_\_cmd\_last\_delimiters\_tl is cleared by every mandatory argument and filled by every optional argument).

```

__cmd_normalize_arg_spec:n Loop through the argument specification, calling an auxiliary specific to each argument
    __cmd_normalize_arg_spec_loop:n type. If any argument is unknown stop the definition.

447 \cs_new_protected:Npn __cmd_normalize_arg_spec:n #1
448 {
449     \int_zero:N \l__cmd_current_arg_int
450     \int_zero:N \l__cmd_last_mandatory_arg_int
451     \tl_clear:N \l__cmd_last_delimiters_tl
452     \tl_clear:N \l__cmd_arg_spec_tl
453     \bool_set_true:N \l__cmd_grab_expandably_bool
454     \bool_set_false:N \l__cmd_obey_spaces_bool
455     \bool_set_false:N \l__cmd_long_bool
456     \bool_set_false:N \l__cmd_suppress_strip_bool
457     \bool_set_false:N \l__cmd_some_obey_spaces_bool
458     \bool_set_false:N \l__cmd_some_long_bool
459     \bool_set_false:N \l__cmd_some_short_bool
460     __cmd_normalize_arg_spec_loop:n #1
461     \q_recursion_tail \q_recursion_tail \q_recursion_tail \q_recursion_stop
462     \int_compare:nNnT \l__cmd_current_arg_int > 9
463     {
464         \msg_error:nnxx { cmd } { too-many-args }
465         { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
466         \__cmd_bad_def:wn
467     }
468     \bool_if:NT \l__cmd_expandable_bool
469     {
470         \tl_if_empty:NF \l__cmd_last_delimiters_tl
471         {
472             \msg_error:nnxx { cmd } { expandable-ending-optional }
473             { \iow_char:N \ \l__cmd_function_tl } { \tl_to_str:n {#1} }
474             \__cmd_bad_def:wn
475         }
476     }
477     \bool_if:NT \l__cmd_expandable_bool
478     { \bool_set_true:N \l__cmd_grab_expandably_bool }
479     \bool_if:NT \l__cmd_environment_bool
480     { \bool_set_false:N \l__cmd_grab_expandably_bool }
481 }
482 \cs_new_protected:Npn __cmd_normalize_arg_spec_loop:n #1
483 {
484     \quark_if_recursion_tail_stop:n {#1}
485     \int_incr:N \l__cmd_current_arg_int
486     \cs_if_exist_use:cF { __cmd_normalize_type_ \tl_to_str:n {#1} :w }
487     {
488         \bool_lazy_any:nTF
489         {
490             { \str_if_eq_p:nn {#1} { G } }
491             { \str_if_eq_p:nn {#1} { g } }
492             { \str_if_eq_p:nn {#1} { l } }
493             { \str_if_eq_p:nn {#1} { u } }
494         }
495         {
496             \msg_error:nnxx { cmd } { xparse-arg-type }
497             { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
498         }
499     }

```

```

499         {
500             \msg_error:nnxx { cmd } { unknown-argument-type }
501             { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
502         }
503     \__cmd_bad_def:wn
504 }
505 }

```

(End of definition for \\_\_cmd\_normalize\_arg\_spec:n and \\_\_cmd\_normalize\_arg\_spec\_loop:n.)

\\_\_cmd\_normalize\_type\_d:w These argument types are aliases of more general ones, for example with the default argument -NoValue-. To easily insert that marker expanded in the definitions we call \\_\_cmd\_tmp:w with the argument -NoValue-. For argument types that need additional data, check that the data is present (not \q\_recursion\_tail) before proceeding.

```

506 \cs_set_protected:Npn \__cmd_tmp:w #1
507 {
508     \cs_new_protected:Npn \__cmd_normalize_type_d:w ##1##2
509     {
510         \quark_if_recursion_tail_stop_do:nn {##2} { \__cmd_bad_arg_spec:wn }
511         \__cmd_normalize_type_D:w {##1} {##2} {#1}
512     }
513     \cs_new_protected:Npn \__cmd_normalize_type_e:w ##1
514     {
515         \quark_if_recursion_tail_stop_do:nn {##1} { \__cmd_bad_arg_spec:wn }
516         \__cmd_normalize_type_E:w {##1} { }
517     }
518     \cs_new_protected:Npn \__cmd_normalize_type_o:w
519     { \__cmd_normalize_type_D:w [ ] {#1} }
520     \cs_new_protected:Npn \__cmd_normalize_type_O:w
521     { \__cmd_normalize_type_D:w [ ] }
522     \cs_new_protected:Npn \__cmd_normalize_type_r:w ##1##2
523     {
524         \quark_if_recursion_tail_stop_do:nn {##2} { \__cmd_bad_arg_spec:wn }
525         \__cmd_normalize_type_R:w {##1} {##2} {#1}
526     }
527     \cs_new_protected:Npn \__cmd_normalize_type_s:w
528     { \__cmd_normalize_type_t:w * }
529 }
530 \exp_args:No \__cmd_tmp:w { \c_novalue_tl }

```

(End of definition for \\_\_cmd\_normalize\_type\_d:w and others.)

\\_\_cmd\_normalize\_type\_>:w Check that these prefixes have arguments, namely that the next token is not \q\_recursion\_tail, and remember to leave it after the looping macro. Processors are forbidden in expandable commands. If all is good, store the prefix in the cleaned up \l\_\_cmd\_arg\_spec\_tl, and decrement the argument number as prefixes do not correspond to arguments.

```

531 \cs_new_protected:cpn { __cmd_normalize_type_>:w } #1#2
532 {
533     \quark_if_recursion_tail_stop_do:nn {#2} { \__cmd_bad_arg_spec:wn }
534     \bool_if:NT \l__cmd_expandable_bool
535     {
536         \msg_error:nnxx { cmd } { processor-in-expandable }
537         { \iow_char:N \ \ \l__cmd_function_tl } { \tl_to_str:n {#1} }

```

```

538     \_cmd_bad_def:wn
539   }
540   \tl_put_right:Nx \l__cmd_arg_spec_tl { > { \tl_trim_spaces:n {#1} } }
541   \int_decr:N \l__cmd_current_arg_int
542   \bool_set_false:N \l__cmd_grab_expandably_bool
543   \_cmd_normalize_arg_spec_loop:n {#2}
544 }
545 \cs_new_protected:cpn { __cmd_normalize_type_+ :w } #1
546 {
547   \_cmd_normalize_type_aux:NnNn + {#1}
548   \l__cmd_long_bool
549   { \bool_set_true:N \l__cmd_long_bool }
550 }
551 \cs_new_protected:cpn { __cmd_normalize_type_! :w } #1
552 {
553   \_cmd_normalize_type_aux:NnNn ! {#1}
554   \l__cmd_obey_spaces_bool
555   {
556     \bool_set_true:N \l__cmd_obey_spaces_bool
557     \bool_set_true:N \l__cmd_some_obey_spaces_bool
558   }
559 }
560 \cs_new_protected:cpn { __cmd_normalize_type_= :w } #1#2
561 {
562   \_cmd_normalize_type_aux:NnNn = {#2}
563   \l__cmd_suppress_strip_bool
564   {
565     \bool_if:NT \l__cmd_expandable_bool
566     {
567       \msg_error:nxxx { cmd } { keyval-in-expandable }
568       { \iow_char:N \ \l__cmd_function_tl } { \tl_to_str:n {#1} }
569       \_cmd_bad_def:wn
570     }
571     \bool_set_true:N \l__cmd_suppress_strip_bool
572     \bool_set_false:N \l__cmd_grab_expandably_bool
573     \tl_put_right:Nx \l__cmd_arg_spec_tl
574     { = { \tl_trim_spaces:n {#1} } }
575   }
576 }
577 \cs_new_protected:Npn \_cmd_normalize_type_aux:NnNn #1#2#3#4
578 {
579   \quark_if_recursion_tail_stop_do:nn {#2} { \_cmd_bad_arg_spec:wn }
580   \bool_if:NT #3
581   {
582     \msg_error:nxxx { cmd } { two-markers }
583     { \_cmd_environment_or_command: } { #1 }
584     \_cmd_bad_def:wn
585   }
586   #4
587   \int_decr:N \l__cmd_current_arg_int
588   \_cmd_normalize_arg_spec_loop:n {#2}
589 }

```

(End of definition for \\_cmd\_normalize\_type\_>:w and others.)

```

\__cmd_normalize_type_D:w Optional argument types. Check that all required data is present (and consists of single
\__cmd_normalize_type_E:w characters if applicable) and check for forbidden types for expandable commands. For
\__cmd_normalize_type_t:w E-type require that there is at least one embellishment, that each one is a single character,
\__cmd_normalize_E_unique_check:w and that there aren't more optional arguments than embellishments; also remember that
each embellishment counts as one argument for \l__cmd_current_arg_int. Then in
each case store the data in \l__cmd_arg_spec_tl, and for later checks store in \l__-
cmd_last_delimiters_tl the tokens whose presence determines whether there is an
optional argument (for braces store {}, seen later as an empty delimiter).

590 \cs_new_protected:Npn \__cmd_normalize_type_D:w #1#2#3
591 {
592   \quark_if_recursion_tail_stop_do:nn {#3} { \__cmd_bad_arg_spec:wn }
593   \__cmd_single_token_check:n {#1} \__cmd_allowed_token_check:N #1
594   \__cmd_single_token_check:n {#2}
595   \__cmd_add_arg_spec:n { D #1 #2 {#3} }
596   \tl_put_right:Nn \l__cmd_last_delimiters_tl {#1}
597   \bool_set_false:N \l__cmd_grab_expandably_bool
598   \__cmd_normalize_arg_spec_loop:n
599 }
600 \cs_new_protected:Npn \__cmd_normalize_type_E:w #1#2
601 {
602   \quark_if_recursion_tail_stop_do:nn {#2} { \__cmd_bad_arg_spec:wn }
603   \tl_if_blank:nT {#1} { \__cmd_bad_arg_spec:wn }
604   \tl_map_function:nN {#1} \__cmd_single_token_check:n
605   \tl_map_function:nN {#1} \__cmd_allowed_token_check:N
606   \__cmd_normalize_E_unique_check:w #1 \q_nil \q_stop
607   \int_compare:nNnT { \tl_count:n {#2} } > { \tl_count:n {#1} }
608     { \__cmd_bad_arg_spec:wn }
609   \__cmd_add_arg_spec:n { E {#1} {#2} }
610   \tl_put_right:Nn \l__cmd_last_delimiters_tl {#1}
611   \bool_set_false:N \l__cmd_grab_expandably_bool
612   \int_add:Nn \l__cmd_current_arg_int { \tl_count:n {#1} - 1 }
613   \__cmd_normalize_arg_spec_loop:n
614 }
615 \cs_new_protected:Npn \__cmd_normalize_E_unique_check:w #1#2 \q_stop
616 {
617   \quark_if_nil:NF #1
618   {
619     \tl_if_in:nnT {#2} {#1} { \__cmd_bad_arg_spec:wn }
620     \__cmd_normalize_E_unique_check:w #2 \q_stop
621   }
622 }
623 \cs_new_protected:Npn \__cmd_normalize_type_t:w #1
624 {
625   \quark_if_recursion_tail_stop_do:Nn #1 { \__cmd_bad_arg_spec:wn }
626   \__cmd_single_token_check:n {#1} \__cmd_allowed_token_check:N #1
627   \tl_put_right:Nx \l__cmd_arg_spec_tl
628     {
629       \bool_if:NT \l__cmd_obey_spaces_bool { ! }
630       t \exp_not:n {#1}
631     }
632   \tl_put_right:Nn \l__cmd_last_delimiters_tl {#1}
633   \bool_set_false:N \l__cmd_grab_expandably_bool
634   \bool_set_false:N \l__cmd_obey_spaces_bool

```

```

635     \bool_set_false:N \l__cmd_long_bool
636     \__cmd_normalize_arg_spec_loop:n
637 }

```

(End of definition for \\_\_cmd\_normalize\_type\_D:w and others.)

\\_\_cmd\_normalize\_type\_m:w Mandatory arguments. First check the required data is present, consists of single characters where applicable, and that the argument type is allowed for expandable commands if applicable. For the m and R argument types check that they do not follow some optional argument with that delimiter as otherwise the optional argument could not be omitted. Then save data in \l\_\_cmd\_arg\_spec\_tl, count the mandatory argument, and empty the list of last delimiters.

```

638 \cs_new_protected:Npn \__cmd_normalize_type_m:w
639 {
640     \__cmd_delimiter_check:nnn { } { m } { \iow_char:N \{ }
641     \__cmd_add_arg_spec_mandatory:n { m }
642     \__cmd_normalize_arg_spec_loop:n
643 }
644 \cs_new_protected:Npn \__cmd_normalize_type_R:w #1#2#3
645 {
646     \quark_if_recursion_tail_stop_do:nn {#3} { \__cmd_bad_arg_spec:wn }
647     \__cmd_single_token_check:n {#1} \__cmd_allowed_token_check:N #1
648     \__cmd_single_token_check:n {#2}
649     \__cmd_delimiter_check:nnn {#1} { R/r } { \tl_to_str:n {#1} }
650     \bool_set_false:N \l__cmd_grab_expandably_bool
651     \__cmd_add_arg_spec_mandatory:n { R #1 #2 {#3} }
652     \__cmd_normalize_arg_spec_loop:n
653 }
654 \cs_new_protected:Npn \__cmd_normalize_type_v:w
655 {
656     \__cmd_normalize_check_gv:N v
657     \__cmd_add_arg_spec_mandatory:n { v }
658     \__cmd_normalize_arg_spec_loop:n
659 }

```

(End of definition for \\_\_cmd\_normalize\_type\_m:w, \\_\_cmd\_normalize\_type\_R:w, and \\_\_cmd\_normalize\_type\_v:w.)

\\_\_cmd\_normalize\_type\_b:w These argument types are not allowed for commands. They are only allowed at the end of the argument specification, hence we check that #1 is the end.

```

\__cmd_normalize_type_c:w
\__cmd_normalize_type_b_or_c:nn
660 \cs_new_protected:Npn \__cmd_normalize_type_b:w #1
661 { \__cmd_normalize_type_b_or_c:nn {#1} { b } }
662 \cs_new_protected:Npn \__cmd_normalize_type_c:w #1
663 { \__cmd_normalize_type_b_or_c:nn {#1} { c } }
664 \cs_new_protected:Npn \__cmd_normalize_type_b_or_c:nn #1#2
665 {
666     \bool_if:NF \l__cmd_environment_bool
667     {
668         \msg_error:nnxx { cmd } { invalid-command-arg }
669         { \__cmd_environment_or_command: } {#2}
670         \__cmd_bad_def:wn
671     }
672     \tl_clear:N \l__cmd_last_delimiters_tl
673     \__cmd_add_arg_spec:n {#2}

```

```

674 \quark_if_recursion_tail_stop:n {#1}
675 \msg_error:nnxxx { cmd } { arg-after-body }
676 {#2}
677 { \__cmd_environment_or_command: }
678 { \tl_to_str:n {#1} }
679 \__cmd_bad_def:wn
680 }

(End of definition for \__cmd_normalize_type_b:w, \__cmd_normalize_type_c:w, and
 \__cmd_normalize_type_b_or_c:nn.)

```

`\__cmd_single_token_check:n` Checks that the argument is a single (non-space) token (possibly surrounded by spaces), and aborts the definition otherwise.

```

681 \cs_new_protected:Npn \__cmd_single_token_check:n #1
682 {
683   \tl_trim_spaces_apply:nN {#1} \tl_if_single_token:nF
684   {
685     \msg_error:nnxx { cmd } { not-single-token }
686     { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
687     \__cmd_bad_def:wn
688   }
689 }

(End of definition for \__cmd_single_token_check:n.)

```

`\__cmd_allowed_token_check:N` Some tokens are not allowed as delimiters for some argument types, notably implicit begin/end-group tokens (`\bgroup`/`\egroup`). The major problem with these tokens is that for `\peek_...` functions, a literal `{`<sub>1</sub> is virtually indistinguishable from a `\bgroup` or other token which was `\let` to a `{`<sub>1</sub>, and the same goes for `}`<sub>2</sub>. All other tokens can be easily distinguished from their implicit counterparts by grabbing them and looking at the string length (see `\__cmd_token_if_cs:NTF`), but for begin/end group tokens that is not possible without the risk of mistakenly grabbing the entire brace group (potentially leading to a ! Runaway argument error) or trying to grab a `}`<sub>2</sub>, leading to an ! Argument of `\dots` has an extra `}` error.

```

690 \cs_new_protected:Npn \__cmd_allowed_token_check:N #1
691 {
692   \token_if_eq_meaning:NNTF #1 \c_group_begin_token
693   { \use:n }
694   {
695     \token_if_eq_meaning:NNTF #1 \c_group_end_token
696     { \use:n }
697     { \use_none:n }
698   }
699   {
700     \msg_error:nnxxx { cmd } { forbidden-group-token }
701     { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
702     {
703       \token_if_eq_meaning:NNTF #1 \c_group_begin_token
704       { begin } { end }
705     }
706     \__cmd_bad_def:wn
707   }
708 }

```

(End of definition for \\_cmd\_allowed\_token\_check:N.)

\\_cmd\_normalize\_check\_gv:N Called for arguments that are always forbidden, or forbidden after an optional argument,  
\\_cmd\_normalize\_check\_lu:N for expandable commands.

```

709 \cs_new_protected:Npn \_cmd_normalize_check_gv:N #1
710 {
711   \bool_if:NT \l__cmd_expandable_bool
712   {
713     \msg_error:nnxx { cmd } { invalid-expandable-arg }
714     { \iow_char:N \ \ \l__cmd_function_tl } { \tl_to_str:n {#1} }
715     \_cmd_bad_def:wn
716   }
717   \bool_set_false:N \l__cmd_grab_expandably_bool
718 }
719 \cs_new_protected:Npn \_cmd_normalize_check_lu:N #1
720 {
721   \bool_if:NT \l__cmd_expandable_bool
722   {
723     \tl_if_empty:NF \l__cmd_last_delimiters_tl
724     {
725       \msg_error:nnxx { cmd } { invalid-after-optional-expandably }
726       { \iow_char:N \ \ \l__cmd_function_tl } { \tl_to_str:n {#1} }
727       \_cmd_bad_def:wn
728     }
729   }
730 }
```

(End of definition for \\_cmd\_normalize\_check\_gv:N and \\_cmd\_normalize\_check\_lu:N.)

\\_cmd\_delimiter\_check:nnn Called for m and R arguments. Checks that the leading token does not coincide with the token denoting the presence of a previous optional argument. Instead of dealing with braces for the m-type we use an empty delimiter to denote that case.

```

731 \cs_new_protected:Npn \_cmd_delimiter_check:nnn #1#2#3
732 {
733   \tl_map_inline:Nn \l__cmd_last_delimiters_tl
734   {
735     \tl_if_eq:nnT {##1} {#1}
736     {
737       \msg_warning:nnxx { cmd } { optional-mandatory }
738       {#2} {#3}
739     }
740   }
741 }
```

(End of definition for \\_cmd\_delimiter\_check:nnn.)

\\_cmd\_bad\_arg\_spec:wn If the argument specification is wrong, this provides an escape from the entire definition process.  
\\_cmd\_bad\_def:wn

```

742 \cs_new_protected:Npn \_cmd_bad_arg_spec:wn #1 \_cmd_break_point:n #2
743 {
744   \msg_error:nnxx { cmd } { bad-arg-spec }
745   { \_cmd_environment_or_command: } { \tl_to_str:n {#2} }
746 }
747 \cs_new_protected:Npn \_cmd_bad_def:wn #1 \_cmd_break_point:n #2 { }
```

(End of definition for `\__cmd_bad_arg_spec:wn` and `\__cmd_bad_def:wn`.)

`\__cmd_add_arg_spec:n` When adding an argument to the argument specification, set the `some_long` or `some_short` booleans as appropriate and clear the booleans keeping track of +, ! and = markers. Before that, test for a short argument following some long arguments: this is forbidden for expandable commands and prevents grabbing arguments expandably.

For mandatory arguments do some more work, in particular complain if they were preceded by !.

```

748 \cs_new_protected:Npn \__cmd_add_arg_spec:n #1
749 {
750   \bool_lazy_and:nnT
751     { ! \l__cmd_long_bool }
752     { \l__cmd_some_long_bool }
753   {
754     \bool_if:NT \l__cmd_expandable_bool
755     {
756       \msg_error:nnx { cmd } { long-short-mix }
757       { \iow_char:N \ \ \l__cmd_function_tl }
758       \__cmd_bad_def:wn
759     }
760     \bool_set_false:N \l__cmd_grab_expandably_bool
761   }
762   \bool_if:NTF \l__cmd_long_bool
763     { \bool_set_true:N \l__cmd_some_long_bool }
764     { \bool_set_true:N \l__cmd_some_short_bool }
765   \tl_put_right:Nx \l__cmd_arg_spec_tl
766   {
767     \bool_lazy_and:nnT
768       { \l__cmd_long_bool }
769       { ! \str_if_eq_p:nn {#1} { c } }
770     { + }
771     \bool_if:NT \l__cmd_obey_spaces_bool { ! }
772     \exp_not:n {#1}
773   }
774   \bool_set_false:N \l__cmd_long_bool
775   \bool_set_false:N \l__cmd_obey_spaces_bool
776 }
777 \cs_new_protected:Npn \__cmd_add_arg_spec_mandatory:n #1
778 {
779   \bool_if:NT \l__cmd_some_obey_spaces_bool
780   {
781     \msg_error:nnxx { cmd } { invalid-bang }
782     { \__cmd_environment_or_command: }
783     {
784       \bool_if:NTF \l__cmd_obey_spaces_bool
785         { \tl_to_str:n {'#1'} }
786         { an~optional~argument~before~mandatory~ \tl_to_str:n {'#1'} }
787     }
788     \__cmd_bad_def:wn
789   }
790   \tl_clear:N \l__cmd_last_delimiters_tl
791   \int_set_eq:NN \l__cmd_last_mandatory_arg_int \l__cmd_current_arg_int
792   \__cmd_add_arg_spec:n {#1}
793 }

```

(End of definition for `\__cmd_add_arg_spec:n` and `\__cmd_add_arg_spec_mandatory:n`.)

## 1.5 Preparing the signature: general mechanism

```
\__cmd_prepare_signature:n
  \__cmd_prepare_signature_verb_chk:n
\__cmd_prepare_signature:N
  \__cmd_prepare_signature_bypass:N
```

Actually creating the signature uses the same loop approach as normalizing the signature. There are first a number of variables which need to be set to track what is going on. Many of these variables are unused when defining expandable commands.

```
794 \cs_new_protected:Npn \__cmd_prepare_signature:n #1
795 {
796   \int_set_eq:NN \l__cmd_total_args_int \l__cmd_current_arg_int
797   \int_zero:N \l__cmd_current_arg_int
798   \bool_set_false:N \l__cmd_long_bool
799   \bool_set_false:N \l__cmd_obey_spaces_bool
800   \bool_set_false:N \l__cmd_suppress_strip_bool
801   \int_zero:N \l__cmd_m_args_int
802   \bool_set_false:N \l__cmd_defaults_bool
803   \tl_clear:N \l__cmd_defaults_tl
804   \tl_clear:N \l__cmd_process_all_tl
805   \tl_clear:N \l__cmd_process_one_tl
806   \bool_set_false:N \l__cmd_process_some_bool
807   \tl_clear:N \l__cmd_signature_tl
808   \__cmd_prepare_signature_verb_chk:n {#1}
809   \__cmd_prepare_signature:N #1 \q_recursion_tail \q_recursion_stop
810   \bool_if:NF \l__cmd_expandable_bool { \__cmd_flush_m_args: }
811 }
```

A quick check on the final arg. type.

```
812 \cs_new_protected:Npn \__cmd_prepare_signature_verb_chk:n #1
813 {
814   \str_if_eq:eeTF { \tl_head:e { \tl_reverse:n {#1} } } { c }
815   { \bool_set_true:N \l__cmd_final_verb_bool }
816   { \bool_set_false:N \l__cmd_final_verb_bool }
817 }
```

The main looping function does not take an argument, but carries out the reset on the processor boolean. This is split off from the rest of the process so that when actually setting up processors the flag-reset can be bypassed.

For each known argument type there is an appropriate function to actually do the addition to the signature. These are separate for expandable and standard functions, as the approaches are different.

```
818 \cs_new_protected:Npn \__cmd_prepare_signature:N
819 {
820   \bool_set_false:N \l__cmd_prefixed_bool
821   \__cmd_prepare_signature_bypass:N
822 }
823 \cs_new_protected:Npn \__cmd_prepare_signature_bypass:N #1
824 {
825   \quark_if_recursion_tail_stop:N #1
826   \use:c
827   {
828     __cmd_add
829     \bool_if:NT \l__cmd_grab_expandably_bool { _expandable }
830     _type_ \token_to_str:N #1 :w
831   }
```

```
832 }
```

(End of definition for `\__cmd_prepare_signature:n` and others.)

## 1.6 Setting up a standard signature

Each argument-adding function appends to the signature a grabber (and for some types, the delimiters or default value), except the one for `m` arguments. These are collected and added to the signature all at once by `\__cmd_flush_m_args:`, called for every other argument type. All of the functions then call the loop function `\__cmd_prepare_signature:N`. Default values of arguments are collected by `\__cmd_add_default:n` rather than being stored with the argument; this function and `\__cmd_add_default:` are also responsible for keeping track of `\l__cmd_current_arg_int`.

`\__cmd_add_type+:w` Making the next argument long means setting the flag. The `m` arguments are recorded here as this has to be done for every case where there is then a long argument.

```
833 \cs_new_protected:cpn { __cmd_add_type+:w }
834 {
835   \__cmd_flush_m_args:
836   \bool_set_true:N \l__cmd_long_bool
837   \bool_set_true:N \l__cmd_prefixed_bool
838   \__cmd_prepare_signature_bypass:N
839 }
```

(End of definition for `\__cmd_add_type+:w`.)

`\__cmd_add_type_!:w` Much the same for controlling trailing optional arguments.

```
840 \cs_new_protected:cpn { __cmd_add_type_!:w }
841 {
842   \__cmd_flush_m_args:
843   \bool_set_true:N \l__cmd_obey_spaces_bool
844   \bool_set_true:N \l__cmd_prefixed_bool
845   \__cmd_prepare_signature_bypass:N
846 }
```

(End of definition for `\__cmd_add_type_!:w`.)

`\__cmd_add_type_>:w` When a processor is found, the processor code is stored. It will be used by `\__cmd_args_process:` once arguments are all found. Here too the loop calls `\__cmd_prepare_signature_bypass:N` rather than `\__cmd_prepare_signature:N` so that the flag is not reset.

```
847 \cs_new_protected:cpn { __cmd_add_type_>:w } #1
848 {
849   \__cmd_flush_m_args:
850   \bool_set_true:N \l__cmd_prefixed_bool
851   \bool_set_true:N \l__cmd_process_some_bool
852   \tl_put_left:Nn \l__cmd_process_one_tl { {#1} }
853   \__cmd_prepare_signature_bypass:N
854 }
```

(End of definition for `\__cmd_add_type_>:w`.)

`\__cmd_add_type_=:w` A mix of the ideas from above: set a flag and add a processor.

```

855 \cs_new_protected:cpn { __cmd_add_type_=:w } #1
856 {
857   \__cmd_flush_m_args:
858   \bool_set_true:N \l__cmd_prefixed_bool
859   \bool_set_true:N \l__cmd_suppress_strip_bool
860   \bool_set_true:N \l__cmd_process_some_bool
861   \tl_put_left:Nn \l__cmd_process_one_tl
862     { { \__cmd_arg_to_keyvalue:nn {#1} } }
863   \__cmd_prepare_signature_bypass:N
864 }

```

*(End of definition for \\_\_cmd\_add\_type\_=:w.)*

```

\__cmd_add_type_b:w
\__cmd_add_type_c:w
\__cmd_add_type_b_or_c:N
865 \cs_new_protected:Npn \__cmd_add_type_b:w
866 { \__cmd_add_type_b_or_c:N b }
867 \cs_new_protected:Npn \__cmd_add_type_c:w
868 { \__cmd_add_type_b_or_c:N c }
869 \cs_new_protected:Npn \__cmd_add_type_b_or_c:N #1
870 {
871   \__cmd_flush_m_args:
872   \__cmd_add_default:
873   \__cmd_add_grabber:N #1
874   \__cmd_prepare_signature:N
875 }

```

*(End of definition for \\_\_cmd\_add\_type\_b:w, \\_\_cmd\_add\_type\_c:w, and \\_\_cmd\_add\_type\_b\_or\_c:N.)*

```

\__cmd_add_type_D:w
876 \cs_new_protected:Npn \__cmd_add_type_D:w #1#2#3
877 {
878   \__cmd_flush_m_args:
879   \__cmd_add_default:n {#3}
880   \__cmd_add_grabber:N D
881   \tl_put_right:Nn \l__cmd_signature_tl { #1 #2 }
882   \__cmd_prepare_signature:N
883 }

```

*(End of definition for \\_\_cmd\_add\_type\_D:w.)*

`\__cmd_add_type_E:w` The E-type argument needs a special handling of default values. Since each embellishment is a separate argument, it also needs to replicate the argument processors for each embellishment argument so that the numbers of arguments and processors remain in sync.

```

884 \cs_new_protected:Npn \__cmd_add_type_E:w #1#2
885 {
886   \__cmd_flush_m_args:
887   \__cmd_add_default_E:nn {#1} {#2}
888   \use:x
889   {
890     \__cmd_replicate_processor:nn { \tl_count:n {#1} }
891     { \exp_not:o \l__cmd_process_one_tl }
892   }

```

```

893 \__cmd_add_grabber:N E
894 \tl_put_right:Nn \l__cmd_signature_tl { {#1} }
895 \__cmd_prepare_signature:N
896 }

```

(End of definition for \\_\_cmd\_add\_type\_E:w.)

\\_\_cmd\_replicate\_processor:nn In the command's argument processor signature (the final argument of \\_\_cmd\_start:nnNnnn) there is one braced item for each formal argument (up to nine), and in each of these items there is one braced item for each processor (as many as there were processors declared for a given argument). Something like this:

```

{ % argument processors
  { % argument 1
    { processor 1 } { processor 2 } ... { processor n }
  } % end argument 1
  { ... } % argument 2
  :
  { ... } % argument n
} % end argument processors

```

The function \\_\_cmd\_add\_grabber:N adds one single grabber for an argument, and adds the braced item for that one argument. However, in an E-type argument each embellishment requires its own formal argument, so we need to break out of one layer of braces in \l\_\_cmd\_process\_one\_tl, add copies of the processor as necessary, and then return the removed brace. The function below does just that: it defines \l\_\_cmd\_process\_one\_tl starting with a }<sub>2</sub> and ending with a {<sub>1</sub>, so that it adds as many processors as needed when x-expanded.

```

897 \cs_new_protected:Npn \__cmd_replicate_processor:nn #1 #2
898 {
899   \int_compare:nNnF {#1} > { 1 } { \use_none:nnn }
900   \tl_set:Nx \l__cmd_process_one_tl
901   {
902     \exp_not:n { \exp_not:n {#2} \if_false: { \fi: } }
903     \prg_replicate:nn { #1 - 2 }
904     { \exp_not:n { \exp_not:n { {#2} } } }
905     \exp_not:n { { \if_false: } \fi: \exp_not:n {#2} }
906   }
907 }

```

(End of definition for \\_\_cmd\_replicate\_processor:nn.)

\\_\_cmd\_add\_type\_m:w The m type is special as short arguments which are not post-processed are simply counted at this stage. Thus there is a check to see if either of these cases apply. If so, a one-argument grabber is added to the signature. On the other hand, if a standard short argument is required it is simply counted at this stage, to be added later using \\_\_cmd\_flush\_m\_args:.

```

908 \cs_new_protected:Npn \__cmd_add_type_m:w
909 {
910   \__cmd_add_default:

```

```

911     \bool_if:NTF \l__cmd_prefixed_bool
912     { \__cmd_add_grabber:N m }
913     { \int_incr:N \l__cmd_m_args_int }
914     \__cmd_prepare_signature:N
915 }

```

*(End of definition for \\_\_cmd\_add\_type\_m:w.)*

`\__cmd_add_type_R:w` The R-type argument is very similar to the D-type.

```

916 \cs_new_protected:Npn \__cmd_add_type_R:w #1#2#3
917 {
918     \__cmd_flush_m_args:
919     \__cmd_add_default:n {#3}
920     \__cmd_add_grabber:N R
921     \tl_put_right:Nn \l__cmd_signature_tl { #1 #2 }
922     \__cmd_prepare_signature:N
923 }

```

*(End of definition for \\_\_cmd\_add\_type\_R:w.)*

`\__cmd_add_type_t:w` Setting up a t argument means collecting one token for the test, and adding it along with the grabber to the signature.

```

924 \cs_new_protected:Npn \__cmd_add_type_t:w #1
925 {
926     \__cmd_flush_m_args:
927     \__cmd_add_default:
928     \__cmd_add_grabber:N t
929     \tl_put_right:Nn \l__cmd_signature_tl {#1}
930     \__cmd_prepare_signature:N
931 }

```

*(End of definition for \\_\_cmd\_add\_type\_t:w.)*

`\__cmd_add_type_v:w` At this stage, the v argument is identical to l except that since the grabber may fail to read a verbatim argument we need a default value.

```

932 \cs_new_protected:Npn \__cmd_add_type_v:w
933 {
934     \__cmd_flush_m_args:
935     \exp_args:No \__cmd_add_default:n \c_novalue_tl
936     \__cmd_add_grabber:N v
937     \__cmd_prepare_signature:N
938 }

```

*(End of definition for \\_\_cmd\_add\_type\_v:w.)*

`\__cmd_flush_m_args:` As m arguments are simply counted, there is a need to add them to the token register in a block. As this function can only be called if something other than m turns up, the flag can be switched here.

```

939 \cs_new_protected:Npn \__cmd_flush_m_args:
940 {
941     \int_compare:nNnT \l__cmd_m_args_int > 0
942     {
943         \tl_put_right:Nx \l__cmd_signature_tl
944         { \exp_not:c { __cmd_grab_m_ \int_use:N \l__cmd_m_args_int :w } }
945         \tl_put_right:Nx \l__cmd_process_all_tl

```

```

946         { \prg_replicate:nn { \l__cmd_m_args_int } { { } } }
947     }
948     \int_zero:N \l__cmd_m_args_int
949 }

```

*(End of definition for \\_\_cmd\_flush\_m\_args:.)*

`\__cmd_add_grabber:N` To keep the various checks needed in one place, adding the grabber to the signature is done here. The only questions are whether the grabber should be long or not, and whether to obey spaces. The `\l__cmd_obey_spaces_bool` boolean can only be `true` for trailing optional arguments. In that case spaces will not be ignored when looking for that optional argument.

```

950 \cs_new_protected:Npn \__cmd_add_grabber:N #1
951 {
952     \tl_put_right:Nx \l__cmd_signature_tl
953     {
954         \exp_not:c
955         {
956             __cmd_grab_ #1
957             \bool_if:NT \l__cmd_long_bool { _long }
958             \bool_if:NT \l__cmd_obey_spaces_bool { _obey_spaces }
959             \bool_lazy_and:nnT
960             { \l__cmd_suppress_strip_bool }
961             { \str_if_eq_p:nn {#1} { D } }
962             { _no_strip }
963             \bool_lazy_all:nT
964             {
965                 { \l__cmd_final_verb_bool }
966                 { \str_if_eq_p:nn {#1} { D } }
967                 {
968                     \int_compare_p:nNn \l__cmd_current_arg_int
969                     > \l__cmd_last_mandatory_arg_int
970                 }
971             }
972             { _verb_safe }
973             :w
974         }
975     }
976     \bool_set_false:N \l__cmd_long_bool
977     \bool_set_false:N \l__cmd_obey_spaces_bool
978     \bool_set_false:N \l__cmd_suppress_strip_bool
979     \bool_set_false:N \l__cmd_verb_safe_bool
980     \tl_put_right:Nx \l__cmd_process_all_tl
981     {
982         {
983             \if_charcode:w E #1 \use_i:nn \fi:
984             \exp_not:o \l__cmd_process_one_tl
985         }
986     }
987     \tl_clear:N \l__cmd_process_one_tl
988 }

```

*(End of definition for \\_\_cmd\_add\_grabber:N.)*

`\__cmd_add_default:n` Store the default value of an argument, or rather code that gives that default value (it may involve other arguments). This is `\c_novalue_tl` for arguments with no actual default or with default `-NoValue-`; and (in a brace group) `\prg_do_nothing:` followed by a default value for others. For E-type arguments, pad the defaults #2 with some `\c_novalue_tl` until there are as many as embellishments #1. These functions are also used when defining expandable commands.

```

989 \cs_new_protected:Npn \__cmd_add_default:n #1
990 {
991   \tl_if_novalue:nTF {#1}
992     { \__cmd_add_default: }
993     {
994       \int_incr:N \l__cmd_current_arg_int
995       \bool_set_true:N \l__cmd_defaults_bool
996       \tl_put_right:Nn \l__cmd_defaults_tl { { \prg_do_nothing: #1 } }
997     }
998   }
999 \cs_new_protected:Npn \__cmd_add_default:
1000 {
1001   \int_incr:N \l__cmd_current_arg_int
1002   \tl_put_right:Nn \l__cmd_defaults_tl { \c_novalue_tl }
1003 }
1004 \cs_new_protected:Npn \__cmd_add_default_E:nn #1#2
1005 {
1006   \tl_map_function:nN {#2} \__cmd_add_default:n
1007   \prg_replicate:nn
1008     { \tl_count:n {#1} - \tl_count:n {#2} }
1009     { \__cmd_add_default: }
1010 }

```

(End of definition for `\__cmd_add_default:n`, `\__cmd_add_default:`, and `\__cmd_add_default_E:nn`.)

## 1.7 Setting up expandable types

The approach here is not dissimilar to that for standard types, but fewer types are supported. There is also a need to define the per-function auxiliaries: this is done here, while the general grabbers are dealt with later.

`\__cmd_add_expandable_type_+:w` We have already checked that short arguments are before long arguments, so `\l__cmd_long_bool` only changes from `false` to `true` once (and there is no need to reset it after each argument). Continue the loop.

```

1011 \cs_new_protected:cpn { __cmd_add_expandable_type_+:w }
1012 {
1013   \bool_set_true:N \l__cmd_long_bool
1014   \__cmd_prepare_signature:N
1015 }

```

(End of definition for `\__cmd_add_expandable_type_+:w`.)

`\__cmd_add_expandable_type_D:w` The set up for D-type arguments involves constructing a rather complex auxiliary which is used repeatedly when grabbing. There is an auxiliary here so that the R-type can share code readily: #1 is D or R. The `_aux:NN` auxiliary is needed if the two delimiting tokens are identical: in contrast to the non-expandable route, the grabber here has to act differently for this case.

```

1016 \cs_new_protected:Npn \__cmd_add_expandable_type_D:w
1017   { \__cmd_add_expandable_type_D_aux:NNNn D }
1018 \cs_new_protected:Npn \__cmd_add_expandable_type_D_aux:NNNn #1#2#3#4
1019   {
1020     \__cmd_add_default:n {#4}
1021     \tl_if_eq:nnTF {#2} {#3}
1022       { \__cmd_add_expandable_type_D_aux:NN #1 #2 }
1023       { \__cmd_add_expandable_type_D_aux:NNN #1 #2 #3 }
1024     \__cmd_prepare_signature:N
1025   }
1026 \cs_new_protected:Npn \__cmd_add_expandable_type_D_aux:NNN #1#2#3
1027   {
1028     \bool_if:NTF \l__cmd_long_bool
1029       { \cs_set:cpx }
1030       { \cs_set_nopar:cpx }
1031     { \l__cmd_expandable_aux_name_tl } ##1 ##2 #2 ##3 \q__cmd ##4 #3
1032     { ##1 {##2} {##3} {##4} }
1033     \__cmd_add_expandable_grabber:nn {#1}
1034     {
1035       \exp_not:c { \l__cmd_expandable_aux_name_tl }
1036       \exp_not:n { #2 #3 }
1037     }
1038   }
1039 \cs_new_protected:Npn \__cmd_add_expandable_type_D_aux:NN #1#2
1040   {
1041     \bool_if:NTF \l__cmd_long_bool
1042       { \cs_set:cpx }
1043       { \cs_set_nopar:cpx }
1044     { \l__cmd_expandable_aux_name_tl } ##1 #2 ##2 #2
1045     { ##1 {##2} }
1046     \__cmd_add_expandable_grabber:nn { #1_alt }
1047     {
1048       \exp_not:c { \l__cmd_expandable_aux_name_tl }
1049       \exp_not:n {#2}
1050     }
1051   }

```

(End of definition for \\_\_cmd\_add\_expandable\_type\_D:w and others.)

\\_\_cmd\_add\_expandable\_type\_E:w  
 \\_\_cmd\_add\_expandable\_type\_E\_aux:n

For each embellishment, use \\_\_cmd\_get\_grabber:NN to obtain an auxiliary delimited by that token and store a pair constituted of the auxiliary and the token in \l\_\_cmd\_tmpb\_tl, before appending the whole set of these pairs to the signature, and an equal number of -NoValue- markers (regardless of the default values of arguments). Set the current argument appropriately.

```

1052 \cs_new_protected:Npn \__cmd_add_expandable_type_E:w #1#2
1053   {
1054     \__cmd_add_default_E:nn {#1} {#2}
1055     \tl_clear:N \l__cmd_tmpb_tl
1056     \tl_map_function:nn {#1} \__cmd_add_expandable_type_E_aux:n
1057     \__cmd_add_expandable_grabber:nn
1058       { E \bool_if:NT \l__cmd_long_bool { _long } }
1059     {
1060       { \exp_not:o \l__cmd_tmpb_tl }
1061       {

```

```

1062         \prg_replicate:nn { \tl_count:n {#1} }
1063         { { \c_novalue_tl } }
1064     }
1065 }
1066 \__cmd_prepare_signature:N
1067 }
1068 \cs_new_protected:Npn \__cmd_add_expandable_type_E_aux:n #1
1069 {
1070     \__cmd_get_grabber:NN #1 \l__cmd_tmpa_tl
1071     \tl_put_right:Nx \l__cmd_tmpb_tl
1072     { \exp_not:o \l__cmd_tmpa_tl \exp_not:N #1 }
1073 }

```

(End of definition for \\_\_cmd\_add\_expandable\_type\_E:w and \\_\_cmd\_add\_expandable\_type\_E\_aux:n.)

\\_\_cmd\_add\_expandable\_type\_m:w Unlike the standard case, when working expandably each argument is always grabbed separately.

```

1074 \cs_new_protected:Npn \__cmd_add_expandable_type_m:w
1075 {
1076     \__cmd_add_default:
1077     \__cmd_add_expandable_grabber:nn
1078     { m \bool_if:NT \l__cmd_long_bool { _long } } { }
1079     \__cmd_prepare_signature:N
1080 }

```

(End of definition for \\_\_cmd\_add\_expandable\_type\_m:w.)

\\_\_cmd\_add\_expandable\_type\_R:w The R-type is very similar to the D-type argument, and so the same internals are used.

```

1081 \cs_new_protected:Npn \__cmd_add_expandable_type_R:w
1082 { \__cmd_add_expandable_type_D_aux:NNNn R }

```

(End of definition for \\_\_cmd\_add\_expandable\_type\_R:w.)

\\_\_cmd\_add\_expandable\_type\_t:w An auxiliary delimited by #1 is built now. It will be used to test for the presence of that token.

```

1083 \cs_new_protected:Npn \__cmd_add_expandable_type_t:w #1
1084 {
1085     \__cmd_add_default:
1086     \__cmd_get_grabber:NN #1 \l__cmd_tmpa_tl
1087     \__cmd_add_expandable_grabber:nn { t }
1088     {
1089         \exp_not:o \l__cmd_tmpa_tl
1090         \exp_not:N #1
1091     }
1092     \__cmd_prepare_signature:N
1093 }

```

(End of definition for \\_\_cmd\_add\_expandable\_type\_t:w.)

\\_\_cmd\_add\_expandable\_grabber:nn This is called for all arguments to place the right grabber in the signature.

```

1094 \cs_new_protected:Npn \__cmd_add_expandable_grabber:nn #1#2
1095 {
1096     \tl_put_right:Nx \l__cmd_signature_tl
1097     { \exp_not:c { __cmd_expandable_grab_ #1 :w } #2 }
1098 }

```

(End of definition for `\__cmd_add_expandable_grabber:nn`.)

`\__cmd_get_grabber:NN`  
`\__cmd_get_grabber_auxi:NN`  
`\__cmd_get_grabber_auxii:NN`

Given a token #1, defines an expandable function delimited by that token and stores it in the token list #2. The function is named after the token, unless that function name is already taken by some other grabber (this can happen in the rare case where delimiters with different category codes are used in the same document): in that case use a global counter to get a unique name. Since the grabbers are not named after `xparse` commands they should not be used to get material from the input stream.

```

1099 \cs_new_protected:Npn \__cmd_get_grabber:NN #1#2
1100 {
1101   \cs_set:Npn \__cmd_tmp:w ##1 #1 {##1}
1102   \exp_args:Nc \__cmd_get_grabber_auxi:NN
1103     { \__cmd_grabber_ \token_to_str:N #1 :w } #2
1104 }
1105 \cs_new_protected:Npn \__cmd_get_grabber_auxi:NN #1#2
1106 {
1107   \cs_if_eq:NNTF \__cmd_tmp:w #1
1108     { \tl_set:Nn #2 {#1} }
1109     {
1110       \cs_if_exist:NTF #1
1111         {
1112           \int_gincr:N \g__cmd_grabber_int
1113           \exp_args:Nc \__cmd_get_grabber_auxi:NN
1114             {
1115               \__cmd_grabber_
1116               - \int_use:N \g__cmd_grabber_int :w
1117             }
1118           #2
1119         }
1120         { \__cmd_get_grabber_auxii:NN #1 #2 }
1121       }
1122 }
1123 \cs_new_protected:Npn \__cmd_get_grabber_auxii:NN #1#2
1124 {
1125   \cs_set_eq:NN #1 \__cmd_tmp:w
1126   \tl_set:Nn #2 {#1}
1127 }

```

(End of definition for `\__cmd_get_grabber:NN`, `\__cmd_get_grabber_auxi:NN`, and `\__cmd_get_grabber_auxii:NN`.)

### 1.7.1 Copying a command and its internal structure

```

1128 <latexrelease>\IncludeInRelease{2021/11/15}{\__cmd_copy:NN}%
1129 <latexrelease> {Support~\NewCommandCopy~in~ltxcmd}

```

Since the 2020-10-01 L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> release, support for copying, and showing the definition of, robust commands has been available, but the specifics of each command are implemented separately. Here we'll add support for copying and showing `ltxcmd` definitions.

To fully support copying, we need two commands: a conditional to test if a command is in fact a `ltxcmd` command, and another command to actually copy the command. The conditional is defined later as `\__kernel_cmd_if_xparse:NTF`, so now to the copying:

`\__cmd_copy:NN` This macro just branches to the proper copying command by using `\__cmd_cmd_type_cases:NnnnnnF`. The copying command takes the names of the commands to be copied to and from, and the actual commands as its four arguments.

```

1130 \cs_new_protected:Npn \__cmd_copy:NN #1 #2
1131 {
1132   \use:x
1133   {
1134     \int_set:Nn \tex_escapechar:D { 92 }
1135     \exp_not:N \__cmd_cmd_type_cases:NnnnnnF \exp_not:N #2
1136     { \__cmd_copy_command:nnNN }
1137     { \__cmd_copy_expandable:nnNN }
1138     { \__cmd_copy_optimized:nnNN }
1139     { \__cmd_copy_environment:nnNN }
1140     { \__cmd_copy_environment_end:nnNN }
1141     { \__cmd_cant_copy:nwn { non-ltcmd } }
1142     { \cs_to_str:N #1 } { \cs_to_str:N #2 }
1143     \exp_not:N #1 \exp_not:N #2
1144     \exp_not:N \__cmd_break_point:n { \cs_to_str:N #2 }
1145     \int_set:Nn \tex_escapechar:D { \int_use:N \tex_escapechar:D }
1146   }
1147 }
1148 \cs_new_protected:Npn \__cmd_set_eq_if_exist:NN #1 #2
1149 { \cs_if_exist:NTF #2 { \cs_set_eq:NN } { \use_none:nn } #1 #2 }
1150 \cs_generate_variant:Nn \__cmd_set_eq_if_exist:NN { cc }

```

An utility macro similar to `\__cmd_bad_def:wn` to abort a command copy. Contrary to `\__cmd_bad_def:wn` though, when this happens the issue is most likely internal, because the command was already (supposedly) correctly defined so it should be copyable. Hopefully this macro will never be used ever, but if it does, apologise and give the reason for the failure so the user can report.

```

1151 \cs_new_protected:Npn \__cmd_cant_copy:nwn #1 #2 \__cmd_break_point:n #3
1152 { \msg_error:nnnn { cmd } { copy-bug } {#1} {#3} }
1153 \msg_new:nnn { cmd } { copy-bug }
1154 {
1155   Error-while-copying-command-\iow_char:N\#2:\
1156   \str_case:nn {#1}
1157   {
1158     { non-ltcmd } { Command-is-not-a-valid-ltcmd-command. }
1159     { unknown-type } { Found-an-unknown-argument-type. }
1160     { invalid-end }
1161     { Target-command-is-not-named-\iow_char:N \end<name>. }
1162   }
1163 }

```

And, of course, add `\__kernel_cmd_if_xparse:NTF` and `\__cmd_copy:NN` to `\@declarecommandcopylisthook`:

```

1164 \tl_gput_right:Nn \@declarecommandcopylisthook
1165 { { \__kernel_cmd_if_xparse:NTF \__cmd_copy:NN } }

```

(End of definition for `\__cmd_copy:NN`, `\__cmd_set_eq_if_exist:NN`, and `\__cmd_cant_copy:nwn`.)

`\__cmd_copy_command:nnNN` A normal (non-expandable) command has a pretty straightforward structure. Its definition is stored in `\<cmd>_code`, its defaults (if any) are stored in `\<cmd>_defaults`, and its

top-level definition contains its signature, which can just be copied over. `\__cmd_copy_command:nnNN` copies the command code and defaults, and then defines the top-level command using the auxiliary `\__cmd_copy_command:NnNNnnnn`. This macro takes the signature of the command being copied from its top-level definition, and replaces the named bits with the new name.

```

1166 \cs_new_protected:Npn \__cmd_copy_command:nnNN #1 #2 #3 #4
1167 {
1168   \cs_set_eq:cc { #1 ~ code } { #2 ~ code }
1169   \__cmd_set_eq_if_exist:cc { #1 ~ defaults } { #2 ~ defaults }
1170   \cs_set_protected_nopar:Npx #3
1171   { \exp_after:wN \__cmd_copy_command:NnNNnnnn #4 {#1} }
1172 }
1173 \cs_new:Npn \__cmd_copy_command:NnNNnnnn #1 #2 #3 #4 #5 #6 #7 #8
1174 {
1175   #1 \exp_not:n { {#2} }
1176   \exp_not:c { #8 ~ } \exp_not:c { #8 ~ code }
1177   \exp_not:n { {#5} {#6} {#7} }
1178 }

```

(End of definition for `\__cmd_copy_command:nnNN` and `\__cmd_copy_command:NnNNnnnn`.)

`\__cmd_copy_expandable:nnNN` An expandable command is slightly more complicated. Besides the `\<cmd>_code`, and `\<cmd>_defaults`, it also has an auxiliary `\<cmd>_l` for grabbing delimited arguments, and possibly another auxiliary `\<cmd>_ll`, if the command has both long and short arguments. Then, its signature also has several specific bits that are unique to that command; this is in contrast to non-expandable commands, which use a common set of parsing functions.

We start by copying the basics, then call `\__cmd_copy_expandable_signature:NnNNNNnnnn` to parse the signature of the command and build up the modified copy in a temporary token list, then we call `\__cmd_copy_expandable:NnNNNNnnnn` that will copy the top-level definition of the command, with the proper internal renames.

```

1179 <latexrelease> \EndIncludeInRelease
1180 <latexrelease> \IncludeInRelease{2020/10/01}{\__cmd_copy:NN}%
1181 <latexrelease> {Support~\NewCommandCopy~in~ltxcmd}
1182 <latexrelease> \EndIncludeInRelease

```

There's one variant: a command begins with `\__cmd_start_expandable:nNNNNn` may still be un-expandable/protected if it's defined by `\NewDocumentCommand` and friends, with empty or only m-type arguments.

```

1183 <latexrelease> \IncludeInRelease{2023/06/01}{\__cmd_copy_expandable:nnNN}%
1184 <latexrelease> {Distinguish~non-expandable~document~commands}
1185 \cs_new_protected:Npn \__cmd_copy_expandable:nnNN #1 #2 #3 #4
1186 {
1187   \cs_set_eq:cc { #1 ~ code } { #2 ~ code }
1188   \__cmd_set_eq_if_exist:cc { #1 ~ } { #2 ~ }
1189   \__cmd_set_eq_if_exist:cc { #1 ~ \c_space_tl } { #2 ~ \c_space_tl }
1190   \__cmd_set_eq_if_exist:cc { #1 ~ defaults } { #2 ~ defaults }
1191   \exp_after:wN \__cmd_copy_expandable_signature:NnNNNNnnnn #4 {#1} {#2}
1192   \token_if_protected_macro:NTF #4
1193   { \cs_set_protected_nopar:Npx } { \cs_set_nopar:Npx }
1194   #3
1195   { \exp_after:wN \__cmd_copy_expandable:NnNNNNnnnn #4 {#1} {#2} }
1196 }
1197 <latexrelease> \EndIncludeInRelease

```

```

1198 <latexrelease>\IncludeInRelease{2021/11/15}{\__cmd_copy_expandable:nnNN}%
1199 <latexrelease> {Support~\NewCommandCopy~in~ltxcmd}
1200 <latexrelease>\cs_new_protected:Npn \__cmd_copy_expandable:nnNN #1 #2 #3 #4
1201 <latexrelease> {
1202 <latexrelease> \cs_set_eq:cc { #1 ~ code } { #2 ~ code }
1203 <latexrelease> \__cmd_set_eq_if_exist:cc { #1 ~ } { #2 ~ }
1204 <latexrelease> \__cmd_set_eq_if_exist:cc { #1 ~ \c_space_tl } { #2 ~ \c_space_tl }
1205 <latexrelease> \__cmd_set_eq_if_exist:cc { #1 ~ defaults } { #2 ~ defaults }
1206 <latexrelease> \exp_after:wN \__cmd_copy_expandable_signature:NnNNNNnnn #4 {#1} {#2}
1207 <latexrelease> \cs_set_nopar:Npx #3
1208 <latexrelease> { \exp_after:wN \__cmd_copy_expandable:NnNNNNnnn #4 {#1} {#2} }
1209 <latexrelease> }
1210 <latexrelease>\EndIncludeInRelease
1211 <latexrelease>\IncludeInRelease{2020/10/01}{\__cmd_copy_expandable:nnNN}%
1212 <latexrelease> {Support~\NewCommandCopy~in~ltxcmd}
1213 <latexrelease>\EndIncludeInRelease

```

Copy the code, simply define the wrapper.

```

\__cmd_copy_optimized:nnNN
1214 \cs_new_protected:Npn \__cmd_copy_optimized:nnNN #1#2#3#4
1215 {
1216 \cs_set_eq:cc { #1 ~ code } { #2 ~ code }
1217 \token_if_protected_macro:NTF #4
1218 { \cs_set_protected_nopar:Npe }
1219 { \cs_set_nopar:Npe }
1220 #3
1221 {
1222 \exp_not:N \__cmd_start_optimized:
1223 \exp_not:c { #1 ~ code }
1224 }
1225 }

1226 <latexrelease>\IncludeInRelease{2021/11/15}{\__cmd_copy:NN (part 2)}%
1227 <latexrelease> {Support~\NewCommandCopy~in~ltxcmd}

1228 \cs_new:Npn \__cmd_copy_expandable:NnNNNNnnn #1 #2 #3 #4 #5 #6 #7 #8 #9
1229 {
1230 \exp_not:N #1 \exp_not:n { {#2} }
1231 \exp_not:c { #8 ~ }
1232 \exp_not:c
1233 {
1234 #8 ~
1235 \str_if_eq:eeT
1236 { \exp_not:c { #9 ~ \c_space_tl } } { \exp_not:N #4 }
1237 { \c_space_tl }
1238 }
1239 \exp_not:c { #8 ~ code }
1240 \str_if_eq:eeTF { \exp_not:N #6 } { ? }
1241 { ? }
1242 { \exp_not:c { #8 ~ defaults } }
1243 { \exp_not:V \l__cmd_tmpa_tl }
1244 }

```

A signature for an expandable command contains as many `\expandable_grab_⟨type⟩:w` as there are arguments, and what follows this macro depends on the `⟨type⟩`. We'll start a loop through the signature, and at each argument grabber, we'll step the argument

```

\__cmd_copy_expandable_signature:NnNNNNnnn
\__cmd_copy_expandable:nnN
\__cmd_copy_parse_grabber:w

```

count, and look for the  $\langle type \rangle$  with `\__cmd_copy_parse_grabber:w` so that we know which `\__cmd_copy_grabber_<type>:w` to call next.

```

1245 \cs_new_protected:Npn \__cmd_copy_expandable_signature:NnNNNNnnn
1246   #1 #2 #3 #4 #5 #6 #7 #8 #9
1247   {
1248     \int_zero:N \l__cmd_current_arg_int
1249     \tl_clear:N \l__cmd_tmpa_tl
1250     \__cmd_copy_expandable:nnN {#8} {#9} #7
1251     \q_recursion_tail \q_recursion_stop
1252   }
1253 \cs_new_protected:Npn \__cmd_copy_expandable:nnN #1 #2 #3
1254   {
1255     \quark_if_recursion_tail_stop:n {#3}
1256     \int_incr:N \l__cmd_current_arg_int
1257     \exp_after:wN \__cmd_copy_parse_grabber:w \token_to_str:N #3 {#1} {#2}
1258   }
1259 \use:x
1260   {
1261     \cs_new_protected:Npn \exp_not:N \__cmd_copy_parse_grabber:w ##1
1262       \tl_to_str:n { expandable_grab_ } ##2 \tl_to_str:n { :w }
1263     {
1264       \tl_put_right:Nx \exp_not:N \l__cmd_tmpa_tl
1265         { \exp_not:N \exp_not:c { __cmd_expandable_grab_##2:w } }
1266       \exp_not:N \cs_if_exist_use:cF { __cmd_copy_grabber_##2:w }
1267         { \__cmd_cant_copy:nwn { unknown-type } }
1268     }
1269   }

```

The most complicated is the Delimited argument: each argument has a dedicated grabbing function named after the command that has to be copied over (of the form  $\backslash\langle cmd \rangle_{\square}(\arg_{\square}\langle num \rangle)$ ).

```

1270 \cs_new_protected:Npn \__cmd_copy_grabber_D:w #1 #2 #3 #4 #5
1271   {
1272     \tl_put_right:Nx \l__cmd_tmpa_tl
1273     {
1274       \exp_not:c { #1 ~ (arg ~ \int_use:N \l__cmd_current_arg_int ) }
1275       \exp_not:n { #4 #5 }
1276     }
1277     \cs_set_eq:cc
1278       { #1 ~ (arg ~ \int_use:N \l__cmd_current_arg_int ) }
1279       { #2 ~ (arg ~ \int_use:N \l__cmd_current_arg_int ) }
1280     \__cmd_copy_expandable:nnN {#1} {#2}
1281   }

```

`\__cmd_copy_grabber_D:w`  
`\__cmd_copy_grabber_D_alt:w`  
`\__cmd_copy_grabber_R:w`  
`\__cmd_copy_grabber_R_alt:w`  
`\__cmd_copy_grabber_E:w`  
`\__cmd_copy_grabber_E_long:w`  
`\__cmd_copy_grabber_t:w`  
`\__cmd_copy_grabber_m:w`  
`\__cmd_copy_grabber_m_long:w`

`D_alt` is just a special case of `D` that uses a single delimiter (used when both delimiters of the argument are identical):

```

1282 \cs_new_protected:Npn \__cmd_copy_grabber_D_alt:w #1 #2 #3 #4
1283   { \__cmd_copy_grabber_D:w {#1} {#2} {#3} {#4} { } }

```

As far as copying is concerned, `R` is identical to `D`:

```

1284 \cs_new_eq:NN \__cmd_copy_grabber_R:w \__cmd_copy_grabber_D:w
1285 \cs_new_eq:NN \__cmd_copy_grabber_R_alt:w \__cmd_copy_grabber_D_alt:w

```

E is straightforward: we just copy the embellishments over, and increase the current argument number `\l__cmd_current_arg_int` by the number of embellishments (minus one because there is a `\int_incr:N` down the line).

```

1286 \cs_new_protected:Npn \__cmd_copy_grabber_E:w #1 #2 #3 #4
1287 {
1288   \tl_put_right:Nn \l__cmd_tmpa_tl { {#3} {#4} }
1289   \int_add:Nn \l__cmd_current_arg_int { \tl_count:n {#4} - 1 }
1290   \__cmd_copy_expandable:nnN {#1} {#2}
1291 }
1292 \cs_new_eq:NN \__cmd_copy_grabber_E_long:w \__cmd_copy_grabber_E:w
      t just needs copying the token to be tested for:
1293 \cs_new_protected:Npn \__cmd_copy_grabber_t:w #1 #2 #3 #4
1294 {
1295   \tl_put_right:Nn \l__cmd_tmpa_tl { #3 #4 }
1296   \__cmd_copy_expandable:nnN {#1} {#2}
1297 }

```

And last but not least, `m` is the simplest; the grabber is just `\__cmd_expandable_grab_m:w`, which is already added to the new command so here we just resume the loop:

```

1298 \cs_new_protected:Npn \__cmd_copy_grabber_m:w { \__cmd_copy_expandable:nnN }
1299 \cs_new_eq:NN \__cmd_copy_grabber_m_long:w \__cmd_copy_grabber_m:w

```

*(End of definition for `\__cmd_copy_expandable:nnNN` and others.)*

`\__cmd_copy_environment:nnNN` Copying an environment's `\begin` part is pretty much like copying a command, except it has a longer name, and at the end we have to copy `\environment <name>` into `\<name>`.

```

1300 \cs_new_protected:Npn \__cmd_copy_environment:nnNN #1 #2 #3 #4
1301 {
1302   \cs_set_eq:cc { environment~ #1 ~ code } { environment~ #2 ~ code }
1303   \__cmd_set_eq_if_exist:cc
1304     { environment~ #1 ~ defaults } { environment~ #2 ~ defaults }
1305   \cs_set_protected_nopar:cpx { environment~ #1 }
1306     { \exp_after:wN \__cmd_copy_environment:Nnnnnnn #4 {#1} }
1307   \cs_set_eq:cc {#1} { environment~ #1 }
1308 }
1309 \cs_new:Npn \__cmd_copy_environment:Nnnnnnn #1 #2 #3 #4 #5 #6 #7
1310 { #1 \exp_not:n { {#2} } {#7} \exp_not:n { {#4} {#5} {#6} } }

```

*(End of definition for `\__cmd_copy_environment:nnNN` and `\__cmd_copy_environment:Nnnnnnn`.)*

`\__cmd_copy_environment_end:nnNN` Copying an environment's `\end` part is a bit trickier. We first have to make sure that both parts are named `\end<name>` (that's actually not a hard requirement, but an environment `\end` command makes no sense without the `end` in its name), and strip the leading `end` from the strings. After that, copying is straightforward.

```

1311 \cs_new_protected:Npn \__cmd_copy_environment_end:nnNN #1 #2
1312 {
1313   \__cmd_check_end:Nn \l__cmd_tmpa_tl {#1}
1314   \__cmd_check_end:Nn \l__cmd_tmpb_tl {#2}
1315   \exp_args:Noo \__cmd_copy_environment_end_aux:nnNN
1316     { \l__cmd_tmpa_tl } { \l__cmd_tmpb_tl }
1317 }
1318 \cs_new_protected:Npn \__cmd_copy_environment_end_aux:nnNN #1 #2 #3 #4
1319 {

```

```

1320 \cs_set_nopar:cpx { environment~ #1 ~end }
1321 { \exp_not:c { environment~ #1 ~end~aux } }
1322 \cs_set_eq:cc
1323 { environment~ #1 ~end~aux~ } { environment~ #2 ~end~aux~ }
1324 \cs_set_eq:cc { end #1 } { environment~ #1 ~end }
1325 }

```

To check whether an `\end` command is valid, we look for the string `end` at the beginning of the command name, and if not found, raise an error:

```

\__cmd_check_end:Nn 1326 \cs_new_protected:Npn \__cmd_check_end:Nn #1 #2
\__cmd_check_end:n 1327 {
\__cmd_check_end:w 1328 \tl_set:Nx #1 { \__cmd_check_end:n {#2} }
1329 \token_if_eq_meaning:NNT #1 \q_nil
1330 { \__cmd_cant_copy:nwn { invalid-end } }
1331 }
1332 \cs_set_protected:Npn \__cmd_tmp:w #1
1333 {
1334 \cs_new:Npn \__cmd_check_end:n ##1
1335 {
1336 \exp_after:wN \__cmd_check_end:w \tl_to_str:n {##1}
1337 #1 \q_mark #1 \q_stop
1338 }
1339 \cs_new:Npn \__cmd_check_end:w ##1 #1 ##2 #1 ##3 \q_stop
1340 { \if_meaning:w ##2 \q_mark \exp_not:N \q_nil \else: ##2 \fi: }
1341 }
1342 \exp_args:No \__cmd_tmp:w { \tl_to_str:n { end } }

```

(End of definition for `\__cmd_copy_environment_end:nnNN` and others.)

Not much to do regarding `latexrelease`: we could remove the entries from `\@declarecommandcopylist` but it doesn't seem worth it.

```

1343 <latexrelease> \EndIncludeInRelease
1344 <latexrelease> \IncludeInRelease{2020/10/01}{\__cmd_copy:NN (part 2)}%
1345 <latexrelease> {Support~\NewCommandCopy~in~ltxcmd}
1346 <latexrelease> \EndIncludeInRelease

```

## 1.7.2 Showing the definition of a command

```

1347 <latexrelease> \IncludeInRelease{2021/11/15}{\__cmd_show:N}%
1348 <latexrelease> {Support~\ShowCommand~in~ltxcmd}

```

To show the definition of a command we need more or less the same building blocks as for copying, except that instead of making a copy, we'll just print stuff to the terminal.

`\__cmd_show:N` This macro just branches to the proper showing command by using `\__cmd_cmd_type_cases:NnnnnnF`. The showing command takes the command to be shown as argument.

```

1349 \cs_new_protected:Npn \__cmd_show:N #1
1350 {
1351 \use:x
1352 {
1353 \int_set:Nn \tex_escapechar:D { 92 }
1354 \exp_not:N \__cmd_cmd_type_cases:NnnnnnF \exp_not:N #1
1355 { \__cmd_show_command:N }
1356 { \__cmd_show_expandable:N }
1357 { \__cmd_show_optimized:N }
1358 { \__cmd_show_environment:N }

```

```

1359         { \_cmd_show_environment_end:N }
1360         { \_cmd_cant_copy:nwn { non-ltcmd } }
1361         \exp_not:N #1
1362         \exp_not:N \_cmd_break_point:n { \cs_to_str:N #1 }
1363         \int_set:Nn \tex_escapechar:D { \int_use:N \tex_escapechar:D }
1364     }
1365 }

```

(End of definition for \\_cmd\_show:N.)

\\_cmd\_show\_command:N These commands just expand the command once to reveal its innards, then pass the type of command, the control sequence, the signature, and the code macro to \\_cmd\_show\_command\_aux:NnNNn.

```

1366 \cs_new_protected:Npn \_cmd_show_command:N #1
1367 { \exp_after:wN \_cmd_show_command:NnNNwN #1 \q_cmd #1 }
1368 \cs_new_protected:Npn \_cmd_show_command:NnNNwN #1 #2 #3 #4 #5 \q_cmd #6
1369 {
1370     \_cmd_show_command_aux:NnNNn \tl_show:x
1371     { document~command } #6 #4 {#2}
1372 }
1373 \cs_new_protected:Npn \_cmd_show_expandable:N #1
1374 { \exp_after:wN \_cmd_show_expandable:NnNNNNnN #1 #1 }
1375 <latexrelease> \EndIncludeInRelease
1376 <latexrelease> \IncludeInRelease{2020/10/01}{\_cmd_show:N}%
1377 <latexrelease> {Support~\ShowCommand~in~ltcmd}
1378 <latexrelease> \EndIncludeInRelease

```

There's one variant: a command begins with \\_cmd\_start\_expandable:nNNNNn may still be un-expandable/protected if it's defined by \NewDocumentCommand and friends, with empty or only m-type arguments.

```

1379 <latexrelease> \IncludeInRelease{2023/06/01}{\_cmd_show_expandable:NnNNNNnN}%
1380 <latexrelease> {Distinguish~non~expandable~document~commands}
1381 \cs_new_protected:Npn \_cmd_show_expandable:NnNNNNnN #1 #2 #3 #4 #5 #6 #7 #8
1382 {
1383     \exp_args:NNe \_cmd_show_command_aux:NnNNn \tl_show:x
1384     { \token_if_protected_macro:NF #8 { expandable~ } document~command }
1385     #8 #5 {#2}
1386 }
1387 <latexrelease> \EndIncludeInRelease
1388 <latexrelease> \IncludeInRelease{2021/11/15}{\_cmd_show_expandable:NnNNNNnN}%
1389 <latexrelease> {Support~\ShowCommand~in~ltcmd}
1390 <latexrelease> \cs_new_protected:Npn \_cmd_show_expandable:NnNNNNnN #1 #2 #3 #4 #5 #6 #7 #8
1391 <latexrelease> {
1392     \_cmd_show_command_aux:NnNNn \tl_show:x
1393     { expandable~document~command } #8 #5 {#2}
1394 }
1395 <latexrelease> \EndIncludeInRelease
1396 <latexrelease> \IncludeInRelease{2020/10/01}{\_cmd_show_expandable:NnNNNNnN}%
1397 <latexrelease> {Support~\ShowCommand~in~ltcmd}
1398 <latexrelease> \EndIncludeInRelease
1399 <latexrelease> \IncludeInRelease{2021/11/15}{\_cmd_show:N (part 2)}%
1400 <latexrelease> {Support~\ShowCommand~in~ltcmd}

```

Now just print everything in the required format. The auxiliary `\__cmd_split_signature:n` stores a ready-to-print token list in `\l__cmd_tmpa_tl`, so we use that here:

```

1401 \cs_new_protected:Npn \__cmd_show_command_aux:NnNnNn #1 #2 #3 #4 #5
1402 {
1403   \__cmd_split_signature:n {#5}
1404   #1
1405   {
1406     \token_to_str:N #3 = #2: \iow_newline:
1407     \tl_use:N \l__cmd_tmpa_tl
1408     -> \cs_replacement_spec:N #4
1409   }
1410 }

```

Optimized functions need things done a bit differently as we need to reconstruct the argument spec.

```

1411 \cs_new_protected:Npn \__cmd_show_optimized:N #1
1412 {
1413   \exp_args:Nc \__cmd_show_optimized:NN
1414   { \cs_to_str:N #1 \c_space_tl code }
1415   #1
1416 }
1417 \cs_new_protected:Npn \__cmd_show_optimized:NN #1#2
1418 {
1419   \cs_set:Npe \__cmd_show_optimized_aux:N ##1
1420   {
1421     \c_space_tl \c_space_tl \c_hash_str ##1 :
1422     \bool_lazy_or:nnT
1423     { \token_if_long_macro_p:N #1 }
1424     { \token_if_protected_long_macro_p:N #1 }
1425     { + } m
1426     \iow_newline:
1427   }
1428   \tl_show:e
1429   {
1430     \token_to_str:N #2 =
1431     \bool_lazy_or:nnF
1432     { \token_if_protected_macro_p:N #1 }
1433     { \token_if_protected_long_macro_p:N #1 }
1434     { expandable ~ } document-command:
1435     \iow_newline:
1436     \int_step_function:nN
1437     {
1438       \int_div_truncate:nn
1439       { \tl_count:e { \cs_parameter_spec:N #1 } }
1440       { 2 }
1441     }
1442     \__cmd_show_optimized_aux:N
1443     ->
1444     \cs_replacement_spec:N #1
1445   }
1446 }
1447 \cs_generate_variant:Nn \tl_count:n { e }

```

We can reuse most of the above to show an environment, except that we need to ensure that the proper `\environment ...` are passed to `\__cmd_show_command_aux:NnnNn`. Additionally, when `\ShowCommand\foo` is used (if `foo` is an environment), we show `\endfoo` as well, and when `\ShowCommand\endfoo` is used, change that to `\ShowCommand\foo` and do the same.

```

1448 \cs_new_protected:Npn \__cmd_show_environment:N #1
1449 {
1450   \exp_after:wN \__cmd_show_environment:Nnnw #1 \q__cmd
1451   \tl_show:x
1452   {
1453     \token_to_str:N \end { \cs_to_str:N #1 } : \iow_newline:
1454     -> \exp_args:Nc \cs_replacement_spec:N
1455       { environment~ \cs_to_str:N #1 ~end~aux~ }
1456   }
1457 }
1458 \cs_new_protected:Npn \__cmd_show_environment:Nnnw #1 #2 #3 #4 \q__cmd
1459 {
1460   \use:x
1461   {
1462     \__cmd_show_command_aux:NnnNn \__cmd_show:x { document~environment }
1463     { \exp_not:N \begin {#3} }
1464     \exp_not:c { environment~ #3 ~ code }
1465     {#2}
1466   }
1467 }
1468 \cs_if_exist:NTF \iow_show:e
1469 {
1470   \cs_new_protected:Npn \__cmd_show:x #1
1471   { \iow_show:e { > ~ #1 . \iow_newline: } }
1472 }
1473 {
1474   \cs_new_protected:Npn \__cmd_show:x #1
1475   { \iow_term:x { > ~ #1 . \iow_newline: } }
1476 }
1477 \cs_new_protected:Npn \__cmd_show_environment_end:N #1
1478 {
1479   \exp_args:NNx \__cmd_check_end:Nn \l__cmd_tmpa_tl { \cs_to_str:N #1 }
1480   \exp_args:Nc \__cmd_show_environment:N { \l__cmd_tmpa_tl }
1481 }

```

And, of course, add `\__kernel_cmd_if_xparse:N` and `\__cmd_show:N` to `\@showcommandlisthook` and to `\@showenvironmentlisthook` (`\__cmd_show:N` takes care of the environment case as well, so both entries are identical):

```

1482 \tl_gput_right:Nn \@showcommandlisthook
1483 { { \__kernel_cmd_if_xparse:N \__cmd_show:N } }
1484 \tl_gput_right:Nn \@showenvironmentlisthook
1485 { { \__kernel_cmd_if_xparse:N \__cmd_show:N } }

```

*(End of definition for `\__cmd_show_command:N` and others.)*

`\__cmd_split_signature:n` Now we'll try a least-effort adventure into splitting the symbolic user-provided signature for a command into individual parameters for pretty-printing. A counter is used to keep track of the current argument number, and two token lists are used: `\l__cmd_tmpa_tl` holds the final token list to be printed, and `\l__cmd_tmpb_tl` holds just the current item,

so that we can make changes to an individual item without having to dissect the whole thing (this is used for e- and E-types).

```

1486 \cs_new_protected:Npn \__cmd_split_signature:n #1
1487 {
1488   \int_set:Nn \l__cmd_current_arg_int { 1 }
1489   \tl_clear:N \l__cmd_tmpa_tl
1490   \tl_clear:N \l__cmd_tmpb_tl
1491   \__cmd_split_signature_loop:Nw #1 \q_recursion_tail \q_recursion_stop
1492 }

```

\\_\_cmd\_split\_signature\_loop:Nw This is the main chunk of the loop: it starts an item with \\_\_cmd\_split\_start\_item: (this adds indentation and the argument number to \l\_\_cmd\_tmpb\_tl), then checks if a special token list \c\_\_cmd\_show\_type\_⟨type⟩\_tl exists. If it doesn't, the current argument is a “simple” type which needs no extra processing. Otherwise, call a specific function depending on the value of said token list.

```

1493 \cs_new_protected:Npn \__cmd_split_signature_loop:Nw #1
1494 {
1495   \quark_if_recursion_tail_stop:N #1
1496   \tl_if_empty:NT \l__cmd_tmpb_tl { \__cmd_split_start_item: }
1497   \tl_if_exist:cTF { c__cmd_show_type_#1_tl }
1498   {
1499     \use:c
1500     {
1501       __cmd_show_
1502       \if_case:w \tl_use:c { c__cmd_show_type_#1_tl } \exp_stop_f:
1503       delim \or: delims \or: delims_opt \or: opt \or:
1504       e \or: E \or: prefix \or: processor \fi: :Nw
1505     } #1
1506   }
1507   { \__cmd_split_end_item:n {#1} \__cmd_split_signature_loop:Nw }
1508 }

```

The token lists \c\_\_cmd\_show\_type\_⟨type⟩\_tl exist for nontrivial (for printing) ⟨types⟩ that require special parsing (like delimiters or optional arguments). Values from 0 to 7 are assigned to each type:

\c\_\_cmd\_show\_type\_t\_tl  
 \c\_\_cmd\_show\_type\_r\_tl  
 \c\_\_cmd\_show\_type\_d\_tl  
 \c\_\_cmd\_show\_type\_R\_tl  
 \c\_\_cmd\_show\_type\_D\_tl  
 \c\_\_cmd\_show\_type\_0\_tl  
 \c\_\_cmd\_show\_type\_e\_tl  
 \c\_\_cmd\_show\_type\_E\_tl  
 \c\_\_cmd\_show\_type\_+\_tl  
 \c\_\_cmd\_show\_type\_!\_tl  
 \c\_\_cmd\_show\_type\_>\_tl

1. a single delimiter token;
2. two delimiter tokens;
3. two delimiter tokens plus a default value;
4. a default value;
5. a list of embellishments (exclusive for e-type);
6. embellishments plus defaults (exclusive for E-type);
7. simple prefixes;
8. prefixes with arguments (argument processors);

```

1509 \cs_set_protected:Npn \__cmd_tmp:w #1 #2
1510 {
1511   \quark_if_nil:nF {#1}
1512   { \tl_const:cn { c__cmd_show_type_#1_tl } {#2} \__cmd_tmp:w }
1513 }
1514 \__cmd_tmp:w t0 r1 d1 R2 D2 O3 e4 E5 +6 !6 >7 =7 \q_nil \q_nil

```

Now, based on each type we know how to act. In most cases it is just a matter of feeding in the grabbed arguments and resuming the loop. The embellishments require a bit more attention: the e-type loops through the list of embellishments and adds each to the token list as a separate argument. The E-type does more or less the same, but uses `\__cmd_tl_mapthread_function:nnN` to map over two lists simultaneously, adding each token and default to the token list for printing.

```

1515 \cs_new_protected:Npn \__cmd_show_delim:Nw #1 #2
1516 { \__cmd_split_end_item:n { #1 #2 } \__cmd_split_signature_loop:Nw }
1517 \cs_new_protected:Npn \__cmd_show_delims:Nw #1 #2 #3
1518 { \__cmd_split_end_item:n { #1 #2 #3 } \__cmd_split_signature_loop:Nw }
1519 \cs_new_protected:Npn \__cmd_show_delims_opt:Nw #1 #2 #3 #4
1520 { \__cmd_split_end_item:n { #1 #2 #3 {#4} } \__cmd_split_signature_loop:Nw }
1521 \cs_new_protected:Npn \__cmd_show_opt:Nw #1 #2
1522 { \__cmd_split_end_item:n { #1 {#2} } \__cmd_split_signature_loop:Nw }
1523 \cs_new_protected:Npn \__cmd_show_e:Nw #1 #2
1524 {
1525   \tl_map_inline:nn {#2}
1526   {
1527     \__cmd_split_start_item:
1528     \__cmd_split_end_item:n { #1 {#1} }
1529   }
1530   \__cmd_split_signature_loop:Nw
1531 }
1532 \cs_set_protected:Npn \__cmd_tmp:w #1
1533 {
1534   \cs_new_protected:Npn \__cmd_show_E:Nw ##1 ##2 ##3
1535   {
1536     \cs_set_protected:Npn \__cmd_tmp:w #####1 #####2
1537     {
1538       \__cmd_split_start_item:
1539       \__cmd_split_end_item:n { ##1 #####1 {#####2} }
1540     }
1541     \__cmd_tl_mapthread_function:nnN {##2}
1542     { ##3 {#1} {#1} {#1} {#1} {#1} {#1} {#1} {#1} {#1} {#1} } \__cmd_tmp:w
1543     \__cmd_split_signature_loop:Nw
1544   }
1545 }
1546 \exp_args:NW \__cmd_tmp:w \c_novalue_tl

```

Minor wrinkle with the prefixes: they use `\__cmd_split_add_item:n` instead of `\__cmd_split_end_item:n` (add *vs.* end) because they are followed by an argument, so they can't end the item.

```

1547 \cs_new_protected:Npn \__cmd_show_prefix:Nw #1
1548 { \__cmd_split_add_item:n {#1} \__cmd_split_signature_loop:Nw }
1549 \cs_new_protected:Npn \__cmd_show_processor:Nw #1 #2
1550 { \__cmd_split_add_item:n { #1 {#2} } \__cmd_split_signature_loop:Nw }

```

And now the auxiliaries that store the strings to be printed. `\__cmd_split_start_item:` starts an item from scratch, `\__cmd_split_add_item:n` adds tokens to an item without adding a newline, and `\__cmd_split_end_item:n` adds tokens, terminates the item with a newline, and steps the argument count.

```

1551 \cs_new_protected:Npn \__cmd_split_start_item:
1552 {
1553   \tl_set:Nx \l__cmd_tmpb_tl
1554   { ~ \c_space_tl \c_hash_str \int_use:N \l__cmd_current_arg_int : }
1555 }
1556 \cs_new_protected:Npn \__cmd_split_add_item:n #1
1557 { \tl_put_right:Nx \l__cmd_tmpb_tl { \tl_to_str:n {#1} } }
1558 \cs_new_protected:Npn \__cmd_split_end_item:n #1
1559 {
1560   \tl_put_right:Nx \l__cmd_tmppa_tl
1561   { \l__cmd_tmpb_tl \tl_to_str:n {#1} \iow_newline: }
1562   \tl_clear:N \l__cmd_tmpb_tl
1563   \int_incr:N \l__cmd_current_arg_int
1564 }

```

(End of definition for `\__cmd_split_signature:n` and others.)

Not much to do regarding `latexrelease`: we could remove the entries from `\@showcommandlisthook`, but it doesn't seem worth it.

```

\__cmd_split_start_item: 1565 <latexrelease>\EndIncludeInRelease
\__cmd_split_add_item:n 1566 %
\__cmd_split_end_item:n 1567 <latexrelease>\IncludeInRelease{2020/10/01}{\__cmd_show:N (part 2)}%
1568 <latexrelease> {Support~\ShowCommand~in~ltcmd}
1569 <latexrelease>\EndIncludeInRelease

```

## 1.8 Grabbing arguments

All of the grabbers follow the same basic pattern. The initial function stores in `\l__cmd_signature_tl` the code to grab further arguments, defines (the function in) `\l__cmd_fn_tl` that will grab the argument, and calls it.

Defining `\l__cmd_fn_tl` means determining whether to use `\cs_set:Npn` or `\cs_set_nopar:Npn`, and for optional arguments whether to skip spaces. Once the argument is found, `\l__cmd_fn_tl` calls `\__cmd_add_arg:n`, responsible for calling processors and grabbing further arguments.

<pre> \__cmd_grab_b:w \__cmd_grab_b_long:w \__cmd_grab_b_obey_spaces:w \__cmd_grab_b_long_obey_spaces:w \__cmd_grab_b_aux:NNw \__cmd_grab_b_end:Nw </pre>	<p>This uses the well-tested code of D-type arguments, skipping the peeking step because the b-type argument is always present, and adding a cleanup stage at the end by hijacking the signature. The clean-up consists of properly dealing with <code>\l__cmd_args_tl</code> and also putting back the <code>\end</code> that served as an end-delimiter: this <code>\end</code> receives the environment name as its argument and is run normally. The D-type code stores the argument found (body of the environment) as a brace group in <code>\l__cmd_args_tl</code> and depending on the presence of a prefix <code>!</code> we trim spaces or not before adding this braced argument into the saved <code>\l__cmd_args_tl</code>. The strange <code>\begin_</code> control sequence is there for display purposes only: it has to look like <code>\begin</code> in the terminal but not to delimited arguments.</p>
---	--

```

1570 \cs_new_protected:Npn \__cmd_grab_b:w
1571 { \__cmd_grab_b_aux:NNw \cs_set_protected_nopar:Npn \tl_trim_spaces:n }
1572 \cs_new_protected:Npn \__cmd_grab_b_long:w
1573 { \__cmd_grab_b_aux:NNw \cs_set_protected:Npn \tl_trim_spaces:n }
1574 \cs_new_protected:Npn \__cmd_grab_b_obey_spaces:w

```

```

1575 { \__cmd_grab_b_aux:NNw \cs_set_protected_nopar:Npn \exp_not:n }
1576 \cs_new_protected:Npn \__cmd_grab_b_long_obey_spaces:w
1577 { \__cmd_grab_b_aux:NNw \cs_set_protected:Npn \exp_not:n }
1578 \cs_new_protected:Npn \__cmd_grab_b_aux:NNw #1#2#3 \__cmd_run_code:
1579 {
1580   \__cmd_grab_D_aux:NNNN \begin \end {#3} #1 \use_ii:nn
1581   \tl_put_left:Nn \l__cmd_signature_tl { \__cmd_grab_b_end:Nw #2 }
1582   \tl_set_eq:NN \l__cmd_saved_args_tl \l__cmd_args_tl
1583   \tl_clear:N \l__cmd_args_tl
1584   \exp_args:Nc \l__cmd_fn_tl { begin ~ }
1585 }
1586 \cs_new_protected:Npn \__cmd_grab_b_end:Nw #1#2 \__cmd_run_code:
1587 {
1588   \tl_set:Nx \l__cmd_args_tl
1589   {
1590     \exp_not:V \l__cmd_saved_args_tl
1591     { \exp_after:wN #1 \l__cmd_args_tl }
1592   }
1593   #2
1594   \__cmd_run_code:
1595   \end
1596 }

```

(End of definition for \\_\_cmd\_grab\_b:w and others.)

\\_\_cmd\_grab\_c:w Collecting an environment body verbatim shares some ideas with the v-type grabber, and  
\\_\_cmd\_grab\_c\_obey\_spaces:w others with the standard filecontents environment. The start is to set the end-of-line  
\\_\_cmd\_grab\_c\_start:n to a predictable value and to deactivate the specials.

```

1597 \cs_new_protected:Npn \__cmd_grab_c:w #1 \__cmd_run_code:
1598 {
1599   \bool_set_false:N \l__cmd_obey_spaces_bool
1600   \__cmd_grab_c_start:n {#1}
1601 }
1602 \cs_new_protected:Npn \__cmd_grab_c_obey_spaces:w #1 \__cmd_run_code:
1603 {
1604   \bool_set_true:N \l__cmd_obey_spaces_bool
1605   \__cmd_grab_c_start:n {#1}
1606 }
1607 \cs_new_protected:Npn \__cmd_grab_c_start:n #1
1608 {
1609   \tl_set:Nn \l__cmd_signature_tl {#1}
1610   \group_begin:
1611     \tl_clear:N \l__cmd_v_arg_tl
1612     \tex_escapechar:D = 92 \scan_stop:
1613     \tex_endlinechar:D = '\^M \scan_stop:
1614     \cs_set_eq:NN \do \char_set_catcode_other:N
1615     \dospecials
1616     \char_set_catcode_other:n { '\^M }
1617     \__cmd_grab_c_first:w
1618   }

```

Notice here and below that we cannot use \token\_to\_str:N \end as that would have the wrong category codes for the letters.

```

1619 \group_begin:

```

```

1620 \char_set_catcode_other:N \^^M %
1621 \cs_new_protected:Npn \__cmd_grab_c_first:w #1 \^^M %
1622 { %
1623   \tl_if_blank:nTF {#1} %
1624   { %
1625     \__cmd_grab_c_loop:w #1 \^^M %
1626   } %
1627   { %
1628     \msg_warning:nnee { cmd } { chars-dropped-first-line } %
1629     { \exp_not:n {#1} } %
1630     { \exp_not:V \@currenvir } %
1631     \__cmd_grab_c_loop:w \^^M %
1632   } %
1633 } %
1634 \cs_new_protected:Npe \__cmd_grab_c_loop:w #1 \^^M %
1635 { %
1636   \exp_not:N \__cmd_grab_c_auxi:w #1 %
1637   \c_backslash_str end %
1638   \scan_stop: %
1639 } %
1640 \group_end:

```

(End of definition for `\__cmd_grab_c:w` and others.)

`\__cmd_grab_c_auxi:w` We need to see if the current line contains `\end` followed by the name of the current environment. To do that and allow for spaces, we have to work stepwise. First, establish `\__cmd_grab_c_auxii:w` if there is an `\end` at all: remember that here we are dealing with “other” tokens. Whether `\__cmd_grab_c_auxiii:N` these is an `\end` or not, the tokens *before* it form part of the line.

```

1641 \use:e
1642 {
1643   \cs_new_protected:Npn \exp_not:N \__cmd_grab_c_auxi:w
1644   #1 \c_backslash_str end #2 \scan_stop:
1645 }
1646 {
1647   \tl_put_right:Nn \l__cmd_v_arg_tl {#1}
1648   \tl_if_empty:nTF {#2}
1649   {
1650     \tl_put_right:Nn \l__cmd_v_arg_tl { \obeyedline }
1651     \__cmd_grab_c_loop:w
1652   }
1653   { \__cmd_grab_c_auxii:w #2 \scan_stop: }
1654 }

```

There is an `\end`, so we now remove the trailing marker we needed to do the test. This is stripped off, then we need to examine the rest of the line one token at a time: see `verbatim.dtx` for the inspiration. Notice that we use `\^^M` here as the end marker: this allows looping to look for multiple `\end` entries in the line.

```

1655 \group_begin:
1656   \char_set_catcode_other:N \^^M %
1657   \use:e %
1658   { %
1659     \cs_new_protected:Npe \exp_not:N \__cmd_grab_c_auxii:w %
1660     #1 \c_backslash_str end \scan_stop: %
1661   } %

```

```

1662 { %
1663   \tl_set:Nn \exp_not:N \l__cmd_tmpa_tl
1664   { \c_backslash_str end } %
1665   \exp_not:N \__cmd_grab_c_auxiii:N #1 ^^M %
1666 } %

```

Within the line, we need to collect up the tokens: if we do not find the end-of-environment argument, we will need those to reinsert. There are three special cases here: ^^M (end of line: tidy up and back to the main loop), \ (possibly skip over) and { (start the inner loop). Anything else means we move back to examine the rest of the line for any more \end entries.

```

1667 \cs_new_protected:Npn \__cmd_grab_c_auxiii:N #1 %
1668 { %
1669   \token_case_charcode:NnF #1 %
1670   { %
1671     ^^M %
1672     { \__cmd_grab_c_auxiv: } %
1673     \c_space_token %
1674     { %
1675       \tl_put_right:Nn \l__cmd_tmpa_tl {#1} %
1676       \__cmd_grab_c_auxiii:N %
1677     } %
1678     \c_group_begin_token %
1679     { %
1680       \tl_set:Nn \l__cmd_tmppb_tl {#1} %
1681       \__cmd_grab_c_auxvi:N %
1682     } %
1683   } %
1684   { %
1685     \tl_put_right:Nn \l__cmd_tmpa_tl {#1} %
1686     \__cmd_grab_c_auxv: %
1687   } %
1688 } %
1689 \group_end:
1690 \cs_new_protected:Npn \__cmd_grab_c_auxiv:
1691 {
1692   \tl_put_right:Ne \l__cmd_v_arg_tl
1693   {
1694     \exp_not:V \l__cmd_tmpa_tl
1695     \exp_not:N \obeyedline
1696   }
1697   \__cmd_grab_c_loop:w
1698 }
1699 \cs_new_protected:Npn \__cmd_grab_c_auxv:
1700 {
1701   \tl_put_right:NV \l__cmd_v_arg_tl \l__cmd_tmpa_tl
1702   \__cmd_grab_c_loop:w
1703 }

```

In the inner loop, we again have only a few special cases. First, we could again have ^^M, in which case we tidy up using a common auxiliary. Second, we check for the escape char: this cannot happen inside the end of an environment and means we loop, re-inserting the token. Finally, we have }, where we need to move on to check what has been collected. Otherwise, collect up and loop. Notice here that the inner loop needs to

collect tokens separately: this leaves any spaces after \end in \l\_\_cmd\_tmpa\_tl, so we can test \l\_\_cmd\_tmppb\_tl directly.

```

1704 \group_begin:
1705   \char_set_catcode_other:N \^^M %
1706   \cs_new_protected:Npe \__cmd_grab_c_auxvi:N #1 %
1707     { %
1708       \exp_not:N \token_case_charcode:NnF #1 %
1709       { %
1710         ^^M %
1711         {
1712           \exp_not:N \__cmd_grab_c_auxvii: %
1713           \exp_not:N \__cmd_grab_c_auxiv: %
1714         }%
1715         \c_backslash_str %
1716         { %
1717           \exp_not:N \__cmd_grab_c_auxvii: %
1718           \exp_not:N \__cmd_grab_c_auxv: #1
1719         } %
1720         \c_group_end_token %
1721         { %
1722           \tl_put_right:Nn \exp_not:N \l__cmd_tmppb_tl {#1} %
1723           \exp_not:N \__cmd_grab_c_auxviii: %
1724         } %
1725       } %
1726     } %
1727     \tl_put_right:Nn \exp_not:N \l__cmd_tmppb_tl {#1} %
1728     \exp_not:N \__cmd_grab_c_auxvi:N %
1729   } %
1730 } %
1731 \group_end: %
1732 \cs_new_protected:Npn \__cmd_grab_c_auxvii:
1733 { \tl_put_right:NV \l__cmd_tmppa_tl \l__cmd_tmppb_tl }
1734 \cs_new_protected:Npn \__cmd_grab_c_auxviii:
1735 {
1736   \str_if_eq:eeTF { \exp_not:N \l__cmd_tmppb_tl } { { \@currenvir } }
1737   { \__cmd_grab_c_end:w }
1738   {
1739     \__cmd_grab_c_auxvii:
1740     \__cmd_grab_c_auxv:
1741   }
1742 }

```

(End of definition for \\_\_cmd\_grab\_c\_auxi:w and others.)

<pre> \__cmd_grab_c_end:w \__cmd_grab_c_end:n \__cmd_grab_c_end_auxi:w \__cmd_grab_c_end_auxii:w \__cmd_grab_c_end_auxiii:w </pre>	<pre> 1743 \group_begin: 1744   \char_set_catcode_other:N \^^M % 1745   \cs_new_protected:Npn \__cmd_grab_c_end:w #1 ^^M % 1746     { % 1747       \tl_if_blank:nF {#1} % 1748       { % 1749         \msg_warning:nnee { cmd } { chars-dropped-last-line } % 1750         { \exp_not:n {#1} } % </pre>	<p>To end the collection, we clean up the last line: once again we need to find ^^M. Once that is done, we can warn if there is anything left behind.</p>
--	---	---

```

1751         { \exp_not:V \@currenvir } %
1752     } %
1753     \exp_args:NNNo \group_end: %
1754     \tl_set:Nn \l__cmd_v_arg_tl { \l__cmd_v_arg_tl } %
1755     \__cmd_add_arg:x %
1756     { %
1757         \bool_if:NTF \l__cmd_obey_spaces_bool %
1758         { \exp_not:V } %
1759         { \exp_args:NV \__cmd_grab_c_end:n } %
1760         \l__cmd_v_arg_tl %
1761     } %
1762     \exp_args:NV \end \@currenvir %
1763 } %
1764 \group_end: %

```

Look for line markers at each end and tidy up if required.

```

1765 \cs_new:Npn \__cmd_grab_c_end:n #1
1766 {
1767     \__cmd_grab_c_end_auxi:w \q_nil #1 \q_nil
1768     \obeyedline \obeyedline \q_nil \q_stop
1769 }
1770 \cs_new:Npn \__cmd_grab_c_end_auxi:w #1 \q_nil \obeyedline
1771 { \__cmd_grab_c_end_auxii:w #1 \q_nil }
1772 \cs_new:Npn \__cmd_grab_c_end_auxii:w \q_nil #1 \obeyedline \q_nil
1773 { \__cmd_grab_c_end_auxiii:w #1 \q_nil }
1774 \cs_new:Npn \__cmd_grab_c_end_auxiii:w #1 \q_nil #2 \q_stop
1775 { \exp_not:n {#1} }

```

(End of definition for \\_\_cmd\_grab\_c\_end:w and others.)

```

\__cmd_grab_D:w The generic delimited argument grabber. The auxiliary function does a peek test before
\__cmd_grab_D_no_strip:w calling \__cmd_grab_D_call:Nw, so that the optional nature of the argument works as
\__cmd_grab_D_obey_spaces:w expected.
\__cmd_grab_D_obey_spaces_no_strip:w
\__cmd_grab_D_long:w
\__cmd_grab_D_long_no_strip:w
\__cmd_grab_D_long_obey_spaces:w
\__cmd_grab_D_long_obey_spaces_no_strip:w
1776 \tl_map_inline:nn { { } { _long } }
1777 {
1778     \tl_map_inline:nn { { } { _obey_spaces } }
1779     {
1780         \tl_map_inline:nn { { } { _no_strip } }
1781         {
1782             \tl_map_inline:nn { { } { _verb_safe } }
1783             {
1784                 \cs_new_protected:cpe { __cmd_grab_D #1 ##1 #####1 #####1 :w }
1785                 #####1#####2#####3
1786                 \__cmd_run_code:
1787                 {
1788                     \exp_not:N \__cmd_grab_D_aux:NNnNNNN
1789                     #####1 #####2 {#####3}
1790                     \str_if_eq:nnTF {#1} { _long }
1791                     \cs_set_protected:Npn
1792                     \cs_set_protected_nopar:Npn
1793                     \str_if_eq:nnTF {##1} { _obey_spaces }
1794                     { \exp_not:N \__cmd_peek_meaning_remove:NTF }
1795                     { \exp_not:N \__cmd_peek_nonspace_remove:NTF }
1796                     \str_if_eq:nnTF {#####1} { _no_strip }
1797                     { \exp_not:N \use_none:n }

```

```

1798         { \exp_not:N \use_ii:nn }
1799     \str_if_eq:nnTF {#####1} { _verb_safe }
1800     { \exp_not:N \use:n }
1801     { \exp_not:N \use_none:n }
1802   }
1803 }
1804 }
1805 }
1806 }

```

This is a bit complicated. The idea is that, in order to check for nested optional argument tokens (`[...] and so on`) the argument needs to be grabbed without removing any braces at all. If this is not done, then cases like `[[]]` fail. So after testing for an optional argument, it is collected piece-wise. Inserting a quark prevents loss of braces, and there is then a test to see if there are nested delimiters to handle.

```

1807 \group_begin:
1808   \char_set_catcode_other:N \^^M
1809   \cs_new_protected:Npn \__cmd_grab_D_aux:NNnNNNN #1#2#3#4#5#6#7
1810   {
1811     \__cmd_grab_D_aux:NNnNN #1#2 {#3} #4 #6
1812     #7
1813     {
1814       \group_begin:
1815         \__cmd_grab_D_verb_safe:NN #1#5
1816       }
1817     #5 #1
1818     {
1819       #7 { \group_end: }
1820       \__cmd_grab_D_call:Nw #1
1821     }
1822     {
1823       #7 { \group_end: }
1824       \__cmd_add_arg:o \c_novalue_tl
1825     }
1826   }
1827 \group_end:

```

The only awkwardness here is the need to preserve the catcode of the search token: this is done low-level for performance reasons. Only values that are realistic are included. As this does not cover spaces when they are skipped that has to be covered separately.

```

1828 \cs_new_protected:Npn \__cmd_grab_D_verb_safe:NN #1#2
1829 {
1830   \cs_set_eq:NN \do \char_set_catcode_other:N
1831   \dospecials
1832   \char_set_catcode_other:N \^^M
1833   \token_if_eq_meaning:NNT #2 \__cmd_peek_nonspace_remove:NTF
1834   { \char_set_catcode_space:n { '\ } }
1835   \use:c
1836   {
1837     char_set_catcode_
1838     \if_catcode:w \c_math_toggle_token #1 math_toggle \else:
1839     \if_catcode:w ^ #1 math_superscript \else:
1840     \if_catcode:w \c_math_subscript_token #1 math_subscript \else:
1841     \if_catcode:w A #1 letter \else:

```

```

1842         other \fi: \fi: \fi: \fi:
1843         :N
1844     }
1845     #1
1846 }

```

Inside the “standard” grabber, there is a test to see if the grabbed argument is entirely enclosed by braces. There are a couple of extra factors to allow for: the argument might be entirely empty, and spaces at the start and end of the input must be retained around a brace group. Also notice that a *blank* argument might still contain spaces. To allow for suppression of brace stripping, the business end is passed here as #5.

```

1847 \cs_new_protected:Npn \__cmd_grab_D_aux:NNnN #1#2#3#4#5
1848 {
1849     \tl_set:Nn \l__cmd_signature_tl {#3}
1850     \exp_after:wN #4 \l__cmd_fn_tl ##1 #2
1851     {
1852         \tl_if_in:nnTF {##1} {#1}
1853         { \__cmd_grab_D_nested:NNnN #1 #2 {##1} #4 }
1854         {
1855             \tl_if_blank:oTF { \use_none:n ##1 }
1856             { \__cmd_add_arg:o { \use_none:n ##1 } }
1857             {
1858                 \str_if_eq:eeTF
1859                 { \exp_not:o { \use_none:n ##1 } }
1860                 { { \exp_not:o { \use_ii:nnn ##1 \q_nil } } }
1861                 { \__cmd_add_arg:o { #5 ##1 } }
1862                 { \__cmd_add_arg:o { \use_none:n ##1 } }
1863             }
1864         }
1865     }
1866 }

```

(End of definition for \\_\_cmd\_grab\_D:w and others.)

```

\__cmd_grab_D_nested:NNnN
\__cmd_grab_D_nested:w
\l__cmd_nesting_a_tl
\l__cmd_nesting_b_tl
\q__cmd

```

Catching nested optional arguments means more work. The aim here is to collect up each pair of optional tokens without T<sub>E</sub>X helping out, and without counting anything. The code above will already have removed the leading opening token and a closing token, but the wrong one. The aim is then to work through the material grabbed so far and divide it up on each opening token, grabbing a closing token to match (thus working in pairs). Once there are no opening tokens, then there is a second check to see if there are any opening tokens in the second part of the argument (for things like `[] []`). Once everything has been found, the entire collected material is added to the output as a single argument. The only tricky part here is ensuring that any grabbing function that might run away is named after the function currently being parsed and not after `xparse`. That leads to some rather complex nesting! There is also a need to prevent the loss of any braces, hence the insertion and removal of quarks along the way.

```

1867 \tl_new:N \l__cmd_nesting_a_tl
1868 \tl_new:N \l__cmd_nesting_b_tl
1869 \quark_new:N \q__cmd
1870 \cs_new_protected:Npn \__cmd_grab_D_nested:NNnN #1#2#3#4
1871 {
1872     \tl_clear:N \l__cmd_nesting_a_tl
1873     \tl_clear:N \l__cmd_nesting_b_tl

```

```

1874 \exp_after:wN #4 \l__cmd_fn_tl ##1 #1 ##2 \q__cmd ##3 #2
1875 {
1876   \tl_put_right:No \l__cmd_nesting_a_tl { \use_none:n ##1 #1 }
1877   \tl_put_right:No \l__cmd_nesting_b_tl { \use_i:nn #2 ##3 }
1878   \tl_if_in:nnTF {##2} {#1}
1879   {
1880     \l__cmd_fn_tl
1881     \q_nil ##2 \q__cmd \ERROR
1882   }
1883   {
1884     \tl_put_right:Nx \l__cmd_nesting_a_tl
1885     { \__cmd_grab_D_nested:w \q_nil ##2 \q_stop }
1886     \tl_if_in:NnTF \l__cmd_nesting_b_tl {#1}
1887     {
1888       \tl_set_eq:NN \l__cmd_tmpa_tl \l__cmd_nesting_b_tl
1889       \tl_clear:N \l__cmd_nesting_b_tl
1890       \exp_after:wN \l__cmd_fn_tl \exp_after:wN
1891       \q_nil \l__cmd_tmpa_tl \q_nil \q__cmd \ERROR
1892     }
1893     {
1894       \tl_put_right:No \l__cmd_nesting_a_tl
1895       \l__cmd_nesting_b_tl
1896       \__cmd_add_arg:V \l__cmd_nesting_a_tl
1897     }
1898   }
1899 }
1900 \l__cmd_fn_tl #3 \q_nil \q__cmd \ERROR
1901 }
1902 \cs_new:Npn \__cmd_grab_D_nested:w #1 \q_nil \q_stop
1903 { \exp_not:o { \use_none:n #1 } }

```

(End of definition for \\_\_cmd\_grab\_D\_nested:NNnN and others.)

\\_\_cmd\_grab\_D\_call:Nw For D and R-type arguments, to avoid losing any braces, a token needs to be inserted before the argument to be grabbed. If the argument runs away because the closing token is missing then this inserted token shows up in the terminal. Ideally, #1 would therefore be used directly, but that is no good as it will mess up the rest of the grabber. Instead, a copy of #1 with an altered category code is used, as this will look right in the terminal but will not mess up the grabber. The only issue then is that the category code of #1 is unknown. So there is a quick test to ensure that the inserted token can never be matched by the grabber. (This assumes that the open and close delimiters are not the same character with different category codes, but that really should not happen in any sensible document-level syntax.) An exception is when #1 is a control sequence token, in which case the character-token treatment is no good because if hit with \token\_to\_str:N it would add sputios tokens to the argument. In this case a different branch is taken. The token inserted is then the same *<csname>* as #1, but with a space appended, so that the grabber don't see it as another of the same delimiter.

```

1904 \cs_new_protected_nopar:Npn \__cmd_grab_D_call:Nw #1
1905 {
1906   \token_if_eq_catcode:NNTF + #1
1907   {
1908     \exp_after:wN \exp_after:wN \exp_after:wN
1909     \l__cmd_fn_tl \char_generate:nn { ' #1 } { 11 }

```

```

1910     }
1911     {
1912         \__cmd_token_if_cs:NTF #1
1913         {
1914             \exp_after:wN \l__cmd_fn_tl
1915             \cs:w \cs_to_str:N #1 ~ \cs_end:
1916         }
1917         {
1918             \exp_after:wN \l__cmd_fn_tl
1919             \token_to_str:N #1
1920         }
1921     }
1922 }

```

(End of definition for \\_\_cmd\_grab\_D\_call:Nw.)

```

\__cmd_grab_E:w Everything here needs to point to a loop.
\__cmd_grab_E_long:w
\__cmd_grab_E_obey_spaces:w 1923 \cs_new_protected:Npn \__cmd_grab_E:w #1#2 \__cmd_run_code:
\__cmd_grab_E_long_obey_spaces:w 1924 {
\__cmd_grab_E:nnNN {#1} {#2} 1925 \__cmd_grab_E:nnNN {#1} {#2}
\__cmd_grab_E:nnNN 1926 \cs_set_protected_nopar:Npn
\__cmd_grab_E_loop:NnN 1927 \__cmd_peek_nonspace_remove:NTF
\__cmd_grab_E_finalise: 1928 }
1929 \cs_new_protected:Npn \__cmd_grab_E_long:w #1#2 \__cmd_run_code:
1930 {
1931     \__cmd_grab_E:nnNN {#1} {#2}
1932     \cs_set_protected:Npn
1933     \__cmd_peek_nonspace_remove:NTF
1934 }
1935 \cs_new_protected:Npn \__cmd_grab_E_obey_spaces:w #1#2 \__cmd_run_code:
1936 {
1937     \__cmd_grab_E:nnNN {#1} {#2}
1938     \cs_set_protected_nopar:Npn
1939     \__cmd_peek_meaning_remove:NTF
1940 }
1941 \cs_new_protected:Npn \__cmd_grab_E_long_obey_spaces:w #1#2 \__cmd_run_code:
1942 {
1943     \__cmd_grab_E:nnNN {#1} {#2}
1944     \cs_set_protected:Npn
1945     \__cmd_peek_meaning_remove:NTF
1946 }

```

A loop is needed here to allow a random ordering of keys. These are searched for one at a time, with any not found needing to be tracked: they can appear later. The grabbed values are held in a property list which is then turned into an ordered list to be passed back to the user.

```

1947 \cs_new_protected:Npn \__cmd_grab_E:nnNN #1#2#3#4
1948 {
1949     \exp_after:wN #3 \l__cmd_fn_tl ##1##2##3
1950     {
1951         \prop_put:Nnn \l__cmd_tmp_prop {##1} {##3}
1952         \__cmd_grab_E_loop:NnN #4 { } ##2 \q_recursion_stop
1953     }
1954     \prop_clear:N \l__cmd_tmp_prop

```

```

1955 \tl_set:Nn \l__cmd_signature_tl {#2}
1956 \cs_set_protected:Npn \__cmd_grab_E_finalise:
1957 {
1958   \tl_map_inline:nn {#1}
1959   {
1960     \prop_get:NnNF \l__cmd_tmp_prop {###1} \l__cmd_tmpb_tl
1961     { \tl_set_eq:NN \l__cmd_tmpb_tl \c_novalue_tl }
1962     \tl_put_right:Nx \l__cmd_args_tl
1963     { { \exp_not:V \l__cmd_tmpb_tl } }
1964   }
1965   \l__cmd_signature_tl \__cmd_run_code:
1966 }
1967 \__cmd_grab_E_loop:NnN #4 { } #1 \q_recursion_tail \q_recursion_stop
1968 }
1969 \cs_new_protected:Npn \__cmd_grab_E_loop:NnN #1#2#3#4 \q_recursion_stop
1970 {
1971   \cs_if_eq:NNTF #3 \q_recursion_tail
1972   { \__cmd_grab_E_finalise: }
1973   {
1974     #1 #3
1975     { \l__cmd_fn_tl #3 {#2#4} }
1976     { \__cmd_grab_E_loop:NnN #1 {#2#3} #4 \q_recursion_stop }
1977   }
1978 }
1979 \cs_new_protected:Npn \__cmd_grab_E_finalise: { }

```

(End of definition for \\_\_cmd\_grab\_E:w and others.)

```

\__cmd_grab_m:w Collecting a single mandatory argument is quite easy.
\__cmd_grab_m_long:w
1980 \cs_new_protected:Npn \__cmd_grab_m:w #1 \__cmd_run_code:
1981 {
1982   \tl_set:Nn \l__cmd_signature_tl {#1}
1983   \exp_after:wN \cs_set_protected_nopar:Npn \l__cmd_fn_tl ##1
1984   { \__cmd_add_arg:n {##1} }
1985   \l__cmd_fn_tl
1986 }
1987 \cs_new_protected:Npn \__cmd_grab_m_long:w #1 \__cmd_run_code:
1988 {
1989   \tl_set:Nn \l__cmd_signature_tl {#1}
1990   \exp_after:wN \cs_set_protected:Npn \l__cmd_fn_tl ##1
1991   { \__cmd_add_arg:n {##1} }
1992   \l__cmd_fn_tl
1993 }

```

(End of definition for \\_\_cmd\_grab\_m:w and \\_\_cmd\_grab\_m\_long:w.)

```

\__cmd_grab_m_1:w Grabbing 1–8 mandatory arguments is done by giving 8–1 known arguments to a 9-
\__cmd_grab_m_2:w argument function that stores them in \l__cmd_args_tl. For simplicity, grabbing 9
\__cmd_grab_m_3:w mandatory arguments is done by grabbing 5 then 4 arguments.
\__cmd_grab_m_4:w
1994 \cs_new_protected_nopar:Npn \__cmd_grab_m_aux:Nnnnnnnnn #1#2#3#4#5#6#7#8#9
\__cmd_grab_m_5:w {
\__cmd_grab_m_6:w   \tl_put_right:No \l__cmd_args_tl
\__cmd_grab_m_7:w   { #1 {#2} {#3} {#4} {#5} {#6} {#7} {#8} {#9} }
\__cmd_grab_m_8:w   \l__cmd_signature_tl \__cmd_run_code:
\__cmd_grab_m_9:w
\__cmd_grab_m_aux:Nnnnnnnnn

```

```

1999     }
2000 \cs_new_protected:cpn { __cmd_grab_m_1:w } #1 \__cmd_run_code:
2001     {
2002         \tl_set:Nn \l__cmd_signature_tl {#1}
2003         \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
2004         \l__cmd_fn_tl \use_none:nnnnnn { } { } { } { } { } { } { }
2005     }
2006 \cs_new_protected:cpn { __cmd_grab_m_2:w } #1 \__cmd_run_code:
2007     {
2008         \tl_set:Nn \l__cmd_signature_tl {#1}
2009         \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
2010         \l__cmd_fn_tl \use_none:nnnnnn { } { } { } { } { } { } { }
2011     }
2012 \cs_new_protected:cpn { __cmd_grab_m_3:w } #1 \__cmd_run_code:
2013     {
2014         \tl_set:Nn \l__cmd_signature_tl {#1}
2015         \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
2016         \l__cmd_fn_tl \use_none:nnnnnn { } { } { } { } { } { }
2017     }
2018 \cs_new_protected:cpn { __cmd_grab_m_4:w } #1 \__cmd_run_code:
2019     {
2020         \tl_set:Nn \l__cmd_signature_tl {#1}
2021         \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
2022         \l__cmd_fn_tl \use_none:nnnn { } { } { } { } { }
2023     }
2024 \cs_new_protected:cpn { __cmd_grab_m_5:w } #1 \__cmd_run_code:
2025     {
2026         \tl_set:Nn \l__cmd_signature_tl {#1}
2027         \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
2028         \l__cmd_fn_tl \use_none:nnn { } { } { } { }
2029     }
2030 \cs_new_protected:cpn { __cmd_grab_m_6:w } #1 \__cmd_run_code:
2031     {
2032         \tl_set:Nn \l__cmd_signature_tl {#1}
2033         \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
2034         \l__cmd_fn_tl \use_none:nn { } { } { } { }
2035     }
2036 \cs_new_protected:cpn { __cmd_grab_m_7:w } #1 \__cmd_run_code:
2037     {
2038         \tl_set:Nn \l__cmd_signature_tl {#1}
2039         \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
2040         \l__cmd_fn_tl \use_none:n { } { } { } { }
2041     }
2042 \cs_new_protected:cpn { __cmd_grab_m_8:w } #1 \__cmd_run_code:
2043     {
2044         \tl_set:Nn \l__cmd_signature_tl {#1}
2045         \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
2046         \l__cmd_fn_tl \prg_do_nothing:
2047     }
2048 \cs_new_protected:cpx { __cmd_grab_m_9:w }
2049     {
2050         \exp_not:c { __cmd_grab_m_5:w }
2051         \exp_not:c { __cmd_grab_m_4:w }
2052     }

```

(End of definition for `\__cmd_grab_m_1:w` and others.)

`\__cmd_grab_R:w` The grabber for R-type arguments is basically the same as that for D-type ones, but  
`\__cmd_grab_R_long:w` always skips spaces (as it is mandatory) and has a hard-coded error message.  
`\__cmd_grab_R_aux:NNnN`

```

2053 \cs_new_protected:Npn \__cmd_grab_R:w #1#2#3 \__cmd_run_code:
2054 { \__cmd_grab_R_aux:NNnN #1 #2 {#3} \cs_set_protected_nopar:Npn }
2055 \cs_new_protected:Npn \__cmd_grab_R_long:w #1#2#3 \__cmd_run_code:
2056 { \__cmd_grab_R_aux:NNnN #1 #2 {#3} \cs_set_protected:Npn }
2057 \cs_new_protected:Npn \__cmd_grab_R_aux:NNnN #1#2#3#4
2058 {
2059   \__cmd_grab_D_aux:NNnNN #1 #2 {#3} #4 \use_ii:nn
2060   \__cmd_peek_nonspace_remove:NTF #1
2061   { \__cmd_grab_D_call:Nw #1 }
2062   {
2063     \msg_error:nxxx { cmd } { missing-required }
2064     { \__cmd_environment_or_command: }
2065     { \token_to_str:N #1 }
2066     \__cmd_add_arg:o \c_novalue_tl
2067   }
2068 }
```

(End of definition for `\__cmd_grab_R:w`, `\__cmd_grab_R_long:w`, and `\__cmd_grab_R_aux:NNnN`.)

`\__cmd_grab_t:w` Dealing with a token is quite easy. Check the match, remove the token if needed and add  
`\__cmd_grab_t_obey_spaces:w` a flag to the output.  
`\__cmd_grab_t_aux:NNw`

```

2069 \cs_new_protected:Npn \__cmd_grab_t:w
2070 { \__cmd_grab_t_aux:NNw \__cmd_peek_nonspace_remove:NTF }
2071 \cs_new_protected:Npn \__cmd_grab_t_obey_spaces:w
2072 { \__cmd_grab_t_aux:NNw \__cmd_peek_meaning_remove:NTF }
2073 \cs_new_protected:Npn \__cmd_grab_t_aux:NNw #1#2#3 \__cmd_run_code:
2074 {
2075   \tl_set:Nn \l__cmd_signature_tl {#3}
2076   \exp_after:wN \cs_set_protected:Npn \l__cmd_fn_tl
2077   {
2078     #1 #2
2079     { \__cmd_add_arg:n { \BooleanTrue } }
2080     { \__cmd_add_arg:n { \BooleanFalse } }
2081   }
2082   \l__cmd_fn_tl
2083 }
```

(End of definition for `\__cmd_grab_t:w`, `\__cmd_grab_t_obey_spaces:w`, and `\__cmd_grab_t_aux:NNw`.)

---

`\l__cmd_v_arg_tl` 2084 `\tl_new:N \l__cmd_v_arg_tl`

`\__cmd_grab_v:w` Firstly, it is necessary to change `\tex_endlinechar:D` so that newlines in different cat-  
`\__cmd_grab_v_long:w` code regimes (e.g., `\ExplSyntaxOn`) are not misinterpreted as spaces. The opening de-  
`\__cmd_grab_v_aux:w` limiter is the first non-space token, and is never read verbatim. This is required by  
`\__cmd_grab_v_group_end:` consistency with the case where the preceding argument was optional and absent: then  
 $\TeX$  has already read and tokenized that token when looking for the optional argument.  
 The first thing is thus to check is that this delimiter is a character, and to distinguish

the case of a left brace (in that case, `\group_align_safe_end:` is needed to compensate for the begin-group character that was just seen). Then set verbatim catcodes with `\__cmd_grab_v_aux_catcodes:`.

The group keep catcode changes local, and `\group_align_safe_begin/end:` allow to use a character with category code 4 (normally `&`) as the delimiter (all commands do `\group_align_safe_begin/end:`, so there's no need to do that again here). It is ended by `\__cmd_grab_v_group_end:`, which smuggles the collected argument out of the group.

```

2085 \cs_new_protected:Npn \__cmd_grab_v:w
2086 {
2087   \bool_set_false:N \l__cmd_long_bool
2088   \__cmd_grab_v_aux:w
2089 }
2090 \cs_new_protected:Npn \__cmd_grab_v_long:w
2091 {
2092   \bool_set_true:N \l__cmd_long_bool
2093   \__cmd_grab_v_aux:w
2094 }
2095 \cs_new_protected:Npn \__cmd_grab_v_aux:w #1 \__cmd_run_code:
2096 {
2097   \tl_set:Nn \l__cmd_signature_tl {#1}
2098   \group_begin:
2099   \tex_escapechar:D = 92 \scan_stop:
2100   \tex_endlinechar:D = '\^M \scan_stop:
2101   \tl_clear:N \l__cmd_v_arg_tl
2102   \peek_remove_spaces:n
2103   {
2104     \peek_meaning_remove:NTF \c_group_begin_token
2105     {
2106       \group_align_safe_end:
2107       \__cmd_grab_v_bgroup:
2108     }
2109     {
2110       \peek_N_type:TF
2111       { \__cmd_grab_v_aux_test:N }
2112       { \__cmd_grab_v_aux_abort:n { } }
2113     }
2114   }
2115 }
2116 \cs_new_protected:Npn \__cmd_grab_v_group_end:
2117 {
2118   \exp_args:NNNo
2119   \group_end:
2120   \tl_set:Nn \l__cmd_v_arg_tl { \l__cmd_v_arg_tl }
2121 }

```

*(End of definition for `\__cmd_grab_v:w` and others.)*

<code>\__cmd_grab_v_aux_test:N</code> <code>\__cmd_grab_v_aux_loop:N</code> <code>\__cmd_grab_v_aux_loop:NN</code> <code>\__cmd_grab_v_aux_loop_end:</code>	<p>Check that the opening delimiter is a character, setup category codes, then start reading tokens one by one, keeping the delimiter as an argument. If the verbatim was not nested, we will be grabbing one character at each step. Unfortunately, it can happen that what follows the verbatim argument is already tokenized. Thus, we check at each step that the next token is indeed a “nice” character, <i>i.e.</i>, is not a character with category code</p>
--	---

1 (begin-group), 2 (end-group) or 6 (macro parameter), nor the space character, with category code 10 and character code 32, nor a control sequence. The partially built argument is stored in `\l__cmd_v_arg_tl`. If we ever meet a token which we cannot grab (non-N-type), or which is not a character according to `\__cmd_grab_v_token_if_char:N`, then we bail out with `\__cmd_grab_v_aux_abort:n`. Otherwise, we stop at the first character matching the delimiter.

```

2122 \cs_new_protected:Npn \__cmd_grab_v_aux_test:N #1
2123 {
2124   \__cmd_grab_v_token_if_char:N #1
2125   {
2126     \__cmd_grab_v_aux_put:N #1
2127     \__cmd_grab_v_aux_catcodes:
2128     \__cmd_grab_v_aux_loop:N #1
2129   }
2130   { \__cmd_grab_v_aux_abort:n {#1} #1 }
2131 }
2132 \cs_new_protected:Npn \__cmd_grab_v_aux_loop:N #1
2133 {
2134   \peek_N_type:TF
2135   { \__cmd_grab_v_aux_loop:NN #1 }
2136   { \__cmd_grab_v_aux_abort:n { } }
2137 }
2138 \cs_new_protected:Npn \__cmd_grab_v_aux_loop:NN #1#2
2139 {
2140   \__cmd_grab_v_token_if_char:N #2
2141   {
2142     \token_if_eq_charcode:NNTF #1 #2
2143     { \__cmd_grab_v_aux_loop_end: }
2144     {
2145       \__cmd_grab_v_aux_put:N #2
2146       \__cmd_grab_v_aux_loop:N #1
2147     }
2148   }
2149   { \__cmd_grab_v_aux_abort:n {#2} #2 }
2150 }
2151 \cs_new_protected:Npn \__cmd_grab_v_aux_loop_end:
2152 {
2153   \__cmd_grab_v_group_end:
2154   \__cmd_add_arg:x { \tl_tail:N \l__cmd_v_arg_tl }
2155 }

```

*(End of definition for `\__cmd_grab_v_aux_test:N` and others.)*

---

## `\l__cmd_v_nesting_int`

```

2156 \int_new:N \l__cmd_v_nesting_int

```

`\__cmd_grab_v_bgroup:` If the opening delimiter is a left brace, we keep track of how many left and right braces were encountered so far in `\l__cmd_v_nesting_int` (the methods used for optional arguments cannot apply here), and stop as soon as it reaches 0.

`\__cmd_grab_v_bgroup_loop:`  
`\__cmd_grab_v_bgroup_loop:N`

Some care was needed when removing the opening delimiter, which has already been assigned category code 1: using `\peek_meaning_remove:N` in the `\__cmd_grab_v_aux:w` function would break within alignments. Instead, we first convert that token to a string, and remove the result as a normal undelimited argument.

```

2157 \cs_new_protected:Npx \__cmd_grab_v_bgroup:
2158 {
2159   \exp_not:N \__cmd_grab_v_aux_catcodes:
2160   \exp_not:n { \int_set:Nn \l__cmd_v_nesting_int { 1 } }
2161   \exp_not:N \__cmd_grab_v_aux_put:N \iow_char:N \{
2162   \exp_not:N \__cmd_grab_v_bgroup_loop:
2163 }
2164 \cs_new_protected:Npn \__cmd_grab_v_bgroup_loop:
2165 {
2166   \peek_N_type:TF
2167   { \__cmd_grab_v_bgroup_loop:N }
2168   { \__cmd_grab_v_aux_abort:n { } }
2169 }
2170 \cs_new_protected:Npn \__cmd_grab_v_bgroup_loop:N #1
2171 {
2172   \__cmd_grab_v_token_if_char:NTF #1
2173   {
2174     \token_if_eq_charcode:NNTF \c_group_end_token #1
2175     {
2176       \int_decr:N \l__cmd_v_nesting_int
2177       \int_compare:nNnTF \l__cmd_v_nesting_int > 0
2178       {
2179         \__cmd_grab_v_aux_put:N #1
2180         \__cmd_grab_v_bgroup_loop:
2181       }
2182       { \__cmd_grab_v_aux_loop_end: }
2183     }
2184     {
2185       \token_if_eq_charcode:NNT \c_group_begin_token #1
2186       { \int_incr:N \l__cmd_v_nesting_int }
2187       \__cmd_grab_v_aux_put:N #1
2188       \__cmd_grab_v_bgroup_loop:
2189     }
2190   }
2191   { \__cmd_grab_v_aux_abort:n {#1} #1 }
2192 }

```

(End of definition for \\_\_cmd\_grab\_v\_bgroup:, \\_\_cmd\_grab\_v\_bgroup\_loop:, and \\_\_cmd\_grab\_v\_bgroup\_loop:N.)

\\_\_cmd\_grab\_v\_aux\_catcodes: The approach for short verbatim arguments is to make the end-line character a macro parameter character: this is forbidden by the rest of the code. Then the error branch can check what caused the bail out and give the appropriate error message.

```

2193 <latexrelease> \IncludeInRelease{2025/06/01}{\__cmd_grab_v_aux_catcodes:}%
2194 <latexrelease> {Active~spaces~and~tabs}
2195 \cs_new_protected:Npn \__cmd_grab_v_aux_catcodes:
2196 {
2197   \cs_set_eq:NN \do \char_set_catcode_other:N
2198   \dospecials
2199   \char_set_catcode_active:n { '\ }
2200   \char_set_catcode_active:n { '\^~I }
2201   \bool_if:NTF \l__cmd_long_bool
2202   { \char_set_catcode_other:n { \tex_endlinechar:D } }
2203   { \char_set_catcode_parameter:n { \tex_endlinechar:D } }

```

```

2204 }
2205 <latexrelease>\EndIncludeInRelease
2206 <latexrelease>\IncludeInRelease{2020/10/01}{\__cmd_grab_v_aux_catcodes}%
2207 <latexrelease> {Active~spaces~and~tabs}
2208 <latexrelease>\cs_new_protected:Npn \__cmd_grab_v_aux_catcodes:
2209 <latexrelease> {
2210 <latexrelease> \cs_set_eq:NN \do \char_set_catcode_other:N
2211 <latexrelease> \dospecials
2212 <latexrelease> \bool_if:NTF \l__cmd_long_bool
2213 <latexrelease> { \char_set_catcode_other:n { \tex_endlinechar:D } }
2214 <latexrelease> { \char_set_catcode_parameter:n { \tex_endlinechar:D } }
2215 <latexrelease> }
2216 <latexrelease>\EndIncludeInRelease
2217 \cs_new_protected:Npn \__cmd_grab_v_aux_abort:n #1
2218 {
2219 \__cmd_grab_v_group_end:
2220 \exp_after:wN \exp_after:wN \exp_after:wN
2221 \peek_meaning_remove:NTF \char_generate:nn { \tex_endlinechar:D } { 6 }
2222 {
2223 \msg_error:nnxxx { cmd } { verbatim-nl }
2224 { \__cmd_environment_or_command: }
2225 { \tl_to_str:N \l__cmd_v_arg_tl }
2226 { \tl_to_str:n {#1} }
2227 \__cmd_add_arg:o \c_novalue_tl
2228 }
2229 {
2230 \msg_error:nnxxx { cmd } { verbatim-tokenized }
2231 { \__cmd_environment_or_command: }
2232 { \tl_to_str:N \l__cmd_v_arg_tl }
2233 { \tl_to_str:n {#1} }
2234 \__cmd_add_arg:o \c_novalue_tl
2235 }
2236 }

```

(End of definition for \\_\_cmd\_grab\_v\_aux\_catcodes: and \\_\_cmd\_grab\_v\_aux\_abort:n.)

\\_\_cmd\_grab\_v\_aux\_put:N Storing one token in the collected argument: everything as-is except for end-of-lines, with \exp\_not:N to handle actives.

```

2237 <latexrelease>\IncludeInRelease{2025-06-01}{\__cmd_grab_v_aux_put:N}%
2238 <latexrelease> {Use~more~std~catcodes}
2239 \cs_new_protected:Npn \__cmd_grab_v_aux_put:N #1
2240 {
2241 \tl_put_right:Nx \l__cmd_v_arg_tl
2242 {
2243 \int_compare:nNnTF {'#1} = \tex_endlinechar:D
2244 { \exp_not:N \obeyedline }
2245 { \exp_not:N #1 }
2246 }
2247 }
2248 <latexrelease>\EndIncludeInRelease
2249 <latexrelease>\IncludeInRelease{2024/06/01}{\__cmd_grab_v_aux_put:N}%
2250 <latexrelease> {Endlines~as~\obeyedline}
2251 <latexrelease>\cs_new_protected:Npn \__cmd_grab_v_aux_put:N #1
2252 <latexrelease> {

```

```

2253 <latexrelease> \tl_put_right:Nx \l__cmd_v_arg_tl
2254 <latexrelease> {
2255 <latexrelease> \token_if_active:NTF #1
2256 <latexrelease> { \exp_not:N #1 }
2257 <latexrelease> {
2258 <latexrelease> \int_compare:nNnTF {‘#1} = \tex_endlinechar:D
2259 <latexrelease> { \exp_not:N \obeyedline }
2260 <latexrelease> { \token_to_str:N #1 }
2261 <latexrelease> }
2262 <latexrelease> }
2263 <latexrelease> }
2264 <latexrelease> \EndIncludeInRelease
2265 <latexrelease> \IncludeInRelease{2020/10/01}{\__cmd_grab_v_aux_put:N}%
2266 <latexrelease> {Endlines~as~\obeyedline}
2267 <latexrelease> \cs_new_protected:Npn \__cmd_grab_v_aux_put:N #1
2268 <latexrelease> {
2269 <latexrelease> \tl_put_right:Nx \l__cmd_v_arg_tl
2270 <latexrelease> {
2271 <latexrelease> \token_if_active:NTF #1
2272 <latexrelease> { \exp_not:N #1 } { \token_to_str:N #1 }
2273 <latexrelease> }
2274 <latexrelease> }
2275 <latexrelease> \EndIncludeInRelease

```

(End of definition for \\_\_cmd\_grab\_v\_aux\_put:N.)

\\_\_cmd\_grab\_v\_token\_if\_char:N

This function assumes that the escape character is printable. Then the string representation of control sequences is at least two characters, and \str\_tail:n only removes the escape character. Macro parameter characters are doubled by \tl\_to\_str:n, and will also yield a non-empty result, hence are not considered as characters.

```

2276 \cs_new_protected:Npn \__cmd_grab_v_token_if_char:N #1
2277 { \str_if_eq:eeTF { } { \str_tail:n {#1} } }

```

(End of definition for \\_\_cmd\_grab\_v\_token\_if\_char:N.)

\\_\_cmd\_add\_arg:n  
\\_\_cmd\_add\_arg:V  
\\_\_cmd\_add\_arg:o  
\\_\_cmd\_add\_arg:x

When an argument is found it is stored, then further arguments are grabbed by calling \l\_\_cmd\_signature\_tl.

```

2278 \cs_new_protected:Npn \__cmd_add_arg:n #1
2279 {
2280 \tl_put_right:Nn \l__cmd_args_tl { {#1} }
2281 \l__cmd_signature_tl \__cmd_run_code:
2282 }
2283 \cs_generate_variant:Nn \__cmd_add_arg:n { V , o , x }

```

(End of definition for \\_\_cmd\_add\_arg:n.)

## 1.9 Grabbing arguments expandably

\\_\_cmd\_expandable\_grab\_D:w  
\\_\_cmd\_expandable\_grab\_D:NNNwNNn  
\\_\_cmd\_expandable\_grab\_D:NNNwNNnn  
\\_\_cmd\_expandable\_grab\_D:Nw  
\\_\_cmd\_expandable\_grab\_D:nnNNwNN

The first step is to grab the first token or group. The generic grabbers \<function>\_ and \<function>\_ are just after \q\_\_cmd, we go and find them (and use the long one).

```

2284 \cs_new:Npn \__cmd_expandable_grab_D:w #1 \q__cmd #2#3
2285 { #2 { \__cmd_expandable_grab_D:NNNwNNn #1 \q__cmd #2 #3 } }

```

We then wish to test whether #7, which we just grabbed, is exactly #2. A preliminary test is whether their string representations coincide, then expand the only grabber function we have, #1, once: the two strings below are equal if and only if #7 matches #2 exactly.<sup>2</sup> The preliminary test is needed as #7 could validly contain \par (because a later mandatory argument could be long) and our grabber may be short. If #7 does not match #2, then the optional argument is missing, we use the default -NoValue-, and put back the argument #7 in the input stream.

If it does match, then interesting things need to be done. We will grab the argument piece by piece, with the following pattern:

```

<grabber> {<tokens>}
\q_nil {<piece 1>} <piece 2> \ERROR \q__cmd
\q_nil <input stream>

```

The <grabber> will find an opening delimiter in <piece 2>, take the \q\_\_cmd as a second delimiter, and find more material delimited by the closing delimiter in the <input stream>. We then move the part before the opening delimiter from <piece 2> to <piece 1>, and the material taken from the <input stream> to the <piece 2>. Thus, the argument moves gradually from the <input stream> to the <piece 2>, then to the <piece 1> when we have made sure to find all opening and closing delimiters. This two-step process ensures that nesting works: the number of opening delimiters minus closing delimiters in <piece 1> is always equal to the number of closing delimiters in <piece 2>. We stop grabbing arguments once the <piece 2> contains no opening delimiter any more, hence the balance is reached, and the final argument is <piece 1> <piece 2>. The indirection via \\_\_cmd\_tmp:w allows to insert -NoValue- expanded.

```

2286 \cs_set_protected:Npn \__cmd_tmp:w #1
2287 {
2288   \cs_new:Npn \__cmd_expandable_grab_D:NNNwNNn ##1##2##3##4 \q__cmd ##5##6##7
2289   {
2290     \str_if_eq:nnTF {##2} {##7}
2291     {
2292       \str_if_eq:onTF
2293       { ##1 { } { } ##7 ##2 \q__cmd ##3 }
2294       { { } {##2} { } }
2295     }
2296     { \use_ii:nn }
2297     {
2298       ##1
2299       { \__cmd_expandable_grab_D:NNNwNNnn ##1##2##3##4 \q__cmd ##5##6 }
2300       \q_nil { } ##2 \ERROR \q__cmd \ERROR
2301     }
2302     { ##4 {##1} \q__cmd ##5 ##6 {##7} }
2303   }
2304 }
2305 \exp_args:No \__cmd_tmp:w { \c_novalue_tl }

```

<sup>2</sup>It is obvious that if #7 matches #2 then the strings are equal. We must check the converse. The right-hand-side of \str\_if\_eq:onTF does not end with #3, implying that the grabber function took everything as its arguments. The first brace group can only be empty if #7 starts with #2, otherwise the brace group preceding #7 would not vanish. The third brace group is empty, thus the \q\_\_cmd that was used by our grabber #1 must be the one that we inserted (not some token in #7), hence the second brace group contains the end of #7 followed by #2. Since this is #2 on the right-hand-side, and no brace can be lost there, #7 must contain nothing else than its leading #2.

At this stage, #7 is `\q_nil {<piece 1>} <more for piece 1>`, and we want to concatenate all that, removing `\q_nil`, and keeping the opening delimiter #2. Simply use `\use_ii:nn`. Also, #8 is `<remainder of piece 2> \ERROR`, and #9 is `\ERROR <more for piece 2>`. We concatenate those, replacing the two `\ERROR` by the closing delimiter #3.

```

2306 \cs_new:Npn \__cmd_expandable_grab_D:NNNwNNnnn #1#2#3#4 \q__cmd #5#6#7#8#9
2307 {
2308   \exp_args:Nof \__cmd_expandable_grab_D:nnNNwNN
2309   { \use_ii:nn #7 #2 }
2310   { \__cmd_expandable_grab_D:Nw #3 \exp_stop_f: #8 #9 }
2311   #1#2#3 #4 \q__cmd #5 #6
2312 }
2313 \cs_new:Npn \__cmd_expandable_grab_D:Nw #1#2 \ERROR \ERROR { #2 #1 }

```

Armed with our two new `<pieces>`, we are ready to loop. However, we must first see if `<piece 2>` (here #2) contains any opening delimiter #4. Again, we expand #3, this time removing its whole output with `\use_none:nnn`. The test is similar to `\tl_if_in:nnTF`. The token list is empty if and only if #2 does not contain the opening delimiter. In that case, we are done, and put the argument (from which we remove a spurious pair of delimiters coming from how we started the loop). Otherwise, we go back to looping with `\__cmd_expandable_grab_D:NNNwNNnnn`. The code to deal with brace stripping is much the same as for the non-expandable case.

```

2314 \cs_new:Npn \__cmd_expandable_grab_D:nnNNwNN #1#2#3#4#5#6 \q__cmd #7#8
2315 {
2316   \exp_args:No \tl_if_empty:oTF
2317   { #3 { \use_none:nnn } #2 \q__cmd #5 #4 \q__cmd #5 }
2318   {
2319     \tl_if_blank:oTF { \use_none:nn #1#2 }
2320     { \__cmd_put_arg_expandable:ow { \use_none:nn #1#2 } }
2321     {
2322       \str_if_eq:eeTF
2323       { \exp_not:o { \use_none:nn #1#2 } }
2324       { { \exp_not:o { \use_iii:nnnn #1#2 \q_nil } } }
2325       { \__cmd_put_arg_expandable:ow { \use_iii:nnn #1#2 } }
2326       { \__cmd_put_arg_expandable:ow { \use_none:nn #1#2 } }
2327     }
2328     #6 \q__cmd #7 #8
2329   }
2330   {
2331     #3
2332     { \__cmd_expandable_grab_D:NNNwNNnnn #3#4#5#6 \q__cmd #7 #8 }
2333     \q_nil {#1} #2 \ERROR \q__cmd \ERROR
2334   }
2335 }

```

(End of definition for `\__cmd_expandable_grab_D:w` and others.)

```

\__cmd_expandable_grab_D_alt:w
\__cmd_expandable_grab_D_alt:NNwNNn
\__cmd_expandable_grab_D_alt:Nwn

```

When the delimiters are identical, nesting is not possible and a simplified approach is used. The test concept here is the same as for the case where the delimiters are different but there cannot be any nesting.

```

2336 \cs_new:Npn \__cmd_expandable_grab_D_alt:w #1 \q__cmd #2#3
2337 { #2 { \__cmd_expandable_grab_D_alt:NNwNNn #1 \q__cmd #2 #3 } }
2338 \cs_set_protected:Npn \__cmd_tmp:w #1
2339 {

```

```

2340 \cs_new:Npn \__cmd_expandable_grab_D_alt:NNwNNn ##1##2##3 \q__cmd ##4##5##6
2341 {
2342   \str_if_eq:nnTF {##6} {##2}
2343   {
2344     \str_if_eq:onTF
2345     { ##1 { } ##6 ##2 ##2 }
2346     { { } ##2 }
2347   }
2348   { \use_ii:nn }
2349   {
2350     ##1
2351     { \__cmd_expandable_grab_D_alt:NNwn ##4 ##5 ##3 \q__cmd }
2352     ##6 \ERROR
2353   }
2354   { ##3 {##1} \q__cmd ##4 ##5 {##6} }
2355 }
2356 }
2357 \exp_args:No \__cmd_tmp:w { \c_novalue_tl }
2358 \cs_new:Npn \__cmd_expandable_grab_D_alt:NNwn #1#2#3 \q__cmd #4
2359 {
2360   \tl_if_blank:oTF { \use_none:n #4 }
2361   { \__cmd_put_arg_expandable:ow { \use_none:n #4 } }
2362   {
2363     \str_if_eq:eeTF
2364     { \exp_not:o { \use_none:n #4 } }
2365     { { \exp_not:o { \use_ii:nnn #4 \q_nil } } }
2366     { \__cmd_put_arg_expandable:ow { \use_ii:nn #4 } }
2367     { \__cmd_put_arg_expandable:ow { \use_none:n #4 } }
2368   }
2369   #3 \q__cmd #1 #2
2370 }

```

(End of definition for \\_\_cmd\_expandable\_grab\_D\_alt:w, \\_\_cmd\_expandable\_grab\_D\_alt:NNwNNn, and \\_\_cmd\_expandable\_grab\_D\_alt:Nwn.)

\\_\_cmd\_expandable\_grab\_E:w  
 \\_\_cmd\_expandable\_grab\_E\_long:w  
 \\_\_cmd\_expandable\_grab\_E\_aux:w  
 \\_\_cmd\_expandable\_grab\_E\_test:nnw  
 \\_\_cmd\_expandable\_grab\_E\_loop:nnnNNw  
 \\_\_cmd\_expandable\_grab\_E\_find:w  
 \\_\_cmd\_expandable\_grab\_E\_find:nnw  
 \\_\_cmd\_expandable\_grab\_E\_end:nnw

We keep track of long/short by placing the appropriate grabber as the third token after \q\_\_cmd; it is eventually removed by the end:nnw auxiliary. The aux:w auxiliary will be called repeatedly with two arguments: the set of pairs *<parser>* *<token>*, and the set of arguments found so far (initially all {-NoValue-}). At each step, grab what follows in the input stream then call the loop:nnnNNw auxiliary to compare it with each possible embellishment in turn. This auxiliary's #1 is what was found in the input, #2 collects *<parser>* *<token>* pairs that did not match, #3 collects the corresponding arguments found previously, #4 and #5 is the current pair, #6 is the remaining pairs, #7 is empty or two \q\_nil, and #8 is the current argument. If none of the pairs matched (determined by \quark\_if\_nil:NTF) then call the end auxiliary to stop looking for embellishments, remembering to put what was grabbed in the input back where it belongs, and storing the arguments found just before \q\_\_cmd. If the current argument #8 is not -NoValue- or if the input #1 does not match #5 (see t-type arguments below for a similar \str\_if\_eq:onTF test) then carry on the loop. Otherwise, we found a new embellishment: grab the corresponding argument in the input using the find:w auxiliary. To avoid losing braces around that auxiliary's argument we include a space, which will be eliminated in the next loop through embellishments.

```

2371 \cs_new:Npn \__cmd_expandable_grab_E:w #1 \q__cmd #2#3

```

```

2372 { \__cmd_expandable_grab_E_aux:w #1 \q__cmd #2 #3 #3 }
2373 \cs_new:Npn \__cmd_expandable_grab_E_long:w #1 \q__cmd #2#3
2374 { \__cmd_expandable_grab_E_aux:w #1 \q__cmd #2 #3 #2 }
2375 \cs_new:Npn \__cmd_expandable_grab_E_aux:w #1 \q__cmd #2#3#4
2376 { #2 { \__cmd_expandable_grab_E_test:nnw #1 \q__cmd #2 #3 #4 } }
2377 \cs_new:Npn \__cmd_expandable_grab_E_test:nnw #1#2#3 \q__cmd #4#5#6#7
2378 {
2379   \__cmd_expandable_grab_E_loop:nnnNNw {#7} { } { }
2380   #1 \q_nil \q_nil \q_nil \q_mark #2 \q_nil
2381   #3 \q__cmd #4 #5 #6
2382 }
2383 \cs_new:Npn \__cmd_expandable_grab_E_loop:nnnNNw
2384 #1#2#3#4#5#6 \q_nil #7 \q_mark #8
2385 {
2386   \quark_if_nil:NTF #4
2387   { \__cmd_expandable_grab_E_end:nnw {#1} {#3} }
2388   {
2389     \tl_if_novalue:NTF {#8}
2390     { \str_if_eq:onTF { #4 { } #1 #5 } {#5} }
2391     { \use_ii:nn }
2392     { \__cmd_expandable_grab_E_find:w { #2 #4 #5 #6 } {#3} ~ }
2393     {
2394       \__cmd_expandable_grab_E_loop:nnnNNw
2395       {#1} { #2 #4 #5 } { #3 {#8} }
2396       #6 \q_nil #7 \q_mark
2397     }
2398   }
2399 }
2400 \cs_new:Npn \__cmd_expandable_grab_E_find:w #1 \q__cmd #2#3#4
2401 { #4 { \__cmd_expandable_grab_E_find:nnw #1 \q__cmd #2 #3 #4 } }
2402 \cs_new:Npn \__cmd_expandable_grab_E_find:nnw #1#2#3 \q_nil #4 \q__cmd #5#6#7#8
2403 { \__cmd_expandable_grab_E_aux:w {#1} { #2 {#8} #3 } #4 \q__cmd #5 #6 #7 }
2404 \cs_new:Npn \__cmd_expandable_grab_E_end:nnw #1#2#3 \q__cmd #4#5#6
2405 { #3 #2 \q__cmd #4 #5 {#1} }

```

(End of definition for \\_\_cmd\_expandable\_grab\_E:w and others.)

\\_\_cmd\_expandable\_grab\_m:w The mandatory case is easy: find the auxiliary after the \q\_\_cmd, and use it directly to grab the argument, then correctly position the argument before \q\_\_cmd.

```

2406 \cs_new:Npn \__cmd_expandable_grab_m:w #1 \q__cmd #2#3
2407 { #3 { \__cmd_expandable_grab_m_aux:wNn #1 \q__cmd #2 #3 } }
2408 \cs_new:Npn \__cmd_expandable_grab_m_long:w #1 \q__cmd #2#3
2409 { #2 { \__cmd_expandable_grab_m_aux:wNn #1 \q__cmd #2 #3 } }
2410 \cs_new:Npn \__cmd_expandable_grab_m_aux:wNn #1 \q__cmd #2#3#4
2411 { #1 {#4} \q__cmd #2 #3 }

```

(End of definition for \\_\_cmd\_expandable\_grab\_m:w, \\_\_cmd\_expandable\_grab\_m\_long:w, and \\_\_cmd\_expandable\_grab\_m\_aux:wNn.)

\\_\_cmd\_expandable\_grab\_R:w Much the same as for the D-type argument, with only the lead-off function varying.

```

2412 \cs_new:Npn \__cmd_expandable_grab_R:w #1 \q__cmd #2#3
2413 { #2 { \__cmd_expandable_grab_R_aux:NNwNNn #1 \q__cmd #2#3 } }
2414 \cs_set_protected:Npn \__cmd_tmp:w #1
2415 {
2416   \cs_new:Npn \__cmd_expandable_grab_R_aux:NNwNNn ##1##2##3##4 \q__cmd ##5##6##7

```

```

2417 {
2418   \str_if_eq:nnTF {##7} {##2}
2419   {
2420     \str_if_eq:onTF
2421     { ##1 { } { } } ##7 ##2 \q__cmd ##3 }
2422     { { } {##2} { } }
2423   }
2424   { \use_ii:nn }
2425   {
2426     ##1
2427     { \__cmd_expandable_grab_D:NNwNNnnn ##1##2##3##4 \q__cmd ##5##6 }
2428     \q__nil { } ##2 \ERROR \q__cmd \ERROR
2429   }
2430   {
2431     \msg_expandable_error:nnff { cmd } { missing-required }
2432     { \exp_args:Nf \tl_trim_spaces:n { \token_to_str:N ##5 } }
2433     { \tl_to_str:n {##2} }
2434     ##4 {#1} \q__cmd ##5 ##6 {##7}
2435   }
2436 }
2437 }
2438 \exp_args:No \__cmd_tmp:w { \c_novalue_tl }

```

(End of definition for \\_\_cmd\_expandable\_grab\_R:w and \\_\_cmd\_expandable\_grab\_R\_aux:NNwNNn.)

\\_\_cmd\_expandable\_grab\_R\_alt:w  
 \\_\_cmd\_expandable\_grab\_R\_alt\_aux:NNwNNn

When the delimiters are identical, nesting is not possible and a simplified approach is used. The test concept here is the same as for the case where the delimiters are different.

```

2439 \cs_new:Npn \__cmd_expandable_grab_R_alt:w #1 \q__cmd #2#3
2440 { #2 { \__cmd_expandable_grab_R_alt_aux:NNwNNn #1 \q__cmd #2#3 } }
2441 \cs_set_protected:Npn \__cmd_tmp:w #1
2442 {
2443   \cs_new:Npn \__cmd_expandable_grab_R_alt_aux:NNwNNn ##1##2##3 \q__cmd ##4##5##6
2444   {
2445     \str_if_eq:nnTF {##6} {##2}
2446     {
2447       \str_if_eq:onTF
2448       { ##1 { } ##6 ##2 ##2 }
2449       { { } ##2 }
2450     }
2451     { \use_ii:nn }
2452     {
2453       ##1
2454       { \__cmd_expandable_grab_D_alt:NNwn ##4 ##5 ##3 \q__cmd }
2455       ##6 \ERROR
2456     }
2457     {
2458       \msg_expandable_error:nnff { cmd } { missing-required }
2459       { \exp_args:Nf \tl_trim_spaces:n { \token_to_str:N ##4 } }
2460       { \tl_to_str:n {##2} }
2461       ##3 {#1} \q__cmd ##4 ##5 {##6}
2462     }
2463   }
2464 }
2465 \exp_args:No \__cmd_tmp:w { \c_novalue_tl }

```

(End of definition for `\_cmd_expandable_grab_R_alt:w` and  
`\_cmd_expandable_grab_R_alt_aux:NNwNNn`.)

`\_cmd_expandable_grab_t:w` As for a D-type argument, here we compare the grabbed tokens using the only parser we  
`\_cmd_expandable_grab_t_aux:NNwn` have in order to work out if #2 is exactly equal to the output of the grabber.

```
2466 \cs_new:Npn \_cmd_expandable_grab_t:w #1 \q__cmd #2#3
2467   { #2 { \_cmd_expandable_grab_t_aux:NNwn #1 \q__cmd #2 #3 } }
2468 \cs_new:Npn \_cmd_expandable_grab_t_aux:NNwn #1#2#3 \q__cmd #4#5#6
2469   {
2470     \str_if_eq:onTF { #1 { } #6 #2 } {#2}
2471     { #3 { \BooleanTrue } \q__cmd #4 #5 }
2472     { #3 { \BooleanFalse } \q__cmd #4 #5 {#6} }
2473   }
```

(End of definition for `\_cmd_expandable_grab_t:w` and `\_cmd_expandable_grab_t_aux:NNwn`.)

`\_cmd_put_arg_expandable:nw` A useful helper, to store arguments when they are ready.

`\_cmd_put_arg_expandable:ow` 2474 \cs\_new:Npn \\_cmd\_put\_arg\_expandable:nw #1#2 \q\_\_cmd { #2 {#1} \q\_\_cmd }  
2475 \cs\_generate\_variant:Nn \\_cmd\_put\_arg\_expandable:nw { o }

(End of definition for `\_cmd_put_arg_expandable:nw`.)

## 1.10 Argument processors

`\_cmd_bool_reverse:N` A simple reversal.

```
2476 \cs_new_protected:Npn \_cmd_bool_reverse:N #1
2477   {
2478     \bool_if:NTF #1
2479     { \tl_set:Nn \ProcessedArgument { \c_false_bool } }
2480     { \tl_set:Nn \ProcessedArgument { \c_true_bool } }
2481   }
```

(End of definition for `\_cmd_bool_reverse:N`.)

---

<code>\l__cmd_split_list_seq</code> <code>\l__cmd_split_list_tl</code> <code>\__cmd_split_list_multi:nn</code> <code>\__cmd_split_list_multi:nV</code> <code>\__cmd_split_list_single:Nn</code>	<p>Splitting can take place either at a single token or at a longer identifier. To deal with single active tokens, a two-part procedure is needed.</p> <pre> 2482 \seq_new:N \l__cmd_split_list_seq 2483 \tl_new:N \l__cmd_split_list_tl 2484 \cs_new_protected:Npn \__cmd_split_list:nn #1#2 2485 { 2486   \tl_if_single:nTF {#1} 2487   { 2488     \token_if_cs:NTF #1 2489     { \__cmd_split_list_multi:nn {#1} {#2} } 2490     { \__cmd_split_list_single:Nn #1 {#2} } 2491   } 2492   { \__cmd_split_list_multi:nn {#1} {#2} } 2493 } 2494 \cs_new_protected:Npn \__cmd_split_list_multi:nn #1#2 2495 { 2496   \seq_set_split:Nnn \l__cmd_split_list_seq {#1} {#2} 2497   \tl_clear:N \ProcessedArgument 2498   \seq_map_inline:Nn \l__cmd_split_list_seq 2499   { \tl_put_right:Nn \ProcessedArgument { {##1} } } 2500 } 2501 \cs_generate_variant:Nn \__cmd_split_list_multi:nn { nV } 2502 \group_begin: 2503 \char_set_catcode_active:N ^^@ 2504 \cs_new_protected:Npn \__cmd_split_list_single:Nn #1#2 2505 { 2506   \tl_set:Nn \l__cmd_split_list_tl {#2} 2507   \group_begin: 2508   \char_set_lccode:nn { '^^@ } { '#1 } 2509   \tex_lowercase:D 2510   { 2511     \group_end: 2512     \tl_replace_all:Nnn \l__cmd_split_list_tl { ^^@ } 2513     } {#1} 2514   \__cmd_split_list_multi:nV {#1} \l__cmd_split_list_tl 2515 } 2516 \group_end: </pre> <p><i>(End of definition for \__cmd_split_list:nn, \__cmd_split_list_multi:nn, and \__cmd_split_list_single:Nn.)</i></p>
---	--

  

<code>\__cmd_split_argument:nnn</code> <code>\__cmd_split_argument_aux:nnnn</code> <code>\__cmd_split_argument_aux:n</code> <code>\__cmd_split_argument_aux:wn</code>	<p>Splitting to a known number of items is a special version of splitting a list, in which the limit is hard-coded and where there will always be exactly the correct number of output items. An auxiliary function is used to save on working out the token list length several times.</p> <pre> 2517 \cs_new_protected:Npn \__cmd_split_argument:nnn #1#2#3 2518 { 2519   \__cmd_split_list:nn {#2} {#3} 2520   \exp_args:Nf \__cmd_split_argument_aux:nnnn 2521   { \tl_count:N \ProcessedArgument } 2522   {#1} {#2} {#3} 2523 } </pre>
--	---

```

2524 \cs_new_protected:Npn \__cmd_split_argument_aux:nnnn #1#2#3#4
2525 {
2526   \int_compare:nNnF {#1} = { #2 + 1 }
2527   {
2528     \int_compare:nNnTF {#1} > { #2 + 1 }
2529     {
2530       \tl_set:Nx \ProcessedArgument
2531       {
2532         \exp_last_unbraced:NnNo
2533         \__cmd_split_argument_aux:n
2534         { #2 + 1 }
2535         \use_none_delimit_by_q_stop:w
2536         \ProcessedArgument
2537         \q_stop
2538       }
2539       \msg_error:nnxxx { cmd } { arg-split }
2540       { \tl_to_str:n {#3} } { \int_eval:n { #2 + 1 } }
2541       { \tl_to_str:n {#4} }
2542     }
2543   {
2544     \tl_put_right:Nx \ProcessedArgument
2545     {
2546       \prg_replicate:nn { #2 + 1 - (#1) }
2547       { { \exp_not:V \c_novalue_tl } }
2548     }
2549   }
2550 }
2551 }

```

Auxiliaries to leave exactly the correct number of arguments in \ProcessedArgument.

```

2552 \cs_new:Npn \__cmd_split_argument_aux:n #1
2553 { \prg_replicate:nn {#1} { \__cmd_split_argument_aux:wn } }
2554 \cs_new:Npn \__cmd_split_argument_aux:wn #1 \use_none_delimit_by_q_stop:w #2
2555 {
2556   \exp_not:n { {#2} }
2557   #1
2558   \use_none_delimit_by_q_stop:w
2559 }

```

(End of definition for \\_\_cmd\_split\_argument:nnn and others.)

\\_\_cmd\_trim\_spaces:n This one is almost trivial.

```

2560 \cs_new_protected:Npn \__cmd_trim_spaces:n #1
2561 { \tl_set:Nx \ProcessedArgument { \tl_trim_spaces:n {#1} } }

```

(End of definition for \\_\_cmd\_trim\_spaces:n.)

## 1.11 Conversion to key–value form

This is implemented as a process but with no public interfaces, hence is treated separately from the others: it's a feature of ltcmd which just happens to use the same mechanism as a processor.

```

\__cmd_arg_to_keyvalue:nn
  \__cmd_arg_to_keyvalue_braces:nnn
  \__cmd_arg_to_keyvalue_auxi:nnn
  \__cmd_arg_to_keyvalue_auxii:Nnnn
  \__cmd_arg_to_keyvalue_auxiii:nnn
  \__cmd_arg_to_keyvalue_auxiv:Nnnn
  \__cmd_arg_to_keyvalue_loop:w
\__cmd_arg_to_keyvalue_loop_group:n
\__cmd_arg_to_keyvalue_loop_space:w
\__cmd_arg_to_keyvalue_loop_N_type:N
  \__cmd_arg_to_keyvalue_math:w
\__cmd_arg_to_keyvalue_math_N_type:N
\__cmd_arg_to_keyvalue_math_group:n
\__cmd_arg_to_keyvalue_math_space:w
\__cmd_arg_to_keyvalue_set_default:nn
\__cmd_arg_to_keyvalue_set_keyvalue:nn
\__cmd_split_N_head_apply:Nn
  \__cmd_split_N_head_apply_aux:NNw

```

If the entire argument is braced, we treat as free text and return as the value for the text key. Alternatively, if the start of the input is =, then it is forced to be key-value. To avoid needing to worry about catcodes for this, and to allow spaces around the =, we use a series of steps rather than a delimited argument.

```

2562 \cs_new_protected:Npn \__cmd_arg_to_keyvalue:nn #1#2
2563 {
2564   \tl_trim_spaces_apply:nN {#2} \__cmd_arg_to_keyvalue_braces:nnn
2565   {#1} {#2}
2566 }
2567 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_braces:nnn #1#2#3
2568 {
2569   \tl_if_head_is_group:nT {#1}
2570   {
2571     \tl_if_blank:oT { \use_none:n #1 }
2572     {
2573       \tl_set:Nx \ProcessedArgument { #2 = { \exp_not:n #1 } }
2574       \use_none:nnnn
2575     }
2576   }
2577   \__cmd_arg_to_keyvalue_auxi:nnn {#1} {#2} {#3}
2578 }
2579 \cs_new:Npn \__cmd_arg_to_keyvalue_auxi:nnn #1
2580 {
2581   \tl_if_head_is_N_type:nTF {#1}
2582   { \__cmd_split_N_head_apply:Nn \__cmd_arg_to_keyvalue_auxii:Nnnn {#1} }
2583   { \__cmd_arg_to_keyvalue_auxv:nn }
2584 }
2585 \cs_new:Npn \__cmd_arg_to_keyvalue_auxii:Nnnn #1#2
2586 {
2587   \str_if_eq:eeTF { \exp_not:n {#1} } { = }
2588   { \tl_trim_spaces_apply:nN {#2} \__cmd_arg_to_keyvalue_auxiii:nnn }
2589   { \__cmd_arg_to_keyvalue_auxv:nn }
2590 }
2591 \cs_new:Npn \__cmd_arg_to_keyvalue_auxiii:nnn #1
2592 {
2593   \tl_if_head_is_N_type:nTF {#1}
2594   { \__cmd_split_N_head_apply:Nn \__cmd_arg_to_keyvalue_auxiv:Nnnn {#1} }
2595   { \__cmd_arg_to_keyvalue_auxv:nn }
2596 }
2597 \cs_new:Npn \__cmd_arg_to_keyvalue_auxiv:Nnnn #1#2
2598 {
2599   \str_if_eq:eeTF { \exp_not:n {#1} } { , }
2600   { \tl_set:Nn \ProcessedArgument {#2} \use_none:nn }
2601   { \__cmd_arg_to_keyvalue_auxv:nn }
2602 }

```

The two clear-cut cases have been eliminated, and we therefore have to deal with a search for = signs. We need an “action” loop here so we do not get misled by for example {=}. As the code here is for very much predictable types of input, we hard-code what constitutes math mode opening and closing. At the very beginning, the default key (#1) and the argument as given by the user (#2) are placed right after the `\q__cmd_recursion_stop`, so that when the recursion ends, the macros `\__cmd_arg_to_keyvalue_set_default:nn` or `\__cmd_arg_to_keyvalue_set_keyvalue:nn` can be used to grab these two items and

set the `\ProcessedArgument` accordingly.

```

2603 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_auxv:nn #1#2
2604 {
2605   \__cmd_arg_to_keyvalue_loop:w #2
2606   \q__cmd_recursion_tail \q__cmd_recursion_stop {#1} {#2}
2607 }
2608 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_loop:w #1 \q__cmd_recursion_stop
2609 {
2610   \tl_if_head_is_N_type:nTF {#1}
2611   { \__cmd_arg_to_keyvalue_loop_N_type:N }
2612   {
2613     \tl_if_head_is_group:nTF {#1}
2614     { \__cmd_arg_to_keyvalue_loop_group:n }
2615     { \__cmd_arg_to_keyvalue_loop_space:w }
2616   }
2617   #1 \q__cmd_recursion_stop
2618 }
2619 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_loop_group:n #1
2620 { \__cmd_arg_to_keyvalue_loop:w }
2621 \use:n { \cs_new_protected:Npn \__cmd_arg_to_keyvalue_loop_space:w } ~
2622 { \__cmd_arg_to_keyvalue_loop:w }
2623 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_loop_N_type:N #1
2624 {
2625   \__cmd_if_recursion_tail_stop_do:Nn #1
2626   { \__cmd_arg_to_keyvalue_set_default:nn }
2627   \str_if_eq:nnTF {#1} { = }
2628   {
2629     \__cmd_use_i_delimit_by_q_recursion_stop:nw
2630     { \__cmd_arg_to_keyvalue_set_keyvalue:nn }
2631   }
2632   {
2633     \bool_lazy_or:nnTF
2634     { \token_if_math_toggle_p:N #1 }
2635     { \str_if_eq_p:nn {#1} { \ ( } }
2636     { \__cmd_arg_to_keyvalue_math:w }
2637     { \__cmd_arg_to_keyvalue_loop:w }
2638   }
2639 }
2640 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_math:w #1 \q__cmd_recursion_stop
2641 {
2642   \tl_if_head_is_N_type:nTF {#1}
2643   { \__cmd_arg_to_keyvalue_math_N_type:N }
2644   {
2645     \tl_if_head_is_group:nTF {#1}
2646     { \__cmd_arg_to_keyvalue_math_group:n }
2647     { \__cmd_arg_to_keyvalue_math_space:w }
2648   }
2649   #1 \q__cmd_recursion_stop
2650 }
2651 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_math_N_type:N #1
2652 {
2653   \__cmd_if_recursion_tail_stop_do:Nn #1
2654   { \__cmd_arg_to_keyvalue_set_default:nn }
2655   \bool_lazy_or:nnTF

```

```

2656         { \token_if_math_toggle_p:N #1 }
2657         { \str_if_eq_p:nn {#1} { \ } } }
2658     { \__cmd_arg_to_keyvalue_loop:w }
2659     { \__cmd_arg_to_keyvalue_math:w }
2660 }
2661 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_math_group:n #1
2662 { \__cmd_arg_to_keyvalue_math:w }
2663 \use:n { \cs_new_protected:Npn \__cmd_arg_to_keyvalue_math_space:w } ~
2664 { \__cmd_arg_to_keyvalue_math:w }
2665 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_set_default:nn #1#2
2666 { \tl_set:Nn \ProcessedArgument { #1 = {#2} } }
2667 \cs_new_protected:Npn \__cmd_arg_to_keyvalue_set_keyvalue:nn #1#2
2668 { \tl_set:Nn \ProcessedArgument {#2} }

```

A utility to allow us to grab the first N-type token without risking brace stripping the rest of the input.

```

2669 \cs_new:Npn \__cmd_split_N_head_apply:Nn #1#2
2670 { \exp:w \if_false: { \fi: \__cmd_split_N_head_apply_aux:NNw #1#2 } }
2671 \cs_new:Npn \__cmd_split_N_head_apply_aux:NNw #1#2
2672 {
2673     \exp_after:wN \exp_end:
2674     \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN { \if_false: } \fi:
2675 }
2676

```

*(End of definition for \\_\_cmd\_arg\_to\_keyvalue:nn and others.)*

## 1.12 Utilities

```

\__cmd_check_definable:nNT
  \__cmd_check_definable_aux:nN

```

Check that a token list is appropriate as a first argument of `\NewDocumentCommand` and similar functions and otherwise produce an error. First trim whitespace to allow for spaces around the actual command to be defined. If the result has multiple tokens, it is not a valid argument. The single token is a control sequence exactly if its string representation has more than one character (using `\token_to_str:N` rather than `\tl_to_str:n` to avoid problems with macro parameter characters, and setting `\tex_escapechar:D` to prevent it from being non-printable). Finally, check for an active character: this is done by lowercasing the token to fix its character code (arbitrarily to that of `?`) and comparing the result to an active `?`. Both control sequences and active characters are valid arguments, and non-active character tokens are not. In all cases, the group opened to keep assignments local must be closed.

```

2677 \cs_new_protected:Npn \__cmd_check_definable:nNT #1
2678 { \tl_trim_spaces_apply:nN {#1} \__cmd_check_definable_aux:nN }
2679 \group_begin:
2680   \char_set_catcode_active:n { '?' }
2681   \cs_new_protected:Npn \__cmd_check_definable_aux:nN #1#2
2682   {
2683     \group_begin:
2684     \tl_if_single_token:nTF {#1}
2685     {
2686       \int_set:Nn \tex_escapechar:D { 92 }
2687       \exp_args:Nx \tl_if_empty:nTF
2688       { \exp_args:No \str_tail:n { \token_to_str:N #1 } }
2689       {

```

```

2690         \exp_args:Nx \char_set_lccode:nn
2691         { ' \str_head:n {#1} } { '?' }
2692         \tex_lowercase:D { \tl_if_eq:nnTF {#1} } { ? }
2693         { \group_end: \use_iii:nnn }
2694         { \group_end: \use_i:nnn }
2695     }
2696     { \group_end: \use_iii:nnn }
2697 }
2698 { \group_end: \use_ii:nnn }
2699 {
2700     \msg_error:nnxx { cmd } { not-definable }
2701     { \tl_to_str:n {#1} } { \token_to_str:N #2 }
2702 }
2703 {
2704     \msg_error:nnxx { cmd } { not-one-token }
2705     { \tl_to_str:n {#1} } { \token_to_str:N #2 }
2706 }
2707 }
2708 \group_end:

```

(End of definition for `\__cmd_check_definable:nNT` and `\__cmd_check_definable_aux:nN`.)

`\__cmd_token_if_cs:N` Based on the definition of `\__cmd_check_definable_aux:nN` above, but only checks for an actual control sequence (*i.e.*, `\<anything>`). `\tex_escapechar:D` is temporarily changed to a known value and then it checks if `\string#1` contains more than one character: if it does, it's a control sequence. This test differs from `\token_if_cs:N` for example in `\token_if_cs:N` `\c_group_begin_token {T}{F}`, where `\token_if_cs:N` returns false.

```

2709 \cs_new_protected:Npn \__cmd_token_if_cs:NTF #1
2710 {
2711     \group_begin:
2712     \int_set:Nn \tex_escapechar:D { 92 }
2713     \exp_args:Nx \tl_if_empty:nTF
2714     { \exp_args:No \str_tail:n { \token_to_str:N #1 } }
2715     { \group_end: \use_ii:nn }
2716     { \group_end: \use_i:nn }
2717 }

```

(End of definition for `\__cmd_token_if_cs:N`.)

`\__cmd_tl_mapthread_function:NNN` Analogue of `\seq_mapthread_function:NNN` for token lists.

```

\__cmd_tl_mapthread_function:nnN
\__cmd_tl_mapthread_loop:w
2718 \cs_new:Npn \__cmd_tl_mapthread_function:NNN #1#2#3
2719 {
2720     \exp_after:wN \exp_after:wN
2721     \exp_after:wN \__cmd_tl_mapthread_loop:w
2722     \exp_after:wN \exp_after:wN
2723     \exp_after:wN #3
2724     \exp_after:wN #1
2725     \exp_after:wN \q_recursion_tail
2726     \exp_after:wN \q_mark
2727     #2
2728     \q_recursion_tail
2729     \q_recursion_stop
2730 }

```

```

2731 \cs_new:Npn \__cmd_tl_mapthread_function:nnN #1#2#3
2732 {
2733   \__cmd_tl_mapthread_loop:w #3
2734   #1 \q_recursion_tail \q_mark
2735   #2 \q_recursion_tail \q_recursion_stop
2736 }
2737 \cs_new:Npn \__cmd_tl_mapthread_loop:w #1#2#3 \q_mark #4
2738 {
2739   \quark_if_recursion_tail_stop:n {#2}
2740   \quark_if_recursion_tail_stop:n {#4}
2741   #1 {#2} {#4}
2742   \__cmd_tl_mapthread_loop:w #1#3 \q_mark
2743 }

```

(End of definition for \\_\_cmd\_tl\_mapthread\_function:NNN, \\_\_cmd\_tl\_mapthread\_function:nnN, and \\_\_cmd\_tl\_mapthread\_loop:w.)

```

\__kernel_cmd_if_xparse:NTF
  \__cmd_cmd_type_cases:NnnnnnF
\__cmd_cmd_if_xparse_aux:N

```

To determine whether the command is an xparse command check that its `arg_spec` is empty (this also excludes non-macros) and that its `replacement_spec` starts with either `\__cmd_start:nNNnnn` (non-expandable command) or `\__cmd_start_expandable:nNNNNn` (expandable command) or `\__cmd_start_optimized:` (optimized command) or `\__cmd_start_env:nnnnn` (environment) or `\environment #1 end aux` (environment end).

This conditional is needed in several kernel modules and is therefore has a kernel-internal name.

```

2744 \cs_new:Npn \__cmd_cmd_type_cases:NnnnnnF #1 #2 #3 #4 #5 #6 #7
2745 {
2746   \exp_args:Ne \str_case_e:nnF
2747   {
2748     \exp_args:Nf \tl_if_empty:nT { \__kernel_cs_parameter_spec:N #1 }
2749     { \exp_not:N \exp_not:n { \exp_not:e { \tl_head:N #1 } } }
2750   }
2751   {
2752     { \exp_not:N \__cmd_start:nNNnnn } {#2}
2753     { \exp_not:N \__cmd_start_expandable:nNNNNn } {#3}
2754     { \exp_not:N \__cmd_start_optimized: } {#4}
2755     { \exp_not:N \__cmd_start_env:nnnnn } {#5}
2756     {
2757       \exp_after:wN \exp_not:N
2758       \cs:w environment~
2759       \exp_last_unbraced:Ne \use_none:nnn
2760       { \cs_to_str:N #1 } ~end~aux \cs_end:
2761     } {#6}
2762   }
2763   {#7}
2764 }
2765 \cs_new:Npn \__kernel_cmd_if_xparse:NTF #1
2766 {
2767   \__cmd_cmd_type_cases:NnnnnnF #1
2768   { } { } { } { } { } { } { } { \use_iii:nnn }
2769   \use_i:nn
2770 }

```

(End of definition for \\_\_kernel\_cmd\_if\_xparse:NTF, \\_\_cmd\_cmd\_type\_cases:NnnnnnF, and \\_\_cmd\_cmd\_if\_xparse\_aux:N.)

\\_cmd\_peek\_nonspace:NTF Collect spaces in a loop, and put the collected spaces back in the false branch of a call to \peek\_meaning:NTF or \peek\_meaning\_remove:NTF.

```

2771 \cs_new_protected:Npn \_cmd_peek_nonspace:NTF
2772   { \_cmd_peek_nonspace_aux:nNNTF { } \_cmd_peek_meaning:NTF }
2773 \cs_new_protected:Npn \_cmd_peek_nonspace_remove:NTF
2774   { \_cmd_peek_nonspace_aux:nNNTF { } \_cmd_peek_meaning_remove:NTF }
2775 \cs_new_protected:Npn \_cmd_peek_nonspace_aux:nNNTF #1#2#3#4#5
2776   {
2777     \peek_meaning_remove:NTF \c_space_token
2778     { \_cmd_peek_nonspace_aux:nNNTF { #1 ~ } #2 #3 {#4} {#5} }
2779     { #2 #3 { #4 } { #5 #1 } }
2780   }

```

(End of definition for \\_cmd\_peek\_nonspace:NTF, \\_cmd\_peek\_nonspace\_remove:NTF, and \\_cmd\_peek\_nonspace\_aux:nNNTF.)

\\_cmd\_peek\_meaning:NTF Peek ahead for a token with a given meaning. In case the search token is a control sequence, also check that the <csname> is the same as the control sequence peeked at. This extra verification is necessary when the command is delimited by control sequence tokens (as opposed to character tokens), and we want the exact same control sequence to match.

```

2781 \cs_new_protected:Npn \_cmd_peek_meaning:NTF
2782   { \_cmd_peek_meaning_aux:NNTF \c_false_bool }
2783 \cs_new_protected:Npn \_cmd_peek_meaning_remove:NTF
2784   { \_cmd_peek_meaning_aux:NNTF \c_true_bool }
2785 \cs_new_protected:Npn \_cmd_peek_meaning_aux:NNTF #1#2#3#4
2786   {
2787     \tl_set:Nn \l__cmd_tmpa_tl {#3}
2788     \tl_set:Nn \l__cmd_tmpb_tl {#4}
2789     \peek_meaning:NTF #2
2790     {
2791       \token_if_eq_meaning:NNTF #2 \c_group_begin_token
2792       { \_cmd_peek_true_remove:Nw #1 }
2793       {
2794         \_cmd_token_if_cs:NTF #2
2795         { \_cmd_peek_cs_check_equal:NNN #1 #2 }
2796         { \_cmd_peek_true_remove:Nw #1 }
2797       }
2798     }
2799     { \l__cmd_tmpb_tl }
2800   }
2801 \cs_new_protected:Npn \_cmd_peek_cs_check_equal:NNN #1#2#3
2802   {
2803     \str_if_eq:nnTF {#2} {#3}
2804     { \_cmd_peek_true_remove:Nw #1 }
2805     { \l__cmd_tmpb_tl }
2806     #3
2807   }
2808 \cs_new_protected:Npn \_cmd_peek_true_remove:Nw #1
2809   {
2810     \bool_if:NTF #1
2811     {
2812       \tex_afterassignment:D \l__cmd_tmpa_tl
2813       \cs_set_eq:NN \_cmd_tmp:w

```

```

2814     }
2815     { \l__cmd_tmpa_tl }
2816 }

```

(End of definition for `\__cmd_peek_meaning:NTF` and others.)

### 1.13 Access to the argument specification

`\cmd_arg_spec:N` First we check that the command passed does exist, and is one with the correct form.  
`\cmd_arg_spec:c` If it does then there are two cases. For optimised commands, we can reconstruct the  
`\__cmd_arg_spec_opt:N` arg. spec. from the T<sub>E</sub>X parameter spec, taking care to add + if required. For the non-  
optimized cases, the arg. spec. is stored in the top-level macro. We treat this as a `tl` and  
extract the appropriate balanced text: the second item.

```

2817 \cs_new:Npn \cmd_arg_spec:N #1
2818 {
2819   \cs_if_exist:NTF #1
2820   {
2821     \__kernel_cmd_if_xparse:NTF #1
2822     {
2823       \exp_args:No \tl_if_head_eq_meaning:nNTF #1
2824       \__cmd_start_optimized:
2825       {
2826         \exp_args:Nc \__cmd_arg_spec_opt:N
2827         { \cs_to_str:N #1 \c_space_tl code }
2828       }
2829       { \tl_item:Nn #1 { 2 } }
2830     }
2831     { X }
2832   }
2833   { X }
2834 }
2835 \cs_generate_variant:Nn \cmd_arg_spec:N { c }
2836 \cs_new:Npn \__cmd_arg_spec_opt:N #1
2837 {
2838   \prg_replicate:nn { \str_count:e { \cs_parameter_spec:N #1 } / 2 }
2839   {
2840     \bool_lazy_or:nnT
2841     { \token_if_long_macro_p:N #1 }
2842     { \token_if_protected_long_macro_p:N #1 }
2843     { + }
2844   m
2845   }
2846 }

```

(End of definition for `\cmd_arg_spec:N` and `\__cmd_arg_spec_opt:N`.)

### 1.14 Messages

---

```

2847 \tl_const:Nn \c__cmd_ignore_def_tl
2848 { \\ \\ LaTeX-will-ignore-this-entire-definition. }

```

---

\\_cmd\_environment\_or\_command: Two texts used in several messages.

```
2849 \cs_new:Npn \_cmd_environment_or_command:
2850 {
2851   \bool_if:NTF \l__cmd_environment_bool
2852     { environment ~ ' \l__cmd_environment_str ' }
2853     {
2854       command ~
2855         ' \c_backslash_str \tl_to_str:N \l__cmd_function_tl '
2856     }
2857 }
```

(End of definition for \\_cmd\_environment\_or\_command:.)

Some messages intended as errors when defining commands/environments.

```
2858 \msg_new:nnnn { cmd } { arg-after-body }
2859 { Argument~type~'#1'~must~be~last~in~#2. }
2860 {
2861   The~'#1'~argument~type~must~come~last~but~it~is~followed~
2862   by~'#3'~in~the~argument~specification.~This~is~not~allowed.
2863   \c__cmd_ignore_def_tl
2864 }
2865 \msg_new:nnnn { cmd } { bad-arg-spec }
2866 { Bad~argument~specification~'#2'~for~#1. }
2867 {
2868   The~argument~specification~provided~is~not~valid:~
2869   one~or~more~mandatory~parts~are~missing.
2870   \c__cmd_ignore_def_tl
2871 }
2872 \msg_new:nnnn { cmd } { already-defined }
2873 { Command~'#1'~already~defined. }
2874 {
2875   You~have~used~#2~
2876   with~a~command~that~already~has~a~definition. \ \ \
2877   The~existing~definition~of~'#1'~will~not~be~altered.
2878 }
2879 \msg_new:nnnn { cmd } { undefined }
2880 { Command ~'#1'~undefined. }
2881 {
2882   You~have~used~#2~
2883   with~a~command~that~was~never~defined.
2884   \c__cmd_ignore_def_tl
2885 }
2886 \msg_new:nnnn { cmd } { chars-dropped-first-line }
2887 { Characters~'#1'~dropped~on~first~line~of~#2~environment. }
2888 {
2889   LaTeX~was~collecting~a~verbatim~like~environment,~and~the~characters~
2890   '#1'~were~found~after~'\begin{#2}'~on~the~first~line:~this~is~not~supported.
2891 }
2892 \msg_new:nnnn { cmd } { chars-dropped-last-line }
2893 { Characters~'#1'~dropped~after~end~of~#2~environment. }
2894 {
2895   LaTeX~was~collecting~a~verbatim~like~environment,~and~the~characters~
2896   '#1'~were~found~after~'\end{#2}'~on~the~last~line:~this~is~not~supported.
2897 }
```

```

2898 \msg_new:nnnn { cmd } { env-already-defined }
2899 { Environment~'#1'~already~defined. }
2900 {
2901   You~have~used~\NewDocumentEnvironment
2902   with~an~environment~that~already~has~a~definition. \\ \\
2903   The~existing~definition~of~'#1'~will~not~be~altered.
2904 }
2905 \msg_new:nnnn { cmd } { env-end-already-defined }
2906 { End~of~environment~'#1'~already~defined. }
2907 {
2908   You~have~used~\NewDocumentEnvironment
2909   with~an~environment~that~already~has~a~definition~for~'end#1'. \\ \\
2910   The~existing~definition~of~'#1'~will~not~be~altered.
2911 }
2912 \msg_new:nnnn { cmd } { env-undefined }
2913 { Environment~'#1'~undefined. }
2914 {
2915   You~have~used~\RenewDocumentEnvironment
2916   with~an~environment~that~was~never~defined.
2917   \c__cmd_ignore_def_tl
2918 }
2919 \msg_new:nnnn { cmd } { expandable-ending-optional }
2920 { Bad~argument~specification~'#2'~for~#1. }
2921 {
2922   Expandable~commands~must~have~a~final~mandatory~argument~
2923   (or~no~arguments~at~all).~You~cannot~have~a~terminal~optional~
2924   argument~with~expandable~commands.
2925 }
2926 \msg_new:nnnn { cmd } { long-short-mix }
2927 { Invalid~argument~prefix~'+ '~in~command~'#1'. }
2928 {
2929   The~arguments~for~an~expandable~command~must~not~involve~short~
2930   arguments~after~long~arguments.~You~have~tried~to~mix~the~two~types~
2931   when~defining~'#1'.
2932 }
2933 \msg_new:nnnn { cmd } { invalid-command-arg }
2934 { Invalid~argument~type~'#2'~in~#1. }
2935 {
2936   The~letter~'#2'~can~only~be~used~in~environment~argument~
2937   specifications,~but~not~for~commands.
2938   \\ \\
2939   LaTeX~will~ignore~the~entire~definition.
2940 }
2941 \msg_new:nnnn { cmd } { invalid-expandable-arg }
2942 { Invalid~argument~type~'#2'~in~#1. }
2943 {
2944   The~letter~'#2'~specifies~an~argument~type~which~cannot~be~used~
2945   in~an~expandable~command.
2946   \c__cmd_ignore_def_tl
2947 }
2948 \msg_new:nnnn { cmd } { invalid-after-optional-expandably }
2949 { Argument~'#2'~invalid~after~optional~arg~in~#1. }
2950 {
2951   The~letter~'#2'~specifies~an~argument~type~which~cannot~be~used~

```

```

2952     in-an-expandable-command-after-an-optional-argument.
2953     \c__cmd_ignore_def_tl
2954   }
2955   \msg_new:nnnn { cmd } { invalid-bang }
2956   { Invalid-argument-prefix~'!'~in~#1. }
2957   {
2958     The-prefix~'!'~is-only-allowed-for-trailing-optional-arguments.~
2959     You-tried-to-apply-it-to~#2.
2960     \c__cmd_ignore_def_tl
2961   }
2962   \msg_new:nnnn { cmd } { not-definable }
2963   { First-argument-of~'#2'~must-be-a-command. }
2964   {
2965     The-first-argument-of~'#2'~should-be-the-document-command-that-will~
2966     be-defined.~The-provided-argument~'#1'~is-a-character.~Perhaps-a~
2967     backslash-is-missing?
2968     \c__cmd_ignore_def_tl
2969   }
2970   \msg_new:nnnn { cmd } { not-one-token }
2971   { First-argument-of~'#2'~must-be-a-command. }
2972   {
2973     The-first-argument-of~'#2'~should-be-the-document-command-that-will~
2974     be-defined.~The-provided-argument~'#1'~contains-more-than-one~
2975     token.~Perhaps-a-backslash-is-missing?
2976     \c__cmd_ignore_def_tl
2977   }
2978   \msg_new:nnnn { cmd } { not-single-token }
2979   { Argument-delimiter~'#2'~invalid-in~#1. }
2980   {
2981     The-argument-specification-contains~
2982     \tl_if_empty:nTF{#2}{nothing}{'#2'}~
2983     in-a-place~
2984     where-a-single-token-is-required.
2985     \c__cmd_ignore_def_tl
2986   }
2987   \msg_new:nnnn { cmd } { forbidden-group-token }
2988   { Argument-delimiter~'#2'~invalid-in~#1. }
2989   {
2990     The-argument-specification-contains-the-implicit~
2991     #3-group-token~'#2'~which-is-not-allowed-as-an-argument-delimiter.
2992     \c__cmd_ignore_def_tl
2993   }
2994   \msg_new:nnnn { cmd } { processor-in-expandable }
2995   { Invalid-argument-prefix~'>'~in-command~'#1'. }
2996   {
2997     The-argument-specification-for~'#1'~contains-the-processor-function~'>{#2}'.~
2998     This-is-only-supported-for-robust-commands,~but-not-for-expandable-ones.
2999     \c__cmd_ignore_def_tl
3000   }
3001   \msg_new:nnnn { cmd } { keyval-in-expandable }
3002   { Invalid-argument-prefix~'='~in-command~'#1'. }
3003   {
3004     The-argument-specification-for~'#1'~contains-a-key--value-marker~'={#2}'.~
3005     This-is-only-supported-for-robust-commands,~but-not-for-expandable-ones.

```

```

3006 \c__cmd_ignore_def_tl
3007 }
3008 \msg_new:nnnn { cmd } { too-many-args }
3009 { Too-many-arguments-for~#1. }
3010 {
3011   The~argument~specification~'#2'~asks~for~more~than~9~arguments.~
3012   This~cannot~be~implemented.
3013   \c__cmd_ignore_def_tl
3014 }
3015 \msg_new:nnnn { cmd } { two-markers }
3016 { Invalid~argument~prefix~'#2'~in~#1. }
3017 {
3018   The~argument~specification~provided~for~#1~has~two~'#2'~markers~applied~
3019   to~the~same~argument;~one~is~redundant.
3020 }
3021 \msg_new:nnnn { cmd } { unknown-argument-type } % should be unkown-arg-type but dep in xparse
3022 { Invalid~argument~type~'#2'~in~#1. }
3023 {
3024   The~letter~'#2'~does~not~specify~a~known~argument~type.
3025   \c__cmd_ignore_def_tl
3026 }
3027 \msg_new:nnnn { cmd } { xparse-arg-type }
3028 { Invalid~argument~type~'#2'~in~#1~(requires~xparse). }
3029 {
3030   The~letter~'#2'~specifies~a~known~but~deprecated~argument~type.~
3031   If~you~really~need~it~you~have~to~load~the~xparse~package.
3032   \c__cmd_ignore_def_tl
3033 }

```

Errors when using commands/environments. The if-boolean message is always used in expandable errors. The default-loop and missing-required messages can be expandable or not expandable.

```

3034 \msg_new:nnn { cmd } { if-boolean }
3035 { Invalid~argument~{#1}~to~\iow_char:N\\IfBoolean... }
3036 \msg_new:nnnn { cmd } { default-loop }
3037 { Circular~dependency~in~defaults~of~#1. }
3038 {
3039   The~default~values~of~two~or~more~arguments~of~the~#1~
3040   depend~on~each~other~in~a~way~that~cannot~be~resolved.
3041 }
3042 \msg_new:nnnn { cmd } { missing-required }
3043 { Required~argument~missing~for~#1. }
3044 {
3045   The~#1~expects~one~of~its~arguments~to~start~with~'#2'.~
3046   LaTeX~did~not~find~this~argument~and~will~insert~a~default~value~
3047   for~further~processing.
3048 }
3049 \msg_new:nnnn { cmd } { arg-split }
3050 { Too~many~'#1'~separators~in~argument. }
3051 {
3052   LaTeX~was~asked~to~split~the~input~'#3'~
3053   at~each~occurrence~of~the~separator~'#1'~into~#2~parts.~
3054   Too~many~separators~were~found.
3055 }

```

```

3056 \msg_new:nnnn { cmd } { verbatim-nl }
3057 { Verbatim-like~#1-ended-by~end-of~line. }
3058 {
3059   The~verbatim~argument~of~the~#1~cannot~contain~more~than~one~line,~
3060   but~the~end~
3061   of~the~current~line~has~been~reached.~You~may~have~forgotten~the~
3062   closing~delimiter.
3063   \\ \\
3064   LaTeX~will~ignore~'#2'~and~you~may~get~some~additional~
3065   (low-level)~errors.
3066 }
3067 \msg_new:nnnn { cmd } { verbatim-tokenized }
3068 { Verbatim-like~#1-illegal~in~argument. }
3069 {
3070   The~#1~takes~a~verbatim~argument~and~should~therefore~normally~
3071   not~be~used~in~arguments~of~other~commands~or~environments.~
3072   LaTeX~found~an~illegal~token~ \tl_if_empty:nF {#3} { (#3)~ }
3073   after~'#2'~and~will~drop~everything~up~to~this~point.
3074   \\ \\
3075   Expect~further~(low-level)~errors.
3076 }
3077 \msg_new:nnn { cmd } { define-command } % should be just 'define' but dep in xparse
3078 {
3079   Defining~command~#1~
3080   with~sig.~'#2'~\msg_line_context:.
3081 }
3082 \msg_new:nnn { cmd } { define-env }
3083 {
3084   Defining~environment~'#1'~
3085   with~sig.~'#2'~\msg_line_context:.
3086 }
3087 \msg_new:nnn { cmd } { redefine }
3088 {
3089   Redefining~command~#1~
3090   with~sig.~'#2'~\msg_line_context:.
3091 }
3092 \msg_new:nnn { cmd } { redefine-env }
3093 {
3094   Redefining~environment~'#1'~
3095   with~sig.~'#2'~\msg_line_context:.
3096 }
3097 \msg_new:nnn { cmd } { optional-mandatory }
3098 {
3099   Optional~and~mandatory~argument~with~same~delimiter~'#2'.
3100   \\ \\
3101   The~mandatory~argument~specified~with~
3102   '\str_case:nnF{#1}{ {R/r}{r'~or~'R} }{#1}'~has~the~
3103   same~delimiter~'#2'~as~an~earlier~optional~argument.~
3104   It~will~therefore~not~be~possible~to~omit~all~the~earlier~
3105   optional~arguments~when~calling~this~command.
3106   \\ \\
3107   This~may~be~intentional,~but~then~it~might~be~a~mistake.
3108 }

```

```

3109 \msg_new:nnn { cmd } { unsupported-let }
3110 {
3111   The~command~'#1'~was~undefined~but~not~the~associated~commands~
3112   '#1~code'~and/or~'#1~defaults'.~Maybe~you~tried~using~
3113   \iow_char:N\\let.~This~may~lead~to~an~infinite~loop.
3114 }

```

## 1.15 User functions

The user functions are more or less just the internal functions renamed.

`\BooleanFalse` Design-space names for the Boolean values.

```

\BooleanTrue 3115 \cs_new_eq:NN \BooleanFalse \c_false_bool
3116 \cs_new_eq:NN \BooleanTrue \c_true_bool

```

*(End of definition for \BooleanFalse and \BooleanTrue.)*

`\NewDocumentCommand` The user macros are pretty simple wrappers around the internal ones. There is however  
`\RenewDocumentCommand` a check that the first argument is a single token, possibly surrounded by spaces (hence  
`\ProvideDocumentCommand` the strange `\use:nnn`), and is definable.  
`\DeclareDocumentCommand`

```

3117 \cs_new_protected:Npn \NewDocumentCommand #1#2#3
3118 {
3119   \__cmd_check_definable:nNT {#1} \NewDocumentCommand
3120   {
3121     \cs_if_exist:NTF #1
3122     {
3123       \msg_error:nnxx { cmd } { already-defined }
3124       { \use:nnn \token_to_str:N #1 { } }
3125       { \token_to_str:N \NewDocumentCommand }
3126     }
3127     { \__cmd_declare_cmd:Nnn #1 {#2} {#3} }
3128   }
3129 }
3130 \cs_new_protected:Npn \RenewDocumentCommand #1#2#3
3131 {
3132   \__cmd_check_definable:nNT {#1} \RenewDocumentCommand
3133   {
3134     \cs_if_exist:NTF #1
3135     { \__cmd_declare_cmd:Nnn #1 {#2} {#3} }
3136     {
3137       \msg_error:nnxx { cmd } { undefined }
3138       { \use:nnn \token_to_str:N #1 { } }
3139       { \token_to_str:N \RenewDocumentCommand }
3140     }
3141   }
3142 }
3143 \cs_new_protected:Npn \ProvideDocumentCommand #1#2#3
3144 {
3145   \__cmd_check_definable:nNT {#1} \ProvideDocumentCommand
3146   { \cs_if_exist:NF #1 { \__cmd_declare_cmd:Nnn #1 {#2} {#3} } }
3147 }
3148 \cs_new_protected:Npn \DeclareDocumentCommand #1#2#3
3149 {
3150   \__cmd_check_definable:nNT {#1} \DeclareDocumentCommand

```

```

3151     { \_cmd_declare_cmd:Nnn #1 {#2} {#3} }
3152   }

```

(End of definition for \NewDocumentCommand and others.)

\NewDocumentEnvironment Very similar for environments. Trim spaces from user-specified `<envname>`, do existence check then hand off to `\_cmd_declare_env:nnnn`.

```

\RenewDocumentEnvironment
\ProvideDocumentEnvironment 3153 <latexrelease>\IncludeInRelease{2024/11/01}{\NewDocumentEnvironment}%
\DeclareDocumentEnvironment 3154 <latexrelease> {Trim~spaces~from~envname~first}
    \_cmd_new_env:nnnn 3155 \cs_new_protected:Npn \NewDocumentEnvironment #1#2#3#4
    \_cmd_renew_env:nnnn 3156 {
    \_cmd_provide_env:nnnn 3157   \_cmd_new_env:ennn { \tl_trim_spaces:e {#1} } {#2} {#3} {#4}
    \_cmd_new_env:ennn 3158 }
    \_cmd_renew_env:ennn 3159 \cs_new_protected:Npn \RenewDocumentEnvironment #1#2#3#4
    \_cmd_provide_env:ennn 3160 {
    \_cmd_renew_env:ennn { \tl_trim_spaces:e {#1} } {#2} {#3} {#4}
    \cs_new_protected:Npn \ProvideDocumentEnvironment #1#2#3#4
    {
    \_cmd_provide_env:ennn { \tl_trim_spaces:e {#1} } {#2} {#3} {#4}
    }
    \cs_new_protected:Npn \DeclareDocumentEnvironment #1#2#3#4
    {
    \_cmd_declare_env:ennn { \tl_trim_spaces:e {#1} } {#2} {#3} {#4}
    }

```

Each of `\_cmd_(new|renew|provide)_env:nnnn` is curried.

```

3171 \cs_new_protected:Npn \_cmd_new_env:nnnn #1
3172 {
3173   \cs_if_exist:cTF {#1}
3174   {
3175     \msg_error:nnx { cmd } { env-already-defined } {#1}
3176     \use_none:nnn
3177   }
3178   {
3179     \cs_if_exist:cTF { end #1 }
3180     {
3181       \msg_error:nnx { cmd } { env-end-already-defined } {#1}
3182       \use_none:nnn
3183     }
3184     { \_cmd_declare_env:nnnn {#1} }
3185   }
3186 }
3187 \cs_new_protected:Npn \_cmd_renew_env:nnnn #1
3188 {
3189   \cs_if_exist:cTF {#1}
3190   { \_cmd_declare_env:nnnn {#1} }
3191   {
3192     \msg_error:nnx { cmd } { env-undefined } {#1}
3193     \use_none:nnn
3194   }
3195 }
3196 \cs_new_protected:Npn \_cmd_provide_env:nnnn #1
3197 {
3198   \cs_if_exist:cTF {#1}

```

```

3199     { \use_none:nnn }
3200     { \__cmd_declare_env:nnnn {#1} }
3201   }
3202   \cs_generate_variant:Nn \__cmd_new_env:nnnn { e }
3203   \cs_generate_variant:Nn \__cmd_renew_env:nnnn { e }
3204   \cs_generate_variant:Nn \__cmd_provide_env:nnnn { e }
3205   \<latexrelease>\EndIncludeInRelease
3206   \<latexrelease>\IncludeInRelease{2024/06/01}{\NewDocumentEnvironment}%
3207   \<latexrelease>{Trim~spaces~from~envname~first}
3208   \<latexrelease>\cs_new_protected:Npn \NewDocumentEnvironment #1#2#3#4
3209   \<latexrelease> {
3210     \<latexrelease> \cs_if_exist:cTF {#1}
3211     \<latexrelease> { \msg_error:nnx { cmd } { env-already-defined } {#1} }
3212     \<latexrelease> {
3213       \cs_if_exist:cTF { end #1 }
3214       \<latexrelease> { \msg_error:nnx { cmd } { env-end-already-defined } {#1} }
3215       \<latexrelease> { \__cmd_declare_env:nnnn {#1} {#2} {#3} {#4} }
3216     }
3217   \<latexrelease> }
3218   \<latexrelease>\cs_new_protected:Npn \RenewDocumentEnvironment #1#2#3#4
3219   \<latexrelease> {
3220     \<latexrelease> \cs_if_exist:cTF {#1}
3221     \<latexrelease> { \__cmd_declare_env:nnnn {#1} {#2} {#3} {#4} }
3222     \<latexrelease> { \msg_error:nnx { cmd } { env-undefined } {#1} }
3223   \<latexrelease> }
3224   \<latexrelease>\cs_new_protected:Npn \ProvideDocumentEnvironment #1#2#3#4
3225   \<latexrelease> { \cs_if_exist:cF {#1} { \__cmd_declare_env:nnnn {#1} {#2} {#3} {#4} } }
3226   \<latexrelease>\cs_new_protected:Npn \DeclareDocumentEnvironment #1#2#3#4
3227   \<latexrelease> { \__cmd_declare_env:nnnn {#1} {#2} {#3} {#4} }
3228   \<latexrelease>\cs_undefine:N \__cmd_new_env:nnnn
3229   \<latexrelease>\cs_undefine:N \__cmd_new_env:ennn
3230   \<latexrelease>\cs_undefine:N \__cmd_renew_env:nnnn
3231   \<latexrelease>\cs_undefine:N \__cmd_renew_env:ennn
3232   \<latexrelease>\cs_undefine:N \__cmd_provide_env:nnnn
3233   \<latexrelease>\cs_undefine:N \__cmd_provide_env:ennn
3234   \<latexrelease>
3235   \<latexrelease>\EndIncludeInRelease

```

(End of definition for \NewDocumentEnvironment and others.)

\NewExpandableDocumentCommand  
\RenewExpandableDocumentCommand  
\ProvideExpandableDocumentCommand  
\DeclareExpandableDocumentCommand

The expandable versions are essentially the same as the basic functions. The strange \use:nnn is there in case #1 is surrounded with spaces, as can happen with usual document catcodes in \RenewExpandableDocumentCommand { \! } ...

```

3236   \cs_new_protected:Npn \NewExpandableDocumentCommand #1#2#3
3237   {
3238     \__cmd_check_definable:nNT {#1} \NewExpandableDocumentCommand
3239     {
3240       \cs_if_exist:NTF #1
3241       {
3242         \msg_error:nnxx { cmd } { already-defined }
3243         { \use:nnn \token_to_str:N #1 { } }
3244         { \token_to_str:N \NewExpandableDocumentCommand }
3245       }
3246       { \__cmd_declare_expandable_cmd:Nnn #1 {#2} {#3} }

```

```

3247     }
3248   }
3249   \cs_new_protected:Npn \RenewExpandableDocumentCommand #1#2#3
3250   {
3251     \__cmd_check_definable:nNT {#1} \RenewExpandableDocumentCommand
3252     {
3253       \cs_if_exist:NTF #1
3254       { \__cmd_declare_expandable_cmd:Nnn #1 {#2} {#3} }
3255       {
3256         \msg_error:nnxx { cmd } { undefined }
3257         { \use:nnn \token_to_str:N #1 { } }
3258         { \token_to_str:N \RenewExpandableDocumentCommand }
3259       }
3260     }
3261   }
3262   \cs_new_protected:Npn \ProvideExpandableDocumentCommand #1#2#3
3263   {
3264     \__cmd_check_definable:nNT {#1} \ProvideExpandableDocumentCommand
3265     {
3266       \cs_if_exist:NF #1
3267       { \__cmd_declare_expandable_cmd:Nnn #1 {#2} {#3} }
3268     }
3269   }
3270   \cs_new_protected:Npn \DeclareExpandableDocumentCommand #1#2#3
3271   {
3272     \__cmd_check_definable:nNT {#1} \DeclareExpandableDocumentCommand
3273     { \__cmd_declare_expandable_cmd:Nnn #1 {#2} {#3} }
3274   }

```

(End of definition for \NewExpandableDocumentCommand and others.)

\IfBooleanT The logical `<true>` and `<false>` statements are just the normal `\c_true_bool` and `\c_false_bool` so `\bool_if:NTF` is almost enough. However, this code-level function blows up badly when passed invalid input. We want `\IfBooleanTF` to accept a single (non-space) token equal to `\c_true_bool` or `\c_false_bool`, possibly surrounded by spaces. If the input is blank or multiple items, jump to the error and pick the false branch. If the input, ignoring spaces (we do this by omitting braces in the `\tl_if_single_token:nF` test), is not a single token then jump to the error as well. It is then safe to compare the token to the two booleans, picking the appropriate branch. If neither matches, we jump to the error as well.

```

3275   \cs_new:Npn \IfBooleanTF #1
3276   {
3277     \tl_if_single:nF {#1}
3278     { \prg_break:n { \use:n } }
3279     \tl_if_single_token:nF #1
3280     { \prg_break:n { \use:n } }
3281     \token_if_eq_meaning:NNT #1 \c_true_bool
3282     { \prg_break:n { \use_ii:nnn } }
3283     \token_if_eq_meaning:NNT #1 \c_false_bool
3284     { \prg_break:n { \use_iii:nnn } }
3285     \prg_break:n { \use:n }
3286     \prg_break_point:
3287     {
3288       \msg_expandable_error:nnn { cmd } { if-boolean } {#1}

```

```

3289     \use_ii:nn
3290   }
3291 }
3292 \cs_new:Npn \IfBooleanT #1#2 { \IfBooleanTF {#1} {#2} { } }
3293 \cs_new:Npn \IfBooleanF #1 { \IfBooleanTF {#1} { } }

```

*(End of definition for \IfBooleanT, \IfBooleanF, and \IfBooleanTF.)*

**\IfNoValueT** Simple re-naming.

```

\IfNoValueF 3294 \cs_new_eq:NN \IfNoValueF \tl_if_novalue:nF
\IfNoValueTF 3295 \cs_new_eq:NN \IfNoValueT \tl_if_novalue:nT
3296 \cs_new_eq:NN \IfNoValueTF \tl_if_novalue:nTF

```

*(End of definition for \IfNoValueT, \IfNoValueF, and \IfNoValueTF.)*

**\IfValueT** Inverted logic.

```

\IfValueF 3297 \cs_new:Npn \IfValueF { \tl_if_novalue:nT }
\IfValueTF 3298 \cs_new:Npn \IfValueT { \tl_if_novalue:nF }
3299 \cs_new:Npn \IfValueTF #1#2#3 { \tl_if_novalue:nTF {#1} {#3} {#2} }

```

*(End of definition for \IfValueT, \IfValueF, and \IfValueTF.)*

**\IfBlankT** Another simple re-naming.

```

\IfBlankF 3300 <latexrelease> \IncludeInRelease{2022/06/01}%
\IfBlankTF 3301 <latexrelease> { \IfBlankTF } { Testing-for-empty-or-blank } %
3302 \cs_new_eq:NN \IfBlankF \tl_if_blank:nF
3303 \cs_new_eq:NN \IfBlankT \tl_if_blank:nT
3304 \cs_new_eq:NN \IfBlankTF \tl_if_blank:nTF
3305 <latexrelease> \EndIncludeInRelease
3306 <latexrelease> \IncludeInRelease{2021/11/15}%
3307 <latexrelease> { \IfBlankTF } { Testing-for-empty-or-blank } %
3308 <latexrelease> \cs_undefine:N \IfBlankF
3309 <latexrelease> \cs_undefine:N \IfBlankT
3310 <latexrelease> \cs_undefine:N \IfBlankTF
3311 <latexrelease>
3312 <latexrelease> \EndIncludeInRelease

```

*(End of definition for \IfBlankT, \IfBlankF, and \IfBlankTF.)*

**\ProcessedArgument** Processed arguments are returned using this name, which is reserved here although the definition will change.

```

3313 \tl_new:N \ProcessedArgument

```

*(End of definition for \ProcessedArgument.)*

**\ReverseBoolean** Simple copies.

```

\SplitArgument 3314 \cs_new_eq:NN \ReverseBoolean \__cmd_bool_reverse:N
\SplitList 3315 \cs_new_eq:NN \SplitArgument \__cmd_split_argument:nnn
\TrimSpaces 3316 \cs_new_eq:NN \SplitList \__cmd_split_list:nn
3317 \cs_new_eq:NN \TrimSpaces \__cmd_trim_spaces:n

```

*(End of definition for \ReverseBoolean and others.)*

**\ProcessList** To support \SplitList.

```

3318 \cs_new_eq:NN \ProcessList \tl_map_tokens:nn

```

(End of definition for \ProcessList.)

Finally as promised, restore \\_kernel\_chk\_if\_free\_cs:N:

```
3319 <latexrelease>\cs_gset_eq:NN \_kernel_chk_if_free_cs:N \_cmd_chk_if_free_cs:N
```

```
3320 <latexrelease>\cs_undefine:N \_cmd_chk_if_free_cs:N
```

```
3321 <latexrelease>
```

```
3322 <latexrelease>\IncludeInRelease{0000/00/00}{ltxcmd}%
```

```
3323 <latexrelease>{Document~command~parser}%
```

```
3324 <latexrelease>
```

```
3325 <latexrelease>\EndModuleRelease
```

```
3326 \ExplSyntaxOff
```

Now in latexrelease mode, redefine \NewDocumentCommand to not complain on commands already defined.

```
3327 <latexrelease>\@ifundefined{ExplSyntaxOff}{\{\}\latexrelease@postltxcmd}
```

```
3328 <latexrelease>\catcode'\^@=\@latexrelease@catcode@null\relax
```

```
3329 </2ekernel | latexrelease>
```

We need to stop DocStrip treating @@ in a special way at this point.

```
3330 <@@=>
```

# File 08

## lthooks.dtx

### 1 Introduction

Hooks are points in the code of commands or environments where it is possible to add processing code into existing commands. This can be done by different packages that do not know about each other, and to allow for hopefully safe processing it is necessary to sort different chunks of code added by different packages into a suitable processing order.

This is done by the packages adding chunks of code (via `\AddToHook`) and labeling their code with some label by default using the package name as a label.

At `\begin{document}` all code for a hook is then sorted according to some rules (given by `\DeclareHookRule`) for fast execution without processing overhead. If the hook code is modified afterwards (or the rules are changed), a new version for fast processing is generated.

Some hooks are used already in the preamble of the document. If that happens then the hook is prepared for execution (and sorted) already at that point.

### 2 Package writer interface

The hook management system is offered as a set of CamelCase commands for traditional  $\text{\LaTeX 2}_{\epsilon}$  packages (and for use in the document preamble if needed) as well as `expl3` commands for modern packages, that use the L3 programming layer of  $\text{\LaTeX}$ . Behind the scenes, a single set of data structures is accessed so that packages from both worlds can coexist and access hooks in other packages.

#### 2.1 $\text{\LaTeX 2}_{\epsilon}$ interfaces

##### 2.1.1 Declaring hooks

With a few exceptions, hooks have to be declared before they can be used. The exceptions are the generic hooks for commands and environments (executed at `\begin` and `\end`), and the generic hooks run when loading files (see section 3.1).

---

<code>\NewHook</code>	<code>\NewHook {&lt;hook&gt;}</code>
-----------------------	--------------------------------------

Creates a new `<hook>`. If this hook is declared within a package it is suggested that its name is always structured as follows: `<package-name>/<hook-name>`. If necessary you can further subdivide the name by adding more / parts. If a hook name is already taken, an error is raised and the hook is not created.

The `<hook>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5. The string `??` can't be used as a hook name because it has a special significance as a placeholder in hook rules.

---

<code>\NewReversedHook</code>	<code>\NewReversedHook {⟨hook⟩}</code>
-------------------------------	--

---

Like `\NewHook` declares a new `⟨hook⟩`. the difference is that the code chunks for this hook are in reverse order by default (those added last are executed first). Any rules for the hook are applied after the default ordering. See sections 2.3 and 2.4 for further details.

The `⟨hook⟩` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\NewMirroredHookPair</code>	<code>\NewMirroredHookPair {⟨hook-1⟩} {⟨hook-2⟩}</code>
-----------------------------------	---

---

A shorthand for `\NewHook{⟨hook-1⟩}\NewReversedHook{⟨hook-2⟩}`.

The `⟨hook⟩` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\NewHookWithArguments</code>	<code>\NewHookWithArguments {⟨hook⟩} {⟨number⟩}</code>
------------------------------------	--

---

Creates a new `⟨hook⟩` whose code takes `⟨number⟩` arguments, and otherwise works exactly like `\NewHook`. Section 2.7 explains hooks with arguments.

The `⟨hook⟩` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\NewReversedHookWithArguments</code>	<code>\NewReversedHookWithArguments {⟨hook⟩} {⟨number⟩}</code>
--	--

---

Like `\NewReversedHook`, but creates a hook whose code takes `⟨number⟩` arguments. Section 2.7 explains hooks with arguments.

The `⟨hook⟩` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\NewMirroredHookPairWithArguments</code>	<code>\NewMirroredHookPairWithArguments {⟨hook-1⟩} {⟨hook-2⟩} {⟨number⟩}</code>
--	---

---

A shorthand for `\NewHookWithArguments{⟨hook-1⟩}{⟨number⟩}`

`\NewReversedHookWithArguments{⟨hook-2⟩}{⟨number⟩}`. Section 2.7 explains hooks with arguments.

The `⟨hook⟩` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

## 2.1.2 Special declarations for generic hooks

The declarations here should normally not be used. They are available to provide support for special use cases mainly involving generic command hooks.

---

<code>\DisableGenericHook</code>	<code>\DisableGenericHook {⟨hook⟩}</code>
----------------------------------	---

---

After this declaration<sup>3</sup> the `⟨hook⟩` is no longer usable: Any further attempt to add code to it will result in an error and any use, e.g., via `\UseHook`, will simply do nothing.

This is intended to be used with generic command hooks (see `lthcmdhooks-doc`) as depending on the definition of the command such generic hooks may be unusable. If that is known, a package developer can disable such hooks up front.

The `⟨hook⟩` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<sup>3</sup>In the 2020/06 release this command was called `\DisableHook`, but that name was misleading as it shouldn't be used to disable non-generic hooks.

---

<code>\ActivateGenericHook</code>	<code>\ActivateGenericHook {&lt;hook&gt;}</code>
-----------------------------------	--

---

This declaration activates a generic hook provided by a package/class (e.g., one used in code with `\UseHook` or `\UseOneTimeHook`) without it being explicitly declared with `\NewHook`). If the hook is already activated, this command does nothing.

Note that this command does not undo the effect of `\DisableGenericHook`. See section 2.6 for a discussion of when this declaration is appropriate.

### 2.1.3 Using hooks in code

Using a hook that is executing the code that has been associated with it is only allowed if the hook has been previously declared with `\NewHook`. For performance reason there are no runtime checks for this and it is the responsibility of the programmer of a package to ensure that all hooks that are used in a package (with one of the commands in this section) are declared first.

---

<code>\UseHook</code>	<code>\UseHook {&lt;hook&gt;}</code>
-----------------------	--------------------------------------

---

Execute the code stored in the `<hook>`.

Before `\begin{document}` the fast execution code for a hook is not set up, so in order to use a hook there it is explicitly initialized first. As that involves assignments using a hook at those times is not 100% the same as using it after `\begin{document}`.

The `<hook>` *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

---

<code>\UseHookWithArguments</code>	<code>\UseHookWithArguments {&lt;hook&gt;} {&lt;number&gt;} {&lt;arg<sub>1</sub>&gt;} ... {&lt;arg<sub>n</sub>&gt;}</code>
------------------------------------	--

---

Execute the code stored in the `<hook>` and pass the arguments `{<arg1>}` through `{<argn>}` to the `<hook>`. Otherwise, it works exactly like `\UseHook`. The `<number>` should be the number of arguments declared for the hook. If the hook is not declared, this command does nothing and it will remove `<number>` items from the input. Section 2.7 explains hooks with arguments.

The `<hook>` *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

---

<code>\UseOneTimeHook</code>	<code>\UseOneTimeHook {&lt;hook&gt;}</code>
------------------------------	---

---

Some hooks are only used (and can be only used) in one place, for example, those in `\begin{document}` or `\end{document}`. From that point onwards, adding to the hook through a defined `\<addto-cmd>` command (e.g., `\AddToHook` or `\AtBeginDocument`, etc.) would have no effect (as would the use of such a command inside the hook code itself). It is therefore customary to redefine `\<addto-cmd>` to simply process its argument, i.e., essentially make it behave like `\@firstofone`.

`\UseOneTimeHook` does that: it records that the hook has been consumed and any further attempt to add to it will result in executing the code to be added immediately.

Using `\UseOneTimeHook` several times with the same `{<hook>}` means that it only executes the first time it is used. For example, if it is used in a command that can be called several times then the hook executes during only the *first* invocation of that command; this allows its use as an “initialization hook”.

Mixing `\UseHook` and `\UseOneTimeHook` for the same `{<hook>}` should be avoided, but if this is done then neither will execute after the first `\UseOneTimeHook`.

The `<hook>` *cannot* be specified using the dot-syntax. A leading `.` is treated literally. See section 2.1.5 for details.

---

<code>\UseOneTimeHookWithArguments</code>	<code>\UseOneTimeHookWithArguments {&lt;hook&gt;} {&lt;number&gt;} {&lt;arg<sub>1</sub>&gt;} ... {&lt;arg<sub>n</sub>&gt;}</code>
---	---

---

Works exactly like `\UseOneTimeHook`, but passes arguments  $\{<arg_1>\}$  through  $\{<arg_n>\}$  to the  $\langle hook \rangle$ . The  $\langle number \rangle$  should be the number of arguments declared for the hook. If the hook is not declared, this command does nothing and it will remove  $\langle number \rangle$  items from the input.

It should be noted that after a one-time hook is used, it is no longer possible to use `\AddToHookWithArguments` or similar with that hook. `\AddToHook` continues to work as normal. Section 2.7 explains hooks with arguments.

The  $\langle hook \rangle$  *cannot* be specified using the dot-syntax. A leading `.` is treated literally. See section 2.1.5 for details.

#### 2.1.4 Updating code for hooks

In contrast to the commands from the previous section, declarations such as `\AddToHook` or `\DeclareHookRule` can be used even when the hook is not yet declared. The rationale is that the hook declaration may be in some package that is loaded later, or perhaps not loaded at all.

A side effect of this design is that misspellings do not raise an error but are simply regarded as declarations for hooks with a different name.

---

<code>\AddToHook</code>	<code>\AddToHook {&lt;hook&gt;} [&lt;label&gt;] {&lt;code&gt;}</code>
-------------------------	---

---

Adds  $\langle code \rangle$  to the  $\langle hook \rangle$  labeled by  $\langle label \rangle$ . When the optional argument  $\langle label \rangle$  is not provided, the  $\langle default\ label \rangle$  is used (see section 2.1.5). If `\AddToHook` is used in a package/class, the  $\langle default\ label \rangle$  is the package/class name, otherwise it is `top-level` (the `top-level` label is treated differently: see section 2.1.6).

If there already exists code under the  $\langle label \rangle$  then the new  $\langle code \rangle$  is appended to the existing one (even if this is a reversed hook). If you want to replace existing code under the  $\langle label \rangle$ , first apply `\RemoveFromHook`.

The hook doesn't have to exist for code to be added to it. However, if it is not declared, then obviously the added  $\langle code \rangle$  will never be executed. This allows for hooks to work regardless of package loading order and enables packages to add to hooks from other packages without worrying whether they are actually used in the current document. See section 2.1.8.

The  $\langle hook \rangle$  and  $\langle label \rangle$  can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\AddToHookWithArguments</code>	<code>\AddToHookWithArguments {&lt;hook&gt;} [&lt;label&gt;] {&lt;code&gt;}</code>
--------------------------------------	--

---

Works exactly like `\AddToHook`, except that the `<code>` can access the arguments passed to the hook using `#1`, `#2`, ..., `#n` (up to the number of arguments declared for the hook). If the `<code>` should contain *parameter tokens* (`#`) that are not supposed to be understood as the arguments of the hook, such tokens should be doubled. For example, with `\AddToHook` one can write:

```
\AddToHook{myhook}{\def\foo#1{Hello, #1!}}
```

but to achieve the same with `\AddToHookWithArguments`, one should write:

```
\AddToHookWithArguments{myhook}{\def\foo##1{Hello, ##1!}}
```

because in the latter case, `#1` refers to the first argument of the hook `myhook`. Section 2.7 explains hooks with arguments.

The `<hook>` and `<label>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\RemoveFromHook</code>	<code>\RemoveFromHook {&lt;hook&gt;} [&lt;label&gt;]</code>
------------------------------	---

---

Removes any code labeled by `<label>` from the `<hook>`. When the optional argument `<label>` is not provided, the `<default label>` is used (see section 2.1.5).

If there is no code under the `<label>` in the `<hook>`, or if the `<hook>` does not exist, a warning is issued when you attempt to `\RemoveFromHook`, and the command is ignored. `\RemoveFromHook` should be used only when you know exactly what labels are in a hook. Typically this will be when some code gets added to a hook by a package, then later this code is removed by that same package. If you want to prevent the execution of code from another package, use the `voids` rule instead (see section 2.1.7).

If the optional `<label>` argument is `*`, then all code chunks are removed. This is rather dangerous as it may well drop code from other packages (that one may not know about); it should therefore not be used in packages but only in document preambles!

The `<hook>` and `<label>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

In contrast to the `voids` relationship between two labels in a `\DeclareHookRule` this is a destructive operation as the labeled code is removed from the hook data structure, whereas the relationship setting can be undone by providing a different relationship later.

A useful application for this declaration inside the document body is when one wants to temporarily add code to hooks and later remove it again, e.g.,

```
\AddToHook{env/quote/begin}{\small}
\begin{quote}
  A quote set in a smaller typeface
\end{quote}
...
\RemoveFromHook{env/quote/begin}
... now back to normal for further quotes
```

Note that you can't cancel the setting with

```
\AddToHook{env/quote/begin}{}
```

### **Important:**

*The `\RemoveFromHook` command should be only used if one has full control over the code chunk to be removed. In particular it should not be used to remove code chunks from other packages! For this the `voids` relation is provided.*

because that only “adds” a further empty chunk of code to the hook. Adding `\normalsize` would work but that means the hook then contained `\small\normalsize` which means two font size changes for no good reason.

The above is only needed if one wants to typeset several quotes in a smaller typeface. If the hook is only needed once then `\AddToHookNext` is simpler, because it resets itself after one use.

---

**`\AddToHookNext`**    `\AddToHookNext {<hook>} {<code>}`

---

Adds `<code>` to the next invocation of the `<hook>`. The code is executed after the normal hook code has finished and it is executed only once, i.e. it is deleted after it was used.

Using this declaration is a global operation, i.e., the code is not lost even if the declaration is used inside a group and the next invocation of the hook happens after the end of that group. If the declaration is used several times before the hook is executed then all code is executed in the order in which it was declared.<sup>4</sup>

If this declaration is used with a one-time hook then the code is only ever used if the declaration comes before the hook’s invocation. This is because, in contrast to `\AddToHook`, the code in this declaration is not executed immediately in the case when the invocation of the hook has already happened—in other words, this code will truly execute only on the next invocation of the hook (and in the case of a one-time hook there is no such “next invocation”). This gives you a choice: should my code execute always, or should it execute only at the point where the one-time hook is used (and not at all if this is impossible)? For both of these possibilities there are use cases.

It is possible to nest this declaration using the same hook (or different hooks): e.g.,

`\AddToHookNext{<hook>}{<code-1>\AddToHookNext{<hook>}{<code-2>}}`

will execute `<code-1>` next time the `<hook>` is used and at that point puts `<code-2>` into the `<hook>` so that it gets executed on following time the hook is run.

A hook doesn’t have to exist for code to be added to it. This allows for hooks to work regardless of package loading order. See section 2.1.8.

The `<hook>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

**`\AddToHookNextWithArguments`**    `\AddToHookNextWithArguments {<hook>} {<code>}`

---

Works exactly like `\AddToHookNext`, but the `<code>` can contain references to the arguments of the `<hook>` as described for `\AddToHookWithArguments` above. Section 2.7 explains hooks with arguments.

The `<hook>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

**`\ClearHookNext`**    `\ClearHookNext {<hook>}`

---

Normally `\AddToHookNext` is only used when you know precisely where it will apply and why you want some extra code at that point. However, there are a few use cases in which such a declaration needs to be canceled, for example, when discarding a page with `\DiscardShipoutBox` (but even then not always), and in such situations `\ClearHookNext` can be used.

---

<sup>4</sup>There is no mechanism to reorder such code chunks (or delete them).

### 2.1.5 Hook names and default labels

It is best practice to use `\AddToHook` in packages or classes *without specifying a  $\langle label \rangle$*  because then the package or class name is automatically used, which is helpful if rules are needed, and avoids mistyping the  $\langle label \rangle$ .

Using an explicit  $\langle label \rangle$  is only necessary in very specific situations, e.g., if you want to add several chunks of code into a single hook and have them placed in different parts of the hook (by providing some rules).

The other case is when you develop a larger package with several sub-packages. In that case you may want to use the same  $\langle label \rangle$  throughout the sub-packages in order to avoid that the labels change if you internally reorganize your code.

Except for `\UseHook`, `\UseOneTimeHook` and `\IfHookEmptyTF` (and their `expl3` interfaces `\hook_use:n`, `\hook_use_once:n` and `\hook_if_empty:nTF`), all  $\langle hook \rangle$  and  $\langle label \rangle$  arguments are processed in the same way: first, spaces are trimmed around the argument, then it is fully expanded until only character tokens remain. If the full expansion of the  $\langle hook \rangle$  or  $\langle label \rangle$  contains a non-expandable non-character token, a low-level  $\TeX$  error is raised (namely, the  $\langle hook \rangle$  is expanded using  $\TeX$ 's `\csname...\endcsname`, as such, Unicode characters are allowed in  $\langle hook \rangle$  and  $\langle label \rangle$  arguments). The arguments of `\UseHook`, `\UseOneTimeHook`, and `\IfHookEmptyTF` are processed much in the same way except that spaces are not trimmed around the argument, for better performance.

It is not enforced, but highly recommended that the hooks defined by a package, and the  $\langle labels \rangle$  used to add code to other hooks contain the package name to easily identify the source of the code chunk and to prevent clashes. This should be the standard practice, so this hook management code provides a shortcut to refer to the current package in the name of a  $\langle hook \rangle$  and in a  $\langle label \rangle$ . If the  $\langle hook \rangle$  name or the  $\langle label \rangle$  consist just of a single dot (`.`), or starts with a dot followed by a slash (`./`) then the dot denotes the  $\langle default label \rangle$  (usually the current package or class name—see `\SetDefaultHookLabel`). A “.” or “./” anywhere else in a  $\langle hook \rangle$  or in  $\langle label \rangle$  is treated literally and is not replaced.

For example, inside the package `mypackage.sty`, the default label is `mypackage`, so the instructions:

```
\NewHook    {./hook}
\AddToHook {./hook}[.]{code}      % Same as \AddToHook{./hook}{code}
\AddToHook {./hook}[./sub]{code}
\DeclareHookRule{begindocument}{.}{before}{babel}
\AddToHook {file/foo.tex/after}{code}
```

are equivalent to:

```
\NewHook    {mypackage/hook}
\AddToHook {mypackage/hook}[mypackage]{code}
\AddToHook {mypackage/hook}[mypackage/sub]{code}
\DeclareHookRule{begindocument}{mypackage}{before}{babel}
\AddToHook {file/foo.tex/after}{code} % unchanged
```

The  $\langle default label \rangle$  is automatically set equal to the name of the current package or class at the time the package is loaded. If the hook command is used outside of a package, or the current file wasn't loaded with `\usepackage` or `\documentclass`, then the `top-level` is used as the  $\langle default label \rangle$ . This may have exceptions—see `\PushDefaultHookLabel`.

This syntax is available in all  $\langle label \rangle$  arguments and most  $\langle hook \rangle$  arguments, both in the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interface, and the L<sup>A</sup>T<sub>E</sub>X 3 interface described in section 2.2.

**Important:**

*The dot-syntax is **not** available with `\UseHook` and some other commands that are typically used within code!*

Note, however, that the replacement of `.` by the  $\langle default label \rangle$  takes place when the hook command is executed, so actions that are somehow executed after the package ends will have the wrong  $\langle default label \rangle$  if the dot-syntax is used. For that reason, this syntax is not available in `\UseHook` (and `\hook_use:n`) because the hook is most of the time used outside of the package file in which it was defined. This syntax is also not available in the hook conditionals `\IfHookEmptyTF` (and `\hook_if_empty:nTF`), because these conditionals are used in some performance-critical parts of the hook management code, and because they are usually used to refer to other package's hooks, so the dot-syntax doesn't make much sense.

In some cases, for example in large packages, one may want to separate the code in logical parts, but still use the main package name as the  $\langle label \rangle$ , then the  $\langle default label \rangle$  can be set using `\PushDefaultHookLabel{...}`...`\PopDefaultHookLabel` or `\SetDefaultHookLabel{...}`.

---

<code>\PushDefaultHookLabel</code>	<code>\PushDefaultHookLabel {<math>\langle default label \rangle</math>}</code>
<code>\PopDefaultHookLabel</code>	<code><math>\langle code \rangle</math></code>

---

`\PopDefaultHookLabel`

`\PushDefaultHookLabel` sets the current  $\langle default label \rangle$  to be used in  $\langle label \rangle$  arguments, or when replacing a leading “.” (see above). `\PopDefaultHookLabel` reverts the  $\langle default label \rangle$  to its previous value.

Inside a package or class, the  $\langle default label \rangle$  is equal to the package or class name, unless explicitly changed. Everywhere else, the  $\langle default label \rangle$  is `top-level` (see section 2.1.6) unless explicitly changed.

The effect of `\PushDefaultHookLabel` holds until the next `\PopDefaultHookLabel`. `\usepackage` (and `\RequirePackage` and `\documentclass`) internally use

```
\PushDefaultHookLabel{ $\langle package name \rangle$ }
 $\langle package code \rangle$ 
\PopDefaultHookLabel
```

to set the  $\langle default label \rangle$  for the package or class file. Inside the  $\langle package code \rangle$  the  $\langle default label \rangle$  can also be changed with `\SetDefaultHookLabel`. `\input` and other file input-related commands from the L<sup>A</sup>T<sub>E</sub>X kernel do not use `\PushDefaultHookLabel`, so code within files loaded by these commands does *not* get a dedicated  $\langle label \rangle$ ! (that is, the  $\langle default label \rangle$  is the current active one when the file was loaded.)

Packages that provide their own package-like interfaces (TikZ's `\usetikzlibrary`, for example) can use `\PushDefaultHookLabel` and `\PopDefaultHookLabel` to set dedicated labels and to emulate `\usepackage`-like hook behavior within those contexts.

The `top-level` label is treated differently, and is reserved to the user document, so it is not allowed to change the  $\langle default label \rangle$  to `top-level`.

---

<code>\SetDefaultHookLabel</code>	<code>\SetDefaultHookLabel {⟨default label⟩}</code>
-----------------------------------	---

---

Similarly to `\PushDefaultHookLabel`, sets the current `⟨default label⟩` to be used in `⟨label⟩` arguments, or when replacing a leading “.”. The effect holds until the label is changed again or until the next `\PopDefaultHookLabel`. The difference between `\PushDefaultHookLabel` and `\SetDefaultHookLabel` is that the latter does not save the current `⟨default label⟩`.

This command is useful when a large package is composed of several smaller packages, but all should have the same `⟨label⟩`, so `\SetDefaultHookLabel` can be used at the beginning of each package file to set the correct label.

`\SetDefaultHookLabel` is not allowed in the main document, where the `⟨default label⟩` is `top-level` and there is no `\PopDefaultHookLabel` to end its effect. It is also not allowed to change the `⟨default label⟩` to `top-level`.

### 2.1.6 The `top-level` label

The `top-level` label, assigned to code added from the main document, is different from other labels. Code added to hooks (usually `\AtBeginDocument`) in the preamble is almost always to change something defined by a package, so it should go at the very end of the hook.

Therefore, code added in the `top-level` is always executed at the end of the hook, regardless of where it was declared. If the hook is reversed (see `\NewReversedHook`), the `top-level` chunk is executed at the very beginning instead.

Rules regarding `top-level` have no effect: if a user wants to have a specific set of rules for a code chunk, they should use a different label to said code chunk, and provide a rule for that label instead.

The `top-level` label is exclusive for the user, so trying to add code with that label from a package results in an error.

### 2.1.7 Defining relations between hook code

The default assumption is that code added to hooks by different packages are independent and the order in which they are executed is irrelevant. While this is true in many cases it is obviously false in others.

Before the hook management system was introduced packages had to take elaborate precautions to determine whether some other package had also been loaded (before or after) and then to find some ways to alter its behavior accordingly. In addition it was often the user’s responsibility to load packages in the right order so that alterations made by packages were done in that same order; and in some cases even altering the loading order wouldn’t resolve the conflicts.

With the new hook management system it is now possible to define rules (i.e., relationships) between code chunks added by different packages and to specify explicitly the order in which they should be processed.

The rules can be declared for hooks before the hook has been declared with `\NewHook` and they are allowed to refer to code labels that do not yet exist, e.g., because a package defining the code chunk with that label has not yet been loaded. When the hook code is finally sorted for fast execution, all rules that apply are acted on and the others are ignored.

This offers the flexibility needed to handle complicated relationships between code from different packages and to set this up beforehand in a way that is independent of whether or not the packages are actually loaded in a specific document. The downside

of this is that misspellings of hook names or code labels will not raise any error, instead the rule will simply never apply!

---

**\DeclareHookRule** `\DeclareHookRule {<hook>} {<label1>} {<relation>} {<label2>}`

---

Defines a relation between `<label1>` and `<label2>` for a given `<hook>`. If `<hook>` is `??` this defines a default relation for all hooks that use the two labels, i.e., that have chunks of code labeled with `<label1>` and `<label2>`.

Currently, the supported relations are the following:

**before** or **<** Code for `<label1>` comes before code for `<label2>`.

**after** or **>** Code for `<label1>` comes after code for `<label2>`.

**incompatible-warning** Only code for either `<label1>` or `<label2>` can appear for that hook (a way to say that two packages—or parts of them—are incompatible). A warning is raised if both labels appear in the same hook.

**incompatible-error** Like **incompatible-warning** but instead of a warning a L<sup>A</sup>T<sub>E</sub>X error is raised, and the code for both labels are dropped from that hook until the conflict is resolved.

**voids** Code for `<label1>` overwrites code for `<label2>`. More precisely, code for `<label2>` is dropped for that hook. This can be used, for example if one package is a superset in functionality of another one and therefore wants to undo code in some hook and replace it with its own version.

**unrelated** The order of code for `<label1>` and `<label2>` is irrelevant. This rule is there to undo an incorrect rule specified earlier.

There can only be a single relation between two labels for a given hook, i.e., a later `\DeclareHookRule` overwrites any previous declaration. In all cases rules specific to a given hook take precedence over default rules that use `??` as the `<hook>`.

If a default rule is applied, it is done before reversing the label order in a reversed hook, e.g., **before** in a default rule effectively becomes **after** in such a hook. In contrast, a rule for a specific hook is always applied to the state after any reversal (i.e., the state you see when using `\ShowHook` on that hook).

The `<hook>` and `<label>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

**\ClearHookRule** `\ClearHookRule {<hook>} {<label1>} {<label2>}`

---

Syntactic sugar for saying that `<label1>` and `<label2>` are unrelated for the given `<hook>`.

---

`\DeclareDefaultHookRule` `\DeclareDefaultHookRule {<label1>} {<relation>} {<label2>}`

---

This sets up a relation between `<label1>` and `<label2>` for all hooks unless overwritten by a specific rule for a hook. Useful for cases where one package has a specific relation to some other package, e.g., is `incompatible` or always needs a special ordering `before` or `after`. (Technically it is just a shorthand for using `\DeclareHookRule` with `??` as the hook name.)

If such a rule is applied to a reversed hook it behaves as if the rule is reversed (e.g., `after` becomes `before`) because those rules are applied first and then the order is reversed. The rationale is that in hook pairs (in which the ordering in one is reversed) default rules have to be reversed too in nearly all scenarios. If this is not the case, a default rule can't be used or has to be overwritten with an explicit `\DeclareHookRule` for that specific hook.

Declaring default rules is only supported in the document preamble.<sup>5</sup>

The `<label>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

### 2.1.8 Querying hooks

Simpler data types, like token lists, have three possible states; they can:

- exist and be empty;
- exist and be non-empty; and
- not exist (in which case emptiness doesn't apply);

Hooks are a bit more complicated: a hook may exist or not, and independently it may or may not be empty. This means that even a hook that doesn't exist may be non-empty and it can also be disabled.

This seemingly strange state may happen when, for example, package *A* defines hook `A/foo`, and package *B* adds some code to that hook. However, a document may load package *B* before package *A*, or may not load package *A* at all. In both cases some code is added to hook `A/foo` without that hook being defined yet, thus that hook is said to be non-empty, whereas it doesn't exist. Therefore, querying the existence of a hook doesn't imply its emptiness, neither does the other way around.

Given that code or rules can be added to a hook even if it doesn't physically exist yet, means that a querying its existence has no real use case (in contrast to other variables that can only be update if they have already been declared). For that reason only the test for emptiness has a public interface.

A hook is said to be empty when no code was added to it, either to its permanent code pool, or to its “next” token list. The hook doesn't need to be declared to have code added to its code pool. A hook is said to exist when it was declared with `\NewHook` or some variant thereof. Generic hooks such as `file` and `env` hooks are automatically declared when code is added to them.

---

<sup>5</sup>Trying to do so, e.g., via `\DeclareHookRule` with `??` has bad side-effects and is not supported (though not explicitly caught for performance reasons).

---

<code>\IfHookEmptyTF</code>	★	<code>\IfHookEmptyTF {&lt;hook&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\IfHookEmptyT</code>	★	
<code>\IfHookEmptyF</code>	★	Tests if the <code>&lt;hook&gt;</code> is empty ( <i>i.e.</i> , no code was added to it using either <code>\AddToHook</code> or <code>\AddToHookNext</code> ) or such code was removed again (via <code>\RemoveFromHook</code> ), and branches to either <code>&lt;true code&gt;</code> or <code>&lt;false code&gt;</code> depending on the result.

---

The `<hook>` *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

### 2.1.9 Displaying hook code

If one has to adjust the code execution in a hook using a hook rule it is helpful to get some information about the code associated with a hook, its current order and the existing rules.

---

<code>\ShowHook</code>	<code>\ShowHook {&lt;hook&gt;}</code>
<code>\LogHook</code>	<code>\LogHook {&lt;hook&gt;}</code>

---

Displays information about the `<hook>` such as

- the code chunks (and their labels) added to it,
- any rules set up to order them,
- the computed order in which the chunks are executed,
- any code executed on the next invocation only.

`\LogHook` prints the information to the `.log` file, and `\ShowHook` prints them to the terminal/command window and starts `TEX`'s prompt (only in `\errorstopmode`) to wait for user action.

The `<hook>` can be specified using the dot-syntax to denote the current package name. See section [2.1.5](#).

Suppose a hook `example-hook` whose output of `\ShowHook{example-hook}` is:

```

1  -> The hook 'example-hook':
2  > Code chunks:
3  >   foo -> [code from package 'foo']
4  >   bar -> [from package 'bar']
5  >   baz -> [package 'baz' is here]
6  > Document-level (top-level) code (executed last):
7  >   -> [code from 'top-level']
8  > Extra code for next invocation:
9  >   -> [one-time code]
10 > Rules:
11 >   foo|baz with relation >
12 >   baz|bar with default relation <
13 > Execution order (after applying rules):
14 >   baz, foo, bar.
```

In the listing above, lines 3 to 5 show the three code chunks added to the hook and their respective labels in the format

`<label> -> <code>`

Line 7 shows the code chunk added by the user in the main document (labeled `top-level`) in the format

```
Document-level (top-level) code (executed  $\langle first/last \rangle$ ):
->  $\langle top-level\ code \rangle$ 
```

This code will be either the first or last code executed by the hook (`last` if the hook is normal, `first` if it is reversed). This chunk is not affected by rules and does not take part in sorting.

Line 9 shows the code chunk for the next execution of the hook in the format

```
->  $\langle next-code \rangle$ 
```

This code will be used and disappear at the next `\UseHook{example-hook}`, in contrast to the chunks mentioned earlier, which can only be removed from that hook by doing `\RemoveFromHook{label}[example-hook]`.

Lines 11 and 12 show the rules declared that affect this hook in the format

```
 $\langle label-1 \rangle | \langle label-2 \rangle$  with  $\langle default? \rangle$  relation  $\langle relation \rangle$ 
```

which means that the  $\langle relation \rangle$  applies to  $\langle label-1 \rangle$  and  $\langle label-2 \rangle$ , in that order, as detailed in `\DeclareHookRule`. If the relation is `default` it means that this rule applies to  $\langle label-1 \rangle$  and  $\langle label-2 \rangle$  in *all* hooks, (unless overridden by a non-default relation).

Finally, line 14 lists the labels in the hook after sorting; that is, in the order they will be executed when the hook is used.

### 2.1.10 Debugging hook code

---

```
\DebugHooksOn \DebugHooksOn ... \DebugHooksOff
\DebugHooksOff
```

---

Turn the debugging of hook code on or off. This displays most changes made to the hook data structures. The output is rather coarse and not really intended for normal use, but it can be helpful in case hooks do not work as expected. See also [2.1.9](#) for commands to inspect individual hooks.

## 2.2 L3 programming layer (expl3) interfaces

This is a quick summary of the L<sup>A</sup>T<sub>E</sub>X3 programming interfaces for use with packages written in `expl3`. In contrast to the L<sup>A</sup>T<sub>E</sub>X<sub>2 $\epsilon$</sub>  interfaces they always use mandatory arguments only, e.g., you always have to specify the  $\langle label \rangle$  for a code chunk. We therefore suggest to use the declarations discussed in the previous section even in `expl3` packages, but the choice is yours.

---

```
\hook_new:n \hook_new:n {hook}
\hook_new_reversed:n \hook_new_reversed:n {hook}
\hook_new_pair:nn \hook_new_pair:nn {hook-1} {hook-2}
```

---

Creates a new  $\langle hook \rangle$  with normal or reverse ordering of code chunks. `\hook_new_pair:nn` creates a pair of such hooks with  $\{hook-2\}$  being a reversed hook. If a hook name is already taken, an error is raised and the hook is not created.

The  $\langle hook \rangle$  can be specified using the dot-syntax to denote the current package name. See section [2.1.5](#).

<hr/> <hr/>	<code>\hook_new_with_args:nn</code>	<code>\hook_new_with_args:nn {\langle hook \rangle} {\langle number \rangle}</code>
<hr/>	<code>\hook_new_reversed_with_args:nn</code>	<code>\hook_new_reversed_with_args:nn {\langle hook \rangle} {\langle number \rangle}</code>
<hr/>	<code>\hook_new_pair_with_args:nnn</code>	<code>\hook_new_pair_with_args:nnn {\langle hook-1 \rangle} {\langle hook-2 \rangle} {\langle number \rangle}</code>

Creates a new  $\langle hook \rangle$  with normal or reverse ordering of code chunks, that takes  $\langle number \rangle$  arguments from the input stream when it is used. `\hook_new_pair_with_args:nn` creates a pair of such hooks with  $\{\langle hook-2 \rangle\}$  being a reversed hook. If a hook name is already taken, an error is raised and the hook is not created.

The  $\langle hook \rangle$  can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

<hr/> <hr/>	<code>\hook_disable_generic:n</code>	<code>\hook_disable_generic:n {\langle hook \rangle}</code>
-------------	--------------------------------------	---

Marks  $\{\langle hook \rangle\}$  as disabled. Any further attempt to add code to it or declare it, will result in an error and any call to `\hook_use:n` will simply do nothing.

This declaration is intended for use with generic hooks that are known not to work (see `lthcmdhooks-doc`) if they receive code.

The  $\langle hook \rangle$  can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

<hr/> <hr/>	<code>\hook_activate_generic:n</code>	<code>\hook_activate_generic:n {\langle hook \rangle}</code>
-------------	---------------------------------------	--

This is like `\hook_new:n` but it does nothing if the hook was previously declared with `\hook_new:n`. This declaration should be used only in special situations, e.g., when a command from another package needs to be altered and it is not clear whether a generic cmd hook (for that command) has been previously explicitly declared.

Normally `\hook_new:n` should be used instead of this.

<hr/> <hr/>	<code>\hook_use:n</code>	<code>\hook_use:n {\langle hook \rangle}</code>
<hr/>	<code>\hook_use:nnw</code>	<code>\hook_use:nnw {\langle hook \rangle} {\langle number \rangle} {\langle arg_1 \rangle} \dots {\langle arg_n \rangle}</code>

Executes the  $\{\langle hook \rangle\}$  code followed (if set up) by the code for next invocation only, then empties that next invocation code. `\hook_use:nnw` should be used for hooks declared with arguments, and should be followed by as many brace groups as the declared number of arguments. The  $\langle number \rangle$  should be the number of arguments declared for the hook. If the hook is not declared, this command does nothing and it will remove  $\langle number \rangle$  items from the input.

The  $\langle hook \rangle$  *cannot* be specified using the dot-syntax. A leading . is treated literally.

<hr/> <hr/>	<code>\hook_use_once:n</code>	<code>\hook_use_once:n {\langle hook \rangle}</code>
<hr/>	<code>\hook_use_once:nnw</code>	<code>\hook_use_once:nnw {\langle hook \rangle} {\langle number \rangle} {\langle arg_1 \rangle} \dots {\langle arg_n \rangle}</code>

Changes the  $\{\langle hook \rangle\}$  status so that from now on any addition to the hook code is executed immediately. Then execute any  $\{\langle hook \rangle\}$  code already set up. `\hook_use_once:nnw` should be used for hooks declared with arguments, and should be followed by as many brace groups as the declared number of arguments. The  $\langle number \rangle$  should be the number of arguments declared for the hook. If the hook is not declared, this command does nothing and it will remove  $\langle number \rangle$  items from the input.

The  $\langle hook \rangle$  *cannot* be specified using the dot-syntax. A leading . is treated literally.

<hr/> <hr/>	<code>\hook_gput_code:nnn</code>	<code>\hook_gput_code:nnn {\langle hook \rangle} {\langle label \rangle} {\langle code \rangle}</code>
-------------	----------------------------------	--

---

<code>\hook_gput_code_with_args:nnn</code>	<code>\hook_gput_code_with_args:nnn {&lt;hook&gt;} {&lt;label&gt;} {&lt;code&gt;}</code>
--	--

---

Adds a chunk of `<code>` to the `<hook>` labeled `<label>`. If the label already exists the `<code>` is appended to the already existing code.

If `\hook_gput_code_with_args:nnn` is used, the `<code>` can access the arguments passed to `\hook_use:nnw` (or `\hook_use_once:nnw`) with `#1`, `#2`, ..., `#n` (up to the number of arguments declared for the hook). In that case, if an actual parameter token should be added to the code, it should be doubled.

If code is added to an external `<hook>` (of the kernel or another package) then the convention is to use the package name as the `<label>` not some internal module name or some other arbitrary string.

The `<hook>` and `<label>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\hook_gput_next_code:nn</code>	<code>\hook_gput_next_code:nn {&lt;hook&gt;} {&lt;code&gt;}</code>
--------------------------------------	--

---

<code>\hook_gput_next_code_with_args:nn</code>	<code>\hook_gput_next_code_with_args:nn {&lt;hook&gt;} {&lt;code&gt;}</code>
--	--

---

Adds a chunk of `<code>` for use only in the next invocation of the `<hook>`. Once used it is gone.

If `\hook_gput_next_code_with_args:nn` is used, the `<code>` can access the arguments passed to `\hook_use:nnw` (or `\hook_use_once:nnw`) with `#1`, `#2`, ..., `#n` (up to the number of arguments declared for the hook). In that case, if an actual parameter token should be added to the code, it should be doubled.

This is simpler than `\hook_gput_code:nnn`, the code is simply appended to the hook in the order of declaration at the very end, i.e., after all standard code for the hook got executed. Thus if one needs to undo what the standard does one has to do that as part of `<code>`.

The `<hook>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\hook_gclear_next_code:n</code>	<code>\hook_gclear_next_code:n {&lt;hook&gt;}</code>
---------------------------------------	--

---

Undo any earlier `\hook_gput_next_code:nn`.

---

<code>\hook_gremove_code:nn</code>	<code>\hook_gremove_code:nn {&lt;hook&gt;} {&lt;label&gt;}</code>
------------------------------------	---

---

Removes any code for `<hook>` labeled `<label>`.

If there is no code under the `<label>` in the `<hook>`, or if the `<hook>` does not exist, a warning is issued when you attempt to use `\hook_gremove_code:nn`, and the command is ignored.

If the second argument is `*`, then all code chunks are removed. This is rather dangerous as it drops code from other packages one may not know about, so think twice before using that!

The `<hook>` and `<label>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\hook_gset_rule:nnnn</code>	<code>\hook_gset_rule:nnnn {&lt;hook&gt;} {&lt;label1&gt;} {&lt;relation&gt;} {&lt;label2&gt;}</code>
-----------------------------------	---

---

Relate `<label1>` with `<label2>` when used in `<hook>`. See `\DeclareHookRule` for the allowed `<relation>`s. If `<hook>` is ?? a default rule is specified.

The `<hook>` and `<label>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5. The dot-syntax is parsed in both `<label>` arguments, but it usually makes sense to be used in only one of them.

---

<code>\hook_if_empty_p:n *</code>	<code>\hook_if_empty:nTF {&lt;hook&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\hook_if_empty:nTF *</code>	Tests if the <code>&lt;hook&gt;</code> is empty ( <i>i.e.</i> , no code was added to it using either <code>\AddToHook</code> or <code>\AddToHookNext</code> ), and branches to either <code>&lt;true code&gt;</code> or <code>&lt;false code&gt;</code> depending on the result.

---

The `<hook>` *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

---

<code>\hook_show:n</code>	<code>\hook_show:n {&lt;hook&gt;}</code>
<code>\hook_log:n</code>	<code>\hook_log:n {&lt;hook&gt;}</code>

---

Displays information about the `<hook>` such as

- the code chunks (and their labels) added to it,
- any rules set up to order them,
- the computed order in which the chunks are executed,
- any code executed on the next invocation only.

`\hook_log:n` prints the information to the `.log` file, and `\hook_show:n` prints them to the terminal/command window and starts `TEX`'s prompt (only if `\errorstopmode`) to wait for user action.

The `<hook>` can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

---

<code>\hook_debug_on:</code>	<code>\hook_debug_on:</code>
<code>\hook_debug_off:</code>	Turns the debugging of hook code on or off. This displays changes to the hook data.

---

## 2.3 On the order of hook code execution

Chunks of code for a `<hook>` under different labels are supposed to be independent if there are no special rules set up that define a relation between the chunks. This means that you can't make assumptions about the order of execution!

Suppose you have the following declarations:

```
\NewHook{myhook}
\AddToHook{myhook}[packageA]{\typeout{A}}
\AddToHook{myhook}[packageB]{\typeout{B}}
\AddToHook{myhook}[packageC]{\typeout{C}}
```

then executing the hook with `\UseHook` will produce the `\typeout` A B C in that order. In other words, the execution order is computed to be `packageA`, `packageB`, `packageC` which you can verify with `\ShowHook{myhook}`:

```
-> The hook 'myhook':
> Code chunks:
>   packageA -> \typeout {A}
>   packageB -> \typeout {B}
>   packageC -> \typeout {C}
> Document-level (top-level) code (executed last):
>   ---
> Extra code for next invocation:
```

```

> ---
> Rules:
> ---
> Execution order:
>   packageA, packageB, packageC.

```

The reason is that the code chunks are internally saved in a property list and the initial order of such a property list is the order in which key-value pairs got added. However, that is only true if nothing other than adding happens!

Suppose, for example, you want to replace the code chunk for `packageA`, e.g.,

```

\RemoveFromHook{myhook}[packageA]
\AddToHook{myhook}[packageA]{\typeout{A alt}}

```

then your order becomes `packageB`, `packageC`, `packageA` because the label got removed from the property list and then re-added (at its end).

While that may not be too surprising, the execution order is also sometimes altered if you add a redundant rule, e.g. if you specify

```

\DeclareHookRule{myhook}{packageA}{before}{packageB}

```

instead of the previous lines we get

```

-> The hook 'myhook':
> Code chunks:
>   packageA -> \typeout {A}
>   packageB -> \typeout {B}
>   packageC -> \typeout {C}
> Document-level (top-level) code (executed last):
>   ---
> Extra code for next invocation:
>   ---
> Rules:
>   packageB|packageA with relation >
> Execution order (after applying rules):
>   packageA, packageC, packageB.

```

As you can see the code chunks are still in the same order, but in the execution order for the labels `packageB` and `packageC` have swapped places. The reason is that, with the rule there are two orders that satisfy it, and the algorithm for sorting happened to pick a different one compared to the case without rules (where it doesn't run at all as there is nothing to resolve). Incidentally, if we had instead specified the redundant rule

```

\DeclareHookRule{myhook}{packageB}{before}{packageC}

```

the execution order would not have changed.

In summary: it is not possible to rely on the order of execution unless there are rules that partially or fully define the order (in which you can rely on them being fulfilled).

## 2.4 The use of “reversed” hooks

You may have wondered why you can declare a “reversed” hook with `\NewReversedHook` and what that does exactly.

In short: the execution order of a reversed hook (without any rules!) is exactly reversed to the order you would have gotten for a hook declared with `\NewHook`.

This is helpful if you have a pair of hooks where you expect to see code added that involves grouping, e.g., starting an environment in the first and closing that environment in the second hook. To give a somewhat contrived example<sup>6</sup>, suppose there is a package adding the following:

```
\AddToHook{env/quote/before}[package-1]{\begin{itshape}}
\AddToHook{env/quote/after} [package-1]{\end{itshape}}
```

As a result, all quotes will be in italics. Now suppose further that another `package-too` makes the quotes also in blue and therefore adds:

```
\usepackage{color}
\AddToHook{env/quote/before}[package-too]{\begin{color}{blue}}
\AddToHook{env/quote/after} [package-too]{\end{color}}
```

Now if the `env/quote/after` hook would be a normal hook we would get the same execution order in both hooks, namely:

```
package-1, package-too
```

(or vice versa) and as a result, would get:

```
\begin{itshape}\begin{color}{blue} ...
\end{itshape}\end{color}
```

and an error message saying that `\begin{color}` was ended by `\end{itshape}`. With `env/quote/after` declared as a reversed hook the execution order is reversed and so all environments are closed in the correct sequence and `\ShowHook` would give us the following output:

```
-> The hook 'env/quote/after':
> Code chunks:
>   package-1 -> \end {itshape}
>   package-too -> \end {color}
> Document-level (top-level) code (executed first):
>   ---
> Extra code for next invocation:
>   ---
> Rules:
>   ---
> Execution order (after reversal):
>   package-too, package-1.
```

If there is a matching default rule (done with `\DeclareDefaultHookRule` or with `??` for the hook name) then this default rule is applied before the reversal so that the order in the reversed hook mirrors the one in the normal hook. However, all rules specific to a hook happen always after the reversal of the execution order, so if you alter the order you will probably have to alter it in both hooks, not just in one, but that depends on the use case.

---

<sup>6</sup>There are simpler ways to achieve the same effect.

## 2.5 Difference between “normal” and “one-time” hooks

When executing a hook a developer has the choice of using either `\UseHook` or `\UseOneTimeHook` (or their expl3 equivalents `\hook_use:n` and `\hook_use_once:n`). This choice affects how `\AddToHook` is handled after the hook has been executed for the first time.

With normal hooks adding code via `\AddToHook` means that the code chunk is added to the hook data structure and then used each time `\UseHook` is called.

With one-time hooks it this is handled slightly differently: After `\UseOneTimeHook` has been called, any further attempts to add code to the hook via `\AddToHook` will simply execute the `<code>` immediately.

This has some consequences one needs to be aware of:

- If `<code>` is added to a normal hook after the hook was executed and it is never executed again for one or the other reason, then this new `<code>` will never be executed.
- In contrast if that happens with a one-time hook the `<code>` is executed immediately.

In particular this means that construct such as

```
\AddToHook{myhook}  
{ <code-1> \AddToHook{myhook}{<code-2>} <code-3> }
```

works for one-time hooks<sup>7</sup> (all three code chunks are executed one after another), but it makes little sense with a normal hook, because with a normal hook the first time `\UseHook{myhook}` is executed it would

- execute `<code-1>`,
- then execute `\AddToHook{myhook}{code-2}` which adds the code chunk `<code-2>` to the hook for use on the next invocation,
- and finally execute `<code-3>`.

The second time `\UseHook` is called it would execute the above and in addition `<code-2>` as that was added as a code chunk to the hook in the meantime. So each time the hook is used another copy of `<code-2>` is added and so that code chunk is executed `<# of invocations> - 1` times.

## 2.6 Generic hooks provided by packages

The hook management system also implements a category of hooks that are called “Generic Hooks”. Normally a hook has to be explicitly declared before it can be used in code. This ensures that different packages are not using the same hook name for unrelated purposes—something that would result in absolute chaos. However, there are a number of “standard” hooks where it is unreasonable to declare them beforehand, e.g., each and every command has (in theory) an associated **before** and **after** hook. In such cases, i.e., for command, environment or file hooks, they can be used simply by adding code to them with `\AddToHook`. For more specialized generic hooks, e.g., those provided

---

<sup>7</sup>This is sometimes used with `\AtBeginDocument` which is why it is supported.

by `babel`, you have to additionally enable them with `\ActivateGenericHook` as explained below.

The generic hooks provided by L<sup>A</sup>T<sub>E</sub>X are those for `cmd`, `env`, `file`, `include`, `package`, and `class`, and all these are available out of the box: you only have to use `\AddToHook` to add code to them, but you don't have to add `\UseHook` or `\UseOneTimeHook` to your code, because this is already done for you (or, in the case of `cmd` hooks, the command's code is patched at `\begin{document}`, if necessary).

However, if you want to provide further generic hooks in your own code, the situation is slightly different. To do this you should use `\UseHook` or `\UseOneTimeHook`, but *without declaring the hook* with `\NewHook`. As mentioned earlier, a call to `\UseHook` with an undeclared hook name does nothing. So as an additional setup step, you need to explicitly activate your generic hook. Note that a generic hook produced in this way is always a normal hook.

For a truly generic hook, with a variable part in the hook name, such upfront activation would be difficult or impossible, because you typically do not know what kind of variable parts may come up in real documents.

For example, `babel` provides hooks such as `babel/<language>/afterextras`. However, language support in `babel` is often done through external language packages. Thus doing the activation for all languages inside the core `babel` code is not a viable approach. Instead it needs to be done by each language package (or by the user who wants to use a particular hook).

Because the hooks are not declared with `\NewHook` their names should be carefully chosen to ensure that they are (likely to be) unique. Best practice is to include the package or command name, as was done in the `babel` example above.

Generic hooks defined in this way are always normal hooks (i.e., you can't implement reversed hooks this way). This is a deliberate limitation, because it speeds up the processing considerably.

## 2.7 Hooks with arguments

Sometimes it is necessary to pass contextual information to a hook, and, for one reason or another, it is not feasible to store such information in macros. To serve this purpose, hooks can be declared with arguments, so that the programmer can pass along the data necessary for the code in the hook to function properly.

A hook with arguments works mostly like a regular hook, and most commands that work for regular hooks, also work for hooks that take arguments. The differences are when the hook is declared (`\NewHookWithArguments` is used instead of `\NewHook`), then code can be added with both `\AddToHook` and `\AddToHookWithArguments`, and when the hook is used (`\UseHookWithArguments` instead of `\UseHook`).

A hook with arguments must be declared as such (before it is first used, as all regular hooks) using `\NewHookWithArguments{<hook>}{<number>}`. All code added to that hook can then use `#1` to access the first argument, `#2` to access the second, and so forth up to the number of arguments declared. However, it is still possible to add code with references to the arguments of a hook that was not yet declared (we will discuss that later). At their core, hooks are macros, so T<sub>E</sub>X's limit of 9 arguments applies, and a low-level T<sub>E</sub>X error is raised if you try to reference an argument number that doesn't exist.

To use a hook with arguments, just write `\UseHookWithArguments{<hook>}{<number>}` followed by a braced list of the arguments. For example, if the hook `test` takes three arguments, write:

```
\UseHookWithArguments{test}{3}{arg-1}{arg-2}{arg-3}
```

then, in the `<code>` of the hook, all instances of `#1` will be replaced by `arg-1`, `#2` by `arg-2` and so on. If, at the point of usage, the programmer provides more arguments than the hook is declared to take, the excess arguments are simply ignored by the hook. Behavior is unpredictable<sup>8</sup> if too few arguments are provided. If the hook isn't declared, `<number>` arguments are removed from the input stream.

Adding code to a hook with arguments can be done with `\AddToHookWithArguments` as well as with the regular `\AddToHook`, to achieve different outcomes. The main difference when it comes to adding code to a hook, in this case, is firstly the possibility of accessing a hook's arguments, of course, and second, how parameter tokens (`#6`) are treated.

Using `\AddToHook` in a hook that takes arguments will work as it does for all other hooks. This allows a package developer to add arguments to a hook that otherwise had none without having to worry about compatibility. This means that, for example:

```
\AddToHook{test}{\def\foo#1{Hello, #1!}}
```

will define the same macro `\foo` regardless if the hook `test` takes arguments or not.

Using `\AddToHookWithArguments` allows the `<code>` added to access the arguments of the hook with `#1`, `#2`, and so forth, up to the number of the arguments declared in the hook. This means that if one wants to add a `#6` to the `<code>` that token must be doubled in the input. The same definition from above, using `\AddToHookWithArguments`, needs to be rewritten:

```
\AddToHookWithArguments{test}{\def\foo##1{Hello, ##1!}}
```

Extending the above example to use the hook arguments, we could rewrite something like (now from declaration to usage, to get the whole picture):

```
\NewHookWithArguments{test}{1}
\AddToHookWithArguments{test}{%
  \typeout{Defining foo with "#1"}
  \def\foo##1{Hello, ##1! Some text after: #1}%
}
\UseHook{test}{Howdy!}
\ShowCommand\foo
```

Running the code above prints in the terminal:

```
Defining foo with "Howdy!"
> \foo=macro:
#1->Hello, #1! Some text after: Howdy!.
```

---

<sup>8</sup>The hook *will* take the declared number of arguments, and what will happen depends on what was grabbed, and what the hook code does with its arguments.

Note how `##1` in the call to `\AddToHookWithArguments` became `#1`, and the `#1` was replaced by the argument passed to the hook. Should the hook be used again, with a different argument, the definition would naturally change.

It is possible to add code referencing a hook’s arguments before such hook is declared and the number of hooks is fixed. However, if some code is added to the hook, that references more arguments than will be declared for the hook, there will be a low-level `TeX` error about an “Illegal parameter number” at the time the hook is declared, which will be hard to track down because at that point `TeX` can’t know whence the offending code came from. Thus it is important that package writers explicitly document how many arguments (if any) each hook can take, so users of those packages know how many arguments can be referenced, and equally important, what each argument means.

## 2.8 Private `LaTeX` kernel hooks

There are a few places where it is absolutely essential for `LaTeX` to function correctly that code is executed in a precisely defined order. Even that could have been implemented with the hook management (by adding various rules to ensure the appropriate ordering with respect to other code added by packages). However, this makes every document unnecessary slow, because there has to be sorting even though the result is predetermined. Furthermore it forces package writers to unnecessarily add such rules if they add further code to the hook (or break `LaTeX`).

For that reason such code is not using the hook management, but instead private kernel commands directly before or after a public hook with the following naming convention: `\@kernel@before@hook` or `\@kernel@after@hook`. For example, in `\enddocument` you find

```
\UseHook{enddocument}%
\@kernel@after@enddocument
```

which means first the user/package-accessible `enddocument` hook is executed and then the internal kernel hook. As their name indicates these kernel commands should not be altered by third-party packages, so please refrain from that in the interest of stability and instead use the public hook next to it.<sup>9</sup>

## 2.9 Legacy `LaTeX 2ε` interfaces

`LaTeX 2ε` offered a small number of hooks together with commands to add to them. They are listed here and are retained for backwards compatibility.

With the new hook management, several additional hooks have been added to `LaTeX` and more will follow. See the next section for what is already available.

---

<sup>9</sup>As with everything in `TeX` there is not enforcement of this rule, and by looking at the code it is easy to find out how the kernel adds to them. The main reason of this section is therefore to say “please don’t do that, this is unconfigurable code!”

---

<code>\AtBeginDocument</code>	<code>\AtBeginDocument [<i>&lt;label&gt;</i>] {<i>&lt;code&gt;</i>}</code>
-------------------------------	--

---

If used without the optional argument *<label>*, it works essentially like before, i.e., it is adding *<code>* to the hook `begindocument` (which is executed inside `\begin{document}`). However, all code added this way is labeled with the label `top-level` (see section 2.1.6) if done outside of a package or class or with the package/class name if called inside such a file (see section 2.1.5).

This way one can add code to the hook using `\AddToHook` or `\AtBeginDocument` using a different label and explicitly order the code chunks as necessary, e.g., run some code before or after another package's code. When using the optional argument the call is equivalent to running `\AddToHook {begindocument} [<label>] {<code>}`.

`\AtBeginDocument` is a wrapper around the `begindocument` hook (see section 3.2), which is a one-time hook. As such, after the `begindocument` hook is executed at `\begin{document}` any attempt to add *<code>* to this hook with `\AtBeginDocument` or with `\AddToHook` will cause that *<code>* to execute immediately instead. See section 2.5 for more on one-time hooks.

For important packages with known order requirement we may over time add rules to the kernel (or to those packages) so that they work regardless of the loading-order in the document.

---

<code>\AtEndDocument</code>	<code>\AtEndDocument [<i>&lt;label&gt;</i>] {<i>&lt;code&gt;</i>}</code>
-----------------------------	--

---

Like `\AtBeginDocument` but for the `enddocument` hook.

The few hooks that existed previously in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> used internally commands such as `@begindocumenthook` and packages sometimes augmented them directly rather than working through `\AtBeginDocument`. For that reason there is currently support for this, that is, if the system detects that such an internal legacy hook command contains code it adds it to the new hook system under the label `legacy` so that it doesn't get lost.

However, over time the remaining cases of direct usage need updating because in one of the future release of L<sup>A</sup>T<sub>E</sub>X we will turn this legacy support off, as it does unnecessary slow down the processing.

### 3 L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> commands and environments augmented by hooks

In this section we describe the standard hooks that are now offered by L<sup>A</sup>T<sub>E</sub>X, or give pointers to other documents in which they are described. This section will grow over time (and perhaps eventually move to `usrguide3`).

#### 3.1 Generic hooks

As stated earlier, with the exception of generic hooks, all hooks must be declared with `\NewHook` before they can be used. All generic hooks have names of the form “*<type>/<name>/<position>*”, where *<type>* is from the predefined list shown below, and *<name>* is the variable part whose meaning will depend on the *<type>*. The last component, *<position>*, has more complex possibilities: it can always be `before` or `after`; for `env` hooks, it can also be `begin` or `end`; and for `include` hooks it can also be `end`. Each specific hook is documented below, or in `lthooks-doc.pdf` or `ltfilehook-doc.pdf`.

The generic hooks provided by L<sup>A</sup>T<sub>E</sub>X belong to one of the six types:

- env** Hooks executed before and after environments –  $\langle name \rangle$  is the name of the environment, and available values for  $\langle position \rangle$  are **before**, **begin**, **end**, and **after**;
- cmd** Hooks added to and executed before and after commands –  $\langle name \rangle$  is the name of the command, and available values for  $\langle position \rangle$  are **before** and **after**;
- file** Hooks executed before and after reading a file –  $\langle name \rangle$  is the name of the file (with extension), and available values for  $\langle position \rangle$  are **before** and **after**;
- package** Hooks executed before and after loading packages –  $\langle name \rangle$  is the name of the package, and available values for  $\langle position \rangle$  are **before** and **after**;
- class** Hooks executed before and after loading classes –  $\langle name \rangle$  is the name of the class, and available values for  $\langle position \rangle$  are **before** and **after**;
- include** Hooks executed before and after `\included` files –  $\langle name \rangle$  is the name of the included file (without the `.tex` extension), and available values for  $\langle position \rangle$  are **before**, **end**, and **after**.

Each of the hooks above are detailed in the following sections and in linked documentation.

### 3.1.1 Generic hooks for all environments

Every environment  $\langle env \rangle$  has now four associated hooks coming with it:

- env/ $\langle env \rangle$ /before** This hook is executed as part of `\begin` as the very first action, in particular prior to starting the environment group. Its scope is therefore not restricted by the environment.
- env/ $\langle env \rangle$ /begin** This hook is executed as part of `\begin` directly in front of the code specific to the environment start (e.g., the third argument of `\NewDocumentEnvironment` and the second argument of `\newenvironment`). Its scope is the environment body.
- env/ $\langle env \rangle$ /end** This hook is executed as part of `\end` directly in front of the code specific to the end of the environment (e.g., the forth argument of `\NewDocumentEnvironment` and the third argument of `\newenvironment`).
- env/ $\langle env \rangle$ /after** This hook is executed as part of `\end` after the code specific to the environment end and after the environment group has ended. Its scope is therefore not restricted by the environment.  
  
The hook is implemented as a reversed hook so if two packages add code to **env/ $\langle env \rangle$ /before** and to **env/ $\langle env \rangle$ /after** they can add surrounding environments and the order of closing them happens in the right sequence.

Given that these generic hook names involve `/` as part of their name they would not work if one tries to define an environment using a name that involves a `/`.<sup>10</sup>

Generic environment hooks are never one-time hooks even with environments that are supposed to appear only once in a document.<sup>11</sup> In contrast to other hooks there is also no need to declare them using `\NewHook`.

<sup>10</sup>Officially, L<sup>A</sup>T<sub>E</sub>X names for environments should only consist of a sequence of letters, numbers, and the character `*`, i.e., this is not a new restriction.

<sup>11</sup>Thus if one adds code to such hooks after the environment has been processed, it will only be executed if the environment appears again and if that doesn't happen the code will never get executed.

The hooks are only executed if `\begin{env}` and `\end{env}` is used. If the environment code is executed via low-level calls to `\env` and `\endenv` (e.g., to avoid the environment grouping) they are not available. If you want them available in code using this method, you would need to add them yourself, i.e., write something like

```
\UseHook{env/quote/before}\quote
...
\endquote\UseHook{env/quote/after}
```

to add the outer hooks, etc.

Largely for compatibility with existing packages, the following four commands are also available to set the environment hooks; but for new packages we recommend directly using the hook names and `\AddToHook`.

---

---

<code>\BeforeBeginEnvironment</code>	<code>\BeforeBeginEnvironment</code> [ <i>label</i> ] { <i>env</i> } { <i>code</i> }
--------------------------------------	--

This declaration adds to the `env/⟨env⟩/before` hook using the *label*. If *label* is not given, the *default label* is used (see section 2.1.5).

---

---

<code>\AtBeginEnvironment</code>	<code>\AtBeginEnvironment</code> [ <i>label</i> ] { <i>env</i> } { <i>code</i> }
----------------------------------	--

This is like `\BeforeBeginEnvironment` but it adds to the `env/⟨env⟩/begin` hook.

---

---

<code>\AtEndEnvironment</code>	<code>\AtEndEnvironment</code> [ <i>label</i> ] { <i>env</i> } { <i>code</i> }
--------------------------------	--

This is like `\BeforeBeginEnvironment` but it adds to the `env/⟨env⟩/end` hook.

---

---

<code>\AfterEndEnvironment</code>	<code>\AfterEndEnvironment</code> [ <i>label</i> ] { <i>env</i> } { <i>code</i> }
-----------------------------------	---

This is like `\BeforeBeginEnvironment` but it adds to the `env/⟨env⟩/after` hook.

### 3.1.2 Generic hooks for commands

Similar to environments there are now (at least in theory) two generic hooks available for any L<sup>A</sup>T<sub>E</sub>X command. These are

**cmd/⟨name⟩/before** This hook is executed at the very start of the command execution.

**cmd/⟨name⟩/after** This hook is executed at the very end of the command body. It is implemented as a reversed hook.

In practice there are restrictions and especially the **after** hook works only with a subset of commands. Details about these restrictions are documented in `ltxcmdhooks-doc.pdf` or with code in `ltxcmdhooks-code.pdf`.

### 3.1.3 Generic hooks provided by file loading operations

There are several hooks added to L<sup>A</sup>T<sub>E</sub>X's process of loading file via its high-level interfaces such as `\input`, `\include`, `\usepackage`, `\RequirePackage`, etc. These are documented in `ltfilehook-doc.pdf` or with code in `ltfilehook-code.pdf`.

### 3.2 Hooks provided by `\begin{document}`

Until 2020 `\begin{document}` offered exactly one hook that one could add to using `\AtBeginDocument`. Experiences over the years have shown that this single hook in one place was not enough and as part of adding the general hook management system a number of additional hooks have been added at this point. The places for these hooks have been chosen to provide the same support as offered by external packages, such as `etoolbox` and others that augmented `\document` to gain better control.

Supported are now the following hooks (all of them one-time hooks):

**`begindocument/before`** This hook is executed at the very start of `\document`, one can think of it as a hook for code at the end of the preamble section and this is how it is used by `etoolbox`'s `\AtEndPreamble`.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

**`begindocument`** This hook is added to by using `\AddToHook{begindocument}` or by using `\AtBeginDocument` and it is executed after the `.aux` file has been read and most initialization are done, so they can be altered and inspected by the hook code. It is followed by a small number of further initializations that shouldn't be altered and are therefore coming later.

The hook should not be used to add material for typesetting as we are still in  $\text{\LaTeX}$ 's initialization phase and not in the document body. If such material needs to be added to the document body use the next hook instead.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

**`begindocument/end`** This hook is executed at the end of the `\document` code in other words at the beginning of the document body. The only command that follows it is `\ignorespaces`.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

The generic hooks executed by `\begin` also exist, i.e., `env/document/before` and `env/document/begin`, but with this special environment it is better use the dedicated one-time hooks above.

### 3.3 Hooks provided by `\end{document}`

$\text{\LaTeX} 2_{\epsilon}$  has always provided `\AtEndDocument` to add code to the `\end{document}`, just in front of the code that is normally executed there. While this was a big improvement over the situation in  $\text{\LaTeX} 2.09$ , it was not flexible enough for a number of use cases and so packages, such as `etoolbox`, `atveryend` and others patched `\enddocument` to add additional points where code could be hooked into.

Patching using packages is always problematical as leads to conflicts (code availability, ordering of patches, incompatible patches, etc.). For this reason a number of additional hooks have been added to the `\enddocument` code to allow packages to add code in various places in a controlled way without the need for overwriting or patching the core code.

Supported are now the following hooks (all of them one-time hooks):

**enddocument** The hook associated with `\AtEndDocument`. It is immediately called at the beginning of `\enddocument`.

When this hook is executed there may be still unprocessed material (e.g., floats on the deferlist) and the hook may add further material to be typeset. After it, `\clearpage` is called to ensure that all such material gets typeset. If there is nothing waiting the `\clearpage` has no effect.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

**enddocument/afterlastpage** As the name indicates this hook should not receive code that generates material for further pages. It is the right place to do some final housekeeping and possibly write out some information to the `.aux` file (which is still open at this point to receive data, but since there will be no more pages you need to write to it using `\immediate\write`). It is also the correct place to set up any testing code to be run when the `.aux` file is re-read in the next step.

After this hook has been executed the `.aux` file is closed for writing and then read back in to do some tests (e.g., looking for missing references or duplicated labels, etc.).

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

**enddocument/afteraux** At this point, the `.aux` file has been reprocessed and so this is a possible place for final checks and display of information to the user. However, for the latter you might prefer the next hook, so that your information is displayed after the (possibly longish) list of files if that got requested via `\listfiles`.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

**enddocument/info** This hook is meant to receive code that write final information messages to the terminal. It follows immediately after the previous hook (so both could have been combined, but then packages adding further code would always need to also supply an explicit rule to specify where it should go.

This hook already contains some code added by the kernel (under the labels `kernel/filelist` and `kernel/warnings`), namely the list of files when `\listfiles` has been used and the warnings for duplicate labels, missing references, font substitutions etc.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

**enddocument/end** Finally, this hook is executed just in front of the final call to `\@@end`.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).is it even possible to add code after this one?

There is also the hook `shipout/lastpage`. This hook is executed as part of the last `\shipout` in the document to allow package to add final `\special`'s to that page. Where this hook is executed in relation to those from the above list can vary from document to document. Furthermore to determine correctly which of the `\shipouts` is the last one,

L<sup>A</sup>T<sub>E</sub>X needs to be run several times, so initially it might get executed on the wrong page. See section 3.4 for where to find the details.

It is also possible to use the generic `env/document/end` hook which is executed by `\end`, i.e., just in front of the first hook above. Note however that the other generic `\end` environment hook, i.e., `env/document/after` will never get executed, because by that time L<sup>A</sup>T<sub>E</sub>X has finished the document processing.

### 3.4 Hooks provided by `\shipout` operations

There are several hooks and mechanisms added to L<sup>A</sup>T<sub>E</sub>X's process of generating pages. These are documented in `ltshipout-doc.pdf` or with code in `ltshipout-code.pdf`.

### 3.5 Hooks provided for paragraphs

The paragraph processing has been augmented to include a number of internal and public hooks. These are documented in `ltpara-doc.pdf` or with code in `ltpara-code.pdf`.

### 3.6 Hooks provided in NFSS commands

In languages that need to support for more than one script in parallel (and thus several sets of fonts, e.g., supporting both Latin and Japanese fonts), NFSS font commands such as `\sffamily` need to switch both the Latin family to “Sans Serif” and in addition alter a second set of fonts.

To support this, several NFSS commands have hooks to which such support can be added.

**rmfamily** After `\rmfamily` has done its initial checks and prepared a font series update, this hook is executed before `\selectfont`.

**sffamily** This is like the `rmfamily` hook, but for the `\sffamily` command.

**ttfamily** This is like the `rmfamily` hook, but for the `\ttfamily` command.

**normalfont** The `\normalfont` command resets the font encoding, family, series and shape to their document defaults. It then executes this hook and finally calls `\selectfont`.

**expand@font@defaults** The internal `\expand@font@defaults` command expands and saves the current defaults for the metafamilies (`rm/sf/tt`) and the metaseries (`bf/md`). If the NFSS machinery has been augmented, e.g., for Chinese or Japanese fonts, then further defaults may need to be set at this point. This can be done in this hook which is executed at the end of this macro.

**bfseries/defaults, bfseries** If the `\bfdefault` was explicitly changed by the user, its new value is used to set the `bf` series defaults for the metafamilies (`rm/sf/tt`) when `\bfseries` is called. The `bfseries/defaults` hook allows further adjustments to be made in this case. This hook is only executed if such a change is detected. In contrast, the `bfseries` hook is always executed just before `\selectfont` is called to change to the new series.

**mdseries/defaults, mdseries** These two hooks are like the previous ones but they are in the `\mdseries` command.

**selectfont** This hook is executed inside `\selectfont`, after the current values for *encoding*, *family*, *series*, *shape*, and *size* are evaluated and the new font is selected (and if necessary loaded). After the hook has executed, NFSS will still do any updates necessary for a new *size* (such as changing the size of `\strut`) and any updates necessary to a change in *encoding*.

This hook is intended for use cases where, in parallel to a change in the main font, some other fonts need to be altered (e.g., in CJK processing where you may need to deal with several different alphabets).

### 3.7 Hook provided by the mark mechanism

See `ltmarks-doc.pdf` for details.

**insertmark** This hook allows for a special setup while `\InsertMark` inserts a mark. It is executed in group so local changes only apply to the mark being inserted.

## 4 The Implementation

```

1 <@@=hook>
2 <*2ekernel | latexrelease>
3 \ExplSyntaxOn
4 <latexrelease> \NewModuleRelease{2020/10/01}{lthooks}
5 <latexrelease> {The~hook~management~system}
```

### 4.1 Debugging

```

\g__hook_debug_bool Holds the current debugging state.
6 \bool_new:N \g__hook_debug_bool
(End of definition for \g__hook_debug_bool.)

\hook_debug_on: Turns debugging on and off by redefining \__hook_debug:n.
\hook_debug_off:
\__hook_debug:n
\__hook_debug_gset:
7 \cs_new_eq:NN \__hook_debug:n \use_none:n
8 \cs_new_protected:Npn \hook_debug_on:
9 {
10   \bool_gset_true:N \g__hook_debug_bool
11   \__hook_debug_gset:
12 }
13 \cs_new_protected:Npn \hook_debug_off:
14 {
15   \bool_gset_false:N \g__hook_debug_bool
16   \__hook_debug_gset:
17 }
18 \cs_new_protected:Npn \__hook_debug_gset:
19 {
20   \cs_gset_protected:Npx \__hook_debug:n ##1
21   { \bool_if:NT \g__hook_debug_bool {##1} }
22 }
```

(End of definition for `\hook_debug_on:` and others. These functions are documented on page 216.)

## 4.2 Borrowing from internals of other kernel modules

`\__hook_str_compare:nn` Private copy of `\__str_if_eq:nn`  
`23 \cs_new_eq:NN \__hook_str_compare:nn \__str_if_eq:nn`  
*(End of definition for \\_\_hook\_str\_compare:nn.)*

## 4.3 Declarations

`\l__hook_tmpa_bool` Scratch boolean used throughout the package.  
`24 \bool_new:N \l__hook_tmpa_bool`  
*(End of definition for \l\_\_hook\_tmpa\_bool.)*

`\l__hook_return_tl` Scratch variables used throughout the package.  
`\l__hook_tmpa_tl` `25 \tl_new:N \l__hook_return_tl`  
`\l__hook_tmpb_tl` `26 \tl_new:N \l__hook_tmpa_tl`  
`27 \tl_new:N \l__hook_tmpb_tl`  
*(End of definition for \l\_\_hook\_return\_tl, \l\_\_hook\_tmpa\_tl, and \l\_\_hook\_tmpb\_tl.)*

`\g__hook_all_seq` In a few places we need a list of all hook names ever defined so we keep track if them in this sequence.  
`28 \seq_new:N \g__hook_all_seq`  
*(End of definition for \g\_\_hook\_all\_seq.)*

`\l__hook_cur_hook_tl` Stores the name of the hook currently being sorted.  
`29 \tl_new:N \l__hook_cur_hook_tl`  
*(End of definition for \l\_\_hook\_cur\_hook\_tl.)*

`\l__hook_work_prop` A property list holding a copy of the `\g__hook_⟨hook⟩_code_prop` of the hook being sorted to work on, so that changes don't act destructively on the hook data structure.  
`30 \prop_new:N \l__hook_work_prop`  
*(End of definition for \l\_\_hook\_work\_prop.)*

`\g__hook_used_prop` All hooks that receive code (for use in debugging display).  
`31 \prop_new:N \g__hook_used_prop`  
*(End of definition for \g\_\_hook\_used\_prop.)*

`\g__hook_hook_curr_name_tl` Default label used for hook commands, and a stack to keep track of packages within packages.  
`\g__hook_name_stack_seq` `32 \tl_new:N \g__hook_hook_curr_name_tl`  
`33 \seq_new:N \g__hook_name_stack_seq`  
*(End of definition for \g\_\_hook\_hook\_curr\_name\_tl and \g\_\_hook\_name\_stack\_seq.)*

`\__hook_tmp:w` Temporary macro for generic usage.  
`34 \cs_new_eq:NN \__hook_tmp:w ?`  
*(End of definition for \\_\_hook\_tmp:w.)*

\c__hook_empty_tl \c__hook_nine_parameters_tl	An empty token list, and one containing nine parameters. <pre> 35 \tl_const:Nn \c__hook_empty_tl { } 36 \tl_const:Nn \c__hook_nine_parameters_tl { #1#2#3#4#5#6#7#8#9 } </pre> <i>(End of definition for \c__hook_empty_tl and \c__hook_nine_parameters_tl.)</i>
\tl_gremove_once:Nx \tl_show:x \tl_log:x \tl_set:Ne \cs_replacement_spec:c \prop_put:Nne \str_count:e	Some variants of expl3 functions. <i>FMi: should probably be moved to expl3</i> <pre> 37 \cs_generate_variant:Nn \tl_gremove_once:Nn { Nx } 38 \cs_generate_variant:Nn \tl_show:n { x } 39 \cs_generate_variant:Nn \tl_log:n { x } 40 \cs_generate_variant:Nn \tl_set:Nn { Ne } 41 \cs_generate_variant:Nn \cs_replacement_spec:N { c } 42 \cs_generate_variant:Nn \prop_put:Nnn { Nne } 43 \cs_generate_variant:Nn \str_count:n { e } </pre> <i>(End of definition for \tl_gremove_once:Nx and others.)</i>
\s__hook_mark	Scan mark used for delimited arguments. <pre> 44 \scan_new:N \s__hook_mark </pre> <i>(End of definition for \s__hook_mark.)</i>
\_hook_use_none_delimit_by_s_mark:w \_hook_use_i_delimit_by_s_mark:nw	Removes tokens until the next \s__hook_mark. <pre> 45 \cs_new:Npn \_hook_use_none_delimit_by_s_mark:w #1 \s__hook_mark { } 46 \cs_new:Npn \_hook_use_i_delimit_by_s_mark:nw #1 #2 \s__hook_mark {#1} </pre> <i>(End of definition for \_hook_use_none_delimit_by_s_mark:w and \_hook_use_i_delimit_by_s_mark:nw.)</i>
\_hook_tl_set:cn	Private copies of a few expl3 functions. l3debug will only add debugging to the public names, not to these copies, so we don't have to use \debug_suspend: and \debug_resume: everywhere. Functions like \_hook_tl_set:Nn have to be redefined, rather than copied because in expl3 they use \__kernel_tl_(g)set:Nx, which is also patched by l3debug. <pre> 47 \cs_new_protected:Npn \_hook_tl_set:cn #1#2 48 { \cs_set_nopar:cpx {#1} { \__kernel_exp_not:w {#2} } } </pre> <i>(End of definition for \_hook_tl_set:cn.)</i>
\_hook_tl_gset:Nn \_hook_tl_gset:Nx \_hook_tl_gset:cn \_hook_tl_gset:co \_hook_tl_gset:cx	Same as above. <pre> 49 \cs_new_protected:Npn \_hook_tl_gset:Nn #1#2 50 { \cs_gset_nopar:Npx #1 { \__kernel_exp_not:w {#2} } } 51 \cs_new_protected:Npn \_hook_tl_gset:Nx #1#2 52 { \cs_gset_nopar:Npx #1 {#2} } 53 \cs_generate_variant:Nn \_hook_tl_gset:Nn { c, co } 54 \cs_generate_variant:Nn \_hook_tl_gset:Nx { c } </pre> <i>(End of definition for \_hook_tl_gset:Nn.)</i>
\_hook_tl_gput_right:Nn \_hook_tl_gput_right:Ne \_hook_tl_gput_right:cn	Same as above. <pre> 55 \cs_new_protected:Npn \_hook_tl_gput_right:Nn #1#2 56 { \_hook_tl_gset:Nx #1 { \__kernel_exp_not:w \exp_after:wN { #1 #2 } } } 57 \cs_generate_variant:Nn \_hook_tl_gput_right:Nn { Ne, cn } </pre>

(End of definition for `\__hook_tl_gput_right:Nn`.)

`\__hook_tl_gput_left:Nn` Same as above.

```
58 \cs_new_protected:Npn \__hook_tl_gput_left:Nn #1#2
59 {
60   \__hook_tl_gset:Nx #1
61   { \__kernel_exp_not:w {#2} \__kernel_exp_not:w \exp_after:wN {#1} }
62 }
```

(End of definition for `\__hook_tl_gput_left:Nn`.)

`\__hook_tl_gset_eq:NN` Same as above.

```
63 \cs_new_eq:NN \__hook_tl_gset_eq:NN \tl_gset_eq:NN
```

(End of definition for `\__hook_tl_gset_eq:NN`.)

`\__hook_tl_gclear:N` Same as above.

```
\__hook_tl_gclear:c
64 \cs_new_protected:Npn \__hook_tl_gclear:N #1
65 { \__hook_tl_gset_eq:NN #1 \c_empty_tl }
66 \cs_generate_variant:Nn \__hook_tl_gclear:N { c }
```

(End of definition for `\__hook_tl_gclear:N`.)

## 4.4 Providing new hooks

### 4.4.1 The data structures of a hook

`\g__hook_⟨hook⟩_code_prop` Hooks have a name (called `⟨hook⟩` in the description below) and for each hook we have  
`\__hook_⟨hook⟩` to provide a number of data structures. These are

`\g__hook_⟨hook⟩_reversed_tl` `\g__hook_⟨hook⟩_code_prop` A property list holding the code for the hook in separate  
`\g__hook_⟨hook⟩_declared_tl` chunks. The keys are by default the package names that add code to the hook, but  
`\g__hook_⟨hook⟩_parameter_tl` it is possible for packages to define other keys.  
`\__hook_next_⟨hook⟩`

`\__hook_toplevel_⟨hook⟩` `\g__hook_⟨hook⟩_rule_⟨label1⟩|⟨label2⟩_tl` A token list holding the relation be-  
 tween `⟨label1⟩` and `⟨label2⟩` in the `⟨hook⟩`. The `⟨labels⟩` are lexically (reverse)  
 sorted to ensure that two labels always point to the same token list. For global  
 rules, the `⟨hook⟩` name is ??.

`\__hook_⟨hook⟩` The code that is actually executed when the hook is called in the doc-  
 ument is stored in this token list. It is constructed from the code chunks applying  
 the information. This token list is named like that so that in case of an error inside  
 the hook, the reported token list in the error is shorter, and to make it simpler to  
 normalize hook names in `\__hook_make_name:n`.

`\g__hook_⟨hook⟩_reversed_tl` Some hooks are “reversed”. This token list stores a - for  
 such hook so that it can be identified. The - character is used because `⟨reversed⟩`1  
 is +1 for normal hooks and -1 for reversed ones.

`\g__hook_⟨hook⟩_declared_tl` This token list serves as a marker for the hook being  
 officially declared. Its existence is tested to raise an error in case another declaration  
 is attempted.

`\c_hook_⟨hook⟩_parameter_tl` This token list stores the parameter text for a declared hook (its existence almost completely intersects the token list above), which is used for managing hooks with arguments.

`\__hook_toplevel_⟨hook⟩` This token list stores the code inserted in the hook from the user’s document, in the `top-level` label. This label is special, and doesn’t participate in sorting. Instead, all code is appended to it and executed after (or before, if the hook is reversed) the normal hook code, but before the `next` code chunk.

`\__hook_next_⟨hook⟩` Finally there is extra code (normally empty) that is used on the next invocation of the hook (and then deleted). This can be used to define some special behavior for a single occasion from within the document. This token list follows the same naming scheme than the main `\__hook_⟨hook⟩` token list. It is called `\__hook_next_⟨hook⟩` rather than `\__hook_next_⟨hook⟩` because otherwise a hook whose name is `next_⟨hook⟩` would clash with the next code-token list of the hook called `⟨hook⟩`.

#### 4.4.2 On the existence of hooks

A hook may be in different states of existence. Here we give an overview of the internal commands to set up hooks and explain how the different states are distinguished. The actual implementation then follows in subsequent sections.

One problem we have to solve is that we need to be able to add code to hooks (e.g., with `\AddToHook`) even if that code has not yet been declared. For example, one package needs to write into a hook of another package, but that package may not get loaded, or is loaded only later. Another problem is that most hooks, but not the generic hooks, require a declaration.

We therefore distinguish the following states for a hook, which are managed by four different tests: structure existence (`\__hook_if_structure_exist:nTF`), creation (`\__hook_if_usable:nTF`), declaration (`\__hook_if_declared:nTF`) and disabled or not (`\__hook_if_disabled:nTF`)

**not existing** Nothing is known about the hook so far. This state can be detected with `\__hook_if_structure_exist:nTF` (which uses the false branch).

In this state the hook can be declared, disabled, rules can be defined or code could be added to it, but it is not possible to use the hook (with `\UseHook`).

**basic data structure set up** A hook is in this state when its basic data structure has been set up (using `\__hook_init_structure:n`). The data structure setup happens automatically when commands such as `\AddToHook` are used and the hook is at that point in state “not existing”.

In this state the four tests give the following results:

```
\__hook_if_structure_exist:nTF returns true.
      \__hook_if_usable:nTF returns false.
      \__hook_if_declared:nTF returns false.
      \__hook_if_disabled:nTF returns false.
```

The allowed actions are the same as in the “not existing” state.

**declared** A hook is in this state it is not disabled and was explicitly declared (e.g., with `\NewHook`). In this case the four tests give the following results:

```

\__hook_if_structure_exist:nTF returns true.
    \__hook_if_usable:nTF returns true.
    \__hook_if_declared:nTF returns true.
    \__hook_if_disabled:nTF returns false.

```

**usable** A hook is in this state if it is not disabled, was not explicitly declared but nevertheless is allowed to be used (with `\UseHook` or `\hook_use:n`). This state is only possible for generic hooks as they do not need to be declared. Therefore such hooks move directly from state “not existing” to “usable” the moment a declaration such as `\AddToHook` wants to add to the hook data structure. In this state the tests give the following results:

```

\__hook_if_structure_exist:nTF returns true.
    \__hook_if_usable:nTF returns true.
    \__hook_if_declared:nTF returns false.
    \__hook_if_disabled:nTF returns false.

```

**disabled** A generic hook in any state is moved to this state when `\DisableGenericHook` is used. This changes the tests to give the following results:

```

\__hook_if_structure_exist:nTF unchanged.
    \__hook_if_usable:nTF returns false.
    \__hook_if_declared:nTF returns true.
    \__hook_if_disabled:nTF returns true.

```

The structure test is unchanged (if the hook was unknown before it is **false**, otherwise **true**). The usable test returns **false** so that any `\UseHook` will bypass the hook from now on. The declared test returns **true** so that any further `\NewHook` generates an error and the disabled test returns **true** so that `\AddToHook` can return an error.

*FMi: maybe it should do this only after begin document?*

#### 4.4.3 Setting hooks up

`\hook_new:n` The `\hook_new:n` declaration declares a new hook and expects the hook `<name>` as its argument, e.g., `begindocument`.

```

\hook_new_with_args:nn
\__hook_new:nn
67 <latexrelease> \IncludeInRelease{2023/06/01}{\hook_new_with_args:nn}
68 <latexrelease> {Hooks-with-args}
69 \cs_new_protected:Npn \hook_new:n #1
70 { \__hook_normalize_hook_args:Nn \__hook_new:nn {#1} { 0 } }
71 \cs_new_protected:Npn \hook_new_with_args:nn #1 #2
72 { \__hook_normalize_hook_args:Nn \__hook_new:nn {#1} {#2} }
73 \cs_new_protected:Npn \__hook_new:nn #1 #2
74 {

```

We check if the hook was already *explicitly* declared with `\hook_new:n`, and if it already exists we complain, otherwise set the “created” flag for the hook so that it errors next time `\hook_new:n` is used.

```

75   \__hook_if_declared:nTF {#1}
76   { \msg_error:nnn { hooks } { exists } {#1} }
77   {
78     \tl_new:c { g__hook_#1_declared_tl }
79     \cs_undefine:c { __hook~#1 }
80     \cs_undefine:c { c__hook_#1_parameter_tl }
81     \__hook_make_usable:nn {#1} {#2}

```

In case there is already code in a hook, but it’s undeclared, run `\__hook_update_hook_code:n` to make it ready to be executed (see test `lthooks-034`).

```

82     \__hook_update_hook_code:n {#1}
83   }
84 }
85 <latexrelease>\EndIncludeInRelease
86 <latexrelease>\IncludeInRelease{2020/10/01}{\hook_new_with_args:nn}
87 <latexrelease>      {Hooks-with-args}
88 <latexrelease>\cs_gset_protected:Npn \hook_new:n #1
89 <latexrelease>  { \__hook_normalize_hook_args:Nn \__hook_new:n {#1} }
90 <latexrelease>\cs_undefine:N \__hook_new:nn
91 <latexrelease>\cs_gset_protected:Npn \__hook_new:n #1
92 <latexrelease>  {
93    <latexrelease>    \__hook_if_declared:nTF {#1}
94    <latexrelease>    { \msg_error:nnn { hooks } { exists } {#1} }
95    <latexrelease>    {
96      <latexrelease>      \tl_new:c { g__hook_#1_declared_tl }
97      <latexrelease>      \__hook_make_usable:n {#1}
98    <latexrelease>    }
99  <latexrelease>  }
100 <latexrelease>\cs_gset_protected:Npn \hook_new_with_args:nn #1 { }
101 <latexrelease>\EndIncludeInRelease

```

(End of definition for `\hook_new:n`, `\hook_new_with_args:nn`, and `\__hook_new:nn`. These functions are documented on page [213](#).)

`\__hook_make_usable:nn` This initializes all hook data structures for the hook but if used on its own doesn’t mark the hook as declared (as `\hook_new:n` does, so a later `\hook_new:n` on that hook will not result in an error. This command is internally used by `\hook_gput_code:nnn` when adding code to a generic hook.

```

102 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_make_usable:nn}
103 <latexrelease>      {Hooks-with-args}
104 \cs_new_protected:Npn \__hook_make_usable:nn #1 #2
105 {

```

Now we check if the hook’s data structure can be safely created without `expl3` raising errors, then we add the hook name to the list of all hooks and allocate the necessary data structures for the new hook, otherwise just do nothing.

```

106   \__hook_if_usable:nF {#1}
107   {
108     \seq_gput_right:Nn \g__hook_all_seq {#1}

```

Here we'll define the `\c__hook_⟨hook⟩_parameter_tl` to hold a run of parameters up to the number of arguments of the hook (`#2`).

```

109     \__kernel_cs_parm_from_arg_count:nnF
110     { \tl_const:cn { c__hook_#1_parameter_tl } } {#2}
111     {
112         \msg_error:nnnn { hooks } { too-many-args } {#1} {#2}
113         \tl_const:cx { c__hook_#1_parameter_tl }
114         { \exp_not:V \c__hook_nine_parameters_tl }
115     }

```

After that, use `\__hook_normalise_cs_args:nn` to correct the number of parameters of the macros `\__hook_toplevel_⟨hook⟩` and `\__hook_next_⟨hook⟩`. We need to be able to add code with arguments to a hook without prior knowledge of the number of arguments of that hook, so `lthooks` assumes 9 until the hook is properly declared and the number of arguments is known. `\__hook_normalise_cs_args:nn` does the normalization by using the `\c__hook_⟨hook⟩_parameter_tl` defined just above.

```

116     \__hook_normalise_cs_args:nn { _toplevel } {#1}
117     \__hook_normalise_cs_args:nn { _next } {#1}

```

This is only used by the actual code of the current hook, so declare it normally:

```

118     \__hook_code_gset:nn {#1} { }

```

Now ensure that the base data structure for the hook exists:

```

119     \__hook_init_structure:n {#1}

```

The call to `\__hook_normalise_code_pool:n` will correct any improper reference to arguments that don't exist in the hook, raising a low-level `TeX` error and doubling the offending parameter tokens. It has to be done after `\__hook_init_structure:n` because it operates on `\g__hook_⟨hook⟩_code_prop`.

```

120     \__hook_normalise_code_pool:n {#1}

```

The `\g__hook_⟨hook⟩_labels_clist` holds the sorted list of labels (once it got sorted). This is used only for debugging. These are defined conditionally, in case `\__hook_make_usable:nn` is being used to redefine a hook.

```

121     \clist_if_exist:cF { g__hook_#1_labels_clist }
122     {
123         \clist_new:c { g__hook_#1_labels_clist }

```

Some hooks should reverse the default order of code chunks. To signal this we have a token list which is empty for normal hooks and contains a `-` for reversed hooks.

```

124         \tl_new:c { g__hook_#1_reversed_tl }
125     }

```

The above is all in L3 convention, but we also provide an interface to legacy `LATEX 2ε` hooks of the form `\@...hook`, e.g., `\@begindocumenthook`. There have been a few of them and they have been added to using `\g@addto@macro`. If there exists such a macro matching the name of the new hook, i.e., `\@⟨hook-name⟩hook` and it is not empty then we add its contents as a code chunk under the label `legacy`.

**Warning: this support will vanish in future releases!**

```

126     \__hook_include_legacy_code_chunk:n {#1}
127     }
128 }
129 \<latexrelease>\EndIncludeInRelease

```

```

130 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_make_usable:nn}
131 <latexrelease>          {Hooks~with~args}
132 <latexrelease>\cs_undefine:N \__hook_make_usable:nn
133 <latexrelease>\cs_gset_protected:Npn \__hook_make_usable:n #1
134 <latexrelease> {
135 <latexrelease>   \tl_if_exist:cF { __hook~#1 }
136 <latexrelease>   {
137 <latexrelease>     \seq_gput_right:Nn \g__hook_all_seq {#1}
138 <latexrelease>     \tl_new:c { __hook~#1 }
139 <latexrelease>     \__hook_init_structure:n {#1}
140 <latexrelease>     \clist_new:c { g__hook_#1_labels_clist }
141 <latexrelease>     \tl_new:c { g__hook_#1_reversed_tl }
142 <latexrelease>     \__hook_include_legacy_code_chunk:n {#1}
143 <latexrelease>   }
144 <latexrelease> }
145 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_make\_usable:nn.)

\\_\_hook\_init\_structure:n

This function declares the basic data structures for a hook without explicit declaring the hook itself. This is needed to allow adding to undeclared hooks. Here it is unnecessary to check whether all variables exist, since all three are declared at the same time (either all of them exist, or none).

It creates the hook code pool (\g\_\_hook\_<hook>\_code\_prop) and the top-level and next token lists. A hook is initialized with \\_\_hook\_init\_structure:n the first time anything is added to it. Initializing a hook just with \\_\_hook\_init\_structure:n will not make it usable with \hook\_use:n.

```

146 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_init_structure:n}
147 <latexrelease>          {Hooks~with~args}
148 <latexrelease>\cs_new_protected:Npn \__hook_init_structure:n #1
149 <latexrelease> {
150 <latexrelease>   \__hook_if_structure_exist:nF {#1}
151 <latexrelease>   {
152 <latexrelease>     \prop_new:c { g__hook_#1_code_prop }
153 <latexrelease>     \__hook_toplevel_gset:nn {#1} { }
154 <latexrelease>     \__hook_next_gset:nn {#1} { }
155 <latexrelease>   }
156 <latexrelease> }
157 <latexrelease>\EndIncludeInRelease

```

```

158 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_init_structure:n}
159 <latexrelease>          {Hooks~with~args}
160 <latexrelease>\cs_gset_protected:Npn \__hook_init_structure:n #1
161 <latexrelease> {
162 <latexrelease>   \__hook_if_structure_exist:nF {#1}
163 <latexrelease>   {
164 <latexrelease>     \prop_new:c { g__hook_#1_code_prop }
165 <latexrelease>     \tl_new:c { __hook_toplevel~#1 }
166 <latexrelease>     \tl_new:c { __hook_next~#1 }
167 <latexrelease>   }
168 <latexrelease> }
169 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_init\_structure:n.)

`\hook_new_reversed:n` Declare a new hook. The default ordering of code chunks is reversed, signaled by setting the token list to a minus sign.

`\hook_new_reversed_with_args:nn`

`\__hook_new_reversed:nn`

```

170 <latexrelease>\IncludeInRelease{2023/06/01}{\hook_new_reversed_with_args:nn}
171 <latexrelease>{Hooks-with-args}
172 \cs_new_protected:Npn \hook_new_reversed:n #1
173 { \__hook_normalize_hook_args:Nn \__hook_new_reversed:nn {#1} { 0 } }
174 \cs_new_protected:Npn \hook_new_reversed_with_args:nn #1 #2
175 { \__hook_normalize_hook_args:Nn \__hook_new_reversed:nn {#1} {#2} }
176 \cs_new_protected:Npn \__hook_new_reversed:nn #1 #2
177 {
178   \__hook_if_declared:nTF {#1}
179   { \msg_error:nnn { hooks } { exists } {#1} }
180   {
181     \__hook_new:nn {#1} {#2}
182     \tl_gset:cn { g__hook_#1_reversed_tl } { - }
183   }
184 }
185 <latexrelease>\EndIncludeInRelease

186 <latexrelease>\IncludeInRelease{2020/10/01}{\hook_new_reversed_with_args:nn}
187 <latexrelease>{Hooks-with-args}
188 <latexrelease>\cs_gset_protected:Npn \hook_new_reversed:n #1
189 <latexrelease>{ \__hook_normalize_hook_args:Nn \__hook_new_reversed:n {#1} }
190 <latexrelease>\cs_undefine:N \__hook_new_reversed:nn
191 <latexrelease>\cs_gset_protected:Npn \__hook_new_reversed:n #1
192 <latexrelease>{
193 <latexrelease> \__hook_new:n {#1}
194 <latexrelease> \tl_gset:cn { g__hook_#1_reversed_tl } { - }
195 <latexrelease> }
196 <latexrelease>\cs_undefine:N \__hook_new_reversed:nn
197 <latexrelease>\cs_gset_protected:Npn \hook_new_reversed_with_args:nn #1 #2 { }
198 <latexrelease>\EndIncludeInRelease

```

(End of definition for `\hook_new_reversed:n`, `\hook_new_reversed_with_args:nn`, and `\__hook_new_reversed:nn`. These functions are documented on page 213.)

`\hook_new_pair:nn` A shorthand for declaring a normal and a (matching) reversed hook in one go.

`\hook_new_pair_with_args:nnn`

```

199 <latexrelease>\IncludeInRelease{2023/06/01}{\hook_new_pair_with_args:nnn}
200 <latexrelease>{Hooks-with-args}
201 \cs_new_protected:Npn \hook_new_pair:nn #1#2
202 { \__hook_normalize_hook_args:Nnn \__hook_new_pair:nnn {#1} {#2} { 0 } }
203 \cs_new_protected:Npn \hook_new_pair_with_args:nnn #1#2#3
204 { \__hook_normalize_hook_args:Nnn \__hook_new_pair:nnn {#1} {#2} {#3} }
205 \cs_new_protected:Npn \__hook_new_pair:nnn #1 #2 #3
206 {
207   \__hook_if_declared:nTF {#1}
208   { \msg_error:nnn { hooks } { exists } {#1} }
209   {
210     \__hook_if_declared:nTF {#2}
211     { \msg_error:nnn { hooks } { exists } {#2} }
212     {
213       \__hook_new:nn {#1} {#3}
214       \__hook_new_reversed:nn {#2} {#3}
215     }
216   }

```

```

217 }
218 \<latexrelease>\EndIncludeInRelease
219 \<latexrelease>\IncludeInRelease{2020/10/01}{\hook_new_pair_with_args:nnn}
220 \<latexrelease>{Hooks~with~args}
221 \<latexrelease>\cs_gset_protected:Npn \hook_new_pair:nn #1#2
222 \<latexrelease>{
223 \<latexrelease>\hook_new:n {#1}
224 \<latexrelease>\hook_new_reversed:n {#2}
225 \<latexrelease>}
226 \<latexrelease>\cs_gset_protected:Npn \hook_new_pair_with_args:nnn #1#2#3
227 \<latexrelease>{ }
228 \<latexrelease>\EndIncludeInRelease

```

(End of definition for `\hook_new_pair:nn` and `\hook_new_pair_with_args:nnn`. These functions are documented on page [213](#).)

`\__hook_include_legacy_code_chunk:n`

The L<sup>A</sup>T<sub>E</sub>X legacy concept for hooks uses with hooks the following naming scheme in the code: `\@...hook`.

If this macro is not empty we add it under the label `legacy` to the current hook and then empty it globally. This way packages or classes directly manipulating commands such as `\@begindocumenthook` still get their hook data added.

**Warning: this support will vanish in future releases!**

```

229 \<latexrelease>\IncludeInRelease{2023/06/01}{\__hook_include_legacy_code_chunk:n}
230 \<latexrelease>{Hooks~with~args}
231 \cs_new_protected:Npn \__hook_include_legacy_code_chunk:n #1
232 {

```

If the macro doesn't exist (which is the usual case) then nothing needs to be done.

```

233 \tl_if_exist:cT { @#1hook }
234 {

```

Of course if the legacy hook exists but is empty, there is no need to add anything under `legacy` the legacy label.

```

235 \tl_if_empty:cF { @#1hook }
236 {

```

Here we set `\__hook_replacing_args_false:` because no legacy code will reference hook arguments.

```

237 \__hook_replacing_args_false:
238 \use:e
239 {
240 \__hook_hook_gput_code_do:nnn {#1} { legacy }
241 { \exp_not:v { @#1hook } }
242 }
243 \__hook_replacing_args_reset:

```

Once added to the hook, we need to clear it otherwise it might get added again later if the hook data gets updated.

```

244 \__hook_tl_gclear:c { @#1hook }
245 }
246 }
247 }
248 \<latexrelease>\EndIncludeInRelease
249 \<latexrelease>\IncludeInRelease{2020/10/01}{\__hook_include_legacy_code_chunk:n}

```

```

250 <latexrelease> {Hooks~with~args}
251 <latexrelease> \cs_gset_protected:Npn \__hook_include_legacy_code_chunk:n #1
252 <latexrelease> {
253 <latexrelease> \tl_if_exist:cT { @#1hook }
254 <latexrelease> {
255 <latexrelease> \tl_if_empty:cF { @#1hook }
256 <latexrelease> {
257 <latexrelease> \exp_args:Nnnv \__hook_hook_gput_code_do:nnn
258 <latexrelease> {#1} { legacy } { @#1hook }
259 <latexrelease> \__hook_tl_gclear:c { @#1hook }
260 <latexrelease> }
261 <latexrelease> }
262 <latexrelease> }
263 <latexrelease> \EndIncludeInRelease

```

(End of definition for \\_\_hook\_include\_legacy\_code\_chunk:n.)

#### 4.4.4 Disabling and providing hooks

**\hook\_disable\_generic:n** Disables a hook by creating its `\g__hook_{hook}_declared_tl` so that the hook errors when used with `\hook_new:n`, then it undefines `\__hook_{hook}` so that it may not be executed.

`\__hook_disable:n`  
`\__hook_if_disabled_p:n`  
`\__hook_if_disabled:nTF`

This does not clear any code that may be already stored in the hook's structure, but doesn't allow adding more code. `\__hook_if_disabled:nTF` uses that specific combination to check if the hook is disabled.

```

264 <latexrelease> \IncludeInRelease{2021/06/01}{\hook_disable_generic:n}
265 <latexrelease> {Disable~hooks}

266 \cs_new_protected:Npn \hook_disable_generic:n #1
267 { \__hook_normalize_hook_args:Nn \__hook_disable:n {#1} }
268 \cs_new_protected:Npn \__hook_disable:n #1
269 {
270 \tl_gclear_new:c { g__hook_#1_declared_tl }
271 \cs_undefine:c { __hook_#1 }
272 }
273 \prg_new_conditional:Npnn \__hook_if_disabled:n #1 { p, T, F, TF }
274 {
275 \bool_lazy_and:nnTF
276 { \tl_if_exist_p:c { g__hook_#1_declared_tl } }
277 { ! \cs_if_exist_p:c { __hook_#1 } }
278 { \prg_return_true: }
279 { \prg_return_false: }
280 }
281 <latexrelease> \EndIncludeInRelease

282 <latexrelease> \IncludeInRelease{2020/10/01}{\hook_disable_generic:n}
283 <latexrelease> {Disable~hooks}
284 <latexrelease>
285 <latexrelease> \cs_new_protected:Npn \hook_disable_generic:n #1 {}
286 <latexrelease>
287 <latexrelease> \EndIncludeInRelease

```

(End of definition for `\hook_disable_generic:n`, `\__hook_disable:n`, and `\__hook_if_disabled:nTF`.  
This function is documented on page 214.)

`\hook_activate_generic:n` The `\hook_activate_generic:n` declaration declares a new hook if it wasn't declared already, in which case it only checks that the already existing hook is not a reversed hook.

```

288 <latexrelease> \IncludeInRelease{2023/06/01}{\hook_activate_generic:n}
289 <latexrelease> {Providing-hooks}

290 \cs_new_protected:Npn \hook_activate_generic:n #1
291 { \__hook_normalize_hook_args:Nn \__hook_activate_generic:nn {#1} { } }

292 \cs_new_protected:Npn \__hook_activate_generic:nn #1 #2
293 {

```

If the hook to be activated was disabled we warn (for now — this may change).

```

294 \__hook_if_disabled:nTF {#1}
295 { \msg_warning:nnn { hooks } { activate-disabled } {#1} }

```

Otherwise we check if the hook is not declared, and if it isn't, figure out if it's reversed or not, then declare it accordingly.

```

296 {
297   \__hook_if_declared:nF {#1}
298   {
299     \tl_new:c { g__hook_#1_declared_tl }
300     \__hook_make_usable:nn {#1} { 0 }
301     \tl_gset:cx { g__hook_#1_reversed_tl }
302     { \__hook_if_generic_reversed:nT {#1} { - } }

```

Reflect that we have activated the generic hook and set its execution code.

```

303   \__hook_update_hook_code:n {#1}
304 }
305 }
306 }

```

```

307 <latexrelease> \EndIncludeInRelease

308 <latexrelease> \IncludeInRelease{2021/06/01}{\hook_activate_generic:n}
309 <latexrelease> {Providing-hooks}

310 <latexrelease> \cs_gset_protected:Npn \__hook_activate_generic:nn #1 #2
311 <latexrelease> {
312 <latexrelease>   \__hook_if_disabled:nTF {#1}
313 <latexrelease>   { \msg_warning:nnn { hooks } { activate-disabled } {#1} }
314 <latexrelease>   {
315 <latexrelease>     \__hook_if_declared:nF {#1}
316 <latexrelease>     {
317 <latexrelease>       \tl_new:c { g__hook_#1_declared_tl }
318 <latexrelease>       \__hook_make_usable:n {#1}
319 <latexrelease>       \tl_gset:cx { g__hook_#1_reversed_tl }
320 <latexrelease>       { \__hook_if_generic_reversed:nT {#1} { - } }
321 <latexrelease>       \__hook_update_hook_code:n {#1}
322 <latexrelease>     }
323 <latexrelease>   }
324 <latexrelease> }
325 <latexrelease> \EndIncludeInRelease

326 <latexrelease> \IncludeInRelease{2020/10/01}{\hook_activate_generic:n}
327 <latexrelease> {Providing-hooks}
328 <latexrelease> \cs_gset_protected:Npn \hook_activate_generic:n #1 { }
329 <latexrelease> \EndIncludeInRelease

```

(End of definition for `\hook_activate_generic:n` and `\__hook_activate_generic:n`. This function is documented on page 214.)

## 4.5 Parsing a label

`\__hook_parse_label_default:nN` This macro checks if a label was given (not `\c_novalue_tl`), and if so, tries to parse the label looking for a leading `.` to replace by `\__hook_currname_or_default:.` #2 is a boolean representing if #1 is a label name.

```

330 \cs_new:Npn \__hook_parse_label_default:nN #1#2
331 {
332   \tl_if_novalue:nTF {#1}
333     { \__hook_currname_or_default: }
334     { \tl_trim_spaces_apply:nN {#1} \__hook_parse_dot_label:nN #2 }
335 }
```

(End of definition for `\__hook_parse_label_default:nN`.)

`\__hook_parse_dot_label:nN` Start by checking if the label is empty, which raises an error, and uses the fallback value.  
`\__hook_parse_dot_label:w` If not, split the label at a `./`, if any, and check if no tokens are before the `./`, or if the  
`\__hook_parse_dot_label_cleanup:w` only character is a `..`. If these requirements are fulfilled, the leading `.` is replaced with  
`\__hook_parse_dot_label_aux:w` `\__hook_currname_or_default:.` Otherwise the label is returned unchanged. #2 is a boolean representing if #1 is a label name.

```

336 \cs_new:Npn \__hook_parse_dot_label:nN #1#2
337 {
338   \tl_if_empty:nTF {#1}
339     {
340       \bool_if:NTF #2
341         { \msg_expandable_error:nn { hooks } { empty-label } }
342         { \msg_expandable_error:nn { hooks } { empty-hook } }
343       \__hook_currname_or_default:
344     }
345     {
346       \str_if_eq:nnTF {#1} { . }
347         { \__hook_currname_or_default: }
348         { \__hook_parse_dot_label:w #1 ./ \s__hook_mark }
349     }
350 }
351 \cs_new:Npn \__hook_parse_dot_label:w #1 ./ #2 \s__hook_mark
352 {
353   \tl_if_empty:nTF {#1}
354     { \__hook_parse_dot_label_aux:w #2 \s__hook_mark }
355     {
356       \tl_if_empty:nTF {#2}
357         { \__hook_make_name:n {#1} }
358         { \__hook_parse_dot_label_cleanup:w #1 ./ #2 \s__hook_mark }
359     }
360 }
361 \cs_new:Npn \__hook_parse_dot_label_cleanup:w #1 ./ \s__hook_mark {#1}
362 \cs_new:Npn \__hook_parse_dot_label_aux:w #1 ./ \s__hook_mark
363 { \__hook_currname_or_default: / \__hook_make_name:n {#1} }
```

(End of definition for `\__hook_parse_dot_label:nN` and others.)

`\__hook_currname_or_default:` This uses `\g__hook_hook_curr_name_tl` if it is set, otherwise it tries `\@currname`. If neither is set, it raises an error and uses the fallback value `label-missing`.

```

364 \cs_new:Npn \__hook_currname_or_default:
365 {
366   \tl_if_empty:NTF \g__hook_hook_curr_name_tl
367   {
368     \tl_if_empty:NTF \@currname
369     {
370       \msg_expandable_error:nnn { latex2e } { should-not-happen }
371       { Empty~default~label. }
372       \__hook_make_name:n { label-missing }
373     }
374     { \@currname }
375   }
376   { \g__hook_hook_curr_name_tl }
377 }

```

(End of definition for `\__hook_currname_or_default:`.)

`\__hook_make_name:n` This provides a standard sanitization of a hook’s name. It uses `\cs:w` to build a control sequence out of the hook name, then uses `\cs_to_str:N` to get the string representation of that, without the escape character. `\cs:w`-based expansion is used instead of `e`-based because Unicode characters don’t behave well inside `\expanded`. The macro adds the `\_hook_` prefix to the hook name to reuse the hook’s code token list to build the csname and avoid leaving “public” control sequences defined (as `\relax`) in TeX’s memory.

`\__hook_make_name:w`

```

378 \cs_new:Npn \__hook_make_name:n #1
379 {
380   \exp_after:wN \exp_after:wN \exp_after:wN \__hook_make_name:w
381   \exp_after:wN \token_to_str:N \cs:w __hook~ #1 \cs_end:
382 }
383 \exp_last_unbraced:NNNno
384 \cs_new:Npn \__hook_make_name:w #1 \tl_to_str:n { __hook~ } { }

```

(End of definition for `\__hook_make_name:n` and `\__hook_make_name:w`.)

`\__hook_normalize_hook_args:Nn` This is the standard route for normalizing hook and label arguments. The main macro does the entire operation within a group so that csnames made by `\__hook_make_name:n` are wiped off before continuing. This means that this function cannot be used for `\hook_use:n!`

`\__hook_normalize_hook_args:Nnn`

`\__hook_normalize_hook_rule_args:Nnnnn`

`\__hook_normalize_hook_args_aux:Nn`

```

385 \cs_new_protected:Npn \__hook_normalize_hook_args_aux:Nn #1 #2
386 {
387   \group_begin:
388   \use:e
389   {
390     \group_end:
391     \exp_not:N #1 #2
392   }
393 }
394 \cs_new_protected:Npn \__hook_normalize_hook_args:Nn #1 #2
395 {
396   \__hook_normalize_hook_args_aux:Nn #1
397   { { \__hook_parse_label_default:nN {#2} \c_false_bool } }
398 }

```

```

399 \cs_new_protected:Npn \__hook_normalize_hook_args:Nnn #1 #2 #3
400 {
401   \__hook_normalize_hook_args_aux:Nn #1
402   {
403     { \__hook_parse_label_default:nN {#2} \c_false_bool }
404     { \__hook_parse_label_default:nN {#3} \c_true_bool }
405   }
406 }
407 \cs_new_protected:Npn \__hook_normalize_hook_rule_args:Nnnnn #1 #2 #3 #4 #5
408 {
409   \__hook_normalize_hook_args_aux:Nn #1
410   {
411     { \__hook_parse_label_default:nN {#2} \c_false_bool }
412     { \__hook_parse_label_default:nN {#3} \c_true_bool }
413     { \tl_trim_spaces:n {#4} }
414     { \__hook_parse_label_default:nN {#5} \c_true_bool }
415   }
416 }

```

(End of definition for \\_\_hook\_normalize\_hook\_args:Nn and others.)

\\_\_hook\_curr\_name\_push:n The token list \g\_\_hook\_hook\_curr\_name\_tl stores the name of the current package/file to be used as the default label in hooks. Providing a consistent interface is tricky because packages can be loaded within packages, and some packages may not use \SetDefaultHookLabel to change the default label (in which case \@currname is used).

To pull that one off, we keep a stack that contains the default label for each level of input. The bottom of the stack contains the default label for the top-level (this stack should never go empty). If we're building the format, set the default label to be top-level:

```

417 \tl_gset:Nn \g__hook_hook_curr_name_tl { top-level }

```

Then, in case we're in latexrelease we push something on the stack to support roll forward. But in some rare cases, latexrelease may be loaded inside another package (notably platexrelease), so we'll first push the top-level entry:

```

418 <latexrelease> \seq_if_empty:NT \g__hook_name_stack_seq
419 <latexrelease> { \seq_gput_right:Nn \g__hook_name_stack_seq { top-level } }

```

then we dissect the \@currnamestack, adding \@currname to the stack:

```

420 <latexrelease> \cs_set_protected:Npn \__hook_tmp:w #1 #2 #3
421 <latexrelease> {
422   <latexrelease> \quark_if_recursion_tail_stop:n {#1}
423   <latexrelease> \seq_gput_right:Nn \g__hook_name_stack_seq {#1}
424   <latexrelease> \__hook_tmp:w
425   <latexrelease> }
426 <latexrelease> \exp_after:wN \__hook_tmp:w \@currnamestack
427 <latexrelease> \q_recursion_tail \q_recursion_tail
428 <latexrelease> \q_recursion_tail \q_recursion_stop

```

and finally set the default label to be the \@currname:

```

429 <latexrelease> \tl_gset:Nx \g__hook_hook_curr_name_tl { \@currname }
430 <latexrelease> \seq_gpop_right:NN \g__hook_name_stack_seq \l__hook_tmpa_tl

```

Two commands keep track of the stack: when a file is input, \\_\_hook\_curr\_name\_push:n pushes the current default label onto the stack and sets the new default label (all in one go):

```

431 \cs_new_protected:Npn \__hook_curr_name_push:n #1
432 { \exp_args:Nx \__hook_curr_name_push_aux:n { \__hook_make_name:n {#1} } }
433 \cs_new_protected:Npn \__hook_curr_name_push_aux:n #1
434 {
435   \tl_if_blank:nTF {#1}
436   { \msg_error:nn { hooks } { no-default-label } }
437   {
438     \str_if_eq:nnTF {#1} { top-level }
439     {
440       \msg_error:nnnnn { hooks } { set-top-level }
441       { to } { PushDefaultHookLabel } {#1}
442     }
443     {
444       \seq_gpush:NV \g__hook_name_stack_seq \g__hook_hook_curr_name_tl
445       \tl_gset:Nn \g__hook_hook_curr_name_tl {#1}
446     }
447   }
448 }

```

and when an input is over, the topmost item of the stack is popped, since that label will not be used again, and `\g__hook_hook_curr_name_tl` is updated to equal the now topmost item of the stack:

```

449 \cs_new_protected:Npn \__hook_curr_name_pop:
450 {
451   \seq_gpop:NNTF \g__hook_name_stack_seq \l__hook_return_tl
452   { \tl_gset_eq:NN \g__hook_hook_curr_name_tl \l__hook_return_tl }
453   { \msg_error:nn { hooks } { extra-pop-label } }
454 }

```

At the end of the document we want to check if there was no `\__hook_curr_name_push:n` without a matching `\__hook_curr_name_pop:` (not a critical error, but it might indicate that something else is not quite right):

```

455 \tl_gput_right:Nn \@kernel@after@enddocument@afterlastpage
456 { \__hook_end_document_label_check: }
457 \cs_new_protected:Npn \__hook_end_document_label_check:
458 {
459   \seq_gpop:NNT \g__hook_name_stack_seq \l__hook_return_tl
460   {
461     \msg_error:nnx { hooks } { missing-pop-label }
462     { \g__hook_hook_curr_name_tl }
463     \tl_gset_eq:NN \g__hook_hook_curr_name_tl \l__hook_return_tl
464     \__hook_end_document_label_check:
465   }
466 }

```

The token list `\g__hook_hook_curr_name_tl` is but a mirror of the top of the stack.

Now define a wrapper that replaces the top of the stack with the argument, and updates `\g__hook_hook_curr_name_tl` accordingly.

```

467 \cs_new_protected:Npn \__hook_set_default_hook_label:n #1
468 {
469   \seq_if_empty:NNTF \g__hook_name_stack_seq
470   {
471     \msg_error:nnnnn { hooks } { set-top-level }
472     { for } { SetDefaultHookLabel } {#1}

```

`\__hook_set_default_hook_label:n`

```

473     }
474     { \exp_args:Nx
475       \__hook_set_default_label:n { \__hook_make_name:n {#1} } }
476   }
477 \cs_new_protected:Npn \__hook_set_default_label:n #1
478 {
479   \str_if_eq:nnTF {#1} { top-level }
480   {
481     \msg_error:nnnn { hooks } { set-top-level }
482     { to } { SetDefaultHookLabel } {#1}
483   }
484   { \tl_gset:Nn \g__hook_hook_curr_name_tl {#1} }
485 }

```

(End of definition for \\_\_hook\_curr\_name\_push:n and others.)

## 4.6 Adding or removing hook code

`\hook_gput_code:nnn` With `\hook_gput_code:nnn{<hook>}{<label>}{<code>}` a chunk of `<code>` is added to an existing `<hook>` labeled with `<label>`.

`\hook_gput_code_with_args:nnn`

```

\__hook_gput_code:nnn 486 <latexrelease> \IncludeInRelease{2023/06/01}{\hook_gput_code:nnn}
\__hook_gput_code_store:nnn 487 <latexrelease> {Hooks-with-args}
\__hook_hook_gput_code_do:nnn 488 \cs_new_protected:Npn \hook_gput_code:nnn #1 #2 #3
\hook_prop_gput_labeled_cleanup:nnn 489 {
\__hook_prop_gput_labeled_do:Nnnn 490   \__hook_replacing_args_false:
\__hook_hash_check:nTF 491   \__hook_normalize_hook_args:Nnn \__hook_gput_code:nnn {#1} {#2} {#3}
\__hook_hash_check_aux:w 492   \__hook_replacing_args_reset:
493 }
494 \cs_new_protected:Npn \hook_gput_code_with_args:nnn #1 #2 #3
495 {
496   \__hook_replacing_args_true:
497   \__hook_normalize_hook_args:Nnn \__hook_gput_code:nnn {#1} {#2} {#3}
498   \__hook_replacing_args_reset:
499 }

```

If `\AddToHookWithArguments` was used, do some sanity checking, and if it's not possible to use arguments at this point, fall back to regular `\AddToHook` by using `\__hook_replacing_args_false:`.

```

500 \cs_new_protected:Npn \__hook_gput_code:nnn #1 #2 #3
501 {
502   \__hook_chk_args_allowed:nn {#1} { AddToHook }

```

Then check if the code should be executed immediately, rather than stored:

```

503   \__hook_if_execute_immediately:nTF {#1}
504   {

```

`\AddToHookWithArguments` can't be used on one-time hooks (that were already used).

```

505     \__hook_if_replacing_args:TF
506     {
507       \msg_error:nnnn { hooks } { one-time-args }
508       {#1} { AddToHook }
509     }
510     { }
511   \use:n
512 }

```

```

513     { \__hook_gput_code_store:nnn {#1} {#2} }
514         {#3}
515     }
516 \cs_new_protected:Npn \__hook_gput_code_store:nnn #1 #2 #3
517 {

```

Then check if the hook is usable.

```

518     \__hook_if_usable:nTF {#1}

```

If so we simply add (or append) the new code to the property list holding different chunks for the hook. At `\begin{document}` this is then sorted into a token list for fast execution.

```

519     {
520         \__hook_hook_gput_code_do:nnn {#1} {#2} {#3}

```

However, if there is an update within the document we need to alter this execution code which is done by `\__hook_update_hook_code:n`. In the preamble this does nothing.

```

521         \__hook_update_hook_code:n {#1}
522     }

```

If the hook is not usable, before giving up, check if it's not disabled and otherwise try to declare it as a generic hook, if its name matches one of the valid patterns.

```

523     {
524         \__hook_if_disabled:nTF {#1}
525         { \msg_error:nnn { hooks } { hook-disabled } {#1} }
526         { \__hook_try_declaring_generic_hook:nnn {#1} {#2} {#3} }
527     }
528 }

```

This macro will unconditionally add a chunk of code to the given hook.

```

529 \cs_new_protected:Npn \__hook_hook_gput_code_do:nnn #1 #2 #3
530 {

```

However, first some debugging info if debugging is enabled:

```

531     \__hook_debug:n{\iow_term:x{[lthooks]~ Add~ to~
532         \__hook_if_usable:nF {#1} { undeclared~ }
533         hook~ ' #1'~ ( #2) \on@line
534         ^^J [lthooks] \@spaces
535         <-- \tl_to_str:n{#3}} }

```

Then try to get the code chunk labeled #2 from the hook. If there's code already there, then append #3 to that, otherwise just put #3. If the current label is `top-level`, the code is added to a dedicated token list `\__hook_toplevel_<hook>` that goes at the end of the hook (or at the beginning, for a reversed hook), just before `\__hook_next_<hook>`.

```

536     \str_if_eq:nnTF {#2} { top-level }
537     {
538         \str_if_eq:eeTF { top-level } { \__hook_currname_or_default: }
539     {

```

If the hook's basic structure does not exist, we need to declare it with `\__hook_init_structure:n`.

```

540         \__hook_init_structure:n {#1}

```

Then append to the `_toplevel` container for the hook.

```

541         \__hook_cs_gput_right:nnn { _toplevel } {#1} {#3}
542     }
543     { \msg_error:nnn { hooks } { misused-top-level } {#1} }
544 }
545 {

```

When adding to the code pool, we have to double hashes if `\AddToHook` was used (`replacing_args` is false), so that later it is turned into a single parameter token, rather than a parameter to the hook macro. We skip this step if there are no hashes at all in the argument: the token-by-token approach otherwise becomes a major performance issue when the contents of the hook are long.

```

546     \exp_args:Nx \__hook_prop_gput_labeled_cleanup:nnn
547     {
548         \__hook_if_replacing_args:TF
549         { \exp_not:n }
550         {
551             \__hook_hash_check:nTF {#3}
552             { \exp_not:n }
553             { \__hook_double_hashes:n }
554         }
555         {#3}
556     }
557     {#1} {#2}
558 }
559 }
560 \cs_new:Npx \__hook_hash_check:nTF #1
561 {
562     \exp_not:N \exp_after:wN \exp_not:N \__hook_hash_check_aux:w
563     \exp_not:N \tl_to_str:n {#1} \c_hash_str \c_hash_str
564     \exp_not:N \q_stop
565 }
566 \use:x
567 {
568     \cs_new:Npn \exp_not:N \__hook_hash_check_aux:w
569     ##1 \c_hash_str ##2 \c_hash_str ##3 \exp_not:N \q_stop
570 }
571 { \tl_if_empty:nTF {#3} }

```

Adds code to a hook's code pool.

```

572 \cs_new_protected:Npn \__hook_prop_gput_labeled_cleanup:nnn #1 #2 #3
573 {
574     \tl_set:Nn \l__hook_return_tl {#1}
575     \__hook_if_replacing_args:TF
576     {
577         \__hook_if_usable:nT {#2}
578         {
579             \__hook_set_normalise_fn:nn {#2}
580             { Invalid~code~added~\msg_line_context: }
581             \__hook_normalise_fn:nn {#3} {#1}
582             \prop_get:NnN \l__hook_work_prop {#3} \l__hook_return_tl
583         }
584     }
585     { }

```

```

586 \exp_args:NcV \__hook_prop_gput_labeled_do:Nnn
587 { g__hook_#2_code_prop } \l__hook_return_tl {#3}
588 }
589 \cs_new_protected:Npn \__hook_prop_gput_labeled_do:Nnn #1 #2 #3
590 {
591 \prop_get:NnNTF #1 {#3} \l__hook_return_tl
592 { \prop_gput:Nno #1 {#3} { \l__hook_return_tl #2 } }
593 { \prop_gput:Nnn #1 {#3} {#2} }
594 }
595 <latexrelease> \EndIncludeInRelease

596 <latexrelease> \IncludeInRelease{2020/10/01}{\hook_gput_code:nnn}
597 <latexrelease> {Providing~hooks}
598 <latexrelease> \cs_gset_protected:Npn \hook_gput_code:nnn #1 #2
599 <latexrelease> { \__hook_normalize_hook_args:Nnn
600 <latexrelease> \__hook_gput_code:nnn {#1} {#2} }
601 <latexrelease> \cs_gset_protected:Npn \__hook_gput_code:nnn #1 #2 #3
602 <latexrelease> {
603 <latexrelease> \__hook_if_execute_immediately:nTF {#1}
604 <latexrelease> {#3}
605 <latexrelease> {
606 <latexrelease> \__hook_if_usable:nTF {#1}
607 <latexrelease> {
608 <latexrelease> \__hook_hook_gput_code_do:nnn {#1} {#2} {#3}
609 <latexrelease> \__hook_update_hook_code:n {#1}
610 <latexrelease> }
611 <latexrelease> {
612 <latexrelease> \__hook_if_disabled:nTF {#1}
613 <latexrelease> { \msg_error:nnn { hooks } { hook-disabled } {#1} }
614 <latexrelease> { \__hook_try_declaring_generic_hook:nnn
615 <latexrelease> {#1} {#2} {#3} }
616 <latexrelease> }
617 <latexrelease> }
618 <latexrelease> }
619 <latexrelease> \cs_gset_protected:Npn \__hook_hook_gput_code_do:nnn #1 #2 #3
620 <latexrelease> {
621 <latexrelease> \__hook_debug:n{\iow_term:x{****~ Add~ to~
622 <latexrelease> \__hook_if_usable:nF {#1} { undeclared~ }
623 <latexrelease> hook~ #1~ (#2)
624 <latexrelease> \on@line\space <~ \tl_to_str:n{#3}} }
625 <latexrelease> \str_if_eq:nnTF {#2} { top-level }
626 <latexrelease> {
627 <latexrelease> \str_if_eq:eeTF { top-level }
628 <latexrelease> { \__hook_currname_or_default: }
629 <latexrelease> {
630 <latexrelease> \__hook_init_structure:n {#1}
631 <latexrelease> \__hook_tl_gput_right:cn { \__hook_toplevel~#1 } {#3}
632 <latexrelease> }
633 <latexrelease> { \msg_error:nnn { hooks } { misused-top-level } {#1} }
634 <latexrelease> }
635 <latexrelease> {
636 <latexrelease> \prop_get:cnNTF
637 <latexrelease> { g__hook_#1_code_prop } {#2} \l__hook_return_tl
638 <latexrelease> {

```

```

639 \<latexrelease> \prop_gput:cno { g__hook_#1_code_prop } {#2}
640 \<latexrelease> { \l__hook_return_tl #3 }
641 \<latexrelease> }
642 \<latexrelease> { \prop_gput:cnn { g__hook_#1_code_prop } {#2} {#3} }
643 \<latexrelease> }
644 \<latexrelease> }
645 \<latexrelease> \cs_gset_protected:Npn \hook_gput_code_with_args:nnn #1#2#3 { }
646 \<latexrelease> \EndIncludeInRelease

```

(End of definition for \hook\_gput\_code:nnn and others. These functions are documented on page 214.)

`\__hook_chk_args_allowed:nn` This macro checks if it is possible to add code with references to a hook's arguments for hook #1. It only does something if the function being run is `replacing_args`. This macro will error if the hook is declared and takes no arguments, then it will set `\__hook_replacing_args_false:` so that the macro which called it will add the code normally.

```

647 \<latexrelease> \IncludeInRelease{2023/06/01}{\__hook_chk_args_allowed:nn}
648 \<latexrelease> {Hooks-with-args}
649 \cs_new_protected:Npn \__hook_chk_args_allowed:nn #1 #2
650 {
651   \__hook_if_replacing_args:TF
652   {
653     \__hook_if_declared:nT {#1}
654     { \tl_if_empty:cT { c__hook_#1_parameter_tl } { \use_i:nn } }
655     \use_none:n
656     {
657       \msg_error:nnnn { hooks } { without-args } {#1} {#2}
658       \__hook_replacing_args_false:
659     }
660   }
661   { }
662 }
663 \<latexrelease> \EndIncludeInRelease
664 \<latexrelease> \IncludeInRelease{2020/10/01}{\__hook_chk_args_allowed:nn}
665 \<latexrelease> {Hooks-with-args}
666 \<latexrelease> \cs_undefine:N \__hook_chk_args_allowed:nn
667 \<latexrelease> \EndIncludeInRelease

```

(End of definition for \\_\_hook\_chk\_args\_allowed:nn.)

`\__hook_gput_undeclared_hook:nnn` Often it may happen that a package *A* defines a hook `foo`, but package *B*, that adds code to that hook, is loaded before *A*. In such case we need to add code to the hook before it is declared. An implicitly declared hook doesn't have arguments (in principle), so use `\c_false_bool` here.

```

668 \cs_new_protected:Npn \__hook_gput_undeclared_hook:nnn #1 #2 #3
669 {
670   \__hook_init_structure:n {#1}
671   \__hook_hook_gput_code_do:nnn {#1} {#2} {#3}
672 }

```

(End of definition for \\_\_hook\_gput\_undeclared\_hook:nnn.)

`\__hook_try_declaring_generic_hook:nnn`  
`\__hook_try_declaring_generic_next_hook:nn` These entry-level macros just pass the arguments along to the common `\__hook_try_declaring_generic_hook:nNNnn` with the right functions to execute when some action is to be taken.

The wrapper `\__hook_try_declaring_generic_hook:nnn` then defers `\hook_gput_code:nnn` if the generic hook was declared, or to `\__hook_gput_undeclared_hook:nnn` otherwise (the hook was tested for existence before, so at this point if it isn't generic, it doesn't exist).

The wrapper `\__hook_try_declaring_generic_next_hook:nn` for next-execution hooks does the same: it defers the code to `\hook_gput_next_code:nn` if the generic hook was declared, or to `\__hook_gput_next_do:nn` otherwise.

```

673 <latexrelease> \IncludeInRelease{2023/06/01}
674 <latexrelease> { \__hook_try_declaring_generic_hook:nnn }
675 <latexrelease> { Hooks-with-args }
676 \cs_new_protected:Npn \__hook_try_declaring_generic_hook:nnn #1
677 {
678   \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop: {#1}
679   \__hook_gput_code:nnn
680   \__hook_gput_undeclared_hook:nnn
681   {#1}
682 }
683 \cs_new_protected:Npn \__hook_try_declaring_generic_next_hook:nn #1
684 {
685   \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop: {#1}
686   \__hook_gput_next_code:nn
687   \__hook_gput_next_do:nn
688   {#1}
689 }
690 <latexrelease> \EndIncludeInRelease
691 <latexrelease> \IncludeInRelease{2021/11/15}
692 <latexrelease> { \__hook_try_declaring_generic_hook:nnn }
693 <latexrelease> { Standardize-generic-hook-names }
694 <latexrelease> \cs_gset_protected:Npn \__hook_try_declaring_generic_hook:nnn #1
695 <latexrelease> {
696 <latexrelease>   \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop:
697 <latexrelease>   {#1}
698 <latexrelease>   \hook_gput_code:nnn
699 <latexrelease>   \__hook_gput_undeclared_hook:nnn
700 <latexrelease>   {#1}
701 <latexrelease> }
702 <latexrelease> \cs_gset_protected:Npn
703 <latexrelease>   \__hook_try_declaring_generic_next_hook:nn #1
704 <latexrelease> {
705 <latexrelease>   \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop:
706 <latexrelease>   {#1}
707 <latexrelease>   \hook_gput_next_code:nn
708 <latexrelease>   \__hook_gput_next_do:nn
709 <latexrelease>   {#1}
710 <latexrelease> }
711 <latexrelease> \EndIncludeInRelease
712 <latexrelease> \IncludeInRelease{2020/10/01}
713 <latexrelease> { \__hook_try_declaring_generic_hook:nnn }
714 <latexrelease> { Standardize-generic-hook-names }
715 <latexrelease> \cs_new_protected:Npn
716 <latexrelease>   \__hook_try_declaring_generic_hook:nnn #1
717 <latexrelease> {
718 <latexrelease>   \__hook_try_declaring_generic_hook:nNNnn {#1}

```

```

719 <latexrelease> \hook_gput_code:nnn \__hook_gput_undeclared_hook:nnn
720 <latexrelease> }
721 <latexrelease> \cs_new_protected:Npn
722 <latexrelease> \__hook_try_declaring_generic_next_hook:nn #1
723 <latexrelease> {
724 <latexrelease> \__hook_try_declaring_generic_hook:nNNnn {#1}
725 <latexrelease> \hook_gput_next_code:nn \__hook_gput_next_do:nn
726 <latexrelease> }

```

(End of definition for \\_\_hook\_try\_declaring\_generic\_hook:nnn and  
\\_\_hook\_try\_declaring\_generic\_next\_hook:nn.)

\\_\_hook\_try\_declaring\_generic\_hook:nNNnn now splits the hook name at the first /  
(if any) and first checks if it is a file-specific hook (they require some normalization) using  
\\_\_hook\_if\_file\_hook:wTF. If not then check it is one of a predefined set for generic  
names. We also split off the second component to see if we have to make a reversed hook.  
In either case the function returns <true> for a generic hook and <false> in other cases.

```

727 <latexrelease> \cs_new_protected:Npn \__hook_try_declaring_generic_hook:nNNnn #1
728 <latexrelease> {
729 <latexrelease> \__hook_if_file_hook:wTF #1 / / \s__hook_mark
730 <latexrelease> {
731 <latexrelease> \exp_args:Ne
732 <latexrelease> \__hook_try_declaring_generic_hook_split:nNNnn
733 <latexrelease> { \exp_args:Ne \__hook_file_hook_normalize:n {#1} }
734 <latexrelease> }
735 <latexrelease> { \__hook_try_declaring_generic_hook_split:nNNnn {#1} }
736 <latexrelease> }

```

```

737 <latexrelease> \cs_new_protected:Npn
738 <latexrelease> \__hook_try_declaring_generic_hook_split:nNNnn #1 #2 #3
739 <latexrelease> {
740 <latexrelease> \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop:
741 <latexrelease> {#1}
742 <latexrelease> { #2 }
743 <latexrelease> { #3 } {#1}
744 <latexrelease> }
745 <latexrelease> \EndIncludeInRelease

```

(End of definition for \\_\_hook\_try\_declaring\_generic\_hook:nNNnn and  
\\_\_hook\_try\_declaring\_generic\_hook\_split:nNNnn.)

\\_\_hook\_try\_declaring\_generic\_hook:wnTF

```

746 <latexrelease> \IncludeInRelease{2023/06/01}
747 <latexrelease> {\__hook_try_declaring_generic_hook:wn}
748 <latexrelease> {Hooks-with-args}
749 \prg_new_protected_conditional:Npnn
750 \__hook_try_declaring_generic_hook:wn
751 #1 / #2 / #3 / #4 \scan_stop: #5 { TF }
752 {
753 \__hook_if_generic:nTF {#5}
754 {
755 \__hook_if_usable:nF {#5}
756 {

```

If the hook doesn't exist yet we check if it is a `cmd` hook and if so we attempt patching the command in addition to declaring the hook.

For some commands this will not be possible, in which case `\__hook_patch_cmd_-or_delay:Nnn` (defined in `ltxcmdhooks`) will generate an appropriate error message.

```

757         \str_if_eq:nnT {#1} { cmd }
758         {
759             \__hook_try_put_cmd_hook:n {#5}
760             \__hook_make_usable:nn {#5} { 9 }
761             \use_none:nnn
762         }

```

Declare the hook always even if it can't really be used (error message generated elsewhere).

Here we use `\__hook_make_usable:nn`, so that a `\hook_new:n` is still possible later. Generic hooks (except `cmd` hooks) take no arguments, so use zero as the second argument.

```

763         \__hook_make_usable:nn {#5} { 0 }
764     }
765     \__hook_if_generic_reversed:nT {#5}
766     { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
767     \prg_return_true:
768 }
769 {

```

Generic hooks are all named `<type>/<name>/<place>`, where `<type>` and `<place>` are predefined (`\c__hook_generic_<type>/./<place>_tl`), and `<name>` is the variable component. Older releases had some hooks with the `<name>` in the third part, so the code below supports that syntax for a while, with a warning.

The `\exp_after:wN ... \exp:w` trick is there to remove the conditional structure inserted by `\__hook_try_declaring_generic_hook:wnTF` and thus allow access to the tokens that follow it, as is needed to keep things going.

When the deprecation cycle ends, the lines below should all be replaced by `\prg_return_false:.`

```

770     \__hook_if_deprecated_generic:nTF {#5}
771     {
772         \__hook_deprecated_generic_warn:n {#5}
773         \exp_after:wN \__hook_declare_deprecated_generic:NNn
774         \exp:w % \exp_end:
775     }
776     { \prg_return_false: }
777 }
778 }

```

`\__hook_deprecated_generic_warn:n` will issue a deprecation warning for a given hook, and mark that hook such that the warning will not be issued again (multiple warnings can be issued, but only once per hook).

`\__hook_deprecated_generic_warn:Nn`  
`\__hook_deprecated_generic_warn:Nw`

```

779 \cs_new_protected:Npn \__hook_deprecated_generic_warn:n #1
780 { \__hook_deprecated_generic_warn:w #1 \s__hook_mark }
781 \cs_new_protected:Npn \__hook_deprecated_generic_warn:w
782 #1 / #2 / #3 \s__hook_mark
783 {
784     \if_cs_exist:w __hook~#1/#2/#3 \cs_end: \else:
785         \msg_warning:nnnnn { hooks } { generic-deprecated } {#1} {#2} {#3}
786     \fi:

```

```

787 \cs_gset_eq:cN { __hook~#1/#2/#3 } \scan_stop:
788 }

```

Now that the user has been told about the deprecation, we proceed by swapping `<name>` and `<place>` and adding the code to the correct hook.

```

\__hook_do_deprecated_generic:Nn
\__hook_do_deprecated_generic:Nw
\__hook_declare_deprecated_generic:NNw
\__hook_declare_deprecated_generic:NNw
789 \cs_new_protected:Npn \__hook_do_deprecated_generic:Nn #1 #2
790 { \__hook_do_deprecated_generic:Nw #1 #2 \s__hook_mark }
791 \cs_new_protected:Npn \__hook_do_deprecated_generic:Nw #1
792 #2 / #3 / #4 \s__hook_mark
793 { #1 { #2 / #4 / #3 } }
794 \cs_new_protected:Npn \__hook_declare_deprecated_generic:NNn #1 #2 #3
795 { \__hook_declare_deprecated_generic:NNw #1 #2 #3 \s__hook_mark }
796 \cs_new_protected:Npn \__hook_declare_deprecated_generic:NNw #1 #2
797 #3 / #4 / #5 \s__hook_mark
798 {
799 \__hook_try_declaring_generic_hook:wnTF #3 / #5 / #4 / \scan_stop:
800 { #3 / #5 / #4 }
801 #1 #2 { #3 / #5 / #4 }
802 }
803 \<latexrelease>\EndIncludeInRelease

804 \<latexrelease>\IncludeInRelease{2021/11/15}
805 \<latexrelease>{\__hook_try_declaring_generic_hook:wn}
806 \<latexrelease>{\Standardize-generic-hook-names}
807 \<latexrelease>\prg_new_protected_conditional:Npnn
808 \__hook_try_declaring_generic_hook:wn
809 #1 / #2 / #3 / #4 \scan_stop: #5 { TF }
810 \<latexrelease>{
811 \<latexrelease>\__hook_if_generic:nTF {#5}
812 \<latexrelease>{
813 \<latexrelease>\__hook_if_usable:nF {#5}
814 \<latexrelease>{
815 \<latexrelease>\str_if_eq:nnT {#1} { cmd }
816 \<latexrelease>{ \__hook_try_put_cmd_hook:n {#5} }
817 \<latexrelease>\__hook_make_usable:n {#5}
818 \<latexrelease>}
819 \<latexrelease>\__hook_if_generic_reversed:nT {#5}
820 \<latexrelease>{ \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
821 \<latexrelease>\prg_return_true:
822 \<latexrelease>}
823 \<latexrelease>{
824 \<latexrelease>\__hook_if_deprecated_generic:nTF {#5}
825 \<latexrelease>{
826 \<latexrelease>\__hook_deprecated_generic_warn:n {#5}
827 \<latexrelease>\exp_after:wN \__hook_declare_deprecated_generic:NNn
828 \<latexrelease>\exp:w % \exp_end:
829 \<latexrelease>}
830 \<latexrelease>{ \prg_return_false: }
831 \<latexrelease>}
832 \<latexrelease>}
833 \<latexrelease>\EndIncludeInRelease

834 \<latexrelease>\IncludeInRelease{2021/06/01}
835 \<latexrelease>{\__hook_try_declaring_generic_hook:wn}
836 \<latexrelease>{\Support~cmd~hooks}

```

```

837 <latexrelease> \prg_new_protected_conditional:Npnn
838 <latexrelease>     \__hook_try_declaring_generic_hook:wn
839 <latexrelease>     #1 / #2 / #3 / #4 \scan_stop: #5 { TF }
840 <latexrelease> {
841 <latexrelease>     \tl_if_empty:nTF {#2}
842 <latexrelease>     { \prg_return_false: }
843 <latexrelease>     {
844 <latexrelease>         \prop_if_in:NnTF \c__hook_generics_prop {#1}
845 <latexrelease>         {
846 <latexrelease>             \__hook_if_usable:nF {#5}
847 <latexrelease>             {
848 <latexrelease>                 \str_if_eq:nnT {#1} { cmd }
849 <latexrelease>                 { \__hook_try_put_cmd_hook:n {#5} }
850 <latexrelease>                 \__hook_make_usable:n {#5}
851 <latexrelease>             }
852 <latexrelease>         \prop_if_in:NnTF
853 <latexrelease>         \c__hook_generics_reversed_ii_prop {#2}
854 <latexrelease>         { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
855 <latexrelease>         {
856 <latexrelease>             \prop_if_in:NnT
857 <latexrelease>             \c__hook_generics_reversed_iii_prop {#3}
858 <latexrelease>             { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
859 <latexrelease>         }
860 <latexrelease>         \prg_return_true:
861 <latexrelease>     }
862 <latexrelease>     { \prg_return_false: }
863 <latexrelease> }
864 <latexrelease> }
865 <latexrelease> \EndIncludeInRelease

866 <latexrelease> \IncludeInRelease{2020/10/01}
867 <latexrelease>     { \__hook_try_declaring_generic_hook:wn }
868 <latexrelease>     { Support~cmd~hooks }
869 <latexrelease> \prg_new_protected_conditional:Npnn
870 <latexrelease>     \__hook_try_declaring_generic_hook:wn
871 <latexrelease>     #1 / #2 / #3 / #4 \scan_stop: #5 { TF }
872 <latexrelease> {
873 <latexrelease>     \tl_if_empty:nTF {#2}
874 <latexrelease>     { \prg_return_false: }
875 <latexrelease>     {
876 <latexrelease>         \prop_if_in:NnTF \c__hook_generics_prop {#1}
877 <latexrelease>         {
878 <latexrelease>             \__hook_if_declared:nF {#5} { \hook_new:n {#5} }
879 <latexrelease>         \prop_if_in:NnTF
880 <latexrelease>         \c__hook_generics_reversed_ii_prop {#2}
881 <latexrelease>         { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
882 <latexrelease>         {
883 <latexrelease>             \prop_if_in:NnT
884 <latexrelease>             \c__hook_generics_reversed_iii_prop {#3}
885 <latexrelease>             { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
886 <latexrelease>         }
887 <latexrelease>         \prg_return_true:
888 <latexrelease>     }
889 <latexrelease>     { \prg_return_false: }
890 <latexrelease> }

```

```

891 <latexrelease> }
892 <latexrelease> \EndIncludeInRelease

(End of definition for \__hook_try_declaring_generic_hook:wTF and others.)

```

`\__hook_if_file_hook:wTF` checks if the argument is a valid file-specific hook (not, for example, `file/before`, but `file/foo.tex/before`). If it is a file-specific hook, then it executes the `<true>` branch, otherwise `<false>`.

```

893 <latexrelease> \IncludeInRelease{2021/11/15}{\__hook_if_file_hook:w}
894 <latexrelease> {Standardize-generic-hook-names}
895 <latexrelease> \EndIncludeInRelease
896 <latexrelease> \IncludeInRelease{2020/10/01}{\__hook_if_file_hook:w}
897 <latexrelease> {Standardize-generic-hook-names}
898 <latexrelease> \prg_new_conditional:Npnn \__hook_if_file_hook:w
899 <latexrelease> #1 / #2 / #3 \s__hook_mark { TF }
900 <latexrelease> {
901 <latexrelease> \str_if_eq:nnTF {#1} { file }
902 <latexrelease> {
903 <latexrelease> \bool_lazy_or:nnTF
904 <latexrelease> { \tl_if_empty_p:n {#3} }
905 <latexrelease> { \str_if_eq_p:nn {#3} { / } }
906 <latexrelease> { \prg_return_false: }
907 <latexrelease> {
908 <latexrelease> \prop_if_in:NnTF \c__hook_generics_file_prop {#2}
909 <latexrelease> { \prg_return_true: }
910 <latexrelease> { \prg_return_false: }
911 <latexrelease> }
912 <latexrelease> }
913 <latexrelease> { \prg_return_false: }
914 <latexrelease> }
915 <latexrelease> \EndIncludeInRelease

```

(End of definition for `\__hook_if_file_hook:wTF`.)

```

\__hook_file_hook_normalize:n
\__hook_strip_double_slash:n 916 <latexrelease> \IncludeInRelease{2021/11/15}{\__hook_file_hook_normalize:n}
\__hook_strip_double_slash:w 917 <latexrelease> {Standardize-generic-hook-names}
918 <latexrelease> \EndIncludeInRelease

```

When a file-specific hook is found, before being declared it is lightly normalized by `\__hook_file_hook_normalize:n`. The current implementation just replaces two consecutive slashes (`//`) by a single one, to cope with simple cases where the user did something like `\def\input@path{./mypath/}`, in which case a hook would have to be `\AddToHook{file}/./mypath//file.tex/after`.

```

919 <latexrelease> \IncludeInRelease{2020/10/01}{\__hook_file_hook_normalize:n}
920 <latexrelease> {Standardize-generic-hook-names}
921 <latexrelease> \cs_new:Npn \__hook_file_hook_normalize:n #1
922 <latexrelease> { \__hook_strip_double_slash:n {#1} }
923 <latexrelease> \cs_new:Npn \__hook_strip_double_slash:n #1
924 <latexrelease> { \__hook_strip_double_slash:w #1 // \s__hook_mark }

```

This function is always called after testing if the argument is a file hook with `\__hook_if_file_hook:wTF`, so we can assume it has three parts (it is either `file/.../before` or `file/.../after`), so we use `#1/#2/#3 //` instead of just `#1 //` to prevent losing a slash if the file name is empty.

```

925 <latexrelease>\cs_new:Npn \__hook_strip_double_slash:w #1/#2/#3//#4\s__hook_mark
926 <latexrelease> {
927 <latexrelease> \tl_if_empty:nTF {#4}
928 <latexrelease> { #1/#2/#3 }
929 <latexrelease> { \__hook_strip_double_slash:w #1/#2/#3 /#4\s__hook_mark }
930 <latexrelease> }
931 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_file\_hook\_normalize:n, \\_\_hook\_strip\_double\_slash:n, and \\_\_hook\_strip\_double\_slash:w.)

```

\c__hook_generic_cmd/.before_tl
\c__hook_generic_cmd/.after_tl
\c__hook_generic_env/.before_tl
\c__hook_generic_env/.after_tl
\c__hook_generic_file/.before_tl
\c__hook_generic_file/.after_tl
\c__hook_generic_package/.before_tl
\c__hook_generic_package/.after_tl
\c__hook_generic_class/.before_tl
\c__hook_generic_class/.after_tl
\c__hook_generic_include/.before_tl
\c__hook_generic_include/.after_tl
\c__hook_generic_env/.begin_tl
\c__hook_generic_env/.end_tl
\c__hook_generic_include/.end_tl

```

Token lists defining the possible generic hooks. We don't provide any user interface to this as this is meant to be static.

**cmd** The generic hooks used for commands.

**env** The generic hooks used in \begin and \end.

**file, package, class, include** The generic hooks used when loading a file

```

932 <latexrelease>\IncludeInRelease{2021/11/15}{\c__hook_generics_prop}
933 <latexrelease> {Standardize-generic-hook-names}
934 <clist_map_inline:nn { cmd , env , file , package , class , include }
935 {
936 \tl_const:cn { c__hook_generic_#1/.before_tl } { + }
937 \tl_const:cn { c__hook_generic_#1/.after_tl } { - }
938 }
939 \tl_const:cn { c__hook_generic_env/.begin_tl } { + }
940 \tl_const:cn { c__hook_generic_env/.end_tl } { + }
941 \tl_const:cn { c__hook_generic_include/.end_tl } { - }
942 \tl_const:cn { c__hook_generic_include/.excluded_tl } { + }

```

Deprecated generic hooks:

```

943 <clist_map_inline:nn { file , package , class , include }
944 {
945 \tl_const:cn { c__hook_deprecated_#1/.before_tl } { }
946 \tl_const:cn { c__hook_deprecated_#1/.after_tl } { }
947 }
948 \tl_const:cn { c__hook_deprecated_include/.end_tl } { }
949 <latexrelease>\EndIncludeInRelease
950 <latexrelease>\IncludeInRelease{2020/10/01}{\c__hook_generics_prop}
951 <latexrelease> {Standardize-generic-hook-names}
952 <latexrelease>\prop_const_from_keyval:Nn \c__hook_generics_prop
953 <latexrelease> {cmd=,env=,file=,package=,class=,include=}
954 <latexrelease>\EndIncludeInRelease

```

(End of definition for \c\_\_hook\_generic\_cmd/.before\_tl and others.)

```

\c__hook_generics_reversed_ii_prop
\c__hook_generics_reversed_iii_prop
\c__hook_generics_file_prop

```

The following generic hooks are supposed to use reverse ordering (the ii and iii names are kept for the deprecation cycle):

```

955 <latexrelease>\IncludeInRelease{2021/11/15}{\c__hook_generics_reversed_ii_prop}
956 <latexrelease> {Standardize-generic-hook-names}
957 <latexrelease>\EndIncludeInRelease

```

```

958 \<latexrelease>\IncludeInRelease{2020/10/01}{\c__hook_generics_reversed_ii_prop}
959 \<latexrelease>{Standardize-generic-hook-names}
960 \<latexrelease>\prop_const_from_keyval:Nn
961 \<latexrelease>\c__hook_generics_reversed_ii_prop {after=,end=}
962 \<latexrelease>\prop_const_from_keyval:Nn
963 \<latexrelease>\c__hook_generics_reversed_iii_prop {after=}
964 \<latexrelease>\prop_const_from_keyval:Nn
965 \<latexrelease>\c__hook_generics_file_prop {before=,after=}
966 \<latexrelease>\EndIncludeInRelease

```

(End of definition for \c\_\_hook\_generics\_reversed\_ii\_prop, \c\_\_hook\_generics\_reversed\_iii\_prop, and \c\_\_hook\_generics\_file\_prop.)

\c\_\_hook\_parameter\_cmd/.before\_tl  
\c\_\_hook\_parameter\_cmd/.after\_tl

Token lists defining the number of arguments for a given type of generic hook.

```

967 \<latexrelease>\IncludeInRelease{2023/06/01}{\c__hook_parameter_cmd/.before_tl}
968 \<latexrelease>{Hooks-with-args}

```

cmd hooks are declared with 9 arguments because they have a variable number of arguments (depending on the command they are attached to), so we use the maximum here.

```

969 \tl_const:cn { c__hook_parameter_cmd/.before_tl } { #1#2#3#4#5#6#7#8#9 }
970 \tl_const:cn { c__hook_parameter_cmd/.after_tl } { #1#2#3#4#5#6#7#8#9 }
971 \<latexrelease>\EndIncludeInRelease
972 \<latexrelease>\IncludeInRelease{2020/10/01}{\c__hook_parameter_cmd/.before_tl}
973 \<latexrelease>{Hooks-with-args}
974 \<latexrelease>\EndIncludeInRelease

```

(End of definition for \c\_\_hook\_parameter\_cmd/.before\_tl and \c\_\_hook\_parameter\_cmd/.after\_tl.)

\hook\_gremove\_code:nn  
\\_\_hook\_gremove\_code:nn

With \hook\_gremove\_code:nn{<hook>}{<label>} any code for <hook> stored under <label> is removed.

```

975 \<latexrelease>\IncludeInRelease{2023/06/01}{\hook_gremove_code:nn}
976 \<latexrelease>{Hooks-with-args}
977 \cs_new_protected:Npn \hook_gremove_code:nn #1 #2
978 { \__hook_normalize_hook_args:Nnn \__hook_gremove_code:nn {#1} {#2} }
979 \cs_new_protected:Npn \__hook_gremove_code:nn #1 #2
980 {

```

First check that the hook code pool exists. \\_\_hook\_if\_usable:nTF isn't used here because it should be possible to remove code from a hook before its defined (see section 2.1.8).

```

981 \__hook_if_structure_exist:nTF {#1}
982 {

```

Then remove the chunk and run \\_\_hook\_update\_hook\_code:n so that the execution token list reflects the change if we are after \begin{document}.

If all code is to be removed, clear the code pool \g\_\_hook\_<hook>\_code\_prop, the top-level code \\_\_hook\_toplevel\_<hook>, and the next-execution code \\_\_hook\_next\_<hook>.

```

983 \str_if_eq:nnTF {#2} {*}
984 {
985 \prop_gclear:c { g__hook_#1_code_prop }
986 \__hook_toplevel_gset:nn {#1} { }
987 \__hook_next_gset:nn {#1} { }

```

```

988     }
989     {

```

If the label is `top-level` then clear the token list, as all code there is under the same label.

```

990         \str_if_eq:nnTF {#2} { top-level }
991         { \__hook_toplevel_gset:nn {#1} { } }
992         {
993             \prop_gpop:cnNF { g__hook_#1_code_prop }
994             {#2} \l__hook_return_tl
995             { \msg_warning:nnnn { hooks } { cannot-remove } {#1} {#2} }
996         }
997     }

```

Finally update the code, if the hook exists.

```

998         \__hook_if_usable:nT {#1}
999         { \__hook_update_hook_code:n {#1} }
1000     }

```

If the code pool for this hook doesn't exist, show a warning:

```

1001     {
1002         \__hook_if_deprecated_generic:nTF {#1}
1003         {
1004             \__hook_deprecated_generic_warn:n {#1}
1005             \__hook_do_deprecated_generic:Nn
1006             \__hook_gremove_code:nn {#1} {#2}
1007         }
1008         { \msg_warning:nnnn { hooks } { cannot-remove } {#1} {#2} }
1009     }
1010 }

```

```

1011 \<latexrelease>\EndIncludeInRelease

```

```

1012 \<latexrelease>\IncludeInRelease{2020/10/01}{\hook_gremove_code:nn}
1013 \<latexrelease>{Hooks-with-args}
1014 \<latexrelease>\cs_new_protected:Npn \__hook_gremove_code:nn #1 #2
1015 \<latexrelease> {
1016     \<latexrelease> \__hook_if_structure_exist:nTF {#1}
1017     {
1018         \<latexrelease> \str_if_eq:nnTF {#2} { *}
1019         {
1020             \<latexrelease> \prop_gclear:c { g__hook_#1_code_prop }
1021             \<latexrelease> \__hook_tl_gclear:c { __hook_toplevel~#1 }
1022             \<latexrelease> \__hook_tl_gclear:c { __hook_next~#1 }
1023         }
1024         {
1025             \<latexrelease> \str_if_eq:nnTF {#2} { top-level }
1026             { \<latexrelease> \__hook_tl_gclear:c { __hook_toplevel~#1 } }
1027             {
1028                 \<latexrelease> \prop_gpop:cnNF { g__hook_#1_code_prop }
1029                 {#2} \l__hook_return_tl
1030                 { \<latexrelease> \msg_warning:nnnn { hooks } { cannot-remove }
1031                     {#1} {#2} }
1032             }
1033         }
1034         \<latexrelease> \__hook_if_usable:nT {#1}
1035         { \<latexrelease> \__hook_update_hook_code:n {#1} }

```

```

1036 <latexrelease>      }
1037 <latexrelease>      {
1038 <latexrelease>      \_hook_if_deprecated_generic:nTF {#1}
1039 <latexrelease>      {
1040 <latexrelease>      \_hook_deprecated_generic_warn:n {#1}
1041 <latexrelease>      \_hook_do_deprecated_generic:Nn
1042 <latexrelease>      \_hook_gremove_code:nn {#1} {#2}
1043 <latexrelease>      }
1044 <latexrelease>      { \msg_warning:nnnn { hooks } { cannot-remove }
1045 <latexrelease>      {#1} {#2} }
1046 <latexrelease>      }
1047 <latexrelease>    }
1048 <latexrelease> \EndIncludeInRelease

```

(End of definition for `\hook_gremove_code:nn` and `\_hook_gremove_code:nn`. This function is documented on page 215.)

```

\_hook_cs_gput_right:nnn
\_hook_cs_gput_right_fast:nnn
\_hook_cs_gput_right_slow:nnn
\_hook_code_gset_auxi:nnnn
\_hook_code_gset_auxi:eeen

```

This macro is used to append code to the `toplevel` and `next` token lists, treating them correctly depending on their number of arguments, and depending on whether the code being added should have parameter tokens understood as parameters, or doubled to be stored as parameter tokens.

```

1049 <latexrelease> \IncludeInRelease{2023/06/01}{\_hook_cs_gput_right:nnn}
1050 <latexrelease> {Hooks~with~args}

```

Check if the current hook is declared and takes no arguments. In this case, we short-circuit and use the simpler and much faster approach that doesn't require hash-doubling.

```

1051 \cs_new_protected:Npn \_hook_cs_gput_right:nnn #1 #2
1052 {
1053   \if:w T
1054     \_hook_if_declared:nF {#2} { F }
1055     \tl_if_empty:cF { c\_hook\_#2\_parameter\_tl } { F }
1056     T
1057     \exp_after:wN \_hook_cs_gput_right_fast:nnn
1058   \else:
1059     \exp_after:wN \_hook_cs_gput_right_slow:nnn
1060   \fi:
1061   {#1} {#2}
1062 }
1063 \cs_new_protected:Npn \_hook_cs_gput_right_fast:nnn #1 #2 #3
1064 { \cs_gset:cpx { \_hook#1~#2 }
1065   { \exp_not:v { \_hook#1~#2 } \exp_not:n {#3} } }
1066 \cs_new_protected:Npn \_hook_cs_gput_right_slow:nnn #1 #2 #3
1067 {

```

The auxiliary `\_hook_code_gset_auxi:eeen` just does the assignment at the end. Its first argument is the parameter text of the macro, which is chosen here depending if `\c\_hook\_hook\_parameter\_tl` exists, if the hook is declared, and if it's a generic hook.

```

1068   \cs_if_exist:cF { \_hook#1~#2 }
1069   { \_hook_code_gset_aux:nnn {#1} {#2} { } }
1070   \_hook_code_gset_auxi:eeen
1071   {
1072     \_hook_if_declared:nTF {#2}
1073     { \tl_use:c { c\_hook\_#2\_parameter\_tl } }
1074     {
1075       \_hook_if_generic:nTF {#2}

```

```

1076         { \__hook_generic_parameter:n {#2} }
1077         { \c__hook_nine_parameters_tl }
1078     }
1079 }

```

Here we take the existing code in the macro, expand it with as many arguments as it takes, then double the hashes so the code can be reused.

PhO: Maybe can be improved. The case of adding to an empty cs can be optimized by quickly checking \cs\_replacement\_spec.

```

1080 {
1081     \exp_args:NNo \exp_args:No \__hook_double_hashes:n
1082     {
1083         \cs:w \__hook#1~#2 \exp_last_unbraced:Ne \cs_end:
1084         { \__hook_braced_cs_parameter:n { \__hook#1~#2 } }
1085     }
1086 }

```

Now the new code: if we are replacing arguments, then hashes are left untouched, otherwise they are doubled.

```

1087 {
1088     \__hook_if_replacing_args:TF
1089     { \exp_not:n }
1090     { \__hook_double_hashes:n }
1091     {#3}
1092 }

```

And finally, the csname which we'll define with all the above.

```

1093 { \__hook#1~#2 }
1094 }

```

And as promised, the auxiliary that does the definition.

```

1095 \cs_new_protected:Npn \__hook_code_gset_auxi:nnnn #1 #2 #3 #4
1096 { \cs_gset:cpn {#4} #1 { #2 #3 } }
1097 \cs_generate_variant:Nn \__hook_code_gset_auxi:nnnn { een }
1098 <latexrelease>\EndIncludeInRelease
1099 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_cs_gput_right:nnn}
1100 <latexrelease>{Hooks-with-args}
1101 <latexrelease>\cs_undefine:N \__hook_cs_gput_right:nnn
1102 <latexrelease>\cs_undefine:N \__hook_cs_gput_right_fast:nnn
1103 <latexrelease>\cs_undefine:N \__hook_cs_gput_right_slow:nnn
1104 <latexrelease>\cs_undefine:N \__hook_code_gset_auxi:nnnn
1105 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_cs\_gput\_right:nnn and others.)

These macros define \\_\_hook<type>\_<hook> (with <type> being \_next, \_toplevel, or empty) with the given code and the parameters stored in \c\_\_hook\_<hook>\_parameter\_tl (or none, if that doesn't exist).

```

\__hook_code_gset:nn
\__hook_code_gset:ne
\__hook_toplevel_gset:nn
\__hook_next_gset:nn
\__hook_code_gset_aux:nnn
1106 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_code_gset:nn}
1107 <latexrelease>{Hooks-with-args}
1108 \cs_new_protected:Npn \__hook_code_gset:nn
1109 { \__hook_code_gset_aux:nnn { } }
1110 \cs_new_protected:Npn \__hook_toplevel_gset:nn
1111 { \__hook_code_gset_aux:nnn { _toplevel } }
1112 \cs_new_protected:Npn \__hook_next_gset:nn
1113 { \__hook_code_gset_aux:nnn { _next } }
1114 \cs_new_protected:Npn \__hook_code_gset_aux:nnn #1 #2 #3

```

```

1115 {
1116   \cs_gset:cpn { __hook#1~#2 \exp_last_unbraced:Ne }
1117   { \__hook_parameter:n {#2} }
1118   {#3}
1119 }
1120 \cs_generate_variant:Nn \__hook_code_gset:nn { ne }
1121 <latexrelease>\EndIncludeInRelease
1122 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_code_gset:nn}
1123 <latexrelease>{Hooks-with-args}
1124 <latexrelease>\cs_undefine:N \__hook_code_gset:nn
1125 <latexrelease>\cs_undefine:N \__hook_toplevel_gset:nn
1126 <latexrelease>\cs_undefine:N \__hook_next_gset:nn
1127 <latexrelease>\cs_undefine:N \__hook_code_gset_aux:nnn
1128 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_code\_gset:nn and others.)

\\_\_hook\_normalise\_cs\_args:nn This macro normalizes the parameters of the macros \\_\_hook<type>\\_hook to take the right number of arguments after a hook is declared. At this point we know \c\_\_hook\\_hook\\_parameter\\_tl exists, so use that to count the arguments and use that as <parameter text> for the newly (re)defined macro.

```

1129 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_normalise_cs_args:nn}
1130 <latexrelease>{Hooks-with-args}
1131 \cs_new_protected:Npn \__hook_normalise_cs_args:nn #1 #2
1132 {
1133   \cs_if_exist:cT { __hook#1~#2 }
1134   {
1135     \__hook_code_gset_auxi:eeen
1136     { \tl_use:c { c__hook_#2_parameter_tl } }
1137     {
1138       \exp_args:NNo \exp_args:No \__hook_double_hashes:n
1139       {
1140         \cs:w __hook#1~#2 \exp_last_unbraced:Ne \cs_end:
1141         { \__hook_braced_cs_parameter:n { __hook#1~#2 } }
1142       }
1143     }
1144     { }
1145     { __hook#1~#2 }
1146   }
1147 }
1148 <latexrelease>\EndIncludeInRelease
1149 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_normalise_cs_args:nn}
1150 <latexrelease>{Hooks-with-args}
1151 <latexrelease>\cs_undefine:N \__hook_normalise_cs_args:nn
1152 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_normalise\_cs\_args:nn.)

\\_\_hook\_normalise\_code\_pool:n This one's a bit of a hack. It takes a hook, and iterates over its code pool (\g\_\_hook\\_hook\\_code\\_prop), redefining each code label to use only valid arguments. This is used when, for example, a code is added referencing arguments #1 and #2, but the hook has only #1. In this example, every reference to #2 is changed to ##2. This is done because

otherwise T<sub>E</sub>X will throw a low-level error every time some change happens to the hook (code is added, a rule is set, etc), which can get quite repetitive for no good reason.

```

1153 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_normalise_code_pool:n}
1154 <latexrelease>{Hooks-with-args}
1155 \cs_new_protected:Npn \__hook_normalise_code_pool:n #1
1156 {

```

First, call `\__hook_set_normalise_fn:nn` with the hook name to set everything up, then we'll loop over the hook's code pool applying the normalization above. After that's done, copy the temporary property list back to the hook's.

```

1157   \__hook_set_normalise_fn:nn {#1} { Offending~label:~'##1' }
1158   \prop_clear:N \l__hook_work_prop
1159   \prop_map_function:cN { g__hook_#1_code_prop } \__hook_normalise_fn:nn
1160   \prop_gset_eq:cN { g__hook_#1_code_prop } \l__hook_work_prop
1161 }

```

The sole purpose of this function is to define `\__hook_normalise_fn:nn`, which will then do the correcting of the code being added to the hook.

```

1162 \cs_new_protected:Npn \__hook_set_normalise_fn:nn #1 #2
1163 {

```

To start, we define two auxiliary token lists. `\l__hook_tmpb_tl` contains:

```

    {\c__hook_hashes_tl 1}
    {\c__hook_hashes_tl 2}
    ...
    {\c__hook_hashes_tl 9}

1164   \cs_set:Npn \__hook_tmp:w ##1##2##3##4##5##6##7##8##9 { }
1165   \tl_set:Nx \l__hook_tmpb_tl
1166     { \__hook_braced_cs_parameter:n { __hook_tmp:w } }
1167   \group_begin:
1168     \__hook_tl_set:cn { c__hook_hash_tl } { \exp_not:N \c__hook_hashes_tl }
1169     \use:e
1170     {
1171     \group_end:
1172     \tl_set:Nn \exp_not:N \l__hook_tmpb_tl { \l__hook_tmpb_tl }
1173     }

```

And `\l__hook_tmpa_tl` contains:

```

    {\c__hook_hash_tl 1}
    {\c__hook_hash_tl 2}
    ...
    {\c__hook_hash_tl <n>}

```

with `<n>` being the number of arguments declared for the hook.

```

1174   \exp_last_unbraced:NNf
1175   \cs_set:Npn \__hook_tmp:w { \__hook_parameter:n {#1} } { }
1176   \tl_set:Nx \l__hook_tmpa_tl
1177     { \__hook_braced_cs_parameter:n { __hook_tmp:w } }

```

Now this function does the fun part. It is meant to be used with `\prop_map_function:NN`, taking a label name in `##1` and the code stored in that label in `##2`.

```

1178   \cs_gset_protected:Npx \__hook_normalise_fn:nn ##1 ##2
1179   {

```

Here we'll define two auxiliary macros: the first one throws an error when it detects an invalid argument reference. It piggybacks on T<sub>E</sub>X's low-level "Illegal parameter number" error, but it defines a weirdly-named control sequence so that the error comes out nicely formatted. For example, if the label "badpkg" adds some code that references argument #3 in the hook "foo", which takes only two arguments, the error will be:

```
! Illegal parameter number in definition of hook 'foo'.
(hooks)          Offending label: 'badpkg'.
<to be read again>
3
```

At the point of this definition, the error is raised if the code happens to reference an invalid argument. If it was possible to detect that this definition raised no error, the next step would be unnecessary. We'll do all this in a group so this weird definition doesn't leak out, and set `\tex_escapechar:D` to -1 so this hack shows up extra nice in the case of an error.

```
1180 \group_begin:
1181 \int_set:Nn \tex_escapechar:D { -1 }
1182 \cs_set:cpn
1183 {
1184 hook~'#1'. ^^J
1185 (hooks) \prg_replicate:nn { 13 } { ~ }
1186 #2 % more message text
1187 }
1188 \exp_not:v { c__hook_#1_parameter_tl }
1189 {##2}
1190 \group_end:
```

This next macro, with a much less fabulous name, takes always nine arguments, and it just transfers the code `##2` under the label `##1` to the temporary property list. The first  $\langle n \rangle$  arguments are taken from `\l__hook_tmpa_tl`, and the other  $9 - \langle n \rangle$  taken from `\l__hook_tmpb_tl` (which contains twice as many # tokens as the former). Then, `\__hook_double_hashes:n` is used to double non-argument hashes, and expand the `\c__hook_hash_tl` and `\c__hook_hashes_tl` to the actual parameter tokens.

```
1191 \cs_set:Npn \exp_not:N \__hook_tmp:w
1192 \exp_not:V \c__hook_nine_parameters_tl
1193 {
1194 \prop_put:Nne \exp_not:N \l__hook_work_prop
1195 {##1} { \exp_not:N \__hook_double_hashes:n {##2} }
1196 }
```

This next macro, with a much less fabulous name, takes always nine arguments, and it just transfers the code `##2` under the label `##1` to the temporary property list. The first  $\langle n \rangle$  arguments are taken from `\l__hook_tmpa_tl`, and the other  $9 - \langle n \rangle$  taken from `\l__hook_tmpb_tl` (which contains twice as many # tokens as the former). Then, `\__hook_double_hashes:n` is used to double non-argument hashes, and expand the `\c__hook_hash_tl` and `\c__hook_hashes_tl` to the actual parameter tokens.

```
1197 \exp_not:N \__hook_tmp:w
1198 \exp_not:V \l__hook_tmpa_tl
1199 \exp_args:No \exp_not:o
1200 { \exp_after:wN \__hook_tmp:w \l__hook_tmpb_tl }
1201 }
1202 }
```

```

1203 \cs_new_eq:NN \__hook_normalise_fn:nn ?
1204 \<latexrelease>\EndIncludeInRelease
1205 \<latexrelease>\IncludeInRelease{2020/10/01}{\__hook_normalise_code_pool:n}
1206 \<latexrelease>{Hooks-with-args}
1207 \<latexrelease>\cs_undefine:N \__hook_normalise_code_pool:n
1208 \<latexrelease>\EndIncludeInRelease

```

Check if the expansion of a control sequence is empty by looking at its replacement text.

```

\__hook_cs_if_empty_p:c
\__hook_cs_if_empty:cTF

```

```

1209 \<latexrelease>\IncludeInRelease{2023/06/01}{\__hook_cs_if_empty:c}
1210 \<latexrelease>{Hooks-with-args}
1211 \prg_new_conditional:Npnn \__hook_cs_if_empty:c #1 { p, T, F, TF }
1212 {
1213   \if:w \scan_stop: \__hook_replacement_spec:c {#1} \scan_stop:
1214   \prg_return_true:
1215   \else:
1216   \prg_return_false:
1217   \fi:
1218 }
1219 \cs_new:Npn \__hook_replacement_spec:c #1
1220 {
1221   \exp_args:Nc \token_if_macro:NT {#1}
1222   { \cs_replacement_spec:c {#1} }
1223 }
1224 \<latexrelease>\EndIncludeInRelease
1225 \<latexrelease>\IncludeInRelease{2020/10/01}{\__hook_cs_if_empty:c}
1226 \<latexrelease>{Hooks-with-args}
1227 \<latexrelease>\cs_undefine:N \__hook_cs_if_empty:c
1228 \<latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_normalise\_code\_pool:n, \\_\_hook\_set\_normalise\_fn:nn, and \\_\_hook\_cs\_if\_empty:cTF.)

```

\__hook_braced_cs_parameter:n
\__hook_braced_hidden_loop:w
\__hook_cs_parameter_count:N
\__hook_cs_parameter_count:w
\__hook_cs_end:w

```

Looks at the *<parameter text>* of a control sequence, and returns a run of “hidden” braced parameters for that macro. This works as long as the macros take a simple run of zero to nine arguments. The parameters are “hidden” because the parameter tokens are returned inside \c\_\_hook\_hash\_tl instead of explicitly, so that \\_\_hook\_double\_hashes:n won’t touch these.

```

1229 \<latexrelease>\IncludeInRelease{2023/06/01}{\__hook_braced_cs_parameter:n}
1230 \<latexrelease>{Hooks-with-args}
1231 \cs_new:Npn \__hook_braced_cs_parameter:n #1
1232 {
1233   \exp_last_unbraced:Ne \__hook_braced_hidden_loop:w
1234   { \exp_args:Nc \__hook_cs_parameter_count:N {#1} } ? \s__hook_mark
1235 }
1236 \cs_new:Npn \__hook_braced_hidden_loop:w #1
1237 {
1238   \if:w ? #1
1239   \__hook_use_i_delimit_by_s_mark:nw
1240   \fi:
1241   { \exp_not:N \c__hook_hash_tl #1 }
1242   \__hook_braced_hidden_loop:w
1243 }

```

```

1244 \cs_new:Npn \__hook_cs_parameter_count:N #1
1245 {
1246   \exp_last_unbraced:Nf \__hook_cs_parameter_count:w
1247   { \token_if_macro:NT #1 { \cs_parameter_spec:N #1 } }
1248   ? \__hook_cs_end:w ? \__hook_cs_end:w ? \__hook_cs_end:w
1249   ? \__hook_cs_end:w ? \__hook_cs_end:w ? \__hook_cs_end:w
1250   ? \__hook_cs_end:w ? \__hook_cs_end:w ? \__hook_cs_end:w
1251   \s__hook_mark
1252 }
1253 \cs_new:Npn \__hook_cs_parameter_count:w #1#2 #3#4 #5#6 #7#8
1254 { #2 #4 #6 #8 \__hook_cs_parameter_count:w }
1255 \cs_new:Npn \__hook_cs_end:w #1 \s__hook_mark { }
1256 \<latexrelease>\EndIncludeInRelease

```

This function can't be undefined when rolling back because it's used at the end of this module to adequate the hook data structures to previous versions.

```

1257 \<latexrelease>\IncludeInRelease{2020/10/01}{\__hook_braced_cs_parameter:n}
1258 \<latexrelease>{Hooks-with-args}
1259 \<latexrelease>\EndIncludeInRelease

```

*(End of definition for \\_\_hook\_braced\_cs\_parameter:n and others.)*

\\_\_hook\_braced\_parameter:n  
 \\_\_hook\_braced\_real\_loop:w

This one is used in simpler cases, where no special handling of hashes is required. This is used only inside \\_\_hook\_initialize\_hook\_code:n, so it assumes \c\_\_hook\_{hook}\_parameter\_tl is defined, but should work otherwise.

```

1260 \<latexrelease>\IncludeInRelease{2023/06/01}{\__hook_braced_parameter:n}
1261 \<latexrelease>{Hooks-with-args}
1262 \cs_new:Npn \__hook_braced_parameter:n #1
1263 {
1264   \if_case:w
1265     \int_eval:n
1266     { \exp_args:Nv \str_count:n { c__hook_#1_parameter_tl } / 3 }
1267     \exp_stop_f:
1268     \or: {##1}
1269     \or: {##1} {##2}
1270     \or: {##1} {##2} {##3}
1271     \or: {##1} {##2} {##3} {##4}
1272     \or: {##1} {##2} {##3} {##4} {##5}
1273     \or: {##1} {##2} {##3} {##4} {##5} {##6}
1274     \or: {##1} {##2} {##3} {##4} {##5} {##6} {##7}
1275     \or: {##1} {##2} {##3} {##4} {##5} {##6} {##7} {##8}
1276     \or: {##1} {##2} {##3} {##4} {##5} {##6} {##7} {##8} {##9}
1277     \else:
1278       \msg_expandable_error:nnn { latex2e } { should-not-happen }
1279       { Invalid-parameter-spec. }
1280     \fi:
1281 }
1282 \<latexrelease>\EndIncludeInRelease
1283 \<latexrelease>\IncludeInRelease{2020/10/01}{\__hook_braced_parameter:n}
1284 \<latexrelease>{Hooks-with-args}
1285 \<latexrelease>\cs_undefine:N \__hook_braced_parameter:n
1286 \<latexrelease>\EndIncludeInRelease

```

*(End of definition for \\_\_hook\_braced\_parameter:n and \\_\_hook\_braced\_real\_loop:w.)*

`\__hook_parameter:n` This is just a shortcut to e- or f-expand to the `<parameter text>` of the hook.

```

1287 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_parameter:n}
1288 <latexrelease>{Hooks-with-args}
1289 \cs_new:Npn \__hook_parameter:n #1
1290 {
1291   \cs:w c__hook_
1292   \tl_if_exist:cTF { c__hook_#1_parameter_tl }
1293     { #1_parameter } { empty }
1294   _tl \cs_end:
1295 }
1296 \cs_new:Npn \__hook_generic_parameter:n #1
1297 { \__hook_generic_parameter:w #1 / / / \s__hook_mark }
1298 \cs_new:Npn \__hook_generic_parameter:w #1 / #2 / #3 / #4 \s__hook_mark
1299 {
1300   \cs_if_exist_use:cF { c__hook_parameter_#1/./#3_tl }
1301     { \c__hook_empty_tl }
1302 }
1303 <latexrelease>\EndIncludeInRelease
1304 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_parameter:n}
1305 <latexrelease>{Hooks-with-args}
1306 <latexrelease>\cs_undefine:N \__hook_parameter:n
1307 <latexrelease>\cs_undefine:N \__hook_generic_parameter:n
1308 <latexrelease>\EndIncludeInRelease

```

(End of definition for `\__hook_parameter:n`.)

## 4.7 Setting rules for hooks code

`\g__hook_??_code_prop`  
`\__hook~??`  
`\g__hook_??_reversed_tl`  
`\c__hook_??_parameter_tl`

Initially these variables simply used an empty “label” name (not two question marks). This was a bit unfortunate, because then `l3doc` complains about `__` in the middle of a command name when trying to typeset the documentation. However using a “normal” name such as `default` has the disadvantage of that being not really distinguishable from a real hook name. I now have settled for `??` which needs some gymnastics to get it into the csname, but since this is used a lot, the code should be fast, so this is not done with `c` expansion in the code later on.

`\__hook_` isn’t used, but it has to be defined to trick the code into thinking that `??` is actually a hook.

```

1309 \prop_new:c { g__hook_??_code_prop }
1310 \prop_new:c { __hook~?? }

```

Default rules are always given in normal ordering (never in reversed ordering). If such a rule is applied to a reversed hook it behaves as if the rule is reversed (e.g., **after** becomes **before**) because those rules are applied first and then the order is reversed.

```

1311 \tl_new:c { g__hook_??_reversed_tl }

```

The parameter text for the “default” hook is empty.

```

1312 <latexrelease>\IncludeInRelease{2023/06/01}{\c__hook_??_parameter_tl}
1313 <latexrelease>{Hooks-with-args}
1314 \tl_const:cn { c__hook_??_parameter_tl } { }
1315 <latexrelease>\EndIncludeInRelease
1316 <latexrelease>\IncludeInRelease{2020/10/01}{\c__hook_??_parameter_tl}
1317 <latexrelease>{Hooks-with-args}
1318 <latexrelease>\cs_undefine:c { c__hook_??_parameter_tl }
1319 <latexrelease>\EndIncludeInRelease

```

(End of definition for `\g_hook_??_code_prop` and others.)

`\hook_gset_rule:nnnn` With `\hook_gset_rule:nnnn{<hook>}{<label1>}{<relation>}{<label2>}` a relation is defined between the two code labels for the given `<hook>`. The special hook `??` stands for *any* hook, which sets a default rule (to be used if no other relation between the two hooks exist).

```

1320 \cs_new_protected:Npn \hook_gset_rule:nnnn #1#2#3#4
1321 {
1322   \__hook_normalize_hook_rule_args:Nnnnn \__hook_gset_rule:nnnn
1323   {#1} {#2} {#3} {#4}
1324 }
1325 <latexrelease>\IncludeInRelease{2022/06/01}{\__hook_gset_rule:nnnn}
1326 <latexrelease>          {Refuse-setting-rule-for-one-time-hooks}
1327 \cs_new_protected:Npn \__hook_gset_rule:nnnn #1#2#3#4
1328 {
1329   \__hook_if_deprecated_generic:nT {#1}
1330   {
1331     \__hook_deprecated_generic_warn:n {#1}
1332     \__hook_do_deprecated_generic:Nn \__hook_gset_rule:nnnn {#1}
1333     {#2} {#3} {#4}
1334     \__hook_use_none_delimit_by_s_mark:w
1335   }
1336   \__hook_if_execute_immediately:nT {#1}
1337   {
1338     \msg_error:nnnnnn { hooks } { rule-too-late }
1339     {#1} {#2} {#3} {#4}
1340     \__hook_use_none_delimit_by_s_mark:w
1341   }

```

First we ensure the basic data structure of the hook exists:

```

1342 \__hook_init_structure:n {#1}

```

Then we clear any previous relationship between both labels.

```

1343 \__hook_rule_gclear:nnn {#1} {#2} {#4}

```

Then we call the function to handle the given rule. Throw an error if the rule is invalid.

```

1344 \cs_if_exist_use:cTF { __hook_rule_#3_gset:nnn }
1345 {
1346   {#1} {#2} {#4}
1347   \__hook_update_hook_code:n {#1}
1348 }
1349 {
1350   \msg_error:nnnnnn { hooks } { unknown-rule }
1351   {#1} {#2} {#3} {#4}
1352 }
1353 \s__hook_mark
1354 }
1355 <latexrelease>\EndIncludeInRelease
1356 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_gset_rule:nnnn}
1357 <latexrelease>          {Refuse-setting-rule-for-one-time-hooks}
1358 <latexrelease>\cs_new_protected:Npn \__hook_gset_rule:nnnn #1#2#3#4
1359 <latexrelease> {
1360 <latexrelease>   \__hook_if_deprecated_generic:nT {#1}

```

```

1361 <latexrelease>      {
1362 <latexrelease>      \_hook_deprecated_generic_warn:n {#1}
1363 <latexrelease>      \_hook_do_deprecated_generic:Nn \_hook_gset_rule:nnnn
1364 <latexrelease>      {#1} {#2} {#3} {#4}
1365 <latexrelease>      \exp_after:wN \use_none:nnnnnnnnn \use_none:n
1366 <latexrelease>      }
1367 <latexrelease>      \_hook_init_structure:n {#1}
1368 <latexrelease>      \_hook_rule_gclear:nnn {#1} {#2} {#4}
1369 <latexrelease>      \cs_if_exist_use:cTF { \_hook_rule_#3_gset:nnn }
1370 <latexrelease>      {
1371 <latexrelease>          {#1} {#2} {#4}
1372 <latexrelease>          \_hook_update_hook_code:n {#1}
1373 <latexrelease>      }
1374 <latexrelease>      {
1375 <latexrelease>          \msg_error:nnnnnn { hooks } { unknown-rule }
1376 <latexrelease>          {#1} {#2} {#3} {#4}
1377 <latexrelease>      }
1378 <latexrelease>  }
1379 <latexrelease> \EndIncludeInRelease

```

(End of definition for `\hook_gset_rule:nnnn` and `\_hook_gset_rule:nnnn`. This function is documented on page 215.)

```

\_hook_rule_before_gset:nnn
\_hook_rule_after_gset:nnn
\_hook_rule_<_gset:nnn
\_hook_rule_>_gset:nnn

```

Then we add the new rule. We need to normalize the rules here to allow for faster processing later. Given a pair of labels  $l_A$  and  $l_B$ , the rule  $l_A > l_B$  is the same as  $l_B < l_A$  only presented differently. But by normalizing the forms of the rule to a single representation, say,  $l_B < l_A$ , reduces the time spent looking for the rules later considerably.

Here we do that normalization by using `\(pdf)strcmp` to lexically sort labels  $l_A$  and  $l_B$  to a fixed order. This order is then enforced every time these two labels are used together.

Here we use `\_hook_label_pair:nn {<hook>} {<lA>} {<lB>}` to build a string  $l_B || l_A$  with a fixed order, and use `\_hook_label_ordered:nnTF` to apply the correct rule to the pair of labels, depending if it was sorted or not.

```

1380 \cs_new_protected:Npn \_hook_rule_before_gset:nnn #1#2#3
1381 {
1382   \_hook_tl_gset:cx
1383   { g\_hook_#1_rule_ \_hook_label_pair:nn {#2} {#3} _tl }
1384   { \_hook_label_ordered:nnTF {#2} {#3} { < } { > } }
1385 }
1386 \cs_new_eq:cN { \_hook_rule_<_gset:nnn } \_hook_rule_before_gset:nnn
1387 \cs_new_protected:Npn \_hook_rule_after_gset:nnn #1#2#3
1388 {
1389   \_hook_tl_gset:cx
1390   { g\_hook_#1_rule_ \_hook_label_pair:nn {#3} {#2} _tl }
1391   { \_hook_label_ordered:nnTF {#3} {#2} { < } { > } }
1392 }
1393 \cs_new_eq:cN { \_hook_rule_>_gset:nnn } \_hook_rule_after_gset:nnn

```

(End of definition for `\_hook_rule_before_gset:nnn` and others.)

```

\_hook_rule_voids_gset:nnn

```

This rule removes (clears, actually) the code from label #3 if label #2 is in the hook #1.

```

1394 \cs_new_protected:Npn \_hook_rule_voids_gset:nnn #1#2#3
1395 {

```

```

1396 \__hook_tl_gset:cx
1397 { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl }
1398 { \__hook_label_ordered:nnTF {#2} {#3} { -> } { <- } }
1399 }

```

(End of definition for \\_\_hook\_rule\_voids\_gset:nnn.)

These relations make an error/warning if labels #2 and #3 appear together in hook #1.

```

1400 \cs_new_protected:cpn { \__hook_rule_incompatible-error_gset:nnn } #1#2#3
1401 { \__hook_tl_gset:cn
1402   { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl }
1403   { xE }
1404 }
1405 \cs_new_protected:cpn { \__hook_rule_incompatible-warning_gset:nnn } #1#2#3
1406 { \__hook_tl_gset:cn
1407   { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl }
1408   { xW }
1409 }

```

(End of definition for \\_\_hook\_rule\_incompatible-error\_gset:nnn and  
\\_\_hook\_rule\_incompatible-warning\_gset:nnn.)

Undo a setting. \\_\_hook\_rule\_unrelated\_gset:nnn doesn't need to do anything, since we use \\_\_hook\_rule\_gclear:nnn before setting any rule.

```

1410 \cs_new_protected:Npn \__hook_rule_unrelated_gset:nnn #1#2#3 { }
1411 \cs_new_protected:Npn \__hook_rule_gclear:nnn #1#2#3
1412 { \cs_undefine:c { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl } }

```

(End of definition for \\_\_hook\_rule\_unrelated\_gset:nnn and \\_\_hook\_rule\_gclear:nnn.)

Ensure that the lexically greater label comes first.

```

1413 \cs_new:Npn \__hook_label_pair:nn #1#2
1414 {
1415   \if_case:w \__hook_str_compare:nn {#1} {#2} \exp_stop_f:
1416     #1 | #1 % 0
1417   \or:   #1 | #2 % +1
1418   \else: #2 | #1 % -1
1419   \fi:
1420 }

```

(End of definition for \\_\_hook\_label\_pair:nn.)

Check that labels #1 and #2 are in the correct order (as returned by \\_\_hook\_label\_pair:nn) and if so return true, else return false.

```

1421 \prg_new_conditional:Npnn \__hook_label_ordered:nn #1#2 { TF }
1422 {
1423   \if_int_compare:w \__hook_str_compare:nn {#1} {#2} > 0 \exp_stop_f:
1424   \prg_return_true:
1425   \else:
1426   \prg_return_false:
1427   \fi:
1428 }

```

(End of definition for \\_\_hook\_label\_ordered:nnTF.)

`\__hook_if_label_case:nnnnn` To avoid doing the string comparison twice in `\__hook_initialize_single:NNn` (once with `\str_if_eq:nn` and again with `\__hook_label_ordered:nn`), we use a three-way branching macro that will compare #1 and #2 and expand to `\use_i:nnn` if they are equal, `\use_ii:nn` if #1 is lexically greater, and `\use_iii:nn` otherwise.

```

1429 \cs_new:Npn \__hook_if_label_case:nnnnn #1#2
1430 {
1431   \cs:w use_
1432   \if_case:w \__hook_str_compare:nn {#1} {#2}
1433     i \or: ii \else: iii \fi: :nnn
1434   \cs_end:
1435 }

```

(End of definition for `\__hook_if_label_case:nnnnn`.)

`\__hook_update_hook_code:n` Before `\begin{document}` this does nothing, in the body it reinitializes the hook code using the altered data.

```

1436 \cs_new_eq:NN \__hook_update_hook_code:n \use_none:n

```

(End of definition for `\__hook_update_hook_code:n`.)

`\__hook_initialize_all:` Initialize all known hooks (at `\begin{document}`), i.e., update the fast execution token lists to hold the necessary code in the right order.

```

1437 <latexrelease> \IncludeInRelease{2023/06/01}{\__hook_initialize_all:}
1438 <latexrelease> {Hooks-with-args}
1439 \cs_new_protected:Npn \__hook_initialize_all:
1440 {

```

First we change `\__hook_update_hook_code:n` which so far was a no-op to now initialize one hook. This way any later updates to the hook will run that code and also update the execution token list.

```

1441   \cs_gset_eq:NN \__hook_update_hook_code:n \__hook_initialize_hook_code:n

```

Now we loop over all hooks that have been defined and update each of them. Here we have to determine if the hook has arguments so that auxiliaries know what to do with hashes. We look at `\c__hook_<hook>_parameter_tl`, if it has any parameters, and set `replacing_args` accordingly.

```

1442   \__hook_debug:n { \prop_gclear:N \g__hook_used_prop }
1443   \seq_map_inline:Nn \g__hook_all_seq
1444   {
1445     \tl_if_empty:cTF { c__hook_##1_parameter_tl }
1446     { \__hook_replacing_args_false: }
1447     { \__hook_replacing_args_true: }
1448     \__hook_update_hook_code:n {##1}
1449     \__hook_replacing_args_reset:
1450   }

```

If we are debugging we show results hook by hook for all hooks that have data.

```

1451   \__hook_debug:n
1452   {
1453     \iow_term:x { ^^J[lthooks]~ All-initialized~(non-empty)~hooks: }
1454     \prop_map_inline:Nn \g__hook_used_prop
1455     {
1456       \iow_term:x
1457       { ^^J ~ ##1 ~ -> ~ \cs_replacement_spec:c { __hook-##1 } ~ }
1458     }
1459   }

```

After all hooks are initialized we change the “use” to just call the hook code and not initialize it (as this was already done in the preamble.

```

1460 \_\hook_post_initialization_defs:
1461 }

1462 <latexrelease>\EndIncludeInRelease
1463 <latexrelease>\IncludeInRelease{2020/10/01}{\_\hook_initialize_all:}
1464 <latexrelease> {Hooks-with-args}
1465 <latexrelease>\cs_gset_protected:Npn \_\hook_initialize_all:
1466 <latexrelease> {
1467 <latexrelease> \cs_gset_eq:NN \_\hook_update_hook_code:n
1468 <latexrelease> \_\hook_initialize_hook_code:n
1469 <latexrelease> \_\hook_debug:n { \prop_gc_clear:N \g_\hook_used_prop }
1470 <latexrelease> \seq_map_inline:Nn \g_\hook_all_seq
1471 <latexrelease> { \_\hook_update_hook_code:n {##1} }
1472 <latexrelease> \_\hook_debug:n
1473 <latexrelease> {
1474 <latexrelease> \iow_term:x{^^JAll~ initialized~ (non-empty)~ hooks:}
1475 <latexrelease> \prop_map_inline:Nn \g_\hook_used_prop
1476 <latexrelease> {
1477 <latexrelease> \iow_term:x
1478 <latexrelease> { ^^J ~ ##1 ~ -> ~
1479 <latexrelease> \cs_replacement_spec:c { \_\hook-##1 } ~ }
1480 <latexrelease> }
1481 <latexrelease> }
1482 <latexrelease> \cs_gset_eq:NN \hook_use:n \_\hook_use_initialized:n
1483 <latexrelease> \cs_gset_eq:NN \_\hook_preamble_hook:n \use_none:n
1484 <latexrelease> }
1485 <@@=
1486 <latexrelease>\cs_gset_eq:NN \@expl@@@initialize@all@@
1487 <latexrelease> \_\hook_initialize_all:
1488 <@@=hook>
1489 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\hook\_initialize\_all:.)

\\_\hook\_initialize\_hook\_code:n Initializing or reinitializing the fast execution hook code. In the preamble this is selectively done in case a hook gets used and at \begin{document} this is done for all hooks and afterwards only if the hook code changes.

```

1490 <latexrelease>\IncludeInRelease{2023/06/01}{\_\hook_initialize_hook_code:n}
1491 <latexrelease> {Hooks-with-args}
1492 \cs_new_protected:Npn \_\hook_initialize_hook_code:n #1
1493 {
1494 \_\hook_debug:n
1495 { \iow_term:x { ^^J[lthooks]~ Update-code-for-hook~'##1' \on@line :^^J } }

```

This does the sorting and the updates. First thing we do is to check if a legacy hook macro exists and if so we add it to the hook under the label `legacy`. This might make the hook non-empty so we have to do this before the then following test.

```

1496 \_\hook_include_legacy_code_chunk:n {##1}

```

If there aren't any code chunks for the current hook, there is no point in even starting the sorting routine so we make a quick test for that and in that case just update \\_\hook\_⟨hook⟩ to hold the top-level and next code chunks. If there are code chunks we call \\_\hook\_initialize\_single:NNn and pass to it ready made csnames as they are

needed several times inside. This way we save a bit on processing time if we do that up front.

```

1497 \__hook_if_usable:nT {#1}
1498 {
1499   \prop_if_empty:cTF { g__hook_#1_code_prop }
1500   {
1501     \__hook_code_gset:ne {#1}
1502     {

```

The hook may take arguments, so we add a run of braced parameters after the `_next` and `_toplevel` macros, so that the arguments passed to the hook are forwarded to them.

```

1503       \exp_not:c { __hook_toplevel~#1 }
1504       \__hook_braced_parameter:n {#1}
1505       \exp_not:c { __hook_next~#1 }
1506       \__hook_braced_parameter:n {#1}
1507     }
1508   }
1509   {

```

By default the algorithm sorts the code chunks and then saves the result in a token list for fast execution; this is done by adding the code chunks one after another, using `\tl_gput_right:NV`. When we sort code for a reversed hook, all we have to do is to add the code chunks in the opposite order into the token list. So all we have to do in preparation is to change two definitions that are used later on.

```

1510 \__hook_if_reversed:nTF {#1}
1511 { \cs_set_eq:NN \__hook_tl_gput:Nn \__hook_tl_gput_left:Nn
1512   \cs_set_eq:NN \__hook_clist_gput:NV \clist_gput_left:NV }
1513 { \cs_set_eq:NN \__hook_tl_gput:Nn \__hook_tl_gput_right:Nn
1514   \cs_set_eq:NN \__hook_clist_gput:NV \clist_gput_right:NV }

```

When sorting, some relations (namely voids) need to act destructively on the code property lists to remove code that shouldn't appear in the sorted hook token list, so we make a copy of the code property list that we can safely work on without changing the main one.

```

1515 \prop_set_eq:Nc \l__hook_work_prop { g__hook_#1_code_prop }
1516 \__hook_initialize_single:ccn
1517 { __hook~#1 } { g__hook_#1_labels_clist } {#1}

```

For debug display we want to keep track of those hooks that actually got code added to them, so we record that in `plist`. We use a `plist` to ensure that we record each hook name only once, i.e., we are only interested in storing the keys and the value is arbitrary.

```

1518 \__hook_debug:n
1519 { \exp_args:NNx \prop_gput:Nnn \g__hook_used_prop {#1} { } }
1520 }
1521 }
1522 }
1523 <latexrelease>\EndIncludeInRelease
1524 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_initialize_hook_code:n}
1525 <latexrelease>{Hooks-with-args}
1526 <latexrelease>\cs_gset_protected:Npn \__hook_initialize_hook_code:n #1
1527 <latexrelease>{
1528   \__hook_debug:n
1529   { \iow_term:x { ^^J Update-code-for-hook~'~#1'
1530     \on@line :^^J } }

```

```

1531 <latexrelease> \_hook_include_legacy_code_chunk:n {#1}
1532 <latexrelease> \_hook_if_usable:nT {#1}
1533 <latexrelease> {
1534 <latexrelease> \prop_if_empty:cTF { g__hook_#1_code_prop }
1535 <latexrelease> {
1536 <latexrelease> \_hook_tl_gset:co { __hook~#1 }
1537 <latexrelease> {
1538 <latexrelease> \cs:w __hook_toplevel~#1 \exp_after:wN \cs_end:
1539 <latexrelease> \cs:w __hook_next~#1 \cs_end:
1540 <latexrelease> }
1541 <latexrelease> }
1542 <latexrelease> {
1543 <latexrelease> \_hook_if_reversed:nTF {#1}
1544 <latexrelease> { \cs_set_eq:NN \_hook_tl_gput:Nn
1545 <latexrelease> \_hook_tl_gput_left:Nn
1546 <latexrelease> \cs_set_eq:NN \_hook_clist_gput:NV
1547 <latexrelease> \clist_gput_left:NV }
1548 <latexrelease> { \cs_set_eq:NN \_hook_tl_gput:Nn
1549 <latexrelease> \_hook_tl_gput_right:Nn
1550 <latexrelease> \cs_set_eq:NN \_hook_clist_gput:NV
1551 <latexrelease> \clist_gput_right:NV }
1552 <latexrelease> \prop_set_eq:Nc \l__hook_work_prop
1553 <latexrelease> { g__hook_#1_code_prop }
1554 <latexrelease> \_hook_initialize_single:ccn
1555 <latexrelease> { __hook~#1 } { g__hook_#1_labels_clist } {#1}
1556 <latexrelease> \_hook_debug:n
1557 <latexrelease> { \exp_args:NNx \prop_gput:Nnn \g__hook_used_prop
1558 <latexrelease> {#1} { } }
1559 <latexrelease> }
1560 <latexrelease> }
1561 <latexrelease> }
1562 <latexrelease> \EndIncludeInRelease

```

(End of definition for \\_hook\_initialize\_hook\_code:n.)

\\_hook\_tl\_csname:n It is faster to pass a single token and expand it when necessary than to pass a bunch of  
\\_hook\_seq\_csname:n character tokens around.

*FMi: note to myself: verify*

```

1563 \cs_new:Npn \_hook_tl_csname:n #1 { l__hook_label_#1_tl }
1564 \cs_new:Npn \_hook_seq_csname:n #1 { l__hook_label_#1_seq }

```

(End of definition for \\_hook\_tl\_csname:n and \\_hook\_seq\_csname:n.)

\l\_\_hook\_labels\_seq For the sorting I am basically implementing Knuth's algorithm for topological sorting as  
given in TAOCP volume 1 pages 263–266. For this algorithm we need a number of local  
variables:

```

\l__hook_front_tl
\l__hook_rear_tl
\l__hook_label_0_tl

```

- List of labels used in the current hook to label code chunks:

```

1565 \seq_new:N \l__hook_labels_seq

```

- Number of labels used in the current hook. In Knuth's algorithm this is called  $N$ :

```

1566 \int_new:N \l__hook_labels_int

```

- The sorted code list to be build is managed using two pointers one to the front of the queue and one to the rear. We model this using token list pointers. Knuth calls them  $F$  and  $R$ :

```
1567 \tl_new:N \l__hook_front_tl
1568 \tl_new:N \l__hook_rear_tl
```

- The data for the start of the queue is kept in this token list, it corresponds to what Don calls `QLINK[0]` but since we aren't manipulating individual words in memory it is slightly differently done:

```
1569 \tl_new:c { \__hook_tl_csname:n { 0 } }
```

(End of definition for `\l__hook_labels_seq` and others.)

`\__hook_initialize_single:NNn` implements the sorting of the code chunks for a hook and saves the result in the token list for fast execution (#4). The arguments are `<hook-code-plist>`, `<hook-code-tl>`, `<hook-top-level-code-tl>`, `<hook-next-code-tl>`, `<hook-ordered-labels-clist>` and `<hook-name>` (the latter is only used for debugging—the `<hook-rule-plist>` is accessed using the `<hook-name>`).

The additional complexity compared to Don's algorithm is that we do not use simple positive integers but have arbitrary alphanumeric labels. As usual Don's data structures are chosen in a way that one can omit a lot of tests and I have mimicked that as far as possible. The result is a restriction I do not test for at the moment: a label can't be equal to the number 0!

*FMi: Needs checking for, just in case ... maybe*

```
1570 <latexrelease> \IncludeInRelease{2023/06/01}{\__hook_initialize_single:NNn}
1571 <latexrelease> {Hooks-with-args}
1572 \cs_new_protected:Npn \__hook_initialize_single:NNn #1#2#3
1573 {
```

Step T1: Initialize the data structure ...

```
1574 \seq_clear:N \l__hook_labels_seq
1575 \int_zero:N \l__hook_labels_int
```

Store the name of the hook:

```
1576 \tl_set:Nn \l__hook_cur_hook_tl {#3}
```

We loop over the property list holding the code and record all the labels listed there. Only the rules for those labels are of interest to us. While we are at it we count them (which gives us the  $N$  in Knuth's algorithm). The prefix `label_` is added to the variables to ensure that labels named `front`, `rear`, `labels`, or `return` don't interact with our code.

```
1577 \prop_map_inline:Nn \l__hook_work_prop
1578 {
1579     \int_incr:N \l__hook_labels_int
1580     \seq_put_right:Nn \l__hook_labels_seq {##1}
1581     \__hook_tl_set:cn { \__hook_tl_csname:n {##1} } { 0 }
1582     \seq_clear_new:c { \__hook_seq_csname:n {##1} }
1583 }
```

Steps T2 and T3: Here we sort the relevant rules into the data structure...

This loop constitutes a square matrix of the labels in `\l__hook_work_prop` in the vertical and the horizontal directions. However, since the rule  $l_A\langle rel \rangle l_B$  is the same as  $l_B\langle rel \rangle^{-1}l_A$  we can cut the loop short at the diagonal of the matrix (*i.e.*, when both labels are equal), saving a good amount of time. The way the rules were set up (see the implementation of `\__hook_rule_before_gset:nnn` above) ensures that we have no rule in the ignored side of the matrix, and all rules are seen. The rules are applied in `\__hook_apply_label_pair:nnn`, which takes the properly-ordered pair of labels as argument.

```

1584 \prop_map_inline:Nn \l__hook_work_prop
1585 {
1586   \prop_map_inline:Nn \l__hook_work_prop
1587   {
1588     \__hook_if_label_case:nnnnn {##1} {####1}
1589     { \prop_map_break: }
1590     { \__hook_apply_label_pair:nnn {##1} {####1} }
1591     { \__hook_apply_label_pair:nnn {####1} {##1} }
1592     {#3}
1593   }
1594 }

```

Now take a breath, and look at the data structures that have been set up:

```

1595 \__hook_debug:n { \__hook_debug_label_data:N \l__hook_work_prop }

```

Step T4:

```

1596 \tl_set:Nn \l__hook_rear_tl { 0 }
1597 \tl_set:cn { \__hook_tl_csname:n { 0 } } { 0 }
1598 \seq_map_inline:Nn \l__hook_labels_seq
1599 {
1600   \int_compare:nNnT { \cs:w \__hook_tl_csname:n {##1} \cs_end: } = 0
1601   {
1602     \tl_set:cn { \__hook_tl_csname:n { \l__hook_rear_tl } } {##1}
1603     \tl_set:Nn \l__hook_rear_tl {##1}
1604   }
1605 }
1606 \tl_set_eq:Nc \l__hook_front_tl { \__hook_tl_csname:n { 0 } }
1607 \__hook_tl_gclear:N #1
1608 \clist_gclear:N #2

```

The whole loop gets combined in steps T5–T7:

```

1609 \bool_while_do:nn { ! \str_if_eq_p:Vn \l__hook_front_tl { 0 } }
1610 {

```

This part is step T5:

```

1611 \int_decr:N \l__hook_labels_int
1612 \prop_get:NVN \l__hook_work_prop \l__hook_front_tl \l__hook_return_tl
1613 \exp_args:NNV \__hook_tl_gput:Nn #1 \l__hook_return_tl

1614 \__hook_clist_gput:NV #2 \l__hook_front_tl
1615 \__hook_debug:n{ \iow_term:x{[lthooks]~ Handled~ code~ for~ \l__hook_front_tl} }

```

This is step T6, except that we don't use a pointer  $P$  to move through the successors, but instead use `##1` of the mapping function.

```

1616 \seq_map_inline:cn { \__hook_seq_csname:n { \l__hook_front_tl } }

```

```

1617 {
1618   \tl_set:cx { \__hook_tl_csname:n {##1} }
1619   { \int_eval:n
1620     { \cs:w \__hook_tl_csname:n {##1} \cs_end: - 1 }
1621   }
1622   \int_compare:nNnT
1623     { \cs:w \__hook_tl_csname:n {##1} \cs_end: } = 0
1624   {
1625     \tl_set:cn
1626       { \__hook_tl_csname:n { \l__hook_rear_tl } } {##1}
1627     \tl_set:Nn \l__hook_rear_tl {##1}
1628   }
1629 }

```

and here is step T7:

```

1630   \tl_set_eq:Nc \l__hook_front_tl
1631   { \__hook_tl_csname:n { \l__hook_front_tl } }

```

This is step T8: If we haven't moved the code for all labels (i.e., if `\l__hook_labels_int` is still greater than zero) we have a loop and our partial order can't be flattened out.

```

1632 }
1633 \int_compare:nNnF \l__hook_labels_int = 0
1634 {
1635   \iow_term:x{=====}
1636   \iow_term:x{Error:~ label~ rules~ are~ incompatible:}

```

This is not really the information one needs in the error case but it will do for now  
...

*FMi: improve output on a rainy day*

```

1637   \__hook_debug_label_data:N \l__hook_work_prop
1638   \iow_term:x{=====}
1639 }

```

After we have added all hook code to #1, we finish it off by adding extra code for the **top-level** (#2) and for one time execution (#3). These should normally be empty. The **top-level** code is added with `\__hook_tl_gput:Nn` as that might change for a reversed hook (then **top-level** is the very first code chunk added). The **next** code is always added last (to the right). The hook may take arguments, so we add a run of braced parameters after the `_next` and `_toplevel` macros, so that the arguments passed to the hook are forwarded to them.

```

1640   \exp_args:NNe \__hook_tl_gput:Nn #1
1641   { \exp_not:c { \__hook_toplevel~#3 } \__hook_braced_parameter:n {#3} }
1642   \__hook_tl_gput_right:Ne #1
1643   { \exp_not:c { \__hook_next~#3 } \__hook_braced_parameter:n {#3} }
1644   \use:e
1645   {
1646     \cs_gset:cpn { \__hook~#3 } \use:c { c__hook_#3_parameter_tl }
1647     { \exp_not:V #1 }
1648   }
1649 }

1650 \cs_generate_variant:Nn \__hook_initialize_single:NNn { cc }
1651 \<latexrelease>\EndIncludeInRelease

```

```

1652 <latexrelease> \IncludeInRelease{2020/10/01}{\__hook_initialize_single:Nn}
1653 <latexrelease> {Hooks~with~args}
1654 <latexrelease> \cs_new_protected:Npn \__hook_initialize_single:Nn #1#2#3
1655 <latexrelease> {
1656 <latexrelease> \seq_clear:N \l__hook_labels_seq
1657 <latexrelease> \int_zero:N \l__hook_labels_int
1658 <latexrelease> \tl_set:Nn \l__hook_cur_hook_tl {#3}
1659 <latexrelease> \prop_map_inline:Nn \l__hook_work_prop
1660 <latexrelease> {
1661 <latexrelease> \int_incr:N \l__hook_labels_int
1662 <latexrelease> \seq_put_right:Nn \l__hook_labels_seq {##1}
1663 <latexrelease> \__hook_tl_set:cn { \__hook_tl_csname:n {##1} } { 0 }
1664 <latexrelease> \seq_clear_new:c { \__hook_seq_csname:n {##1} }
1665 <latexrelease> }
1666 <latexrelease> \prop_map_inline:Nn \l__hook_work_prop
1667 <latexrelease> {
1668 <latexrelease> \prop_map_inline:Nn \l__hook_work_prop
1669 <latexrelease> {
1670 <latexrelease> \__hook_if_label_case:nnnnn {##1} {####1}
1671 <latexrelease> { \prop_map_break: }
1672 <latexrelease> { \__hook_apply_label_pair:nnn {##1} {####1} }
1673 <latexrelease> { \__hook_apply_label_pair:nnn {####1} {##1} }
1674 <latexrelease> {#3}
1675 <latexrelease> }
1676 <latexrelease> }
1677 <latexrelease> \__hook_debug:n
1678 <latexrelease> { \__hook_debug_label_data:N \l__hook_work_prop }
1679 <latexrelease> \tl_set:Nn \l__hook_rear_tl { 0 }
1680 <latexrelease> \tl_set:cn { \__hook_tl_csname:n { 0 } } { 0 }
1681 <latexrelease> \seq_map_inline:Nn \l__hook_labels_seq
1682 <latexrelease> {
1683 <latexrelease> \int_compare:nNnT
1684 <latexrelease> { \cs:w \__hook_tl_csname:n {##1} \cs_end: } = 0
1685 <latexrelease> {
1686 <latexrelease> \tl_set:cn { \__hook_tl_csname:n
1687 <latexrelease> { \l__hook_rear_tl } } {##1}
1688 <latexrelease> \tl_set:Nn \l__hook_rear_tl {##1}
1689 <latexrelease> }
1690 <latexrelease> }
1691 <latexrelease> \tl_set_eq:Nc \l__hook_front_tl { \__hook_tl_csname:n { 0 } }
1692 <latexrelease> \__hook_tl_gclear:N #1
1693 <latexrelease> \clist_gclear:N #2
1694 <latexrelease> \bool_while_do:nn
1695 <latexrelease> { ! \str_if_eq_p:Vn \l__hook_front_tl { 0 } }
1696 <latexrelease> {
1697 <latexrelease> \int_decr:N \l__hook_labels_int
1698 <latexrelease> \prop_get:NVN \l__hook_work_prop
1699 <latexrelease> \l__hook_front_tl \l__hook_return_tl
1700 <latexrelease> \exp_args:NNV \__hook_tl_gput:Nn #1 \l__hook_return_tl
1701 <latexrelease> \__hook_clist_gput:NV #2 \l__hook_front_tl
1702 <latexrelease> \__hook_debug:n{ \iow_term:x
1703 <latexrelease> {Handled~ code~ for~ \l__hook_front_tl} }
1704 <latexrelease> \seq_map_inline:cn
1705 <latexrelease> { \__hook_seq_csname:n { \l__hook_front_tl } }

```

```

1706 <latexrelease>      {
1707 <latexrelease>      \tl_set:cx { \__hook_tl_csname:n {##1} }
1708 <latexrelease>      { \int_eval:n
1709 <latexrelease>      { \cs:w \__hook_tl_csname:n {##1} \cs_end: - 1 }
1710 <latexrelease>      }
1711 <latexrelease>      \int_compare:nNnT
1712 <latexrelease>      { \cs:w \__hook_tl_csname:n {##1} \cs_end: } = 0
1713 <latexrelease>      {
1714 <latexrelease>      \tl_set:cn { \__hook_tl_csname:n
1715 <latexrelease>      { \l__hook_rear_tl } } {##1}
1716 <latexrelease>      \tl_set:Nn \l__hook_rear_tl {##1}
1717 <latexrelease>      }
1718 <latexrelease>      }
1719 <latexrelease>      \tl_set_eq:Nc \l__hook_front_tl
1720 <latexrelease>      { \__hook_tl_csname:n { \l__hook_front_tl } }
1721 <latexrelease>      }
1722 <latexrelease>      \int_compare:nNnF \l__hook_labels_int = 0
1723 <latexrelease>      {
1724 <latexrelease>      \iow_term:x{=====}
1725 <latexrelease>      \iow_term:x{Error:~ label~ rules~ are~ incompatible:}
1726 <latexrelease>      \__hook_debug_label_data:N \l__hook_work_prop
1727 <latexrelease>      \iow_term:x{=====}
1728 <latexrelease>      }
1729 <latexrelease>      \exp_args:NNo \__hook_tl_gput:Nn #1
1730 <latexrelease>      { \cs:w \__hook_toplevel~#3 \cs_end: }
1731 <latexrelease>      \__hook_tl_gput_right:No #1 { \cs:w \__hook_next~#3 \cs_end: }
1732 <latexrelease>      }
1733 <latexrelease>      \cs_generate_variant:Nn \__hook_tl_gput_right:Nn { No }
1734 <latexrelease>      \EndIncludeInRelease

```

(End of definition for \\_\_hook\_initialize\_single:Nn.)

\\_\_hook\_tl\_gput:Nn These append either on the right (normal hook) or on the left (reversed hook). This is  
\\_\_hook\_clist\_gput:NV setup up in \\_\_hook\_initialize\_hook\_code:n, elsewhere their behavior is undefined.

```

1735 \cs_new:Npn \__hook_tl_gput:Nn { \ERROR }
1736 \cs_new:Npn \__hook_clist_gput:NV { \ERROR }

```

(End of definition for \\_\_hook\_tl\_gput:Nn and \\_\_hook\_clist\_gput:NV.)

\\_\_hook\_apply\_label\_pair:nnn This is the payload of steps T2 and T3 executed in the loop described above. This macro  
\\_\_hook\_label\_if\_exist\_apply:nnnF assumes #1 and #2 are ordered, which means that any rule pertaining the pair #1 and #2  
is \g\_\_hook\_<hook>\_rule\_#1|#2\_tl, and not \g\_\_hook\_<hook>\_rule\_#2|#1\_tl. This  
also saves a great deal of time since we only need to check the order of the labels once.

The arguments here are <label1>, <label2>, <hook>, and <hook-code-plist>. We  
are about to apply the next rule and enter it into the data structure. \\_\_hook\_apply\_-  
label\_pair:nnn will just call \\_\_hook\_label\_if\_exist\_apply:nnnF for the <hook>,  
and if no rule is found, also try the <hook> name ?? denoting a default hook rule.

\\_\_hook\_label\_if\_exist\_apply:nnnF will check if the rule exists for the given  
hook, and if so call \\_\_hook\_apply\_rule:nnn.

```

1737 \cs_new_protected:Npn \__hook_apply_label_pair:nnn #1#2#3
1738 {

```

Extra complication: as we use default rules and local hook specific rules we first have to check if there is a local rule and if that exist use it. Otherwise check if there is a default rule and use that.

```
1739 \__hook_label_if_exist_apply:nnnF {#1} {#2} {#3}
1740 {
```

If there is no hook-specific rule we check for a default one and use that if it exists.

```
1741 \__hook_label_if_exist_apply:nnnF {#1} {#2} { ?? } { }
1742 }
1743 }
```

```
1744 \cs_new_protected:Npn \__hook_label_if_exist_apply:nnnF #1#2#3
1745 {
1746 \if_cs_exist:w g__hook_ #3 _rule_ #1 | #2 _tl \cs_end:
```

What to do precisely depends on the type of rule we have encountered. If it is a `before` rule it will be handled by the algorithm but other types need to be managed differently. All this is done in `\__hook_apply_rule:nnnN`.

```
1747 \__hook_apply_rule:nnn {#1} {#2} {#3}
1748 \exp_after:wN \use_none:n
1749 \else:
1750 \use:nn
1751 \fi:
1752 }
```

(End of definition for `\__hook_apply_label_pair:nnn` and `\__hook_label_if_exist_apply:nnnF`.)

`\__hook_apply_rule:nnn` This is the code executed in steps T2 and T3 while looping through the matrix This is part of step T3. We are about to apply the next rule and enter it into the data structure. The arguments are  $\langle label1 \rangle$ ,  $\langle label2 \rangle$ ,  $\langle hook-name \rangle$ , and  $\langle hook-code-plist \rangle$ .

```
1753 \cs_new_protected:Npn \__hook_apply_rule:nnn #1#2#3
1754 {
1755 \cs:w __hook_apply_
1756 \cs:w g__hook_#3_reversed_tl \cs_end: rule_
1757 \cs:w g__hook_ #3 _rule_ #1 | #2 _tl \cs_end: :nnn \cs_end:
1758 {#1} {#2} {#3}
1759 }
```

(End of definition for `\__hook_apply_rule:nnn`.)

`\__hook_apply_rule_<:nnn` The most common cases are `<` and `>` so we handle that first. They are relations `<` and `>` in TAOCP, and they dictate sorting.

```
\__hook_apply_rule_>:nnn
1760 \cs_new_protected:cpn { __hook_apply_rule_<:nnn } #1#2#3
1761 {
1762 \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
1763 \tl_set:cx { \__hook_tl_csname:n {#2} }
1764 { \int_eval:n{ \cs:w \__hook_tl_csname:n {#2} \cs_end: + 1 } }
1765 \seq_put_right:cn{ \__hook_seq_csname:n {#1} }{#2}
1766 }
1767 \cs_new_protected:cpn { __hook_apply_rule_>:nnn } #1#2#3
1768 {
1769 \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
1770 \tl_set:cx { \__hook_tl_csname:n {#1} }
1771 { \int_eval:n{ \cs:w \__hook_tl_csname:n {#1} \cs_end: + 1 } }
1772 \seq_put_right:cn{ \__hook_seq_csname:n {#2} }{#1}
1773 }
```

(End of definition for `\__hook_apply_rule_<:nnn` and `\__hook_apply_rule_>:nnn`.)

`\__hook_apply_rule_xE:nnn` These relations make two labels incompatible within a hook. `xE` makes raises an error if the labels are found in the same hook, and `xW` makes it a warning.

```

\__hook_apply_rule_xW:nnn
1774 \cs_new_protected:cpn { __hook_apply_rule_xE:nnn } #1#2#3
1775 {
1776   \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
1777   \msg_error:nnnnnn { hooks } { labels-incompatible }
1778   {#1} {#2} {#3} { 1 }
1779   \use:c { __hook_apply_rule_>:nnn } {#1} {#2} {#3}
1780   \use:c { __hook_apply_rule_<:nnn } {#1} {#2} {#3}
1781 }
1782 \cs_new_protected:cpn { __hook_apply_rule_xW:nnn } #1#2#3
1783 {
1784   \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
1785   \msg_warning:nnnnnn { hooks } { labels-incompatible }
1786   {#1} {#2} {#3} { 0 }
1787 }

```

(End of definition for `\__hook_apply_rule_xE:nnn` and `\__hook_apply_rule_xW:nnn`.)

`\__hook_apply_rule_>:nnn` If we see `->` we have to drop code for label `#3` and carry on. We could do a little better and drop everything for that label since it doesn't matter where we put such empty code. However that would complicate the algorithm a lot with little gain.<sup>12</sup> So we still unnecessarily try to sort it in and depending on the rules that might result in a loop that is otherwise resolved. If that turns out to be a real issue, we can improve the code.

`\__hook_apply_rule_<:nnn`

Here the code is removed from `\l__hook_cur_hook_tl` rather than `#3` because the latter may be `??`, and the default hook doesn't store any code. Removing it instead from `\l__hook_cur_hook_tl` makes the default rules `->` and `<-` work properly.

```

1788 \cs_new_protected:cpn { __hook_apply_rule_>:nnn } #1#2#3
1789 {
1790   \__hook_debug:n
1791   {
1792     \__hook_msg_pair_found:nnn {#1} {#2} {#3}
1793     \iow_term:x{--->~ Drop~ '#2'~ code~ from~
1794       \iow_char:N \ g__hook_ \l__hook_cur_hook_tl _code_prop ~
1795       because~ of~ '#1' }
1796   }
1797   \prop_put:Nnn \l__hook_work_prop {#2} { }
1798 }
1799 \cs_new_protected:cpn { __hook_apply_rule_<:nnn } #1#2#3
1800 {
1801   \__hook_debug:n
1802   {
1803     \__hook_msg_pair_found:nnn {#1} {#2} {#3}
1804     \iow_term:x{--->~ Drop~ '#1'~ code~ from~
1805       \iow_char:N \ g__hook_ \l__hook_cur_hook_tl _code_prop ~
1806       because~ of~ '#2' }
1807   }
1808   \prop_put:Nnn \l__hook_work_prop {#1} { }
1809 }

```

<sup>12</sup>This also has the advantage that the result of the sorting doesn't change, as it might otherwise do (for unrelated chunks) if we aren't careful.

(End of definition for `\__hook_apply_rule->:nnn` and `\__hook_apply_rule<-:nnn`.)

```

\__hook_apply_rule<:nnn   Reversed rules.
\__hook_apply_rule>:nnn
\__hook_apply_rule<-:nnn 1810 \cs_new_eq:cc { __hook_apply_rule<:nnn } { __hook_apply_rule>:nnn }
\__hook_apply_rule->:nnn 1811 \cs_new_eq:cc { __hook_apply_rule>:nnn } { __hook_apply_rule<:nnn }
\__hook_apply_rule_xW:nnn 1812 \cs_new_eq:cc { __hook_apply_rule<-:nnn } { __hook_apply_rule->:nnn }
\__hook_apply_rule_xE:nnn 1813 \cs_new_eq:cc { __hook_apply_rule->:nnn } { __hook_apply_rule_xE:nnn }
1814 \cs_new_eq:cc { __hook_apply_rule_xE:nnn } { __hook_apply_rule_xW:nnn }
1815 \cs_new_eq:cc { __hook_apply_rule_xW:nnn } { __hook_apply_rule_xE:nnn }

```

(End of definition for `\__hook_apply_rule<:nnn` and others.)

```

\__hook_msg_pair_found:nnn A macro to avoid moving this many tokens around.
1816 \cs_new_protected:Npn \__hook_msg_pair_found:nnn #1#2#3
1817 {
1818   \iow_term:x{~ \str_if_eq:nnTF {#3} {??} {default} {~normal} ~
1819     rule~ \__hook_label_pair:nn {#1} {#2}:~
1820     \use:c { g__hook_#3_rule_ \__hook_label_pair:nn {#1} {#2} _tl } ~
1821     found}
1822 }

```

(End of definition for `\__hook_msg_pair_found:nnn`.)

```

\__hook_debug_label_data:N
1823 \cs_new_protected:Npn \__hook_debug_label_data:N #1 {
1824   \iow_term:x{Code~ labels~ for~ sorting:}
1825   \iow_term:x{~ \seq_use:Nnnn\l__hook_labels_seq {~and~}{,~}{~and~} }
1826   \iow_term:x{^^J Data~ structure~ for~ label~ rules:}
1827   \prop_map_inline:Nn #1
1828   {
1829     \iow_term:x{~ ##1~ =~ \tl_use:c{ \__hook_tl_csname:n {##1} }~ ->~
1830       \seq_use:cnnn{ \__hook_seq_csname:n {##1} }{~>~}{~>~}{~>~}
1831   }
1832 }
1833 \iow_term:x{}
1834 }

```

(End of definition for `\__hook_debug_label_data:N`.)

**\hook\_show:n** This writes out information about the hook given in its argument onto the `.log` file and the terminal, if `\show_hook:n` is used. Internally both share the same structure, except that at the end, `\hook_show:n` triggers T<sub>E</sub>X's prompt.

**\hook\_log:n**

```

\__hook_log_line:x
\__hook_log_line_indent:x
\__hook_log:nN
1835 \cs_new_protected:Npn \hook_log:n #1
1836 {
1837   \cs_set_eq:NN \__hook_log_cmd:x \iow_log:x
1838   \__hook_normalize_hook_args:Nn \__hook_log:nN {#1} \tl_log:x
1839 }
1840 \cs_if_exist:NTF \iow_show:e
1841 {
1842   \cs_new_protected:Npn \hook_show:n #1
1843   {
1844     \cs_set_eq:NN \__hook_log_cmd:x \iow_show:e
1845     \__hook_normalize_hook_args:Nn \__hook_log:nN {#1} \tl_show:x
1846   }

```

```

1847 }
1848 {
1849   \cs_new_protected:Npn \hook_show:n #1
1850   {
1851     \cs_set_eq:NN \__hook_log_cmd:x \iow_term:x
1852     \__hook_normalize_hook_args:Nn \__hook_log:nN {#1} \tl_show:x
1853   }
1854 }
1855 \cs_new_protected:Npn \__hook_log_line:x #1
1856 { \__hook_log_cmd:x { >~#1 } }
1857 \cs_new_protected:Npn \__hook_log_line_indent:x #1
1858 { \__hook_log_cmd:x { >~\@spaces #1 } }
1859 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_log:nN}
1860 <latexrelease>{Hooks~with~args}
1861 \cs_new_protected:Npn \__hook_log:nN #1 #2
1862 {
1863   \__hook_if_deprecated_generic:nT {#1}
1864   {
1865     \__hook_deprecated_generic_warn:n {#1}
1866     \__hook_do_deprecated_generic:Nn \__hook_log:nN {#1} #2
1867     \exp_after:wN \use_none:nnnnnnnnn \use_none:nnnnn
1868   }
1869   \__hook_preamble_hook:n {#1}
1870   \__hook_log_cmd:x
1871   {
1872     ^^J ->~The~
1873     \__hook_if_generic:nT {#1} { generic~ }
1874     hook~'~#1'
1875     \__hook_if_disabled:nF {#1}
1876     {
1877       \exp_args:Nne \__hook_print_args:nn {#1}
1878       {
1879         \int_eval:n
1880         { \str_count:e { \__hook_parameter:n {#1} } / 3 }
1881       }
1882     }
1883   }
1884 }
1885 \__hook_if_usable:nF {#1}
1886 { \__hook_log_line:x { The~hook~is~not~declared. } }
1887 \__hook_if_disabled:nT {#1}
1888 { \__hook_log_line:x { The~hook~is~disabled. } }
1889 \hook_if_empty:nTF {#1}
1890 { #2 { The~hook~is~empty } }
1891 {
1892   \__hook_log_line:x { Code~chunks: }
1893   \bool_lazy_or:nnTF
1894   { ! \prop_if_exist_p:c { g__hook_#1_code_prop } }
1895   { \prop_if_empty_p:c { g__hook_#1_code_prop } }
1896   { \__hook_log_line_indent:x { --- } }
1897   {
1898     \prop_map_inline:cn { g__hook_#1_code_prop }
1899     {

```

```

1900         \exp_after:wN \cs_set:Npn \exp_after:wN \__hook_tmp:w
1901         \c__hook_nine_parameters_tl {##2}
1902         \__hook_log_line_indent:x
1903         { ##1~-->~\cs_replacement_spec:N \__hook_tmp:w }
1904     }
1905 }

```

If there is code in the top-level token list, print it:

```

1906 \__hook_log_line:x
1907 {
1908     Document-level~(top-level)~code
1909     \__hook_if_usable:nT {#1}
1910     { ~(executed~\__hook_if_reversed:nTF {#1} {first} {last} ) } :
1911 }
1912 \__hook_log_line_indent:x
1913 {
1914     \__hook_cs_if_empty:cTF { __hook_toplevel~#1 }
1915     { --- }
1916     { -> ~ \cs_replacement_spec:c { __hook_toplevel~#1 } }
1917 }
1918 \__hook_log_line:x { Extra~code~for~next~invocation: }
1919 \__hook_log_line_indent:x
1920 {
1921     \__hook_cs_if_empty:cTF { __hook_next~#1 }
1922     { --- }

```

If the token list is not empty we want to display it but without the first tokens (the code to clear itself) so we call a helper command to get rid of them.

```

1923 {
1924     -> ~ \exp_last_unbraced:Nf \__hook_log_next_code:w
1925     { \cs_replacement_spec:c { __hook_next~#1 } }
1926 }
1927 }

```

Loop through the rules in a hook and for every rule found, print it. If no rule is there, print ---. The boolean \l\_\_hook\_tmpa\_bool here indicates if the hook has no rules.

```

1928 \__hook_log_line:x { Rules: }
1929 \bool_set_true:N \l__hook_tmpa_bool
1930 \__hook_list_rules:nm {#1}
1931 {
1932     \bool_set_false:N \l__hook_tmpa_bool
1933     \__hook_log_line_indent:x
1934     {
1935         ##2~ with~
1936         \str_if_eq:nnT {##3} {??} { default~ }
1937         relation~ ##1
1938     }
1939 }
1940 \bool_if:NT \l__hook_tmpa_bool
1941 { \__hook_log_line_indent:x { --- } }

```

When the hook is declared (that is, the sorting algorithm is applied to that hook) and not empty

```

1942 \bool_lazy_and:nnTF
1943 { \__hook_if_usable_p:n {#1} }
1944 { ! \hook_if_empty_p:n {#1} }
1945 {
1946   \__hook_log_line:x
1947   {
1948     Execution~order
1949     \bool_if:NTF \l__hook_tmpa_bool
1950     { \__hook_if_reversed:nT {#1} { ~(after~reversal) } }
1951     { ~(after~
1952       \__hook_if_reversed:nT {#1} { reversal~and~ }
1953       applying~rules)
1954     } :
1955   }
1956   #2 % \tl_show:n
1957   {
1958     \@spaces
1959     \clist_if_empty:ctF { g__hook_#1_labels_clist }
1960     { --- }
1961     { \clist_use:cn { g__hook_#1_labels_clist } { ,~ } }
1962   }
1963 }
1964 {
1965   \__hook_log_line:x { Execution~order: }
1966   #2
1967   {
1968     \@spaces Not~set~because~the~hook~ \__hook_if_usable:nTF {#1}
1969     { code~pool~is~empty }
1970     { is~\__hook_if_disabled:nTF {#1} {disabled} {undeclared} }
1971   }
1972 }
1973 }
1974 }
1975 \<latexrelease>\EndIncludeInRelease
1976 %
1977 \<latexrelease>\IncludeInRelease{2020/10/01}{\__hook_log:nN}
1978 \<latexrelease>{Hooks~with~args}
1979 \<latexrelease>\cs_new_protected:Npn \__hook_log:nN #1 #2
1980 \<latexrelease> {
1981 \<latexrelease>   \__hook_if_deprecated_generic:nT {#1}
1982 \<latexrelease>   {
1983 \<latexrelease>     \__hook_deprecated_generic_warn:n {#1}
1984 \<latexrelease>     \__hook_do_deprecated_generic:Nn \__hook_log:nN {#1} #2
1985 \<latexrelease>     \exp_after:wN \use_none:nnnnnnnnn \use_none:nnnnn
1986 \<latexrelease>   }
1987 \<latexrelease>   \__hook_preamble_hook:n {#1}
1988 \<latexrelease>   \__hook_log_cmd:x
1989 \<latexrelease>   { ^^J ->~The~ \__hook_if_generic:nT
1990 \<latexrelease>     {#1} { generic~ } hook~'#1': }
1991 \<latexrelease>   \__hook_if_usable:nF {#1}
1992 \<latexrelease>   { \__hook_log_line:x { The~hook~is~not~declared. } }
1993 \<latexrelease>   \__hook_if_disabled:nT {#1}
1994 \<latexrelease>   { \__hook_log_line:x { The~hook~is~disabled. } }
1995 \<latexrelease>   \hook_if_empty:nTF {#1}

```

```

1996 <latexrelease> { #2 { The~hook~is~empty } }
1997 <latexrelease> {
1998 <latexrelease>   \__hook_log_line:x { Code~chunks: }
1999 <latexrelease>   \prop_if_empty:cTF { g__hook_#1_code_prop }
2000 <latexrelease>     { \__hook_log_line_indent:x { --- } }
2001 <latexrelease>     {
2002 <latexrelease>       \prop_map_inline:cn { g__hook_#1_code_prop }
2003 <latexrelease>       { \__hook_log_line_indent:x
2004 <latexrelease>         { ##1~-->~\tl_to_str:n {##2} } }
2005 <latexrelease>     }
2006 <latexrelease>   \__hook_log_line:x
2007 <latexrelease>   {
2008 <latexrelease>     Document~level~(top~level)~code
2009 <latexrelease>     \__hook_if_usable:nT {#1}
2010 <latexrelease>       { ~(executed~
2011 <latexrelease>         \__hook_if_reversed:nTF {#1} {first} {last} ) } :
2012 <latexrelease>   }
2013 <latexrelease>   \__hook_log_line_indent:x
2014 <latexrelease>   {
2015 <latexrelease>     \tl_if_empty:cTF { __hook_toplevel~#1 }
2016 <latexrelease>     { --- }
2017 <latexrelease>     { -> ~ \exp_args:Nv \tl_to_str:n
2018 <latexrelease>       { __hook_toplevel~#1 } }
2019 <latexrelease>   }
2020 <latexrelease>   \__hook_log_line:x { Extra~code~for~next~invocation: }
2021 <latexrelease>   \__hook_log_line_indent:x
2022 <latexrelease>   {
2023 <latexrelease>     \tl_if_empty:cTF { __hook_next~#1 }
2024 <latexrelease>     { --- }
2025 <latexrelease>     { ->~ \exp_args:Nv \__hook_log_next_code:n
2026 <latexrelease>       { __hook_next~#1 } }
2027 <latexrelease>   }
2028 <latexrelease>   \__hook_log_line:x { Rules: }
2029 <latexrelease>   \bool_set_true:N \l__hook_tmpa_bool
2030 <latexrelease>   \__hook_list_rules:nn {#1}
2031 <latexrelease>   {
2032 <latexrelease>     \bool_set_false:N \l__hook_tmpa_bool
2033 <latexrelease>     \__hook_log_line_indent:x
2034 <latexrelease>     {
2035 <latexrelease>       ##2~ with~
2036 <latexrelease>       \str_if_eq:nnT {##3} {??} { default~ }
2037 <latexrelease>       relation~ ##1
2038 <latexrelease>     }
2039 <latexrelease>   }
2040 <latexrelease>   \bool_if:NT \l__hook_tmpa_bool
2041 <latexrelease>     { \__hook_log_line_indent:x { --- } }
2042 <latexrelease>   \bool_lazy_and:nnTF
2043 <latexrelease>     { \__hook_if_usable_p:n {#1} }
2044 <latexrelease>     { ! \hook_if_empty_p:n {#1} }
2045 <latexrelease>   {
2046 <latexrelease>     \__hook_log_line:x
2047 <latexrelease>     {
2048 <latexrelease>       Execution~order
2049 <latexrelease>       \bool_if:NTF \l__hook_tmpa_bool

```

```

2050 <latexrelease>          { \_hook_if_reversed:nT
2051 <latexrelease>          {#1}{ ~(after~reversal) } }
2052 <latexrelease>          { ~(after~
2053 <latexrelease>          \_hook_if_reversed:nT {#1} { reversal~and~
2054 <latexrelease>          applying~rules)
2055 <latexrelease>          } :
2056 <latexrelease>          }
2057 <latexrelease>          #2 % \tl_show:n
2058 <latexrelease>          {
2059 <latexrelease>          \@spaces
2060 <latexrelease>          \clist_if_empty:cTF { g__hook_#1_labels_clist }
2061 <latexrelease>          { --- }
2062 <latexrelease>          { \clist_use:cn
2063 <latexrelease>          { g__hook_#1_labels_clist } { ,~ } }
2064 <latexrelease>          }
2065 <latexrelease>          }
2066 <latexrelease>          {
2067 <latexrelease>          \_hook_log_line:x { Execution-order: }
2068 <latexrelease>          #2
2069 <latexrelease>          {
2070 <latexrelease>          \@spaces Not~set~because~the~hook~
2071 <latexrelease>          \_hook_if_usable:nTF {#1}
2072 <latexrelease>          { code~pool~is~empty }
2073 <latexrelease>          { is~\_hook_if_disabled:nTF
2074 <latexrelease>          {#1} {disabled} {undeclared} }
2075 <latexrelease>          }
2076 <latexrelease>          }
2077 <latexrelease>          }
2078 <latexrelease>          }
2079 <latexrelease> \EndIncludeInRelease

```

To display the code for next invocation only (i.e., from \AddToHookNext we have to remove the string \\_hook\_clear\_next:n{hook}), so the simplest is to use a macro delimited by a }<sub>1</sub>2.

```

2080 <latexrelease> \IncludeInRelease{2023/06/01}{\_hook_log_next_code:n}
2081 <latexrelease>          {Hooks~with~args}
\_hook_log_next_code:n
2082 \exp_last_unbraced:NNNno
2083 \cs_new:Npn \_hook_log_next_code:w #1 \c_right_brace_str { }
2084 <latexrelease> \EndIncludeInRelease
2085 <latexrelease> \IncludeInRelease{2020/10/01}{\_hook_log_next_code:n}
2086 <latexrelease>          {Hooks~with~args}
2087 <latexrelease> \cs_gset:Npn \_hook_log_next_code:n #1
2088 <latexrelease> { \exp_args:No \tl_to_str:n { \use_none:nn #1 } }
2089 <latexrelease> \EndIncludeInRelease

```

Pretty-prints the number of arguments of a hook.

```

2090 \cs_new:Npn \_hook_print_args:nn #1 #2
2091 {
2092   \int_compare:nNnT {#2} > { 0 }
2093   {
\_hook_print_args:n
2094     \_hook_if_declared:nT {#1} { \use_none:nnn }
2095     \_hook_if_cmd_hook:nT {#1}
2096     { \use_i:nnn { ~ (unknown ~ ) } }
2097     \use:n { ~ (#2 ~ ) }

```

```

2098     argument \int_compare:nNtT {#2} > { 1 } { s } )
2099   }
2100 }

```

(End of definition for `\hook_show:n` and others. These functions are documented on page 216.)

`\__hook_list_rules:nn` This macro takes a *<hook>* and an *<inline function>* and loops through each pair of *<labels>* in the *<hook>*, and if there is a relation between this pair of *<labels>*, the *<inline function>* is executed with `#1 = <relation>`, `#2 = <label1>|<label2>`, and `#3 = <hook>` (the latter may be the argument `#1` to `\__hook_list_rules:nn`, or `??` if it is a default rule).

```

2101 \cs_new_protected:Npn \__hook_list_rules:nn #1 #2
2102 {
2103   \prop_if_exist:cT { g__hook_#1_code_prop }
2104   {
2105     \cs_set_protected:Npn \__hook_tmp:w ##1 ##2 ##3 {#2}
2106     \prop_map_inline:cn { g__hook_#1_code_prop }
2107     {
2108       \prop_map_inline:cn { g__hook_#1_code_prop }
2109       {
2110         \__hook_if_label_case:nnnnn {##1} {####1}
2111         { \prop_map_break: }
2112         { \__hook_list_one_rule:nnn {##1} {####1} }
2113         { \__hook_list_one_rule:nnn {####1} {##1} }
2114         {#1}
2115       }
2116     }
2117   }
2118 }

```

These two are quite similar to `\__hook_apply_label_pair:nnn` and `\__hook_label_if_exist_apply:nnnF`, respectively, but rather than applying the rule, they pass it to the *<inline function>*.

```

2119 \cs_new_protected:Npn \__hook_list_one_rule:nnn #1#2#3
2120 {
2121   \__hook_list_if_rule_exists:nnnF {#1} {#2} {#3}
2122   { \__hook_list_if_rule_exists:nnnF {#1} {#2} { ?? } { } }
2123 }
2124 \cs_new_protected:Npn \__hook_list_if_rule_exists:nnnF #1#2#3
2125 {
2126   \if_cs_exist:w g__hook_ #3 _rule_ #1 | #2 _tl \cs_end:
2127   \exp_args:Nv \__hook_tmp:w
2128   { g__hook_ #3 _rule_ #1 | #2 _tl } { #1 | #2 } {#3}
2129   \exp_after:wN \use_none:nn
2130   \fi:
2131   \use:n
2132 }

```

(End of definition for `\__hook_list_rules:nn`, `\__hook_list_one_rule:nnn`, and `\__hook_list_if_rule_exists:nnnF`.)

`\__hook_debug_print_rules:n` A shorthand for debugging that prints similar to `\prop_show:N`.

```

2133 \cs_new_protected:Npn \__hook_debug_print_rules:n #1
2134 {

```

```

2135 \iow_term:n { The~hook~#1~contains~the~rules: }
2136 \cs_set_protected:Npn \__hook_tmp:w ##1
2137 {
2138   \__hook_list_rules:nn {#1}
2139   {
2140     \iow_term:x
2141     {
2142       > ##1 {####2} ##1 => ##1 {####1}
2143       \str_if_eq:nnT {####3} {??} { ~(default) }
2144     }
2145   }
2146 }
2147 \exp_args:No \__hook_tmp:w { \use:nn { ~ } { ~ } }
2148 }

```

(End of definition for \\_\_hook\_debug\_print\_rules:n.)

## 4.8 Specifying code for next invocation

`\hook_gput_next_code:nn`

```

2149 <latexrelease>\IncludeInRelease{2023/06/01}{\hook_gput_next_code:nn}
2150 <latexrelease> {Hooks-with-args}
2151 \cs_new_protected:Npn \hook_gput_next_code:nn #1 #2
2152 {
2153   \__hook_replacing_args_false:
2154   \__hook_normalize_hook_args:Nn \__hook_gput_next_code:nn {#1} {#2}
2155
2156   \__hook_debug:n{\iow_term:x{[lthooks]~ Add~ to~
2157     \__hook_if_usable:nF {#1} { undeclared~ }
2158     hook~ '#1'~ ( next~ invocation~ only )
2159     \on@line
2160     ^^J [lthooks] \@spaces
2161     <-- \tl_to_str:n{#2}
2162   }
2163 }
2164 \__hook_replacing_args_reset:
2165 \cs_new_protected:Npn \hook_gput_next_code_with_args:nn #1 #2
2166 {
2167   \__hook_replacing_args_true:
2168   \__hook_normalize_hook_args:Nn \__hook_gput_next_code:nn {#1} {#2}
2169
2170   \__hook_debug:n{\iow_term:x{[lthooks]~ Add~ to~
2171     \__hook_if_usable:nF {#1} { undeclared~ }
2172     hook~ '#1'~ ( next~ invocation~ only )
2173     \on@line
2174     ^^J [lthooks] \@spaces
2175     <-- \tl_to_str:n{#2}
2176   }
2177 }
2178 \__hook_replacing_args_reset:
2179 <latexrelease>\EndIncludeInRelease
2180 <latexrelease>\IncludeInRelease{2020/10/01}{\hook_gput_next_code:nn}

```

```

2181 <latexrelease> {Hooks~with~args}
2182 <latexrelease> \cs_gset_protected:Npn \hook_gput_next_code:nn #1
2183 <latexrelease> { \__hook_normalize_hook_args:Nn
2184 <latexrelease> \__hook_gput_next_code:nn {#1} }
2185 <latexrelease> \cs_gset_protected:Npn \hook_gput_next_code_with_args:nn #1 #2 { }
2186 <latexrelease> \EndIncludeInRelease

```

(End of definition for \hook\_gput\_next\_code:nn. This function is documented on page 215.)

\\_\_hook\_gput\_next\_code:nn

```

2187 \cs_new_protected:Npn \__hook_gput_next_code:nn #1 #2
2188 {
2189   \__hook_if_disabled:nTF {#1}
2190   { \msg_error:nnn { hooks } { hook-disabled } {#1} }
2191   {
2192     \__hook_if_structure_exist:nTF {#1}
2193     { \__hook_gput_next_do:nn }
2194     { \__hook_try_declaring_generic_next_hook:nn
2195       {#1} {#2}
2196     }
2197   }

```

(End of definition for \\_\_hook\_gput\_next\_code:nn.)

\\_\_hook\_gput\_next\_do:nn

Start by sanity-checking with \\_\_hook\_chk\_args\_allowed:nn. Then check if the “next code” token list is empty: if so we need to add a \tl\_gclear:c to clear it, so the code lasts for one usage only. The token list is cleared early so that nested usages don’t get lost. \tl\_gclear:c is used instead of \tl\_gclear:N in case the hook is used in an expansion-only context, so the token list doesn’t expand before \tl\_gclear:N: that would make an infinite loop. Also in case the main code token list is empty, the hook code has to be updated to add the next execution token list.

```

2198 <latexrelease> \IncludeInRelease{2023/06/01}{\__hook_gput_next_do:nn}
2199 <latexrelease> {Hooks~with~args}
2200 \cs_new_protected:Npn \__hook_gput_next_do:nn #1
2201 {
2202   \__hook_init_structure:n {#1}
2203   \__hook_chk_args_allowed:nn {#1} { AddToHookNext }
2204   \__hook_cs_if_empty:cT { \__hook~#1 }
2205   { \__hook_update_hook_code:n {#1} }
2206   \__hook_cs_if_empty:cT { \__hook_next~#1 }
2207   { \__hook_next_gset:nn {#1} { \__hook_clear_next:n {#1} } }
2208   \__hook_cs_gput_right:nnn { _next } {#1}
2209 }
2210 <latexrelease> \EndIncludeInRelease
2211 <latexrelease> \IncludeInRelease{2020/10/01}{\__hook_gput_next_do:nn}
2212 <latexrelease> {Hooks~with~args}
2213 <latexrelease> \cs_gset_protected:Npn \__hook_gput_next_do:nn #1
2214 <latexrelease> {
2215 <latexrelease> \exp_args:Nc \__hook_gput_next_do:Nnn
2216 <latexrelease> { \__hook_next~#1 } {#1}
2217 <latexrelease> }
2218 <latexrelease> \cs_gset_protected:Npn \__hook_gput_next_do:Nnn #1 #2
2219 <latexrelease> {
2220 <latexrelease> \tl_if_empty:cT { \__hook~#2 }

```

```

2221 <latexrelease> { \__hook_update_hook_code:n {#2} }
2222 <latexrelease> \tl_if_empty:NT #1
2223 <latexrelease> { \__hook_tl_gset:Nn #1 { \__hook_clear_next:n {#2} } }
2224 <latexrelease> \__hook_tl_gput_right:Nn #1
2225 <latexrelease> }
2226 <latexrelease> \EndIncludeInRelease

(End of definition for \__hook_gput_next_do:nn.)

```

**\hook\_gclear\_next\_code:n** Discard anything set up for next invocation of the hook.

```

2227 \cs_new_protected:Npn \hook_gclear_next_code:n #1
2228 { \__hook_normalize_hook_args:Nn \__hook_clear_next:n {#1} }

(End of definition for \hook_gclear_next_code:n. This function is documented on page 215.)

```

**\\_\_hook\_clear\_next:n**

```

2229 <latexrelease> \IncludeInRelease{2023/06/01}{\__hook_clear_next:n}
2230 <latexrelease> {Hooks-with-args}
2231 \cs_new_protected:Npn \__hook_clear_next:n #1
2232 { \__hook_next_gset:nn {#1} { } }
2233 <latexrelease> \EndIncludeInRelease
2234 <latexrelease> \IncludeInRelease{2020/10/01}{\__hook_clear_next:n}
2235 <latexrelease> {Hooks-with-args}
2236 <latexrelease> \cs_gset_protected:Npn \__hook_clear_next:n #1
2237 <latexrelease> { \cs_gset_eq:cN { \__hook_next~#1 } \c_empty_tl }
2238 <latexrelease> \EndIncludeInRelease

(End of definition for \__hook_clear_next:n.)

```

## 4.9 Using the hook

**\hook\_use:n** **\hook\_use:n** as defined here is used in the preamble, where hooks aren't initialized by default. **\\_\_hook\_use\_initialized:n** is also defined, which is the non-**\protected** version for use within the document. Their definition is identical, except for the **\\_\_hook\_preamble\_hook:n** (which wouldn't hurt in the expandable version, but it would be an unnecessary extra expansion).

**\\_\_hook\_use\_initialized:n** holds the expandable definition while in the preamble. **\\_\_hook\_preamble\_hook:n** initializes the hook in the preamble, and is redefined to **\use\_none:n** at **\begin{document}**.

Both versions do the same thing internally: they check that the hook exists as given, and if so they use it as quickly as possible.

At **\begin{document}**, all hooks are initialized, and any change in them causes an update, so **\hook\_use:n** can be made expandable. This one is better not protected so that it can expand into nothing if containing no code. Also important in case of generic hooks that we do not generate a **\relax** as a side effect of checking for a csname. In contrast to the T<sub>E</sub>X low-level **\csname ... \endcsname** construct **\tl\_if\_exist:c** is careful to avoid this.

```

2239 <latexrelease> \IncludeInRelease{2023/06/01}{\hook_use:n}
2240 <latexrelease> {Hooks-with-args}
2241 \cs_new_protected:Npn \hook_use:n #1
2242 {
2243   \__hook_preamble_hook:n {#1}
2244   \__hook_use_initialized:n {#1}

```

```

2245 }
2246 \cs_new:Npn \__hook_use_initialized:n #1
2247 {
2248   \if_cs_exist:w __hook~#1 \cs_end:
2249   \cs:w __hook~#1 \use_i:nn
2250   \fi:
2251   \use_none:n
2252   \cs_end:
2253 }
2254 \cs_new_protected:Npn \__hook_preamble_hook:n #1
2255 {
2256   \if_cs_exist:w __hook~#1 \cs_end:
2257   \__hook_initialize_hook_code:n {#1}
2258   \fi:
2259 }
2260 <latexrelease> \EndIncludeInRelease

2261 <latexrelease> \IncludeInRelease{2021/11/15}{\hook_use:n}
2262 <latexrelease> {Standardize-generic-hook-names}
2263 <latexrelease> \cs_new_protected:Npn \hook_use:n #1
2264 <latexrelease> {
2265   <latexrelease> \tl_if_exist:cT { __hook~#1 }
2266   <latexrelease> {
2267     <latexrelease> \__hook_preamble_hook:n {#1}
2268     <latexrelease> \cs:w __hook~#1 \cs_end:
2269   <latexrelease> }
2270 <latexrelease> }
2271 <latexrelease> \cs_new:Npn \__hook_use_initialized:n #1
2272 <latexrelease> {
2273   <latexrelease> \if_cs_exist:w __hook~#1 \cs_end:
2274   <latexrelease> \cs:w __hook~#1 \exp_after:wN \cs_end:
2275   <latexrelease> \fi:
2276 <latexrelease> }
2277 <latexrelease> \cs_new_protected:Npn \__hook_preamble_hook:n #1
2278 <latexrelease> { \__hook_initialize_hook_code:n {#1} }
2279 <latexrelease> \cs_new:Npn \hook_use:nnw #1 { }
2280 <latexrelease> \EndIncludeInRelease

2281 <latexrelease> \IncludeInRelease{2020/10/01}{\hook_use:n}
2282 <latexrelease> {Standardize-generic-hook-names}
2283 <latexrelease> \cs_new_protected:Npn \hook_use:n #1
2284 <latexrelease> {
2285   <latexrelease> \tl_if_exist:cTF { __hook~#1 }
2286   <latexrelease> {
2287     <latexrelease> \__hook_preamble_hook:n {#1}
2288     <latexrelease> \cs:w __hook~#1 \cs_end:
2289   <latexrelease> }
2290   <latexrelease> { \__hook_use:wn #1 / \s__hook_mark {#1} }
2291 <latexrelease> }
2292 <latexrelease> \cs_new:Npn \__hook_use_initialized:n #1
2293 <latexrelease> {
2294   <latexrelease> \if_cs_exist:w __hook~#1 \cs_end:
2295   <latexrelease> \else:
2296     <latexrelease> \__hook_use_undefined:w
2297   <latexrelease> \fi:

```

```

2298 <latexrelease> \cs:w __hook~#1 \__hook_use_end:
2299 <latexrelease> }
2300 <latexrelease> \cs_new:Npn \__hook_use_undefined:w
2301 <latexrelease> #1 #2 __hook~#3 \__hook_use_end:
2302 <latexrelease> {
2303 <latexrelease> #1 % fi
2304 <latexrelease> \__hook_use:wn #3 / \s__hook_mark {#3}
2305 <latexrelease> }
2306 <latexrelease> \cs_new_protected:Npn \__hook_preamble_hook:n #1
2307 <latexrelease> { \__hook_initialize_hook_code:n {#1} }
2308 <latexrelease> \cs_new_eq:NN \__hook_use_end: \cs_end:
2309 <latexrelease> \cs_new:Npn \hook_use:nnw #1 { }
2310 <latexrelease> \EndIncludeInRelease

```

(End of definition for \hook\_use:n, \\_\_hook\_use\_initialized:n, and \\_\_hook\_preamble\_hook:n. This function is documented on page 214.)

**\hook\_use:nnw**

**\\_\_hook\_use\_initialized:nnw**

```

2311 <latexrelease> \IncludeInRelease{2023/06/01}{\hook_use:nnw}
2312 <latexrelease> {Hooks~with~args}
2313 \cs_new_protected:Npn \hook_use:nnw #1
2314 {
2315 \__hook_preamble_hook:n {#1}
2316 \__hook_use_initialized:nnw {#1}
2317 }
2318 \cs_new:Npn \__hook_use_initialized:nnw #1 #2
2319 {
2320 \cs:w
2321 \if_cs_exist:w __hook~#1 \cs_end:
2322 __hook~#1
2323 \else:
2324 use_none: \prg_replicate:nn {#2} { n }
2325 \fi:
2326 \cs_end:
2327 }
2328 <latexrelease> \EndIncludeInRelease
2329 <latexrelease> \IncludeInRelease{2020/10/01}{\hook_use:nnw}
2330 <latexrelease> {Hooks~with~args}
2331 <latexrelease> \cs_gset:Npn \hook_use:nnw #1 #2
2332 <latexrelease> { \use:c { use_none: \prg_replicate:nn {#2} { n } } }
2333 <latexrelease> \EndIncludeInRelease

```

(End of definition for \hook\_use:nnw and \\_\_hook\_use\_initialized:nnw. This function is documented on page 214.)

**\\_\_hook\_post\_initialization\_defs:**

```

2334 <latexrelease> \IncludeInRelease{2023/06/01}{\__hook_post_initialization_defs:}
2335 <latexrelease> {Hooks~with~args}
2336 \cs_new_protected:Npn \__hook_post_initialization_defs:
2337 {
2338 \cs_gset_eq:NN \hook_use:n \__hook_use_initialized:n
2339 \cs_gset_eq:NN \hook_use:nnw \__hook_use_initialized:nnw
2340 \cs_gset_eq:NN \__hook_preamble_hook:n \use_none:n
2341 \cs_gset_eq:NN \__hook_post_initialization_defs: \prg_do_nothing:
2342 }

```

```

2343 <latexrelease>\EndIncludeInRelease
2344 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_post_initialization_defs:}
2345 <latexrelease>{Hooks~with~args}
2346 <latexrelease>\cs_undefine:N \__hook_post_initialization_defs:
2347 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_post\_initialization\_defs:.)

\\_\_hook\_use:wn \\_\_hook\_use:wn does a quick check to test if the current hook is a file hook: those need a special treatment. If it is not, the hook does not exist. If it is, then \\_\_hook\_try\_file\_hook:n is called, and checks that the current hook is a file-specific hook using \\_\_hook\_if\_file\_hook:wTF. If it's not, then it's a generic file/ hook and is used if it exist.

If it is a file-specific hook, it passes through the same normalization as during declaration, and then it is used if defined. \\_\_hook\_if\_usable\_use:n checks if the hook exist, and calls \\_\_hook\_preamble\_hook:n if so, then uses the hook.

```

2348 <latexrelease>\IncludeInRelease{2021/11/15}{\__hook_use:wn}
2349 <latexrelease>{Standardize-generic-hook-names}
2350 <latexrelease>\EndIncludeInRelease
2351 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_use:wn}
2352 <latexrelease>{Standardize-generic-hook-names}
2353 <latexrelease>\cs_new:Npn \__hook_use:wn #1 / #2 \s__hook_mark #3
2354 <latexrelease> {
2355 <latexrelease> \str_if_eq:nnTF {#1} { file }
2356 <latexrelease> { \__hook_try_file_hook:n {#3} }
2357 <latexrelease> { } % Hook doesn't exist
2358 <latexrelease> }

2359 <latexrelease>\cs_new_protected:Npn \__hook_try_file_hook:n #1
2360 <latexrelease> {
2361 <latexrelease> \__hook_if_file_hook:wTF #1 / / \s__hook_mark
2362 <latexrelease> {
2363 <latexrelease> \exp_args:Ne \__hook_if_usable_use:n
2364 <latexrelease> { \exp_args:Ne \__hook_file_hook_normalize:n {#1} }
2365 <latexrelease> }
2366 <latexrelease> { \__hook_if_usable_use:n {#1} }
2367 <latexrelease> % file/ generic hook (e.g. file/before)
2368 <latexrelease> }

2369 <latexrelease>\cs_new_protected:Npn \__hook_if_usable_use:n #1
2370 <latexrelease> {
2371 <latexrelease> \tl_if_exist:cT { __hook~#1 }
2372 <latexrelease> {
2373 <latexrelease> \__hook_preamble_hook:n {#1}
2374 <latexrelease> \cs:w __hook~#1 \cs_end:
2375 <latexrelease> }
2376 <latexrelease> }
2377 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_use:wn, \\_\_hook\_try\_file\_hook:n, and \\_\_hook\_if\_usable\_use:n.)

\hook\_use\_once:n For hooks that can and should be used only once we have a special use command that further inhibits the hook from getting more code added to it. This has the effect that any further code added to the hook is executed immediately rather than stored in the hook.

The code needs some gymnastics to prevent space trimming from the hook name, since `\hook_use:n` and `\hook_use_once:n` are documented to not trim spaces.

```

2378 <latexrelease>\IncludeInRelease{2023/06/01}{\hook_use_once:nnw}
2379 <latexrelease> {Hooks-with-args}
2380 \cs_new_protected:Npn \hook_use_once:n #1
2381 {
2382   \__hook_if_execute_immediately:nF {#1}
2383   { \__hook_normalize_hook_args:Nn \__hook_use_once:nn
2384     { \use:n {#1} } { 0 } }
2385 }
2386 \cs_new_protected:Npn \hook_use_once:nnw #1 #2
2387 {
2388   \__hook_if_execute_immediately:nF {#1}
2389   { \__hook_normalize_hook_args:Nn \__hook_use_once:nn
2390     { \use:n {#1} } {#2} }
2391 }
2392 <latexrelease>\EndIncludeInRelease

```

*(End of definition for `\hook_use_once:n` and `\hook_use_once:nnw`. These functions are documented on page 214.)*

```

2393 <latexrelease>\IncludeInRelease{2020/10/01}{\hook_use_once:nnw}
2394 <latexrelease> {Hooks-with-args}
2395 <latexrelease>\cs_gset_protected:Npn \hook_use_once:n #1
2396 <latexrelease> {
2397 <latexrelease>   \__hook_if_execute_immediately:nF {#1}
2398 <latexrelease>   { \__hook_normalize_hook_args:Nn \__hook_use_once:n
2399 <latexrelease>     { \use:n {#1} } } }
2400 <latexrelease> }
2401 <latexrelease>\cs_gset:Npn \hook_use_once:nnw #1 #2
2402 <latexrelease> { \use:c { use_none: \prg_replicate:nn {#2} { n } } }
2403 <latexrelease>\EndIncludeInRelease

```

`\__hook_use_once:nn`

```

2404 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_use_once:nn}
2405 <latexrelease> {Hooks-with-args}
2406 \cs_new_protected:Npn \__hook_use_once:nn #1 #2
2407 {
2408   \__hook_preamble_hook:n {#1}
2409   \__hook_use_once_set:n {#1}

```

When a hook has arguments, the call to `\__hook_use_initialized:n`, should be the very last thing to happen, otherwise the arguments grabbed will be wrong. So, to clean up after the hook we need to cheat a bit and sneak the cleanup code at the end of the hook, along with the next execution code.

```

2410   \__hook_replacing_args_false:
2411   \__hook_cs_gput_right:nnn { _next } {#1}
2412   { \__hook_use_once_clear:n {#1} }
2413   \__hook_replacing_args_reset:
2414   \__hook_if_usable:nTF {#1}
2415   { \__hook_use_initialized:n {#1} }
2416   {
2417     \int_compare:nNnT {#2} > { 0 }
2418     { \use:c { use_none: \prg_replicate:nn {#2} { n } } }
2419   }

```

```

2420 }
2421 \<latexrelease>\EndIncludeInRelease
2422 %
2423 \<latexrelease>\IncludeInRelease{2020/10/01}{\__hook_use_once:nn}
2424 \<latexrelease>{Hooks-with-args}
2425 \<latexrelease>\cs_gset_protected:Npn \__hook_use_once:n #1
2426 \<latexrelease> {
2427 \<latexrelease> \__hook_preamble_hook:n {#1}
2428 \<latexrelease> \__hook_use_once_set:n {#1}
2429 \<latexrelease> \__hook_use_initialized:n {#1}
2430 \<latexrelease> \__hook_use_once_clear:n {#1}
2431 \<latexrelease> }
2432 \<latexrelease>\cs_undefine:N \__hook_use_once:nn
2433 \<latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_use\_once:nn.)

\\_\_hook\_use\_once\_set:n \\_\_hook\_use\_once\_set:n is used before the actual hook code is executed so that any usage of \AddToHook inside the hook causes the code to execute immediately. Setting \g\_\_hook\_<hook>\_reversed\_tl to I prevents further code from being added to the hook. \\_\_hook\_use\_once\_clear:n then clears the hook so that any further call to \hook\_use:n or \hook\_use\_once:n will expand to nothing.

```

2434 \<latexrelease>\IncludeInRelease{2023/06/01}{\__hook_use_once_clear:n}
2435 \<latexrelease>{Hooks-with-args}
2436 \cs_new_protected:Npn \__hook_use_once_set:n #1
2437 { \__hook_tl_gset:cn { g__hook_#1_reversed_tl } { I } }
2438 \cs_new_protected:Npn \__hook_use_once_clear:n #1
2439 {
2440 \__hook_code_gset:nn {#1} { }
2441 \__hook_next_gset:nn {#1} { }
2442 \__hook_toplevel_gset:nn {#1} { }
2443 \prop_gclear_new:c { g__hook_#1_code_prop }
2444 }
2445 \<latexrelease>\EndIncludeInRelease
2446 \<latexrelease>\IncludeInRelease{2020/10/01}{\__hook_use_once_clear:n}
2447 \<latexrelease>{Hooks-with-args}
2448 \<latexrelease>\cs_new_protected:Npn \__hook_use_once_clear:n #1
2449 \<latexrelease> {
2450 \<latexrelease> \__hook_tl_gclear:c { __hook-#1 }
2451 \<latexrelease> \__hook_tl_gclear:c { __hook_next-#1 }
2452 \<latexrelease> \__hook_tl_gclear:c { __hook_toplevel-#1 }
2453 \<latexrelease> \prop_gclear_new:c { g__hook_#1_code_prop }
2454 \<latexrelease> }
2455 \<latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_use\_once\_set:n and \\_\_hook\_use\_once\_clear:n.)

\\_hook\_if\_execute\_immediately\_p:n To check whether the code being added should be executed immediately (that is, if the hook is a one-time hook), we check if \g\_\_hook\_<hook>\_reversed\_tl is I. The gymnastics around \if:w is there to allow the reversed token list to be empty.

```

2456 \prg_new_conditional:Npnn \__hook_if_execute_immediately:n #1 { T, F, TF }
2457 {
2458 \exp_after:wN \__hook_use_none_delimit_by_s_mark:w
2459 \if:w I

```

```

2460         \if_cs_exist:w g__hook_#1_reversed_tl \cs_end:
2461         \cs:w g__hook_#1_reversed_tl \exp_after:wN \cs_end:
2462         \fi:
2463         X
2464         \s__hook_mark \prg_return_true:
2465     \else:
2466         \s__hook_mark \prg_return_false:
2467     \fi:
2468 }

```

(End of definition for \\_\_hook\_if\_execute\_immediately:nTF.)

## 4.10 Querying a hook

Simpler data types, like token lists, have three possible states; they can exist and be empty, exist and be non-empty, and they may not exist, in which case emptiness doesn’t apply (though \tl\_if\_empty:N returns false in this case).

Hooks are a bit more complicated: they have several other states as discussed in 4.4.2. A hook may exist or not, and either way it may or may not be empty (even a hook that doesn’t exist may be non-empty) or may be disabled.

A hook is said to be empty when no code was added to it, either to its permanent code pool, or to its “next” token list. The hook doesn’t need to be declared to have code added to its code pool (it may happen that a package *A* defines a hook `foo`, but it’s loaded after package *B*, which adds some code to that hook. In this case it is important that the code added by package *B* is remembered until package *A* is loaded).

All other states can only be queried with internal tests as the different states are irrelevant for package code.

**\hook\_if\_empty\_p:n** Test if a hook is empty (that is, no code was added to that hook). A  $\langle\text{hook}\rangle$  being empty means that all three of its `\g__hook_<hook>_code_prop`, its `\__hook_toplevel_<hook>` and its `\__hook_next_<hook>` are empty.

**\hook\_if\_empty:nTF**

```

2469 <latexrelease> \IncludeInRelease{2023/06/01}{\hook_if_empty:n}
2470 <latexrelease> {Hooks-with-args}
2471 \prg_new_conditional:Npnn \hook_if_empty:n #1 { p , T , F , TF }
2472 {
2473     \if:w
2474         T
2475         \prop_if_exist:cT { g__hook_#1_code_prop }
2476         { \prop_if_empty:cF { g__hook_#1_code_prop } { F } }
2477         \__hook_cs_if_empty:cF { __hook_toplevel~#1 } { F }
2478         \__hook_cs_if_empty:cF { __hook_next~#1 } { F }
2479         T
2480         \prg_return_true:
2481     \else:
2482         \prg_return_false:
2483     \fi:
2484 }
2485 <latexrelease> \EndIncludeInRelease
2486 <latexrelease> \IncludeInRelease{2020/10/01}{\hook_if_empty:n}
2487 <latexrelease> {Hooks-with-args}
2488 <latexrelease> \prg_new_conditional:Npnn \hook_if_empty:n #1 { p , T , F , TF }
2489 <latexrelease> {

```

```

2490 <latexrelease> \_hook_if_structure_exist:nTF {#1}
2491 <latexrelease> {
2492 <latexrelease> \bool_lazy_and:nnTF
2493 <latexrelease> { \prop_if_empty_p:c { g__hook_#1_code_prop } }
2494 <latexrelease> {
2495 <latexrelease> \bool_lazy_and_p:nn
2496 <latexrelease> { \tl_if_empty_p:c { __hook_toplevel~#1 } }
2497 <latexrelease> { \tl_if_empty_p:c { __hook_next~#1 } }
2498 <latexrelease> }
2499 <latexrelease> { \prg_return_true: }
2500 <latexrelease> { \prg_return_false: }
2501 <latexrelease> }
2502 <latexrelease> { \prg_return_true: }
2503 <latexrelease> }
2504 <latexrelease> \EndIncludeInRelease

```

(End of definition for `\hook_if_empty:nTF`. This function is documented on page 216.)

`\_hook_if_usable_p:n` A hook is usable if the token list that stores the sorted code for that hook, `\_hook_<hook>`, exists. The property list `g__hook_<hook>_code_prop` cannot be used here because often it is necessary to add code to a hook without knowing if such hook was already declared, or even if it will ever be (for example, in case the package that defines it isn't loaded).

```

2505 \prg_new_conditional:Npnn \_hook_if_usable:n #1 { p , T , F , TF }
2506 {
2507 \cs_if_exist:cTF { __hook~#1 }
2508 { \prg_return_true: }
2509 { \prg_return_false: }
2510 }

```

(End of definition for `\_hook_if_usable:nTF`.)

`\_hook_if_structure_exist_p:n` An internal check if the hook has already its basic internal structure set up with `\_hook_init_structure:n`. This means that the hook was already used somehow (a code chunk or rule was added to it), but it still wasn't declared with `\hook_new:n`.

```

2511 \prg_new_conditional:Npnn \_hook_if_structure_exist:n #1 { p , T , F , TF }
2512 {
2513 \prop_if_exist:cTF { g__hook_#1_code_prop }
2514 { \prg_return_true: }
2515 { \prg_return_false: }
2516 }

```

(End of definition for `\_hook_if_structure_exist:nTF`.)

`\_hook_if_declared_p:n` Internal test to check if the hook was officially declared with `\hook_new:n` or a variant.

```

2517 \prg_new_conditional:Npnn \_hook_if_declared:n #1 { p , T , F , TF }
2518 {
2519 \tl_if_exist:cTF { g__hook_#1_declared_tl }
2520 { \prg_return_true: }
2521 { \prg_return_false: }
2522 }

```

(End of definition for `\_hook_if_declared:nTF`.)

`\__hook_if_reversed_p:n` An internal conditional that checks if a hook is reversed.

`\__hook_if_reversed:nTF`

```

2523 \prg_new_conditional:Npnn \__hook_if_reversed:n #1 { p , T , F , TF }
2524 {
2525   \exp_after:wN \__hook_use_none_delimit_by_s_mark:w
2526   \if:w - \cs:w g__hook_#1_reversed_tl \cs_end:
2527     \s__hook_mark \prg_return_true:
2528   \else:
2529     \s__hook_mark \prg_return_false:
2530   \fi:
2531 }

```

(End of definition for `\__hook_if_reversed:nTF`.)

`\__hook_if_generic_p:n` An internal conditional that checks if a name belongs to a generic hook. The deprecated version needs to check if #3 is empty to avoid returning true on file/before, for example.

`\__hook_if_generic:nTF`

`\__hook_if_deprecated_generic_p:n`

`\__hook_if_deprecated_generic:nTF`

```

2532 \prg_new_conditional:Npnn \__hook_if_generic:n #1 { T, TF }
2533 { \__hook_if_generic:w #1 / / / \s__hook_mark }
2534 \cs_new:Npn \__hook_if_generic:w #1 / #2 / #3 / #4 \s__hook_mark
2535 {
2536   \cs_if_exist:cTF { c__hook_generic_#1/./#3_tl }
2537   { \prg_return_true: }
2538   { \prg_return_false: }
2539 }
2540 \prg_new_conditional:Npnn \__hook_if_deprecated_generic:n #1 { T, TF }
2541 { \__hook_if_deprecated_generic:w #1 / / / \s__hook_mark }
2542 \cs_new:Npn \__hook_if_deprecated_generic:w #1 / #2 / #3 / #4 \s__hook_mark
2543 {
2544   \cs_if_exist:cTF { c__hook_deprecated_#1/./#2_tl }
2545   {
2546     \tl_if_empty:nTF {#3}
2547     { \prg_return_false: }
2548     { \prg_return_true: }
2549   }
2550   { \prg_return_false: }
2551 }

```

(End of definition for `\__hook_if_generic:nTF` and `\__hook_if_deprecated_generic:nTF`.)

`\__hook_if_cmd_hook_p:n` An internal conditional that checks if a given hook is a valid generic cmd hook.

`\__hook_if_cmd_hook:nTF`

`\__hook_if_cmd_hook_p:w`

`\__hook_if_cmd_hook:wTF`

```

2552 <latexrelease> \IncludeInRelease{2023/06/01}{\__hook_if_cmd_hook:n}
2553 <latexrelease> {Hooks-with-args}
2554 \prg_new_conditional:Npnn \__hook_if_cmd_hook:n #1 { T }
2555 { \__hook_if_cmd_hook:w #1 / / / \s__hook_mark }
2556 \cs_new:Npn \__hook_if_cmd_hook:w #1 / #2 / #3 / #4 \s__hook_mark
2557 {
2558   \if:w Y
2559     \str_if_eq:nnF {#1} { cmd } { N }
2560     \tl_if_exist:cF { c__hook_generic_#1/./#3_tl } { N }
2561     Y
2562     \prg_return_true:
2563   \else:
2564     \prg_return_false:
2565   \fi:
2566 }

```

```

2567 <latexrelease>\EndIncludeInRelease
2568 <latexrelease>\IncludeInRelease{2020/10/01}{\__hook_if_cmd_hook:n}
2569 <latexrelease>{Hooks-with-args}
2570 <latexrelease>\cs_undefine:N \__hook_if_cmd_hook:nT
2571 <latexrelease>\EndIncludeInRelease

```

*(End of definition for \\_\_hook\_if\_cmd\_hook:nTF and \\_\_hook\_if\_cmd\_hook:wTF.)*

\\_\_hook\_if\_generic\_reversed\_p:n An internal conditional that checks if a name belongs to a generic reversed hook.  
 \\_\_hook\_if\_generic\_reversed:nTF

```

2572 \prg_new_conditional:Npnn \__hook_if_generic_reversed:n #1 { T }
2573 { \__hook_if_generic_reversed:w #1 / / / \scan_stop: }
2574 \cs_new:Npn \__hook_if_generic_reversed:w #1 / #2 / #3 / #4 \scan_stop:
2575 {
2576   \if_charcode:w - \cs:w c__hook_generic_#1/./#3_tl \cs_end:
2577   \prg_return_true:
2578   \else:
2579   \prg_return_false:
2580   \fi:
2581 }

```

*(End of definition for \\_\_hook\_if\_generic\_reversed:nTF.)*

\\_\_hook\_if\_replacing\_args:TF An internal conditional that checks if the code being added to the hook contains arguments.  
 \\_\_hook\_misused\_if\_replacing\_args:nn

```

\__hook_replacing_args_true: 2582 \seq_new:N \g__hook_replacing_stack_seq
\__hook_replacing_args_false: 2583 \cs_new:Npn \__hook_misused_if_replacing_args:nn #1 #2
\__hook_replacing_args_reset: 2584 {
\g__hook_replacing_stack_seq 2585   \msg_expandable_error:nnn { latex2e } { should-not-happen }
2586   { Misused-\__hook_if_replacing_args:. }
2587 }
2588 \cs_new:Npn \__hook_if_replacing_args:TF
2589 { \__hook_misused_if_replacing_args:nn }
2590 \cs_new_protected:Npn \__hook_replacing_args_true:
2591 {
2592   \seq_gpush:No \g__hook_replacing_stack_seq
2593   { \__hook_if_replacing_args:TF }
2594   \cs_set:Npn \__hook_if_replacing_args:TF { \use_i:nn }
2595 }
2596 \cs_new_protected:Npn \__hook_replacing_args_false:
2597 {
2598   \seq_gpush:No \g__hook_replacing_stack_seq
2599   { \__hook_if_replacing_args:TF }
2600   \cs_set:Npn \__hook_if_replacing_args:TF { \use_ii:nn }
2601 }
2602 \cs_new_protected:Npn \__hook_replacing_args_reset:
2603 {
2604   \seq_gpop:NN \g__hook_replacing_stack_seq \l__hook_return_tl
2605   \cs_gset_eq:NN \__hook_if_replacing_args:TF \l__hook_return_tl
2606 }

```

*(End of definition for \\_\_hook\_if\_replacing\_args:TF and others.)*

## 4.11 Messages

Hook errors are LaTeX kernel errors:

```
2607 \prop_gput:Nnn \g_msg_module_type_prop { hooks } { LaTeX }
And so are kernel errors (this should move elsewhere eventually).
2608 \prop_gput:Nnn \g_msg_module_type_prop { latex2e } { LaTeX }
2609 \prop_gput:Nnn \g_msg_module_name_prop { latex2e } { kernel }

2610 \msg_new:nnnn { hooks } { labels-incompatible }
2611 {
2612   Labels~'#1'~and~'#2'~are~incompatible
2613   \str_if_eq:nnF {#3} {??} { ~in-hook~'#3' } .~
2614   \int_compare:nNnTF {#4} = { 1 }
2615     { The~ code~ for~ both~ labels~ will~ be~ dropped. }
2616     { You~ may~ see~ errors~ later. }
2617 }
2618 { LaTeX~found~two~incompatible~labels~in~the~same~hook.~
2619   This~indicates~an~incompatibility~between~packages. }

2620 \msg_new:nnnn { hooks } { exists }
2621 { Hook~'#1'~ has~ already~ been~ declared. }
2622 { There~ already~ exists~ a~ hook~ declaration~ with~ this~
2623   name.\\
2624   Please~ use~ a~ different~ name~ for~ your~ hook.}

2625 \<latexrelease>\IncludeInRelease{2023/06/01}{too-many-args}
2626 \<latexrelease>{Hooks-with-args}

2627 \msg_new:nnnn { hooks } { too-many-args }
2628 { Too-many-arguments-for-hook~'#1'. }
2629 {
2630   You~tried~to~declare~a~hook~with~#2~arguments,~but~a~
2631   hook~can~only~have~up~to~nine.~LaTeX~will~define~this~
2632   hook~with~nine~arguments.
2633 }

2634 \msg_new:nnnn { hooks } { without-args }
2635 { Hook~'#1'~has~no~arguments. }
2636 {
2637   You~tried~to~use~\iow_char:N\\#2WithArguments~
2638   on~a~hook~that~takes~no~arguments.\\
2639   Check~the~usage~of~the~hook~or~use~\iow_char:N\\#2~instead.\\
2640   \\
2641   LaTeX~will~use~\iow_char:N\\#2.
2642 }

2643 \msg_new:nnnn { hooks } { one-time-args }
2644 { You~can't~have~arguments~in~used~one-time~hook~'#1'. }
2645 {
2646   You~tried~to~use~\iow_char:N\\#2WithArguments~
2647   on~a~one-time~hook~that~has~already~been~used.~
2648   You~have~to~add~the~code~before~the~hook~is~used,~
2649   or~add~the~code~without~arguments~using~\iow_char:N\\#2~instead.\\
2650   \\
2651   LaTeX~will~use~\iow_char:N\\#2.
2652 }
```

```

2653 \<latexrelease>\EndIncludeInRelease
2654 \<latexrelease>\IncludeInRelease{2020/10/01}{too-many-args}
2655 \<latexrelease>{Hooks-with-args}
2656 \<latexrelease>\EndIncludeInRelease

2657 \msg_new:nnnn { hooks } { hook-disabled }
2658 { Cannot-add-code-to-disabled-hook~'#1'. }
2659 {
2660   The~hook~'#1'~you~tried~to~add~code~to~was~previously~disabled~
2661   with~\iow_char:N\hook_disable_generic:n-or~
2662   \iow_char:N\DisableGenericHook,~so~
2663   it~cannot~have~code~added~to~it.
2664 }

2665 \msg_new:nnn { hooks } { empty-label }
2666 {
2667   Empty~code~label~\msg_line_context:~
2668   Using~'\_hook_currname_or_default:'~instead.
2669 }

2670 \msg_new:nnn { hooks } { empty-hook }
2671 {
2672   Empty~hook~name~\msg_line_context:.
2673 }

2674 \msg_new:nnn { hooks } { no-default-label }
2675 {
2676   Missing~(empty)~default~label~\msg_line_context:. \\\
2677   This~command~was~ignored.
2678 }

2679 \msg_new:nnnn { hooks } { unknown-rule }
2680 {
2681   Unknown~ relationship~ '#3'~
2682   between~ labels~ '#2'~ and~ '#4'~
2683   \str_if_eq:nnF {#1} {??} { ~in~hook~'#1' }. ~
2684   Perhaps~ a~ misspelling?
2685 }
2686 {
2687   The~ relation~ used~ not~ known~ to~ the~ system.~ Allowed~ values~ are~
2688   'before'~ or~ '<',~
2689   'after'~ or~ '>',~
2690   'incompatible-warning',~
2691   'incompatible-error',~
2692   'voids'~ or~
2693   'unrelated'.
2694 }

2695 \msg_new:nnnn { hooks } { rule-too-late }
2696 {
2697   Sorting~rule~for~'#1'~hook~applied~too~late.\\
2698   Try~setting~this~rule~earlier.
2699 }
2700 {
2701   You~tried~to~set~the~ordering~of~hook~'#1'~using\\
2702   \ \ \iow_char:N\DeclareHookRule{#1}{#2}{#3}{#4}\\
2703   but~hook~'#1'~was~already~used~as~a~one-time~hook,~

```

```

2704 thus~sorting~is~\
2705 no~longer~possible.~Declare~the~rule~
2706 before~the~hook~is~used.
2707 }
2708 \msg_new:nnnn { hooks } { misused-top-level }
2709 {
2710 Illegal~use~of~\iow_char:N \AddToHook{#1}[top-level]{...}.\
2711 'top-level'~is~reserved~for~the~user's~document.
2712 }
2713 {
2714 The~'top-level'~label~is~meant~for~user~code~only,~and~should~only~
2715 be~used~(sparingly)~in~the~main~document.~Use~the~default~label~
2716 '\__hook_currname_or_default:'~for~this~\@cls@pkg,~or~another~
2717 suitable~label.
2718 }
2719 \msg_new:nnn { hooks } { set-top-level }
2720 {
2721 You~cannot~change~the~default~label~#1~'top-level'.~Illegal \
2722 \use:nn { ~ } { ~ } \iow_char:N \#2{#3} \
2723 \msg_line_context:.
2724 }
2725 \msg_new:nnn { hooks } { extra-pop-label }
2726 {
2727 Extra~\iow_char:N \PopDefaultHookLabel. \
2728 This~command~will~be~ignored.
2729 }
2730 \msg_new:nnn { hooks } { missing-pop-label }
2731 {
2732 Missing~\iow_char:N \PopDefaultHookLabel. \
2733 The~label~'#1'~was~pushed~but~never~popped.~Something~is~wrong.
2734 }
2735 \msg_new:nnn { latex2e } { should-not-happen }
2736 {
2737 This~should~not~happen.~#1 \
2738 Please~report~at~https://github.com/latex3/latex2e.
2739 }
2740 \msg_new:nnn { hooks } { activate-disabled }
2741 {
2742 Cannot~ activate~ hook~ '#1'~ because~ it~ is~ disabled!
2743 }
2744 \msg_new:nnn { hooks } { cannot-remove }
2745 {
2746 Cannot~remove~chunk~'#2'~from~hook~'#1'~because~
2747 \__hook_if_structure_exist:nTF {#1}
2748 { it~does~not~exist~in~that~hook. }
2749 { the~hook~does~not~exist. }
2750 }
2751 \msg_new:nnn { hooks } { generic-deprecated }
2752 {
2753 Generic~hook~'#1/#2/#3'~is~deprecated. \
2754 Use~hook~'#1/#3/#2'~instead.
2755 }

```

## 4.12 L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> package interface commands

**\NewHook** Declaring new hooks ...

```

\NewReversedHook 2756 \NewDocumentCommand \NewHook          { m }
\NewMirroredHookPair 2757 { \hook_new:n {#1} }
2758 \NewDocumentCommand \NewReversedHook      { m }
2759 { \hook_new_reversed:n {#1} }
2760 \NewDocumentCommand \NewMirroredHookPair { mm }
2761 { \hook_new_pair:nn {#1}{#2} }
```

(End of definition for \NewHook, \NewReversedHook, and \NewMirroredHookPair. These functions are documented on page 201.)

**\NewHookWithArguments** Declaring new hooks with arguments...

```

\NewReversedHookWithArguments 2762 <latexrelease>\IncludeInRelease{2023/06/01}{\NewHookWithArguments}
\NewMirroredHookPairWithArguments 2763 <latexrelease>          {Hooks-with-args}
2764 \NewDocumentCommand \NewHookWithArguments          { mm }
2765 { \hook_new_with_args:nn {#1} {#2} }
2766 \NewDocumentCommand \NewReversedHookWithArguments  { mm }
2767 { \hook_new_reversed_with_args:nn {#1} {#2} }
2768 \NewDocumentCommand \NewMirroredHookPairWithArguments { mmm }
2769 { \hook_new_pair_with_args:nnn {#1} {#2} {#3} }
2770 <latexrelease>\EndIncludeInRelease
2771 <latexrelease>\IncludeInRelease{2020/10/01}{\NewHookWithArguments}
2772 <latexrelease>          {Hooks-with-args}
2773 <latexrelease>\cs_new_protected:Npn \NewHookWithArguments #1 #2 { }
2774 <latexrelease>\cs_new_protected:Npn \NewReversedHookWithArguments #1 #2 { }
2775 <latexrelease>\cs_new_protected:Npn \NewMirroredHookPairWithArguments #1 #2 #3 { }
2776 <latexrelease>\EndIncludeInRelease
```

(End of definition for \NewHookWithArguments, \NewReversedHookWithArguments, and \NewMirroredHookPairWithArguments. These functions are documented on page 202.)

```

2777 <latexrelease>\IncludeInRelease{2021/06/01}{\ActivateGenericHook}
2778 <latexrelease>          {Providing-hooks}
```

**\ActivateGenericHook** Providing new hooks ...

```

2779 \NewDocumentCommand \ActivateGenericHook { m }
2780 { \hook_activate_generic:n {#1} }
```

(End of definition for \ActivateGenericHook. This function is documented on page 203.)

**\DisableGenericHook** Disabling a generic hook.

```

2781 \NewDocumentCommand \DisableGenericHook { m }
2782 { \hook_disable_generic:n {#1} }
```

(End of definition for \DisableGenericHook. This function is documented on page 202.)

```

2783 <latexrelease>\EndIncludeInRelease
2784 <latexrelease>\IncludeInRelease{2020/10/01}{\ActivateGenericHook}
2785 <latexrelease>          {Providing-hooks}
2786 <latexrelease>\def \ActivateGenericHook #1 { }
2787 <latexrelease>\def \DisableGenericHook #1 { }
2788 <latexrelease>\EndIncludeInRelease
```

**\AddToHook**

**\AddToHookWithArguments**

```
2789 <latexrelease> \IncludeInRelease{2023/06/01}{\AddToHookWithArguments}
2790 <latexrelease> {Hooks~with~args}
2791 \NewDocumentCommand \AddToHook { m o +m }
2792 { \hook_gput_code:nnn {#1} {#2} {#3} }
2793 \NewDocumentCommand \AddToHookWithArguments { m o +m }
2794 { \hook_gput_code_with_args:nnn {#1} {#2} {#3} }
2795 <latexrelease> \EndIncludeInRelease
2796 <latexrelease> \IncludeInRelease{2020/10/01}{\AddToHookWithArguments}
2797 <latexrelease> {Hooks~with~args}
2798 <latexrelease> \cs_new_protected:Npn \AddToHookWithArguments #1 #2 #3 { }
2799 <latexrelease> \EndIncludeInRelease
```

(End of definition for \AddToHook and \AddToHookWithArguments. These functions are documented on page 204.)

**\AddToHookNext**

**\AddToHookNextWithArguments**

```
2800 <latexrelease> \IncludeInRelease{2023/06/01}{\AddToHookNextWithArguments}
2801 <latexrelease> {Hooks~with~args}
2802 \NewDocumentCommand \AddToHookNext { m +m }
2803 { \hook_gput_next_code:nn {#1} {#2} }
2804 \NewDocumentCommand \AddToHookNextWithArguments { m +m }
2805 { \hook_gput_next_code_with_args:nn {#1} {#2} }
2806 <latexrelease> \EndIncludeInRelease
2807 <latexrelease> \IncludeInRelease{2020/10/01}{\AddToHookNextWithArguments}
2808 <latexrelease> {Hooks~with~args}
2809 <latexrelease> \cs_new_protected:Npn \AddToHookNextWithArguments #1 #2 { }
2810 <latexrelease> \EndIncludeInRelease
```

(End of definition for \AddToHookNext and \AddToHookNextWithArguments. These functions are documented on page 206.)

**\ClearHookNext**

```
2811 \NewDocumentCommand \ClearHookNext { m }
2812 { \hook_gclear_next_code:n {#1} }
```

(End of definition for \ClearHookNext. This function is documented on page 206.)

**\RemoveFromHook**

```
2813 \NewDocumentCommand \RemoveFromHook { m o }
2814 { \hook_gremove_code:nn {#1} {#2} }
```

(End of definition for \RemoveFromHook. This function is documented on page 205.)

**\SetDefaultHookLabel**

**\PushDefaultHookLabel**

**\PopDefaultHookLabel**

Now define a wrapper that replaces the top of the stack with the argument, and updates `\g__hook_hook_curr_name_tl` accordingly.

```
2815 \NewDocumentCommand \SetDefaultHookLabel { m }
2816 { \__hook_set_default_hook_label:n {#1} }
```

The label is only automatically updated with `\@onefilewithoptions` (`\usepackage` and `\documentclass`), but some packages, like `TikZ`, define package-like interfaces, like `\usetikzlibrary` that are wrappers around `\input`, so they inherit the default label currently in force (usually `top-level`, but it may change if loaded in another package). To provide a package-like behavior also for hooks in these files, we provide high-level access to the default label stack.

```

2817 \NewDocumentCommand \PushDefaultHookLabel { m }
2818 { \__hook_curr_name_push:n {#1} }
2819 \NewDocumentCommand \PopDefaultHookLabel { }
2820 { \__hook_curr_name_pop: }

```

The current label stack holds the labels for all files but the current one (more or less like `\@currnamestack`), and the current label token list, `\g__hook_hook_curr_name_tl`, holds the label for the current file. However `\@pushfilename` happens before `\@currname` is set, so we need to look ahead to get the `\@currname` for the label. `expl3` also requires the current file in `\@pushfilename`, so here we abuse `\@expl@push@filename@aux@@` to do `\__hook_curr_name_push:n`.

```

2821 \cs_gset_protected:Npn \@expl@push@filename@aux@@ #1#2#3
2822 {
2823   \__hook_curr_name_push:n {#3}
2824   \str_gset:Nx \g_file_curr_name_str {#3}
2825   #1 #2 {#3}
2826 }

```

(End of definition for `\SetDefaultHookLabel`, `\PushDefaultHookLabel`, and `\PopDefaultHookLabel`. These functions are documented on page 209.)

**`\UseHook`** Avoid the overhead of `xparse` and its protection that we don't want here (since the hook should vanish without trace if empty)!

**`\UseOneTimeHook`**

**`\UseHookWithArguments`**

**`\UseOneTimeHookWithArguments`**

```

2827 <latexrelease>\IncludeInRelease{2023/06/01}{\UseHookWithArguments}
2828 <latexrelease> {Hooks-with-args}
2829 \cs_new:Npn \UseHook { \hook_use:n }
2830 \cs_new:Npn \UseOneTimeHook { \hook_use_once:n }
2831 \cs_new:Npn \UseHookWithArguments { \hook_use:nnw }
2832 \cs_new:Npn \UseOneTimeHookWithArguments { \hook_use_once:nnw }
2833 <latexrelease>\EndIncludeInRelease
2834 <latexrelease>\IncludeInRelease{2020/10/01}{\UseHookWithArguments}
2835 <latexrelease> {Hooks-with-args}
2836 <latexrelease>\cs_new:Npn \UseHookWithArguments #1 #2 { }
2837 <latexrelease>\cs_new:Npn \UseOneTimeHookWithArguments #1 #2 { }
2838 <latexrelease>\EndIncludeInRelease

```

(End of definition for `\UseHook` and others. These functions are documented on page 203.)

**`\ShowHook`**

**`\LogHook`**

```

2839 \cs_new_protected:Npn \ShowHook { \hook_show:n }
2840 \cs_new_protected:Npn \LogHook { \hook_log:n }

```

(End of definition for `\ShowHook` and `\LogHook`. These functions are documented on page 212.)

**`\DebugHooksOn`**

**`\DebugHooksOff`**

```

2841 \cs_new_protected:Npn \DebugHooksOn { \hook_debug_on: }
2842 \cs_new_protected:Npn \DebugHooksOff { \hook_debug_off: }

```

(End of definition for `\DebugHooksOn` and `\DebugHooksOff`. These functions are documented on page 213.)

**`\DeclareHookRule`**

```

2843 \NewDocumentCommand \DeclareHookRule { m m m m }
2844 { \hook_gset_rule:nnnn {#1}{#2}{#3}{#4} }

```

(End of definition for `\DeclareHookRule`. This function is documented on page 210.)

**`\DeclareDefaultHookRule`** This declaration is only supported before `\begin{document}`.

```
2845 \NewDocumentCommand \DeclareDefaultHookRule { m m m }
2846         { \hook_gset_rule:nnnn {??}{#1}{#2}{#3} }
2847 \AtOnlyPreamble\DeclareDefaultHookRule
```

(End of definition for `\DeclareDefaultHookRule`. This function is documented on page 211.)

**`\ClearHookRule`** A special setup rule that removes an existing relation. Basically `\_hook_rule\_gclear:nnn` plus fixing the property list for debugging.

*FMi: Needs perhaps an L3 interface, or maybe it should get dropped?*

```
2848 \NewDocumentCommand \ClearHookRule { m m m }
2849 { \hook_gset_rule:nnnn {#1}{#2}{unrelated}{#3} }
```

(End of definition for `\ClearHookRule`. This function is documented on page 210.)

**`\IfHookEmptyTF`** Here we avoid the overhead of `xparse`, since `\IfHookEmptyTF` is used in `\end` (that is, every L<sup>A</sup>T<sub>E</sub>X environment). As a further optimization, use `\let` rather than `\def` to avoid one expansion step.

**`\IfHookEmptyT`**  
**`\IfHookEmptyF`**

```
2850 \cs_new_eq:NN \IfHookEmptyTF \hook_if_empty:nTF
2851 \cs_new_eq:NN \IfHookEmptyT \hook_if_empty:nT
2852 \cs_new_eq:NN \IfHookEmptyF \hook_if_empty:nF
```

(End of definition for `\IfHookEmptyTF`, `\IfHookEmptyT`, and `\IfHookEmptyF`. These functions are documented on page 212.)

**`\IfHookExistsTF`** Marked for removal and no longer documented in the doc section!

*PhO: `\IfHookExistsTF` is used in `jlreq.cls`, `pxatbegshi.sty`, `pxeveryse1.sty`, `pxeveryshi.sty`, so the public name may be an alias of the internal conditional for a while. Regardless, those packages' use for `\IfHookExistsTF` is not really correct and can be changed.*

```
2853 \cs_new_eq:NN \IfHookExistsTF \_hook_if_usable:nTF
```

(End of definition for `\IfHookExistsTF`.)

## 4.13 Deprecated that needs cleanup at some point

**`\hook_disable:n`** Deprecated.

**`\hook_provide:n`** **`\cs_new_protected:Npn \hook_disable:n`**

```
2854 \cs_new_protected:Npn \hook_disable:n
2855 {
2856     \_hook_deprecated_warn:nn
2857     { hook_disable:n }
2858     { hook_disable_generic:n }
2859     \hook_disable_generic:n
2860 }
2861 \cs_new_protected:Npn \hook_provide:n
2862 {
2863     \_hook_deprecated_warn:nn
2864     { hook_provide:n }
2865     { hook_activate_generic:n }
2866     \hook_activate_generic:n
2867 }
2868 \cs_new_protected:Npn \hook_provide_reversed:n
```

```

2869 {
2870   \__hook_deprecated_warn:nn
2871   { hook_provide_reversed:n }
2872   { hook_activate_generic:n }
2873   \__hook_activate_generic_reversed:n
2874 }
2875 \cs_new_protected:Npn \hook_provide_pair:nn
2876 {
2877   \__hook_deprecated_warn:nn
2878   { hook_provide_pair:nn }
2879   { hook_activate_generic:n }
2880   \__hook_activate_generic_pair:nn
2881 }
2882 \cs_new_protected:Npn \__hook_activate_generic_reversed:n #1
2883 { \__hook_normalize_hook_args:Nn \__hook_activate_generic:nn {#1} { - } }
2884 \cs_new_protected:Npn \__hook_activate_generic_pair:nn #1#2
2885 { \hook_activate_generic:n {#1} \__hook_activate_generic_reversed:n {#2} }

```

*(End of definition for \hook\_disable:n and others.)*

```

\DisableHook   Deprecated.
\ProvideHook   2886 \cs_new_protected:Npn \DisableHook
\ProvideReversedHook 2887 {
\ProvideMirroredHookPair 2888   \__hook_deprecated_warn:nn
2889   { DisableHook }
2890   { DisableGenericHook }
2891   \hook_disable_generic:n
2892 }
2893 \cs_new_protected:Npn \ProvideHook
2894 {
2895   \__hook_deprecated_warn:nn
2896   { ProvideHook }
2897   { ActivateGenericHook }
2898   \hook_activate_generic:n
2899 }
2900 \cs_new_protected:Npn \ProvideReversedHook
2901 {
2902   \__hook_deprecated_warn:nn
2903   { ProvideReversedHook }
2904   { ActivateGenericHook }
2905   \__hook_activate_generic_reversed:n
2906 }
2907 \cs_new_protected:Npn \ProvideMirroredHookPair
2908 {
2909   \__hook_deprecated_warn:nn
2910   { ProvideMirroredHookPair }
2911   { ActivateGenericHook }
2912   \__hook_activate_generic_pair:nn
2913 }

```

*(End of definition for \DisableHook and others.)*

```

\__hook_deprecated_warn:nn Warns about a deprecation, telling what should be used instead.
2914 \cs_new_protected:Npn \__hook_deprecated_warn:nn #1 #2
2915 { \msg_warning:nnnn { hooks } { deprecated } {#1} {#2} }

```

```

2916 \msg_new:nnn { hooks } { deprecated }
2917 {
2918   Command~\iow_char:N\|#1~is-deprecated-and-will-be-removed-in-a~
2919   future-release. \\ \\
2920   Use~\iow_char:N\|#2~instead.
2921 }

```

(End of definition for `\_hook_deprecated_warn:nn`.)

#### 4.14 Internal commands needed elsewhere

Here we set up a few horrible (but consistent) L<sup>A</sup>T<sub>E</sub>X<sub>2 $\epsilon$</sub>  names to allow for internal commands to be used outside this module. We have to unset the `@@` since we want double “at” sign in place of double underscores.

```

2922 <@@= >

```

```

\@expl@@@initialize@all@@
\@expl@@@hook@curr@name@pop@@
2923 \cs_new_eq:NN \@expl@@@initialize@all@@
2924   \_hook_initialize_all:
2925 \cs_new_eq:NN \@expl@@@hook@curr@name@pop@@
2926   \_hook_curr_name_pop:

```

(End of definition for `\@expl@@@initialize@all@@` and `\@expl@@@hook@curr@name@pop@@`.)

Rolling back here doesn’t undefine the interface commands as they may be used in packages without rollback functionality. So we just make them do nothing which may or may not work depending on the code usage.

```

2927 %
2928 <latexrelease> \IncludeInRelease{0000/00/00}{1thooks}
2929 <latexrelease> {The~hook~management}%
2930 <latexrelease>
2931 <latexrelease> \def \NewHook#1{}
2932 <latexrelease> \def \NewReversedHook#1{}
2933 <latexrelease> \def \NewMirroredHookPair#1#2{}
2934 <latexrelease>
2935 <latexrelease> \def \DisableGenericHook #1{}
2936 <latexrelease>
2937 <latexrelease> \long\def \AddToHookNext#1#2{}
2938 <latexrelease>
2939 <latexrelease> \def \AddToHook#1{\@gobble\AddToHook@args}
2940 <latexrelease> \providecommand\@gobble\AddToHook@args[2] [] {}
2941 <latexrelease>
2942 <latexrelease> \def \RemoveFromHook#1{\@gobble\RemoveFromHook@arg}
2943 <latexrelease> \providecommand\@gobble\RemoveFromHook@arg[1] [] {}
2944 <latexrelease>
2945 <latexrelease> \def \UseHook #1{}
2946 <latexrelease> \def \UseOneTimeHook #1{}
2947 <latexrelease> \def \ShowHook #1{}
2948 <latexrelease> \let \DebugHooksOn \@empty
2949 <latexrelease> \let \DebugHooksOff \@empty
2950 <latexrelease>
2951 <latexrelease> \def \DeclareHookRule #1#2#3#4{}
2952 <latexrelease> \def \DeclareDefaultHookRule #1#2#3{}
2953 <latexrelease> \def \ClearHookRule #1#2#3{}

```

If the hook management is not provided we make the test for existence false and the test for empty true in the hope that this is most of the time reasonable. If not a package would need to guard against running in an old kernel.

```

2954 <latexrelease>\long\def \IfHookExistsTF #1#2#3{#3}
2955 <latexrelease>\long\def \IfHookEmptyTF #1#2#3{#2}
2956 <latexrelease>
2957 <latexrelease>\EndModuleRelease
2958 <@@=hook>

2959 <latexrelease>\cs:w __hook_rollback_tidying: \cs_end:
2960 <latexrelease>\bool_lazy_and:nnT
2961 <latexrelease>    { \int_compare_p:nNn { \sourceLaTeXdate } > { 20230600 } }
2962 <latexrelease>    { \int_compare_p:nNn { \requestedLaTeXdate } < { 20230601 } }
2963 <latexrelease> {
2964 <latexrelease>     \cs_gset_protected:Npn \__hook_rollback_tidying:
2965 <latexrelease>     {
2966 <latexrelease>         \@latex@error { Rollback-code-executed-twice }
2967 <latexrelease>         {
2968 <latexrelease>             Something~went~wrong~(unless~this~was~
2969 <latexrelease>             done~on~purpose~in~a~testing~environment).
2970 <latexrelease>         }
2971 <latexrelease>         \use_none:nnnn
2972 <latexrelease>     }
2973 <latexrelease> \cs_set:Npn \__hook_tmp:w #1 #2
2974 <latexrelease> {
2975 <latexrelease>     \__hook_tl_gset:cx { __hook#1~#2 }
2976 <latexrelease>     {
2977 <latexrelease>         \exp_args:No \exp_not:o
2978 <latexrelease>         {
2979 <latexrelease>             \cs:w __hook#1~#2 \exp_last_unbraced:Ne \cs_end:
2980 <latexrelease>             { \__hook_braced_cs_parameter:n
2981 <latexrelease>               { __hook#1~#2 } }
2982 <latexrelease>         }
2983 <latexrelease>     }
2984 <latexrelease> }
2985 <latexrelease> \seq_map_inline:Nn \g__hook_all_seq
2986 <latexrelease> {
2987 <latexrelease>     \exp_after:wN \cs_gset_nopar:Npn
2988 <latexrelease>     \cs:w g__hook_#1_code_prop \exp_args:NNo \exp_args:No
2989 <latexrelease>     \cs_end: { \cs:w g__hook_#1_code_prop \cs_end: }
2990 <latexrelease>     \__hook_tmp:w { _toplevel } {#1}
2991 <latexrelease>     \__hook_tmp:w { _next } {#1}
2992 <latexrelease> }
2993 <latexrelease> }
2994 <latexrelease> \ExplSyntaxOff
2995 </2ekernel | latexrelease>
2996 <@@=>

```

## File 09

# ltxcmdhooks.dtx

## 1 Introduction

This file implements generic hooks for (arbitrary) commands. In theory every command `\<name>` offers now two associated hooks to which code can be added using `\AddToHook`,<sup>13</sup> `\AddToHookNext`, `\AddToHookWithArguments`, and `\AddToHookNextWithArguments`.<sup>14</sup>

However, this is only true “in theory”. In practice there are a number of restrictions that makes it impossible to use such generic command hooks in a number of cases, so please read all of section 2 to understand what may prevent you from using them successfully.

The generic command hooks are:

**cmd/<name>/before** This hook is executed at the very start of the command, right after its arguments (if any) are parsed. The hook `<code>` runs in the command inside a call to `\UseHookWithArguments`. Any code added to this hook using `\AddToHookWithArguments` or `\AddToHookNextWithArguments` can access the command’s arguments using `#1`, `#2`, etc., up to the number of arguments of the command. If `\AddToHook` or `\AddToHookNext` are used, the arguments cannot be accessed (see the `lthooks` documentation<sup>15</sup> on hooks with arguments).

**cmd/<name>/after** This hook is similar to **cmd/<name>/before**, but it is executed at the very end of the command body. This hook is implemented as a reversed hook.

The hooks are not physically present before `\begin{document}`<sup>16</sup> (i.e., using a command in the preamble will never execute the hook) and if nobody has declared any code for them, then they are not added to the command code ever. For example, if we have the following definition

```
\newcommand\foo[2]{Code #1 for #2!}
```

then executing `\foo{A}{B}` will simply run `Code_A_for_B!` as it was always the case. However, if somebody, somewhere (e.g., in a package) adds

```
\AddToHook{cmd/foo/before}{<before code>}
```

then, after `\begin{document}` the definition of `\foo` will be:

```
\renewcommand\foo[2]{%
  \UseHookWithArguments{cmd/foo/before}{2}{#1}{#2}%
  Code #1 for #2!}
```

and similarly `\AddToHook{cmd/foo/after}{<after code>}` alters the definition to

---

<sup>13</sup>In this documentation, when something is being said about `\AddToHook`, the same will be valid for `\AddToHookWithArguments`, unless that particular paragraph is highlighting the differences between both. The same is true for the other hook-related functions and their `...WithArguments` counterparts.

<sup>14</sup>In practice this is not supported for all types of commands, see section 2.2 for the restrictions that apply and what happens if one tries to use this with commands for which this is not supported.

<sup>15</sup>`texdoc lthooks-doc`

<sup>16</sup>More specifically, they are inserted in the commands after the `begindocument` hook, so they are also not present while `LATEX` is reading the `.aux` file.

```

\renewcommand\foo[2]{%
  Code #1 for #2!%
  \UseHookWithArguments{cmd/foo/after}{2}{#1}{#2}}

```

In other words, the mechanism is similar to what `etoolbox` offers with `\pretocmd` and `\apptocmd` with the important differences

- that code can be prepended or appended (i.e., added to the hooks) even if the command itself is not (yet) defined, because the defining package has not been loaded at this point;
- and that by using the hook management interface it is now possible to define how the code chunks added in these places are ordered, if different packages want to add code at these points.

## 2 Restrictions and Operational details

Adding arbitrary material to commands is tricky because most of the time we do not know what the macro expects as arguments when expanding and  $\text{\TeX}$  doesn't have a reliable way to see that, so some guesswork has to be employed.

We can do this in most cases when commands are defined using `\NewDocumentCommand` or `\newcommand` (with a few exceptions). For commands defined with `\def` the situation is less good. Common cases where the command hooks will not work are:

- Commands that use special catcode settings within their definition. In that case it is usually not possible to augment the definition (see 2.1).
- If a command is defined while `\ExplSyntaxOn` is in force **and** the command contains `~` characters to represent spaces, then it can't be patched to include the command hooks. In fact in some very special circumstances you might even get a low-level error rather than the information that the command can't be patched (see, for example, <https://github.com/latex3/latex2e/issues/1430>).
- Commands that have arguments as far as the user is concerned (e.g., `\section` or `\caption`), but are defined in a way that these arguments are not read by the user level command but only later during the processing. In that case the `after` hook doesn't work at all. The before hook only works with `\AddToHook` but not with `\AddToHookWithArguments` because the arguments haven't been read at that point where the hook is patched in. See section 2.2.
- Adding a specific generic command hook is only attempted once per command, thus after redefining a command such hooks will no longer be there and will also not being re-added, see section 2.1.1.

All this means that you have to have a good understanding of how commands are defined when you attempt to make use of such hooks and something goes wrong. What can help in that case is to turn on `\DebugHooksOn` in which case you get much more (low-level) details on why something fails and what was tried to enable the hooks.

## 2.1 Patching

The code here tries to find out if a command was defined with `\newcommand` or `\DeclareRobustCommand` or `\NewDocumentCommand`, and if so it *assumes* that the argument specification of the command is as expected (which is not fail-proof, if someone redefines the internals of these commands in devious ways, but is a reasonable assumption).

If the command is one of the defined types, the code here does a sandboxed expansion of the command such that it can be redefined again exactly as before, but with the hook code added.

If however the command is not a known type (it was defined with `\def`, for example), then the code uses an approach similar to `etoolbox`'s `\patchcmd` to retokenize the command with the hook code in place. This procedure, however, is more likely to fail if the catcode settings are not the same as the ones at the time of command's definition, so not always adding a hook to a command will work.

### 2.1.1 Timing

When `\AddToHook` (or its `expl3` equivalent) is called with a generic `cmd` hook, say, `cmd/foo/before`, for the first time (that is, no code was added to that same hook before), in the preamble of a document, it will store a patch instruction for that command until `\begin{document}`, and only then all the commands which had hooks added will be patched in one go. That means that no command in the preamble will have hooks patched into them.

At `\begin{document}` all the delayed patches will be executed, and if the command doesn't exist the code is still added to the hook, but it will not be executed. After `\begin{document}`, when `\AddToHook` is called with a generic `cmd` hook the first time, the command will be immediately patched to include the hook, and if it doesn't exist or if it can't be patched for any reason, an error is thrown; if `\AddToHook` was already used in the preamble no new patching is attempted.

This has the consequence that a command defined or redefined after `\begin{document}` only uses generic `cmd` hook code if `\AddToHook` is called for the first time after the definition is made, or if the command explicitly uses the generic hook in its definition by declaring it with `\NewHookPair` adding `\UseHook` as part of the code.<sup>17</sup>

## 2.2 Commands that look ahead

Some commands are defined in different “steps” and they look ahead in the input stream to find more arguments. If you try to add some code to the `cmd/<name>/after` hook of such command, it will not work, and it is not possible to detect that programmatically, so the user has to know (or find out) which commands can or cannot have hooks attached to them.

One good example is the `\section` command. You can add something to the `cmd/section/before` hook (but only with `\AddToHook` not `\AddToHookWithArguments`), but if you try to add anything to the `cmd/section/after` hook, `\section` will no longer work at all. That happens because the `\section` macro takes no argument, but instead calls a few internal `LATEX` macros to look for the optional and mandatory arguments. By adding code to the `cmd/section/after` hook, you get in the way of that scanning.

---

<sup>17</sup>We might change this behavior in the main document slightly after gaining some usage experience.

In such a case, where it is known that a specific generic command hook does not work if code is added to it, the package author can add a `\DisableGenericHook`<sup>18</sup> declaration to prevent this from happening in user documents and thereby avoiding obscure errors.

### 3 Package Author Interface

The `cmd` hooks are, by default, available for all commands that can be patched to add the hooks. For some commands, however, the very beginning or the very end of the code is not the best place to put the hooks, for example, if the command looks ahead for arguments (see section 2.2).

If you are a package author and you want to add the hooks to your own commands in the proper position you can define the command and manually add the `\UseHookWithArguments` calls inside the command in the proper positions, and manually define the hooks with `\NewHookWithArguments` or `\NewReversedHookWithArguments`. When the hooks are explicitly defined, patching is not attempted so you can make sure your command works properly. For example, an (admittedly not really useful) command that typesets its contents in a framed box with width optionally given in parentheses:

```
\newcommand\fancybox{\@ifnextchar({\@fancybox}{\@fancybox(5cm)}}
\def\@fancybox(#1)#2{\fbox{\parbox{#1}{#2}}}
```

If you try that definition, then add some code after it with

```
\AddToHook{cmd/fancybox/after}{<code>}
```

and then use the `\fancybox` command you will see that it will be completely broken, because the hook will get executed in the middle of parsing for optional (...) argument.

If, on the other hand, you want to add hooks to your command you can do something like:

```
\newcommand\fancybox{\@ifnextchar({\@fancybox}{\@fancybox(5cm)}}
\def\@fancybox(#1)#2{\fbox{%
    \UseHookWithArguments{cmd/fancybox/before}{2}{#1}{#2}%
    \parbox{#1}{#2}%
    \UseHookWithArguments{cmd/fancybox/after}{2}{#1}{#2}}}
\NewHookWithArguments{cmd/fancybox/before}{2}
\NewReversedHookWithArguments{cmd/fancybox/after}{2}
```

then the hooks will be executed where they should and no patching will be attempted. It is important that the hooks are declared with `\NewHookWithArguments` or `\NewReversedHookWithArguments`, otherwise the command hook code will try to patch the command. Note also that the call to `\UseHookWithArguments{cmd/fancybox/before}` does not need to be in the definition of `\fancybox`, but anywhere it makes sense to insert it (in this case in the internal `\@fancybox`).

Alternatively, if for whatever reason your command does not support the generic hooks provided here, you can disable a hook with `\DisableGenericHook`<sup>19</sup>, so that when someone tries to add code to it they will get an error. Or if you don't want the error, you can simply declare the hook with `\NewHook` and never use it.

<sup>18</sup>Please use `\DisableGenericHook` if at all, only on hooks that you “own”, i.e., for commands your package or class defines and not second guess whether or not hooks of other packages should get disabled!

<sup>19</sup>Please use `\DisableGenericHook` if at all, only on hooks that you “own”, i.e., for commands your package or class defines and not second guess whether or not hooks of other packages should get disabled!

The above approach is useful for really complex commands where for one or the other reason the hooks can't be placed at the very beginning and end of the command body and some hand-crafting is needed. However, in the example above the real (and in fact only) issue is the cascading argument parsing in the style developed long ago in L<sup>A</sup>T<sub>E</sub>X 2.09. Thus, a much simpler solution for this case is to replace it with the modern `\NewDocumentCommand` syntax and define the command as follows:

```
\DeclareDocumentCommand\fancybox{D() {5cm}m}{\fbox{\parbox{#1}{#2}}}
```

If you do that then both hooks automatically work and are patched into the right places.

### 3.1 Arguments and redefining commands

The code in `ltxcmdhooks` does its best to find out how many arguments a given command has, and to insert the appropriate call to `\UseHookWithArguments`, so that the arguments seen by the hook are exactly those grabbed by the command (the hook, after all, is a macro call, so the arguments have to be placed in the right order, or they won't match).

When using the package writer interface, as discussed in section 3, to change the position of the hooks in your commands, you are also free to change how the hook code in your command sees its arguments. When a `cmd` hook is declared with `\NewHook` (or `\NewHookWithArguments` or other variations of that), it loses its “generic” nature and works as a regular hook. This means that you may choose to declare it without arguments regardless if the command takes arguments or not, or declare it with arguments, even if the command takes none.

However, this flexibility should not be abused. When using a nonstandard configuration for the hook arguments, think reasonably: a user will expect that the argument `#1` in the hook corresponds to the argument's first argument, and so on. Any other configuration is likely to cause confusion and, if used, will have to be well documented.

This flexibility, however, allows you to “correct” the arguments for the hooks. For example, L<sup>A</sup>T<sub>E</sub>X's `\refstepcounter` has a single argument, the name of the counter. The `cleveref` package adds an optional argument to `\refstepcounter`, making the name of the counter argument `#2`. If the author of `cleveref` wanted, for whatever reason, to add hooks to `\refstepcounter`, to preserve compatibility he could write something along the lines of:

```
\NewHookWithArguments{cmd/refstepcounter/before}{1}
\renewcommand\refstepcounter[2][<default>]{%
  \UseHookWithArguments{cmd/refstepcounter/before}{1}{#2}%
  <code for \refstepcounter>}
```

so that the mandatory argument, which is arg `#2` in the definition, would still be seen as `#1` in the hook code.

Another possibility would be to place the optional argument as the second argument for the hook, so that people looking for it would be able to use it. In either case, it would have to be well documented to cause as little confusion as possible.

## 4 The Implementation

### 4.1 Execution plan

To add `before` and `after` hooks to a command we will need to peek into the definition of a command, which is always a tricky thing to do. Some cases are easy because we

know how the command was defined, so we can assume how its  $\langle parameter\ text \rangle$  looks like (for example a command defined with `\newcommand` may have an optional argument followed by a run of mandatory arguments), so we can just expand that command and make it grab `#1`, `#2`, etc. as arguments and define it all back with the hooks added.

Life’s usually not that easy, so with some commands we can’t do that (a `#1` might as well be `#12112` instead of the expected `#6112`, for example) so we need to resort to “patching” the command: read its `\meaning`, and tokenize it again with `\scantokens` and hope for the best.

So the overall plan is:

1. Check if a command is of a known type (that is, defined with `\newcommand`<sup>20</sup>, `\DeclareRobustCommand`, or `\New(Expandable)DocumentCommand`), and if is, take appropriate action.
2. If the command is not a known type, we’ll check if the command can be patched. Two things will prevent a command from being patched: if it was defined in a nonstandard catcode setting, or if it is an internal `expl3` command with `__\module` in its name, in which case we refuse to patch.
3. If the command was defined in nonstandard catcode settings, we will try a few standard ones to try our best to carry out the patching. If this doesn’t help either, the code will give up and throw an error.

```

1 <@@=hook>
2 <*2ekernel | latexrelease>
3 \ExplSyntaxOn
4 <latexrelease> \NewModuleRelease{2021/06/01}{ltxcmdhooks}
5 <latexrelease> {The~hook~management~system~for~commands}
```

## 4.2 Variables

`\g_hook_patch_action_list_tl` Pairs of `\if<cmd>...\patch<cmd>` to be used with `\robust@command@act` when looking for a known patching rule. This token list is exposed because we see some future applications (with very specialized packages, such as `etoolbox` that may want to extend the pairs processed. It is not meant for general use which is why it is not documented in the interface documentation above.

```
6 \tl_new:N \g_hook_patch_action_list_tl
```

(End of definition for `\g_hook_patch_action_list_tl`.)

`\l__hook_patch_num_args_int` The number of arguments in a macro being patched.

```
7 \int_new:N \l__hook_patch_num_args_int
```

(End of definition for `\l__hook_patch_num_args_int`.)

`\l__hook_patch_prefixes_tl` The prefixes and parameters of the definition for the macro being patched.

```

8 \tl_new:N \l__hook_patch_prefixes_tl
9 \tl_new:N \l__hook_param_text_tl
10 \tl_new:N \l__hook_replace_text_tl
```

<sup>20</sup>It’s not always possible to reliably detect this case because a command defined with no optional argument is indistinguishable from a `\defed` command.

(End of definition for `\l__hook_patch_prefixes_tl`, `\l__hook_param_text_tl`, and `\l__hook_replace_text_tl`.)

`\c__hook_hash_tl` `\c__hook_hashes_tl` Two constant token lists that contain one and two parameter tokens.

```
11 \tl_const:Nn \c__hook_hash_tl { # }
12 \tl_const:Nn \c__hook_hashes_tl { # # }
```

(End of definition for `\c__hook_hash_tl` and `\c__hook_hashes_tl`.)

`\__hook_exp_not:NN` `\__hook_def_cmd:w` Two temporary macros that change depending on the macro being patched.

```
13 \cs_new_eq:NN \__hook_exp_not:NN ?
14 \cs_new_eq:NN \__hook_def_cmd:w ?
```

(End of definition for `\__hook_exp_not:NN` and `\__hook_def_cmd:w`.)

`\q__hook_recursion_tail` `\q__hook_recursion_stop` Internal quarks for recursion: they can't appear in any macro being patched.

```
15 \quark_new:N \q__hook_recursion_tail
16 \quark_new:N \q__hook_recursion_stop
```

(End of definition for `\q__hook_recursion_tail` and `\q__hook_recursion_stop`.)

`\g__hook_delayed_patches_prop` A list containing the patches delayed to `\begin{document}`, so that patching is not attempted twice.

```
17 \prop_new:N \g__hook_delayed_patches_prop
```

(End of definition for `\g__hook_delayed_patches_prop`.)

`\__hook_patch_debug:x` A helper for patching debug info.

```
18 \cs_new_protected:Npn \__hook_patch_debug:x #1
19 { \__hook_debug:n { \iow_term:x { [lthooks]~#1 } } }
```

(End of definition for `\__hook_patch_debug:x`.)

### 4.3 Variants

`\tl_rescan:nV` `expl3` function variants used throughout the code.

```
20 \cs_generate_variant:Nn \tl_rescan:nn { nV }
```

(End of definition for `\tl_rescan:nV`.)

### 4.4 Patching or delaying

Before `\begin{document}` all patching is delayed.

`\__hook_try_put_cmd_hook:n` `\__hook_try_put_cmd_hook:w` This function is called from within `\AddToHook`, when code is first added to a generic `cmd` hook. If it is called within in the preamble, it delays the action until `\begin{document}`; otherwise it tries to update the hook.

```
21 <latexrelease>\IncludeInRelease{2024/12/22}{\__hook_try_put_cmd_hook:n}%
22 <latexrelease>{Don't~define~command}
23 \cs_new_protected:Npn \__hook_try_put_cmd_hook:n #1
24 { \__hook_try_put_cmd_hook:w #1 / / / \s__hook_mark {#1} }
25 \cs_new_protected:Npn \__hook_try_put_cmd_hook:w
26 #1 / #2 / #3 / #4 \s__hook_mark #5
27 {
28 \__hook_debug:n { \iow_term:n { ->~Adding~cmd~hook~to~'#2'~(#{3}): } }
```

`\__hook_patch_cmd_or_delay:Nnn` expects the command to be patched as its first argument so we need to construct it from its name (`#2`). However, at this moment it may not exist yet, so using `\cs:w` would incorrectly turn it from “undefined” into `\relax`. We therefore use the following curious construction: we start a group and expand out of it to call `\cs:w`. If the command is now changed to `\relax` the `\group_end:` will undo that change, but the token is nevertheless there to be consumed by `\__hook_patch_cmd_or_delay:Nnn`.

```

29   \group_begin:
30   \exp_after:wN
31   \group_end:
32   \exp_after:wN
33   \__hook_patch_cmd_or_delay:Nnn
34   \cs:w #2\cs_end:
35   {#2} {#3}
36 }
37 <latexrelease>\EndIncludeInRelease

38 <latexrelease>\IncludeInRelease{2021/11/15}{\__hook_try_put_cmd_hook:n}%
39 <latexrelease>          {Standardise-generic-hook-names}
40 <latexrelease>\cs_new_protected:Npn \__hook_try_put_cmd_hook:n #1
41 <latexrelease> { \__hook_try_put_cmd_hook:w #1 / / / \s__hook_mark {#1} }
42 <latexrelease>\cs_new_protected:Npn \__hook_try_put_cmd_hook:w
43 <latexrelease>      #1 / #2 / #3 / #4 \s__hook_mark #5
44 <latexrelease> {
45 <latexrelease>   \__hook_debug:n { \iow_term:n { ->~Adding~cmd~hook~to~'~#2'~(#3): } }
46 <latexrelease>   \exp_args:Nc \__hook_patch_cmd_or_delay:Nnn {#2} {#2} {#3}
47 <latexrelease> }
48 <latexrelease>\EndIncludeInRelease

49 <latexrelease>\IncludeInRelease{2021/06/01}{\__hook_try_put_cmd_hook:n}%
50 <latexrelease>          {Standardise-generic-hook-names}
51 <latexrelease>\cs_new_protected:Npn \__hook_try_put_cmd_hook:n #1
52 <latexrelease> { \__hook_try_put_cmd_hook:w #1 / / / \s__hook_mark {#1} }
53 <latexrelease>\cs_new_protected:Npn \__hook_try_put_cmd_hook:w
54 <latexrelease>      #1 / #2 / #3 / #4 \s__hook_mark #5
55 <latexrelease> {
56 <latexrelease>   \__hook_debug:n { \iow_term:n { ->~Adding~cmd~hook~to~'~#2'~(#3): } }
57 <latexrelease>   \str_case:nnTF {#3}
58 <latexrelease>     { { before } { } } { after } { } }
59 <latexrelease>     { \exp_args:Nc \__hook_patch_cmd_or_delay:Nnn {#2} {#2} {#3} }
60 <latexrelease>     { \msg_error:nnnn { hooks } { wrong-cmd-hook } {#2} {#3} }
61 <latexrelease> }
62 <latexrelease>\EndIncludeInRelease

```

(End of definition for `\__hook_try_put_cmd_hook:n` and `\__hook_try_put_cmd_hook:w`.)

`\__hook_patch_cmd_or_delay:Nnn`  
`\__hook_cmd_begindocument_code:`

In the preamble, `\__hook_patch_cmd_or_delay:Nnn` just adds the patch instruction to a property list to be executed later.

```

63 \cs_new_protected:Npn \__hook_patch_cmd_or_delay:Nnn #1 #2 #3
64 {
65   \__hook_debug:n { \iow_term:n { ->~Add~generic~cmd~hook~for~#2~(#3). } }
66   \__hook_debug:n
67   { \iow_term:n { !~In-the-preamble:~delaying. } }
68   \prop_gput:Nnn \g__hook_delayed_patches_prop { #2 / #3 }
69   { \__hook_cmd_try_patch:nn {#2} {#3} }

```

```
70 }
```

The delayed patches are added to a property list to prevent duplication, and the code stored in the property list for each key is executed. The function `\__hook_patch_cmd_or_delay:Nnn` is also redefined to be `\__hook_patch_command:Nnn` so that no further delaying is attempted.

```
71 \cs_new_protected:Npn \__hook_cmd_begindocument_code:
72 {
73   \cs_gset_eq:NN \__hook_patch_cmd_or_delay:Nnn \__hook_patch_command:Nnn
74   \prop_map_function:NN \g__hook_delayed_patches_prop { \use_i:nn }
75   \prop_gclear:N \g__hook_delayed_patches_prop
76   \cs_undefine:N \__hook_cmd_begindocument_code:
77 }
78 \g@addto@macro \@kernel@after@begindocument
79 { \__hook_cmd_begindocument_code: }
```

(End of definition for `\__hook_patch_cmd_or_delay:Nnn` and `\__hook_cmd_begindocument_code:.`)

```
\__hook_cmd_try_patch:nn
```

At `\begin{document}` tries patching the command if the hook was not manually created in the meantime. If the document does not exist, no error is raised here as it may hook into a package that wasn't loaded. Hooks added to commands in the document body still raise an error if the command is not defined.

```
80 \cs_new_protected:Npn \__hook_cmd_try_patch:nn #1 #2
81 {
82   \__hook_debug:n
83   { \iow_term:x { ->~\string\begin{document}-try-cmd / #1 / #2. } }
84   \__hook_if_declared:nTF { cmd / #1 / #2 }
85   {
86     \__hook_debug:n
87     { \iow_term:n { .->~Giving-up:~hook~already~created. } }
88   }
89   {
90     \cs_if_exist:cT {#1}
91     { \exp_args:Nc \__hook_patch_command:Nnn {#1} {#1} {#2} }
92   }
93 }
```

(End of definition for `\__hook_cmd_try_patch:nn.`)

## 4.5 Patching commands

```
\__hook_patch_command:Nnn
\__hook_patch_check:NNnn
\__hook_if_public_command:NTF
\__hook_if_public_command:w
```

`\__hook_patch_command:Nnn` will do some sanity checks on the argument to detect if it is possible to add hooks to the command, and raises an error otherwise. If the command can contain hooks, then it uses `\robust@command@act` to find out what type is the command, and patch it accordingly.

```
94 \cs_new_protected:Npn \__hook_patch_command:Nnn #1 #2 #3
95 {
96   \__hook_patch_debug:x { analyzing~'\token_to_str:N #1' }
97   \__hook_patch_debug:x { \token_to_str:N #1 = \token_to_meaning:N #1 }
98   \__hook_patch_check:NNnn \cs_if_exist:NTF #1 { undef }
99   {
100     \__hook_patch_debug:x { ++~control~sequence~is~defined }
101     \__hook_patch_check:NNnn \token_if_macro:NTF #1 { macro }
102     {
```

```

103         \__hook_patch_debug:x { ++~control~sequence~is~a~macro }
104         \__hook_patch_check:NNnn \__hook_if_public_command:NTF #1 { expl3 }
105         {
106             \__hook_patch_debug:x { ++~macro~is~not~private }
107             \robust@command@act
108             \g_hook_patch_action_list_tl #1
109             \__hook_retokenize_patch:Nnn { #1 {#2} {#3} }
110         }
111     }
112 }
113 }

```

And here's the auxiliary used above:

```

114 \cs_new_protected:Npn \__hook_patch_check:NNnn #1 #2 #3 #4
115 {
116     #1 #2 {#4}
117     {
118         \msg_error:nxxx { hooks } { cant-patch }
119         { \token_to_str:N #2 } {#3}
120     }
121 }

```

and a conditional `\__hook_if_public_command:NTF` to check if a command has `__` in its name (no other checking is performed). Primitives with `:D` in their name could be included here, but they are already discarded in the `\token_if_macro:NTF` test above.

```

122 \use:x
123 {
124     \prg_new_protected_conditional:Npnn
125     \exp_not:N \__hook_if_public_command:N ##1 { TF }
126     {
127         \exp_not:N \exp_last_unbraced:Nf
128         \exp_not:N \__hook_if_public_command:w
129         { \exp_not:N \cs_to_str:N ##1 }
130         \tl_to_str:n { _ _ } \s__hook_mark
131     }
132 }
133 \exp_last_unbraced:NNNno
134 \cs_new_protected:Npn \__hook_if_public_command:w
135     #1 \tl_to_str:n { _ _ } #2 \s__hook_mark
136 {
137     \tl_if_empty:nTF {#2}
138     { \prg_return_true: }
139     { \prg_return_false: }
140 }

```

(End of definition for `\__hook_patch_command:Nnn` and others.)

#### 4.5.1 Patching by expansion and redefinition

`\g_hook_patch_action_list_tl` This is the list of known command types and the function that patches the command hooks into them. The conditionals are taken from `\ShowCommand`, `\NewCommandCopy` and `\__kernel_cmd_if_xparse:NTF` defined in `ltxcmd`.

```

141 \tl_gset:Nn \g_hook_patch_action_list_tl
142 {
143     { \@if@DeclareRobustCommand \__hook_patch_DeclareRobustCommand:Nnn }

```

```

144     { \@ifnewcommand \__hook_patch_newcommand:Nnn }
145     { \__kernel_cmd_if_xparse:NTF \__hook_cmd_patch_xparse:Nnn }
146   }

```

*(End of definition for \g\_hook\_patch\_action\_list\_tl.)*

\\_\_hook\_patch\_DeclareRobustCommand:Nnn

At this point we know that the commands can be patched by expanding then redefining. These are the cases of commands defined with \newcommand with an optional argument or with \DeclareRobustCommand.

With \\_\_hook\_patch\_DeclareRobustCommand:Nnn we check if the command has an optional argument (with a test counter-intuitively called \@ifnewcommand; also make sure the command doesn't take args by calling \robust@command@chk@safe). If so, we pass the patching action to \\_\_hook\_patch\_newcommand:Nnn, otherwise we call the patching engine \\_\_hook\_patch\_expand\_redefine:NNnn with a \c\_false\_bool to indicate that there is no optional argument.

```

147 \cs_new_protected:Npn \__hook_patch_DeclareRobustCommand:Nnn #1
148 {
149   \exp_args:Nc \__hook_patch_DeclareRobustCommand_aux:Nnn
150   { \cs_to_str:N #1 ~ }
151 }
152 \cs_new_protected:Npn \__hook_patch_DeclareRobustCommand_aux:Nnn #1
153 {
154   \robust@command@chk@safe #1
155   { \@ifnewcommand #1 }
156   { \use_ii:nn }
157   { \__hook_patch_newcommand:Nnn }
158   { \__hook_patch_expand_redefine:NNnn \c_false_bool }
159   #1
160 }

```

*(End of definition for \\_\_hook\_patch\_DeclareRobustCommand:Nnn.)*

\\_\_hook\_patch\_newcommand:Nnn

If the command was defined with \newcommand and an optional argument, call the patching engine with a \c\_true\_bool to flag the presence of an optional argument, and with \command to patch the actual code for \command.

```

161 \cs_new_protected:Npn \__hook_patch_newcommand:Nnn #1
162 {
163   \exp_args:NNc \__hook_patch_expand_redefine:NNnn \c_true_bool
164   { \c_backslash_str \cs_to_str:N #1 }
165 }

```

*(End of definition for \\_\_hook\_patch\_newcommand:Nnn.)*

\\_\_hook\_cmd\_patch\_xparse:Nnn

And for commands defined by the xparse commands use this for patching:

```

166 \cs_new_protected:Npn \__hook_cmd_patch_xparse:Nnn #1
167 {
168   \exp_args:NNc \__hook_patch_expand_redefine:NNnn \c_false_bool
169   { \cs_to_str:N #1 ~ code }
170 }

```

*(End of definition for \\_\_hook\_cmd\_patch\_xparse:Nnn.)*

```

\__hook_patch_expand_redefine:NNnn
\__hook_redefine_with_hooks:NNnn
\__hook_make_prefixes:w

```

Now the real action begins. Here we have in #1 a boolean indicating if the command has a leading [...] delimited argument, in #2 the command control sequence, in #3 the name of the command (note that #1  $\neq$  \csname#2\endcsname at this point!), and in #4 the hook position, either **before** or **after**.

Patching with expansion+redefinition is trickier than it looks like at first glance. Suppose the simple definition:

```
\def\foo#1{#1##2}
```

When defined, its *<replacement text>* will be a token list containing:

```
out_param 1, mac_param #, character 2
```

Then, after expanding \foo{##1} (here ## denotes a single #6) we end up with a token list with *out\_param 1* replaced:

```
mac_param #, character 1, mac_param #, character 2
```

that is, the definition would be:

```
\def\foo#1{#1#2}
```

which obviously fails, because the original input in the definition was ## but T<sub>E</sub>X reduced that to a single parameter token #6 when carrying out the definition. That leaves no room for a clever solution with (say) \unexpanded, because anything that would double the second #6, would also (incorrectly) double the first, so there's not much to do other than a manual solution.

There are three cases we can distinguish to make things hopefully faster on simpler cases:

1. a macro with no parameters;
2. a macro with no parameter tokens in its definition;
3. a macro with parameters *and* parameter tokens.

The first case is trivial: if the macro has no parameters, we can just use \unexpanded around it, and if there is a parameter token in it, it is handled correctly (the macro can be treated as a t<sub>l</sub> variable).

The second case requires looking at the *<replacement text>* of the macro to see if it has a parameter token in there. If it does not, then there is no worry, and the macro can be redefined normally (without \unexpanded).

The third case, as usual, is the devious one. Here we'll have to loop through the definition token by token, and double every parameter token, so that this case can be handled like the previous one.

```

171 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_patch_expand_redefine:NNnn}
172 <latexrelease>{cmd~hooks~with~args}
173 \cs_new_protected:Npn \__hook_patch_expand_redefine:NNnn #1 #2 #3 #4
174 {
175   \__hook_patch_debug:x { ++~command~can~be~patched~without~rescanning }

```

We'll start by counting the number of arguments in the command by counting the number of characters in the `\cs_parameter_spec:N` of the macro, divided by two, and subtracting one if the command has an optional argument (that is, an extra `[]` in its `\parameter text`)).

```

176 \int_set:Nn \l__hook_patch_num_args_int
177 {
178   \exp_args:Nf \str_count:n { \__kernel_cs_parameter_spec:N #2 } / 2
179   \bool_if:NT #1 { -1 }
180 }

```

Now build two token lists:

`\l__hook_param_text_tl` will contain the `\parameter text` to be used when redefining the macro. It should be identical to the `\parameter text` used when originally defining that macro.

`\l__hook_replace_text_tl` will contain braced pairs of `\c__hook_hashes_tl<num>` to feed to the macro when expanded. This token list as well as the previous will have the first item surrounded by `[...]` in the case of an optional argument.

The use of `\c__hook_hashes_tl` here is to differentiate actual parameters in the macro from parameter tokens in the original definition of the macro. Later on, `\c__hook_hashes_tl` is either replaced by actual parameter tokens, or expanded into them.

```

181 \int_compare:nNnTF { \l__hook_patch_num_args_int } > { \c_zero_int }
182 {

```

We'll first check if the command has any parameter token in its definition (feeding it empty arguments), and set `\__hook_exp_not:n` accordingly. `\__hook_exp_not:n` will be used later to either leave `\c__hook_hashes_tl` or expand it, and also to remember the result of `\__hook_if_has_hash:nTF` to avoid testing twice (the test can be rather slow).

```

183   \tl_set:Nx \l__hook_tmpa_tl { \bool_if:NTF #1 { [] } { { } } }
184   \int_step_inline:nnn { 2 } { \l__hook_patch_num_args_int }
185   { \tl_put_right:Nn \l__hook_tmpa_tl { { } } }
186   \exp_args:NNo \exp_args:No \__hook_if_has_hash:nTF
187   { \exp_after:wN #2 \l__hook_tmpa_tl }
188   { \cs_set_eq:NN \__hook_exp_not:n \exp_not:n }
189   { \cs_set_eq:NN \__hook_exp_not:n \use:n }
190   \cs_set_protected:Npn \__hook_tmp:w ##1 ##2
191   {
192     ##1 \l__hook_param_text_tl { \use:n ##2 }
193     ##1 \l__hook_replace_text_tl { \__hook_exp_not:n {##2} }
194   }

```

Here we'll conditionally add `[...]` around the first parameter:

```

195   \bool_if:NTF #1
196   { \__hook_tmp:w \tl_set:Nx { [ \c__hook_hashes_tl 1 ] } }
197   { \__hook_tmp:w \tl_set:Nx { { \c__hook_hashes_tl 1 } } }

```

Then, for every parameter from the second, just add it normally:

```

198   \int_step_inline:nnn { 2 } { \l__hook_patch_num_args_int }
199   { \__hook_tmp:w \tl_put_right:Nx { { \c__hook_hashes_tl ##1 } } }

```

Now, if the command has any parameter token in its definition (then `\__hook_exp_not:n` is `\exp_not:n`), call `\__hook_double_hashes:n` to double them, and replace every `\c__hook_hashes_tl` by #:

```

200     \tl_set:Nx \l__hook_replace_text_tl
201     { \exp_not:N #2 \exp_not:V \l__hook_replace_text_tl }
202     \tl_set:Nx \l__hook_replace_text_tl
203     {
204         \token_if_eq_meaning:NNTF \__hook_exp_not:n \exp_not:n
205         { \exp_args:NNV \exp_args:No \__hook_double_hashes:n }
206         { \exp_args:NV \exp_not:o }
207         \l__hook_replace_text_tl
208     }

```

And now, set a few auxiliaries for the case that the macro has parameters, so it won't be passed through `\unexpanded` (twice):

```

209     \cs_set_eq:NN \__hook_def_cmd:w \tex_gdef:D
210     \cs_set_eq:NN \__hook_exp_not:NN \prg_do_nothing:
211 }
212 {

```

In the case the macro has no parameters, we'll treat it as a token list and things are much simpler (expansion control looks a bit complicated, but it's just a pair of `\exp_not:N` preventing another `\exp_not:n` from expanding):

```

213     \tl_clear:N \l__hook_param_text_tl
214     \tl_set_eq:NN \l__hook_replace_text_tl #2
215     \cs_set_eq:NN \__hook_def_cmd:w \tex_xdef:D
216     \cs_set:Npn \__hook_exp_not:NN ##1 { \exp_not:N ##1 \exp_not:N }
217 }

```

Before redefining, we need to also get the prefixes used when defining the command. Here we ensure that the `\escapechar` is printable, otherwise a macro defined with prefixes `\protected` `\long` will have it `\meaning` printed as `protectedlong`, making life unnecessarily complicated. Here the `\escapechar` is changed to /, then we loop between pairs of `/.../` extracting the prefixes.

```

218     \group_begin:
219     \int_set:Nn \tex_escapechar:D { '/' }
220     \use:x
221     {
222     \group_end:
223     \tl_set:Nx \exp_not:N \l__hook_patch_prefixes_tl
224     { \exp_not:N \__hook_make_prefixes:w \cs_prefix_spec:N #2 / / }
225     }

```

Here we redefine the hook to have the right number of arguments. Disabling the hook, undefining the `parameter` token list then calling `\__hook_make_usable:nn` are enough to redefine the hook to the extent we want. Code stored in the hook and other metadata about it are not lost in the process.

```

226     \__hook_disable:n { cmd / #3 / #4 }
227     \cs_undefine:c { c__hook_cmd / #3 / #4_parameter_tl }
228     \__hook_make_usable:nn { cmd / #3 / #4 } { \l__hook_patch_num_args_int }

```

Now call `\__hook_redefine_with_hooks:Nnnn` with the macro being redefined in #1, then `\UseHook{cmd/<name>/before}` in #2 or `\UseHook{cmd/<name>/after}` in #3 (one is always empty), and in #4 the *<replacement text>* of the macro.

```

229 \use:e
230 {
231   \_hook_redefine_with_hooks:Nnnn \exp_not:N #2
232   \str_if_eq:nnTF {#4} { after }
233   { \use_ii_i:nn }
234   { \use:nn }
235   { {
236     \_hook_exp_not:NN \exp_not:N \UseHookWithArguments
237     { cmd / #3 / #4 } { \int_use:N \l__hook_patch_num_args_int }
238     \_hook_braced_parameter:n { cmd / #3 / #4 }
239   } }
240   { { } }
241   { \_hook_exp_not:NN \exp_not:V \l__hook_replace_text_tl }
242 }

```

Finally, update the hook code.

```

243 \_hook_update_hook_code:n { cmd / #3 / #4 }
244 }
245 <latexrelease> \EndIncludeInRelease
246 <latexrelease> \IncludeInRelease{2021/06/01}{\_hook_patch_expand_redefine:NNnn}
247 <latexrelease> {cmd~hooks~with~args}
248 <latexrelease> \cs_gset_protected:Npn \_hook_patch_expand_redefine:NNnn #1 #2 #3 #4
249 <latexrelease> {
250 <latexrelease> \_hook_patch_debug:x { ++~command~can~be~patched~without~rescanning }
251 <latexrelease> \int_set:Nn \l__hook_patch_num_args_int
252 <latexrelease> {
253 <latexrelease> \exp_args:Nf \str_count:n { \_kernel_cs_parameter_spec:N #2 } / 2
254 <latexrelease> \bool_if:NT #1 { -1 }
255 <latexrelease> }
256 <latexrelease> \int_compare:nNnTF { \l__hook_patch_num_args_int } > { \c_zero_int }
257 <latexrelease> {
258 <latexrelease> \tl_set:Nx \l__hook_tmpa_tl { \bool_if:NTF #1 { [ ] } { { } } }
259 <latexrelease> \int_step_inline:nnn { 2 } { \l__hook_patch_num_args_int }
260 <latexrelease> { \tl_put_right:Nn \l__hook_tmpa_tl { { } } }
261 <latexrelease> \exp_args:NNo \exp_args:No \_hook_if_has_hash:nTF
262 <latexrelease> { \exp_after:wN #2 \l__hook_tmpa_tl }
263 <latexrelease> { \cs_set_eq:NN \_hook_exp_not:n \exp_not:n }
264 <latexrelease> { \cs_set_eq:NN \_hook_exp_not:n \use:n }
265 <latexrelease> \cs_set_protected:Npn \_hook_tmp:w ##1 ##2
266 <latexrelease> {
267 <latexrelease> ##1 \l__hook_param_text_tl { \use:n ##2 }
268 <latexrelease> ##1 \l__hook_replace_text_tl { \_hook_exp_not:n {##2} }
269 <latexrelease> }
270 <latexrelease> \bool_if:NTF #1
271 <latexrelease> { \_hook_tmp:w \tl_set:Nx { [ \c__hook_hash_tl 1 ] } }
272 <latexrelease> { \_hook_tmp:w \tl_set:Nx { { \c__hook_hash_tl 1 } } }
273 <latexrelease> \int_step_inline:nnn { 2 } { \l__hook_patch_num_args_int }
274 <latexrelease> { \_hook_tmp:w \tl_put_right:Nx { { \c__hook_hash_tl ##1 } } }
275 <latexrelease> \tl_set:Nx \l__hook_replace_text_tl
276 <latexrelease> { \exp_not:N #2 \exp_not:V \l__hook_replace_text_tl }
277 <latexrelease> \tl_set:Nx \l__hook_replace_text_tl
278 <latexrelease> {
279 <latexrelease> \token_if_eq_meaning:NNTF \_hook_exp_not:n \exp_not:n
280 <latexrelease> { \exp_args:NNV \exp_args:No \_hook_double_hashes:n }
281 <latexrelease> { \exp_args:NV \exp_not:o }

```

```

282 <latexrelease> \l__hook_replace_text_tl
283 <latexrelease> }
284 <latexrelease> \cs_set_eq:NN \__hook_def_cmd:w \tex_gdef:D
285 <latexrelease> \cs_set_eq:NN \__hook_exp_not:NN \prg_do_nothing:
286 <latexrelease> }
287 <latexrelease> {
288 <latexrelease> \tl_clear:N \l__hook_param_text_tl
289 <latexrelease> \tl_set_eq:NN \l__hook_replace_text_tl #2
290 <latexrelease> \cs_set_eq:NN \__hook_def_cmd:w \tex_xdef:D
291 <latexrelease> \cs_set:Npn \__hook_exp_not:NN ##1 { \exp_not:N ##1 \exp_not:N }
292 <latexrelease> }
293 <latexrelease> \group_begin:
294 <latexrelease> \int_set:Nn \tex_escapechar:D { ‘\ / }
295 <latexrelease> \use:x
296 <latexrelease> {
297 <latexrelease> \group_end:
298 <latexrelease> \tl_set:Nx \exp_not:N \l__hook_patch_prefixes_tl
299 <latexrelease> { \exp_not:N \__hook_make_prefixes:w \cs_prefix_spec:N #2 / / }
300 <latexrelease> }
301 <latexrelease> \use:x
302 <latexrelease> {
303 <latexrelease> \__hook_redefine_with_hooks:Nnnn \exp_not:N #2
304 <latexrelease> \str_if_eq:nnTF {#4} { after }
305 <latexrelease> { \use_ii_i:nn }
306 <latexrelease> { \use:nn }
307 <latexrelease> { { \__hook_exp_not:NN \exp_not:N \UseHook { cmd / #3 / #4 } } }
308 <latexrelease> { { } }
309 <latexrelease> { \__hook_exp_not:NN \exp_not:N \l__hook_replace_text_tl }
310 <latexrelease> }
311 <latexrelease> }
312 <latexrelease> \EndIncludeInRelease

```

Now that all the needed tools are ready, without further ado we'll redefine the command. The definition uses the prefixes gathered in `\l__hook_patch_prefixes_tl`, a primitive `\__hook_def_cmd:w` (which is `\tex_gdef:D` or `\tex_xdef:D`) to avoid adding extra prefixes, and the `<parameter text>` from `\l__hook_param_text_tl`.

Then finally, in the body of the definition, we insert #2, which is `cmd/#1/before` or empty, #4 which is the `<replacement text>`, and #3 which is `cmd/#1/after` or empty.

```

313 \cs_new_protected:Npn \__hook_redefine_with_hooks:Nnnn #1 #2 #3 #4
314 {
315   \l__hook_patch_prefixes_tl
316   \exp_after:wN \__hook_def_cmd:w
317   \exp_after:wN #1 \l__hook_param_text_tl
318   { #2 #4 #3 }
319 }

```

Here's the auxiliary that makes the prefix control sequences for the redefinition. Each item has to be `\tl_trim_spaces:n`'d because the last item (and not any other) has a trailing space.

```

320 \cs_new:Npn \__hook_make_prefixes:w / #1 /
321 {
322   \tl_if_empty:nF {#1}
323   {
324     \exp_not:c { tex_ \tl_trim_spaces:n {#1} :D }

```

```

325     \__hook_make_prefixes:w /
326   }
327 }

```

(End of definition for \\_\_hook\_patch\_expand\_redefine:NNnn, \\_\_hook\_redefine\_with\_hooks:Nnnn, and \\_\_hook\_make\_prefixes:w.)

Here are some auxiliaries for the contraption above.

\\_\_hook\_if\_has\_hash\_p:n \\_\_hook\_if\_has\_hash:nTF searches the token list #1 for a catcode 6 token, and if any is found, it returns true, and false otherwise. The searching doesn't care about preserving groups or spaces: we can ignore those safely (braces are removed) so that searching is as fast as possible.

```

328 \prg_new_conditional:Npnn \__hook_if_has_hash:n #1 { TF }
329 { \__hook_if_has_hash:w #1 ## \s__hook_mark }
330 \cs_new:Npn \__hook_if_has_hash:w #1
331 {
332   \tl_if_single_token:nTF {#1}
333   {
334     \token_if_eq_catcode:NNTF ## #1
335     { \__hook_if_has_hash_check:w }
336     { \__hook_if_has_hash:w }
337   }
338   { \__hook_if_has_hash:w #1 }
339 }
340 \cs_new:Npn \__hook_if_has_hash_check:w #1 \s__hook_mark
341 { \tl_if_empty:nTF {#1} { \prg_return_false: } { \prg_return_true: } }

```

(End of definition for \\_\_hook\_if\_has\_hash:nTF, \\_\_hook\_if\_has\_hash:w, and \\_\_hook\_if\_has\_hash\_check:w.)

\\_\_hook\_double\_hashes:n \\_\_hook\_double\_hashes:w loops through the token list #1 and duplicates any catcode 6 token, and expands tokens \ifx-equal to \c\_\_hook\_hashes\_tl, and leaves all other tokens \notexpanded with \exp\_not:N. Unfortunately pairs of explicit catcode 1 and catcode 2 character tokens are normalised to {<sub>1</sub> and }<sub>1</sub> because it's not feasible to expandably detect the character code (*maybe* it could be done using something along the lines of <https://tex.stackexchange.com/a/527538>, but it's far too much work for close to zero benefit).

\\_\_hook\_double\_hashes:w is the tail-recursive loop macro, that tests which of the three types of item is in the head of the token list.

```

342 \cs_new:Npn \__hook_double_hashes:n #1
343 { \__hook_double_hashes:w #1 \q__hook_recursion_tail \q__hook_recursion_stop }
344 \cs_new:Npn \__hook_double_hashes:w #1 \q__hook_recursion_stop
345 {
346   \tl_if_head_is_N_type:nTF {#1}
347   { \__hook_double_hashes_output:N }
348   {
349     \tl_if_head_is_group:nTF {#1}
350     { \__hook_double_hashes_group:n }
351     { \__hook_double_hashes_space:w }
352   }
353   #1 \q__hook_recursion_stop
354 }

```

`\__hook_double_hashes_output:N` checks for the end of the token list, then checks if the token is `\c__hook_hashes_tl`, and if so just leaves it.

```

355 \cs_new:Npn \__hook_double_hashes_output:N #1
356 {
357   \if_meaning:w \q__hook_recursion_tail #1
358   \__hook_double_hashes_stop:w
359   \fi:
360   \if:w ?
361     \if_meaning:w \c__hook_hash_tl #1 ! \fi:
362     \if_meaning:w \c__hook_hashes_tl #1 ! \fi:
363     ?
364   \else:

```

(this `\use_i:nnnn` uses `\fi:` and consumes `\use:n`, the whole `\if_catcode:w` block, and the `\exp_not:N`, leaving just `#1` which is `\c__hook_hashes_tl`.)

```

365   \use_i:nnnn
366   \fi:
367   \use:n
368   {

```

If `#1` is not `\c__hook_hashes_tl`, then check if its catcode is 6, and if so, leave it doubled in `\exp_not:n` and consume the following `\exp_not:N #1`.

```

369   \if_catcode:w ## \exp_not:N #1
370   \exp_after:wN \use_ii:nnnn
371   \fi:
372   \use_none:n
373   { \exp_not:n { #1 #1 } }
374 }

```

If both previous tests returned false, then leave the token unexpanded and resume the loop.

```

375   \exp_not:N #1
376   \__hook_double_hashes:w
377 }
378 \cs_new:Npn \__hook_double_hashes_stop:w #1 \q__hook_recursion_stop { \fi: }

```

Dealing with spaces and grouped tokens is trivial:

```

379 \cs_new:Npn \__hook_double_hashes_group:n #1
380 { { \__hook_double_hashes:n {#1} } \__hook_double_hashes:w }
381 \exp_last_unbraced:NNo
382 \cs_new:Npn \__hook_double_hashes_space:w \c_space_tl
383 { ~ \__hook_double_hashes:w }

```

(End of definition for `\__hook_double_hashes:n` and others.)

#### 4.5.2 Patching by retokenization

At this point we've drained the possibilities of patching a command by expansion-and-redefinition, so we have to resort to patching by retokenizing the command. Patching by retokenization is done by getting the `\meaning` of the command, doing the necessary manipulations on the generated string, and the retokenizing that again by using `\scantokens`.

Patching by retokenization is definitely a riskier business, because it relies that the tokens printed by `\meaning` produce the exact same tokens as the ones in the original

definition. That is, the catcode régime must be exactly(ish) the same, and there is no way of telling except by trial and error.

`\__hook_retokenize_patch:Nnn` This is the macro that will control the whole process. First we'll try out one final, rather trivial case, of a command with no arguments; that is, a token list. This case can be patched with the expand-and-redefine routine but it has to be the very last case tested for, because most (all?) robust commands start with a top-level macro with no arguments, so testing this first would short-circuit `\robust@command@act` and the top-level macros would be incorrectly patched. In that case, we just check if the `\cs_parameter_spec:N` is empty, and call `\__hook_patch_expand_redefine:NNnn`.

```

384 \cs_new_protected:Npn \__hook_retokenize_patch:Nnn #1 #2 #3
385 {
386   \str_if_eq:eeTF { \__kernel_cs_parameter_spec:N #1 } { }
387   { \__hook_patch_expand_redefine:NNnn \c_false_bool #1 {#2} {#3} }
388   {
389     \__hook_patch_debug:x { ..~command~can~only~be~patched~by~rescanning }

```

Otherwise, we start the actual patching by retokenization job. The code calls `\__hook_try_patch_with_catcodes:Nnnnw` with a different catcode setting:

- The current catcode setting;
- Switching the catcode of `@`;
- Switching the `expl3` syntax on or off;
- Both of the above.

If patching succeeds, `\__hook_try_patch_with_catcodes:Nnnnw` has the side-effect of patching the macro `#1` (which may be an internal from the command whose name is `#2`).

```

390   \tl_set:Nx \l__hook_tmpa_tl
391   {
392     \int_compare:nNnTF { \char_value_catcode:n {'\@ } } = { 12 }
393     { \exp_not:N \makeatletter } { \exp_not:N \makeatother }
394   }
395   \tl_set:Nx \l__hook_tmpb_tl
396   {
397     \bool_if:NTF \l__kernel_expl_bool
398     { \ExplSyntaxOff }
399     { \ExplSyntaxOn \char_set_catcode_space:n { 32 }}
400   }
401   \use:x
402   {
403     \exp_not:N \__hook_try_patch_with_catcodes:Nnnnw
404     \exp_not:n { #1 {#2} {#3} }
405     { \prg_do_nothing: }
406     { \exp_not:V \l__hook_tmpa_tl } % @
407     { \exp_not:V \l__hook_tmpb_tl } % _:
408     {
409       \exp_not:V \l__hook_tmpa_tl   % @
410       \exp_not:V \l__hook_tmpb_tl   % _:
411     }
412   }
413   \q_recursion_tail \q_recursion_stop

```

If no catcode setting succeeds, give up and raise an error. The command isn't changed in any way in that case.

```

414     {
415         \msg_error:nnxx { hooks } { cant-patch }
416         { \c_backslash_str #2 } { retok }
417     }
418 }
419 }

```

(End of definition for \\_\_hook\_retokenize\_patch:Nnn.)

\\_\_hook\_try\_patch\_with\_catcodes:Nnnnw

This function is a simple wrapper around \\_\_hook\_cmd\_if\_scanable:NnTF and \\_\_hook\_patch\_retokenize:Nnnn if the former returns `<true>`, plus some debug messages.

```

420 <latexrelease> \IncludeInRelease{2023/06/01}{\__hook_try_patch_with_catcodes:Nnnnw}
421 <latexrelease> {cmd-hooks-with-args}
422 \cs_new_protected:Npn \__hook_try_patch_with_catcodes:Nnnnw #1 #2 #3 #4
423 {
424     \quark_if_recursion_tail_stop_do:nn {#4} { \use:n }
425     \__hook_patch_debug:x { ++~trying~to~patch~by~retokenization }
426     \__hook_cmd_if_scanable:NnTF {#1} {#4}
427     {
428         \__hook_patch_debug:x { ++~macro~can~be~retokenized~cleanly }
429         \__hook_patch_debug:x { ==~retokenizing~macro~now }
430         \__hook_patch_retokenize:Nnnn #1 { cmd / #2 / #3 } {#3} {#4}
431         \use_i_delimit_by_q_recursion_stop:nw \use_none:n
432     }
433     {
434         \__hook_patch_debug:x { ---macro~cannot~be~retokenized~cleanly }
435         \__hook_try_patch_with_catcodes:Nnnnw #1 {#2} {#3}
436     }
437 }
438 <latexrelease> \EndIncludeInRelease
439 <latexrelease> \IncludeInRelease{2021/06/01}{\__hook_try_patch_with_catcodes:Nnnnw}
440 <latexrelease> {cmd-hooks-with-args}
441 <latexrelease> \cs_gset_protected:Npn \__hook_try_patch_with_catcodes:Nnnnw #1 #2 #3 #4
442 <latexrelease> {
443 <latexrelease>     \quark_if_recursion_tail_stop_do:nn {#4} { \use:n }
444 <latexrelease>     \__hook_patch_debug:x { ++~trying~to~patch~by~retokenization }
445 <latexrelease>     \__hook_cmd_if_scanable:NnTF {#1} {#4}
446 <latexrelease>     {
447 <latexrelease>         \__hook_patch_debug:x { ++~macro~can~be~retokenized~cleanly }
448 <latexrelease>         \__hook_patch_debug:x { ==~retokenizing~macro~now }
449 <latexrelease>         \__hook_patch_retokenize:Nnnn #1 {#2} {#3} {#4}
450 <latexrelease>         \use_i_delimit_by_q_recursion_stop:nw \use_none:n
451 <latexrelease>     }
452 <latexrelease>     {
453 <latexrelease>         \__hook_patch_debug:x { ---macro~cannot~be~retokenized~cleanly }
454 <latexrelease>         \__hook_try_patch_with_catcodes:Nnnnw #1 {#2} {#3}
455 <latexrelease>     }
456 <latexrelease> }
457 <latexrelease> \EndIncludeInRelease

```

(End of definition for \\_\_hook\_try\_patch\_with\_catcodes:Nnnnw.)

`\kerneltmpDoNotUse` This is an oddity required to be safe (as safe as reasonably possible) when patching the command. The entirety of

```
⟨prefixes⟩ \def ⟨cs⟩ ⟨parameter text⟩ {⟨replacement text⟩}
```

will go through `\scantokens`. The `⟨parameter text⟩` and `⟨replacement text⟩` are what we are trying to retokenize, so not much worry there. The other items, however, should “just work”, so some care is needed to not use too fancy catcode settings. Therefore we can’t use an `expl3`-named macro for `⟨cs⟩`, nor the `expl3` versions of `\def` or the `⟨prefixes⟩`. That is why the definitions that will eventually go into `\scantokens` will use the oddly (but hopefully clearly)-named `\kerneltmpDoNotUse`:

```
458 \cs_new_eq:NN \kerneltmpDoNotUse !
```

*PhO: Maybe this can be avoided by running the `⟨parameter text⟩` and the `⟨replacement text⟩` separately through `\scantokens` and then putting everything together at the end.*

(End of definition for `\kerneltmpDoNotUse`.)

`\_hook_patch_required_catcodes:` Here are the catcode settings that are *mandatory* when retokenizing commands. These are the minimum necessary settings to perform the definitions: they identify control sequences, which must be escaped with `\_0`, delimit the definition with `{\_1` and `}\_2`, and mark parameters with `\_6`. Everything else may be changed, but not these.

```
459 \cs_new_protected:Npn \_hook_patch_required_catcodes:
460 {
461   \char_set_catcode_escape:N \_
462   \char_set_catcode_group_begin:N \_
463   \char_set_catcode_group_end:N \_
464   \char_set_catcode_parameter:N \_6
465   % \int_set:Nn \tex_endlinechar:D { -1 }
466   % \int_set:Nn \tex_newlinechar:D { -1 }
467 }
```

*PhO: etoolbox sets the `\endlinechar` and `\newlinechar` when patching, but as far as I tested these didn’t make much of a difference, so I left them out for now. Maybe `\newlinechar=-1` avoids a space token being added after the definition.*

*PhO: If the patching is split by `⟨parameter text⟩` and `⟨replacement text⟩`, then only `\_#` will have to stay in that list.*

*PhO: Actually now that we patch `\UseHook{cmd/foo/before}`, all the tokens there need to have the right catcodes, so this list now includes all lowercase letters, *U* and *H*, the slash, and whatever characters in the command name... sigh...*

(End of definition for `\_hook_patch_required_catcodes:`.)

`\_hook_cmd_if_scanable:NnTF` Here we’ll do a quick test if the command being patched can in fact be retokenized with the specific catcode setting without changing in meaning. The test is straightforward:

1. apply `\meaning` to the command;
2. split the `⟨prefixes⟩`, `⟨parameter text⟩` and `⟨replacement text⟩` and arrange them as

```
⟨prefixes⟩ \def \kerneltmpDoNotUse ⟨parameter text⟩ {⟨replacement text⟩}
```

3. rescan that with the given catcode settings, and do the definition; then finally

4. compare `\kerneltmpDoNotUse` with the original command.

If both are `\ifx-equal`, the command can be safely patched.

```

468 \prg_new_protected_conditional:Npnn \__hook_cmd_if_scanable:Nn #1 #2 { TF }
469 {
470   \cs_set_eq:NN \kerneltmpDoNotUse \scan_stop:
471   \cs_set_eq:NN \__hook_tmp:w \scan_stop:
472   \use:x
473   {
474     \cs_set:Npn \__hook_tmp:w
475       #####1 \tl_to_str:n { macro: } #####2 -> #####3 \s__hook_mark
476       { #####1 \def \kerneltmpDoNotUse #####2 {#####3} }
477     \tl_set:Nx \exp_not:N \l__hook_tmpa_tl
478       { \exp_not:N \__hook_tmp:w \token_to_meaning:N #1 \s__hook_mark }
479   }
480   \tl_rescan:nV { #2 \__hook_patch_required_catcodes: } \l__hook_tmpa_tl
481   \token_if_eq_meaning:NNTF #1 \kerneltmpDoNotUse
482     { \prg_return_true: }
483     { \prg_return_false: }
484 }

```

(End of definition for `\__hook_cmd_if_scanable:NnTF`.)

`\__hook_guess_arg_count:NN`  
`\__hook_guess_arg_count:wN`  
`\__hook_guess_arg_count:nw`

Looks at the parameter text of a macro, and counts the parameters by looking at the number after a #, and checking if they are sequential. This macro assumes that all parameters are marked with hashes, and not other characters, and that there is no “trick parameter”.

```

485 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_guess_arg_count:NN}
486 <latexrelease>          {cmd~hooks~with~args}
487 \cs_new_protected:Npn \__hook_guess_arg_count:NN #1
488 {
489   \exp_after:wN \__hook_guess_arg_count:wN
490   \token_to_meaning:N #1 \s__hook_mark
491 }
492 \exp_last_unbraced:NNNNo
493 \cs_new_protected:Npx \__hook_guess_arg_count:wN
494   #1 { \tl_to_str:n { macro: } } #2 \s__hook_mark #3
495 {
496   \int_set:Nn #3
497   {
498     \exp_not:N \__hook_guess_arg_count:nw { 0 } #2
499     \c_hash_str 0 \s__hook_mark
500   }
501 }
502 \use:e
503 { \cs_new:Npn \exp_not:N \__hook_guess_arg_count:nw #1 #2 \c_hash_str #3 }
504 {
505   \int_compare:nNnTF { #1 + 1 } = {#3}
506     { \__hook_guess_arg_count:nw {#3} }
507     { #1 \__hook_use_none_delimit_by_s_mark:w }
508 }
509 <latexrelease>\EndIncludeInRelease
510 <latexrelease>\IncludeInRelease{2021/06/01}{\__hook_guess_arg_count:NN}
511 <latexrelease>          {cmd~hooks~with~args}

```

```

512 <latexrelease>\cs_undefine:N \__hook_guess_arg_count:NN
513 <latexrelease>\EndIncludeInRelease

```

(End of definition for \\_\_hook\_guess\_arg\_count:NN, \\_\_hook\_guess\_arg\_count:wN, and \\_\_hook\_guess\_arg\_count:nw.)

\\_\_hook\_patch\_retokenize:Nnnn

Then, if \\_\_hook\_cmd\_if\_scanable:NnTF returned true, we can go on and patch the command.

```

514 <latexrelease>\IncludeInRelease{2023/06/01}{\__hook_patch_retokenize:Nnnn}
515 <latexrelease>{cmd-hooks-with-args}
516 \cs_new_protected:Npn \__hook_patch_retokenize:Nnnn #1 #2 #3 #4
517 {

```

Here, when patching by retokenization, we can only guess the number of arguments of the macro.

```

518 \__hook_guess_arg_count:NN #1 \l__hook_patch_num_args_int

```

Then we redefine the hook to have the right number of arguments. Disabling the hook, undefining the `parameter` token list then calling `\__hook_make_usable:nn` are enough to redefine the hook to the extent we want. Code stored in the hook and other metadata about it are not lost in the process.

```

519 \__hook_disable:n {#2}
520 \cs_undefine:c { c__hook_#2_parameter_tl }
521 \__hook_make_usable:nn {#2} { \l__hook_patch_num_args_int }
522 \tl_set:Ne \l__hook_tmpa_tl
523 { \exp_args:Ne \tl_to_str:n { \__hook_braced_parameter:n {#2} } }
524 \use:x
525 {
526 \str_replace_all:Nnn \exp_not:N \l__hook_tmpa_tl
527 { #### } { \c_hash_str }
528 }

```

Then, make some things `\relax` to avoid lots of `\noexpand` below.

```

529 \cs_set_eq:NN \kerneltmpDoNotUse \scan_stop:
530 \cs_set_eq:NN \__hook_tmp:w \scan_stop:
531 \use:x
532 {

```

Now we'll define `\__hook_tmp:w` such that it splits the `\meaning` of the macro (`#1`) into its three parts:

```

####1. <prefixes>

####2. <parameter text>

####3. <replacement text>

```

and arrange that a complete definition, then place the `before` or `after` hooks around the `<replacement text>`: accordingly.

```

533 \cs_set:Npn \__hook_tmp:w
534 ####1 \tl_to_str:n { macro: } ####2 -> ####3 \s__hook_mark
535 {
536 ####1 \def \kerneltmpDoNotUse ####2
537 {
538 \str_if_eq:nnT {#3} { before }
539 {

```

```

540         \token_to_str:N \UseHookWithArguments {#2}
541         { \int_use:N \l__hook_patch_num_args_int }
542         \l__hook_tmpa_tl
543     }
544     ####3
545     \str_if_eq:nnT {#3} { after }
546     {
547         \token_to_str:N \UseHookWithArguments {#2}
548         { \int_use:N \l__hook_patch_num_args_int }
549         \l__hook_tmpa_tl
550     }
551 }
552 }

```

Now we just have to get the `\meaning` of the command being patched and pass it through the meat grinder above.

```

553     \tl_set:Nx \exp_not:N \l__hook_tmpa_tl
554     { \exp_not:N \__hook_tmp:w \token_to_meaning:N #1 \s__hook_mark }
555 }

```

Now rescan with the given catcode settings (overridden by the `\__hook_patch_required_catcodes:`), and implicitly (by using the rescanned token list) carry out the definition from above.

```

556     \tl_rescan:nV { #4 \__hook_patch_required_catcodes: } \l__hook_tmpa_tl

```

And to close, copy the newly-defined command into the old name and the patching is finally completed:

```

557     \cs_gset_eq:NN #1 \kerneltmpDoNotUse

```

Finally, update the hook code.

```

558     \__hook_update_hook_code:n {#2}
559 }
560 <latexrelease> \EndIncludeInRelease
561 <latexrelease> \IncludeInRelease{2021/06/01}{\__hook_patch_retokenize:Nnnn}
562 <latexrelease> {cmd~hooks~with~args}
563 <latexrelease> \cs_gset_protected:Npn \__hook_patch_retokenize:Nnnn #1 #2 #3 #4
564 <latexrelease> {
565 <latexrelease>     \cs_set_eq:NN \kerneltmpDoNotUse \scan_stop:
566 <latexrelease>     \cs_set_eq:NN \__hook_tmp:w \scan_stop:
567 <latexrelease>     \use:x
568 <latexrelease>     {
569 <latexrelease>         \cs_set:Npn \__hook_tmp:w
570 <latexrelease>             ####1 \tl_to_str:n { macro: } ####2 -> ####3 \s__hook_mark
571 <latexrelease>         {
572 <latexrelease>             ####1 \def \kerneltmpDoNotUse ####2
573 <latexrelease>             {
574 <latexrelease>                 \str_if_eq:nnT {#3} { before }
575 <latexrelease>                 { \token_to_str:N \UseHook { cmd / #2 / #3 } }
576 <latexrelease>                 ####3
577 <latexrelease>                 \str_if_eq:nnT {#3} { after }
578 <latexrelease>                 { \token_to_str:N \UseHook { cmd / #2 / #3 } }
579 <latexrelease>             }
580 <latexrelease>         }
581 <latexrelease>         \tl_set:Nx \exp_not:N \l__hook_tmpa_tl
582 <latexrelease>         { \exp_not:N \__hook_tmp:w \token_to_meaning:N #1 \s__hook_mark }

```

```

583 <latexrelease>      }
584 <latexrelease>      \tl_rescan:nV { #4 \__hook_patch_required_catcodes: } \l__hook_tmpa_tl
585 <latexrelease>      \cs_gset_eq:NN #1 \kerneltmpDoNotUse
586 <latexrelease>    }
587 <latexrelease> \EndIncludeInRelease

```

(End of definition for \\_\_hook\_patch\_retokenize:Nnnn.)

## 4.6 Messages

```

588 <latexrelease> \IncludeInRelease{2023/06/01}{wrong-cmd-hook}%
589 <latexrelease>      {Standardise-generic-hook-names}
590 <latexrelease> \EndIncludeInRelease
591 <latexrelease> \IncludeInRelease{2021/06/01}{wrong-cmd-hook}%
592 <latexrelease>      {Standardise-generic-hook-names}
593 <latexrelease> \msg_new:nnnn { hooks } { wrong-cmd-hook }
594 <latexrelease> {
595 <latexrelease>   Generic-hook~‘cmd/#1/#2’~is~invalid.
596 <latexrelease> %   The-hook-should-be~‘cmd/#1/before’~or~‘cmd/#1/after’.
597 <latexrelease> }
598 <latexrelease> {
599 <latexrelease>   You~tried~to~add~a~generic~hook~to~command~\iow_char:N \#1,~but~‘#2’~
600 <latexrelease>   is~an~invalid~component.~Only~‘before’~or~‘after’~are~allowed.
601 <latexrelease> }
602 <latexrelease> \EndIncludeInRelease
603 \msg_new:nnnn { hooks } { cant-patch }
604 {
605   Generic-hooks~cannot~be~added~to~‘#1’.
606 }
607 {
608   You~tried~to~add~a~hook~to~‘#1’,~but~LaTeX~was~unable~to~
609   patch~the~command~because~it~\__hook_unpatchable_cases:n {#2}.
610 }
611 \cs_new:Npn \__hook_unpatchable_cases:n #1
612 {
613   \str_case:nn {#1}
614   {
615     { undef } { doesn’t~exist }
616     { macro } { is~not~a~macro }
617     { expl3 } { is~a~private~expl3~macro }
618     { retok } { can’t~be~retokenized~cleanly }
619   }
620 }
621 <latexrelease> \IncludeInRelease{0000/00/00}{ltxcmdhooks}%
622 <latexrelease>      {The~hook~management~system~for~commands}
623 <latexrelease>

```

The command \\_\_hook\_cmd\_begindocument\_code: is used in an internal hook, so we need to make sure it has a harmless definition after rollback as that will not remove it from the kernel hook.

```

624 <latexrelease> \cs_set_eq:NN \__hook_cmd_begindocument_code: \prg_do_nothing:
625 <latexrelease>
626 <latexrelease> \EndModuleRelease
627 \ExplSyntaxOff

```

628 </2ekernel | latexrelease>  
629 <@@=>

# File 10

## ltsockets.dtx

### Abstract

This code implements sockets which are places in the code into which predeclared chunks of code (plugs) can be placed. Both the sockets and the plugs are “named” and each socket is assigned exactly one plug at any given time.

## 1 Introduction

A L<sup>A</sup>T<sub>E</sub>X source file is transformed into a typeset document by executing code for each command or environment in the document source. Through various steps this code transforms the input and eventually generates typeset output appearing in a “galley” from which individual pages are cut off in an asynchronous way. This page generating process is normally not directly associated with commands in the input<sup>21</sup> but is triggered whenever the galley has received enough material to form another page (giving current settings).

As part of this transformation input data may get stored in some form and later reused, for example, as part of the output routine processing.

## 2 Configuration of the transformation process

There are three different major methods offered by L<sup>A</sup>T<sub>E</sub>X to configure the transformation process:

- through the template mechanism,
- through the hook mechanism, or
- through sockets and plugs.

They offer different possibilities (with different features and limitations) and are intended for specific use cases, though it is possible to combine them.

### 2.1 The template mechanism

The template mechanism is intended for more complex document-level elements (e.g., headings such as `\section` or environments like `itemize`). The template code implements the overall processing logic for such an element and offers a set of parameters to influence the final result.

The document element is then implemented by (a) selecting a suitable template (there may be more than one available for the kind of document element) and (b) by setting its parameters to desired values. This then forms a so-called instance which is executed when the document element is found in the source.

By altering the parameter values (in a document class or in the document preamble) or, if more drastic layout changes are desired, by selecting a different template and

---

<sup>21</sup>Excepts for directives such as `\newpage`.

then adjusting its parameters, a wide variety of layouts can be realized through simple configuration setups without the need to develop new code.

The target audience of this method are therefore document class developers or users who wish to alter an existing layout (implemented by a document class) in certain (minor) ways.

The template mechanism is currently documented as part of the `xtemplate` package and one more elaborate implementation can be found as part of the `latex-lab` code for lists (to be documented further).

## 2.2 The hook mechanism

Hooks are places in the kernel code (or in packages) that offer packages the possibility to inject additional code at specific points in the processing in a controlled way without the need to replace the existing code block (and thereby overwriting modifications/extensions made by other packages). The target audience is therefore mainly package developers, even though some hooks can be useful for document authors.

Obviously, what can reasonably be added into a hook depends on the individual hook (hopefully documented as part of the hook documentation), but in general the idea behind hooks is that more than one package could add code into the hook at the same time. Perhaps the most famous hook (that L<sup>A</sup>T<sub>E</sub>X had for a very long time) is `begindocument` into which many packages add code to through `\AtBeginDocument{<code>}` (which is nowadays implemented as a shorthand for `\AddToHook{begindocument}{<code>}`). To resolve possible conflicts between injections by different packages there is a rule mechanism by which code chunks in a hook can be ordered in a certain way and by which incompatible packages can be detected if a resolution is impossible.

In contrast to template code, there is no standard configuration method through parameters for hooks, i.e., the code added to a hook “is” the configuration. If it wants to provide for configuration through parameters it has to also provide its own method to set such parameters in some way. However, in that case it is likely that using a hook is not the right approach and the developer better calls a template instance instead which then offers configuration through a key/value interface.

In most cases, hooks do not take any arguments as input. Instead, the data that they can (and are allowed to) access depends on the surrounding context.

For example, the various hooks available during the page shipout process in L<sup>A</sup>T<sub>E</sub>X’s output routine can (and have to) access the accumulated page material stored in a box named `\ShipoutBox`. This way, code added to, say, the `shipout/before` hook could access the page content, alter it, and then write it back into `\ShipoutBox` and any other code added to this hook could then operate on the modified content. Of course, for such a scheme to work the code prior to executing the hook would need to setup up data in appropriate places and the hook documentation would need to document what kind of storage can be accessed (and possibly altered) by the hook.

There are also hooks that take arguments (typically portions of document data) and in that case the hook code can access these arguments through `#1`, `#2`, etc.

The hook mechanism is documented in `lthooks-doc.pdf`.

## 2.3 The socket mechanism

In some cases there is code that implements a certain programming logic (for example, combining footnotes, floats, and the text for the current page to be shipped out) and

if this logic should change (e.g., footnotes to be placed above bottom floats instead of below) then this whole code block needs to be replaced with different code.

In theory, this could be implemented with templates, i.e., the code simply calls some instance that implements the logic and that instance is altered by selecting a different templates and/or adjusting their parameters. However, in many cases customization through parameters is overkill in such a case (or otherwise awkward, because parameterization is better done on a higher level instead of individually for small blocks of code) and using the template mechanism just to replace one block of code with a different one results in a fairly high performance hit. It is therefore usually not a good choice.

In theory, it would also be possible to use a hook, but again that is basically a misuse of the concept, because in this use case there should never be more than one block of code inside the hook; thus, to alter the processing logic one would need to set up rules that replace code rather than (as intended) execute all code added to the hook.

For this reason L<sup>A</sup>T<sub>E</sub>X now offers a third mechanism: “sockets” into which one can place exactly one code block — a “plug”.

In a nutshell: instead of having a fixed code block somewhere as part of the code, implementing a certain programming logic there is a reference to a named socket at this point. This is done by first declaring the named socket with:

```
\NewSocket{<socket-name>}{<number-of-inputs>}
```

This is then referenced at the point where the replaceable code block should be executed with:

```
\UseSocket{<socket-name>}
```

or, if the socket should take a number of inputs (additional arguments beside the name) with

```
\UseSocket{<socket-name>}{<arg1>}...{<argnumber-of-inputs>}}
```

In addition, several code blocks (a.k.a. plugs) implementing different logic for this socket are set up, each with a declaration of the form:

```
\NewSocketPlug{<socket-name>}{<socket-plug-name>}{<code>}
```

Finally, one of them is assigned to the socket:

```
\AssignSocketPlug{<socket-name>}{<socket-plug-name>}
```

If the programming logic should change, then all that is necessary is to make a new assignment with `\AssignSocketPlug` to a different `{<socket-plug-name>}`. This assignment obeys scope so that an environment can alter a socket without the need to restore the previous setting manually.

If the socket takes inputs, then those need to be provided to `\UseSocket` and in that case they can be referenced in the `<code>` argument of `\NewSocketPlug` with `#1`, `#2`, etc.

In most cases a named socket is used only in a single place, but there is, of course, nothing wrong with using it in several places, as long as the code in all places is supposed to change in the same way.

### 2.3.1 Examples

We start by declaring a new socket named `foo` that expects two inputs:

```
\NewSocket{foo}{2}
```

Such a declaration has to be unique across the whole L<sup>A</sup>T<sub>E</sub>X run. Thus, if another package attempts to use the same name (regardless of the number of inputs) it will generate an error:

```
\NewSocket{foo}{2}
\NewSocket{foo}{1}
```

Both declarations would therefore produce:

```
! LaTeX socket Error: Socket 'foo' already declared!
```

You also get an error if you attempt to declare some socket plug and the socket name is not yet declared, e.g.,

```
\NewSocketPlug{baz}{undeclared}{some code}
```

generates

```
! LaTeX socket Error: Socket 'baz' undeclared!
```

Setting up plugs for the socket is done like this:

```
\NewSocketPlug{foo}{plug-A}
  {\begin{quote}\itshape foo-A: #1!#2\end{quote}}
\NewSocketPlug{foo}{plug-B}
  {\begin{quote}\sffamily foo-B: #2\textsuperscript{2}\end{quote}}
```

This will set up the plugs `plug-A` and `plug-B` for this socket.

We still have to assign one or the other to the socket, thus without doing that the line

```
\UseSocket{foo}{hello}{world}
```

produces nothing because the default plug for sockets with 2 inputs is `noop` (which grabs the additional arguments and throws them away).<sup>22</sup>

So let's do the assignment

```
\AssignSocketPlug{foo}{plug-A}
```

and then

```
\UseSocket{foo}{hello}{world}
```

will properly typeset

*foo-A: hello!world*

and after

```
\AssignSocketPlug{foo}{plug-B}
```

---

<sup>22</sup>If socket `foo` would have been a socket with one input, then the default plug would be `identity`, in which case the socket input would remain without braces and gets typeset!

and another call to

```
\UseSocket{foo}{hello}{world}
```

we get

```
foo-B: world2
```

If we attempt to assign a plug that was not defined, e.g.,

```
\AssignSocketPlug{foo}{plug-C}
```

then we get an error during the assignment

```
! LaTeX socket Error: Plug 'plug-C' for socket 'foo' undeclared!
```

and the previous assignment remains in place.

To see what is known about a socket and its plugs you can use `\ShowSocket` or `\LogSocket` which displays information similar to this on the terminal or in the transcript file:

```
Socket foo:
  number of inputs = 2
  available plugs = noop, plug-A, plug-B
  current plug = plug-B
  definition = \long macro:#1#2->\begin {quote}\sffamily
foo-B: #2\textsuperscript {2}\end {quote}
```

### 2.3.2 Details and semantics

In this section we collect some normative statements.

- From a functional point of view sockets are like simple `TeX` macros, i.e., they expect 0 to 9 mandatory arguments (the socket inputs) and get replaced by their “expansion”
- A socket is “named” and the name consists of ASCII letters `[a-z]`, `[A-Z]`, `[0-9]`, `[-/@]` only
- Socket names have to be unique, i.e., there can be only one socket named `<name>`. This is ensured by declaring each socket with `\NewSocket`.

However, there is no requirement that sockets and hook names have to be different. In fact, if a certain action that could otherwise be specified as hook code has to be executed always last (or first) one could ensure this by placing a socket (single action) after a hook (or vice versa) and using the same name to indicate the relationship, e.g.,

```
\UseHook{foo}           % different package can add code here
\UseSocket{foo}          % only one package can assign a plug
```

This avoids the need to order the hook code to ensure that something is always last.

- Best practice naming conventions are ... *to be documented*

- A socket has documented inputs which are
  - the positional arguments (if any) with a description of what they contain when used
  - implicit data (registers and other 2e/expl3 data stores) that the socket is allowed to make use of, with a documented description of what they contain (if relevant for the task at hand—no need to describe the whole L<sup>A</sup>T<sub>E</sub>X universe)
  - information about the state of the T<sub>E</sub>X engine (again when relevant), e.g. is called in mmode or vmode or in the output routine or ...
  - ... anything missing?
- A socket has documented results/outputs which can be
  - what kind of data it should write to the current list (if that is part of its task)
  - what kind of registers and other 2e/expl3 data stores it should modify and in what way
  - what kind of state changes it should do (if any)
  - ... *anything else*?
- At any time a socket has one block of code (a plug :-)) associated with it. Such code is itself named and the association is done by linking the socket name to the code name (putting a plug into the socket).
- The name of a plug consists of ASCII letters [a-z], [A-Z], [0-9], [-/@] only.
- Socket plug names have to be unique within on a per socket basis, but it is perfectly allowed (and sensible in some cases) to use the same plug name with different sockets (where based on the sockets' purposes, different actions may be associated with the plug name). For example `noop` is a plug name declared for every socket, yet its action “grab the socket inputs and throw them away” obviously differs depending on how many inputs the socket has.
- When declaring a plug it is stated for which socket it is meant (i.e., its code can only be used with that socket). This means that the same plug name can be used with different sockets referring to different code in each case.
- Configuration of a socket can only be done by linking different code to it. Nevertheless the code linked to it can provide its own means of configuration (but this is outside of the spec).
- Technically execution of a socket (`\UseSocket`) involves
  - doing any house keeping (like writing debugging info, ...);
  - looking up the current code association (what plug is in the socket);
  - executing this code which will pick up the mandatory arguments (happens at this point, not before), i.e., it is like calling a csname defined with
 

```
\def\foo#1#2...{\...#1...#2...}
```
  - do some further house keeping (if needed).
- A socket is typically only used in one place in code, but this is not a requirement, i.e., if the same operation with the same inputs need to be carried out in several places the same named socket can be used.

### 2.3.3 Command syntax

We give both the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> and the L3 programming layer command names.

---

<code>\NewSocket</code>	<code>\NewSocket</code>	<code>{\socket-name}</code>	<code>{\number-of-inputs}</code>
<code>\socket_new:nn</code>	<code>\socket_new:nn</code>	<code>{\socket-name}</code>	<code>{\number-of-inputs}</code>

---

Declares a new socket with name `\socket-name` having `\number-of-inputs` inputs. There is automatically a plug `noop` declared for it, which does nothing, i.e., it gobbles the socket inputs (if any). This is made the default plug except for sockets with one input which additionally define the plug `identity` and assign that as their default.

This `identity` plug simply returns the socket input without its outer braces. The use case for this plug are situations like this:

`\UseSocket{taggsupport/footnote}{\code}`

If tagging is not active and the socket contains the plug `identity` then this returns `\code` without the outer braces and to activate tagging all that is necessary is to change the plug to say `tagpdf` so that it surrounds `\code` by some tagging magic. This is the most common use case for sockets with one input, which is why they have this special default.

The socket documentation should describe its purpose, its inputs and the expected results as discussed above.

The declaration is only allowed at top-level, i.e., not inside a group.

---

<code>\NewSocketPlug</code>	<code>\NewSocketPlug</code>	<code>{\socket-name}</code>	<code>{\socket-plug-name}</code>	<code>{\code}</code>
<code>\socket_new_plug:nnn</code>	<code>\socket_new_plug:nnn</code>	<code>{\socket-name}</code>	<code>{\socket-plug-name}</code>	<code>{\code}</code>
<code>\socket_set_plug:nnn</code>	<code>\socket_set_plug:nnn</code>	<code>{\socket-name}</code>	<code>{\socket-plug-name}</code>	<code>{\code}</code>

---

Declares a new plug for socket `\socket-name` that runs `\code` when executing. It complains if the plug was already declared previously.

The form `\socket_set_plug:nnn` changes an existing plug. As this should normally not be necessary, we currently have only an L3 layer name for the few cases it might be useful.

The declarations can be made inside a group and obey scope, i.e., they vanish if the group ends.

---

<code>\AssignSocketPlug</code>	<code>\AssignSocketPlug</code>	<code>{\socket-name}</code>	<code>{\socket-plug-name}</code>
<code>\socket_assign_plug:nn</code>	<code>\socket_assign_plug:nn</code>	<code>{\socket-name}</code>	<code>{\socket-plug-name}</code>

---

Assigns the plug `\socket-plug-name` to the socket `\socket-name`. It errors if either socket or plug is not defined.

The assignment is local, i.e., it obeys scope.

<hr/>	<hr/>
<code>\UseSocket</code>	<code>\UseSocket      {&lt;socket-name&gt;}</code>
<code>\socket_use:nw</code>	<code>\socket_use:nnn {&lt;socket-name&gt;} {&lt;socket-arg<sub>1</sub>&gt;} {&lt;socket-arg<sub>2</sub>&gt;}</code>
<code>\socket_use:n</code>	Executes the socket <code>&lt;socket-name&gt;</code> by retrieving the <code>&lt;code&gt;</code> of the current plug assigned to the socket. This is the only command that would appear inside macro code in packages.
<code>\socket_use:nn</code>	For performance reasons there is no explicit check that the socket was declared!
<code>\socket_use:nnn</code>	The different L3 programming layer commands are really doing the same thing: they grab as many arguments as defined as inputs for the socket and then pass them to the plug. The different names are only there to make the code more readable, i.e., to indicate how many arguments are grabbed in total (note that no runtime check is made to verify that this is actually true). We only provide them for sockets with up to 3 inputs (most likely those with zero or one input would have been sufficient). If you happen to have a socket with more inputs, use <code>\socket_use:nw</code> .
<code>\socket_use:nnnn</code>	

<hr/>	<hr/>
<code>\socket_use_expandable:nw</code>	<code>* \socket_use_expandable:n {&lt;socket-name&gt;}</code>
<code>\socket_use_expandable:n</code>	<code>*</code>

Fully expandable variant of `\socket_use:n`. This can be used in macro code to retrieve code from sockets which need to appear in an expandable context.

This usually requires the plug to only contain expandable code and should therefore only be used for sockets which are clearly documented to be used in an expandable context. This command does not print any debugging info when `\DebugSocketsOn` is active and should therefore be avoided whenever possible.

For performance reasons there is no explicit check that the socket was declared!

<hr/>	<hr/>
<code>\ShowSocket</code>	<code>\ShowSocket    {&lt;socket-name&gt;}</code>
<code>\LogSocket</code>	<code>\socket_show:n {&lt;socket-name&gt;}</code>
<code>\socket_show:n</code>	Displays information about the socket <code>&lt;socket-name&gt;</code> and its state then stops and waits for further instructions — at the moment some what rudimentary.
<code>\socket_log:n</code>	<code>\LogSocket</code> and <code>\socket_log:n</code> only differ in that they don't stop.

It is sometimes necessary/helpful to know if a particular socket or plug exists (or is assigned to a certain socket) and based on that take different actions.

<hr/>	<hr/>
<code>\IfSocketExistsTF</code>	<code>* \IfSocketExistsTF {&lt;socket-name&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\socket_if_exist:nTF</code>	<code>*</code> If socket <code>&lt;socket-name&gt;</code> exists then execute <code>&lt;true code&gt;</code> otherwise <code>&lt;false code&gt;</code> . Variants with only T or F are also available.

<hr/>	<hr/>
<code>\IfSocketPlugExistsTF</code>	<code>* \IfSocketPlugExistsTF {&lt;socket-name&gt;} {&lt;plug-name&gt;}</code>
<code>\socket_if_plug_exist:nnTF</code>	<code>*      {&lt;true code&gt;} {&lt;false code&gt;}</code>
	If plug <code>&lt;plug-name&gt;</code> for socket <code>&lt;socket-name&gt;</code> exists then execute <code>&lt;true code&gt;</code> otherwise <code>&lt;false code&gt;</code> . Variants with only T or F are also available.

<hr/>	<hr/>
<code>\IfSocketPlugAssignedTF</code>	<code>* \IfSocketPlugAssignedTF {&lt;socket-name&gt;} {&lt;plug-name&gt;}</code>
<code>\socket_if_plug_assigned:nnTF</code>	<code>*      {&lt;true code&gt;} {&lt;false code&gt;}</code>

If plug `<plug-name>` is assigned to socket `<socket-name>` then execute `<true code>` otherwise `<false code>`. Variants with only T or F are also available.

---

<code>\DebugSocketsOn</code>	<code>\DebugSocketsOn ... \DebugSocketsOff</code>
<code>\DebugSocketsOff</code>	Turns debugging of sockets on or off.
<code>\socket_debug_on:</code>	
<code>\socket_debug_off:</code>	

---

### 2.3.4 Rationale for error handling

The errors during the declarations are produced to help with typos—after all, such declarations might be part of a document preamble (not that likely, but possible). However, `\UseSocket` is not doing much checking, e.g.,

```
\UseSocket{mispelled-socket}{hello}{world}
```

will generate a rather low-level error and then typesets “helloworld” because there is no dedicated runtime check if `mispelled-socket` is a known socket.

The reason is that if the misspelling is in the code, then this is a programming error in the package and for speed reasons L<sup>A</sup>T<sub>E</sub>X does not repeatedly make runtime checks for coding errors unless they can or are likely to be user introduced.

## 3 The Implementation

The implementation of the socket mechanism should be (partially) redone and we should probably store the different code chunks in a property list so that we can have a decent `\ShowSocket` command that shows the available alternatives.

TODO: *implement?*

```

1 <*2ekernel | latexrelease>
2 \ExplSyntaxOn
3 <@@=socket>
4 <latexrelease> \NewModuleRelease{2023/11/01}{ltsockets}
5 <latexrelease> {The~socket~management~system}
```

### 3.1 Debugging the socket structures

Code and commands in this section are not final, it needs more experimentation to see what kind of tracing information is going to be useful in practice. For now the tracing is mainly meant to be used for code testing and not so much for application testing.

It is quite likely that the commands and the behavior of the tracing might change in the future once we gained some experience with it.

<code>\g__socket_debug_bool</code>	Holds the current debugging state.
<code>\bool_new:N \g__socket_debug_bool</code>	
<i>(End of definition for \g__socket_debug_bool.)</i>	
<code>\socket_debug_on:</code>	Turns debugging on and off by redefining <code>\__socket_debug:n</code> and <code>\__socket_debug_term:n</code> . By default they do nothing.
<code>\socket_debug_off:</code>	
<code>\__socket_debug:n</code>	<code>\cs_new_eq:NN \__socket_debug:n \use_none:n</code>
<code>\__socket_debug_term:n</code>	<code>\cs_new_eq:NN \__socket_debug_term:n \use_none:n</code>
<code>\__socket_debug_gset:</code>	

```

9 \cs_new_protected:Npn \socket_debug_on:
10 {
11   \bool_gset_true:N \g__socket_debug_bool
12   \__socket_debug_gset:
13 }
14 \cs_new_protected:Npn \socket_debug_off:
15 {
16   \bool_gset_false:N \g__socket_debug_bool
17   \__socket_debug_gset:
18 }
19 \cs_new_protected:Npn \__socket_debug_gset:
20 {
21   \cs_gset_protected:Npx \__socket_debug:n ##1
22   { \bool_if:NT \g__socket_debug_bool {##1} }
23   \cs_gset_protected:Npx \__socket_debug_term:n ##1
24   { \bool_if:NT \g__socket_debug_bool
25     { \iow_term:x { ^^J [Sockets]~ ==>~ ##1} } }
26 }

```

(End of definition for `\socket_debug_on:` and others. These functions are documented on page 345.)

### 3.2 The L3 layer commands

`\socket_new:nn` Declaring a socket creates a str to hold the name (a pointer) to the code that should be used when the socket is executed, and an integer to hold the number of inputs of that socket. Initially, an “empty” code chunk is created and assigned so the socket does nothing by default other than swallowing its inputs (if any).

```

27 \cs_new_protected:Npn \socket_new:nn #1 #2 {
28   \socket_if_exist:nTF {#1}
29   {
30     \msg_error:nnn { socket } { already-declared } {#1}
31   }
32   {

```

We only support declarations on top-level.

```

33   \int_if_zero:nTF \tex_currentgrouplevel:D
34   {
35     \str_new:c { l__socket_#1_plug_str }
36     \seq_new:c { l__socket_#1_plugs_seq }
37     \int_const:cn { c__socket_#1_args_int } {#2}
38     \socket_new_plug:nnn {#1} { noop } {}
39     \int_compare:nNnTF {#2} = 1
40     {
41       \socket_new_plug:nnn {#1} { identity } {##1}
42       \socket_assign_plug:nn {#1} { identity }
43     }
44     { \socket_assign_plug:nn {#1} { noop } }
45     \__socket_debug_term:n
46     { Socket~ '##1'~ declared~ with~ #2~ input(s) }
47   }
48   {
49     \msg_error:nn { socket } { not-top-level }
50   }
51 }

```

```
52 }
```

(End of definition for `\socket_new:nn`. This function is documented on page 343.)

`\socket_if_exist_p:n` Conditional testing the existence of a socket. The argument is fully expanded as part of the csname generation.

`\socket_if_exist:nTF`

```
53 \prg_new_conditional:Npnn \socket_if_exist:n #1 { p , T , F , TF }
54 { \str_if_exist:cTF { l__socket_#1_plug_str }
55   \prg_return_true:
56   \prg_return_false:
57 }
```

(End of definition for `\socket_if_exist:nTF`. This function is documented on page 344.)

`\socket_log:n` Show the current state of the socket — for now this is just a quick draft and should be redone and extended.

`\socket_show:n`

```
58 \cs_new_protected:Npn \socket_log:n #1 {
59   \typeout{ Socket~ #1:}
60   \socket_if_exist:nTF {#1}
61   {
62     \typeout{ @spaces number~ of~ inputs~ =~
63               \int_use:c { c__socket_#1_args_int } }
64     \typeout{ @spaces available~plugs~ =~
65               \seq_use:cnnn { l__socket_#1_plugs_seq }{,~}{,~}{,~} }
66     \typeout{ @spaces current~ plug~ =~
67               \str_use:c { l__socket_#1_plug_str } }
68     \typeout{ @spaces definition~ =~
69               \cs_meaning:c
70               { __socket_#1_plug_ \str_use:c { l__socket_#1_plug_str } :w } }
71     \typeout{}
72   }
73 }
```

If we are showing a socket it is not an error if it doesn't exist.

```
74   \typeout { Socket~ is~ not~ declared! }
75 }
76 }
```

And here the version that stops:

```
77 \cs_new_protected:Npn \socket_show:n #1 {\socket_log:n {#1} \errmessage{}}
```

(End of definition for `\socket_log:n` and `\socket_show:n`. These functions are documented on page 344.)

`\socket_new_plug:nnn` Declaring a code for a socket is just making a definition, taking the number of arguments from the saved int.

`\socket_set_plug:nnn`

```
78 \cs_new_protected:Npn \socket_new_plug:nnn #1#2#3 {
79   \socket_if_exist:nTF {#1}
80   {
81     \socket_if_plug_exist:nnTF {#1} {#2}
82     {
83       \msg_error:nnnn { socket } { plug-already-declared } {#1} {#2}
84     }
85     {
86       \cs_generate_from_arg_count:cNnn
```

```

87         { __socket_#1_plug_#2:w }
88         \cs_new:Npn
89         { \int_use:c { c__socket_#1_args_int } }
90         {#3}

```

This is a new declaration so we add the name to a seq for the debugging info.

```

91         \seq_put_right:cn { l__socket_#1_plugs_seq } {#2}
92         \__socket_debug_term:n
93         { Plug~ '2'~ for~ socket~ '1'~ declared. }
94     }
95 }
96 { \msg_error:nnn { socket } { undeclared } {#1} }
97 }

```

Changing the plug of an existing socket is rather similar, except that we don't have to deal with adding it to the debugging sequence.

```

98 \cs_new_protected:Npn \socket_set_plug:nnn #1#2#3 {
99     \socket_if_exist:nTF {#1}
100     {
101         \socket_if_plug_exist:nnTF {#1} {#2}
102         {
103             \cs_generate_from_arg_count:cNnn
104             { __socket_#1_plug_#2:w }
105             \cs_set:Npn
106             { \int_use:c { c__socket_#1_args_int } }
107             {#3}
108             \__socket_debug_term:n
109             { Plug~ '2'~ for~ socket~ '1'~ changed. }
110         }
111         {
112             \msg_error:nnnn { socket } { plug-undeclared } {#1} {#2}
113         }
114     }
115     { \msg_error:nnn { socket } { undeclared } {#1} }
116 }

```

(End of definition for `\socket_new_plug:nnn` and `\socket_set_plug:nnn`. These functions are documented on page 343.)

`\socket_if_plug_exist_p:nn`  
`\socket_if_plug_exist:nnTF`

Conditional testing the existence of a plug. Both arguments are fully expanded as part of the csname generation.

```

117 \prg_new_conditional:Npnn \socket_if_plug_exist:nn #1#2 { p , T , F , TF }
118 { \cs_if_exist:cTF { __socket_#1_plug_#2:w }
119     \prg_return_true:
120     \prg_return_false:
121 }

```

(End of definition for `\socket_if_plug_exist:nnTF`. This function is documented on page 344.)

`\socket_assign_plug:nn`

Assigning a plug to a socket just changes the name in the socket string. The assignment is local to the current group.

```

122 \cs_new_protected:Npn \socket_assign_plug:nn #1 #2 {
123     \socket_if_exist:nTF {#1}
124     {
125         \socket_if_plug_exist:nnTF {#1} {#2}

```

```

126     {
127         \__socket_debug_term:n
128         { Replacing~ plug~ '\str_use:c { l__socket_#1_plug_str }'~
129           with~ '#2'~ in~ socket~ '#1'. }
130         \str_set:cn { l__socket_#1_plug_str } {#2}
131     }
132     {
133         \msg_error:nnnn { socket } { plug-undeclared } {#1} {#2}
134     }
135 }
136 { \msg_error:nnn { socket } { undeclared } {#1} }
137 }

```

(End of definition for `\socket_assign_plug:nn`. This function is documented on page 343.)

```

\socket_if_plug_assigned_p:nn Conditional testing the assignment of a plug. Both arguments are fully expanded.
\socket_if_plug_assigned:nnTF
138 \prg_new_conditional:Npnn \socket_if_plug_assigned:nn #1#2 { p , T , F , TF }
139 { \exp_args:Ne
140   \str_if_eq:nvTF {#2} { l__socket_#1_plug_str }
141   \prg_return_true:
142   \prg_return_false:
143 }

```

(End of definition for `\socket_if_plug_assigned:nnTF`. This function is documented on page 344.)

`\socket_use:nw` And using it is more or less a `\use:c` so very lightweight. We do not add a runtime check for speed reasons!

`\socket_use:n` This command is named `\socket_use:nw` because we don't know how many inputs the socket has until we have looked at the socket name (in argument #1). But, of course,

`\socket_use:nn` the developer knows so we also offer a few aliases `\socket_use:nn`, etc. so that one can indicate the correct number of arguments (socket inputs plus one) in the L3 layer code.

`\socket_use:nnnn`

```

144 \cs_new_protected:Npn \socket_use:nw #1 {
145   \__socket_debug_term:n
146   { Socket~ '#1'~ containing~ plug~
147     '\str_use:c { l__socket_#1_plug_str }'~ used. }
148   \use:c { __socket_#1_plug_ \str_use:c { l__socket_#1_plug_str } :w }
149 }

```

To make code a bit more readable we also define functions that indicate how many arguments are picked up. However, this is just for code documentation: internally they all do the same and the number of arguments isn't checked by default.

```

150 \cs_new_eq:NN \socket_use:n \socket_use:nw % socket with no inputs
151 \cs_new_eq:NN \socket_use:nn \socket_use:nw % socket with one input
152 \cs_new_eq:NN \socket_use:nnn \socket_use:nw % socket with two inputs
153 \cs_new_eq:NN \socket_use:nnnn \socket_use:nw % socket with three inputs

```

The above commands could be changed to check how many inputs the socket is declared with (for example, when checking is in force).

TODO: Implement?

(End of definition for `\socket_use:nw` and others. These functions are documented on page 344.)

`\socket_use_expandable:nw`  
`\socket_use_expandable:n`

The same as the non-expandable code, except for the missing debug output.

```
154 \cs_new:Npn \socket_use_expandable:nw #1 {
155   \use:c { __socket_#1_plug_ \str_use:c { l__socket_#1_plug_str } :w }
156 }
157 \cs_new_eq:NN \socket_use_expandable:n \socket_use_expandable:nw % socket with no inputs
```

(End of definition for `\socket_use_expandable:nw` and `\socket_use_expandable:n`. These functions are documented on page 344.)

### 3.3 Error messages

```
158 \msg_new:nnnn { socket } { already-declared }
159   { Socket~ '#1'~ already~ declared! }
160   { A~ socket~ can~ only~ be~ declared~ once.~ The~ name~ '#1'~ is~
161     already~ taken.~ Use~ \ShowSocket{#1}~ to~ see~ its~ definition. }
162
163 \msg_new:nnnn { socket } { undeclared }
164   { Socket~ '#1'~ undeclared! }
165   { You~ tried~ to~ use~ a~ socket~ that~ was~ not~ declared~ before. }
166
167 \msg_new:nnnn { socket } { not-top-level }
168   { Sockets~ can~ only~ be~ declared~ at~ top-level! }
169   { It~ is~ not~ allowed~ to~ declare~ sockets~ inside~ a~
170     group.~ Move~ the~ declaration~ to~ the~ top-level. }
171
172 \msg_new:nnnn { socket } { plug-already-declared }
173   { Plug~ '#2'~ for~ socket~ '#1'~ already~ declared! }
174   { You~ can't~ change~ an~ existing~ plug~ with~ \NewSocketPlug~ and~ it~
175     is~ normally~ not~ sensible~ to~ do~ so.~ Use~ the~ L3~ programming~
176     layer~ function~ \socket_set_plug:nnn~ if~ you~ really~ have~ to. }
177
178 \msg_new:nnnn { socket } { plug-undeclared }
179   { Plug~ '#2'~ for~ socket~ '#1'~ undeclared! }
180   { The~ plug~ name~ is~ unknown.~ Is~ the~ name~ misspelled~ or~ did~ you~
181     intend~ to~ assign~ it~ to~ a~ different~ socket? }
182
183 \prop_gput:Nnn \g_msg_module_type_prop { socket } { LaTeX }
```

### 3.4 The L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interface commands

`\NewSocket`  
`\NewSocketPlug`  
`\ShowSocket`  
`\LogSocket`  
`\AssignSocketPlug`  
`\UseSocket`  
`\DebugSocketsOn`  
`\DebugSocketsOff`

As we expect that there are existing L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> packages that may want to make use of the socket mechanism, we provide 2<sub>ε</sub> names for most of the commands.

```
182 \cs_new_eq:NN \NewSocket \socket_new:nn
183 \cs_new_eq:NN \ShowSocket \socket_show:n
184 \cs_new_eq:NN \LogSocket \socket_log:n
185 \cs_new_eq:NN \NewSocketPlug \socket_new_plug:nnn
186 \cs_new_eq:NN \AssignSocketPlug \socket_assign_plug:nn
187 \cs_new_eq:NN \UseSocket \socket_use:nw
188 \cs_new_eq:NN \DebugSocketsOn \socket_debug_on:
189 \cs_new_eq:NN \DebugSocketsOff \socket_debug_off:
```

(End of definition for `\NewSocket` and others. These functions are documented on page 343.)

```

\IfSocketExistsTF A bunch of conditionals:
\IfSocketExistsT 190 \cs_new_eq:NN \IfSocketExistsTF \socket_if_exist:nTF
\IfSocketExistsF 191 \cs_new_eq:NN \IfSocketExistsT \socket_if_exist:nT
\IfSocketPlugExistsTF 192 \cs_new_eq:NN \IfSocketExistsF \socket_if_exist:nF
\IfSocketPlugExistsT 193 \cs_new_eq:NN \IfSocketPlugExistsTF \socket_if_plug_exist:nnTF
\IfSocketPlugExistsF 194 \cs_new_eq:NN \IfSocketPlugExistsT \socket_if_plug_exist:nnT
\IfSocketPlugAssignedTF 195 \cs_new_eq:NN \IfSocketPlugExistsF \socket_if_plug_exist:nnF
\IfSocketPlugAssignedT 196 \cs_new_eq:NN \IfSocketPlugAssignedTF \socket_if_plug_assigned:nnTF
\IfSocketPlugAssignedF 197 \cs_new_eq:NN \IfSocketPlugAssignedT \socket_if_plug_assigned:nnT
198 \cs_new_eq:NN \IfSocketPlugAssignedF \socket_if_plug_assigned:nnF

(End of definition for \IfSocketExistsTF and others. These functions are documented on page 344.)

199 %
200 <latexrelease> \IncludeInRelease{0000/00/00}{ltsockets}
201 <latexrelease> {The~socket~management~(undo)}%
202 <latexrelease>
203 <latexrelease> \let \NewSocket \@undefined
204 <latexrelease> \let \ShowSocket \@undefined
205 <latexrelease> \let \LogSocket \@undefined
206 <latexrelease>
207 <latexrelease> \let \NewSocketPlug \@undefined
208 <latexrelease> \let \AssignSocketPlug \@undefined
209 <latexrelease> \let \UseSocket \@undefined
210 <latexrelease>
211 <latexrelease> \let \DebugSocketsOn \@undefined
212 <latexrelease> \let \DebugSocketsOff \@undefined
213 <latexrelease>
214 <latexrelease> \let \IfSocketExistsTF \@undefined
215 <latexrelease> \let \IfSocketExistsT \@undefined
216 <latexrelease> \let \IfSocketExistsF \@undefined
217 <latexrelease> \let \IfSocketPlugExistsTF \@undefined
218 <latexrelease> \let \IfSocketPlugExistsT \@undefined
219 <latexrelease> \let \IfSocketPlugExistsF \@undefined
220 <latexrelease> \let \IfSocketPlugAssignedTF \@undefined
221 <latexrelease> \let \IfSocketPlugAssignedT \@undefined
222 <latexrelease> \let \IfSocketPlugAssignedF \@undefined
223 <latexrelease>
224 <latexrelease> \EndModuleRelease

225 \ExplSyntaxOff

226 </2ekernel | latexrelease>

Reset module prefix:
227 <@@=>

```

## File 11

# lttemplates.dtx

## 1 Introduction

There are three broad “layers” between putting down ideas into a source file and ending up with a typeset document. These layers of document writing are

1. authoring of the text with mark-up;
2. document layout design;
3. implementation (with T<sub>E</sub>X programming) of the design.

We write the text as an author, and we see the visual output of the design after the document is generated; the T<sub>E</sub>X implementation in the middle is the glue between the two.

L<sup>A</sup>T<sub>E</sub>X’s greatest success has been to standardise a system of mark-up that balances the trade-off between ease of reading and ease of writing to suit almost all forms of technical writing. It’s other original strength was a good background in typographical design; while the standard L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> classes look somewhat dated now in terms of their visual design, their typography is generally sound (barring the occasional minor faults).

However, L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> has always lacked a standard approach to customising the visual design of a document. Changing the looks of the standard classes involved either:

- Creating a new version of the implementation code of the class and editing it.
- Loading one of the many packages to customise certain elements of the standard classes.
- Loading a completely different document class, such as KOMA-Script or memoir, that allows easy customization.

All three of these approaches have their drawbacks and learning curves.

The idea behind `lttemplates` is to cleanly separate the three layers introduced at the beginning of this section, so that document authors who are not programmers can easily change the design of their documents. `lttemplates` also makes it easier for L<sup>A</sup>T<sub>E</sub>X programmers to provide their own customizations on top of a pre-existing class.

## 2 What is a document?

Besides the textual content of the words themselves, the source file of a document contains mark-up elements that add structure to the document. These elements include sectional divisions, figure/table captions, lists of various sorts, theorems/proofs, and so on. The list will be different for every document that can be written.

Each element can be represented logically without worrying about the formatting, with mark-up such as `\section`, `\caption`, `\begin{enumerate}` and so on. The output of each one of these document elements will be a typeset representation of the information marked up, and the visual arrangement and design of these elements can vary widely in producing a variety of desired outcomes.

For each type of document element, there may be design variations that contain the same sort of information but present it in slightly different ways. For example, the difference between a numbered and an unnumbered section, `\section` and `\section*`, or the difference between an itemized list or an enumerated list.

There are three distinct layers in the definition of “a document” at this level

1. semantic elements such as the ideas of sections and lists;
2. a set of design solutions for representing these elements visually;
3. specific variations for these designs that represent the elements in the document.

In the parlance of the template system, these are called types, templates, and instances, and they are discussed below in sections 4, 5, and 7, respectively.

### 3 Types, templates, and instances

By formally declaring documents to be composed of mark-up elements grouped into types, which are interpreted and typeset with a set of templates, each of which has one or more instances with which to compose each and every semantic unit of the text, we can cleanly separate the components of document construction.

All of the structures provided by the template system are global, and do not respect  $\TeX$  grouping.

### 4 Template types

An *template type* (sometimes just “type”) is an abstract idea of a document element that takes a fixed number of arguments corresponding to the information from the document author that it is representing. A sectioning type, for example, might take three inputs: “title”, “short title”, and “label”.

Any given document class will define which types are to be used in the document, and any template of a given type can be used to generate an instance for the type. (Of course, different templates will produce different typeset representations, but the underlying content will be the same.)

---

```
\NewTemplateType <template type> {<no. of args>}
```

---

This function defines an `<template type>` taking `<number of arguments>`, where the `<type>` is an abstraction as discussed above. For example,

```
\NewTemplateType{sectioning}{3}
```

creates a type “sectioning”, where each use of that type will need three arguments.

### 5 Templates

A *template* is a generalized design solution for representing the information of a specified type. Templates that do the same thing, but in different ways, are grouped together by their type and given separate names. There are two important parts to a template:

- the parameters it takes to vary the design it is producing;

Key-type	Description of input
<code>boolean</code>	<code>true</code> or <code>false</code>
<code>choice{⟨choices⟩}</code>	A list of pre-defined <code>⟨choices⟩</code>
<code>commalist</code>	A comma-separated list
<code>function{⟨N⟩}</code>	A function definition with $N$ arguments ( $N$ from 0 to 9)
<code>instance{⟨name⟩}</code>	An instance of type <code>⟨name⟩</code>
<code>integer</code>	An integer or integer expression
<code>length</code>	A fixed length
<code>muskip</code>	A math length with shrink and stretch components
<code>real</code>	A real (floating point) value
<code>skip</code>	A length with shrink and stretch components
<code>tokenlist</code>	A token list: any text or commands

Table 1: Key-types for defining template interfaces with `\DeclareTemplateInterface`.

- the implementation of the design.

As a document author or designer does not care about the implementation but rather only the interface to the template, these two aspects of the template definition are split into two independent declarations, `\DeclareTemplateInterface` and `\DeclareTemplateCode`.

---

```

\DeclareTemplateInterface \DeclareTemplateInterface
  {⟨type⟩} {⟨template⟩} {⟨no. of args⟩}
  {⟨key list⟩}

```

---

A `⟨template⟩` interface is declared for a particular `⟨type⟩`, where the `⟨number of arguments⟩` must agree with the type declaration. The interface itself is defined by the `⟨key list⟩`, which is itself a key–value list taking a specialized format:

```

⟨key1⟩ ":" ⟨key type1⟩ ","
⟨key2⟩ ":" ⟨key type2⟩ ","
⟨key3⟩ ":" ⟨key type3⟩ "=" ⟨default3⟩ ","
⟨key4⟩ ":" ⟨key type4⟩ "=" ⟨default4⟩ ","
...

```

Each `⟨key⟩` name should consist of ASCII characters, with the exception of `,`, `=` and `:`. The recommended form for key names is to use lower case letters, with dashes to separate out different parts. Spaces are ignored in key names, so they can be included or missed out at will. Each `⟨key⟩` must have a `⟨key type⟩`, which defines the type of input that the `⟨key⟩` requires. A full list of key types is given in Table 1. Each key may have a `⟨default⟩` value, which will be used in by the template if the `⟨key⟩` is not set explicitly. The `⟨default⟩` should be of the correct form to be accepted by the `⟨key type⟩` of the `⟨key⟩`: this is not checked by the code. Expressions for numerical values are evaluated when the template is used, thus for example values given in terms of `em` or `ex` will be set respecting the prevailing font.

---

**\KeyValue** \KeyValue {<key name>}

---

There are occasions where the default (or value) for one key should be taken from another. The `\KeyValue` function can be used to transfer this information without needing to know the internal implementation of the key:

```
\DeclareTemplateInterface { type } { template } { no. of args }
{
  key-name-1 : key-type = value ,
  key-name-2 : key-type = \KeyValue { key-name-1 },
  ...
}
```

---

**\DeclareTemplateCode** \DeclareTemplateCode  
 {<type>} {<template>} {<no. of args>}  
 {<key bindings>} {<code>}

---

The relationship between a templates keys and the internal implementation is created using the `\DeclareTemplateCode` function. As with `\DeclareTemplateInterface`, the `<template>` name is given along with the `<type>` and `<number of arguments>` required. The `<key bindings>` argument is a key-value list which specifies the relationship between each `<key>` of the template interface with an underlying `<variable>`.

```
<key1> "=" <variable1>,
<key2> "=" <variable2>,
<key3> "=" global <variable3>,
<key4> "=" global <variable4>,
...
```

With the exception of the choice, code and function key types, the `<variable>` here should be the name of an existing L<sup>A</sup>T<sub>E</sub>X3 register. As illustrated, the key word “global” may be included in the listing to indicate that the `<variable>` should be assigned globally. A full list of variable bindings is given in Table 2.

The `<code>` argument of `\DeclareTemplateCode` is used as the replacement text for the template when it is used, either directly or as an instance. This may therefore accept arguments #1, #2, *etc.* as detailed by the `<number of arguments>` taken by the type.

---

**\AssignTemplateKeys** \AssignTemplateKeys

---

In the final argument of `\DeclareTemplateCode` the assignment of keys defined by the template may be delayed by including the command `\AssignTemplateKeys`. If this is *not* present, keys are assigned immediately before the template code. If an `\AssignTemplateKeys` command is present, assignment is delayed until this point. Note that the command must be *directly* present in the code, not placed within a nested command/macro.

Key-type	Description of binding
<code>boolean</code>	Boolean variable, <i>e.g.</i> <code>\l_tmpa_bool</code>
<code>choice</code>	List of choice implementations (see Section 6)
<code>commalist</code>	Comma list, <i>e.g.</i> <code>\l_tmpa_clist</code>
<code>function</code>	Function taking $N$ arguments, <i>e.g.</i> <code>\use_i:nn</code>
<code>instance</code>	
<code>integer</code>	Integer variable, <i>e.g.</i> <code>\l_tmpa_int</code>
<code>length</code>	Dimension variable, <i>e.g.</i> <code>\l_tmpa_dim</code>
<code>muskip</code>	Muskip variable, <i>e.g.</i> <code>\l_tmpa_muskip</code>
<code>real</code>	Floating-point variable, <i>e.g.</i> <code>\l_tmpa_fp</code>
<code>skip</code>	Skip variable, <i>e.g.</i> <code>\l_tmpa_skip</code>
<code>tokenlist</code>	Token list variable, <i>e.g.</i> <code>\l_tmpa_tl</code>

Table 2: Bindings required for different key types when defining template implementations with `\DeclareTemplateCode`. Apart from `code`, `choice` and `function` all of these accept the key word `global` to carry out a global assignment.

<code>\SetKnownTemplateKeys</code>	<code>\SetKnownTemplateKeys {&lt;type&gt;} {&lt;template&gt;} {&lt;keyvals&gt;}</code>
<code>\SetTemplateKeys</code>	<code>\SetTemplateKeys {&lt;type&gt;} {&lt;template&gt;} {&lt;keyvals&gt;}</code>
<code>\UnusedTemplateKeys</code>	<code>\UnusedTemplateKeys % all &lt;keyvals&gt; unused by previous \SetKnownTemplateKeys</code>

In the final argument of `\DeclareTemplateCode` one can also overwrite (some of) the current template key value settings by using the command `\SetKnownTemplateKeys` or `\SetTemplateKeys`, i.e., they can overwrite the template default values and the values assigned by the instance.

The `\SetKnownTemplateKeys` and `\SetTemplateKeys` commands are only supported within the code of a template; using them elsewhere has unpredictable results. If they are used together with `\AssignTemplateKeys` then the latter command should come first in the template code.

The main use case for these commands is the situation where there is an argument (normally #1) to the template in which a key/value list can be specified that overwrites the normal settings. In that case one could use

`\SetKnownTemplateKeys{<type>}{<template>}{#1}`

to process this key/value list inside the template.

If `\SetKnownTemplateKeys` is executed and the `<keyvals>` argument contains keys not known to the `<template>` they are simply ignored and stored in the tokenlist `\UnusedTemplateKeys` without generating an error. This way it is possible to apply the same key/val list specified by the user on a document-level command or environment to several templates, which is useful, if the command or environment is implemented by calling several different template instances.

As a variation of that, you can use this key/val list the first time, and for the next template instance use what remains in `\UnusedTemplateKeys` (i.e., the key/val list with only the keys that have not been processed previously). The final processing step could then be `\SetTemplateKeys`, which unconditionally attempts to set the `<keyvals>` received in its third argument. This command complains if any of them are unknown keys. Alternatively, you could use `\SetKnownTemplateKeys` and afterwards

check whether `\UnusedTemplateKeys` is empty.<sup>23</sup>

For example, a list, such as `enumerate`, is made up from a `blockenv`, `block`, `list`, and a `para` template and in the single user-supplied optional argument of `enumerate` key/values for any of these templates might be specified.

In fact, in the particular example of list environments, the supplied key/value list is also saved and then applied to each `\item` which is implemented through an `item` template. This way, one can specify one-off settings for all the items of a single list (on the environment level), as well as to individual items within that list (by specifying them in the optional argument of an `\item`). With `\SetKnownTemplateKeys` and `\SetTemplateKeys` working together, it is possible to provide this flexibility and still alert the user when one of their keys is misspelled.

On the other hand you may want to allow for “misspellings” without generating an error or a warning. For example, if you define a template that accepts only a few keys, you might just want to ignore anything specified in the source when you use this template in place of a different one, without the need to alter the document source. Or you might just generate a warning message, which is easy, given that the unused key/values are available in the `\UnusedTemplateKeys` variable.

---

<code>\DeclareTemplateCopy</code>	<code>\DeclareTemplateCopy</code> <code>{&lt;type&gt;} {&lt;template2&gt;} {&lt;template1&gt;}</code>
-----------------------------------	--

---

Copies `<template1>` of `<type>` to a new name `<template2>`: the copy can then be edited independent of the original.

## 6 Multiple choices

The `choice` key type implements multiple choice input. At the interface level, only the list of valid choices is needed:

```
\DeclareTemplateInterface { foo } { bar } { 0 }  
  { key-name : choice { A, B, C } }
```

where the choices are given as a comma-list (which must therefore be wrapped in braces). A default value can also be given:

```
\DeclareTemplateInterface { foo } { bar } { 0 }  
  { key-name : choice { A, B, C } = A }
```

At the implementation level, each choice is associated with code, using a nested key-value list.

```
\DeclareTemplateCode { foo } { bar } { 0 }  
{  
  key-name =  
  {  
    A = Code-A ,  
    B = Code-B ,  
    C = Code-C
```

---

<sup>23</sup>Using `\SetTemplateKeys` exposes the inner structure of the template keys when generating an error. This is something one may want to avoid as it can be confusing to the user, especially if several templates are involved. In that case use `\SetKnownTemplateKeys` and afterwards check whether `\UnusedTemplateKeys` is empty; if it is not empty then generate your own error message.

```

    }
  }
  { ... }

```

The two choice lists should match, but in the implementation a special **unknown** choice is also available. This can be used to ignore values and implement an “else” branch:

```

\DeclareTemplateCode { foo } { bar } { 0 }
{
  key-name =
  {
    A      = Code-A ,
    B      = Code-B ,
    C      = Code-C ,
    unknown = Else-code
  }
}
{ ... }

```

The **unknown** entry must be the last one given, and should *not* be listed in the interface part of the template.

For keys which accept the values **true** and **false** both the boolean and choice key types can be used. As template interfaces are intended to prompt clarity at the design level, the boolean key type should be favored, with the choice type reserved for keys which take arbitrary values.

## 7 Instances

After a template is defined it still needs to be put to use. The parameters that it expects need to be defined before it can be used in a document. Every time a template has parameters given to it, an *instance* is created, and this is the code that ends up in the document to perform the typesetting of whatever pieces of information are input into it.

For example, a template might say “here is a section with or without a number that might be centered or left aligned and print its contents in a certain font of a certain size, with a bit of a gap before and after it” whereas an instance declares “this is a section with a number, which is centered and set in 12pt italic with a 10pt skip before and a 12pt skip after it”. Therefore, an instance is just a frozen version of a template with specific settings as chosen by the designer.

---



---

<code>\DeclareInstance</code>	<code>\DeclareInstance</code>
-------------------------------	-------------------------------

<code>{\type}</code>	<code>{\instance}</code>	<code>{\template}</code>	<code>{\parameters}</code>
----------------------	--------------------------	--------------------------	----------------------------

This function uses a `\template` for an `\type` to create an `\instance`. The `\instance` will be set up using the `\parameters`, which will set some of the `\keys` in the `\template`.

As a practical example, consider a type for document sections (which might include chapters, parts, sections, *etc.*), which is called `sectioning`. One possible template for this type might be called `basic`, and one instance of this template would be a numbered section. The instance declaration might read:

```
\DeclareInstance { sectioning } { section-num } { basic }
{
  numbered      = true ,
  justification = center ,
  font          =\normalsize\itshape ,
  before-skip   = 10pt ,
  after-skip    = 12pt ,
}
```

Of course, the key names here are entirely imaginary, but illustrate the general idea of fixing some settings.

---

<code>\IfInstanceExistsT</code>	<code>\IfInstanceExistsTF</code>	<code>{\type}</code>	<code>{\instance}</code>	<code>{\true code}</code>	<code>{\false code}</code>
---------------------------------	----------------------------------	----------------------	--------------------------	---------------------------	----------------------------

---

<code>\IfInstanceExistsF</code>
---------------------------------

---

<code>\IfInstanceExistsTF</code>
----------------------------------

Tests if the named `\instance` of a `\type` exists, and then inserts the appropriate code into the input stream.

---

<code>\DeclareInstanceCopy</code>	<code>\DeclareInstanceCopy</code>
-----------------------------------	-----------------------------------

<code>{\type}</code>	<code>{\instance2}</code>	<code>{\instance1}</code>
----------------------	---------------------------	---------------------------

Copies the `\values` for `\instance1` for an `\type` to `\instance2`.

## 8 Document interface

After the instances have been chosen, document commands must be declared to use those instances in the document. `\UseInstance` calls instances directly, and this command should be used internally in document-level mark-up.

---

<code>\UseInstance</code>	<code>\UseInstance</code>
---------------------------	---------------------------

<code>{\type}</code>	<code>{\instance}</code>	<code>\arguments</code>
----------------------	--------------------------	-------------------------

Uses an `\instance` of the `\type`, which will require `\arguments` as determined by the number specified for the `\type`. The `\instance` must have been declared before it can be used, otherwise an error is raised.

---

<code>\UseTemplate</code>	<code>\UseTemplate {&lt;type&gt;} {&lt;template&gt;}</code> <code>{&lt;settings&gt;} &lt;arguments&gt;</code>
---------------------------	--

---

Uses the `<template>` of the specified `<type>`, applying the `<settings>` and absorbing `<arguments>` as detailed by the `<type>` declaration. This in effect is the same as creating an instance using `\DeclareInstance` and immediately using it with `\UseInstance`, but without the instance having any further existence. This command is therefore useful when a template needs to be used only once.

This function can also be used as the argument to `instance` key types:

```
\DeclareInstance { type } { template } { instance }
{
  instance-key =
    \UseTemplate { type2 } { template2 } { <settings> }
}
```

## 9 Changing existing definitions

Template parameters may be assigned specific defaults for instances to use if the instance declaration doesn't explicit set those parameters. In some cases, the document designer will wish to edit these defaults to allow them to “cascade” to the instances. The alternative would be to set each parameter identically for each instance declaration, a tedious and error-prone process.

---

<code>\EditTemplateDefaults</code>	<code>\EditTemplateDefaults</code> <code>{&lt;type&gt;} {&lt;template&gt;} {&lt;new defaults&gt;}</code>
------------------------------------	---

---

Edits the `<defaults>` for a `<template>` for an `<type>`. The `<new defaults>`, given as a key–value list, replace the existing defaults for the `<template>`. This means that the change will apply to instances declared after the editing, but that instances which have already been created are unaffected.

---

<code>\EditInstance</code>	<code>\EditInstance</code> <code>{&lt;type&gt;} {&lt;instance&gt;} {&lt;new values&gt;}</code>
----------------------------	---

---

Edits the `<values>` for an `<instance>` for an `<type>`. The `<new values>`, given as a key–value list, replace the existing values for the `<instance>`. This function is complementary to `\EditTemplateDefaults`: `\EditInstance` changes a single instance while leaving the template untouched.

### 9.1 Expanding the values of keys

To allow the user to apply expansion of values when the key is set, key names can be followed by an expansion specifier. This is given by appending `:` and a single letter specifier to the key name. These letters are the normal argument specifiers for `expl3`, thus they may be one of `n` (redundant but supported), `o`, `V`, `v`, `e`, `N` (again redundant) or `c`. Expansion of a control sequence name is particularly useful when you need to refer to an internal L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> or an L<sup>3</sup> programming layer variable, e.g.,

```
key-a:c = @itemdepth , % use \@itemdepth as the value
key-b:v = @itemdepth   % use the current value of \@itemdepth as the value
```

## 10 Getting information about templates and instances

<hr/> <hr/>	<code>\ShowInstanceValues {&lt;type&gt;} {&lt;instance&gt;}</code>	Shows the <i>&lt;values&gt;</i> for an <i>&lt;instance&gt;</i> of the given <i>&lt;type&gt;</i> at the terminal.
<hr/> <hr/>	<code>\ShowTemplateCode {&lt;type&gt;} {&lt;template&gt;}</code>	Shows the <i>&lt;code&gt;</i> of a <i>&lt;template&gt;</i> for an <i>&lt;type&gt;</i> in the terminal.
<hr/> <hr/>	<code>\ShowTemplateDefaults {&lt;type&gt;} {&lt;template&gt;}</code>	Shows the <i>&lt;default&gt;</i> values of a <i>&lt;template&gt;</i> for an <i>&lt;type&gt;</i> in the terminal.
<hr/> <hr/>	<code>\ShowTemplateInterface {&lt;type&gt;} {&lt;template&gt;}</code>	Shows the <i>&lt;keys&gt;</i> and associated <i>&lt;key types&gt;</i> of a <i>&lt;template&gt;</i> for an <i>&lt;type&gt;</i> in the terminal.
<hr/> <hr/>	<code>\ShowTemplateVariables {&lt;type&gt;} {&lt;template&gt;}</code>	Shows the <i>&lt;variables&gt;</i> and associated <i>&lt;keys&gt;</i> of a <i>&lt;template&gt;</i> for an <i>&lt;type&gt;</i> in the terminal. Note that <i>code</i> and <i>choice</i> keys do not map directly to variables but to arbitrary code. For <i>choice</i> keys, each valid choice is shown as a separate entry in the list, with the key name and choice separated by a space, for example <div style="margin-left: 40px;"> <p>Template 'example' of type 'example' has variable mapping:</p> <pre> &gt; demo unknown =&gt; \def \demo {?} &gt; demo c      =&gt; \def \demo {c} &gt; demo b      =&gt; \def \demo {b} &gt; demo a      =&gt; \def \demo {a}.</pre> </div> <p>would be shown for a choice key <i>demo</i> with valid choices <i>a</i>, <i>b</i> and <i>c</i>, plus code for an <i>unknown</i> branch.</p>

## 11 The implementation

```

1 <@@=template>
2 <*2kernel>
3 \message{templates,}
4 </2kernel>
5 <*2kernel | latexrelease>
6 \ExplSyntaxOn
7 <latexrelease> \NewModuleRelease{2024/06/01}{lttemplates}
8 <latexrelease> {Prototype-document~commands}%

```

## 11.1 Variables and constants

---

```
\c__template_code_root_tl
\c__template_defaults_root_tl
\c__template_instances_root_tl
\c__template_keytypes_root_tl
\c__template_key_order_root_tl
\c__template_restrict_root_tl
\c__template_values_root_tl
\c__template_vars_root_tl
```

---

So that literal values are kept to a minimum.

```
9 \tl_const:Nn \c__template_code_root_tl { template~code~>~ }
10 \tl_const:Nn \c__template_defaults_root_tl { template~defaults~>~ }
11 \tl_const:Nn \c__template_instances_root_tl { template~instance~>~ }
12 \tl_const:Nn \c__template_keytypes_root_tl { template~key~types~>~ }
13 \tl_const:Nn \c__template_key_order_root_tl { template~key~order~>~ }
14 \tl_const:Nn \c__template_values_root_tl { template~values~>~ }
15 \tl_const:Nn \c__template_vars_root_tl { template~vars~>~ }
```

---

```
\c__template_keytypes_arg_seq
```

---

A list of keytypes which also need additional data (an argument), used to parse the keytype correctly.

```
16 \seq_const_from_clist:Nn \c__template_keytypes_arg_seq
17 { choice , function , instance }
```

---

```
\g__template_type_prop
```

---

For storing types and the associated number of arguments.

```
18 \prop_new:N \g__template_type_prop
```

---

```
\l__template_assignments_tl
```

---

When creating an instance, the assigned values are collected here.

```
19 \tl_new:N \l__template_assignments_tl
```

---

```
\l__template_default_tl
```

---

The default value for a key is recovered here from the property list in which it is stored.

```
20 \tl_new:N \l__template_default_tl
```

---

```
\l__template_error_bool
```

---

A flag for errors to be carried forward.

```
21 \bool_new:N \l__template_error_bool
```

---

```
\l__template_global_bool
```

---

Used to indicate that assignments should be global.

```
22 \bool_new:N \l__template_global_bool
```

---

```

\l__template_key_name_tl
\l__template_keytype_tl
\l__template_keytype_arg_tl
\l__template_value_tl
\l__template_var_tl

```

---

When defining each key in a template, the name and type of the key need to be separated and stored. Any argument needed by the keytype is also stored separately.

```

23 \tl_new:N \l__template_key_name_tl
24 \tl_new:N \l__template_keytype_tl
25 \tl_new:N \l__template_keytype_arg_tl
26 \tl_new:N \l__template_value_tl
27 \tl_new:N \l__template_var_tl

```

---

```

\l__template_value_exp_str

```

---

```

28 \str_new:N \l__template_value_exp_str

```

---

```

\l__template_keytypes_prop
\l__template_key_order_seq
\l__template_values_prop
\l__template_vars_prop

```

---

To avoid needing too many difficult-to-follow csname assignments, various scratch token registers are used to build up data, which is then transferred

```

29 \prop_new:N \l__template_keytypes_prop
30 \seq_new:N \l__template_key_order_seq
31 \prop_new:N \l__template_values_prop
32 \prop_new:N \l__template_vars_prop

```

---

```

\l__template_tmp_clist
\l__template_tmp_dim
\l__template_tmp_int
\l__template_tmp_muskip
\l__template_tmp_skip
\l__template_tmp_tl

```

---

Scratch space.

```

33 \clist_new:N \l__template_tmp_clist
34 \dim_new:N \l__template_tmp_dim
35 \int_new:N \l__template_tmp_int
36 \muskip_new:N \l__template_tmp_muskip
37 \skip_new:N \l__template_tmp_skip
38 \tl_new:N \l__template_tmp_tl

```

---

```

\s__template_mark
\s__template_stop

```

---

Internal scan marks.

```

39 \scan_new:N \s__template_mark
40 \scan_new:N \s__template_stop

```

---

```

\q__template_nil

```

---

Internal quarks.

```

41 \quark_new:N \q__template_nil

```

```

\__template_quark_if_nil_p:n
\__template_quark_if_nil:nTF

```

Branching quark conditional.

```

42 \__kernel_quark_new_conditional:Nn \__template_quark_if_nil:N { F }

```

(End of definition for \\_\_template\_quark\_if\_nil:nTF.)

## 11.2 Testing existence and validity

There are a number of checks needed for either the existence of a type, template or instance. There are also some for the validity of a particular call. All of these are collected up here.

`\_template\_execute\_if\_arg\_agree:nnT`

A test agreement between the number of arguments for the template type and that specified when creating a template. This is not done as a separate conditional for efficiency and better error message

```

43 \cs_new_protected:Npn \_template\_execute\_if\_arg\_agree:nnT #1#2#3
44 {
45   \prop_get:NnN \g__template_type_prop {#1} \l__template_tmp_tl
46   \int_compare:nNnTF {#2} = \l__template_tmp_tl
47     {#3}
48   {
49     \msg_error:nneee { template } { argument-number-mismatch }
50     {#1} { \l__template_tmp_tl } {#2}
51   }
52 }
```

*(End of definition for \\_template\\_execute\\_if\\_arg\\_agree:nnT.)*

`\_template\_execute\_if\_code\_exist:nnT`

A template is only fully declared if the code has been set up, which can be checked by looking for the template function itself.

```

53 \cs_new_protected:Npn \_template\_execute\_if\_code\_exist:nnT #1#2#3
54 {
55   \cs_if_exist:ctF { \c__template_code_root_tl #1 / #2 }
56   {#3}
57   { \msg_error:nnnn { template } { no-template-code } {#1} {#2} }
58 }
```

*(End of definition for \\_template\\_execute\\_if\\_code\\_exist:nnT.)*

`\_template\_execute\_if\_keytype\_exist:nT`

The test for valid keytypes looks for a function to set up the key, which is part of the “code” side of the template definition. This avoids having different lists for the two parts of the process.

```

59 \cs_new_protected:Npn \_template\_execute\_if\_keytype\_exist:nT #1#2
60 {
61   \cs_if_exist:ctF { __template_store_value_ #1 :n }
62   {#2}
63   { \msg_error:nnn { template } { unknown-keytype } {#1} }
64 }
65 \cs_generate_variant:Nn \_template\_execute\_if\_keytype\_exist:nT { V }
```

*(End of definition for \\_template\\_execute\\_if\\_keytype\\_exist:nT.)*

`\_template\_execute\_if\_type\_exist:nT`

To check that a particular type is valid.

```

66 \cs_new_protected:Npn \_template\_execute\_if\_type\_exist:nT #1#2
67 {
68   \prop_if_in:NnTF \g__template_type_prop {#1}
69   {#2}
70   { \msg_error:nnn { template } { unknown-type } {#1} }
71 }
```

*(End of definition for \\_template\\_execute\\_if\\_type\\_exist:nT.)*

`\_template\_execute\_if\_keys\_exist:nnT` To check that the keys for a template have been set up before trying to create any code, a simple check for the correctly-named keytype property list.

```

72 \cs_new_protected:Npn \_template_if_keys_exist:nnT #1#2#3
73 {
74     \cs_if_exist:cTF { \c__template_keytypes_root_tl #1 / #2 }
75     {#3}
76     { \msg_error:nnnn { template } { unknown-template } {#1} {#2} }
77 }

```

*(End of definition for \\_template\\_execute\\_if\\_keys\\_exist:nnT.)*

`\_template\_if\_key\_value:nTF` Tests for the first token in a string being `\KeyValue`.

`\_template\_if\_key\_value:VTF`

```

78 \prg_new_conditional:Npnn \_template_if_key_value:n #1 { T , F , TF }
79 {
80     \str_if_eq:noTF { \KeyValue } { \tl_head:w #1 \q_nil \q_stop }
81     \prg_return_true:
82     \prg_return_false:
83 }
84 \prg_generate_conditional_variant:Nnn \_template_if_key_value:n { V } { T , F , TF }

```

*(End of definition for \\_template\\_if\\_key\\_value:nTF.)*

`\_template\_if\_instance\_exist:nnTF` Testing for an instance

```

85 \prg_new_conditional:Npnn \_template_if_instance_exist:nn #1#2 { T, F, TF }
86 {
87     \cs_if_exist:cTF { \c__template_instances_root_tl #1 / #2 }
88     \prg_return_true:
89     \prg_return_false:
90 }

```

*(End of definition for \\_template\\_if\\_instance\\_exist:nnTF.)*

`\_template\_if\_use\_template:nTF` Tests for the first token in a string being `\UseTemplate`.

```

91 \prg_new_conditional:Npnn \_template_if_use_template:n #1 { TF }
92 {
93     \str_if_eq:noTF { \UseTemplate } { \tl_head:w #1 \q_nil \q_stop }
94     \prg_return_true:
95     \prg_return_false:
96 }

```

*(End of definition for \\_template\\_if\\_use\\_template:nTF.)*

## 11.3 Saving and recovering property lists

The various property lists for templates have to be shuffled in and out of storage.

`\_template\_store\_defaults:nn`

`\_template\_store\_keytypes:nn`

`\_template\_store\_values:nn`

`\_template\_store\_vars:nn`

The defaults and keytypes are transferred from the scratch property lists to the “proper” lists for the template being created.

```

97 \cs_new_protected:Npn \_template_store_defaults:nn #1#2
98 {
99     \debug_suspend:
100     \prop_gclear_new:c { \c__template_defaults_root_tl #1 / #2 }
101     \prop_gset_eq:cN { \c__template_defaults_root_tl #1 / #2 }
102     \l__template_values_prop

```

```

103     \debug_resume:
104 }
105 \cs_new_protected:Npn \__template_store_keytypes:nn #1#2
106 {
107     \debug_suspend:
108     \prop_if_exist:cTF { \c__template_keytypes_root_tl #1 / #2 }
109     {
110         \msg_info:nnnn { template } { declare-template-interface } {#1} {#2}
111         \prop_gclear:c { \c__template_keytypes_root_tl #1 / #2 }
112     }
113     { \prop_new:c { \c__template_keytypes_root_tl #1 / #2 } }
114     \prop_gset_eq:cN { \c__template_keytypes_root_tl #1 / #2 }
115     \l__template_keytypes_prop
116     \seq_gclear_new:c { \c__template_key_order_root_tl #1 / #2 }
117     \seq_gset_eq:cN { \c__template_key_order_root_tl #1 / #2 }
118     \l__template_key_order_seq
119     \debug_resume:
120 }
121 \cs_new_protected:Npn \__template_store_values:nn #1#2
122 {
123     \debug_suspend:
124     \prop_clear_new:c { \c__template_values_root_tl #1 / #2 }
125     \prop_set_eq:cN { \c__template_values_root_tl #1 / #2 }
126     \l__template_values_prop
127     \debug_resume:
128 }
129 \cs_new_protected:Npn \__template_store_vars:nn #1#2
130 {
131     \debug_suspend:
132     \prop_gclear_new:c { \c__template_vars_root_tl #1 / #2 }
133     \prop_gset_eq:cN { \c__template_vars_root_tl #1 / #2 }
134     \l__template_vars_prop
135     \debug_resume:
136 }

```

(End of definition for \\_\_template\_store\_defaults:nn and others.)

```

\__template_recover_defaults:nn
\__template_recover_keytypes:nn
\__template_recover_values:nn
\__template_recover_vars:nn

```

Recovering the stored data for a template is rather less complex than storing it. All that happens is the data is transferred from the permanent to the scratch storage. However, we need to check the scratch storage does exist.

```

137 \cs_new_protected:Npn \__template_recover_defaults:nn #1#2
138 {
139     \prop_if_exist:cTF
140     { \c__template_defaults_root_tl #1 / #2 }
141     {
142         \prop_set_eq:Nc \l__template_values_prop
143         { \c__template_defaults_root_tl #1 / #2 }
144     }
145     { \prop_clear:N \l__template_values_prop }
146 }
147 \cs_new_protected:Npn \__template_recover_keytypes:nn #1#2
148 {
149     \prop_if_exist:cTF
150     { \c__template_keytypes_root_tl #1 / #2 }

```

```

151     {
152         \prop_set_eq:Nc \l__template_keytypes_prop
153         { \c__template_keytypes_root_tl #1 / #2 }
154     }
155     { \prop_clear:N \l__template_keytypes_prop }
156 \seq_if_exist:cTF { \c__template_key_order_root_tl #1 / #2 }
157     {
158         \seq_set_eq:Nc \l__template_key_order_seq
159         { \c__template_key_order_root_tl #1 / #2 }
160     }
161     { \seq_clear:N \l__template_key_order_seq }
162 }
163 \cs_new_protected:Npn \__template_recover_values:nn #1#2
164 {
165     \prop_if_exist:cTF
166     { \c__template_values_root_tl #1 / #2 }
167     {
168         \prop_set_eq:Nc \l__template_values_prop
169         { \c__template_values_root_tl #1 / #2 }
170     }
171     { \prop_clear:N \l__template_values_prop }
172 }
173 \cs_new_protected:Npn \__template_recover_vars:nn #1#2
174 {
175     \prop_if_exist:cTF
176     { \c__template_vars_root_tl #1 / #2 }
177     {
178         \prop_set_eq:Nc \l__template_vars_prop
179         { \c__template_vars_root_tl #1 / #2 }
180     }
181     { \prop_clear:N \l__template_vars_prop }
182 }

```

(End of definition for \\_\_template\_recover\_defaults:nn and others.)

## 11.4 Creating new template types

\\_\_template\_define\_type:nn Although the type is the “top level” of the template system, it is actually very easy to implement. All that happens is that the number of arguments required is recorded, indexed by the name of the type.

```

183 \cs_new_protected:Npn \__template_define_type:nn #1#2
184 {
185     \prop_if_in:NnTF \g__template_type_prop {#1}
186     { \msg_error:nnn { template } { type-already-defined } {#1} }
187     { \__template_declare_type:nn {#1} {#2} }
188 }
189 \cs_new_protected:Npn \__template_declare_type:nn #1#2
190 {
191     \int_set:Nn \l__template_tmp_int {#2}
192     \int_compare:nTF { 0 <= \l__template_tmp_int <= 9 }
193     {
194         \msg_info:nnnV { template } { declare-type }
195         {#1} \l__template_tmp_int
196         \prop_gput:NnV \g__template_type_prop {#1}

```

```

197         \l__template_tmp_int
198     }
199     {
200         \msg_error:nnnV { template } { bad-number-of-arguments }
201         {#1} \l__template_tmp_int
202     }
203 }

```

(End of definition for `\__template_define_type:nn` and `\__template_declare_type:nn`.)

## 11.5 Design part of template declaration

The “design” part of a template declaration defines the general behaviour of each key, and possibly a default value. However, it does not include the implementation. This means that what happens here is the two properties are saved to appropriate lists, which can then be used later to recover the information when implementing the keys.

`\__template_declare_template_keys:nnnn`

The main function for the “design” part of creating a template starts by checking that the type exists and that the number of arguments required agree. If that is all fine, then the two storage areas for defaults and keytypes are initialised. The mechanism is then set up for the `l3keys` module to actually parse the keys. Finally, the code hands of to the storage routine to save the parsed information properly.

```

204 \cs_new_protected:Npn \__template_declare_template_keys:nnnn #1#2#3#4
205 {
206     \__template_execute_if_type_exist:nT {#1}
207     {
208         \__template_execute_if_arg_agree:nnT {#1} {#3}
209         {
210             \prop_clear:N \l__template_values_prop
211             \prop_clear:N \l__template_keytypes_prop
212             \seq_clear:N \l__template_key_order_seq
213             \keyval_parse:NNn
214             \__template_parse_keys_elt:n \__template_parse_keys_elt:nn {#4}
215             \__template_store_defaults:nn {#1} {#2}
216             \__template_store_keytypes:nn {#1} {#2}
217         }
218     }
219 }

```

(End of definition for `\__template_declare_template_keys:nnnn`.)

`\__template_parse_keys_elt:n`

`\__template_parse_keys_elt_aux:n`

`\__template_parse_keys_elt_aux:`

Processing the key part of the key–value pair is always carried out using this function, even if a value was found. First, the key name is separated from the keytype, and if necessary the keytype is separated into two parts. This information is then used to check that the keytype is valid, before storing the keytype (plus argument if necessary) as a property of the key name. The key name is also stored (in braces) in the token list to record the order the keys are defined in.

```

220 \cs_new_protected:Npn \__template_parse_keys_elt:n #1
221 {
222     \__template_split_keytype:n {#1}
223     \bool_if:NF \l__template_error_bool
224     {
225         \__template_execute_if_keytype_exist:VT \l__template_keytype_tl

```

```

226     {
227         \seq_map_function:NN \c__template_keytypes_arg_seq
228         \__template_parse_keys_elt_aux:n
229         \bool_if:NF \l__template_error_bool
230         {
231             \seq_if_in:NoTF \l__template_key_order_seq
232             \l__template_key_name_tl
233             {
234                 \msg_error:nnV { template } { duplicate-key-interface }
235                 \l__template_key_name_tl
236             }
237             { \__template_parse_keys_elt_aux: }
238         }
239     }
240 }
241 }
242 \cs_new_protected:Npn \__template_parse_keys_elt_aux:n #1
243 {
244     \str_if_eq:VnT \l__template_keytype_tl {#1}
245     {
246         \tl_if_empty:NT \l__template_keytype_arg_tl
247         {
248             \msg_error:nnn { template } { keytype-requires-argument } {#1}
249             \bool_set_true:N \l__template_error_bool
250             \seq_map_break:
251         }
252     }
253 }
254 \cs_new_protected:Npn \__template_parse_keys_elt_aux:
255 {
256     \tl_set:Ne \l__template_tmp_tl
257     {
258         \l__template_keytype_tl
259         \tl_if_empty:NF \l__template_keytype_arg_tl
260         { { \l__template_keytype_arg_tl } }
261     }
262     \prop_put:NVV \l__template_keytypes_prop \l__template_key_name_tl
263     \l__template_tmp_tl
264     \seq_put_right:NV \l__template_key_order_seq \l__template_key_name_tl
265     \str_if_eq:VnT \l__template_keytype_tl { choice }
266     {
267         \clist_if_in:NnT \l__template_keytype_arg_tl { unknown }
268         { \msg_error:nn { template } { choice-unknown-reserved } }
269     }
270 }

```

(End of definition for \\_\_template\_parse\_keys\_elt:n, \\_\_template\_parse\_keys\_elt\_aux:n, and \\_\_template\_parse\_keys\_elt\_aux:.)

\\_\_template\_parse\_keys\_elt:nn For keys which have a default, the keytype and key name are first separated out by the \\_\_template\_parse\_keys\_elt:n routine, before storing the default value in the scratch property list.

```

271 \cs_new_protected:Npn \__template_parse_keys_elt:nn #1#2
272 {

```

```

273 \__template_parse_keys_elt:n {#1}
274 \use:c { __template_store_value_ \l__template_keytype_tl :n } {#2}
275 }

```

(End of definition for \\_\_template\_parse\_keys\_elt:nn.)

```

\__template_split_keytype:n
  \__template_split_keytype_aux:w

```

The keytype and key name should be separated by :. As the definition might be given inside or outside of a code block, the category code of colons is standardised. After that, the standard delimited argument method is used to separate the two parts.

```

276 \cs_new_protected:Npe \__template_split_keytype:n #1
277 {
278   \exp_not:N \bool_set_false:N \exp_not:N \l__template_error_bool
279   \tl_set:Nn \exp_not:N \l__template_tmp_tl {#1}
280   \tl_replace_all:Nnn \exp_not:N \l__template_tmp_tl { : } { \token_to_str:N : }
281   \tl_if_in:VnTF \exp_not:N \l__template_tmp_tl { \token_to_str:N : }
282   {
283     \exp_not:n
284     {
285       \tl_clear:N \l__template_key_name_tl
286       \exp_after:wN \__template_split_keytype_aux:w
287       \l__template_tmp_tl \s__template_stop
288     }
289   }
290   {
291     \exp_not:N \bool_set_true:N \exp_not:N \l__template_error_bool
292     \msg_error:nnn { template } { missing-keytype } {#1}
293   }
294 }
295 \use:e
296 {
297   \cs_new_protected:Npn \exp_not:N \__template_split_keytype_aux:w
298   #1 \token_to_str:N : #2 \s__template_stop
299   {
300     \tl_put_right:Ne \exp_not:N \l__template_key_name_tl
301     {
302       \exp_not:N \tl_trim_spaces:e
303       { \exp_not:N \tl_to_str:n {#1} }
304     }
305     \tl_if_in:nnTF {#2} { \token_to_str:N : }
306     {
307       \tl_put_right:Nn \exp_not:N \l__template_key_name_tl
308       { \token_to_str:N : }
309       \exp_not:N \__template_split_keytype_aux:w #2 \s__template_stop
310     }
311     {
312       \exp_not:N \tl_if_empty:NTF \exp_not:N \l__template_key_name_tl
313       {
314         \msg_error:nnn { template } { empty-key-name }
315         { \token_to_str:N : #2 }
316       }
317       { \exp_not:N \__template_split_keytype_arg:n {#2} }
318     }
319   }
320 }

```

(End of definition for `\__template_split_keytype:n` and `\__template_split_keytype_aux:w`.)

`\__template_split_keytype_arg:n`  
`\__template_split_keytype_arg:V`  
`\__template_split_keytype_arg_aux:n`  
`\__template_split_keytype_arg_aux:w`

The second stage of sorting out the keytype is to check for an argument. As there is no convenient delimiting token to look for, a check is made instead for each possible text value for the keytype. To keep things faster, this only involves the keytypes that need an argument. If a match is made, then a check is also needed to see that it is at the start of the keytype information. All being well, the split can then be applied. Any non-matching keytypes are assumed to be “correct” as given, and are left alone (this is checked by other code).

```

321 \cs_new_protected:Npn \__template_split_keytype_arg:n #1
322 {
323   \tl_set:Nx \l__template_keytype_tl { \tl_trim_spaces:n {#1} }
324   \tl_clear:N \l__template_keytype_arg_tl
325   \cs_set_protected:Npn \__template_split_keytype_arg_aux:n ##1
326   {
327     \tl_if_in:nnT {#1} {##1}
328     {
329       \cs_set:Npn \__template_split_keytype_arg_aux:w
330       ####1 ##1 ####2 \s__template_stop
331       {
332         \tl_if_blank:nT {####1}
333         {
334           \tl_set:Nx \l__template_keytype_tl
335           { \tl_trim_spaces:n {##1} }
336           \tl_if_blank:nF {####2}
337           {
338             \tl_set:Nx \l__template_keytype_arg_tl
339             { \use:n {####2} }
340           }
341           \seq_map_break:
342         }
343       }
344       \__template_split_keytype_arg_aux:w #1 \s__template_stop
345     }
346   }
347   \seq_map_function:NN \c__template_keytypes_arg_seq
348   \__template_split_keytype_arg_aux:n
349 }
350 \cs_generate_variant:Nn \__template_split_keytype_arg:n { V }
351 \cs_new:Npn \__template_split_keytype_arg_aux:n #1 { }
352 \cs_new:Npn \__template_split_keytype_arg_aux:w #1 \s__template_stop { }

```

(End of definition for `\__template_split_keytype_arg:n`, `\__template_split_keytype_arg_aux:n`,  
and `\__template_split_keytype_arg_aux:w`.)

### 11.5.1 Storing values

As `ltxtemplates` pre-processes key values for efficiency reasons, there is a need to convert the values given as defaults into “ready to use” data. The same general idea is true when an instance is declared. However, assignments are not made until an instance is used, and so there has to be some intermediate storage. Furthermore, the ability to delay evaluation of results is needed. To achieve these aims, a series of “process and store” functions are defined here.

All of the information about the key (the key name and the keytype) is already stored as variables. The same property list is always used to store the data, meaning that the only argument required is the value to be processed and potentially stored.

```

\__template_store_value_boolean:n
353 \cs_new_protected:Npn \__template_store_value_boolean:n #1
354   { \prop_put:Non \l__template_values_prop \l__template_key_name_tl {#1} }

(End of definition for \__template_store_value_boolean:n.)

\__template_store_value:n
\__template_store_value_choice:n
\__template_store_value_function:n
\__template_store_value_instance:n
355 \cs_new_protected:Npn \__template_store_value:n #1
356   { \prop_put:Non \l__template_values_prop \l__template_key_name_tl {#1} }
357 \cs_new_eq:NN \__template_store_value_choice:n \__template_store_value:n
358 \cs_new_eq:NN \__template_store_value_function:n \__template_store_value:n
359 \cs_new_eq:NN \__template_store_value_instance:n \__template_store_value:n

(End of definition for \__template_store_value:n and others.)

```

```

\__template_store_value_aux:Nn
\__template_store_value_integer:n
\__template_store_value_length:n
\__template_store_value_muskip:n
\__template_store_value_real:n
\__template_store_value_skip:n
\__template_store_value_tokenlist:n
\__template_store_value_commalist:n
239 Storing values in \l__template_values_prop is in most cases the same.
360 \cs_new_protected:Npn \__template_store_value_aux:Nn #1#2
361   { \prop_put:Non \l__template_values_prop \l__template_key_name_tl {#2} }
362 \cs_new_protected:Npn \__template_store_value_integer:n
363   { \__template_store_value_aux:Nn \int_eval:n }
364 \cs_new_protected:Npn \__template_store_value_length:n
365   { \__template_store_value_aux:Nn \dim_eval:n }
366 \cs_new_protected:Npn \__template_store_value_muskip:n
367   { \__template_store_value_aux:Nn \muskip_eval:n }
368 \cs_new_protected:Npn \__template_store_value_real:n
369   { \__template_store_value_aux:Nn \fp_eval:n }
370 \cs_new_protected:Npn \__template_store_value_skip:n
371   { \__template_store_value_aux:Nn \skip_eval:n }
372 \cs_new_protected:Npn \__template_store_value_tokenlist:n
373   { \__template_store_value_aux:Nn \use:n }
374 \cs_new_eq:NN \__template_store_value_commalist:n \__template_store_value_tokenlist:n

(End of definition for \__template_store_value_aux:Nn and others.)

```

## 11.6 Implementation part of template declaration

The main function for implementing a template starts with a couple of simple checks to make sure that there are no obvious mistakes: the number of arguments must agree and the template keys must have been declared.

```

\__template_declare_template_code:nnnnn
\__template_declare_template_code:nnnn
375 \cs_new_protected:Npn \__template_declare_template_code:nnnnn #1#2#3#4#5
376   {
377     \__template_execute_if_type_exist:nT {#1}
378     {
379       \__template_execute_if_arg_agree:nnT {#1} {#3}
380       {
381         \__template_if_keys_exist:nnT {#1} {#2}
382         {
383           \__template_store_key_implementation:nnn {#1} {#2} {#4}
384           \str_if_in:nnTF {#5} { AssignTemplateKeys }

```

```

385         {
386             \regex_match:nnTF { \c { AssignTemplateKeys } } {#5}
387             { \__template_declare_template_code:nnnn {#1} {#2} {#3} {#5} }
388             {
389                 \__template_declare_template_code:nnnn
390                 {#1} {#2} {#3} { \AssignTemplateKeys #5 }
391             }
392         }
393     {
394         \__template_declare_template_code:nnnn
395         {#1} {#2} {#3} { \AssignTemplateKeys #5 }
396     }
397 }
398 }
399 }
400 }
401 \cs_new_protected:Npn \__template_declare_template_code:nnnn #1#2#3#4
402 {
403     \cs_if_exist:cT { \c__template_code_root_tl #1 / #2 }
404     { \msg_info:nnnn { template } { declare-template-code } {#1} {#2} }
405     \cs_generate_from_arg_count:cNnn
406     { \c__template_code_root_tl #1 / #2 }
407     \cs_gset_protected:Npn {#3} {#4}
408 }

```

(End of definition for \\_\_template\_declare\_template\_code:nnnn and  
\\_\_template\_declare\_template\_code:nnnn.)

\\_\_template\_store\_key\_implementation:nnn

Actually storing the implementation part of a template is quite easy as it only requires the list of keys given to be turned into a property list. There is also some error-checking to do, hence the need to have the list of defined keytypes available. In certain cases (when choices are involved) parsing the key results in changes to the default values. That is why they are loaded and then saved again.

```

409 \cs_new_protected:Npn \__template_store_key_implementation:nnn #1#2#3
410 {
411     \__template_recover_defaults:nn {#1} {#2}
412     \__template_recover_keytypes:nn {#1} {#2}
413     \prop_clear:N \l__template_vars_prop
414     \keyval_parse:nnn
415     { \__template_parse_vars_elt:n } { \__template_parse_vars_elt:nnn { #1 / #2 } } {#3}
416     \__template_store_vars:nn {#1} {#2}
417     \prop_map_inline:Nn \l__template_keytypes_prop
418     { \msg_error:nnnnn { template } { key-not-implemented } {##1} {#2} {#1} }
419 }

```

(End of definition for \\_\_template\_store\_key\_implementation:nnn.)

\\_\_template\_parse\_vars\_elt:n

At the implementation stage, every key must have a value given. So this is an error function.

```

420 \cs_new_protected:Npn \__template_parse_vars_elt:n #1
421 { \msg_error:nnn { template } { key-no-variable } {#1} }

```

(End of definition for \\_\_template\_parse\_vars\_elt:n.)

```

\__template_parse_vars_elt:nnn
\__template_parse_vars_elt_aux:nn
\__template_parse_vars_elt_aux:nw
\__template_parse_vars_elt_aux:nnn
\__template_parse_vars_elt_aux:nne
\__template_parse_vars_elt_key:nn

```

The actual storage part here is very simple: the storage bin name is placed into the property list. At the same time, a comparison is made with the keytypes defined earlier: if there is a mismatch then an error is raised.

```

422 \cs_new_protected:Npn \__template_parse_vars_elt:nnn #1#2#3
423 {
424   \tl_set:Nx \l__template_key_name_tl
425     { \tl_trim_spaces:e { \tl_to_str:n {#2} } }
426   \prop_get:NVNTF \l__template_keytypes_prop
427     \l__template_key_name_tl
428     \l__template_keytype_tl
429     {
430       \__template_split_keytype_arg:V \l__template_keytype_tl
431       \__template_parse_vars_elt_aux:nn {#1} {#3}
432       \prop_remove:NV \l__template_keytypes_prop \l__template_key_name_tl
433     }
434   { \msg_error:nnn { template } { unknown-key } {#2} }
435 }

```

Split off any leading global and they look for the way to implement.

```

436 \cs_new_protected:Npn \__template_parse_vars_elt_aux:nn #1#2
437 {
438   \__template_parse_vars_elt_aux:nw {#1} #2 global global \s__template_stop
439 }
440 \cs_new_protected:Npn \__template_parse_vars_elt_aux:nw
441   #1#2 global #3 global #4 \s__template_stop
442 {
443   \tl_if_blank:nTF {#4}
444     { \__template_parse_vars_elt_aux:nnn {#1} { } {#2} }
445     {
446       \tl_if_blank:nTF {#2}
447       {
448         \__template_parse_vars_elt_aux:nne
449           {#1} { global } { \tl_trim_spaces:n {#3} }
450       }
451       { \msg_error:nnn { template } { bad-variable } { #2 global #3 } }
452     }
453 }
454 \cs_new_protected:Npn \__template_parse_vars_elt_aux:nnn #1#2#3
455 {
456   \str_case:VnF \l__template_keytype_tl
457   {
458     { choice } { \__template_implement_choices:nn {#1} {#3} }
459     { function }
460     {
461       \cs_if_exist:NF #3
462       { \cs_new:Npn #3 { } }
463       \__template_parse_vars_elt_key:nn {#1}
464       {
465         .code:n =
466         {
467           \cs_generate_from_arg_count:NNnn
468             \exp_not:N #3
469             \exp_not:c
470               { cs_ \str_if_eq:nnT {#1} { global } { g } set:Npn }

```

```

471         { \exp_not:V \l__template_keytype_arg_tl }
472         {##1}
473     }
474 }
475 \prop_put:NVn \l__template_vars_prop
476 \l__template_key_name_tl {#2#3}
477 }
478 { instance }
479 {
480     \__template_parse_vars_elt_key:nn {#1}
481     {
482         .code:n =
483         {
484             \exp_not:c
485             { cs_ \str_if_eq:nnT {#1} { global } { g } set:Npn }
486             \exp_not:N #3 { \UseInstance {##1} }
487         }
488     }
489     \prop_put:NVn \l__template_vars_prop
490     \l__template_key_name_tl {#2#3}
491 }
492 }
493 {
494     \tl_if_single:nTF {#3}
495     {
496         \cs_if_exist:NF #3
497         { \use:c { \__template_map_var_type: _new:N } #3 }
498         \__template_parse_vars_elt_key:nn {#1}
499         {
500             . \__template_map_var_type:
501             _ \str_if_eq:nnT {#1} { global } { g } set:N
502             = \exp_not:N #3
503         }
504         \prop_put:NVn \l__template_vars_prop
505         \l__template_key_name_tl {#2#3}
506     }
507     { \msg_error:nnn { template } { bad-variable } {#2#3} }
508 }
509 }
510 \cs_generate_variant:Nn \__template_parse_vars_elt_aux:nnn { nne }
511 \cs_new_protected:Npn \__template_parse_vars_elt_key:nn #1#2
512 {
513     \keys_define:ne { template / #1 }
514     { \l__template_key_name_tl #2 }
515 }

```

(End of definition for \\_\_template\_parse\_vars\_elt:nnn and others.)

\\_\_template\_map\_var\_type: Turn a “friendly” variable type into an expl3 one.

```

516 \cs_new:Npn \__template_map_var_type:
517 {
518     \str_case:Vn \l__template_keytype_tl
519     {
520         { boolean }    { bool }

```

```

521     { commalist } { clist }
522     { integer }   { int }
523     { length }    { dim }
524     { muskip }    { muskip }
525     { real }      { fp }
526     { skip }      { skip }
527     { tokenlist } { tl }
528   }
529 }

```

(End of definition for `\__template_map_var_type:`.)

`\__template_implement_choices:nn`  
`\__template_implement_choices_default:`

Implementing choices requires a second key–value loop. So after a little set-up, the standard parser is called.

```

530 \cs_new_protected:Npn \__template_implement_choices:nn #1#2
531 {
532   \clist_set:NV \l__template_tmp_clist \l__template_keytype_arg_tl
533   \prop_put:NVn \l__template_vars_prop \l__template_key_name_tl { }
534   \keys_define:ne { template / #1 } { \l__template_key_name_tl .choice: }
535   \keyval_parse:nnn
536     { \__template_implement_choice_elt:n }
537     { \__template_implement_choice_elt:nnn {#1} }
538     {#2}
539   \prop_get:NVNT \l__template_values_prop \l__template_key_name_tl
540     \l__template_tmp_tl
541     { \__template_implement_choices_default: }
542   \clist_if_empty:NF \l__template_tmp_clist
543     {
544       \clist_map_inline:Nn \l__template_tmp_clist
545         { \msg_error:nnn { template } { choice-not-implemented } {##1} }
546     }
547 }

```

A sanity check for the default value, so that an error is raised now and not when converting to assignments.

```

548 \cs_new_protected:Npn \__template_implement_choices_default:
549 {
550   \tl_set:Ne \l__template_tmp_tl
551     { \l__template_key_name_tl \c_space_tl \l__template_tmp_tl }
552   \prop_if_in:NVF \l__template_vars_prop \l__template_tmp_tl
553     {
554       \tl_set:Ne \l__template_tmp_tl
555         { \l__template_key_name_tl \c_space_tl \l__template_tmp_tl }
556       \prop_if_in:NVF \l__template_vars_prop \l__template_tmp_tl
557         {
558           \prop_get:NVN \l__template_keytypes_prop \l__template_key_name_tl
559             \l__template_tmp_tl
560           \__template_split_keytype_arg:V \l__template_tmp_tl
561           \prop_get:NVN \l__template_values_prop \l__template_key_name_tl
562             \l__template_tmp_tl
563           \msg_error:nnVV { template } { unknown-default-choice }
564             \l__template_key_name_tl
565             \l__template_key_name_tl
566         }
567     }

```

```
568 }
```

(End of definition for `\__template_implement_choices:nn` and  
`\__template_implement_choices_default:.`)

```
\__template_implement_choice_elt:nnn
\__template_implement_choice_elt_aux:nnn
\__template_implement_choice_elt_aux:n
\__template_implement_choice_elt:n
```

The actual storage of the implementation of a choice is mainly about error checking. The code here ensures that all choices have to have been declared, apart from the special **unknown** choice, which must come last. The code for each choice is stored along with the key name in the variables property list.

```
569 \cs_new_protected:Npn \__template_implement_choice_elt:nnn #1#2#3
570 {
571   \clist_if_empty:NTF \l__template_tmp_clist
572   {
573     \str_if_eq:nnTF {#2} { unknown }
574     { \__template_implement_choice_elt_aux:nnn {#1} {#2} {#3} }
575     { \__template_implement_choice_elt_aux:n {#2} }
576   }
577   {
578     \clist_if_in:NnTF \l__template_tmp_clist {#2}
579     {
580       \clist_remove_all:Nn \l__template_tmp_clist {#2}
581       \__template_implement_choice_elt_aux:nnn {#1} {#2} {#3}
582     }
583     { \__template_implement_choice_elt_aux:n {#2} }
584   }
585 }
586 \cs_new_protected:Npn \__template_implement_choice_elt_aux:n #1
587 {
588   \prop_get:NVN \l__template_keytypes_prop \l__template_key_name_tl
589   \l__template_tmp_tl
590   \__template_split_keytype_arg:V \l__template_tmp_tl
591   \msg_error:nnVn { template } { unknown-choice } \l__template_key_name_tl {#1}
592 }
593 \cs_new_protected:Npn \__template_implement_choice_elt_aux:nnn #1#2#3
594 {
595   \keys_define:ne { template / #1 }
596   { \l__template_key_name_tl / #2 .code:n = { \exp_not:n {#3} } }
597   \tl_set:Nc \l__template_tmp_tl
598   { \l__template_key_name_tl \c_space_tl #2 }
599   \prop_put:NVN \l__template_vars_prop \l__template_tmp_tl {#3}
600 }
601 \cs_new_protected:Npn \__template_implement_choice_elt:n #1
602 {
603   \msg_error:nnVn { template } { choice-requires-code }
604   \l__template_key_name_tl {#1}
605 }
```

(End of definition for `\__template_implement_choice_elt:nnn` and others.)

## 11.7 Editing template defaults

```
\__template_edit_defaults:nnn
```

Editing the template defaults means getting the values back out of the store, then parsing the list of new values before putting the updated list back into storage.

```
606 \cs_new_protected:Npn \__template_edit_defaults:nnn #1#2#3
```

```

607 {
608   \__template_if_keys_exist:nnT {#1} {#2}
609   {
610     \__template_recover_defaults:nn {#1} {#2}
611     \__template_parse_values:nnn {#1} {#2} {#3}
612     \__template_store_defaults:nn {#1} {#2}
613   }
614 }

```

(End of definition for \\_\_template\_edit\_defaults:nnn.)

\\_\_template\_parse\_values:nnn The routine to parse values is the same for both editing a template and setting up an instance. So the code here does only the minimum necessary for reading the values.

```

615 \cs_new_protected:Npn \__template_parse_values:nnn #1#2#3
616 {
617   \__template_recover_keytypes:nn {#1} {#2}
618   \keyval_parse:NNn
619   \__template_parse_values_elt:n \__template_parse_values_elt:nn {#3}
620 }

```

(End of definition for \\_\_template\_parse\_values:nnn.)

\\_\_template\_parse\_values\_elt:n Every key needs a value, so this is just an error routine.

```

621 \cs_new_protected:Npn \__template_parse_values_elt:n #1
622 {
623   \bool_set_true:N \l__template_error_bool
624   \msg_error:nnn { template } { key-no-value } {#1}
625 }

```

(End of definition for \\_\_template\_parse\_values\_elt:n.)

\\_\_template\_parse\_values\_elt:nn To store the value, find the keytype then call the saving function. These need the current key name, stored in \l\_\_template\_key\_name\_tl.

```

\__template_parse_values_elt_aux:w
\__template_parse_values_elt_aux:n
\__template_parse_values_exp:n
\__template_parse_values_exp:o
\__template_parse_values_exp:V
\__template_parse_values_exp:v
\__template_parse_values_exp:e
\__template_parse_values_exp:N
\__template_parse_values_exp:c
626 \cs_new_protected:Npn \__template_parse_values_elt:nn #1#2
627 {
628   \use:e
629   {
630     \__template_parse_values_elt_aux:w
631     \tl_trim_spaces:e { \tl_to_str:n { #1 : n : } }
632     \exp_not:N \q_stop
633   }
634   \prop_get:NVNTF \l__template_keytypes_prop \l__template_key_name_tl
635   \l__template_tmp_tl
636   { \__template_parse_values_elt_aux:n {#2} }
637   { \msg_error:nnV { template } { unknown-key } \l__template_key_name_tl }
638 }
639 \use:e
640 {
641   \cs_new_protected:Npn \exp_not:N \__template_parse_values_elt_aux:w
642   #1 \token_to_str:N : #2 \token_to_str:N : #3 \exp_not:N \q_stop
643 }
644 {
645   \tl_set:Nn \l__template_key_name_tl {#1}
646   \str_set:Nn \l__template_value_exp_str {#2}
647 }

```

```

648 \cs_new_protected:Npn \__template_parse_values_elt_aux:n #1
649 {
650   \__template_split_keytype_arg:V \l__template_tmp_tl
651   \cs_if_exist_use:cF { __template_parse_values_exp: \l__template_value_exp_str }
652   {
653     \msg_error:nnV { template } { unknown-expansion } \l__template_value_exp_str
654     \use_none:n
655   }
656   {#1}
657 }
658 \cs_new_protected:Npn \__template_parse_values_exp:n #1
659 { \use:c { __template_store_value_ \l__template_keytype_tl :n } {#1} }
660 \cs_generate_variant:Nn \__template_parse_values_exp:n { o , V , v , e }
661 \cs_new_eq:NN \__template_parse_values_exp:N \__template_parse_values_exp:n
662 \cs_generate_variant:Nn \__template_parse_values_exp:N { c }

```

(End of definition for \\_\_template\_parse\_values\_elt:nn and others.)

\\_\_template\_template\_set\_eq:nnn

To copy a template, each of the lists plus the code has to be copied across. To keep this independent of the list storage system, it is all done with two-part shuffles.

```

663 \cs_new_protected:Npn \__template_template_set_eq:nnn #1#2#3
664 {
665   \__template_recover_defaults:nn {#1} {#3}
666   \__template_store_defaults:nn {#1} {#2}
667   \__template_recover_keytypes:nn {#1} {#3}
668   \__template_store_keytypes:nn {#1} {#2}
669   \__template_recover_vars:nn {#1} {#3}
670   \__template_store_vars:nn {#1} {#2}
671   \cs_if_exist:cT { \c__template_code_root_tl #1 / #2 }
672   { \msg_info:nnnn { template } { declare-template-code } {#1} {#2} }
673   \cs_gset_eq:cc { \c__template_code_root_tl #1 / #2 }
674   { \c__template_code_root_tl #1 / #3 }
675 }

```

(End of definition for \\_\_template\_template\_set\_eq:nnn.)

## 11.8 Creating instances of templates

\\_\_template\_declare\_instance:nnnn  
\\_\_template\_declare\_instance\_aux:nnnn

Making an instance has two distinct parts. First, the keys given are parsed to transfer the values into the structured data format used internally. This allows the default and given values to be combined with no repetition. In the second step, the structured data is converted to pre-defined variable assignments, and these are stored in the function for the instance.

```

676 \cs_new_protected:Npn \__template_declare_instance:nnnn #1#2#3#4
677 {
678   \__template_execute_if_code_exist:nnT {#1} {#2}
679   {
680     \__template_recover_defaults:nn {#1} {#2}
681     \__template_recover_vars:nn {#1} {#2}
682     \__template_declare_instance_aux:nnnn {#1} {#2} {#3} {#4}
683   }
684 }
685 \cs_new_protected:Npn \__template_declare_instance_aux:nnnn #1#2#3#4
686 {

```

```

687 \bool_set_false:N \l__template_error_bool
688 \__template_parse_values:nnn {#1} {#2} {#4}
689 \bool_if:NF \l__template_error_bool
690 {
691   \prop_put:Nnn \l__template_values_prop { from-template } {#2}
692   \__template_store_values:nn {#1} {#3}
693   \__template_convert_to_assignments:
694   \cs_if_exist:cT { \c__template_instances_root_tl #1 / #3 }
695     { \msg_info:nnnn { template } { declare-instance } {#3} {#1} }
696   \cs_set_protected:cpe { \c__template_instances_root_tl #1 / #3 }
697     {
698       \exp_not:N \__template_assignments_push:n
699       { \exp_not:V \l__template_assignments_tl }
700       \exp_not:c { \c__template_code_root_tl #1 / #2 }
701     }
702 }
703 }

```

(End of definition for \\_\_template\_declare\_instance:nnnn and  
\\_\_template\_declare\_instance\_aux:nnnn.)

\\_\_template\_instance\_set\_eq:nnn Copy-paste an instance.

```

704 \cs_new_protected:Npn \__template_instance_set_eq:nnn #1#2#3
705 {
706   \__template_if_instance_exist:nnTF {#1} {#3}
707   {
708     \__template_recover_values:nn {#1} {#3}
709     \__template_store_values:nn {#1} {#2}
710     \cs_if_exist:cT { \c__template_instances_root_tl #1 / #2 }
711       { \msg_info:nnnn { template } { declare-instance } {#2} {#1} }
712     \cs_set_eq:cc { \c__template_instances_root_tl #1 / #2 }
713       { \c__template_instances_root_tl #1 / #3 }
714   }
715   { \msg_error:nnnn { template } { unknown-instance } {#1} {#3} }
716 }

```

(End of definition for \\_\_template\_instance\_set\_eq:nnn.)

\\_\_template\_edit\_instance:nnn  
\\_\_template\_edit\_instance\_aux:nnnn  
\\_\_template\_edit\_instance\_aux:nVnnn

Editing an instance is almost identical to declaring one. The only variation is the source of the values to use. When editing, they are recovered from the previous instance run.

```

717 \cs_new_protected:Npn \__template_edit_instance:nnn #1#2#3
718 {
719   \__template_if_instance_exist:nnTF {#1} {#2}
720   {
721     \__template_recover_values:nn {#1} {#2}
722     \prop_get:NnN \l__template_values_prop { from-template }
723     \l__template_tmp_tl
724     \__template_edit_instance_aux:nVnn
725     {#1} \l__template_tmp_tl {#2} {#3}
726   }
727   { \msg_error:nnnn { template } { unknown-instance } {#1} {#2} }
728 }
729 \cs_new_protected:Npn \__template_edit_instance_aux:nnnn #1#2#3#4
730 {
731   \__template_recover_vars:nn {#1} {#2}

```

```

732   \__template_declare_instance_aux:nnnn {#1} {#2} {#3} {#4}
733   }
734   \cs_generate_variant:Nn \__template_edit_instance_aux:nnnn { nV }

(End of definition for \__template_edit_instance:nnn and \__template_edit_instance_aux:nnnn.)

```

```

\__template_convert_to_assignments:
\__template_convert_to_assignments_aux:n
\__template_convert_to_assignments_aux:nn
\__template_convert_to_assignments_aux:nV

```

The idea on converting to a set of assignments is to loop over each key, so that the loop order follows the declaration order of the keys. This is done using a sequence as property lists are not “ordered”.

```

735   \cs_new_protected:Npn \__template_convert_to_assignments:
736   {
737     \tl_clear:N \l__template_assignments_tl
738     \seq_map_function:NN \l__template_key_order_seq
739     \__template_convert_to_assignments_aux:n
740   }
741   \cs_new_protected:Npn \__template_convert_to_assignments_aux:n #1
742   {
743     \prop_get:NnN \l__template_keytypes_prop {#1} \l__template_tmp_tl
744     \__template_convert_to_assignments_aux:nV {#1} \l__template_tmp_tl
745   }

```

The second auxiliary function actually does the work. The arguments here are the key name (#1) and the keytype (#2). From those, the value to assign and the name of the appropriate variable are recovered. A bit of work is then needed to sort out keytypes with arguments (for example instances), and to look for global assignments. Once that is done, a hand-off can be made to the handler for the relevant keytype.

```

746   \cs_new_protected:Npn \__template_convert_to_assignments_aux:nn #1#2
747   {
748     \prop_get:NnNT \l__template_values_prop {#1} \l__template_value_tl
749     {
750       \prop_get:NnNTF \l__template_vars_prop {#1} \l__template_var_tl
751       {
752         \__template_split_keytype_arg:n {#2}
753         \str_if_eq:VnF \l__template_keytype_tl { choice }
754         {
755           \str_if_eq:VnF \l__template_keytype_tl { code }
756           { \__template_find_global: }
757         }
758         \tl_set:Nn \l__template_key_name_tl {#1}
759         \cs_if_exist_use:cF { __template_assign_ \l__template_keytype_tl : }
760         { \__template_assign_variable: }
761       }
762       { \msg_error:nnn { template } { unknown-attribute } {#1} }
763     }
764   }
765   \cs_generate_variant:Nn \__template_convert_to_assignments_aux:nn { nV }

```

(End of definition for \\_\_template\_convert\_to\_assignments:,  
\\_\_template\_convert\_to\_assignments\_aux:n, and \\_\_template\_convert\_to\_assignments\_aux:nn.)

```

\__template_find_global:
\__template_find_global_aux:w

```

Global assignments should have the phrase global at the front. This is pretty easy to find: no other error checking, though.

```

766   \cs_new_protected:Npn \__template_find_global:
767   {

```

```

768 \bool_set_false:N \l__template_global_bool
769 \tl_if_in:onT \l__template_var_tl { global }
770 {
771   \exp_after:wN \__template_find_global_aux:w \l__template_var_tl \s__template_stop
772 }
773 }
774 \cs_new_protected:Npn \__template_find_global_aux:w #1 global #2 \s__template_stop
775 {
776   \tl_set:Nn \l__template_var_tl {#2}
777   \bool_set_true:N \l__template_global_bool
778 }

```

(End of definition for \\_\_template\_find\_global: and \\_\_template\_find\_global\_aux:w.)

## 11.9 Using templates directly

\\_\_template\_use\_template:nnn Directly use a template with a particular parameter setting. This is also picked up if used in a nested fashion inside a parameter list. The idea is essentially the same as creating an instance, just with no saving of the result.

```

779 \cs_new_protected:Npn \__template_use_template:nnn #1#2#3
780 {
781   \__template_execute_if_code_exist:nnT {#1} {#2}
782   {
783     \__template_recover_defaults:nn {#1} {#2}
784     \__template_recover_vars:nn {#1} {#2}
785     \__template_parse_values:nnn {#1} {#2} {#3}
786     \__template_convert_to_assignments:
787     \use:c { \c__template_code_root_tl #1 / #2 }
788   }
789 }

```

(End of definition for \\_\_template\_use\_template:nnn.)

## 11.10 Assigning values to variables

\\_\_template\_assign\_boolean: Setting a Boolean value is slightly different to everything else as the value can be used to work out which set function to call. As long as there is no need to recover things from another variable, everything is pretty easy. If there is, then we need to allow for the fact that the recovered value here will *not* be expandable, so needs to be converted to something that is.

```

790 \cs_new_protected:Npn \__template_assign_boolean:
791 {
792   \bool_if:NTF \l__template_global_bool
793   { \__template_assign_boolean_aux:n { bool_gset } }
794   { \__template_assign_boolean_aux:n { bool_set } }
795 }
796 \cs_new_protected:Npn \__template_assign_boolean_aux:n #1
797 {
798   \__template_if_key_value:VTF \l__template_value_tl
799   {
800     \__template_key_to_value:
801     \tl_put_right:Ne \l__template_assignments_tl
802     {

```

```

803         \exp_not:c { #1 _eq:NN }
804         \exp_not:V \l__template_var_tl
805         \exp_not:V \l__template_value_tl
806     }
807 }
808 {
809     \tl_put_right:Ne \l__template_assignments_tl
810     {
811         \exp_not:c { #1 _ \l__template_value_tl :N }
812         \exp_not:V \l__template_var_tl
813     }
814 }
815 }

```

(End of definition for \\_\_template\_assign\_boolean: and \\_\_template\_assign\_boolean\_aux:n.)

\\_\_template\_assign\_choice: The idea here is to find either the choice as-given or else the special `unknown` choice, and to copy the appropriate code across.

```

\__template_assign_choice_aux:nF
\__template_assign_choice_aux:eF
816 \cs_new_protected:Npn \__template_assign_choice:
817 {
818     \__template_assign_choice_aux:eF
819     { \l__template_key_name_tl \c_space_tl \l__template_value_tl }
820     {
821         \__template_assign_choice_aux:eF
822         { \l__template_key_name_tl \c_space_tl unknown }
823         {
824             \prop_get:NVN \l__template_keytypes_prop \l__template_key_name_tl
825             \l__template_tmp_tl
826             \__template_split_keytype_arg:V \l__template_tmp_tl
827             \msg_error:nnVV { template } { unknown-choice }
828             \l__template_key_name_tl
829             \l__template_value_tl
830         }
831     }
832 }
833 \cs_new_protected:Npn \__template_assign_choice_aux:nF #1
834 {
835     \prop_get:NnNTF \l__template_vars_prop {#1} \l__template_tmp_tl
836     { \tl_put_right:NV \l__template_assignments_tl \l__template_tmp_tl }
837 }
838 \cs_generate_variant:Nn \__template_assign_choice_aux:nF { e }

```

(End of definition for \\_\_template\_assign\_choice: and \\_\_template\_assign\_choice\_aux:nF.)

\\_\_template\_assign\_function: This looks a bit messy but is only actually one function.

```

\__template_assign_function_aux:N
839 \cs_new_protected:Npn \__template_assign_function:
840 {
841     \bool_if:NTF \l__template_global_bool
842     { \__template_assign_function_aux:N \cs_gset:Npn }
843     { \__template_assign_function_aux:N \cs_set:Npn }
844 }
845 \cs_new_protected:Npn \__template_assign_function_aux:N #1
846 {
847     \tl_put_right:Ne \l__template_assignments_tl

```

```

848     {
849         \cs_generate_from_arg_count:NNnn
850         \exp_not:V \l__template_var_tl
851         \exp_not:N #1
852         { \exp_not:V \l__template_keytype_arg_tl }
853         { \exp_not:V \l__template_value_tl }
854     }
855 }

```

(End of definition for `\__template_assign_function:` and `\__template_assign_function_aux:N`.)

`\__template_assign_instance:` Using an instance means adding the appropriate function creation to the tl. No checks are made at this stage, so if the instance is not valid then errors will arise later.

```

856 \cs_new_protected:Npn \__template_assign_instance:
857 {
858     \bool_if:NTF \l__template_global_bool
859     { \__template_assign_instance_aux:N \cs_gset_protected:Npn }
860     { \__template_assign_instance_aux:N \cs_set_protected:Npn }
861 }
862 \cs_new_protected:Npn \__template_assign_instance_aux:N #1
863 {
864     \tl_put_right:Ne \l__template_assignments_tl
865     {
866         \exp_not:N #1 \exp_not:V \l__template_var_tl
867         {
868             \__template_use_instance:nn
869             { \exp_not:V \l__template_keytype_arg_tl }
870             { \exp_not:V \l__template_value_tl }
871         }
872     }
873 }

```

(End of definition for `\__template_assign_instance:` and `\__template_assign_instance_aux:N`.)

`\__template_assign_variable:` A general-purpose function for all of the other assignments. As long as the value is not coming from another variable, the stored value is simply transferred for output. We use V-type expansion for the `\KeyValue` case: for token lists this is essential, whilst for register-based variables, it does no harm and avoids needing a low-level test.

```

874 \cs_new_protected:Npn \__template_assign_variable:
875 {
876     \exp_args:Ne \__template_assign_variable:n
877     {
878         \__template_map_var_type:
879         -
880         \bool_if:NT \l__template_global_bool { g }
881         set:N
882     }
883 }

```

Notice we need a V-type variant for each (g)set operation here: these need to be provided by `expl3`.

```

884 \cs_new_protected:Npn \__template_assign_variable:n #1
885 {
886     \__template_if_key_value:VTF \l__template_value_tl

```

```

887 {
888   \__template_key_to_value:
889   \tl_put_right:Ne \l__template_assignments_tl
890   {
891     \exp_not:c { #1 V } \exp_not:V \l__template_var_tl
892     \exp_not:V \l__template_value_tl
893   }
894 }
895 {
896   \tl_put_right:Ne \l__template_assignments_tl
897   {
898     \exp_not:c { #1 n } \exp_not:V \l__template_var_tl
899     { \exp_not:V \l__template_value_tl }
900   }
901 }
902 }

```

(End of definition for \\_\_template\_assign\_variable: and \\_\_template\_assign\_variable:n.)

```

\__template_key_to_value:
  \__template_key_to_value_auxi:w
  \__template_key_to_value_auxii:w

```

The idea here is to recover the attribute value of another key. To do that, the marker is removed and a look up takes place. If this is successful, then the name of the variable of the attribute is returned. This assumes that the value will be used in context where it will be converted to a value, for example when setting a number. There is also a need to check in case the copied value happens to be global.

```

903 \cs_new_protected:Npn \__template_key_to_value:
904 { \exp_after:wN \__template_key_to_value_auxi:w \l__template_value_tl }
905 \cs_new_protected:Npn \__template_key_to_value_auxi:w \KeyValue #1
906 {
907   \tl_set:Ne \l__template_tmp_tl { \tl_trim_spaces:e { \tl_to_str:n {#1} } }
908   \prop_get:NVNTF \l__template_vars_prop \l__template_tmp_tl
909   \l__template_value_tl
910   {
911     \exp_after:wN \__template_key_to_value_auxii:w \l__template_value_tl
912     \s__template_mark global \q__template_nil \s__template_stop
913   }
914   { \msg_error:nnV { template } { unknown-attribute } \l__template_tmp_tl }
915 }
916 \cs_new_protected:Npn \__template_key_to_value_auxii:w #1 global #2#3 \s__template_stop
917 {
918   \__template_quark_if_nil:NF #2
919   { \tl_set:Nn \l__template_value_tl {#2} }
920 }

```

(End of definition for \\_\_template\_key\_to\_value:, \\_\_template\_key\_to\_value\_auxi:w, and \\_\_template\_key\_to\_value\_auxii:w.)

## 11.11 Using instances

```

\__template_use_instance:nn
  \__template_use_instance_aux:nNnnn
  \__template_use_instance_aux:nn

```

Using an instance is just a question of finding the appropriate function. If nothing is found, an error is raised. One complication is that if the first token of argument #2 is \UseTemplate then that is also valid. There is an error-test to make sure that the types agree, and if so the template is used directly.

```

921 \cs_new_protected:Npn \__template_use_instance:nn #1#2
922 {

```

```

923 \__template_if_use_template:nTF {#2}
924 { \__template_use_instance_aux:nNnnn {#1} #2 }
925 { \__template_use_instance_aux:nn {#1} {#2} }
926 }
927 \cs_new_protected:Npn \__template_use_instance_aux:nNnnn #1#2#3#4#5
928 {
929 \str_if_eq:nnTF {#1} {#3}
930 { \__template_use_template:nnn {#3} {#4} {#5} }
931 { \msg_error:nnnn { template } { type-mismatch } {#1} {#3} }
932 }
933 \cs_new_protected:Npn \__template_use_instance_aux:nn #1#2
934 {
935 \__template_if_instance_exist:nnTF {#1} {#2}
936 { \use:c { \c__template_instances_root_tl #1 / #2 } }
937 { \msg_error:nnnn { template } { unknown-instance } {#1} {#2} }
938 }

(End of definition for \__template_use_instance:nn, \__template_use_instance_aux:nNnnn, and
 \__template_use_instance_aux:nn.)

```

## 11.12 Assignment manipulation

A few functions to transfer assignments about, as this is needed by `\AssignTemplateKeys`.

`\__template_assignments_pop:` To actually use the assignments.

```

939 \cs_new:Npn \__template_assignments_pop: { \l__template_assignments_tl }

(End of definition for \__template_assignments_pop:.)

```

`\__template_assignments_push:n` Here, the assignments are stored for later use.

```

940 \cs_new_protected:Npn \__template_assignments_push:n #1
941 { \tl_set:Nn \l__template_assignments_tl {#1} }

(End of definition for \__template_assignments_push:n.)

```

## 11.13 Showing templates and instances

`\__template_show_code:nn` Showing the code for a template is just a translation of `\cs_show:c`.

```

942 \cs_new_protected:Npn \__template_show_code:nn #1#2
943 { \cs_show:c { \c__template_code_root_tl #1 / #2 } }

(End of definition for \__template_show_code:nn.)

```

`\__template_show_defaults:nn` A modified version of the property-list printing code, such that the output refers to templates and instances rather than to the underlying structures.

`\__template_show_keytypes:nn`

`\__template_show_vars:nn`

`\__template_show:Nnnn`

```

944 \cs_new_protected:Npn \__template_show_defaults:nn #1#2
945 {
946 \__template_if_keys_exist:nnT {#1} {#2}
947 {
948 \__template_recover_defaults:nn {#1} {#2}
949 \__template_show:Nnnn \l__template_values_prop
950 {#1} {#2} { default~values }
951 }
952 }

```

```

953 \cs_new_protected:Npn \__template_show_keytypes:nn #1#2
954 {
955   \__template_if_keys_exist:nnT {#1} {#2}
956   {
957     \__template_recover_keytypes:nn {#1} {#2}
958     \__template_show:Nnnn \l__template_keytypes_prop
959     {#1} {#2} { interface }
960   }
961 }
962 \cs_new_protected:Npn \__template_show_vars:nn #1#2
963 {
964   \__template_execute_if_code_exist:nnT {#1} {#2}
965   {
966     \__template_recover_vars:nn {#1} {#2}
967     \__template_show:Nnnn \l__template_vars_prop
968     {#1} {#2} { variable~mapping }
969   }
970 }
971 \cs_new_protected:Npn \__template_show:Nnnn #1#2#3#4
972 {
973   \msg_show:nneeee { template } { show-attribute }
974   { \tl_to_str:n {#2} }
975   { \tl_to_str:n {#3} }
976   { \tl_to_str:n {#4} }
977   { \prop_map_function:NN #1 \msg_show_item_unbraced:nn }
978 }

```

*(End of definition for \\_\_template\_show\_defaults:nn and others.)*

\\_\_template\_show\_values:nn Instance values are a little more complex, as is the template to consider.

```

979 \cs_new_protected:Npn \__template_show_values:nn #1#2
980 {
981   \__template_if_instance_exist:nnT {#1} {#2}
982   {
983     \__template_recover_values:nn {#1} {#2}
984     \msg_show:nneee { template } { show-values }
985     { \tl_to_str:n {#1} }
986     { \tl_to_str:n {#2} }
987     {
988       \prop_map_function:NN \l__template_values_prop
989       \msg_show_item_unbraced:nn
990     }
991   }
992 }

```

*(End of definition for \\_\_template\_show\_values:nn.)*

## 11.14 Messages

The text for error messages: short and long text for all of them.

```

993 \msg_new:nnnn { template } { argument-number-mismatch }
994 { Template~type~'#1'~takes~#2~argument(s). }
995 {
996   Templates~of~type~'#1'~require~#2~argument(s).\

```

```

997     You-have-~tried-to-make-a-template-for~'#1'~
998     with~#3~argument(s),~which-is-not-possible:~
999     the-number-of-arguments~must-agree.
1000 }
1001 \msg_new:nnnn { template } { bad-number-of-arguments }
1002 { Bad-number-of-arguments-for-template-type~'#1'. }
1003 {
1004     A-template-may-accept-between-0-and-9-arguments.\\
1005     You-asked-to-use-#2-arguments:~this-is-not-supported.
1006 }
1007 \msg_new:nnnn { template } { bad-variable }
1008 { Incorrect-variable-description~'#1'. }
1009 {
1010     The-argument~'#1'~is-not-of-the-form \\
1011     ~'<variable>'\\
1012     ~or~\\
1013     ~'global-<variable>'\\.\\
1014     It-must-be-given-in-one-of-these-formats-to-be-used-in-a-template.
1015 }
1016 \msg_new:nnnn { template } { choice-not-implemented }
1017 { The-choice~'#1'~has-no-implementation. }
1018 {
1019     Each-choice-listed-in-the-interface-for-a-template-must~
1020     have-an-implementation.
1021 }
1022 \msg_new:nnnn { template } { choice-no-code }
1023 { The-choice~'#1'~requires-implementation-details. }
1024 {
1025     When-creating-template-code-using~\DeclareTemplateCode,~
1026     each-choice-name-must-have-an-associated-implementation.\\
1027     This-should-be-given-after-a~'= '~sign:~LaTeX-did-not-find-one.
1028 }
1029 \msg_new:nnnn { template } { choice-requires-code }
1030 { The-choice~'#2'~for-key~'#1'~requires-an-implementation. }
1031 {
1032     You-should-have-put:\\
1033     \ \ #1::~choice-{\#2 = <code> ~} \\
1034     but~LaTeX-did-not-find-any~<code>.
1035 }
1036 \msg_new:nnnn { template } { duplicate-key-interface }
1037 { Key~'#1'~appears-twice-in-interface-definition~\msg_line_context:. }
1038 {
1039     Each-key-can-only-have-one-interface-declared-in-a-template.\\
1040     LaTeX-found-two-interfaces-for~'#1'.
1041 }
1042 \msg_new:nnnn { template } { keytype-requires-argument }
1043 { The-key-type~'#1'~requires-an-argument~\msg_line_context:. }
1044 {
1045     You-should-have-put:\\
1046     \ \ <key-name>::~#1~{~<argument>~} \\
1047     but~LaTeX-did-not-find-an~<argument>.
1048 }
1049 \msg_new:nnnn { template } { invalid-keytype }
1050 { The-key~'#1'~is-missing-a-key-type~\msg_line_context:. }

```

```

1051 {
1052   Each~key~in~a~template~requires~a~key~type,~given~in~the~form:\\
1053   \ \ <key>::~~<key~type>\\
1054   LaTeX~could~not~find~a~<key~type>~in~your~input.
1055 }
1056 \msg_new:nnnn { template } { key-no-value }
1057 { The~key~'#1'~has~no~value~\msg_line_context:. }
1058 {
1059   When~creating~an~instance~of~a~template~
1060   every~key~listed~must~include~a~value:\\
1061   \ \ <key>::~~<value>
1062 }
1063 \msg_new:nnnn { template } { key-no-variable }
1064 { The~key~'#1'~requires~implementation~details~\msg_line_context:. }
1065 {
1066   When~creating~template~code~using~\DeclareTemplateCode,~
1067   each~key~name~must~have~an~associated~implementation.\\
1068   This~should~be~given~after~a~'= '~sign:~LaTeX~did~not~find~one.
1069 }
1070 \msg_new:nnnn { template } { key-not-implemented }
1071 { Key~'#1'~has~no~implementation~\msg_line_context:. }
1072 {
1073   The~definition~of~key~implementations~for~template~'#2'~
1074   of~template~type~'#3'~does~not~include~any~details~for~key~'#1'.\\
1075   The~key~was~declared~in~the~interface~definition,~
1076   and~so~an~implementation~is~required.
1077 }
1078 \msg_new:nnnn { template } { missing-keytype }
1079 { The~key~'#1'~is~missing~a~key~type~\msg_line_context:. }
1080 {
1081   Key~interface~definitions~should~be~of~the~form\\
1082   \ \ #1::~~<key~type>\\
1083   but~LaTeX~could~not~find~a~<key~type>.
1084 }
1085 \msg_new:nnnn { template } { no-template-code }
1086 {
1087   The~template~'#2'~of~type~'#1'~is~unknown~
1088   or~has~no~implementation.
1089 }
1090 {
1091   There~is~no~code~available~for~the~template~name~given.\\
1092   This~should~be~given~using~\DeclareTemplateCode.
1093 }
1094 \msg_new:nnnn { template } { type-already-defined }
1095 { Template~type~'#1'~already~defined. }
1096 {
1097   You~have~used~\NewTemplateType~
1098   with~a~template~type~that~has~already~been~defined.
1099 }
1100 \msg_new:nnnn { template } { type-mismatch }
1101 { Template~types~'#1'~and~'#2'~do~not~agree. }
1102 {
1103   You~are~trying~to~use~a~template~directly~with~\UseInstance
1104   (or~a~similar~function),~but~the~template~types~do~not~match.

```

```

1105 }
1106 \msg_new:nnnn { template } { unknown-attribute }
1107 { The~template~attribute~'#1'~is~unknown. }
1108 {
1109   There~is~a~definition~in~the~current~template~reading\\
1110   \ \ \token_to_str:N \KeyValue {~#1~} \ \
1111   but~there~is~no~key~called~'#1'.
1112 }
1113 \msg_new:nnnn { template } { unknown-choice }
1114 { The~choice~'#2'~was~not~declared~for~key~'#1'. }
1115 {
1116   The~key~'#1'~takes~a~fixed~list~of~choices~
1117   and~this~list~does~not~include~'#2'.
1118 }
1119 \msg_new:nnnn { template } { unknown-default-choice }
1120 { The~default~choice~'#2'~was~not~declared~for~key~'#1'. }
1121 {
1122   The~key~'#1'~takes~a~fixed~list~of~choices~
1123   and~this~list~does~not~include~'#2'.
1124 }
1125 \msg_new:nnnn { template } { unknown-expansion }
1126 { The~expansion~type~'#1'~is~unknown. }
1127 {
1128   Key~values~can~only~be~expanded~using~one~of~the~pre-defined~methods:~
1129   n,~o,~V,~v,~e,~N~or~c.
1130 }
1131 \msg_new:nnnn { template } { unknown-instance }
1132 { The~instance~'#2'~of~type~'#1'~is~unknown. }
1133 {
1134   You~have~asked~to~use~an~instance~'#2',~
1135   but~this~has~not~been~created.
1136 }
1137 \msg_new:nnnn { template } { unknown-key }
1138 { Unknown~template~key~'#1'. }
1139 {
1140   The~key~'#1'~was~not~declared~in~the~interface~
1141   for~the~current~template.
1142 }
1143 \msg_new:nnnn { template } { unknown-keytype }
1144 { The~key~type~'#1'~is~unknown. }
1145 {
1146   Valid~key~types~are:\\
1147   --boolean;\\
1148   --choice;\\
1149   --commalist;\\
1150   --function;\\
1151   --instance;\\
1152   --integer;\\
1153   --length;\\
1154   --muskip;\\
1155   --real;\\
1156   --skip;\\
1157   --tokenlist.
1158 }

```

```

1159 \msg_new:nnnn { template } { unknown-type }
1160 { The~template~type~'#1'~is~unknown. }
1161 {
1162   A~template~type~needs~to~be~defined~with~\NewTemplateType
1163   prior~to~using~it.
1164 }
1165 \msg_new:nnnn { template } { unknown-template }
1166 { The~template~'#2'~of~type~'#1'~is~unknown. }
1167 {
1168   No~interface~has~been~declared~for~a~template~
1169   '#2'~of~template~type~'#1'.
1170 }

```

Information messages only have text: more text should not be needed.

```

1171 \msg_new:nnn { template } { declare-instance }
1172 { Declaring~instance~'#1'~of~type~'#2'~\msg_line_context:. }
1173 \msg_new:nnn { template } { declare-template-code }
1174 { Declaring~code~for~template~'#2'~of~template~type~'#1'~\msg_line_context:. }
1175 \msg_new:nnn { template } { declare-template-interface }
1176 {
1177   Declaring~interface~for~template~'#2'~of~template~type~'#1'~
1178   \msg_line_context:.
1179 }
1180 \msg_new:nnn { template } { declare-type }
1181 { Declaring~template~type~'#1'~taking~#2~argument(s)~\msg_line_context:. }
1182 \msg_new:nnn { template } { show-attribute }
1183 {
1184   The~template~'#2'~of~type~'#1'~has~
1185   \tl_if_empty:nTF {#4} { no~#3. } { #3 : #4 }
1186 }
1187 \msg_new:nnn { template } { show-values }
1188 {
1189   The~instance~'#2'~of~type~'#1'~has~
1190   \tl_if_empty:nTF {#3} { no~values. } { values: #3 }
1191 }

```

Also add template to the LaTeX messages.

```

1192 \prop_gput:Nnn \g_msg_module_type_prop { template } { LaTeX }

```

## 11.15 User functions

All simple translations.

```

\NewTemplateType \DeclareTemplateInterface \DeclareTemplateCode \DeclareTemplateCopy \EditTemplateDefaults \UseTemplate \DeclareInstance \DeclareInstanceCopy \EditInstance \UseInstance
1193 \cs_new_protected:Npn \NewTemplateType #1#2
1194 { \__template_define_type:nn {#1} {#2} }
1195 \cs_new_protected:Npn \DeclareTemplateInterface #1#2#3#4
1196 { \__template_declare_template_keys:nnnn {#1} {#2} {#3} {#4} }
1197 \cs_new_protected:Npn \DeclareTemplateCode #1#2#3#4#5
1198 { \__template_declare_template_code:nnnnn {#1} {#2} {#3} {#4} {#5} }
1199 \cs_new_protected:Npn \DeclareTemplateCopy #1#2#3
1200 { \__template_template_set_eq:nnn {#1} {#2} {#3} }
1201 \cs_new_protected:Npn \EditTemplateDefaults #1#2#3
1202 { \__template_edit_defaults:nnn {#1} {#2} {#3} }
1203 \cs_new_protected:Npn \UseTemplate #1#2#3
1204 { \__template_use_template:nnn {#1} {#2} {#3} }

```

```

1205 \cs_new_protected:Npn \DeclareInstance #1#2#3#4
1206   { \__template_declare_instance:nnnn {#1} {#3} {#2} {#4} }
1207 \cs_new_protected:Npn \DeclareInstanceCopy #1#2#3
1208   { \__template_instance_set_eq:nnn {#1} {#2} {#3} }
1209 \cs_new_protected:Npn \EditInstance #1#2#3
1210   { \__template_edit_instance:nnn {#1} {#2} {#3} }
1211 \cs_new_protected:Npn \UseInstance #1#2
1212   { \__template_use_instance:nn {#1} {#2} }

```

(End of definition for `\NewTemplateType` and others. These functions are documented on page 353.)

```

\ShowTemplateCode The show functions are again just translation.
\ShowTemplateDefaults 1213 \cs_new_protected:Npn \ShowTemplateCode #1#2
\ShowTemplateInterface 1214   { \__template_show_code:nn {#1} {#2} }
\ShowTemplateVariables 1215 \cs_new_protected:Npn \ShowTemplateDefaults #1#2
\ShowInstanceValues 1216   { \__template_show_defaults:nn {#1} {#2} }
1217 \cs_new_protected:Npn \ShowTemplateInterface #1#2
1218   { \__template_show_keytypes:nn {#1} {#2} }
1219 \cs_new_protected:Npn \ShowTemplateVariables #1#2
1220   { \__template_show_vars:nn {#1} {#2} }
1221 \cs_new_protected:Npn \ShowInstanceValues #1#2
1222   { \__template_show_values:nn {#1} {#2} }

```

(End of definition for `\ShowTemplateCode` and others. These functions are documented on page 361.)

```

\IfInstanceExistsT More direct translation.
\IfInstanceExistsF 1223 \cs_new:Npn \IfInstanceExistsTF #1#2
\IfInstanceExistsTF 1224   { \__template_if_instance_exist:nnTF {#1} {#2} }
1225 \cs_new:Npn \IfInstanceExistsT #1#2
1226   { \__template_if_instance_exist:nnT {#1} {#2} }
1227 \cs_new:Npn \IfInstanceExistsF #1#2
1228   { \__template_if_instance_exist:nnF {#1} {#2} }

```

(End of definition for `\IfInstanceExistsT`, `\IfInstanceExistsF`, and `\IfInstanceExistsTF`. These functions are documented on page 359.)

**\KeyValue** Simply dump the argument when executed: this should not happen.

```

1229 \cs_new_protected:Npn \KeyValue #1 {#1}

```

(End of definition for `\KeyValue`. This function is documented on page 355.)

**\AssignTemplateKeys** A short call to use a token register by proxy.

```

1230 \cs_new_protected:Npn \AssignTemplateKeys { \__template_assignments_pop: }

```

(End of definition for `\AssignTemplateKeys`. This function is documented on page 355.)

**\SetKnownTemplateKeys** A friendly wrapper, with some speed up for the common case of the third argument being empty.  
**\SetTemplateKeys**

```

1231 \cs_new_protected:Npn \SetKnownTemplateKeys #1#2#3
1232   {
1233     \tl_if_empty:oTF {#3}
1234     {
1235       \tl_set_eq:NN \UnusedTemplateKeys \c_empty_tl
1236     }
1237   }

```

```

1238     \keys_set_known:noN { template / #1 / #2 } {#3} \UnusedTemplateKeys
1239   }
1240 }
1241 \cs_new_protected:Npn \SetTemplateKeys #1#2#3
1242 {
1243   \tl_if_empty:oF {#3}
1244   {
1245     \keys_set:no { template / #1 / #2 } {#3}
1246   }
1247 }
1248 \tl_new:N \UnusedTemplateKeys

(End of definition for \SetKnownTemplateKeys and \SetTemplateKeys. These functions are
documented on page 356.)

1249 <latexrelease> \IncludeInRelease{0000/00/00}{lttemplates}%
1250 <latexrelease>           {Prototype~document~commands}%
1251 <latexrelease>
1252 <latexrelease> \EndModuleRelease

1253 \ExplSyntaxOff
1254 </2ekernel | latexrelease>

  We need to stop DocStrip treating @@ in a special way at this point.
1255 <@@=>

```

# File 12

## lalloc.dtx

### 1 Counters

This section deals with counter and other variable allocation.

1 `<*2ekernel>`

The following are from plain T<sub>E</sub>X:

`\z@` A zero dimen or number. It's more efficient to write `\parindent\z@` than `\parindent 0pt`.

`\@ne` The number 1.

`\m@ne` The number −1.

`\tw@` The number 2.

`\sift@@n` The number 16.

`\@m` The number 1000.

`\@MM` The number 20000.

`\@xxxii` The constant 32.

2 `\chardef\@xxxii=32`

*(End of definition for \@xxxii.)*

`\@Mi` Constants 10001–10004.

`\@Mii` 3 `\mathchardef\@Mi=10001`

`\@Miii` 4 `\mathchardef\@Mii=10002`

`\@Miv` 5 `\mathchardef\@Miii=10003`

6 `\mathchardef\@Miv=10004`

*(End of definition for \@Mi and others.)*

`\@tempcnta` Scratch count registers used by L<sup>A</sup>T<sub>E</sub>X kernel commands.

`\@tempcntb` 7 `\newcount\@tempcnta`

8 `\newcount\@tempcntb`

*(End of definition for \@tempcnta and \@tempcntb.)*

`\if@tempswa` General boolean switch used by L<sup>A</sup>T<sub>E</sub>X kernel commands.

9 `\newif\if@tempswa`

*(End of definition for \if@tempswa.)*

`\@tempdima` Scratch dimen registers used by L<sup>A</sup>T<sub>E</sub>X kernel commands.

`\@tempdimb` 10 `\newdimen\@tempdima`

`\@tempdimc` 11 `\newdimen\@tempdimb`

12 `\newdimen\@tempdimc`

*(End of definition for \@tempdima, \@tempdimb, and \@tempdimc.)*

`\@tempboxa` Scratch box register used by L<sup>A</sup>T<sub>E</sub>X kernel commands.  
<sup>13</sup> `\newbox\@tempboxa`  
*(End of definition for \@tempboxa.)*

`\@tempskipa` Scratch skip registers used by L<sup>A</sup>T<sub>E</sub>X kernel commands.  
`\@tempskipb` <sup>14</sup> `\newskip\@tempskipa`  
<sup>15</sup> `\newskip\@tempskipb`  
*(End of definition for \@tempskipa and \@tempskipb.)*

`\@temptokena` Scratch token register used by L<sup>A</sup>T<sub>E</sub>X kernel commands.  
<sup>16</sup> `\newtoks\@temptokena`  
*(End of definition for \@temptokena.)*

`\@flushglue` Glue used for `\right-` & `\leftskip = 0pt plus 1fil`  
<sup>17</sup> `\newskip\@flushglue \@flushglue = 0pt plus 1fil`  
*(End of definition for \@flushglue.)*  
<sup>18</sup> `\</2ekernel>`

## File 13

# ltnctrl.dtx

## 1 Program control structure

This section defines a number of control structure macros, such as while-loops and for-loops.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
1 \<2kernel>
2 \message{control,}
```

```
\@whilenum TEST \do {BODY}
\@whiledim TEST \do {BODY} : These implement the loop
    while TEST do BODY od
    where TEST is a TeX \ifnum or \ifdim test, respectively.
    They are optimized for the normal case of TEST initially false.
```

```
\@whilesw SWITCH \fi {BODY} : Implements the loop
    while SWITCH do BODY od
    Optimized for normal case of SWITCH initially false.
```

```
\@for NAME := LIST \do {BODY} : Assumes that LIST expands to A1,A2,
    ... ,An .
    Executes BODY n times, with NAME = Ai on the i-th iteration.
    Optimized for the normal case of n = 1. Works for n=0.
```

```
\@tfor NAME := LIST \do {BODY}
    if, before expansion, LIST = T1 ... Tn where each Ti is a
    token or {...}, then executes BODY n times, with NAME = Ti
    on the i-th iteration. Works for n=0.
```

NOTES: 1. These macros use no \@temp sequences.  
2. These macros do not work if the body contains anything that looks syntactically to TeX like an improperly balanced \if \else \fi.

```
\@whilenum TEST \do {BODY} ==
BEGIN
    if TEST
    then BODY
        \@iwhilenum{TEST \relax BODY}
END
```

```
\@iwhilenum {TEST BODY} ==
BEGIN
    if TEST
    then BODY
```

```

        \@nextwhile = def(\@iwhilenum)
    else \@nextwhile = def(\@whilenoop)
    fi
    \@nextwhile {TEST BODY}
END

\@whilesw SWITCH \fi {BODY} ==
BEGIN
    if SWITCH
    then BODY
        \@iwhilesw {SWITCH BODY}\fi
    fi
END

\@iwhilesw {SWITCH BODY} \fi ==
BEGIN
    if SWITCH
    then BODY
        \@nextwhile = def(\@iwhilesw)
    else \@nextwhile = def(\@whileswnoop)
    fi
    \@nextwhile {SWITCH BODY} \fi
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

\@whilenoop
\@whilenum    3 \long\def\@whilenum#1\do #2{\ifnum #1\relax #2\relax\@iwhilenum{#1\relax
\@iwhilenum    4     #2\relax}\fi}
               5 \long\def\@iwhilenum#1{\ifnum #1\expandafter\@iwhilenum
               6     \else\expandafter\@gobble\fi{#1}}

```

*(End of definition for \@whilenoop, \@whilenum, and \@iwhilenum.)*

```

\@whiledim
\@iwhiledim    7 \long\def\@whiledim#1\do #2{\ifdim #1\relax#2\@iwhiledim{#1\relax#2}\fi}
               8 \long\def\@iwhiledim#1{\ifdim #1\expandafter\@iwhiledim
               9     \else\expandafter\@gobble\fi{#1}}

```

*(End of definition for \@whiledim and \@iwhiledim.)*

```

\@whileswnoop
\@whilesw      10 \long\def\@whilesw#1\fi#2{#1#2\@iwhilesw{#1#2}\fi\fi}
\@iwhilesw     11 \long\def\@iwhilesw#1\fi{#1\expandafter\@iwhilesw
               12     \else\@gobbletwo\fi{#1}\fi}

```

(End of definition for \@whileswnoop, \@whilesw, and \@iwhilesw.)

Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):

```
\@for NAME := LIST \do {BODY} ==
  BEGIN \@forloop expand(LIST),\@nil,\@nil \@@ NAME {BODY} END
```

```
\@forloop CAR, CARCDR, CDRCDR \@@ NAME {BODY} ==
  BEGIN
    NAME = CAR
    if def(NAME) = def(\@nnil)
      else BODY;
      NAME = CARCDR
      if def(NAME) = def(\@nnil)
        else BODY
          \@iforloop CDRCDR \@@ NAME \do {BODY}
        fi
      fi
  END
```

```
\@iforloop CAR, CDR \@@ NAME {BODY} =
  NAME = CAR
  if def(NAME) = def(\@nnil)
    then \@nextwhile = def(\@fornoop)
    else BODY ;
      \@nextwhile = def(\@iforloop)
    fi
  \@nextwhile name cdr {body}
```

```
\@tfor NAME := LIST \do {BODY}
  = \@tforloop LIST \@nil \@@ NAME {BODY}
```

```
\@tforloop car cdr \@@ name {body} =
  name = car
  if def(name) = def(\@nnil)
    then \@nextwhile == \@fornoop
    else body ;
      \@nextwhile == \@forloop
    fi
  \@nextwhile name cdr {body}
```

End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.

\@nnil

```
13 \def\@nnil{\@nil}
```

(End of definition for \@nnil.)

\@empty

```
14 \def\@empty{}
```

(End of definition for \@empty.)

```

\@fornoop
15 \long\def\@fornoop#1\@@#2#3{}
(End of definition for \@fornoop.)

\@for
16 \long\def\@for#1:=#2\do#3{%
17   \expandafter\def\expandafter\@fortmp\expandafter{#2}%
18   \ifx\@fortmp\@empty \else
19     \expandafter\@forloop#2,\@nil,\@nil\@@#1{#3}\fi}
(End of definition for \@for.)

\@forloop
20 \long\def\@forloop#1,#2,#3\@@#4#5{\def#4{#1}\ifx #4\@nnil \else
21   #5\def#4{#2}\ifx #4\@nnil \else#5\@iforloop #3\@@#4{#5}\fi\fi}
(End of definition for \@forloop.)

\@iforloop
22 \long\def\@iforloop#1,#2\@@#3#4{\def#3{#1}\ifx #3\@nnil
23   \expandafter\@fornoop \else
24   #4\relax\expandafter\@iforloop\fi#2\@@#3{#4}}
(End of definition for \@iforloop.)

\@tfor
25 \def\@tfor#1:={\@tfor#1 }
26 \long\def\@tfor#1#2\do#3{\def\@fortmp{#2}\ifx\@fortmp\space\else
27   \@tforloop#2\@nil\@nil\@@#1{#3}\fi}
28 \long\def\@tforloop#1#2\@@#3#4{\def#3{#1}\ifx #3\@nnil
29   \expandafter\@fornoop \else
30   #4\relax\expandafter\@tforloop\fi#2\@@#3{#4}}
(End of definition for \@tfor.)

\@break@tfor Break out of a \@tfor loop. This should be called inside the scope of an \if. See
\@iffileonpath for an example.
31 \long\def\@break@tfor#1\@@#2#3{\fi\fi}
(End of definition for \@break@tfor.)

\@removeelement Removes an element from a comma-separated list and puts it into a control sequence,
called as \@removeelement{<element>}{<list>}{<cs>}. Due to the implementation
method the <element> is not allowed to contain braces.
32 \def\@removeelement#1#2#3{%
33   \def\reserved@a##1,#1,##2\reserved@a{##1,##2\reserved@b}%
34   \def\reserved@b##1,\reserved@b##2\reserved@b{%
35     \ifx,##1\@empty\else##1\fi}%
36   \edef#3{%
37     \expandafter\reserved@b\reserved@a,#2,\reserved@b,#1,\reserved@a}}
(End of definition for \@removeelement.)
38 </2ekernel>

```

## File 14

# lterror.dtx

## 1 Error handling and tracing

This section defines L<sup>A</sup>T<sub>E</sub>X's error commands.

```
1 <*2kernel>
```

The ‘2kernel’ code ensures that a `\usepackage{autoerr}` is essentially ignored if a ‘full’ format is being used that has the error messages already in the format.

These days we don't support autoloading approach any longer, but this part bit is kept in case it is used in old documents.

```
2 \expandafter\let\csname ver@autoerr.sty\endcsname\fmtversion
```

### 1.1 General commands

**\MessageBreak** This command prints a new-line inside a message, followed by a continuation line begun with `\@msg@continuation`. Normally it is defined to be `\relax`, but inside messages, it is let to `\@message@break`.

```
3 \let\MessageBreak\relax
```

*(End of definition for \MessageBreak.)*

**\GenericInfo** This takes two arguments: a continuation and a message, and sends the result to the log file.

```
4 \DeclareRobustCommand{\GenericInfo}[2]{%
5   \begingroup
6     \def\MessageBreak{^^J#1}%
7     \set@display@protect
8     \immediate\write\m@ne{#2\on@line.}%
9   \endgroup
10 }
```

*(End of definition for \GenericInfo.)*

**\GenericWarning** This takes two arguments: a continuation and a message, and sends the result to the screen.

```
11 \DeclareRobustCommand{\GenericWarning}[2]{%
12   \begingroup
13     \def\MessageBreak{^^J#1}%
14     \set@display@protect
15     \immediate\write\@unused{^^J#2\on@line.^^J}%
16   \endgroup
17 }
```

*(End of definition for \GenericWarning.)*

`\GenericError` This macro takes four arguments: a continuation, an error message, where to go for further information, and the help information. It displays the error message, and sets the error help (the result of typing `h` to the prompt), and does a horrible hack to turn the last context line (which by default is the only context line) into just three dots. This could be made more efficient.

```

18 \bgroup
19 \lccode'\@=' \ %
20 \lccode'\~=' \ %
21 \lccode'\}=' \ %
22 \lccode'\{=' \ %
23 \lccode'\T=' \T%
24 \lccode'\H=' \H%
25 \catcode'\ =11\relax%
26 \lowercase{%
27 \egroup%
```

Unfortunately  $\text{\TeX}$  versions older than 3.141 have a bug which means that `^^J` does not force a linebreak in `\message` and `\errmessage` commands. So for these old  $\text{\TeX}$ 's we use `\typeout` to produce the message, and then have an empty `\errmessage` command. This causes an extra line of the form

.

To appear on the terminal, but if you do not like it, you can always upgrade your  $\text{\TeX}$ ! In order for your format to use this version, you must define the macro `\@TeXversion` to be the version number, e.g., 3.14 of the underlying  $\text{\TeX}$ . See the comments in `ltdircheck.dtx`.

```

28 \dimen@ifx\@TeXversion\@undefined4\else\@TeXversion\fi\p@%
29 \ifdim\dimen@>3.14\p@%
    First the 'standard case'.
30 \DeclareRobustCommand{\GenericError}[4]{%
31 \begingroup%
32 \immediate\write\@unused{}%
33 \def\MessageBreak{^^J}%
34 \set@display@protect%
35 \edef%
36 % %<-----do not delete this space!----->%
37 \@err@
38 {{#4}}%
39 \errhelp
40 % %<-----do not delete this space!----->%
41 \@err@
42 \let
43 % %<-----do not delete this space!----->%
44 \@err@
45 \@empty
46 \def\MessageBreak{^^J#1}%
47 \def~{\errmessage{%
48 #2.^^J^^J%
49 #3^^J%
50 Type H <return> for immediate help%
51 % %<-----do not delete this space!----->%
52 \@err@
```

```

53 }}%
54 ~%
55 \endgroup}%
56 \else%
    Secondly the version for old TEX's.
57 \DeclareRobustCommand{\GenericError}[4]{%
58 \begingroup%
59 \immediate\write\@unused{}%
60 \def\MessageBreak{^^J}%
61 \set@display@protect%
62 \edef%
63 %    %<-----do not delete this space!----->%
64 \@err@
65 {{#4}}%
66 \errhelp
67 %    %<-----do not delete this space!----->%
68 \@err@
69 \let
70 %    %<-----do not delete this space!----->%
71 \@err@
72 \errmessage
73 \def\MessageBreak{^^J#1}%
74 \def~{\typeout{! %
75 #2.^^J^^J%
76 #3^^J%
77 Type H <return> for immediate help.}%
78 %    %<-----do not delete this space!----->%
79 \@err@
80 }}%
81 ~%
82 \endgroup}%
83 \fi}%

```

(End of definition for \GenericError.)

<code>\PackageError</code> <code>\PackageWarning</code> <code>\PackageWarningNoLine</code> <code>\PackageInfo</code> <code>\ClassError</code> <code>\ClassWarning</code> <code>\ClassWarningNoLine</code> <code>\ClassInfo</code>	<p>These commands are intended for use by package and class writers, to give information to authors. The syntax is:</p> <pre> \PackageError{&lt;package&gt;}{&lt;error&gt;}{&lt;help&gt;} \PackageWarning{&lt;package&gt;}{&lt;warning&gt;} \PackageWarningNoLine{&lt;package&gt;}{&lt;warning&gt;} \PackageInfo{&lt;package&gt;}{&lt;info&gt;} </pre>
--	--

and similarly for classes. The **Error** commands print the `<error>` message, and present the interactive prompt; if the author types `h`, then the `<help>` information is displayed. The **Warning** commands produce a warning but do not present the interactive prompt. The **WarningNoLine** commands do the same, but don't print the input line number. The **Info** commands write the message to the `log` file. Within the messages, the command `\MessageBreak` can be used to break a line, `\protect` can be used to protect command names, and `\space` is a space, for example:

```

\newcommand{\foo}{F00}
\PackageWarning{ethel}{%
  Your hovercraft is full of eels,\MessageBreak
  and \protect\foo\space is \foo}

```

produces:

```

Package ethel warning: Your hovercraft is full of eels,
(ethel)                and \foo is F00 on input line 54.

```

```

84 \gdef\PackageError#1#2#3{%
85   \GenericError{%
86     (#1)\@spaces\@spaces\@spaces\@spaces
87   }{%
88     Package #1 Error: #2%
89   }{%
90     See the #1 package documentation for explanation.%
91   }{#3}%
92 }
93 \def\PackageWarning#1#2{%
94   \GenericWarning{%
95     (#1)\@spaces\@spaces\@spaces\@spaces
96   }{%
97     Package #1 Warning: #2%
98   }%
99 }
100 \def\PackageWarningNoLine#1#2{%
101   \PackageWarning{#1}{#2\@gobble}%
102 }
103 \def\PackageInfo#1#2{%
104   \GenericInfo{%
105     (#1) \@spaces\@spaces\@spaces
106   }{%
107     Package #1 Info: #2%
108   }%
109 }
110 \gdef\ClassError#1#2#3{%
111   \GenericError{%
112     (#1) \space\@spaces\@spaces\@spaces
113   }{%
114     Class #1 Error: #2%
115   }{%
116     See the #1 class documentation for explanation.%
117   }{#3}%
118 }
119 \def\ClassWarning#1#2{%
120   \GenericWarning{%
121     (#1) \space\@spaces\@spaces\@spaces
122   }{%
123     Class #1 Warning: #2%
124   }%
125 }
126 \def\ClassWarningNoLine#1#2{%

```

```

127 \ClassWarning{#1}{#2@gobble}%
128 }
129 \def\ClassInfo#1#2{%
130 \GenericInfo{%
131 (#1) \space\space\@spaces\@spaces
132 }{%
133 Class #1 Info: #2%
134 }%
135 }

```

(End of definition for \PackageError and others.)

```

\ClassNote
\ClassNoteNoLine 136 </2ekernel>
\PackageNote      137 <*2ekernel | latexrelease>
\PackageNoteNoLine 138 <latexrelease> \IncludeInRelease{2021/11/15}%
                  139 <latexrelease> \ClassNote{Notes for classes/packages}%
                  140 \def\ClassNote#1#2{%
                  141 \GenericWarning{%
                  142 (#1) \space\space\@spaces\@spaces
                  143 }{%
                  144 Class #1 Info: #2%
                  145 }%
                  146 }
                  147 \def\ClassNoteNoLine#1#2{\ClassNote{#1}{#2@gobble}}
                  148 \def\PackageNote#1#2{%
                  149 \GenericWarning{%
                  150 (#1) \@spaces\@spaces\@spaces
                  151 }{%
                  152 Package #1 Info: #2%
                  153 }%
                  154 }
                  155 \def\PackageNoteNoLine#1#2{\PackageNote{#1}{#2@gobble}}
                  156 </2ekernel | latexrelease>
                  157 <latexrelease> \EndIncludeInRelease

```

We don't roll back, because if this code is used by packages then most often they will not have rollback code implemented, so they would immediately break even if they otherwise would work fine.

```

158 <latexrelease> \IncludeInRelease{0000/00/00}%
159 <latexrelease> \ClassNote{Notes for classes/packages}%
160 <latexrelease>
161 <latexrelease> \EndIncludeInRelease
162 <*2ekernel>

```

(End of definition for \ClassNote and others.)

```

\@latex@error      Errors and other info, for use in the LATEX core.
\@latex@warning    163 \gdef\@latex@error#1#2{%
\@latex@warning@no@line 164 \GenericError{%
\@latex@info        165 \space\space\space\@spaces\@spaces\@spaces
\@latex@info@no@line 166 }{%
167 LaTeX Error: #1%
168 }%

```

```

169     See the LaTeX manual or LaTeX Companion for explanation.%
170   }{#2}%
171 }
172 \def\@latex@warning#1{%
173   \GenericWarning{%
174     \space\space\space\@spaces\@spaces\@spaces
175   }{%
176     LaTeX Warning: #1%
177   }%
178 }
179 \def\@latex@warning@no@line#1{%
180   \@latex@warning{#1\@gobble}}
181 \def\@latex@info#1{%
182   \GenericInfo{%
183     \@spaces\@spaces\@spaces
184   }{%
185     LaTeX Info: #1%
186   }%
187 }
188 \def\@latex@info@no@line#1{%
189   \@latex@info{#1\@gobble}}

```

\@font@warning and \@font@info are defined later since they have to be redefined by the tracefnt package.

```

def\@font@warning#1{%
  \GenericWarning{%
    {(font)\@spaces\@spaces}%
    {Font Warning: #1}%
  }
def\@font@info#1{%
  \GenericInfo{%
    (font)\space\@spaces
  }{%
    Font Info: #1%
  }%
}

```

*(End of definition for \@latex@error and others.)*

```

\@latex@note These are “info” messages that display on the terminal not just in the transcript.
\@latex@note@no@line
190 </2ekernel>
191 <*2ekernel | latexrelease>
192 <latexrelease> \IncludeInRelease{2021/11/15}%
193 <latexrelease> {\@latex@note}{Display notes}%
194 \def\@latex@note#1{%
195   \GenericWarning{%
196     \@spaces\@spaces\@spaces
197   }{%
198     LaTeX Info: #1%
199   }%
200 }

```

```

201 \def\@latex@note@no@line#1{%
202   \@latex@note{#1@gobble}}

```

We don't make them undefined but rather point to `\@latex@info` because that's what they replace. This way we can change `\@latex@info` elsewhere without the need to further rollback sections.

```

203 </2ekernel | latexrelease>
204 <latexrelease>\EndIncludeInRelease
205 <latexrelease>\IncludeInRelease{0000/00/00}%
206 <latexrelease>          {\@latex@note}{Display notes}%
207 <latexrelease>
208 <latexrelease>\let\@latex@note\@latex@info
209 <latexrelease>\let\@latex@note@no@line\@latex@info@no@line
210 <latexrelease>\EndIncludeInRelease
211 <*2ekernel>

```

*(End of definition for \@latex@note and \@latex@note@no@line.)*

**\c@errorcontextlines** `\errorcontextlines` as a L<sup>A</sup>T<sub>E</sub>X counter, so that it may be manipulated with `\setcounter` (once it is defined :-)

```

212 \let\c@errorcontextlines\errorcontextlines
213 \c@errorcontextlines=-1

```

*(End of definition for \c@errorcontextlines.)*

**\on@line** The message ‘on input line *n*’.

```

214 \def\on@line{ on input line \the\inputlineno}

```

*(End of definition for \on@line.)*

**\@warning** Older L<sup>A</sup>T<sub>E</sub>X messages. For the moment, these `\let` to the new message commands. They may be changed later, once only obsolete packages and classes contain them.

**\@latexerr**

```

215 \let\@warning\@latex@warning
216 \let\@@warning\@latex@warning@no@line
217 \global\let\@latexerr\@latex@error

```

*(End of definition for \@warning, \@@warning, and \@latexerr.)*

**\@spaces** Four spaces.

```

218 \def\@spaces{\space\space\space\space}

```

*(End of definition for \@spaces.)*

## 1.2 Specific errors

**\@eha** The more common error help messages.

```

219 \gdef\@eha{%
220   Your command was ignored.\MessageBreak
221   Type \space I <command> <return> \space to replace it %
222   with another command,\MessageBreak
223   or \space <return> \space to continue without it.}
224 \gdef\@ehb{%
225   You've lost some text. \space \@ehc}
226 \gdef\@ehc{%
227   Try typing \space <return> %

```

```

228 \space to proceed.\MessageBreak
229 If that doesn't work, type \space X <return> \space to quit.}
230 \gdef\@ehd{%
231 You're in trouble here. \space\@ehc}

(End of definition for \@eha and others.)

\@notdefinable Error message generated in \@ifdefinable from calls to one of the commands \newcommand,
\newlength or \newtheorem specifying an already-defined command name or one that
begins \end....
232 \gdef\@notdefinable{%
233 \@latex@error{%
234 Command \@backslashchar\reserved@a\space
235 already defined.\MessageBreak
236 Or name \@backslashchar\@qend... illegal,
237 see p.192 of the manual}\@eha}

(End of definition for \@notdefinable.)

\@nolnerr Generated by \newline and \\ when called in vertical mode.
238 \gdef\@nolnerr{%
239 \@latex@error{There's no line here to end}\@eha}

(End of definition for \@nolnerr.)

\@nocounterr Generated by \setcounter, \addtocounter or \newcounter if applied to an undefined
counter <cnt>.

\@nocnterr Obsolete error message generated in LATEX2.09 by \setcounter, \addtocounter or
\newcounter for undefined counter. DO NOT use for LATEX 2ε it MIGHT vanish! Use
\@nocounterr{<cnt>} instead.
240 \gdef\@nocounterr#1{%
241 \@latex@error{No counter '#1' defined}\@eha}
242 \gdef\@nocnterr{\@nocounterr?}

(End of definition for \@nocounterr and \@nocnterr.)

\@ctrerr Called when trying to print the value of a counter numbered by letters that's greater
than 26.
243 \gdef\@ctrerr{%
244 \@latex@error{Counter too large}\@ehb}

(End of definition for \@ctrerr.)

\@nodocument Error produced if paragraphs are typeset in the preamble.
245 \gdef\@nodocument{%
246 \@latex@error{Missing \protect\begin{document}}\@ehd}

(End of definition for \@nodocument.)

```

`\@badend` Called by `\end` that doesn't match its `\begin`. RmS 1992/08/24: added code to `\@badend` to display position of non-matching `\begin`. FMi 1993/01/14: missing space added.

The environment name has to literally match, i.e., what is stored in `\@currenvir` (after one expansion) must match what is passed to `\end` (without expansion). If not we complain. Not the absolute best solution but at least it avoids getting `\begin{foo}` ended by `\end{foo}` which was possible in the past.

```
247 \gdef\@badend#1{%
248   \latex@error{\protect\begin
249     {\detokenize\expandafter{\@currenvir}}\@currenvline
250     \space ended by \protect\end{\detokenize{#1}}}\@eha}
```

*(End of definition for \@badend.)*

`\@badmath` Called by `\[, \]`, `\(` or `\)` when used in wrong mode.

```
251 \gdef\@badmath{%
252   \latex@error{Bad math environment delimiter}\@eha}
```

*(End of definition for \@badmath.)*

`\@toodeep` Called by a list environment nested more than six levels deep, or an `enumerate` or `itemize` nested more than four levels.

```
253 \gdef\@toodeep{%
254   \latex@error{Too deeply nested}\@ehd}
```

*(End of definition for \@toodeep.)*

`\@badpoptabs` Called by `\endtabbing` when not enough `\poptabs` have occurred, or by `\poptabs` when too many have occurred.

```
255 \gdef\@badpoptabs{%
256   \latex@error{\protect\pushtabs\space and \protect\poptabs
257     \space don't match}\@ehd}
```

*(End of definition for \@badpoptabs.)*

`\@badtab` Called by `\>`, `\+`, `\-` or `\<` when stepping to an undefined tab.

```
258 \gdef\@badtab{%
259   \latex@error{Undefined tab position}\@ehd}
```

*(End of definition for \@badtab.)*

`\@preamerr` This error is special: it appears in places where we normally have to `\protect` expansions. However, to prevent a protection of the error message itself (which would result in the message getting printed not issued on the terminal) we need to locally reset `\protect` to `\relax`.

```
260 \gdef\@preamerr#1{%
261   \begingroup
262     \let\protect\relax
263     \latex@error{\ifcase #1 Illegal character\or
264       Missing @-exp\or Missing p-arg\fi\space
265       in array arg}\@ehd
266   \endgroup}
```

*(End of definition for \@preamerr.)*

`\@badlinearg` Occurs in `\line` and `\vector` command when a bad slope argument is encountered.

```

267 \gdef\@badlinearg{%
268   \latexerror{%
269     Bad \protect\line\space or \protect\vector
270     \space argument}\@ehb}

```

*(End of definition for \@badlinearg.)*

`\@LRmoderr` A command is not allowed in restricted horizontal mode, i.e., in LR-mode in L<sup>A</sup>T<sub>E</sub>X terminology.

```

271 \gdef\@LRmoderr{%
272   \latexerror{Not allowed in LR mode}\@ehb}

```

*(End of definition for \@LRmoderr.)*

`\@parmoderr` Occurs in a float environment or a `\marginpar` when encountered in inner vertical mode.

```

273 \gdef\@parmoderr{%
274   \latexerror{Not in outer par mode}\@ehb}

```

*(End of definition for \@parmoderr.)*

`\@fltovf` Occurs in float environment or `\marginpar` when there are no more free boxes for storing floats.

```

275 \gdef\@fltovf{%
276   \latexerror{Too many unprocessed floats}\@ehb}

```

*(End of definition for \@fltovf.)*

`\@latexbug` Occurs in output routine. This is bad news.

```

277 \gdef\@latexbug{%
278   \latexerror{This may be a LaTeX bug}{Call for help}}

```

*(End of definition for \@latexbug.)*

`\@badcrerr` This error was removed and replaced by `\@nolnerr`.

```

279 %\def\@badcrerr {\latexerror{Bad use of \protect\\}\@ehc}

```

*(End of definition for \@badcrerr.)*

`\@noitemerr` `\addvspace` or `\addpenalty` was called when not in vmode. Probably caused by a missing `\item`.

```

280 \gdef\@noitemerr{%
281   \latexerror{Something's wrong--perhaps a missing %
282     \protect\item}\@ehc}

```

*(End of definition for \@noitemerr.)*

`\@notprerr` A command that can be used only in the preamble appears after the command `\begin{document}`.

```

283 \gdef\@notprerr{%
284   \latexerror{Can be used only in preamble}\@eha}

```

*(End of definition for \@notprerr.)*

`\@inmatherr` Issued by commands that don't work correctly within math (like `\item`). There is no real error recovery happening, e.g., the user might get additional errors afterwards.

```

285 \gdef\@inmatherr#1{%
286   \relax
287   \ifmmode
288     \@latex@error{Command \protect#1 invalid in math mode}\@ehc
289   \fi}

```

*(End of definition for \@inmatherr.)*

`\@invalidchar` An error for use with invalid characters. This is commented out, since we decided to use catcode 15 instead.

```

290 %\def\@invalidchar{\@latex@error{Invalid character in input}\@ehc}

```

*(End of definition for \@invalidchar.)*

As well as the above error commands some error messages are directly coded to save space. The messages already present in L<sup>A</sup>T<sub>E</sub>X2.09 include:

**Environment --- undefined**

Issued by `\begin` for undefined environment.

**Tab overflow**

Occurs in `\=` when maximum number of tabs exceeded.

**< in mid line**

Occurs in `<` when it appears in middle of line.

**Float(s) lost**

In output routine, caused by a float environment or `\marginpar` occurring in inner vertical mode.

### 1.3 Tracing

The `trace` package implements the commands `\traceon` and `\traceoff` that work similar to `\tracingall` but skip certain code blocks that produce a lot of tracing output being of no interest during debugging (for example loading a font). Code blocks that should be hidden during tracing need to be surrounded by the macros `\conditionally@traceoff` and `\contionally@traceon`.

For the kernel code the `trace` package then redefines a number of macros to include this tracing support.

However, in order to allow any macro package to react to `\traceon` we also provide dummy definitions for the two commands in the kernel so that they can be used by external packages without the need to distinguish between `trace` being loaded or not.

`\conditionally@traceon` These are only dummy definitions. For details see the `trace` package.

```

\conditionally@traceoff
291 \let\conditionally@traceon\@empty
292 \let\conditionally@traceoff\@empty

```

*(End of definition for \conditionally@traceon and \conditionally@traceoff.)*

```

293 \</2kernel>

```

## File 15

# ltpar.dtx

## 1 Paragraphs

This section of the kernel declares the commands used to set `\par` and `\everypar` when ever their function needs to be changed for a long time.

This file here describes the interfaces that have been in the kernel forever, used to implement the scenarios described below. They remain valid but are now augmented in the next file (`ltpara.dtx`) to add hooks to paragraphs. At some point we will consolidate the two files further.

There are two situations in which `\par` may be changed:

- Long-term changes, in which the new value is to remain in effect until the current environment is left. The environments that change `\par` in this way are the following:
  - All list environments (itemize, quote, etc.)
  - Environments that turn `\par` into a noop: tabbing, array and tabular.
- Temporary changes, in which `\par` is restored to its previous value the next time it is executed. The following are all such uses.
  - `\end` when preceded by `\@endparenv`, which is called by `\endtrivlist`
  - The mechanism for avoiding page breaks and getting the spacing right after section heads.

### 1.1 Implementation

`\@setpar` To permit the proper interaction of these two situations, long-term changes are made by the `\@setpar{<VAL>}` command. Its function is:

To set `\par`. It `\def`'s `\par` and `\@par` to `<VAL>`.

`\@restorepar` Short-term changes are made by the usual `\def\par` commands. The original values are restored after a short-term change by the `\@restorepar` commands.

`\@@par` `\@@par` always is defined to be the original TeX `\par`.

`\everypar` `\everypar` is changed only for the short term. Whenever `\everypar` is set non-null, it should restore itself to null when executed.

The following commands change `\everypar` in this way:

- `\item`
- `\end` when preceded by `\@endparenv`, which is called by `\endtrivlist`
- `\minipage`

When dealing with `\par` and `\everypar` remember the following two warnings:

1. Commands that make short-term changes to `\par` and `\everypar` must take account of the possibility that the new commands and the ones that do the restoration may be executed inside a group. In particular, `\everypar` is executed inside a group whenever a new paragraph begins with a left brace. The `\everypar` command that restores its definition should be local to the current group (in case the command is inside a minipage used inside someplace where `\everypar` has been redefined). Thus, if `\everypar` is redefined to do an `\everypar{}` it could take several executions of `\everypar` before the restoration “holds”. This usually causes no problem. However, to prevent the extra executions from doing harm, use a global switch to keep anything harmful in the new `\everypar` from being done twice.
2. Commands that change `\everypar` should remember that `\everypar` might be supposed to set the following switches false:
  - `@nobreak`
  - `@minipage`

they should do the setting if necessary.

```

1 <*2kernel>
2 \message{par,}

```

```

\@setpar  Initiate a long-term change to \par.
\@par    3 \def\@setpar#1{\def\par{#1}\def\@par{#1}}

```

The default definition of `\@par` will ensure that if `\@restorepar` defines `\par` to execute `\@par` it will redefine itself to the primitive `\@@par` after one iteration.

```

4 \def\@par{\let\par\@@par\par}

```

*(End of definition for \@setpar and \@par.)*

```

\@restorepar  Restore from a short-term change to \par.

```

```

5 \def\@restorepar{\def\par{\@par}}
6 </2kernel>

```

*(End of definition for \@restorepar.)*

## File 16

# ltpara.dtx

### Abstract

This code defines four special kernel hooks to support paragraph tagging as well as four public hooks which can be occasionally useful.

## 1 Introduction

The building of paragraphs in the T<sub>E</sub>X engine(s) has a number of peculiarities that makes it on one hand fairly flexible but on the other hand somewhat awkward to control or reliably to extend. Thus to better understand the code below we start with a brief introduction of the mechanism; for more details refer to the T<sub>E</sub>Xbook [?, chap. 14] (for the full truth you may even have to study the program code).

### 1.1 The default processing done by the engine

T<sub>E</sub>X automatically starts building a paragraph when it is currently in vertical mode and encounters anything that can only live in horizontal mode. Most often this is a character, but there are also many commands that can be used only in horizontal mode. If any of them is encountered, T<sub>E</sub>X will immediately back up (i.e., the character or command is read later again), adds a `\parskip` glue to the current vertical list unless the list is empty, switches to horizontal mode, starts its special “start of paragraph processing” and only then rereads the character or command that caused the mode change.<sup>24</sup>

This “start of paragraph processing” first adds an empty box at the start of the horizontal list of width `\parindent` (which represents the paragraph indentation) unless the paragraph was started with `\noindent` in which case no such box is added<sup>25</sup>. It then reads and processes all tokens stored in the special engine token register `\everypar`. After that it reads and processes whatever has caused the paragraph to start.

Thus out of the box, T<sub>E</sub>X offers the possibility to put some special code into `\everypar` to gain control at (more or less) the start of the paragraph. For example, in LaTeX and a number of packages, special code like the following is sometimes used:

```
\everypar{\setbox\z@\lastbox}\everypar{} ...}
```

This removes the paragraph indentation box again (that was already placed by T<sub>E</sub>X), then resets `\everypar` so that it doesn’t do anything on the next paragraph start and then does whatever it wants to do, e.g., in an `\item` of a list it will typeset the label in front of the paragraph text. However, there is only one such `\everypar` token register and if different packages and/or the kernel all attempt to add their own code here, coordination is very difficult if not impossible.

The process when the paragraph ends has different mechanisms and interfaces. A paragraph ends when the engine primitive `\par` is called while T<sub>E</sub>X is in unrestricted horizontal mode, i.e., is building a paragraph. At other times this primitive does nothing or generates as an error depending on the mode T<sub>E</sub>X is in, e.g., the `\par` in `\hbox{a\par b}` is ignored, but `$a\par b$` would complain.

---

<sup>24</sup>Already not quite true: the command `\noindent` starts the paragraph but influences the special processing by suppressing the paragraph indentation box normally inserted by it.

<sup>25</sup>That’s a bit different from placing a zero-sized box!

If this primitive ends the paragraph it does some special “end of horizontal list” processing, then calls  $\text{\TeX}$ ’s paragraph builder; this breaks the horizontal list into lines and then these lines are added as boxes to the enclosing vertical list and  $\text{\TeX}$  returns to vertical mode.

This  $\text{\par}$  command can be given explicitly, but there are also situations in which  $\text{\TeX}$  is generating it on the fly. Most often this happens when  $\text{\TeX}$  encounters a blank line which is automatically changed to a  $\text{\par}$  command which is then executed. The other possibility is that  $\text{\TeX}$  encounters a command which is incompatible with horizontal processing, e.g.,  $\text{\vskip}$  (a request for adding vertical space). In such cases it silently backs up, and inserts a  $\text{\par}$  in the hope that this gets it out of horizontal mode and makes the vertical command acceptable.

The important point to note here is that  $\text{\TeX}$  really inserts the command with the name  $\text{\par}$ , which can be redefined. Thus, it may not have its original “primitive” meaning and therefore may not end the horizontal list and call the paragraph builder. This approach offers some flexibility but also allows you to easily produce a  $\text{\TeX}$  document that loops forever, for example, the simple line

```
A \let\par\relax \vskip
```

will start a horizontal list at A, redefines  $\text{\par}$ , then sees  $\text{\vskip}$  and inserts  $\text{\par}$  to end the paragraph. But this now only runs  $\text{\relax}$  so nothing changes and  $\text{\vskip}$  is read again, issues a  $\text{\par}$  which .... In short, it only takes a plain  $\text{\TeX}$  document with five tokens to run forever (since no memory is consumed and therefore eventually exhausted).

There is no way other than changing  $\text{\par}$  to gain control at the end of a paragraph, i.e., there is no token list like  $\text{\everypar}$  that is inserted. Hence the only way to change the default behavior is to modify the action that  $\text{\par}$  executes, with similar issues as outlined before: different processes need to ensure that they do not overwrite their modifications or worse, think that the  $\text{\par}$  in front of them is the engine primitive while in fact it has already been changed by other code.

To make matters slightly worse there are a few places where  $\text{\TeX}$  handles the situation differently (most likely for speed reasons back when computers were much slower). If  $\text{\TeX}$  finds itself in unrestricted horizontal mode at the end of building a vertical box (for an  $\text{\insert}$ ,  $\text{\vadjust}$  or executing the output routine code), it will finish the horizontal list not by issuing a  $\text{\par}$  command (which would be consistent with all other places) but by simply executing the primitive meaning of  $\text{\par}$ , regardless of the actual definition that  $\text{\par}$  has at the time.

Thus, if you have carefully crafted a redefined  $\text{\par}$  to execute some special actions at the end of a paragraph and you write something like

```
\vbox{Some paragraph ... text.}
```

you will find that your code does not get run for the last paragraph in that box.  $\text{\LaTeX}$  avoids this problem, by making sure that its boxes (such as  $\text{\parbox}$  or the  $\text{\minipage}$  environment, etc.) all internally add an explicit  $\text{\par}$  at the end so that such code is run and  $\text{\TeX}$  finds itself in vertical mode already without the need to start up the paragraph builder internally. But, of course, this only works for boxes under direct control of the  $\text{\LaTeX}$  kernel; if some package uses low-level  $\text{\vboxes}$  without adding this precaution the  $\text{\TeX}$  optimization kicks in and no special  $\text{\par}$  code is executed.

And there is another optimization that is painful: if a paragraph is interrupted by a mathematical display, e.g.,  $\text{\[...]}$  in  $\text{\LaTeX}$  or  $\text{\$...\$}$  in plain  $\text{\TeX}$ , then  $\text{\TeX}$  will resume horizontal mode afterward, i.e., it will start to build a new horizontal list

without inserting an indentation box or `\everypar` at that point. However, if that list immediately ends with an explicit or implicit `\par` then  $\text{\TeX}$  will simply throw away this “null” paragraph and not do its usual “end of horizontal list” processing, so this special case also needs to be accounted for when introducing any extended processing.

## 2 The new mechanism implemented for $\text{\LaTeX}$

To improve the situation (and also to support automatic tagging of PDF documents) we now offer public as well as private hooks at the start and end of the paragraph processing. The public hooks can be used by packages (or by the user in the preamble or within the document) and using the hook mechanisms it is possible to reorder or arrange code from different packages in such a way that these can safely coexist.

To make that happen we have to make use of the basic functionality that is offered by  $\text{\TeX}$ , e.g., we install special code inside `\everypar` to provide hooks at the beginning and we redefine `\par` to do some special processing when appropriate to install hooks at the end of the paragraph.

In order to make this work, we have to ensure that package use of `\everypar` is not overwriting our code. This is done through a trick: we basically hide the real `\everypar` from the packages and offer them a new token register (with the same name). So if they install their own code it doesn’t overwrite ours. Our code then inserts the new `\everypar` at the right place inside the process so that it looks as if it was the primitive `\everypar`.<sup>26</sup>

At the end of the paragraph it would be great if we could use a similar trick. However, due to the fact that  $\text{\TeX}$  inserts the token `\par` (that doesn’t have a defined meaning) we can’t hide “the real thing<sup>TM</sup>” and offer the package an indistinguishable alternate.

Fortunately,  $\text{\LaTeX}$  has already redefined `\par` for its own purposes. As a result there aren’t many packages that attempt to change `\par`, because without a lot of extra care that would fail miserably. But the bottom line is that, if you load a package that alters `\par` then the end of paragraph hooks are most likely not executing while that redefinition is active.<sup>27</sup>

---

<sup>26</sup>Ideally, `\everypar` wouldn’t be used at all by packages and instead they would simply write their code into the hooks now offered by the kernel. However, while this is the longterm goal and clearly an improvement (because then the packages do no longer need to worry about getting their code overwritten or needing to account for already existing code in `\everypar`), this will not happen overnight. For that reason support for this legacy method is retained.

<sup>27</sup>Similarly to the `\everypar` situation, the remedy is that such packages stop doing this and instead add their alterations into the paragraph hooks now provided.

## 2.1 The provided hooks

<hr/>	The following four public hooks are defined and executed for each paragraph:
para/before	
para/begin	
para/end	<b>para/before</b> This hook is executed after the kernel hook <code>\@kernel@before@para@before</code> (discussed below) in vertical mode immediately after $\text{\TeX}$ has contributed <code>\parskip</code> to the vertical list and before the actual paragraph processing in horizontal mode starts.
para/after	This hook should either not produce any typeset material or add only vertical material. If it starts a paragraph an error is generated. The reason is that we are in the starting process of processing a paragraph and so this would lead to endless recursion. <sup>28</sup>
	<b>para/begin</b> This hook is executed after the kernel hook <code>\@kernel@before@para@begin</code> (discussed below) in horizontal mode immediately before the indentation box is placed (if there is any, i.e., if the paragraph hasn't been started with <code>\noindent</code> ). The indentation box to be typeset is available to the hook as <code>\IndentBox</code> and its automatic placement (after the hook is executed) can be prevented through <code>\OmitIndent</code> . More precisely <code>\OmitIndent</code> voids the box. The indentation box is then typeset directly after the hook execution by something equivalent to <code>\box\IndentBox</code> followed by the current content of the token register <code>\everypar</code> that it is available to the kernel or to packages (that run some legacy code). One has to be careful not to add any code to the hook that starts its own paragraph (e.g., by adding a <code>\parbox</code> or a <code>\marginpar</code> inside) because that would call the hook inside again (as a new paragraph is started there) and thus lead to an endless recursion ending only after exhausting the available memory. This can only be done by making sure that is not executed for the inner paragraphs (or at least not recursively forever).
	<b>para/end</b> This hook is executed at the end of a paragraph when $\text{\TeX}$ is ready to return to vertical mode and after it has removed the last horizontal glue (but not any kerns) placed on the horizontal list. The code is still executed in horizontal mode so it is possible to add further horizontal material at this point, but it should not alter the mode (even a temporary exit from horizontal mode would create chaos—any attempt will cause an error message)! After the hook has ended the kernel hook <code>\@kernel@after@para@end</code> is executed and then $\text{\TeX}$ returns to vertical mode. The hook is offered as public hook, but because of the requirement to stay within horizontal mode one needs to be careful in what is placed into the hook. <sup>29</sup> This hook is implemented as a reversed hook.
	<b>para/after</b> This hook is executed directly after $\text{\TeX}$ has returned to vertical mode and after any material that migrated out of the horizontal list (e.g., from a <code>\vadjust</code> ) has processed.

<sup>28</sup>One could allow it but only if the newly started paragraph is processed without any hooks. Further—more correct spacing would be a bit of a nightmare so for now this is forbidden.

<sup>29</sup>Maybe we should guard against that, but it would be rather tricky to implement as mode changes can happen across group boundaries so one would need to keep a private stack just for that. Well, something to ponder.

This hook should either not produce any typeset material or add only vertical material. However, for this hook starting a new paragraph is not a disaster so that it isn't prevented.

This hook is implemented as a reversed hook.

Once that hook code has been processed the kernel hook `\@kernel@after@para@after` is executed as the final action of the paragraph processing.

---

```
\@kernel@before@para@before
\@kernel@after@para@after
\@kernel@before@para@begin
\@kernel@after@para@end
```

---

As already mentioned above there are also four kernel hooks that are executed at the start and end of the processing.

`\@kernel@before@para@before` For future extensions, not currently used by the kernel.

`\@kernel@after@para@after` For future extensions, not currently used by the kernel.

`\@kernel@before@para@begin` Used by the kernel to implement tagging. This hook is executed at the very beginning of a paragraph after `TEX` has switched to horizontal mode but before any indentation box got added or any `\everypar` was run.

It should not generate typeset material that could alter the position. Note that it should never leave hmode, otherwise you will end with a loop! We could guard against this, but since it is an internal kernel hook that shouldn't be touched this isn't checked.

`\@kernel@after@para@end` Used by the kernel to implement tagging. It is executed directly after the public `para/end` hook. After it there is a quick check that we are still in horizontal mode, i.e., that the public hook has not mistakenly ended horizontal mode prematurely (this is an incomplete check just testing the mode and could perhaps be improved (at the cost of speed)).

## 2.2 Altered and newly provided commands

---

```
\par
\endgraf
\para_end:
```

---

An explicit request for ending a paragraph is provided in plain `TEX` under the name `\endgraf`, which simply uses the primitive meaning (regardless of what `\par` may have as its current definition). In `LATEX` `\endgraf` (with that behavior) was originally also available.

With the new paragraph handling in `LATEX`, ending a paragraph means a bit more than just calling the engine's paragraph builder: the process also has to add any hook code for the end of a paragraph. Thus `\endgraf` was changed to provide this additional functionality (along with `\par` remaining subject to its current meaning).

The `expl3` name for this functionality is `\para_end:`.

**Note:** *The next two commands are still under discussion and may slightly change their semantics (as described in the document) and/or their names between now and the 2021 Spring release!*

<hr/> <code>\OmitIndent</code> <hr/>	
<code>\para_omit_indent:</code>	Inside the <code>para/begin</code> hook one can use this command to suppress the indentation box at the start of the paragraph. (Technically it is possible to use this command outside the hook as well, but this should not be relied upon.) The box itself remains available for use.
	The expl3 name for the function is <code>\para_omit_indent:</code> .
<hr/> <code>\IndentBox</code> <hr/>	
<code>\g_para_indent_box</code>	The box register holding the indentation box for the paragraph is available for inspection (or changes) inside hooks. It remains available even if the <code>\OmitIndent</code> command was used; in that case it will just not be automatically placed.
	The expl3 name for the box register is <code>\g_para_indent_box</code> .
<hr/> <code>\RawIndent</code> <hr/>	<code>\RawIndent    <i>hmode material</i> \RawParEnd</code>
<code>\para_raw_indent:</code>	<code>\RawNoindent <i>hmode material</i> \RawParEnd</code>
<code>\RawNoindent</code>	The commands <code>\RawIndent</code> and <code>\RawNoindent</code> are not meant for normal paragraph building (where the result is a textual paragraph in the traditional meaning of the word), but for special cases where TeX's low-level algorithm is used to achieve special effects, but where the result is not a "paragraph".
<code>\para_raw_noindent:</code>	
<code>\RawParEnd</code>	
<code>\para_raw_end:</code>	
	They are called "raw", because they bypass L <sup>A</sup> T <sub>E</sub> X's hook mechanism for paragraphs and simply invoke the low-level TeX algorithm. I.e., they are like the original TeX primitives <code>\indent</code> and <code>\noindent</code> (that is they execute no hooks other than <code>\everypar</code> ) except that they can only be used in vertical mode and generate an error if found elsewhere.
	To avoid issues a paragraph started by them should always be ended by <code>\RawParEnd</code> <sup>30</sup> and not by <code>\par</code> (or a blank line), because the latter will execute hooks which then have no counterpart at the beginning of the paragraph. It is the responsibility of the programmer to make sure that they are properly paired. This also means that one should not put arbitrary user content between these commands if that content could contain stray <code>\pars</code> .
	The expl3 names for the functions are <code>\para_raw_indent:</code> , <code>\para_raw_indent:</code> and <code>\para_raw_end:</code> .

## 2.3 Examples

None of the examples in this section are meant for real use as they are far too simple-minded but they should give some ideas of what could be possible if a bit more care is applied.

### 2.3.1 Testing the mechanism

The idea is to output for each paragraph encountered some information: a paragraph sequence number, a level number in roman numerals, the environment in which this paragraph appears, and the line number where the start or end of the paragraph is, e.g., something like

<sup>30</sup>Technical note for those who know their *T<sub>E</sub>Xbook*: the `\RawParEnd` command invokes the original TeX engine definition of `\par` that (solely) triggers the paragraph builder in TeX when found inside unrestricted horizontal mode and does nothing in other processing modes.

```

PARA: 1-i start (document env. on input line 38)
PARA: 1-i end   (document env. on input line 38)
PARA: 2-i start (document env. on input line 40)
PARA: 3-ii start (minipage env. on input line 40)
PARA: 3-ii end   (minipage env. on input line 40)
PARA: 2-i end   (document env. on input line 41)

```

As you can see paragraph 2 starts on line 40 and ends on 41 and inside a minipage started paragraph 3 (start and end on line 40). If you run this on some document you will find that L<sup>A</sup>T<sub>E</sub>X considers more things “a paragraph” than you have probably thought.

This was generated by the following hook code:

```

\newcounter{paracnt}          % sequence counter
\newcounter{paralevel}        % level counter

```

To support paragraph nesting we need to maintain a stack of the sequence numbers. This is most easily done using expl3 functions, so we switch over. This is not a very general implementation, just enough for what we need and a bit of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> thrown in as well. When popping, the result gets stored in `\paracntvalue` and the `\ERROR` should never happen because it means we have tried to pop from an empty stack.

```

\ExplSyntaxOn
\seq_new:N \g_para_seq
\cs_new:Npn \ParaPush
  {\seq_gpush:No \g_para_seq {\the\value{paracnt}}}
\cs_new:Npn \ParaPop {\seq_gpop:NNF \g_para_seq \paracntvalue \ERROR }
\ExplSyntaxOff

```

At the start of the paragraph increment both sequence counter and level and also save the then current sequence number on our stack.

```

\makeatletter % because we use a few internal 2e commands
\AddToHook{para/begin}{%
  \stepcounter{paracnt}\stepcounter{paralevel}%
  \ParaPush
}

```

To display the sequence number we `\typeout` the current sequence and level number. The command `\@currenvir` gives us the current environment and `\on@line` produces a space and the current input line number.

```

\typeout{PARA: \arabic{paracnt}-\roman{paralevel} start
  (\@currenvir\space env.\on@line)}%

```

We also typeset the sequence number as a tiny red number in a box that takes up no horizontal space. This helps us seeing where L<sup>A</sup>T<sub>E</sub>X sees the start and end of the paragraphs in the document.

```

\llap{\color{red}\tiny\arabic{paracnt}\ }%
}

```

At the end of the paragraph we display sequence number and level again. The level counter has the correct value but we need to retrieve the right sequence value by popping it off the stack after which it is available in `\paracntvalue` the way we have set this up above.

```

\AddToHook{para/end}{%
  \ParaPop
  \typeout{PARA: \paracntvalue-\roman{paralevel} end \space\space
    (\@currenvir\space env.\on@line)}%
}

```

We also typeset again a tiny red number with that value, this time sticking out to the right.<sup>31</sup> We also decrement the level counter since our level has finished.

```

\rlap{\color{red}\tiny\ \paracntvalue}%
\addtocounter{paralevel}{-1}%
}
\makeatother

```

### 2.3.2 Mark the first paragraph of each `itemize`

The code for this is rather simple. We supply some code that is executed only once inside a hook at the start of each `itemize`. We explicitly change the color back and forth so that we don't introduce grouping around the paragraph.

```

\AddToHook{env/itemize/begin}{%
  \AddToHookNext{para/begin}{\color{blue}}%
  \AddToHookNext{para/end}{\color{black}}%
}

```

As a result the first paragraph of each `itemize` will appear in blue.

## 2.4 Some technical notes

The code tries hard to be transparent for package code, but of course any change means that there is a potential for breaking other code. So in section we collect a few cases that may be of importance if low-level code is dealing with paragraphs that are now behaving slightly differently. The notes are from issues we observed and will probably grow over time.

### 2.4.1 Glue items between paragraphs (found with `fancypar`)

In the past  $\text{\LaTeX}$  placed two glue items between two consecutive paragraphs, e.g.,

```
text1 \par text2 \par
```

would show something like

```

\glue(\parskip) 0.0 plus 1.0
\glue(\baselineskip) 5.16669

```

but now there is another `\parskip` glue (that is always 0pt):

```

\glue(\parskip) 0.0 plus 1.0
\glue(\parskip) 0.0
\glue(\baselineskip) 5.16669

```

---

<sup>31</sup>Note that this can alter the document pagination, because a paragraph ending in a display (e.g., an equation) will get an extra line—in that case our tiny number has an effect even though it doesn't take up any space, because it paragraph is no longer empty and thus isn't dropped!

The reason is that we generate a “fake” paragraph to gain control and safely add the early hooks, but this generates an additional glue item. That item doesn’t contribute anything vertically but if somebody writes code that unravels a constructed list using `\lastbox`, `\unskip` and `\unpenalty` then the code has to remove one additional glue item or else it will fail.

## 3 The Implementation

```

1 <@=para>
2 <*2kernel | latexrelease>
3 \ExplSyntaxOn
4 <latexrelease> \NewModuleRelease{2021/06/01}{ltpara}
5 <latexrelease> {Paragraph-handling-and-hooks}

```

### 3.1 Providing hooks for paragraphs

`para/before` The public hooks. They are implemented as a paired set of hooks.

```

para/after 6 \hook_new_pair:nn{para/before}{para/after}
para/begin 7 \hook_new_pair:nn{para/begin}{para/end}
para/end

```

*(End of definition for `para/before` and others. These functions are documented on page 416.)*

`\@kernel@before@para@before` The corresponding kernel hooks (for tagging and future extensions).

```

8 \let \@kernel@before@para@before \@empty
9 \let \@kernel@before@para@begin \@empty
10 \let \@kernel@after@para@end \@empty
11 \let \@kernel@after@para@after \@empty

```

*(End of definition for `\@kernel@before@para@before` and others. These functions are documented on page 417.)*

`\g__para_standard_everypar_tl`

Whenever  $\text{T}_{\text{E}}\text{X}$  starts a paragraph it inserts first an indentation box and then executes the tokens stored in `\tex_everypar:D` (known to  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$  as `\everypar`). We alter this behavior slightly here, so that hooks are added into the right place. Otherwise the process change remains transparent to any legacy code for this space.

We keep the standard code to be used by `\tex_everypar:D` in a separate token list because we have to switch back and forth for error recovery and so altering `\tex_everypar:D` all the time should be a tiny bit faster.

```

12 <latexrelease> \IncludeInRelease{2023/06/01}
13 <latexrelease> { \g__para_standard_everypar_tl } { minipage~ fix }
14 \tl_new:N \g__para_standard_everypar_tl

```

Here is now its definition:

```

15 \tl_gset:Nn \g__para_standard_everypar_tl {

```

First we remove the indentation box and store it in `\g_para_indent_box`. If there was none because the paragraph was started by `\noindent` the box register will be void.

```

16 \box_gset_to_last:N \g_para_indent_box

```

This will make the newly started horizontal list empty, so if we stop it now and return to vertical mode it will be dropped by  $\text{T}_{\text{E}}\text{X}$ . We do that but inside a group so that any `\parshape` settings will not get lost as we need them for later.

```

17 \group_begin:
18 \tex_par:D
19 \group_end:

```

We then change `\tex_everypar:D` to generate an error so that we can detect and report if the `para/before` hook illegally changed out of vmode.

```

20 \tex_everypar:D { \msg_error:nnnn { hooks }{ para-mode }{before}{vertical} }
21 \@kernel@before@para@before
22 \hook_use:n {para/before}

```

Assuming the hooks have been well behaved it is time to return to horizontal mode and start the paragraph in earnest. We already have the indentation box saved away so we now have to restart the paragraph with an empty `\tex_everypar:D` and with `\tex_noindent:D`. And we need to make sure not to get another `\parskip` or rather (since we can't prevent that) that it is of zero size.

```

23 \group_begin:
24 \tex_everypar:D {}

```

There has been a long-standing problem with L<sup>A</sup>T<sub>E</sub>X's minipages in that invisible material at the beginning of a minipage (such as a `\color` setting) would result in `\parskip` being added in front of the first paragraph—something that is not done by T<sub>E</sub>X if a vertical list is completely empty. As this is happening on a very low-level in the engine it wasn't really possible to find out if this `\parskip` was added or if a space we see in front of the current point is legitimate. However, with the new paragraph handling we are in a better position: while we still don't know if there is such a space or not, we do know if we have just created an empty paragraph. Thus, if we now set `\parskip` to `-\parskip` the two will cancel each other if present and if the first was ignored because the vertical list was empty, then the second will be ignored too because it is still empty. Of course, we don't want to cancel always but only at the start of a minipage and that is signaled with the `@minipage` switch.

```

25 \skip_set:Nn \tex_parskip:D
26 { \if@minipage -\tex_parskip:D \else: \c_zero_skip \fi: }
27 \tex_noindent:D
28 \group_end:

```

That brings us back to the start of the horizontal list but we need to change `\tex_everypar:D` back to its normal content in case there are nested paragraphs coming up.

```

29 \tex_everypar:D{\g__para_standard_everypar_tl}

```

This is followed by executing the kernel and the public hook. The kernel hook is there to enable tagging.

```

30 \@kernel@before@para@begin
31 \hook_use:n {para/begin}

```

If we aren't in horizontal mode any longer the hooks above misbehaved.

```

32 \if_mode_horizontal: \else:
33 \msg_error:nnnn { hooks }{ para-mode }{begin}{horizontal} \fi:

```

Finally we reinsert the indentation box (unless suppressed) and then call `\everypar` the way legacy L<sup>A</sup>T<sub>E</sub>X code expects it.

However, adding the public `\everypar` is a bit tricky (see below) so we add that later, and indirectly.

```

34 \__para_handle_indent:
35 % \the \everypar % <--- done differently below
36 }

```

```

37 <latexrelease>\cs_set:Npn \__para_tmp:w #1#2#3#4#5 { }
38 <latexrelease>\tl_gput_right:Nx \g__para_standard_everypar_tl {
39 <latexrelease>  \exp_not:N \the
40 <latexrelease>  \exp_not:N \toks
41 <latexrelease>  \exp_after:wN \__para_tmp:w \token_to_meaning:N \everypar
42 <latexrelease>  \c_space_tl
43 <latexrelease>}
44 <latexrelease>\EndIncludeInRelease
45 <latexrelease>\IncludeInRelease{2021/06/01}
46 <latexrelease>      {\g__para_standard_everypar_tl}{minipage~ fix}
47 <latexrelease>
48 <latexrelease>\tl_gset:Nn \g__para_standard_everypar_tl {
49 <latexrelease>  \box_gset_to_last:N \g_para_indent_box
50 <latexrelease>  \group_begin:
51 <latexrelease>    \tex_par:D
52 <latexrelease>  \group_end:
53 <latexrelease>  \tex_everypar:D { \msg_error:nnnn { hooks }{ para-mode }{before}{vertical} }
54 <latexrelease>  \@kernel@before@para@before
55 <latexrelease>  \hook_use:n {para/before}
56 <latexrelease>  \group_begin:
57 <latexrelease>    \tex_everypar:D {}
58 <latexrelease>    \skip_zero:N \tex_parskip:D
59 <latexrelease>    \tex_noindent:D
60 <latexrelease>  \group_end:
61 <latexrelease>  \tex_everypar:D{\g__para_standard_everypar_tl}
62 <latexrelease>  \@kernel@before@para@begin
63 <latexrelease>  \hook_use:n {para/begin}
64 <latexrelease>  \if_mode_horizontal: \else:
65 <latexrelease>    \msg_error:nnnn { hooks }{ para-mode }{begin}{horizontal} \fi:
66 <latexrelease>  \__para_handle_indent:
67 <latexrelease>}

```

We also have to add the `\everypar` toks register at the end. In case of rollback this is already allocated and we have to find out the correct number (hope this is correctly done)

```

68 <latexrelease>\cs_set:Npn \__para_tmp:w #1#2#3#4#5 { }
69 <latexrelease>\tl_gput_right:Nx \g__para_standard_everypar_tl {
70 <latexrelease>  \exp_not:N \the
71 <latexrelease>  \exp_not:N \toks
72 <latexrelease>  \exp_after:wN \__para_tmp:w \token_to_meaning:N \everypar
73 <latexrelease>  \c_space_tl
74 <latexrelease>}
75 <latexrelease>\EndIncludeInRelease

```

(End of definition for `\g__para_standard_everypar_tl`.)

`\tex_everypar:D` `\tex_everypar:D` then only has to execute `\g__para_standard_everypar_tl` by default.

```

76 \tex_everypar:D{\g__para_standard_everypar_tl}

```

(End of definition for `\tex_everypar:D`.)

`\everypar` Tokens inserted at the beginning of the paragraph are placed into `\everypar` inside legacy L<sup>A</sup>T<sub>E</sub>X code, e.g., by the list environments or by headings to handle `\clubpenalty`, etc.

Now this isn't any longer the primitive but simply a toks register used in the code above but to legacy L<sup>A</sup>T<sub>E</sub>X code that is transparent.

There is, however, a problem: a handful packages use exactly the same trick and replace the primitive with a token register and call the token register inside the renamed primitive. That is they assume that `\everypar` is the primitive and that it will still be called at the start of the paragraph even if renamed.

But if we have already replaced it by a token register then all they do is to give that token register a new name. Thus our code in `\tex_everypar:D` would call `\everypar` (which is now their token register) and the code that they added ends up in our token register which is then never used at all. A bit mind boggling I guess.

So what we have to do is not to call the token register `\everypar` by its name inside `\tex_everypar:D` but by using its actual register number.

```
77 \newtoks \everypar
```

After we have allocated a new toks register with the name `\everypar` the actual register number is available (briefly) inside `\allocationnumber`. So instead of `\the\everypar` we have to put `\the\toks{allocated number}` at the end of `\tex_everypar:D`.

So what remains doing is to append a few tokens to the token list `\g__para_standard_everypar_tl` which we do now. We use `x` expansion here to get the value of `\allocationnumber` in, all the other tokens should not be expanded at this point.

One important point here is to terminate the register allocation number with a real space. This space will get swallowed up when the number is read. Anything else, such as `\scan_stop:` would remain in the input and that would mean that it would interfere with `\everypar` code that attempts to scan ahead to see how the paragraph text starts.

```
78 \tl_gput_right:Nx \g__para_standard_everypar_tl {
79   \exp_not:N \the
80   \exp_not:N \toks
81   \the \allocationnumber
82   \c_space_tl
83 }
```

*(End of definition for \everypar.)*

**`\g_para_indent_box`** For managing the indentation we need to provide a public accessible box register

```
84 \box_new:N \g_para_indent_box
```

*(End of definition for \g\_para\_indent\_box. This function is documented on page 418.)*

**`\__para_handle_indent:`** Adding (typesetting) the indent box is straight forward. If it was emptied before it does nothing.

```
85 \cs_new:Npn \__para_handle_indent: {
86   \box_use_drop:N \g_para_indent_box
87 }
```

The declaration `\para_omit_indent:` (or `\OmitIndent`) changes that to do nothing.

```
88 \cs_new:Npn \para_omit_indent: {
89   \box_gclear:N \g_para_indent_box
90 }
```

*(End of definition for \\_\_para\_handle\_indent:.)*

**\IndentBox** The L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> names for the indentation box and for suppressing it for use in the **para/begin** hook.

**\OmitIndent**

```

91 \cs_set_eq:NN \IndentBox \g_para_indent_box
92 \cs_set_eq:NN \OmitIndent \para_omit_indent:

```

(End of definition for **\IndentBox** and **\OmitIndent**. These functions are documented on page 418.)

**\para\_end:** Adding hooks to the end of a paragraph is similar but here we need to alter the command that is used by T<sub>E</sub>X to end horizontal mode and return to vertical mode, i.e., **\par**.

This is a bit more complicated as this command can appear anywhere either explicitly or implicitly added by T<sub>E</sub>X in certain situations:

- when using **\par** in the code or the document
- when using a blank line (which is converted to **\par**)
- when T<sub>E</sub>X finds any commands incompatible with horizontal mode it issues a **\par** and then rereads the command.

Unfortunately, T<sub>E</sub>X has some (these days) unnecessary optimizations: if a **\vbox** ends and T<sub>E</sub>X is still in horizontal mode it simply exercises the paragraph builder instead of issuing a **\par**. It is therefore necessary for L<sup>A</sup>T<sub>E</sub>X to ensure that this case doesn't happen and all boxes internally have a **\par** command at their end.

This **\par** may or may not run the “par primitive” (which is always available as **\tex\_par:D** in expl3); it is permissible to have a changed meaning and it is in fact changed by L<sup>A</sup>T<sub>E</sub>X in various ways at various points inside **latex.ltx**. For this L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> code has the following conventions: **\@@par** and **\endgraf** both refer to the default meaning (in the past this was the initex primitive) while **\par** is the current meaning which maybe does something else.

We are now going to change this default meaning to instead run **\para\_end:**, which ultimately executes the initex primitive but additionally adds our hooks when appropriate. This way the change is again transparent to the legacy L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> code.

In most cases **\para\_end:** should behave exactly like the primitive and we achieve this by simply expanding it to the primitive which is available to us as **\tex\_par:D**. This way we don't have to care about whether T<sub>E</sub>X just does nothing (e.g., if in vertical mode already) or generates an error, etc.

```

93 \cs_new_protected:Npn \para_end: {

```

CCC Maybe needs more explanation. TEMP NOTE: What should happen if in outer hmode with an empty hlist?

The only case we care about is when we are in horizontal mode (i.e., doing typesetting) and not also in inner mode (i.e., making paragraphs and not building an **\hbox**).

```

\bool_lazy_and:nnT
  { \mode_if_horizontal_p: }
  { \bool_not_p:n { \mode_if_inner_p: } }
{ ...

```

Since this is executed for each and every paragraph in a document we try to stay as fast as possible, so we do not use the above construct but two conditionals instead. Using low-level **\if\_mode...** conditions would be even faster but has the danger to conflict with conditionals in the user hooks.

If **\para\_end:** is executed while T<sub>E</sub>X is currently doing a low-level assignment the test for horizontal mode may get executed as part of the assignment. That is normally not an issue but we just found one case where it is:

```
\afterassignment\lst@vskip\@tempskipa \z@ \par
```

If T<sub>E</sub>X is in hmode while that assignment happens then the `\par` is seen in hmode because in the above case the assignment may not be finished (one should have used `\z@skip`) and the `\lst@vskip` will get inserted into the middle of the conditional. The `\lst@vskip` then changes to vmode and you get a surprising error about the `para/end` hook having changed modes even if you don't have any hook code(!): it is the inserted `\lst@vskip` that is actually causing the change of mode. This is what happened when the output routines got started while a `lstlisting` environment (that redefines `\vskip` in this way) was active. This is really faulty coding, but we try to be proactive and guard the conditional so that any scanning is first stopped, thus:

```
94 \scan_stop:
95 \mode_if_horizontal:TF {
96   \mode_if_inner:F {
```

In that case the action of the primitive would be to remove the last glue (but no kerns) from the horizontal list (constructed to form a paragraph) and then to append a penalty of 10000 and the `\parfillskip`; it then passes the whole list to the paragraph builder, which breaks it into lines and T<sub>E</sub>X then returns to vertical mode.

What we want to do is to add this hook code at the end of the horizontal list before any of the above happens. If there was a glue item at the end of the list then it should get removed before the hook code gets added so we have to arrange for this removal.

As in other similar cases, it may be best to add here a `\nobreak` in case the hook itself adds glue and thus creates a non-explicit and unwanted potential breakpoint. On the other hand (as has been argued) the code in the hook should perhaps have the responsibility for adding such a guard penalty in this case. This needs further analysis and decisions (as in emails).

In either case, good documentation of these hooks is essential, covering what the hook may or should provide and all such related considerations concerning the content.

There is not much point in checking if there was really a glue item at the end of the horizontal list, instead we simply try to remove one using `\tex_unskip:D`: if there wasn't one this will do nothing.

```
97 \tex_unskip:D
```

We then execute the public hook (which may add some final typeset material) followed by the kernel hook that we need for adding tagging support. None of this is supposed to change the mode—at the moment we make only a very simple test for this, more devious changes go unnoticed, but too bad as they will then probably backfire badly.

```
98 \hook_use:n{para/end}
99 \@kernel@after@para@end
100 \mode_if_horizontal:TF {
```

The final action (before getting to the point where `\tex_par:D` is called) is to add an extra glue item so that the primitive is prevented from removing intended glue (if there was some). If we don't do this and the horizontal list ends in several glue items we would end up removing two glue items instead of just the last one, which would be wrong. We use glue (rather than a kern) as that will be removed by the primitive.

There is however one other T<sub>E</sub>X optimization that hurts: in a sequence like this `$$ ... $$ \par` (with `\par` being the primitive) T<sub>E</sub>X will be in horizontal mode after the display, ready to receive further paragraph text, but since the `\par` follows immediately there is a “null” paragraph at the end and T<sub>E</sub>X simply throws that away. The space between `$$` and `\par` got already dropped during the display processing so the `\par` is

not removing any space and appending `\parfillskip`, instead it simply goes silently to vmode.

Now if we would have added something (to prevent glue removal) that would look to  $\TeX$  like material after the display and so we would end up with an empty paragraph just containing a penalty and `\parfillskip`.

We therefore check if the current hlist does end in glue (`\tex_lastnodetype:D` has the value 11) and if so we add a zero-length guard skip which will be removed by the following `\tex_par:D`.

```
101         \if_int_compare:w 11 = \tex_lastnodetype:D
102         \tex_hskip:D \c_zero_dim
103         \fi:
```

To run the `para/after` hook we first end the paragraph. This means that the `\tex_par:D` at the very end is unnecessary but executing it there unnecessarily is better than having code that tests for all the different mode possibilities.

```
104         \tex_par:D
105         \hook_use:n{para/after}
106         \@kernel@after@para@after
107     }
```

If we were not horizontal mode (the F case from above) then the earlier hook `para/end` must have been at fault, so we report that.

```
108         { \msg_error:nnnn { hooks }{ para-mode }{end}{horizontal} }
```

Finally close out the nested conditionals.

```
109     }
110 }
```

And then we can use the primitive to truly end the paragraph.

```
111 \tex_par:D
112 }
```

*(End of definition for `\para_end:`. This function is documented on page 417.)*

**`\para_raw_indent:`** The commands `\para_raw_indent:` and `\para_raw_noindent:` are like the primitives `\indent` and `\noindent` except that they can only be used in vertical mode.

**`\para_raw_noindent:`** To avoid issues a paragraph started by them should always be ended by `\para_raw_end:` and not by `\para_end:` or `\par` as the latter will execute hooks which then have no counterpart at the beginning of the paragraph. It is the responsibility of the programmer to make sure that they are properly paired.

**`\para_raw_end:`**

```
113 \cs_new:Npn \para_raw_indent: {
114     \mode_if_vertical:TF
115     {
116         \tex_everypar:D {
117             \box_gset_to_last:N \g_para_indent_box
118             \tex_everypar:D { \g__para_standard_everypar_tl }
119             \__para_handle_indent:
120             \the\everypar }
121     }
122     { \msg_error:nn { latex2e }{ raw-para } }
123 \tex_indent:D
124 }
```

```

125 \cs_new:Npn \para_raw_noindent: {
126   \mode_if_vertical:TF
127   {
128     \tex_everypar:D {
129       \tex_everypar:D { \g__para_standard_everypar_tl }
130       \the\everypar }
131   }
132   { \msg_error:nn { latex2e }{ raw-para } }
133   \tex_noindent:D
134 }
135 \cs_new_eq:NN \para_raw_end: \tex_par:D

```

(End of definition for `\para_raw_indent:`, `\para_raw_noindent:`, and `\para_raw_end:`. These functions are documented on page 418.)

**\RawIndent** The L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> names for starting and ending a paragraph without adding any hooks.  
**\RawNoIndent**  
**\RawParEnd**

```

136 \cs_set_eq:NN \RawIndent \para_raw_indent:
137 \cs_set_eq:NN \RawNoindent \para_raw_noindent:
138 \cs_set_eq:NN \RawParEnd \para_raw_end:

```

(End of definition for `\RawIndent`, `\RawNoIndent`, and `\RawParEnd`. These functions are documented on page 418.)

This ends the `para` module code.

```

139 \@@=

```

**\par** Having the new default definition for `\par` we also have to set it up so that it gets used.  
**\endgraf** This involves three commands: `\par`, `\@@par` (to which L<sup>A</sup>T<sub>E</sub>X resets `\par` occasionally)  
**\@@par** and `\endgraf`, which is another name for the “default” action of `\par`.

```

140 \cs_set_eq:NN \par \para_end:
141 \cs_set_eq:NN \@@par \para_end:
142 \cs_set_eq:NN \endgraf \para_end:

```

(End of definition for `\par`, `\endgraf`, and `\@@par`. These functions are documented on page 417.)

While this is not integrated properly into the format we have to redo the `\everypar` setting from the kernel, otherwise that gets lost (as it happens before that file is loaded).

```

143 \everypar{\@nodocument} %% To get an error if text appears before the \document

```

### 3.2 The error messages

This one is used when we detect that some hook code has changed the mode where it shouldn’t, e.g., by starting or ending a paragraph. The first argument is the hook name second the mode it should have stayed in but didn’t.

```

144 \msg_new:nnnn { hooks } { para-mode }
145 {
146   Illegal-mode~ change~ in~ hook~ 'para/#1'.\\
147   Hook~ code~ did~ not~ remain~ in~ #2~ mode.
148 }
149 {
150   Paragraph~ hooks~ cannot~ change~ the~ TeX~ mode~ without~ causing~
151   endless~ recursion.~ The~ hook~ code~ in~ 'para/#1'~ needs~ to~ stay~
152   in~ #2~ mode,~ but~ it~ didn't.~ Examine~ the~ hook~
153   code~ with~ \iow_char:N \ShowHook~ to~ find~ the~ issue.
154 }

```

And here is one used in the “raw” commands when they are used outside of vertical mode.

```

155 \msg_new:nnnn { latex2e } { raw-para }
156 {
157   Not~ in~ vertical~ mode.
158 }
159 {
160   Starting~ a~ paragraph~ with~ \iow_char:N \\\RawIndent~ or~
161   \iow_char:N \\\RawNoindent \\\
162   (or~ \iow_char:N \\\para_raw_indent:~ or~
163   \iow_char:N \\\para_raw_noindent:~ is~ only~ allowed \\\
164   if~ LaTeX~ is~ in~ vertical~ mode.
165 }

166 %
167 <latexrelease> \IncludeInRelease{0000/00/00}%
168 <latexrelease> {ltpara}{Undo-hooks-for-paragraphs}
169 <latexrelease>
170 <latexrelease> \let \OmitIndent \@undefined
171 <latexrelease> \let \IndentBox \@undefined
172 <latexrelease> \let \RawIndent \@undefined
173 <latexrelease> \let \RawNoindent \@undefined
174 <latexrelease> \let \RawParEnd \@undefined
175 <latexrelease>
176 <latexrelease> \cs_set_eq:NN \par \tex_par:D
177 <latexrelease> \cs_set_eq:NN \@@par \tex_par:D
178 <latexrelease> \cs_set_eq:NN \endgraf \tex_par:D
179 <latexrelease>

```

We also need to clean up the primitive “everypar” as that should no longer execute any code by default. And, of course, make \everypar become the primitive again.

```

180 <latexrelease> \tex_everypar:D {}
181 <latexrelease> \cs_set_eq:NN \everypar \tex_everypar:D
182 <latexrelease>
183 <latexrelease> \EndModuleRelease
184 \ExplSyntaxOff
185 </2ekernel | latexrelease>

```

## File 17

# ltmeta.dtx

### Abstract

This code defines the `\DocumentMetadata` interface.

## 1 Introduction

In the past there was no dedicated location to declare settings concerning a document as a whole. Settings are placed somewhere in the preamble or with the class options or even with some package options. For some settings this can be too late, for example the pdf version can no longer be changed if a package has used code which already opened the PDF.

`\DocumentMetadata` as a new command unifies such settings in one place. It must be used before `\documentclass` but can be issued more than once there.

At the moment most of the code run by `\DocumentMetadata` is external to the format and subject to change. This includes the supported key/values.

For that reason all that happens right now in the format is to look for suitable support files and if found, to redirect the processing to them.

### 1.1 `\DocumentMetadata`

---

<code>\DocumentMetadata</code>	<code>\DocumentMetadata{&lt;key-value list&gt;}</code>
--------------------------------	--

---

The keys defined for `\DocumentMetadata` currently allow to set the PDF version, to set the PDF `/Lang`, to uncompress a PDF, to set the language and to declare a few PDF standards and some color profiles.

`\DocumentMetadata` is also used to activate the new PDF management code and it loads a number of required files for the PDF management code. As this forces the loading of the backend files, a backend which can't be detected automatically like `dvipdfmx`, must be set in the first `\DocumentMetadata` call (if there is more than one).

The full set of keys currently supported is documented in `documentmetadata-support.pdf` for now.

## 2 The Implementation

```
1 <*2ekernel | latexrelease>
```

Not needed yet but ...

```
2 %\ExplSyntaxOn
```

```
3 <latexrelease> \NewModuleRelease{2022/06/01}{ltmeta}
```

```
4 <latexrelease> {Document Metadata handling}
```

We start by making the conditionals testing for the use of `\DocumentMetadata` execute the false branch. Then, inside `\DocumentMetadata`, we change them to select the true branch.

```
5 \let \IfDocumentMetadataTF \@secondoftwo
```

```
6 \let \IfDocumentMetadataT \@gobble
```

```

7 \let \IfDocumentMetadataF \@firstofone
8 \protected\def\DocumentMetadata{%
9   \InputIfFileExists{documentmetadata-support.ltx}%
10  {%

```

Support for \DocumentMetadata is available, so change the conditionals.

```

11     \let \IfDocumentMetadataTF \@firstoftwo
12     \let \IfDocumentMetadataT  \@firstofone
13     \let \IfDocumentMetadataF  \@gobble
14  }%

```

The above file is changing \DocumentMetadata to a suitable definition (or so we hope) so that it can be safely used several times in the preamble.

If the file can't be found we say so and carry on without it.

```

15  {%
16    \latex@error{No support files for
17                \noexpand\DocumentMetadata found}
18    {Is the 'LaTeX-lab' bundle installed?%
19    \MessageBreak
20    Without it, the declaration is ignored.}%

```

No point in trying this more than once if there are several calls in the document.

```

21    \let\DocumentMetadata\@gobble
22  }%
23  \DocumentMetadata
24 }

```

To allow package and class author to support for document links we provide also the new interface commands of the hyperref package for the creation of targets.

```

\MakeLinkTarget
\LinkTargetOn
\LinkTargetOff
\NextLinkTarget
25 <latexrelease> \IncludeInRelease{2024/11/01}%
26 <latexrelease>           {\MakeLinkTarget}{Record target name for tagging support}%
27 \ExplSyntaxOn
28 \int_new:N\g__kernel_target_int
29 \NewDocumentCommand\MakeLinkTarget{sO{}m}{%
30   \ifvmode
31     \special{}}%
32   \else
33     \@savsf\spacefactor
34     \smash{}%
35     \spacefactor\@savsf
36   \fi
37   \IfBooleanTF {#1}
38   {
39     \tl_gset:Ne \@currentHref {#3}
40   }
41   {
42     \int_gincr:N\g__kernel_target_int
43     \tl_gset:Ne \@currentHref {target*.\int_use:N\g__kernel_target_int}
44   }
45   \UseTaggingSocket{recordtarget}
46 }
47 \ExplSyntaxOff
48 <latexrelease> \EndIncludeInRelease
49 <latexrelease> \IncludeInRelease{2022/06/01}%
50 <latexrelease>           {\MakeLinkTarget}{Record target name for tagging support}%

```

```

51 <latexrelease> \NewDocumentCommand\MakeLinkTarget{so{m}}{%
52 <latexrelease> \ifvmode
53 <latexrelease> \special{}%
54 <latexrelease> \else
55 <latexrelease> \@savsf\spacefactor
56 <latexrelease> \smash{}%
57 <latexrelease> \spacefactor\@savsf
58 <latexrelease> \fi}
59 <latexrelease> \EndIncludeInRelease
60 \NewDocumentCommand\LinkTargetOn{}{}
61 \NewDocumentCommand\LinkTargetOff{}{}
62 \NewDocumentCommand\NextLinkTarget{m}{}

```

(End of definition for \MakeLinkTarget and others.)

We do not undo \MakeLinkTarget and friends if we roll back, in case they are used in packages that themselves do not offer rollback. This way a roll forward adds them, but the dummies remain if you roll back and you don't get missing csname errors if they are used.

```

63 <latexrelease> \IncludeInRelease{0000/00/00}{lmeta}%
64 <latexrelease> \Undo Document Metadata handling}
65 <latexrelease>
66 <latexrelease> \let\DocumentMetadata\@undefined
67 <latexrelease>
68 <latexrelease> \EndModuleRelease

```

Again for the future ...

```

69 %\ExplSyntaxOff
70 </2ekernel | latexrelease>

```

Restore module prefix (if any):

```

71 <@@=

```

## File 18

# ltspace.dtx

## 1 Spacing

This section deals with spacing, and line- and page-breaking.

### 1.1 User Commands

`\nopagebreak` [ $\langle i \rangle$ ] :  $\langle i \rangle = 0, \dots, 4$ .  
Default argument = 4. Puts a penalty into the vertical list output as follows:  
0 : penalty = 0  
1 : penalty = `\@lowpenalty`  
2 : penalty = `\@medpenalty`  
3 : penalty = `\@highpenalty`  
4 : penalty = 10000  
`\pagebreak` [ $\langle i \rangle$ ] : same as except negatives of its penalty  
`\linebreak` [ $\langle i \rangle$ ] : analog of the above  
`\nolinebreak` [ $\langle i \rangle$ ] : analog of the above  
`\samepage` : inhibits page breaking most places by setting the following penalties to 10000:  
`\interlinepenalty`  
`\predisplaypenalty`  
`\postdisplaypenalty`  
`\interdisplaylinepenalty`  
`\@beginparpenalty`  
`\@endparpenalty`  
`\@itempenalty`  
`\@secpenalty`  
`\interfootnotelinepenalty`  
`\` : initially defined to be `\newline`  
`\` [ $\langle length \rangle$ ] : initially defined to be `\vspace{\langle length \rangle}\newline`  
Note: `\`\* adds a `\adjust{\penalty 10000}`  
OBSOLETE COMMANDS (which never made it into the manual):  
`\obeycr` : defines `<CR> == \`  
`\restorecr` : restores `<CR>` to its usual meaning.

### 1.2 Chris' comments

There are several aspects of the handling of space in horizontal mode that are inconsistent or do not work well in some cases. These are largely concerned with ignoring the effect of space tokens that would otherwise typeset an inter-word space.

Negating the effect of such space tokens is achieved by two mechanisms:

- `\unskip` is used to remove the glue just added by a space that has already had its effect; it is sometimes invoked after an `\ifdim` test on `\lastskip` (see below);
- `\ignorespaces` is used to ignore space-tokens yet to come.

The test done on `\lastskip` is sometimes for equality with zero and sometimes for being positive. Recall also that the test is only on the natural length of the glue and that no glue cannot be distinguished from glue whose natural length is zero: to summarise, a pretty awful test. It is not clear why these tests are not all the same; I think that they should all be for equality. One place where `\unskip` is often used is just before a `\par` (which itself internally does an `\unskip`) and one bit of code (in `\@item`) even has two `\unskips` before a `\par`. These uses may be fossil code but if they are necessary, maybe `\@killglue` would be even safer.

Such removal of glue by `\unskip` may sometimes have the wrong result, removing not the glue from a space-token but other explicit glue; this is sometimes not what is intended.

A common way to prevent such removal is to add an `\hskip\z@` after the glue that should not be removed. This protects that glue against one `\unskip` with no test but not against more than one. It does work for ‘tested `\unskips`’. This is used by `\hspace*` but not by `\hspace`; this is inconsistent as the star is supposed to prevent removal only at the beginning of a line, not at the end, or in a tabular, etc.

If this reason for removing glue were the only consideration then a tested-`\unskip` and protection by `\hskip\z@` would suffice but would need to be consistently implemented.

However, the class of invisibles, commands and environments tries to be even cleverer: one of these tries to leave only one inter-word space whenever there is one before it and one after it; and it does this quite well.

But problems can arise when there is not a space-token on both sides of it; in particular, when an invisible appears at the beginning or end of a piece of text the method still leaves one space token whereas usually in these cases it should leave none.

Also, the current rules do not work well when more than one such command appears consecutively, separated by space-tokens; it leaves glue between every other invisible.

There is also a question about what these commands should do when they occur next to spaces that do not come from space tokens but, for example, from `\hspace`. Should they still produce ‘just one space’? If so, which one? It is good to note that the manual is sufficiently cautious about invisibles that we are not obliged to make anything work.

Another interesting side-road to explore is whether the space-tokens either side of an `\hspace{...}` should be ignored.

One alternative to the current algorithm that is often suggested is that all glue around the invisible should be consolidated into a space after it (usually without stating how much glue should be put there). The command `\nolinebreak` is implemented this way (and `\linebreak` should also be). This does not work correctly for the following common case:

```
... some text
\index{some-word}
some-word and more text.
```

This is optimal coding since it is normal to index a word that gets split across a page-break on its starting page. This would, on the other hand, fix another common (and documented) failure of the current system: when the invisible is the last thing in a paragraph the space before it is not removed and, worse, it is also hidden from the paragraph-ending mechanism so that an ‘empty’ line can be created at the end of the paragraph.

Another deficiency (I think) of the current system is that the following is treated as having the `\index` command between the paragraphs, which is probably not what the author intended (since there is no empty line after it).

```
\index{beginnings}
Beginnings of paragraphs ...
```

I know of no algorithm that will handle satisfactorily even all the most common cases; note that it could be that the best algorithm may be different for different invisibles since, for example, the common uses and expected behaviour of `\index`, `\marginpar`, `\linebreak`, `\pagebreak` and `\vspace` are somewhat different. [For example, is `\vspace` ever used in the middle of a paragraph?]

One method that can (and is) used to make invisible commands produce no space when used at the beginning of text is to put in some glue that is nearly enough the same as no glue or glue of zero length in all respects except for the precise test for not being exactly equal to zero; examples of such glue are `\hskip 1sp` and, possibly better but more complex, `\hskip -1sp \hskip 1sp`. However, this only works when it is known that user-supplied text is about to start.

Some similar concerns apply to the handling of space and penalties in vertical mode; there is an extra hurdle here as `\unskip` does not work on the main vertical list. The complexity of the tests done by `\addvspace` have never been explained.

The implementation of space hacks etc for vertical mode is another major area that needs further attention; my earlier experiments did not produce much improvement over the current unsatisfactory situation.

One particular problem is what happens when the following very natural coding is used (part of the problem here is that this looks like an hmode problem, but it is not):

```
... end of text.

\begin{enumerate}
  \item \label{item:xxx} Item text.
\end{enumerate}
```

### 1.3 Some immediate actions

- Fix bug in `\linebreak`.
- Fix bug in `\\*`.
- Reimplement `\\`, etc, removing extra `\adjusts` and getting better error trapping (this seems to involve a lot more tokens).
- Investigate whether `\\`, etc need to be errors in vmode; I think that they could be noops (maybe with a warning).
- Make all(?) `\unskips` include test for zero skip (rather than other tests or no test).
- Consider replacing `\hskip 1sp` by something better (here called an ‘infinitesimal’ skip).
- Look at all `\hskip\z@` (or similar) to see if they should be changed to an ‘infinitesimal’ skip.

- Resolve the inconsistency between `\hspace` and `\hspace*`.
- Remove unnecessary `\unskips`.
- Investigate and rationalise the ‘newline’ code.
- Find better algorithms for all sorts of things or, easier(?), fix T<sub>E</sub>X itself.

## 1.4 The code

```

1  <*2ekernel>
2  \message{spacing,}
3  </2ekernel>
4  <*2ekernel | latexrelease>
5  <latexrelease>\IncludeInRelease{2019/10/01}%
6  <latexrelease>                {\pagebreak}{Make commands robust}%

\pagebreak
\nopagebreak
7  \DeclareRobustCommand\pagebreak{\@testopt{\@no@pgbk-}4}
8  \DeclareRobustCommand\nopagebreak{\@testopt{\@no@pgbk4}

(End of definition for \pagebreak and \nopagebreak.)

\linebreak
\nolinebreak
9  \DeclareRobustCommand\linebreak{\@testopt{\@no@lnbk-}4}
10 \DeclareRobustCommand\nolinebreak{\@testopt{\@no@lnbk4}

(End of definition for \linebreak and \nolinebreak.)

\samepage
11 \DeclareRobustCommand\samepage{\interlinepenalty\@M
12   \predisplaypenalty\@M
13   \postdisplaypenalty\@M
14   \interdisplaylinepenalty\@M
15   \@beginparpenalty\@M
16   \@endparpenalty\@M
17   \@itempenalty\@M
18   \@secpenalty\@M
19   \interfootnotelinepenalty\@M}

(End of definition for \samepage.)

20 </2ekernel | latexrelease>
21 <latexrelease>\EndIncludeInRelease
22 <latexrelease>\IncludeInRelease{0000/00/00}%
23 <latexrelease>                {\pagebreak}{Make commands robust}%
24 <latexrelease>
25 <latexrelease>\kernel@make@fragile\pagebreak
26 <latexrelease>\kernel@make@fragile\nopagebreak
27 <latexrelease>\kernel@make@fragile\linebreak
28 <latexrelease>\kernel@make@fragile\nolinebreak
29 <latexrelease>\kernel@make@fragile\samepage
30 <latexrelease>
31 <latexrelease>\EndIncludeInRelease
32 <*2ekernel>

```

`\@no@pgbk`

```
33 \def\@no@pgbk #1[#2]{%
34   \ifvmode
35     \penalty #1\@getpen{#2}%
36   \else
37     \@bsphack
38     \vadjust{\penalty #1\@getpen{#2}}%
39     \@esphack
40   \fi}
```

*(End of definition for \@no@pgbk.)*

`\@no@lnbk`

```
41 \def\@no@lnbk #1[#2]{%
42   \ifvmode
43     \@nolnerr
44   \else
45     \@tempskipa\lastskip
46     \unskip
47     \penalty #1\@getpen{#2}%
48     \ifdim\@tempskipa>\z@
49       \hskip\@tempskipa
50       \ignorespaces
51     \fi
52   \fi}
```

*(End of definition for \@no@lnbk.)*

`\@` The purpose of the new code is to fix a few bugs; however, it also attempts to optimize the following, in order of priority:

1. efficient execution of plain `\@`;
2. efficient execution of `\@[...]`;
3. memory use;
4. name-space use.

The changes should make no difference to the typeset output. It appears to be safe to use `\reserved@e` and `\reserved@f` here (other reserved macros are somewhat disastrous).

These changes made `\newline` even less robust than it had been, so now it is explicitly robust, like `\@`.

The internal definition of the ‘normal’ definition of `\@`.

`\@normalcr`

```
53 </2ekernel>
54 <*2ekernel | latexrelease>
55 <latexrelease> \IncludeInRelease{2020/02/02}%
56 <latexrelease>           {\@normalcr}{Make robust}%
57 \protected\def\@normalcr{%
58   \let \reserved@e \relax
59   \let \reserved@f \relax
60   \@ifstar{\let \reserved@e \vadjust \let \reserved@f \nobreak
61             \@xnewline}%
62   \@xnewline}
```

```

63 \let\\@normalcr
64 </2ekernel | latexrelease>
65 <latexrelease>\EndIncludeInRelease
66 <latexrelease>\IncludeInRelease{0000/00/00}%
67 <latexrelease>          {\@normalcr}{Make robust}%
68 <latexrelease>
69 <latexrelease>\DeclareRobustCommand\\{%
70 <latexrelease>  \let \reserved@e \relax
71 <latexrelease>  \let \reserved@f \relax
72 <latexrelease>  \@ifstar{\let \reserved@e \vadjust \let \reserved@f \nobreak
73 <latexrelease>          \@xnewline}%
74 <latexrelease>  \@xnewline}
75 <latexrelease>\expandafter\let\expandafter\@normalcr
76 <latexrelease>  \csname\expandafter\@gobble\string\\ \endcsname
77 <latexrelease>
78 <latexrelease>\EndIncludeInRelease
79 <*2ekernel>

```

*(End of definition for \\ and \@normalcr.)*

**\@vspace@calcify** Helper command to produce a \vskip that is first run through \setlength. This way the calc package can operate on the argument value.

```

80 </2ekernel>
81 <*2ekernel | latexrelease>
82 <latexrelease>\IncludeInRelease{2020/10/01}%
83 <latexrelease>          {\@vspace@calcify}{Add calc support}%
84 \def\@vspace@calcify#1{\setlength\sp@ce@skip{#1}\vskip\sp@ce@skip}
85 </2ekernel | latexrelease>
86 <latexrelease>\EndIncludeInRelease
87 <latexrelease>\IncludeInRelease{0000/00/00}%
88 <latexrelease>          {\@vspace@calcify}{Add calc support}%
89 <latexrelease>
90 <latexrelease>\let\@vspace@calcify\@undefined
91 <latexrelease>\EndIncludeInRelease
92 <*2ekernel>

```

*(End of definition for \@vspace@calcify.)*

**\newline** A simple form of the ‘normal’ definition of \\.

```

93 \DeclareRobustCommand\newline{\@normalcr\relax}

```

*(End of definition for \newline.)*

**\@xnewline**

```

94 \def\@xnewline{\@ifnextchar[% ] bracket matching
95               \@newline
96               {\@gnewline\relax}}

```

*(End of definition for \@xnewline.)*

**\@newline**

```

97 </2ekernel>
98 <*2ekernel | latexrelease>
99 <latexrelease>\IncludeInRelease{2020/10/01}%

```

```

100 <latexrelease>                {\@newline}{\newline calc support}%
101 \def\@newline[#1]{\let \reserved@e \vadjust
102                 \gnewline {\@vspace@calcify{#1}}}
103 </2ekernel | latexrelease>
104 <latexrelease>\EndIncludeInRelease

105 <latexrelease>\IncludeInRelease{0000/00/00}%
106 <latexrelease>                {\@newline}{\newline calc support}%
107 <latexrelease>
108 <latexrelease>\def\@newline[#1]{\let \reserved@e \vadjust
109 <latexrelease>                \gnewline {\vskip #1}}
110 <latexrelease>\EndIncludeInRelease
111 <*2ekernel>

```

*(End of definition for \@newline.)*

**\@gnewline** The `\nobreak` added to prevent null lines when `\@` ends an overfull line. Change made 24 May 89 as suggested by Frank Mittelbach and Rainer Schöpf

```

112 \def\@gnewline #1{%
113     \ifvmode
114         \@nolnerr
115     \else
116         \unskip \reserved@e {\reserved@f#1}\nobreak \hfil \break
117     \fi}

```

*(End of definition for \@gnewline.)*

**\@getpen**

```

118 \def\@getpen#1{\ifcase #1 \z@ \or \@lowpenalty\or
119                 \@medpenalty \or \@highpenalty
120                 \else \@M \fi}

```

*(End of definition for \@getpen.)*

**\if@nobreak** Switch used to avoid page breaks caused by `\label` after a section heading, etc. It should be **GLOBALLY** set true after the `\nobreak` and **globally** set false by the next invocation of `\everypar`.

Commands that reset `\everypar` should globally set it false if appropriate.

```

121 \def\@nobreakfalse{\global\let\if@nobreak\iffalse}
122 \def\@nobreaktrue {\global\let\if@nobreak\iftrue}
123 \@nobreakfalse

```

*(End of definition for \if@nobreak.)*

**\@savsk** Registers used to save the space factor and last skip.

```

\@savsf
124 \newdimen\@savsk
125 \newcount\@savsf

```

*(End of definition for \@savsk and \@savsf.)*

`\@bsphack` `\@bsphack` and `\@esphack` used by macros such as `\index` and `\begin{@float} ... \end{@float}` that want to be invisible — i.e., not leave any extra space when used in the middle of text. Such a macro should begin with `\@bsphack` and end with `\@esphack`. The macro in question should not create any text, nor change the mode.

Before giving the current definition we give an extended definition that is currently not used (because it doesn't work as advertised:-)

These are generalised hacks which attempt to do sensible things when 'invisible commands' appear in vmode too.

They need to cope with space in both hmode (plus spacefactor) and vmode, and also cope with breaks etc. In vmode this means ensuring that any following `\addvspace`, etc sees the correct glue in `\lastskip`.

In fact, these improved versions should be used for other cases of 'whatsits, thingies etc' which should be invisible. They are only for commands, not environments (see notes on `\@Esphack`).

BTW, anyone know why the standard hacks are surrounded by `\ifmmode\else` rather than simply `\ifhmode`?

And are there any cases where saving the spacefactor is essential? I have some extensions where it is, but it does not appear to be so in the standard uses.

```
def \@bsphack{%
  \relax \ifvmode
    \@savsk \lastskip
    \ifdim \lastskip=\z@
    \else
      \vskip -\lastskip
    \fi
  \else
    \ifhmode
      \@savsk \lastskip
      \@savsf \spacefactor
    \fi
  \fi
}
```

I think that, in vmode, it is the safest to put in a `\nobreak` immediately after such things since writes, inserts etc followed by glue give valid breakpoints and, in general, it is possible to create breaks but impossible to destroy them.

```
def \@esphack{%
  \relax \ifvmode
    \nobreak
    \ifdim \@savsk=\z@
    \else
      \vskip \@savsk
    \fi
  \else
    \ifhmode
      \spacefactor \@savsf
      \ifdim \@savsk>\z@
        \ignorespaces
      \fi
    \fi
  \fi
}
```

```

\fi
\fi

```

For the moment we are going to ignore the vertical versions until they are correct.

```

126 \def\@bsphack{%
127   \relax
128   \ifhmode
129     \@savsk\lastskip
130     \@savsf\spacefactor
131   \fi}

```

(End of definition for \@bsphack.)

**\@esphack** Companion to \@bsphack. If this command is not properly paired with \@bsphack one might end up with a low-level T<sub>E</sub>X error: “BAD spacefactor”. One possible cause is calling \@bsphack in vertical mode, then doing something that gets you (sometimes) into horizontal mode and finally calling \@esphack. Even if no error is generated that is wrong, because \@esphack will then use the saved values for \@savsk and \@savsf from some earlier invocation of \@bsphack which will have nothing to do with the current situation.

```

132 </2ekernel>
133 <latexrelease>\IncludeInRelease{2018/10/10}%
134 <latexrelease>          {\@esphack}{hyphenation and nobreak after space hack}%
135 <*2ekernel | latexrelease>
136 \def\@esphack{%
137   \relax
138   \ifhmode
139     \spacefactor\@savsf
140     \ifdim\@savsk>\z@
141       \ifdim\lastskip=\z@
142         \nobreak \hskip\z@skip
143       \fi
144       \ignorespaces
145     \fi
146   \else
147     \ifvmode
148       \if@nobreak\nobreak\else\if@noskipsec\nobreak\fi\fi
149     \fi
150   \fi}%
151 </2ekernel | latexrelease>
152 <latexrelease>\EndIncludeInRelease
153 <latexrelease>\IncludeInRelease{2015/10/01}%
154 <latexrelease>          {\@esphack}{hyphenation and nobreak after space hack}%
155 <latexrelease>\def\@esphack{%
156 <latexrelease>  \relax
157 <latexrelease>  \ifhmode
158 <latexrelease>    \spacefactor\@savsf
159 <latexrelease>    \ifdim\@savsk>\z@
160 <latexrelease>      \ifdim\lastskip=\z@
161 <latexrelease>        \nobreak \hskip\z@skip
162 <latexrelease>      \fi

```

```

163 <latexrelease> \ignorespaces
164 <latexrelease> \fi
165 <latexrelease> \fi}%
166 <latexrelease>\EndIncludeInRelease
167 <latexrelease>\IncludeInRelease{2015/01/01}%
168 <latexrelease> {\@esphack}{hyphenation and nobreak after space hack}%
169 <latexrelease>\def\@esphack{%
170 <latexrelease> \relax
171 <latexrelease> \ifhmode
172 <latexrelease> \spacefactor\@savsf
173 <latexrelease> \ifdim\@savsk>\z@
174 <latexrelease> \nobreak \hskip\z@skip
175 <latexrelease> \ignorespaces
176 <latexrelease> \fi
177 <latexrelease> \fi}%
178 <latexrelease>\EndIncludeInRelease
179 <latexrelease>\IncludeInRelease{0000/00/00}%
180 <latexrelease> {\@esphack}{hyphenation and nobreak after space hack}%
181 <latexrelease>\def\@esphack{%
182 <latexrelease> \relax
183 <latexrelease> \ifhmode
184 <latexrelease> \spacefactor\@savsf
185 <latexrelease> \ifdim\@savsk>\z@
186 <latexrelease> \ignorespaces
187 <latexrelease> \fi
188 <latexrelease> \fi}%
189 <latexrelease>\EndIncludeInRelease
190 <*2ekernel>

```

(End of definition for \@esphack.)

**\@Esphack** A variant of \@esphack that sets the @ignore switch to true (as \@esphack used to do previously). This is currently used only for floats and similar environments.

```

191 </2ekernel>
192 <latexrelease>\IncludeInRelease{2015/01/01}%
193 <latexrelease> {\@Esphack}{hyphenation after space hack}%
194 <*2ekernel | latexrelease>
195 \def\@Esphack{%
196 \relax
197 \ifhmode
198 \spacefactor\@savsf
199 \ifdim\@savsk>\z@
200 \nobreak \hskip\z@skip
201 \@ignoretrue
202 \ignorespaces
203 \fi
204 \fi}%
205 </2ekernel | latexrelease>
206 <latexrelease>\EndIncludeInRelease
207 <latexrelease>\IncludeInRelease{0000/00/00}%
208 <latexrelease> {\@Esphack}{hyphenation after space hack}%
209 <latexrelease>\def\@Esphack{%
210 <latexrelease> \relax
211 <latexrelease> \ifhmode

```

```

212 <latexrelease> \spacefactor\@savsf
213 <latexrelease> \ifdim\@savsk>\z@
214 <latexrelease> \ignoretrue
215 <latexrelease> \ignorespaces
216 <latexrelease> \fi
217 <latexrelease> \fi}%
218 <latexrelease>\EndIncludeInRelease
219 <*2kernel>

```

(End of definition for \@Esphack.)

**\@vbsphack** Another variant which is useful for invisible things which should not live in vmode (this is how some people feel about marginals).

If it occurs in vmode then it enters hmode and ensures that \@savsk is nonzero so that the \ignorespaces is put in later. It is not used at present.

```

\def \@vbsphack{ %
  \relax \ifvmode
    \leavevmode
    \@savsk 1sp
    \@savsf \spacefactor
  \else
    \ifhmode
      \@savsk \lastskip
      \@savsf \spacefactor
    \fi
  \fi
}

```

(End of definition for \@vbsphack.)

## 1.5 Vertical spacing

L<sup>A</sup>T<sub>E</sub>X supports the plain T<sub>E</sub>X commands \smallskip, \medskip and \bigskip. However, it redefines them using \vspace instead of \vskip.

Extra vertical space is added by the command \addvspace{<skip>}, which adds a vertical skip of <skip> to the document. The sequence \addvspace{<s1>} \addvspace{<s2>} is equivalent to \addvspace{<maximum of s1, s2>}.

\addvspace should be used only in vertical mode, and gives an error if it's not. The \addvspace command does *not* add vertical space if @minipage is true. The minipage environment uses this to inhibit the addition of extra vertical space at the beginning.

Penalties are put into the vertical list with the \addpenalty{<penalty>} command. It works properly when \addpenalty and \addvspace commands are mixed.

The @nobreak switch is set true used when in vertical mode and no page break should occur. (Right now, it is used only by the section heading commands to inhibit page breaking after a heading.)

**\@xaddvskip** Internal macro for \vspace handling the case that space has previously been added.

```

220 \def \@xaddvskip{%
221   \ifdim\lastskip<\@tempskipb
222     \vskip-\lastskip

```

```

223     \vskip\@tempskipb
224   \else
225     \ifdim\@tempskipb<\z@
226       \ifdim\lastskip<\z@
227         \else
228           \advance\@tempskipb\lastskip
229           \vskip-\lastskip
230           \vskip \@tempskipb
231         \fi
232       \fi
233     \fi}

```

(End of definition for \xaddvskip.)

**\addvspace** Add vertical space taking into account space already added, as described above.

```

234 </2ekernel>
235 <*2ekernel | latexrelease>
236 <latexrelease>\IncludeInRelease{2024/11/01}%
237 <latexrelease>          {\addvspace}{drop unnecessary no-item error}%
238 \protected\def\addvspace#1{%

```

When this is encountered in hmode, we check whether we are in an hbox and if so generate a L<sup>A</sup>T<sub>E</sub>X error, as otherwise this would cause a bunch of low-level errors. In unrestricted hmode we simply switch to vmode by issuing a \par.

```

239   \ifhmode \ifinner \@LRmoderr \else \par \fi \fi

240   \if@minipage\else
241     \ifdim \lastskip =\z@
242       \@vspace@calcify{#1}%
243     \else
244       \setlength\@tempskipb{#1}%
245       \@xaddvskip
246     \fi
247   \fi
248 }
249 </2ekernel | latexrelease>
250 <latexrelease>\EndIncludeInRelease

251 <latexrelease>\IncludeInRelease{2020/10/01}%
252 <latexrelease>          {\addvspace}{\addvspace calc support}%
253 <latexrelease>\def\addvspace#1{%
254 <latexrelease>  \ifvmode
255 <latexrelease>    \if@minipage\else
256 <latexrelease>      \ifdim \lastskip =\z@
257 <latexrelease>        \@vspace@calcify{#1}%
258 <latexrelease>      \else
259 <latexrelease>        \setlength\@tempskipb{#1}%
260 <latexrelease>        \@xaddvskip
261 <latexrelease>      \fi
262 <latexrelease>    \fi
263 <latexrelease>  \else
264 <latexrelease>    \@noitemerr
265 <latexrelease>  \fi}
266 <latexrelease>\EndIncludeInRelease

```

```

267 <latexrelease>\IncludeInRelease{0000/00/00}%
268 <latexrelease>          {\addvspace}{\addvspace calc support}%
269 <latexrelease>
270 <latexrelease>\def\addvspace#1{%
271 <latexrelease>  \ifvmode
272 <latexrelease>    \if@minipage\else
273 <latexrelease>      \ifdim \lastskip =\z@
274 <latexrelease>        \vskip #1\relax
275 <latexrelease>      \else
276 <latexrelease>        \@tempskipb#1\relax
277 <latexrelease>        \xaddvskip
278 <latexrelease>      \fi
279 <latexrelease>    \fi
280 <latexrelease>  \else
281 <latexrelease>    \@noitemerr
282 <latexrelease>  \fi}
283 <latexrelease>\EndIncludeInRelease
284 <*2ekernel>

```

(End of definition for \addvspace.)

\addpenalty

```

285 </2ekernel>
286 <latexrelease>\IncludeInRelease{2024/11/01}%
287 <latexrelease>          {\addpenalty}{\addpenalty drop error}%
288 <*2ekernel| latexrelease>
289 \protected\def\addpenalty#1{%

```

See description of \addvspace for documentation of the next line of code.

```

290  \ifhmode \ifinner \@LRmoderr \else \par \fi \fi

```

Fix provided by Donald (though the original fix was not good enough). In 2005 Plamen Tanovski discovered that this fix wasn't good enough either as the \vskip kept getting bigger if several \addpenalty commands followed each other. Donald kindly send a new fix.

```

291  \if@minipage
292  \else
293    \if@nobreak
294    \else
295      \ifdim\lastskip=\z@
296      \penalty#1\relax
297    \else
298      \@tempskipb\lastskip

```

We have to make sure the final \vskip seen by T<sub>E</sub>X is the correct one, namely \@tempskipb. However, we may have to adjust for \prevdepth when placing the penalty; that should not affect the skip we pass on to T<sub>E</sub>X.

```

299    \begingroup
300      \@tempskipa\@tempskipb
301      \advance \@tempskipb
302      \ifdim\prevdepth>\maxdepth\maxdepth\else

```

If `\prevdepth` is -1000pt due to `\nointerlineskip` we better not add it!

```

303         \ifdim \prevdepth = -\@m\p@ \z@ \else \prevdepth \fi
304     \fi
305     \vskip -\@tempskipb
306     \penalty#1%
307     \ifdim \@tempskipa=\@tempskipb

```

Do nothing if the `\prevdepth` check made no adjustment.

```

308     \else

```

Combine the `\prevdepth` adjustment into a single skip.

```

309         \advance\@tempskipb -\@tempskipa
310         \vskip \@tempskipb
311     \fi

```

The final skip is always the specified length.

```

312         \vskip \@tempskipa
313     \endgroup
314 \fi
315 \fi
316 \fi
317 }
318 </2ekernel | latexrelease>
319 <latexrelease>\EndIncludeInRelease
320 <latexrelease>\IncludeInRelease{2015/01/01}%
321 <latexrelease>         {\addpenalty}{\addpenalty}%
322 <latexrelease>\def\addpenalty#1{%
323 <latexrelease> \ifvmode
324 <latexrelease>     \if@minipage
325 <latexrelease>     \else
326 <latexrelease>         \if@nobreak
327 <latexrelease>         \else
328 <latexrelease>             \ifdim\lastskip=\z@
329 <latexrelease>                 \penalty#1\relax
330 <latexrelease>             \else
331 <latexrelease>                 \@tempskipb\lastskip
332 <latexrelease>                 \begingroup
333 <latexrelease>                     \@tempskipa\@tempskipb
334 <latexrelease>                     \advance \@tempskipb
335 <latexrelease>                         \ifdim\prevdepth>\maxdepth\maxdepth\else
336 <latexrelease>                             \ifdim \prevdepth = -\@m\p@ \z@ \else \prevdepth \fi
337 <latexrelease>                         \fi
338 <latexrelease>                     \vskip -\@tempskipb
339 <latexrelease>                     \penalty#1%
340 <latexrelease>                     \ifdim \@tempskipa=\@tempskipb
341 <latexrelease>                     \else
342 <latexrelease>                         \advance\@tempskipb -\@tempskipa
343 <latexrelease>                         \vskip \@tempskipb
344 <latexrelease>                     \fi
345 <latexrelease>                     \vskip \@tempskipa
346 <latexrelease>                 \endgroup
347 <latexrelease>             \fi
348 <latexrelease>         \fi
349 <latexrelease>     \fi
350 <latexrelease> \else

```

```

351 <latexrelease> \@noitemerr
352 <latexrelease> \fi}%

353 <latexrelease>\EndIncludeInRelease
354 <latexrelease>\IncludeInRelease{0000/00/00}%
355 <latexrelease> \addpenalty{\addpenalty}%
356 <latexrelease>\def\addpenalty#1{%
357 <latexrelease> \ifvmode
358 <latexrelease> \if@minipage
359 <latexrelease> \else
360 <latexrelease> \if@nobreak
361 <latexrelease> \else
362 <latexrelease> \ifdim\lastskip=\z@
363 <latexrelease> \penalty#1\relax
364 <latexrelease> \else
365 <latexrelease> \@tempskipb\lastskip
366 <latexrelease> \vskip -\lastskip
367 <latexrelease> \penalty#1%
368 <latexrelease> \vskip\@tempskipb
369 <latexrelease> \fi
370 <latexrelease> \fi
371 <latexrelease> \fi
372 <latexrelease> \else
373 <latexrelease> \@noitemerr
374 <latexrelease> \fi}%
375 <latexrelease>\EndIncludeInRelease
376 <*2ekernel>

```

(End of definition for \addpenalty.)

\vspace  
\@vspace  
\@vspacer

The new code for these commands depends on the following facts:

- The value of prevdepth is changed only when a box or rule is created and added to a vertical list;
- The value of prevdepth is used only when a box is created and added to a vertical list;
- The value of prevdepth is always local to the building of one vertical list.

```

377 \DeclareRobustCommand\vspace{\@ifstar\@vspacer\@vspace}
378 </2ekernel>
379 <*2ekernel | latexrelease>
380 <latexrelease>\IncludeInRelease{2020/10/01}%
381 <latexrelease> \addpenalty{\addpenalty}%

```

We support calc syntax in the argument and therefore use \setlength.

```

382 \def\@vspace #1{%
383 \ifvmode
384 \@vspace@calcify{#1}%
385 \vskip\z@skip
386 \else
387 \@bsphack
388 \vadjust{\@restorepar
389 \@vspace@calcify{#1}%
390 \vskip\z@skip

```

```

391         }%
392     \@esphack
393 \fi}
394 \def\@vspacer#1{%
395     \ifvmode
396         \dimen@\prevdepth
397         \hrule \@height\z@
398         \nobreak
399         \@vspace@calcify{#1}%
400         \vskip\z@skip
401         \prevdepth\dimen@
402     \else
403         \@bsphack
404         \vadjust{\@restorepar
405             \hrule \@height\z@
406             \nobreak
407             \@vspace@calcify{#1}%
408             \vskip\z@skip}%
409         \@esphack
410     \fi}
411 </2ekernel | latexrelease>
412 <latexrelease>\EndIncludeInRelease
413 <latexrelease>\IncludeInRelease{0000/00/00}%
414 <latexrelease>         {\@vspace}{Support calc in \@vspace}%
415 <latexrelease>
416 <latexrelease>\def\@vspace #1{%
417 <latexrelease>     \ifvmode
418 <latexrelease>         \vskip #1
419 <latexrelease>         \vskip\z@skip
420 <latexrelease>     \else
421 <latexrelease>         \@bsphack
422 <latexrelease>         \vadjust{\@restorepar
423 <latexrelease>             \vskip #1
424 <latexrelease>             \vskip\z@skip
425 <latexrelease>             }%
426 <latexrelease>         \@esphack
427 <latexrelease>     \fi}
428 <latexrelease>\def\@vspacer#1{%
429 <latexrelease>     \ifvmode
430 <latexrelease>         \dimen@\prevdepth
431 <latexrelease>         \hrule \@height\z@
432 <latexrelease>         \nobreak
433 <latexrelease>         \vskip #1
434 <latexrelease>         \vskip\z@skip
435 <latexrelease>         \prevdepth\dimen@
436 <latexrelease>     \else
437 <latexrelease>         \@bsphack
438 <latexrelease>         \vadjust{\@restorepar
439 <latexrelease>             \hrule \@height\z@
440 <latexrelease>             \nobreak
441 <latexrelease>             \vskip #1
442 <latexrelease>             \vskip\z@skip}%
443 <latexrelease>         \@esphack
444 <latexrelease>     \fi}

```

```

445 <latexrelease>\EndIncludeInRelease
446 <*2ekernel>

(End of definition for \vspace, \@vspace, and \@vspacer.)

```

```

\smallskip
\medskip 447 \def\smallskip{\vspace\smallskipamount}
\bigskip 448 \def\medskip{\vspace\medskipamount}
449 \def\bigskip{\vspace\bigskipamount}

(End of definition for \smallskip, \medskip, and \bigskip.)

```

```

\smallskipamount
\medskipamount 450 \newskip\smallskipamount \smallskipamount=3pt plus 1pt minus 1pt
\bigskipamount 451 \newskip\medskipamount \medskipamount =6pt plus 2pt minus 2pt
452 \newskip\bigskipamount \bigskipamount =12pt plus 4pt minus 4pt

(End of definition for \smallskipamount, \medskipamount, and \bigskipamount.)

```

## 1.6 Horizontal space (and breaks)

**\nobreakdashes** This idea is borrowed from the `amsmath` package but here we define a robust command. This command is a low-level command designed for use only before hyphens or dashes (such as `-`, `--`, or `---`).

It could probably be better implemented: it may need its own private token register and temporary command.

Setting the hyphen in a box and then unboxing it means that the normal penalty will not be added after it—and if the penalty is not there a break will not be taken (unless an explicit penalty or glue follows, thus the final `\nobreak`).

Note that even if it is not followed by a `'-`, it still leaves `vmode` and sets the spacefactor; so use it carefully!

```

453 \DeclareRobustCommand{\nobreakdashes}{%
454   \leavevmode
455   \toks@{}%
456   \def\reserved@a##1{\toks@\expandafter{\the\toks@-}%
457     \futurelet\@let@token \reserved@b}%
458   \def\reserved@b  {\ifx\@let@token -%
459     \expandafter\reserved@a
460     \else
461     \setbox\z@ \hbox{\the\toks@\nobreak}%
462     \unhbox\z@
463     \spacefactor\sffcode'\-
464     \fi}%
465   \futurelet\@let@token \reserved@b
466 }

```

(End of definition for `\nobreakdashes`.)

**\nobreakspace** This is a robust command that produces a horizontal space at which, in paragraph-mode, a line-break is not possible. We then define an active `~` to expand to it since this is the documented behaviour of `~`. One reason for introducing this is that some 8-bit input encodings have a slot for such a space and we do not want to use active characters as the L<sup>A</sup>T<sub>E</sub>X internal commands.

The braces in the definition of `~` are needed to ensure that a following space is preserved when reading to/from internal files.

We need to keep `\@xobeysp` as it is widely used; so here it is let to the non-robust command `\nobreakspace` .

The fragile version of `~` needs a brace group after `\nobreakspace` to prevent loss of spaces if it occurs in an expansion context. That's not an issue with the updated `\protected` definition, so we keep the code shorter and avoid that.

```

467 \DeclareRobustCommand{\nobreakspace}{%
468   \leavevmode\nobreak\ }
469 \catcode '\~ =13
470 \</2ekernel>
471 \<latexrelease>\IncludeInRelease{2023/11/01}%
472 \<latexrelease>           {\tilde}{Protected tilde}%
473 \<*2ekernel | latexrelease>
474 \protected\edef~{%
475   \noexpand\ifincsname\noexpand\expandafter\string~%
476   \noexpand\else
477     \noexpand\expandafter\noexpand\nobreakspace
478   \noexpand\fi
479 }
480 \</2ekernel | latexrelease>
481 \<latexrelease>\EndIncludeInRelease
482 \<latexrelease>\IncludeInRelease{0000/00/00}%
483 \<latexrelease>           {\tilde}{Protected tilde}%
484 \<latexrelease>\def~{\nobreakspace{}}
485 \<latexrelease>\EndIncludeInRelease
486 \<*2ekernel>
487 \expandafter\let\expandafter\@xobeysp\csname nobreakspace \endcsname

```

*(End of definition for \nobreakspace and \@xobeysp.)*

`\@xobeytab` Equivalent to the space case with the default settings.

```

488 \</2ekernel>
489 \<latexrelease>\IncludeInRelease{2023/11/01}%
490 \<latexrelease>           {\@xobeytab}{Obeyed tabs}%
491 \<*2ekernel | latexrelease>
492 \let\@xobeytab\@xobeysp
493 \</2ekernel | latexrelease>
494 \<latexrelease>\EndIncludeInRelease
495 \<latexrelease>\IncludeInRelease{0000/00/00}%
496 \<latexrelease>           {\@xobeytab}{Obeyed tabs}%
497 \<latexrelease>\let\@xobeytab\@undefined
498 \<latexrelease>\EndIncludeInRelease
499 \<*2ekernel>

```

*(End of definition for \@xobeytab.)*

`\@` Placed before a `'`, makes it a sentence-ending period. Does the right thing for other punctuation marks as well. Does this by setting `spacefactor` to 1000.

```

500 \</2ekernel>
501 \<latexrelease>\IncludeInRelease{2015/01/01}%
502 \<latexrelease>           {\@}{Space after \@}%
503 \<*2ekernel | latexrelease>

```

```

504 \def\@{\spacefactor\@m{}}%
505 </2ekernel | latexrelease>
506 <latexrelease>\EndIncludeInRelease
507 <latexrelease>\IncludeInRelease{0000/00/00}%
508 <latexrelease>          {\@}{Space after \@}%
509 <latexrelease>\def\@{\spacefactor\@m}%
510 <latexrelease>\EndIncludeInRelease
511 <*2ekernel>

```

(End of definition for \@.)

**\hspace**

```

512 \DeclareRobustCommand\hspace{\@ifstar\@hspacer\@hspace}

```

(End of definition for \hspace.)

**\@hspace**

```

513 </2ekernel>
514 <*2ekernel | latexrelease>
515 <latexrelease>\IncludeInRelease{2020/10/01}%
516 <latexrelease>          {\@hspace}{Support calc with \hspace}%

```

We use a private register to calculate the space (if calc is used). Previously we used a group but that results in \everypar etc. being executed inside the group if the \hspace starts a paragraph. This is a bug fix so we do not provide rollback to the incorrect intermediate version.

```

517 \newskip\sp@ce@skip
518 \def\@hspace#1{\setlength\sp@ce@skip{#1}\hskip\sp@ce@skip}
519 </2ekernel | latexrelease>
520 <latexrelease>\EndIncludeInRelease
521 <latexrelease>\IncludeInRelease{0000/00/00}%
522 <latexrelease>          {\@hspace}{Support calc with \hspace}%
523
524 <latexrelease>
525 <latexrelease>\def\@hspace#1{\hskip #1\relax}
526 <latexrelease>\EndIncludeInRelease
527 <*2ekernel>

```

(End of definition for \@hspace.)

**\@hspacer** Extra \hskip 0pt added 1985/17/12 to guard against a following \unskip \relax added 13 Oct 88 for usual T<sub>E</sub>X lossage replaced both changes by \hskip\z@skip 27 Nov 91

```

528 \def\@hspacer#1{\vrule \width\z@\nobreak
529                \@hspace{#1}\hskip \z@skip}

```

(End of definition for \@hspacer.)

**\fill**

```

530 \newskip\fill
531 \fill = 0pt plus 1fill

```

(End of definition for \fill.)

**\stretch**

```

532 \def\stretch#1{\z@ \@plus #1fill\relax}

```

```

(End of definition for \stretch.)

533 </2ekernel>
534 <*2ekernel | latexrelease>
535 <latexrelease>\IncludeInRelease{2018/12/01}%
536 <latexrelease>{\thinspace}{Start LR-mode}%

\enspace
537 \DeclareRobustCommand\enspace{\leavevmode@ifvmode\kern.5em }

(End of definition for \enspace.)

\leavevmode@ifvmode Leave vmode but only if we are really in vmode, otherwise the expansion is empty (which
is not the case with the default definition).
538 \protected\def\leavevmode@ifvmode{\ifvmode\expandafter\indent\fi}

(End of definition for \leavevmode@ifvmode.)

539 </2ekernel | latexrelease>
540 <latexrelease>\EndIncludeInRelease
541 <latexrelease>\IncludeInRelease{0000/00/00}%
542 <latexrelease>{\thinspace}{Start LR-mode}%
543 <latexrelease>\def\thinspace{\kern.16667em }
544 <latexrelease>\def\negthinspace{\kern-.16667em }
545 <latexrelease>\def\enspace{\kern.5em }
546 <latexrelease>\let\leavevmode@ifvmode\@undefined
547 <latexrelease>\EndIncludeInRelease
548 <*2ekernel>

\enskip
\quad 549 \def\enskip{\hskip.5em\relax}
\qquad 550 \def\quad{\hskip1em\relax}
551 \def\qquad{\hskip2em\relax}

(End of definition for \enskip, \quad, and \qquad.)
For Unicode engines, make the Unicode soft hyphen an active character defined as
\-.
552 \ifx\Umathcode\@undefined\else
553 \catcode "\AD=13
554 \def^^ad{\-}
555 \fi

\obeycr The following definitions will probably get deleted or moved to compatibility mode soon.
\restorecr
556 {\catcode'\^^M=13 \gdef\obeycr{\catcode'\^^M13 \def^^M{\\relax}%
557 \gobblecr}%
558 {\catcode'\^^M=13 \gdef\gobblecr{\@ifnextchar
559 \gobble\ignorespaces}}
560 \gdef\restorecr{\catcode'\^^M5 }}

(End of definition for \obeycr and \restorecr.)

561 </2ekernel>

```

## File 19

# ltlogos.dtx

## 1 Logos

Various logos are defined here.

`\TeX` The  $\TeX$  logo, adjusted so that a full stop after the logo counts as ending a sentence.

```
1 <*/2ekernel>
2 \DeclareRobustCommand\TeX{T\kern-.1667em\lower.5ex\hbox{E}\kern-.125emX\@}
```

*(End of definition for \TeX.)*

`\LaTeX` The  $\LaTeX$  logo.

```
3 \DeclareRobustCommand{\LaTeX}{L\kern-.36em%
4   {\sbox\z@ T%
5     \vbox to\ht\z@{\hbox{\check@mathfonts
6       \fontsize\sf@size\z@
7       \math@fontsfalse\selectfont
8       A}%
9     \vss}%
10  }%
11  \kern-.15em%
12  \TeX}
```

*(End of definition for \LaTeX.)*

`\LaTeXe` The  $\LaTeX_{\epsilon}$  logo as proposed by A-W designers.

```
13 \DeclareRobustCommand{\LaTeXe}{\mbox{\m@th
14   \if b\expandafter\@car\fi@series\@nil\boldmath\fi
15   \LaTeX\kern.15em2$_{\textstyle\varepsilon}$}}
16 </2ekernel>
```

*(End of definition for \LaTeXe.)*

## File 20

# ltfiles.dtx

## 1 File Handling

The following user commands are defined in this part:

<code>\document</code>	<code>(ie \begin{document})</code>
	Reads in the .AUX files and <code>\catcode</code> 's @ to 12.
<code>\nofiles</code>	
	Suppresses all file output by setting <code>\@files</code> false.
<code>\includeonly</code>	<code>{\NAME1, ... ,NAMEn}</code>
	Causes only parts NAME1, ... ,NAMEn to be read by their <code>\include</code> commands. Works by setting <code>partsw</code> true and setting <code>\@partlist</code> to NAME1, ... ,NAMEn.
<code>\include</code>	<code>{\NAME}</code>
	Does an <code>\input</code> NAME unless <code>\@partsw</code> is true and NAME is not in <code>\@partlist</code> . If <code>\@files</code> is true, then it directs .AUX output to NAME.AUX, including a checkpoint at the end.
<code>\input</code>	<code>{\NAME}</code>
	The same as TeX's <code>\input</code> , except it allows optional braces around the file name. In $\text{\LaTeX 2}_{\epsilon}$ , it also avoids the primitive 'missing file' error, if the file can not be found.
<code>\IfFileExists</code>	<code>{\NAME}{\then}{\else}</code>
	If the file exists on the system, execute <i>then</i> otherwise execute <i>else</i> .
<code>\InputIfFileExists</code>	<code>{\NAME}{\then}{\else}</code>
	If the file exists on the system, execute <i>then</i> and input NAME otherwise execute <i>else</i> . <i>Historical <math>\text{\LaTeX 2.09}</math> comments (not necessarily accurate any more):</i>

```
1 <*2kernel>
2 \message{files,}
```

### VARIABLES, SWITCHES AND INTERNAL COMMANDS:

<code>\@mainaux</code>	: Output file number for main .AUX file.
<code>\@partaux</code>	: Output file number for current part's .AUX file.
<code>\@auxout</code>	: Either <code>\@mainout</code> or <code>\@partout</code> , depending on which .AUX file output goes to.
<code>\@input{foo}</code>	: If file foo exists, then <code>\input</code> 's it, otherwise types a warning message.
<code>@files</code>	: Switch – set false if no .AUX, .TOC, .IDX etc files are to be written
<code>@partsw</code>	: Set true by a <code>\includeonly</code> command.
<code>\@partlist</code>	: Set to the argument of the <code>\includeonly</code> command.
<code>\cp@FOO</code>	: The checkpoint for <code>\include</code> 'd file FOO.TEX, written by <code>\@writeckpt</code> at the end of file FOO.AUX

```
\includeonly{FILELIST} ==
BEGIN
```

```

\@partsw := T
\@partlist := FILELIST
END

\include{FILE} ==
BEGIN
\clearpage
if \@filesw = T
then \immediate\write\@mainaux{\string\@input{FILE.AUX}}
fi
if \@partsw = T
then \@tempswa := F
\reserved@a := FILE
for \reserved@a := \@partlist
do if eval(\reserved@a) = eval(\reserved@b)
then \@tempswa := T fi
od
fi

if \@tempswa = T
then \@auxout := \@partaux
if \@filesw = T
then \immediate\openout\@partaux{FILE.AUX}
\immediate\write\@partaux{\relax}
fi
\@input{FILE.TEX}
\clearpage
\@writeckpt{FILE}
if @filesw then \closeout \@partaux fi
\@auxout := \@mainaux
else \cp@FILE
fi
END

\@writeckpt{FILE} ==
BEGIN
if \@filesw = T
\immediate\write on file \@partaux:
\@setckpt{FILE}{
%% }
for \reserved@a := \cl@ckpt
do \immediate\write on file \@partaux:
\global\string\setcounter
{eval(\reserved@a)}{eval(\c@eval(\reserved@a))}
od
%% {
\immediate\write on file \@partaux: }
fi
END

\@setckpt{FILE}{LIST} ==
BEGIN

```

```

G \cp@FILE := LIST
END

INITIALIZATION
\@tempswa := T

End of historical LATEX 2.09 comments.

\@mainaux
\@partaux 3 \newwrite\@mainaux
4 \newwrite\@partaux

(End of definition for \@mainaux and \@partaux.)

\if@files
\if@partsw 5 \newif\if@files \@filestrue
6 \newif\if@partsw \@partswfalse

(End of definition for \if@files and \if@partsw.)

\clubpenalty This stores the current normal (non-infinite) value of \clubpenalty; it should therefore
be reset whenever the normal value is changed (as in the bibliography in the standard
styles).
7 \newcount\clubpenalty
8 \clubpenalty \clubpenalty

(End of definition for \clubpenalty.)

\document
9 \</2kernel>
10 \<latexrelease>\IncludeInRelease{2020/10/01}%
11 \<latexrelease> {\document}{Added hook to load l3backend code}%
12 \<*2kernel | latexrelease>
13 \def\document{%
We do cancel the grouping as part of the \begin handling (this is now done inside
\begin instead) so that the env/<env>/begin hook is not hidden inside \begingroup
... \endgroup.
14 % \endgroup
15 \UseOneTimeHook{begindocument/before}%
16 \kernel@after@begindocument@before
Added hook to load l3backend code:
17 \expl@sys@load@backend@@
18 \ifx\@unusedoptionlist\@empty\else
19 \latex@warning@no@line{Unused global option(s):^^J%
20 \spaces[\@unusedoptionlist]}%
21 \fi
22 \@colht\textheight
23 \@colroom\textheight \vsize\textheight
24 \columnwidth\textwidth
25 \clubpenalty\clubpenalty
26 \if@twocolumn
27 \advance\columnwidth -\columnsep

```

```

28     \divide\columnwidth\tw@ \hsize\columnwidth \@firstcolumntrue
29 \fi
30 \hsize\columnwidth \linewidth\hsize
31 \begingroup\@floatplacement\@dblfloatplacement
32     \makeatletter\let\@writefile\@gobbletwo
33
34     \global \let \@multiplelabels \relax
35     \input{\jobname.aux}%
36 \endgroup
37 \if@files
38     \immediate\openout\@mainaux\jobname.aux
39     \immediate\write\@mainaux{\relax}%
40 \fi

```

Dateline 1991/03/26: FMi added `\process@table` to support NFSS; This will also work with old lfonts if no other style defines `\process@table`. The following line forces the initialization of the math fonts.

```

40 \process@table
41 \let\glb@currsize\@empty % Force math initialization.
42
43 \normalsize
44 \everypar{}%

```

So that punctuation in headings is not disturbed by verbatim or other local changes to the space factor codes, save the document default here. This will be locally reset by the output routine. For special cases a class may want to define `\normalsfcodes` directly, in case that definition will be used. (This is an old bug, problem existed in L<sup>A</sup>T<sub>E</sub>X2.0x and plain T<sub>E</sub>X.)

```

44 \ifx\normalsfcodes\@empty
45     \ifnum\sfcode'\.=\@m
46         \let\normalsfcodes\frenchspacing
47     \else
48         \let\normalsfcodes\nonfrenchspacing
49 \fi
50 \fi

```

For similar reasons also save the default language, this will be reset locally in the output routine. In particular it allows hyphenation in the page head even if the page break happens in verbatim. If this has already been set by a package, set to the value of `\language` at this point.

```

51 \ifx\document@default@language\m@ne
52     \chardef\document@default@language\language
53 \fi

```

Way back in 1991 (08/26) FMi & RmS set the `@noskipsec` switch to true in the preamble and to false here. This was done to trap lists and related text in the preamble but it does not catch everything; hence Change 1.1g was introduced.

```

54 \noskipsecfalse
55
56 \let \@refundefined \relax

```

Just before disabling the preamble commands we execute the begin document hook which contains any code contributed by `\AtBeginDocument`. Also disable the gathering of the file list, if no `\listfiles` has been issued. `\AtBeginDocument` is redefined at this point so that and such commands that get into the hook do not chase their tail...

```

56 \@kernel@before@begindocument
57 \UseOneTimeHook{begindocument}%
58 \@kernel@after@begindocument

```

Most of the following assignments will be done globally in case the user adds something like `\begin{multicols}` to the document hook, i.e. starts are group in `\begin{document}`.

Since a value of exactly 0pt for `\topskip` causes `\twocolumn[]` to misbehave, we add this check, hoping that it will not cause any problems elsewhere.

```

59 \ifdim\topskip<1sp\global\topskip 1sp\relax\fi
60 \global\@maxdepth\maxdepth
61 \global\let\@begindocumenthook\@undefined
62 \ifx\@listfiles\@undefined
63   \global\let\@filelist\relax
64   \global\let\@addtofilelist\@gobble
65 \fi

```

At the very end we disable all preamble commands. This has to happen after the begin document hooks was executed so that this hook can still use such commands.

```

66 \gdef\do##1{\global\let ##1\@notprerr}%
67 \@preamblecmds

```

The next line saves tokens and also allows `\@nodocument` to be used directly to trap preamble errors.

```

68 \global\let \@nodocument \relax

```

The next line is a pure safety measure in case a do list is ever expanded at the wrong place. In addition it will save a few tokens to get rid of the above definition.

```

69 \global\let\do\noexpand
70 \UseOneTimeHook{begindocument/end}%

```

Use of the hook might mean that we are already in horizontal mode, so ignore the space after `\begin{document}`.

```

71 \ignorespaces}

```

Provide a global definition for `\do` as well, so that it is already defined in the preamble and not late as `\begin{document}` overwriting some definition given by the unsuspecting user in the preamble.

```

72 \let\do\noexpand

```

The `begindocument` hook already existed in the kernel since 1994 under the name `\atbegindocumenthook` the additional ones are originally from the `etoolbox` package under the names `\@endpreamblehook` `\afterpreamble`.

```

73 \NewHook{begindocument}
74 \NewHook{begindocument/before}
75 \NewHook{begindocument/end}

```

Above we used two kernel only hooks to be run after the public `begindocument/before` and after `begindocument` hooks.

```

\@kernel@after@begindocument@before
\@kernel@before@begindocument
\@kernel@after@begindocument

```

In `\@kernel@after@begindocument@before` we already place one action: drop the fast execution code for the `env/document/begin` hook. That hook marks the end of the preamble and should therefore only be run once. In a normal document that is anyway the case (so the code would just sit there taking up space afterwards, which these days is rather harmless), however, in more complicated scenarios where several full documents are combined to a single document it might get applied several times with harmful effects.

We therefore explicitly drop it at this point. the coding is somewhat obscure due to the name of the macro which requires constructing.

```

76 \edef \@kernel@after@begindocument@before {%
77   \let\expandafter\noexpand\csname
78     __hook env/document/begin\endcsname
79   \noexpand\@empty}

```

These internal hooks are already declared earlier (in `ltxpl`) so that other modules could write to them.

```

80 %\let \@kernel@before@begindocument \@empty
81 %\let \@kernel@after@begindocument \@empty

82 </2kernel | latexrelease>
83 <latexrelease>\EndIncludeInRelease

84 <latexrelease>\IncludeInRelease{2017/04/15}%
85 <latexrelease> {\document}{Save language for hyphenation}%
86 <latexrelease>
87 <latexrelease>\def\document{\endgroup
88 <latexrelease>   \ifx\@unusedoptionlist\@empty\else
89 <latexrelease>     \@latex@warning@no@line{Unused global option(s):^^J%
90 <latexrelease>       \@spaces[\@unusedoptionlist]}}%
91 <latexrelease> \fi
92 <latexrelease> \@colht\textheight
93 <latexrelease> \@colroom\textheight \vsize\textheight
94 <latexrelease> \columnwidth\textwidth
95 <latexrelease> \@clubpenalty\clubpenalty
96 <latexrelease> \if@twocolumn
97 <latexrelease>   \advance\columnwidth -\columnsep
98 <latexrelease>   \divide\columnwidth\tw@ \hsize\columnwidth \@firstcolumntrue
99 <latexrelease> \fi
100 <latexrelease> \hsize\columnwidth \linewidth\hsize
101 <latexrelease> \begingroup\@floatplacement\@dblfloatplacement
102 <latexrelease>   \makeatletter\let\@writefile\@gobbletwo
103 <latexrelease>   \global \let \@multiplelabels \relax
104 <latexrelease>   \@input{\jobname.aux}%
105 <latexrelease> \endgroup
106 <latexrelease> \if@filesw
107 <latexrelease>   \immediate\openout\@mainaux\jobname.aux
108 <latexrelease>   \immediate\write\@mainaux{\relax}%
109 <latexrelease> \fi
110 <latexrelease> \process@table
111 <latexrelease> \let\glb@currsize\@empty % Force math initialization.
112 <latexrelease> \normalsize
113 <latexrelease> \everypar{}%
114 <latexrelease> \ifx\normalsfcodes\@empty
115 <latexrelease>   \ifnum\sfcode'\.=\@m
116 <latexrelease>     \let\normalsfcodes\frenchspacing
117 <latexrelease>   \else
118 <latexrelease>     \let\normalsfcodes\nonfrenchspacing
119 <latexrelease>   \fi
120 <latexrelease> \fi
121 <latexrelease> \ifx\document@default@language@m@ne
122 <latexrelease>   \chardef\document@default@language\language
123 <latexrelease> \fi

```

```

124 <latexrelease> \noskipsecfalse
125 <latexrelease> \let \@refundefined \relax
126 <latexrelease> \let \AtBeginDocument \@firstofone
127 <latexrelease> \@begindocumenthook
128 <latexrelease> \ifdim\topskip<1sp\global\topskip 1sp\relax\fi
129 <latexrelease> \global\@maxdepth\maxdepth
130 <latexrelease> \global\let\@begindocumenthook\@undefined
131 <latexrelease> \ifx\@listfiles\@undefined
132 <latexrelease> \global\let\@filelist\relax
133 <latexrelease> \global\let\@addtofilelist\@gobble
134 <latexrelease> \fi
135 <latexrelease> \gdef\do##1{\global\let ##1\@notprerr}%
136 <latexrelease> \@preamblecmds
137 <latexrelease> \global\let \@nodocument \relax
138 <latexrelease> \global\let\do\noexpand
139 <latexrelease> \ignorespaces}
140 <latexrelease> \EndIncludeInRelease
141 <latexrelease>
142 <latexrelease> \IncludeInRelease{0000/00/00}%
143 <latexrelease> {\document}{Save language for hyphenation}
144 <latexrelease> \def\document{\endgroup
145 <latexrelease> \ifx\@unusedoptionlist\@empty\else
146 <latexrelease> \@latex@warning@no@line{Unused global option(s):^^J%
147 <latexrelease> \@spaces[\@unusedoptionlist]}}%
148 <latexrelease> \fi
149 <latexrelease> \@colht\textheight
150 <latexrelease> \@colroom\textheight \vsize\textheight
151 <latexrelease> \columnwidth\textwidth
152 <latexrelease> \@clubpenalty\clubpenalty
153 <latexrelease> \if@twocolumn
154 <latexrelease> \advance\columnwidth -\columnsep
155 <latexrelease> \divide\columnwidth\tw@ \hsize\columnwidth
156 <latexrelease> \@firstcolumntrue
157 <latexrelease> \fi
158 <latexrelease> \hsize\columnwidth \linewidth\hsize
159 <latexrelease> \begingroup\@floatplacement\@dblfloatplacement
160 <latexrelease> \makeatletter\let\@writefile\@gobbletwo
161 <latexrelease> \global \let \@multiplelabels \relax
162 <latexrelease> \@input{\jobname.aux}%
163 <latexrelease> \endgroup
164 <latexrelease> \if@filesw
165 <latexrelease> \immediate\openout\@mainaux\jobname.aux
166 <latexrelease> \immediate\write\@mainaux{\relax}%
167 <latexrelease> \fi
168 <latexrelease> \process@table
169 <latexrelease> \let\glb@currsz\@empty
170 <latexrelease> \normalsize
171 <latexrelease> \everypar{}%
172 <latexrelease> \ifx\normalsfcodes\@empty
173 <latexrelease> \ifnum\sfcode'\.=\@m
174 <latexrelease> \let\normalsfcodes\frenchspacing
175 <latexrelease> \else
176 <latexrelease> \let\normalsfcodes\nonfrenchspacing
177 <latexrelease> \fi

```

```

178 <latexrelease> \fi
179 <latexrelease> \@noskipsecfalse
180 <latexrelease> \let \@refundefined \relax
181 <latexrelease> \let \@AtBeginDocument \@firstofone
182 <latexrelease> \@begindocumenthook
183 <latexrelease> \ifdim\topskip<1sp\global\topskip 1sp\relax\fi
184 <latexrelease> \global\@maxdepth\maxdepth
185 <latexrelease> \global\let \@begindocumenthook \@undefined
186 <latexrelease> \ifx \@listfiles \@undefined
187 <latexrelease> \global\let \@filelist \relax
188 <latexrelease> \global\let \@addtofilelist \@gobble
189 <latexrelease> \fi
190 <latexrelease> \gdef\do##1{\global\let ##1\@notprerr}%
191 <latexrelease> \@preamblecmds
192 <latexrelease> \global\let \@nodocument \relax
193 <latexrelease> \global\let \do\noexpand
194 <latexrelease> \ignorespaces}
195 <latexrelease> \EndIncludeInRelease
196 <*2ekernel>
197 \@onlypreamble\document

```

*(End of definition for \document and others.)*

**\normalsfcodes** The setting of `\@empty` is just a flag. This command may be defined in a class or package file. If it is still `\@empty` at `\begin{document}` it will be defined to be `\frenchspacing` or `\nonfrenchspacing`, depending on which of those appears to be in effect at that point.

```
198 \let\normalsfcodes\@empty
```

*(End of definition for \normalsfcodes.)*

**\nofiles** Set `\@fileswfalse` which suppresses the places where L<sup>A</sup>T<sub>E</sub>X makes `\immediate` writes. The `\makeindex` and `\makeglossary` are disabled. `\protected@write` is redefined not to write to the file specified, but rather to write a blank line to the log file. This ensures that a *<whatsit>* node is still created, and so spacing is not affected by the `\nofiles` command; to ensure this more generally, the `\if@nobreak` test is needed.

```

199 \def\nofiles{%
200   \@fileswfalse
201   \typeout{No auxiliary output files.^^J}%
202   \long\def\protected@write##1##2##3%
203     {\write\m@ne{}\if@nobreak\ifvmode\nobreak\fi\fi}%
204   \let\makeindex\relax
205   \let\makeglossary\relax}
206 \@onlypreamble\nofiles

```

*(End of definition for \nofiles.)*

**\protected@write** This takes three arguments: an output stream, some initialization code, and some text to write. It then writes this, with appropriate handling of `\protect` and `\thepage`.

```

207 </2ekernel>
208 <*2ekernel | latexrelease>
209 <latexrelease> \IncludeInRelease{2025/06/01}%
210 <latexrelease> \def\protected@write#1#2#3%
211 \long\def \protected@write#1#2#3%

```

```

212 \begingroup
213 \let\thepage\relax
214 #2%
215 \let\protect\@unexpandable@protect
216 \edef\reserved@a{\endgroup\write#1{#3}}%
217 \reserved@a
218 \if@nobreak\ifvmode\nobreak\fi\fi
219 }
220 </2ekernel | latexrelease>
221 <latexrelease>\EndIncludeInRelease
222 <latexrelease>\IncludeInRelease{0000/00/00}%
223 <latexrelease> \protected@write}{Allow for immediate write}%
224 <latexrelease>\long\def \protected@write#1#2#3{%
225 <latexrelease> \begingroup
226 <latexrelease> \let\thepage\relax
227 <latexrelease> #2%
228 <latexrelease> \let\protect\@unexpandable@protect
229 <latexrelease> \edef\reserved@a{\write#1{#3}}%
230 <latexrelease> \reserved@a
231 <latexrelease> \endgroup
232 <latexrelease> \if@nobreak\ifvmode\nobreak\fi\fi
233 <latexrelease>}
234 <latexrelease>\EndIncludeInRelease
235 <*2ekernel>

```

(End of definition for \protected@write.)

```

236 \let\@auxout=\@mainaux

```

`\include` In the definition of `\include`, `\def\reserved@b` changed to `\edef\reserved@b` to be consistent with the `\edef` in `\includeonly`. (Suggested by Rainer Schöpf & Frank Mittelbach. Change made 20 Jul 88.)

Changed definition of `\include` to allow space at end of file name — otherwise, typing `\include{foo }` would cause L<sup>A</sup>T<sub>E</sub>X to overwrite `foo.tex`. Change made 24 May 89, suggested by Rainer Schöpf and Frank Mittelbach

Made `\include` check for being used inside an `\include`'d file, as this will not work and cause surprising results.

```

237 </2ekernel>
238 <*2ekernel | latexrelease>
239 <latexrelease>\IncludeInRelease{2020/10/01}%
240 <latexrelease> \includeonly}{Spaces in file names}%
241 \def\include#1{\relax
242 \ifnum\@auxout=\@partaux
243 \latex@error{\string\include\space cannot be nested}\@eha
244 \else

```

Here the normalization will add `.tex` for all files, (it uses the same normalization as the hooks), so we need to remove that manually. `\@strip@tex@ext` does that.

```

245 \set@curr@file{#1}%
246 \edef\@curr@file{\@strip@tex@ext\@curr@file}%

```

For historical reasons `\@include` expects an argument delimited by a space. This is kept (though unnecessary now) to avoid errors in other packages that use `\@include` directly.

```

247 \expandafter\@include\expandafter{\@curr@file} % deliberate space
248 \fi}

```

Here in `\includeonly` we also need to strip `.tex` after normalization:

```

249 \def\includeonly#1{%
250   \@partswtrue
251   \let\@partlist\@empty
252   \@for\reserved@a:=#1 \do
253     {%
254       \expandafter\set@curr@file\expandafter{\reserved@a}%
255       \ifx\@partlist\@empty
256         \edef\@partlist{\@strip@tex@ext\@curr@file}%
257       \else
258         \edef\@partlist{\@partlist,\@strip@tex@ext\@curr@file}%
259       \fi
260     }%
261   }
262 \@onlypreamble\includeonly

```

(End of definition for `\include` and `\includeonly`.)

`\@strip@tex@ext`  
`\@strip@tex@ext@aux`

These macros take a (`\detokenized` file name and remove any `.tex` extension). Extra care is taken to not remove the string `.tex` from the middle of a file name: it is only removed if it's the very last thing in the file name.

```

263 \def\reserved@a#1{%
264   \def\@strip@tex@ext##1{%
265     \expandafter\@strip@tex@ext@aux
266     ##1\@nil\@nil
267     #1\@nil\relax\@nnil}
268 \def\@strip@tex@ext@aux##1#1\@nil##2\@nnil{%
269   \ifx\relax##2\@empty
270     \expandafter\@cdr\expandafter\@empty\@cdr{ }##1%
271   \else##1\fi}}%
272 \expandafter\reserved@a
273 \expandafter{\detokenize{.tex}}
274 </2ekernel | latexrelease>

```

(End of definition for `\@strip@tex@ext` and `\@strip@tex@ext@aux`.)

```

275 <latexrelease>\EndIncludeInRelease
276 <latexrelease>\IncludeInRelease{2019/10/01}%
277 <latexrelease>          {\includeonly}{Spaces in file names}%
278 <latexrelease>
279 <latexrelease>\def\includeonly#1{%
280 <latexrelease>  \@partswtrue
281 <latexrelease>  \set@curr@file{\zap@space#1 \@empty}%
282 <latexrelease>  \let\@partlist\@curr@file
283 <latexrelease>  }
284 <latexrelease>
285 <latexrelease>\def\include#1{\relax
286 <latexrelease>  \ifnum\@auxout=\@partaux
287 <latexrelease>    \@latex@error{\string\include\space cannot be nested}\@eha
288 <latexrelease>  \else

```

```

289 <latexrelease> \set@curr@file{#1 }%
290 <latexrelease> \expandafter\@include\@curr@file
291 <latexrelease> \fi}
292 <latexrelease>
293 <latexrelease>\let\@strip@tex@ext\@undefined
294 <latexrelease>\let\@strip@tex@ext@aux\@undefined
295 <latexrelease>
296 <latexrelease>\EndIncludeInRelease

297 <latexrelease>\IncludeInRelease{0000/00/00}%
298 <latexrelease> \{\includeonly\}{Spaces in file names}%
299 <latexrelease>\def\includeonly#1{%
300 <latexrelease> \@partswtrue
301 <latexrelease> \edef\@partlist{\zap@space#1 \@empty}}
302 <latexrelease>
303 <latexrelease>\def\include#1{\relax
304 <latexrelease> \ifnum\@auxout=\@partaux
305 <latexrelease> \@latex@error{\string\include\space cannot be nested}\@eha
306 <latexrelease> \else \@include#1 \fi}
307 <latexrelease>
308 <latexrelease>\EndIncludeInRelease
309 <*2ekernel>

```

\@include

```

310 </2ekernel>
311 <*2ekernel | latexrelease>
312 <latexrelease>\IncludeInRelease{2022/06/01}%
313 <latexrelease> \{\@include\}{Spaces in file names and hooks}%

314 \def\@include#1 {%
315 \ifx\@nodocument\relax

316 \clearpage
317 \if@filesw
318 \immediate\write\@mainaux{\string\@input{#1.aux}}%
319 \fi
320 \@tempwattrue
321 \if@partsw
322 \@tempswafalse
323 \edef\reserved@a{\#1}%
324 \@for\reserved@a:=\@partlist\do
325 {\ifx\reserved@a\reserved@b\@tempwattrue\fi}%
326 \fi
327 \if@tempswa
328 \let\@auxout\@partaux
329 \if@filesw
330 \immediate\openout\@partaux "#1.aux"
331 \immediate\write\@partaux{\relax}%
332 \fi

```

Now before going to the hooks we need to set \CurrentFile:

```

333 %-----
334 \@filehook@set@CurrentFile

```

Execute the `before` hooks just after we switched the `.aux` file ...

```

335 \UseHook{include/before}%
336 \UseOneTimeHook{include/#1/before}%
337 %-----
338 \input@{#1.tex}%
339 %-----

```

... then end hooks ...

```

340 \UseOneTimeHook{include/#1/end}%
341 \UseHook{include/end}%
342 %-----
343 \clearpage
344 %-----

```

... and after the `\clearpage` the after hooks followed by another `\clearpage` just in case new material got added (after all we need to be in well defined state after the `\include`).

```

345 \UseOneTimeHook{include/#1/after}%
346 \UseHook{include/after}%
347 \clearpage
348 %-----
349 \@writeckpt{#1}%
350 \if@filesw
351 \immediate\closeout\@partaux
352 \fi
353 \else

```

If the file is not included, reset `\deadcycles`, so that a long list of non-included files does not generate an ‘Output loop’ error.

```

354 \deadcycles\z@
355 \@nameuse{cp@#1}%

```

We also execute a hook in this case, first a general used for every include file that is exclude and then a specific one that contains the name of the include file.

```

356 %-----
357 \UseHook{include/excluded}%
358 \UseOneTimeHook{include/#1/excluded}%
359 %-----
360 \fi
361 \let\@auxout\@mainaux
362 \else
363 \@latex@warning{%
364 \noexpand\include should only be used after \string\begin{document}}%
365 \input@{#1}%
366 \fi}

```

Now declare the non-generic `include` hooks used above:

```

367 \NewHook{include/before}
368 \NewReversedHook{include/end}
369 \NewReversedHook{include/after}
370 \NewHook{include/excluded}
371 \<latexrelease>\EndIncludeInRelease
372 \</2ekernel|latexrelease>

```

```

373 <latexrelease>\IncludeInRelease{2020/10/01}%
374 <latexrelease>          {\@include}{Spaces in file names and hooks}%
375 <latexrelease>\EndIncludeInRelease
376 <latexrelease>\def\@include#1 {%
377 <latexrelease>\ifx\@nodocument\relax
378 <latexrelease>  \clearpage
379 <latexrelease>  \if@filesw
380 <latexrelease>    \immediate\write\@mainaux{\string\@input{#1.aux}}%
381 <latexrelease>  \fi
382 <latexrelease>  \@tempswatrue
383 <latexrelease>  \if@partsw
384 <latexrelease>    \@tempswafalse
385 <latexrelease>    \edef\reserved@b{#1}%
386 <latexrelease>    \@for\reserved@a:=\@partlist\do
387 <latexrelease>      {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
388 <latexrelease>  \fi
389 <latexrelease>  \if@tempswa
390 <latexrelease>    \let\@auxout\@partaux
391 <latexrelease>    \if@filesw
392 <latexrelease>      \immediate\openout\@partaux "#1.aux"
393 <latexrelease>      \immediate\write\@partaux{\relax}%
394 <latexrelease>    \fi
395 <latexrelease>    \@filehook@set@CurrentFile
396 <latexrelease>    \UseHook{include/before}%
397 <latexrelease>    \UseOneTimeHook{include/#1/before}%
398 <latexrelease>    \@input@{#1.tex}%
399 <latexrelease>    \UseOneTimeHook{include/#1/end}%
400 <latexrelease>    \UseHook{include/end}%
401 <latexrelease>    \clearpage
402 <latexrelease>    \UseOneTimeHook{include/#1/after}%
403 <latexrelease>    \UseHook{include/after}%
404 <latexrelease>    \clearpage
405 <latexrelease>    \@writeckpt{#1}%
406 <latexrelease>    \if@filesw
407 <latexrelease>      \immediate\closeout\@partaux
408 <latexrelease>    \fi
409 <latexrelease>  \else
410 <latexrelease>    \deadcycles\z@
411 <latexrelease>    \@nameuse{cp@#1}%
412 <latexrelease>  \fi
413 <latexrelease>  \let\@auxout\@mainaux
414 <latexrelease>\else
415 <latexrelease>\@latex@warning{%
416 <latexrelease>  \noexpand\include should only be used after \string\begin{document}}%
417 <latexrelease>\@input@{#1}%
418 <latexrelease>\fi}
419 <latexrelease>\NewHook{include/before}
420 <latexrelease>\NewReversedHook{include/end}
421 <latexrelease>\NewReversedHook{include/after}
422 <latexrelease>\IncludeInRelease{0000/00/00}%
423 <latexrelease>          {\@include}{Spaces in file names and hooks}%
424 <latexrelease>\def\@include#1 {%
425 <latexrelease>  \clearpage
426 <latexrelease>  \if@filesw

```

```

427 <latexrelease> \immediate\write\@mainaux{\string\@input{#1.aux}}%
428 <latexrelease> \fi
429 <latexrelease> \@tempswatrue
430 <latexrelease> \if@partsw
431 <latexrelease> \@tempswafalse
432 <latexrelease> \edef\reserved@b{#1}%
433 <latexrelease> \@for\reserved@a:=\@partlist\do
434 <latexrelease> {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
435 <latexrelease> \fi
436 <latexrelease> \if@tempswa
437 <latexrelease> \let\@auxout\@partaux
438 <latexrelease> \if@filesw
439 <latexrelease> \immediate\openout\@partaux #1.aux
440 <latexrelease> \immediate\write\@partaux{\relax}%
441 <latexrelease> \fi
442 <latexrelease> \@input@{#1.tex}%
443 <latexrelease> \clearpage
444 <latexrelease> \@writeckpt{#1}%
445 <latexrelease> \if@filesw
446 <latexrelease> \immediate\closeout\@partaux
447 <latexrelease> \fi
448 <latexrelease> \else
449 <latexrelease> \deadcycles\z@
450 <latexrelease> \@nameuse{cp@#1}%
451 <latexrelease> \fi
452 <latexrelease> \let\@auxout\@mainaux}
453 <latexrelease>
454 <latexrelease>\EndIncludeInRelease
455 <*2ekernel>

```

*(End of definition for \@include.)*

**\@writeckpt**

```

456 \def\@writeckpt#1{%
457   \if@filesw
458     \immediate\write\@partaux{\string\@setckpt{#1}\@charlb}%
459     {\let\@elt\@wckptelt \cl@ckpt}%
460     \immediate\write\@partaux{\@charrb}%
461   \fi}

```

*(End of definition for \@writeckpt.)*

**\@wckptelt**

```

462 \def\@wckptelt#1{%
463   \immediate\write\@partaux{%
464     \string\setcounter{#1}{\the\@nameuse{c@#1}}}}

```

*(End of definition for \@wckptelt.)*

**\@setckpt** RmS 93/08/31: introduced \@setckpt

```

465 \def\@setckpt#1{\global\@namedef{cp@#1}}

```

*(End of definition for \@setckpt.)*

`\@charlb` The following defines `\@charlb` and `\@charrb` to be { and }, respectively with `\catcode`  
`\@charrb` 11.

```
466 {\catcode' [=1 \catcode']=2
467 \catcode' {=11 \catcode'}=11
468 \gdef\@charlb[{
469 \gdef\@charrb[]
470 ]% }brace matching
```

*(End of definition for \@charlb and \@charrb.)*

## 1.1 Safe Input Macros

`\@curr@file` File name handling is done by generating a csname from the provided file name (which  
`\set@curr@file` means that UTF-8 octets gets turned into strings as this is what happens if they appear  
in a csname due to the code in `utf8.def`). By setting `\escapechar` to -1 we ensure that  
we don't get a backslash in front. As a result we end up with all characters as catcode  
12 (plus spaces). We then sometimes add quotes around the construct (removing any  
existing inner quotes). Sometimes we only remove the quotes if they have been supplied  
by the user. There is clearly some room for improvement.

A side effect of the new code is that we will see quotes around file name displays  
where there haven't been any before.

For compatibility with existing code using `{abc}.tex` or `{one.two}.png`, an initial  
brace group is discarded before expansion and `\string` is applied. The content of the  
brace group is discarded. This means that a leading space will be lost unless protected  
(by { } or " " or `\space`) but filenames with a space are hopefully rare.

The definition below is from 2019 and only used during kernel bootstrapping, later  
on in `ltfilehook.dtx` it will get overwritten.

```
471 \def\set@curr@file#1{%
472   \begingroup
473   \escapechar\m@ne
474   \xdef\@curr@file{%
475     \expandafter\expandafter\expandafter\unquote@name
476     \expandafter\expandafter\expandafter{%
477       \expandafter\string
478       \csname\@firstofone#1\@empty\endcsname}%
479   \endgroup
480 }
```

*(End of definition for \@curr@file and \set@curr@file.)*

`\quote@name` Quoting spaces  
`\quote@@name`  
`\unquote@name`

<code>a b c</code>	<code>-&gt; "a b c"</code>
<code>"a b c"</code>	<code>-&gt; "a b c"</code>
<code>a" "b" "c</code>	<code>-&gt; "a b c"</code>
	<code>-&gt; ""</code>

```
481 </2ekernel>
482 <*2ekernel | latexrelease>
483 <latexrelease> \IncludeInRelease{2019/10/01}%
484 <latexrelease> { \quote@name } { Quote file names }%
485 \def\quote@name#1{ "\quote@@name#1\@gobble" }
486 \def\quote@@name#1{ #1\quote@@name }
```

and removing quotes ...

```
487 \def\unquote@name#1{\quote@@name#1@gobble"}
(End of definition for \quote@name, \quote@@name, and \unquote@name.)
```

**\IfFileExists**

```
488 \DeclareRobustCommand\IfFileExists[1]{%
489   \set@curr@file{#1}%
490   \expandafter\IfFileExists@\expandafter{\@curr@file}}
(End of definition for \IfFileExists.)
491 </2ekernel | latexrelease>
492 <latexrelease>\EndIncludeInRelease
493 <latexrelease>\IncludeInRelease{0000/00/00}%
494 <latexrelease>           {\quote@name}{Quote file names}%
495 <latexrelease>
496 <latexrelease>\let\quote@name\@undefined
497 <latexrelease>\let\quote@@name\@undefined
498 <latexrelease>\let\unquote@name\@undefined
499 <latexrelease>
500 <latexrelease>\long\def \IfFileExists#1#2#3{%
501 <latexrelease>  \openin\@inputcheck#1 %
502 <latexrelease>  \ifeof\@inputcheck
503 <latexrelease>    \ifx\input@path\@undefined
504 <latexrelease>    \def\reserved@a{#3}%
505 <latexrelease>    \else
506 <latexrelease>    \def\reserved@a{\@iffileonpath{#1}{#2}{#3}}%
507 <latexrelease>    \fi
508 <latexrelease>  \else
509 <latexrelease>    \closein\@inputcheck
510 <latexrelease>    \edef\@filef@und{#1 }%
511 <latexrelease>    \def\reserved@a{#2}%
512 <latexrelease>    \fi
513 <latexrelease>    \reserved@a}
514 <latexrelease>
515 <latexrelease>\EndIncludeInRelease
516 <*2ekernel>
```

**\IfFileExists@** Argument #1 is \@curr@file so catcode 12 string with no quotes.

**\IfFileExists@@** The original definition picked up arguments #2 and #3 in a way that they couldn't contain unbalanced conditionals. A better implementation would have been not to pick up the arguments at all but instead use the usual \@firstoftwo and \@secondoftwo. However, that changes how # is interpreted and so we can't do that nowadays without invalidating a lot of code. Therefore the somewhat curious construction near the end.

Earlier versions used \openin here, but this led to two code paths, one in expl3 and one here. To avoid that, and as the expl3 approach works by expansion, we use that here. As we need the file name to include the path, the actual expl3 function used is not the file existence test!

```
517 </2ekernel>
518 <*2ekernel | latexrelease>
519 <latexrelease>\IncludeInRelease{2023/06/01}%
520 <latexrelease>           {\IfFileExists@}{\IfFileExists}
521 \long\def \IfFileExists@#1#2#3{%
522   \edef\@filef@und{\IfFileExists@@{#1}}%
```

The `expl3` function regards an empty argument as nothing at all, but the  $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X} 2_{\varepsilon}$  convention is that this is equal to the special `.tex` file.

```

523 \ifx\@filef@und\@empty
524 \if\relax\detokenize{#1}\relax
525 \let\reserved@a\@firstoftwo
526 \def\@filef@und{" .tex" }%
527 \else
528 \let\reserved@a\@secondoftwo
529 \fi
530 \else
531 \let\reserved@a\@firstoftwo
532 \edef\@filef@und{"\@filef@und" }%
533 \fi

```

This is just there so that any `#` inside `#2` or `#3` needs doubling (as that was the case in the past).

```

534 \expandafter\def\expandafter\reserved@a
535 \expandafter{\reserved@a{#2}{#3}}%
536 \reserved@a}

```

Pipes are not really files, but at the document level they are supported. To quickly trim of any leading spaces, we use a blank test and `\use:n` rather than `\tl_trim_spaces:n` for speed as we don't care about the end of the input.

```

537 \ExplSyntaxOn
538 \cs_new:Npn \IfFileExists@@ #1
539 {
540   \tl_if_blank:nF {#1}
541   {
542     \tl_if_head_eq_charcode:oNTF { \use:n #1 } |
543     {#1}
544     { \file_full_name:n {#1} }
545   }
546 }
547 \cs_generate_variant:Nn \tl_if_head_eq_charcode:nNTF { o }
548 \ExplSyntaxOff
549 </2ekernel | latexrelease>
550 <latexrelease>\EndIncludeInRelease
551 <latexrelease>\IncludeInRelease{2021/06/01}%
552 <latexrelease>          {\IfFileExists@}{\IfFileExists}
553 <latexrelease>
554 <latexrelease>\long\def \IfFileExists@#1#2#3{%
555 <latexrelease> \openin\@inputcheck"#1" %
556 <latexrelease> \ifeof\@inputcheck
557 <latexrelease> \ifx\input@path\@undefined
558 <latexrelease> \let\reserved@a\@secondoftwo
559 <latexrelease> \else
560 <latexrelease> \def\reserved@a{\@iffileonpath{#1}}%
561 <latexrelease> \fi
562 <latexrelease> \else
563 <latexrelease> \closein\@inputcheck
564 <latexrelease> \edef\@filef@und{"#1" }%
565 <latexrelease> \let\reserved@a\@firstoftwo
566 <latexrelease> \fi
567 <latexrelease> \expandafter\def\expandafter\reserved@a

```

```

568 <latexrelease> \expandafter{\reserved@a{#2}{#3}}%
569 <latexrelease>\reserved@a}
570 <latexrelease>\let\IfFileExists@@\undefined
571 <latexrelease>\EndIncludeInRelease
572 <latexrelease>
573 <latexrelease>\IncludeInRelease{2019/10/01}%
574 <latexrelease> \IfFileExists@{\IfFileExists}
575 <latexrelease>
576 <latexrelease>\long\def \IfFileExists@#1#2#3{%
577 <latexrelease> \openin\@inputcheck"#1" %
578 <latexrelease> \ifeof\@inputcheck
579 <latexrelease> \ifx\input@path\@undefined
580 <latexrelease> \def\reserved@a{#3}%
581 <latexrelease> \else
582 <latexrelease> \def\reserved@a{\@iffileonpath{#1}{#2}{#3}}%
583 <latexrelease> \fi
584 <latexrelease> \else
585 <latexrelease> \closein\@inputcheck
586 <latexrelease> \edef\@filef@und{"#1" }%
587 <latexrelease> \def\reserved@a{#2}%
588 <latexrelease> \fi
589 <latexrelease> \reserved@a}
590 <latexrelease>\EndIncludeInRelease
591 <latexrelease>\IncludeInRelease{0000/00/00}%
592 <latexrelease> \IfFileExists@{\IfFileExists}
593 <latexrelease>
594 <latexrelease>\let\IfFileExists@\@undefined
595 <latexrelease>
596 <latexrelease>
597 <latexrelease>\EndIncludeInRelease
598 <*2ekernel>

```

(End of definition for \IfFileExists@ and \IfFileExists@@.)

**\@iffileonpath** If the file is not found by \openin, and \input@path is defined, look in all the directories specified in \input@path.

```

599 </2ekernel>
600 <*2ekernel | latexrelease>
601 <latexrelease>\IncludeInRelease{2019/10/01}%
602 <latexrelease> \@iffileonpath{\Quote file names}
603 \long\def\@iffileonpath#1{%
604 \let\reserved@a\@secondoftwo
605 \expandafter\@tfor\expandafter\reserved@b\expandafter
606 : \expandafter=\input@path\do{%
607 \openin\@inputcheck\expandafter\quote@name\expandafter{\reserved@b#1} %
608 \ifeof\@inputcheck\else
609 \edef\@filef@und{\expandafter\quote@name\expandafter{\reserved@b#1} }%
610 \let\reserved@a\@firstoftwo%
611 \closein\@inputcheck
612 \@break@tfor
613 \fi}%
614 \reserved@a}

```

(End of definition for \@iffileonpath.)

```

615 </2ekernel | latexrelease>
616 <latexrelease>\EndIncludeInRelease
617 <latexrelease>\IncludeInRelease{0000/00/00}%
618 <latexrelease>          {\quote@name}{Quote file names}
619 <latexrelease>
620 <latexrelease>\long\def\@iffileonpath#1{%
621 <latexrelease>  \let\reserved@a\@secondoftwo
622 <latexrelease>  \expandafter\@tfor\expandafter\reserved@b\expandafter
623 <latexrelease>          :\expandafter=\input@path\do{%
624 <latexrelease>    \openin\@inputcheck\reserved@b#1 %
625 <latexrelease>    \ifeof\@inputcheck\else
626 <latexrelease>    \edef\@filef@und{\reserved@b#1 }%
627 <latexrelease>    \let\reserved@a\@firstoftwo%
628 <latexrelease>    \closein\@inputcheck
629 <latexrelease>    \@break@tfor
630 <latexrelease>    \fi}%
631 <latexrelease>  \reserved@a}
632 <latexrelease>
633 <latexrelease>\EndIncludeInRelease
634 <*2ekernel>

```

**\InputIfFileExists** Now define `\InputIfFileExists` to input #1 if it seems to exist. Immediately prior to the input, #2 is executed. If the file #1 does not exist, execute ‘#3’.

This here is a temporary definition for the kernel. The real one comes somewhat later in the file `ltxfilehook.dtx`.

```

635 \DeclareRobustCommand \InputIfFileExists[2]{%
636   \IfFileExists{#1}%
637   {%
638     \expandafter\@swaptwoargs\expandafter
639     {\@filef@und}{#2\@addtofilelist{#1}\@input}}

```

*(End of definition for \InputIfFileExists.)*

**\@swaptwoargs** Swap two arguments and return them unbraced (like `\@firstoftwo` etc).

```

640 </2ekernel>
641 <*2ekernel | latexrelease>
642 <latexrelease>\IncludeInRelease{2019/10/01}%
643 <latexrelease>  {\@swaptwoargs}{Don't lose the file name}%
644 <long\def\@swaptwoargs#1#2{#2#1}

645 </2ekernel | latexrelease>
646 <latexrelease>\EndIncludeInRelease
647 <latexrelease>\IncludeInRelease{0000/00/00}%
648 <latexrelease>  {\@swaptwoargs}{Don't lose the file name}%
649 <latexrelease>\let\@swaptwoargs\undefined
650 <latexrelease>\EndIncludeInRelease
651 <*2ekernel>

```

*(End of definition for \@swaptwoargs.)*

**\input** Input a file: if the argument is given in braces use safe input macros, otherwise use TeX’s primitive `\input` command (which is called `\@input` in L<sup>A</sup>T<sub>E</sub>X).

```

652 \def\input{\@ifnextchar\bgroup\@input\@input}

```

*(End of definition for \input.)*

`\@input` Define `\@input` (i.e., `\input`) in terms of `\InputIfFileExists`.  
 Changes to `\@input`: adapt to the changes to `\@missingfileerror`.

```

653 </2ekernel>
654 <*2ekernel | latexrelease>
655 <latexrelease> \IncludeInRelease{2020/10/01}%
656 <latexrelease>           {\@input}{Change in file error handling}%
657 \def\@input#1{%
658   \InputIfFileExists{#1}{}%
659   {\filename@parse\@curr@file
660    \edef\reserved@a{\noexpand\@missingfileerror
661     {\filename@area\filename@base}%
662     {\ifx\filename@ext\relax tex\else\filename@ext\fi}}%

```

This line now just sets `\@missingfile@<part>`:

```

663   \reserved@a

```

Now here we have to use it. The file here is guaranteed to exist, because `\@missingfileerror` ensures so, but we have to use `\InputIfFileExists` because it executes the file hooks.

```

664   \edef\reserved@a{\noexpand\@input{%
665    \@missingfile@area\@missingfile@base.\@missingfile@ext}}%
666   \reserved@a}}
667 </2ekernel | latexrelease>
668 <latexrelease> \EndIncludeInRelease
669 <latexrelease> \IncludeInRelease{2019/10/01}%
670 <latexrelease>           {\@input}{Quote file names}%
671 <latexrelease>
672 <latexrelease> \def\@input#1{%
673 <latexrelease>   \InputIfFileExists{#1}{}%
674 <latexrelease>   {\filename@parse\@curr@file
675 <latexrelease>   \edef\reserved@a{\noexpand\@missingfileerror
676 <latexrelease>     {\filename@area\filename@base}%
677 <latexrelease>     {\ifx\filename@ext\relax tex\else\filename@ext\fi}}%
678 <latexrelease>   \reserved@a}}
679 <latexrelease> \EndIncludeInRelease
680 <latexrelease> \IncludeInRelease{0000/00/00}%
681 <latexrelease>           {\@input}{Quote file names}%
682 <latexrelease> \def\@input#1{%
683 <latexrelease>   \InputIfFileExists{#1}{}%
684 <latexrelease>   {\filename@parse{#1}%
685 <latexrelease>   \edef\reserved@a{\noexpand\@missingfileerror
686 <latexrelease>     {\filename@area\filename@base}%
687 <latexrelease>     {\ifx\filename@ext\relax tex\else\filename@ext\fi}}%
688 <latexrelease>   \reserved@a}}
689 <latexrelease> \EndIncludeInRelease
690 <*2ekernel>

```

(End of definition for `\@input`.)

`\@input` Define `\@input` in terms of `\IfFileExists`. So this is a ‘safe input’ command, but the files input are not listed by `\listfiles`.

We don’t want `.aux`, `.toc` files etc be listed by `\listfiles`. However, something like `.bbl` probably should be listed and thus should be implemented not by `\@input`.

```

691 \def\@input#1{%
692   \IfFileExists{#1}{\@input\@filef@und}{\typeout{No file #1.}}

```

(End of definition for \@input.)

**\@input@** Version of \@input that does add the file to \@filelist.

```
693 \def\@input@#1{\InputIfFileExists{#1}{\typeout{No file #1.}}}
```

(End of definition for \@input@.)

**\@missingfileerror** This ‘error’ command avoids T<sub>E</sub>X’s primitive missing file loop.

Missing file error. Prompt for a new filename, offering a default extension.

Changes to \@missingfileerror: rather than trying to input the file by force, now \@missingfileerror just returns three \@missingfile@⟨part⟩ and the caller macro is responsible for doing the right thing with it.

```
694 </2ekernel>
695 <*2ekernel|latexrelease>
696 <latexrelease>\IncludeInRelease{2020/10/01}%
697 <latexrelease>{\@missingfileerror}{Do not load missing file immediately}%
698 \gdef\@missingfileerror#1#2{%
699   \typeout{^^J! LaTeX Error: File ‘#1.#2’ not found.^^J^^J%
700   Type X to quit or <RETURN> to proceed,^^J%
701   or enter new name. (Default extension: #2)^^J}%
702   \message{Enter file name: }%
703   {\endlinechar\m@ne
704   \global\read\m@ne to\@gtempa}%
705   \ifx\@gtempa\@empty
```

If the user answers with ⟨return⟩, fallback to the .tex file (previously it did nothing).

```
706   \let\@missingfile@area\@empty
707   \let\@missingfile@base\@empty
708   \def\@missingfile@ext{tex}%
709   \else
```

Use \batchmode\read-1 to ⟨t1⟩ to end the T<sub>E</sub>X run, same as expl3 does (it was \batchmode\@@end before).

```
710   \def\reserved@b{\batchmode\read-1 to \reserved@a}%
711   \def\reserved@a{x}\ifx\reserved@a\@gtempa\reserved@b\fi
712   \def\reserved@a{X}\ifx\reserved@a\@gtempa\reserved@b\fi
713   \filename@parse\@gtempa
714   \edef\filename@ext{%
715     \ifx\filename@ext\relax#2\else\filename@ext\fi}%
716   \edef\reserved@a{%
```

Only check \IfFileExists (it was \InputIfFileExists).

```
717   \noexpand\IfFileExists
718     {\filename@area\filename@base.\filename@ext}%
```

If the file exists, define \@missingfile@⟨part⟩.

```
719     {\def\noexpand\@missingfile@area{\filename@area}%
720     \def\noexpand\@missingfile@base{\filename@base}%
721     \def\noexpand\@missingfile@ext {\filename@ext}}%
722     {\noexpand\@missingfileerror
723     {\filename@area\filename@base}{\filename@ext}}}%
724   \reserved@a
725   \fi
726 }
727 </2ekernel|latexrelease>
728 <latexrelease>\EndIncludeInRelease
```

```

729 <latexrelease>\IncludeInRelease{0000/00/00}%
730 <latexrelease>      {\@missingfileerror}{Do not load missing file immediately}%
731 <latexrelease>
732 <latexrelease>\gdef\@missingfileerror#1#2{%
733 <latexrelease>      \typeout{^^J! LaTeX Error: File ‘#1.#2’ not found.^^J^^J%
734 <latexrelease>      Type X to quit or <RETURN> to proceed,^^J%
735 <latexrelease>      or enter new name. (Default extension: #2)^^J}%
736 <latexrelease>      \message{Enter file name: }%
737 <latexrelease>      {\endlinechar\m@ne
738 <latexrelease>      \global\read\m@ne to\@gtempa}%
739 <latexrelease>      \ifx\@gtempa\@empty
740 <latexrelease>      \else
741 <latexrelease>          \def\reserved@a{x}\ifx\reserved@a\@gtempa\batchmode\@end\fi
742 <latexrelease>          \def\reserved@a{X}\ifx\reserved@a\@gtempa\batchmode\@end\fi
743 <latexrelease>          \filename@parse\@gtempa
744 <latexrelease>          \edef\filename@ext{%
745 <latexrelease>              \ifx\filename@ext\relax#2\else\filename@ext\fi}%
746 <latexrelease>          \edef\reserved@a{%
747 <latexrelease>              \noexpand\InputIfFileExists
748 <latexrelease>              {\filename@area\filename@base.\filename@ext}%
749 <latexrelease>              {}%
750 <latexrelease>              {\noexpand\@missingfileerror
751 <latexrelease>                  {\filename@area\filename@base}{\filename@ext}}}%
752 <latexrelease>          \reserved@a
753 <latexrelease>      \fi}
754 <latexrelease>
755 <latexrelease>\EndIncludeInRelease
756 <*2ekernel>

```

(End of definition for \@missingfileerror.)

**\@obsoletefile** For compatibility with L<sup>A</sup>T<sub>E</sub>X 2.09 document styles, we distribute files called `article.sty`, `book.sty`, `report.sty`, `slides.sty` and `letter.sty`. These use the command `\@obsoletefile`, which produces a warning message.

```

757 \def\@obsoletefile#1#2{%
758     \@latex@warning@no@line{inputting ‘#1’ instead of obsolete ‘#2’}}
759 \@onlypreamble\@obsoletefile

```

## 1.2 Listing files

A list of files input so far. The initial value of `\@gobble` eats the comma before the first file name.

**\@filelist** `\let\@filelist\@gobble`

**\@addtofilelist** Add to the list of files input so far. This ‘real’ definition is only used for ‘cfg’ files during intex. An initial definition of `\@gobble` has already been set.

```

761 %\def\@addtofilelist#1{\xdef\@filelist{\@filelist,#1}}

```

```

\if@listfiles@hashes 762 \ExplSyntaxOn
\if@listfiles@sizes 763 \keys_define:nn { __kernel / listfiles }
764 {
765     hashes .legacy_if_set:n = @listfiles@hashes ,

```

```

766     sizes .legacy_if_set:n = @listfiles@sizes
767   }
768 \ExplSyntaxOff

```

A preamble command to cause `\end{document}` to list files input from the main file.

```

\listfiles
769 \NewDocumentCommand\listfiles{0{}}{%
770   \SetKeys[_kernel/listfiles]{#1}%
771   \let\listfiles\relax
772   \def\@listfiles##1##2##3##4##5##6##7##8##9\@{%
773     \def\reserved@d{\}%
774     \@tfor\reserved@c:=##1##2##3##4##5##6##7##8\do{%
775       \ifx\reserved@c\reserved@d
776         \edef\filename@area{ \filename@area}%
777       \fi}}%
778   \def\@dofilelist{%
779     \typeout{^^J *File List*}%
780     \@for\@currname:=\@filelist\do{%
781       \filename@parse\@currname
782       \edef\reserved@a{%
783         \filename@base.%
784         \ifx\filename@ext\relax tex\else\filename@ext\fi}%
785       \expandafter\let\expandafter\reserved@b
786         \csname ver@\reserved@a\endcsname

```

Packages that `\relax` their `\ver@...` string to allow for multiple loading (e.g., fontenc) can use `\ver@@...` to store the version information instead.

```

787     \ifx\reserved@b\relax
788       \expandafter\let\expandafter\reserved@b
789         \csname ver@@\reserved@a\endcsname
790     \fi
791     \expandafter\expandafter\expandafter\@listfiles\expandafter
792       \filename@area\filename@base\////////////////////////////////\@
793     \typeout{%
794       \filename@area\reserved@a
795       \ifx\reserved@b\relax\else\@spaces\reserved@b\fi

```

Now we add the additional information if requested.

```

796     \ifnum0%
797       \if@listfiles@hashes1\fi
798       \if@listfiles@sizes1\fi
799       >0 %
800       ^^J\@spaces
801       (%
802         \if@listfiles@sizes
803           size \@dofilelist@size\@currname
804           \if@listfiles@hashes
805             , %
806           \fi
807         \fi
808         \if@listfiles@hashes
809           hash \@dofilelist@hash\@currname
810         \fi
811       )%
812     \fi

```

```

813     }}%
814     \typeout{ *****^~J}}

815 \ExplSyntaxOn
\@dofilelist@hash 816 \cs_new_eq:NN \@dofilelist@hash \file_md5five_hash:n
\@dofilelist@size 817 \cs_new_eq:NN \@dofilelist@size \file_size:n
818 \ExplSyntaxOff

    The \@filelist will be de-activated if \listfiles does not appear in the preamble.
    \begin{document} contains code equivalent to the following:

\AtBeginDocument{%
    \ifx\@listfiles\@undefined
        \let\@filelist\relax
        \let\@addtofilelist\@gobble
    \fi}

819 \@onlypreamble\listfiles

\@dofilelist 820 \let\@dofilelist\relax

821 </2ekernel>

(End of definition for \@obsoletefile and others.)

```

## File 21

# ltoutenc.dtx

## 1 Font encodings

This section of the kernel contains commands for declaring encoding-specific commands, such as accents. It also contains the code for some of the encoding files, including `omlenc.def`, `omsenc.def`, `t1enc.def` and `ot1enc.def` files, which define the OML, OMS, T1 and OT1 encodings, and the `fontenc` package for selecting encodings.

The `fontenc` package has options for encodings, of which the last option is the default encoding. For example, to use the OT2, OT3 and T1 encodings, with T1 as the default, you say:

```
\usepackage[OT2,OT3,T1]{fontenc}
```

The standard kernel set-up loads font encoding files and selects an encoding as follows.

```
\input {omlenc.def}
\input {t1enc.def}
\input {ot1enc.def}
\input {omsenc.def}
\fontencoding{OT1}
```

Note that the files in the standard `inputenc` package depend on this behaviour of the kernel.

The syntax for declaring encoding-specific commands is:

```
\DeclareTextCommand{<command>}{<encoding>}
[<number>][<default>]{<commands>}
```

This command is like `\newcommand`, except that it defines a command which is specific to one encoding. The resulting command is always robust, even if its definition is fragile. For example, the definition of `\l` in the OT1 encoding is:

```
\DeclareTextCommand{\l}{OT1}{\@xxxii l}
```

`\DeclareTextCommand` takes the same optional arguments as `\newcommand`.

```
\ProvideTextCommand{<command>}{<encoding>}
[<number>][<default>]{<commands>}
```

This acts like `\DeclareTextCommand`, but does nothing if the command is already defined.

```
\DeclareTextSymbol{<command>}{<encoding>}{<slot>}
```

This command defines a text symbol, with a particular slot in that encoding. The commands:

```
\DeclareTextSymbol{\ss}{OT1}{25}
\DeclareTextCommand{\ss}{OT1}{\char25 }
```

have the same effect, but the `\DeclareTextSymbol` is faster.

```
\DeclareTextAccent{<command>}{<encoding>}{<slot>}
```

This command declares a text accent. The commands:

```
\DeclareTextAccent{"}{OT1}{127}
\DeclareTextCommand{"}{OT1}{\add@accent {127}}
```

have the same effect.

```
\DeclareTextComposite{<command>}
                               {<encoding>}{<argument>}{<slot>}
```

This command declares a composite letter, for example in the T1 encoding `\'a` is slot 225, which is declared by:

```
\DeclareTextComposite{\'}{T1}{a}{225}
```

The *command* will normally have been declared with `\DeclareTextAccent`, or as a one-argument `\DeclareTextCommand`.

`\DeclareTextComposite` is the most common example of using the more general declaration `\DeclareTextCompositeCommand`, which can define a composite to be an arbitrary piece of text.

```
\DeclareTextCompositeCommand{<command>}
                               {<encoding>}{<argument>}{<text>}
```

For example, in the OT1 encoding Å has a hand-crafted definition this is declared as follows

```
\DeclareTextCompositeCommand{\r}{OT1}{A}
{\leavevmode\setbox\z@\hbox{!}\dimen@ht\z@\advance\dimen@-1ex%
 \rlap{\raise.67\dimen@\hbox{\char23}}A}
```

The *command* will normally have been declared with `\DeclareTextAccent`, or as a one-argument `\DeclareTextCommand`.

The commands defined using the above declarations can be used in two ways. Normally they are used by just calling the command in the appropriate encoding, for example `\ss`. However, sometimes you may wish to use a command in an encoding where it is not defined. If the command has no arguments, then you can use it in another encoding by calling `\UseTextSymbol`:

```
\UseTextSymbol{<encoding>}{<command>}
```

For example, `\UseTextSymbol{OT1}{\ss}` has the same effect as:

```
{\fontencoding{OT1}\selectfont\ss}
```

If the command has one argument then you can use it in another encoding by calling `\UseTextAccent`:

```
\UseTextAccent{<encoding>}{<command>}{<text>}
```

For example, if the current encoding is OT2 then `\UseTextAccent{OT1}{\'}{a}` has the same effect as:

```
{\fontencoding{OT1}\selectfont\'{\fontencoding{OT2}\selectfont a}}
```

You can also declare a default definition for a text command, which will be used if the current encoding has no appropriate definition. Such use will also set the definition for this command in the current encoding to equal this default definition; this makes subsequent uses of the command much faster.

```
\DeclareTextCommandDefault{<command>}{<definition>}
```

For example, the default definition of the command `\textonequarter` (which produces the fraction  $\frac{1}{4}$ ) could be built using math mode:

```
\DeclareTextCommandDefault{\textonequarter}{\ensuremath {\frac{1}{4}}}
```

There is a matching `\Provide` command which will not override an existing default definition:

```
\ProvideTextCommandDefault{<command>}{<definition>}
```

The most common use for these commands is to use symbols from other encodings, so there are some optimizations provided:

```
\DeclareTextSymbolDefault{<command>}{<encoding>}
\DeclareTextAccentDefault{<command>}{<encoding>}
```

are short for:

```
\DeclareTextCommandDefault{<command>}
    {\UseTextSymbol{<encoding>}{<command>}}
\DeclareTextCommandDefault[1]{<command>}
    {\UseTextAccent{<encoding>}{<command>}{#1}}
```

For example, to make OT1 the default encoding for `\ss` and `\'` you say:

```
\DeclareTextSymbolDefault{\ss}{OT1}
\DeclareTextAccentDefault{\'}{OT1}
```

Note that you can use these commands on any zero- or one-argument commands declared with `\DeclareText*` or `\ProvideText*`, not just those defined using `\DeclareTextSymbol` or `\DeclareTextAccent`.

## 1.1 Removing encoding-specific commands

In some cases encoding definitions are given to provide some limited support since nothing better is available, for example, the definition for `\textdollar` in OT1 is a hack since \$ and £ actually share the same slot in this encoding. Thus if such a glyph becomes available in a different encoding (e.g., TS1) one would like to get rid of the flaky one and make the default definition point to the new encoding. In such a case defining

```
\DeclareTextSymbol{\textdollar}{TS1}{36}
\DeclareTextSymbolDefault{\textdollar}{TS1}
```

is not enough since if typesetting in OT1 L<sup>A</sup>T<sub>E</sub>X will still find the encoding specific-definition for OT1 and therefore ignore the new default. Therefore to ensure that in this case the TS1 version is used we have to remove the OT1 declaration:

```
\UndeclareTextCommand{\textdollar}{OT1}
```

Since the \$ sign is a proper glyph in the T1 encoding there is no point removing its definition and forcing L<sup>A</sup>T<sub>E</sub>X to pick up the TS1 version if typesetting in this encoding. However, assume you want to use the variant dollar sign, i.e., \$ for your dollars. In that case you have to get rid of the T1 declaration as well, e.g., the following would do that for you:

```
\UndeclareTextCommand{\textdollar}{OT1}
\UndeclareTextCommand{\textdollar}{T1}
\DeclareTextCommandDefault{\textdollar}
{\UseTextSymbol{TS1}\textdollaroldstyle}
```

## 1.2 The order of declarations

If an encoding-specific command is defined for more than one encoding, then it will execute fastest in the encoding in which it was defined last since its top-level definition will be set up to execute in that encoding without any overhead.

For this reason the file `fonttext.ltx` currently first loads the definitions for the T1 encoding and then those for the OT1 encoding so that typesetting in OT1 is optimized since that is (still) the default. However, when T1 is explicitly requested (via `\usepackage[T1]{fontenc}`) the top-level definitions are automatically changed to favour T1 since its declarations are reloaded in the process.

For the same reason default declarations should never come last since they are implemented as a special encoding themselves (with the name ?). Specifying them last would simply mean to make those encoding-specific commands equally inefficient in all encodings. Therefore the `textcomp` package, for example, first sets up all defaults to point to TS1 and then declares the commands in the TS1 encoding.

## 1.3 Docstrip modules

This `.dtx` file is be used to generate several related files containing font encoding definitions. The mutually exclusive docstrip options are listed here.

T1	generates <code>t1enc.def</code> for the Cork encoding.
TS1	generates <code>ts1enc.def</code> for the Text Companion encoding.
TS1sty	generates <code>textcomp.sty</code> , package that sets up use of the Text Companion encoding.
OT1	generates <code>ot1enc.def</code> for Knuth's CM encoding.
OMS	generates <code>omsenc.def</code> for Knuth's math symbol encoding.
OML	generates <code>omlenc.def</code> for Knuth's math letters encoding.
OT4	generates <code>ot4enc.def</code> for the Polish extension to the OT1 encoding, created by B. Jackowski and M. Ryćko for use with the Polish version of Computer Modern and Computer Concrete.
TU	generates <code>tuenc.def</code> for Unicode font encoding.
package	generates <code>fontenc.sty</code> for selecting encodings.
2ekernel	for the kernel commands.

## 1.4 Definitions for the kernel

### 1.4.1 Declaration commands

This section contains definitions for commands such as accents which depend on the current encoding. These commands will usually be kept in .def files, for example `ot1enc.def` contains the definitions for the OT1 encoding.

```
1 <*2ekernel>
2 \message{font encodings,}
```

Far too many macros in one block here!

`\DeclareTextCommand` If you say:

`\ProvideTextCommand` `\DeclareTextCommand{\foo}{T1}...`

`\DeclareTextSymbol`

`\@dec@text@cmd`

`\chardef@text@cmd`

`\@changed@cmd`

`\@changed@x`

`\TextSymbolUnavailable`

`\@inmathwarn`

then `\foo` is defined to be `\T1-cmd \foo \T1\foo`, where `\T1\foo` is *one* control sequence, not two! We then call `\newcommand` to define `\T1\foo`.

```
3 \def\DeclareTextCommand{%
4   \@dec@text@cmd\newcommand}
5 \def\ProvideTextCommand{%
6   \@dec@text@cmd\providecommand}
7 \def\@enc@info#1{%
8   \GenericInfo{(Encoding)\@spaces\@spaces\@spaces\space\space}%
9   {LaTeX Encoding Info: \space\space\space#1}}%
10 \def\@dec@text@cmd#1#2#3{%
```

For logging, there are a number of different cases to cater for.

```
11 \ifcsname #3\string#2\endcsname
12 \@enc@info{%
13   \ifx#1\providecommand
14     Ignoring declaration for
15   \else
16     Redeclaring
17   \fi
18   text
```

This test distinguishes between commands and symbols:

```
19 \ifx#1\chardef@text@cmd
20   symbol
21 \else
22   command
23 \fi
24 \string#2 (encoding #3)}%
25 \fi
26 \expandafter\def\expandafter#2%
27   \expandafter{%
28     \csname#3-cmd\expandafter\endcsname
29     \expandafter#2%
30     \csname#3\string#2\endcsname
31   }%
32 \let\@ifdefinable\@rc@ifdefinable
33 \expandafter#1\csname#3\string#2\endcsname}
```

This command was introduced to fix a major bug in `\@dec@text@cmd` without changing that command itself. This was thought to be necessary because it is defined in more than one package. (Perhaps the more serious bug is to put complex low-level commands like this in packages?)

The problem it solves is that whereas both `\newcommand` and `\providecommand` (used just above) both handle the resetting of `\@ifdefinable` (following its disabling in `\@dec@text@cmd`), the primitive `\chardef` neither needs the disabling, nor does the resetting.

```

34 \def\chardef@text@cmd{%
35   \let\@ifdefinable\@ifdefinable
36   \chardef
37 }
38 \def\DeclareTextSymbol#1#2#3{%
39   \@dec@text@cmd\chardef@text@cmd#1{#2}#3\relax
40 }

```

The declarations are only available before `\begin{document}`.

```

41 \@onlypreamble\DeclareTextCommand
42 \@onlypreamble\DeclareTextSymbol

```

The sneaky bit in all this is what `\T1-cmd \foo \T1\foo` does. There are five possibilities, depending on the current values of `\protect`, `\cf@encoding` and `\ifmmode`:

- If `\protect` is `\@typeset@protect` and `\cf@encoding` is `T1`, then we execute `\T1\foo`. This should be the normal behaviour, and is optimized for speed.
- If `\protect` is `\@typeset@protect`, `\cf@encoding` is (say) `OT1`, and `\OT1\foo` is defined, then we execute `\OT1\foo`.
- If `\protect` is `\@typeset@protect`, `\cf@encoding` is (say) `OT1`, we're in text mode, and `\OT1\foo` is undefined, then we define `\OT1\foo` to be the default value of `\foo`, and execute `\OT1\foo`.
- If `\protect` is `\@typeset@protect`, `\cf@encoding` is (say) `OT1`, we're in math mode, and `\OT1\foo` is undefined, then we execute the default value of `\foo`. (This is necessary so that things like `$X_\copyright$` work properly.)
- If `\protect` is not `\@typeset@protect` then we execute `\noexpand\foo`. For example, if we are writing to a file, then this results in `\foo` being written. If we are in a `\mark`, then `\foo` will be put in the mark—since `\foo` is robust, it will then survive all the things which may happen to it whilst it's a `\mark`.

So after all that, we will either execute the appropriate definition of `\foo` for the current encoding, or we will execute `\noexpand\foo`.

The default value of `\foo` is `\?\foo` if it is defined, and an error message otherwise.

When the encoding is changed from `T1` to `OT1`, `\T1-cmd` is defined to be `\@changed@cmd` and `\OT1-cmd` is defined to be `\@current@cmd`. This means that the test for what the current encoding is can be performed quickly.

```

43 \def\@current@cmd#1{%
44   \ifx\protect\@typeset@protect
45     \inmathwarn#1%
46   \else
47     \noexpand#1\expandafter\@gobble
48   \fi}

```

```

49 \def\@changed@cmd#1#2{%
50   \ifx\protect\@typeset@protect
51     \@inmathwarn#1%
52     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
53       \expandafter\ifx\csname ?\string#1\endcsname\relax
54         \expandafter\def\csname ?\string#1\endcsname{%
55           \TextSymbolUnavailable#1%
56         }%
57       \fi
58       \global\expandafter\let
59         \csname\cf@encoding\string#1\endcsname\expandafter\endcsname
60         \csname ?\string#1\endcsname
61       \fi
62       \csname\cf@encoding\string#1\endcsname
63       \expandafter\endcsname
64     \else
65       \noexpand#1%
66     \fi}

67 \gdef\TextSymbolUnavailable#1{%
68   \@latex@error{%
69     Command \protect#1 unavailable in encoding \cf@encoding%
70   }\@eha}

```

The command `\@inmathwarn` produces a warning message if we are currently in math mode. Note that since this command is used inside text commands, it can't call `\relax` before the `\ifmmode`. This means that it is possible for the warning to fail to be issued at the beginning of a row of an `halign` whose template enters math mode. This is probably a bad feature, but there's not much that can be done about it, since adding a `\relax` would break ligatures and kerning between text symbols.

A more efficient solution would be to make `\@inmathwarn` and `\@inmatherr` equal to `\@empty` and `\relax` by default, and to have `\everymath` reset them to their usual definitions. This is left for future investigation (for example it may break some third party code).

```

71 \def\@inmathwarn#1{%
72   \ifmmode
73     \@latex@warning{Command \protect#1 invalid in math mode}%
74   \fi}

```

(End of definition for `\DeclareTextCommand` and others.)

`\DeclareTextCommandDefault`  
`\ProvideTextCommandDefault`

These define commands with encoding ?.

Note that `\DeclareTextCommandDefault` can only be used in the preamble, but that the `\Provide` version is allowed in inputenc .def files, so is allowed anywhere.

```

75 \def\DeclareTextCommandDefault#1{%
76   \DeclareTextCommand#1?}

77 \def\ProvideTextCommandDefault#1{%
78   \ProvideTextCommand#1?}

79 \@onlypreamble\DeclareTextCommandDefault
80 %\@onlypreamble\ProvideTextCommandDefault

```

They require `\? -cmd` to be initialized as `\@changed@cmd`.

```

81 \expandafter\let\csname?\-cmd\endcsname\@changed@cmd

```

(End of definition for `\DeclareTextCommandDefault` and `\ProvideTextCommandDefault`.)

`\DeclareTextAccent` This is just a disguise for defining a T<sub>E</sub>X `\accent` command.

```
82 \def\DeclareTextAccent#1#2#3{%  
83   \DeclareTextCommand#1{#2}{\add@accent{#3}}}  
84 \@onlypreamble\DeclareTextAccent
```

(End of definition for `\DeclareTextAccent`.)

`\add@accent` To save space this code is shared between all text accents that are set using the `\accent` primitive. The argument is pre-set in a box so that any font loading that is needed is already done within the box. This is needed because font-loading involves grouping and that would prevent the accent mechanism from working so that the accent would not be positioned over the argument. Declarations that change the font should be allowed (only low-level ones are at present) inside the argument of an accent command, but not size changes, as they involve `\setbox` operations which also inhibit the mechanism of the `\accent` primitive.

Note that the whole process is within a group. For a detailed discussion of this reimplementaion and its deficiencies, see pr/3160.

```
85 \def\add@accent#1#2{\hmode@bgroup
```

Turn off the group in `\UseTextSymbol` in case this is used inside the argument of `\add@accent`.

```
86   \let\hmode@start@before@group\@firstofone  
87   \setbox\@tempboxa\hbox{#2%
```

When presetting the argument in a box we record its `\spacefactor` for later use after the accent got typeset. This way something like `\A` gets the spacefactor of `A` (i.e., 999) rather than the default value of 1000.

```
88     \global\mathchardef\accent@spacefactor\spacefactor}%
```

The accent primitive doesn't allow things `\begingroup` to interfere between accent and base character. Therefore we need to avoid that (they are some hidden inside `\maybe@load@fontshape`). As we don't have to load the fontshape in this case (as that already happened in the box above, if necessary), we simply disable that part of the code temporarily. We also ignore `\ignorespaces` which has the same issue and may show up as part of `\normalfont` if that is used.

```
89   \let\maybe@load@fontshape\relax  
90   \let\ignorespaces\relax  
91   \accent#1 #2\egroup\ifmmode\else\spacefactor\accent@spacefactor\fi}
```

Default definition for `\accent@spacefactor` prevents a horrible death of the above macro inside an unprotected `\edef`.

```
92 \let\accent@spacefactor\relax
```

(End of definition for `\add@accent`.)

`\hmode@bgroup`

```
93 \def\hmode@bgroup{\leavevmode\bgroup}
```

(End of definition for `\hmode@bgroup`.)

`\DeclareTextCompositeCommand` Another amusing game to play with `\expandafter`, `\csname`, and `\string`. When you say `\DeclareTextCompositeCommand{\foo}{T1}{a}{bar}`, we look to see if the expansion of `\T1\foo` begins with `\@text@composite`, and if it doesn't, we redefine `\T1\foo` to be:

```

\DeclareTextComposite
  \@text@composite
  \@text@composite@x
    \@strip@args
      #1 -> \@text@composite \T1\foo #1\@empty \@text@composite {...}

```

where ... is the previous definition of `\T1\foo`. Finally, we define `\T1\foo-a` to expand to `bar`.

```

94 </2ekernel>
95 <latexrelease>\IncludeInRelease{2017/04/15}{\DeclareTextCompositeCommand}
96 <latexrelease>                                     {test for undeclared accent}%
97 <*2ekernel | latexrelease>
98 \def\DeclareTextCompositeCommand#1#2#3#4{%
99   \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
100   \ifx\reserved@a\relax
101     \DeclareTextCommand#1{#2}{%
102       \@latex@error{Text composite \string#1 undeclared in encoding #2}\@eha}%
103       \@enc@info{Text composite with undeclared \string#1 in encoding #2}%
104       \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
105       \fi
106       \expandafter\expandafter\expandafter\ifx
107       \expandafter\@car\reserved@a\relax\relax\@nil \@text@composite \else
108       \edef\reserved@b##1{%
109         \def\expandafter\noexpand
110           \csname#2\string#1\endcsname####1{%
111           \noexpand\@text@composite
112             \expandafter\noexpand\csname#2\string#1\endcsname
113             ####1\noexpand\@empty\noexpand\@text@composite
114             {##1}}}%
115       \expandafter\reserved@b\expandafter{\reserved@a{##1}}%
116     \fi
117     \expandafter\def\csname\expandafter\string\csname
118       #2\endcsname\string#1-\string#3\@empty\endcsname{#4}%
119   }
120 </2ekernel | latexrelease>
121 <latexrelease>\EndIncludeInRelease
122 <latexrelease>\IncludeInRelease{0000/00/00}{\DeclareTextCompositeCommand}
123 <latexrelease>                                     {test for undeclared accent}%
124 <latexrelease>\def\DeclareTextCompositeCommand#1#2#3#4{%
125 <latexrelease>   \expandafter\let\expandafter\reserved@a
126 <latexrelease>                                     \csname#2\string#1\endcsname
127 <latexrelease>   \expandafter\expandafter\expandafter\ifx
128 <latexrelease>   \expandafter\@car\reserved@a\relax\relax\@nil
129 <latexrelease>                                     \@text@composite \else
130 <latexrelease>     \edef\reserved@b##1{%
131 <latexrelease>       \def\expandafter\noexpand
132 <latexrelease>         \csname#2\string#1\endcsname####1{%
133 <latexrelease>         \noexpand\@text@composite
134 <latexrelease>           \expandafter\noexpand\csname#2\string#1\endcsname
135 <latexrelease>           ####1\noexpand\@empty\noexpand\@text@composite
136 <latexrelease>           {##1}}}%
137 <latexrelease>     \expandafter\reserved@b\expandafter{\reserved@a{##1}}%

```

```

138 <latexrelease> \fi
139 <latexrelease> \expandafter\def\csname\expandafter\string\csname
140 <latexrelease> #2\endcsname\string#1-\string#3\@empty\endcsname{#4}}
141 <latexrelease>\EndIncludeInRelease
142 <*2ekernel>

143 \@onlypreamble\DeclareTextCompositeCommand

```

This all works because:

```
\@text@composite \T1\foo A\@empty \@text@composite {...}
```

expands to `\T1\foo-A` if `\T1\foo-A` has been defined, and `{...}` otherwise.

Note that `\@text@composite` grabs the first token of the argument and puts just that in the csname. This is so that `\'\{\textit{e}\}` will work—it checks whether `\T1\'-\textit` is defined (which presumably it isn't) and so expands to `\{accent 1 \textit{e}\}`.

This trick won't always work, for example `\'\{\itshape e\}` will expand to (with spaces added for clarity):

```
\csname \string \T1\' - \string {\itshape e} \@empty \endcsname
```

which will die pretty horribly. Unfortunately there's not much can be done about this if we're going to use `\csname` lookups as a fast way of accessing composites.

This has an unfortunate 'misfeature' though, which is that in the T1 encoding, `\'\{aa\}` produces á. This is not the expected behaviour, and should perhaps be fixed if the fix doesn't affect performance too badly.

Finally, it's worth noting that the `\@empty` is used in `\@text@composite` so that accents will work even when the argument is empty. If you say `\'\{}` then this looks up `\T1\'-\@empty`, which ought to be `\relax`, and so all is well. If we didn't include the `\@empty`, then `\'\{}` would expand to:

```
\csname \string \T1\' - \string \endcsname
```

so the `\endcsname` would be `\string'ed` and the whole of the rest of the document would be put inside the `\csname`. This would not be good.

```

144 \def\@text@composite#1#2#3\@text@composite{%
145   \expandafter\@text@composite@x
146   \csname\string#1-\string#2\endcsname}

```

Originally the `\@text@composite@x` macro had two arguments and if `#1` was not `\relax` it was executed, otherwise `#2` was executed. All this happened within the `\ifx` code so that neither `#1` nor `#2` could have picked up any additional arguments from the input stream. This has now been changed using the typical `\@firstoftwo / \@secondoftwo` coding. This way the final expansion will happen without any `\else` or `\fi` intervening in the case that we need to get a further token from the input stream.

```

147 \def\@text@composite@x#1{%
148   \ifx#1\relax
149     \expandafter\@secondoftwo
150   \else
151     \expandafter\@firstoftwo
152   \fi
153   #1}

```

The command `\DeclareTextComposite` uses `\DeclareTextCompositeCommand` to declare a command which expands out to a single glyph.

```

154 \catcode\z@=11\relax
155 \def\DeclareTextComposite#1#2#3#4{%
156   \def\reserved@a{\DeclareTextCompositeCommand#1{#2}{#3}}%
157   \bgroup
158     \lccode\z@#4%
159     \lowercase{%
160       \egroup
161       \reserved@a ^~@}}
162 \catcode\z@=15\relax
163 \@onlypreamble\DeclareTextComposite

```

(End of definition for `\DeclareTextCompositeCommand` and others.)

```

164 </2ekernel>
165 <*2ekernel | latexrelease>
166 <latexrelease>\IncludeInRelease{2019/10/01}%
167 <latexrelease>           {\UseTextAccent}{Make commands robust}%

```

`\UseTextAccent` These fragile commands access glyphs from different encodings. They use grotty low-level calls to the font selection scheme for speed, and in order to make sure that `\UseTextSymbol` doesn't do anything which you're not allowed to do between an `\accent` and its glyph.

`\UseTextSymbol`

`\@use@text@encoding`

For a detailed discussion of this reimplementaion and its deficiencies, see pr/3160.

```

168 \DeclareRobustCommand*\UseTextAccent[3]{%
169   \hmode@start@before@group
170   {%

```

Turn off the group in `\UseTextSymbol` in case this is used inside the arguments of `\UseTextAccent`.

```

171     \let\hmode@start@before@group\@firstofone
172     \let\@curr@enc\cf@encoding
173     \@use@text@encoding{#1}%
174     #2{\@use@text@encoding\@curr@enc#3}%
175   }}

```

```

176 \DeclareRobustCommand*\UseTextSymbol[2]{%
177   \hmode@start@before@group
178   {%
179     \def\@wrong@font@char{\MessageBreak
180       for \noexpand\symbol'\string#2'}%
181     \@use@text@encoding{#1}%
182     #2%
183   }%
184 }

```

```

185 </2ekernel | latexrelease>
186 <latexrelease>\EndIncludeInRelease
187 <latexrelease>\IncludeInRelease{0000/00/00}%
188 <latexrelease>           {\UseTextAccent}{Make commands robust}%
189 <latexrelease>
190 <latexrelease>\kernel@make@fragile\UseTextAccent

```

```

191 <latexrelease>\kernel@make@fragile\UseTextSymbol
192 <latexrelease>
193 <latexrelease>\EndIncludeInRelease
194 <*2ekernel>

```

Switch to a different text encoding without any grouping for use in `\UseTextAccent` or `\UseTextSymbol` (and for `\oldstylenums`).

```

195 \def\@use@text@encoding#1{%
196   \edef\f@encoding{#1}%
197   \xdef\font@name{%
198     \csname\curr@fontshape/\f@size\endcsname}%
199   \pickup@font
200   \font@name
201   \@enc@update}

```

*(End of definition for \UseTextAccent, \UseTextSymbol, and \@use@text@encoding.)*

`\hmode@start@before@group` The `\hmode@start@before@group` starts hmode and should be immediately followed by an explicit `{...}`. Its purpose is to ensure that hmode is started before this group is opened. Inside `\add@accent` and `\UseTextAccent` it is redefined to remove this group so that it doesn't conflict with the `\accent` primitive.

For a detailed discussion see pr/3160.

```

202 \let\hmode@start@before@group\leavevmode

```

*(End of definition for \hmode@start@before@group.)*

`\DeclareTextSymbolDefault` Some syntactic sugar. Again, these should probably be optimized for speed.  
`\DeclareTextAccentDefault`

```

203 \def\DeclareTextSymbolDefault#1#2{%
204   \DeclareTextCommandDefault#1{\UseTextSymbol{#2}#1}}
205 \def\DeclareTextAccentDefault#1#2{%
206   \DeclareTextCommandDefault#1{\UseTextAccent{#2}#1}}
207 \@onlypreamble\DeclareTextSymbolDefault
208 \@onlypreamble\DeclareTextAccentDefault

```

*(End of definition for \DeclareTextSymbolDefault and \DeclareTextAccentDefault.)*

`\UndeclareTextCommand` This command safely removes an encoding specific declaration for a given encoding. It is helpful if one intends to use the default definition always and therefore wants to get rid of a declaration for some specific encoding.

```

209 \def\UndeclareTextCommand#1#2{%

```

If there is no declaration for the current encoding do nothing.

```

210   \ifcsname #2\string#1\endcsname

```

Else: throw away that declaration.

```

211     \@enc@info{Undeclare text command \string#1 (encoding #2)}%
212     \global\expandafter\let\csname#2\string#1\endcsname
213     \undefined

```

But this is unfortunately not enough, we have to take a look at the top-level definition of the encoding specific command which for a command `\foo` would look similar to `\T1-cmd \foo \T1\foo` (three tokens).

Of course, instead of `T1` one could see a different encoding name; which one depends the encoding for which `\foo` was declared last.

Now assume we have just removed the declaration for `\foo` in `T1` and the top-level of `\foo` expands to the above. Then we better change that pretty fast otherwise we do get an “undefined csname error” when we try to typeset `\foo` within `T1` instead of getting the default definition for `\foo`. And what is the best way to change that top-level definition? Well, the only “encoding” we know for sure will still be around is the default encoding denoted by `?`.

Thus in case the last token of the top-level expansion is now undefined we change the declaration to look like `\?-cmd \foo \?\foo` which is done by the following (readable?) code:

```

214     \expandafter\expandafter\expandafter
215     \ifx\expandafter\@thirdofthree#1\@undefined
216     \expandafter\gdef\expandafter#1\expandafter
217         {\csname ?-cmd\expandafter\endcsname\expandafter
218          #1\csname?\string#1\endcsname}%
219     \fi
220 \else
221
222     \@enc@info{Text command \string#1 (encoding #2) is not declared}%
223 \fi
224 }
225 \onlypreamble\UndeclareTextCommand

```

*(End of definition for \UndeclareTextCommand.)*

### 1.4.2 Hyphenation

<code>\patterns</code> <code>\@patterns</code> <code>\hyphenation</code> <code>\@hyphenation</code>	<p>We redefine <code>\patterns</code> and <code>\hyphenation</code> to allow the use of commands declared with <code>\DeclareText*</code> to be used inside them.</p> <pre> 225 %\let\@patterns\patterns 226 %\let\@hyphenation\hyphenation 227 %\def\patterns{% 228 %   \bgroup 229 %   \let\protect\@empty 230 %   \let\@typeset@protect\@empty 231 %   \let\@changed@x\@changed@x@mouth 232 %   \afterassignment\egroup 233 %   \@patterns 234 %} 235 %\def\hyphenation{% 236 %   \bgroup 237 %   \let\protect\@empty 238 %   \let\@typeset@protect\@empty 239 %   \let\@changed@x\@changed@x@mouth 240 %   \afterassignment\egroup 241 %   \@hyphenation 242 %} </pre>
--	--

*(End of definition for \patterns and others.)*

### 1.4.3 Miscellanea

`\a` The `\a` command is used to access the accent commands even when they have been redefined (for example by the `\tabbing` environment). Its internal name is `\@tabacckludge`.

The `\string` within the `\csname` guards against something like `'` being active at the point of use.

```
243 \def\@tabacckludge#1{\expandafter\@changed@cmd
244                               \csname\string#1\endcsname\relax}
245 \let\a=\@tabacckludge
```

*(End of definition for \a.)*

### 1.4.4 Default encodings

We define the default encodings for most commands to be either OT1, OML or OMS. These defaults are in the kernel and therefore fonts with these encodings must be available unless these defaults are redefined elsewhere. Recall that the standard kernel loads the encoding files for these encodings, and also that for the T1 encoding.

The naming conventions in the kernel are not what we would use if we were starting from scratch... Those defined by DEK (like `\ae` and `\ss`) or by the T<sub>E</sub>X Users Group Technical Working Group on multi-lingual typesetting (like `\th` and `\ng`) have short names. Those which were added to the kernel in 1993 and early 1994 are named after their Adobe glyph names (like `\guillemotleft` and `\quotedblbase`). Unfortunately, this naming scheme won't work for all glyphs, since some names (like `\space`) are already used, and some (like `\endash`) are very likely to be defined by users. So we're now using the naming scheme of `\text` followed by the Adobe name, (like `\textendash` and `\textsterling`). Except that some glyphs don't have Adobe names, so we're using the names used by fontinst for those (like `\textcompwordmark`). Sigh.

Some accents from OT1:

```
246 \DeclareTextAccentDefault{"}{OT1}
247 \DeclareTextAccentDefault{'}{OT1}
248 \DeclareTextAccentDefault{.}{OT1}
249 \DeclareTextAccentDefault{=}{OT1}
250 \DeclareTextAccentDefault{H}{OT1}
251 \DeclareTextAccentDefault{^}{OT1}
252 \DeclareTextAccentDefault{'}{OT1}
253 \DeclareTextAccentDefault{b}{OT1}
254 \DeclareTextAccentDefault{c}{OT1}
255 \DeclareTextAccentDefault{d}{OT1}
256 \DeclareTextAccentDefault{r}{OT1}
257 \DeclareTextAccentDefault{u}{OT1}
258 \DeclareTextAccentDefault{v}{OT1}
259 \DeclareTextAccentDefault{~}{OT1}
```

Some symbols from OT1:

```
260 %\DeclareTextSymbolDefault{AA}{OT1}
261 \DeclareTextSymbolDefault{AE}{OT1}
262 \DeclareTextSymbolDefault{L}{OT1}
263 \DeclareTextSymbolDefault{OE}{OT1}
264 \DeclareTextSymbolDefault{O}{OT1}
265 %\DeclareTextSymbolDefault{aa}{OT1}
266 \DeclareTextSymbolDefault{ae}{OT1}
267 \DeclareTextSymbolDefault{i}{OT1}
```

```

268 \DeclareTextSymbolDefault{\j}{OT1}
269 \DeclareTextSymbolDefault{\ij}{OT1}
270 \DeclareTextSymbolDefault{\IJ}{OT1}
271 \DeclareTextSymbolDefault{\l}{OT1}
272 \DeclareTextSymbolDefault{\oe}{OT1}
273 \DeclareTextSymbolDefault{\o}{OT1}
274 \DeclareTextSymbolDefault{\ss}{OT1}
275 \DeclareTextSymbolDefault{\textdollar}{OT1}
276 \DeclareTextSymbolDefault{\textemdash}{OT1}
277 \DeclareTextSymbolDefault{\textendash}{OT1}
278 \DeclareTextSymbolDefault{\textexclamdown}{OT1}
279 %\DeclareTextSymbolDefault{\texthyphenchar}{OT1}
280 %\DeclareTextSymbolDefault{\texthyphen}{OT1}
281 \DeclareTextSymbolDefault{\textquestiondown}{OT1}
282 \DeclareTextSymbolDefault{\textquotedblleft}{OT1}
283 \DeclareTextSymbolDefault{\textquotedblright}{OT1}
284 \DeclareTextSymbolDefault{\textquoteleft}{OT1}
285 \DeclareTextSymbolDefault{\textquoteright}{OT1}
286 \DeclareTextSymbolDefault{\textsterling}{OT1}

```

Some symbols from OMS:

```

287 \DeclareTextSymbolDefault{\textasteriskcentered}{OMS}
288 \DeclareTextSymbolDefault{\textbackslash}{OMS}
289 \DeclareTextSymbolDefault{\textbar}{OMS}
290 \DeclareTextSymbolDefault{\textbardbl}{OMS}
291 \DeclareTextSymbolDefault{\textbraceleft}{OMS}
292 \DeclareTextSymbolDefault{\textbraceright}{OMS}
293 \DeclareTextSymbolDefault{\textbullet}{OMS}
294 \DeclareTextSymbolDefault{\textdaggerdbl}{OMS}
295 \DeclareTextSymbolDefault{\textdagger}{OMS}
296 \DeclareTextSymbolDefault{\textparagraph}{OMS}
297 \DeclareTextSymbolDefault{\textperiodcentered}{OMS}
298 \DeclareTextSymbolDefault{\textsection}{OMS}
299 \DeclareTextAccentDefault{\textcircled}{OMS}

```

Some symbols from OML:

```

300 \DeclareTextSymbolDefault{\textless}{OML}
301 \DeclareTextSymbolDefault{\textgreater}{OML}
302 \DeclareTextAccentDefault{\t}{OML}

```

Some defaults we can fake.

The interface for defining `\copyright` changed, it used to use `\expandafter` to add braces at the appropriate points.

```

303 \DeclareTextCommandDefault{\textcopyright}{\textcircled{c}}
304 % \expandafter\def\expandafter
305 % \copyright\expandafter{\expandafter{\copyright}}
306 \DeclareTextCommandDefault{\textasciicircum}{\~{}}
307 \DeclareTextCommandDefault{\textasciitilde}{\~{}}
308 \DeclareTextCommandDefault{\textunderscore}{%
309 \leavevmode \kern.06em\vbox{\hrule\@width.3em}}

```

There is no good reason anymore to fake `\textcompwordmark`.

```

310 %\DeclareTextCommandDefault{\textcompwordmark}{\leavevmode\kern\z@}
311 \DeclareTextSymbolDefault{\textcompwordmark}{T1}

```

```

312 \DeclareTextCommandDefault{\textvisiblespace}{%
313   \mbox{\kern.06em\vrule \@height.3ex}%
314   \vbox{\hrule \@width.3em}%
315   \hbox{\vrule \@height.3ex}}

```

Using `\fontdimen3` in the next definition is some sort of a kludge (since it is the interword stretch) but it makes the ellipsis come out right in mono-spaced fonts too (since there it is zero).

```

316 \DeclareTextCommandDefault{\textellipsis}{%
317   .\kern\fontdimen3\font
318   .\kern\fontdimen3\font
319   .\kern\fontdimen3\font}

320 %\DeclareTextCommandDefault{\textregistered}{\textcircled{\scshape r}}
321 \DeclareTextCommandDefault{\textregistered}{\textcircled{%
322   \check@mathfonts\fontsize\sf@size\z@\math@fontsfalse\selectfont R}}
323 \DeclareTextCommandDefault{\texttrademark}{\textsuperscript{TM}}
324 \DeclareTextCommandDefault{\SS}{SS}

325 \DeclareTextCommandDefault{\textordfeminine}{\textsuperscript{a}}
326 \DeclareTextCommandDefault{\textordmasculine}{\textsuperscript{o}}

```

#### 1.4.5 Math material

Some commands can be used in both text and math mode:

```

327 \DeclareRobustCommand{\$}{\ifmmode\mathdollar\else\textdollar\fi}

```

We use `\protected` not `\DeclareRobustCommand` so that `\bigl\{` etc. works inside `\protected@edef`.

```

328 \protected\def{\{\ifmmode\lbrace\else\textbraceleft\fi}
329 \protected\def\}\{\ifmmode\rbrace\else\textbraceright\fi}

330 \DeclareRobustCommand{\P}{\ifmmode\mathparagraph\else\textparagraph\fi}
331 \DeclareRobustCommand{\S}{\ifmmode\mathsection\else\textsection\fi}
332 \DeclareRobustCommand{\dag}{\ifmmode{\dagger}\else\textdagger\fi}
333 \DeclareRobustCommand{\ddag}{\ifmmode{\ddagger}\else\textdaggerdbl\fi}

```

For historical reasons `\copyright` needs `{}` around the definition in maths.

```

334 \DeclareRobustCommand{\_}{%
335   \ifmmode\nfss@text{\textunderscore}\else\textunderscore\fi}
336 \DeclareRobustCommand{\copyright}{%
337   \ifmmode{\nfss@text{\textcopyright}}\else\textcopyright\fi}
338 \DeclareRobustCommand{\pounds}{%
339   \ifmmode\mathsterling\else\textsterling\fi}

340 \DeclareRobustCommand{\dots}{%
341   \ifmmode\mathellipsis\else\textellipsis\fi}

342 \let\ldots\dots

```

Default definition of the commabelow accent.

```

343 </2ekernel>
344 <latexrelease>\IncludeInRelease{2015/10/01}{\textcommabelow}{comma accent}%
345 <*2ekernel | latexrelease>
346 \DeclareTextCommandDefault\textcommabelow[1
347   {\hmode\bgroup\oalign{\null#1\crcr\hidewidth\raise-.31ex
348   \hbox{\check@mathfonts\fontsize\ssf@size\z@

```

```

349 \math@fontsfalse\selectfont,}\hidewidth}\egroup}
350 <latexrelease>\EndIncludeInRelease
351 </2ekernel| latexrelease>
352 <latexrelease>\IncludeInRelease{0000/00/00}{\textcommabelow}{comma accent}%
353 <latexrelease>\let\textcommabelow\@undefined
354 <latexrelease>\expandafter
355 <latexrelease> \let\csname\string\T1\string\c-G\endcsname\@undefined
356 <latexrelease>\expandafter
357 <latexrelease> \let\csname\string\T1\string\c-K\endcsname\@undefined
358 <latexrelease>\expandafter
359 <latexrelease> \let\csname\string\T1\string\c-k\endcsname\@undefined
360 <latexrelease>\expandafter
361 <latexrelease> \let\csname\string\T1\string\c-L\endcsname\@undefined
362 <latexrelease>\expandafter
363 <latexrelease> \let\csname\string\T1\string\c-l\endcsname\@undefined
364 <latexrelease>\expandafter
365 <latexrelease> \let\csname\string\T1\string\c-N\endcsname\@undefined
366 <latexrelease>\expandafter
367 <latexrelease> \let\csname\string\T1\string\c-n\endcsname\@undefined
368 <latexrelease>\expandafter
369 <latexrelease> \let\csname\string\T1\string\c-R\endcsname\@undefined
370 <latexrelease>\expandafter
371 <latexrelease> \let\csname\string\T1\string\c-r\endcsname\@undefined
372 <latexrelease>\EndIncludeInRelease
    Default definition of the commaabove accent(E.G.).
373 <latexrelease>\IncludeInRelease{2016/02/01}{\textcommaabove}{comma above}%
374 <*2ekernel| latexrelease>
375 \DeclareTextCommandDefault\textcommaabove[1]{%
376 \hmode\bgroup
377 \ooalign{%
378 \hidewidth
379 \raise.7ex\hbox{%
380 \check@mathfonts\fontsize\ssf@size\z@\math@fontsfalse\selectfont‘%
381 }%
382 \hidewidth\crrc
383 \null#1\crrc
384 }%
385 \egroup
386 }
387 <latexrelease>\EndIncludeInRelease
388 </2ekernel| latexrelease>
389 <latexrelease>\IncludeInRelease{0000/00/00}{\textcommaabove}{comma above}%
390 <latexrelease>\let\textcommaabove\@undefined
391 <latexrelease>\expandafter
392 <latexrelease> \let\csname\string\OT1\string\c-g\endcsname\@undefined
393 <latexrelease>\expandafter
394 <latexrelease> \let\csname\string\T1\string\c-g\endcsname\@undefined
395 <latexrelease>\EndIncludeInRelease

```

## 1.5 Definitions for the OT1 encoding

The definitions for the ‘T<sub>E</sub>X text’ (OT1) encoding.

Declare the encoding.

```

396 <*OT1>
397 \DeclareFontEncoding{OT1}{-}{-}

```

Providing font substitution is essential if accents are missing in a font and substitution tries to find it elsewhere. Without it you might receive a “Corrupted NFSS tables” error.

```

398 \DeclareFontSubstitution{OT1}{cmr}{m}{n}

```

Declare the accents.

```

399 \DeclareTextAccent{"}{OT1}{127}
400 \DeclareTextAccent{'}{OT1}{19}
401 \DeclareTextAccent{.}{OT1}{95}
402 \DeclareTextAccent{=}{OT1}{22}
403 \DeclareTextAccent{~}{OT1}{94}
404 \DeclareTextAccent{'}{OT1}{18}
405 \DeclareTextAccent{~}{OT1}{126}
406 \DeclareTextAccent{H}{OT1}{125}
407 \DeclareTextAccent{u}{OT1}{21}
408 \DeclareTextAccent{v}{OT1}{20}
409 \DeclareTextAccent{r}{OT1}{23}

```

Some accents have to be built by hand: Note that `\ooalign` and `\o@lign` must be inside a group. In these definitions we no longer use the helper function `\sh@ft` from `plain.tex` since that now has two incompatible definitions.

```

410 \DeclareTextCommand{\b}{OT1}[1]
411   {\hmode\bgroup\o@lign{\relax#1\crrcr\hidewidth\ltx@sh@ft{-3ex}%
412     \vbox to.2ex{\hbox{\char22}\vss}\hidewidth}\egroup}
413 \DeclareTextCommand{\c}{OT1}[1]
414   {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent24 #1%
415     \else\ooalign{\unhbox\z@\crrcr\hidewidth\char24\hidewidth}\fi}
416 \DeclareTextCommand{\d}{OT1}[1]
417   {\hmode\bgroup
418     \o@lign{\relax#1\crrcr\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}

```

Declare the text symbols.

```

419 \DeclareTextSymbol{\AE}{OT1}{29}
420 \DeclareTextSymbol{\OE}{OT1}{30}
421 \DeclareTextSymbol{\O}{OT1}{31}
422 \DeclareTextSymbol{\ae}{OT1}{26}
423 \DeclareTextSymbol{\i}{OT1}{16}
424 \DeclareTextSymbol{\j}{OT1}{17}
425 \DeclareTextSymbol{\oe}{OT1}{27}
426 \DeclareTextSymbol{\o}{OT1}{28}
427 \DeclareTextSymbol{\ss}{OT1}{25}
428 \DeclareTextSymbol{\textendash}{OT1}{124}
429 \DeclareTextSymbol{\textendash}{OT1}{123}

```

The `\nobreak\hskip\z@` is there to prevent a break after the hyphen but allow later breaks in the remainder of the word.

```

430 \DeclareTextCommand{\textnonbreakinghyphen}{OT1}{\mbox{-}\nobreak\hskip\z@}
431 \DeclareTextCommand{\textfiguredash}{OT1}{\textendash}
432 \DeclareTextCommand{\texthorizontalbar}{OT1}{\textendash}

```

Using the ligatures helps with OT1 fonts that have `\textexclamdown` and `\textquestiondown` in unusual positions.

```

433 %\DeclareTextSymbol{\textexclamdown}{OT1}{60}

```

```

434 %\DeclareTextSymbol{\textquestiondown}{OT1}{62}
435 \DeclareTextCommand{\textexclamdown}{OT1}{!'}
436 \DeclareTextCommand{\textquestiondown}{OT1}{?' }
437 %\DeclareTextSymbol{\textthyphenchar}{OT1}{'\-}
438 %\DeclareTextSymbol{\textthyphen}{OT1}{'\-}
439 \DeclareTextSymbol{\textquotedblleft}{OT1}{92}
440 \DeclareTextSymbol{\textquotedblright}{OT1}{'\"}
441 \DeclareTextSymbol{\textquoteleft}{OT1}{'\'}
442 \DeclareTextSymbol{\textquoteright}{OT1}{'\'}

```

Some symbols which are faked from others:

```

443 % \DeclareTextCommand{\aa}{OT1}
444 %   {\accent23a}
445 \DeclareTextCommand{\L}{OT1}
446   {\leavevmode\setbox\z@\hbox{L}\hb@xt@\wd\z@{\hss\@xxxii L}}
447 \DeclareTextCommand{\l}{OT1}
448   {\hmode\bgroup\@xxxii l\egroup}
449 % \DeclareTextCommand{\AA}{OT1}
450 %   {\leavevmode\setbox\z@\hbox{h}\dimen@ht\z@\advance\dimen@-1ex%
451 %     \rlap{\raise.67\dimen@\hbox{\char23}}A}

```

In the OT1 encoding Å has a hand-crafted definition, so we have here the first recorded explicit use of `\DeclareTextCompositeCommand`.

```

452 \DeclareTextCompositeCommand{\r}{OT1}{A}
453   {\leavevmode\setbox\z@\hbox{!}\dimen@ht\z@\advance\dimen@-1ex%
454   \rlap{\raise.67\dimen@\hbox{\char23}}A}

```

The dutch language uses the letter ‘ij’. It is available in T1 encoded fonts, but not in the OT1 encoded fonts. Therefore we fake it for the OT1 encoding.

```

455 \DeclareTextCommand{\ij}{OT1}{%
456   \nobreak\hskip\z@skip i\kern-0.02em\nobreak\hskip\z@skip j}
457 \DeclareTextCommand{\IJ}{OT1}{%
458   \nobreak\hskip\z@skip I\kern-0.02em\nobreak\hskip\z@skip J}

```

In the OT1 encoding, £ and \$ share a slot.

```

459 \DeclareTextCommand{\textdollar}{OT1}{\hmode\bgroup
460   \ifdim \fontdimen\@ne\font >\z@
461     \slshape
462   \else
463     \upshape
464   \fi
465   \char'\$\egroup}
466 \DeclareTextCommand{\textsterling}{OT1}{\hmode\bgroup
467   \ifdim \fontdimen\@ne\font >\z@
468     \itshape
469   \else
470     \fontshape{ui}\selectfont
471   \fi
472   \char'\$\egroup}

```

Here we are adding some more composite commands to the OT1 encoding. This makes the use of certain accents with i compatible with their use with the T1 encoding; this enables them to become true L<sup>A</sup>T<sub>E</sub>X internal representations. However, it will make these accents work a little less fast since a check will always be made for the existence of a composite.

```

473 \DeclareTextComposite{\.}{OT1}{i}{'\i}
474 \DeclareTextComposite{\.}{OT1}{i}{'\i}
475 \DeclareTextCompositeCommand{\'}{OT1}{i}{\@tabacckludge'\i}
476 \DeclareTextCompositeCommand{\'}{OT1}{i}{\@tabacckludge'\i}
477 \DeclareTextCompositeCommand{\^}{OT1}{i}{\^i}
478 \DeclareTextCompositeCommand{\^}{OT1}{i}{\^i}
479 \DeclareTextCompositeCommand{\^}{OT1}{i}{\^i}

T1 encoding is given more extensive set of overloads for \c But here we just adjust
\c{g}.

480 \ifx\textcommaabove\undefined\else
481 \DeclareTextCompositeCommand{\c}{OT1}{g}{\textcommaabove{g}}
482 \fi
483 \end{OT1}

```

## 1.6 Definitions for the T1 encoding

The definitions for the ‘Extended T<sub>E</sub>X text’ (T1) encoding.

Declare the encoding.

```

484 \*T1
485 \DeclareFontEncoding{T1}{}{}
486 \DeclareFontSubstitution{T1}{cmr}{m}{n}

```

Declare the accents.

```

487 \DeclareTextAccent{\'}{T1}{0}
488 \DeclareTextAccent{\'}{T1}{1}
489 \DeclareTextAccent{\^}{T1}{2}
490 \DeclareTextAccent{\^}{T1}{3}
491 \DeclareTextAccent{\^}{T1}{4}
492 \DeclareTextAccent{\^}{T1}{5}
493 \DeclareTextAccent{\^}{T1}{6}
494 \DeclareTextAccent{\^}{T1}{7}
495 \DeclareTextAccent{\^}{T1}{8}
496 \DeclareTextAccent{\^}{T1}{9}
497 \DeclareTextAccent{\^}{T1}{10}

```

Some accents have to be built by hand. Note that \ooalign and \o@lign must be inside a group. In these definitions we no longer use the helper function \sh@ft from plain.tex since that now has two incompatible definitions.

```

498 \DeclareTextCommand{\b}{T1}[1]
499   {\hmode\bgroup\o@lign{\relax#1\cr\hidewidth\ltx@sh@ft{-3ex}%
500    \vbox to.2ex{\hbox{\char9}\vss}\hidewidth}\egroup}
501 \DeclareTextCommand{\c}{T1}[1]
502   {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent11 #1%
503    \else\ooalign{\unhbox\z@\cr
504     \hidewidth\char11\hidewidth}\fi}
505 \DeclareTextCommand{\d}{T1}[1]
506   {\hmode\bgroup
507    \o@lign{\relax#1\cr\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}
508 \DeclareTextCommand{\k}{T1}[1]
509   {\hmode\bgroup\ooalign{\null#1\cr\hidewidth\char12}\egroup}
510 \DeclareTextCommand{\textogonekcentered}{T1}[1]
511   {\hmode\bgroup\ooalign{%
512    \null#1\cr\hidewidth\char12\hidewidth}\egroup}

```

Some symbols are constructed.

Slot 24 contains a small circle intended for construction of these two glyphs.

```

513 \DeclareTextCommand{\textperthousand}{T1}
514   {\%\char 24 }           % space or ‘relax as delimiter?
515 \DeclareTextCommand{\textpertenthousand}{T1}
516   {\%\char 24\char 24 } % space or ‘relax as delimiter?

```

For Maltese, \Hwithstroke and \hwithstroke are needed.

```

517 \DeclareTextCommand{\Hwithstroke}{T1}
518   {%
519     \hmode\bgroup
520     \vphantom{H}%
521     \sbox\z@{H}%
522     \oalign{%
523       H\cr
524       \hidewidth
525       \vrule
526         height \dimexpr 0.7\ht\z@+0.1ex\relax
527         depth  -0.7\ht\z@
528         width   0.8\wd\z@
529       \hidewidth\cr
530     }%
531   \egroup
532 }
533 \DeclareTextCommand{\hwithstroke}{T1}
534   {%
535     \hmode\bgroup
536     \vphantom{h}%
537     \sbox\z@{h}%
538     \oalign{%
539       h\cr
540       \kern0.075\wd\z@
541       \vrule
542         height \dimexpr 0.7\ht\z@+0.1ex\relax
543         depth  -0.7\ht\z@
544         width   0.4\wd\z@
545       \hidewidth\cr
546     }%
547   \egroup
548 }

```

Declare the text symbols.

```

549 %\DeclareTextSymbol{\AA}{T1}{197}
550 \DeclareTextSymbol{\AE}{T1}{198}
551 \DeclareTextSymbol{\DH}{T1}{208}
552 \DeclareTextSymbol{\DJ}{T1}{208}
553 \DeclareTextSymbol{\L}{T1}{138}
554 \DeclareTextSymbol{\NG}{T1}{141}
555 \DeclareTextSymbol{\OE}{T1}{215}
556 \DeclareTextSymbol{\O}{T1}{216}
557 \DeclareTextSymbol{\SS}{T1}{223}
558 \DeclareTextSymbol{\TH}{T1}{222}
559 %\DeclareTextSymbol{\aa}{T1}{229}
560 \DeclareTextSymbol{\ae}{T1}{230}

```

```

561 \DeclareTextSymbol{\dh}{T1}{240}
562 \DeclareTextSymbol{\dj}{T1}{158}

563 \DeclareTextSymbol{\guillemetleft}{T1}{19}
564 \DeclareTextSymbol{\guillemetright}{T1}{20}
565 % old Adobe names
566 \DeclareTextSymbol{\guillemotleft}{T1}{19}
567 \DeclareTextSymbol{\guillemotright}{T1}{20}

568 \DeclareTextSymbol{\guilsinglleft}{T1}{14}
569 \DeclareTextSymbol{\guilsinglright}{T1}{15}
570 \DeclareTextSymbol{\i}{T1}{25}
571 \DeclareTextSymbol{\j}{T1}{26}
572 \DeclareTextSymbol{\ij}{T1}{188}
573 \DeclareTextSymbol{\IJ}{T1}{156}
574 \DeclareTextSymbol{\l}{T1}{170}
575 \DeclareTextSymbol{\ng}{T1}{173}
576 \DeclareTextSymbol{\oe}{T1}{247}
577 \DeclareTextSymbol{\o}{T1}{248}
578 \DeclareTextSymbol{\quotedblbase}{T1}{18}
579 \DeclareTextSymbol{\quotesinglbase}{T1}{13}
580 \DeclareTextSymbol{\ss}{T1}{255}
581 \DeclareTextSymbol{\textasciicircum}{T1}{'\^}
582 \DeclareTextSymbol{\textasciitilde}{T1}{'\~}
583 \DeclareTextSymbol{\textbackslash}{T1}{'\'}
584 \DeclareTextSymbol{\textbar}{T1}{'|}
585 \DeclareTextSymbol{\textbraceleft}{T1}{'\{ }
586 \DeclareTextSymbol{\textbraceright}{T1}{'\} }
587 \DeclareTextSymbol{\textcompwordmark}{T1}{23}
588 \DeclareTextSymbol{\textdollar}{T1}{'\$}
589 \DeclareTextSymbol{\textendash}{T1}{22}
590 \DeclareTextSymbol{\textendash}{T1}{21}

```

The `\nobreak\hskip\z@` is there to prevent a break after the hyphen but allow later breaks in the remainder of the word.

```

591 \DeclareTextCommand{\textnonbreakinghyphen}{T1}{\mbox{-}\nobreak\hskip\z@}
592 \DeclareTextCommand{\textfiguredash}{T1}{\textendash}
593 \DeclareTextCommand{\texthorizontalbar}{T1}{\textemdash}

594 \DeclareTextSymbol{\textexclamdown}{T1}{189}
595 \DeclareTextSymbol{\textgreater}{T1}{'\>}
596 %\DeclareTextSymbol{\textthyphenchar}{T1}{127}
597 %\DeclareTextSymbol{\textthyphen}{T1}{'\-}
598 \DeclareTextSymbol{\textless}{T1}{'\<}
599 \DeclareTextSymbol{\textquestiondown}{T1}{190}
600 \DeclareTextSymbol{\textquotedblleft}{T1}{16}
601 \DeclareTextSymbol{\textquotedblright}{T1}{17}
602 \DeclareTextSymbol{\textquotedbl}{T1}{'\'}
603 \DeclareTextSymbol{\textquoteleft}{T1}{'\'}
604 \DeclareTextSymbol{\textquoteright}{T1}{'\'}
605 \DeclareTextSymbol{\textsection}{T1}{159}
606 \DeclareTextSymbol{\textsterling}{T1}{191}
607 \DeclareTextSymbol{\textunderscore}{T1}{95}
608 \DeclareTextSymbol{\textvisiblespace}{T1}{32}
609 \DeclareTextSymbol{\th}{T1}{254}

```

Declare the composites.

```

610 \DeclareTextComposite{\.}{T1}{i}{'\i}
611 \DeclareTextComposite{\.}{T1}{\i}{'\i}
"80 = 128
612 \DeclareTextComposite{\u}{T1}{A}{128}
613 \DeclareTextComposite{\k}{T1}{A}{129}
614 \DeclareTextComposite{\'}{T1}{C}{130}
615 \DeclareTextComposite{\v}{T1}{C}{131}
616 \DeclareTextComposite{\v}{T1}{D}{132}
617 \DeclareTextComposite{\v}{T1}{E}{133}
618 \DeclareTextComposite{\k}{T1}{E}{134}
619 \DeclareTextComposite{\u}{T1}{G}{135}
"88 = 136
620 \DeclareTextComposite{\'}{T1}{L}{136}
621 \DeclareTextComposite{\v}{T1}{L}{137}
622 \DeclareTextComposite{\'}{T1}{N}{139}
623 \DeclareTextComposite{\v}{T1}{N}{140}
624 \DeclareTextComposite{\H}{T1}{O}{142}
625 \DeclareTextComposite{\'}{T1}{R}{143}
"90 = 144
626 \DeclareTextComposite{\v}{T1}{R}{144}
627 \DeclareTextComposite{\'}{T1}{S}{145}
628 \DeclareTextComposite{\v}{T1}{S}{146}
629 \DeclareTextComposite{\c}{T1}{S}{147}
630 \DeclareTextComposite{\v}{T1}{T}{148}
631 \DeclareTextComposite{\c}{T1}{T}{149}
632 \DeclareTextComposite{\H}{T1}{U}{150}
633 \DeclareTextComposite{\r}{T1}{U}{151}
"98 = 152
634 \DeclareTextComposite{\"}{T1}{Y}{152}
635 \DeclareTextComposite{\'}{T1}{Z}{153}
636 \DeclareTextComposite{\v}{T1}{Z}{154}
637 \DeclareTextComposite{\.}{T1}{Z}{155}
638 \DeclareTextComposite{\.}{T1}{I}{157}
"A0 = 160
639 \DeclareTextComposite{\u}{T1}{a}{160}
640 \DeclareTextComposite{\k}{T1}{a}{161}
641 \DeclareTextComposite{\'}{T1}{c}{162}
642 \DeclareTextComposite{\v}{T1}{c}{163}
643 \DeclareTextComposite{\v}{T1}{d}{164}
644 \DeclareTextComposite{\v}{T1}{e}{165}
645 \DeclareTextComposite{\k}{T1}{e}{166}
646 \DeclareTextComposite{\u}{T1}{g}{167}
"A8 = 168
647 \DeclareTextComposite{\'}{T1}{l}{168}
648 \DeclareTextComposite{\v}{T1}{l}{169}
649 \DeclareTextComposite{\'}{T1}{n}{171}
650 \DeclareTextComposite{\v}{T1}{n}{172}
651 \DeclareTextComposite{\H}{T1}{o}{174}
652 \DeclareTextComposite{\'}{T1}{r}{175}

```

```

"B0 = 176
653 \DeclareTextComposite{\v}{T1}{r}{176}
654 \DeclareTextComposite{\'}{T1}{s}{177}
655 \DeclareTextComposite{\v}{T1}{s}{178}
656 \DeclareTextComposite{\c}{T1}{s}{179}
657 \DeclareTextComposite{\v}{T1}{t}{180}
658 \DeclareTextComposite{\c}{T1}{t}{181}
659 \DeclareTextComposite{\H}{T1}{u}{182}
660 \DeclareTextComposite{\r}{T1}{u}{183}
"B8 = 184
661 \DeclareTextComposite{\}{T1}{y}{184}
662 \DeclareTextComposite{\'}{T1}{z}{185}
663 \DeclareTextComposite{\v}{T1}{z}{186}
664 \DeclareTextComposite{\.}{T1}{z}{187}
"C0 = 192
665 \DeclareTextComposite{\'}{T1}{A}{192}
666 \DeclareTextComposite{\'}{T1}{A}{193}
667 \DeclareTextComposite{\^}{T1}{A}{194}
668 \DeclareTextComposite{\~}{T1}{A}{195}
669 \DeclareTextComposite{\}{T1}{A}{196}
670 \DeclareTextComposite{\r}{T1}{A}{197}
671 \DeclareTextComposite{\c}{T1}{C}{199}
"C8 = 200
672 \DeclareTextComposite{\'}{T1}{E}{200}
673 \DeclareTextComposite{\'}{T1}{E}{201}
674 \DeclareTextComposite{\^}{T1}{E}{202}
675 \DeclareTextComposite{\}{T1}{E}{203}
676 \DeclareTextComposite{\'}{T1}{I}{204}
677 \DeclareTextComposite{\'}{T1}{I}{205}
678 \DeclareTextComposite{\^}{T1}{I}{206}
679 \DeclareTextComposite{\}{T1}{I}{207}
"D0 = 208
680 \DeclareTextComposite{\~}{T1}{N}{209}
681 \DeclareTextComposite{\'}{T1}{O}{210}
682 \DeclareTextComposite{\'}{T1}{O}{211}
683 \DeclareTextComposite{\^}{T1}{O}{212}
684 \DeclareTextComposite{\~}{T1}{O}{213}
685 \DeclareTextComposite{\}{T1}{O}{214}
"D8 = 216
686 \DeclareTextComposite{\'}{T1}{U}{217}
687 \DeclareTextComposite{\'}{T1}{U}{218}
688 \DeclareTextComposite{\^}{T1}{U}{219}
689 \DeclareTextComposite{\}{T1}{U}{220}
690 \DeclareTextComposite{\'}{T1}{Y}{221}
"E0 = 224
691 \DeclareTextComposite{\'}{T1}{a}{224}
692 \DeclareTextComposite{\'}{T1}{a}{225}
693 \DeclareTextComposite{\^}{T1}{a}{226}
694 \DeclareTextComposite{\~}{T1}{a}{227}
695 \DeclareTextComposite{\}{T1}{a}{228}

```

```

696 \DeclareTextComposite{\r}{T1}{a}{229}
697 \DeclareTextComposite{\c}{T1}{c}{231}
"E8 = 232
698 \DeclareTextComposite{\'}{T1}{e}{232}
699 \DeclareTextComposite{\'}{T1}{e}{233}
700 \DeclareTextComposite{\^}{T1}{e}{234}
701 \DeclareTextComposite{\"}{T1}{e}{235}
702 \DeclareTextComposite{\'}{T1}{i}{236}
703 \DeclareTextComposite{\'}{T1}{i}{236}
704 \DeclareTextComposite{\'}{T1}{i}{237}
705 \DeclareTextComposite{\'}{T1}{i}{237}
706 \DeclareTextComposite{\^}{T1}{i}{238}
707 \DeclareTextComposite{\^}{T1}{i}{238}
708 \DeclareTextComposite{\"}{T1}{i}{239}
709 \DeclareTextComposite{\"}{T1}{i}{239}
"F0 = 240
710 \DeclareTextComposite{\~}{T1}{n}{241}
711 \DeclareTextComposite{\'}{T1}{o}{242}
712 \DeclareTextComposite{\'}{T1}{o}{243}
713 \DeclareTextComposite{\^}{T1}{o}{244}
714 \DeclareTextComposite{\~}{T1}{o}{245}
715 \DeclareTextComposite{\"}{T1}{o}{246}
"F8 = 248
716 \DeclareTextComposite{\'}{T1}{u}{249}
717 \DeclareTextComposite{\'}{T1}{u}{250}
718 \DeclareTextComposite{\^}{T1}{u}{251}
719 \DeclareTextComposite{\"}{T1}{u}{252}
720 \DeclareTextComposite{\'}{T1}{y}{253}

721 \DeclareTextCompositeCommand{\k}{T1}{o}{\textogonekcentered{o}}
722 \DeclareTextCompositeCommand{\k}{T1}{0}{\textogonekcentered{0}}

723 \ifx\textcommaabove\undefined\else
724 \DeclareTextCompositeCommand{\c}{T1}{g}{\textcommaabove{g}}
725 \fi
726 \ifx\textcommabelow\undefined\else
727 \DeclareTextCompositeCommand{\c}{T1}{G}{\textcommabelow{G}}
728 \DeclareTextCompositeCommand{\c}{T1}{K}{\textcommabelow{K}}
729 \DeclareTextCompositeCommand{\c}{T1}{k}{\textcommabelow{k}}
730 \DeclareTextCompositeCommand{\c}{T1}{L}{\textcommabelow{L}}
731 \DeclareTextCompositeCommand{\c}{T1}{l}{\textcommabelow{l}}
732 \DeclareTextCompositeCommand{\c}{T1}{N}{\textcommabelow{N}}
733 \DeclareTextCompositeCommand{\c}{T1}{n}{\textcommabelow{n}}
734 \DeclareTextCompositeCommand{\c}{T1}{R}{\textcommabelow{R}}
735 \DeclareTextCompositeCommand{\c}{T1}{r}{\textcommabelow{r}}
736 \fi

One oddity.
737 \DeclareTextCompositeCommand{\=}{T1}{i}{\=i}
738 \end{T1}

```

## 1.7 Definitions for the OMS encoding

The definitions for the ‘ $\TeX$  math symbol’ (OMS) encoding. Even though this is meant to be a math font, it includes some of the standard  $\LaTeX$  text symbols.

Declare the encoding.

```
739 ⟨*OMS⟩
740 \DeclareFontEncoding{OMS}{-}{-}

Declare the symbols. Note that slot 13 has in places been named \Orb: please root
out and destroy this impolity wherever you find it!

741 \DeclareTextSymbol{\textasteriskcentered}{OMS}{3} % "03
742 \DeclareTextSymbol{\textbackslash}{OMS}{110} % "6E
743 \DeclareTextSymbol{\textbar}{OMS}{106} % "6A
744 \DeclareTextSymbol{\textbardbl}{OMS}{107} % "6B
745 \DeclareTextSymbol{\textbraceleft}{OMS}{102} % "66
746 \DeclareTextSymbol{\textbraceright}{OMS}{103} % "67
747 \DeclareTextSymbol{\textbullet}{OMS}{15} % "0F
748 \DeclareTextSymbol{\textdaggerdbl}{OMS}{122} % "7A
749 \DeclareTextSymbol{\textdagger}{OMS}{121} % "79
750 \DeclareTextSymbol{\textparagraph}{OMS}{123} % "7B
751 \DeclareTextSymbol{\textperiodcentered}{OMS}{1} % "01
752 \DeclareTextSymbol{\textsection}{OMS}{120} % "78
753 \DeclareTextSymbol{\textbigcircle}{OMS}{13} % "0D
754 \DeclareTextCommand{\textcircled}{OMS}[1]{\hmode@bgroup
755 \oalign{%
756 \hfil \raise .07ex\hbox {\upshape#1}\hfil \crcr
757 \char 13 % "0D
758 }%
759 \egroup}
760 ⟨/OMS⟩
```

## 1.8 Definitions for the OML encoding

The definitions for the ‘ $\TeX$  math italic’ (OML) encoding. Even though this is meant to be a math font, it includes some of the standard  $\LaTeX$  text symbols.

Declare the encoding.

```
761 ⟨*OML⟩
762 \DeclareFontEncoding{OML}{-}{-}

Declare the symbols.

763 \DeclareTextSymbol{\textless}{OML}{‘\<}
764 \DeclareTextSymbol{\textgreater}{OML}{‘\>}
765 \DeclareTextAccent{\t}{OML}{127} % "7F
766 ⟨/OML⟩
```

## 1.9 Definitions for the OT4 encoding

These definitions are for the Polish extension to the ‘ $\TeX$  text’ (OT1) encoding. This encoding was created by B. Jackowski and M. Ryćko for use with the Polish version of Computer Modern and Computer Concrete. In positions 0–127 it is identical to OT1 but it contains some additional characters in the upper half. The  $\LaTeX$  support was developed by Mariusz Olko.

The PL fonts that use it are available as follows:  
 Metafont sources <ftp://ftp.gust.org.pl/TeX/language/polish/pl-mf.zip>;  
 Font files <ftp://ftp.gust.org.pl/TeX/language/polish/pl-tfm.zip>.  
 Declare the encoding.

```

767 <*OT4>
768 \DeclareFontEncoding{OT4}{-}{-}
769 \DeclareFontSubstitution{OT4}{cmr}{m}{n}

```

Declare the accents.

```

770 \DeclareTextAccent{"}{OT4}{127}
771 \DeclareTextAccent{'}{OT4}{19}
772 \DeclareTextAccent{.}{OT4}{95}
773 \DeclareTextAccent{=}{OT4}{22}
774 \DeclareTextAccent{^}{OT4}{94}
775 \DeclareTextAccent{\'}{OT4}{18}
776 \DeclareTextAccent{\~}{OT4}{126}
777 \DeclareTextAccent{\H}{OT4}{125}
778 \DeclareTextAccent{\u}{OT4}{21}
779 \DeclareTextAccent{\v}{OT4}{20}
780 \DeclareTextAccent{\r}{OT4}{23}

```

The ogonek accent is available only under a e A & E. But we have to provide some definition for \k. Some other accents have to be built by hand as in OT1:

```

781 \DeclareTextCommand{\k}{OT4}[1]{%
782   \TextSymbolUnavailable{\k{#1}}#1}

```

In these definitions we no longer use the helper function \sh@ft from plain.tex since that now has two incompatible definitions.

```

783 \DeclareTextCommand{\b}{OT4}[1]
784   {\hmode\bgroup\o@lign{\relax#1\cr cr\hidewidth\ltx@sh@ft{-3ex}%
785     \vbox to.2ex{\hbox{\char22}\vss}\hidewidth}\egroup}
786 \DeclareTextCommand{\c}{OT4}[1]
787   {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent24 #1%
788     \else\o@lign{\unhbox\z@\cr cr\hidewidth\char24\hidewidth}\fi}
789 \DeclareTextCommand{\d}{OT4}[1]
790   {\hmode\bgroup
791     \o@lign{\relax#1\cr cr\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}

```

Declare the text symbols.

```

792 \DeclareTextSymbol{\AE}{OT4}{29}
793 \DeclareTextSymbol{\OE}{OT4}{30}
794 \DeclareTextSymbol{\O}{OT4}{31}
795 \DeclareTextSymbol{\L}{OT4}{138}
796 \DeclareTextSymbol{\ae}{OT4}{26}

797 \DeclareTextSymbol{\guillemetleft}{OT4}{174}
798 \DeclareTextSymbol{\guillemetright}{OT4}{175}
799 % old Adobe names
800 \DeclareTextSymbol{\guillemotleft}{OT4}{174}
801 \DeclareTextSymbol{\guillemotright}{OT4}{175}

802 \DeclareTextSymbol{\i}{OT4}{16}
803 \DeclareTextSymbol{\j}{OT4}{17}
804 \DeclareTextSymbol{\l}{OT4}{170}
805 \DeclareTextSymbol{\o}{OT4}{28}
806 \DeclareTextSymbol{\oe}{OT4}{27}

```

```

807 \DeclareTextSymbol{\quotedblbase}{OT4}{255}
808 \DeclareTextSymbol{\ss}{OT4}{25}
809 \DeclareTextSymbol{\textemdash}{OT4}{124}
810 \DeclareTextSymbol{\textendash}{OT4}{123}
811 \DeclareTextSymbol{\textexclamdown}{OT4}{60}
812 %\DeclareTextSymbol{\textthyphenchar}{OT4}{'\-}
813 %\DeclareTextSymbol{\textthyphen}{OT4}{'\-}
814 \DeclareTextSymbol{\textquestiondown}{OT4}{62}
815 \DeclareTextSymbol{\textquotedblleft}{OT4}{92}
816 \DeclareTextSymbol{\textquotedblright}{OT4}{'\'}
817 \DeclareTextSymbol{\textquoteleft}{OT4}{'\'}
818 \DeclareTextSymbol{\textquoteright}{OT4}{'\'}

```

Definition for Å as in OT1:

```

819 \DeclareTextCompositeCommand{\r}{OT4}{A}
820   {\leavevmode\setbox\z@\hbox{!}\dimen@ht\z@\advance\dimen@-1ex%
821     \rlap{\raise.67\dimen@\hbox{\char23}}A}

```

In the OT4 encoding, £ and \$ share a slot.

```

822 \DeclareTextCommand{\textdollar}{OT4}{\hmode@bgroup
823   \ifdim \fontdimen\@ne\font >\z@
824     \slshape
825   \else
826     \upshape
827   \fi
828   \char'\$ \egroup}
829 \DeclareTextCommand{\textsterling}{OT4}{\hmode@bgroup
830   \ifdim \fontdimen\@ne\font >\z@
831     \itshape
832   \else
833     \fontshape{ui}\selectfont
834   \fi
835   \char'\$ \egroup}

```

Declare the composites.

```

836 \DeclareTextComposite{\k}{OT4}{A}{129}
837 \DeclareTextComposite{\'}{OT4}{C}{130}
838 \DeclareTextComposite{\k}{OT4}{E}{134}
839 \DeclareTextComposite{\'}{OT4}{N}{139}
840 \DeclareTextComposite{\'}{OT4}{S}{145}
841 \DeclareTextComposite{\'}{OT4}{Z}{153}
842 \DeclareTextComposite{\.}{OT4}{Z}{155}
843 \DeclareTextComposite{\k}{OT4}{a}{161}
844 \DeclareTextComposite{\'}{OT4}{c}{162}
845 \DeclareTextComposite{\k}{OT4}{e}{166}
846 \DeclareTextComposite{\'}{OT4}{n}{171}
847 \DeclareTextComposite{\'}{OT4}{s}{177}
848 \DeclareTextComposite{\'}{OT4}{z}{185}
849 \DeclareTextComposite{\.}{OT4}{z}{187}
850 \DeclareTextComposite{\'}{OT4}{0}{211}
851 \DeclareTextComposite{\'}{OT4}{o}{243}
852 </OT4>

```

## 1.10 Definitions for the TS1 encoding

```
853 <*TS1>
854 \DeclareFontEncoding{TS1}{-}{-}
855 \DeclareFontSubstitution{TS1}{cmr}{m}{n}
```

Some accents have to be built by hand. Note that `\ooalign` and `\o@lign` must be inside a group.

```
856 \DeclareTextCommand{\capitalcedilla}{TS1}[1]
857   {\hmode\bgroup
858     \ooalign{\null#1\crrc\hidewidth\char11\hidewidth}\egroup}
859 \DeclareTextCommand{\capitalogonek}{TS1}[1]
860   {\hmode\bgroup
861     \ooalign{\null#1\crrc\hidewidth\char12\hidewidth}\egroup}
```

Accents for capital letters.

These commands can be used by the end user either directly or through definitions of the type

```
\DeclareTextCompositeCommand{\'}{T1}{X}{\capitalacute X}
```

None of the latter definitions are provided by default, since they are probably rarely used.

"00 = 0

```
862 \DeclareTextAccent{\capitalgrave}{TS1}{0}
863 \DeclareTextAccent{\capitalacute}{TS1}{1}
864 \DeclareTextAccent{\capitalcircumflex}{TS1}{2}
865 \DeclareTextAccent{\capitaltilde}{TS1}{3}
866 \DeclareTextAccent{\capitaldieresis}{TS1}{4}
867 \DeclareTextAccent{\capitalhungarumlaut}{TS1}{5}
868 \DeclareTextAccent{\capitalring}{TS1}{6}
869 \DeclareTextAccent{\capitalcaron}{TS1}{7}
```

"08 = 8

```
870 \DeclareTextAccent{\capitalbreve}{TS1}{8}
871 \DeclareTextAccent{\capitalmacron}{TS1}{9}
872 \DeclareTextAccent{\capitaldotaccent}{TS1}{10}
```

Tie accents.

The tie accent was borrowed from the `cmmi` font. The `tc` fonts now provide four tie accents, the first two are done in the classical way with asymmetric glyphs hanging out of their boxes; the new ties are centered in their boxes like all other accents. They need a name: please tell us if you know what to call them.

" =

```
873 \DeclareTextAccent{\t}{TS1}{26}
874 \DeclareTextAccent{\capitaltie}{TS1}{27}
875 \DeclareTextAccent{\newtie}{TS1}{28}
876 \DeclareTextAccent{\capitalnewtie}{TS1}{29}
```

Compound word marks.

The text companion fonts contain two compound word marks of different heights, one has `cap_height`, the other `asc_height`.

```
877 \DeclareTextSymbol{\textcapitalcompwordmark}{TS1}{23}
878 \DeclareTextSymbol{\textascendercompwordmark}{TS1}{31}
```

The text companion symbols.

```
879 \DeclareTextSymbol{\textquotestraightbase}{TS1}{13}
```

"10 = 16

```
880 \DeclareTextSymbol{\textquotestraightdblbase}{TS1}{18}
881 \DeclareTextSymbol{\texttwelveudash}{TS1}{21}
882 \DeclareTextSymbol{\textthreequartersemdash}{TS1}{22}
```

"18 = 24

```
883 \DeclareTextSymbol{\textleftarrow}{TS1}{24}
884 \DeclareTextSymbol{\textrightarrow}{TS1}{25}
```

"20 = 32

```
885 \DeclareTextSymbol{\textblank}{TS1}{32}
886 \DeclareTextSymbol{\textdollar}{TS1}{36}
887 \DeclareTextSymbol{\textquotesingle}{TS1}{39}
```

"28 = 40

The symbol `\textasteriskcentered` “\*” is supposed to be always available in TS1 and that is important as it is used in footnote symbols. However, in a few fonts it is missing even though they are otherwise fairly complete. We therefore use a rather elaborate method and check if the slot has a glyph and if not produce a poor man’s version by using a normal “\*” slightly enlarged and somewhat lowered. The main application for this symbol is in footnote symbols and there it should produce a comparable size and show a similar placement.

```
888 %\DeclareTextSymbol{\textasteriskcentered}{TS1}{42} % that’s wanted
889 \DeclareTextCommand \textasteriskcentered{TS1}{%    % and that’s needed
890   \iffontchar\font 42 \char42 \else
891   \begingroup\fontencoding{T1}%
892     \fontsize
893     {\the\dimexpr1.3\dimexpr\fontsize pt\relax}%
894     {\f@baselineskip}%
895     \selectfont
896     \raisebox{-0.7ex}{\dimexpr\height-0.7ex}[0pt]{*}%
897   \endgroup
898   \fi
899 }
```

Note that ’054 is a comma and ’056 is a full stop: these make numbers using oldstyle digits easier to input.

```
900 \DeclareTextSymbol{\textdblhyphen}{TS1}{45}
901 \DeclareTextSymbol{\textfractionsolidus}{TS1}{47}
```

Oldstyle digits.

"30 = 48

```
902 \DeclareTextSymbol{\textzerooldstyle}{TS1}{48}
903 \DeclareTextSymbol{\textoneoldstyle}{TS1}{49}
904 \DeclareTextSymbol{\texttwooldstyle}{TS1}{50}
905 \DeclareTextSymbol{\textthreeoldstyle}{TS1}{51}
906 \DeclareTextSymbol{\textfouroldstyle}{TS1}{52}
907 \DeclareTextSymbol{\textfiveoldstyle}{TS1}{53}
908 \DeclareTextSymbol{\textsixoldstyle}{TS1}{54}
909 \DeclareTextSymbol{\textsevenoldstyle}{TS1}{55}
```

"38 = 56

```
910 \DeclareTextSymbol{\teightoldstyle}{TS1}{56}
911 \DeclareTextSymbol{\textnineoldstyle}{TS1}{57}
```

More text companion symbols.

```
912 \DeclareTextSymbol{\textlangle}{TS1}{60}
913 \DeclareTextSymbol{\textminus}{TS1}{61}
914 \DeclareTextSymbol{\textrangle}{TS1}{62}
```

"48 = 72

```
915 \DeclareTextSymbol{\textmho}{TS1}{77}
```

The big circle is here to define the command `\textcircled`. Formerly it was taken from the `cmsy` font.

```
916 \DeclareTextSymbol{\textbigcircle}{TS1}{79}
917 \DeclareTextCommand{\textcircled}{TS1}[1]{\hmode\bgroup
918   \oalign{%
919     \hfil \raise .07ex\hbox {\upshape#1}\hfil \crcr
920     \char 79   % '117 = "4F
921   }%
922 \egroup}
```

More text companion symbols.

"50 = 80

```
923 \DeclareTextSymbol{\textohm}{TS1}{87}
```

"58 = 88

```
924 \DeclareTextSymbol{\textlbrackdbl}{TS1}{91}
925 \DeclareTextSymbol{\textrbrackdbl}{TS1}{93}
926 \DeclareTextSymbol{\textuparrow}{TS1}{94}
927 \DeclareTextSymbol{\textdownarrow}{TS1}{95}
```

"60 = 96

```
928 \DeclareTextSymbol{\textasciigrave}{TS1}{96}
929 \DeclareTextSymbol{\textborn}{TS1}{98}
930 \DeclareTextSymbol{\textdivorced}{TS1}{99}
931 \DeclareTextSymbol{\textdied}{TS1}{100}
```

"68 = 104

```
932 \DeclareTextSymbol{\textleaf}{TS1}{108}
933 \DeclareTextSymbol{\textmarried}{TS1}{109}
934 \DeclareTextSymbol{\textmusicalnote}{TS1}{110}
```

"78 = 120

```
935 \DeclareTextSymbol{\texttildebelow}{TS1}{126}
```

This glyph, `\textdblhyphenchar` is hanging, like the `hyphenchar` of the `ec` fonts.

```
936 \DeclareTextSymbol{\textdblhyphenchar}{TS1}{127}
```

"80 = 128

```
937 \DeclareTextSymbol{\textasciibreve}{TS1}{128}
938 \DeclareTextSymbol{\textasciicaron}{TS1}{129}
```

This next glyph is *not* the same as `\textquotedbl`.

```
939 \DeclareTextSymbol{\textacutedbl}{TS1}{130}
940 \DeclareTextSymbol{\textgravedbl}{TS1}{131}
941 \DeclareTextSymbol{\textdagger}{TS1}{132}
942 \DeclareTextSymbol{\textdaggerdbl}{TS1}{133}
943 \DeclareTextSymbol{\textbardbl}{TS1}{134}
944 \DeclareTextSymbol{\textperthousand}{TS1}{135}
```

"88 = 136

```
945 \DeclareTextSymbol{\textbullet}{TS1}{136}
946 \DeclareTextSymbol{\textcelsius}{TS1}{137}
947 \DeclareTextSymbol{\textdollaroldstyle}{TS1}{138}
948 \DeclareTextSymbol{\textcentoldstyle}{TS1}{139}
949 \DeclareTextSymbol{\textflorin}{TS1}{140}
950 \DeclareTextSymbol{\textcolonmonetary}{TS1}{141}
951 \DeclareTextSymbol{\textwon}{TS1}{142}
952 \DeclareTextSymbol{\textnaira}{TS1}{143}
```

"90 = 144

```
953 \DeclareTextSymbol{\textguarani}{TS1}{144}
954 \DeclareTextSymbol{\textpeso}{TS1}{145}
955 \DeclareTextSymbol{\textlira}{TS1}{146}
956 \DeclareTextSymbol{\textrecipe}{TS1}{147}
957 \DeclareTextSymbol{\textinterrobang}{TS1}{148}
958 \DeclareTextSymbol{\textinterrobangdown}{TS1}{149}
959 \DeclareTextSymbol{\textdong}{TS1}{150}
960 \DeclareTextSymbol{\texttrademark}{TS1}{151}
```

"98 = 152

```
961 \DeclareTextSymbol{\textpertenthousand}{TS1}{152}
962 \DeclareTextSymbol{\textpilcrow}{TS1}{153}
963 \DeclareTextSymbol{\textbaht}{TS1}{154}
964 \DeclareTextSymbol{\textnumero}{TS1}{155}
```

This next name may change. For the following sign we know only a german name, which is abzüglich. The meaning is something like “commercial minus”. An ASCII ersatz is ./ (dot slash dot). The temporary English name is \textdiscount.

```
965 \DeclareTextSymbol{\textdiscount}{TS1}{156}
966 \DeclareTextSymbol{\textestimated}{TS1}{157}
967 \DeclareTextSymbol{\textopenbullet}{TS1}{158}
968 \DeclareTextSymbol{\textservicemark}{TS1}{159}
```

"A0 = 160

```
969 \DeclareTextSymbol{\textlquill}{TS1}{160}
970 \DeclareTextSymbol{\textrquill}{TS1}{161}
971 \DeclareTextSymbol{\textcent}{TS1}{162}
972 \DeclareTextSymbol{\textsterling}{TS1}{163}
973 \DeclareTextSymbol{\textcurrency}{TS1}{164}
974 \DeclareTextSymbol{\textyen}{TS1}{165}
975 \DeclareTextSymbol{\textbrokenbar}{TS1}{166}
976 \DeclareTextSymbol{\textsection}{TS1}{167}
```

"A8 = 168

```
977 \DeclareTextSymbol{\textasciidieresis}{TS1}{168}
978 \DeclareTextSymbol{\textcopyright}{TS1}{169}
979 \DeclareTextSymbol{\textordfeminine}{TS1}{170}
980 \DeclareTextSymbol{\textcopyleft}{TS1}{171}
981 \DeclareTextSymbol{\textlnot}{TS1}{172}
```

The meaning of the circled-P is “sound recording copyright”.

```
982 \DeclareTextSymbol{\textcircledP}{TS1}{173}
983 \DeclareTextSymbol{\textregistered}{TS1}{174}
984 \DeclareTextSymbol{\textasciimacron}{TS1}{175}
```

```

"B0 = 176
985 \DeclareTextSymbol{\textdegree}{TS1}{176}
986 \DeclareTextSymbol{\textpm}{TS1}{177}
987 \DeclareTextSymbol{\texttwosuperior}{TS1}{178}
988 \DeclareTextSymbol{\textthreesuperior}{TS1}{179}
989 \DeclareTextSymbol{\textasciicute}{TS1}{180}
990 \DeclareTextSymbol{\textmu}{TS1}{181} % micro sign
991 \DeclareTextSymbol{\textparagraph}{TS1}{182}
992 \DeclareTextSymbol{\textperiodcentered}{TS1}{183}
"B8 = 184
993 \DeclareTextSymbol{\textreferencemark}{TS1}{184}
994 \DeclareTextSymbol{\textonesuperior}{TS1}{185}
995 \DeclareTextSymbol{\textordmasculine}{TS1}{186}
996 \DeclareTextSymbol{\textsurd}{TS1}{187}
997 \DeclareTextSymbol{\textonequarter}{TS1}{188}
998 \DeclareTextSymbol{\textonehalf}{TS1}{189}
999 \DeclareTextSymbol{\textthreequarters}{TS1}{190}
1000 \DeclareTextSymbol{\texteuro}{TS1}{191}
"E0 = 208
1001 \DeclareTextSymbol{\texttimes}{TS1}{214}
"F0 = 240
1002 \DeclareTextSymbol{\textdiv}{TS1}{246}
1003 </TS1>

```

## 1.11 Definitions for the TU encoding

The TU encoding was originally introduced in the contributed package `fontspec` as a Unicode encoding for XeTeX and LuaTeX.

Normally for these engines, the input consists of Unicode characters encoded in UTF-8. There is therefore little need to use the traditional (ASCII) encoding-specific commands

However, sometimes (e.g. for backwards compatibility) it can be useful to access these Unicode characters via such ASCII-based markup. The commands provided here Cover the characters in the T1 and TS1 encodings, but specified in Unicode position. Almost all the command names have been mechanically extracted from the `inputenc` UTF-8 support, which is essentially doing a reverse mapping from UTF-8 data to L<sup>A</sup>T<sub>E</sub>X LICR commands.

A few additional names for character which were supported in the original `fontspec` version of this file have also been added, even though they are not currently in the default `inputenc` UTF-8 declarations.

```

1004 < *TU>

```

In the base interface the Unicode encoding is always known as TU But we parameterize the encoding name to allow for modelling differences in Unicode support by different fonts.

```

1005 \providecommand\UnicodeEncodingName{TU}

```

As the Unicode encoding, TU, is only currently available with XeTeX or LuaTeX, we detect these engines first, and make adjustments for the differing font loading syntax. For other engines, we issue a warning then abort this file, switching back to T1 encoding.

```

1006 \begingroup\expandafter\expandafter\expandafter\endgroup
1007 \expandafter\ifx\csname XeTeXrevision\endcsname\relax
1008 \begingroup\expandafter\expandafter\expandafter\endgroup
1009 \expandafter\ifx\csname directlua\endcsname\relax

```

Not LuaTeX or XeTeX, abort with a warning.

```

1010 \PackageWarningNoLine{fontenc}
1011   {\UnicodeEncodingName\space
1012    encoding is only available with XeTeX and LuaTeX.\MessageBreak
1013    Defaulting to T1 encoding}
1014 \def\encodingdefault{T1}
1015 \expandafter\expandafter\expandafter\endinput
1016 \else

```

LuaTeX. For LuaTeX 1.10+, define a Lua function to disable any handling by the font code. Otherwise we reload the font without TeX ligatures.

```

1017 \def\UnicodeFontTeXLigatures{+tlig;}
1018 \ifnum\luatexversion<110
1019 \def\reserved@a#1{%
1020 \def\@remove@tlig##1{\@remove@tlig@##1\@nil#1\@nil\relax}
1021 \def\@remove@tlig@##1#1{\@remove@tlig@@##1}}
1022 \edef\reserved@b{\detokenize{+tlig;}}
1023 \expandafter\reserved@a\expandafter{\reserved@b}
1024 \def\@remove@tlig@@#1\@nil#2\relax{#1}
1025 \def\remove@tlig#1{%
1026 \begingroup
1027 \font\remove@tlig
1028 \expandafter\@remove@tlig\expandafter{\fontname\font}%
1029 \remove@tlig
1030 \char#1\relax
1031 \endgroup
1032 }
1033 \else
1034 \newprotectedluacmd\@remove@tlig@@@

```

Now we can define the function. Mostly we just have to insert a protected glyph node, which is a glyph node with subtype 256. But we have to keep track of the current mode to avoid inserting the glyph into a vlist.

```

1035 \now@and@everyjob{\directlua{
1036   local rawchar_func = token.create'\@remove@tlig@@@'.index
1037   local forcehmode = tex.forcehmode
1038   local put_next = token.put_next
1039   local glyph_id = node.id'glyph'
1040   local rawchar_token = token.new(rawchar_func, token.command_id'lua_call')
1041   lua.get_functions_table()[rawchar_func] = function()
1042     local mode = tex.nest.top.mode
1043     if mode == 1 or mode == -1 then
1044       put_next(rawchar_token)
1045       return forcehmode(true)

```

```

1046         end
1047         local n = node.new(glyph_id, 256)
1048         n.font = font.current()
1049         n.char = token.scan_int()
1050         return node.write(n)
1051     end
1052 }

```

Now `\remove@tlig` can be implemented almost as in XeTeX.

```

1053     \def\remove@tlig#1{\@remove@tlig@@@#1\relax}
1054     \fi
1055     \fi
1056 \else
1057     XeTeX
1058     \def\UnicodeFontTeXLigatures{mapping=tex-text;}
1059     \def\remove@tlig#1{\XeTeXglyph\numexpr\XeTeXcharglyph#1\relax}
1060     \fi
1061 \def\UnicodeFontFile#1#2{"[#1]:#2"}
1062 \def\UnicodeFontName#1#2{"#1:#2"}
1063
1064     Declare the encoding
1065 \DeclareFontEncoding\UnicodeEncodingName{}{}
1066
1067     Declare accent command to use a postpended combining character rather than the
1068     TeX \accent primitive
1069 \def\add@unicode@accent#1#2{%
1070     \if\relax\detokenize{#2}\relax~^a0\else#2\fi
1071     \char#1\relax}

```

In its original implementation `\DeclareUnicodeAccent` was given 3 arguments (with second the “Unicode encoding” a.k.a., `\UnicodeEncodingName`) while in other places, e.g., `\DeclareUnicodeComposite`, we always made encoding implicit. So we now change it here to implicit too so that the interfaces become a bit more consistent. To avoid making that a breaking change (even though it only affects two packages on CTAN) we test for #2 being `\UnicodeEncodingName`. This would not catch if somebody used `\DeclareUnicodeAccent{=}{TU-sub}{0304}` but that fortunately hasn’t happened. With the implicit argument you would need to change `\UnicodeEncodingName` instead, as you have to do anyway for the other interface commands.

```

1066 \def\DeclareUnicodeAccent#1#2{%
1067     \edef\reserved@a{#2}%
1068     \edef\reserved@b{\UnicodeEncodingName}%
1069     \ifx\reserved@a\reserved@b
1070         \def\reserved@a{\DeclareUnicodeAccent@{#1}}%
1071     \else
1072         \def\reserved@a{\DeclareUnicodeAccent@{#1}\UnicodeEncodingName}%
1073     \fi
1074     \reserved@a{#2}%
1075 }
1076 \def\DeclareUnicodeAccent@#1#2#3{%
1077     \DeclareTextCommand{#1}{#2}{\add@unicode@accent{#3}}%
1078 }

```

Wrapper around `\DeclareTextCompositeCommand` that uses the declared composite if it exists in the current font or falls back to the default definition for the TU accent if not.

```

1079 {
1080 \catcode\z@=11\relax
1081 \gdef\DeclareUnicodeComposite#1#2#3{%
1082   \def\reserved@a##1##2{%
1083     \DeclareTextCompositeCommand#1\UnicodeEncodingName{#2}{%
1084       \iffontchar\font#3 ##2%
1085       \else ##1\fi}}%
1086   \expandafter\expandafter\expandafter\extract@default@composite
1087   \csname\UnicodeEncodingName\string#1\endcsname{#2}\@nil
1088   \bgroup
1089     \lccode\z@#3 %
1090     \lowercase{\egroup
1091       \expandafter\reserved@a\expandafter{\reserved@b}{^^@}}}%
1092   }

1093 \def\extract@default@composite#1{%
1094   \ifx\@text@composite#1%
1095     \expandafter\extract@default@composite@a
1096   \else
1097     \expandafter\extract@default@composite@b\expandafter#1%
1098   \fi}

1099 \def\extract@default@composite@a#1\@text@composite#2\@nil{%
1100   \def\reserved@b{#2}}
1101 \def\extract@default@composite@b#1#2\@nil{%
1102   \def\reserved@b{#1#2}}

```

Next two commands are simply syntactic sugar to go with the other `\DeclareUnicode...` declarations.

```

1103 \def\DeclareUnicodeSymbol#1{\DeclareTextSymbol{#1}{\UnicodeEncodingName}}
1104 \def\DeclareUnicodeCommand#1{\DeclareTextCommand{#1}{\UnicodeEncodingName}}

1105 \DeclareUnicodeCommand\textquotesingle {\remove@tlig{"0027}}
1106 \DeclareUnicodeCommand\textasciigrave {\remove@tlig{"0060}}
1107 \DeclareUnicodeCommand\textquotedbl {\remove@tlig{"0022}}

1108 \DeclareUnicodeSymbol{\textdollar} {"0024}
1109 \DeclareUnicodeSymbol{\textless} {"003C}
1110 \DeclareUnicodeSymbol{\textgreater} {"003E}
1111 \DeclareUnicodeSymbol{\textbackslash} {"005C}
1112 \DeclareUnicodeSymbol{\textasciicircum} {"005E}
1113 \DeclareUnicodeSymbol{\textunderscore} {"005F}
1114 \DeclareUnicodeSymbol{\textbraceleft} {"007B}
1115 \DeclareUnicodeSymbol{\textbar} {"007C}
1116 \DeclareUnicodeSymbol{\textbraceright} {"007D}
1117 \DeclareUnicodeSymbol{\textasciitilde} {"007E}
1118 \DeclareUnicodeSymbol{\textexclamdown} {"00A1}
1119 \DeclareUnicodeSymbol{\textcent} {"00A2}
1120 \DeclareUnicodeSymbol{\textsterling} {"00A3}
1121 \DeclareUnicodeSymbol{\textcurrency} {"00A4}
1122 \DeclareUnicodeSymbol{\textyen} {"00A5}
1123 \DeclareUnicodeSymbol{\textbrokenbar} {"00A6}
1124 \DeclareUnicodeSymbol{\textsection} {"00A7}

```

```

1125 \DeclareUnicodeSymbol{\textasciidieresis} {"00A8}
1126 \DeclareUnicodeSymbol{\textcopyright} {"00A9}
1127 \DeclareUnicodeSymbol{\textordfeminine} {"00AA}

1128 \DeclareUnicodeSymbol{\guillemetleft} {"00AB}
1129 % old Adobe name
1130 \DeclareUnicodeSymbol{\guillemotleft} {"00AB}

1131 \DeclareUnicodeSymbol{\textlnot} {"00AC}
1132 \DeclareUnicodeSymbol{\textregistered} {"00AE}
1133 \DeclareUnicodeSymbol{\textasciimacron} {"00AF}
1134 \DeclareUnicodeSymbol{\textdegree} {"00B0}
1135 \DeclareUnicodeSymbol{\textpm} {"00B1}
1136 \DeclareUnicodeSymbol{\texttwosuperior} {"00B2}
1137 \DeclareUnicodeSymbol{\textthreesuperior} {"00B3}
1138 \DeclareUnicodeSymbol{\textasciiacute} {"00B4}
1139 \DeclareUnicodeSymbol{\textmu} {"00B5}
1140 \DeclareUnicodeSymbol{\textparagraph} {"00B6}
1141 \DeclareUnicodeSymbol{\textperiodcentered} {"00B7}
1142 \DeclareUnicodeSymbol{\textonesuperior} {"00B9}
1143 \DeclareUnicodeSymbol{\textordmasculine} {"00BA}

1144 \DeclareUnicodeSymbol{\guillemetright} {"00BB}
1145 % old Adobe name
1146 \DeclareUnicodeSymbol{\guillemotright} {"00BB}

1147 \DeclareUnicodeSymbol{\textonequarter} {"00BC}
1148 \DeclareUnicodeSymbol{\textonehalf} {"00BD}
1149 \DeclareUnicodeSymbol{\textthreequarters} {"00BE}
1150 \DeclareUnicodeSymbol{\textquestiondown} {"00BF}
1151 \DeclareUnicodeSymbol{\AE} {"00C6}
1152 \DeclareUnicodeSymbol{\DH} {"00D0}
1153 \DeclareUnicodeSymbol{\texttimes} {"00D7}
1154 \DeclareUnicodeSymbol{\O} {"00D8}
1155 \DeclareUnicodeSymbol{\TH} {"00DE}
1156 \DeclareUnicodeSymbol{\ss} {"00DF}
1157 \DeclareUnicodeSymbol{\ae} {"00E6}
1158 \DeclareUnicodeSymbol{\dh} {"00F0}
1159 \DeclareUnicodeSymbol{\textdiv} {"00F7}
1160 \DeclareUnicodeSymbol{\o} {"00F8}
1161 \DeclareUnicodeSymbol{\th} {"00FE}
1162 \DeclareUnicodeSymbol{\DJ} {"0110}
1163 \DeclareUnicodeSymbol{\dj} {"0111}
1164 \DeclareUnicodeSymbol{\i} {"0131}
1165 \DeclareUnicodeSymbol{\IJ} {"0132}
1166 \DeclareUnicodeSymbol{\ij} {"0133}
1167 \DeclareUnicodeSymbol{\L} {"0141}
1168 \DeclareUnicodeSymbol{\l} {"0142}
1169 \DeclareUnicodeSymbol{\NG} {"014A}
1170 \DeclareUnicodeSymbol{\ng} {"014B}
1171 \DeclareUnicodeSymbol{\OE} {"0152}
1172 \DeclareUnicodeSymbol{\oe} {"0153}
1173 \DeclareUnicodeSymbol{\textflorin} {"0192}
1174 \DeclareUnicodeSymbol{\j} {"0237}
1175 \DeclareUnicodeSymbol{\textasciicaron} {"02C7}
1176 \DeclareUnicodeSymbol{\textasciibreve} {"02D8}

```

```

1177 \DeclareUnicodeSymbol{\textacutedbl}      {"02DD}
1178 \DeclareUnicodeSymbol{\textgravedbl}      {"02F5}
1179 \DeclareUnicodeSymbol{\texttildedbl}      {"02F7}
1180 \DeclareUnicodeSymbol{\textbaht}          {"0E3F}
1181 \DeclareUnicodeSymbol{\SS}                 {"1E9E}
1182 \DeclareUnicodeSymbol{\textcompwordmark}   {"200C}

1183 %\DeclareUnicodeSymbol{\textnonbreakinghyphen} {"2011}
1184 %\DeclareUnicodeSymbol{\textfiguredash}      {"2012}
1185 \DeclareUnicodeSymbol{\textendash}          {"2013}
1186 \DeclareUnicodeSymbol{\textemdash}          {"2014}
1187 %\DeclareUnicodeSymbol{\texthorizontalbar}    {"2015}

```

Unfortunately some fonts do not implement "2011, "2012 and/or "2015 (including the L<sup>A</sup>T<sub>E</sub>X default fonts for Unicode engines) so we provide some approximations if the glyph is missing, like we do for OT1 and T1.

The `\nobreak\hskip\z@` is there to prevent a break after the hyphen but allow later breaks in the remainder of the word.

```

1188 \DeclareUnicodeCommand{\textnonbreakinghyphen}
1189     {\iffontchar\font "2011 \char "2011 \else \mbox{-}\nobreak\hskip\z@ \fi}
1190 \DeclareUnicodeCommand{\textfiguredash}
1191     {\iffontchar\font "2012 \char "2012 \else \char "2013 \fi}
1192 \DeclareUnicodeCommand{\texthorizontalbar}
1193     {\iffontchar\font "2015 \char "2015 \else \char "2014 \fi}

1194 \DeclareUnicodeSymbol{\textbardbl}          {"2016}
1195 \DeclareUnicodeSymbol{\textquoteleft}       {"2018}
1196 \DeclareUnicodeSymbol{\textquoteright}     {"2019}
1197 \DeclareUnicodeSymbol{\quotesinglbase}      {"201A}
1198 \DeclareUnicodeSymbol{\textquotedblleft}   {"201C}
1199 \DeclareUnicodeSymbol{\textquotedblright}  {"201D}
1200 \DeclareUnicodeSymbol{\quotedblbase}       {"201E}
1201 \DeclareUnicodeSymbol{\textdagger}          {"2020}
1202 \DeclareUnicodeSymbol{\textdaggerdbl}       {"2021}
1203 \DeclareUnicodeSymbol{\textbullet}          {"2022}
1204 \DeclareUnicodeSymbol{\textellipsis}        {"2026}
1205 \DeclareUnicodeSymbol{\textperthousand}     {"2030}
1206 \DeclareUnicodeSymbol{\textpertenthousand} {"2031}
1207 \DeclareUnicodeSymbol{\guilsinglleft}      {"2039}
1208 \DeclareUnicodeSymbol{\guilsinglright}     {"203A}
1209 \DeclareUnicodeSymbol{\textreferencemark}   {"203B}
1210 \DeclareUnicodeSymbol{\textinterrobang}     {"203D}
1211 \DeclareUnicodeSymbol{\textfractionsolidus} {"2044}
1212 \DeclareUnicodeSymbol{\textlquill}         {"2045}
1213 \DeclareUnicodeSymbol{\textrquill}         {"2046}
1214 \DeclareUnicodeSymbol{\textdiscount}        {"2052}
1215 \DeclareUnicodeSymbol{\textcolonmonetary}   {"20A1}
1216 \DeclareUnicodeSymbol{\textlira}           {"20A4}
1217 \DeclareUnicodeSymbol{\textnaira}          {"20A6}
1218 \DeclareUnicodeSymbol{\textwon}            {"20A9}
1219 \DeclareUnicodeSymbol{\textdong}           {"20AB}
1220 \DeclareUnicodeSymbol{\texteuro}           {"20AC}
1221 \DeclareUnicodeSymbol{\textpeso}           {"20B1}
1222 \DeclareUnicodeSymbol{\textcelsius}        {"2103}
1223 \DeclareUnicodeSymbol{\textnumero}         {"2116}

```

```

1224 \DeclareUnicodeSymbol{\textcircledP}      {"2117}
1225 \DeclareUnicodeSymbol{\textrecipe}        {"211E}
1226 \DeclareUnicodeSymbol{\textservicemark}   {"2120}
1227 \DeclareUnicodeSymbol{\texttrademark}      {"2122}
1228 \DeclareUnicodeSymbol{\textohm}            {"2126}
1229 \DeclareUnicodeSymbol{\textmho}            {"2127}
1230 \DeclareUnicodeSymbol{\textestimated}       {"212E}
1231 \DeclareUnicodeSymbol{\textleftarrow}      {"2190}
1232 \DeclareUnicodeSymbol{\textuparrow}        {"2191}
1233 \DeclareUnicodeSymbol{\textrightarrow}     {"2192}
1234 \DeclareUnicodeSymbol{\textdownarrow}      {"2193}
1235 \DeclareUnicodeSymbol{\textminus}          {"2212}

```

1236

```

1237 \DeclareUnicodeSymbol{\Hwithstroke}        {"0126}
1238 \DeclareUnicodeSymbol{\hwithstroke}        {"0127}

```

Not all fonts have U+2217 but using U+002A requires some adjustment.

```

1239 \DeclareUnicodeCommand{\textasteriskcentered}{%
1240   \iffontchar\font"2217 \char"2217 \else
1241     \begingroup
1242       \fontsize
1243         {\the\dimexpr1.3\dimexpr\fontsize pt\relax}%
1244         {\font@baselineskip}%
1245       \selectfont
1246       \raisebox{-0.7ex}{\dimexpr\height-0.7ex}[0pt]{*}%
1247     \endgroup
1248   \fi
1249 }

```

```

1250 \DeclareUnicodeSymbol{\textsurd}            {"221A}
1251 \DeclareUnicodeSymbol{\textlangle}          {"2329}
1252 \DeclareUnicodeSymbol{\textrangle}          {"232A}
1253 \DeclareUnicodeSymbol{\textblank}           {"2422}
1254 \DeclareUnicodeSymbol{\textvisiblespace}    {"2423}
1255 \DeclareUnicodeSymbol{\textopenbullet}      {"25E6}
1256 \DeclareUnicodeSymbol{\textbigcircle}       {"25EF}
1257 \DeclareUnicodeSymbol{\textmusicalnote}     {"266A}
1258 \DeclareUnicodeSymbol{\textmarried}         {"26AD}
1259 \DeclareUnicodeSymbol{\textdivorced}        {"26AE}
1260 \DeclareUnicodeSymbol{\textinterrobangdown} {"2E18}

```

Accents must be declared before the composites that use them.

```

1261 \DeclareUnicodeAccent{\`}{0300}
1262 \DeclareUnicodeAccent{\'}{"0301}
1263 \DeclareUnicodeAccent{\~}{0302}
1264 \DeclareUnicodeAccent{\~}{0303}
1265 \DeclareUnicodeAccent{\=}{0304}
1266 \DeclareUnicodeAccent{\u}{0306}
1267 \DeclareUnicodeAccent{\.}{0307}
1268 \DeclareUnicodeAccent{\"}{"0308}
1269 \DeclareUnicodeAccent{\r}{030A}
1270 \DeclareUnicodeAccent{\H}{030B}
1271 \DeclareUnicodeAccent{\v}{030C}
1272 \DeclareUnicodeAccent{\b}{0332}

```



1325	\DeclareUnicodeComposite{"}	\i {"00EF}
1326	\DeclareUnicodeComposite{"}	{i}{"00EF}
1327	\DeclareUnicodeComposite{~}	{n}{"00F1}
1328	\DeclareUnicodeComposite{'}	{o}{"00F2}
1329	\DeclareUnicodeComposite{'}	{o}{"00F3}
1330	\DeclareUnicodeComposite{^}	{o}{"00F4}
1331	\DeclareUnicodeComposite{~}	{o}{"00F5}
1332	\DeclareUnicodeComposite{"}	{o}{"00F6}
1333	\DeclareUnicodeComposite{'}	{u}{"00F9}
1334	\DeclareUnicodeComposite{'}	{u}{"00FA}
1335	\DeclareUnicodeComposite{^}	{u}{"00FB}
1336	\DeclareUnicodeComposite{"}	{u}{"00FC}
1337	\DeclareUnicodeComposite{'}	{y}{"00FD}
1338	\DeclareUnicodeComposite{"}	{y}{"00FF}
1339	\DeclareUnicodeComposite{=}	{A}{"0100}
1340	\DeclareUnicodeComposite{=}	{a}{"0101}
1341	\DeclareUnicodeComposite{u}	{A}{"0102}
1342	\DeclareUnicodeComposite{u}	{a}{"0103}
1343	\DeclareUnicodeComposite{k}	{A}{"0104}
1344	\DeclareUnicodeComposite{k}	{a}{"0105}
1345	\DeclareUnicodeComposite{'}	{C}{"0106}
1346	\DeclareUnicodeComposite{'}	{c}{"0107}
1347	\DeclareUnicodeComposite{^}	{C}{"0108}
1348	\DeclareUnicodeComposite{^}	{c}{"0109}
1349	\DeclareUnicodeComposite{.}	{C}{"010A}
1350	\DeclareUnicodeComposite{.}	{c}{"010B}
1351	\DeclareUnicodeComposite{v}	{C}{"010C}
1352	\DeclareUnicodeComposite{v}	{c}{"010D}
1353	\DeclareUnicodeComposite{v}	{D}{"010E}
1354	\DeclareUnicodeComposite{v}	{d}{"010F}
1355	\DeclareUnicodeComposite{=}	{E}{"0112}
1356	\DeclareUnicodeComposite{=}	{e}{"0113}
1357	\DeclareUnicodeComposite{u}	{E}{"0114}
1358	\DeclareUnicodeComposite{u}	{e}{"0115}
1359	\DeclareUnicodeComposite{.}	{E}{"0116}
1360	\DeclareUnicodeComposite{.}	{e}{"0117}
1361	\DeclareUnicodeComposite{k}	{E}{"0118}
1362	\DeclareUnicodeComposite{k}	{e}{"0119}
1363	\DeclareUnicodeComposite{v}	{E}{"011A}
1364	\DeclareUnicodeComposite{v}	{e}{"011B}
1365	\DeclareUnicodeComposite{^}	{G}{"011C}
1366	\DeclareUnicodeComposite{^}	{g}{"011D}
1367	\DeclareUnicodeComposite{u}	{G}{"011E}
1368	\DeclareUnicodeComposite{u}	{g}{"011F}
1369	\DeclareUnicodeComposite{.}	{G}{"0120}
1370	\DeclareUnicodeComposite{.}	{g}{"0121}
1371	\DeclareUnicodeComposite{c}	{G}{"0122}
1372	\DeclareUnicodeComposite{c}	{g}{"0123}
1373	\DeclareUnicodeComposite{^}	{H}{"0124}
1374	\DeclareUnicodeComposite{^}	{h}{"0125}
1375	\DeclareUnicodeComposite{~}	{I}{"0128}
1376	\DeclareUnicodeComposite{~}	\i {"0129}
1377	\DeclareUnicodeComposite{~}	{i}{"0129}
1378	\DeclareUnicodeComposite{=}	{I}{"012A}

1379	\DeclareUnicodeComposite{=}	\i {"012B}
1380	\DeclareUnicodeComposite{=}	{i}{"012B}
1381	\DeclareUnicodeComposite{\u}	{I}{"012C}
1382	\DeclareUnicodeComposite{\u}	\i {"012D}
1383	\DeclareUnicodeComposite{\u}	{i}{"012D}
1384	\DeclareUnicodeComposite{\k}	{I}{"012E}
1385	\DeclareUnicodeComposite{\k}	\i {"012F}
1386	\DeclareUnicodeComposite{\k}	{i}{"012F}
1387	\DeclareUnicodeComposite{.}	{I}{"0130}
1388	\DeclareUnicodeComposite{^}	{J}{"0134}
1389	\DeclareUnicodeComposite{^}	\j {"0135}
1390	\DeclareUnicodeComposite{^}	{j}{"0135}
1391	\DeclareUnicodeComposite{c}	{K}{"0136}
1392	\DeclareUnicodeComposite{c}	{k}{"0137}
1393	\DeclareUnicodeComposite{'}	{L}{"0139}
1394	\DeclareUnicodeComposite{'}	{l}{"013A}
1395	\DeclareUnicodeComposite{c}	{L}{"013B}
1396	\DeclareUnicodeComposite{c}	{l}{"013C}
1397	\DeclareUnicodeComposite{v}	{L}{"013D}
1398	\DeclareUnicodeComposite{v}	{l}{"013E}
1399	\DeclareUnicodeComposite{'}	{N}{"0143}
1400	\DeclareUnicodeComposite{'}	{n}{"0144}
1401	\DeclareUnicodeComposite{c}	{N}{"0145}
1402	\DeclareUnicodeComposite{c}	{n}{"0146}
1403	\DeclareUnicodeComposite{v}	{N}{"0147}
1404	\DeclareUnicodeComposite{v}	{n}{"0148}
1405	\DeclareUnicodeComposite{=}	{O}{"014C}
1406	\DeclareUnicodeComposite{=}	{o}{"014D}
1407	\DeclareUnicodeComposite{\u}	{O}{"014E}
1408	\DeclareUnicodeComposite{\u}	{o}{"014F}
1409	\DeclareUnicodeComposite{H}	{O}{"0150}
1410	\DeclareUnicodeComposite{H}	{o}{"0151}
1411	\DeclareUnicodeComposite{'}	{R}{"0154}
1412	\DeclareUnicodeComposite{'}	{r}{"0155}
1413	\DeclareUnicodeComposite{c}	{R}{"0156}
1414	\DeclareUnicodeComposite{c}	{r}{"0157}
1415	\DeclareUnicodeComposite{v}	{R}{"0158}
1416	\DeclareUnicodeComposite{v}	{r}{"0159}
1417	\DeclareUnicodeComposite{'}	{S}{"015A}
1418	\DeclareUnicodeComposite{'}	{s}{"015B}
1419	\DeclareUnicodeComposite{^}	{S}{"015C}
1420	\DeclareUnicodeComposite{^}	{s}{"015D}
1421	\DeclareUnicodeComposite{c}	{S}{"015E}
1422	\DeclareUnicodeComposite{c}	{s}{"015F}
1423	\DeclareUnicodeComposite{v}	{S}{"0160}
1424	\DeclareUnicodeComposite{v}	{s}{"0161}
1425	\DeclareUnicodeComposite{c}	{T}{"0162}
1426	\DeclareUnicodeComposite{c}	{t}{"0163}
1427	\DeclareUnicodeComposite{v}	{T}{"0164}
1428	\DeclareUnicodeComposite{v}	{t}{"0165}
1429	\DeclareUnicodeComposite{~}	{U}{"0168}
1430	\DeclareUnicodeComposite{~}	{u}{"0169}
1431	\DeclareUnicodeComposite{=}	{U}{"016A}
1432	\DeclareUnicodeComposite{=}	{u}{"016B}

1433	\DeclareUnicodeComposite{\u}	{U}{\016C}
1434	\DeclareUnicodeComposite{\u}	{u}{\016D}
1435	\DeclareUnicodeComposite{\r}	{U}{\016E}
1436	\DeclareUnicodeComposite{\r}	{u}{\016F}
1437	\DeclareUnicodeComposite{\H}	{U}{\0170}
1438	\DeclareUnicodeComposite{\H}	{u}{\0171}
1439	\DeclareUnicodeComposite{\k}	{U}{\0172}
1440	\DeclareUnicodeComposite{\k}	{u}{\0173}
1441	\DeclareUnicodeComposite{\^}	{W}{\0174}
1442	\DeclareUnicodeComposite{\^}	{w}{\0175}
1443	\DeclareUnicodeComposite{\^}	{Y}{\0176}
1444	\DeclareUnicodeComposite{\^}	{y}{\0177}
1445	\DeclareUnicodeComposite{"}	{Y}{\0178}
1446	\DeclareUnicodeComposite{'}	{Z}{\0179}
1447	\DeclareUnicodeComposite{'}	{z}{\017A}
1448	\DeclareUnicodeComposite{.}	{Z}{\017B}
1449	\DeclareUnicodeComposite{.}	{z}{\017C}
1450	\DeclareUnicodeComposite{\v}	{Z}{\017D}
1451	\DeclareUnicodeComposite{\v}	{z}{\017E}
1452	\DeclareUnicodeComposite{\v}	{A}{\01CD}
1453	\DeclareUnicodeComposite{\v}	{a}{\01CE}
1454	\DeclareUnicodeComposite{\v}	{I}{\01CF}
1455	\DeclareUnicodeComposite{\v}	{i}{\01D0}
1456	\DeclareUnicodeComposite{\v}	{i}{\01D0}
1457	\DeclareUnicodeComposite{\v}	{O}{\01D1}
1458	\DeclareUnicodeComposite{\v}	{o}{\01D2}
1459	\DeclareUnicodeComposite{\v}	{U}{\01D3}
1460	\DeclareUnicodeComposite{\v}	{u}{\01D4}
1461	\DeclareUnicodeComposite{'}	\AE{\01FC}
1462	\DeclareUnicodeComposite{'}	{E}{\01FC}
1463	\DeclareUnicodeComposite{'}	\ae{\01FD}
1464	\DeclareUnicodeComposite{'}	{æ}{\01FD}
1465	\DeclareUnicodeComposite{=}	\AE{\01E2}
1466	\DeclareUnicodeComposite{=}	{E}{\01E2}
1467	\DeclareUnicodeComposite{=}	\ae{\01E3}
1468	\DeclareUnicodeComposite{=}	{æ}{\01E3}
1469	\DeclareUnicodeComposite{\v}	{G}{\01E6}
1470	\DeclareUnicodeComposite{\v}	{g}{\01E7}
1471	\DeclareUnicodeComposite{\v}	{K}{\01E8}
1472	\DeclareUnicodeComposite{\v}	{k}{\01E9}
1473	\DeclareUnicodeComposite{\k}	{O}{\01EA}
1474	\DeclareUnicodeComposite{\k}	{o}{\01EB}
1475	\DeclareUnicodeComposite{\v}	\j{\01F0}
1476	\DeclareUnicodeComposite{\v}	{j}{\01F0}
1477	\DeclareUnicodeComposite{'}	{G}{\01F4}
1478	\DeclareUnicodeComposite{'}	{g}{\01F5}
1479	\DeclareUnicodeComposite{\textcommabelow}	{S}{\0218}
1480	\DeclareUnicodeComposite{\textcommabelow}	{s}{\0219}
1481	\DeclareUnicodeComposite{\textcommabelow}	{T}{\021A}
1482	\DeclareUnicodeComposite{\textcommabelow}	{t}{\021B}
1483	\DeclareUnicodeComposite{\=}	{Y}{\0232}
1484	\DeclareUnicodeComposite{\=}	{y}{\0233}
1485	\DeclareUnicodeComposite{.}	{B}{\01E02}

```

1486 \DeclareUnicodeComposite{\.}      {b}{"1E03}
1487 \DeclareUnicodeComposite{\d}      {B}{"1E04}
1488 \DeclareUnicodeComposite{\d}      {b}{"1E05}
1489 \DeclareUnicodeComposite{\d}      {D}{"1E0C}
1490 \DeclareUnicodeComposite{\d}      {d}{"1E0D}
1491 \DeclareUnicodeComposite{\=}      {G}{"1E20}
1492 \DeclareUnicodeComposite{\=}      {g}{"1E21}
1493 \DeclareUnicodeComposite{\d}      {H}{"1E24}
1494 \DeclareUnicodeComposite{\d}      {h}{"1E25}
1495 \DeclareUnicodeComposite{\d}      {K}{"1E32}
1496 \DeclareUnicodeComposite{\d}      {k}{"1E33}
1497 \DeclareUnicodeComposite{\d}      {L}{"1E36}
1498 \DeclareUnicodeComposite{\d}      {l}{"1E37}
1499 \DeclareUnicodeComposite{\d}      {M}{"1E42}
1500 \DeclareUnicodeComposite{\d}      {m}{"1E43}
1501 \DeclareUnicodeComposite{\d}      {N}{"1E46}
1502 \DeclareUnicodeComposite{\d}      {n}{"1E47}
1503 \DeclareUnicodeComposite{\d}      {R}{"1E5A}
1504 \DeclareUnicodeComposite{\d}      {r}{"1E5B}
1505 \DeclareUnicodeComposite{\d}      {S}{"1E62}
1506 \DeclareUnicodeComposite{\d}      {s}{"1E63}
1507 \DeclareUnicodeComposite{\d}      {T}{"1E6C}
1508 \DeclareUnicodeComposite{\d}      {t}{"1E6D}
1509 \DeclareUnicodeComposite{\d}      {V}{"1E7E}
1510 \DeclareUnicodeComposite{\d}      {v}{"1E7F}
1511 \DeclareUnicodeComposite{\d}      {W}{"1E88}
1512 \DeclareUnicodeComposite{\d}      {w}{"1E89}
1513 \DeclareUnicodeComposite{\d}      {Z}{"1E92}
1514 \DeclareUnicodeComposite{\d}      {z}{"1E93}
1515 \DeclareUnicodeComposite{\d}      {A}{"1EA0}
1516 \DeclareUnicodeComposite{\d}      {a}{"1EA1}
1517 \DeclareUnicodeComposite{\d}      {E}{"1EB8}
1518 \DeclareUnicodeComposite{\d}      {e}{"1EB9}
1519 \DeclareUnicodeComposite{\d}      {I}{"1ECA}
1520 \DeclareUnicodeComposite{\d}      {i}{"1ECB}
1521 \DeclareUnicodeComposite{\d}      {O}{"1ECC}
1522 \DeclareUnicodeComposite{\d}      {o}{"1ECD}
1523 \DeclareUnicodeComposite{\d}      {U}{"1EE4}
1524 \DeclareUnicodeComposite{\d}      {u}{"1EE5}
1525 \DeclareUnicodeComposite{\d}      {Y}{"1EF4}
1526 \DeclareUnicodeComposite{\d}      {y}{"1EF5}
1527 \end{fontenc}

```

## 2 Package files

This file now also contains some packages that provide access to the more specialised encodings.

### 2.1 The fontenc package

This package allows authors to specify which encodings they will use. For each encoding F00, the package looks to see if the encoding F00 has already been declared. If it has

not, the file `fooenc.def` is loaded. The default encoding is set to be `F00`.

In addition the package at the moment contains extra code to extend the `\@uclclist` (list of upper/lower case pairs) for encodings that involve cyrillic characters. THIS IS A TEMPORARY SOLUTION and will not stay this way forever (or so we hope) but right now we are missing a proper interface for this and didn't wanted to rush it.

1528 `\*package)`

Here we define a macro that extends the `\@uclclist` if needed and afterwards turns itself in a noop.

```
1529 \def\update@uclc@with@cyrillic{%
1530 \expandafter\def\expandafter\@uclclist\expandafter
1531 {\@uclclist
1532 \cyra\CYRA\cyrabhch\CYRABHCH\cyrabhchdsc\CYRABHCHDSC\cyrabhdze
1533 \CYRABHDZE\cyrabhha\CYRABHHA\cyrae\CYRAE\cyrb\CYRB\cyrbuus
1534 \CYRBYUS\cyrc\CYRC\cyrch\CYRCH\cyrchldsc\CYRCHLDSC\cyrchrdsc
1535 \CYRCHRDSC\cyrchvcrs\CYRCHVCRS\cyrd\CYRD\cyrdelta\CYRDELTA
1536 \cyrdje\CYRDJE\cyrdze\CYRDZE\cyrdzhe\CYRDZHE\cyre\CYRE\cyreps
1537 \CYREPS\cyrerev\CYREREV\cyrery\CYRERY\cyrf\CYRF\cyrfita
1538 \CYRFITA\cyrg\CYRG\cyrgdsc\CYRGDSC\cyrgdschcrs\CYRGDSCHCRS
1539 \cyrgchcrs\CYRGHCRS\cyrgkh\CYRGHK\cyrgup\CYRGUP\cyrh\CYRH
1540 \cyrhdsc\CYRHDSC\cyrhcrs\CYRHHCRS\cyrhkh\CYRHHK\cyrhdsn
1541 \CYRHRDSN\cyri\CYRI\cyrie\CYRIE\cyrii\CYRII\cyrishrt\CYRISHRT
1542 \cyrishrtdsc\CYRISHRTDSC\cyrizh\CYRIZH\cyrje\CYRJE\cyrk\CYRK
1543 \cyrkbeak\CYRKBEAK\cyrkds\CYRKDSC\cyrkchcrs\CYRKHCRS\cyrkhh
1544 \CYRKHK\cyrkvcrs\CYRKVCRS\cyr1\CYRL\cyrldsc\CYRLDSC\cyr1hk
1545 \CYRLHK\cyr1je\CYRLJE\cyrn\CYRM\cyrmdsc\CYRMDSC\cyrmhk\CYRMHK
1546 \cyrn\CYRN\cyrndsc\CYRNDSC\cyrng\CYRNG\cyrnhk\CYRNHK\cyrnje
1547 \CYRNJE\cyrnlhk\CYRNLHK\cyro\CYRO\cyrotld\CYROTLD\cyrp\CYRP
1548 \cyrrhk\CYRPHK\cyrrq\CYRQ\cyrr\CYRR\cyrrdsc\CYRRDSC\cyrrhk
1549 \cyrrhk\cyrrtick\CYRRTICK\cyrs\CYRS\cyrsacrs\CYRSACRS
1550 \cyrschwa\CYRSCHWA\cyrsdsc\CYRSDSC\cyrsemisftsn\CYRSEMISFTSN
1551 \cyrsftsn\CYRSFTSN\cyrrsh\CYRSH\cyrrshch\CYRSHCH\cyrrsha\CYRSHHA
1552 \cyrt\CYRT\cyrtldsc\CYRTDSC\cyrtetse\CYRTETSE\cyrtshe\CYRTSHE
1553 \cyru\CYRU\cyrushrt\CYRUSHRT\cyrv\CYRV\cyrw\CYRW\cyr\CYRY
1554 \cyrya\CYRYA\cyryat\CYRYAT\cyryhcrs\CYRYHCRS\cyryi\CYRYI\cyryo
1555 \CYRYO\cyryu\CYRYU\cyrz\CYRZ\cyrzdsc\CYRZDSC\cyrrzh\CYRZH
1556 \cyrrzhdsc\CYRZHDSC}%
1557 \let\update@uclc@with@cyrillic\relax
1558 }
```

Here we process each option:

```
1559 \DeclareOption*{%
1560 \let\encodingdefault\CurrentOption
```

From 2020/02/02 release onward we only load the encoding files if they haven't be loaded already. To check this we look at whether `\T@encoding` is already defined. If not, we load it later (indicated by setting the switch `@tempswa` to true) and we always load if we are using an older format (or rather in a rollback situation).

```
1561 \@tempswafalse
1562 \@ifl@t@r\fmtversion{2020/02/02}%
1563 {\expandafter\ifx\csname T@\CurrentOption\endcsname\relax
1564 \@tempswatrue\fi}%
1565 {\@tempswatrue}%
```

Load if necessary:

```

1566 \if@tempswa
1567 \edef\reserved@f{%
1568 \lowercase{\def\noexpand\reserved@f{\CurrentOption enc.def}}}%
1569 \reserved@f
1570 \InputIfFileExists\reserved@f
1571 {}{\PackageError{fontenc}%
1572 {Encoding file ‘\reserved@f’ not found.%
1573 \MessageBreak
1574 You might have misspelled the name of the encoding
1575 \MessageBreak
1576 or a required support package (e.g., cyrillic) is
1577 \MessageBreak
1578 missing in your installation}%
1579 {Necessary code for this encoding was not
1580 loaded.\MessageBreak
1581 Thus calling the encoding later on will
1582 produce further error messages.}}%
1583 \let\reserved@f\relax

```

In case the current encoding is one of a list of known cyrillic ones we extend the `\@uclclist`:

```

1584 \expandafter\in@\expandafter{\CurrentOption}%
1585 {T2A,T2B,T2C,X2,LCY,OT2}%
1586 \ifin@

```

But only if it hasn't already been extended. This might happen if there are several calls to fontenc loading one of the above encodings. If we don't do this check the `\@uclclist` gets unnecessarily big, slowing down the processing at runtime.

```

1587 \expandafter\in@\expandafter\cyrillic\expandafter
1588 {\@uclclist}%
1589 \ifin@
1590 \else
1591 \update@uclc@with@cyrillic
1592 \fi
1593 \fi
1594 \fi
1595 }

```

```

1596 \ProcessOptions*

```

We select the new font encoding default (i.e., the last encoding specified in the option list). But this encoding may not work with the current `\fontshape`: e.g., `LY1` is not defined for `cmr` and therefore packages switching to `LY1` usually also change `\rmdefault`. But that only applies at `\begin{document}` so we get a spurious warning if we use what L<sup>A</sup>T<sub>E</sub>X previously used:

```

1597 %\fontencoding\encodingdefault\selectfont

```

So instead we do this here:

```

1598 \usefont\encodingdefault\familydefault\seriesdefault\shapedefault

```

To save some space we get rid of the macro extending the `\@uclclist` (might have happened already).

```

1599 \let\update@uclc@with@cyrillic\relax

```

Finally we pretend that the fontenc package wasn't read in. This allows for using it several times, e.g., in a class file and in the preamble (at the cost of not getting any version info). That kind of hackery shows that using a general purpose package just for loading an encoding is not the right kind of interface for setting up encodings — it will get replaced at some point in the future.

```

1600 \let\@elt\relax
1601 \xdef\@fontenc@load@list{\@fontenc@load@list
1602   \@elt{\csname opt@fontenc.sty\endcsname}}

1603 \global\expandafter\let\csname ver@@fontenc.sty\expandafter\endcsname
1604   \csname ver@fontenc.sty\endcsname
1605 \global\expandafter\let\csname ver@fontenc.sty\endcsname\relax
1606 \global\expandafter\let\csname opt@fontenc.sty\endcsname\relax
1607 \global\let\@ifl@ter@@\@ifl@ter
1608 \def\@ifl@ter#1#2#3#4#5{\global\let\@ifl@ter\@ifl@ter@@}
1609 \endpackage

```

## File 22

# ltcounts.dtx

## 1 Counters and Lengths

Commands for defining and using counters. This file defines the following commands. In each case  $\langle counter \rangle$  may be  $*$  denoting the current counter as set by a previous `\refstepcounter`.

<code>\newcounter</code>	To define a new counter.
<code>\setcounter</code>	To set the value of counters.
<code>\addtocounter</code>	Increase the $\langle counter \rangle$ #1 by the number #2.
<code>\stepcounter</code>	Increase the $\langle counter \rangle$ by one.
<code>\refstepcounter</code>	Increase the $\langle counter \rangle$ by one, also setting the value used by <code>\label</code> .
<code>\value</code>	For accessing the value of the counter as a TeX number (as opposed to <code>\the\langle counter \rangle</code> which expands to the <i>printed</i> representation of $\langle counter \rangle$ )
<code>\arabic</code>	<code>\arabic{\langle counter \rangle}</code> : 1, 2, 3, ...
<code>\roman</code>	<code>\roman{\langle counter \rangle}</code> : i, ii, iii, ...
<code>\Roman</code>	<code>\Roman{\langle counter \rangle}</code> : I, II, III, ...
<code>\alph</code>	<code>\alph{\langle counter \rangle}</code> : a, b, c, ...
<code>\Alph</code>	<code>\Alph{\langle counter \rangle}</code> : A, B, C, ...
<code>\fnsymbol</code>	<code>\fnsymbol{\langle counter \rangle}</code> : *, †, ‡, ...
<code>\counterwithin</code>	<code>\counterwithin[\langle format \rangle]{\langle counter \rangle}{\langle within-counter \rangle}</code> : Resets $\langle counter \rangle$ whenever $\langle within-counter \rangle$ is stepped. Also redefines <code>\the\langle counter \rangle</code> command to produce <code>\the\langle within-counter \rangle.\langle format \rangle{\langle counter \rangle}</code> with <code>\arabic</code> as the default for $\langle format \rangle$ . Star form omits redefining the print representation. The $*$ alias for the current counter may not be used in either argument.
<code>\counterwithout</code>	<code>\counterwithout[\langle format \rangle]{\langle counter \rangle}{\langle within-counter \rangle}</code> : Removes $\langle counter \rangle$ from the reset list of $\langle within-counter \rangle$ . Also redefines <code>\the\langle counter \rangle</code> command to produce <code>\langle format \rangle{\langle counter \rangle}</code> with <code>\arabic</code> as the default for $\langle format \rangle$ . Star form omits redefining the print representation. The $*$ alias for the current counter may not be used in either argument.

<sup>1</sup>  $\langle *2ekernel \rangle$

### 1.1 Document command and environment counter macros

An environment `foo` has an associated counter defined by the following control sequences:

<code>\c@foo</code>	Contains the counter's numerical value. It is defined by <code>\newcount\foocounter</code> .
<code>\thefoo</code>	Macro that expands to the printed value of <code>\foocounter</code> . For example, if sections are numbered within chapters, and section headings look like Section II-3. The Nature of Counters then <code>\thesection</code> might be defined by: <code>\def\thesection</code> <code>{\@Roman{\c@chapter}-\@arabic{\c@section}}</code>
<code>\p@foo</code>	Macro that expands to a printed 'reference prefix' of counter <code>foo</code> . Any <code>\ref</code> to a value created by counter <code>foo</code> will produce the expansion of <code>\p@foo\thefoo</code> when the <code>\label</code> command is executed. See file <code>ltxref.dtx</code> for an extension of this mechanism.
<code>\cl@foo</code>	List of counters to be reset when <code>foo</code> stepped. Has format <code>\@elt{countera}\@elt{counterb}\@elt{counterc}</code> .

For some environments the counter is named slightly differently, e.g., the counters associated with the `enumerate` environment have the names `enumi`, `enumii`, `enumiii`, and `enumiv` depending on the nesting level.

The same internal macros are defined for counters used by commands such as `\chapter`, `\section`, etc.

**NOTE:**

`\thefoo` and `\p@foo` *must* be defined in such a way that `\edef\bar{\thefoo}` or `\edef\bar{\p@foo}` defines `\bar` so that it will evaluate to the counter value at the time of the `\edef`, even after `\foocounter` and any other counters have been changed. This will happen if you use the standard commands `\@arabic`, `\@Roman`, etc.

The following commands are used to define and modify counters.

`\refstepcounter{<foo>}`

Same as `\stepcounter`, but it also defines `\@currentlabel`, `\@currentHref` and `\@currentcounter` and so that a subsequent `\label{<bar>}` command causes `\ref{<bar>}` to generate the current value of counter `<foo>`.

`\@definecounter{<foo>}`

Initializes counter `<foo>` (with empty reset list), defines `\p@foo` and `\thefoo` to be null and `\theHfoo` to be `\number\value{foo}`. Also adds `<foo>` to `\cl@ckpt` – the reset list of a dummy counter `@ckpt` used for taking checkpoints for the `\include` system.

`\@addtoreset{<foo>}{<bar>}` : Adds counter `<foo>` to the list of counters `\cl@bar` to be reset when counter `<bar>` is stepped.

`\@removefromreset{<foo>}{<bar>}` : Removes counter `<foo>` to the list of counters `\cl@bar` to be reset when counter `<bar>` is stepped.

`\setcounter` `\setcounter{<foo>}{<val>}` : Globally sets `\foocounter` equal to `<val>`.

```

2 \def\setcounter#1#2{%
3   \@ifundefined{c#1}%
4     {\@nocounterr{#1}}%
5     {\global\csname c@#1\endcsname#2\relax}}
```

(End of definition for `\setcounter`.)

`\addtocounter` `\addtocounter{<foo>}{<val>}` Globally increments `\foocounter` by `<val>`.

```

6 \def\addtocounter#1#2{%
7   \@ifundefined{c#1}%
```

```

8      {\@nocounterr{#1}}}%
9      {\global\advance\csname c@#1\endcsname #2\relax}}

(End of definition for \addtocounter.)

\newcounter \newcounter{<newctr>}[<oldctr>] Defines <newctr> to be a counter, which is reset when
counter <oldctr> is stepped. If <newctr> already defined produces ‘c@newctr already defined’
error.
10 \def\newcounter#1{%
11   \expandafter\ifdefinable \csname c@#1\endcsname
12   {\@definecounter{#1}}}%
13   \@ifnextchar[{\@newctr{#1}}{}]}

(End of definition for \newcounter.)

\value \value{<ctr>} produces the value of counter <ctr>, for use with a \setcounter or
\addtocounter command.
14 \def\value#1{\csname c@#1\endcsname}

(End of definition for \value.)

\c@* Make the current counter available as a LATEX counter with name *, so \alph* returns
the current counter as a letter, \stepcounter{*} increments the current counter, etc.
15 \protected\expandafter
16   \def\csname c@*\endcsname{\value\@currentcounter}

(End of definition for \c@*.)

\@newctr
17 \def\@newctr#1[#2]{%
18   \@ifundefined{c@#2}{\@nocounterr{#2}}{\@addtoreset{#1}{#2}}}}

(End of definition for \@newctr.)

\stepcounter \stepcounterfoo Globally increments counter \c@F00 and resets all subsidiary counters.
19 \def\stepcounter#1{%
20   \addtocounter{#1}\@ne
21   \begingroup
22     \let\@elt\@stpelt
23     \csname cl@#1\endcsname
24   \endgroup}

(End of definition for \stepcounter.)

\@stpelt Rather than resetting the “within” counter to zero we set it to -1 and then run
\stepcounter that moves it to 0 and also initiates resetting the next level down.
25 \</2ekernel>
26 \<latexrelease>\IncludeInRelease{2015/01/01}{\@stpelt}
27 \<latexrelease>                                {Reset nested counters}%
28 \<*2ekernel | latexrelease>
29 \def\@stpelt#1{\global\csname c@#1\endcsname \m@ne\stepcounter{#1}}%
30 \<latexrelease>\EndIncludeInRelease
31 \</2ekernel | latexrelease>
32 \<latexrelease>\IncludeInRelease{0000/00/00}{\@stpelt}
33 \<latexrelease>                                {Reset nested counters}%%

```

```

34 <latexrelease>\def\@stpelt#1{\global\csname c@#1\endcsname \z@}%
35 <latexrelease>\EndIncludeInRelease
36 <*2ekernel>

(End of definition for \@stpelt.)

\cl@ckpt

37 \def\cl@ckpt{\@elt{page}}

(End of definition for \cl@ckpt.)

\@definecounter

38 </2ekernel>
39 <latexrelease>\IncludeInRelease{2024/11/01}{\@definecounter}
40 <latexrelease> {provide theHfoo commands}%
41 <*2ekernel | latexrelease>
42 \def\@definecounter#1{\expandafter\newcount\csname c@#1\endcsname
43 \setcounter{#1}\z@
44 \global\expandafter\let\csname cl@#1\endcsname\@empty
45 \@addtoreset{#1}{@ckpt}%
46 \global\expandafter\let\csname p@#1\endcsname\@empty
47 \expandafter\xdef\csname theH#1\endcsname{%
48 \noexpand\the\noexpand\value{#1}}%

If \the#1 is undefined or \relax we define it with the standard definition for counters,
otherwise we warn. This will catch, for example, that somebody defines a counter named
“index” conflicting with the theindex environment.

49 \expandafter
50 \ifx\csname the#1\endcsname\relax
51 \expandafter
52 \gdef\csname the#1\expandafter\endcsname\expandafter
53 {\expandafter\@arabic\csname c@#1\endcsname}%
54 \else
55 \latex@warning{Command ‘\string\the#1’ already
56 defined -- not changed}%
57 \fi}
58 <latexrelease>\EndIncludeInRelease
59 </2ekernel | latexrelease>
60 <latexrelease>\IncludeInRelease{0000/00/00}{\@definecounter}
61 <latexrelease> {provide theHfoo commands}%%
62 <latexrelease>\def\@definecounter#1{\expandafter\newcount\csname c@#1\endcsname
63 <latexrelease> \setcounter{#1}\z@
64 <latexrelease> \global\expandafter\let\csname cl@#1\endcsname\@empty
65 <latexrelease> \@addtoreset{#1}{@ckpt}%
66 <latexrelease> \global\expandafter\let\csname p@#1\endcsname\@empty
67 <latexrelease> \expandafter
68 <latexrelease> \ifx\csname the#1\endcsname\relax
69 <latexrelease> \expandafter
70 <latexrelease> \gdef\csname the#1\expandafter\endcsname\expandafter
71 <latexrelease> {\expandafter\@arabic\csname c@#1\endcsname}%
72 <latexrelease> \else
73 <latexrelease> \latex@warning{Command ‘\string\the#1’ already
74 <latexrelease> defined -- not changed}%
75 <latexrelease> \fi}
76 <latexrelease>\EndIncludeInRelease
77 <*2ekernel>

```

(End of definition for \@definecounter.)

**\@addtoreset** If a counter is reset when a parent counter changes it no longer has an unique value across the document. As **\theH<counter>** should be unique this representation is changed to include also the representation of the parent. This is not 100% guaranteed to work but has been used this way by hyperref for many years without causing problems.

```

78 \</2ekernel>
79 \<latexrelease>\IncludeInRelease{2024/11/01}{\@addtoreset}
80 \<latexrelease>                                {provide theHfoo commands}%
81 \<*2ekernel | latexrelease>
82 \def\@addtoreset#1#2{\expandafter\@cons\csname cl@#2\endcsname {{#1}}%
83   \expandafter\xdef\csname theH#1\endcsname{%
84     \expandafter\noexpand\csname theH#2\endcsname.%
85     \noexpand\the\noexpand\value{#1}}%
86 }
87 \<latexrelease>\EndIncludeInRelease
88 \</2ekernel | latexrelease>
89 \<latexrelease>\IncludeInRelease{0000/00/00}{\@addtoreset}
90 \<latexrelease>                                {provide theHfoo commands}%%
91 \<latexrelease>\def\@addtoreset#1#2{\expandafter\@cons\csname cl@#2\endcsname {{#1}}}%
92 \<latexrelease>\EndIncludeInRelease
93 \<*2ekernel>

```

(End of definition for \@addtoreset.)

```

94 \</2ekernel>

```

**\@removefromreset**

```

95 \<latexrelease>\IncludeInRelease{2018-04-01}
96 \<latexrelease>                                {\@removefromreset}{Add interfaces}%
97 \<*2ekernel | latexrelease>
98 \def\@removefromreset#1#2{%

```

Even through this is internal and the programmer should know what he/she is doing we test here if counter #2 is defined. If not, the execution would run into a tight loop.

```

99   \ifundefined{c@#2}\relax
100   {\begingroup
101     \expandafter\let\csname c@#1\endcsname \@removefromreset
102     \def\@elt##1{%
103       \expandafter\ifx\csname c@##1\endcsname \@removefromreset
104       \else
105         \noexpand\@elt{##1}%
106       \fi}%
107     \expandafter\xdef\csname cl@#2\endcsname
108     {\csname cl@#2\endcsname}%
109     \endgroup}}

```

(End of definition for \@removefromreset.)

**\@ifbothcounters** Test if arg #1 and #2 are counters and if so execute #3.

```

110 \begingroup\catcode'\*=11 \lowercase{\endgroup
111 \def\@ifbothcounters#1#2#3{%
112   \begingroup\let\c@*\@undefined

```

```

113 \ifundefined{c@#1}{\nocounterr{#1}}%
114 {% else counter is defined
115 \ifundefined{c@#2}{\nocounterr{#2}}%
116 {% else both counter and within are defined
117 #3}}%
118 \endgroup}}

(End of definition for \@ifbothcounters.)

119 </2ekernel | latexrelease>
120 <latexrelease>\EndIncludeInRelease
121 <latexrelease>\IncludeInRelease{0000-00-00}
122 <latexrelease> {\@removefromreset}{Add interfaces}%
123 <latexrelease>\let \@removefromreset \undefined
124 <latexrelease>\let \@ifbothcounters \undefined
125 <latexrelease>\EndIncludeInRelease
126 <*2ekernel>

```

`\counterwithin` New implementation using xparse and supporting an optional format argument.

```

127 </2ekernel>
128 <*2ekernel | latexrelease>
129 <latexrelease>\IncludeInRelease{2025/06/01}%
130 <latexrelease> {\counterwithin}{counter within}%

131 \NewDocumentCommand \counterwithin {s0{\arabic}mm}{%
132 \ifbothcounters{#3}{#4}{%
133 \@addtoreset{#3}{#4}%
134 \IfBooleanF #1%
135 {\expandafter
136 \xdef\csname the#3\expandafter\endcsname
137 {\expandafter\noexpand\csname the#4\endcsname
138 .\unexpanded{#2}{#3}}}%
139 }%
140 }

141 </2ekernel | latexrelease>
142 <latexrelease>\EndIncludeInRelease
143 <latexrelease>\IncludeInRelease{2021/11/15}%
144 <latexrelease> {\counterwithin}{counter within}%
145 <latexrelease>
146 <latexrelease>\NewDocumentCommand \counterwithin {s0{\arabic}mm}{%
147 <latexrelease> \ifbothcounters{#3}{#4}{%
148 <latexrelease> \@addtoreset{#3}{#4}%
149 <latexrelease> \IfBooleanF #1%
150 <latexrelease> {\expandafter
151 <latexrelease> \gdef\csname the#3\expandafter\endcsname
152 <latexrelease> \expandafter
153 <latexrelease> {\csname the#4\endcsname .#2{#3}}}%
154 <latexrelease> }%
155 <latexrelease>}
156 <latexrelease>\EndIncludeInRelease

157 <latexrelease>\IncludeInRelease{2018-04-01}
158 <latexrelease> {\counterwithin}{counter within}%
159 <latexrelease>
160 <latexrelease>\def\counterwithin{\@ifstar\counterwithin@s\counterwithin@x}

```

```

161 <latexrelease>\def\counterwithin@s#1#2{%
162 <latexrelease> \ifbothcounters{#1}{#2}{\@addtoreset{#1}{#2}}

163 <latexrelease>\def\counterwithin@x#1#2{%
164 <latexrelease> \ifbothcounters{#1}{#2}%
165 <latexrelease> {\@addtoreset{#1}{#2}%
166 <latexrelease> \expandafter
167 <latexrelease> \gdef\csname the#1\expandafter\endcsname\expandafter
168 <latexrelease> {\csname the#2\expandafter\endcsname\expandafter
169 <latexrelease> .\expandafter
170 <latexrelease> \@arabic\csname c@#1\endcsname}}
171 <latexrelease>
172 <latexrelease>\EndIncludeInRelease
173 <latexrelease>\IncludeInRelease{0000-00-00}
174 <latexrelease> {\counterwithin}{counter without}%
175 <latexrelease>\let \counterwithin \undefined
176 <latexrelease>\let \counterwithin@s \undefined
177 <latexrelease>\let \counterwithin@x \undefined
178 <latexrelease>\EndIncludeInRelease
179 <*2ekernel>

```

(End of definition for \counterwithin.)

\counterwithout New implementation using xparse and supporting an optional format argument.

```

180 </2ekernel>
181 <*2ekernel | latexrelease>
182 <latexrelease>\IncludeInRelease{2025/06/01}%
183 <latexrelease> {\counterwithout}{counter without}%

184 \NewDocumentCommand \counterwithout {s0{\arabic}mm}{%
185 \ifbothcounters{#3}{#4}{%
186 \removefromreset{#3}{#4}%
187 \IfBooleanF #1%
188 {\expandafter
189 \xdef\csname the#3\endcsname {\unexpanded{#2}{#3}}}%
190 }%
191 }

192 </2ekernel | latexrelease>
193 <latexrelease>\EndIncludeInRelease

194 <latexrelease>\IncludeInRelease{2021/11/15}%
195 <latexrelease> {\counterwithout}{counter without}%
196 <latexrelease>\NewDocumentCommand \counterwithout {s0{\arabic}mm}{%
197 <latexrelease> \ifbothcounters{#3}{#4}{%
198 <latexrelease> \removefromreset{#3}{#4}%
199 <latexrelease> \IfBooleanF #1%
200 <latexrelease> {\expandafter
201 <latexrelease> \gdef\csname the#3\endcsname {#2{#3}}}%
202 <latexrelease> }%
203 <latexrelease>}
204 <latexrelease>\EndIncludeInRelease

205 <latexrelease>\IncludeInRelease{2018-04-01}
206 <latexrelease> {\counterwithout}{counter without}%
207 <latexrelease>

```

```

208 <latexrelease>\def\counterwithout {\@ifstar\counterwithout@s\counterwithout@x}
209 <latexrelease>\def\counterwithout@s#1#2{%
210 <latexrelease> \@ifbothcounters{#1}{#2}{\@removefromreset{#1}{#2}}
211 <latexrelease>\def\counterwithout@x#1#2{%
212 <latexrelease> \@ifbothcounters{#1}{#2}%
213 <latexrelease> \@removefromreset{#1}{#2}%
214 <latexrelease> \expandafter
215 <latexrelease> \gdef\csname the#1\expandafter\endcsname\expandafter
216 <latexrelease> {\expandafter
217 <latexrelease> \@arabic\csname c@#1\endcsname}}
218 <latexrelease>\EndIncludeInRelease
219 <latexrelease>
220 <latexrelease>\IncludeInRelease{0000-00-00}
221 <latexrelease> {\counterwithout}{counter without}%
222 <latexrelease>\let \counterwithout \undefined
223 <latexrelease>\let \counterwithout@s \undefined
224 <latexrelease>\let \counterwithout@x \undefined
225 <latexrelease>\EndIncludeInRelease
226 <*2ekernel>

```

(End of definition for \counterwithout.)

Numbering commands for definitions of \theCOUNTER and \list arguments.

All commands can now be used in text and math mode.

**\arabic** Representation of *<counter>* as arabic numerals. Changed 29 Apr 86 to make it print the obvious thing it COUNTER not positive.

```
227 \def\arabic#1{\expandafter\@arabic\csname c@#1\endcsname}
```

(End of definition for \arabic.)

**\roman** Representation of *<counter>* as lower-case Roman numerals.

```
228 \def\roman#1{\expandafter\@roman\csname c@#1\endcsname}
```

(End of definition for \roman.)

**\Roman** Representation of *<counter>* as upper-case Roman numerals.

```
229 \def\Roman#1{\expandafter\@Roman\csname c@#1\endcsname}
```

(End of definition for \Roman.)

**\alph** Representation of *<counter>* as a lower-case letter: 1 = a, 2 = b, etc.

```
230 \def\alph#1{\expandafter\@alph\csname c@#1\endcsname}
```

(End of definition for \alph.)

**\Alph** Representation of *<counter>* as an upper-case letter: 1 = A, 2 = B, etc.

```
231 \def\Alph#1{\expandafter\@Alph\csname c@#1\endcsname}
```

(End of definition for \Alph.)

**\fnsymbol** Representation of *<COUNTER>* as a footnote symbol: 1 = \*, 2 = †, etc.

```
232 \def\fnsymbol#1{\expandafter\@fnsymbol\csname c@#1\endcsname}
```

(End of definition for \fnsymbol.)

```

\@arabic \F00counter Representation of \F00counter as arabic numerals.
233 \def\@arabic#1{\number #1} %% changed 29 Apr 86
(End of definition for \@arabic.)

\@roman \F00counter Representation of \F00counter as lower-case Roman numerals.
234 \def\@roman#1{\romannumeral #1}
(End of definition for \@roman.)

\@Roman \F00counter Representation of \F00counter as upper-case Roman numerals.
235 \def\@Roman#1{\expandafter\@slowromancap\romannumeral #1@}
(End of definition for \@Roman.)

\@slowromancap Fully expandable macro to change a roman number to uppercase.
236 \def\@slowromancap#1{\ifx @#1% then terminate
237 \else
238 \if i#1I\else\if v#1V\else\if x#1X\else\if l#1L\else\if
239 c#1C\else\if d#1D\else \if m#1M\else#1\fi\fi\fi\fi\fi\fi
240 \expandafter\@slowromancap
241 \fi
242 }
(End of definition for \@slowromancap.)

\@alph \F00counter Representation of \F00counter as a lower-case letter: 1 = a, 2 =
b, etc.
243 \def\@alph#1{%
244 \ifcase#1\or a\or b\or c\or d\or e\or f\or g\or h\or i\or j\or
245 k\or l\or m\or n\or o\or p\or q\or r\or s\or t\or u\or v\or w\or x\or
246 y\or z\else\@ctrerr\fi}
(End of definition for \@alph.)

\@Alph \F00counter Representation of \F00counter as an upper-case letter: 1 = A, 2
= B, etc.
247 \def\@Alph#1{%
248 \ifcase#1\or A\or B\or C\or D\or E\or F\or G\or H\or I\or J\or
249 K\or L\or M\or N\or O\or P\or Q\or R\or S\or T\or U\or V\or W\or X\or
250 Y\or Z\else\@ctrerr\fi}
(End of definition for \@Alph.)

\@fnsymbol Typesetting old fashioned footnote symbols. This can be done both in text or math mode
now.

This macro is another example of an ever recurring problem in TEX: Determining
if something is text-mode or math-mode. It is imperative for the decision between text
and math to be delayed until the actual typesetting is done as the code in question may
go through an \edef or \write where an \ifmmode test would be executed prematurely.
Hence in the implementation below, \@fnsymbol is not robust in itself but the parts
doing the actual typesetting are.

```

In the case of `\@fnsymbol` we make use of the robust command `\TextOrMath` which takes two arguments and typesets the first if in text-mode and the second if in math-mode. Note that in order for this command to make the correct decision, it must insert a `\relax` token if run under regular  $\text{\TeX}$ , which ruins any kerning between the preceding characters and whatever awaits typesetting. If you use  $\text{\eTeX}$  as engine for  $\text{\LaTeX}$  (as recommended) this unfortunate side effect is not present.

```

251 </2ekernel>
252 <latexrelease>\IncludeInRelease{2015/01/01}{\@fnsymbol}{Use \TextOrMath}%
253 <*2ekernel | latexrelease>
254 \def\@fnsymbol#1{%
255   \ifcase#1\or \TextOrMath\textasteriskcentered *\or
256   \TextOrMath \textdagger \dagger\or
257   \TextOrMath \textdaggerdbl \ddagger \or
258   \TextOrMath \textsection \mathsection\or
259   \TextOrMath \textparagraph \mathparagraph\or
260   \TextOrMath \textbardbl ||\or
261   \TextOrMath {\textasteriskcentered\textasteriskcentered}{**}\or
262   \TextOrMath {\textdagger\textdagger}{\dagger\dagger}\or
263   \TextOrMath {\textdaggerdbl\textdaggerdbl}{\ddagger\ddagger}\else
264   \@ctrerr \fi
265 }%
266 </2ekernel | latexrelease>
267 <latexrelease>\EndIncludeInRelease
268 <latexrelease>\IncludeInRelease{0000/00/00}{\@fnsymbol}{Use \TextOrMath}%
269 <latexrelease>\def\@fnsymbol#1{\ensuremath{%
270 <latexrelease>   \ifcase#1\or *\or \dagger\or \ddagger\or \mathsection\or
271 <latexrelease>     \mathparagraph\or ||\or **\or \dagger\dagger
272 <latexrelease>       \or \ddagger\ddagger \else\@ctrerr\fi}}%
273 <latexrelease>\EndIncludeInRelease
274 <*2ekernel>

```

*(End of definition for \@fnsymbol.)*

`\TextOrMath` When using regular  $\text{\TeX}$ , we make this command robust so that it always selects the correct branch in an `\ifmmode` switch with the usual disadvantage of ruining kerning. For the application we use it for here that shouldn't matter. The alternative would be to mimic `\IeC` from `inputenc` but then it will have the disadvantage of choosing the wrong branch if appearing at the beginning of an alignment cell. However, users of  $\text{\eTeX}$  will be pleasantly surprised to get the best of both worlds and no bad side effects.

First some code for checking if we are running  $\text{\eTeX}$  but making sure not to permanently turn `\protected` into `\relax`.

```

275 </2ekernel>
276 <latexrelease>\IncludeInRelease{2015/01/01}{\TextOrMath}{\TextOrMath}%
277 <*2ekernel | latexrelease>
278 \begingroup\expandafter\expandafter\expandafter\endgroup
279 \expandafter\ifx\csname protected\endcsname\relax

```

In case of ordinary  $\text{\TeX}$  we define `\TextOrMath` as a robust command but make sure it always grabs its arguments. If we didn't do this it might very well gobble spaces in the input stream.

```

280 \DeclareRobustCommand\TextOrMath{%
281   \ifmmode \expandafter\@secondoftwo
282   \else    \expandafter\@firstoftwo \fi}

```

```

283 \protected@edef\TextOrMath#1#2{\TextOrMath{#1}{#2}}
284 \else

```

For eTeX the situation is similar. The robust macro is a hidden one so that we again avoid problems of gobbling spaces in the input.

```

285 \protected\expandafter\def\csname TextOrMath\space\endcsname{%
286   \ifmmode \expandafter\@secondoftwo
287   \else    \expandafter\@firstoftwo \fi}
288 \edef\TextOrMath#1#2{%
289   \expandafter\noexpand\csname TextOrMath\space\endcsname
290   {#1}{#2}}
291 \fi
292 </2ekernel | latexrelease>
293 <latexrelease>\EndIncludeInRelease
294 <latexrelease>\IncludeInRelease{0000/00/00}{\TextOrMath}{\TextOrMath}%
295 <latexrelease>\let\TextOrMath\@undefined
296 <latexrelease>\EndIncludeInRelease
297 <*2ekernel>

```

*(End of definition for \TextOrMath.)*

```

298 </2ekernel>

```

## File 23

# ltnlength.dtx

## 1 Lengths

```
\newlength Declare #1 to be a new length command.
\setlength Set the length command, #1, to the value #2.
\addtolength Increase the value of the length command, #1, by the value #2.
\settowidth Set the length, #1 to the width of a box containing #2.
\settoheight Set the length, #1 to the height of a box containing #2.
\settodepth Set the length, #1 to the depth of a box containing #2.

1 <*2ekernel>
2 \message{lengths,}

\newlength
3 \def\newlength#1{\@ifdefinable#1{\newskip#1}}
(End of definition for \newlength.)

\setlength
4 </2ekernel>
5 <latexrelease>\IncludeInRelease{2015/01/01}%
6 <latexrelease> \setlength}{Using \setlength with \dimen0}%
7 <*2ekernel | latexrelease>
8 \def\setlength#1#2{#1 #2\relax}
9 </2ekernel | latexrelease>
10 <latexrelease>\EndIncludeInRelease
11 <latexrelease>\IncludeInRelease{0000/00/00}%
12 <latexrelease> \setlength}{Using \setlength with \dimen0}%
13 <latexrelease>\def\setlength#1#2{#1#2\relax}
14 <latexrelease>\EndIncludeInRelease
15 <*2ekernel>
(End of definition for \setlength.)

\addtolength \relax added 24 Mar 86
16 \def\addtolength#1#2{\advance#1 #2\relax}
(End of definition for \addtolength.)

\settoheight The obvious analogs of \settowidth.
\settodepth
\settowidth
17 </2ekernel>
18 <*2ekernel | latexrelease>
19 <latexrelease>\IncludeInRelease{2024/11/01}%
20 <latexrelease> {\@settodim}{suspend tagging}%
21 \def\@settodim#1#2#3{\setbox\@tempboxa\hbox
22 {{\SuspendTagging{\@settodim}#3\ResumeTagging{\@settodim}}}\#2#1\@tempboxa
Clear the memory afterwards (which might be a lot).
23 \setbox\@tempboxa\box\voidb@x}
24 </2ekernel | latexrelease>
25 <latexrelease>\EndIncludeInRelease
```

```

26 <latexrelease>\IncludeInRelease{0000/00/00}%
27 <latexrelease>{\@settodim}{suspend tagging}%
28 <latexrelease>\def\@settodim#1#2#3{\setbox\@tempboxa\hbox{{#3}}#2#1\@tempboxa
29 <latexrelease>\setbox\@tempboxa\box\voidb@x}
30 <latexrelease>\EndIncludeInRelease
31 <*2ekernel>

32 \DeclareRobustCommand\settoheight{\@settodim\ht}
33 \DeclareRobustCommand\settodepth {\@settodim\dp}
34 \DeclareRobustCommand\settowidth {\@settodim\wd}

```

*(End of definition for \settoheight and others.)*

**\@settopoint** This macro takes the contents of the skip register that is supplied as its argument and removes the fractional part to make it a whole number of points. This can be used in class files to avoid values like 345.4666666pt when calculating a dimension.

```

35 \def\@settopoint#1{\divide#1\p@\multiply#1\p@}
36 </2ekernel>

```

*(End of definition for \@settopoint.)*

## File 24

# ltfssbas.dtx

This file contains the main implementation of the ‘low level’ font selection commands. See other parts of the L<sup>A</sup>T<sub>E</sub>X distribution, or *The L<sup>A</sup>T<sub>E</sub>X Companion* for higher level documentation of the L<sup>A</sup>T<sub>E</sub>X ‘New’ Font Selection Scheme.

**Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

## 1 Preliminary macros

We define a number of macros that will be used later.

```

1 <*2ekernel>
2 \message{NFSS base,}
```

`\@nomath` `\@nomath` is used by most macros that will have no effect in math mode. It issues a warning message.

```

3 \def\@nomath#1{\relax\ifmmode
4   \@font@warning{Command \noexpand#1invalid in math mode}\fi}
```

(End of definition for \@nomath.)

`\no@alphabet@error` The macro `\no@alphabet@error` is called whenever the user requests a math *alphabet* that is not available in the current *version*. In math mode an error message is produced otherwise the command keeps silent. The argument is the name of the control sequence that identifies the math *alphabet*. The `\relax` at the beginning is necessary to prevent T<sub>E</sub>X from scanning too far in certain situations.

```

5 \gdef\no@alphabet@error#1{\relax \ifmmode
6   \@latex@error{Math\space alphabet\space identifier\space
7     \noexpand#1is\space undefined\space in\space math\space
8     version\space '\math@version'}%
9   {Your\space requested\space math\space alphabet\space
10    is\space undefined\space in\space the\space current\space
11    math\space version.^^JCheck\space the\space spelling\space
12    or\space use\space the\space \noexpand\SetMathAlphabet\space
13    command.}
14   \fi}
```

(End of definition for \no@alphabet@error.)

`\new@mathgroup` We also give a new name to `\newfam` and `\fam` to avoid verbal confusion (see the introduction).<sup>32</sup>

`\mathgroup`

```

15 %\def\new@mathgroup{\alloc@8\mathgroup\chardef\sixt@@n}
16 \let\mathgroup\fam
17 %\let\newfam\new@mathgroup
18 \@onlypreamble\new@mathgroup
```

(End of definition for \new@mathgroup and \mathgroup.)

<sup>32</sup>For the same reason it seems advisable to `\let\fam` and `\newfam` equal to `\relax`, but this is commented out to retain compatibility to existing style files.

## 2 Macros for setting up the tables

`\DeclareFontShape` The macro `\DeclareFontShape` takes 6 arguments:

```
19 \def\DeclareFontShape{\begingroup
```

First we restore the catcodes of all characters used in the syntax.

```
20 \nfss@catcodes
```

We use `\expandafter \endgroup` to restore catcode in case something goes wrong with the argument parsing (suggested by Tim Van Zandt)

```
21 \expandafter\endgroup
```

```
22 \DeclareFontShape@}
```

(End of definition for `\DeclareFontShape`.)

`\DeclareFontShape@`

```
23 \</2kernel>
```

```
24 \<*2kernel | latexrelease>
```

```
25 \<latexrelease>\IncludeInRelease{2020/02/02}%
```

```
26 \<latexrelease>{\DeclareFontShape@}{Maybe drop one m}%
```

```
27 \def\DeclareFontShape@#1#2#3#4#5#6{%
```

```
28 \expandafter\ifx\csname #1+#2\endcsname\relax
```

```
29 \<@latex@error{Font family ‘#1+#2’ unknown}\@eha
```

```
30 \else
```

If the series value is incorrectly specified with an extra “m”, e.g., “mc” instead of just “c”, drop the surplus “m” but keep the “m” if it is by its own. In that case also issue a warning that the declaration needs correction.

For this we compare the given value #3 with one where we may have dropped an “m”. If nothing has changes, fine. Otherwise there was a wrong value which is now corrected in `\reserved@b` so we use that and also issue a warning.

```
31 \edef\reserved@a{#3}%
```

```
32 \series@maybe@drop@one@m\reserved@a\reserved@b
```

```
33 \ifx\reserved@a\reserved@b\else
```

```
34 \<@latex@note{Font shape #1/#2/#3/#4 has incorrect series
```

```
35 value ‘#3’.\MessageBreak It should not contain an ‘m’!
```

```
36 Please correct it.\MessageBreak Found}%
```

```
37 \fi
```

```
38 \expandafter
```

```
39 \xdef\csname#1/#2/\reserved@b/#4\endcsname
```

```
40 {\expandafter\noexpand\csname #5\endcsname}%
```

```
41 %
```

Most of the time #6 is empty so using `\let` to `\@empty` saves on space compared to using `\def`. That’s really one of the old space saving techniques and probably not necessary these days.

```
42 \def\reserved@a{#6}%
```

```
43 \global
```

```
44 \expandafter\let\csname#5\endcsname\expandafter\endcsname
```

```
45 \ifx\reserved@a\@empty
```

```
46 \@empty
```

```
47 \else
```

```
48 \reserved@a
```

```
49 \fi
```

```
50 \fi
```

```
51 }
```

```

52 </2ekernel | latexrelease>
53 <latexrelease>\EndIncludeInRelease
54 <latexrelease>\IncludeInRelease{0000/00/00}%
55 <latexrelease>          {\DeclareFontShape@}{Maybe drop one m}%
56 <latexrelease>
57 <latexrelease>\def\DeclareFontShape@#1#2#3#4#5#6{%
58 <latexrelease>  \expandafter\ifx\csname #1+#2\endcsname\relax
59 <latexrelease>    \@latex@error{Font family ‘#1+#2’ unknown}\@eha
60 <latexrelease>  \else
61 <latexrelease>    \expandafter
62 <latexrelease>      \xdef\csname#1/#2/#3/#4\endcsname{\expandafter\noexpand
63 <latexrelease>                                                \csname #5\endcsname}%
64 <latexrelease>    \def\reserved@a{#6}%
65 <latexrelease>    \global
66 <latexrelease>    \expandafter\let\csname#5\endcsname\expandafter\endcsname
67 <latexrelease>    \ifx\reserved@a\@empty
68 <latexrelease>      \@empty
69 <latexrelease>    \else
70 <latexrelease>      \reserved@a
71 <latexrelease>    \fi
72 <latexrelease>  \fi
73 <latexrelease> }
74 <latexrelease>\EndIncludeInRelease
75 <*2ekernel>

```

*(End of definition for \DeclareFontShape@.)*

**\DeclareFixedFont** Define a direct font switch that avoids all overhead.

```

76 \def\DeclareFixedFont#1#2#3#4#5#6{%
77   \begingroup
78     \math@fontsfalse
79     \every@math@size{}%
80     \fontsize{#6}\z@
81     \usefont{#2}{#3}{#4}{#5}%
82     \global\expandafter\let\expandafter#1\the\font
83   \endgroup
84 }

```

*(End of definition for \DeclareFixedFont.)*

**\do@subst@correction**

```

85 \def\do@subst@correction{%
86   \xdef\subst@correction{%
87     \font@name
88     \global\expandafter\font
89     \csname \curr@fontshape/\f@size\endcsname
90     \noexpand\fontname\font
91     \relax}%

```

Calling `\subst@correction` after the current group means calling it after we have loaded the substitution font which is done inside a group.

```

92     \aftergroup\subst@correction
93 }

```

*(End of definition for \do@subst@correction.)*

`\DeclareFontFamily`

```

94 \def\DeclareFontFamily#1#2#3{%
    If we want fast checking for the encoding scheme we can just check for \T@.. being
    defined.
95 % \@tempswafalse
96 % \def\reserved@b{#1}%
97 % \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
98 %     \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
99 % \cdp@list
100 % \if@tempswa
101 % \ifundefined{T@#1}%
102 %     {%
103 %         \@latex@error{Encoding scheme ‘#1’ unknown}\@eha
104 %     }%
105 % }
```

Now we have to define the macro `\<#1>+<#2>` to contain `#3`. But since most of the time `#3` will be empty we use `\let` in a tricky way rather than a simple `\def` since this will save internal memory. We store the argument `#3` in a temporary macro `\reserved@a`.

```

106     \def\reserved@a{#3}%
    We compare \reserved@a with \@empty If these two are the same we \let the ‘extra’
    macro equal to \@empty which is not the same a doing a \let to \reserved@a — the
    latter would blow one extra memory location rather then reusing the one from \@empty.
107     \global
108     \expandafter\let\csname #1+#2\expandafter\endcsname
109         \ifx \reserved@a\@empty
110             \@empty
111         \else \reserved@a
112         \fi
113     }%
114 }
```

*(End of definition for \DeclareFontFamily.)*

`\cdp@list` We initialize the code page list to be empty.

```

115 \let\cdp@list\@empty
116 \@onlypreamble\cdp@list
```

*(End of definition for \cdp@list.)*

`\cdp@elt`

```

117 \let\cdp@elt\relax
118 \@onlypreamble\cdp@elt
```

*(End of definition for \cdp@elt.)*

`\DeclareFontEncoding`

```

119 \def\DeclareFontEncoding{%
```

First we start with ignoring all blanks and newlines since every surplus space in the second or third argument will come out in a weird place in the document.

```

120 \begingroup
121 \nfss@catcodes
122 \expandafter\endgroup
123 \DeclareFontEncoding@
124 \@onlypreamble\DeclareFontEncoding

125 \def\DeclareFontEncoding@#1#2#3{%
126 \expandafter
127 \ifx\csname T@#1\endcsname\relax
128 \def\cdp@elt{\noexpand\cdp@elt}%
129 \xdef\cdp@list{\cdp@list\cdp@elt{#1}%
130 \{\default@family\}\{\default@series\}%
131 \{\default@shape\}}%

```

To support encoding dependent commands (like accents) we initialise the command `\encoding`-cmd to be `\changed@cmd`. (See `ltoutenc.dtx` for details.)

```

132 \expandafter\let\csname#1-cmd\endcsname\@changed@cmd
133 \else
134 \@font@info{Redefining font encoding #1}%
135 \fi

136 \global\@namedef{T@#1}{#2}%
137 \global\@namedef{M@#1}{\default@M#3}%

```

Keep a record of the last encoding being declared:

```

138 \xdef\LastDeclaredEncoding{#1}%
139 }
140 \@onlypreamble\DeclareFontEncoding@

```

*(End of definition for \DeclareFontEncoding.)*

`\LastDeclaredEncoding` The last encoding being declared by `\DeclareFontEncoding`.

```

141 \def\LastDeclaredEncoding{}

```

*(End of definition for \LastDeclaredEncoding.)*

`\DeclareFontSubstitution`

```

142 \def\DeclareFontSubstitution#1#2#3#4{%
143 \expandafter
144 \ifx\csname T@#1\endcsname\relax
145 \@latex@error{Encoding scheme ‘#1’ unknown}\@eha
146 \else
147 \begingroup

```

We loop through the `\cdp@list` and rebuild it anew in `\toks@` thereby replacing the defaults for the encoding in question with the new defaults. It is important to store the encoding to test against expanded in `\reserved@a` since it might just be `\LastDeclaredEncoding` that is passed as `#1`.

```

148 \edef\reserved@a{#1}%
149 \toks@{}%
150 \def\cdp@elt##1##2##3##4{%
151 \def\reserved@b{##1}%
152 \ifx\reserved@a\reserved@b

```

Here we use the new defaults but we use `##1` (i.e., the encoding name already stored previously) since we know that it is expanded.

```

153         \addto@hook\toks@{\cdp@elt{##1}{#2}{#3}{#4}}%
154     \else
If \reserved@a and \reserved@b differ then we simply copy from the old list to the new.
155         \addto@hook\toks@{\cdp@elt{##1}{##2}{##3}{##4}}%
156     \fi}%
157     \cdp@list
158     \xdef\cdp@list{\the\toks@}%
159 \endgroup
160 \global
161 \@namedef{D@#1}{%
162     \def\default@family{#2}%
163     \def\default@series{#3}%
164     \def\default@shape{#4}%
165     }%
166 \fi
167 }
168 \@onlypreamble\DeclareFontSubstitution

```

(End of definition for `\DeclareFontSubstitution`.)

`\DeclareFontEncodingDefaults`

```

169 \def\DeclareFontEncodingDefaults#1#2{%
170     \ifx\relax#1\else
171         \ifx\default@T\@empty\else
172             \@font@info{Overwriting encoding scheme text defaults}%
173         \fi
174         \gdef\default@T{#1}%
175     \fi
176     \ifx\relax#2\else
177         \ifx\default@M\@empty\else
178             \@font@info{Overwriting encoding scheme math defaults}%
179         \fi
180         \gdef\default@M{#2}%
181     \fi
182 }
183 \@onlypreamble\DeclareFontEncodingDefaults

```

(End of definition for `\DeclareFontEncodingDefaults`.)

`\default@T`  
`\default@M`

```

184 \let\default@T\@empty
185 \let\default@M\@empty

```

(End of definition for `\default@T` and `\default@M`.)

`\DeclareEncodingSubset`

The declaration takes 3 mandatory arguments: an *encoding* for which a subsetting is wanted (currently always `TS1`, and most likely forever), the *font family* for which we declare the subset and finally the *subset* number, with a value between 0 (all of the encoding is supported) and 9 (many glyphs are missing).

For `TS1` the numbers have been chosen in a way that most fonts can be fairly correctly categorized, but the default settings are always conservative, that is they may claim that fewer glyphs are supported than there actually are.

As these days many font families are set up to end in `-LF` (lining figures), `-OsF` (oldstyle figures), etc. the declaration supports a shortcut: if the *font family* name ends in `-*` then the star gets replaced by these common ending, e.g.,

```
\DeclareEncodingSubset{TS1}{Alegreya-*}{2}
```

is the same as writing

```
\DeclareEncodingSubset{TS1}{Alegreya-LF}{2}
\DeclareEncodingSubset{TS1}{Alegreya-OsF}{2}
\DeclareEncodingSubset{TS1}{Alegreya-TLF}{2}
\DeclareEncodingSubset{TS1}{Alegreya-TOsF}{2}
```

If only some are needed then one can define them individually but in many cases all four are wanted, hence the shortcut.

The coding of the declaration has no error checking as it is mostly for internal use.

```
186 \def\DeclareEncodingSubset#1#2{%
187   \DeclareEncodingSubset@aux{#1}#2*\DeclareEncodingSubset@aux
188 }
189 \def\DeclareEncodingSubset@aux#1#2*#3\DeclareEncodingSubset@aux#4{%
if #3 is empty then there was no star, otherwise we define all four variants.
190   \expandafter\ifx\expandafter X\detokenize{#3}X%
191     \@DeclareEncodingSubset{#1}{#2}{#4}%
192   \else
193     \@DeclareEncodingSubset{#1}{#2LF}{#4}%
194     \@DeclareEncodingSubset{#1}{#2TLF}{#4}%
195     \@DeclareEncodingSubset{#1}{#2OsF}{#4}%
196     \@DeclareEncodingSubset{#1}{#2TOsF}{#4}%
197   \fi
198 }
```

The subset info is stored in a command with the name `\family:subset` so if that already exists we change otherwise declare a subset.

```
199 \def\@DeclareEncodingSubset#1#2#3{%
200   \@ifundefined{#1:#2}%
201     {\font@info{Setting #2 sub-encoding to #1/#3}}%
202     {\font@info{Changing #2 sub-encoding to #1/#3}}%
This declaration should be usable in .fd files and therefore has to make its definition globally, because such files can get loaded in random places.
203   \global\@namedef{#1:#2}{#3}}
```

(End of definition for `\DeclareEncodingSubset`.)

**\CheckEncodingSubset** The command `\CheckEncodingSubset` will check if the current font family has the right encoding subset to typeset a certain command. It takes five arguments as follows: first argument is either `\UseTextSymbol`, `\UseTextAccent` depending on whether or not the symbol is a text symbol or a text accent.

The second argument is the encoding from which this symbol should be fetched.

The third argument is either a fake accessor command or an error message. the code in that argument (if ever executed) receives two arguments: `#2` and `#5` of `\CheckEncodingSubset`.

Argument four is the subset encoding id to test against: if this value is higher than the subset id of the current font family then we typeset the symbol, i.e., execute `#1{#2}#5` otherwise it runs `#3#5`, e.g., to produce an error message or fake the glyph somehow.

Argument five is the symbol or accent command that is being checked.

For usage examples see definitions in `ltxtextcomp.dtx`.

```

204 </2ekernel>
205 <*2ekernel | latexrelease>
206 <latexrelease> \IncludeInRelease{2025/06/01}%
207 <latexrelease>          {\CheckEncodingSubset}{preload .fd file}%
208 \def\CheckEncodingSubset#1#2#3#4#5{%

```

If the `.fd` is not yet loaded we make an attempt to load it now because it may contain a `\DeclareEncodingSubset` declaration for the font.

```

209   \expandafter\ifx\csname #2:\f@family\endcsname\relax
210     \LoadFontDefinitionFile{#2}\f@family
211   \fi
212   \ifnum #4>%
213     \expandafter\ifx\csname #2:\f@family\endcsname\relax
214       0\csname #2:?\endcsname
215     \else
216       \csname #2:\f@family\endcsname
217     \fi
218   \relax
219   \expandafter\@firstoftwo
220 \else
221   \expandafter\@secondoftwo
222 \fi
223   {#1{#2}}{#3}%
224   #5%
225 }
226 </2ekernel | latexrelease>
227 <latexrelease> \EndIncludeInRelease
228 <latexrelease> \IncludeInRelease{0000/00/00}%
229 <latexrelease>          {\CheckEncodingSubset}{preload .fd file}%
230 <latexrelease>
231 <latexrelease> \def\CheckEncodingSubset#1#2#3#4#5{%
232 <latexrelease>   \ifnum #4>%
233 <latexrelease>     \expandafter\ifx\csname #2:\f@family\endcsname\relax
234 <latexrelease>       0\csname #2:?\endcsname
235 <latexrelease>     \else
236 <latexrelease>       \csname #2:\f@family\endcsname
237 <latexrelease>     \fi
238 <latexrelease>   \relax
239 <latexrelease>   \expandafter\@firstoftwo
240 <latexrelease> \else
241 <latexrelease>   \expandafter\@secondoftwo
242 <latexrelease> \fi
243 <latexrelease>   {#1{#2}}{#3}%
244 <latexrelease>   #5%
245 <latexrelease> }
246 <latexrelease> \EndIncludeInRelease
247 <*2ekernel>

```

*(End of definition for \CheckEncodingSubset.)*

`\DeclarePreloadSizes`

```

248 \def\DeclarePreloadSizes#1#2#3#4#5{%
249   \@ifundefined{T@#1}%
250   {\@latex@error{Encoding scheme ‘#1’ unknown}\@eha}%
251   {%

```

Don’t know at the moment what this group here does!

```

252   \begingroup

```

We define a macro `\reserved@f`<sup>33</sup> that grabs the next *size* and loads the corresponding font. This is done by delimiting `\reserved@f`’s only argument by the token `,` (comma).

```

253   \def\reserved@f##1,{%

```

The end of the list will be detected when there are no more elements, i.e. when `\reserved@f`’s argument is empty. The trick used here is explained in Appendix D of the *T<sub>E</sub>Xbook*: if the argument is empty the `\if` will select the first clause and `\let \reserved@f equal to \relax`. (We use the `>` character here since it cannot appear in font file names.)

```

254       \if>##1>%
255       \let\reserved@f\relax
256       \else

```

Otherwise, we define `\font@name` appropriately and call `\pickup@font` to do the work. Note that the requested `\curr@fontshape` combination must have been defined, or you will get an error. The definition of `\font@name` is carried out globally to be consistent with the rest of the code in this file.

```

257       \xdef\font@name{\csname#1/#2/#3/#4/##1\endcsname}%
258       \pickup@font

```

Now we forget the name of the font just loaded. More precisely, we set the corresponding control sequence to `\relax`. This means that later on, when the font is first used, the macro `\define@newfont` is called again to execute the ‘extra’ macro for this font.

```

259       \global\expandafter\let\font@name\relax
260   \fi

```

Finally we call `\reserved@f` again to process the next *size*. If `\reserved@f` was `\let equal to \relax` this will end the macro.

```

261       \reserved@f}%

```

We finish with reinserting the list of sizes after the `\reserved@f` macro and appending an empty element so that the end of the list is recognized properly.

```

262   \reserved@f#5,,%
263   \endgroup
264 }%
265 }
266 \@onlypreamble\DeclarePreloadSizes

```

(End of definition for `\DeclarePreloadSizes`.)

`\ifmath@fonts` We need a switch to decide if we have to switch math fonts. For this purpose we provide `\ifmath@fonts` that can be set to true or false by the `\S@...` macros depending on if math fonts are provided for this size or not. The default is of course to switch all fonts.

```

267 \newif\ifmath@fonts \math@fontstrue

```

---

<sup>33</sup>We cannot use `\@tempa` since it is needed in `\pickup@font`.

(End of definition for \ifmath@fonts.)

**\DeclareMathSizes** \DeclareMathSizes takes the text size, math text size, math script size, and math scriptscript size as arguments and defines the right \S@... macro.

```
268 \def\DeclareMathSizes{%
269   \ifstar{\@DeclareMathSizes\math@fontsfalse}%
270   {\@DeclareMathSizes{}}}%
271 \@onlypreamble\DeclareMathSizes
```

(End of definition for \DeclareMathSizes and \DeclareMathSizes\*.)

**\@DeclareMathSizes** This modification by Michael J. Downes on comp.text.tex on 2002/10/17 allows the user to have settings such as

**\DeclareMathSizes{9.5dd}{9.5dd}{7.4dd}{6.6dd}.**

```
272 \</2kernel>
273 \<latexrelease>\IncludeInRelease{2015/01/01}{\@DeclareMathSizes}%
274 \<latexrelease>          {Arbitrary units in \DeclareMathSizes}%
275 \<*2kernel | latexrelease>
276 \def\@DeclareMathSizes #1#2#3#4#5{%
277   \@defaultunits\dimen@ #2pt\relax\@nnil
278   \if $#3$%
279     \expandafter\let\csname S@\strip@pt\dimen@\endcsname\math@fontsfalse
280   \else
281     \@defaultunits\dimen@ii #3pt\relax\@nnil
282     \@defaultunits\@tempdima #4pt\relax\@nnil
283     \@defaultunits\@tempdimb #5pt\relax\@nnil
284     \toks@{#1}%
285     \expandafter\xdef\csname S@\strip@pt\dimen@\endcsname{%
286       \gdef\noexpand\tf@size{\strip@pt\dimen@ii}%
287       \gdef\noexpand\sf@size{\strip@pt\@tempdima}%
288       \gdef\noexpand\ssf@size{\strip@pt\@tempdimb}%
289       \the\toks@
290     }%
291   \fi
292 }%
293 \</2kernel | latexrelease>
294 \<latexrelease>\EndIncludeInRelease
295 \<latexrelease>\IncludeInRelease{0000/00/00}{\@DeclareMathSizes}%
296 \<latexrelease>          {Arbitrary units in \DeclareMathSizes}%
297 \<latexrelease>\def\@DeclareMathSizes#1#2#3#4#5{%
298 \<latexrelease>   \@defaultunits\dimen@#2pt\relax\@nnil
299 \<latexrelease>   \if $#3$%
300 \<latexrelease>     \expandafter \let
301 \<latexrelease>       \csname S@\strip@pt\dimen@\endcsname
302 \<latexrelease>       \math@fontsfalse
303 \<latexrelease>   \else
304 \<latexrelease>     \expandafter \gdef
305 \<latexrelease>       \csname S@\strip@pt\dimen@\endcsname
306 \<latexrelease>         {\gdef\tf@size{#3}\gdef\sf@size{#4}%
307 \<latexrelease>           \gdef\ssf@size{#5}%
308 \<latexrelease>           #1%
309 \<latexrelease>           }%
310 \<latexrelease>   \fi}%
311 \<latexrelease>\EndIncludeInRelease
```

```

312 <*2kernel>
313 \onlypreamble\@DeclareMathSizes
(End of definition for \@DeclareMathSizes.)

```

## 3 Selecting a new font

### 3.1 Macros for the user

`\fontencoding` As we said in the introduction a font is described by four parameters. We first define  
`\f@encoding` macros to specify the wanted *family*, *series*, or *shape*. These are simply recorded in internal macros `\f@family`, `\f@series`, and `\f@shape`, resp. We use `\edef`'s so that the arguments can also be macros.

```

314 \DeclareRobustCommand\fontencoding[1]{%
315   \expandafter\ifx\csname T@#1\endcsname\relax
316     \latex@error{Encoding scheme ‘#1’ unknown}\@eha
317   \else
318     \edef\f@encoding{#1}%
319     \ifx\cf@encoding\f@encoding

```

If the new encoding is the same as the old encoding we have nothing to do. However, in case we had a sequence of several encoding changes without a `\selectfont` in-between we can save processing by making sure that `\enc@update` is `\relax`.

```

320       \let\enc@update\relax
321     \else

```

If current and new encoding differ we define the macro `\enc@update` to contain all updates necessary at `\selectfont` time.

```

322       \let\enc@update\@enc@update
323     \fi
324   \fi
325 }

```

(End of definition for `\fontencoding` and `\f@encoding`.)

`\@enc@update`

```

326 \def\@enc@update{%

```

When `\@enc@update` is executed `\f@encoding` holds the encoding name for the new encoding and `\cf@encoding` the name of the last active encoding.

We start by setting the init command for encoding dependent macros to `\@changed@cmd`.

```

327   \expandafter
328   \let
329   \csname\cf@encoding -cmd\endcsname
330   \@changed@cmd

```

Then we turn the one for the new encoding to `\@current@cmd` (see `ltoutenc.dtx` for further explanations).

```

331   \expandafter
332   \let
333   \csname\f@encoding-cmd\endcsname
334   \@current@cmd

```

We execute the default settings `\default@T`, followed by the one for the new encoding.

```
335      \default@T
336      \csname T@f@encoding\endcsname
```

Finally we change the default substitution values, disable `\enc@update` and make `\f@encoding` officially the current encoding.

```
337      \csname D@f@encoding\endcsname
338      \let\enc@update\relax
339      \let\cf@encoding\f@encoding
340  }
```

*(End of definition for `\@enc@update`.)*

`\enc@update` The default action in `\selectfont` is to do nothing.

```
341 \let\enc@update\relax
```

*(End of definition for `\enc@update`.)*

`\fontfamily` They are now all defined later (and differently).

```
\f@family 342 %\DeclareRobustCommand\fontfamily[1]{\edef\f@family{#1}}
\fontseries 343 %\DeclareRobustCommand\fontseries[1]{\edef\f@series{#1}}
\f@series 344 %\DeclareRobustCommand\fontshape [1]{\edef\f@shape{#1}}
\fontshape
\f@shape
```

*(End of definition for `\fontfamily` and others.)*

`\usefont` Some handy abbreviation if you want to get some particular font in the current size. If also the size should change one has to issue a `\fontsize` command first.

`\fontencoding` needs to do some setup work so we call that, but instead of calling `\fontfamily`, `\fontseries` and `\fontshape` it earlier versions of this code did, we now set `\f@family`, etc. directly. If we would call `\fontseries` or `\fontshape` as it was done in the past, they would now interact with the existing series and shape which is not desired if we intend to use an explicit font shape!

```
345 </2ekernel>
346 <*2ekernel | latexrelease>
347 <latexrelease> \IncludeInRelease{2021/06/01}%
348 <latexrelease>          {\usefont}{Force font face}%
349 \DeclareRobustCommand\usefont[4]{\fontencoding{#1}%
350   \edef\f@family{#2}%
351   \set@target@series{#3}%
352   \edef\f@shape{#4}%
```

Any earlier `\fontseries`, etc. should be canceled and we should switch unconditionally to the requested font face so we drop any code that may have been stored in `\delayed@f@adjustment`.

```
353   \let\delayed@f@adjustment\@empty
354   \selectfont
355   \ignorespaces}
356 </2ekernel | latexrelease>
357 <latexrelease> \EndIncludeInRelease
358 <latexrelease> \IncludeInRelease{2020/02/02}%
359 <latexrelease>          {\usefont}{Drop m in usefont}%
360 <latexrelease>
361 <latexrelease> \DeclareRobustCommand\usefont[4]{\fontencoding{#1}%
362 <latexrelease>   \edef\f@family{#2}%
```

```

363 <latexrelease> \set@target@series{#3}%
364 <latexrelease> \edef\f@shape{#4}\selectfont
365 <latexrelease> \ignorespaces}
366 <latexrelease>
367 <latexrelease>\EndIncludeInRelease
368 <latexrelease>\IncludeInRelease{0000/00/00}%
369 <latexrelease> \usefont{Drop m in usefont}%
370 <latexrelease>
371 <latexrelease>\DeclareRobustCommand\usefont[4]{\fontencoding{#1}%
372 <latexrelease> \edef\f@family{#2}%
373 <latexrelease> \edef\f@series{#3}%
374 <latexrelease> \edef\f@shape{#4}\selectfont
375 <latexrelease> \ignorespaces}
376 <latexrelease>
377 <latexrelease>\EndIncludeInRelease
378 <*2kernel>

```

*(End of definition for \usefont.)*

**\linespread** The command `\linespread` changes the current `\baselinestretch` by calling `\set@fontsize`. The values for `\f@size` and `\f@baselineskip` will be left unchanged.

```

379 \DeclareRobustCommand\linespread[1]
380 { \set@fontsize{#1}\f@size\f@baselineskip}

```

*(End of definition for \linespread.)*

**\fontsize** We also define a macro that allows to specify a size. In this case, however, we also need the value of `\baselineskip`. As the first argument to `\set@fontsize` we pass the current value of `\baselinestretch`. This will either match the internal value (in which case nothing changes) or it will be an updated value due to a user change of that macro using `\renewcommand`. If we would pass the internal `\f@linespread` such a change would be effectively overwritten by a size change.

```

381 \DeclareRobustCommand\fontsize[2]
382 { \set@fontsize\baselinestretch{#1}{#2}}

```

*(End of definition for \fontsize.)*

**\f@linespread** This macro holds the current internal value for `\baselinestretch`.

```

383 \let\f@family\@empty
384 \let\f@series\@empty
385 \let\f@shape\@empty
386 \let\f@size\@empty
387 \let\f@baselineskip\@empty
388 \let\f@linespread\@empty

```

*(End of definition for \f@linespread.)*

**\cf@encoding**

```

389 \let\f@encoding\@empty
390 \let\cf@encoding\@empty

```

*(End of definition for \cf@encoding.)*

`\@defaultunits` The function `\@defaultunits` when wrapped around a `dimen` or `skip` assignment supplies default units. Usage:

```
\@defaultunits\dimen@=#1pt\relax\@nnil
```

Note: the `\relax` is *important*. Other units can be substituted for the ‘pt’ if desired.

We use `\remove@to@nnil` as an auxiliary macros for `\@defaultunits`. It just has to gobble the supplied default unit ‘pt’ or whatever, if it wasn’t used in the assignment.

```
391 \def\@defaultunits{\afterassignment\remove@to@nnil}
```

(End of definition for `\@defaultunits`.)

`\strip@pt` This macro strips the characters `pt` produced by using `\the` on a `dimen` register.

`\rem@pt`

```
392 \begingroup
393   \catcode‘P=12
394   \catcode‘T=12
395   \lowercase{
396     \def\x{\def\rem@pt##1.##2PT{##1\ifnum##2>\z@.##2\fi}}
397   \expandafter\endgroup\x
398   \def\strip@pt{\expandafter\rem@pt\the}
```

(End of definition for `\strip@pt` and `\rem@pt`.)

`\mathversion` `\mathversion` takes the *math version* name as argument, defines `\math@version` appropriately and switches to the font selected forcing a call to `\glb@settings` if the *version* is known to the system.

`\math@version`

```
399 \DeclareRobustCommand\mathversion[1]
400   {\nomath\mathversion
401     \expandafter\ifx\csname mv@#1\endcsname\relax
402     \latex@error{Math version ‘#1’ is not defined}\@eha\else
```

If there has been a frozen math version reset unconditionally to it if we are at `\@math@level` one, so that in the typical case of one bold symbol within the normal version this doesn’t allocate an additional math alphabet. If the nesting is deeper we do nothing, which means alphabet allocations accumulate until the end of the formula. One could do slightly better but that would mean keeping track of the allocations on all levels severately and this is likely to be overkill in nearly all situations.

```
403   \ifcsname mv@#1\endcsname
404   \ifnum \@math@level = \@ne
405     \unconditionally@reset@math@version {#1}%
406   \fi
407   \fi
408   \edef\math@version{#1}%
```

We need to force a math font setup both now and at the point where we return to the previous math version. Forcing a math font setup can simply be done by setting `\glb@currsize` to an invalid value since this will trigger the setup when the formula starts.

```
409   \gdef\glb@currsize{}
```

When the scope of the current `\mathversion` ends we need to restore the old setup. However this time we need to force it directly at least if we are inside math, otherwise we could wait. Another way to enhance this code here is to do the setting only if the version really has changed after all. This might be interesting in case of `amstext` and `boldsymbol`.

```
410         \aftergroup\glb@settings
411         \fi}
```

Resetting the math version unconditionally means that we have to copy the frozen version to `\mv@#1` and also reset the counter `\c@mv@#1` to the number of math alphabets allocated in the frozen version.

```
412 \ExplSyntaxOn
413 \cs_new_protected:Npn \unconditionally@reset@math@version #1 {
414   \cs_gset_eq:cc { mv@#1 }{ mv@#1@frozen }
415   \int_gset:cn { c@mv@#1 }{ \tl_use:c {g__nfss_frozen_mv_ #1 _tl} }
416 }
417 \ExplSyntaxOff
```

*(End of definition for \mathversion and \math@version.)*

If  $\TeX$  would support a hook just before the end of a formula (opposite of `\everymath` so to speak) the implementation of the algorithm would be much simpler because in that case we would set up the correct math fonts at this point without having to worry about incorrect settings due to nesting. The same would be true if in  $\LaTeX$  the use of `$` (as the primitive  $\TeX$  command) would be impossible and instead only a higher-level interface would be available. Note that this does not mean that a `$` couldn't be the short-hand for starting and stopping that higher-level interface, it only means that the direct  $\TeX$  function must be hidden.

Anyway, since we don't have this and won't have it in  $\LaTeX 2_\epsilon$  we need to implement it in a somewhat slower way.

We test for the current math font setup on entry of a formula, i.e., on the hooks `\everymath` and `\everydisplay`. But since these hooks may contain user data we provide ourselves with an internal version of these hooks which stays frozen.

```
\frozen@everymath New internal names for \everymath and \everydisplay.
\frozen@everydisplay 418 \let\frozen@everymath\everymath
                     419 \let\frozen@everydisplay\everydisplay
```

*(End of definition for \frozen@everymath and \frozen@everydisplay.)*

```
\everymath Now we provide now user hooks that will be called in the frozen internals.
\everydisplay 420 \newtoks\everymath
               421 \newtoks\everydisplay
```

*(End of definition for \everymath and \everydisplay.)*

```
\@math@level This counter records the nesting level of math within math.
              422 \newcount\@math@level
```

*(End of definition for \@math@level.)*

`\frozen@everydisplay` Now we define the behaviour of the frozen hooks: first check the math setup then call the user hook.

The check code may push tokens after the math formula with `\aftergroup` and they would prevent a `$$` from dropping following spaces. We therefore use a switch to be set as the first thing after the group so that following code can determine if there was a display or some inline math (in the latter case we better not drop spaces). After setting the switch we also have to place `\ignorespaces` because setting the switch may be the only thing that happens after the display. The issue with handling of spaces was found in 2022, but it is really a bug fix for the code added in 2021/11.

```

423 </2ekernel>
424 <latexrelease>\IncludeInRelease{2021/11/15}
425 <latexrelease> {\frozen@everydisplay}{Handle spaces after math}%
426 <*2ekernel| latexrelease>
427 \frozen@everydisplay = {%
428   \aftergroup\@ignoretrue \aftergroup\ignorespaces

```

Record that we entered another math level.

```

429   \advance\@math@level\@ne
430   \check@mathfonts
431   \the\everydisplay}

```

*(End of definition for \frozen@everydisplay.)*

`\frozen@everymath` The frozen code for inline math is similar, except that here we do not want to drop following spaces.

```

432 \frozen@everymath = {%
433   \aftergroup\@ignorefalse

```

Record that we entered another math level.

```

434   \advance\@math@level\@ne
435   \check@mathfonts
436   \the\everymath}

```

*(End of definition for \frozen@everymath.)*

```

437 </2ekernel| latexrelease>
438 <latexrelease>\EndIncludeInRelease
439 <latexrelease>\IncludeInRelease{2020/10/01}
440 <latexrelease> {\frozen@everydisplay}{Handle spaces after math}%
441 <latexrelease>
442 <latexrelease>\frozen@everydisplay = {\check@mathfonts
443                                     \the\everydisplay}
444 <latexrelease>\frozen@everymath = {\check@mathfonts
445                                     \the\everymath}
446 <latexrelease>
447 <latexrelease>\EndIncludeInRelease
448 <*2ekernel>

```

`\curr@math@size` This holds locally the current math size.

```

449 \let\curr@math@size\@empty

```

*(End of definition for \curr@math@size.)*

## 3.2 Macros for loading fonts

`\pickup@font` The macro `\pickup@font` which is used in `\selectfont` is very simple: if the font name is undefined (i.e. not known yet) it calls `\define@newfont` to load it.

```
450 \def\pickup@font{%
451     \expandafter \ifx \font@name \relax
452         \define@newfont
453     \fi}
```

(End of definition for `\pickup@font`.)

`\split@name` `\pickup@font` assumes that `\font@name` is set but it is sometimes called when `\f@family`, `\f@series`, `\f@shape`, or `\f@size` may have the wrong settings (see, e.g., the definition of `\getanddefine@fonts`). Therefore we need a macro to extract font *family*, *series*, *shape*, and *size* from the font name. To this end we define `\split@name` which takes the font name as a list of characters of `\catcode 12` (without the backslash at the beginning) delimited by the special control sequence `\@nil`. This is not very complicated: we first ensure that `/` has the right `\catcode`

```
454 {\catcode'\/=12
```

and define `\split@name` so that it will define our private `\f@encoding`, `\f@family`, `\f@series`, `\f@shape`, and `\f@size` macros.

```
455 \gdef\split@name#1/#2/#3/#4/#5\@nil{\def\f@encoding{#1}%
456                                     \def\f@family{#2}%
457                                     \def\f@series{#3}%
458                                     \def\f@shape{#4}%
459                                     \def\f@size{#5}}}
```

(End of definition for `\split@name`.)

`\curr@fontshape` Abbreviation which may get removed again for speed.

```
460 \def\curr@fontshape{\f@encoding/\f@family/\f@series/\f@shape}
```

(End of definition for `\curr@fontshape`.)

`\define@newfont` Now we can tackle the problem of defining a new font.

```
461 \def\define@newfont{%
```

We have already mentioned that the token list that `\split@name` will get as argument must not start with a backslash. To reach this goal we will set the `\escapechar` to `-1` so that the `\string` primitive will not generate an escape character. To keep this change local we open a group. We use `\begingroup` for this purpose since `\define@newfont` might be called in math mode, and an empty `\bgroup... \egroup` would add an empty Ord atom to the math list and thus affect the spacing.

Also locally redefine `\typeout` so that ‘No file ...fd’ Warnings become Font Info message just sent to the log file.

```
462 \begingroup
463     \let\typeout\@font@info
464     \escapechar\m@ne
```

Then we extract *encoding scheme*, *family*, *series*, *shape*, and *size* from the font name. Note the four `\expandafter`’s so that `\font@name` is expanded first, then `\string`, and finally `\split@name`.

```
465     \expandafter\expandafter\expandafter
466     \split@name\expandafter\string\font@name\@nil
```

If the `\curr@fontshape` combination is not available, (i.e. undefined) we call the macro `\wrong@fontshape` to take care of this case. Otherwise `\extract@font` will load the external font for us.

```

467 %    \expandafter\ifx
468 %        \csname\curr@fontshape\endcsname \relax
469 %    \try@load@fontshape % try always
470 %    \fi
471 %    \expandafter\ifx
472 %        \csname\curr@fontshape\endcsname \relax
473 %    \wrong@fontshape\else

```

To allow substitution we call the `curr@fontshape` macro which usually will expand to `\relax` but may hold code for substitution (see `\subst@fontshape` definition).

```

474 %    \csname\curr@fontshape\endcsname
475 %    \extract@font\fi

```

We are nearly finished and must only restore the `\escapechar` by closing the group.

```

476 \endgroup}

477 \def\try@load@fontshape{%
478     \expandafter
479     \ifx\csname \f@encoding+\f@family\endcsname\relax
480         \@font@info{Trying to load font information for
481             \f@encoding+\f@family}%

```

We predefine this combination to be `\@empty` which means that next time we don't try again unnecessary in case we don't find a `.fd` file. If the file contains a `\DeclareFontFamily` command than this setting will be overwritten.

```

482     \global\expandafter\let
483     \csname \f@encoding+\f@family\endcsname\@empty

```

Set the catcodes used in the syntax, but do it only once (this will be restored at the end of the font loading group).

```

484     \nfss@catcodes
485     \let\nfss@catcodes\relax

```

For increased portability make the external filename monospace, but look for the (old style) mixed case filename if the first attempt fails.

On any monospace system this means that the file is looked for twice which takes up time and string space, but at least for this release Check for both names to give people time to re-install their private fd files with lowercase names.

```

486     \edef\reserved@a{%
487         \lowercase{%
488             \noexpand\InputIfFileExists{\f@encoding\f@family.fd}}}%
489     \reserved@a\relax
490     {\@input@\f@encoding\f@family.fd}%
491 \fi}

```

*(End of definition for \define@newfont.)*

**\nfss@catcodes** This macro should contain the standard `\catcode` assignments to all characters which are used in the commands found in an `.fd` file and which might have special `\catcodes` in the middle of a document. If necessary, this list can be extended in a package file using a suitable number of `\expandafter`, i.e.,

```
\expandafter\def\expandafter\nfss@catcodes
\expandafter{\nfss@catcodes <additional settings>}
```

Note, that this macro might get executed several times since it is also called by `\DeclareFontShape`, thus it probably should not be misused as a general purpose hook.

```
492 \def\nfss@catcodes{%
```

We start by making `@` a letter and ignoring all blanks and newlines.

```
493 \makeatletter
494 \catcode'\ 9%
495 \catcode'\^~I9%
496 \catcode'\^~M9%
```

Then we set up `\`, `{`, `}`, `#` and `%` in case an `.fd` file is loaded during a verbatim environment.

```
497 \catcode'\\\z@
498 \catcode'\{\@ne
499 \catcode'\}\tw@
500 \catcode'\#6%
501 \catcode'\^7%
502 \catcode'\%14%
```

The we make sure that the important syntax parts have the right `\catcode`.

```
503 \@makeother\<%
504 \@makeother\>%
505 \@makeother\*%
506 \@makeother\.%
507 \@makeother\-%
508 \@makeother\/%
509 \@makeother\[%
510 \@makeother\]%
511 \@makeother\'%
512 \@makeother\'%
513 \@makeother\"%
514 }
```

*(End of definition for \nfss@catcodes.)*

`\LoadFontDefinitionFile` Load and `.fd` files for some encoding and family (if it exists).

```
515 </2kernel>
516 <*2kernel | latexrelease>
517 <latexrelease>\IncludeInRelease{2020/02/02}%
518 <latexrelease>\LoadFontDefinitionFile}{Loading .fd files}%
519 \def\LoadFontDefinitionFile#1#2{%
520 \begingroup
521 \edef\f@encoding{#1}%
522 \edef\f@family{#2}%
523 \try@load@fontshape
524 \endgroup
525 }
526 </2kernel | latexrelease>
527 <latexrelease>\EndIncludeInRelease
528 <latexrelease>\IncludeInRelease{0000/00/00}%
529 <latexrelease>\LoadFontDefinitionFile}{Loading .fd files}%
530 <latexrelease>
```

```

531 \let\LoadFontDefinitionFile\undefined
532 \let\EndIncludeInRelease
533 \*2ekernel

```

(End of definition for \LoadFontDefinitionFile.)

`\DeclareFontFamilySubstitution` The idea for this macro is stolen from the `substitutefont` package by Günter Milde, with some modifications and a new name.

Its purpose is to provide characters in a special encoding that are not available in the current font family to be taken from a different family that is visually compatible (or not if you choose badly). For example, you can match the GFS Didot Greek characters with T<sub>E</sub>X Gyre Pagella (Palatino) by specifying

```
\DeclareFontFamilySubstitution{LGR}{qpl}{udidot}
```

This way if you ask for the LGR encoding in for the `qpl` family you get the characters from the `udidot` family substituted.

We need to ensure that the macro is defined with `\nfss@catcodes` in force (not quite sure why at the moment to be honest).

```

534 \</2ekernel>
535 \*2ekernel | latexrelease>
536 \<latexrelease>\IncludeInRelease{2020/02/02}%
537 \<latexrelease>      {\DeclareFontFamilySubstitution}{Provide family substitution}%
538 \beginingroup
539 \nfss@catcodes
540 \gdef\DeclareFontFamilySubstitution#1#2#3{%

```

We only provide a set of silent substitutions. The package also (re)declared the family, but this is incorrect in my eyes and it is better to handle that differently.

Of course the families may still need loading at this point and so we arrange for this. Otherwise we might run into trouble because the necessary `\DeclareFontFamily` has not been seen.

```

541 \LoadFontDefinitionFile{#1}{#2}%
542 \LoadFontDefinitionFile{#1}{#3}%
543 \DeclareFontShape{#1}{#2}{m}{it}{<->ssub * #3/m/it}{}%
544 \DeclareFontShape{#1}{#2}{m}{n}{<->ssub * #3/m/n}{}%
545 \DeclareFontShape{#1}{#2}{m}{sc}{<->ssub * #3/m/sc}{}%
546 \DeclareFontShape{#1}{#2}{m}{sl}{<->ssub * #3/m/sl}{}%

```

These days a few more shapes might be around, so we declare those too. If they don't exist then after the first substitution normal fallbacks will happen.

```

547 \DeclareFontShape{#1}{#2}{m}{sw}{<->ssub * #3/m/sw}{}%
548 \DeclareFontShape{#1}{#2}{m}{scit}{<->ssub * #3/m/scit}{}%
549 \DeclareFontShape{#1}{#2}{m}{scsl}{<->ssub * #3/m/scsl}{}%

```

Same game with `b` and `bx`, for other weights you are on your own:

```

550 \DeclareFontShape{#1}{#2}{b}{it}{<->ssub * #3/b/it}{}%
551 \DeclareFontShape{#1}{#2}{b}{n}{<->ssub * #3/b/n}{}%
552 \DeclareFontShape{#1}{#2}{b}{scit}{<->ssub * #3/b/scit}{}%
553 \DeclareFontShape{#1}{#2}{b}{scsl}{<->ssub * #3/b/scsl}{}%
554 \DeclareFontShape{#1}{#2}{b}{sc}{<->ssub * #3/b/sc}{}%
555 \DeclareFontShape{#1}{#2}{b}{sl}{<->ssub * #3/b/sl}{}%
556 \DeclareFontShape{#1}{#2}{b}{sw}{<->ssub * #3/b/sw}{}%
557 \DeclareFontShape{#1}{#2}{bx}{it}{<->ssub * #3/bx/it}{}%

```

```

558 \DeclareFontShape{#1}{#2}{bx}{n}{<->ssub * #3/bx/n}{}%
559 \DeclareFontShape{#1}{#2}{bx}{scit}{<->ssub * #3/bx/scit}{}%
560 \DeclareFontShape{#1}{#2}{bx}{scsl}{<->ssub * #3/bx/scsl}{}%
561 \DeclareFontShape{#1}{#2}{bx}{sc}{<->ssub * #3/bx/sc}{}%
562 \DeclareFontShape{#1}{#2}{bx}{sl}{<->ssub * #3/bx/sl}{}%
563 \DeclareFontShape{#1}{#2}{bx}{sw}{<->ssub * #3/bx/sw}{}%
564 }
565 \endgroup
566 </2ekernel | latexrelease>
567 <latexrelease>\EndIncludeInRelease
568 <latexrelease>\IncludeInRelease{0000/00/00}%
569 <latexrelease> \DeclareFontFamilySubstitution{Provide family substitution}%
570 <latexrelease>
571 <latexrelease>\let\DeclareFontFamilySubstitution\@undefined
572 <latexrelease>\EndIncludeInRelease
573 <*2ekernel>

```

(End of definition for \DeclareFontFamilySubstitution.)

**\DeclareErrorFont** Declare the last resort shape! We assume that in this fontshape there is a 10pt font but it doesn't really matter. We only loose one macro name if the assumption is false. But at least the font should be there!

```

574 </2ekernel>
575 <*2ekernel | latexrelease>
576 <latexrelease>\IncludeInRelease{2019/10/01}%
577 <latexrelease> \DeclareErrorFont{No side effects please}%
578 \def\DeclareErrorFont#1#2#3#4#5{%
579 \xdef\error@fontshape{%
580 \noexpand\expandafter\noexpand\split@name\noexpand\string
581 \expandafter\noexpand\csname#1/#2/#3/#4/#5\endcsname
582 \noexpand\@nil}%

```

Initialize all those internal variables which may or may not have values in the first seconds of NFSS' bootstrapping process. Later on such values will be updated when an encoding is selected, etc.

We definitely don't want to set \f@encoding; we can set all the others since if they are left "blank" any selection would grab "error default values" as well. However, this probably should go also—and now it did.

```

583 % \gdef\f@encoding{#1}%
584 \gdef\default@family{#2}%
585 \gdef\default@series{#3}%
586 \gdef\default@shape{#4}%
587 }
588 </2ekernel | latexrelease>
589 <latexrelease>\EndIncludeInRelease
590 <latexrelease>\IncludeInRelease{0000/00/00}%
591 <latexrelease> \DeclareErrorFont{No side effects please}%
592 <latexrelease>
593 <latexrelease>\def\DeclareErrorFont#1#2#3#4#5{%
594 <latexrelease> \xdef\error@fontshape{%
595 <latexrelease> \noexpand\expandafter\noexpand\split@name\noexpand\string
596 <latexrelease> \expandafter\noexpand\csname#1/#2/#3/#4/#5\endcsname
597 <latexrelease> \noexpand\@nil}%
598 <latexrelease> \gdef\default@family{#2}%

```

```

599 <latexrelease>      \gdef\default@series{#3}%
600 <latexrelease>      \gdef\default@shape{#4}%
601 <latexrelease>      \global\let\f@family\default@family
602 <latexrelease>      \global\let\f@series\default@series
603 <latexrelease>      \global\let\f@shape\default@shape
604 <latexrelease>      \gdef\f@size{#5}%
605 <latexrelease>      \gdef\f@baselineskip{#5pt}%
606 <latexrelease>}}
607 <latexrelease>\EndIncludeInRelease
608 <*2ekernel>
609 \@onlypreamble\DeclareErrorFont

```

(End of definition for \DeclareErrorFont.)

`\wrong@fontshape` Before we come to the macro `\extract@font` we have to take care of unknown `\curr@fontshape` combinations. The general strategy is to issue a warning and to try a default *shape*, then a default *series*, and finally a default *family*. If this last one also fails T<sub>E</sub>X will go into an infinite loop. But if the defaults are set incorrectly one deserves nothing else!

```

610 </2ekernel>
611 <latexrelease>\IncludeInRelease{2015/01/01}{\wrong@fontshape}%
612 <latexrelease>      {Font substitution in preamble}%
613 <*2ekernel | latexrelease>
614 \def\wrong@fontshape{%
615     \csname D@f@encoding\endcsname % install defaults if in math

```

We remember the wanted `\curr@fontshape` combination which we will need in a moment.

```

616     \edef\reserved@a{\csname\curr@fontshape\endcsname}%
617     \ifx\last@fontshape\reserved@a
618         \errmessage{Corrupted NFSS tables}%
619         \error@fontshape
620     \else

```

Then we warn the user about the mess and set the shape to its default.

```

621     \let\f@shape\default@shape

```

If the combination is not known, try the default *series*.

```

622     \expandafter\ifx\csname\curr@fontshape\endcsname\relax
623         \let\f@series\default@series

```

If this is still undefined, try the default *family*. Otherwise give up. We never try to change the encoding scheme!

```

624     \expandafter
625     \ifx\csname\curr@fontshape\endcsname\relax
626         \let\f@family\default@family

```

If we change the font family and we are in the preamble then the corresponding `.fd` file may not been loaded yet. Therefore we try this now. Otherwise equating the requested font shape with the finally selected fontshape below will fail and can result in “NFSS tables corrupted”. After begin document that will not happen as all `.fd` files involved in substitution are loaded at `\begin{document}`.

```

627         \begingroup
628         \try@load@fontshape
629         \endgroup
630     \fi \fi
631 \fi

```

At this point a valid `\curr@fontshape` combination must have been found. We inform the user about this fact.

The `\expandafter\string` here stops  $\TeX$  adding the space that it usually puts after command names in messages. The similar construction with `\@undefined` just produces ‘undefined’, but saves a few tokens.

`\@wrong@font@char` is locally redefined in `\UseTextSymbol` from its normal (empty) definition, to report the symbol generating the font switch.

```
632 \font@warning{Font shape ‘\expandafter\string\reserved@a’
633 \expandafter\@gobble\string\@undefined\MessageBreak
634 using ‘\curr@fontshape’ instead\@wrong@font@char}%
635 \global\let\last@fontshape\reserved@a
```

We change `\@defaultsubs` to produce a warning at the end of the document. The macro `\@defaultsubs` is initially `\relax` but gets changed here if some default font substitution happens. It is then executed in `\enddocument`.

```
636 \gdef\@defaultsubs{%
637 \font@warning{Some font shapes were not available, defaults
638 substituted.\@gobbletwo}}%
```

If we substitute a `\curr@fontshape` combination by the default one we don’t want the warning to be printed out whenever this (unknown) combination is used. Therefore we globally `\let` the macro corresponding to the wanted combination equal to its substitution. This requires the use of four `\expandafter`’s since `\csname...\endcsname` has to be expanded before `\reserved@a` (i.e. the requested combination), and this must happen before the `\let` is executed.

```
639 \global\expandafter\expandafter\expandafter\let
640 \expandafter\reserved@a
641 \csname\curr@fontshape\endcsname
```

Now we can redefine `\font@name` accordingly. This *must* be done globally since it might occur in the group opened by `\define@newfont`. If we would this definition were local the closing `\endgroup` there would restore the old meaning of `\font@name` and then switch to the wrong font at the end of `\selectfont` although the correct font was loaded.

```
642 \xdef\font@name{%
643 \csname\curr@fontshape/\f@size\endcsname}%
```

The last thing this macro does is to call `\pickup@font` again to load the font if it is not defined yet. At this point this code will loop endlessly if the defaults are not well defined.

```
644 \pickup@font}
645 </2ekernel|latexrelease>
646 <latexrelease>\EndIncludeInRelease
647 <latexrelease>\IncludeInRelease{0000/00/00}{\wrong@fontshape}%
648 <latexrelease> {Font substitution in preamble}%
649 <latexrelease>\def\wrong@fontshape{%
650 <latexrelease> \csname D@f@encoding\endcsname
651 <latexrelease> \edef\reserved@a{\csname\curr@fontshape\endcsname}%
652 <latexrelease> \ifx\last@fontshape\reserved@a
653 <latexrelease> \errmessage{Corrupted NFSS tables}%
654 <latexrelease> \error@fontshape
655 <latexrelease> \else
656 <latexrelease> \let\f@shape\default@shape
657 <latexrelease> \expandafter\ifx\csname\curr@fontshape\endcsname\relax
658 <latexrelease> \let\f@series\default@series
659 <latexrelease> \expandafter
```

```

660 <latexrelease>          \ifx\curname\curr@fontshape\endcsname\relax
661 <latexrelease>          \let\f@family\default@family
662 <latexrelease>          \fi \fi
663 <latexrelease>    \fi
664 <latexrelease>    \@font@warning{Font shape
665 <latexrelease>          '\expandafter\string\reserved@a'
666 <latexrelease>          \expandafter\@gobble\string\@undefined
667 <latexrelease>          \MessageBreak
668 <latexrelease>          using '\curr@fontshape' instead\@wrong@font@char}%
669 <latexrelease>    \global\let\last@fontshape\reserved@a
670 <latexrelease>    \gdef\@defaultsubs{%
671 <latexrelease>      \@font@warning{Some font shapes were not available,
672 <latexrelease>                defaults substituted.\@gobbletwo}}%
673 <latexrelease>    \global\expandafter\expandafter\expandafter\let
674 <latexrelease>      \expandafter\reserved@a
675 <latexrelease>      \curname\curr@fontshape\endcsname
676 <latexrelease>    \xdef\font@name{%
677 <latexrelease>      \curname\curr@fontshape/\f@size\endcsname}%
678 <latexrelease>    \pickup@font}
679 <latexrelease>\EndIncludeInRelease
680 <*2ekernel>

```

(End of definition for \wrong@fontshape.)

\@wrong@font@char Normally empty but redefined in \UseTextSymbol so that the Font shape undefined message can refer to the symbol causing the problem.

```
681 \let\@wrong@font@char\@empty
```

(End of definition for \@wrong@font@char.)

\@@defaultsubs See above.

```
\@defaultsubs 682 \let\@defaultsubs\relax
```

(End of definition for \@@defaultsubs and \@defaultsubs.)

\strip@prefix In \extract@font we will need a way to recover the replacement text of a macro. This is done by the primitive \meaning together with the macro \strip@prefix (for the details see appendix D of the T<sub>E</sub>Xbook, p. 382).

```
683 \def\strip@prefix#1>{\}
```

(End of definition for \strip@prefix.)

## 4 Assigning math fonts to *versions*

\install@mathalphabet This is just another name for \gdef but we can redefine it if necessary later on.

```
684 \let\install@mathalphabet\gdef
```

(End of definition for \install@mathalphabet.)

\math@fonts

```
685 \let\math@fonts\@empty
```

(End of definition for \math@fonts.)

`\select@group` `\select@group` has four arguments: the new  $\langle\textit{math alphabet identifier}\rangle$  (a control sequence), the  $\langle\textit{math group number}\rangle$ , the extra macro for math mode and the `\curr@fontshape` definition macro name. We first check if we are in math mode.

```
686 %\def\select@group#1#2#3{\relax\ifmmode
```

We do these things locally using `\begingroup` instead of `\bgroup` to avoid the appearance of an empty Ord atom on the math list.

```
687 % \begingroup
```

We set the math fonts for the *family* in question by calling `\getanddefine@fonts` in the correct environment.

```
688 % \escapechar\m@ne
```

```
689 % \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
```

We globally select the math fonts...

```
690 % \globaldefs\@ne \math@fonts
```

... and close the group to restore `\globaldefs` and `\escapechar`.

```
691 % \endgroup
```

As long as no *size* or *version* change occurs the  $\langle\textit{math alphabet identifier}\rangle$  should simply switch to the installed *math group* instead of calling `\select@group` unnecessarily. So we globally redefine the first argument (the new  $\langle\textit{math alphabet identifier}\rangle$ ) to expand into a `\mathgroup` switch and then select this *alphabet*. Note that this redefinition will be overwritten by the next call to a *version* macro. The original code for the end of `\select@group` was

```
\gdef#1{#3\mathgroup #2}#1\fi}
```

i.e. first redefining the  $\langle\textit{math alphabet identifier}\rangle$  and then calling the new definition to switch to the wanted  $\langle\textit{math group}\rangle$ . Now we define the  $\langle\textit{math alphabet identifier}\rangle$  as a call to the `\use@mathgroup` command.

```
692 % \xdef#1{\noexpand\use@mathgroup\noexpand#2%
```

```
693 % {\number\csname c@mv@\math@version\endcsname}}%
```

But this is not sufficient, as we learned the hard way. The problem here is that the loading of the fonts that comprise the alphabet identifier `#1`, as well as the necessary math font assignments is deferred until it is used. This is OK so far, but if the fonts are switched within the current formula (which may happen if a sub-formula is a box that contains a math version switch) the font assignments for `#1` are not restored unless `#1` is used again. This is disastrous since TeX sees the wrong fonts at the end of the math formula, when it converts the math list into a horizontal list.

This is taken into account as follows: When a math alphabet identifier is used for the first time in a certain version it modifies the corresponding macro `\mv@<version>` so that it calls `\getanddefine@fonts` directly in future as well. We use the macro `\extract@alph@from@version` to do this. It takes the math alphabet identifier `#1` and the math version macro as arguments.

```
694 % \expandafter\extract@alph@from@version
```

```
695 % \csname mv@\math@version\expandafter\endcsname
```

```
696 % \expandafter{\number\csname c@mv@\math@version\endcsname}%
```

```
697 % #1%
```

```
698 % \stepcounter{mv@\math@version}%
```

Finally, it is not possible to simply call the new definition since we have an argument (the third argument of `\use@mathgroup` or more exactly the argument of `\math@egroup` if the `margid` option is in force) which would swallow our closing `\fi`. So we use the `\expandafter` technique to remove the `\fi` before the `\use@mathgroup` is expanded.

```
699 %\expandafter #1\fi}
```

(End of definition for `\select@group`.)

`\extract@alph@from@version`

We proceed to the definition of the macro `\extract@alph@from@version`. As stated above, it takes a math alphabet identifier and a math version macro (e.g. `\mv@normal`) as its arguments.

```
700 \def\extract@alph@from@version#1#2#3{%
```

To extract and replace the definition of math alphabet identifier `#3` in macro `#1` we have to recall how this definition looks like: Somewhere in the replacement text of `#1` there is the sequence

```
\install@mathalphabet<math alphabet identifier> #3{%
  <Definitions for >#3}
```

Hence, the first thing we do is to extract the tokens preceding this definitions, the definition itself, and the tokens following it. To this end we define one auxiliary macro `\reserved@a`.

```
701 \def\reserved@a##1\install@mathalphabet#3##2##3\@nil{%
```

When `\reserved@a` is expanded, it will have the tokens preceding the definition in question in its first argument (`##1`), the following tokens in its third argument (`##3`), and the replacement text for the math alphabet identifier `#3` in its second argument. (`##2`). This is then recorded for later use in a temporary macro `\reserved@b`.

```
702 \def\reserved@b{##2}%
```

Additionally, we define a macro `\reserved@c` to reconstruct the definitions for the math version in question from the tokens that will remain unchanged (`##1` and `##3`) and the yet to build new definitions for the math alphabet identifier `#3`.

```
703 \def\reserved@c####1{\gdef#1{##1####1##3}}%
```

Then we execute our auxiliary macro.

```
704 \expandafter\reserved@a#1\@nil
```

OK, so now we have to build the new definition for `#3`. To do so, we first extract the interesting parts out of the old one. The old definition looks like:

```
\select@group<math alphabet identifier>
  <math group number><math extra part>
<curr@fontshape definition>
```

So we define a new temporary macro `\reserved@a` that extracts these parts.

```
705 \def\reserved@a\select@group#3##1##2\@nil{%
```

This macro can now directly rebuild the math version definition by calling `\reserved@c`:

```
706 \reserved@c{%
707 \getanddefine@fonts{#2}##2%
708 \install@mathalphabet#3{%
709 \relax\ifmmode \else \non@alpherr#3\fi
710 \use@mathgroup##1{#2}}%
```

In addition it defines the alphabet the way it should be used from now on.

```
711 \gdef#3{\relax\ifmmode \else \non@alpherr#3\fi
712 \use@mathgroup##1{#2}}}%
```

Finally, we only have to call this macro `\reserved@a` on the old definitions recorded in `\reserved@b`:

```
713 \expandafter\reserved@a\reserved@b\@nil
714 }
```

*(End of definition for \extract@alph@from@version.)*

`\math@bgroup` Here are the default definitions for `\math@bgroup` and `\math@egroup`. We use `\bgroup` instead of `\begingroup` to avoid ‘leaking out’ of style changes. This has the side effect of always producing mathord atoms.

```
715 \let\math@bgroup\bgroup
716 \def\math@egroup#1{#1\egroup}
```

*(End of definition for \math@bgroup and \math@egroup.)*

`\calculate@math@sizes` Here is the default definition for `\calculate@math@sizes` a more elaborate interface is under testing in `mthscale.sty`.

```
717 \gdef\calculate@math@sizes{%
718 \font@info{Calculating\space math\space sizes\space for\space
719 size\space <\f@size>}%
720 \dimen@ \f@size \p@
721 \tempdimb \defaultscriptratio \dimen@
722 \dimen@ \defaultscriptscriptratio \dimen@
723 \expandafter\xdef\csname S@\f@size\endcsname{%
724 \gdef\noexpand\tf@size{\f@size}%
725 \gdef\noexpand\s@size{\strip@pt\tempdimb}%
726 \gdef\noexpand\ssf@size{\strip@pt\dimen@}%
727 \noexpand\math@fontstrue}}
```

*(End of definition for \calculate@math@sizes.)*

`\defaultscriptratio` The default ratio for math sizes is:  
`\defaultscriptscriptratio` 1 to `\defaultscriptratio` to `\defaultscriptscriptratio`.  
 By default this is 1 to .7 to .5.

```
728 \def\defaultscriptratio{.7}
729 \def\defaultscriptscriptratio{.5}
```

*(End of definition for \defaultscriptratio and \defaultscriptscriptratio.)*

`\noaccents@` If we don’t have a definition for `\noaccents@` we provide a dummy.

```
730 \ifx\noaccents@\@undefined
731 \let\noaccents@\@empty
732 \fi
```

*(End of definition for \noaccents@.)*

`\showhyphens` The `\showhyphens` command must be redefined since the version in `plain.tex` uses `\tenrm`. We have also made some further adjustments for its use in L<sup>A</sup>T<sub>E</sub>X.

```

733 </2ekernel>
734 <latexrelease>\IncludeInRelease{2017/01/01}{\showhyphens}%
735 <latexrelease>                {XeTeX support for \showhyphens}%
736 <*2ekernel|latexrelease>
737 \ifx\XeTeXcharclass\@undefined
Version for engines other than XeTEX.
738 \DeclareRobustCommand\showhyphens[1]{%
739   \setbox0\vbox{%
740     \color@begingroup
741     \tracinglostchars\z@
742     \everypar{}%
743     \parfillskip\z@skip\hsize\maxdimen
744     \normalfont
745     \pretolerance\m@ne\tolerance\m@ne\hbadness\z@\showboxdepth\z@\ #1%
746     \color@endgroup}}
747 \else

```

XeT<sub>E</sub>X version. When using system fonts XeT<sub>E</sub>X reports consecutive runs of characters as a single item in box logging, which means the standard `\showhyphens` does not work. This version typesets the text into a narrow box to force hyphenation and then reconstructs a horizontal list with explicit hyphens to generate the display. Note that the `lmr` OpenType font is forced, this works even if the characters are not in the font as hyphenation is attempted due to the width of the space and hyphen character. It would generate spurious Missing Character warnings in the log, these are however suppressed from the terminal and log output by ensuring that `\tracinglostchars` is locally zero.

```

748 \DeclareRobustCommand\showhyphens[1]{%
749   \setbox0\vbox{%
750     \usefont{TU}{lmr}{m}{n}%
751     \hsize 1sp %
752     \hbadness\@M
753     \hfuzz\maxdimen
754     \tracingonline\z@
755     \tracinglostchars\z@
756     \everypar={}%
757     \leftskip\z@skip
758     \rightskip\z@skip
759     \parfillskip\z@skip
760     \hyphenpenalty=-\@M
761     \pretolerance\m@ne
762     \interlinepenalty\z@
763     \clubpenalty\z@
764     \widowpenalty\z@
765     \brokenpenalty1127 %
766     \setbox\z@\hbox{}%
767     \noindent
768     \hskip\z@skip
769     #1%
770     \par

```

Note here we stop the loop if made no progress, non-removable items may mean that we can not process the whole list (which would be testable as `\lastnodetype=-1`).

```

771 \loop
772 \@tempswafalse
773 \ifnum\lastnodetype=11\unskip\@tempswatrue\fi
774 \ifnum\lastnodetype=12\unkern\@tempswatrue\fi
775 \ifnum\lastnodetype=13 %
776 \count@\lastpenalty
777 \unpenalty\@tempswatrue
778 \fi
779 \ifnum\lastnodetype=\@ne
780 \setbox\tw@\lastbox\@tempswatrue
781 \setbox0\hbox{\unhbox\tw@\unskip\unskip\unpenalty
782 \ifnum\count@=1127 \else\ \fi
783 \unhbox0}%
784 \count@\z@
785 \fi
786 \if@tempswa
787 \repeat
788 \hbadness\z@
789 \hsize\maxdimen
790 \showboxdepth\z@
791 \tolerance\m@ne
792 \hyphenpenalty\z@
793 \noindent\unhbox\z@
794 }}
795 \fi

796 </2ekernel | latexrelease>
797 <latexrelease>\EndIncludeInRelease
798 <latexrelease>\IncludeInRelease{0000/00/00}{\showhyphens}%
799 <latexrelease> {XeTeX support for \showhyphens}%
800 <latexrelease>\gdef\showhyphens#1{%
801 <latexrelease> \setbox0\vbox{%
802 <latexrelease> \color@begingroup
803 <latexrelease> \everypar{%
804 <latexrelease> \parfillskip\z@skip\hsize\maxdimen
805 <latexrelease> \normalfont
806 <latexrelease> \pretolerance\m@ne\tolerance\m@ne
807 <latexrelease> \hbadness\z@\showboxdepth\z@\ #1%
808 <latexrelease> \color@endgroup}}
809 <latexrelease>\EndIncludeInRelease
810 <*2ekernel>

```

*(End of definition for \showhyphens.)*

**\addto@hook** We need a macro to add tokens to a hook.

```
811 \long\def\addto@hook#1#2{#1\expandafter{\the#1#2}}
```

*(End of definition for \addto@hook.)*

**\@vpt**

```
812 \def\@vpt{5}
```

*(End of definition for \@vpt.)*

```

\@vipt
813 \def\@vipt{6}
      (End of definition for \@vipt.)

\@viipt
814 \def\@viipt{7}
      (End of definition for \@viipt.)

\@viipt
815 \def\@viipt{8}
      (End of definition for \@viipt.)

\@ixpt
816 \def\@ixpt{9}
      (End of definition for \@ixpt.)

\@xpt
817 \def\@xpt{10}
      (End of definition for \@xpt.)

\@xipt
818 \def\@xipt{10.95}
      (End of definition for \@xipt.)

\@xiipt
819 \def\@xiipt{12}
      (End of definition for \@xiipt.)

\@xivpt
820 \def\@xivpt{14.4}
      (End of definition for \@xivpt.)

\@xvipt
821 \def\@xvipt{17.28}
      (End of definition for \@xvipt.)

\@xxpt
822 \def\@xxpt{20.74}
      (End of definition for \@xxpt.)

\@xxvpt
823 \def\@xxvpt{24.88}
      (End of definition for \@xxvpt.)
824 </2ekernel>

```

## File 25

# ltfssaxes.dtx

This file contains the implementation for handling extra axes by splitting the series and the shape values into sub-categories. See other parts of the L<sup>A</sup>T<sub>E</sub>X distribution, or *The L<sup>A</sup>T<sub>E</sub>X Companion* for higher level documentation of the L<sup>A</sup>T<sub>E</sub>X Font Selection Scheme.

```
1 <2ekernel>\message{NFSS axes,}
```

Everything in the this file got introduced 2020/02/02, so we use large rollback chunks, only interrupted if necessary.

```
2 <*2ekernel | latexrelease>
```

```
3 <latexrelease>\IncludeInRelease{2025/06/01}%
```

```
4 <latexrelease> {\DeclareFontSeriesChangeRule}{Series change rules}%
```

## 1 Changing the font series

In the original NFSS implementation the series was a single attribute stored in `\f@series` and so one always had to specify both weight and width together. This meant that it was impossible to typeset a paragraph in a condensed font and inside have a few words in bold weight (but still condensed) without doing this manually by requesting `\fontseries{bc}\selectfont`.

The new implementation now works differently, by looking at both the current value of `\f@series` and the requested new series; these are then used to select a new series value. Thus, if the current series is `c` and we ask for `b` we now get `bc`.

This is done by consulting a simple lookup table. This table is configurable (though most likely that flexibility will seldom if ever be needed). Adding or changing entries in this table is done with `\DeclareFontSeriesChangeRule`.

### 1.1 The series lookup table

`\DeclareFontSeriesChangeRule` The macro `\DeclareFontSeriesChangeRule` defines entries in a simple database (implemented as a set of commands) that define mappings from the current series and a requested new series to a result series (and additionally offers an alternative if the desired one is unavailable):

**#1** current `\f@series`

**#2** requested new series

**#3** result (provided this series exists in the given font family)

**#4** alternative result (if **#3** does not exist)

If an `.fd` file has its own substitution rules then **#3** exist and thus **#4** is not applied.

If there is no matching database entry, or if neither the result nor the alternative result exists in this font family, then the requested new series is used (which then may trigger substitutions later on).

```
5 \def\DeclareFontSeriesChangeRule#1#2#3#4{%
```

```
6 \@namedef{series@#1@#2}{{#3}{#4}}}
```

(End of definition for `\DeclareFontSeriesChangeRule`.)

## 1.2 Mapping rules for series changes

The rules set up use explicit series values not `\..default` indirections; my current feeling is that this is in fact better.

With 9 weight values (from `ul` to `ub`) and 9 width values (from `uc` to `ux`), this table is now rather large (far more than 1000 entries), but, on the other hand, the table doesn't change and accessing rules is fast when using a table implemented in this way.

We could alternatively split the axis and maintain weight and width separately, but that would take more processing time and would not allow for setting up explicit exceptions nicely (not sure that this would ever get used though).

Design considerations for mapping entries:

- We make `m` reset both weight and width (as this is how it always worked). To reset just the width `?m` is provided and to reset just the weight `m?` is provided.
- We support “`m<width>`” and “`<weight>m`”, e.g., `mec` to mean “go to medium weight and extra-condensed width”. At the end of the process we automatically drop any leftover `m` in the series name (unless it is just a single `m`).
- If there is no table entry then the requested series is used unconditionally. This means that we usually do not need entries where the second argument (the requested series) and the third argument (the result series) are identical (unless we want to use the fourth argument to specify an alternative result series). In particular, this means:
  - Any request for `m` needs no entry, i.e., there are no entries which have `m` as the second argument.
  - Any request to set both weight and width (e.g., `sbx` or `ulc`) needs no entry. For that reason, there are no entries which have a weight+width as second argument (except for cases involving `bx`, see below). In particular, this is also true for cases involving `m`, e.g., `bm` (bold medium width) which automatically gets reduced to `b`, or `mc` (medium weight condensed) which becomes `c` as a result.

There is one exception: we do have rules for a request for `bx`; this is because the Computer Modern fonts (or related families like Latin Modern) need `bx` as their bold series default (`\bfdefault`), since they only have a `b` series for a restricted set of font faces. Many other font families have only `b` but no `bx`, so we have explicit rules that fall back from `bx` to `b`.

- For each combination of a non-`m` `<weight>` and a non-`m` `<width>`, there are 19 entries which have “`<weight><width>`” as first argument: 8 of them have the weight values from `ul` to `ub` except `m` as second argument, another 8 have the width values from `uc` to `ux` except `m` as second argument, and (further down in this file) there is one entry which has `bx` as second argument and two further entries which have `m?` and `?m` as second argument. Rules which have `m` or a weight+width (other than `bx`) as second argument aren't needed (see above).
- For each non-`m` `<weight>`, there are at least 11 entries which have “`<weight>`” as first argument: 8 of them have the width values from `uc` to `ux` except `m` as second argument, and (further down in this file) there is one entry which has `bx` as second argument and two further entries which have `m?` and `?m` as second argument. Rules which have a single weight value as second argument aren't needed because the

second and third arguments would then be identical. In some cases, there are extra rules which make use of the fourth argument to specify an alternative result series.

- Similarly, for each non- $\mathbf{m}$   $\langle width \rangle$ , there are at least 11 entries which have “ $\langle width \rangle$ ” as first argument: 8 of them have the weight values from  $\mathbf{ul}$  to  $\mathbf{ub}$  except  $\mathbf{m}$  as second argument, and (further down in this file) there is one entry which has  $\mathbf{bx}$  as second argument and two further entries which have  $\mathbf{m?}$  and  $\mathbf{?m}$  as second argument. Rules which have a single width value as second argument aren’t needed because the second and third arguments would then be identical. In some cases, there are extra rules which make use of the fourth argument to specify an alternative result series.
- Only a few entries have “alternative” values.

The idea is that you don’t want the normal substitution to kick in because that would reset the shape first and it may be better to stay with  $\mathbf{b}$  when a change to  $\mathbf{c}$  is requested and  $\mathbf{bc}$  doesn’t exist, than to go to first change the shape to  $\mathbf{n}$  and then find that  $\mathbf{bc/n}$  doesn’t exist either and thus ending up with  $\mathbf{m/n}$ .

We do this, for example, when  $\mathbf{sb}$ ,  $\mathbf{eb}$ , or  $\mathbf{ub}$  is requested but can’t be fulfilled. In that case it is better to try to stay with some sort of bold rather than ending up with  $\mathbf{m}$ . There are some other cases where an “alternative” value is specified; these are explained below in the appropriate places.

```

7 \DeclareFontSeriesChangeRule {uluc}{ul} {uluc} {}
8 \DeclareFontSeriesChangeRule {uluc}{el} {eluc} {}
9 \DeclareFontSeriesChangeRule {uluc}{l} {luc} {}
10 \DeclareFontSeriesChangeRule {uluc}{sl} {sluc} {}
11 \DeclareFontSeriesChangeRule {uluc}{sb} {sbuc} {buc}
12 \DeclareFontSeriesChangeRule {uluc}{b} {buc} {}
13 \DeclareFontSeriesChangeRule {uluc}{eb} {ebuc} {buc}
14 \DeclareFontSeriesChangeRule {uluc}{ub} {ubuc} {buc}
15 \DeclareFontSeriesChangeRule {uluc}{uc} {uluc} {}
16 \DeclareFontSeriesChangeRule {uluc}{ec} {ulec} {}
17 \DeclareFontSeriesChangeRule {uluc}{c} {ulc} {}
18 \DeclareFontSeriesChangeRule {uluc}{sc} {ulsc} {}
19 \DeclareFontSeriesChangeRule {uluc}{sx} {ulsx} {}
20 \DeclareFontSeriesChangeRule {uluc}{x} {ulx} {}
21 \DeclareFontSeriesChangeRule {uluc}{ex} {ulex} {}
22 \DeclareFontSeriesChangeRule {uluc}{ux} {ulux} {}

23 \DeclareFontSeriesChangeRule {ulec}{ul} {ulec} {}
24 \DeclareFontSeriesChangeRule {ulec}{el} {elec} {}
25 \DeclareFontSeriesChangeRule {ulec}{l} {lec} {}
26 \DeclareFontSeriesChangeRule {ulec}{sl} {slec} {}
27 \DeclareFontSeriesChangeRule {ulec}{sb} {sbec} {bec}
28 \DeclareFontSeriesChangeRule {ulec}{b} {bec} {}
29 \DeclareFontSeriesChangeRule {ulec}{eb} {ebec} {bec}
30 \DeclareFontSeriesChangeRule {ulec}{ub} {ubec} {bec}
31 \DeclareFontSeriesChangeRule {ulec}{uc} {uluc} {}
32 \DeclareFontSeriesChangeRule {ulec}{ec} {ulec} {}
33 \DeclareFontSeriesChangeRule {ulec}{c} {ulc} {}
34 \DeclareFontSeriesChangeRule {ulec}{sc} {ulsc} {}
35 \DeclareFontSeriesChangeRule {ulec}{sx} {ulsx} {}
36 \DeclareFontSeriesChangeRule {ulec}{x} {ulx} {}
37 \DeclareFontSeriesChangeRule {ulec}{ex} {ulex} {}
38 \DeclareFontSeriesChangeRule {ulec}{ux} {ulux} {}

```

```

39 \DeclareFontSeriesChangeRule {ulc}{ul} {ulc} {}
40 \DeclareFontSeriesChangeRule {ulc}{el} {elc} {}
41 \DeclareFontSeriesChangeRule {ulc}{l} {lc} {}
42 \DeclareFontSeriesChangeRule {ulc}{sl} {slc} {}
43 \DeclareFontSeriesChangeRule {ulc}{sb} {sbc} {bc}
44 \DeclareFontSeriesChangeRule {ulc}{b} {bc} {}
45 \DeclareFontSeriesChangeRule {ulc}{eb} {ebc} {bc}
46 \DeclareFontSeriesChangeRule {ulc}{ub} {ubc} {bc}
47 \DeclareFontSeriesChangeRule {ulc}{uc} {uluc} {}
48 \DeclareFontSeriesChangeRule {ulc}{ec} {ulec} {}
49 \DeclareFontSeriesChangeRule {ulc}{c} {ulc} {}
50 \DeclareFontSeriesChangeRule {ulc}{sc} {ulsc} {}
51 \DeclareFontSeriesChangeRule {ulc}{sx} {ulsx} {}
52 \DeclareFontSeriesChangeRule {ulc}{x} {ulx} {}
53 \DeclareFontSeriesChangeRule {ulc}{ex} {ulex} {}
54 \DeclareFontSeriesChangeRule {ulc}{ux} {ulux} {}

55 \DeclareFontSeriesChangeRule {ulsc}{ul} {ulsc} {}
56 \DeclareFontSeriesChangeRule {ulsc}{el} {elsc} {}
57 \DeclareFontSeriesChangeRule {ulsc}{l} {lsc} {}
58 \DeclareFontSeriesChangeRule {ulsc}{sl} {slsc} {}
59 \DeclareFontSeriesChangeRule {ulsc}{sb} {sbsc} {bsc}
60 \DeclareFontSeriesChangeRule {ulsc}{b} {bsc} {}
61 \DeclareFontSeriesChangeRule {ulsc}{eb} {ebsc} {bsc}
62 \DeclareFontSeriesChangeRule {ulsc}{ub} {ubsc} {bsc}
63 \DeclareFontSeriesChangeRule {ulsc}{uc} {uluc} {}
64 \DeclareFontSeriesChangeRule {ulsc}{ec} {ulec} {}
65 \DeclareFontSeriesChangeRule {ulsc}{c} {ulc} {}
66 \DeclareFontSeriesChangeRule {ulsc}{sc} {ulsc} {}
67 \DeclareFontSeriesChangeRule {ulsc}{sx} {ulsx} {}
68 \DeclareFontSeriesChangeRule {ulsc}{x} {ulx} {}
69 \DeclareFontSeriesChangeRule {ulsc}{ex} {ulex} {}
70 \DeclareFontSeriesChangeRule {ulsc}{ux} {ulux} {}

71 \DeclareFontSeriesChangeRule {ul}{uc} {uluc} {}
72 \DeclareFontSeriesChangeRule {ul}{ec} {ulec} {}
73 \DeclareFontSeriesChangeRule {ul}{c} {ulc} {}
74 \DeclareFontSeriesChangeRule {ul}{sc} {ulsc} {}
75 \DeclareFontSeriesChangeRule {ul}{sx} {ulsx} {}
76 \DeclareFontSeriesChangeRule {ul}{x} {ulx} {}
77 \DeclareFontSeriesChangeRule {ul}{ex} {ulex} {}
78 \DeclareFontSeriesChangeRule {ul}{ux} {ulux} {}
79 \DeclareFontSeriesChangeRule {ul}{sb} {sb} {b}
80 \DeclareFontSeriesChangeRule {ul}{eb} {eb} {b}
81 \DeclareFontSeriesChangeRule {ul}{ub} {ub} {b}

82 \DeclareFontSeriesChangeRule {ulsx}{ul} {ulsx} {}
83 \DeclareFontSeriesChangeRule {ulsx}{el} {elsx} {}
84 \DeclareFontSeriesChangeRule {ulsx}{l} {lsx} {}
85 \DeclareFontSeriesChangeRule {ulsx}{sl} {slsx} {}
86 \DeclareFontSeriesChangeRule {ulsx}{sb} {sbsx} {bsx}
87 \DeclareFontSeriesChangeRule {ulsx}{b} {bsx} {}
88 \DeclareFontSeriesChangeRule {ulsx}{eb} {ebsx} {bsx}
89 \DeclareFontSeriesChangeRule {ulsx}{ub} {ubsx} {bsx}
90 \DeclareFontSeriesChangeRule {ulsx}{uc} {uluc} {}
91 \DeclareFontSeriesChangeRule {ulsx}{ec} {ulec} {}

```

```

92 \DeclareFontSeriesChangeRule {ulsx}{c} {ulc} {}
93 \DeclareFontSeriesChangeRule {ulsx}{sc} {ulsc} {}
94 \DeclareFontSeriesChangeRule {ulsx}{sx} {ulsx} {}
95 \DeclareFontSeriesChangeRule {ulsx}{x} {ulx} {}
96 \DeclareFontSeriesChangeRule {ulsx}{ex} {ulex} {}
97 \DeclareFontSeriesChangeRule {ulsx}{ux} {ulux} {}

98 \DeclareFontSeriesChangeRule {ulx}{ul} {ulx} {}
99 \DeclareFontSeriesChangeRule {ulx}{el} {elx} {}
100 \DeclareFontSeriesChangeRule {ulx}{l} {lx} {}
101 \DeclareFontSeriesChangeRule {ulx}{sl} {slx} {}
102 \DeclareFontSeriesChangeRule {ulx}{sb} {sbx} {bx}
103 \DeclareFontSeriesChangeRule {ulx}{b} {bx} {}
104 \DeclareFontSeriesChangeRule {ulx}{eb} {ebx} {bx}
105 \DeclareFontSeriesChangeRule {ulx}{ub} {ubx} {bx}
106 \DeclareFontSeriesChangeRule {ulx}{uc} {uluc} {}
107 \DeclareFontSeriesChangeRule {ulx}{ec} {ulec} {}
108 \DeclareFontSeriesChangeRule {ulx}{c} {ulc} {}
109 \DeclareFontSeriesChangeRule {ulx}{sc} {ulsc} {}
110 \DeclareFontSeriesChangeRule {ulx}{sx} {ulsx} {}
111 \DeclareFontSeriesChangeRule {ulx}{x} {ulx} {}
112 \DeclareFontSeriesChangeRule {ulx}{ex} {ulex} {}
113 \DeclareFontSeriesChangeRule {ulx}{ux} {ulux} {}

114 \DeclareFontSeriesChangeRule {ulex}{ul} {ulex} {}
115 \DeclareFontSeriesChangeRule {ulex}{el} {ele} {}
116 \DeclareFontSeriesChangeRule {ulex}{l} {lex} {}
117 \DeclareFontSeriesChangeRule {ulex}{sl} {slex} {}
118 \DeclareFontSeriesChangeRule {ulex}{sb} {sbex} {bex}
119 \DeclareFontSeriesChangeRule {ulex}{b} {bex} {}
120 \DeclareFontSeriesChangeRule {ulex}{eb} {ebex} {bex}
121 \DeclareFontSeriesChangeRule {ulex}{ub} {ubex} {bex}
122 \DeclareFontSeriesChangeRule {ulex}{uc} {uluc} {}
123 \DeclareFontSeriesChangeRule {ulex}{ec} {ulec} {}
124 \DeclareFontSeriesChangeRule {ulex}{c} {ulc} {}
125 \DeclareFontSeriesChangeRule {ulex}{sc} {ulsc} {}
126 \DeclareFontSeriesChangeRule {ulex}{sx} {ulsx} {}
127 \DeclareFontSeriesChangeRule {ulex}{x} {ulx} {}
128 \DeclareFontSeriesChangeRule {ulex}{ex} {ulex} {}
129 \DeclareFontSeriesChangeRule {ulex}{ux} {ulux} {}

130 \DeclareFontSeriesChangeRule {ulux}{ul} {ulux} {}
131 \DeclareFontSeriesChangeRule {ulux}{el} {elux} {}
132 \DeclareFontSeriesChangeRule {ulux}{l} {lux} {}
133 \DeclareFontSeriesChangeRule {ulux}{sl} {slux} {}
134 \DeclareFontSeriesChangeRule {ulux}{sb} {sbux} {bux}
135 \DeclareFontSeriesChangeRule {ulux}{b} {bux} {}
136 \DeclareFontSeriesChangeRule {ulux}{eb} {ebux} {bux}
137 \DeclareFontSeriesChangeRule {ulux}{ub} {ubux} {bux}
138 \DeclareFontSeriesChangeRule {ulux}{uc} {uluc} {}
139 \DeclareFontSeriesChangeRule {ulux}{ec} {ulec} {}
140 \DeclareFontSeriesChangeRule {ulux}{c} {ulc} {}
141 \DeclareFontSeriesChangeRule {ulux}{sc} {ulsc} {}
142 \DeclareFontSeriesChangeRule {ulux}{sx} {ulsx} {}
143 \DeclareFontSeriesChangeRule {ulux}{x} {ulx} {}
144 \DeclareFontSeriesChangeRule {ulux}{ex} {ulex} {}

```

```

145 \DeclareFontSeriesChangeRule {ulux}{ux} {ulux} {}
146 \DeclareFontSeriesChangeRule {eluc}{ul} {uluc} {}
147 \DeclareFontSeriesChangeRule {eluc}{el} {eluc} {}
148 \DeclareFontSeriesChangeRule {eluc}{l} {luc} {}
149 \DeclareFontSeriesChangeRule {eluc}{sl} {sluc} {}
150 \DeclareFontSeriesChangeRule {eluc}{sb} {sbuc} {buc}
151 \DeclareFontSeriesChangeRule {eluc}{b} {buc} {}
152 \DeclareFontSeriesChangeRule {eluc}{eb} {ebuc} {buc}
153 \DeclareFontSeriesChangeRule {eluc}{ub} {ubuc} {buc}
154 \DeclareFontSeriesChangeRule {eluc}{uc} {eluc} {}
155 \DeclareFontSeriesChangeRule {eluc}{ec} {elec} {}
156 \DeclareFontSeriesChangeRule {eluc}{c} {elc} {}
157 \DeclareFontSeriesChangeRule {eluc}{sc} {elsc} {}
158 \DeclareFontSeriesChangeRule {eluc}{sx} {elsx} {}
159 \DeclareFontSeriesChangeRule {eluc}{x} {elx} {}
160 \DeclareFontSeriesChangeRule {eluc}{ex} {elex} {}
161 \DeclareFontSeriesChangeRule {eluc}{ux} {elux} {}

162 \DeclareFontSeriesChangeRule {elec}{ul} {ulec} {}
163 \DeclareFontSeriesChangeRule {elec}{el} {elec} {}
164 \DeclareFontSeriesChangeRule {elec}{l} {lec} {}
165 \DeclareFontSeriesChangeRule {elec}{sl} {slec} {}
166 \DeclareFontSeriesChangeRule {elec}{sb} {sbec} {bec}
167 \DeclareFontSeriesChangeRule {elec}{b} {bec} {}
168 \DeclareFontSeriesChangeRule {elec}{eb} {ebec} {bec}
169 \DeclareFontSeriesChangeRule {elec}{ub} {ubec} {bec}
170 \DeclareFontSeriesChangeRule {elec}{uc} {eluc} {}
171 \DeclareFontSeriesChangeRule {elec}{ec} {elec} {}
172 \DeclareFontSeriesChangeRule {elec}{c} {elc} {}
173 \DeclareFontSeriesChangeRule {elec}{sc} {elsc} {}
174 \DeclareFontSeriesChangeRule {elec}{sx} {elsx} {}
175 \DeclareFontSeriesChangeRule {elec}{x} {elx} {}
176 \DeclareFontSeriesChangeRule {elec}{ex} {elex} {}
177 \DeclareFontSeriesChangeRule {elec}{ux} {elux} {}

178 \DeclareFontSeriesChangeRule {elc}{ul} {ulc} {}
179 \DeclareFontSeriesChangeRule {elc}{el} {elc} {}
180 \DeclareFontSeriesChangeRule {elc}{l} {lc} {}
181 \DeclareFontSeriesChangeRule {elc}{sl} {slc} {}
182 \DeclareFontSeriesChangeRule {elc}{sb} {sbc} {bc}
183 \DeclareFontSeriesChangeRule {elc}{b} {bc} {}
184 \DeclareFontSeriesChangeRule {elc}{eb} {ebc} {bc}
185 \DeclareFontSeriesChangeRule {elc}{ub} {ubc} {bc}
186 \DeclareFontSeriesChangeRule {elc}{uc} {eluc} {}
187 \DeclareFontSeriesChangeRule {elc}{ec} {elec} {}
188 \DeclareFontSeriesChangeRule {elc}{c} {elc} {}
189 \DeclareFontSeriesChangeRule {elc}{sc} {elsc} {}
190 \DeclareFontSeriesChangeRule {elc}{sx} {elsx} {}
191 \DeclareFontSeriesChangeRule {elc}{x} {elx} {}
192 \DeclareFontSeriesChangeRule {elc}{ex} {elex} {}
193 \DeclareFontSeriesChangeRule {elc}{ux} {elux} {}

194 \DeclareFontSeriesChangeRule {elsc}{ul} {ulsc} {}
195 \DeclareFontSeriesChangeRule {elsc}{el} {elsc} {}
196 \DeclareFontSeriesChangeRule {elsc}{l} {lsc} {}
197 \DeclareFontSeriesChangeRule {elsc}{sl} {slsc} {}

```

```

198 \DeclareFontSeriesChangeRule {elsc}{sb} {sbsc} {bsc}
199 \DeclareFontSeriesChangeRule {elsc}{b} {bsc} {}
200 \DeclareFontSeriesChangeRule {elsc}{eb} {ebsc} {bsc}
201 \DeclareFontSeriesChangeRule {elsc}{ub} {ubsc} {bsc}
202 \DeclareFontSeriesChangeRule {elsc}{uc} {eluc} {}
203 \DeclareFontSeriesChangeRule {elsc}{ec} {elec} {}
204 \DeclareFontSeriesChangeRule {elsc}{c} {elc} {}
205 \DeclareFontSeriesChangeRule {elsc}{sc} {elsc} {}
206 \DeclareFontSeriesChangeRule {elsc}{sx} {elsx} {}
207 \DeclareFontSeriesChangeRule {elsc}{x} {elx} {}
208 \DeclareFontSeriesChangeRule {elsc}{ex} {elex} {}
209 \DeclareFontSeriesChangeRule {elsc}{ux} {elux} {}

210 \DeclareFontSeriesChangeRule {el}{uc} {eluc} {}
211 \DeclareFontSeriesChangeRule {el}{ec} {elec} {}
212 \DeclareFontSeriesChangeRule {el}{c} {elc} {}
213 \DeclareFontSeriesChangeRule {el}{sc} {elsc} {}
214 \DeclareFontSeriesChangeRule {el}{sx} {elsx} {}
215 \DeclareFontSeriesChangeRule {el}{x} {elx} {}
216 \DeclareFontSeriesChangeRule {el}{ex} {elex} {}
217 \DeclareFontSeriesChangeRule {el}{ux} {elux} {}
218 \DeclareFontSeriesChangeRule {el}{sb} {sb} {b}
219 \DeclareFontSeriesChangeRule {el}{eb} {eb} {b}
220 \DeclareFontSeriesChangeRule {el}{ub} {ub} {b}

221 \DeclareFontSeriesChangeRule {elsx}{ul} {ulsx} {}
222 \DeclareFontSeriesChangeRule {elsx}{el} {elsx} {}
223 \DeclareFontSeriesChangeRule {elsx}{l} {lsx} {}
224 \DeclareFontSeriesChangeRule {elsx}{sl} {slsx} {}
225 \DeclareFontSeriesChangeRule {elsx}{sb} {sbsx} {bsx}
226 \DeclareFontSeriesChangeRule {elsx}{b} {bsx} {}
227 \DeclareFontSeriesChangeRule {elsx}{eb} {ebsx} {bsx}
228 \DeclareFontSeriesChangeRule {elsx}{ub} {ubsx} {bsx}
229 \DeclareFontSeriesChangeRule {elsx}{uc} {eluc} {}
230 \DeclareFontSeriesChangeRule {elsx}{ec} {elec} {}
231 \DeclareFontSeriesChangeRule {elsx}{c} {elc} {}
232 \DeclareFontSeriesChangeRule {elsx}{sc} {elsc} {}
233 \DeclareFontSeriesChangeRule {elsx}{sx} {elsx} {}
234 \DeclareFontSeriesChangeRule {elsx}{x} {elx} {}
235 \DeclareFontSeriesChangeRule {elsx}{ex} {elex} {}
236 \DeclareFontSeriesChangeRule {elsx}{ux} {elux} {}

237 \DeclareFontSeriesChangeRule {elx}{ul} {ulx} {}
238 \DeclareFontSeriesChangeRule {elx}{el} {elx} {}
239 \DeclareFontSeriesChangeRule {elx}{l} {lx} {}
240 \DeclareFontSeriesChangeRule {elx}{sl} {slx} {}
241 \DeclareFontSeriesChangeRule {elx}{sb} {sbx} {bx}
242 \DeclareFontSeriesChangeRule {elx}{b} {bx} {}
243 \DeclareFontSeriesChangeRule {elx}{eb} {ebx} {bx}
244 \DeclareFontSeriesChangeRule {elx}{ub} {ubx} {bx}
245 \DeclareFontSeriesChangeRule {elx}{uc} {eluc} {}
246 \DeclareFontSeriesChangeRule {elx}{ec} {elec} {}
247 \DeclareFontSeriesChangeRule {elx}{c} {elc} {}
248 \DeclareFontSeriesChangeRule {elx}{sc} {elsc} {}
249 \DeclareFontSeriesChangeRule {elx}{sx} {elsx} {}
250 \DeclareFontSeriesChangeRule {elx}{x} {elx} {}

```

```

251 \DeclareFontSeriesChangeRule {elx}{ex} {elex} {}
252 \DeclareFontSeriesChangeRule {elx}{ux} {elux} {}

253 \DeclareFontSeriesChangeRule {elex}{ul} {ulex} {}
254 \DeclareFontSeriesChangeRule {elex}{el} {elex} {}
255 \DeclareFontSeriesChangeRule {elex}{l} {lex} {}
256 \DeclareFontSeriesChangeRule {elex}{sl} {slex} {}
257 \DeclareFontSeriesChangeRule {elex}{sb} {sbex} {bex}
258 \DeclareFontSeriesChangeRule {elex}{b} {bex} {}
259 \DeclareFontSeriesChangeRule {elex}{eb} {ebex} {bex}
260 \DeclareFontSeriesChangeRule {elex}{ub} {ubex} {bex}
261 \DeclareFontSeriesChangeRule {elex}{uc} {eluc} {}
262 \DeclareFontSeriesChangeRule {elex}{ec} {elec} {}
263 \DeclareFontSeriesChangeRule {elex}{c} {elc} {}
264 \DeclareFontSeriesChangeRule {elex}{sc} {elsc} {}
265 \DeclareFontSeriesChangeRule {elex}{sx} {elsx} {}
266 \DeclareFontSeriesChangeRule {elex}{x} {elx} {}
267 \DeclareFontSeriesChangeRule {elex}{ex} {elex} {}
268 \DeclareFontSeriesChangeRule {elex}{ux} {elux} {}

269 \DeclareFontSeriesChangeRule {elux}{ul} {ulux} {}
270 \DeclareFontSeriesChangeRule {elux}{el} {elux} {}
271 \DeclareFontSeriesChangeRule {elux}{l} {lux} {}
272 \DeclareFontSeriesChangeRule {elux}{sl} {slux} {}
273 \DeclareFontSeriesChangeRule {elux}{sb} {sbux} {bux}
274 \DeclareFontSeriesChangeRule {elux}{b} {bux} {}
275 \DeclareFontSeriesChangeRule {elux}{eb} {ebux} {bux}
276 \DeclareFontSeriesChangeRule {elux}{ub} {ubux} {bux}
277 \DeclareFontSeriesChangeRule {elux}{uc} {eluc} {}
278 \DeclareFontSeriesChangeRule {elux}{ec} {elec} {}
279 \DeclareFontSeriesChangeRule {elux}{c} {elc} {}
280 \DeclareFontSeriesChangeRule {elux}{sc} {elsc} {}
281 \DeclareFontSeriesChangeRule {elux}{sx} {elsx} {}
282 \DeclareFontSeriesChangeRule {elux}{x} {elx} {}
283 \DeclareFontSeriesChangeRule {elux}{ex} {elex} {}
284 \DeclareFontSeriesChangeRule {elux}{ux} {elux} {}

285 \DeclareFontSeriesChangeRule {luc}{ul} {uluc} {}
286 \DeclareFontSeriesChangeRule {luc}{el} {eluc} {}
287 \DeclareFontSeriesChangeRule {luc}{l} {luc} {}
288 \DeclareFontSeriesChangeRule {luc}{sl} {sluc} {}
289 \DeclareFontSeriesChangeRule {luc}{sb} {sbuc} {buc}
290 \DeclareFontSeriesChangeRule {luc}{b} {buc} {}
291 \DeclareFontSeriesChangeRule {luc}{eb} {ebuc} {buc}
292 \DeclareFontSeriesChangeRule {luc}{ub} {ubuc} {buc}
293 \DeclareFontSeriesChangeRule {luc}{uc} {luc} {}
294 \DeclareFontSeriesChangeRule {luc}{ec} {lec} {}
295 \DeclareFontSeriesChangeRule {luc}{c} {lc} {}
296 \DeclareFontSeriesChangeRule {luc}{sc} {lsc} {}
297 \DeclareFontSeriesChangeRule {luc}{sx} {lsx} {}
298 \DeclareFontSeriesChangeRule {luc}{x} {lx} {}
299 \DeclareFontSeriesChangeRule {luc}{ex} {lex} {}
300 \DeclareFontSeriesChangeRule {luc}{ux} {lux} {}

301 \DeclareFontSeriesChangeRule {lec}{ul} {ulec} {}
302 \DeclareFontSeriesChangeRule {lec}{el} {elec} {}
303 \DeclareFontSeriesChangeRule {lec}{l} {lec} {}

```

```

304 \DeclareFontSeriesChangeRule {lec}{sl} {slec} {}
305 \DeclareFontSeriesChangeRule {lec}{sb} {sbec} {bec}
306 \DeclareFontSeriesChangeRule {lec}{b} {bec} {}
307 \DeclareFontSeriesChangeRule {lec}{eb} {ebec} {bec}
308 \DeclareFontSeriesChangeRule {lec}{ub} {ubec} {bec}
309 \DeclareFontSeriesChangeRule {lec}{uc} {luc} {}
310 \DeclareFontSeriesChangeRule {lec}{ec} {lec} {}
311 \DeclareFontSeriesChangeRule {lec}{c} {lc} {}
312 \DeclareFontSeriesChangeRule {lec}{sc} {lsc} {}
313 \DeclareFontSeriesChangeRule {lec}{sx} {lsx} {}
314 \DeclareFontSeriesChangeRule {lec}{x} {lx} {}
315 \DeclareFontSeriesChangeRule {lec}{ex} {lex} {}
316 \DeclareFontSeriesChangeRule {lec}{ux} {lux} {}

317 \DeclareFontSeriesChangeRule {lc}{ul} {ulc} {}
318 \DeclareFontSeriesChangeRule {lc}{el} {elc} {}
319 \DeclareFontSeriesChangeRule {lc}{l} {lc} {}
320 \DeclareFontSeriesChangeRule {lc}{sl} {slc} {}
321 \DeclareFontSeriesChangeRule {lc}{sb} {sbc} {bc}
322 \DeclareFontSeriesChangeRule {lc}{b} {bc} {}
323 \DeclareFontSeriesChangeRule {lc}{eb} {ebc} {bc}
324 \DeclareFontSeriesChangeRule {lc}{ub} {ubc} {bc}
325 \DeclareFontSeriesChangeRule {lc}{uc} {luc} {}
326 \DeclareFontSeriesChangeRule {lc}{ec} {lec} {}
327 \DeclareFontSeriesChangeRule {lc}{c} {lc} {}
328 \DeclareFontSeriesChangeRule {lc}{sc} {lsc} {}
329 \DeclareFontSeriesChangeRule {lc}{sx} {lsx} {}
330 \DeclareFontSeriesChangeRule {lc}{x} {lx} {}
331 \DeclareFontSeriesChangeRule {lc}{ex} {lex} {}
332 \DeclareFontSeriesChangeRule {lc}{ux} {lux} {}

333 \DeclareFontSeriesChangeRule {lsc}{ul} {ulsc} {}
334 \DeclareFontSeriesChangeRule {lsc}{el} {elsc} {}
335 \DeclareFontSeriesChangeRule {lsc}{l} {lsc} {}
336 \DeclareFontSeriesChangeRule {lsc}{sl} {slsc} {}
337 \DeclareFontSeriesChangeRule {lsc}{sb} {sbsc} {bsc}
338 \DeclareFontSeriesChangeRule {lsc}{b} {bsc} {}
339 \DeclareFontSeriesChangeRule {lsc}{eb} {ebsc} {bsc}
340 \DeclareFontSeriesChangeRule {lsc}{ub} {ubsc} {bsc}
341 \DeclareFontSeriesChangeRule {lsc}{uc} {luc} {}
342 \DeclareFontSeriesChangeRule {lsc}{ec} {lec} {}
343 \DeclareFontSeriesChangeRule {lsc}{c} {lc} {}
344 \DeclareFontSeriesChangeRule {lsc}{sc} {lsc} {}
345 \DeclareFontSeriesChangeRule {lsc}{sx} {lsx} {}
346 \DeclareFontSeriesChangeRule {lsc}{x} {lx} {}
347 \DeclareFontSeriesChangeRule {lsc}{ex} {lex} {}
348 \DeclareFontSeriesChangeRule {lsc}{ux} {lux} {}

349 \DeclareFontSeriesChangeRule {l}{uc} {luc} {}
350 \DeclareFontSeriesChangeRule {l}{ec} {lec} {}
351 \DeclareFontSeriesChangeRule {l}{c} {lc} {}
352 \DeclareFontSeriesChangeRule {l}{sc} {lsc} {}
353 \DeclareFontSeriesChangeRule {l}{sx} {lsx} {}
354 \DeclareFontSeriesChangeRule {l}{x} {lx} {}
355 \DeclareFontSeriesChangeRule {l}{ex} {lex} {}
356 \DeclareFontSeriesChangeRule {l}{ux} {lux} {}

```

```

357 \DeclareFontSeriesChangeRule {l}{sb}      {sb}    {b}
358 \DeclareFontSeriesChangeRule {l}{eb}      {eb}    {b}
359 \DeclareFontSeriesChangeRule {l}{ub}      {ub}    {b}

360 \DeclareFontSeriesChangeRule {lsx}{ul}    {ulsx} {}
361 \DeclareFontSeriesChangeRule {lsx}{el}    {elsx} {}
362 \DeclareFontSeriesChangeRule {lsx}{l}     {lsx}  {}
363 \DeclareFontSeriesChangeRule {lsx}{sl}    {slsx} {}
364 \DeclareFontSeriesChangeRule {lsx}{sb}    {sbsx} {bsx}
365 \DeclareFontSeriesChangeRule {lsx}{b}     {bsx}  {}
366 \DeclareFontSeriesChangeRule {lsx}{eb}    {ebsx} {bsx}
367 \DeclareFontSeriesChangeRule {lsx}{ub}    {ubsx} {bsx}
368 \DeclareFontSeriesChangeRule {lsx}{uc}    {luc}  {}
369 \DeclareFontSeriesChangeRule {lsx}{ec}    {lec}  {}
370 \DeclareFontSeriesChangeRule {lsx}{c}     {lc}   {}
371 \DeclareFontSeriesChangeRule {lsx}{sc}    {lsc}  {}
372 \DeclareFontSeriesChangeRule {lsx}{sx}    {lsx}  {}
373 \DeclareFontSeriesChangeRule {lsx}{x}     {lx}   {}
374 \DeclareFontSeriesChangeRule {lsx}{ex}    {lex}  {}
375 \DeclareFontSeriesChangeRule {lsx}{ux}    {lux}  {}

376 \DeclareFontSeriesChangeRule {lx}{ul}    {ulx}  {}
377 \DeclareFontSeriesChangeRule {lx}{el}    {elx}  {}
378 \DeclareFontSeriesChangeRule {lx}{l}     {lx}   {}
379 \DeclareFontSeriesChangeRule {lx}{sl}    {slx}  {}
380 \DeclareFontSeriesChangeRule {lx}{sb}    {sbx}  {bx}
381 \DeclareFontSeriesChangeRule {lx}{b}     {bx}   {}
382 \DeclareFontSeriesChangeRule {lx}{eb}    {ebx}  {bx}
383 \DeclareFontSeriesChangeRule {lx}{ub}    {ubx}  {bx}
384 \DeclareFontSeriesChangeRule {lx}{uc}    {luc}  {}
385 \DeclareFontSeriesChangeRule {lx}{ec}    {lec}  {}
386 \DeclareFontSeriesChangeRule {lx}{c}     {lc}   {}
387 \DeclareFontSeriesChangeRule {lx}{sc}    {lsc}  {}
388 \DeclareFontSeriesChangeRule {lx}{sx}    {lsx}  {}
389 \DeclareFontSeriesChangeRule {lx}{x}     {lx}   {}
390 \DeclareFontSeriesChangeRule {lx}{ex}    {lex}  {}
391 \DeclareFontSeriesChangeRule {lx}{ux}    {lux}  {}

392 \DeclareFontSeriesChangeRule {lex}{ul}    {ulex} {}
393 \DeclareFontSeriesChangeRule {lex}{el}    {ele}  {}
394 \DeclareFontSeriesChangeRule {lex}{l}     {lex}  {}
395 \DeclareFontSeriesChangeRule {lex}{sl}    {slex} {}
396 \DeclareFontSeriesChangeRule {lex}{sb}    {sbex} {bex}
397 \DeclareFontSeriesChangeRule {lex}{b}     {bex}  {}
398 \DeclareFontSeriesChangeRule {lex}{eb}    {ebex} {bex}
399 \DeclareFontSeriesChangeRule {lex}{ub}    {ubex} {bex}
400 \DeclareFontSeriesChangeRule {lex}{uc}    {luc}  {}
401 \DeclareFontSeriesChangeRule {lex}{ec}    {lec}  {}
402 \DeclareFontSeriesChangeRule {lex}{c}     {lc}   {}
403 \DeclareFontSeriesChangeRule {lex}{sc}    {lsc}  {}
404 \DeclareFontSeriesChangeRule {lex}{sx}    {lsx}  {}
405 \DeclareFontSeriesChangeRule {lex}{x}     {lx}   {}
406 \DeclareFontSeriesChangeRule {lex}{ex}    {lex}  {}
407 \DeclareFontSeriesChangeRule {lex}{ux}    {lux}  {}

408 \DeclareFontSeriesChangeRule {lux}{ul}    {ulux} {}
409 \DeclareFontSeriesChangeRule {lux}{el}    {elux} {}

```

```

410 \DeclareFontSeriesChangeRule {lux}{l} {lux} {}
411 \DeclareFontSeriesChangeRule {lux}{sl} {slux} {}
412 \DeclareFontSeriesChangeRule {lux}{sb} {sbux} {bux}
413 \DeclareFontSeriesChangeRule {lux}{b} {bux} {}
414 \DeclareFontSeriesChangeRule {lux}{eb} {ebux} {bux}
415 \DeclareFontSeriesChangeRule {lux}{ub} {ubux} {bux}
416 \DeclareFontSeriesChangeRule {lux}{uc} {luc} {}
417 \DeclareFontSeriesChangeRule {lux}{ec} {lec} {}
418 \DeclareFontSeriesChangeRule {lux}{c} {lc} {}
419 \DeclareFontSeriesChangeRule {lux}{sc} {lsc} {}
420 \DeclareFontSeriesChangeRule {lux}{sx} {lsx} {}
421 \DeclareFontSeriesChangeRule {lux}{x} {lx} {}
422 \DeclareFontSeriesChangeRule {lux}{ex} {lex} {}
423 \DeclareFontSeriesChangeRule {lux}{ux} {lux} {}

424 \DeclareFontSeriesChangeRule {sluc}{ul} {uluc} {}
425 \DeclareFontSeriesChangeRule {sluc}{el} {eluc} {}
426 \DeclareFontSeriesChangeRule {sluc}{l} {luc} {}
427 \DeclareFontSeriesChangeRule {sluc}{sl} {sluc} {}
428 \DeclareFontSeriesChangeRule {sluc}{sb} {sbuc} {buc}
429 \DeclareFontSeriesChangeRule {sluc}{b} {buc} {}
430 \DeclareFontSeriesChangeRule {sluc}{eb} {ebuc} {buc}
431 \DeclareFontSeriesChangeRule {sluc}{ub} {ubuc} {buc}
432 \DeclareFontSeriesChangeRule {sluc}{uc} {sluc} {}
433 \DeclareFontSeriesChangeRule {sluc}{ec} {slec} {}
434 \DeclareFontSeriesChangeRule {sluc}{c} {slc} {}
435 \DeclareFontSeriesChangeRule {sluc}{sc} {slsc} {}
436 \DeclareFontSeriesChangeRule {sluc}{sx} {slsx} {}
437 \DeclareFontSeriesChangeRule {sluc}{x} {slx} {}
438 \DeclareFontSeriesChangeRule {sluc}{ex} {slex} {}
439 \DeclareFontSeriesChangeRule {sluc}{ux} {slux} {}

440 \DeclareFontSeriesChangeRule {slec}{ul} {ulec} {}
441 \DeclareFontSeriesChangeRule {slec}{el} {elec} {}
442 \DeclareFontSeriesChangeRule {slec}{l} {lec} {}
443 \DeclareFontSeriesChangeRule {slec}{sl} {slec} {}
444 \DeclareFontSeriesChangeRule {slec}{sb} {sbec} {bec}
445 \DeclareFontSeriesChangeRule {slec}{b} {bec} {}
446 \DeclareFontSeriesChangeRule {slec}{eb} {ebec} {bec}
447 \DeclareFontSeriesChangeRule {slec}{ub} {ubec} {bec}
448 \DeclareFontSeriesChangeRule {slec}{uc} {sluc} {}
449 \DeclareFontSeriesChangeRule {slec}{ec} {slec} {}
450 \DeclareFontSeriesChangeRule {slec}{c} {slc} {}
451 \DeclareFontSeriesChangeRule {slec}{sc} {slsc} {}
452 \DeclareFontSeriesChangeRule {slec}{sx} {slsx} {}
453 \DeclareFontSeriesChangeRule {slec}{x} {slx} {}
454 \DeclareFontSeriesChangeRule {slec}{ex} {slex} {}
455 \DeclareFontSeriesChangeRule {slec}{ux} {slux} {}

456 \DeclareFontSeriesChangeRule {slc}{ul} {ulc} {}
457 \DeclareFontSeriesChangeRule {slc}{el} {elc} {}
458 \DeclareFontSeriesChangeRule {slc}{l} {lc} {}
459 \DeclareFontSeriesChangeRule {slc}{sl} {slc} {}
460 \DeclareFontSeriesChangeRule {slc}{sb} {sbc} {bc}
461 \DeclareFontSeriesChangeRule {slc}{b} {bc} {}
462 \DeclareFontSeriesChangeRule {slc}{eb} {ebc} {bc}

```

```

463 \DeclareFontSeriesChangeRule {slc}{ub} {ubc} {bc}
464 \DeclareFontSeriesChangeRule {slc}{uc} {sluc} {}
465 \DeclareFontSeriesChangeRule {slc}{ec} {slec} {}
466 \DeclareFontSeriesChangeRule {slc}{c} {slc} {}
467 \DeclareFontSeriesChangeRule {slc}{sc} {slsc} {}
468 \DeclareFontSeriesChangeRule {slc}{sx} {slsx} {}
469 \DeclareFontSeriesChangeRule {slc}{x} {slx} {}
470 \DeclareFontSeriesChangeRule {slc}{ex} {slex} {}
471 \DeclareFontSeriesChangeRule {slc}{ux} {slux} {}

472 \DeclareFontSeriesChangeRule {slsc}{ul} {ulsc} {}
473 \DeclareFontSeriesChangeRule {slsc}{el} {elsc} {}
474 \DeclareFontSeriesChangeRule {slsc}{l} {lsc} {}
475 \DeclareFontSeriesChangeRule {slsc}{sl} {slsc} {}
476 \DeclareFontSeriesChangeRule {slsc}{sb} {sbsc} {bsc}
477 \DeclareFontSeriesChangeRule {slsc}{b} {bsc} {}
478 \DeclareFontSeriesChangeRule {slsc}{eb} {ebsc} {bsc}
479 \DeclareFontSeriesChangeRule {slsc}{ub} {ubsc} {bsc}
480 \DeclareFontSeriesChangeRule {slsc}{uc} {sluc} {}
481 \DeclareFontSeriesChangeRule {slsc}{ec} {slec} {}
482 \DeclareFontSeriesChangeRule {slsc}{c} {slc} {}
483 \DeclareFontSeriesChangeRule {slsc}{sc} {slsc} {}
484 \DeclareFontSeriesChangeRule {slsc}{sx} {slsx} {}
485 \DeclareFontSeriesChangeRule {slsc}{x} {slx} {}
486 \DeclareFontSeriesChangeRule {slsc}{ex} {slex} {}
487 \DeclareFontSeriesChangeRule {slsc}{ux} {slux} {}

488 \DeclareFontSeriesChangeRule {sl}{uc} {sluc} {}
489 \DeclareFontSeriesChangeRule {sl}{ec} {slec} {}
490 \DeclareFontSeriesChangeRule {sl}{c} {slc} {}
491 \DeclareFontSeriesChangeRule {sl}{sc} {slsc} {}
492 \DeclareFontSeriesChangeRule {sl}{sx} {slsx} {}
493 \DeclareFontSeriesChangeRule {sl}{x} {slx} {}
494 \DeclareFontSeriesChangeRule {sl}{ex} {slex} {}
495 \DeclareFontSeriesChangeRule {sl}{ux} {slux} {}
496 \DeclareFontSeriesChangeRule {sl}{sb} {sb} {b}
497 \DeclareFontSeriesChangeRule {sl}{eb} {eb} {b}
498 \DeclareFontSeriesChangeRule {sl}{ub} {ub} {b}

499 \DeclareFontSeriesChangeRule {slsx}{ul} {ulsx} {}
500 \DeclareFontSeriesChangeRule {slsx}{el} {elsx} {}
501 \DeclareFontSeriesChangeRule {slsx}{l} {lsx} {}
502 \DeclareFontSeriesChangeRule {slsx}{sl} {slsx} {}
503 \DeclareFontSeriesChangeRule {slsx}{sb} {sbsx} {bsx}
504 \DeclareFontSeriesChangeRule {slsx}{b} {bsx} {}
505 \DeclareFontSeriesChangeRule {slsx}{eb} {ebsx} {bsx}
506 \DeclareFontSeriesChangeRule {slsx}{ub} {ubsx} {bsx}
507 \DeclareFontSeriesChangeRule {slsx}{uc} {sluc} {}
508 \DeclareFontSeriesChangeRule {slsx}{ec} {slec} {}
509 \DeclareFontSeriesChangeRule {slsx}{c} {slc} {}
510 \DeclareFontSeriesChangeRule {slsx}{sc} {slsc} {}
511 \DeclareFontSeriesChangeRule {slsx}{sx} {slsx} {}
512 \DeclareFontSeriesChangeRule {slsx}{x} {slx} {}
513 \DeclareFontSeriesChangeRule {slsx}{ex} {slex} {}
514 \DeclareFontSeriesChangeRule {slsx}{ux} {slux} {}
515 \DeclareFontSeriesChangeRule {slx}{ul} {ulx} {}

```

```

516 \DeclareFontSeriesChangeRule {slx}{el} {elx} {}
517 \DeclareFontSeriesChangeRule {slx}{l} {lx} {}
518 \DeclareFontSeriesChangeRule {slx}{sl} {slx} {}
519 \DeclareFontSeriesChangeRule {slx}{sb} {sbx} {bx}
520 \DeclareFontSeriesChangeRule {slx}{b} {bx} {}
521 \DeclareFontSeriesChangeRule {slx}{eb} {ebx} {bx}
522 \DeclareFontSeriesChangeRule {slx}{ub} {ubx} {bx}
523 \DeclareFontSeriesChangeRule {slx}{uc} {sluc} {}
524 \DeclareFontSeriesChangeRule {slx}{ec} {slec} {}
525 \DeclareFontSeriesChangeRule {slx}{c} {slc} {}
526 \DeclareFontSeriesChangeRule {slx}{sc} {slsc} {}
527 \DeclareFontSeriesChangeRule {slx}{sx} {slsx} {}
528 \DeclareFontSeriesChangeRule {slx}{x} {slx} {}
529 \DeclareFontSeriesChangeRule {slx}{ex} {slex} {}
530 \DeclareFontSeriesChangeRule {slx}{ux} {slux} {}

531 \DeclareFontSeriesChangeRule {slex}{ul} {ulex} {}
532 \DeclareFontSeriesChangeRule {slex}{el} {elex} {}
533 \DeclareFontSeriesChangeRule {slex}{l} {lex} {}
534 \DeclareFontSeriesChangeRule {slex}{sl} {slex} {}
535 \DeclareFontSeriesChangeRule {slex}{sb} {sbex} {bex}
536 \DeclareFontSeriesChangeRule {slex}{b} {bex} {}
537 \DeclareFontSeriesChangeRule {slex}{eb} {ebex} {bex}
538 \DeclareFontSeriesChangeRule {slex}{ub} {ubex} {bex}
539 \DeclareFontSeriesChangeRule {slex}{uc} {sluc} {}
540 \DeclareFontSeriesChangeRule {slex}{ec} {slec} {}
541 \DeclareFontSeriesChangeRule {slex}{c} {slc} {}
542 \DeclareFontSeriesChangeRule {slex}{sc} {slsc} {}
543 \DeclareFontSeriesChangeRule {slex}{sx} {slsx} {}
544 \DeclareFontSeriesChangeRule {slex}{x} {slx} {}
545 \DeclareFontSeriesChangeRule {slex}{ex} {slex} {}
546 \DeclareFontSeriesChangeRule {slex}{ux} {slux} {}

547 \DeclareFontSeriesChangeRule {slux}{ul} {ulux} {}
548 \DeclareFontSeriesChangeRule {slux}{el} {elux} {}
549 \DeclareFontSeriesChangeRule {slux}{l} {lux} {}
550 \DeclareFontSeriesChangeRule {slux}{sl} {slux} {}
551 \DeclareFontSeriesChangeRule {slux}{sb} {sbux} {bux}
552 \DeclareFontSeriesChangeRule {slux}{b} {bux} {}
553 \DeclareFontSeriesChangeRule {slux}{eb} {ebux} {bux}
554 \DeclareFontSeriesChangeRule {slux}{ub} {ubux} {bux}
555 \DeclareFontSeriesChangeRule {slux}{uc} {sluc} {}
556 \DeclareFontSeriesChangeRule {slux}{ec} {slec} {}
557 \DeclareFontSeriesChangeRule {slux}{c} {slc} {}
558 \DeclareFontSeriesChangeRule {slux}{sc} {slsc} {}
559 \DeclareFontSeriesChangeRule {slux}{sx} {slsx} {}
560 \DeclareFontSeriesChangeRule {slux}{x} {slx} {}
561 \DeclareFontSeriesChangeRule {slux}{ex} {slex} {}
562 \DeclareFontSeriesChangeRule {slux}{ux} {slux} {}

563 \DeclareFontSeriesChangeRule {uc}{ul} {uluc} {}
564 \DeclareFontSeriesChangeRule {uc}{el} {eluc} {}
565 \DeclareFontSeriesChangeRule {uc}{l} {luc} {}
566 \DeclareFontSeriesChangeRule {uc}{sl} {sluc} {}
567 \DeclareFontSeriesChangeRule {uc}{sb} {sbuc} {buc}
568 \DeclareFontSeriesChangeRule {uc}{b} {buc} {}

```

```

569 \DeclareFontSeriesChangeRule {uc}{eb} {ebuc} {buc}
570 \DeclareFontSeriesChangeRule {uc}{ub} {ubuc} {buc}

571 \DeclareFontSeriesChangeRule {ec}{ul} {ulec} {}
572 \DeclareFontSeriesChangeRule {ec}{el} {elec} {}
573 \DeclareFontSeriesChangeRule {ec}{l} {lec} {}
574 \DeclareFontSeriesChangeRule {ec}{sl} {slec} {}
575 \DeclareFontSeriesChangeRule {ec}{sb} {sbec} {bec}
576 \DeclareFontSeriesChangeRule {ec}{b} {bec} {}
577 \DeclareFontSeriesChangeRule {ec}{eb} {ebec} {bec}
578 \DeclareFontSeriesChangeRule {ec}{ub} {ubec} {bec}

```

There are a number of font families that implement condensed series, but often only **c** and **bc**. Therefore, if we see a weight or width change request that can't be fulfilled we try to stay with **c** or **bc**.

```

579 \DeclareFontSeriesChangeRule {c}{ul} {ulc} {c}
580 \DeclareFontSeriesChangeRule {c}{el} {elc} {c}
581 \DeclareFontSeriesChangeRule {c}{l} {lc} {c}
582 \DeclareFontSeriesChangeRule {c}{sl} {slc} {c}
583 \DeclareFontSeriesChangeRule {c}{sb} {sbc} {bc}
584 \DeclareFontSeriesChangeRule {c}{b} {bc} {}
585 \DeclareFontSeriesChangeRule {c}{eb} {ebc} {bc}
586 \DeclareFontSeriesChangeRule {c}{ub} {ubc} {bc}
587 \DeclareFontSeriesChangeRule {c}{uc} {uc} {c}
588 \DeclareFontSeriesChangeRule {c}{ec} {ec} {c}
589 \DeclareFontSeriesChangeRule {c}{sc} {sc} {c}

590 \DeclareFontSeriesChangeRule {sc}{ul} {ulsc} {}
591 \DeclareFontSeriesChangeRule {sc}{el} {elsc} {}
592 \DeclareFontSeriesChangeRule {sc}{l} {lsc} {}
593 \DeclareFontSeriesChangeRule {sc}{sl} {slsc} {}
594 \DeclareFontSeriesChangeRule {sc}{sb} {bsc} {bsc}
595 \DeclareFontSeriesChangeRule {sc}{b} {bsc} {}
596 \DeclareFontSeriesChangeRule {sc}{eb} {ebsc} {bsc}
597 \DeclareFontSeriesChangeRule {sc}{ub} {ubsc} {bsc}

598 \DeclareFontSeriesChangeRule {m}{sb} {sb} {b}
599 \DeclareFontSeriesChangeRule {m}{eb} {eb} {b}
600 \DeclareFontSeriesChangeRule {m}{ub} {ub} {b}

```

This special rule normally does nothing since nearly every font implements the **b** bold series. The exception are Computer Modern and Latin Modern and fonts based on them. They usually only have **bx**, but then they normally provide an `.fd` file declaration mapping from **b** to **bx** and thus pretend that **b** exists. But in case any of them does not, we offer an alternative result and switch to **bx** if **b** can't be found.

```

601 \DeclareFontSeriesChangeRule {m}{b} {b} {bx}

602 \DeclareFontSeriesChangeRule {sx}{ul} {ulsx} {}
603 \DeclareFontSeriesChangeRule {sx}{el} {elsx} {}
604 \DeclareFontSeriesChangeRule {sx}{l} {lsx} {}
605 \DeclareFontSeriesChangeRule {sx}{sl} {slsx} {}
606 \DeclareFontSeriesChangeRule {sx}{sb} {bsx} {bsx}
607 \DeclareFontSeriesChangeRule {sx}{b} {bsx} {}
608 \DeclareFontSeriesChangeRule {sx}{eb} {ebsx} {bsx}
609 \DeclareFontSeriesChangeRule {sx}{ub} {ubsx} {bsx}

```

```

610 \DeclareFontSeriesChangeRule {x}{ul}    {ulx} {}
611 \DeclareFontSeriesChangeRule {x}{el}    {elx} {}
612 \DeclareFontSeriesChangeRule {x}{l}     {lx} {}
613 \DeclareFontSeriesChangeRule {x}{sl}    {slx} {}
614 \DeclareFontSeriesChangeRule {x}{sb}    {sbx} {bx}
615 \DeclareFontSeriesChangeRule {x}{b}     {bx} {}
616 \DeclareFontSeriesChangeRule {x}{eb}    {ebx} {bx}
617 \DeclareFontSeriesChangeRule {x}{ub}    {ubx} {bx}

618 \DeclareFontSeriesChangeRule {ex}{ul}   {ulex} {}
619 \DeclareFontSeriesChangeRule {ex}{el}   {elx} {}
620 \DeclareFontSeriesChangeRule {ex}{l}    {lex} {}
621 \DeclareFontSeriesChangeRule {ex}{sl}   {slex} {}
622 \DeclareFontSeriesChangeRule {ex}{sb}   {sbex} {bex}
623 \DeclareFontSeriesChangeRule {ex}{b}    {bex} {}
624 \DeclareFontSeriesChangeRule {ex}{eb}   {ebex} {bex}
625 \DeclareFontSeriesChangeRule {ex}{ub}   {ubex} {bex}

626 \DeclareFontSeriesChangeRule {ux}{ul}   {ulux} {}
627 \DeclareFontSeriesChangeRule {ux}{el}   {elux} {}
628 \DeclareFontSeriesChangeRule {ux}{l}    {lux} {}
629 \DeclareFontSeriesChangeRule {ux}{sl}   {slux} {}
630 \DeclareFontSeriesChangeRule {ux}{sb}   {sbux} {bux}
631 \DeclareFontSeriesChangeRule {ux}{b}    {bux} {}
632 \DeclareFontSeriesChangeRule {ux}{eb}   {ebux} {bux}
633 \DeclareFontSeriesChangeRule {ux}{ub}   {ubux} {bux}

634 \DeclareFontSeriesChangeRule {sbuc}{ul} {uluc} {}
635 \DeclareFontSeriesChangeRule {sbuc}{el} {eluc} {}
636 \DeclareFontSeriesChangeRule {sbuc}{l}  {luc} {}
637 \DeclareFontSeriesChangeRule {sbuc}{sl} {sluc} {}
638 \DeclareFontSeriesChangeRule {sbuc}{sb} {sbuc} {}
639 \DeclareFontSeriesChangeRule {sbuc}{b}  {buc} {}
640 \DeclareFontSeriesChangeRule {sbuc}{eb} {ebuc} {buc}
641 \DeclareFontSeriesChangeRule {sbuc}{ub} {ubuc} {buc}
642 \DeclareFontSeriesChangeRule {sbuc}{uc} {sbuc} {}
643 \DeclareFontSeriesChangeRule {sbuc}{ec} {sbec} {}
644 \DeclareFontSeriesChangeRule {sbuc}{c}  {sbc} {}
645 \DeclareFontSeriesChangeRule {sbuc}{sc} {sbsc} {}
646 \DeclareFontSeriesChangeRule {sbuc}{sx} {sbsx} {}
647 \DeclareFontSeriesChangeRule {sbuc}{x}  {sbx} {}
648 \DeclareFontSeriesChangeRule {sbuc}{ex} {sbex} {}
649 \DeclareFontSeriesChangeRule {sbuc}{ux} {sbux} {}

650 \DeclareFontSeriesChangeRule {sbec}{ul} {ulec} {}
651 \DeclareFontSeriesChangeRule {sbec}{el} {elec} {}
652 \DeclareFontSeriesChangeRule {sbec}{l}  {lec} {}
653 \DeclareFontSeriesChangeRule {sbec}{sl} {slec} {}
654 \DeclareFontSeriesChangeRule {sbec}{sb} {sbec} {}
655 \DeclareFontSeriesChangeRule {sbec}{b}  {bec} {}
656 \DeclareFontSeriesChangeRule {sbec}{eb} {ebec} {bec}
657 \DeclareFontSeriesChangeRule {sbec}{ub} {ubec} {bec}
658 \DeclareFontSeriesChangeRule {sbec}{uc} {sbuc} {}
659 \DeclareFontSeriesChangeRule {sbec}{ec} {sbec} {}
660 \DeclareFontSeriesChangeRule {sbec}{c}  {sbc} {}
661 \DeclareFontSeriesChangeRule {sbec}{sc} {sbsc} {}
662 \DeclareFontSeriesChangeRule {sbec}{sx} {sbsx} {}

```

```

663 \DeclareFontSeriesChangeRule {sbec}{x} {sbx} {}
664 \DeclareFontSeriesChangeRule {sbec}{ex} {sbex} {}
665 \DeclareFontSeriesChangeRule {sbec}{ux} {sbux} {}

666 \DeclareFontSeriesChangeRule {sbc}{ul} {ulc} {}
667 \DeclareFontSeriesChangeRule {sbc}{el} {elc} {}
668 \DeclareFontSeriesChangeRule {sbc}{l} {lc} {}
669 \DeclareFontSeriesChangeRule {sbc}{sl} {slc} {}
670 \DeclareFontSeriesChangeRule {sbc}{sb} {sbc} {}
671 \DeclareFontSeriesChangeRule {sbc}{b} {bc} {}
672 \DeclareFontSeriesChangeRule {sbc}{eb} {ebc} {bc}
673 \DeclareFontSeriesChangeRule {sbc}{ub} {ubc} {bc}
674 \DeclareFontSeriesChangeRule {sbc}{uc} {sbuc} {}
675 \DeclareFontSeriesChangeRule {sbc}{ec} {sbec} {}
676 \DeclareFontSeriesChangeRule {sbc}{c} {sbc} {}
677 \DeclareFontSeriesChangeRule {sbc}{sc} {bsbc} {}
678 \DeclareFontSeriesChangeRule {sbc}{sx} {bsbx} {}
679 \DeclareFontSeriesChangeRule {sbc}{x} {sbx} {}
680 \DeclareFontSeriesChangeRule {sbc}{ex} {sbex} {}
681 \DeclareFontSeriesChangeRule {sbc}{ux} {sbux} {}

682 \DeclareFontSeriesChangeRule {bsbc}{ul} {ulsc} {}
683 \DeclareFontSeriesChangeRule {bsbc}{el} {elsc} {}
684 \DeclareFontSeriesChangeRule {bsbc}{l} {lsc} {}
685 \DeclareFontSeriesChangeRule {bsbc}{sl} {slsc} {}
686 \DeclareFontSeriesChangeRule {bsbc}{sb} {bsbc} {}
687 \DeclareFontSeriesChangeRule {bsbc}{b} {bsc} {}
688 \DeclareFontSeriesChangeRule {bsbc}{eb} {ebsc} {bsc}
689 \DeclareFontSeriesChangeRule {bsbc}{ub} {ubsc} {bsc}
690 \DeclareFontSeriesChangeRule {bsbc}{uc} {sbuc} {}
691 \DeclareFontSeriesChangeRule {bsbc}{ec} {sbec} {}
692 \DeclareFontSeriesChangeRule {bsbc}{c} {sbc} {}
693 \DeclareFontSeriesChangeRule {bsbc}{sc} {bsbc} {}
694 \DeclareFontSeriesChangeRule {bsbc}{sx} {bsbx} {}
695 \DeclareFontSeriesChangeRule {bsbc}{x} {sbx} {}
696 \DeclareFontSeriesChangeRule {bsbc}{ex} {sbex} {}
697 \DeclareFontSeriesChangeRule {bsbc}{ux} {sbux} {}

698 \DeclareFontSeriesChangeRule {sb}{uc} {sbuc} {}
699 \DeclareFontSeriesChangeRule {sb}{ec} {sbec} {}
700 \DeclareFontSeriesChangeRule {sb}{c} {sbc} {}
701 \DeclareFontSeriesChangeRule {sb}{sc} {bsbc} {}
702 \DeclareFontSeriesChangeRule {sb}{sx} {bsbx} {}
703 \DeclareFontSeriesChangeRule {sb}{x} {sbx} {}
704 \DeclareFontSeriesChangeRule {sb}{ex} {sbex} {}
705 \DeclareFontSeriesChangeRule {sb}{ux} {sbux} {}
706 \DeclareFontSeriesChangeRule {sb}{eb} {eb} {b}
707 \DeclareFontSeriesChangeRule {sb}{ub} {ub} {b}

708 \DeclareFontSeriesChangeRule {bsbx}{ul} {ulsx} {}
709 \DeclareFontSeriesChangeRule {bsbx}{el} {elsx} {}
710 \DeclareFontSeriesChangeRule {bsbx}{l} {lsx} {}
711 \DeclareFontSeriesChangeRule {bsbx}{sl} {slsx} {}
712 \DeclareFontSeriesChangeRule {bsbx}{sb} {bsbx} {}
713 \DeclareFontSeriesChangeRule {bsbx}{b} {bsx} {}
714 \DeclareFontSeriesChangeRule {bsbx}{eb} {ebsx} {bsx}
715 \DeclareFontSeriesChangeRule {bsbx}{ub} {ubsx} {bsx}

```

```

716 \DeclareFontSeriesChangeRule {sbsx}{uc} {sbuc} {}
717 \DeclareFontSeriesChangeRule {sbsx}{ec} {sbec} {}
718 \DeclareFontSeriesChangeRule {sbsx}{c} {sbc} {}
719 \DeclareFontSeriesChangeRule {sbsx}{sc} {sbsc} {}
720 \DeclareFontSeriesChangeRule {sbsx}{sx} {sbsx} {}
721 \DeclareFontSeriesChangeRule {sbsx}{x} {sbx} {}
722 \DeclareFontSeriesChangeRule {sbsx}{ex} {sbex} {}
723 \DeclareFontSeriesChangeRule {sbsx}{ux} {sbux} {}

724 \DeclareFontSeriesChangeRule {sbx}{ul} {ulx} {}
725 \DeclareFontSeriesChangeRule {sbx}{el} {elx} {}
726 \DeclareFontSeriesChangeRule {sbx}{l} {lx} {}
727 \DeclareFontSeriesChangeRule {sbx}{sl} {slx} {}
728 \DeclareFontSeriesChangeRule {sbx}{sb} {sbx} {}
729 \DeclareFontSeriesChangeRule {sbx}{b} {bx} {}
730 \DeclareFontSeriesChangeRule {sbx}{eb} {ebx} {bx}
731 \DeclareFontSeriesChangeRule {sbx}{ub} {ubx} {bx}
732 \DeclareFontSeriesChangeRule {sbx}{uc} {sbuc} {}
733 \DeclareFontSeriesChangeRule {sbx}{ec} {sbec} {}
734 \DeclareFontSeriesChangeRule {sbx}{c} {sbc} {}
735 \DeclareFontSeriesChangeRule {sbx}{sc} {sbsc} {}
736 \DeclareFontSeriesChangeRule {sbx}{sx} {sbsx} {}
737 \DeclareFontSeriesChangeRule {sbx}{x} {sbx} {}
738 \DeclareFontSeriesChangeRule {sbx}{ex} {sbex} {}
739 \DeclareFontSeriesChangeRule {sbx}{ux} {sbux} {}

740 \DeclareFontSeriesChangeRule {sbex}{ul} {ulex} {}
741 \DeclareFontSeriesChangeRule {sbex}{el} {elex} {}
742 \DeclareFontSeriesChangeRule {sbex}{l} {lex} {}
743 \DeclareFontSeriesChangeRule {sbex}{sl} {slex} {}
744 \DeclareFontSeriesChangeRule {sbex}{sb} {sbex} {}
745 \DeclareFontSeriesChangeRule {sbex}{b} {bex} {}
746 \DeclareFontSeriesChangeRule {sbex}{eb} {ebex} {bex}
747 \DeclareFontSeriesChangeRule {sbex}{ub} {ubex} {bex}
748 \DeclareFontSeriesChangeRule {sbex}{uc} {sbuc} {}
749 \DeclareFontSeriesChangeRule {sbex}{ec} {sbec} {}
750 \DeclareFontSeriesChangeRule {sbex}{c} {sbc} {}
751 \DeclareFontSeriesChangeRule {sbex}{sc} {sbsc} {}
752 \DeclareFontSeriesChangeRule {sbex}{sx} {sbsx} {}
753 \DeclareFontSeriesChangeRule {sbex}{x} {sbx} {}
754 \DeclareFontSeriesChangeRule {sbex}{ex} {sbex} {}
755 \DeclareFontSeriesChangeRule {sbex}{ux} {sbux} {}

756 \DeclareFontSeriesChangeRule {sbux}{ul} {ulux} {}
757 \DeclareFontSeriesChangeRule {sbux}{el} {elux} {}
758 \DeclareFontSeriesChangeRule {sbux}{l} {lux} {}
759 \DeclareFontSeriesChangeRule {sbux}{sl} {slux} {}
760 \DeclareFontSeriesChangeRule {sbux}{sb} {sbux} {}
761 \DeclareFontSeriesChangeRule {sbux}{b} {bux} {}
762 \DeclareFontSeriesChangeRule {sbux}{eb} {ebux} {bux}
763 \DeclareFontSeriesChangeRule {sbux}{ub} {ubux} {bux}
764 \DeclareFontSeriesChangeRule {sbux}{uc} {sbuc} {}
765 \DeclareFontSeriesChangeRule {sbux}{ec} {sbec} {}
766 \DeclareFontSeriesChangeRule {sbux}{c} {sbc} {}
767 \DeclareFontSeriesChangeRule {sbux}{sc} {sbsc} {}
768 \DeclareFontSeriesChangeRule {sbux}{sx} {sbsx} {}

```

```

769 \DeclareFontSeriesChangeRule {sbux}{x} {sbx} {}
770 \DeclareFontSeriesChangeRule {sbux}{ex} {sbex} {}
771 \DeclareFontSeriesChangeRule {sbux}{ux} {sbux} {}

772 \DeclareFontSeriesChangeRule {buc}{ul} {uluc} {}
773 \DeclareFontSeriesChangeRule {buc}{el} {eluc} {}
774 \DeclareFontSeriesChangeRule {buc}{l} {luc} {}
775 \DeclareFontSeriesChangeRule {buc}{sl} {sluc} {}
776 \DeclareFontSeriesChangeRule {buc}{sb} {sbuc} {buc}
777 \DeclareFontSeriesChangeRule {buc}{b} {buc} {}
778 \DeclareFontSeriesChangeRule {buc}{eb} {ebuc} {buc}
779 \DeclareFontSeriesChangeRule {buc}{ub} {ubuc} {buc}
780 \DeclareFontSeriesChangeRule {buc}{uc} {buc} {}
781 \DeclareFontSeriesChangeRule {buc}{ec} {bec} {}
782 \DeclareFontSeriesChangeRule {buc}{c} {bc} {}
783 \DeclareFontSeriesChangeRule {buc}{sc} {bsc} {}
784 \DeclareFontSeriesChangeRule {buc}{sx} {bsx} {}
785 \DeclareFontSeriesChangeRule {buc}{x} {bx} {}
786 \DeclareFontSeriesChangeRule {buc}{ex} {bex} {}
787 \DeclareFontSeriesChangeRule {buc}{ux} {bux} {}

788 \DeclareFontSeriesChangeRule {bec}{ul} {ulec} {}
789 \DeclareFontSeriesChangeRule {bec}{el} {elec} {}
790 \DeclareFontSeriesChangeRule {bec}{l} {lec} {}
791 \DeclareFontSeriesChangeRule {bec}{sl} {slec} {}
792 \DeclareFontSeriesChangeRule {bec}{sb} {sbec} {bec}
793 \DeclareFontSeriesChangeRule {bec}{b} {bec} {}
794 \DeclareFontSeriesChangeRule {bec}{eb} {ebec} {bec}
795 \DeclareFontSeriesChangeRule {bec}{ub} {ubec} {bec}
796 \DeclareFontSeriesChangeRule {bec}{uc} {buc} {}
797 \DeclareFontSeriesChangeRule {bec}{ec} {bec} {}
798 \DeclareFontSeriesChangeRule {bec}{c} {bc} {}
799 \DeclareFontSeriesChangeRule {bec}{sc} {bsc} {}
800 \DeclareFontSeriesChangeRule {bec}{sx} {bsx} {}
801 \DeclareFontSeriesChangeRule {bec}{x} {bx} {}
802 \DeclareFontSeriesChangeRule {bec}{ex} {bex} {}
803 \DeclareFontSeriesChangeRule {bec}{ux} {bux} {}

804 \DeclareFontSeriesChangeRule {bc}{ul} {ulc} {}
805 \DeclareFontSeriesChangeRule {bc}{el} {elc} {}
806 \DeclareFontSeriesChangeRule {bc}{l} {lc} {}
807 \DeclareFontSeriesChangeRule {bc}{sl} {slc} {}
808 \DeclareFontSeriesChangeRule {bc}{sb} {sbc} {bc}
809 \DeclareFontSeriesChangeRule {bc}{b} {bc} {}
810 \DeclareFontSeriesChangeRule {bc}{eb} {ebc} {bc}
811 \DeclareFontSeriesChangeRule {bc}{ub} {ubc} {bc}
812 \DeclareFontSeriesChangeRule {bc}{uc} {buc} {}
813 \DeclareFontSeriesChangeRule {bc}{ec} {bec} {}
814 \DeclareFontSeriesChangeRule {bc}{c} {bc} {}
815 \DeclareFontSeriesChangeRule {bc}{sc} {bsc} {}
816 \DeclareFontSeriesChangeRule {bc}{sx} {bsx} {}
817 \DeclareFontSeriesChangeRule {bc}{x} {bx} {}
818 \DeclareFontSeriesChangeRule {bc}{ex} {bex} {}
819 \DeclareFontSeriesChangeRule {bc}{ux} {bux} {}

820 \DeclareFontSeriesChangeRule {bsc}{ul} {ulsc} {}
821 \DeclareFontSeriesChangeRule {bsc}{el} {elsc} {}

```

```

822 \DeclareFontSeriesChangeRule {bsc}{l}  {lsc}  {}
823 \DeclareFontSeriesChangeRule {bsc}{sl} {slsc} {}
824 \DeclareFontSeriesChangeRule {bsc}{sb}  {sbsc} {bsc}
825 \DeclareFontSeriesChangeRule {bsc}{b}   {bsc}  {}
826 \DeclareFontSeriesChangeRule {bsc}{eb}  {ebsc}  {bsc}
827 \DeclareFontSeriesChangeRule {bsc}{ub}  {ubsc}  {bsc}
828 \DeclareFontSeriesChangeRule {bsc}{uc}  {buc}   {}
829 \DeclareFontSeriesChangeRule {bsc}{ec}  {bec}   {}
830 \DeclareFontSeriesChangeRule {bsc}{c}   {bc}    {}
831 \DeclareFontSeriesChangeRule {bsc}{sc}  {bsc}   {}
832 \DeclareFontSeriesChangeRule {bsc}{sx}  {bsx}   {}
833 \DeclareFontSeriesChangeRule {bsc}{x}   {bx}    {}
834 \DeclareFontSeriesChangeRule {bsc}{ex}  {bex}   {}
835 \DeclareFontSeriesChangeRule {bsc}{ux}  {bux}   {}

```

If we are in **b** and a width change is requested that leads to a missing font face we stay in **b** because then the font family probably doesn't implement width changes at all.

```

836 \DeclareFontSeriesChangeRule {b}{uc}    {buc}   {b}
837 \DeclareFontSeriesChangeRule {b}{ec}    {bec}   {b}
838 \DeclareFontSeriesChangeRule {b}{c}     {bc}    {b}
839 \DeclareFontSeriesChangeRule {b}{sc}    {bsc}   {b}
840 \DeclareFontSeriesChangeRule {b}{sx}    {bsx}   {b}
841 \DeclareFontSeriesChangeRule {b}{x}     {bx}    {b}
842 \DeclareFontSeriesChangeRule {b}{ex}    {bex}   {b}
843 \DeclareFontSeriesChangeRule {b}{ux}    {bux}   {b}
844 \DeclareFontSeriesChangeRule {b}{sb}    {sb}    {b}
845 \DeclareFontSeriesChangeRule {b}{eb}    {eb}    {b}
846 \DeclareFontSeriesChangeRule {b}{ub}    {ub}    {b}

847 \DeclareFontSeriesChangeRule {bsx}{ul}  {ulsx}  {}
848 \DeclareFontSeriesChangeRule {bsx}{el}  {elsx}  {}
849 \DeclareFontSeriesChangeRule {bsx}{l}   {lsx}   {}
850 \DeclareFontSeriesChangeRule {bsx}{sl}  {slsx}  {}
851 \DeclareFontSeriesChangeRule {bsx}{sb}  {sbsx}  {bsx}
852 \DeclareFontSeriesChangeRule {bsx}{b}   {bsx}   {}
853 \DeclareFontSeriesChangeRule {bsx}{eb}  {ebsx}  {bsx}
854 \DeclareFontSeriesChangeRule {bsx}{ub}  {ubsx}  {bsx}
855 \DeclareFontSeriesChangeRule {bsx}{uc}  {buc}   {}
856 \DeclareFontSeriesChangeRule {bsx}{ec}  {bec}   {}
857 \DeclareFontSeriesChangeRule {bsx}{c}   {bc}    {}
858 \DeclareFontSeriesChangeRule {bsx}{sc}  {bsc}   {}
859 \DeclareFontSeriesChangeRule {bsx}{sx}  {bsx}   {}
860 \DeclareFontSeriesChangeRule {bsx}{x}   {bx}    {}
861 \DeclareFontSeriesChangeRule {bsx}{ex}  {bex}   {}
862 \DeclareFontSeriesChangeRule {bsx}{ux}  {bux}   {}

863 \DeclareFontSeriesChangeRule {bx}{ul}   {ulx}   {}
864 \DeclareFontSeriesChangeRule {bx}{el}   {elx}   {}
865 \DeclareFontSeriesChangeRule {bx}{l}    {lx}    {}
866 \DeclareFontSeriesChangeRule {bx}{sl}   {slx}   {}
867 \DeclareFontSeriesChangeRule {bx}{sb}   {sbx}   {bx}
868 \DeclareFontSeriesChangeRule {bx}{b}    {bx}    {}
869 \DeclareFontSeriesChangeRule {bx}{eb}   {ebx}   {bx}
870 \DeclareFontSeriesChangeRule {bx}{ub}   {ubx}   {bx}
871 \DeclareFontSeriesChangeRule {bx}{uc}   {buc}   {}

```

```

872 \DeclareFontSeriesChangeRule {bx}{ec} {bec} {}
873 \DeclareFontSeriesChangeRule {bx}{c} {bc} {}
874 \DeclareFontSeriesChangeRule {bx}{sc} {bsc} {}
875 \DeclareFontSeriesChangeRule {bx}{sx} {bsx} {}
876 \DeclareFontSeriesChangeRule {bx}{x} {bx} {}
877 \DeclareFontSeriesChangeRule {bx}{ex} {bex} {}
878 \DeclareFontSeriesChangeRule {bx}{ux} {bux} {}

879 \DeclareFontSeriesChangeRule {bex}{ul} {ulex} {}
880 \DeclareFontSeriesChangeRule {bex}{el} {ellex} {}
881 \DeclareFontSeriesChangeRule {bex}{l} {llex} {}
882 \DeclareFontSeriesChangeRule {bex}{sl} {sllex} {}
883 \DeclareFontSeriesChangeRule {bex}{sb} {sbex} {bex}
884 \DeclareFontSeriesChangeRule {bex}{b} {bex} {}
885 \DeclareFontSeriesChangeRule {bex}{eb} {ebex} {bex}
886 \DeclareFontSeriesChangeRule {bex}{ub} {ubex} {bex}
887 \DeclareFontSeriesChangeRule {bex}{uc} {buc} {}
888 \DeclareFontSeriesChangeRule {bex}{ec} {bec} {}
889 \DeclareFontSeriesChangeRule {bex}{c} {bc} {}
890 \DeclareFontSeriesChangeRule {bex}{sc} {bsc} {}
891 \DeclareFontSeriesChangeRule {bex}{sx} {bsx} {}
892 \DeclareFontSeriesChangeRule {bex}{x} {bx} {}
893 \DeclareFontSeriesChangeRule {bex}{ex} {bex} {}
894 \DeclareFontSeriesChangeRule {bex}{ux} {bux} {}

895 \DeclareFontSeriesChangeRule {bux}{ul} {ulux} {}
896 \DeclareFontSeriesChangeRule {bux}{el} {elux} {}
897 \DeclareFontSeriesChangeRule {bux}{l} {lux} {}
898 \DeclareFontSeriesChangeRule {bux}{sl} {slux} {}
899 \DeclareFontSeriesChangeRule {bux}{sb} {sbux} {bux}
900 \DeclareFontSeriesChangeRule {bux}{b} {bux} {}
901 \DeclareFontSeriesChangeRule {bux}{eb} {ebux} {bux}
902 \DeclareFontSeriesChangeRule {bux}{ub} {ubux} {bux}
903 \DeclareFontSeriesChangeRule {bux}{uc} {buc} {}
904 \DeclareFontSeriesChangeRule {bux}{ec} {bec} {}
905 \DeclareFontSeriesChangeRule {bux}{c} {bc} {}
906 \DeclareFontSeriesChangeRule {bux}{sc} {bsc} {}
907 \DeclareFontSeriesChangeRule {bux}{sx} {bsx} {}
908 \DeclareFontSeriesChangeRule {bux}{x} {bx} {}
909 \DeclareFontSeriesChangeRule {bux}{ex} {bex} {}
910 \DeclareFontSeriesChangeRule {bux}{ux} {bux} {}

911 \DeclareFontSeriesChangeRule {ebuc}{ul} {uluc} {}
912 \DeclareFontSeriesChangeRule {ebuc}{el} {eluc} {}
913 \DeclareFontSeriesChangeRule {ebuc}{l} {luc} {}
914 \DeclareFontSeriesChangeRule {ebuc}{sl} {sluc} {}
915 \DeclareFontSeriesChangeRule {ebuc}{sb} {sbuc} {buc}
916 \DeclareFontSeriesChangeRule {ebuc}{b} {buc} {}
917 \DeclareFontSeriesChangeRule {ebuc}{eb} {ebuc} {}

```

In the following rule, we use **eb** instead of **b** in the fourth argument, since **eb** is a better approximation to **ub** than **b** and **ebuc** is already in the first argument and therefore this font face probably actually exists. A similar consideration also applies to some other rules in the following.

```

918 \DeclareFontSeriesChangeRule {ebuc}{ub} {ubuc} {ebuc}
919 \DeclareFontSeriesChangeRule {ebuc}{uc} {ebuc} {}

```

```

920 \DeclareFontSeriesChangeRule {ebuc}{ec} {ebec} {}
921 \DeclareFontSeriesChangeRule {ebuc}{c} {ebc} {}
922 \DeclareFontSeriesChangeRule {ebuc}{sc} {ebsc} {}
923 \DeclareFontSeriesChangeRule {ebuc}{sx} {ebsx} {}
924 \DeclareFontSeriesChangeRule {ebuc}{x} {ebx} {}
925 \DeclareFontSeriesChangeRule {ebuc}{ex} {ebex} {}
926 \DeclareFontSeriesChangeRule {ebuc}{ux} {ebux} {}

927 \DeclareFontSeriesChangeRule {ebec}{ul} {ulec} {}
928 \DeclareFontSeriesChangeRule {ebec}{el} {elec} {}
929 \DeclareFontSeriesChangeRule {ebec}{l} {lec} {}
930 \DeclareFontSeriesChangeRule {ebec}{sl} {slec} {}
931 \DeclareFontSeriesChangeRule {ebec}{sb} {sbec} {bec}
932 \DeclareFontSeriesChangeRule {ebec}{b} {bec} {}
933 \DeclareFontSeriesChangeRule {ebec}{eb} {ebec} {}
934 \DeclareFontSeriesChangeRule {ebec}{ub} {ubec} {ebec}
935 \DeclareFontSeriesChangeRule {ebec}{uc} {ebuc} {}
936 \DeclareFontSeriesChangeRule {ebec}{ec} {ebec} {}
937 \DeclareFontSeriesChangeRule {ebec}{c} {ebc} {}
938 \DeclareFontSeriesChangeRule {ebec}{sc} {ebsc} {}
939 \DeclareFontSeriesChangeRule {ebec}{sx} {ebsx} {}
940 \DeclareFontSeriesChangeRule {ebec}{x} {ebx} {}
941 \DeclareFontSeriesChangeRule {ebec}{ex} {ebex} {}
942 \DeclareFontSeriesChangeRule {ebec}{ux} {ebux} {}

943 \DeclareFontSeriesChangeRule {ebc}{ul} {ulc} {}
944 \DeclareFontSeriesChangeRule {ebc}{el} {elc} {}
945 \DeclareFontSeriesChangeRule {ebc}{l} {lc} {}
946 \DeclareFontSeriesChangeRule {ebc}{sl} {slc} {}
947 \DeclareFontSeriesChangeRule {ebc}{sb} {sbc} {bc}
948 \DeclareFontSeriesChangeRule {ebc}{b} {bc} {}
949 \DeclareFontSeriesChangeRule {ebc}{eb} {ebc} {}
950 \DeclareFontSeriesChangeRule {ebc}{ub} {ubc} {ebc}
951 \DeclareFontSeriesChangeRule {ebc}{uc} {ebuc} {}
952 \DeclareFontSeriesChangeRule {ebc}{ec} {ebec} {}
953 \DeclareFontSeriesChangeRule {ebc}{c} {ebc} {}
954 \DeclareFontSeriesChangeRule {ebc}{sc} {ebsc} {}
955 \DeclareFontSeriesChangeRule {ebc}{sx} {ebsx} {}
956 \DeclareFontSeriesChangeRule {ebc}{x} {ebx} {}
957 \DeclareFontSeriesChangeRule {ebc}{ex} {ebex} {}
958 \DeclareFontSeriesChangeRule {ebc}{ux} {ebux} {}

959 \DeclareFontSeriesChangeRule {ebsc}{ul} {ulsc} {}
960 \DeclareFontSeriesChangeRule {ebsc}{el} {elsc} {}
961 \DeclareFontSeriesChangeRule {ebsc}{l} {lsc} {}
962 \DeclareFontSeriesChangeRule {ebsc}{sl} {slsc} {}
963 \DeclareFontSeriesChangeRule {ebsc}{sb} {sbsc} {bsc}
964 \DeclareFontSeriesChangeRule {ebsc}{b} {bsc} {}
965 \DeclareFontSeriesChangeRule {ebsc}{eb} {ebsc} {}
966 \DeclareFontSeriesChangeRule {ebsc}{ub} {ubsc} {ebsc}
967 \DeclareFontSeriesChangeRule {ebsc}{uc} {ebuc} {}
968 \DeclareFontSeriesChangeRule {ebsc}{ec} {ebec} {}
969 \DeclareFontSeriesChangeRule {ebsc}{c} {ebc} {}
970 \DeclareFontSeriesChangeRule {ebsc}{sc} {ebsc} {}
971 \DeclareFontSeriesChangeRule {ebsc}{sx} {ebsx} {}
972 \DeclareFontSeriesChangeRule {ebsc}{x} {ebx} {}

```

```

973 \DeclareFontSeriesChangeRule {ebsc}{ex} {ebex} {}
974 \DeclareFontSeriesChangeRule {ebsc}{ux} {ebux} {}

975 \DeclareFontSeriesChangeRule {eb}{uc} {ebuc} {}
976 \DeclareFontSeriesChangeRule {eb}{ec} {ebec} {}
977 \DeclareFontSeriesChangeRule {eb}{c} {ebc} {}
978 \DeclareFontSeriesChangeRule {eb}{sc} {ebsc} {}
979 \DeclareFontSeriesChangeRule {eb}{sx} {ebsx} {}
980 \DeclareFontSeriesChangeRule {eb}{x} {ebx} {}
981 \DeclareFontSeriesChangeRule {eb}{ex} {ebex} {}
982 \DeclareFontSeriesChangeRule {eb}{ux} {ebux} {}
983 \DeclareFontSeriesChangeRule {eb}{sb} {sb} {b}
984 \DeclareFontSeriesChangeRule {eb}{ub} {ub} {eb}

985 \DeclareFontSeriesChangeRule {ebsx}{ul} {ulsx} {}
986 \DeclareFontSeriesChangeRule {ebsx}{el} {elsx} {}
987 \DeclareFontSeriesChangeRule {ebsx}{l} {lsx} {}
988 \DeclareFontSeriesChangeRule {ebsx}{sl} {slsx} {}
989 \DeclareFontSeriesChangeRule {ebsx}{sb} {sbsx} {bsx}
990 \DeclareFontSeriesChangeRule {ebsx}{b} {bsx} {}
991 \DeclareFontSeriesChangeRule {ebsx}{eb} {ebsx} {}
992 \DeclareFontSeriesChangeRule {ebsx}{ub} {ubsx} {ebsx}
993 \DeclareFontSeriesChangeRule {ebsx}{uc} {ebuc} {}
994 \DeclareFontSeriesChangeRule {ebsx}{ec} {ebec} {}
995 \DeclareFontSeriesChangeRule {ebsx}{c} {ebc} {}
996 \DeclareFontSeriesChangeRule {ebsx}{sc} {ebsc} {}
997 \DeclareFontSeriesChangeRule {ebsx}{sx} {ebsx} {}
998 \DeclareFontSeriesChangeRule {ebsx}{x} {ebx} {}
999 \DeclareFontSeriesChangeRule {ebsx}{ex} {ebex} {}
1000 \DeclareFontSeriesChangeRule {ebsx}{ux} {ebux} {}

1001 \DeclareFontSeriesChangeRule {ebx}{ul} {ulx} {}
1002 \DeclareFontSeriesChangeRule {ebx}{el} {elx} {}
1003 \DeclareFontSeriesChangeRule {ebx}{l} {lx} {}
1004 \DeclareFontSeriesChangeRule {ebx}{sl} {slx} {}
1005 \DeclareFontSeriesChangeRule {ebx}{sb} {sbx} {bx}
1006 \DeclareFontSeriesChangeRule {ebx}{b} {bx} {}
1007 \DeclareFontSeriesChangeRule {ebx}{eb} {ebx} {}
1008 \DeclareFontSeriesChangeRule {ebx}{ub} {ubx} {ebx}
1009 \DeclareFontSeriesChangeRule {ebx}{uc} {ebuc} {}
1010 \DeclareFontSeriesChangeRule {ebx}{ec} {ebec} {}
1011 \DeclareFontSeriesChangeRule {ebx}{c} {ebc} {}
1012 \DeclareFontSeriesChangeRule {ebx}{sc} {ebsc} {}
1013 \DeclareFontSeriesChangeRule {ebx}{sx} {ebsx} {}
1014 \DeclareFontSeriesChangeRule {ebx}{x} {ebx} {}
1015 \DeclareFontSeriesChangeRule {ebx}{ex} {ebex} {}
1016 \DeclareFontSeriesChangeRule {ebx}{ux} {ebux} {}

1017 \DeclareFontSeriesChangeRule {ebex}{ul} {ulex} {}
1018 \DeclareFontSeriesChangeRule {ebex}{el} {ele x} {}
1019 \DeclareFontSeriesChangeRule {ebex}{l} {lex} {}
1020 \DeclareFontSeriesChangeRule {ebex}{sl} {slex} {}
1021 \DeclareFontSeriesChangeRule {ebex}{sb} {sbox} {box}
1022 \DeclareFontSeriesChangeRule {ebex}{b} {box} {}
1023 \DeclareFontSeriesChangeRule {ebex}{eb} {ebex} {}
1024 \DeclareFontSeriesChangeRule {ebex}{ub} {ubex} {ebex}
1025 \DeclareFontSeriesChangeRule {ebex}{uc} {ebuc} {}

```

```

1026 \DeclareFontSeriesChangeRule {ebex}{ec} {ebec} {}
1027 \DeclareFontSeriesChangeRule {ebex}{c} {ebc} {}
1028 \DeclareFontSeriesChangeRule {ebex}{sc} {ebsc} {}
1029 \DeclareFontSeriesChangeRule {ebex}{sx} {ebsx} {}
1030 \DeclareFontSeriesChangeRule {ebex}{x} {ebx} {}
1031 \DeclareFontSeriesChangeRule {ebex}{ex} {ebex} {}
1032 \DeclareFontSeriesChangeRule {ebex}{ux} {ebux} {}

1033 \DeclareFontSeriesChangeRule {ebux}{ul} {ulux} {}
1034 \DeclareFontSeriesChangeRule {ebux}{el} {elux} {}
1035 \DeclareFontSeriesChangeRule {ebux}{l} {lux} {}
1036 \DeclareFontSeriesChangeRule {ebux}{sl} {slux} {}
1037 \DeclareFontSeriesChangeRule {ebux}{sb} {sbux} {bux}
1038 \DeclareFontSeriesChangeRule {ebux}{b} {bux} {}
1039 \DeclareFontSeriesChangeRule {ebux}{eb} {ebux} {}
1040 \DeclareFontSeriesChangeRule {ebux}{ub} {ubux} {ebux}
1041 \DeclareFontSeriesChangeRule {ebux}{uc} {ebuc} {}
1042 \DeclareFontSeriesChangeRule {ebux}{ec} {ebec} {}
1043 \DeclareFontSeriesChangeRule {ebux}{c} {ebc} {}
1044 \DeclareFontSeriesChangeRule {ebux}{sc} {ebsc} {}
1045 \DeclareFontSeriesChangeRule {ebux}{sx} {ebsx} {}
1046 \DeclareFontSeriesChangeRule {ebux}{x} {ebx} {}
1047 \DeclareFontSeriesChangeRule {ebux}{ex} {ebex} {}
1048 \DeclareFontSeriesChangeRule {ebux}{ux} {ebux} {}

1049 \DeclareFontSeriesChangeRule {ubuc}{ul} {uluc} {}
1050 \DeclareFontSeriesChangeRule {ubuc}{el} {eluc} {}
1051 \DeclareFontSeriesChangeRule {ubuc}{l} {luc} {}
1052 \DeclareFontSeriesChangeRule {ubuc}{sl} {sluc} {}
1053 \DeclareFontSeriesChangeRule {ubuc}{sb} {sbuc} {buc}
1054 \DeclareFontSeriesChangeRule {ubuc}{b} {buc} {}
1055 \DeclareFontSeriesChangeRule {ubuc}{eb} {ebuc} {ubuc}
1056 \DeclareFontSeriesChangeRule {ubuc}{ub} {ubuc} {}
1057 \DeclareFontSeriesChangeRule {ubuc}{uc} {ubuc} {}
1058 \DeclareFontSeriesChangeRule {ubuc}{ec} {ubec} {}
1059 \DeclareFontSeriesChangeRule {ubuc}{c} {ubc} {}
1060 \DeclareFontSeriesChangeRule {ubuc}{sc} {ubsc} {}
1061 \DeclareFontSeriesChangeRule {ubuc}{sx} {ubsx} {}
1062 \DeclareFontSeriesChangeRule {ubuc}{x} {ubx} {}
1063 \DeclareFontSeriesChangeRule {ubuc}{ex} {ubex} {}
1064 \DeclareFontSeriesChangeRule {ubuc}{ux} {ubux} {}

1065 \DeclareFontSeriesChangeRule {ubec}{ul} {ulec} {}
1066 \DeclareFontSeriesChangeRule {ubec}{el} {elec} {}
1067 \DeclareFontSeriesChangeRule {ubec}{l} {lec} {}
1068 \DeclareFontSeriesChangeRule {ubec}{sl} {slec} {}
1069 \DeclareFontSeriesChangeRule {ubec}{sb} {sbec} {bec}
1070 \DeclareFontSeriesChangeRule {ubec}{b} {bec} {}
1071 \DeclareFontSeriesChangeRule {ubec}{eb} {ebec} {ubec}
1072 \DeclareFontSeriesChangeRule {ubec}{ub} {ubec} {}
1073 \DeclareFontSeriesChangeRule {ubec}{uc} {ubuc} {}
1074 \DeclareFontSeriesChangeRule {ubec}{ec} {ubec} {}
1075 \DeclareFontSeriesChangeRule {ubec}{c} {ubc} {}
1076 \DeclareFontSeriesChangeRule {ubec}{sc} {ubsc} {}
1077 \DeclareFontSeriesChangeRule {ubec}{sx} {ubsx} {}
1078 \DeclareFontSeriesChangeRule {ubec}{x} {ubx} {}

```

```

1079 \DeclareFontSeriesChangeRule {ubec}{ex} {ubex} {}
1080 \DeclareFontSeriesChangeRule {ubec}{ux} {ubux} {}

1081 \DeclareFontSeriesChangeRule {ubc}{ul} {ulc} {}
1082 \DeclareFontSeriesChangeRule {ubc}{el} {elc} {}
1083 \DeclareFontSeriesChangeRule {ubc}{l} {lc} {}
1084 \DeclareFontSeriesChangeRule {ubc}{sl} {slc} {}
1085 \DeclareFontSeriesChangeRule {ubc}{sb} {sbc} {bc}
1086 \DeclareFontSeriesChangeRule {ubc}{b} {bc} {}
1087 \DeclareFontSeriesChangeRule {ubc}{eb} {ebc} {ubc}
1088 \DeclareFontSeriesChangeRule {ubc}{ub} {ubc} {}
1089 \DeclareFontSeriesChangeRule {ubc}{uc} {ubuc} {}
1090 \DeclareFontSeriesChangeRule {ubc}{ec} {ubec} {}
1091 \DeclareFontSeriesChangeRule {ubc}{c} {ubc} {}
1092 \DeclareFontSeriesChangeRule {ubc}{sc} {ubsc} {}
1093 \DeclareFontSeriesChangeRule {ubc}{sx} {ubsx} {}
1094 \DeclareFontSeriesChangeRule {ubc}{x} {ubx} {}
1095 \DeclareFontSeriesChangeRule {ubc}{ex} {ubex} {}
1096 \DeclareFontSeriesChangeRule {ubc}{ux} {ubux} {}

1097 \DeclareFontSeriesChangeRule {ubsc}{ul} {ulsc} {}
1098 \DeclareFontSeriesChangeRule {ubsc}{el} {elsc} {}
1099 \DeclareFontSeriesChangeRule {ubsc}{l} {lsc} {}
1100 \DeclareFontSeriesChangeRule {ubsc}{sl} {slsc} {}
1101 \DeclareFontSeriesChangeRule {ubsc}{sb} {sbsc} {bsc}
1102 \DeclareFontSeriesChangeRule {ubsc}{b} {bsc} {}
1103 \DeclareFontSeriesChangeRule {ubsc}{eb} {ebsc} {ubsc}
1104 \DeclareFontSeriesChangeRule {ubsc}{ub} {ubsc} {}
1105 \DeclareFontSeriesChangeRule {ubsc}{uc} {ubuc} {}
1106 \DeclareFontSeriesChangeRule {ubsc}{ec} {ubec} {}
1107 \DeclareFontSeriesChangeRule {ubsc}{c} {ubc} {}
1108 \DeclareFontSeriesChangeRule {ubsc}{sc} {ubsc} {}
1109 \DeclareFontSeriesChangeRule {ubsc}{sx} {ubsx} {}
1110 \DeclareFontSeriesChangeRule {ubsc}{x} {ubx} {}
1111 \DeclareFontSeriesChangeRule {ubsc}{ex} {ubex} {}
1112 \DeclareFontSeriesChangeRule {ubsc}{ux} {ubux} {}

1113 \DeclareFontSeriesChangeRule {ub}{uc} {ubuc} {}
1114 \DeclareFontSeriesChangeRule {ub}{ec} {ubec} {}
1115 \DeclareFontSeriesChangeRule {ub}{c} {ubc} {}
1116 \DeclareFontSeriesChangeRule {ub}{sc} {ubsc} {}
1117 \DeclareFontSeriesChangeRule {ub}{sx} {ubsx} {}
1118 \DeclareFontSeriesChangeRule {ub}{x} {ubx} {}
1119 \DeclareFontSeriesChangeRule {ub}{ex} {ubex} {}
1120 \DeclareFontSeriesChangeRule {ub}{ux} {ubux} {}
1121 \DeclareFontSeriesChangeRule {ub}{sb} {sb} {b}
1122 \DeclareFontSeriesChangeRule {ub}{eb} {eb} {ub}

1123 \DeclareFontSeriesChangeRule {ubsx}{ul} {ulsx} {}
1124 \DeclareFontSeriesChangeRule {ubsx}{el} {elsx} {}
1125 \DeclareFontSeriesChangeRule {ubsx}{l} {lsx} {}
1126 \DeclareFontSeriesChangeRule {ubsx}{sl} {slsx} {}
1127 \DeclareFontSeriesChangeRule {ubsx}{sb} {sbsx} {bsx}
1128 \DeclareFontSeriesChangeRule {ubsx}{b} {bsx} {}
1129 \DeclareFontSeriesChangeRule {ubsx}{eb} {ebsx} {ubsx}
1130 \DeclareFontSeriesChangeRule {ubsx}{ub} {ubsx} {}
1131 \DeclareFontSeriesChangeRule {ubsx}{uc} {ubuc} {}

```

```

1132 \DeclareFontSeriesChangeRule {ubsx}{ec} {ubec} {}
1133 \DeclareFontSeriesChangeRule {ubsx}{c} {ubc} {}
1134 \DeclareFontSeriesChangeRule {ubsx}{sc} {ubsc} {}
1135 \DeclareFontSeriesChangeRule {ubsx}{sx} {ubsx} {}
1136 \DeclareFontSeriesChangeRule {ubsx}{x} {ubx} {}
1137 \DeclareFontSeriesChangeRule {ubsx}{ex} {ubex} {}
1138 \DeclareFontSeriesChangeRule {ubsx}{ux} {ubux} {}

1139 \DeclareFontSeriesChangeRule {ubx}{ul} {ulx} {}
1140 \DeclareFontSeriesChangeRule {ubx}{el} {elx} {}
1141 \DeclareFontSeriesChangeRule {ubx}{l} {lx} {}
1142 \DeclareFontSeriesChangeRule {ubx}{sl} {slx} {}
1143 \DeclareFontSeriesChangeRule {ubx}{sb} {sbx} {bx}
1144 \DeclareFontSeriesChangeRule {ubx}{b} {bx} {}
1145 \DeclareFontSeriesChangeRule {ubx}{eb} {ebx} {ubx}
1146 \DeclareFontSeriesChangeRule {ubx}{ub} {ubx} {}
1147 \DeclareFontSeriesChangeRule {ubx}{uc} {ubuc} {}
1148 \DeclareFontSeriesChangeRule {ubx}{ec} {ubec} {}
1149 \DeclareFontSeriesChangeRule {ubx}{c} {ubc} {}
1150 \DeclareFontSeriesChangeRule {ubx}{sc} {ubsc} {}
1151 \DeclareFontSeriesChangeRule {ubx}{sx} {ubsx} {}
1152 \DeclareFontSeriesChangeRule {ubx}{x} {ubx} {}
1153 \DeclareFontSeriesChangeRule {ubx}{ex} {ubex} {}
1154 \DeclareFontSeriesChangeRule {ubx}{ux} {ubux} {}

1155 \DeclareFontSeriesChangeRule {ubex}{ul} {ulex} {}
1156 \DeclareFontSeriesChangeRule {ubex}{el} {elx} {}
1157 \DeclareFontSeriesChangeRule {ubex}{l} {lex} {}
1158 \DeclareFontSeriesChangeRule {ubex}{sl} {slex} {}
1159 \DeclareFontSeriesChangeRule {ubex}{sb} {sbex} {bex}
1160 \DeclareFontSeriesChangeRule {ubex}{b} {bex} {}
1161 \DeclareFontSeriesChangeRule {ubex}{eb} {ebex} {ubex}
1162 \DeclareFontSeriesChangeRule {ubex}{ub} {ubex} {}
1163 \DeclareFontSeriesChangeRule {ubex}{uc} {ubuc} {}
1164 \DeclareFontSeriesChangeRule {ubex}{ec} {ubec} {}
1165 \DeclareFontSeriesChangeRule {ubex}{c} {ubc} {}
1166 \DeclareFontSeriesChangeRule {ubex}{sc} {ubsc} {}
1167 \DeclareFontSeriesChangeRule {ubex}{sx} {ubsx} {}
1168 \DeclareFontSeriesChangeRule {ubex}{x} {ubx} {}
1169 \DeclareFontSeriesChangeRule {ubex}{ex} {ubex} {}
1170 \DeclareFontSeriesChangeRule {ubex}{ux} {ubux} {}

1171 \DeclareFontSeriesChangeRule {ubux}{ul} {ulux} {}
1172 \DeclareFontSeriesChangeRule {ubux}{el} {elux} {}
1173 \DeclareFontSeriesChangeRule {ubux}{l} {lux} {}
1174 \DeclareFontSeriesChangeRule {ubux}{sl} {slux} {}
1175 \DeclareFontSeriesChangeRule {ubux}{sb} {sbux} {bux}
1176 \DeclareFontSeriesChangeRule {ubux}{b} {bux} {}
1177 \DeclareFontSeriesChangeRule {ubux}{eb} {ebux} {ubux}
1178 \DeclareFontSeriesChangeRule {ubux}{ub} {ubux} {}
1179 \DeclareFontSeriesChangeRule {ubux}{uc} {ubuc} {}
1180 \DeclareFontSeriesChangeRule {ubux}{ec} {ubec} {}
1181 \DeclareFontSeriesChangeRule {ubux}{c} {ubc} {}
1182 \DeclareFontSeriesChangeRule {ubux}{sc} {ubsc} {}
1183 \DeclareFontSeriesChangeRule {ubux}{sx} {ubsx} {}
1184 \DeclareFontSeriesChangeRule {ubux}{x} {ubx} {}

```

```

1185 \DeclareFontSeriesChangeRule {ubux}{ex} {ubex} {}
1186 \DeclareFontSeriesChangeRule {ubux}{ux} {ubux} {}

```

Special rules for `lm` etc. aren't needed because if `lm` is requested, it will be used if there is no rule, and that is then reduced to `l` automatically. Same for `mc` and friends.

The following entries handle a request for `bx` and fall back to `b` if that can't be fulfilled.

```

1187 \DeclareFontSeriesChangeRule {uluc}{bx} {bx} {b}
1188 \DeclareFontSeriesChangeRule {ulec}{bx} {bx} {b}
1189 \DeclareFontSeriesChangeRule {ulc}{bx} {bx} {b}
1190 \DeclareFontSeriesChangeRule {ulsc}{bx} {bx} {b}
1191 \DeclareFontSeriesChangeRule {ul}{bx} {bx} {b}
1192 \DeclareFontSeriesChangeRule {ulsx}{bx} {bx} {b}
1193 \DeclareFontSeriesChangeRule {ulx}{bx} {bx} {b}
1194 \DeclareFontSeriesChangeRule {ulex}{bx} {bx} {b}
1195 \DeclareFontSeriesChangeRule {ulux}{bx} {bx} {b}

1196 \DeclareFontSeriesChangeRule {eluc}{bx} {bx} {b}
1197 \DeclareFontSeriesChangeRule {elec}{bx} {bx} {b}
1198 \DeclareFontSeriesChangeRule {elc}{bx} {bx} {b}
1199 \DeclareFontSeriesChangeRule {elsc}{bx} {bx} {b}
1200 \DeclareFontSeriesChangeRule {el}{bx} {bx} {b}
1201 \DeclareFontSeriesChangeRule {elsx}{bx} {bx} {b}
1202 \DeclareFontSeriesChangeRule {elx}{bx} {bx} {b}
1203 \DeclareFontSeriesChangeRule {ellex}{bx} {bx} {b}
1204 \DeclareFontSeriesChangeRule {elux}{bx} {bx} {b}

1205 \DeclareFontSeriesChangeRule {luc}{bx} {bx} {b}
1206 \DeclareFontSeriesChangeRule {lec}{bx} {bx} {b}
1207 \DeclareFontSeriesChangeRule {lc}{bx} {bx} {b}
1208 \DeclareFontSeriesChangeRule {lsc}{bx} {bx} {b}
1209 \DeclareFontSeriesChangeRule {l}{bx} {bx} {b}
1210 \DeclareFontSeriesChangeRule {lsx}{bx} {bx} {b}
1211 \DeclareFontSeriesChangeRule {lx}{bx} {bx} {b}
1212 \DeclareFontSeriesChangeRule {lex}{bx} {bx} {b}
1213 \DeclareFontSeriesChangeRule {lux}{bx} {bx} {b}

1214 \DeclareFontSeriesChangeRule {sluc}{bx} {bx} {b}
1215 \DeclareFontSeriesChangeRule {slec}{bx} {bx} {b}
1216 \DeclareFontSeriesChangeRule {slc}{bx} {bx} {b}
1217 \DeclareFontSeriesChangeRule {slsc}{bx} {bx} {b}
1218 \DeclareFontSeriesChangeRule {sl}{bx} {bx} {b}
1219 \DeclareFontSeriesChangeRule {slsx}{bx} {bx} {b}
1220 \DeclareFontSeriesChangeRule {slx}{bx} {bx} {b}
1221 \DeclareFontSeriesChangeRule {slex}{bx} {bx} {b}
1222 \DeclareFontSeriesChangeRule {slux}{bx} {bx} {b}

1223 \DeclareFontSeriesChangeRule {uc}{bx} {bx} {b}
1224 \DeclareFontSeriesChangeRule {ec}{bx} {bx} {b}
1225 \DeclareFontSeriesChangeRule {c}{bx} {bx} {b}
1226 \DeclareFontSeriesChangeRule {sc}{bx} {bx} {b}
1227 \DeclareFontSeriesChangeRule {m}{bx} {bx} {b}
1228 \DeclareFontSeriesChangeRule {sx}{bx} {bx} {b}
1229 \DeclareFontSeriesChangeRule {x}{bx} {bx} {b}
1230 \DeclareFontSeriesChangeRule {ex}{bx} {bx} {b}
1231 \DeclareFontSeriesChangeRule {ux}{bx} {bx} {b}

```

```

1232 \DeclareFontSeriesChangeRule {sbuc}{bx} {bx} {b}
1233 \DeclareFontSeriesChangeRule {sbec}{bx} {bx} {b}
1234 \DeclareFontSeriesChangeRule {sbc}{bx} {bx} {b}
1235 \DeclareFontSeriesChangeRule {sbsc}{bx} {bx} {b}
1236 \DeclareFontSeriesChangeRule {sb}{bx} {bx} {b}
1237 \DeclareFontSeriesChangeRule {sbsx}{bx} {bx} {b}
1238 \DeclareFontSeriesChangeRule {sbx}{bx} {bx} {b}
1239 \DeclareFontSeriesChangeRule {sbex}{bx} {bx} {b}
1240 \DeclareFontSeriesChangeRule {sbux}{bx} {bx} {b}

1241 \DeclareFontSeriesChangeRule {buc}{bx} {bx} {b}
1242 \DeclareFontSeriesChangeRule {bec}{bx} {bx} {b}
1243 \DeclareFontSeriesChangeRule {bc}{bx} {bx} {b}
1244 \DeclareFontSeriesChangeRule {bsc}{bx} {bx} {b}
1245 \DeclareFontSeriesChangeRule {b}{bx} {bx} {b}
1246 \DeclareFontSeriesChangeRule {bsx}{bx} {bx} {b}
1247 \DeclareFontSeriesChangeRule {bx}{bx} {bx} {b}
1248 \DeclareFontSeriesChangeRule {bex}{bx} {bx} {b}
1249 \DeclareFontSeriesChangeRule {bux}{bx} {bx} {b}

1250 \DeclareFontSeriesChangeRule {ebuc}{bx} {bx} {b}
1251 \DeclareFontSeriesChangeRule {ebec}{bx} {bx} {b}
1252 \DeclareFontSeriesChangeRule {ebc}{bx} {bx} {b}
1253 \DeclareFontSeriesChangeRule {ebsc}{bx} {bx} {b}
1254 \DeclareFontSeriesChangeRule {eb}{bx} {bx} {b}
1255 \DeclareFontSeriesChangeRule {ebsx}{bx} {bx} {b}
1256 \DeclareFontSeriesChangeRule {ebx}{bx} {bx} {b}
1257 \DeclareFontSeriesChangeRule {ebex}{bx} {bx} {b}
1258 \DeclareFontSeriesChangeRule {ebux}{bx} {bx} {b}

1259 \DeclareFontSeriesChangeRule {ubuc}{bx} {bx} {b}
1260 \DeclareFontSeriesChangeRule {ubec}{bx} {bx} {b}
1261 \DeclareFontSeriesChangeRule {ubc}{bx} {bx} {b}
1262 \DeclareFontSeriesChangeRule {ubsc}{bx} {bx} {b}
1263 \DeclareFontSeriesChangeRule {ub}{bx} {bx} {b}
1264 \DeclareFontSeriesChangeRule {ubsx}{bx} {bx} {b}
1265 \DeclareFontSeriesChangeRule {ubx}{bx} {bx} {b}
1266 \DeclareFontSeriesChangeRule {ubex}{bx} {bx} {b}
1267 \DeclareFontSeriesChangeRule {ubux}{bx} {bx} {b}

```

Here are the special rules for  $m$ ?. We offer  $m$  as alternative result series for all entries where this is not already the result series, because otherwise, if the result series does not exist,  $m$ ? would be tried as the series value, which cannot work. (Of course, this does not help if the  $m$  series does not exist either, but this should only affect very few fonts.)

```

1268 \DeclareFontSeriesChangeRule {uluc}{m?} {uc} {m}
1269 \DeclareFontSeriesChangeRule {ulec}{m?} {ec} {m}
1270 \DeclareFontSeriesChangeRule {ulc}{m?} {c} {m}
1271 \DeclareFontSeriesChangeRule {ulsc}{m?} {sc} {m}
1272 \DeclareFontSeriesChangeRule {ul}{m?} {m} {}
1273 \DeclareFontSeriesChangeRule {ulsx}{m?} {sx} {m}
1274 \DeclareFontSeriesChangeRule {ulx}{m?} {x} {m}
1275 \DeclareFontSeriesChangeRule {ulex}{m?} {ex} {m}
1276 \DeclareFontSeriesChangeRule {ulux}{m?} {ux} {m}

1277 \DeclareFontSeriesChangeRule {eluc}{m?} {uc} {m}
1278 \DeclareFontSeriesChangeRule {elec}{m?} {ec} {m}

```

```

1279 \DeclareFontSeriesChangeRule {elc}{m?} {c} {m}
1280 \DeclareFontSeriesChangeRule {elsc}{m?} {sc} {m}
1281 \DeclareFontSeriesChangeRule {el}{m?} {m} {}
1282 \DeclareFontSeriesChangeRule {elsx}{m?} {sx} {m}
1283 \DeclareFontSeriesChangeRule {elx}{m?} {x} {m}
1284 \DeclareFontSeriesChangeRule {elex}{m?} {ex} {m}
1285 \DeclareFontSeriesChangeRule {elux}{m?} {ux} {m}

1286 \DeclareFontSeriesChangeRule {luc}{m?} {uc} {m}
1287 \DeclareFontSeriesChangeRule {lec}{m?} {ec} {m}
1288 \DeclareFontSeriesChangeRule {lc}{m?} {c} {m}
1289 \DeclareFontSeriesChangeRule {lsc}{m?} {sc} {m}
1290 \DeclareFontSeriesChangeRule {l}{m?} {m} {}
1291 \DeclareFontSeriesChangeRule {lsx}{m?} {sx} {m}
1292 \DeclareFontSeriesChangeRule {lx}{m?} {x} {m}
1293 \DeclareFontSeriesChangeRule {lex}{m?} {ex} {m}
1294 \DeclareFontSeriesChangeRule {lux}{m?} {ux} {m}

1295 \DeclareFontSeriesChangeRule {sluc}{m?} {uc} {m}
1296 \DeclareFontSeriesChangeRule {slec}{m?} {ec} {m}
1297 \DeclareFontSeriesChangeRule {slc}{m?} {c} {m}
1298 \DeclareFontSeriesChangeRule {slsc}{m?} {sc} {m}
1299 \DeclareFontSeriesChangeRule {sl}{m?} {m} {}
1300 \DeclareFontSeriesChangeRule {slsx}{m?} {sx} {m}
1301 \DeclareFontSeriesChangeRule {slx}{m?} {x} {m}
1302 \DeclareFontSeriesChangeRule {slex}{m?} {ex} {m}
1303 \DeclareFontSeriesChangeRule {slux}{m?} {ux} {m}

1304 \DeclareFontSeriesChangeRule {uc}{m?} {uc} {m}
1305 \DeclareFontSeriesChangeRule {ec}{m?} {ec} {m}
1306 \DeclareFontSeriesChangeRule {c}{m?} {c} {m}
1307 \DeclareFontSeriesChangeRule {sc}{m?} {sc} {m}
1308 \DeclareFontSeriesChangeRule {m}{m?} {m} {}
1309 \DeclareFontSeriesChangeRule {sx}{m?} {sx} {m}
1310 \DeclareFontSeriesChangeRule {x}{m?} {x} {m}
1311 \DeclareFontSeriesChangeRule {ex}{m?} {ex} {m}
1312 \DeclareFontSeriesChangeRule {ux}{m?} {ux} {m}

1313 \DeclareFontSeriesChangeRule {sbuc}{m?} {uc} {m}
1314 \DeclareFontSeriesChangeRule {sbec}{m?} {ec} {m}
1315 \DeclareFontSeriesChangeRule {sbc}{m?} {c} {m}
1316 \DeclareFontSeriesChangeRule {sbsc}{m?} {sc} {m}
1317 \DeclareFontSeriesChangeRule {sb}{m?} {m} {}
1318 \DeclareFontSeriesChangeRule {sbsx}{m?} {sx} {m}
1319 \DeclareFontSeriesChangeRule {sbx}{m?} {x} {m}
1320 \DeclareFontSeriesChangeRule {sbex}{m?} {ex} {m}
1321 \DeclareFontSeriesChangeRule {sbux}{m?} {ux} {m}

1322 \DeclareFontSeriesChangeRule {buc}{m?} {uc} {m}
1323 \DeclareFontSeriesChangeRule {bec}{m?} {ec} {m}
1324 \DeclareFontSeriesChangeRule {bc}{m?} {c} {m}
1325 \DeclareFontSeriesChangeRule {bsc}{m?} {sc} {m}
1326 \DeclareFontSeriesChangeRule {b}{m?} {m} {}
1327 \DeclareFontSeriesChangeRule {bsx}{m?} {sx} {m}
1328 \DeclareFontSeriesChangeRule {bx}{m?} {x} {m}
1329 \DeclareFontSeriesChangeRule {bex}{m?} {ex} {m}
1330 \DeclareFontSeriesChangeRule {bux}{m?} {ux} {m}

```

```

1331 \DeclareFontSeriesChangeRule {ebuc}{m?} {uc} {m}
1332 \DeclareFontSeriesChangeRule {ebec}{m?} {ec} {m}
1333 \DeclareFontSeriesChangeRule {ebc}{m?} {c} {m}
1334 \DeclareFontSeriesChangeRule {ebsc}{m?} {sc} {m}
1335 \DeclareFontSeriesChangeRule {eb}{m?} {m} {}
1336 \DeclareFontSeriesChangeRule {ebsx}{m?} {sx} {m}
1337 \DeclareFontSeriesChangeRule {ebx}{m?} {x} {m}
1338 \DeclareFontSeriesChangeRule {ebex}{m?} {ex} {m}
1339 \DeclareFontSeriesChangeRule {ebux}{m?} {ux} {m}

1340 \DeclareFontSeriesChangeRule {ubuc}{m?} {uc} {m}
1341 \DeclareFontSeriesChangeRule {ubec}{m?} {ec} {m}
1342 \DeclareFontSeriesChangeRule {ubc}{m?} {c} {m}
1343 \DeclareFontSeriesChangeRule {ubsc}{m?} {sc} {m}
1344 \DeclareFontSeriesChangeRule {ub}{m?} {m} {}
1345 \DeclareFontSeriesChangeRule {ubsx}{m?} {sx} {m}
1346 \DeclareFontSeriesChangeRule {ubx}{m?} {x} {m}
1347 \DeclareFontSeriesChangeRule {ubex}{m?} {ex} {m}
1348 \DeclareFontSeriesChangeRule {ubux}{m?} {ux} {m}

```

And here are the special rules for ?m. Again, we offer m as alternative result series for all entries where this is not already the result series.

```

1349 \DeclareFontSeriesChangeRule {uluc}{?m} {ul} {m}
1350 \DeclareFontSeriesChangeRule {ulec}{?m} {ul} {m}
1351 \DeclareFontSeriesChangeRule {ulc}{?m} {ul} {m}
1352 \DeclareFontSeriesChangeRule {ulsc}{?m} {ul} {m}
1353 \DeclareFontSeriesChangeRule {ul}{?m} {ul} {m}
1354 \DeclareFontSeriesChangeRule {ulsx}{?m} {ul} {m}
1355 \DeclareFontSeriesChangeRule {ulx}{?m} {ul} {m}
1356 \DeclareFontSeriesChangeRule {ulex}{?m} {ul} {m}
1357 \DeclareFontSeriesChangeRule {ulux}{?m} {ul} {m}

1358 \DeclareFontSeriesChangeRule {eluc}{?m} {el} {m}
1359 \DeclareFontSeriesChangeRule {elec}{?m} {el} {m}
1360 \DeclareFontSeriesChangeRule {elc}{?m} {el} {m}
1361 \DeclareFontSeriesChangeRule {elsc}{?m} {el} {m}
1362 \DeclareFontSeriesChangeRule {el}{?m} {el} {m}
1363 \DeclareFontSeriesChangeRule {elsx}{?m} {el} {m}
1364 \DeclareFontSeriesChangeRule {elx}{?m} {el} {m}
1365 \DeclareFontSeriesChangeRule {ellex}{?m} {el} {m}
1366 \DeclareFontSeriesChangeRule {elux}{?m} {el} {m}

1367 \DeclareFontSeriesChangeRule {luc}{?m} {l} {m}
1368 \DeclareFontSeriesChangeRule {lec}{?m} {l} {m}
1369 \DeclareFontSeriesChangeRule {lc}{?m} {l} {m}
1370 \DeclareFontSeriesChangeRule {lsc}{?m} {l} {m}
1371 \DeclareFontSeriesChangeRule {l}{?m} {l} {m}
1372 \DeclareFontSeriesChangeRule {lsx}{?m} {l} {m}
1373 \DeclareFontSeriesChangeRule {lx}{?m} {l} {m}
1374 \DeclareFontSeriesChangeRule {lex}{?m} {l} {m}
1375 \DeclareFontSeriesChangeRule {lux}{?m} {l} {m}

1376 \DeclareFontSeriesChangeRule {sluc}{?m} {sl} {m}
1377 \DeclareFontSeriesChangeRule {slec}{?m} {sl} {m}
1378 \DeclareFontSeriesChangeRule {slc}{?m} {sl} {m}
1379 \DeclareFontSeriesChangeRule {slsc}{?m} {sl} {m}
1380 \DeclareFontSeriesChangeRule {sl}{?m} {sl} {m}

```

```

1381 \DeclareFontSeriesChangeRule {slsx}{?m} {sl} {m}
1382 \DeclareFontSeriesChangeRule {slx}{?m} {sl} {m}
1383 \DeclareFontSeriesChangeRule {slex}{?m} {sl} {m}
1384 \DeclareFontSeriesChangeRule {slux}{?m} {sl} {m}

1385 \DeclareFontSeriesChangeRule {uc}{?m} {m} {}
1386 \DeclareFontSeriesChangeRule {ec}{?m} {m} {}
1387 \DeclareFontSeriesChangeRule {c}{?m} {m} {}
1388 \DeclareFontSeriesChangeRule {sc}{?m} {m} {}
1389 \DeclareFontSeriesChangeRule {m}{?m} {m} {}
1390 \DeclareFontSeriesChangeRule {sx}{?m} {m} {}
1391 \DeclareFontSeriesChangeRule {x}{?m} {m} {}
1392 \DeclareFontSeriesChangeRule {ex}{?m} {m} {}
1393 \DeclareFontSeriesChangeRule {ux}{?m} {m} {}

1394 \DeclareFontSeriesChangeRule {sbuc}{?m} {sb} {m}
1395 \DeclareFontSeriesChangeRule {sbec}{?m} {sb} {m}
1396 \DeclareFontSeriesChangeRule {sbc}{?m} {sb} {m}
1397 \DeclareFontSeriesChangeRule {sbsc}{?m} {sb} {m}
1398 \DeclareFontSeriesChangeRule {sb}{?m} {sb} {m}
1399 \DeclareFontSeriesChangeRule {sbsx}{?m} {sb} {m}
1400 \DeclareFontSeriesChangeRule {sbx}{?m} {sb} {m}
1401 \DeclareFontSeriesChangeRule {sbex}{?m} {sb} {m}
1402 \DeclareFontSeriesChangeRule {sbux}{?m} {sb} {m}

1403 \DeclareFontSeriesChangeRule {buc}{?m} {b} {m}
1404 \DeclareFontSeriesChangeRule {bec}{?m} {b} {m}
1405 \DeclareFontSeriesChangeRule {bc}{?m} {b} {m}
1406 \DeclareFontSeriesChangeRule {bsc}{?m} {b} {m}
1407 \DeclareFontSeriesChangeRule {b}{?m} {b} {m}
1408 \DeclareFontSeriesChangeRule {bsx}{?m} {b} {m}
1409 \DeclareFontSeriesChangeRule {bx}{?m} {b} {m}
1410 \DeclareFontSeriesChangeRule {bex}{?m} {b} {m}
1411 \DeclareFontSeriesChangeRule {bux}{?m} {b} {m}

1412 \DeclareFontSeriesChangeRule {ebuc}{?m} {eb} {m}
1413 \DeclareFontSeriesChangeRule {ebec}{?m} {eb} {m}
1414 \DeclareFontSeriesChangeRule {ebc}{?m} {eb} {m}
1415 \DeclareFontSeriesChangeRule {ebsc}{?m} {eb} {m}
1416 \DeclareFontSeriesChangeRule {eb}{?m} {eb} {m}
1417 \DeclareFontSeriesChangeRule {ebsx}{?m} {eb} {m}
1418 \DeclareFontSeriesChangeRule {ebx}{?m} {eb} {m}
1419 \DeclareFontSeriesChangeRule {ebex}{?m} {eb} {m}
1420 \DeclareFontSeriesChangeRule {ebux}{?m} {eb} {m}

1421 \DeclareFontSeriesChangeRule {ubuc}{?m} {ub} {m}
1422 \DeclareFontSeriesChangeRule {ubec}{?m} {ub} {m}
1423 \DeclareFontSeriesChangeRule {ubc}{?m} {ub} {m}
1424 \DeclareFontSeriesChangeRule {ubsc}{?m} {ub} {m}
1425 \DeclareFontSeriesChangeRule {ub}{?m} {ub} {m}
1426 \DeclareFontSeriesChangeRule {ubsx}{?m} {ub} {m}
1427 \DeclareFontSeriesChangeRule {ubx}{?m} {ub} {m}
1428 \DeclareFontSeriesChangeRule {ubex}{?m} {ub} {m}
1429 \DeclareFontSeriesChangeRule {ubux}{?m} {ub} {m}

1430 </2ekernel | latexrelease>
1431 <latexrelease>\EndIncludeInRelease

```

Supporting rollback ...

```
1432 <latexrelease>\IncludeInRelease{2020/02/02}%
1433 <latexrelease> \DeclareFontSeriesChangeRule{Series change rules}%
```

The next definition is only needed if somebody rolls forward from a release older than 2020-02-02 but not to the latest version but one before 2025-06-01. Pretty unlikely, but ...

```
1434 <latexrelease>
1435 <latexrelease>\def\DeclareFontSeriesChangeRule#1#2#3#4{%
1436 <latexrelease> \@namedef{series0#10#2}{#{#3}{#4}}
1437 <latexrelease>
```

The huge set of declarations below are those from 2020-02-02 plus all from above that were newly added (but now with empty result and alternative result arguments). To compile this list I sorted both together and then dropped entries appearing twice. This is why the sorting is now different from the one above.

```
1438 <latexrelease>\DeclareFontSeriesChangeRule {bc}{bx} {} {}
1439 <latexrelease>\DeclareFontSeriesChangeRule {bc}{b}{bc}{}
1440 <latexrelease>\DeclareFontSeriesChangeRule {bc}{c}{bc}{}
1441 <latexrelease>\DeclareFontSeriesChangeRule {bc}{eb}{ebc}{}
1442 <latexrelease>\DeclareFontSeriesChangeRule {bc}{ec}{bec} {bc}
1443 <latexrelease>\DeclareFontSeriesChangeRule {bc}{el}{elc}{}
1444 <latexrelease>\DeclareFontSeriesChangeRule {bc}{ex} {} {}
1445 <latexrelease>\DeclareFontSeriesChangeRule {bc}{l}{lc}{}
1446 <latexrelease>\DeclareFontSeriesChangeRule {bc}{sb}{sbc}{}
1447 <latexrelease>\DeclareFontSeriesChangeRule {bc}{sc}{bsc} {bc}
1448 <latexrelease>\DeclareFontSeriesChangeRule {bc}{sl}{slc}{}
1449 <latexrelease>\DeclareFontSeriesChangeRule {bc}{sx} {} {}
1450 <latexrelease>\DeclareFontSeriesChangeRule {bc}{ub}{ubc}{}
1451 <latexrelease>\DeclareFontSeriesChangeRule {bc}{uc} {} {}
1452 <latexrelease>\DeclareFontSeriesChangeRule {bc}{ul}{ulc}{}
1453 <latexrelease>\DeclareFontSeriesChangeRule {bc}{ux} {} {}
1454 <latexrelease>\DeclareFontSeriesChangeRule {bc}{x}{bx}{}
1455 <latexrelease>\DeclareFontSeriesChangeRule {bec}{bx} {} {}
1456 <latexrelease>\DeclareFontSeriesChangeRule {bec}{b} {} {}
1457 <latexrelease>\DeclareFontSeriesChangeRule {bec}{c} {} {}
1458 <latexrelease>\DeclareFontSeriesChangeRule {bec}{eb} {} {}
1459 <latexrelease>\DeclareFontSeriesChangeRule {bec}{ec} {} {}
1460 <latexrelease>\DeclareFontSeriesChangeRule {bec}{el} {} {}
1461 <latexrelease>\DeclareFontSeriesChangeRule {bec}{ex} {} {}
1462 <latexrelease>\DeclareFontSeriesChangeRule {bec}{l} {} {}
1463 <latexrelease>\DeclareFontSeriesChangeRule {bec}{sb} {} {}
1464 <latexrelease>\DeclareFontSeriesChangeRule {bec}{sc} {} {}
1465 <latexrelease>\DeclareFontSeriesChangeRule {bec}{sl} {} {}
1466 <latexrelease>\DeclareFontSeriesChangeRule {bec}{sx} {} {}
1467 <latexrelease>\DeclareFontSeriesChangeRule {bec}{ub} {} {}
1468 <latexrelease>\DeclareFontSeriesChangeRule {bec}{uc} {} {}
1469 <latexrelease>\DeclareFontSeriesChangeRule {bec}{ul} {} {}
1470 <latexrelease>\DeclareFontSeriesChangeRule {bec}{ux} {} {}
1471 <latexrelease>\DeclareFontSeriesChangeRule {bec}{x} {} {}
1472 <latexrelease>\DeclareFontSeriesChangeRule {bex}{?m} {} {}
1473 <latexrelease>\DeclareFontSeriesChangeRule {bex}{bx} {} {}
1474 <latexrelease>\DeclareFontSeriesChangeRule {bex}{b} {} {}
1475 <latexrelease>\DeclareFontSeriesChangeRule {bex}{c} {} {}
```

```

1476 \latexrelease\DeclareFontSeriesChangeRule {bex}{eb} {} {}
1477 \latexrelease\DeclareFontSeriesChangeRule {bex}{ec} {} {}
1478 \latexrelease\DeclareFontSeriesChangeRule {bex}{el} {} {}
1479 \latexrelease\DeclareFontSeriesChangeRule {bex}{ex} {} {}
1480 \latexrelease\DeclareFontSeriesChangeRule {bex}{l} {} {}
1481 \latexrelease\DeclareFontSeriesChangeRule {bex}{m?} {} {}
1482 \latexrelease\DeclareFontSeriesChangeRule {bex}{sb} {} {}
1483 \latexrelease\DeclareFontSeriesChangeRule {bex}{sc} {} {}
1484 \latexrelease\DeclareFontSeriesChangeRule {bex}{sl} {} {}
1485 \latexrelease\DeclareFontSeriesChangeRule {bex}{sx} {} {}
1486 \latexrelease\DeclareFontSeriesChangeRule {bex}{ub} {} {}
1487 \latexrelease\DeclareFontSeriesChangeRule {bex}{uc} {} {}
1488 \latexrelease\DeclareFontSeriesChangeRule {bex}{ul} {} {}
1489 \latexrelease\DeclareFontSeriesChangeRule {bex}{ux} {} {}
1490 \latexrelease\DeclareFontSeriesChangeRule {bex}{x} {} {}
1491 \latexrelease\DeclareFontSeriesChangeRule {bsc}{bx} {} {}
1492 \latexrelease\DeclareFontSeriesChangeRule {bsc}{b} {} {}
1493 \latexrelease\DeclareFontSeriesChangeRule {bsc}{c} {} {}
1494 \latexrelease\DeclareFontSeriesChangeRule {bsc}{eb} {} {}
1495 \latexrelease\DeclareFontSeriesChangeRule {bsc}{ec} {} {}
1496 \latexrelease\DeclareFontSeriesChangeRule {bsc}{el} {} {}
1497 \latexrelease\DeclareFontSeriesChangeRule {bsc}{ex} {} {}
1498 \latexrelease\DeclareFontSeriesChangeRule {bsc}{l} {} {}
1499 \latexrelease\DeclareFontSeriesChangeRule {bsc}{sb} {} {}
1500 \latexrelease\DeclareFontSeriesChangeRule {bsc}{sc} {} {}
1501 \latexrelease\DeclareFontSeriesChangeRule {bsc}{sl} {} {}
1502 \latexrelease\DeclareFontSeriesChangeRule {bsc}{sx} {} {}
1503 \latexrelease\DeclareFontSeriesChangeRule {bsc}{ub} {} {}
1504 \latexrelease\DeclareFontSeriesChangeRule {bsc}{uc} {} {}
1505 \latexrelease\DeclareFontSeriesChangeRule {bsc}{ul} {} {}
1506 \latexrelease\DeclareFontSeriesChangeRule {bsc}{ux} {} {}
1507 \latexrelease\DeclareFontSeriesChangeRule {bsc}{x} {} {}
1508 \latexrelease\DeclareFontSeriesChangeRule {bsx}{?m} {} {}
1509 \latexrelease\DeclareFontSeriesChangeRule {bsx}{bx} {} {}
1510 \latexrelease\DeclareFontSeriesChangeRule {bsx}{b} {} {}
1511 \latexrelease\DeclareFontSeriesChangeRule {bsx}{c} {} {}
1512 \latexrelease\DeclareFontSeriesChangeRule {bsx}{eb} {} {}
1513 \latexrelease\DeclareFontSeriesChangeRule {bsx}{ec} {} {}
1514 \latexrelease\DeclareFontSeriesChangeRule {bsx}{el} {} {}
1515 \latexrelease\DeclareFontSeriesChangeRule {bsx}{ex} {} {}
1516 \latexrelease\DeclareFontSeriesChangeRule {bsx}{l} {} {}
1517 \latexrelease\DeclareFontSeriesChangeRule {bsx}{m?} {} {}
1518 \latexrelease\DeclareFontSeriesChangeRule {bsx}{sb} {} {}
1519 \latexrelease\DeclareFontSeriesChangeRule {bsx}{sc} {} {}
1520 \latexrelease\DeclareFontSeriesChangeRule {bsx}{sl} {} {}
1521 \latexrelease\DeclareFontSeriesChangeRule {bsx}{sx} {} {}
1522 \latexrelease\DeclareFontSeriesChangeRule {bsx}{ub} {} {}
1523 \latexrelease\DeclareFontSeriesChangeRule {bsx}{uc} {} {}
1524 \latexrelease\DeclareFontSeriesChangeRule {bsx}{ul} {} {}
1525 \latexrelease\DeclareFontSeriesChangeRule {bsx}{ux} {} {}
1526 \latexrelease\DeclareFontSeriesChangeRule {bsx}{x} {} {}
1527 \latexrelease\DeclareFontSeriesChangeRule {buc}{?m} {} {}
1528 \latexrelease\DeclareFontSeriesChangeRule {buc}{bx} {} {}
1529 \latexrelease\DeclareFontSeriesChangeRule {buc}{b} {} {}

```

```

1530 \latexrelease\DeclareFontSeriesChangeRule {buc}{c} {} {}
1531 \latexrelease\DeclareFontSeriesChangeRule {buc}{eb} {} {}
1532 \latexrelease\DeclareFontSeriesChangeRule {buc}{ec} {} {}
1533 \latexrelease\DeclareFontSeriesChangeRule {buc}{el} {} {}
1534 \latexrelease\DeclareFontSeriesChangeRule {buc}{ex} {} {}
1535 \latexrelease\DeclareFontSeriesChangeRule {buc}{l} {} {}
1536 \latexrelease\DeclareFontSeriesChangeRule {buc}{m?} {} {}
1537 \latexrelease\DeclareFontSeriesChangeRule {buc}{sb} {} {}
1538 \latexrelease\DeclareFontSeriesChangeRule {buc}{sc} {} {}
1539 \latexrelease\DeclareFontSeriesChangeRule {buc}{sl} {} {}
1540 \latexrelease\DeclareFontSeriesChangeRule {buc}{sx} {} {}
1541 \latexrelease\DeclareFontSeriesChangeRule {buc}{ub} {} {}
1542 \latexrelease\DeclareFontSeriesChangeRule {buc}{uc} {} {}
1543 \latexrelease\DeclareFontSeriesChangeRule {buc}{ul} {} {}
1544 \latexrelease\DeclareFontSeriesChangeRule {buc}{ux} {} {}
1545 \latexrelease\DeclareFontSeriesChangeRule {buc}{x} {} {}
1546 \latexrelease\DeclareFontSeriesChangeRule {bux}{?m} {} {}
1547 \latexrelease\DeclareFontSeriesChangeRule {bux}{bx} {} {}
1548 \latexrelease\DeclareFontSeriesChangeRule {bux}{b} {} {}
1549 \latexrelease\DeclareFontSeriesChangeRule {bux}{c} {} {}
1550 \latexrelease\DeclareFontSeriesChangeRule {bux}{eb} {} {}
1551 \latexrelease\DeclareFontSeriesChangeRule {bux}{ec} {} {}
1552 \latexrelease\DeclareFontSeriesChangeRule {bux}{el} {} {}
1553 \latexrelease\DeclareFontSeriesChangeRule {bux}{ex} {} {}
1554 \latexrelease\DeclareFontSeriesChangeRule {bux}{l} {} {}
1555 \latexrelease\DeclareFontSeriesChangeRule {bux}{m?} {} {}
1556 \latexrelease\DeclareFontSeriesChangeRule {bux}{sb} {} {}
1557 \latexrelease\DeclareFontSeriesChangeRule {bux}{sc} {} {}
1558 \latexrelease\DeclareFontSeriesChangeRule {bux}{sl} {} {}
1559 \latexrelease\DeclareFontSeriesChangeRule {bux}{sx} {} {}
1560 \latexrelease\DeclareFontSeriesChangeRule {bux}{ub} {} {}
1561 \latexrelease\DeclareFontSeriesChangeRule {bux}{uc} {} {}
1562 \latexrelease\DeclareFontSeriesChangeRule {bux}{ul} {} {}
1563 \latexrelease\DeclareFontSeriesChangeRule {bux}{ux} {} {}
1564 \latexrelease\DeclareFontSeriesChangeRule {bux}{x} {} {}
1565 \latexrelease\DeclareFontSeriesChangeRule {bx}{bx} {} {}
1566 \latexrelease\DeclareFontSeriesChangeRule {bx}{b}{bx} {} {}
1567 \latexrelease\DeclareFontSeriesChangeRule {bx}{c} {bc} {bx}
1568 \latexrelease\DeclareFontSeriesChangeRule {bx}{eb}{ebx} {} {}
1569 \latexrelease\DeclareFontSeriesChangeRule {bx}{ec} {bec} {bx}
1570 \latexrelease\DeclareFontSeriesChangeRule {bx}{el}{elx} {} {}
1571 \latexrelease\DeclareFontSeriesChangeRule {bx}{ex} {} {}
1572 \latexrelease\DeclareFontSeriesChangeRule {bx}{l}{lx} {} {}
1573 \latexrelease\DeclareFontSeriesChangeRule {bx}{sb} {sbx} {} {}
1574 \latexrelease\DeclareFontSeriesChangeRule {bx}{sc} {bsc} {bx}
1575 \latexrelease\DeclareFontSeriesChangeRule {bx}{sl}{slx} {} {}
1576 \latexrelease\DeclareFontSeriesChangeRule {bx}{sx} {} {}
1577 \latexrelease\DeclareFontSeriesChangeRule {bx}{ub}{ubx} {} {}
1578 \latexrelease\DeclareFontSeriesChangeRule {bx}{uc} {} {}
1579 \latexrelease\DeclareFontSeriesChangeRule {bx}{ul}{ulx} {} {}
1580 \latexrelease\DeclareFontSeriesChangeRule {bx}{ux} {} {}
1581 \latexrelease\DeclareFontSeriesChangeRule {bx}{x}{bx} {} {}
1582 \latexrelease\DeclareFontSeriesChangeRule {b}{bx} {bx} {b}
1583 \latexrelease\DeclareFontSeriesChangeRule {b}{c} {bc} {b}

```

```

1584 <latexrelease>\DeclareFontSeriesChangeRule {b}{eb} {} {}
1585 <latexrelease>\DeclareFontSeriesChangeRule {b}{ec} {bec} {b}
1586 <latexrelease>\DeclareFontSeriesChangeRule {b}{ex} {} {}
1587 <latexrelease>\DeclareFontSeriesChangeRule {b}{sb} {sb} {b}
1588 <latexrelease>\DeclareFontSeriesChangeRule {b}{sc} {bsc} {b}
1589 <latexrelease>\DeclareFontSeriesChangeRule {b}{sx} {} {}
1590 <latexrelease>\DeclareFontSeriesChangeRule {b}{ub} {} {}
1591 <latexrelease>\DeclareFontSeriesChangeRule {b}{uc} {} {}
1592 <latexrelease>\DeclareFontSeriesChangeRule {b}{ux} {} {}
1593 <latexrelease>\DeclareFontSeriesChangeRule {b}{x} {bx} {b}
1594 <latexrelease>\DeclareFontSeriesChangeRule {c}{bx} {bx} {b}
1595 <latexrelease>\DeclareFontSeriesChangeRule {c}{b}{bc}{b}
1596 <latexrelease>\DeclareFontSeriesChangeRule {c}{eb}{ebc}{b}
1597 <latexrelease>\DeclareFontSeriesChangeRule {c}{ec} {} {}
1598 <latexrelease>\DeclareFontSeriesChangeRule {c}{el}{elc}{b}
1599 <latexrelease>\DeclareFontSeriesChangeRule {c}{l}{lc}{b}
1600 <latexrelease>\DeclareFontSeriesChangeRule {c}{sb}{sbc}{b}
1601 <latexrelease>\DeclareFontSeriesChangeRule {c}{sc} {} {}
1602 <latexrelease>\DeclareFontSeriesChangeRule {c}{sl}{slc}{b}
1603 <latexrelease>\DeclareFontSeriesChangeRule {c}{ub}{ubc}{b}
1604 <latexrelease>\DeclareFontSeriesChangeRule {c}{uc} {} {}
1605 <latexrelease>\DeclareFontSeriesChangeRule {c}{x}{x}{m}
1606 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{bx} {} {}
1607 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{b}{bc}{b}
1608 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{c}{ebc}{b}
1609 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{eb}{ebc}{b}
1610 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{ec}{ebec}{ebc}
1611 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{el}{elc}{b}
1612 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{ex} {} {}
1613 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{l}{lc}{b}
1614 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{sb}{sbc}{b}
1615 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{sc}{ebsc}{ebc}
1616 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{sl}{slc}{b}
1617 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{sx} {} {}
1618 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{ub}{ubc}{b}
1619 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{uc} {} {}
1620 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{ul}{ulc}{b}
1621 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{ux} {} {}
1622 <latexrelease>\DeclareFontSeriesChangeRule {ebc}{x}{ebx}{b}
1623 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{bx} {} {}
1624 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{b} {} {}
1625 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{c} {} {}
1626 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{eb} {} {}
1627 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{ec} {} {}
1628 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{el} {} {}
1629 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{ex} {} {}
1630 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{l} {} {}
1631 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{sb} {} {}
1632 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{sc} {} {}
1633 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{sl} {} {}
1634 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{sx} {} {}
1635 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{ub} {} {}
1636 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{uc} {} {}
1637 <latexrelease>\DeclareFontSeriesChangeRule {ebec}{ul} {} {}

```

```

1638 \latexrelease\DeclareFontSeriesChangeRule {ebec}{ux} {} {}
1639 \latexrelease\DeclareFontSeriesChangeRule {ebec}{x} {} {}
1640 \latexrelease\DeclareFontSeriesChangeRule {ebex}{?m} {} {}
1641 \latexrelease\DeclareFontSeriesChangeRule {ebex}{bx} {} {}
1642 \latexrelease\DeclareFontSeriesChangeRule {ebex}{b} {} {}
1643 \latexrelease\DeclareFontSeriesChangeRule {ebex}{c} {} {}
1644 \latexrelease\DeclareFontSeriesChangeRule {ebex}{eb} {} {}
1645 \latexrelease\DeclareFontSeriesChangeRule {ebex}{ec} {} {}
1646 \latexrelease\DeclareFontSeriesChangeRule {ebex}{el} {} {}
1647 \latexrelease\DeclareFontSeriesChangeRule {ebex}{ex} {} {}
1648 \latexrelease\DeclareFontSeriesChangeRule {ebex}{l} {} {}
1649 \latexrelease\DeclareFontSeriesChangeRule {ebex}{m?} {} {}
1650 \latexrelease\DeclareFontSeriesChangeRule {ebex}{sb} {} {}
1651 \latexrelease\DeclareFontSeriesChangeRule {ebex}{sc} {} {}
1652 \latexrelease\DeclareFontSeriesChangeRule {ebex}{sl} {} {}
1653 \latexrelease\DeclareFontSeriesChangeRule {ebex}{sx} {} {}
1654 \latexrelease\DeclareFontSeriesChangeRule {ebex}{ub} {} {}
1655 \latexrelease\DeclareFontSeriesChangeRule {ebex}{uc} {} {}
1656 \latexrelease\DeclareFontSeriesChangeRule {ebex}{ul} {} {}
1657 \latexrelease\DeclareFontSeriesChangeRule {ebex}{ux} {} {}
1658 \latexrelease\DeclareFontSeriesChangeRule {ebex}{x} {} {}
1659 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{bx} {} {}
1660 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{b} {} {}
1661 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{c} {} {}
1662 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{eb} {} {}
1663 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{ec} {} {}
1664 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{el} {} {}
1665 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{ex} {} {}
1666 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{l} {} {}
1667 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{sb} {} {}
1668 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{sc} {} {}
1669 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{sl} {} {}
1670 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{sx} {} {}
1671 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{ub} {} {}
1672 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{uc} {} {}
1673 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{ul} {} {}
1674 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{ux} {} {}
1675 \latexrelease\DeclareFontSeriesChangeRule {ebsc}{x} {} {}
1676 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{?m} {} {}
1677 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{bx} {} {}
1678 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{b} {} {}
1679 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{c} {} {}
1680 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{eb} {} {}
1681 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{ec} {} {}
1682 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{el} {} {}
1683 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{ex} {} {}
1684 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{l} {} {}
1685 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{m?} {} {}
1686 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{sb} {} {}
1687 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{sc} {} {}
1688 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{sl} {} {}
1689 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{sx} {} {}
1690 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{ub} {} {}
1691 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{uc} {} {}

```

```

1692 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{ul} {} {}
1693 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{ux} {} {}
1694 \latexrelease\DeclareFontSeriesChangeRule {ebsx}{x} {} {}
1695 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{?m} {} {}
1696 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{bx} {} {}
1697 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{b} {} {}
1698 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{c} {} {}
1699 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{eb} {} {}
1700 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{ec} {} {}
1701 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{el} {} {}
1702 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{ex} {} {}
1703 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{l} {} {}
1704 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{m?} {} {}
1705 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{sb} {} {}
1706 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{sc} {} {}
1707 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{sl} {} {}
1708 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{sx} {} {}
1709 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{ub} {} {}
1710 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{uc} {} {}
1711 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{ul} {} {}
1712 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{ux} {} {}
1713 \latexrelease\DeclareFontSeriesChangeRule {ebuc}{x} {} {}
1714 \latexrelease\DeclareFontSeriesChangeRule {ebux}{?m} {} {}
1715 \latexrelease\DeclareFontSeriesChangeRule {ebux}{bx} {} {}
1716 \latexrelease\DeclareFontSeriesChangeRule {ebux}{b} {} {}
1717 \latexrelease\DeclareFontSeriesChangeRule {ebux}{c} {} {}
1718 \latexrelease\DeclareFontSeriesChangeRule {ebux}{eb} {} {}
1719 \latexrelease\DeclareFontSeriesChangeRule {ebux}{ec} {} {}
1720 \latexrelease\DeclareFontSeriesChangeRule {ebux}{el} {} {}
1721 \latexrelease\DeclareFontSeriesChangeRule {ebux}{ex} {} {}
1722 \latexrelease\DeclareFontSeriesChangeRule {ebux}{l} {} {}
1723 \latexrelease\DeclareFontSeriesChangeRule {ebux}{m?} {} {}
1724 \latexrelease\DeclareFontSeriesChangeRule {ebux}{sb} {} {}
1725 \latexrelease\DeclareFontSeriesChangeRule {ebux}{sc} {} {}
1726 \latexrelease\DeclareFontSeriesChangeRule {ebux}{sl} {} {}
1727 \latexrelease\DeclareFontSeriesChangeRule {ebux}{sx} {} {}
1728 \latexrelease\DeclareFontSeriesChangeRule {ebux}{ub} {} {}
1729 \latexrelease\DeclareFontSeriesChangeRule {ebux}{uc} {} {}
1730 \latexrelease\DeclareFontSeriesChangeRule {ebux}{ul} {} {}
1731 \latexrelease\DeclareFontSeriesChangeRule {ebux}{ux} {} {}
1732 \latexrelease\DeclareFontSeriesChangeRule {ebux}{x} {} {}
1733 \latexrelease\DeclareFontSeriesChangeRule {ebx}{bx} {} {}
1734 \latexrelease\DeclareFontSeriesChangeRule {ebx}{b}{bx}{}
1735 \latexrelease\DeclareFontSeriesChangeRule {ebx}{c}{ebc}{}
1736 \latexrelease\DeclareFontSeriesChangeRule {ebx}{eb}{ebx}{}
1737 \latexrelease\DeclareFontSeriesChangeRule {ebx}{ec}{ebec}{}
1738 \latexrelease\DeclareFontSeriesChangeRule {ebx}{el}{elx}{}
1739 \latexrelease\DeclareFontSeriesChangeRule {ebx}{ex} {} {}
1740 \latexrelease\DeclareFontSeriesChangeRule {ebx}{l}{lx}{}
1741 \latexrelease\DeclareFontSeriesChangeRule {ebx}{sb}{sbx}{}
1742 \latexrelease\DeclareFontSeriesChangeRule {ebx}{sc}{ebxc}{}
1743 \latexrelease\DeclareFontSeriesChangeRule {ebx}{sl}{slx}{}
1744 \latexrelease\DeclareFontSeriesChangeRule {ebx}{sx} {} {}
1745 \latexrelease\DeclareFontSeriesChangeRule {ebx}{ub}{ubx}{}

```

```

1746 <latexrelease>\DeclareFontSeriesChangeRule {ebx}{uc} {} {}
1747 <latexrelease>\DeclareFontSeriesChangeRule {ebx}{ul}{ulx}{}
1748 <latexrelease>\DeclareFontSeriesChangeRule {ebx}{ux} {} {}
1749 <latexrelease>\DeclareFontSeriesChangeRule {ebx}{x}{ebx}{}
1750 <latexrelease>\DeclareFontSeriesChangeRule {eb}{bx} {} {}
1751 <latexrelease>\DeclareFontSeriesChangeRule {eb}{c}{ebc}{}
1752 <latexrelease>\DeclareFontSeriesChangeRule {eb}{ec}{ebec}{}
1753 <latexrelease>\DeclareFontSeriesChangeRule {eb}{ex} {} {}
1754 <latexrelease>\DeclareFontSeriesChangeRule {eb}{sb} {} {}
1755 <latexrelease>\DeclareFontSeriesChangeRule {eb}{sc}{ebsc}{}
1756 <latexrelease>\DeclareFontSeriesChangeRule {eb}{sx} {} {}
1757 <latexrelease>\DeclareFontSeriesChangeRule {eb}{ub} {} {}
1758 <latexrelease>\DeclareFontSeriesChangeRule {eb}{uc} {} {}
1759 <latexrelease>\DeclareFontSeriesChangeRule {eb}{ux} {} {}
1760 <latexrelease>\DeclareFontSeriesChangeRule {eb}{x}{ebx}{}
1761 <latexrelease>\DeclareFontSeriesChangeRule {ec}{bx} {bx} {b}
1762 <latexrelease>\DeclareFontSeriesChangeRule {ec}{b}{bec}{}
1763 <latexrelease>\DeclareFontSeriesChangeRule {ec}{eb}{ebec}{}
1764 <latexrelease>\DeclareFontSeriesChangeRule {ec}{el}{elec}{}
1765 <latexrelease>\DeclareFontSeriesChangeRule {ec}{l}{lec}{}
1766 <latexrelease>\DeclareFontSeriesChangeRule {ec}{sb}{sbec}{}
1767 <latexrelease>\DeclareFontSeriesChangeRule {ec}{sl}{slec}{}
1768 <latexrelease>\DeclareFontSeriesChangeRule {ec}{ub}{ubec}{}
1769 <latexrelease>\DeclareFontSeriesChangeRule {ec}{x}{x}{m}
1770 <latexrelease>\DeclareFontSeriesChangeRule {elc}{bx} {} {}
1771 <latexrelease>\DeclareFontSeriesChangeRule {elc}{b}{bc}{}
1772 <latexrelease>\DeclareFontSeriesChangeRule {elc}{c}{elc}{}
1773 <latexrelease>\DeclareFontSeriesChangeRule {elc}{eb}{ebc}{}
1774 <latexrelease>\DeclareFontSeriesChangeRule {elc}{ec}{elec}{}
1775 <latexrelease>\DeclareFontSeriesChangeRule {elc}{el}{elc}{}
1776 <latexrelease>\DeclareFontSeriesChangeRule {elc}{ex} {} {}
1777 <latexrelease>\DeclareFontSeriesChangeRule {elc}{l}{lc}{}
1778 <latexrelease>\DeclareFontSeriesChangeRule {elc}{sb}{sbc}{}
1779 <latexrelease>\DeclareFontSeriesChangeRule {elc}{sc}{elsc}{}
1780 <latexrelease>\DeclareFontSeriesChangeRule {elc}{sl}{slc}{}
1781 <latexrelease>\DeclareFontSeriesChangeRule {elc}{sx} {} {}
1782 <latexrelease>\DeclareFontSeriesChangeRule {elc}{ub}{ubc}{}
1783 <latexrelease>\DeclareFontSeriesChangeRule {elc}{uc} {} {}
1784 <latexrelease>\DeclareFontSeriesChangeRule {elc}{ul}{ulc}{}
1785 <latexrelease>\DeclareFontSeriesChangeRule {elc}{ux} {} {}
1786 <latexrelease>\DeclareFontSeriesChangeRule {elc}{x}{elx}{}
1787 <latexrelease>\DeclareFontSeriesChangeRule {elec}{bx} {} {}
1788 <latexrelease>\DeclareFontSeriesChangeRule {elec}{b} {} {}
1789 <latexrelease>\DeclareFontSeriesChangeRule {elec}{c} {} {}
1790 <latexrelease>\DeclareFontSeriesChangeRule {elec}{eb} {} {}
1791 <latexrelease>\DeclareFontSeriesChangeRule {elec}{ec} {} {}
1792 <latexrelease>\DeclareFontSeriesChangeRule {elec}{el} {} {}
1793 <latexrelease>\DeclareFontSeriesChangeRule {elec}{ex} {} {}
1794 <latexrelease>\DeclareFontSeriesChangeRule {elec}{l} {} {}
1795 <latexrelease>\DeclareFontSeriesChangeRule {elec}{sb} {} {}
1796 <latexrelease>\DeclareFontSeriesChangeRule {elec}{sc} {} {}
1797 <latexrelease>\DeclareFontSeriesChangeRule {elec}{sl} {} {}
1798 <latexrelease>\DeclareFontSeriesChangeRule {elec}{sx} {} {}
1799 <latexrelease>\DeclareFontSeriesChangeRule {elec}{ub} {} {}

```

```

1800 <latexrelease>\DeclareFontSeriesChangeRule {elec}{uc} {} {}
1801 <latexrelease>\DeclareFontSeriesChangeRule {elec}{ul} {} {}
1802 <latexrelease>\DeclareFontSeriesChangeRule {elec}{ux} {} {}
1803 <latexrelease>\DeclareFontSeriesChangeRule {elec}{x} {} {}
1804 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{?m} {} {}
1805 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{bx} {} {}
1806 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{b} {} {}
1807 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{c} {} {}
1808 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{eb} {} {}
1809 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{ec} {} {}
1810 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{el} {} {}
1811 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{ex} {} {}
1812 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{l} {} {}
1813 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{m?} {} {}
1814 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{sb} {} {}
1815 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{sc} {} {}
1816 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{sl} {} {}
1817 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{sx} {} {}
1818 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{ub} {} {}
1819 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{uc} {} {}
1820 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{ul} {} {}
1821 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{ux} {} {}
1822 <latexrelease>\DeclareFontSeriesChangeRule {ellex}{x} {} {}
1823 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{bx} {} {}
1824 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{b} {} {}
1825 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{c} {} {}
1826 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{eb} {} {}
1827 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{ec} {} {}
1828 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{el} {} {}
1829 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{ex} {} {}
1830 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{l} {} {}
1831 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{sb} {} {}
1832 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{sc} {} {}
1833 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{sl} {} {}
1834 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{sx} {} {}
1835 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{ub} {} {}
1836 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{uc} {} {}
1837 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{ul} {} {}
1838 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{ux} {} {}
1839 <latexrelease>\DeclareFontSeriesChangeRule {elsc}{x} {} {}
1840 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{?m} {} {}
1841 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{bx} {} {}
1842 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{b} {} {}
1843 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{c} {} {}
1844 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{eb} {} {}
1845 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{ec} {} {}
1846 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{el} {} {}
1847 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{ex} {} {}
1848 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{l} {} {}
1849 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{m?} {} {}
1850 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{sb} {} {}
1851 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{sc} {} {}
1852 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{sl} {} {}
1853 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{sx} {} {}

```

```

1854 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{ub} {} {}
1855 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{uc} {} {}
1856 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{ul} {} {}
1857 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{ux} {} {}
1858 <latexrelease>\DeclareFontSeriesChangeRule {elsx}{x} {} {}
1859 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{?m} {} {}
1860 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{bx} {} {}
1861 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{b} {} {}
1862 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{c} {} {}
1863 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{eb} {} {}
1864 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{ec} {} {}
1865 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{el} {} {}
1866 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{ex} {} {}
1867 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{l} {} {}
1868 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{m?} {} {}
1869 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{sb} {} {}
1870 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{sc} {} {}
1871 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{sl} {} {}
1872 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{sx} {} {}
1873 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{ub} {} {}
1874 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{uc} {} {}
1875 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{ul} {} {}
1876 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{ux} {} {}
1877 <latexrelease>\DeclareFontSeriesChangeRule {eluc}{x} {} {}
1878 <latexrelease>\DeclareFontSeriesChangeRule {elux}{?m} {} {}
1879 <latexrelease>\DeclareFontSeriesChangeRule {elux}{bx} {} {}
1880 <latexrelease>\DeclareFontSeriesChangeRule {elux}{b} {} {}
1881 <latexrelease>\DeclareFontSeriesChangeRule {elux}{c} {} {}
1882 <latexrelease>\DeclareFontSeriesChangeRule {elux}{eb} {} {}
1883 <latexrelease>\DeclareFontSeriesChangeRule {elux}{ec} {} {}
1884 <latexrelease>\DeclareFontSeriesChangeRule {elux}{el} {} {}
1885 <latexrelease>\DeclareFontSeriesChangeRule {elux}{ex} {} {}
1886 <latexrelease>\DeclareFontSeriesChangeRule {elux}{l} {} {}
1887 <latexrelease>\DeclareFontSeriesChangeRule {elux}{m?} {} {}
1888 <latexrelease>\DeclareFontSeriesChangeRule {elux}{sb} {} {}
1889 <latexrelease>\DeclareFontSeriesChangeRule {elux}{sc} {} {}
1890 <latexrelease>\DeclareFontSeriesChangeRule {elux}{sl} {} {}
1891 <latexrelease>\DeclareFontSeriesChangeRule {elux}{sx} {} {}
1892 <latexrelease>\DeclareFontSeriesChangeRule {elux}{ub} {} {}
1893 <latexrelease>\DeclareFontSeriesChangeRule {elux}{uc} {} {}
1894 <latexrelease>\DeclareFontSeriesChangeRule {elux}{ul} {} {}
1895 <latexrelease>\DeclareFontSeriesChangeRule {elux}{ux} {} {}
1896 <latexrelease>\DeclareFontSeriesChangeRule {elux}{x} {} {}
1897 <latexrelease>\DeclareFontSeriesChangeRule {elx}{bx} {} {}
1898 <latexrelease>\DeclareFontSeriesChangeRule {elx}{b}{bx}{}
1899 <latexrelease>\DeclareFontSeriesChangeRule {elx}{c}{elc}{}
1900 <latexrelease>\DeclareFontSeriesChangeRule {elx}{eb}{ebx}{}
1901 <latexrelease>\DeclareFontSeriesChangeRule {elx}{ec}{elec}{}
1902 <latexrelease>\DeclareFontSeriesChangeRule {elx}{el}{elx}{}
1903 <latexrelease>\DeclareFontSeriesChangeRule {elx}{ex} {} {}
1904 <latexrelease>\DeclareFontSeriesChangeRule {elx}{l}{lx}{}
1905 <latexrelease>\DeclareFontSeriesChangeRule {elx}{sb}{sbx}{}
1906 <latexrelease>\DeclareFontSeriesChangeRule {elx}{sc}{elsc}{}
1907 <latexrelease>\DeclareFontSeriesChangeRule {elx}{sl}{slx}{}

```

```

1908 <latexrelease>\DeclareFontSeriesChangeRule {elx}{sx} {} {}
1909 <latexrelease>\DeclareFontSeriesChangeRule {elx}{ub}{ubx}{}
1910 <latexrelease>\DeclareFontSeriesChangeRule {elx}{uc} {} {}
1911 <latexrelease>\DeclareFontSeriesChangeRule {elx}{ul}{ulx}{}
1912 <latexrelease>\DeclareFontSeriesChangeRule {elx}{ux} {} {}
1913 <latexrelease>\DeclareFontSeriesChangeRule {elx}{x}{elx}{}
1914 <latexrelease>\DeclareFontSeriesChangeRule {el}{bx} {} {}
1915 <latexrelease>\DeclareFontSeriesChangeRule {el}{c}{elc}{}
1916 <latexrelease>\DeclareFontSeriesChangeRule {el}{eb} {} {}
1917 <latexrelease>\DeclareFontSeriesChangeRule {el}{ec}{elec}{}
1918 <latexrelease>\DeclareFontSeriesChangeRule {el}{ex} {} {}
1919 <latexrelease>\DeclareFontSeriesChangeRule {el}{sb} {} {}
1920 <latexrelease>\DeclareFontSeriesChangeRule {el}{sc}{elsc}{}
1921 <latexrelease>\DeclareFontSeriesChangeRule {el}{sx} {} {}
1922 <latexrelease>\DeclareFontSeriesChangeRule {el}{ub} {} {}
1923 <latexrelease>\DeclareFontSeriesChangeRule {el}{uc} {} {}
1924 <latexrelease>\DeclareFontSeriesChangeRule {el}{ux} {} {}
1925 <latexrelease>\DeclareFontSeriesChangeRule {el}{x}{elx}{}
1926 <latexrelease>\DeclareFontSeriesChangeRule {ex}{?m} {} {}
1927 <latexrelease>\DeclareFontSeriesChangeRule {ex}{bx} {} {}
1928 <latexrelease>\DeclareFontSeriesChangeRule {ex}{b} {} {}
1929 <latexrelease>\DeclareFontSeriesChangeRule {ex}{eb} {} {}
1930 <latexrelease>\DeclareFontSeriesChangeRule {ex}{el} {} {}
1931 <latexrelease>\DeclareFontSeriesChangeRule {ex}{l} {} {}
1932 <latexrelease>\DeclareFontSeriesChangeRule {ex}{m?} {} {}
1933 <latexrelease>\DeclareFontSeriesChangeRule {ex}{sb} {} {}
1934 <latexrelease>\DeclareFontSeriesChangeRule {ex}{sl} {} {}
1935 <latexrelease>\DeclareFontSeriesChangeRule {ex}{ub} {} {}
1936 <latexrelease>\DeclareFontSeriesChangeRule {ex}{ul} {} {}
1937 <latexrelease>\DeclareFontSeriesChangeRule {lc}{bx} {} {}
1938 <latexrelease>\DeclareFontSeriesChangeRule {lc}{b}{bc}{}
1939 <latexrelease>\DeclareFontSeriesChangeRule {lc}{c}{lc}{}
1940 <latexrelease>\DeclareFontSeriesChangeRule {lc}{eb}{ebc}{}
1941 <latexrelease>\DeclareFontSeriesChangeRule {lc}{ec}{lec}{}
1942 <latexrelease>\DeclareFontSeriesChangeRule {lc}{el}{elc}{}
1943 <latexrelease>\DeclareFontSeriesChangeRule {lc}{ex} {} {}
1944 <latexrelease>\DeclareFontSeriesChangeRule {lc}{l}{lc}{}
1945 <latexrelease>\DeclareFontSeriesChangeRule {lc}{sb}{sbc}{}
1946 <latexrelease>\DeclareFontSeriesChangeRule {lc}{sc}{lsc}{}
1947 <latexrelease>\DeclareFontSeriesChangeRule {lc}{sl}{slc}{}
1948 <latexrelease>\DeclareFontSeriesChangeRule {lc}{sx} {} {}
1949 <latexrelease>\DeclareFontSeriesChangeRule {lc}{ub}{ubc}{}
1950 <latexrelease>\DeclareFontSeriesChangeRule {lc}{uc} {} {}
1951 <latexrelease>\DeclareFontSeriesChangeRule {lc}{ul}{ulc}{}
1952 <latexrelease>\DeclareFontSeriesChangeRule {lc}{ux} {} {}
1953 <latexrelease>\DeclareFontSeriesChangeRule {lc}{x}{lx}{}
1954 <latexrelease>\DeclareFontSeriesChangeRule {lec}{bx} {} {}
1955 <latexrelease>\DeclareFontSeriesChangeRule {lec}{b} {} {}
1956 <latexrelease>\DeclareFontSeriesChangeRule {lec}{c} {} {}
1957 <latexrelease>\DeclareFontSeriesChangeRule {lec}{eb} {} {}
1958 <latexrelease>\DeclareFontSeriesChangeRule {lec}{ec} {} {}
1959 <latexrelease>\DeclareFontSeriesChangeRule {lec}{el} {} {}
1960 <latexrelease>\DeclareFontSeriesChangeRule {lec}{ex} {} {}
1961 <latexrelease>\DeclareFontSeriesChangeRule {lec}{l} {} {}

```

```

1962 <latexrelease>\DeclareFontSeriesChangeRule {lec}{sb} {} {}
1963 <latexrelease>\DeclareFontSeriesChangeRule {lec}{sc} {} {}
1964 <latexrelease>\DeclareFontSeriesChangeRule {lec}{sl} {} {}
1965 <latexrelease>\DeclareFontSeriesChangeRule {lec}{sx} {} {}
1966 <latexrelease>\DeclareFontSeriesChangeRule {lec}{ub} {} {}
1967 <latexrelease>\DeclareFontSeriesChangeRule {lec}{uc} {} {}
1968 <latexrelease>\DeclareFontSeriesChangeRule {lec}{ul} {} {}
1969 <latexrelease>\DeclareFontSeriesChangeRule {lec}{ux} {} {}
1970 <latexrelease>\DeclareFontSeriesChangeRule {lec}{x} {} {}
1971 <latexrelease>\DeclareFontSeriesChangeRule {lex}{?m} {} {}
1972 <latexrelease>\DeclareFontSeriesChangeRule {lex}{bx} {} {}
1973 <latexrelease>\DeclareFontSeriesChangeRule {lex}{b} {} {}
1974 <latexrelease>\DeclareFontSeriesChangeRule {lex}{c} {} {}
1975 <latexrelease>\DeclareFontSeriesChangeRule {lex}{eb} {} {}
1976 <latexrelease>\DeclareFontSeriesChangeRule {lex}{ec} {} {}
1977 <latexrelease>\DeclareFontSeriesChangeRule {lex}{el} {} {}
1978 <latexrelease>\DeclareFontSeriesChangeRule {lex}{ex} {} {}
1979 <latexrelease>\DeclareFontSeriesChangeRule {lex}{l} {} {}
1980 <latexrelease>\DeclareFontSeriesChangeRule {lex}{m?} {} {}
1981 <latexrelease>\DeclareFontSeriesChangeRule {lex}{sb} {} {}
1982 <latexrelease>\DeclareFontSeriesChangeRule {lex}{sc} {} {}
1983 <latexrelease>\DeclareFontSeriesChangeRule {lex}{sl} {} {}
1984 <latexrelease>\DeclareFontSeriesChangeRule {lex}{sx} {} {}
1985 <latexrelease>\DeclareFontSeriesChangeRule {lex}{ub} {} {}
1986 <latexrelease>\DeclareFontSeriesChangeRule {lex}{uc} {} {}
1987 <latexrelease>\DeclareFontSeriesChangeRule {lex}{ul} {} {}
1988 <latexrelease>\DeclareFontSeriesChangeRule {lex}{ux} {} {}
1989 <latexrelease>\DeclareFontSeriesChangeRule {lex}{x} {} {}
1990 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{bx} {} {}
1991 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{b} {} {}
1992 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{c} {} {}
1993 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{eb} {} {}
1994 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{ec} {} {}
1995 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{el} {} {}
1996 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{ex} {} {}
1997 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{l} {} {}
1998 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{sb} {} {}
1999 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{sc} {} {}
2000 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{sl} {} {}
2001 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{sx} {} {}
2002 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{ub} {} {}
2003 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{uc} {} {}
2004 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{ul} {} {}
2005 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{ux} {} {}
2006 <latexrelease>\DeclareFontSeriesChangeRule {lsc}{x} {} {}
2007 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{?m} {} {}
2008 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{bx} {} {}
2009 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{b} {} {}
2010 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{c} {} {}
2011 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{eb} {} {}
2012 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{ec} {} {}
2013 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{el} {} {}
2014 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{ex} {} {}
2015 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{l} {} {}

```

```

2016 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{m?} {} {}
2017 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{sb} {} {}
2018 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{sc} {} {}
2019 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{sl} {} {}
2020 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{sx} {} {}
2021 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{ub} {} {}
2022 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{uc} {} {}
2023 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{ul} {} {}
2024 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{ux} {} {}
2025 <latexrelease>\DeclareFontSeriesChangeRule {lsx}{x} {} {}
2026 <latexrelease>\DeclareFontSeriesChangeRule {luc}{?m} {} {}
2027 <latexrelease>\DeclareFontSeriesChangeRule {luc}{bx} {} {}
2028 <latexrelease>\DeclareFontSeriesChangeRule {luc}{b} {} {}
2029 <latexrelease>\DeclareFontSeriesChangeRule {luc}{c} {} {}
2030 <latexrelease>\DeclareFontSeriesChangeRule {luc}{eb} {} {}
2031 <latexrelease>\DeclareFontSeriesChangeRule {luc}{ec} {} {}
2032 <latexrelease>\DeclareFontSeriesChangeRule {luc}{el} {} {}
2033 <latexrelease>\DeclareFontSeriesChangeRule {luc}{ex} {} {}
2034 <latexrelease>\DeclareFontSeriesChangeRule {luc}{l} {} {}
2035 <latexrelease>\DeclareFontSeriesChangeRule {luc}{m?} {} {}
2036 <latexrelease>\DeclareFontSeriesChangeRule {luc}{sb} {} {}
2037 <latexrelease>\DeclareFontSeriesChangeRule {luc}{sc} {} {}
2038 <latexrelease>\DeclareFontSeriesChangeRule {luc}{sl} {} {}
2039 <latexrelease>\DeclareFontSeriesChangeRule {luc}{sx} {} {}
2040 <latexrelease>\DeclareFontSeriesChangeRule {luc}{ub} {} {}
2041 <latexrelease>\DeclareFontSeriesChangeRule {luc}{uc} {} {}
2042 <latexrelease>\DeclareFontSeriesChangeRule {luc}{ul} {} {}
2043 <latexrelease>\DeclareFontSeriesChangeRule {luc}{ux} {} {}
2044 <latexrelease>\DeclareFontSeriesChangeRule {luc}{x} {} {}
2045 <latexrelease>\DeclareFontSeriesChangeRule {lux}{?m} {} {}
2046 <latexrelease>\DeclareFontSeriesChangeRule {lux}{bx} {} {}
2047 <latexrelease>\DeclareFontSeriesChangeRule {lux}{b} {} {}
2048 <latexrelease>\DeclareFontSeriesChangeRule {lux}{c} {} {}
2049 <latexrelease>\DeclareFontSeriesChangeRule {lux}{eb} {} {}
2050 <latexrelease>\DeclareFontSeriesChangeRule {lux}{ec} {} {}
2051 <latexrelease>\DeclareFontSeriesChangeRule {lux}{el} {} {}
2052 <latexrelease>\DeclareFontSeriesChangeRule {lux}{ex} {} {}
2053 <latexrelease>\DeclareFontSeriesChangeRule {lux}{l} {} {}
2054 <latexrelease>\DeclareFontSeriesChangeRule {lux}{m?} {} {}
2055 <latexrelease>\DeclareFontSeriesChangeRule {lux}{sb} {} {}
2056 <latexrelease>\DeclareFontSeriesChangeRule {lux}{sc} {} {}
2057 <latexrelease>\DeclareFontSeriesChangeRule {lux}{sl} {} {}
2058 <latexrelease>\DeclareFontSeriesChangeRule {lux}{sx} {} {}
2059 <latexrelease>\DeclareFontSeriesChangeRule {lux}{ub} {} {}
2060 <latexrelease>\DeclareFontSeriesChangeRule {lux}{uc} {} {}
2061 <latexrelease>\DeclareFontSeriesChangeRule {lux}{ul} {} {}
2062 <latexrelease>\DeclareFontSeriesChangeRule {lux}{ux} {} {}
2063 <latexrelease>\DeclareFontSeriesChangeRule {lux}{x} {} {}
2064 <latexrelease>\DeclareFontSeriesChangeRule {lx}{bx} {} {}
2065 <latexrelease>\DeclareFontSeriesChangeRule {lx}{b}{bx}{}
2066 <latexrelease>\DeclareFontSeriesChangeRule {lx}{c}{lc}{}
2067 <latexrelease>\DeclareFontSeriesChangeRule {lx}{eb}{ebx}{}
2068 <latexrelease>\DeclareFontSeriesChangeRule {lx}{ec}{lec}{}
2069 <latexrelease>\DeclareFontSeriesChangeRule {lx}{el}{elx}{}

```

```

2070 \latexrelease\DeclareFontSeriesChangeRule {lx}{ex} {} {}
2071 \latexrelease\DeclareFontSeriesChangeRule {lx}{l}{lx}{}
2072 \latexrelease\DeclareFontSeriesChangeRule {lx}{sb}{sbx}{}
2073 \latexrelease\DeclareFontSeriesChangeRule {lx}{sc}{lsc}{}
2074 \latexrelease\DeclareFontSeriesChangeRule {lx}{sl}{slx}{}
2075 \latexrelease\DeclareFontSeriesChangeRule {lx}{sx} {} {}
2076 \latexrelease\DeclareFontSeriesChangeRule {lx}{ub}{ubx}{}
2077 \latexrelease\DeclareFontSeriesChangeRule {lx}{uc} {} {}
2078 \latexrelease\DeclareFontSeriesChangeRule {lx}{ul}{ulx}{}
2079 \latexrelease\DeclareFontSeriesChangeRule {lx}{ux} {} {}
2080 \latexrelease\DeclareFontSeriesChangeRule {lx}{x}{lx}{}
2081 \latexrelease\DeclareFontSeriesChangeRule {l}{b} {b} {bx}
2082 \latexrelease\DeclareFontSeriesChangeRule {l}{c} {lc} {l}
2083 \latexrelease\DeclareFontSeriesChangeRule {l}{eb} {} {}
2084 \latexrelease\DeclareFontSeriesChangeRule {l}{ec} {lec} {l}
2085 \latexrelease\DeclareFontSeriesChangeRule {l}{ex} {} {}
2086 \latexrelease\DeclareFontSeriesChangeRule {l}{sb} {sb} {b}
2087 \latexrelease\DeclareFontSeriesChangeRule {l}{sc} {lsc} {l}
2088 \latexrelease\DeclareFontSeriesChangeRule {l}{sx} {} {}
2089 \latexrelease\DeclareFontSeriesChangeRule {l}{ub} {} {}
2090 \latexrelease\DeclareFontSeriesChangeRule {l}{uc} {} {}
2091 \latexrelease\DeclareFontSeriesChangeRule {l}{ux} {} {}
2092 \latexrelease\DeclareFontSeriesChangeRule {l}{x} {lx} {l}
2093 \latexrelease\DeclareFontSeriesChangeRule {m}{bx} {bx} {b}
2094 \latexrelease\DeclareFontSeriesChangeRule {m}{c} {c} {m}
2095 \latexrelease\DeclareFontSeriesChangeRule {m}{l} {l} {m}
2096 \latexrelease\DeclareFontSeriesChangeRule {m}{sc} {sc} {m}
2097 \latexrelease\DeclareFontSeriesChangeRule {m}{x} {x} {m}
2098 \latexrelease\DeclareFontSeriesChangeRule {sbc}{bx} {} {}
2099 \latexrelease\DeclareFontSeriesChangeRule {sbc}{b}{bc}{}
2100 \latexrelease\DeclareFontSeriesChangeRule {sbc}{c}{sbc}{}
2101 \latexrelease\DeclareFontSeriesChangeRule {sbc}{eb}{ebc}{}
2102 \latexrelease\DeclareFontSeriesChangeRule {sbc}{ec}{sbec}{sbc}
2103 \latexrelease\DeclareFontSeriesChangeRule {sbc}{el}{elc}{}
2104 \latexrelease\DeclareFontSeriesChangeRule {sbc}{ex} {} {}
2105 \latexrelease\DeclareFontSeriesChangeRule {sbc}{l}{lc}{}
2106 \latexrelease\DeclareFontSeriesChangeRule {sbc}{sb}{sbc}{}
2107 \latexrelease\DeclareFontSeriesChangeRule {sbc}{sc}{sbsc}{sbc}
2108 \latexrelease\DeclareFontSeriesChangeRule {sbc}{sl}{slc}{}
2109 \latexrelease\DeclareFontSeriesChangeRule {sbc}{sx} {} {}
2110 \latexrelease\DeclareFontSeriesChangeRule {sbc}{ub}{ubc}{}
2111 \latexrelease\DeclareFontSeriesChangeRule {sbc}{uc} {} {}
2112 \latexrelease\DeclareFontSeriesChangeRule {sbc}{ul}{ulc}{}
2113 \latexrelease\DeclareFontSeriesChangeRule {sbc}{ux} {} {}
2114 \latexrelease\DeclareFontSeriesChangeRule {sbc}{x}{sbx}{}
2115 \latexrelease\DeclareFontSeriesChangeRule {sbec}{bx} {} {}
2116 \latexrelease\DeclareFontSeriesChangeRule {sbec}{b} {} {}
2117 \latexrelease\DeclareFontSeriesChangeRule {sbec}{c} {} {}
2118 \latexrelease\DeclareFontSeriesChangeRule {sbec}{eb} {} {}
2119 \latexrelease\DeclareFontSeriesChangeRule {sbec}{ec} {} {}
2120 \latexrelease\DeclareFontSeriesChangeRule {sbec}{el} {} {}
2121 \latexrelease\DeclareFontSeriesChangeRule {sbec}{ex} {} {}
2122 \latexrelease\DeclareFontSeriesChangeRule {sbec}{l} {} {}
2123 \latexrelease\DeclareFontSeriesChangeRule {sbec}{sb} {} {}

```

2124	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbec}{sc}</code>	<code>{}</code>	<code>{}</code>
2125	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbec}{sl}</code>	<code>{}</code>	<code>{}</code>
2126	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbec}{sx}</code>	<code>{}</code>	<code>{}</code>
2127	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbec}{ub}</code>	<code>{}</code>	<code>{}</code>
2128	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbec}{uc}</code>	<code>{}</code>	<code>{}</code>
2129	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbec}{ul}</code>	<code>{}</code>	<code>{}</code>
2130	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbec}{ux}</code>	<code>{}</code>	<code>{}</code>
2131	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbec}{x}</code>	<code>{}</code>	<code>{}</code>
2132	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{?m}</code>	<code>{}</code>	<code>{}</code>
2133	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{bx}</code>	<code>{}</code>	<code>{}</code>
2134	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{b}</code>	<code>{}</code>	<code>{}</code>
2135	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{c}</code>	<code>{}</code>	<code>{}</code>
2136	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{eb}</code>	<code>{}</code>	<code>{}</code>
2137	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{ec}</code>	<code>{}</code>	<code>{}</code>
2138	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{el}</code>	<code>{}</code>	<code>{}</code>
2139	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{ex}</code>	<code>{}</code>	<code>{}</code>
2140	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{l}</code>	<code>{}</code>	<code>{}</code>
2141	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{m?}</code>	<code>{}</code>	<code>{}</code>
2142	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{sb}</code>	<code>{}</code>	<code>{}</code>
2143	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{sc}</code>	<code>{}</code>	<code>{}</code>
2144	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{sl}</code>	<code>{}</code>	<code>{}</code>
2145	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{sx}</code>	<code>{}</code>	<code>{}</code>
2146	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{ub}</code>	<code>{}</code>	<code>{}</code>
2147	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{uc}</code>	<code>{}</code>	<code>{}</code>
2148	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{ul}</code>	<code>{}</code>	<code>{}</code>
2149	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{ux}</code>	<code>{}</code>	<code>{}</code>
2150	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbex}{x}</code>	<code>{}</code>	<code>{}</code>
2151	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{bx}</code>	<code>{}</code>	<code>{}</code>
2152	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{b}</code>	<code>{}</code>	<code>{}</code>
2153	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{c}</code>	<code>{}</code>	<code>{}</code>
2154	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{eb}</code>	<code>{}</code>	<code>{}</code>
2155	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{ec}</code>	<code>{}</code>	<code>{}</code>
2156	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{el}</code>	<code>{}</code>	<code>{}</code>
2157	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{ex}</code>	<code>{}</code>	<code>{}</code>
2158	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{l}</code>	<code>{}</code>	<code>{}</code>
2159	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{sb}</code>	<code>{}</code>	<code>{}</code>
2160	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{sc}</code>	<code>{}</code>	<code>{}</code>
2161	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{sl}</code>	<code>{}</code>	<code>{}</code>
2162	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{sx}</code>	<code>{}</code>	<code>{}</code>
2163	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{ub}</code>	<code>{}</code>	<code>{}</code>
2164	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{uc}</code>	<code>{}</code>	<code>{}</code>
2165	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{ul}</code>	<code>{}</code>	<code>{}</code>
2166	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{ux}</code>	<code>{}</code>	<code>{}</code>
2167	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsc}{x}</code>	<code>{}</code>	<code>{}</code>
2168	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{?m}</code>	<code>{}</code>	<code>{}</code>
2169	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{bx}</code>	<code>{}</code>	<code>{}</code>
2170	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{b}</code>	<code>{}</code>	<code>{}</code>
2171	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{c}</code>	<code>{}</code>	<code>{}</code>
2172	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{eb}</code>	<code>{}</code>	<code>{}</code>
2173	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{ec}</code>	<code>{}</code>	<code>{}</code>
2174	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{el}</code>	<code>{}</code>	<code>{}</code>
2175	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{ex}</code>	<code>{}</code>	<code>{}</code>
2176	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{l}</code>	<code>{}</code>	<code>{}</code>
2177	<code>\DeclareFontSeriesChangeRule</code>	<code>{sbsx}{m?}</code>	<code>{}</code>	<code>{}</code>

```

2178 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{sb} {} {}
2179 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{sc} {} {}
2180 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{sl} {} {}
2181 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{sx} {} {}
2182 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{ub} {} {}
2183 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{uc} {} {}
2184 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{ul} {} {}
2185 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{ux} {} {}
2186 \latexrelease\DeclareFontSeriesChangeRule {sbsx}{x} {} {}
2187 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{?m} {} {}
2188 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{bx} {} {}
2189 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{b} {} {}
2190 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{c} {} {}
2191 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{eb} {} {}
2192 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{ec} {} {}
2193 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{el} {} {}
2194 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{ex} {} {}
2195 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{l} {} {}
2196 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{m?} {} {}
2197 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{sb} {} {}
2198 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{sc} {} {}
2199 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{sl} {} {}
2200 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{sx} {} {}
2201 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{ub} {} {}
2202 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{uc} {} {}
2203 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{ul} {} {}
2204 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{ux} {} {}
2205 \latexrelease\DeclareFontSeriesChangeRule {sbuc}{x} {} {}
2206 \latexrelease\DeclareFontSeriesChangeRule {sbux}{?m} {} {}
2207 \latexrelease\DeclareFontSeriesChangeRule {sbux}{bx} {} {}
2208 \latexrelease\DeclareFontSeriesChangeRule {sbux}{b} {} {}
2209 \latexrelease\DeclareFontSeriesChangeRule {sbux}{c} {} {}
2210 \latexrelease\DeclareFontSeriesChangeRule {sbux}{eb} {} {}
2211 \latexrelease\DeclareFontSeriesChangeRule {sbux}{ec} {} {}
2212 \latexrelease\DeclareFontSeriesChangeRule {sbux}{el} {} {}
2213 \latexrelease\DeclareFontSeriesChangeRule {sbux}{ex} {} {}
2214 \latexrelease\DeclareFontSeriesChangeRule {sbux}{l} {} {}
2215 \latexrelease\DeclareFontSeriesChangeRule {sbux}{m?} {} {}
2216 \latexrelease\DeclareFontSeriesChangeRule {sbux}{sb} {} {}
2217 \latexrelease\DeclareFontSeriesChangeRule {sbux}{sc} {} {}
2218 \latexrelease\DeclareFontSeriesChangeRule {sbux}{sl} {} {}
2219 \latexrelease\DeclareFontSeriesChangeRule {sbux}{sx} {} {}
2220 \latexrelease\DeclareFontSeriesChangeRule {sbux}{ub} {} {}
2221 \latexrelease\DeclareFontSeriesChangeRule {sbux}{uc} {} {}
2222 \latexrelease\DeclareFontSeriesChangeRule {sbux}{ul} {} {}
2223 \latexrelease\DeclareFontSeriesChangeRule {sbux}{ux} {} {}
2224 \latexrelease\DeclareFontSeriesChangeRule {sbux}{x} {} {}
2225 \latexrelease\DeclareFontSeriesChangeRule {sbx}{bx} {} {}
2226 \latexrelease\DeclareFontSeriesChangeRule {sbx}{b}{bx}{}
2227 \latexrelease\DeclareFontSeriesChangeRule {sbx}{c}{sbc}{}
2228 \latexrelease\DeclareFontSeriesChangeRule {sbx}{eb}{ebx}{}
2229 \latexrelease\DeclareFontSeriesChangeRule {sbx}{ec}{sbec}{}
2230 \latexrelease\DeclareFontSeriesChangeRule {sbx}{el}{elx}{}
2231 \latexrelease\DeclareFontSeriesChangeRule {sbx}{ex} {} {}

```

```

2232 \latexrelease\DeclareFontSeriesChangeRule {sbx}{l}{lx}{ }
2233 \latexrelease\DeclareFontSeriesChangeRule {sbx}{sb}{sbs}{ }
2234 \latexrelease\DeclareFontSeriesChangeRule {sbx}{sc}{sbsc}{ }
2235 \latexrelease\DeclareFontSeriesChangeRule {sbx}{sl}{slx}{ }
2236 \latexrelease\DeclareFontSeriesChangeRule {sbx}{sx}{ } { }
2237 \latexrelease\DeclareFontSeriesChangeRule {sbx}{ub}{ubx}{ }
2238 \latexrelease\DeclareFontSeriesChangeRule {sbx}{uc}{ } { }
2239 \latexrelease\DeclareFontSeriesChangeRule {sbx}{ul}{ulx}{ }
2240 \latexrelease\DeclareFontSeriesChangeRule {sbx}{ux}{ } { }
2241 \latexrelease\DeclareFontSeriesChangeRule {sbx}{x}{sbsx}{ }
2242 \latexrelease\DeclareFontSeriesChangeRule {sb}{bx}{ } { }
2243 \latexrelease\DeclareFontSeriesChangeRule {sb}{c}{sbc}{bc}
2244 \latexrelease\DeclareFontSeriesChangeRule {sb}{eb}{ } { }
2245 \latexrelease\DeclareFontSeriesChangeRule {sb}{ec}{sbec}{sbc}
2246 \latexrelease\DeclareFontSeriesChangeRule {sb}{ex}{ } { }
2247 \latexrelease\DeclareFontSeriesChangeRule {sb}{sc}{sbsc}{sbc}
2248 \latexrelease\DeclareFontSeriesChangeRule {sb}{sx}{ } { }
2249 \latexrelease\DeclareFontSeriesChangeRule {sb}{ub}{ } { }
2250 \latexrelease\DeclareFontSeriesChangeRule {sb}{uc}{ } { }
2251 \latexrelease\DeclareFontSeriesChangeRule {sb}{ux}{ } { }
2252 \latexrelease\DeclareFontSeriesChangeRule {sb}{x}{sbsx}{bx}
2253 \latexrelease\DeclareFontSeriesChangeRule {sc}{bx}{bx}{b}
2254 \latexrelease\DeclareFontSeriesChangeRule {sc}{b}{bsc}{ }
2255 \latexrelease\DeclareFontSeriesChangeRule {sc}{eb}{ebsc}{ }
2256 \latexrelease\DeclareFontSeriesChangeRule {sc}{el}{elsc}{ }
2257 \latexrelease\DeclareFontSeriesChangeRule {sc}{l}{lsc}{ }
2258 \latexrelease\DeclareFontSeriesChangeRule {sc}{sb}{sbsc}{ }
2259 \latexrelease\DeclareFontSeriesChangeRule {sc}{sl}{slsc}{ }
2260 \latexrelease\DeclareFontSeriesChangeRule {sc}{ub}{ubsc}{ }
2261 \latexrelease\DeclareFontSeriesChangeRule {sc}{x}{x}{m}
2262 \latexrelease\DeclareFontSeriesChangeRule {slc}{bx}{ } { }
2263 \latexrelease\DeclareFontSeriesChangeRule {slc}{b}{bc}{ }
2264 \latexrelease\DeclareFontSeriesChangeRule {slc}{c}{slc}{ }
2265 \latexrelease\DeclareFontSeriesChangeRule {slc}{eb}{ebc}{ }
2266 \latexrelease\DeclareFontSeriesChangeRule {slc}{ec}{slec}{ }
2267 \latexrelease\DeclareFontSeriesChangeRule {slc}{el}{elc}{ }
2268 \latexrelease\DeclareFontSeriesChangeRule {slc}{ex}{ } { }
2269 \latexrelease\DeclareFontSeriesChangeRule {slc}{l}{lc}{ }
2270 \latexrelease\DeclareFontSeriesChangeRule {slc}{sb}{sbc}{ }
2271 \latexrelease\DeclareFontSeriesChangeRule {slc}{sc}{slsc}{ }
2272 \latexrelease\DeclareFontSeriesChangeRule {slc}{sl}{slc}{ }
2273 \latexrelease\DeclareFontSeriesChangeRule {slc}{sx}{ } { }
2274 \latexrelease\DeclareFontSeriesChangeRule {slc}{ub}{ubc}{ }
2275 \latexrelease\DeclareFontSeriesChangeRule {slc}{uc}{ } { }
2276 \latexrelease\DeclareFontSeriesChangeRule {slc}{ul}{ulc}{ }
2277 \latexrelease\DeclareFontSeriesChangeRule {slc}{ux}{ } { }
2278 \latexrelease\DeclareFontSeriesChangeRule {slc}{x}{slx}{ }
2279 \latexrelease\DeclareFontSeriesChangeRule {slec}{bx}{ } { }
2280 \latexrelease\DeclareFontSeriesChangeRule {slec}{b}{ } { }
2281 \latexrelease\DeclareFontSeriesChangeRule {slec}{c}{ } { }
2282 \latexrelease\DeclareFontSeriesChangeRule {slec}{eb}{ } { }
2283 \latexrelease\DeclareFontSeriesChangeRule {slec}{ec}{ } { }
2284 \latexrelease\DeclareFontSeriesChangeRule {slec}{el}{ } { }
2285 \latexrelease\DeclareFontSeriesChangeRule {slec}{ex}{ } { }

```

```

2286 \latexrelease\DeclareFontSeriesChangeRule {slec}{l} {} {}
2287 \latexrelease\DeclareFontSeriesChangeRule {slec}{sb} {} {}
2288 \latexrelease\DeclareFontSeriesChangeRule {slec}{sc} {} {}
2289 \latexrelease\DeclareFontSeriesChangeRule {slec}{sl} {} {}
2290 \latexrelease\DeclareFontSeriesChangeRule {slec}{sx} {} {}
2291 \latexrelease\DeclareFontSeriesChangeRule {slec}{ub} {} {}
2292 \latexrelease\DeclareFontSeriesChangeRule {slec}{uc} {} {}
2293 \latexrelease\DeclareFontSeriesChangeRule {slec}{ul} {} {}
2294 \latexrelease\DeclareFontSeriesChangeRule {slec}{ux} {} {}
2295 \latexrelease\DeclareFontSeriesChangeRule {slec}{x} {} {}
2296 \latexrelease\DeclareFontSeriesChangeRule {slex}{?m} {} {}
2297 \latexrelease\DeclareFontSeriesChangeRule {slex}{bx} {} {}
2298 \latexrelease\DeclareFontSeriesChangeRule {slex}{b} {} {}
2299 \latexrelease\DeclareFontSeriesChangeRule {slex}{c} {} {}
2300 \latexrelease\DeclareFontSeriesChangeRule {slex}{eb} {} {}
2301 \latexrelease\DeclareFontSeriesChangeRule {slex}{ec} {} {}
2302 \latexrelease\DeclareFontSeriesChangeRule {slex}{el} {} {}
2303 \latexrelease\DeclareFontSeriesChangeRule {slex}{ex} {} {}
2304 \latexrelease\DeclareFontSeriesChangeRule {slex}{l} {} {}
2305 \latexrelease\DeclareFontSeriesChangeRule {slex}{m?} {} {}
2306 \latexrelease\DeclareFontSeriesChangeRule {slex}{sb} {} {}
2307 \latexrelease\DeclareFontSeriesChangeRule {slex}{sc} {} {}
2308 \latexrelease\DeclareFontSeriesChangeRule {slex}{sl} {} {}
2309 \latexrelease\DeclareFontSeriesChangeRule {slex}{sx} {} {}
2310 \latexrelease\DeclareFontSeriesChangeRule {slex}{ub} {} {}
2311 \latexrelease\DeclareFontSeriesChangeRule {slex}{uc} {} {}
2312 \latexrelease\DeclareFontSeriesChangeRule {slex}{ul} {} {}
2313 \latexrelease\DeclareFontSeriesChangeRule {slex}{ux} {} {}
2314 \latexrelease\DeclareFontSeriesChangeRule {slex}{x} {} {}
2315 \latexrelease\DeclareFontSeriesChangeRule {slsc}{bx} {} {}
2316 \latexrelease\DeclareFontSeriesChangeRule {slsc}{b} {} {}
2317 \latexrelease\DeclareFontSeriesChangeRule {slsc}{c} {} {}
2318 \latexrelease\DeclareFontSeriesChangeRule {slsc}{eb} {} {}
2319 \latexrelease\DeclareFontSeriesChangeRule {slsc}{ec} {} {}
2320 \latexrelease\DeclareFontSeriesChangeRule {slsc}{el} {} {}
2321 \latexrelease\DeclareFontSeriesChangeRule {slsc}{ex} {} {}
2322 \latexrelease\DeclareFontSeriesChangeRule {slsc}{l} {} {}
2323 \latexrelease\DeclareFontSeriesChangeRule {slsc}{sb} {} {}
2324 \latexrelease\DeclareFontSeriesChangeRule {slsc}{sc} {} {}
2325 \latexrelease\DeclareFontSeriesChangeRule {slsc}{sl} {} {}
2326 \latexrelease\DeclareFontSeriesChangeRule {slsc}{sx} {} {}
2327 \latexrelease\DeclareFontSeriesChangeRule {slsc}{ub} {} {}
2328 \latexrelease\DeclareFontSeriesChangeRule {slsc}{uc} {} {}
2329 \latexrelease\DeclareFontSeriesChangeRule {slsc}{ul} {} {}
2330 \latexrelease\DeclareFontSeriesChangeRule {slsc}{ux} {} {}
2331 \latexrelease\DeclareFontSeriesChangeRule {slsc}{x} {} {}
2332 \latexrelease\DeclareFontSeriesChangeRule {slsx}{?m} {} {}
2333 \latexrelease\DeclareFontSeriesChangeRule {slsx}{bx} {} {}
2334 \latexrelease\DeclareFontSeriesChangeRule {slsx}{b} {} {}
2335 \latexrelease\DeclareFontSeriesChangeRule {slsx}{c} {} {}
2336 \latexrelease\DeclareFontSeriesChangeRule {slsx}{eb} {} {}
2337 \latexrelease\DeclareFontSeriesChangeRule {slsx}{ec} {} {}
2338 \latexrelease\DeclareFontSeriesChangeRule {slsx}{el} {} {}
2339 \latexrelease\DeclareFontSeriesChangeRule {slsx}{ex} {} {}

```

```

2340 \latexrelease\DeclareFontSeriesChangeRule {slsx}{l} {} {}
2341 \latexrelease\DeclareFontSeriesChangeRule {slsx}{m?} {} {}
2342 \latexrelease\DeclareFontSeriesChangeRule {slsx}{sb} {} {}
2343 \latexrelease\DeclareFontSeriesChangeRule {slsx}{sc} {} {}
2344 \latexrelease\DeclareFontSeriesChangeRule {slsx}{sl} {} {}
2345 \latexrelease\DeclareFontSeriesChangeRule {slsx}{sx} {} {}
2346 \latexrelease\DeclareFontSeriesChangeRule {slsx}{ub} {} {}
2347 \latexrelease\DeclareFontSeriesChangeRule {slsx}{uc} {} {}
2348 \latexrelease\DeclareFontSeriesChangeRule {slsx}{ul} {} {}
2349 \latexrelease\DeclareFontSeriesChangeRule {slsx}{ux} {} {}
2350 \latexrelease\DeclareFontSeriesChangeRule {slsx}{x} {} {}
2351 \latexrelease\DeclareFontSeriesChangeRule {sluc}{?m} {} {}
2352 \latexrelease\DeclareFontSeriesChangeRule {sluc}{bx} {} {}
2353 \latexrelease\DeclareFontSeriesChangeRule {sluc}{b} {} {}
2354 \latexrelease\DeclareFontSeriesChangeRule {sluc}{c} {} {}
2355 \latexrelease\DeclareFontSeriesChangeRule {sluc}{eb} {} {}
2356 \latexrelease\DeclareFontSeriesChangeRule {sluc}{ec} {} {}
2357 \latexrelease\DeclareFontSeriesChangeRule {sluc}{el} {} {}
2358 \latexrelease\DeclareFontSeriesChangeRule {sluc}{ex} {} {}
2359 \latexrelease\DeclareFontSeriesChangeRule {sluc}{l} {} {}
2360 \latexrelease\DeclareFontSeriesChangeRule {sluc}{m?} {} {}
2361 \latexrelease\DeclareFontSeriesChangeRule {sluc}{sb} {} {}
2362 \latexrelease\DeclareFontSeriesChangeRule {sluc}{sc} {} {}
2363 \latexrelease\DeclareFontSeriesChangeRule {sluc}{sl} {} {}
2364 \latexrelease\DeclareFontSeriesChangeRule {sluc}{sx} {} {}
2365 \latexrelease\DeclareFontSeriesChangeRule {sluc}{ub} {} {}
2366 \latexrelease\DeclareFontSeriesChangeRule {sluc}{uc} {} {}
2367 \latexrelease\DeclareFontSeriesChangeRule {sluc}{ul} {} {}
2368 \latexrelease\DeclareFontSeriesChangeRule {sluc}{ux} {} {}
2369 \latexrelease\DeclareFontSeriesChangeRule {sluc}{x} {} {}
2370 \latexrelease\DeclareFontSeriesChangeRule {slux}{?m} {} {}
2371 \latexrelease\DeclareFontSeriesChangeRule {slux}{bx} {} {}
2372 \latexrelease\DeclareFontSeriesChangeRule {slux}{b} {} {}
2373 \latexrelease\DeclareFontSeriesChangeRule {slux}{c} {} {}
2374 \latexrelease\DeclareFontSeriesChangeRule {slux}{eb} {} {}
2375 \latexrelease\DeclareFontSeriesChangeRule {slux}{ec} {} {}
2376 \latexrelease\DeclareFontSeriesChangeRule {slux}{el} {} {}
2377 \latexrelease\DeclareFontSeriesChangeRule {slux}{ex} {} {}
2378 \latexrelease\DeclareFontSeriesChangeRule {slux}{l} {} {}
2379 \latexrelease\DeclareFontSeriesChangeRule {slux}{m?} {} {}
2380 \latexrelease\DeclareFontSeriesChangeRule {slux}{sb} {} {}
2381 \latexrelease\DeclareFontSeriesChangeRule {slux}{sc} {} {}
2382 \latexrelease\DeclareFontSeriesChangeRule {slux}{sl} {} {}
2383 \latexrelease\DeclareFontSeriesChangeRule {slux}{sx} {} {}
2384 \latexrelease\DeclareFontSeriesChangeRule {slux}{ub} {} {}
2385 \latexrelease\DeclareFontSeriesChangeRule {slux}{uc} {} {}
2386 \latexrelease\DeclareFontSeriesChangeRule {slux}{ul} {} {}
2387 \latexrelease\DeclareFontSeriesChangeRule {slux}{ux} {} {}
2388 \latexrelease\DeclareFontSeriesChangeRule {slux}{x} {} {}
2389 \latexrelease\DeclareFontSeriesChangeRule {slx}{bx} {} {}
2390 \latexrelease\DeclareFontSeriesChangeRule {slx}{b}{bx}{}
2391 \latexrelease\DeclareFontSeriesChangeRule {slx}{c}{slc}{}
2392 \latexrelease\DeclareFontSeriesChangeRule {slx}{eb}{ebx}{}
2393 \latexrelease\DeclareFontSeriesChangeRule {slx}{ec}{slec}{}

```

```

2394 \latexrelease\DeclareFontSeriesChangeRule {slx}{el}{elx}{}
2395 \latexrelease\DeclareFontSeriesChangeRule {slx}{ex} {} {}
2396 \latexrelease\DeclareFontSeriesChangeRule {slx}{l}{lx}{}
2397 \latexrelease\DeclareFontSeriesChangeRule {slx}{sb}{sbx}{}
2398 \latexrelease\DeclareFontSeriesChangeRule {slx}{sc}{slsc}{}
2399 \latexrelease\DeclareFontSeriesChangeRule {slx}{sl}{slx}{}
2400 \latexrelease\DeclareFontSeriesChangeRule {slx}{sx} {} {}
2401 \latexrelease\DeclareFontSeriesChangeRule {slx}{ub}{ubx}{}
2402 \latexrelease\DeclareFontSeriesChangeRule {slx}{uc} {} {}
2403 \latexrelease\DeclareFontSeriesChangeRule {slx}{ul}{ulx}{}
2404 \latexrelease\DeclareFontSeriesChangeRule {slx}{ux} {} {}
2405 \latexrelease\DeclareFontSeriesChangeRule {slx}{x}{slx}{}
2406 \latexrelease\DeclareFontSeriesChangeRule {sl}{bx} {} {}
2407 \latexrelease\DeclareFontSeriesChangeRule {sl}{c}{slc}{}
2408 \latexrelease\DeclareFontSeriesChangeRule {sl}{eb} {} {}
2409 \latexrelease\DeclareFontSeriesChangeRule {sl}{ec}{slec}{}
2410 \latexrelease\DeclareFontSeriesChangeRule {sl}{ex} {} {}
2411 \latexrelease\DeclareFontSeriesChangeRule {sl}{sb} {} {}
2412 \latexrelease\DeclareFontSeriesChangeRule {sl}{sc}{slsc}{}
2413 \latexrelease\DeclareFontSeriesChangeRule {sl}{sx} {} {}
2414 \latexrelease\DeclareFontSeriesChangeRule {sl}{ub} {} {}
2415 \latexrelease\DeclareFontSeriesChangeRule {sl}{uc} {} {}
2416 \latexrelease\DeclareFontSeriesChangeRule {sl}{ux} {} {}
2417 \latexrelease\DeclareFontSeriesChangeRule {sl}{x}{slx}{}
2418 \latexrelease\DeclareFontSeriesChangeRule {sx}{?m} {} {}
2419 \latexrelease\DeclareFontSeriesChangeRule {sx}{bx} {} {}
2420 \latexrelease\DeclareFontSeriesChangeRule {sx}{b} {} {}
2421 \latexrelease\DeclareFontSeriesChangeRule {sx}{eb} {} {}
2422 \latexrelease\DeclareFontSeriesChangeRule {sx}{el} {} {}
2423 \latexrelease\DeclareFontSeriesChangeRule {sx}{l} {} {}
2424 \latexrelease\DeclareFontSeriesChangeRule {sx}{m?} {} {}
2425 \latexrelease\DeclareFontSeriesChangeRule {sx}{sb} {} {}
2426 \latexrelease\DeclareFontSeriesChangeRule {sx}{sl} {} {}
2427 \latexrelease\DeclareFontSeriesChangeRule {sx}{ub} {} {}
2428 \latexrelease\DeclareFontSeriesChangeRule {sx}{ul} {} {}
2429 \latexrelease\DeclareFontSeriesChangeRule {ubc}{bx} {} {}
2430 \latexrelease\DeclareFontSeriesChangeRule {ubc}{b}{bc}{}
2431 \latexrelease\DeclareFontSeriesChangeRule {ubc}{c}{ubc}{}
2432 \latexrelease\DeclareFontSeriesChangeRule {ubc}{eb}{ebc}{}
2433 \latexrelease\DeclareFontSeriesChangeRule {ubc}{ec}{ubec}{}
2434 \latexrelease\DeclareFontSeriesChangeRule {ubc}{el}{elc}{}
2435 \latexrelease\DeclareFontSeriesChangeRule {ubc}{ex} {} {}
2436 \latexrelease\DeclareFontSeriesChangeRule {ubc}{l}{lc}{}
2437 \latexrelease\DeclareFontSeriesChangeRule {ubc}{sb}{sbc}{}
2438 \latexrelease\DeclareFontSeriesChangeRule {ubc}{sc}{ubsc}{}
2439 \latexrelease\DeclareFontSeriesChangeRule {ubc}{sl}{slc}{}
2440 \latexrelease\DeclareFontSeriesChangeRule {ubc}{sx} {} {}
2441 \latexrelease\DeclareFontSeriesChangeRule {ubc}{ub}{ubc}{}
2442 \latexrelease\DeclareFontSeriesChangeRule {ubc}{uc} {} {}
2443 \latexrelease\DeclareFontSeriesChangeRule {ubc}{ul}{ulc}{}
2444 \latexrelease\DeclareFontSeriesChangeRule {ubc}{ux} {} {}
2445 \latexrelease\DeclareFontSeriesChangeRule {ubc}{x}{ubx}{}
2446 \latexrelease\DeclareFontSeriesChangeRule {ubec}{bx} {} {}
2447 \latexrelease\DeclareFontSeriesChangeRule {ubec}{b} {} {}

```

```

2448 \latexrelease\DeclareFontSeriesChangeRule {ubec}{c} {} {}
2449 \latexrelease\DeclareFontSeriesChangeRule {ubec}{eb} {} {}
2450 \latexrelease\DeclareFontSeriesChangeRule {ubec}{ec} {} {}
2451 \latexrelease\DeclareFontSeriesChangeRule {ubec}{el} {} {}
2452 \latexrelease\DeclareFontSeriesChangeRule {ubec}{ex} {} {}
2453 \latexrelease\DeclareFontSeriesChangeRule {ubec}{l} {} {}
2454 \latexrelease\DeclareFontSeriesChangeRule {ubec}{sb} {} {}
2455 \latexrelease\DeclareFontSeriesChangeRule {ubec}{sc} {} {}
2456 \latexrelease\DeclareFontSeriesChangeRule {ubec}{sl} {} {}
2457 \latexrelease\DeclareFontSeriesChangeRule {ubec}{sx} {} {}
2458 \latexrelease\DeclareFontSeriesChangeRule {ubec}{ub} {} {}
2459 \latexrelease\DeclareFontSeriesChangeRule {ubec}{uc} {} {}
2460 \latexrelease\DeclareFontSeriesChangeRule {ubec}{ul} {} {}
2461 \latexrelease\DeclareFontSeriesChangeRule {ubec}{ux} {} {}
2462 \latexrelease\DeclareFontSeriesChangeRule {ubex}{x} {} {}
2463 \latexrelease\DeclareFontSeriesChangeRule {ubex}{?m} {} {}
2464 \latexrelease\DeclareFontSeriesChangeRule {ubex}{bx} {} {}
2465 \latexrelease\DeclareFontSeriesChangeRule {ubex}{b} {} {}
2466 \latexrelease\DeclareFontSeriesChangeRule {ubex}{c} {} {}
2467 \latexrelease\DeclareFontSeriesChangeRule {ubex}{eb} {} {}
2468 \latexrelease\DeclareFontSeriesChangeRule {ubex}{ec} {} {}
2469 \latexrelease\DeclareFontSeriesChangeRule {ubex}{el} {} {}
2470 \latexrelease\DeclareFontSeriesChangeRule {ubex}{ex} {} {}
2471 \latexrelease\DeclareFontSeriesChangeRule {ubex}{l} {} {}
2472 \latexrelease\DeclareFontSeriesChangeRule {ubex}{m?} {} {}
2473 \latexrelease\DeclareFontSeriesChangeRule {ubex}{sb} {} {}
2474 \latexrelease\DeclareFontSeriesChangeRule {ubex}{sc} {} {}
2475 \latexrelease\DeclareFontSeriesChangeRule {ubex}{sl} {} {}
2476 \latexrelease\DeclareFontSeriesChangeRule {ubex}{sx} {} {}
2477 \latexrelease\DeclareFontSeriesChangeRule {ubex}{ub} {} {}
2478 \latexrelease\DeclareFontSeriesChangeRule {ubex}{uc} {} {}
2479 \latexrelease\DeclareFontSeriesChangeRule {ubex}{ul} {} {}
2480 \latexrelease\DeclareFontSeriesChangeRule {ubex}{ux} {} {}
2481 \latexrelease\DeclareFontSeriesChangeRule {ubex}{x} {} {}
2482 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{bx} {} {}
2483 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{b} {} {}
2484 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{c} {} {}
2485 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{eb} {} {}
2486 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{ec} {} {}
2487 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{el} {} {}
2488 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{ex} {} {}
2489 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{l} {} {}
2490 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{sb} {} {}
2491 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{sc} {} {}
2492 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{sl} {} {}
2493 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{sx} {} {}
2494 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{ub} {} {}
2495 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{uc} {} {}
2496 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{ul} {} {}
2497 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{ux} {} {}
2498 \latexrelease\DeclareFontSeriesChangeRule {ubsc}{x} {} {}
2499 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{?m} {} {}
2500 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{bx} {} {}
2501 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{b} {} {}

```

```

2502 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{c} {} {}
2503 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{eb} {} {}
2504 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{ec} {} {}
2505 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{el} {} {}
2506 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{ex} {} {}
2507 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{l} {} {}
2508 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{m?} {} {}
2509 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{sb} {} {}
2510 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{sc} {} {}
2511 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{sl} {} {}
2512 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{sx} {} {}
2513 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{ub} {} {}
2514 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{uc} {} {}
2515 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{ul} {} {}
2516 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{ux} {} {}
2517 \latexrelease\DeclareFontSeriesChangeRule {ubsx}{x} {} {}
2518 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{?m} {} {}
2519 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{bx} {} {}
2520 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{b} {} {}
2521 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{c} {} {}
2522 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{eb} {} {}
2523 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{ec} {} {}
2524 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{el} {} {}
2525 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{ex} {} {}
2526 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{l} {} {}
2527 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{m?} {} {}
2528 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{sb} {} {}
2529 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{sc} {} {}
2530 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{sl} {} {}
2531 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{sx} {} {}
2532 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{ub} {} {}
2533 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{uc} {} {}
2534 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{ul} {} {}
2535 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{ux} {} {}
2536 \latexrelease\DeclareFontSeriesChangeRule {ubuc}{x} {} {}
2537 \latexrelease\DeclareFontSeriesChangeRule {ubux}{?m} {} {}
2538 \latexrelease\DeclareFontSeriesChangeRule {ubux}{bx} {} {}
2539 \latexrelease\DeclareFontSeriesChangeRule {ubux}{b} {} {}
2540 \latexrelease\DeclareFontSeriesChangeRule {ubux}{c} {} {}
2541 \latexrelease\DeclareFontSeriesChangeRule {ubux}{eb} {} {}
2542 \latexrelease\DeclareFontSeriesChangeRule {ubux}{ec} {} {}
2543 \latexrelease\DeclareFontSeriesChangeRule {ubux}{el} {} {}
2544 \latexrelease\DeclareFontSeriesChangeRule {ubux}{ex} {} {}
2545 \latexrelease\DeclareFontSeriesChangeRule {ubux}{l} {} {}
2546 \latexrelease\DeclareFontSeriesChangeRule {ubux}{m?} {} {}
2547 \latexrelease\DeclareFontSeriesChangeRule {ubux}{sb} {} {}
2548 \latexrelease\DeclareFontSeriesChangeRule {ubux}{sc} {} {}
2549 \latexrelease\DeclareFontSeriesChangeRule {ubux}{sl} {} {}
2550 \latexrelease\DeclareFontSeriesChangeRule {ubux}{sx} {} {}
2551 \latexrelease\DeclareFontSeriesChangeRule {ubux}{ub} {} {}
2552 \latexrelease\DeclareFontSeriesChangeRule {ubux}{uc} {} {}
2553 \latexrelease\DeclareFontSeriesChangeRule {ubux}{ul} {} {}
2554 \latexrelease\DeclareFontSeriesChangeRule {ubux}{ux} {} {}
2555 \latexrelease\DeclareFontSeriesChangeRule {ubux}{x} {} {}

```

```

2556 \latexrelease\DeclareFontSeriesChangeRule {ubx}{bx} {} {}
2557 \latexrelease\DeclareFontSeriesChangeRule {ubx}{b}{bx}{}
2558 \latexrelease\DeclareFontSeriesChangeRule {ubx}{c}{ubc}{}
2559 \latexrelease\DeclareFontSeriesChangeRule {ubx}{eb}{ebx}{}
2560 \latexrelease\DeclareFontSeriesChangeRule {ubx}{ec}{ubec}{}
2561 \latexrelease\DeclareFontSeriesChangeRule {ubx}{el}{elx}{}
2562 \latexrelease\DeclareFontSeriesChangeRule {ubx}{ex} {} {}
2563 \latexrelease\DeclareFontSeriesChangeRule {ubx}{l}{lx}{}
2564 \latexrelease\DeclareFontSeriesChangeRule {ubx}{sb}{sbx}{}
2565 \latexrelease\DeclareFontSeriesChangeRule {ubx}{sc}{ubsc}{}
2566 \latexrelease\DeclareFontSeriesChangeRule {ubx}{sl}{slx}{}
2567 \latexrelease\DeclareFontSeriesChangeRule {ubx}{sx} {} {}
2568 \latexrelease\DeclareFontSeriesChangeRule {ubx}{ub}{ubx}{}
2569 \latexrelease\DeclareFontSeriesChangeRule {ubx}{uc} {} {}
2570 \latexrelease\DeclareFontSeriesChangeRule {ubx}{ul}{ulx}{}
2571 \latexrelease\DeclareFontSeriesChangeRule {ubx}{ux} {} {}
2572 \latexrelease\DeclareFontSeriesChangeRule {ubx}{x}{ubx}{}
2573 \latexrelease\DeclareFontSeriesChangeRule {ub}{bx} {} {}
2574 \latexrelease\DeclareFontSeriesChangeRule {ub}{c}{ubc}{}
2575 \latexrelease\DeclareFontSeriesChangeRule {ub}{eb} {} {}
2576 \latexrelease\DeclareFontSeriesChangeRule {ub}{ec}{ubec}{}
2577 \latexrelease\DeclareFontSeriesChangeRule {ub}{ex} {} {}
2578 \latexrelease\DeclareFontSeriesChangeRule {ub}{sb} {} {}
2579 \latexrelease\DeclareFontSeriesChangeRule {ub}{sc}{ubsc}{}
2580 \latexrelease\DeclareFontSeriesChangeRule {ub}{sx} {} {}
2581 \latexrelease\DeclareFontSeriesChangeRule {ub}{uc} {} {}
2582 \latexrelease\DeclareFontSeriesChangeRule {ub}{ux} {} {}
2583 \latexrelease\DeclareFontSeriesChangeRule {ub}{x}{ubx}{}
2584 \latexrelease\DeclareFontSeriesChangeRule {uc}{?m} {} {}
2585 \latexrelease\DeclareFontSeriesChangeRule {uc}{bx} {} {}
2586 \latexrelease\DeclareFontSeriesChangeRule {uc}{b} {} {}
2587 \latexrelease\DeclareFontSeriesChangeRule {uc}{eb} {} {}
2588 \latexrelease\DeclareFontSeriesChangeRule {uc}{el} {} {}
2589 \latexrelease\DeclareFontSeriesChangeRule {uc}{l} {} {}
2590 \latexrelease\DeclareFontSeriesChangeRule {uc}{m?} {} {}
2591 \latexrelease\DeclareFontSeriesChangeRule {uc}{sb} {} {}
2592 \latexrelease\DeclareFontSeriesChangeRule {uc}{sl} {} {}
2593 \latexrelease\DeclareFontSeriesChangeRule {uc}{ub} {} {}
2594 \latexrelease\DeclareFontSeriesChangeRule {uc}{ul} {} {}
2595 \latexrelease\DeclareFontSeriesChangeRule {ulc}{bx} {} {}
2596 \latexrelease\DeclareFontSeriesChangeRule {ulc}{b}{bc}{}
2597 \latexrelease\DeclareFontSeriesChangeRule {ulc}{c}{ulc}{}
2598 \latexrelease\DeclareFontSeriesChangeRule {ulc}{eb}{ebc}{}
2599 \latexrelease\DeclareFontSeriesChangeRule {ulc}{ec}{ulec}{ulc}
2600 \latexrelease\DeclareFontSeriesChangeRule {ulc}{el}{elc}{}
2601 \latexrelease\DeclareFontSeriesChangeRule {ulc}{ex} {} {}
2602 \latexrelease\DeclareFontSeriesChangeRule {ulc}{l}{lc}{}
2603 \latexrelease\DeclareFontSeriesChangeRule {ulc}{sb}{sbc}{}
2604 \latexrelease\DeclareFontSeriesChangeRule {ulc}{sc}{ulsc}{ulc}
2605 \latexrelease\DeclareFontSeriesChangeRule {ulc}{sl}{slc}{}
2606 \latexrelease\DeclareFontSeriesChangeRule {ulc}{sx} {} {}
2607 \latexrelease\DeclareFontSeriesChangeRule {ulc}{ub}{ubc}{}
2608 \latexrelease\DeclareFontSeriesChangeRule {ulc}{uc} {} {}
2609 \latexrelease\DeclareFontSeriesChangeRule {ulc}{ul}{ulc}{}

```

```

2610 <latexrelease>\DeclareFontSeriesChangeRule {ulc}{ux} {} {}
2611 <latexrelease>\DeclareFontSeriesChangeRule {ulc}{x}{ulx}{}
2612 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{bx} {} {}
2613 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{b} {} {}
2614 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{c} {} {}
2615 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{eb} {} {}
2616 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{ec} {} {}
2617 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{el} {} {}
2618 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{ex} {} {}
2619 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{l} {} {}
2620 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{sb} {} {}
2621 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{sc} {} {}
2622 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{sl} {} {}
2623 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{sx} {} {}
2624 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{ub} {} {}
2625 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{uc} {} {}
2626 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{ul} {} {}
2627 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{ux} {} {}
2628 <latexrelease>\DeclareFontSeriesChangeRule {ulec}{x} {} {}
2629 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{?m} {} {}
2630 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{bx} {} {}
2631 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{b} {} {}
2632 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{c} {} {}
2633 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{eb} {} {}
2634 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{ec} {} {}
2635 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{el} {} {}
2636 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{ex} {} {}
2637 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{l} {} {}
2638 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{m?} {} {}
2639 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{sb} {} {}
2640 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{sc} {} {}
2641 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{sl} {} {}
2642 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{sx} {} {}
2643 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{ub} {} {}
2644 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{uc} {} {}
2645 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{ul} {} {}
2646 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{ux} {} {}
2647 <latexrelease>\DeclareFontSeriesChangeRule {ulex}{x} {} {}
2648 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{bx} {} {}
2649 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{b} {} {}
2650 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{c} {} {}
2651 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{eb} {} {}
2652 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{ec} {} {}
2653 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{el} {} {}
2654 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{ex} {} {}
2655 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{l} {} {}
2656 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{sb} {} {}
2657 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{sc} {} {}
2658 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{sl} {} {}
2659 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{sx} {} {}
2660 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{ub} {} {}
2661 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{uc} {} {}
2662 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{ul} {} {}
2663 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{ux} {} {}

```

```

2664 <latexrelease>\DeclareFontSeriesChangeRule {ulsc}{x} {} {}
2665 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{?m} {} {}
2666 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{bx} {} {}
2667 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{b} {} {}
2668 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{c} {} {}
2669 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{eb} {} {}
2670 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{ec} {} {}
2671 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{el} {} {}
2672 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{ex} {} {}
2673 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{l} {} {}
2674 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{m?} {} {}
2675 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{sb} {} {}
2676 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{sc} {} {}
2677 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{sl} {} {}
2678 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{sx} {} {}
2679 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{ub} {} {}
2680 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{uc} {} {}
2681 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{ul} {} {}
2682 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{ux} {} {}
2683 <latexrelease>\DeclareFontSeriesChangeRule {ulsx}{x} {} {}
2684 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{?m} {} {}
2685 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{bx} {} {}
2686 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{b} {} {}
2687 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{c} {} {}
2688 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{eb} {} {}
2689 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{ec} {} {}
2690 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{el} {} {}
2691 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{ex} {} {}
2692 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{l} {} {}
2693 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{m?} {} {}
2694 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{sb} {} {}
2695 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{sc} {} {}
2696 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{sl} {} {}
2697 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{sx} {} {}
2698 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{ub} {} {}
2699 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{uc} {} {}
2700 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{ul} {} {}
2701 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{ux} {} {}
2702 <latexrelease>\DeclareFontSeriesChangeRule {uluc}{x} {} {}
2703 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{?m} {} {}
2704 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{bx} {} {}
2705 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{b} {} {}
2706 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{c} {} {}
2707 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{eb} {} {}
2708 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{ec} {} {}
2709 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{el} {} {}
2710 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{ex} {} {}
2711 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{l} {} {}
2712 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{m?} {} {}
2713 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{sb} {} {}
2714 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{sc} {} {}
2715 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{sl} {} {}
2716 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{sx} {} {}
2717 <latexrelease>\DeclareFontSeriesChangeRule {ulux}{ub} {} {}

```

```

2718 \latexrelease\DeclareFontSeriesChangeRule {ulux}{uc} {} {}
2719 \latexrelease\DeclareFontSeriesChangeRule {ulux}{ul} {} {}
2720 \latexrelease\DeclareFontSeriesChangeRule {ulux}{ux} {} {}
2721 \latexrelease\DeclareFontSeriesChangeRule {ulux}{x} {} {}
2722 \latexrelease\DeclareFontSeriesChangeRule {ulx}{bx} {} {}
2723 \latexrelease\DeclareFontSeriesChangeRule {ulx}{b}{bx}{}
2724 \latexrelease\DeclareFontSeriesChangeRule {ulx}{c}{ulc}{}
2725 \latexrelease\DeclareFontSeriesChangeRule {ulx}{eb}{ebx}{}
2726 \latexrelease\DeclareFontSeriesChangeRule {ulx}{ec}{ulec}{}
2727 \latexrelease\DeclareFontSeriesChangeRule {ulx}{el}{elx}{}
2728 \latexrelease\DeclareFontSeriesChangeRule {ulx}{ex} {} {}
2729 \latexrelease\DeclareFontSeriesChangeRule {ulx}{l}{lx}{}
2730 \latexrelease\DeclareFontSeriesChangeRule {ulx}{sb}{sbx}{}
2731 \latexrelease\DeclareFontSeriesChangeRule {ulx}{sc}{ulsc}{}
2732 \latexrelease\DeclareFontSeriesChangeRule {ulx}{sl}{slx}{}
2733 \latexrelease\DeclareFontSeriesChangeRule {ulx}{sx} {} {}
2734 \latexrelease\DeclareFontSeriesChangeRule {ulx}{ub}{ubx}{}
2735 \latexrelease\DeclareFontSeriesChangeRule {ulx}{uc} {} {}
2736 \latexrelease\DeclareFontSeriesChangeRule {ulx}{ul}{ulx}{}
2737 \latexrelease\DeclareFontSeriesChangeRule {ulx}{ux} {} {}
2738 \latexrelease\DeclareFontSeriesChangeRule {ulx}{x}{ulx}{}
2739 \latexrelease\DeclareFontSeriesChangeRule {ul}{bx} {} {}
2740 \latexrelease\DeclareFontSeriesChangeRule {ul}{c}{ulc}{}
2741 \latexrelease\DeclareFontSeriesChangeRule {ul}{eb} {} {}
2742 \latexrelease\DeclareFontSeriesChangeRule {ul}{ec}{ulec}{}
2743 \latexrelease\DeclareFontSeriesChangeRule {ul}{ex} {} {}
2744 \latexrelease\DeclareFontSeriesChangeRule {ul}{sb} {} {}
2745 \latexrelease\DeclareFontSeriesChangeRule {ul}{sc}{ulsc}{}
2746 \latexrelease\DeclareFontSeriesChangeRule {ul}{sx} {} {}
2747 \latexrelease\DeclareFontSeriesChangeRule {ul}{ub} {} {}
2748 \latexrelease\DeclareFontSeriesChangeRule {ul}{uc} {} {}
2749 \latexrelease\DeclareFontSeriesChangeRule {ul}{ux} {} {}
2750 \latexrelease\DeclareFontSeriesChangeRule {ul}{x}{ulx}{}
2751 \latexrelease\DeclareFontSeriesChangeRule {ux}{?m} {} {}
2752 \latexrelease\DeclareFontSeriesChangeRule {ux}{bx} {} {}
2753 \latexrelease\DeclareFontSeriesChangeRule {ux}{b} {} {}
2754 \latexrelease\DeclareFontSeriesChangeRule {ux}{eb} {} {}
2755 \latexrelease\DeclareFontSeriesChangeRule {ux}{el} {} {}
2756 \latexrelease\DeclareFontSeriesChangeRule {ux}{l} {} {}
2757 \latexrelease\DeclareFontSeriesChangeRule {ux}{m?} {} {}
2758 \latexrelease\DeclareFontSeriesChangeRule {ux}{sb} {} {}
2759 \latexrelease\DeclareFontSeriesChangeRule {ux}{sl} {} {}
2760 \latexrelease\DeclareFontSeriesChangeRule {ux}{ub} {} {}
2761 \latexrelease\DeclareFontSeriesChangeRule {ux}{ul} {} {}
2762 \latexrelease\DeclareFontSeriesChangeRule {x}{bx} {} {}
2763 \latexrelease\DeclareFontSeriesChangeRule {x}{c}{c}{}
2764 \latexrelease\DeclareFontSeriesChangeRule {x}{ec}{ec}{}
2765 \latexrelease\DeclareFontSeriesChangeRule {x}{el}{elx}{}
2766 \latexrelease\DeclareFontSeriesChangeRule {x}{l}{lx}{}
2767 \latexrelease\DeclareFontSeriesChangeRule {x}{sc}{sc}{}
2768 \latexrelease\DeclareFontSeriesChangeRule {x}{sl}{slx}{}
2769 \latexrelease\DeclareFontSeriesChangeRule {x}{ub}{ubx}{}
2770 \latexrelease\DeclareFontSeriesChangeRule {x}{ul}{ulx}{}
2771 \latexrelease

```

```

2772 <latexrelease>\EndIncludeInRelease
2773 <latexrelease>\IncludeInRelease{0000/00/00}%
2774 <latexrelease> {\DeclareFontSeriesChangeRule}{Series change rules}%
2775 <latexrelease>
2776 <latexrelease>\let\DeclareFontSeriesChangeRule\@undefined
2777 <latexrelease>
2778 <latexrelease>\EndIncludeInRelease

```

### 1.3 Changing to a new series

```

2779 <*2ekernel | latexrelease>
2780 <latexrelease>\IncludeInRelease{2021/06/01}%
2781 <latexrelease> {\fontseries}{delay fontseries update}%

```

**\fontseries** The `\fontseries` command takes one argument which is the requested new font series. In the original implementation it simply saved the expanded value in `\f@series`. Now we do a bit more processing and look up the final value in the font series data base. This is done by `\merge@font@series`. But the lookup should be done within the target family and call to `\fontseries` might be followed by a `\fontfamily` call. So we delay the processing to `\selectfont` and only record the necessary action in `\delayed@f@adjustment`.

```

2782 \DeclareRobustCommand\fontseries[1]{\@forced@seriesfalse
2783   \expandafter\def\expandafter\delayed@f@adjustment\expandafter
2784     {\delayed@f@adjustment\delayed@merge@font@series{#1}}}

```

*(End of definition for \fontseries.)*

**\delayed@f@adjustment** The macro holding the delayed action(s) for use in `\selectfont`.

```

2785 \let\delayed@f@adjustment\@empty

```

*(End of definition for \delayed@f@adjustment.)*

**\fontseriesforce** To change unconditionally to a new series you can use `\fontseriesforce`. Of course, if the series doesn't exist for the current family substitution still happens, but there is not dependency on the current series.

```

2786 \DeclareRobustCommand\fontseriesforce[1]{\@forced@seriestrue
2787   \expandafter\def\expandafter\delayed@f@adjustment\expandafter
2788     {\delayed@f@adjustment\edef\f@series{#1}}}

```

*(End of definition for \fontseriesforce.)*

**\if@forced@series** If the series gets forced we need to know that fact later on.

```

2789 \newif\if@forced@series

```

*(End of definition for \if@forced@series.)*

```

2790 </2ekernel | latexrelease>
2791 <latexrelease>\EndIncludeInRelease
2792 <latexrelease>\IncludeInRelease{2020/02/02}%
2793 <latexrelease> {\fontseries}{delay fontseries update}%
2794 <latexrelease>
2795 <latexrelease>\DeclareRobustCommand\fontseries[1]{\@forced@seriesfalse
2796 <latexrelease> \merge@font@series{#1}}
2797 <latexrelease>\DeclareRobustCommand\fontseriesforce[1]{\@forced@seriestrue
2798 <latexrelease> \edef\f@series{#1}}
2799 <latexrelease>\let\delayed@f@adjustment\@undefined
2800 <latexrelease>

```

For a roll forward we may have to define `\if@forced@series` but this needs doing in a way that  $\TeX$  doesn't see it when skipping over conditionals.

```

2801 <latexrelease>\expandafter\newif\csname if@forced@series\endcsname
2802 <latexrelease>
2803 <latexrelease>\EndIncludeInRelease
2804 <latexrelease>\IncludeInRelease{0000/00/00}%
2805 <latexrelease>                {\fontseries}{delay fontseries update}%
2806 <latexrelease>
2807 <latexrelease>\DeclareRobustCommand\fontseries[1]{\edef\f@series{#1}}
2808 <latexrelease>\let\fontseriesforce\@undefined
2809 <latexrelease>
2810 <latexrelease>\EndIncludeInRelease
2811 <*2ekernel | latexrelease>
2812 <latexrelease>\IncludeInRelease{2020/02/02}%
2813 <latexrelease>    {\merge@font@series}{Merge series values}%

```

`\merge@font@series` We look up the data base value by expanding the right command twice. If no such value exist then the result will be `\relax` otherwise it will be the two brace groups: the desired result and the alternate result. The first case means that the third argument to `\merge@font@series` will be empty.

```

2814 \def\merge@font@series#1{%
2815   \expandafter\expandafter\expandafter
2816   \merge@font@series@
2817   \csname series@\f@series @#1\endcsname
2818   {#1}%
2819   \@nil
2820 }

```

*(End of definition for \merge@font@series.)*

`\merge@font@series@` This now defines the new `\f@series`:

```

2821 \def\merge@font@series@#1#2#3\@nil{%

```

If the third argument is empty there is no database entry for the combination and the second argument holds the new series so we return that.

Originally the test was simply `\ifx!#3!` but that actually dies if `#3` starts with a conditional and in the definition of `\AmSfont` that is actually the case.

```

2822 %\ifcat\expandafter X\detokenize{#1}X%
2823 \def\reserved@a{#3}%
2824 \ifx\reserved@a\@empty
2825   \set@target@series{#2}%
2826 \else

```

Otherwise we check if the desired result for the series (`#1`) exists for the font family and the current shape. All this happens inside `\selectfont` which has already taken care to load the `.fd`, file if necessary.

```

2827 \edef\reserved@a{\f@encoding /\f@family /#1/\f@shape}%
2828 \ifcsname \reserved@a \endcsname

```

If the desired result is available then we use that. However, we do need some post-processing because we need to drop surplus `ms` due to the way naming convention was designed in the '90s (sigh).

```

2829 \set@target@series{#1}%

```

If not, then we try the alternate result (#2).

```
2830     \else
2831     \ifcsname \f@encoding /\f@family /#2/\f@shape \endcsname
```

If the alternate result exist we use that and also issue a warning (or rather a log entry) that we didn't managed to change to the desired font.

```
2832     \set@target@series{#2}%
2833     \@font@shape@subst@warning
```

If that doesn't exist either, then we use the requested series unmodified (again with a warning).

```
2834     \else
2835     \set@target@series{#3}%
2836     \@font@shape@subst@warning
2837   \fi
2838 \fi
2839 \fi
2840 }
```

It is possible that the previous font and the new one are actually identical (and the font was not found because it still needs loading) in which case a warning would look rather odd. So we make a quick check for that (which is the reason why we defined `\@reserveda` above instead of doing inline testing inside `\ifcsname`).

```
2841 \def\@font@shape@subst@warning{%
2842   \edef\reserved@b{\curr@fontshape}%
2843   \ifx\reserved@a\reserved@b \else
2844     \@font@warning{Font shape '\reserved@a' undefined\MessageBreak
2845                   using '\reserved@b' instead}%
2846   \fi
2847 }
```

(End of definition for `\merge@font@series@`.)

`\merge@font@series@without@substitution`  
`\merge@font@series@without@substitution@`  
`\delayed@merge@font@series`

`\merge@font@series@without@substitution` works like `\merge@font@series`, i.e., it looks up the combination in the rule base and if there exists an entry it uses it and if not it uses the new series value. However, it doesn't check if there is actually a font face with the new series value as `\merge@font@series` does. This simplified command is used in `\selectfont` at a point where other font attributes are not yet updated so that checking the font face might result incorrect in substitutions.

```
2848 \def\merge@font@series@without@substitution#1{%
2849   \expandafter\expandafter\expandafter
2850   \merge@font@series@without@substitution@
2851   \csname series@\f@series @#1\endcsname
2852   {#1}%
2853   \@nil
2854 }
2855 \def\merge@font@series@without@substitution@#1#2#3\@nil{%
2856   \def\reserved@a{#3}%
2857   \ifx\reserved@a\@empty
2858     \set@target@series{#2}%
2859   \else
2860     \set@target@series{#1}%
2861   \fi
2862 }
```

(End of definition for `\merge@font@series@without@substitution`,  
`\merge@font@series@without@substitution@`, and `\delayed@merge@font@series`.)

`\delayed@merge@font@series` When we delay the merge action in `\fontseries` we first attempt to use merging without substitution. If that results in a non-existing font face the merge is redone in `\selectfont` using a version with substitution. See `\selectfont` for details.

```
2863 \let\delayed@merge@font@series\merge@font@series@without@substitution
```

(End of definition for `\delayed@merge@font@series`.)

`\maybe@load@fontshape` A small helper that we use a couple of times: try loading a fontshape (in a group because `\try@load@fontshape` normalizes catcodes and we also want to change `\typeout` so that it doesn't report missing .fd files on the terminal).

```
2864 \def\maybe@load@fontshape{%
2865   \begingroup
2866   \let \typeout \@font@info
2867   \try@load@fontshape
2868   \endgroup}
```

(End of definition for `\maybe@load@fontshape`.)

`\set@target@series` Finally the code for normalizing the `\f@series` value.

The combined series value determined by the mapping may still contain an `m` that we have to remove (as the .fd files use `c` not `mc` to denote a medium weight condensed series, etc.). We do this in all branches above because a user might have written

```
\DeclareFontSeriesChangeRule {m}{sc}{msc}{mc}
```

instead of using `sc` and `c` as needed in the .fd file.

```
2869 \def\set@target@series#1{%
```

We need to `\edef` the argument first in case it starts with a conditional. Then we check (and perhaps drop) an “m” from the value and assign the result to `\f@series`.

```
2870   \edef\f@series{#1}%
2871   \series@maybe@drop@one@m\f@series\f@series
2872 }
```

(End of definition for `\set@target@series`.)

`\series@maybe@drop@one@m` If the series value is in NFSS notation then it should not contain any “m” unless it is just an “m” by its own. So we need to drop surplus “m”s. But we better don't do this for full names, such as “semibold” as used by `autoinst`, for example. So we test against the possible explicit values that should drop an “m”. After that we assign the result to `#2` for further use.

```
2873 \def\series@maybe@drop@one@m#1{%
2874   \expandafter\series@maybe@drop@one@m@x\expandafter{#1}}
2875
2876 \def\series@maybe@drop@one@m@x#1#2{%
```

The code below is an inline version of the `\in@` macro without the group, so that it works in `\accent`.

```
2877   \def\in@@##1,#1,{}%
2878   \series@check@toks\expandafter{\in@@
2879     ,ulm,elm,lm,slm,mm,slm,bm,ebm,ubm,muc,mec,mc,msc,msx,mx,mex,mux,{},{},#1,}%
2880   \edef\in@@{\the\series@check@toks}%
2881   \ifx\in@@\@empty
```

The default definition for `\bfdefault` etc is actually `b\@empty` so that we can detect if the user has changed the default. However that means a) the above test will definitely fail (maybe something to change) and b) we better use `\edef` on the next line to get rid of it as otherwise the test against `#2` (e.g., `\bfdef@ult`) will fail in other places.

```
2882 \edef#2{#1}%
2883 \else
2884 \edef#2{\expandafter\series@drop@one@m #1m\series@drop@one@m}%
2885 \fi
2886 }
```

As a precaution we use a private toks register not `\toks@` as that is no longer hidden inside the group.

```
2887 \newtoks\series@check@toks
```

*(End of definition for \series@maybe@drop@one@m.)*

`\series@drop@one@m` Drop up to two ms but keep one if that makes the series value empty. Actually, with the current implementation we know that there is at least one in the series value itself and we added one after it, so all we have to do is now returning `#1#2` and dropping the rest.

```
2888 \def\series@drop@one@m#1m#2m#3\series@drop@one@m{%
2889 % \ifx\relax#1#2\relax m\else#1#2\fi
2890 #1#2%
2891 }
```

*(End of definition for \series@drop@one@m.)*

Supporting rollback ...

```
2892 </2ekernel | latexrelease>
2893 <latexrelease>\EndIncludeInRelease
2894 <latexrelease>\IncludeInRelease{0000/00/00}%
2895 <latexrelease> {\merge@font@series}{Merge series values}%
2896 <latexrelease>
2897 <latexrelease>\let\merge@font@series\@undefined
2898 <latexrelease>\let\merge@font@series@\@undefined
2899 <latexrelease>\let\@font@shape@subst@warning\@undefined
2900 <latexrelease>\let\merge@font@series@without@substitution\@undefined
2901 <latexrelease>\let\merge@font@series@without@substitution@\@undefined
2902 <latexrelease>\let\delayed@merge@font@series\@undefined
2903 <latexrelease>\let\maybe@load@fontshape\@undefined
2904 <latexrelease>\let\set@target@series\@undefined
2905 <latexrelease>\let\series@maybe@drop@one@m\@undefined
2906 <latexrelease>\let\series@drop@one@m\@undefined
2907 <latexrelease>
2908 <latexrelease>\EndIncludeInRelease
```

## 2 Changing the shape

Shapes are also split in two axes (though it could be more if that is desirable), essentially building in an “sc” axis.

```
2909 <*2ekernel | latexrelease>
2910 <latexrelease>\IncludeInRelease{2020/02/02}%
2911 <latexrelease> {\ulcshape}{Font shape change rules}%
```

`\DeclareFontShapeChangeRule` The database for shapes is done in exactly the same way, only that it is much smaller and we usually have no alternative shape (or rather it is empty thus not used).

```
2912 \def\DeclareFontShapeChangeRule #1#2#3#4{%
2913   \@namedef{shape@#1@#2}{#{#3}#{#4}}}
```

*(End of definition for \DeclareFontShapeChangeRule.)*

There is kind of the same problem with returning back from `sc` to normal. It sort of needs its own letter. In `fontspec` this was solved by the first time `\upshape` changes `it` or `sl` back (so only `sc` remains) and second time it changes then `sc` back to normal. Maybe that's not a bad way to handle it, but decided for a slightly different approach: `n` always returns to "normal", ie resets everything and `up` changes italic or slanted to upright and `ulc` undoes small caps.

So we now offer `\normalshape` (using `\shapedefault`) which is normally the same as calling both `\ulcshape` and `\upshape`, only more efficient.

`\ulcshape` To request going back to upper/lowercase we need a new command. It uses `ulc` as shape name but this shape is virtual, i.e., it doesn't exist as a real shape, it is only used as part of the database table entries and thus only appears in the second argument there (but not in the first).

```
2914 \DeclareRobustCommand\ulcshape
2915   {\not@math@alphabet\ulcshape\relax
2916    \fontshape\ulcdefault\selectfont}
2917 \let\ulcdefault\@undefined      % for rollback
2918 \newcommand\ulcdefault{ulc}
```

*(End of definition for \ulcshape, \textulc, and \ulcdefault.)*

`\swshape` New command to select a swash shape. The standard rules put this in the same category as italics or slanted, i.e., if you ask for it then italics are undone. One could provide more complicated rules so that `it + sw` becomes `swit` but given that there are only very few fonts that have swash letters that level of flexibility (these days) would be just resulting in a lot of combinations that do not exist.

```
2919 \DeclareRobustCommand\swshape
2920   {\not@math@alphabet\swshape\relax
2921    \fontshape\swdefault\selectfont}
2922 \let\swdefault\@undefined      % for rollback
2923 \newcommand\swdefault{sw}
```

*(End of definition for \swshape, \textsw, and \swdefault.)*

`\sscshape` New commands to select spaced small capitals. There isn't a single free font that supports it. However, some commercial ones do, so we offer it. It is also possible to produce spaced small capitals from normal small capitals in OTF fonts using `otftotfm` with calls such as

```
otftotfm -e TEXMF/fonts/enc/dvips/base/txnnansx.enc \
SourceSerifPro-Regular.otf -fkern -fliga --feature=smcp \
--letterspacing=80 SourceSerifPro-Regular-ssc-LY1
```

Michael Ummels kindly prepared the necessary rules for `ssc` ages ago, but until recently they managed to hide deep down in my inbox. I finally got around to integrating them (with a few changes) and I also took the opportunity to rationalize (a bit) the rules for the only other uncommon shape, `sw`.

```

2924 \DeclareRobustCommand\sscshape
2925       {\not@math@alphabet\sscshape\relax
2926        \fontshape\sscdefault\selectfont}
2927 \let\sscdefault\@undefined      % for rollback
2928 \newcommand\sscdefault{ssc}

(End of definition for \sscshape, \textssc, and \sscdefault.)
Supporting rollback ...

2929 </2ekernel | latexrelease>
2930 <latexrelease>\EndIncludeInRelease
2931 <latexrelease>\IncludeInRelease{0000/00/00}%
2932 <latexrelease>    {\ulcshape}{Font shape change rules}%
2933 <latexrelease>
2934 <latexrelease>\let\DeclareFontShapeChangeRule\@undefined
2935 <latexrelease>\let\ulcshape\@undefined
2936 <latexrelease>\let\ulcdefault\@undefined
2937 <latexrelease>\let\swshape\@undefined
2938 <latexrelease>\let\swdefault\@undefined
2939 <latexrelease>\let\sscshape\@undefined
2940 <latexrelease>\let\sscdefault\@undefined
2941 <latexrelease>
2942 <latexrelease>\EndIncludeInRelease
2943 <*2ekernel>

```

## 2.1 Mapping rules for shape combinations

Many of the entries are commented out as we will get that result without any entry.

```

2944 </2ekernel>
2945 <*2ekernel | latexrelease>
2946 <latexrelease>\IncludeInRelease{2025/06/01}%
2947 <latexrelease>    {\DeclareFontShapeChangeRule}{Rules for ssc and sw}%
2948 %
2949 % \DeclareFontShapeChangeRule {n}{n}    {n}    {}
2950 \DeclareFontShapeChangeRule {n}{it}    {it}    {sl}
2951 \DeclareFontShapeChangeRule {n}{sl}    {sl}    {it}

```

If **sw** is requested but not available (not many font families offer it) we try to fallback to **it** instead of **sw**. That isn't always perfect, because some swash shapes are actually upright, but it is only a fallback and most of the time it would be better than **n**.

```

2952 \DeclareFontShapeChangeRule {n}{sw}    {sw}    {it}
2953 % \DeclareFontShapeChangeRule {n}{sc}    {sc}    {}
2954 \DeclareFontShapeChangeRule {n}{ulc}    {n}    {}
2955 \DeclareFontShapeChangeRule {n}{up}    {n}    {}

```

For the **ssc** shape we make the following general assumptions: if **ssc** $\langle X \rangle$  exists then **sc** $\langle X \rangle$  and  $\langle X \rangle$  also exist in the font. If the **ssc** $\langle X \rangle$  shape doesn't exist but the user had asked for **ssc** we try to replace it by **sc** because we then assume that the current font family simply doesn't have any **ssc** shapes. However, if we are already in some **ssc** shape and a shape change is requested we know that at least some **ssc** shapes exist for the current font family, so rather than falling back to some **sc** shape we try to stay within **ssc** shapes in a fallback situation.

```

2956 \DeclareFontShapeChangeRule {n}{ssc}    {ssc}    {sc}

```

```

2957 % \DeclareFontShapeChangeRule {it}{n} {n} {}
2958 % \DeclareFontShapeChangeRule {it}{it} {it} {}
2959 \DeclareFontShapeChangeRule {it}{sl} {sl} {it}
2960 \DeclareFontShapeChangeRule {it}{sw} {sw} {it}

```

If neither `scit` nor `scsl` exist then `sc` will be used as a fallback albeit with a log entry, so except for the latter there will be no change for CM or Latin Modern fonts.

```

2961 \DeclareFontShapeChangeRule {it}{sc} {scit} {scsl}
2962 \DeclareFontShapeChangeRule {it}{ulc} {it} {}
2963 \DeclareFontShapeChangeRule {it}{up} {n} {}
2964 \DeclareFontShapeChangeRule {it}{ssc} {sscit} {scit}

2965 % \DeclareFontShapeChangeRule {sl}{n} {n} {}
2966 \DeclareFontShapeChangeRule {sl}{it} {it} {sl}
2967 % \DeclareFontShapeChangeRule {sl}{sl} {sl} {}
2968 \DeclareFontShapeChangeRule {sl}{sw} {sw} {it}
2969 \DeclareFontShapeChangeRule {sl}{sc} {scsl} {scit}
2970 \DeclareFontShapeChangeRule {sl}{ulc} {sl} {}
2971 \DeclareFontShapeChangeRule {sl}{up} {n} {}
2972 \DeclareFontShapeChangeRule {sl}{ssc} {sscsl} {scsl}

2973 % \DeclareFontShapeChangeRule {sc}{n} {n} {}
2974 \DeclareFontShapeChangeRule {sc}{it} {scit} {scsl}
2975 \DeclareFontShapeChangeRule {sc}{sl} {scsl} {scit}
2976 \DeclareFontShapeChangeRule {sc}{sw} {scsw} {scit}
2977 % \DeclareFontShapeChangeRule {sc}{sc} {sc} {}
2978 \DeclareFontShapeChangeRule {sc}{ulc} {n} {}

```

The next rule might be a bit surprising, and rightly so. It would be more correct if `sc` were not affected by `up`, so that it remains `sc` as shown in the commented out rule. However, for nearly three decades commands such as `\upshape` or `\textup` changed small caps back to the “normal” shape. So for backward compatibility we keep that behavior.

As a result you are currently typesetting in `scit` or `scsl` using `\upshape` twice will return you to the normal shape too, the first will change to `sc` and the second (because of the rule below) change that to `n`. This is the way `fontspec` implemented its version on this interface, so this rule means we are also compatible with the way `fontspec` behaved. Still it remains an oddity which I would rather liked to have avoided.

```

2979 % \DeclareFontShapeChangeRule {sc}{up} {sc} {}
2980 \DeclareFontShapeChangeRule {sc}{up} {n} {}
2981 % \DeclareFontShapeChangeRule {sc}{ssc} {ssc} {}

2982 % \DeclareFontShapeChangeRule {scit}{n} {n} {}
2983 \DeclareFontShapeChangeRule {scit}{it} {scit} {}
2984 \DeclareFontShapeChangeRule {scit}{sl} {scsl} {scit}
2985 \DeclareFontShapeChangeRule {scit}{sw} {scsw} {scit}
2986 \DeclareFontShapeChangeRule {scit}{sc} {scit} {}
2987 \DeclareFontShapeChangeRule {scit}{ulc} {it} {}

```

The next rule assumes that if `scit` exists then `it` exists as well. If not, the mechanism will save `ulc` in `\f@series`, which most certainly doesn’t exist. So when a font is later selected that would result in a substitution (so no harm done really). Alternatively, we could in this case use `n` as alternative, which may be a bit faster, but such a setup would be so weird in the first place that this isn’t worth the effort.

```

2988 \DeclareFontShapeChangeRule {scit}{up} {sc} {}
2989 \DeclareFontShapeChangeRule {scit}{ssc} {sscit} {scit}

```

```

2990 % \DeclareFontShapeChangeRule {scsl}{n} {n} {}
2991 \DeclareFontShapeChangeRule {scsl}{it} {scit} {scsl}
2992 \DeclareFontShapeChangeRule {scsl}{sl} {scsl} {}
2993 \DeclareFontShapeChangeRule {scsl}{sw} {scsw} {scsl}
2994 \DeclareFontShapeChangeRule {scsl}{sc} {scsl} {}
2995 \DeclareFontShapeChangeRule {scsl}{ulc} {sl} {}
2996 \DeclareFontShapeChangeRule {scsl}{up} {sc} {}
2997 \DeclareFontShapeChangeRule {scsl}{ssc} {sscsl} {scsl}

2998 % \DeclareFontShapeChangeRule {scsw}{n} {n} {}
2999 \DeclareFontShapeChangeRule {scsw}{it} {scit} {scsw}
3000 \DeclareFontShapeChangeRule {scsw}{sl} {scsl} {}
3001 \DeclareFontShapeChangeRule {scsw}{sw} {scsw} {}
3002 \DeclareFontShapeChangeRule {scsw}{sc} {scsw} {}
3003 \DeclareFontShapeChangeRule {scsw}{ulc} {sw} {}
3004 \DeclareFontShapeChangeRule {scsw}{up} {sc} {}
3005 \DeclareFontShapeChangeRule {scsw}{ssc} {sscsw} {scsw}

3006 % \DeclareFontShapeChangeRule {sw}{n} {n} {}
3007 % \DeclareFontShapeChangeRule {sw}{it} {it} {}
3008 % \DeclareFontShapeChangeRule {sw}{sl} {sl} {}
3009 % \DeclareFontShapeChangeRule {sw}{sw} {sw} {}
3010 \DeclareFontShapeChangeRule {sw}{sc} {scsw} {scit}
3011 \DeclareFontShapeChangeRule {sw}{ulc} {sw} {}
3012 \DeclareFontShapeChangeRule {sw}{up} {n} {}
3013 \DeclareFontShapeChangeRule {sw}{ssc} {sscsw} {scsw}

3014 % \DeclareFontShapeChangeRule {ssc}{n} {n} {}
3015 \DeclareFontShapeChangeRule {ssc}{it} {sscit} {sscsl}
3016 \DeclareFontShapeChangeRule {ssc}{sl} {sscsl} {sscit}
3017 \DeclareFontShapeChangeRule {ssc}{sw} {sscsw} {sscit}
3018 \DeclareFontShapeChangeRule {ssc}{sc} {sc} {}
3019 % \DeclareFontShapeChangeRule {ssc}{ssc} {ssc} {}
3020 \DeclareFontShapeChangeRule {ssc}{ulc} {n} {}

```

We implement the same logic as for `sc`, see above. The `ssc` shape doesn't have to care about 30 years of history, but it would be surprising if `\sscshape\upshape` did not work like `\scshape\upshape`.

```

3021 % \DeclareFontShapeChangeRule {ssc}{up} {ssc} {}
3022 \DeclareFontShapeChangeRule {ssc}{up} {n} {}

3023 % \DeclareFontShapeChangeRule {sscit}{n} {n} {}
3024 \DeclareFontShapeChangeRule {sscit}{it} {sscit} {}
3025 \DeclareFontShapeChangeRule {sscit}{sl} {sscsl} {sscit}
3026 \DeclareFontShapeChangeRule {sscit}{sw} {sscsw} {sscit}
3027 \DeclareFontShapeChangeRule {sscit}{ssc} {sscit} {}
3028 \DeclareFontShapeChangeRule {sscit}{sc} {scit} {}
3029 \DeclareFontShapeChangeRule {sscit}{ulc} {it} {}
3030 \DeclareFontShapeChangeRule {sscit}{up} {ssc} {}

3031 % \DeclareFontShapeChangeRule {sscsl}{n} {n} {}
3032 \DeclareFontShapeChangeRule {sscsl}{it} {sscit} {sscsl}
3033 \DeclareFontShapeChangeRule {sscsl}{sl} {sscsl} {}
3034 \DeclareFontShapeChangeRule {sscsl}{sw} {sscsw} {sscit}
3035 \DeclareFontShapeChangeRule {sscsl}{sc} {scsl} {}
3036 \DeclareFontShapeChangeRule {sscsl}{ulc} {sl} {}
3037 \DeclareFontShapeChangeRule {sscsl}{up} {ssc} {}

```



just switching to that shape or switching away from it; so we mimic that by providing the corresponding trivial rules to overrule those from above when we roll back.

```

3090 <latexrelease>\DeclareFontShapeChangeRule {n}{ssc} {ssc} {}
3091 <latexrelease>\DeclareFontShapeChangeRule {it}{ssc} {ssc} {}
3092 <latexrelease>\DeclareFontShapeChangeRule {sl}{ssc} {ssc} {}
3093 <latexrelease>\DeclareFontShapeChangeRule {sw}{ssc} {ssc} {}
3094 <latexrelease>
3095 <latexrelease>\DeclareFontShapeChangeRule {scit}{ssc}{ssc} {}
3096 <latexrelease>\DeclareFontShapeChangeRule {scsl}{ssc}{ssc} {}
3097 <latexrelease>\DeclareFontShapeChangeRule {scsw}{ssc}{ssc} {}
3098 <latexrelease>
3099 <latexrelease>\DeclareFontShapeChangeRule {ssc}{it} {it} {}
3100 <latexrelease>\DeclareFontShapeChangeRule {ssc}{sl} {sl} {}
3101 <latexrelease>\DeclareFontShapeChangeRule {ssc}{sw} {sw} {}
3102 <latexrelease>\DeclareFontShapeChangeRule {ssc}{sc} {sc} {}
3103 <latexrelease>\DeclareFontShapeChangeRule {ssc}{ulc} {n} {}
3104 <latexrelease>\DeclareFontShapeChangeRule {ssc}{up} {n} {}
3105 <latexrelease>
3106 <latexrelease>\DeclareFontShapeChangeRule {sscit}{it} {it} {}
3107 <latexrelease>\DeclareFontShapeChangeRule {sscit}{sl} {sl} {}
3108 <latexrelease>\DeclareFontShapeChangeRule {sscit}{sw} {sw} {}
3109 <latexrelease>\DeclareFontShapeChangeRule {sscit}{ssc} {ssc} {}
3110 <latexrelease>\DeclareFontShapeChangeRule {sscit}{sc} {sc} {}
3111 <latexrelease>\DeclareFontShapeChangeRule {sscit}{ulc} {n} {}
3112 <latexrelease>\DeclareFontShapeChangeRule {sscit}{up} {ssc} {}
3113 <latexrelease>
3114 <latexrelease>\DeclareFontShapeChangeRule {sscsl}{it} {it} {}
3115 <latexrelease>\DeclareFontShapeChangeRule {sscsl}{sl} {sl} {}
3116 <latexrelease>\DeclareFontShapeChangeRule {sscsl}{sw} {sw} {}
3117 <latexrelease>\DeclareFontShapeChangeRule {sscsl}{sc} {sc} {}
3118 <latexrelease>\DeclareFontShapeChangeRule {sscsl}{ulc} {n} {}
3119 <latexrelease>\DeclareFontShapeChangeRule {sscsl}{up} {ssc} {}
3120 <latexrelease>
3121 <latexrelease>\DeclareFontShapeChangeRule {sscsw}{it} {it} {}
3122 <latexrelease>\DeclareFontShapeChangeRule {sscsw}{sl} {sl} {}
3123 <latexrelease>\DeclareFontShapeChangeRule {sscsw}{sw} {sw} {}
3124 <latexrelease>\DeclareFontShapeChangeRule {sscsw}{ssc} {ssc} {}
3125 <latexrelease>\DeclareFontShapeChangeRule {sscsw}{sc} {sc} {}
3126 <latexrelease>\DeclareFontShapeChangeRule {sscsw}{ulc} {n} {}
3127 <latexrelease>\DeclareFontShapeChangeRule {sscsw}{up} {ssc} {}
3128 <latexrelease>\EndIncludeInRelease

```

Before 2020-02-02 we don't really care about any existing shape change rules since the mechanism isn't used.

```

3129 <latexrelease>\IncludeInRelease{0000/00/00}%
3130 <latexrelease>      {\DeclareFontShapeChangeRule}{Rules for ssc and sw}%
3131 <latexrelease>\EndIncludeInRelease

```

## 2.2 Changing to a new shape

```

3132 <*2ekernel | latexrelease>
3133 <latexrelease>\IncludeInRelease{2021/06/01}%
3134 <latexrelease>      {\fontshape}{Font shape change}%

```

`\fontshape` Again the `\fontshape` now has to do a lookup to get to its new value in `\f@shape`. The method is exactly the same as in `\fontseries`.

```
3135 \DeclareRobustCommand\fontshape[1]
3136     {\expandafter\def\expandafter\delayed@f@adjustment\expandafter
3137      {\delayed@f@adjustment\delayed@merge@font@shape{#1}}}
```

*(End of definition for \fontshape.)*

`\fontshapeforce` The unconditional version:

```
3138 \DeclareRobustCommand\fontshapeforce[1]
3139     {\expandafter\def\expandafter\delayed@f@adjustment\expandafter
3140      {\delayed@f@adjustment\edef\f@shape{#1}}}
```

*(End of definition for \fontshapeforce.)*

Supporting rollback ...

```
3141 </2ekernel | latexrelease>
3142 <latexrelease>\EndIncludeInRelease
3143 <latexrelease>\IncludeInRelease{2020/02/02}%
3144 <latexrelease>    {\fontshape}{Font shape change}%
3145 <latexrelease>
3146 <latexrelease>\DeclareRobustCommand\fontshape[1]{\merge@font@shape{#1}}
3147 <latexrelease>\DeclareRobustCommand\fontshapeforce[1]{\edef\f@shape{#1}}
3148 <latexrelease>
3149 <latexrelease>\EndIncludeInRelease

3150 <latexrelease>\IncludeInRelease{0000/00/00}%
3151 <latexrelease>    {\fontshape}{Font shape change}%
3152 <latexrelease>
3153 <latexrelease>\DeclareRobustCommand\fontshape [1]{\edef\f@shape{#1}}
3154 <latexrelease>\let\fontshapeforce\@undefined
3155 <latexrelease>
3156 <latexrelease>\EndIncludeInRelease

3157 <*2ekernel | latexrelease>
3158 <latexrelease>\IncludeInRelease{2020/02/02}%
3159 <latexrelease>    {\merge@font@shape}{Font shape change rules}%
```

`\merge@font@shape` Look up the database entry (if existing) and act accordingly.

```
3160 \def\merge@font@shape#1{%
3161     \expandafter\expandafter\expandafter
3162     \merge@font@shape@
3163     \csname shape@\f@shape @#1\endcsname
3164     {#1}%
3165     \@nil
3166 }
```

*(End of definition for \merge@font@shape.)*

`\merge@font@shape@` Same game now, except that we look at shapes not series values and we can set the shape without the complication of dropping “m”s from the name as we had to for the series.

```
3167 \def\merge@font@shape@#1#2#3\@nil{%
3168     \def\reserved@a{#3}%
3169     \ifx\reserved@a\@empty
3170         \edef\f@shape{#2}%
3171     \else
```

`\reserved@a` is used in `\@font@shape@subst@warning` so we have to define it in addition to do the `\ifcstype` test

```

3172 \edef\reserved@a{\f@encoding /\f@family /\f@series/#1}%
3173 \ifcstype \reserved@a\endcstype
3174 \edef\f@shape{#1}%
3175 \else
3176 \ifcstype \f@encoding /\f@family /\f@series/#2\endcstype
3177 \edef\f@shape{#2}%
3178 \@font@shape@subst@warning
3179 \else
3180 \edef\f@shape{#3}%
3181 \@font@shape@subst@warning
3182 \fi
3183 \fi
3184 \fi
3185 }

```

*(End of definition for \merge@font@shape@.)*

`\merge@font@shape@without@substitution`  
`\merge@font@shape@without@substitution@`  
`\delayed@merge@font@shape`

See definition of `\selectfont` for how these macros are used.

```

3186 \def\merge@font@shape@without@substitution#1{%
3187 \expandafter\expandafter\expandafter
3188 \merge@font@shape@without@substitution@
3189 \cstype shape@\f@shape @#1\endcstype
3190 {#1}%
3191 \@nil
3192 }
3193 \def\merge@font@shape@without@substitution@#1#2#3\@nil{%
3194 \def\reserved@a{#3}%
3195 \ifx\reserved@a\@empty
3196 \edef\f@shape{#2}%
3197 \else
3198 \edef\f@shape{#1}%
3199 \fi
3200 }
3201 \let\delayed@merge@font@shape\merge@font@shape@without@substitution

```

*(End of definition for \merge@font@shape@without@substitution,  
\merge@font@shape@without@substitution@, and \delayed@merge@font@shape.)*

`\normalshape` `\normalshape` resets both sub-axes if the default rules are used.

```

3202 \protected\def\normalshape
3203 {\not@math@alphabet\normalshape\relax
3204 \fontshape\shapedefault\selectfont}%

```

*(End of definition for \normalshape.)*

### 3 Make sure we win ...

This code implements one aspect of what the package `fontaxes` provide. So its redefinitions for the various shape commands, such as `\itshape` should no longer happen. We therefore force the standard definitions at `\AtBeginDocument` (later when this is defined). Once `fontaxes` is no longer doing such redefinitions that could be taken out again.

We use a separate macro so that we can easily disable this (in case of rollback).

`\reinstall@nfss@defs` I use `\protected` here not `\DeclareRobustCommand` to avoid extra status lines.

```

3205 \def\reinstall@nfss@defs{%
3206   \protected\def\upshape
3207     {\not@math@alphabet\upshape\relax
3208      \fontshape\updefault\selectfont}%
3209   \protected\def\slshape
3210     {\not@math@alphabet\slshape\relax
3211      \fontshape\sldefault\selectfont}%
3212   \protected\def\scshape
3213     {\not@math@alphabet\scshape\relax
3214      \fontshape\scdefault\selectfont}%
3215   \protected\def\itshape
3216     {\not@math@alphabet\itshape\mathit
3217      \fontshape\itdefault\selectfont}%
3218   \protected\def\ulcshape
3219     {\not@math@alphabet\ulcshape\relax
3220      \fontshape\ulc\selectfont}%
3221   \protected\def\swshape
3222     {\not@math@alphabet\swshape\relax
3223      \fontshape\swdefault\selectfont}%
3224   \protected\def\sscshape
3225     {\not@math@alphabet\sscshape\relax
3226      \fontshape\sscdefault\selectfont}%
3227 }

```

*(End of definition for \reinstall@nfss@defs.)*

Supporting rollback ...

```

3228 </2ekernel | latexrelease>
3229 <latexrelease>\EndIncludeInRelease
3230 <latexrelease>\IncludeInRelease{0000/00/00}%
3231 <latexrelease>  {\merge@font@shape}{Font shape change rules}%
3232 <latexrelease>
3233 <latexrelease>\DeclareRobustCommand\fontshape [1]{\edef\f@shape{#1}}
3234 <latexrelease>\let\fontshapeforce\@undefined
3235 <latexrelease>
3236 <latexrelease>\let\merge@font@shape\@undefined
3237 <latexrelease>\let\merge@font@shape@\@undefined
3238 <latexrelease>
3239 <latexrelease>\let\merge@font@shape@without@substitution\@undefined
3240 <latexrelease>\let\merge@font@shape@without@substitution@\@undefined
3241 <latexrelease>\let\delayed@merge@font@shape\@undefined
3242 <latexrelease>
3243 <latexrelease>\let\normalshape\@undefined
3244 <latexrelease>

```

This is always called in `\document` so don't make it undefined.

```

3245 <latexrelease>
3246 <latexrelease>\let\reinstall@nfss@defs\relax
3247 <latexrelease>\EndIncludeInRelease

```

This initializes the 2020/02/02 extensions to NFSS after any changes in the preamble.

```

3248 <*2ekernel | latexrelease>
3249 <latexrelease>\IncludeInRelease{2020/10/01}%

```

```

3250 <latexrelease>                {\reinstall@nfss@defs}{NFSS series init}%
3251 \g@addto@macro\@kernel@after@begindocument@before
3252                {\reinstall@nfss@defs\init@series@setup}
3253 </2ekernel | latexrelease>
3254 <latexrelease>\EndIncludeInRelease

    The initialization was introduced in 2020/02/02 but
3255 <latexrelease>\IncludeInRelease{2020/02/02}%
3256 <latexrelease>                {\reinstall@nfss@defs}{NFSS series init}%
3257 <latexrelease>\AtBeginDocument{\reinstall@nfss@defs\init@series@setup}
3258 <latexrelease>\EndIncludeInRelease

3259 <latexrelease>\IncludeInRelease{0000/00/00}%
3260 <latexrelease>                {\reinstall@nfss@defs}{NFSS series init}%
3261 <latexrelease>\EndIncludeInRelease
3262 <*2ekernel>
3263 </2ekernel>

```

## File 26

# ltfsstrc.dtx

## 1 Introduction

This package contains the code for tracing font loading and font changes. It basically overlays some of the low-level functions of NFSS with additional code used for tracing.

The package accepts the following options:

**errorshow** Write all information about font changes etc. only to the transcript file unless an error happens. This means that information about font substitution will not be shown on the terminal.

**warningshow** Show all NFSS warnings on the terminal. This setting corresponds to the default behaviour of NFSS if the `tracefnt` package is *not* loaded!

**infoshow** Show all NFSS warning and all NFSS info messages (that are normally only written to the transcript file) also on the terminal. This is the default if the `tracefnt` package is loaded.

**debugshow** In addition to **infoshow** show also changing of math fonts as far as possible (this option can produce a large amount of output).

**loading** Show the name of external fonts when they are loaded. This option shows only “newly” loaded fonts not those already preloaded in the format or the class file before the `tracefnt` package became active.

**pausing** Turn all font warnings into errors so that L<sup>A</sup>T<sub>E</sub>X will stop.

## 2 A driver for this document

The next bit of code contains the documentation driver file for T<sub>E</sub>X, i.e., the file that will produce the documentation you are currently reading. It will be extracted from this file by the DOCSTRIP program.

When this file is processed directly by L<sup>A</sup>T<sub>E</sub>X this will produce the documentation as well.

```
1 <*driver>
2 \documentclass{ltxdoc}
3
4
5 %\OnlyDescription % comment out for implementation details
6
7 \begin{document}
8   \DocInput{ltfsstrc.dtx}
9 \end{document}
10 </driver>
```

### 3 The Implementation

**Warning:** Read the macro documentation with a grain of salt. It is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

If we are making a package file it is a good idea to test whether we are running under 2e. This code is actually placed at the very beginning of this file for easier maintenance, thus commented out here.

```
11 <*package>
12 %\NeedsTeXFormat{LaTeX2e}
13 %\ProvidesPackage{tracefnt}[??/??/?? v?.??]
14 %
15 </package>
```

The `debug` module makes use of commands contained in a special package file named `trace.sty`.<sup>34</sup>

```
16 <+debug> \input trace.sty
```

### 4 Handling Options

`\tracingfonts` Here is the definition of the integer register for the font trace. As a default in a package file we use 1 to give error messages if fonts are substituted. If this code is used for debugging or tracing reasons in the format file (i.e. in `fam.dtx`) we use 0 as the default. But if no font trace is used we build a definition that will produce a warning message.

```
17 <*2ekernel>
18 \message{NFSS tracing,}
19 \def\tracingfonts{%
20   \@font@warning{Command \noexpand\tracingfonts
21     not provided.\MessageBreak
22     Use the ‘tracefnt’ package.\MessageBreak Command found:}%
23   \count@}
24 </2ekernel>
```

The `\count@` in the line above will remove the number after `\tracingfonts`. Note that this definition will be overwritten by the next line if one of these modules are included.

```
25 <*package, trace, debug>
26 \newcount\tracingfonts
27 \tracingfonts=0
28 </package, trace, debug>
```

*(End of definition for \tracingfonts.)*

The option `errorshow` turns off all warnings so that only real errors are shown. `warningshow` corresponds to the NFSS default (when `tracefnt` is not loaded). `info` is the default for this package here; and `debugshow`, `loading`, and `pausing` extend the amount of information even further.

```
29 <*package>
30 \DeclareOption{errorshow}{%
31   \def\@font@info#1{%
32     \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
```

---

<sup>34</sup>This package is not in distribution at the moment (and probably doesn't any longer work). Think of this part of the code as being historical artifacts.

```

33             {LaTeX Font Info: \space\space\space#1}}%
34 \def\@font@warning#1{%
35     \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
36     {LaTeX Font Warning: #1}}%
37 }
38 \DeclareOption{warningshow}{%
39 \def\@font@info#1{%
40     \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
41     {LaTeX Font Info: \space\space\space#1}}%
42 \def\@font@warning#1{%
43     \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
44     {LaTeX Font Warning: #1}}%
45 }
46 \DeclareOption{infoshow}{%
47 \def\@font@info#1{%
48     \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
49     {LaTeX Font Info: \space\space\space#1}}%
50 \def\@font@warning#1{%
51     \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
52     {LaTeX Font Warning: #1}}%
53 }
54 \DeclareOption{loading}{%
55     \tracingfonts\tw@
56 }
57 \DeclareOption{debugshow}{%
58     \ExecuteOptions{infoshow}%
59     \tracingfonts\thr@@
60 }
61 \DeclareOption{pausing}{%
62 \def\@font@warning#1{%
63     \GenericError
64     {(Font)\@spaces\@spaces\@spaces\space\space}%
65     {LaTeX Font Warning: #1}%
66     {See the LaTeX Companion for details.}%
67     {I'll stop for every LaTeX Font Warning because
68     you requested\MessageBreak the 'pausing' option
69     to the tracefnt package.}}%
70 }

```

We make `infoshow` the default, which in turn defines `\font@warning` and `\font@info`.

```

71 \ExecuteOptions{infoshow}
72 \ProcessOptions
73 \endpackage

```

We also need a default definition inside the kernel:

```

74 \ifx\kernel
75 \def\@font@info#1{%
76     \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
77     {LaTeX Font Info: \space\space\space#1}}%
78 \def\@font@warning#1{%
79     \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
80     {LaTeX Font Warning: #1}}%
81 \fi

```

## 5 Macros common to fam.tex and tracefmt.sty

In the first versions of `tracefmt.dtx` some macros of `fam.dtx`<sup>35</sup> were redefined to include the extra tracing information. Now these macros are all defined in this file (i.e. removed from `fam.dtx`) and different production versions can be obtained simply by specifying a different set of modules to include when generating `lftss.dtx`.

### 5.1 General font loading

`\extract@font` This macro organizes the font loading. It first calls `\get@external@font` which will return in `\external@font` the name of the external font file (the `.tfm`) as it was determined by the NFSS tables.

```
82 <*2ekernel|package>
83 \def\extract@font{%
84     \get@external@font
```

Then the external font is loaded and assigned to the font identifier stored inside `\font@name` (for this reason we need `\expandafter`).

```
85     \global\expandafter\font\font@name\external@font\relax
```

When tracing we typeout the internal and external font name.

```
86 <*trace>
87     \ifnum \tracingfonts >\@ne
88     \@font@info{External font '\external@font'
89                 loaded as\MessageBreak \font@name}\fi
90 </trace>
```

Finally we call the corresponding “loading action” macros to finish things. First the font is locally selected to allow the use of `\font` inside the loading action macros.

```
91     \font@name \relax
```

The next two lines execute the “loading actions” for the family and then for the individual font shape.

```
92     \csname \f@encoding+\f@family\endcsname
93     \csname\curr@fontshape\endcsname
94     \relax
95     }
96 </2ekernel|package>
```

The `\relax` at the end needs to be explained. This is inserted to prevent `TEX` from scanning too far when it is executing the replacement text of the loading code macros.

*(End of definition for `\extract@font`.)*

`\get@external@font` This function tries to find an external font name. It will place the name into the macro `\external@font`. If no font is found it will return the one that was defined via `\DeclareErrorFont`.

```
97 <*2ekernel>
98 \def\get@external@font{%
```

We don’t know the external font name at the beginning.

```
99     \let\external@font\@empty
100     \edef\font@info{\expandafter\expandafter\expandafter\string
101                     \csname \curr@fontshape \endcsname}%
102     \try@size@range
```

---

<sup>35</sup>This file is currently not distributed in documented form. Its code is part of `lftss.dtx`.

If this failed, we'll try to substitute another size of the same font. This is done by the `\try@size@substitution` macro. It “knows about” `\do@extract@font`, `\font@name`, `\f@size`, and so on.

```

103 \ifx\external@font\@empty
104 \try@size@substitution
105 \ifx\external@font\@empty
106 \latex@error{Font \expandafter \string\font@name\space
107 not found}\@eha
108 \error@fontshape
109 \get@external@font
110 \fi\fi
111 }
112 \endkernel

```

(End of definition for `\get@external@font`.)

```

113 \<*2kernel | latexrelease | package>
114 \<latexrelease>\IncludeInRelease{2021/06/01}%
115 \<latexrelease>{\selectfont}{Add hook to \selectfont}%

```

`\selectfont` The macro `\selectfont` is called whenever a font change must take place.

```

116 \DeclareRobustCommand\selectfont
117 {%

```

When `debug` is specified we actually want something like ‘undebug’. The font selection is now stable so that using `\tracingall` on some other macros will show us a lot of unwanted information about font loading. Therefore we disable tracing during font loading as long as `\tracingfonts` is less than 4.

```

118 \<+debug> \pushtracing
119 \<+debug> \ifnum\tracingfonts<4 \tracingoff
120 \<+debug> \else \tracingon\p@selectfont \fi

```

If `\baselinestretch` was redefined by the user it will not longer match its internal counterpart `\f@linespread`. If so we call `\set@fontsize` to prepare `\size@update`.

```

121 \ifx\f@linespread\baselinestretch \else
122 \set@fontsize\baselinestretch\f@size\f@baselineskip \fi

```

The series and shape updates are only prepared by `\fontseries` and `\fontshape` but not executed until after we are ready to change the font face. This way they happen after a possibly new family is set which is important because they look at the available font faces in that family and alter the selection based on availability. Several calls to `\fontseries` or `\fontshape` are delayed in the order in which they appear, so that by switching them one can work around missing intermediate font faces and avoid substitutions.

We first attempt to do the merge without any substitution. As we might end up with a non-existing font face we may have to restart and therefore save the current values of `\f@series` and `\f@shape` before the merge.

But first we make a quick test to see if there are any delayed actions, because if not it is pointless to make all the assignments and try loading a missing fontshape.

```

123 \ifx\delayed@f@adjustment\@empty
124 \else
125 \let\f@shape@savd\f@shape
126 \let\f@series@savd\f@series

```

Then we run the delayed adjustments (which use the `\..@without@substitution` commands):

```
127      \delayed@f@adjustment
```

We then check if the resulting combination is valid but for this we have to make sure that the appropriate `.fd` is loaded if that hasn't happened so far.

```
128      \maybe@load@fontshape
```

```
129      \ifcsname \f@encoding/\f@family/\f@series/\f@shape \endcsname
```

If this macro is defined then we are good and no further action is necessary.

Otherwise the combination is not valid, so we redo the merge but this time with substitutions.

```
130      \else
```

```
131          \let\f@shape\f@shape@saved
```

```
132          \let\f@series\f@series@saved
```

```
133          \let\delayed@merge@font@shape\merge@font@shape
```

```
134          \let\delayed@merge@font@series\merge@font@series
```

```
135          \delayed@f@adjustment
```

```
136          \let\delayed@merge@font@shape\merge@font@shape@without@substitution
```

```
137          \let\delayed@merge@font@series\merge@font@series@without@substitution
```

```
138      \fi
```

Now the series and shape values are updated and we clear `\delayed@f@adjustment`. This is important because on the next execution of `\selectfont` we should not mistakenly redo the delayed actions if there wasn't any series or shape change.

```
139      \let\delayed@f@adjustment\@empty
```

```
140      \fi
```

If the series was forced we should now cancel that in case the next series change is done with some low-level setting to `\f@series`.

```
141      \@forced@seriesfalse
```

Then we generate the internal name of the font by concatenating *family*, *series*, *shape*, and current *size*, with slashes as delimiters between them. This is much more readable than standard L<sup>A</sup>T<sub>E</sub>X's `\twbf`, etc. We define `\font@name` globally, as always. The reason for this is explained later on.

```
142      \xdef\font@name{%
```

```
143          \csname\curr@fontshape/\f@size\endcsname}%
```

We call the macro `\pickup@font` which will load the font if necessary.

```
144      \pickup@font
```

Then we select the font.

```
145      \font@name
```

After switching fonts we run a hook, so that packages can make last minute alterations based on the new font (originally provided in `every` but using a different interface).

```
146      \UseHook{selectfont}%
```

Finally we call `\size@update`. This macro is normally empty but will contain actions (like setting the `\baselineskip`) that have to be carried out when the font size, the base `\baselineskip` or the `\baselinestretch` have changed.

```
147      \size@update
```

A similar function is called to handle anything related to encoding updates. This one is changed from `\relax` by `\fontencoding`.

```
148 \enc@update
```

Just before ending this macro we have to pop the tracing stack if it was pushed before.

```
149 <+debug> \poptracing
150 }
```

(End of definition for `\selectfont`.)

**selectfont** Declare the hook used in `selectfont` in the kernel, but not inside the `tracefnt` package.

```
151 <-trace> \NewHook{selectfont}
```

(End of definition for `selectfont`.)

If `\tracingfonts` is greater than 2 we also show the font switch inside `\selectfont`. We do this by adding this code to the hook in the `tracefnt` package: macro might redefine `\font@name`.

```
152 <*trace>
153 \AddToHook{selectfont}
154   {\ifnum \tracingfonts>\tw@
155     \font@info{Switching to \font@name}\fi}
156 </trace>
157 </2ekernel | latexrelease | package>
158 <latexrelease> \EndIncludeInRelease
```

With `\selectfont` having different definitions in different kernels we also have to provide them in the `tracefnt` package to support rollback. In packages that works a bit differently and therefore we have to provide an empty block there.

```
159 <package> \IncludeInRelease{2021/06/01}%
160 <package> \selectfont{\Add hook to \selectfont}%
161 <package> \EndIncludeInRelease

162 <latexrelease | package> \IncludeInRelease{0000/00/00}%
163 <latexrelease | package> \selectfont{\Add hook to \selectfont}%
164 <latexrelease | package>
165 <latexrelease | package> \DeclareRobustCommand\selectfont
166 <latexrelease | package>   {%
167 <latexrelease | package>     \ifx\f@linespread\baselinestretch \else
168 <latexrelease | package>       \set@fontsize\baselinestretch\f@size\f@baselineskip \fi
169 <latexrelease | package>     \xdef\font@name{%
170 <latexrelease | package>       \csname\curr@fontshape/\f@size\endcsname}%
171 <latexrelease | package>     \pickup@font
172 <latexrelease | package>     \font@name
173 <latexrelease | package>     \size@update
174 <latexrelease | package>     \enc@update
175 <latexrelease | package>   }
176 <latexrelease | package>
177 <latexrelease | package> \EndIncludeInRelease
```

**\set@fontsize** The macro `\set@fontsize` does the actual work. First it assigns new values to `\f@size`, `\f@baselineskip` and `\f@linespread`.

```
178 <*2ekernel | package>
179 \def\set@fontsize#1#2#3{%
180   \@defaultunits\@tempdimb#2pt\relax\@nnil
```

```

181 \edef\f@size{\strip@pt\@tempdimb}%
182 \@defaultunits\@tempskipa#3pt\relax\@nnil
183 \edef\f@baselineskip{\the\@tempskipa}%
184 \edef\f@linespread{#1}%

```

For backward compatibility and for later testing within `\selectfont` the internal value of `\f@linespread` is passed back to `\baselinestretch`.

```

185 \let\baselinestretch\f@linespread

```

Additional processing will happen within `\selectfont`. For this reason the macro `\size@update` (which will be called in `\selectfont`) will be defined to be:

```

186 \def\size@update{%

```

First calculate the new `\baselineskip` and also store it in `normalbaselineskip`

```

187 \baselineskip\f@baselineskip\relax
188 \baselineskip\f@linespread\baselineskip
189 \normalbaselineskip\baselineskip

```

then to set up a new `\strutbox`

```

190 \setbox\strutbox\hbox{%
191 \vrule\@height.7\baselineskip
192 \@depth.3\baselineskip
193 \@width\z@}%

```

We end with a bit of tracing information.

```

194 \<trace>
195 \ifnum \tracingfonts>\tw@
196 \ifx\f@linespread\@empty
197 \let\reserved@a\@empty
198 \else
199 \def\reserved@a{\f@linespread x}%
200 \fi
201 \@font@info{Changing size to \f@size/\reserved@a
202 \f@baselineskip}%
203 \aftergroup\type@restoreinfo \fi
204 \</trace>

```

When all this is processed `\size@update` redefines itself to `\relax` so that in later calls of `\selectfont` no extra code will be executed.

```

205 \let\size@update\relax}%
206 }

```

Instead of defining this macro internally we might speed things up by placing the code into a separate macro and use `\let`!

*(End of definition for \set@fontsize.)*

`\size@update` Normally this macro does nothing; it will be redefined by `\set@fontsize` to initiate an update.

```

207 \let\size@update\relax

```

*(End of definition for \size@update.)*

`\type@restoreinfo` This macro produces some info when a font size and/or baseline change will get restored.

```

208 <*trace>
209   \def\type@restoreinfo{%
210     \ifx\f@linespread\@empty
211       \let\reserved@a\@empty
212     \else
213       \def\reserved@a{\f@linespread x}%
214     \fi
215     \@font@info{Restoring size to
216               \f@size/\reserved@a\f@baselineskip}}
217 </trace>

```

(End of definition for `\type@restoreinfo`.)

`\glb@settings` The macro `\glb@settings` globally selects all math fonts for the current size if necessary.  
`\glb@currsz`

```

218 \def\glb@settings{%

```

When `\glb@settings` gains control a size change was requested and all previous font assignments need to be replaced. Therefore the old values of the fonts are no longer needed. For every *math group* the new assignments are appended to `\math@fonts`. But this happens only if the `\math@fonts` switch is set to true. However, we always set up the correct math sizes for script and scriptscript fonts since they may be needed even if we don't set up the whole math machinery.

Here we set the math size, script size and scriptscript size. If the `S@...` macro is not defined we have to first calculate the three sizes.

```

219   \expandafter\ifx\csname S@\f@size\endcsname\relax
220     \calculate@math@sizes
221   \fi

```

The effect of this is that `\calculate@math@sizes` may or may not define the `S@...` macro. In the first case the next time the same size is requested this macro is used, otherwise `\calculate@math@sizes` is called again. This also sets the `\math@fonts` switch. If it is true we must switch the math fonts.

```

222   \csname S@\f@size\endcsname
223   \ifmath@fonts
224 <*trace>
225     \ifnum \tracingfonts>\tw@
226       \@font@info{Setting up math fonts for
227                 \f@size/\f@baselineskip}\fi
228 </trace>

```

Inside a group we execute the macro for the current math *version*. This sets `\math@fonts` to a list of `\textfont...` assignments. `\getanddefine@fonts` (which may be called at this point) needs the `\escapechar` parameter to be set to `-1`.

```

229   \begingroup
230     \escapechar\m@ne
231     \csname mv@\math@version \endcsname

```

Then we set `\globaldefs` to 1 so that all following changes are done globally. The math font assignments recorded in `\math@fonts` are executed and `\glb@currsz` is set equal to `\f@size`. This signals that the fonts for math in this size are set up.

```

232     \globaldefs\@ne
233     \math@fonts

```



2. Whenever we start a formula we compare its value with the local variable `\f@size` that describes the current text font size.
3. If both are the same we assume that we can use the current math font setup without adjustment.
4. If they differ we call `\glb@settings` which changes the math font setup and updates `\glb@currsz`.
  - (a) If we are recursively inside another formula (`\if@inmath`) we ensure that `\glb@settings` is executed again in the outer formula, so that the old setup is automatically restored.
  - (b) Otherwise, we set the switch `@inmath` locally to `true` so that all nested formulae will be able to detect that they are nested in some outer formula.

The above algorithm has the following features:

- For sizes which are not containing any formula no math setup is done. Compared to the original algorithm of NFSS this results in the following savings:
  - No unnecessary loading of math fonts for sizes that are not used to typeset any math formulae (explicit or implicit ones).
  - No time overhead due to unnecessary changes of the math font setup on entrance and exit of the text font size.
- Math font setup changes for top-level formulae will survive (there is no restoration after the formula) thus any following formula in the same size will be directly typesettable. Compared to original implementation in NFSS2 the new algorithm has the overhead of one test per formula to see if the current math setup is valid (in the original algorithm the setup was always valid, thus no test was necessary).
- In nested formulae the math font setup is restored in the outer formula by a series of `\aftergroup` commands and checks. Compared to the original algorithm this involves additional checks ( $2 \times$  (non-math levels) per inner formula).

### 5.2.2 Code for math font size setting

`\check@mathfonts` In the `\check@mathfonts` macros we implement the steps 2 to 4 except that instead of a switch the macro `\init@restore@glb@settings` is used.

```

251 <*2kernel | package>
252 \def\check@mathfonts{%
253   \ifx \glb@currsz \f@size
254   <*trace>
255     \ifnum \tracingfonts>\thr@@
256       \@font@info{*** MATH: no change \f@size\space
257         curr/global (\curr@math@size/\glb@currsz)}\fi
258   </trace>
259   \else
260   <*trace>
261     \ifnum \tracingfonts>\thr@@
262       \@font@info{*** MATH: setting up \f@size\space
263         curr/global (\curr@math@size/\glb@currsz)}\fi
264   </trace>

```

```

265     \glb@settings
266     \init@restore@glb@settings
267   \fi
268   \let\curr@math@size\font@size
269   \def\init@restore@glb@settings{\aftergroup\restglb@settings}%
270 }

```

(End of definition for \check@mathfonts.)

**\init@restore@glb@settings** This macro does by default nothing but get redefined inside \check@mathfonts to initiate fontsize restoring in nested formulas.

```

271 <-trace>\let\init@restore@glb@settings\relax
272 <*trace>
273 \def\init@restore@glb@settings{%
274     \ifnum \tracingfonts>\thr@@
275     \font@info{*** MATH: no resetting (not in
276         nested math)}\fi
277 }
278 </trace>

```

(End of definition for \init@restore@glb@settings.)

**\restglb@settings** This macro will be executed the first time after the current formula.

```

279 \def\restglb@settings{%
280 <*trace>
281     \ifnum \tracingfonts>\thr@@
282     \font@info{*** MATH: restoring}\fi
283 </trace>
284     \begingroup
285     \let\font@size\curr@math@size
286     \ifx\glb@currsz \font@size
287 <*trace>
288     \ifnum \tracingfonts>\thr@@
289     \font@info{*** MATH: ... already okay (\font@size)}\fi
290 </trace>
291     \else
292 <*trace>
293     \ifnum \tracingfonts>\thr@@
294     \font@info{*** MATH: ... to \font@size}\fi
295 </trace>
296     \glb@settings
297   \fi
298 \endgroup
299 }

```

(End of definition for \restglb@settings.)

### 5.2.3 Other code for math

**\use@mathgroup** The \use@mathgroup macro should be used in user macros to select a math group. Depending on whether or not the margid option is in force it has two or three arguments. For this reason it should be called as the last macro.

First we test if we are inside math mode since we don't want to apply a useless definition.

```

300 \def\use@mathgroup#1#2{\relax\ifmmode

```

```

301 <*trace>
302   \ifnum \tracingfonts>\tw@
303     \count@#2\relax
304     \@font@info{Using \noexpand\mathgroup
305               (\the\count@) #2}\fi
306 </trace>

```

If so we first call the ‘=’ macro (i.e. argument three) to set up special things for the selected math group. Then we call `\mathgroup` to select the group given by argument two and finally we place `#1` (i.e., the argument of the `<math alphabet identifier>`) at the end. This part of the code is surrounded by two commands which behave like `\begingroup` and `\endgroup` if we want `<math alphabet identifier>`s but will expand into `\@empty` if we want simply switches to a new math group. Since argument number 2 may be a digit instead of a control sequence we add a `\relax`. Otherwise something like `\mit{1}` would switch to math group 11 (and back) instead of printing an oldstyle 1.

```

307   \math@bgroup
308     \expandafter\ifx\csname M@\f@encoding\endcsname#1\else
309     #1\fi
310     \mathgroup#2\relax

```

Before we reinsert the swallowed token (arg. three) into the input stream, in the case that the `<math alphabet identifier>` isn’t called in math mode, we remove the `\fi` with the `\expandafter` trick. This is necessary if the token is actually an macro with arguments. In such a case the `\fi` will be misinterpreted as the first argument which would be disastrous.

```

311   \expandafter\math@egroup\fi}%

```

The surrounding macros equal `\begingroup` and `\endgroup`. But using internal names makes it possible to overwrite their meaning in certain cases. This is for example used in  $\mathcal{MS}$ -TeX macros for placing accents.

(End of definition for `\use@mathgroup`.)

`\math@egroup` If the `margid` option is in force (which can be tested by looking at the definition of `\math@bgroup`) we change the `\math@egroup` command a bit to display the current `<math group number>` after it closes the scope of `<math alphabet>` with `\endgroup`.

```

312 <*trace>
313   \ifx\math@bgroup\bgroup
314     \def\math@egroup#1{#1\egroup
315       \ifnum \tracingfonts>\tw@
316         \@font@info{Restoring \noexpand\mathgroup
317               (\ifnum\mathgroup=\m@ne default\else \the\mathgroup \fi)%
318       }\fi}
319   \fi
320 </trace>

```

(End of definition for `\math@egroup`.)

`\getanddefine@fonts` `\getanddefine@fonts` has two arguments: the `<math group number>` and the *family/series/shape* name as a control sequence.

```

321 \def\getanddefine@fonts#1#2{%

```

First we turn of tracing when `\tracingfonts` is less than 4.

```

322 <+debug> \pushtracing
323 <+debug> \ifnum\tracingfonts<4 \tracingoff
324 <+debug> \else \tracingon\getanddefine@fonts \fi

325 <*trace>
326 \ifnum \tracingfonts>\tw@
327 \count@#1\relax
328 \font@info{\noexpand\mathgroup (\the\count@) #1 :=\MessageBreak
329 \string#2 \tf@size/\sf@size/\ssf@size}\fi
330 /trace>

```

We append the current `\tf@size` to `#2` to obtain the font name.<sup>36</sup> Again, `font@name` is defined globally, for the reasons explained in the description of `\wrong@fontshape`.

```

331 \xdef\font@name{\csname \string#2/\tf@size\endcsname}%

```

Then we call `\pickup@font` to load it if necessary. We remember the internal name as `\textfont@name`.

```

332 \pickup@font \let\textfont@name\font@name

```

Same game for `\scriptfont` and `\scriptscriptfont`, but here we additionally transform the fontname through `\transform@scriptfont` to allow different family names in math scripts.

```

333 \xdef\font@name{\csname \transform@scriptfont {sf}{#2}/\sf@size\endcsname}%
334 \pickup@font \let\scriptfont@name\font@name
335 \xdef\font@name{\csname \transform@scriptfont {ssf}{#2}/\ssf@size\endcsname}%
336 \pickup@font

```

Then we append the new `\textfont...` assignments to the `\math@fonts`.

```

337 \edef\math@fonts{\math@fonts
338 \textfont#1\textfont@name
339 \scriptfont#1\scriptfont@name
340 \scriptscriptfont#1\font@name}%

```

Just before ending this macro we have to pop the tracing stack if it was pushed before.

```

341 <+debug> \poptracing
342 }

```

(End of definition for `\getanddefine@fonts`.)

`\transform@scriptfont` `\transform@scriptfont` has two arguments: the name of the script size we transform the font for (always `sf` or `ssf`) and the *family/series/shape* name as a `csname`. It expands to a new *family/series/shape* name which will be used for this script. For this `\transform@scriptfont` mostly delegates to `\__nfss_transform_scriptfont:nw`, which searches for a replacement marker `\__nfss_mapped_scriptfont_family_⟨scriptsize⟩_⟨encoding⟩` with a remapped encoding and family.

```

343 \ExplSyntaxOn
344 \cs_set:Npn \transform@scriptfont #1 #2 {
345 \exp_last_unbraced:Nno
346 \__nfss_transform_scriptfont:nw
347 {#1}
348 {\token_to_str:N #2}
349 }

```

<sup>36</sup>One might ask why this expansion does not generate a macro name that starts with an additional `\` character. The solution is that `\escapechar` is set to `-1` before `\getanddefine@fonts` is called.

```

350 \cs_set:Npn \__nfss_transform_scriptfont:nw #1 #2 / #3 / {
351   \cs_if_exist_use:cF { __nfss_mapped_scriptfont_family_ #1 _ #2 / #3 } { #2 / #3 }
352   /
353 }

```

(End of definition for `\transform@scriptfont`.)

`\DeclareMathScriptfontMapping` `\DeclareMathScriptfontMapping` can be used to define replacement font families which will be used for math subscripts or subsubscripts when a specific font family is used as the main math font. For this `\DeclareMathScriptfontMapping` takes three pairs of encoding and family names as arguments: The first pair identifies the base font for which associated script and scriptscript variants should be declared. The second pair describes the family which should be used as scriptfonts (e.g. in subscripts). Finally the third pair describes the family which should be used as scriptscriptfonts (e.g. in nested subscripts).

```

354 \cs_set:Npn \DeclareMathScriptfontMapping #1 #2 #3 #4 #5 #6 {
355   \cs_set:cpn { __nfss_mapped_scriptfont_family_sf_ #1 / #2 } { #3 / #4 }
356   \cs_set:cpn { __nfss_mapped_scriptfont_family_ssf_ #1 / #2 } { #5 / #6 }
357 }
358 \ExplSyntaxOff
359 </2ekernel|package>

```

(End of definition for `\DeclareMathScriptfontMapping`.)

## 6 Scaled font extraction

`\ifnot@nil` We begin with a simple auxiliary macro. It checks whether its argument is the token `\@nil`. If so, it expands to `\@gobble` which discards the following argument, otherwise it expands to `\@firstofone` which reproduces its argument.

```

360 <*2ekernel>
361 \def\ifnot@nil#1{\def\reserved@a{#1}%
362   \ifx\reserved@a\@nnil \expandafter\@gobble
363   \else \expandafter\@firstofone\fi}

```

(End of definition for `\ifnot@nil`.)

`\remove@to@nnil` Three other auxiliary macros will be needed in the following: `\remove@to@nnil` gobbles up everything up to, and including, the next `\@nnil` token, and `\remove@angles` and `\remove@star` do the same for the character `>` and `*`, respectively, instead of `\@nnil`.

```

364 \def\remove@to@nnil#1\@nnil{}
365 \def\remove@angles#1>{\set@simple@size@args}
366 \def\remove@star#1*{#1}

```

(End of definition for `\remove@to@nnil`, `\remove@angles`, and `\remove@star`.)

`\extract@sizefn` This macro takes a size specification and parses it into size function and the optional and mandatory arguments.

```

367 \def\extract@sizefn#1*#2\@nil{%
368   \if>#2>\set@size@funct@args#1\@nil
369     \let\sizefn@info\@empty
370   \else\expandafter\set@size@funct@args\remove@star#2\@nil
371     \def\sizefn@info{#1}\fi
372 }

```

(End of definition for `\extract@sizefn`.)

`\try@simple@size` This function tries to extract the given size (specified by `\f@size`) for the requested font shape. The font information must already be present in `\font@info`. The central macro that does the real work is `\extract@fontinfo`. We will first give a simple example how this macro works, and describe it in full generality later.

Assume that the requested parameters are: *encoding scheme* ‘OT1’, *family* ‘cm’, *series* ‘sansserif’, *shape* ‘normal’, and *size* ‘12’. The corresponding font definitions have already been extracted from the macro `\OT1/cm/sansserif/normal` and stored in `font@info`. (Otherwise `\extract@fontinfo` doesn’t get called.) This information consists of a token list made of characters of category code 12 of the form

```
<10*>cmss10<12*>cmss12<17*>cmss17
```

For reasonable packages one usually needs more sizes but this is sufficient to get the flavour. We will define a macro `\extract@fontinfo` to find the external font name (‘cmss12’) for us:

```
\def\extract@fontinfo#1<12*#2>#3<#4\@nnil{%
  \set@simple@size@args#3<#4\@nnil
  \execute@size@function{#2}}}
```

so that when it gets called via

```
\extract@fontinfo<10*>cmss10<12*>cmss12<17*>cmss17\@nnil
```

#1 will contain all characters before `<12*>`, #2 will be empty, #3 will be exactly `cmss12`, and #4 will be `17>cmss17`. The expansion is therefore

```
\set@simple@size@args cmss12<17*>cmss17\@nnil
\execute@size@function{}
```

This means: the default (empty) size function will be executed, with its optional argument set to empty and its mandatory argument set to `cmss12` by `\set@simple@size@args`. As we discussed earlier, the effect of the default size function is to load the given external font (`cmss12`) at the specified size (12)—which is exactly what was intended.

But this is only part of the whole story. It may be that the size requested does not occur in the token list `\font@info`. And the simple definition of `\extract@fontinfo` we gave above does not allow to specify give more than one size specification in front of the external font name.

Let’s address these two problems separately. The first one is solved with the following trick: We define `\extract@fontinfo` as follows:

```
\def\extract@fontinfo#1<12*#2>#3<#4\@nnil{%
  \ifnot@nil{#3}%
  {\set@simple@size@args#3<#4\@nnil
   \execute@size@function{#2}}%
  }%}
```

How does this work? We call `\extract@fontinfo` via

```
\expandafter\extract@fontinfo\font@info<12*>\@nil\@nnil
```

i.e. by appending `<12*>\@nil<\@nnil`. If the size ('12' in this case) appears in `\font@info` everything works as explained above, the only difference being that argument #4 of `\extract@fontinfo` additionally gets the tokens `<12*>\@nil<\@nnil`. However, if the size is not found everything up to the final `<12*>` is in argument #1, #3 gets `\@nil`, and #2 and #4 are empty. The macro `\ifnot@nil` will discard the calls to `\set@simple@size@args` and `execute@size@function`, and hence `\font@info` will continue to be equal to `\@empty`. This means that no simple size specification matching the requested size could be found.

The second problem (more than one simple size specification for one external font name) will be addressed in `\set@simple@size@args` below.

The macros are hidden inside other control sequences so that we have to build `\extract@fontinfo` in several steps.

So here's the actual definition of `\extract@font` in `\try@simple@size`.

```
373 % % this could be replaced by \try@size@range making the subst slower!
374 \def\try@simple@size{%
```

`\reserved@a` is made an abbreviation for the head of the definition of the macro `\extract@fontinfo`.

```
375 \def\reserved@a{\def\extract@fontinfo####1}%
```

Now we can define `\extract@fontinfo`. Here we handle a small but convenient variation: in case of the default (empty) size function it is allowed to omit the `*` character.

```
376 \expandafter\reserved@a\expandafter<\f@size>##2<##3\@nnil{%
377 \ifnot@nil{##2}%
378 {\set@simple@size@args##2<##3\@nnil
379 \execute@size@function\sizefn@info
380 }%}
```

Now we call `\extract@fontinfo`. Note the `<\@nil` tokens at the end.

```
381 \expandafter\expandafter
382 \expandafter\extract@fontinfo\expandafter\font@info
383 \expandafter<\f@size>\@nil<\@nnil
384 }
```

*(End of definition for \try@simple@size.)*

`\set@simple@size@args` As promised above, the macro `\set@simple@size@args` will handle the case of several size specifications in a row. If another size specification follows, the very first token of its argument list is the character `<`. By starting the definition as follows,

```
385 \def\set@simple@size@args#1<{%
```

parameter #1 is empty in this case, and contains the size function's arguments otherwise. We distinguish these two cases (Note that the character `<` cannot appear in #1) by calling `\remove@angles` for empty #1 and `\extract@sizefn` otherwise. In the latter case we have to take care of the remaining character tokens and discard them. This is done by `\remove@to@nnil`. Note also the use of Kabelschacht's method.

```
386 \if<#1<%
387 \expandafter\remove@angles
388 \else
389 \extract@sizefn#1*\@nil
390 \expandafter\remove@to@nnil
391 \fi}
```

(End of definition for `\set@simple@size@args`.)

Now, we are through with the case of a simple size, except for calling the size function. This will be handled later, as it is the same mechanism for all types of size specification. We will now proceed to macros for extraction of size range specification.

`\extract@rangefontinfo` `\extract@rangefontinfo` goes through a font shape definition in the input until it recognizes the tokens `<\@nil->`. It looks for font ranges with font size functions. It's operation is rather simple: it discards everything up to the next size specification and passes this on to `\is@range` for inspection. The specification (parameter #2) is inserted again, in case it is needed later.

```
392 \def\extract@rangefontinfo#1<#2>{%
393     \is@range#2->\@nil#2>}
```

(End of definition for `\extract@rangefontinfo`.)

`\is@range` `\is@range` is again a sort of dispatcher macro: if the size specification it is looking at is not a range specification it discards it and calls `\extract@rangefontinfo` to continue the search. Otherwise it calls `\check@range` to check the requested size against the specified range.

From the way `\is@range` is called inside `\extract@rangefontinfo` we see that #2 is the character `>` if the size specification found is a simple one (that does not contain a `-` character). This is checked easily enough and `\extract@rangefontinfo` called again. Note that the extra tokens inserted after the `\@nil` in the call to `\is@range` appear at the beginning of the first argument to `\extract@rangefontinfo` and are hence ignored.

```
394 \def\is@range#1-#2\@nil{%
395     \if>#2\expandafter\check@single\else
396     \expandafter\check@range\fi}
```

(End of definition for `\is@range`.)

`\check@range` `\check@range` takes lower bound as parameter #1, upper bound as #2, size function as #3 and the size function's arguments as #4. If #3 is the special token `\@nil \font@info` is exhausted and we can stop searching.

```
397 \def\check@range#1-#2>#3<#4\@nnil{%
398     \ifnot@nil{#3}{%
```

If #3 wasn't `\@nil` we have a range. We start by assuming that we have to recurse. Note that we have to reinsert an `<` as it was already removed by scanning.

```
399     \def\reserved@f{\extract@rangefontinfo<#4\@nnil}%
```

We have to make sure that both boundaries are present, if not we have to set them. Here we check the upper bound. If `\upper@bound` is zero after the assignment we set it to `\maxdimen` (upper open range). We need to use a `<dimen>` register for the scan since we may have a decimal number as the boundary.

```
400     \upper@bound0#2\p@
401     \ifdim\upper@bound=\z@ \upper@bound\maxdimen\fi
```

Now we check the upper boundary against `\f@size`. If it is larger or equal than `\f@size` this range is no good and we have to recurse.

```
402     \ifdim \f@size \p@<\upper@bound
```

Otherwise we have to check the lower bound. This time it is not necessary to scan the boundary value into a register because if it is empty we get zero as desired. We could even omit the 0 which would result in 1pt as default lower boundary. If \f@size is smaller than the boundary we have to recurse.

```
403      \lower@bound0#1\p@
404      \ifdim \f@size \p@<\lower@bound
405      \else
```

If both tests are passed we can try executing the size function.

```
406      \set@simple@size@args#3<#4\@nnil
407      \execute@size@function\sizefn@info
```

If the function was successful it should have left an external font name in \external@font. We use this to see if we can stop scanning. Otherwise we recurse.

```
408      \ifx\external@font\@empty
409      \else
410      \let\reserved@f\@empty
411      \fi
412      \fi
413      \fi
414      \reserved@f}}
```

*(End of definition for \check@range.)*

**\lower@bound** We use two dimen registers \lower@bound and \upper@bound to store the lower and upper endpoints of the range we found.

```
415 \newdimen\lower@bound
416 \newdimen\upper@bound
```

*(End of definition for \lower@bound and \upper@bound.)*

**\check@single** \check@single takes the size as parameter #1, size function as #2 and the size function's arguments as #3. We can assume that there is always something in the pipeline since the very last entry is a faked range (see above).

```
417 \def\check@single#1>#2<#3\@nnil{%
```

We start by assuming that we have to recurse. Note that we have to reinsert an < as it was already removed by scanning.

```
418      \def\reserved@f{\extract@rangefontinfo<#3\@nnil}%
```

Now we check the size against \f@size. If it is not equal \f@size it is no good and we have to recurse.

```
419      \ifdim \f@size \p@=#1\p@
```

Otherwise if this test is passed we can try executing the size function.

```
420      \set@simple@size@args#2<#3\@nnil
421      \execute@size@function\sizefn@info
```

If the function was successful it should have left an external font name in \external@font. We use this to see if we can stop scanning. Otherwise we recurse.

```
422      \ifx\external@font\@empty
423      \else
424      \let\reserved@f\@empty
425      \fi
426      \fi
427      \reserved@f}
```

(End of definition for `\check@single`.)

`\set@size@funct@args` This macro sets the optional and mandatory arguments for a size function. If the optional argument is not present it is set to the empty token list. The mandatory argument is delimited by the token `\@nil`.

```

428 \def\set@size@funct@args{\@ifnextchar[%
429   \set@size@funct@args@\set@size@funct@args@[]}}
430 \def\set@size@funct@args@[#1]#2\@nil{%
431   \def\mandatory@arg{#2}%
432   \def\optional@arg{#1}}
433 \endkernel

```

(End of definition for `\set@size@funct@args` and `\set@size@funct@args@`.)

`\DeclareSizeFunction` This function defines a new size function hiding the internal from the designer. The body of the size function may use `\optional@arg` and `\mandatory@arg` denoting the optional and mandatory argument that may follow the size specification `<...>`.

```

434 \endkernel
435 \def\DeclareSizeFunction#1#2{\@namedef{s@fct@#1}{#2}}
436 \@onlypreamble\DeclareSizeFunction
437 \endkernel

```

(End of definition for `\DeclareSizeFunction`.)

`\execute@size@function` This macro is very simple. The only point worth noting is that calling an undefined size function will do nothing (actually execute a `\relax`).

```

438 \endkernel | package
439 \def\execute@size@function#1{%
440 \trace
441   \ifundefined{s@fct@#1}%
442     {\errmessage{Undefined font size function #1}%
443      \s@fct@}%
444     {\csname s@fct@#1\endcsname}%
445 \traced
446 \trace   \csname s@fct@#1\endcsname
447 }
448 \endkernel | package

```

(End of definition for `\execute@size@function`.)

`\try@size@range` This macro tries to find a suitable range for requested size (specified by `\f@size`) in `\font@info`. All the relevant action is done in `\extract@rangefontinfo`. All that needs to be done is to stuff in the token list in `\font@info` so that `\extract@rangefontinfo` can inspect it. Note the `<-*\@nil>` token at the end to stop scanning.

```

449 \endkernel
450 \def\try@size@range{%
451   \expandafter\extract@rangefontinfo\font@info <-*\@nil>\@nnil
452 }

```

(End of definition for `\try@size@range`.)

`\try@size@substitution` This is the last thing that can be tried. If the desired `\f@size` is found neither among the simple size specifications nor in one of the ranges the whole list of size specifications is searched for a nearby simple size.

```

453 \gdef\try@size@substitution{%

```

First we do some initializations. `\@tempdimb` will hold the difference between the wanted size and the best solution found so far, so we initialise it with `\maxdimen`. The macro `\best@size` will hold the best size found, nothing found is indicated by the empty value.

```
454 \tempdimb \maxdimen
455 \let \best@size \@empty
```

Now we loop over the specification

```
456 \expandafter \try@simples \font@info <\number\@M>\@nil<\@nnil
457 }
```

*(End of definition for \try@size@substitution.)*

`\font@submax` The macro `\font@submax` records the maximal deviation from the desired size encountered so far. Its value is used in a warning message at `\end{document}`. The macro `\fontsubfuzz` contains the amount that will not cause terminal warnings (warnings still go into the transcript file).

```
458 \def\font@submax{0pt}
459 \def\fontsubfuzz{.4pt}
460 </2ekernel>
461 <+package>\def\fontsubfuzz{0pt}
```

*(End of definition for \font@submax and \fontsubfuzz.)*

`\try@simples` `\try@simples` goes through a font shape definition in the input until it recognizes the tokens `<*\@nil>`. It looks for simple sizes to determine the two closest sizes. It is assumed that simple sizes are in increasing order.

```
462 <*2ekernel>
463 \gdef\try@simples#1<#2>{%
464 \tryif@simple#2->\tryif@simple}
```

*(End of definition for \try@simples.)*

`\tryis@simple` `\tryis@simple` is similar to `\is@range`. If it sees a simple size, it checks it against the value of `\f@size` and sets `\lower@font@size` or `\higher@font@size`. In the latter case, it stops the iteration. By adding `<\number\@M>` at the end of the line we always have an end point. This is a hack which probably should be corrected.

First it checks whether it is finished already, then whether the size specification in question is a simple one.

```
465 \gdef\tryif@simple#1-#2\tryif@simple{%
```

Most common case for `\reserved@f` first:

```
466 \let \reserved@f \try@simples
467 \if>#2%
```

If so, it compares it to the value of `\f@size`. This is done using a dimen register since there may be fractional numbers.

```
468 \dimen@ #1\p@
469 \ifdim \dimen@<\@M\p@
```

If `\dimen@` is `\M\p@` we have reached the end of the fontspec (hopefully) otherwise we compare the value with `\f@size` and compute in `\@tempdimc` the absolute value of the difference between the two values.

```

470     \ifdim \f@size\p@<\dimen@
471         \@tempdimc \dimen@
472         \advance\@tempdimc -\f@size\p@
473     \else
474         \@tempdimc \f@size\p@
475         \advance\@tempdimc -\dimen@
476     \fi

```

The result is then compared with the smallest difference we have encountered, if the new value (in `\@tempdimc` is smaller) we have found a size which is a better approximation so we make it the `\best@size` and adjust `\@tempdimb`.

```

477     \ifdim \@tempdimc<\@tempdimb
478         \@tempdimb \@tempdimc
479         \def \best@size{#1}%
480     \fi

```

When we have reached the end of the fontspec we substitute the best size found (if any). We code this inline to save macro space; in the past this was done by a macro called `\subst@size`.

```

481     \else

```

This macro substitutes the size recorded in `\best@size` for the unavailable size `\f@size`. `\subst@size` `\font@submax` records the maximum difference between desired size and selected size in the whole run.

```

482 % \subst@size          %% coded inline
483 % \def\subst@size{%
484     \ifx \external@font\@empty
485         \ifx \best@size\@empty
486         \else
487             \ifdim \@tempdimb>\font@submax \relax
488             \xdef \font@submax {\the\@tempdimb}%
489         \fi
490         \let \f@user@size \f@size
491         \let \f@size \best@size
492         \ifdim \@tempdimb>\fontsubfuzz\relax
493             \@font@warning{Font\space shape\space
494                 '\curr@fontshape'\space in\space size\space
495                 <\f@user@size>\space not\space available\MessageBreak
496                 size\space <\f@size>\space substituted}%
497         \fi
498         \try@simple@size
499         \do@subst@correction
500     \fi
501 \fi
502 % %}

```

This brings us back into the main part of `\tryif@simple`. Finally we get rid of any rubbish left over on the input stack.

```

503     \let \reserved@f \remove@to@nnil
504     \fi
505 \fi

```

If it's a range iterate also.

```
506 \reserved@f}
```

(End of definition for `\tryis@simple` and `\subst@size`.)

## 6.1 Sizefunctions

In the following we define some useful size functions.

`\s@fct@` This is the default size function. Mandatory argument is an external font name, optional argument a scale factor. The font is scaled to `\f@size` if no optional argument is present, and to `\f@size` multiplied by the optional argument otherwise.

```
507 \DeclareSizeFunction{}\empty@sfcnt\@font@warning}
508 \DeclareSizeFunction{s}\empty@sfcnt\@font@info}

509 \def\empty@sfcnt#1{%
510     \@tempdimb \f@size\p@
511     \ifx\optional@arg\empty
512     \else
513         \@tempdimb \optional@arg\@tempdimb
514         #1{Font\space shape\space '\curr@fontshape'\space
515             will\space be\MessageBreak
516             scaled\space to\space size\space \the\@tempdimb}%
517     \fi
518     \edef\external@font{\mandatory@arg\space at\the\@tempdimb}}
```

(End of definition for `\s@fct@`.)

`\s@fct@gen` This size function generates the external name from the mandatory argument and the requested user size, and thus can be used for external names where the size is encoded in the font name. The optional argument a scale factor. The font is scaled to `\f@size` if no optional argument is present, and to `\f@size` multiplied by the optional argument otherwise.

```
519 \DeclareSizeFunction{gen}\gen@sfcnt\@font@warning}
520 \DeclareSizeFunction{sgen}\gen@sfcnt\@font@info}

521 \def\gen@sfcnt{%
522     \edef\mandatory@arg{\mandatory@arg\f@size}%
523     \empty@sfcnt}
```

(End of definition for `\s@fct@gen` and `\s@fct@sgen`.)

`\s@fct@genb` This size function is similar to `gen`, but for fonts where the size is encoded in the font name in centipoints, as in the DC fonts version 1.2. The font is scaled to `\f@size` if no optional argument is present, and to `\f@size` multiplied by the optional argument otherwise.

```
524 \DeclareSizeFunction{genb}\genb@sfcnt\@font@warning}
525 \DeclareSizeFunction{sgenb}\genb@sfcnt\@font@info}

526 \def\genb@sfcnt{%
527     \edef\mandatory@arg{\mandatory@arg\expandafter\genb@x\f@size..\@@}%
528     \empty@sfcnt}
```

(End of definition for `\s@fct@genb` and `\s@fct@sgenb`.)

`\genb@x` The auxiliary macros `\genb@x` and `\genb@y` are used to convert the `\f@size` into centi-points.

```
529 \def\genb@x#1.#2.#3\@@{\two@digits{#1}\genb@y#200\@@}
530 \def\genb@y#1#2#3\@@{#1#2}
```

*(End of definition for `\genb@x` and `\genb@y`.)*

`\s@fct@sub` This size function handles font substitution. The mandatory argument is a family/series/shape combination, the optional argument (if present) is ignored. The font encoding scheme cannot be changed. Therefore, the first thing we do is to prepend the encoding scheme.

```
531 \DeclareSizeFunction{sub}{\sub@sfcnt\@font@warning}
532 \DeclareSizeFunction{ssub}{\sub@sfcnt\@font@info}

533 \def\sub@sfcnt#1{%
534     \edef\mandatory@arg{\f@encoding/\mandatory@arg}%
```

Next action is split the arg into its individual components and allow for a late font shape load.

```
535     \begingroup
536     \expandafter\split@name\mandatory@arg/\@nil
537     \try@load@fontshape
538     \endgroup
```

Then we record the current `\f@size` since it may get clobbered.

```
539     \let\f@user@size\f@size
```

Then we check whether this new combination is defined and give an error message if not. In this case we also switch to `\error@fontshape`.

```
540     \expandafter
541     \ifx\csname\mandatory@arg\endcsname\relax
542         \errmessage{No\space declaration\space for\space
543             shape\space \mandatory@arg}%
544     \error@fontshape
545     \else
```

Otherwise we warn the user about the substitution taking place.

```
546         #1{Font\space shape\space '\curr@fontshape'\space in\space
547             size\space <\f@size>\space not\space available\MessageBreak
548             Font\space shape\space '\mandatory@arg'\space tried\space
549             instead}%
550     \expandafter\split@name\mandatory@arg/\@nil
551     \fi
```

Then we restart the font specification scan by calling `\get@external@font`.

```
552     \edef\f@size{\f@user@size}%
553     \get@external@font
```

Finally `\do@subst@correction` is called to get the font name right.

```
554     \do@subst@correction
555 }
```

*(End of definition for `\s@fct@sub`.)*

`\@font@aliasinfo` Sometimes a substitution is only done to map a long font name to a standard shape or series, e.g.,

```
DeclareFontShape{T1}{Roboto-LF}{b}{it}{<-> alias * Roboto-LF/bold/it}{}
```

Using the `ssub` function in that case will give a strange (and incorrect) warning. As an alternative we therefore offer the size function `alias`. It will still add some info into the `.log` file, but no longer complains that the font shape is not available. It is implemented by grabbing the default warning text and replacing it with a new one.

```
556 </2ekernel>
557 <*2ekernel | latexrelease>
558 <latexrelease>\IncludeInRelease{2020/02/02}%
559 <latexrelease>{\font@aliasinfo}{alias size function}%
560 \DeclareSizeFunction{alias}{\sub@sfcnt\font@aliasinfo}
561 \def\font@aliasinfo#1{%
562   \font@info{Font\space shape\space '\curr@fontshape'\space
563     aliased\space to\MessageBreak '\mandatory@arg'}%
564 }
565 </2ekernel | latexrelease>
566 <latexrelease>\EndIncludeInRelease
567 <latexrelease>\IncludeInRelease{0000/00/00}%
568 <latexrelease>{\font@aliasinfo}{alias size function}%
569 <latexrelease>\let\s@sfcnt@alias\@undefined
570 <latexrelease>\let\font@aliasinfo\@undefined
571 <latexrelease>
572 <latexrelease>\EndIncludeInRelease
573 <*2ekernel>
```

*(End of definition for \font@aliasinfo.)*

**\s@sfcnt@subf** The `subf` size function allows substitution of another font. The mandatory argument is the external name of the font to be substituted, the optional argument a size scaling factor like in the default size function. The main difference to the default size function is the warning message.

```
574 \DeclareSizeFunction{subf}{\sub@sfcnt\font@warning}
575 \DeclareSizeFunction{ssubf}{\sub@sfcnt\font@info}
576 \def\sub@sfcnt#1{%
577   #1{Font\space shape\space '\curr@fontshape'\space in\space
578     size\space \f@size\space not\space available\MessageBreak
579     external\space font\space '\mandatory@arg'\space used}%
580   \empty@sfcnt#1%
581 }
```

*(End of definition for \s@sfcnt@subf.)*

**\s@sfcnt@fixed** The `fixed` size function is for using a font at a different size than requested. A warning message is printed, and the external font to be used is taken from the mandatory argument. If an optional argument is present it is used as the ‘at’ size for the font. Otherwise the font is loaded at its design size.

```
582 \DeclareSizeFunction{fixed}{\fixed@sfcnt\font@warning}
583 \DeclareSizeFunction{sfixed}{\fixed@sfcnt\font@info}
584 \def\fixed@sfcnt#1{%
585   \ifx\optional@arg\@empty
586     \let\external@font\mandatory@arg
587   \else
588     \edef\external@font{\mandatory@arg\space at\optional@arg pt}%
589   \fi
590 }
```

```

589 \fi
590 #1{External\space font\space '\external@font'\space loaded\space
591     for\space size\MessageBreak
592     <\f@size>}%
593 }
594 </2ekernel>

```

*(End of definition for \sfct@fixed.)*

## File 27

# ltfsscmp.dtx

This file contains the implementation of commands giving compatibility with the original ‘NFSS1’ release of the Font Selection Scheme.

**Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

Version 1 of NFSS is obsolete now for about 20 years (and was “current” only for a short intermediate time) so with the 2015 release these internal interface commands are removed from the kernel and made available via `latexrelease` package so that backward compatibility remains ensured for very old documents.

```
1 (*latexrelease)
2 \IncludeInRelease{2015/01/01}{\new@fontshape}%
3                                     {NFSS version1 commands}%
4 \let\new@fontshape\@undefined
5 \let\warn@rel@i\@undefined
6 \let\scan@fontshape\@undefined
7 \let\scan@@fontshape\@undefined
8 \let\subst@fontshape\@undefined
9 \let\extra@def\@undefined
10 \let\default@mextra\@undefined
11 \let\preload@sizes\@undefined
12 \let\err@rel@i\@undefined
13 \let\newmathalphabet\@undefined
14 \let\newmathalphabet@\@undefined
15 \let\newmathalphabet@@@\@undefined
16 \let\if@no@font@opt\@undefined
17 \let\@no@font@optfalse\@undefined
18 \let\define@mathalphabet\@undefined
19 \let\define@mathgroup\@undefined
20 \let\addtoversion\@undefined
21 \EndIncludeInRelease
```

In older releases we provide the original definitions.

```
22 \IncludeInRelease{0000/00/00}{\new@fontshape}%
23                                     {NFSS version1 commands}%
```

`\new@fontshape` The interface is now `\DeclareFontShape`.

```
24 \gdef\new@fontshape#1#2#3#4{%
25     \warn@rel@i\new@fontshape\DeclareFontShape
26     \expandafter\scan@fontshape\@gobble#4<\@nil><<%
27     \DeclareFontShape U{#1}{#2}{#3}\reserved@f}%
28 \@onlypreamble\new@fontshape
```

*(End of definition for \new@fontshape.)*

`\warn@rel@i` The warning message used above.

```
29 \gdef\warn@rel@i#1#2{%
30     \@font@warning{*** NFSS release 1 command
```

```

31          \noexpand#1found\MessageBreak
32      *** Update by using release 2 command
33          \string#2.\MessageBreak
34      *** Recovery is probably possible}%
35 }%
36  \@onlypreamble\warn@rel@i

```

(End of definition for \warn@rel@i.)

\scan@fontshape This will scan the old font shape definition syntax.

```

37  \gdef\scan@fontshape{%
38      \let\reserved@f\@empty
39      \let\reserved@e\@empty %           holds last info
40      \scan@@fontshape
41  }%
42  \@onlypreamble\scan@fontshape

```

(End of definition for \scan@fontshape.)

\scan@@fontshape

```

43  \gdef\scan@@fontshape#1>#2#3<{%
44      \ifx\@nil#1%
45          \edef\reserved@f{\reserved@f\reserved@e}%
46      \else
47          \def\reserved@b{#1}%           nick names
48          \def\reserved@c{#3}%
49          \in@{ at}{#3}%
50          \ifin@
51              \in@{pt}{#3}% not a proof but a good chance
52          \ifin@

```

We grab also everything after pt and discard it if people have forgotten to place a percent sign there.

```

53      \def\reserved@a##1 at##2pt##3\@nil{%
54          \def\reserved@b{##2}%
55          \def\reserved@c{##1}%
56      }%
57      \reserved@a#3\@nil
58      \fi
59      \fi
60      \ifnum 0<0#2
61          \edef\reserved@d{subf*\reserved@c}%
62          \ifcase #2\or
63              \or
64              \else
65                  \errmessage{*** What's this? NFSS release 0? ***}%
66              \fi
67          \else
68              \edef\reserved@d{#2\reserved@c}%
69          \fi
70          \ifx\reserved@d\reserved@e
71              \edef\reserved@f{\reserved@f<\reserved@b>}%
72          \else
73              \edef\reserved@f{\reserved@f\reserved@e<\reserved@b>}%add old info
74              \let\reserved@e\reserved@d

```

```

75     \fi
76     \expandafter\scan@@fontshape
77     \fi
78 }%
79 \@onlypreamble\scan@@fontshape

```

*(End of definition for \scan@@fontshape.)*

**\subst@fontshape** This is now also handled by the extend syntax of `\DeclareFontShape`.

```

80 \gdef\subst@fontshape#1#2#3#4#5#6{%
81     \warn@rel@i\subst@fontshape\DeclareFontShape
82     \DeclareFontShape{U}{#1}{#2}{#3}{<->sub*#4/#5/#6}{}}%
83 \@onlypreamble\subst@fontshape

```

*(End of definition for \subst@fontshape.)*

**\extra@def** This was replaced by `\DeclareFontFamily`.

```

84 \gdef\extra@def#1#2#3{%
85     \warn@rel@i\extra@def\DeclareFontFamily
86     \DeclareFontFamily{U}{#1}{}%
87 }%
88 \@onlypreamble\extra@def

```

*(End of definition for \extra@def.)*

**\default@mextra** The new name is `\DeclareFontEncodingDefaults` but in this case we don't feel comfortable with this either.

```

89 \gdef\default@mextra{%
90     \warn@rel@i\default@mextra\DeclareFontEncodingDefaults

```

We pick up the argument to `\default@mextra` implicitly as the second argument of `\DeclareFontEncodingDefaults`.

```

91     \DeclareFontEncodingDefaults\relax
92 }%
93 \@onlypreamble\default@mextra

```

*(End of definition for \default@mextra.)*

**\preload@sizes** The new interface is `\DeclarePreloadSizes`.

```

94 \gdef\preload@sizes{%
95     \warn@rel@i\preload@sizes\DeclarePreloadSizes
96     \DeclarePreloadSizes U%
97 }%
98 \@onlypreamble\preload@sizes

```

*(End of definition for \preload@sizes.)*

**\err@rel@i** This macro is used in cases where emulation with NFSS2 features is not really possible.

```

99 \gdef\err@rel@i#1#2{%
100     \@latex@error{*** NFSS release 1 command \noexpand#1found%
101         ^^J*** Recovery not possible. Use \string#2}%
102     {The new release of NFSS doesn't support the
103     \noexpand#1command^^Jany longer.
104     Please upgrade your file to the syntax of NFSS
105     release 2^^Jusing the \noexpand#2command.}%

```

Let's die.

```

106 \batchmode\input.\relax
107 }%
108 \@onlypreamble\err@rel@i

```

*(End of definition for \err@rel@i.)*

```

\newmathalphabet \newmathalphabet is the old form.
\newmathalphabet@@ 109 \gdef\newmathalphabet{%
\newmathalphabet@@@ 110 \ifno@font@opt
111 \latex@error{*** NFSS release 1 command
112 \noexpand\newmathalphabet found%
113 ^^J \space*** Automatic recovery not possible.%
114 ^^J \space*** TYPE H for Help%
115 }%
116 {Please look at the file usrguide.tex for hints on
117 how to resolve this problem.}%
118 \else
119 \warn@rel@i\newmathalphabet\DeclareMathAlphabet
120 \fi
121 \@ifstar\newmathalphabet@@@
122 \newmathalphabet@@}%
123 \gdef\newmathalphabet@@#1{\DeclareMathAlphabet#1{U}{-}{-}}%
124 \gdef\newmathalphabet@@@#1#2#3#4{%
125 \DeclareMathAlphabet{#1}{U}{#2}{#3}{#4}}%
126 \@onlypreamble\newmathalphabet
127 \@onlypreamble\newmathalphabet@@
128 \@onlypreamble\newmathalphabet@@@

```

*(End of definition for \newmathalphabet, \newmathalphabet@@, and \newmathalphabet@@@.)*

```

\ifno@font@opt
\@no@font@optfalse 129 \global\let\ifno@font@opt\iftrue
130 \gdef\@no@font@optfalse{\let\ifno@font@opt\iffalse}%

```

*(End of definition for \ifno@font@opt and \@no@font@optfalse.)*

```

\define@mathalphabet This is a case where dying is best.
131 \gdef\define@mathalphabet{%
132 \err@rel@i\define@mathalphabet\DeclareMathAlphabet
133 }%
134 \@onlypreamble\define@mathalphabet

```

*(End of definition for \define@mathalphabet.)*

```

\define@mathgroup And here is another one
135 \gdef\define@mathgroup{%
136 \err@rel@i\define@mathgroup\DeclareSymbolFont
137 }%
138 \@onlypreamble\define@mathgroup

```

*(End of definition for \define@mathgroup.)*

```

\addtoversion \addtoversion is the old form.

139 \def\addtoversion#1#2{%
140   \warn@rel@i\addtoversion\SetMathAlphabet
141   \SetMathAlphabet#2{#1}{U}}%
142 \@onlypreamble\addtoversion

(End of definition for \addtoversion.)
    Finishing off this huge \IncludeInRelease argument:
143 \EndIncludeInRelease
144 </latexrelease>

```

# File 28

## ltfssdcl.dtx

This file contains the main implementation of the font selection scheme commands. See other parts of the L<sup>A</sup>T<sub>E</sub>X distribution, or *The L<sup>A</sup>T<sub>E</sub>X Companion* for higher level documentation of these commands.

**Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

### 1 Interface Commands

```

1  <*2kernel>
2  \message{NFSS declarative interface,}

\in@  \@in is a utility macro with two arguments. It determines whether its first argument
\ifin@ occurs in its second and sets the switch \ifin@ accordingly. The first argument may not
        contain braces nor # (more precisely, tokens of category code 1, 2, or 6).

3  \def\in@#1#2%
4  {%
5      \begingroup
6      \def\in@@##1#1{%
7      \toks@\expandafter{\in@@#2{}-{}#1}%
8      \edef\in@@{\the\toks@}%
9      \expandafter\endgroup
10     \ifx\in@@\@empty
11     \in@false
12     \else
13     \in@true
14     \fi
15 }
16 \newif\ifin@

```

(End of definition for \in@ and \ifin@.)

Before the `\begin{document}` command several  $\langle\textit{math versions}\rangle$  and  $\langle\textit{math alphabet identifiers}\rangle$  may be declared. In principle, there should be exactly one family/series/shape combination be declared for each version/alphabet pair. But we want to allow for defaults as well for automagical filling of holes.

While building the tables for math alphabet identifiers and math versions we keep several lists:

- the list of all math versions, `\version@list`, each entry prefixed by the control sequence `\version@elt`, i.e. this list has the following form

$$\begin{aligned} &\backslash\text{version@elt}\langle\textit{version}_1\rangle\backslash\text{version@elt}\langle\textit{version}_2\rangle\ldots \\ &\hspace{15em}\backslash\text{version@elt}\langle\textit{version}_n\rangle \end{aligned}$$

- the list of all math alphabet identifiers. Here every entry has the form:

$$\begin{aligned} &\backslash\text{group@elt}\langle\textit{math group number}\rangle \\ &\{\{\langle\textit{default family}\rangle\}\{\langle\textit{default series}\rangle\}\{\langle\textit{default shape}\rangle\}\}. \end{aligned}$$

- Each defined math alphabet identifier holds a list containing information about the *versions* for which it is defined. This list has a more complicated structure: it looks as follows:

```

\set@alpha<the alphabet identifier itself>
\reserved@c<math version><font info>
...
\@nil

```

where *<font info>* is either `\reserved@e` (if the combination is not defined yet) or

```
{\family}{\series}{\shape}}
```

`\version@list` We initialize the version list to be empty.

```

17 \let\version@list=\@empty
18 \@onlypreamble\version@list

```

(End of definition for `\version@list`.)

`\version@elt`

```

19 \let\version@elt\relax
20 \@onlypreamble\version@elt

```

(End of definition for `\version@elt`.)

`\new@mathversion` The macro `\new@mathversion` is called with the version control sequence as its argument.

```

21 %\def\new@mathversion#1{%

```

The first thing this macro does is to check if the version identifier is already present in `\version@list`. We enclose `\version@list` in braces since it might be empty (if no *version* is defined yet). But this means that we need a suitable number of `\expandafter` primitives.

```

22 % \expandafter\in@\expandafter#1\expandafter{\version@list}%
23 % \ifin@

```

If so it prints an error message. The `\next` macro is used to get rid of the four characters `\mv@` that would otherwise appear at the begin of the version name in the error message.

```

24 % \latex@error{Math version
25 % '\expandafter\@gobblefour\string#1'
26 % already defined}\@eha

```

Otherwise we have a new version, and we can proceed with entering it into the tables. We add it to `\version@list`. This is very easy: we define `\version@elt` (which is the delimiter in `\version@list`) to protect itself and the following token from being expanded and simply redefine `\version@list`.

```

27 % \else
28 % \global\expandafter\newcount\csname c@\expandafter
29 % \gobble\string#1\endcsname
30 % \global\csname c@\expandafter
31 % \gobble\string#1\endcsname\@ne
32 % \def\version@elt{\noexpand\version@elt\noexpand}%
33 % \edef\version@list{\version@list\version@elt#1}%

```

Then we prepare to enter the new version into all math alphabet identifier lists. Remember that these lists use `\reserved@c` as delimiter, and that there appears the control sequence `\reserved@e` that must not be expanded. Therefore we take suitable precautions.

```
34 % \def\reserved@c{\noexpand\reserved@c\noexpand}%
35 % \let\reserved@e\relax
```

We will now go through the `\alpha@list` to process every *math alphabet identifier* in turn. Since this list has `\group@elt` as a delimiter we define this control sequence. It has three arguments as every entry consists of three items (as explained above).

```
36 % \def\group@elt##1##2##3{%
```

The first of these arguments is the *math alphabet identifier*. We redefine it by appending the information about the new version at the end of the list contained in it. However, there is one subtlety: the definitions for `\reserved@c` and `\reserved@e` made above prevent the main part of the list from being expanded. But we still have to take care of the header and the trailer. To do this we remove the trailer by means of the macro `\remove@nil` which also protect the header from being expanded. Its definition is given below. Now we can prepare to add the new version.

```
37 % \edef##1{\expandafter\remove@nil##1%
38 % \reserved@c
39 % #1%
40 % \reserved@e
41 % \noexpand\@nil}}%
```

Finally we call `\alpha@list` which will now execute the macro `\group@elt` once for every defined *math alphabet identifier*. And that's all for now.

```
42 % \alpha@list
43 % \fi}
```

*(End of definition for \new@mathversion.)*

`\alpha@list` As we explained above every entry in `\alpha@list` has the form  
`\alpha@elt`  
*alphabet identifier internal group number default font assignments*...  
 We initialize it to `\@empty`.

```
44 \let\alpha@list\@empty
45 \@onlypreamble\alpha@list
```

*(End of definition for \alpha@list.)*

`\alpha@elt`

```
46 \let\alpha@elt\relax
47 \@onlypreamble\alpha@elt
```

*(End of definition for \alpha@elt.)*

`\newgroup` Start the group (fam) allocation at 0. (Doesn't belong here.)

```
48 \count18=-1
```

*(End of definition for \newgroup.)*

`\stepcounter`

*(End of definition for \stepcounter.)*

`\select@group` We surround `\select@group` with braces so that functions using it can be used directly after `_` or `^`. However, if we use oldstyle syntax where the math alphabet doesn't have arguments (ie if `\math@bgroup` is not `\bgroup`) we need to get rid of the extra group.

```

49 </2ekernel>
50 <latexrelease>\IncludeInRelease{2015/01/01}
51 <latexrelease>          {\select@group}{\select@group}%
52 <*2ekernel | latexrelease>
53 \def\select@group#1#2#3#4{%
54   \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
55   {%
56     \ifmmode
57       \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
58         \begingroup
59         \escapechar\m@ne
60         \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
61         \globaldefs\@ne \math@fonts
62         \endgroup
63         \init@restore@version
64         \xdef#1{\noexpand\use@mathgroup\noexpand#2%
65           {\number\csname c@mv@\math@version\endcsname}}}%
66         \global\advance\csname c@mv@\math@version\endcsname\@ne
67       \else
68         \let#1\relax
69         \@latex@error{Too many math alphabets used in
70           version \math@version}%
71         \@eha
72       \fi
73     \else \expandafter\non@alpherr\fi
74     #1{#4}%
75   }%
76 }
77 </2ekernel | latexrelease>
78 <latexrelease>\EndIncludeInRelease
79 <latexrelease>\IncludeInRelease{0000/00/00}
80 <latexrelease>          {\select@group}{\select@group}%
81 <latexrelease>\def\select@group#1#2#3#4{%
82   <latexrelease> \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
83   <latexrelease> {%
84     <latexrelease> \ifmmode
85     <latexrelease>   \ifnum\csname c@mv@\math@version\endcsname<\sixt@@n
86     <latexrelease>     \begingroup
87     <latexrelease>     \escapechar\m@ne
88     <latexrelease>     \getanddefine@fonts
89     <latexrelease>       {\csname c@mv@\math@version\endcsname}#3%
90     <latexrelease>     \globaldefs\@ne \math@fonts
91     <latexrelease>     \endgroup
92     <latexrelease>     \init@restore@version
93     <latexrelease>     \xdef#1{\noexpand\use@mathgroup\noexpand#2%
94       <latexrelease>       {\number\csname c@mv@\math@version\endcsname}}}%
95     <latexrelease>     \global\advance\csname c@mv@\math@version\endcsname\@ne
96     <latexrelease>   \else
97     <latexrelease>     \let#1\relax
98     <latexrelease>     \@latex@error{Too many math alphabets used in
99     <latexrelease>       version \math@version}%

```

```

100 <latexrelease>      \@eha
101 <latexrelease>      \fi
102 <latexrelease> \else \expandafter\non@alpherr\fi
103 <latexrelease> #1{#4}%
104 <latexrelease> }%
105 <latexrelease>}
106 <latexrelease>\EndIncludeInRelease
107 <*2ekernel>

108 \@onlypreamble\restore@mathversion

```

*(End of definition for \select@group.)*

**\init@restore@version**

```

109 \def\init@restore@version{%
110     \global\let\init@restore@version\relax
111     \xdef\restore@mathversion
112         {\expandafter\noexpand\csname mv@\math@version\endcsname
113          \global\csname c@mv@\math@version\endcsname
114          \number\csname c@mv@\math@version\endcsname\relax}%
115     \aftergroup\dorestore@version
116 }
117 \@onlypreamble\init@restore@version

```

*(End of definition for \init@restore@version.)*

**\non@alpherr**

```

118 \gdef\non@alpherr#1{\@latex@error{%

```

The command here will have a space at the end of its name, so we make sure not to insert an extra one.

```

119     \string#1allowed only in math mode}\@ehd}

```

*(End of definition for \non@alpherr.)*

**\dorestore@version**

```

120 \def\dorestore@version
121 {\ifmmode
122     \aftergroup\dorestore@version
123 \else
124     \gdef\init@restore@version{%
125         \global\let\init@restore@version\relax
126         \xdef\restore@mathversion
127             {\expandafter\noexpand\csname mv@\math@version\endcsname
128              \global\csname c@mv@\math@version\endcsname
129              \number\csname c@mv@\math@version\endcsname\relax}%
130         \aftergroup\dorestore@version
131     }%
132     \begingroup
133         \let\getanddefine@fonts\@gobbletwo
134         \restore@mathversion
135     \endgroup
136     \fi}%
137 \@onlypreamble\dorestore@version

```

*(End of definition for \dorestore@version.)*

`\c@localmathalphabets` To avoid hitting the “no more math fams available” limit of 16, we keep a defined number of math alphabets flexible/local. If we have to allocate any of those we roll back the allocation after the formula has ended, so the next formula can use other alphabets in the slot(s). This makes the processing a bit slower if you are working at the limit, but that is better than dying with “out of memory”.

```

138 \endkernel
139 \latexrelease\IncludeInRelease{2021/11/15}
140 \latexrelease {\document@select@group}{\document@select@group}%
141 \*2ekernel|latexrelease

```

We don’t really undo the declaration on rollback (as that would be hard to maintain), so rolling forward needs to check if the declaration was already made.

```

142 \ifx\c@localmathalphabets\undefined

```

There is no need to have this counter as part of the include checkpoints, given that it makes little sense to alter its settings mid document. All we want is the ability to change it using the `\setcounter` interface.

By default we keep two math fams flexible.

```

143 \newcount\c@localmathalphabets
144 \setcounter{localmathalphabets}{2}
145 \fi

```

*(End of definition for \c@localmathalphabets.)*

`\document@select@group` The `\document@select@group` command is the version of `\select@group` (inside math versions) that is used in the document body to set up math alphabets (if used).

```

146 \def\document@select@group#1#2#3#4{%
147 \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
148 {%
149 \ifmmode

```

We first check if there is still room for allocating another mathgroup. If there is, we check if it can be globally allocated or if we have reached the limit which is given by `\e@mathgroup@top` with `\c@localmathalphabets` subtracted.

```

150 \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
151 \ifnum \numexpr\e@mathgroup@top-\c@localmathalphabets
152 >\csname c@mv@\math@version\endcsname
153 \else

```

If we are past this point we freeze the current state of the math version so that we can return to it after the formula has ended. Of course, that should be done only once, so we check if `\mv@<version>@frozen` already exists.

```

154 \ifcsname mv@\math@version @frozen\endcsname \else

```

We have to pass the current value of `\math@version` not the macro itself, because some of the processing is delayed to a point where the value may have changed again—not doing this caused a puzzling error in one setup.

```

155 \expandafter\freeze@math@version\expandafter{\math@version}%
156 \fi
157 \fi
158 \begingroup
159 \escapechar\m@ne
160 \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
161 \globaldefs\@ne \math@fonts

```

```

162 \endgroup
163 \expandafter\extract@alph@from@version
164 \csname mv@\math@version\expandafter\endcsname
165 \expandafter{\number\csname
166 c@mv@\math@version\endcsname}%
167 #1%
168 \global\advance\csname c@mv@\math@version\endcsname\@ne
169 \else
170 \let#1\relax
171 \@latex@error{Too many math alphabets used in
172 version \math@version}%
173 \@eha
174 \fi

```

Extra \expandafter to remove the \expandafter added below

```

175 \else \expandafter\expandafter\expandafter\non@alpherr\fi

```

We surround \select@group with braces so that functions using it can be used directly after `_` or `^`.

If the legacy interface is used, e.g., `\sf -1` the math alphabet #1 does not take an argument so we better do not surround #4 with braces, because then we get `{\relax}` into the formula and introduce an extra Ord atom. The two different cases can be distinguished by looking at the current value of `\math@bgroup`.

```

176 \expandafter#1\ifx\math@bgroup\bgroup{#4}\else#4\fi
177 }%
178 }
179 </2ekernel | latexrelease>
180 <latexrelease>\EndIncludeInRelease
181 <latexrelease>\IncludeInRelease{2020/10/01}
182 <latexrelease> {\document@select@group}{\document@select@group}%
183 <latexrelease>
184 <latexrelease>\def\document@select@group#1#2#3#4{%
185 <latexrelease> \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
186 <latexrelease> {%
187 <latexrelease> \ifmmode
188 <latexrelease> \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
189 <latexrelease> \begingroup
190 <latexrelease> \escapechar\m@ne
191 <latexrelease> \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
192 <latexrelease> \globaldefs\@ne \math@fonts
193 <latexrelease> \endgroup
194 <latexrelease> \expandafter\extract@alph@from@version
195 <latexrelease> \csname mv@\math@version\expandafter\endcsname
196 <latexrelease> \expandafter{\number\csname
197 <latexrelease> c@mv@\math@version\endcsname}%
198 <latexrelease> #1%
199 <latexrelease> \global\advance\csname c@mv@\math@version\endcsname\@ne
200 <latexrelease> \else
201 <latexrelease> \let#1\relax
202 <latexrelease> \@latex@error{Too many math alphabets used
203 <latexrelease> in version \math@version}%
204 <latexrelease> \@eha
205 <latexrelease> \fi
206 <latexrelease> \else \expandafter\expandafter\expandafter\non@alpherr\fi

```

```

207 <latexrelease> \expandafter#1\ifx\math@bgroup\bgroup{#4}\else#4\fi
208 <latexrelease> }%
209 <latexrelease> }
210 <latexrelease> \EndIncludeInRelease
211 <latexrelease> \IncludeInRelease{2015/01/01}
212 <latexrelease> {\document@select@group}{\document@select@group}%
213 <latexrelease>
214 <latexrelease> \def\document@select@group#1#2#3#4{%
215 <latexrelease> \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
216 <latexrelease> {%
217 <latexrelease> \ifmmode
218 <latexrelease> \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
219 <latexrelease> \begingroup
220 <latexrelease> \escapechar\m@ne
221 <latexrelease> \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
222 <latexrelease> \globaldefs\@ne \math@fonts
223 <latexrelease> \endgroup
224 <latexrelease> \expandafter\extract@alph@from@version
225 <latexrelease> \csname mv@\math@version\expandafter\endcsname
226 <latexrelease> \expandafter{\number\csname
227 <latexrelease> c@mv@\math@version\endcsname}%
228 <latexrelease> #1%
229 <latexrelease> \global\advance\csname c@mv@\math@version\endcsname\@ne
230 <latexrelease> \else
231 <latexrelease> \let#1\relax
232 <latexrelease> \@latex@error{Too many math alphabets used
233 <latexrelease> in version \math@version}%
234 <latexrelease> \@eha
235 <latexrelease> \fi
236 <latexrelease> \else \expandafter\non@alpherr\fi
237 <latexrelease> #1{#4}%
238 <latexrelease> }%
239 <latexrelease> }
240 <latexrelease> \EndIncludeInRelease
241 <latexrelease>
242 <latexrelease> \IncludeInRelease{0000/00/00}
243 <latexrelease> {\document@select@group}{\document@select@group}%
244 <latexrelease>
245 <latexrelease> \def\document@select@group#1#2#3#4{%
246 <latexrelease> \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
247 <latexrelease> {%
248 <latexrelease> \ifmmode
249 <latexrelease> \ifnum\csname c@mv@\math@version\endcsname<\sixt@@n
250 <latexrelease> \begingroup
251 <latexrelease> \escapechar\m@ne
252 <latexrelease> \getanddefine@fonts
253 <latexrelease> {\csname c@mv@\math@version\endcsname}#3%
254 <latexrelease> \globaldefs\@ne \math@fonts
255 <latexrelease> \endgroup
256 <latexrelease> \expandafter\extract@alph@from@version
257 <latexrelease> \csname mv@\math@version\expandafter\endcsname
258 <latexrelease> \expandafter{\number\csname
259 <latexrelease> c@mv@\math@version\endcsname}%
260 <latexrelease> #1%

```

```

261 <latexrelease> \global\advance\csname c@mv@\math@version\endcsname\@ne
262 <latexrelease> \else
263 <latexrelease> \let#1\relax
264 <latexrelease> \@latex@error{Too many math alphabets used
265 <latexrelease> in version \math@version}%
266 <latexrelease> \@eha
267 <latexrelease> \fi
268 <latexrelease> \else \expandafter\non@alpherr\fi
269 <latexrelease> #1{#4}%
270 <latexrelease> }%
271 <latexrelease> }
272 <latexrelease> \EndIncludeInRelease
273 <*2ekernel>

```

(End of definition for \document@select@group.)

**\freeze@math@version** This command stores the current state of the math version and sets things up to return to it after each formula from now on. We use L3 programming layer code to set it up.

```

274 </2ekernel>
275 <*2ekernel | latexrelease>
276 <latexrelease> \IncludeInRelease{2022/11/01}%
277 <latexrelease> {\freeze@math@version}{freeze math version}%
278 \ExplSyntaxOn
279 \cs_new_protected:Npn\freeze@math@version #1 {

```

Save the current \mv@<version> code and the number of allocated mathgroups inside.

```

280 \@font@info{Freeze~ math~ alphabet~ allocation~ in~ version~
281 #1.\MessageBreak
282 Allocated~math~groups:~\int_use:c{ c@mv@ #1 }~
283 (local:~ \int_use:N\c@localmathalphabets) }
284 \cs_gset_eq:cc { mv@#1@frozen }{ mv@#1 }
285 \tl_gset:cx { g__nfss_frozen_mv_ #1 _tl }{ \int_use:c { c@mv@#1 } }

```

Here is the definition of \mv@<version>@reset. If there has been no new math alphabet allocation, doing a reset would just cause a lot of unnecessary processing, so we do a quick check upfront for this.

```

286 \cs_gset:cpn{mv@#1@reset}
287 {

```

If we are back at top-level, or more precisely outside of any (nested) math, we may have to reset the math version back to its frozen version, if that exists and has fewer alphabets allocated.

```

288 \int_compare:nNnTF \@math@level = 0
289 {
290 \int_compare:nNnTF { \int_use:c{c@mv@#1} } >
291 { \tl_use:c{g__nfss_frozen_mv_ #1 _tl} }
292 {
293 \@font@info{ Undo~ math~ alphabet~ allocation~ in~ version~ #1 }

```

If the undo is necessary, we restore the \mv@<version> code.

```

294 \cs_gset_eq:cc { mv@#1 }{ mv@#1@frozen }
295 \int_gset:cn { c@mv@#1 }{ \tl_use:c {g__nfss_frozen_mv_ #1 _tl} }

```

But we also should undo changes to the top-level math alphabet definitions. We therefore run this code with a modified definition for `\getanddefine@fonts` because there is no need to do anything to the symbol fonts that are permanently allocated. However, we do this only if the resetting was for the current math version, because otherwise we would give the top-level definitions the values for the last math version being resetted (e.g., bold if there are just two).

```

296         \tl_if_eq:NnTF \math@version {#1}
297         {
298             \group_begin:
299             \cs_set_eq:NN \getanddefine@fonts \use_none:nn
300             \use:c {mv@ \math@version }
301             \group_end:
302         }
303     {

```

Once we have hit the boundary and have to revert to the frozen version that happens quite often, but typically only for the normal version. Thus, it is better to report only when we do not revert the top-level definition as this is the exceptional case and happens only if several math versions are used in parallel.

```

304         \font@info{ ...~ but~ do~ not~ reset~ the~
305             top-level~ math~ alphabet~ definitions }
306     }
307 }
308 {

```

If there was no change, we report that in the log (but this branch could go completely).

```

309         \font@info{ No~ math~ alphabet~ change~
310             to~ frozen~ version~ #1 }
311     }
312 }
313 {
314     \font@info{ Nested~ math:~ keeping~ math~ alphabet~
315         allocation~ in~ version~ #1}
316 }

```

If this is executed after a math display, we may have to arrange for ignoring spaces, because they are now hidden if the tokens from above intervene. This is signaled by the 2e switch `@ignore` which is set in `\frozen@everymath` and `\frozen@everydisplay`.

This is all 2e code so we use that syntax.

```

317         \if@ignore \ignorespaces \fi
318     }
319 }
320 \ExplSyntaxOff
321 \</2ekernel | latexrelease>
322 \<latexrelease>\EndIncludeInRelease
323 \<latexrelease>\IncludeInRelease{2021/11/15}
324 \<latexrelease>         {\freeze@math@version}{freeze math version}%
325 \<latexrelease>
326 \<latexrelease>\ExplSyntaxOn
327 \<latexrelease>\cs_set_protected:Npn\freeze@math@version #1 {
328 \<latexrelease>     \font@info{Freeze~ math~ alphabet~ allocation~ in~ version~
329 \<latexrelease>         #1.\MessageBreak
330 \<latexrelease>         Allocated~math~groups:~\int_use:c{ c@mv@ #1 }~
331 \<latexrelease>         (local:~ \int_use:N\c@localmathalphabets)      }

```

```

332 <latexrelease> \cs_gset_eq:cc { mv@#1@frozen }{ mv@#1 }
333 <latexrelease> \tl_gset:cx { g__nfss_frozen_mv_ #1 _tl }{ \int_use:c { c@mv@#1 } }
334 <latexrelease> \group_insert_after:N \__nfss_init_mv_freeze:N
335 <latexrelease> \exp_after:wN \group_insert_after:N \cs:w mv@#1@reset \cs_end:
336 <latexrelease> \tl_gput_right:No \check@mathfonts
337 <latexrelease> {
338 <latexrelease> \exp_after:wN \group_insert_after:N \cs:w mv@#1@reset \cs_end:
339 <latexrelease> }
340 <latexrelease> \cs_gset:cpn{mv@#1@reset}
341 <latexrelease> {
342 <latexrelease> \int_compare:nNnTF { \int_use:c{c@mv@#1} } >
343 <latexrelease> { \tl_use:c{g__nfss_frozen_mv_ #1 _tl} }
344 <latexrelease> {
345 <latexrelease> \font@info{Undo~ math~ alphabet~ allocation~ in~ version~ #1}
346 <latexrelease> \cs_gset_eq:cc { mv@#1 }{ mv@#1@frozen }
347 <latexrelease> \int_gset:cn { c@mv@#1 }{ \tl_use:c {g__nfss_frozen_mv_ #1 _tl} }
348 <latexrelease> \group_begin:
349 <latexrelease> \cs_set_eq:NN \getanddefine@fonts \use_none:nn
350 <latexrelease> \use:c {mv@#1}
351 <latexrelease> \group_end:
352 <latexrelease> }
353 <latexrelease> {
354 <latexrelease> \font@info{No~ math~ alphabet~ change~ to~ frozen~ version~ #1}
355 <latexrelease> }
356 <latexrelease> \if@ignore \ignorespaces \fi
357 <latexrelease> }
358 <latexrelease>}
359 <latexrelease>\cs_set_protected:Npn \__nfss_init_mv_freeze:N #1 {%
360 <latexrelease> \mode_if_math:T { \group_insert_after:N \__nfss_init_mv_freeze:N
361 <latexrelease> \group_insert_after:N } #1
362 <latexrelease>}
363 <latexrelease>\ExplSyntaxOff
364 <latexrelease>
365 <latexrelease>\EndIncludeInRelease
366 <*2ekernel>

```

(End of definition for \freeze@math@version.)

\process@table

```

367 </2ekernel>
368 <*2ekernel | latexrelease>
369 <latexrelease> \IncludeInRelease{2025/11/01}%
370 <latexrelease> {\process@table}{Support metafamily}%
371 \def\process@table{%
372 \def\cdp@elt##1##2##3##4{%
373 \font@info{Checking defaults for
374 ##1/##2/##3/##4}%
375 \expandafter
376 \ifx\csname##1/##2/##3/##4\endcsname\relax

```

Grouping is important for two reasons, first \cdp@elt will get redefined if \Declare... functions are executed within the external .fd file and secondly \try@load@fontshape changes a lot of catcodes without surrounding itself with a group.

```

377 \begingroup
378 \def\f@encoding{##1}\def\f@family{##2}%

```

```

379         \try@load@fontshape
380     \endgroup
381 \fi
382 \expandafter
383 \ifx\csize##1/##2/##3/##4\endcsize\relax
384     \@latex@error{This NFSS system isn't set up properly}%
385     {For encoding scheme ##1 the defaults
386     ##2/##3/##4 do not form a valid font shape}%
387 \else
388     \@font@info{... okay}%
389 \fi}%
390 \csize@list

```

Now we make sure that `\error@fontshape` is okay.

```

391 \begingroup
392     \escapechar\m@ne
393     \error@fontshape
394     \expandafter\ifx\csize \curr@fontshape\endcsize\relax
395     \begingroup
396         \try@load@fontshape
397     \endgroup
398 \fi
399 \expandafter\ifx\csize \curr@fontshape\endcsize\relax
400     \@latex@error{This NFSS system isn't set up properly}%
401     {The system maintainer forgot to specify a suitable
402     substitution
403     font shape using the \noexpand\DeclareErrorFont
404     command}%
405 \fi
406 \endgroup

```

Set `\select@group` to its meaning used within the document body.

```

407 \let\select@group\document@select@group

```

Install the default font attributes as they are currently pointing to error font face. We can speed up the process by just using `\edef`, thereby avoiding all kind of extra processing. Don't use `\reset@font` for this since that would trigger `\selectfont`, but run the `normalfont` hook, since this is really what we are doing here (except for the `\selectfont=`).

```

408 \fontencoding\encodingdefault
409 \edef\f@family{\familydefault}%
410 \edef\f@series{\seriesdefault}%
411 \edef\f@shape{\shapedefault}%

412 \set@current@meta@family
413 \UseHook{normalfont}%

```

Drop stuff not longer needed.

```

414 \everyjob{}%
415 }
416 </2ekernel | latexrelease>
417 <latexrelease>\EndIncludeInRelease

418 <latexrelease>\IncludeInRelease{0000/00/00}%
419 <latexrelease>          {\process@table}{Support metafamily}%
420 <latexrelease>

```

```

421 <latexrelease>\def\process@table{%
422 <latexrelease>    \def\cdp@elt##1##2##3##4{%
423 <latexrelease>        \@font@info{Checking defaults for
424 <latexrelease>            ##1/##2/##3/##4}%
425 <latexrelease>        \expandafter
426 <latexrelease>        \ifx\csname##1/##2/##3/##4\endcsname\relax
427 <latexrelease>            \begingroup
428 <latexrelease>                \def\f@encoding{##1}\def\f@family{##2}%
429 <latexrelease>                \try@load@fontshape
430 <latexrelease>            \endgroup
431 <latexrelease>        \fi
432 <latexrelease>        \expandafter
433 <latexrelease>        \ifx\csname##1/##2/##3/##4\endcsname\relax
434 <latexrelease>            \@latex@error{This NFSS system isn't set up properly}%
435 <latexrelease>                {For encoding scheme ##1 the defaults
436 <latexrelease>                ##2/##3/##4 do not form a valid font shape}%
437 <latexrelease>        \else
438 <latexrelease>            \@font@info{... okay}%
439 <latexrelease>        \fi}%
440 <latexrelease>    \cdp@list
441 <latexrelease>    \begingroup
442 <latexrelease>        \escapechar\m@ne
443 <latexrelease>        \error@fontshape
444 <latexrelease>        \expandafter\ifx\csname \curr@fontshape\endcsname\relax
445 <latexrelease>            \begingroup
446 <latexrelease>                \try@load@fontshape
447 <latexrelease>            \endgroup
448 <latexrelease>        \fi
449 <latexrelease>        \expandafter\ifx\csname \curr@fontshape\endcsname\relax
450 <latexrelease>            \@latex@error{This NFSS system isn't set up properly}%
451 <latexrelease>                {The system maintainer forgot to specify a suitable
452 <latexrelease>                substitution
453 <latexrelease>                font shape using the \noexpand\DeclareErrorFont
454 <latexrelease>                command}%
455 <latexrelease>        \fi
456 <latexrelease>    \endgroup
457 <latexrelease>    \let\select@group\document@select@group
458 <latexrelease>    \fontencoding\encodingdefault
459 <latexrelease>    \edef\f@family{\familydefault}%
460 <latexrelease>    \edef\f@series{\seriesdefault}%
461 <latexrelease>    \edef\f@shape{\shapedefault}%
462 <latexrelease>    \everyjob{}%
463 <latexrelease>}
464 <latexrelease>\EndIncludeInRelease
465 <*2ekernel>

466 \onlypreamble\process@table

(End of definition for \process@table.)

467 %\onlypreamble\set@mathradical

```

\DeclareMathVersion

```

468 </2ekernel>
469 <*2ekernel | latexrelease>

```

```

470 <latexrelease>\IncludeInRelease{2022/11/01}%
471 <latexrelease>          {\DeclareMathVersion}{local alphabets}%
472 \def\DeclareMathVersion#1{%

```

When declaring a new math version we need to instantiate an L3 variable that is used when we freeze the version, because too many alphabets got allocated. If we don't do this, L3 programming layer complains if it is run in checking mode.

```

473   \namedef{g__nfss_frozen_mv_#1_tl}{}%

```

We also extend `\check@mathfonts` to call a version reset (once frozen) after a formula has finished.

```

474   \expandafter\ifx\csname mv@#1\endcsname \relax
475     \expandafter \g@addto@macro \expandafter \check@mathfonts
476       \expandafter {\expandafter \aftergroup \csname mv@#1@reset\endcsname}%

```

Initially this macro does nothing. It is, however, important that it doesn't stop any `\ignorespaces`, so we make it expandable and not `\relax`.

```

477   \namedef{mv@#1@reset}{}%
478 \fi

479 \expandafter\new@mathversion\csname mv@#1\endcsname}
480 \@onlypreamble\DeclareMathVersion
481 </2ekernel| latexrelease>
482 <latexrelease>\EndIncludeInRelease

483 <latexrelease>\IncludeInRelease{2021/11/15}%
484 <latexrelease>          {\DeclareMathVersion}{local alphabets}%
485 <latexrelease>\def\DeclareMathVersion#1{%
486 <latexrelease>   \namedef{g__nfss_frozen_mv_#1_tl}{}%
487 <latexrelease>   \expandafter\new@mathversion\csname mv@#1\endcsname}
488 <latexrelease>\EndIncludeInRelease
489 <latexrelease>\IncludeInRelease{0000/00/00}%
490 <latexrelease>          {\DeclareMathVersion}{local alphabets}%
491 <latexrelease>\def\DeclareMathVersion#1{%
492 <latexrelease>   \expandafter\new@mathversion\csname mv@#1\endcsname}
493 <latexrelease>\EndIncludeInRelease
494 <*2ekernel>

```

*(End of definition for \DeclareMathVersion.)*

`\new@mathversion`

```

495 \def\new@mathversion#1{%
496   \expandafter\in@\expandafter#1\expandafter{\version@list}%
497   \ifin@
498     \@font@info{Redeclaring math version
499               '\expandafter\@gobblefour\string#1'}%
500   \else
501     \expandafter\newcount\csname c@\expandafter
502               \@gobble\string#1\endcsname
503     \def\version@elt{\noexpand\version@elt\noexpand}%
504     \edef\version@list{\version@list\version@elt#1}%
505   \fi

```

`\toks@` is used to gather all tokens for the math version. `\count@` will be used to count the math groups we add to this version.

```

506   \toks@{}%
507   \count@\z@

```

Now we loop over `\group@list` to add all math groups defined so far to the version and at the same time to count them.

```

508 \def\group@elt##1##2{%
509     \advance\count@\@ne
510     \addto@hook\toks@{\getanddefine@fonts##1##2}%
511 }%
512 \group@list

```

We set the counter for this math version to the number of math groups found in `\group@list`.

```

513 \global\csname c@\expandafter\@gobble\string1\endcsname\count@

```

Now we loop over `\alpha@list` to add all math alphabets known so far. We have to distinguish the case that an alphabet by default should produce an error in new versions.

```

514 \def\alpha@elt##1##2##3{%
515     \ifx##2\no@alphabet@error
516     \toks@\expandafter{\the\toks@\install@mathalphabet##1%
517         {\no@alphabet@error##1}}%
518     \else
519     \toks@\expandafter{\the\toks@\install@mathalphabet##1%
520         {\select@group##1##2##3}}%
521     \fi
522 }%
523 \alpha@list

```

Finally we define the math version to expand to the contents of `\toks@`.

```

524 \xdef#1{\the\toks@}%
525 }
526 \@onlypreamble\new@mathversion

```

*(End of definition for \new@mathversion.)*

`\DeclareSymbolFont` First drop any surplus `m` from the series argument then do what has been done since 1994.

```

527 </2ekernel>
528 <*2ekernel | latexrelease>
529 <latexrelease> \IncludeInRelease{2022/11/01}%
530 <latexrelease> { \DeclareSymbolFont } { maybe drop m } %
531 \def\DeclareSymbolFont #1#2#3#4#5{%
532     \def\reserved@a{\DeclareSymbolFont@m@dropped{#1}{#2}{#3}}%
533     \edef\reserved@b{#4}%
534     \series@maybe@drop@one@m\reserved@b\reserved@b
535     \expandafter\reserved@a\expandafter{\reserved@b}{#5}%
536 }
537 \def\DeclareSymbolFont@m@dropped #1#2#3#4#5{%
538     \@tempswafalse
539     \edef\reserved@b{#2}%
540     \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
541         \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
542     \cdp@list
543     \if@tempswa
544         \ifundefined{sym#1}{%

```

```

545 \ifnum\count18<15 %
546 \expandafter\new@mathgroup\csname sym#1\endcsname
547 \expandafter\new@symbolfont\csname sym#1\endcsname
548 {#2}{#3}{#4}{#5}%
549 \else
550 \latex@error{Too many symbol fonts declared}\@eha
551 \fi
552 }%
553 {%
554 \@font@info{Redefining symbol font ‘#1’}%

```

Update the group list.

```

555 \def\group@elt##1##2{%
556 \noexpand\group@elt\noexpand##1%
557 \expandafter\ifx\csname sym#1\endcsname##1%
558 \expandafter\noexpand\csname#2/#3/#4/#5\endcsname
559 \else
560 \noexpand##2%
561 \fi}%
562 \xdef\group@list{\group@list}%

```

Update the version list.

```

563 \def\version@elt##1{%
564 \expandafter
565 \SetSymbolFont@expandafter##1\csname#2/#3/#4/#5\endcsname
566 \endcsname \csname sym#1\endcsname
567 }%
568 \version@list
569 }%
570 \else
571 \latex@error{Encoding scheme ‘#2’ unknown}\@eha
572 \fi
573 }
574 \@onlypreamble\DeclareSymbolFont
575 </2ekernel | latexrelease>
576 <latexrelease>\EndIncludeInRelease
577 <latexrelease>\IncludeInRelease{0000/00/00}%
578 <latexrelease> \{\DeclareSymbolFont\}{maybe drop m}%
579 <latexrelease>
580 <latexrelease>\let\DeclareSymbolFont\DeclareSymbolFont@m@dropped
581 <latexrelease>\let\DeclareSymbolFont@m@dropped\@undefined
582 <latexrelease>
583 <latexrelease>\EndIncludeInRelease
584 <*2ekernel>

```

*(End of definition for \DeclareSymbolFont.)*

**\group@list**

```

585 \let\group@list\@empty
586 \@onlypreamble\group@list

```

*(End of definition for \group@list.)*

**\group@elt**

```

587 \let\group@elt\relax
588 \@onlypreamble\group@elt

```

(End of definition for \group@elt.)

\new@symbolfont

```

589 \def\new@symbolfont#1#2#3#4#5{%
590   \toks@{\expandafter{\group@list}}%
591   \edef\group@list{\the\toks@\noexpand\group@elt\noexpand#1%
592     \expandafter\noexpand\csname#2/#3/#4/#5\endcsname}%
593   \def\version@elt##1{\toks@\expandafter{##1}}%
594   \edef##1{\the\toks@\noexpand\getanddefine@fonts
595     #1\expandafter\noexpand\csname#2/#3/#4/#5\endcsname}%
596   \global\advance\csname c@\expandafter
597     \gobble\string##1\endcsname\@ne
598   }%
599   \version@list
600 }
601 \@onlypreamble\new@symbolfont

```

(End of definition for \new@symbolfont.)

\SetSymbolFont First drop any surplus m from the series argument then do what has been done since 1994.

```

602 </2ekernel>
603 <*2ekernel | latexrelease>
604 <latexrelease> \IncludeInRelease{2022/11/01}%
605 <latexrelease> {\SetSymbolFont}{maybe drop m}%
606 \def\SetSymbolFont #1#2#3#4#5#6{%
607   \def\reserved@a{\SetSymbolFont@m@dropped{#1}{#2}{#3}{#4}}%
608   \edef\reserved@b{#5}%
609   \series@maybe@drop@one@m\reserved@b\reserved@b
610   \expandafter\reserved@a\expandafter{\reserved@b}{#6}%
611 }
612 \def\SetSymbolFont@m@dropped#1#2#3#4#5#6{%
613   \@tempswafalse
614   \edef\reserved@b{#3}%
615   \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
616     \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
617   \cdp@list
618   \if@tempswa
619     \expandafter\SetSymbolFont@
620     \csname mv@#2\expandafter\endcsname\csname#3/#4/#5/#6\expandafter
621       \endcsname \csname sym#1\endcsname
622   \else
623     \@latex@error{Encoding scheme ‘#3’ unknown}\@eha
624   \fi
625 }
626 \@onlypreamble\SetSymbolFont
627 </2ekernel | latexrelease>
628 <latexrelease> \EndIncludeInRelease
629 <latexrelease> \IncludeInRelease{0000/00/00}%
630 <latexrelease> {\SetSymbolFont}{maybe drop m}%
631 <latexrelease>
632 <latexrelease> \let\SetSymbolFont\SetSymbolFont@m@dropped
633 <latexrelease> \let\SetSymbolFont@m@dropped\@undefined
634 <latexrelease>

```

```

635 \latexrelease\EndIncludeInRelease
636 \*2ekernel)

```

(End of definition for \SetSymbolFont.)

\SetSymbolFont@

```

637 \def\SetSymbolFont@#1#2#3{%
638   \expandafter\in@\expandafter#1\expandafter{\version@list}%
639   \ifin@
640     \expandafter\in@\expandafter#3\expandafter{\group@list}%
641     \ifin@
642       \begingroup
643         \expandafter\get@cdp\string#2\@nil\reserved@a
644         \toks@{}%
645         \def\install@mathalphabet##1##2{%
646           \addto@hook\toks@{\install@mathalphabet##1{##2}}%
647         }%
648         \def\getanddefine@fonts##1##2{%
649           \ifnum##1=#3%
650             \addto@hook\toks@{\getanddefine@fonts#3#2}%
651             \expandafter\get@cdp\string##2\@nil\reserved@b
652             \ifx\reserved@a\reserved@b\else
653               \@font@info{Encoding '\reserved@b' has changed
654                 to '\reserved@a' for symbol font\MessageBreak
655                 '\expandafter\@gobblefour\string#3' in the
656                 math version '\expandafter
657                 \@gobblefour\string#1'}%
658             \fi
659             \@font@info{%
660               Overwriting symbol font
661               '\expandafter\@gobblefour\string#3' in
662               version '\expandafter
663               \@gobblefour\string#1'\MessageBreak
664               \@spaces \expandafter\@gobble\string##2 -->
665               \expandafter\@gobble\string#2}%
666             \else
667               \addto@hook\toks@{\getanddefine@fonts##1##2}%
668             \fi}%
669         #1%
670         \xdef#1{\the\toks@}%
671       \endgroup
672     \else
673       \latex@error{Symbol font '\expandafter\@gobblefour\string#3'
674         not defined}\@eha
675     \fi
676   \else
677     \latex@error{Math version '\expandafter\@gobblefour\string#1'
678       is not
679       defined}{You probably misspelled the name of the math
680       version.^^JOr you have to specify an additional package.}%
681   \fi
682 }
683 \@onlypreamble\SetSymbolFont@

```

(End of definition for \SetSymbolFont.)

`\get@cdp`

```
684 \def\get@cdp#1#2/#3\@nil#4{\def#4{#2}}
685 \@onlypreamble\get@cdp
```

*(End of definition for \get@cdp.)*

`\DeclareMathAlphabet`

```
686 \def\DeclareMathAlphabet#1#2#3#4#5{%
687   \@tempswafalse
688   \edef\reserved@b{#2}%
689   \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
690     \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
691   \cdp@list
692   \if@tempswa
693     \expandafter\ifx
694     \csname\expandafter\@gobble\string#1\endcsname
695     \relax
696     \new@mathalphabet#1{#2}{#3}{#4}{#5}%
697   \else
```

Check if it is already a math alphabet.

```
698   \edef\reserved@a{\noexpand\in@{\string\select@group}%
699     {\expandafter\meaning\csname \expandafter
700       \@gobble\string#1\space\endcsname}}%
701   \reserved@a
702   \ifin@
703     \@font@info{Redeclaring math alphabet \string#1}%
704     \def\version@elt##1{%
705       \expandafter\SetMathAlphabet@\expandafter
706         ##1\csname#2/#3/#4/#5\expandafter\endcsname
707
708       \csname M@#2\expandafter\endcsname
709       \csname \expandafter\@gobble\string#1\space\endcsname#1}%
710     \version@list
711   \else
```

Check if it is a math alphabet defined via `\DeclareSymbolFontAlphabet`.

```
711   \edef\reserved@a{\noexpand\in@{\string\use@mathgroup}%
712     {\expandafter\meaning\csname \expandafter
713       \@gobble\string#1\space\endcsname}}%
714   \reserved@a
715   \ifin@
```

In that case overwriting is simple since there is nothing inserted in the math version macros.

```
716     \@font@info{Redeclaring math alphabet \string#1}%
717     \new@mathalphabet#1{#2}{#3}{#4}{#5}%
```

Otherwise panic.

```
718   \else
719     \@latex@error{Command ‘\string#1’ already defined}\@eha
720   \fi
721   \fi
722   \fi
723   \else
724     \@latex@error{Encoding scheme ‘#2’ unknown}\@eha
```

```

725 \fi
726 }
727 \@onlypreamble\DeclareMathAlphabet

```

(End of definition for \DeclareMathAlphabet.)

\new@mathalphabet

```

728 \def\new@mathalphabet#1#2#3#4#5{%
729   \toks@\expandafter{\alpha@list}%
730   \edef#1{\expandafter\noexpand\csname \expandafter
731     \@gobble\string#1\space\endcsname
732     \if/#5/%
733       \noexpand\no@alphabet@error
734       \noexpand\no@alphabet@error
735     \else
736       \expandafter\noexpand\csname M@#2\endcsname
737       \expandafter\noexpand\csname#2/#3/#4/#5\endcsname
738     \fi
739   }%
740   \toks2\expandafter{#1}%
741   \edef\alpha@list{\the\toks@\noexpand\alpha@elt\the\toks2}%
742   \def\version@elt##1{\toks@\expandafter{##1}%
743     \edef##1{\the\toks@\install@mathalphabet
744       \expandafter\noexpand
745       \csname \expandafter\@gobble
746         \string#1\space\endcsname
747       {\if/#5/%
748         \noexpand\no@alphabet@error
749         \noexpand#1%
750       \else
751         \noexpand\select@group\the\toks2
752       \fi}}%
753   }%
754   \version@list
755   \expandafter\edef\csname \expandafter\@gobble
756     \string#1\space\endcsname{\if/#5/%
757     \noexpand\no@alphabet@error
758     \noexpand#1%
759   \else
760     \noexpand\select@group\the\toks2
761   \fi}%
762   \edef#1{\noexpand\protect
763     \expandafter\noexpand\csname \expandafter
764       \@gobble\string#1\space\endcsname}%
765 }
766 \@onlypreamble\new@mathalphabet

```

(End of definition for \new@mathalphabet.)

\SetMathAlphabet

```

767 \def\SetMathAlphabet#1#2#3#4#5#6{%
768   \@tempswafalse
769   \edef\reserved@b{#3}%
770   \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
771     \ifx\reserved@b\reserved@c \@tempswattrue\fi}%

```

```

772 \cdp@list
773 \if@tempswa
774 \expandafter\SetMathAlphabet@
775 \csname mv@#2\expandafter\endcsname\csname#3/#4/#5/#6\expandafter
776 \endcsname \csname M@#3\expandafter\endcsname
777 \csname \expandafter\@gobble\string#1\space\endcsname#1%
778 \else
779 \@latex@error{Encoding scheme '#3' unknown}\@eha
780 \fi
781 }
782 \@onlypreamble\SetMathAlphabet

```

(End of definition for \SetMathAlphabet.)

\SetMathAlphabet@

```

783 \def\SetMathAlphabet@#1#2#3#4#5{%
784 \expandafter\in@\expandafter#1\expandafter{\version@list}%
785 \ifin@
786 \expandafter\in@\expandafter#4\expandafter{\alpha@list}%
787 \ifin@
788 \begingroup
789 \toks@{%
790 \def\getanddefine@fonts##1##2{%
791 \addto@hook\toks@{\getanddefine@fonts##1##2}%
792 }%
793 \def\reserved@c##1##2##3##4{% % for message below
794 \expandafter\@gobble\string##4}%
795 \def\install@mathalphabet##1##2{%
796 \ifx##1#4%
797 \addto@hook\toks@
798 {\install@mathalphabet#4{\select@group#4#3#2}}%
799 \@font@info{Overwriting math alphabet
800 '\string#5' in version '\expandafter
801 \@gobblefour\string#1'\MessageBreak
802 \@spaces \reserved@c##2 -->
803 \expandafter\@gobble\string#2}%
804 \else
805 \addto@hook\toks@{\install@mathalphabet##1{##2}}%
806 \fi
807 }%
808 #1%
809 \xdef#1{\the\toks@}%
810 \endgroup
811 \else

```

If the math alphabet was defined via \DeclareSymbolFontAlphabet we have remove its external definition and add it as a normal math alphabet to every version before trying to change it in one version.

```

812 \edef\reserved@a{%
813 \noexpand\in@{\string\use@mathgroup}{\meaning#4}}%
814 \reserved@a
815 \ifin@
816 \def\reserved@b##1\use@mathgroup##2##3{%
817 \def\reserved@b{##3}\def\reserved@c{##2}}%
818 \expandafter\reserved@b#4%

```

```

819 \begingroup
820 \def\install@mathalphabet##1##2{%
821   \addto@hook\toks@{\install@mathalphabet##1{##2}}%
822   }%
823 \def\getanddefine@fonts##1##2{%
824   \addto@hook\toks@{\getanddefine@fonts##1##2}%
825   \ifnum##1=\reserved@b
826     \expandafter
827     \addto@hook\expandafter\toks@
828     \expandafter\expandafter\install@mathalphabet
829     \expandafter#4\expandafter
830     {\expandafter\select@group\expandafter
831      #4\reserved@c##2}}%
832   \fi
833   }%
834 \def\version@elt##1{%
835   \toks@{}%
836   ##1%
837   \xdef##1{\the\toks@}%
838   }%
839 \version@list
840 \endgroup

```

Put it into the `\alpha@list` with default ‘error’

```

841 \expandafter\gdef\expandafter\alpha@list\expandafter
842   {\alpha@list
843    \alpha@elt #4\no@alphabet@error \no@alphabet@error}%
844 \gdef#4{\no@alphabet@error #5}% fake things :-)

```

Then call the internal setting routine again:

```

845 \SetMathAlphabet@{#1}{#2}{#3}#4#5%
846 \else
847   \@latex@error{Command ‘\string#5’ not defined as a
848     math alphabet}%
849   {Use \noexpand\DeclareMathAlphabet to define it.}%
850 \fi
851 \fi
852 \else
853   \@latex@error{Math version ‘\expandafter\@gobblefour\string#1’
854     is not
855     defined}{You probably misspelled the name of the math
856     version.^^JOr you have to specify an additional package.}%
857 \fi
858 }
859 \@onlypreamble\SetMathAlphabet@

```

(End of definition for `\SetMathAlphabet@`.)

`\DeclareMathAccent` Could do with more checks like allowing single number in #4 lowercase in #4 etc

```

860 \</2ekernel>
861 \*2ekernel|latexrelease>
862 \<latexrelease>\IncludeInRelease{2019/10/01}%
863 \<latexrelease>{DeclareMathAccent}{Make math accents robust}%
864 \def\DeclareMathAccent#1#2#3#4{%
865   \expandafter\in@\csname sym#3\expandafter\endcsname

```

```

866     \expandafter{\group@list}%
867 \ifin@
868     \begingroup
869     \count\z@=#4\relax
870     \count\tw@\count\z@
871     \divide\count\z@\sist@@n
872     \count@\count\z@
873     \multiply\count@\sist@@n
874     \advance\count\tw@-\count@
875     \if\relax\noexpand#1% is command?
876     \edef\reserved@a{\noexpand\in@
877         {\expandafter\@gobble\string\mathaccent}
878         {\expandafter\meaning
879         \csname\expandafter\@gobble\string#1\space\endcsname}}%
880     \reserved@a
881     \ifin@
882     \expandafter\let
883     \csname\expandafter\@gobble\string#1\space\endcsname
884     \@undefined
885     \expandafter\set@mathaccent
886     \csname sym#3\endcsname#1#2%
887     {\hexnumber@\count\z@}\hexnumber@\count\tw@}%
888     \@font@info{Redefining math accent \string#1}%
889 \else
890     \expandafter\ifx
891     \csname\expandafter\@gobble\string#1\endcsname
892     \relax
893     \expandafter\set@mathaccent
894     \csname sym#3\endcsname#1#2%
895     {\hexnumber@\count\z@}\hexnumber@\count\tw@}%
896     \else
897     \@latex@error{Command '\string#1' already defined}\@eha
898     \fi
899 \fi
900 \else
901 \@latex@error{Not a command name: '\noexpand#1'}\@eha
902 \fi
903 \endgroup
904 \else
905 \@latex@error{Symbol font '#3' is not defined}\@eha
906 \fi
907 }
908 </2ekernel | latexrelease>
909 <latexrelease>\EndIncludeInRelease
910 <latexrelease>\IncludeInRelease{0000/00/00}%
911 <latexrelease>{DeclareMathAccent}{Make math accents robust}%
912 <latexrelease>\def\DeclareMathAccent#1#2#3#4{%
913 <latexrelease> \expandafter\in@\csname sym#3\expandafter\endcsname
914 <latexrelease> \expandafter{\group@list}%
915 <latexrelease> \ifin@
916 <latexrelease> \begingroup
917 <latexrelease> \count\z@=#4\relax
918 <latexrelease> \count\tw@\count\z@
919 <latexrelease> \divide\count\z@\sist@@n

```

```

920 <latexrelease> \count@ \count\z@
921 <latexrelease> \multiply \count@ \sixt@@n
922 <latexrelease> \advance \count\tw@ - \count@
923 <latexrelease> \if \relax \noexpand#1% is command?
924 <latexrelease> \edef \reserved@a {\noexpand \in@
925 <latexrelease> {\expandafter \@gobble \string \mathaccent} {\meaning#1}}%
926 <latexrelease> \reserved@a
927 <latexrelease> \ifin@
928 <latexrelease> \expandafter \set@mathaccent
929 <latexrelease> \csname sym#3 \endcsname #1#2%
930 <latexrelease> {\hexnumber@{\count\z@} \hexnumber@{\count\tw@}}%
931 <latexrelease> \@font@info {Redefining math accent \string#1}%
932 <latexrelease> \else
933 <latexrelease> \expandafter \ifx
934 <latexrelease> \csname \expandafter \@gobble \string#1 \endcsname
935 <latexrelease> \relax
936 <latexrelease> \expandafter \set@mathaccent
937 <latexrelease> \csname sym#3 \endcsname #1#2%
938 <latexrelease> {\hexnumber@{\count\z@} \hexnumber@{\count\tw@}}%
939 <latexrelease> \else
940 <latexrelease> \@latex@error {Command ‘\string#1’ already defined} \@eha
941 <latexrelease> \fi
942 <latexrelease> \fi
943 <latexrelease> \else
944 <latexrelease> \@latex@error {Not a command name: ‘\noexpand#1’} \@eha
945 <latexrelease> \fi
946 <latexrelease> \endgroup
947 <latexrelease> \else
948 <latexrelease> \@latex@error {Symbol font ‘#3’ is not defined} \@eha
949 <latexrelease> \fi
950 <latexrelease> }
951 <latexrelease> \EndIncludeInRelease
952 <*2ekernel>

```

953 \onlypreamble \DeclareMathAccent

(End of definition for \DeclareMathAccent.)

\set@mathaccent

```

954 </2ekernel>
955 <*2ekernel | latexrelease>
956 <latexrelease> \IncludeInRelease {2019/10/01}%
957 <latexrelease> {\set@mathaccent} {makemath accents robust}%
958 \def \set@mathaccent#1#2#3#4{%
959 \xdef#2 {\mathaccent "\mathchar@type#3 \hexnumber@#1#4 \relax}%
960 \MakeRobust#2%
961 }
962 \onlypreamble \set@mathaccent
963 </2ekernel | latexrelease>
964 <latexrelease> \EndIncludeInRelease
965 <latexrelease> \IncludeInRelease {0000/00/00}%
966 <latexrelease> {\set@mathaccent} {makemath accents robust}%
967 <latexrelease>
968 <latexrelease> \def \set@mathaccent#1#2#3#4{%
969 <latexrelease> \xdef#2 {\mathaccent "\mathchar@type#3 \hexnumber@#1#4 \relax}%

```

```

970 <latexrelease>
971 <latexrelease>\EndIncludeInRelease
972 <*2ekernel>

```

(End of definition for \set@mathaccent.)

## \DeclareMathSymbol

```

973 \def\DeclareMathSymbol#1#2#3#4{%
974   \expandafter\in@\csname sym#3\expandafter\endcsname
975   \expandafter{\group@list}%
976   \ifin@
977     \begingroup
978       \count\z@=#4\relax
979       \count\tw@\count\z@
980       \divide\count\z@\sist@@n
981       \count@\count\z@
982       \multiply\count@\sist@@n
983       \advance\count\tw@-\count@
984       \if\relax\noexpand#1% is command?

```

Store the command name with a space attached inside \reserved@@b in case we look at a robust definition.

```

985       \edef\reserved@b{\expandafter\noexpand
986         \csname\expandafter@gobble\string#1\space\endcsname}%

```

Test both #1 and #1<sub>␣</sub> for containing mathchar.

```

987       \edef\reserved@a
988         {\noexpand\in@{\expandafter@gobble\string\mathchar}%
989          {\meaning#1\expandafter\meaning\reserved@b}}%
990       \reserved@a

```

Drop #1<sub>␣</sub> in case it was defined before.

```

991       \global\expandafter\let\reserved@b\@undefined
992       \ifin@
993         \expandafter\set@mathsymbol
994         \csname sym#3\endcsname#1#2%
995         {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
996         \@font@info{Redeclaring math symbol \string#1}%
997       \else
998         \expandafter\ifx
999         \csname\expandafter@gobble\string#1\endcsname
1000         \relax
1001         \expandafter\set@mathsymbol
1002         \csname sym#3\endcsname#1#2%
1003         {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
1004       \else
1005         \@latex@error{Command ‘\string#1’ already defined}\@eha
1006       \fi
1007     \fi
1008   \else
1009     \expandafter\set@mathchar
1010     \csname sym#3\endcsname#1#2
1011     {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
1012   \fi
1013 \endgroup

```

```

1014 \else
1015 \latex@error{Symbol font ‘#3’ is not defined}\@eha
1016 \fi
1017 }
1018 \@onlypreamble\DeclareMathSymbol

```

*(End of definition for \DeclareMathSymbol.)*

**\set@mathchar**

```

1019 \def\set@mathchar#1#2#3#4{%
1020 \global\mathcode‘#2="\mathchar@type#3\hexnumber@#1#4\relax}
1021 \@onlypreamble\set@mathchar

```

*(End of definition for \set@mathchar.)*

**\set@mathsymbol**

```

1022 \def\set@mathsymbol#1#2#3#4{%
1023 \global\mathchardef#2"\mathchar@type#3\hexnumber@#1#4\relax}
1024 \@onlypreamble\set@mathsymbol

```

*(End of definition for \set@mathsymbol.)*

```

1025 %\def\mathsymbol#1#2#3{%
1026 % \@tempcnta=#3\relax
1027 % \@tempcntb\@tempcnta
1028 % \divide\@tempcnta\sixt@@n
1029 % \count@\@tempcnta
1030 % \multiply\count@\sixt@@n
1031 % \advance\@tempcntb-\count@
1032 % \mathchar"\mathchar@type#1\hexnumber@#2%
1033 % \hexnumber@\@tempcnta\hexnumber@\@tempcntb\relax}
1034 %
1035 %\def\DeclareMathAlphabetCharacter#1#2#3{%
1036 % \DeclareMathSymbol{#1}7{#2}{#3}

```

**\DeclareMathDelimiter**

```

1037 \def\DeclareMathDelimiter#1{%
1038 \if\relax\noexpand#1%
1039 \expandafter\@DeclareMathDelimiter
1040 \else
1041 \expandafter\@xxDeclareMathDelimiter
1042 \fi
1043 #1}
1044 \@onlypreamble\DeclareMathDelimiter

```

*(End of definition for \DeclareMathDelimiter.)*

**\@xxDeclareMathDelimiter**

This macro checks if the second arg is a “math type” such as `\mathopen`. The undocumented original code didn’t use math types when the delimiter was a single letter. For this reason the coding is a bit strange as it tries to support the undocumented syntax for compatibility reasons.

```

1045 \def\@xxDeclareMathDelimiter#1#2#3#4{%

```

7 is the default value returned in the case that `\mathchar@type` is passed something unexpected, like a math symbol font name. We locally move `\mathalpha` out of the way so if you use that the right branch is taken. This will still fail if an explicit number 7 is used!

```
1046 \begingroup
1047 \let\mathalpha\mathord
1048 \ifnum7=\mathchar@type{#2}%
1049 \endgroup
```

If this branch is taken we have old syntax (5 arguments).

```
1050 \expandafter\@firstofone
1051 \else
```

If this branch is taken `\mathchar@type` is different from 7 so we assume new syntax. In this case we also use the arguments to set up the letter as a math symbol for the case where it is not used as a delimiter.

```
1052 \endgroup
1053 \DeclareMathSymbol#1{#2}{#3}{#4}%
```

Then we arrange that `\@xDeclareMathDelimiter` only gets #1, #3, #4 ... as it does not expect a math type as argument.

```
1054 \expandafter\@firstoftwo
1055 \fi
1056 {\@xDeclareMathDelimiter#1}{#2}{#3}{#4}}
1057 \@onlypreamble\@xxDeclareMathDelimiter
```

*(End of definition for \@xxDeclareMathDelimiter.)*

`\@DeclareMathDelimiter`

```
1058 \def\@DeclareMathDelimiter#1#2#3#4#5#6{%
1059 \expandafter\in@\csname sym#3\expandafter\endcsname
1060 \expandafter{\group@list}%
1061 \ifin@
1062 \expandafter\in@\csname sym#5\expandafter\endcsname
1063 \expandafter{\group@list}%
1064 \ifin@
1065 \begingroup
1066 \count\z@=#4\relax
1067 \count\tw@\count\z@
1068 \divide\count\z@\sist@@n
1069 \count@\count\z@
1070 \multiply\count@\sist@@n
1071 \advance\count\tw@-\count@
1072 \edef\reserved@c{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
1073 %
1074 \count\z@=#6\relax
1075 \count\tw@\count\z@
1076 \divide\count\z@\sist@@n
1077 \count@\count\z@
1078 \multiply\count@\sist@@n
1079 \advance\count\tw@-\count@
1080 \edef\reserved@d{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
1081 %
1082 \edef\reserved@a{\noexpand\in@
1083 {\expandafter\@gobble\string\delimiter}{\meaning#1}}%
```

```

1084     \reserved@a
1085     \ifin@
1086         \expandafter\set@mathdelimiter
1087             \csname sym#3\expandafter\endcsname
1088             \csname sym#5\endcsname#1#2%
1089             \reserved@c\reserved@d
1090             \@font@info{Redeclaring math delimiter \string#1}%
1091     \else
1092         \expandafter\ifx
1093             \csname\expandafter\@gobble\string#1\endcsname
1094             \relax
1095         \expandafter\set@mathdelimiter
1096             \csname sym#3\expandafter\endcsname
1097             \csname sym#5\endcsname#1#2%
1098             \reserved@c\reserved@d
1099     \else
1100         \@latex@error{Command ‘\string#1’ already defined}\@eha
1101     \fi
1102 \fi
1103 \endgroup
1104 \else
1105     \@latex@error{Symbol font ‘#5’ is not defined}\@eha
1106 \fi
1107 \else
1108     \@latex@error{Symbol font ‘#3’ is not defined}\@eha
1109 \fi
1110 }

```

1111 \@onlypreamble\@DeclareMathDelimiter

(End of definition for \@DeclareMathDelimiter.)

\@xDeclareMathDelimiter

```

1112 \def\@xDeclareMathDelimiter#1#2#3#4#5{%
1113     \expandafter\in@\csname sym#2\expandafter\endcsname
1114     \expandafter{\group@list}%
1115     \ifin@
1116         \expandafter\in@\csname sym#4\expandafter\endcsname
1117         \expandafter{\group@list}%
1118     \ifin@
1119         \begingroup
1120             \count\z@=#3\relax
1121             \count\tw@\count\z@
1122             \divide\count\z@\sixt@@n
1123             \count@\count\z@
1124             \multiply\count@\sixt@@n
1125             \advance\count\tw@-\count@
1126             \edef\reserved@c{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
1127         %
1128         \count\z@=#5\relax
1129         \count\tw@\count\z@
1130         \divide\count\z@\sixt@@n
1131         \count@\count\z@
1132         \multiply\count@\sixt@@n
1133         \advance\count\tw@-\count@

```

```

1134 \edef\reserved@d{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
1135 \expandafter\set@mathdelimiter
1136 \csname sym#2\expandafter\endcsname\csname sym#4\endcsname#1%
1137 \reserved@c\reserved@d
1138 \endgroup
1139 \else
1140 \@latex@error{Symbol font ‘#4’ is not defined}\@eha
1141 \fi
1142 \else
1143 \@latex@error{Symbol font ‘#2’ is not defined}\@eha
1144 \fi
1145 }
1146 \@onlypreamble\@xDeclareMathDelimiter

```

(End of definition for \@xDeclareMathDelimiter.)

`\set@mathdelimiter` We have to end the definition of a math delimiter like `\lfloor` with a space and not with `\relax` as we did before, because otherwise constructs involving `\abovewithdelims` will prematurely end (pr/1329)

```

1147 </2ekernel>
1148 <*2ekernel | latexrelease>
1149 <latexrelease>\IncludeInRelease{2019/10/01}%
1150 <latexrelease> \set@mathdelimiter}{make delimiters robust}%
1151 \def\set@mathdelimiter#1#2#3#4#5#6{%

```

We use `\protected` not `\MakeRobust` so that `\bigl\lfloor` etc. works inside the argument of `\protected@edef`.

```

1152 \protected
1153 \xdef#3{\delimiter"\mathchar@type#4\hexnumber@#1#5%
1154 \hexnumber@#2#6 }%
1155 % \MakeRobust#3%
1156 }
1157 \@onlypreamble\set@mathdelimiter
1158 </2ekernel | latexrelease>
1159 <latexrelease>\EndIncludeInRelease
1160 <latexrelease>\IncludeInRelease{0000/00/00}%
1161 <latexrelease> \set@mathdelimiter}{make delimiters robust}%
1162 <latexrelease>
1163 <latexrelease>\def\set@mathdelimiter#1#2#3#4#5#6{%
1164 <latexrelease> \xdef#3{\delimiter"\mathchar@type#4\hexnumber@#1#5%
1165 <latexrelease> \hexnumber@#2#6 }}
1166 <latexrelease>
1167 <latexrelease>\EndIncludeInRelease
1168 <*2ekernel>

```

(End of definition for \set@mathdelimiter.)

`\set@@mathdelimiter`

```

1169 \def\set@@mathdelimiter#1#2#3#4#5{%
1170 \global\delcode‘#3’=\hexnumber@#1#4\hexnumber@#2#5\relax}
1171 \@onlypreamble\set@@mathdelimiter

```

(End of definition for \set@@mathdelimiter.)

`\DeclareMathRadical`

1172 `\def\DeclareMathRadical#1#2#3#4#5{%`  
 Below is a crude fix to make this macro work if #1 is undefined or `\relax`. Should be improved!

```

1173   \expandafter\ifx
1174     \csname\expandafter\@gobble\string#1\endcsname
1175     \relax
1176     \let#1\radical
1177   \fi
1178   \edef\reserved@a{\noexpand\in@
1179     {\expandafter\@gobble\string\radical}{\meaning#1}}%
1180   \reserved@a
1181   \ifin@
1182     \expandafter\in@\csname sym#2\expandafter\endcsname
1183     \expandafter{\group@list}%
1184   \ifin@
1185     \expandafter\in@\csname sym#4\expandafter\endcsname
1186     \expandafter{\group@list}%
1187   \ifin@
1188     \begingroup
1189       \count\z@=#3\relax
1190       \count\tw@\count\z@
1191       \divide\count\z@\sist@@n
1192       \count@\count\z@
1193       \multiply\count@\sist@@n
1194       \advance\count\tw@-\count@
1195       \edef\reserved@c{%
1196         \hexnumber@\count\z@}\hexnumber@\count\tw@}%
1197       \count\z@=#5\relax
1198       \count\tw@\count\z@
1199       \divide\count\z@\sist@@n
1200       \count@\count\z@
1201       \multiply\count@\sist@@n
1202       \advance\count\tw@-\count@
1203       \edef\reserved@d{%
1204         \hexnumber@\count\z@}\hexnumber@\count\tw@}%

```

Coded inline instead of using `\set@mathradical`

```

1205 %       \expandafter\set@mathradical
1206 %       \csname sym#2\expandafter\endcsname
1207 %       \csname sym#4\endcsname#1%
1208 %       \reserved@c\reserved@d
1209       \xdef#1{\radical"\expandafter\hexnumber@
1210         \csname sym#2\endcsname\reserved@c
1211         \expandafter\hexnumber@
1212         \csname sym#4\endcsname\reserved@d
1213         \relax}%
1214     \endgroup
1215   \else
1216     \@latex@error{Symbol font ‘#4’ is not defined}\@eha
1217   \fi
1218   \else
1219     \@latex@error{Symbol font ‘#2’ is not defined}\@eha
1220   \fi

```

```

1221 \else
1222 \latexerror{Command '\string#1' already defined}\@eha
1223 \fi
1224 }
1225 \@onlypreamble\DeclareMathRadical

(End of definition for \DeclareMathRadical.)
Definition below was wrong it contained \delimiter !

def\set@mathradical#1#2#3#4#5{%
\xdef#3{\radical"\hexnumber@#1#4\hexnumber@#2#5\relax}}

\mathalpha just a dummy currently
1226 \let\mathalpha\relax

(End of definition for \mathalpha.)

\mathchar@type
1227 \def\mathchar@type#1{%
1228 \ifodd 2#1#1 #1\else % is this non-negative number?
1229 \ifx#1\mathord 0\else
1230 \ifx#1\mathop 1\else
1231 \ifx#1\mathbin 2\else
1232 \ifx#1\mathrel 3\else
1233 \ifx#1\mathopen 4\else
1234 \ifx#1\mathclose 5\else
1235 \ifx#1\mathpunct 6\else
1236 7% % anything else is variable ord
1237 \fi
1238 \fi
1239 \fi
1240 \fi
1241 \fi
1242 \fi
1243 \fi
1244 \fi}
1245 \@onlypreamble\mathchar@type

(End of definition for \mathchar@type.)

\DeclareSymbolFontAlphabet

1246 \def\DeclareSymbolFontAlphabet#1#2{%
1247 \expandafter\DeclareSymbolFontAlphabet@
1248 \csname \expandafter\@gobble\string#1\space\endcsname{#2}#1}
1249 \@onlypreamble\DeclareSymbolFontAlphabet

(End of definition for \DeclareSymbolFontAlphabet.)

\DeclareSymbolFontAlphabet@
1250 \def\DeclareSymbolFontAlphabet@#1#2#3{%
We use the switch \if@tempswa to decide if we can declare this symbol font alphabet.
1251 \@tempwatrue

```

First check if #2 is known to be a symbol font

```
1252 \expandafter\in@\csname sym#2\expandafter\endcsname
1253 \expandafter{\group@list}%
1254 \ifin@
```

Check if #1 is defined as a math alphabet defined via \DeclareMathAlphabet:

```
1255 \expandafter\in@\expandafter#1\expandafter{\alpha@list}%
1256 \ifin@
```

If so remove it from the \alpha@list and from all math version macros.

```
1257 \@font@info{Redeclaring math alphabet \string#3}%
1258 \toks@{}%
1259 \def\alpha@elt##1##2##3{%
1260 \ifx##1#1\else\addto@hook\toks@{\alpha@elt##1##2##3}\fi}%
1261 \alpha@list
1262 \xdef\alpha@list{\the\toks@}%

```

Now we loop over all versions and remove the math alphabet:

```
1263 \def\version@elt##1{%
1264 \begingroup
1265 \toks@{}%
1266 \def\getanddefine@fonts####1####2{%
1267 \addto@hook\toks@{\getanddefine@fonts####1####2}}%
1268 \def\install@mathalphabet####1####2{%
1269 \ifx####1#1\else
1270 \addto@hook\toks@{\install@mathalphabet
1271 #####1{####2}}\fi}%
1272 ##1%
1273 \xdef##1{\the\toks@}%
1274 \endgroup
1275 }%
1276 \version@list
1277 \else

```

If #3 is not defined as a math alphabet check if it is defined at all:

```
1278 \expandafter\ifx
1279 \csname\expandafter\@gobble\string#1\space\endcsname
1280 \relax

```

If it is undefined, fine otherwise check if it is a math alphabet defined via \DeclareSymbolFontAlphabet:

```
1281 \else
1282 \edef\reserved@a{%
1283 \noexpand\in@{\string\use@mathgroup}{\meaning#1}}%
1284 \reserved@a
1285 \ifin@
1286 \@font@info{Redeclaring math alphabet \string#3}%
1287 \else

```

Since the command #3 is defined to be something which is not a math alphabet we have to skip redefining it.

```
1288 \@tempswafalse
1289 \@latex@error{Command ‘\string#3’ already defined}\@eha
1290 \fi
1291 \fi
1292 \fi
1293 \else

```

Since the symbol font is not known we better skip defining this alphabet.

```

1294     \@tempswafalse
1295     \@latex@error{Unknown symbol font '#2'}\@eha
1296     \fi
1297     \if@tempswa

```

When we reach this point we are allowed to define #1 to be a symbol font math alphabet. This means that we have to set it to

```
\use@mathgroup <math-settings> \sym<name>
```

The `<math-settings>` are the one for the encoding that is used in the font shape where `\sym<name>` is pointing to. This means that we have to get it from the information stored in `\group@list`. Thus we loop through that list after defining `\group@elt` in a suitable way.

```

1298     \def\group@elt##1##2{%
1299         \expandafter\ifx\csname sym#2\endcsname##1%
1300         \expandafter\reserved@a\string##2\@nil
1301         \fi}%
1302     \def\reserved@a###2/##3\@nil{%
1303         \def\reserved@a{##2}}%
1304     \group@list
1305     \toks@{\relax\ifmmode \else \non@alpherr#1\fi}%
1306     \edef#1{\the\toks@
1307         \noexpand\use@mathgroup
1308         \expandafter\noexpand\csname M@\reserved@a\endcsname
1309         \csname sym#2\endcsname}%
1310     \def#3{\protect#1}%
1311     \fi
1312 }
1313 \@onlypreamble\DeclareSymbolFontAlphabet@
1314 </2ekernel>

```

*(End of definition for \DeclareSymbolFontAlphabet@.)*

## File 29

# ltfssini.dtx

This file contains the top level L<sup>A</sup>T<sub>E</sub>X interface to the font selection scheme commands. See other parts of the L<sup>A</sup>T<sub>E</sub>X distribution, or *The L<sup>A</sup>T<sub>E</sub>X Companion* for higher level documentation of these commands.

## 1 NFSS Initialization

Finally, there are six commands that are to be used in L<sup>A</sup>T<sub>E</sub>X and that we will therefore protect against expansion at the wrong point: `\fontfamily`, `\fontseries`, `\fontshape`, `\fontsize`, `\selectfont`, and `\mathversion`.

```
1 <*2kernel>
2 \message{NFSS initialization,}
```

### 1.1 Providing math *versions*

L<sup>A</sup>T<sub>E</sub>X provides two *versions*. We call them normal and bold, respectively.

```
3 \DeclareMathVersion{normal}
4 \DeclareMathVersion{bold}
```

Now we define the standard font change commands. We don't allow the use of `\rmfamily` etc. in math mode.

(Actually most are now defined further down in the file.)

First the changes to another *family*:

```
5 %\DeclareRobustCommand\rmfamily
6 %      {\not@math@alphabet\rmfamily\mathrm}
7 %      \fontfamily\rmdefault\selectfont}
8 %\DeclareRobustCommand\sffamily
9 %      {\not@math@alphabet\sffamily\mathsf}
10 %      \fontfamily\sfdefault\selectfont}
11 %\DeclareRobustCommand\ttfamily
12 %      {\not@math@alphabet\ttfamily\mathtt}
13 %      \fontfamily\ttdefault\selectfont}
```

Then the commands changing the *series*:

```
14 %\DeclareRobustCommand\bfseries
15 %      {\not@math@alphabet\bfseries\mathbf}
16 %      \fontseries\bfdefault\selectfont}
17 %\DeclareRobustCommand\mdseries
18 %      {\not@math@alphabet\mdseries\relax}
19 %      \fontseries\mddefault\selectfont}
20 \DeclareRobustCommand\upshape
21      {\not@math@alphabet\upshape\relax}
22      \fontshape\updefault\selectfont}
```

Then the commands changing the *shape*:

```
23 \DeclareRobustCommand\slshape
24      {\not@math@alphabet\slshape\relax}
25      \fontshape\sldefault\selectfont}
26 \DeclareRobustCommand\scshape
```

```

27         {\not@math@alphabet\scshape\relax
28          \fontshape\scdefault\selectfont}
29 \DeclareRobustCommand\itshape
30     {\not@math@alphabet\itshape\mathit
31      \fontshape\itdefault\selectfont}

```

## 2 Custom series settings for main document families

This section was introduced 2020/02/02 and for now we support a full rollback (may need splitting later).

```

32 </2ekernel>
33 <*2ekernel | latexrelease>
34 <latexrelease> \IncludeInRelease{2021/11/15}%
35 <latexrelease>          {\DeclareFontSeriesDefault}{Custom series}%

```

One problem with the NFSS approach of handling the series axis turned out to be that (especially with respect to “boldness”) different font families implemented different strategies. For example, with Computer Modern fonts you normally only have **bx** whereas most PostScript fonts offered only **b** but not **bx**. As a result L<sup>A</sup>T<sub>E</sub>X’s standard setting for `\bfdefault` didn’t work with such fonts, but if it got changed to produce **b**, then that didn’t work with Computer Modern if the fonts got combined (e.g., using Computer Modern Typewriter with such fonts).

The solution back then was to provide substitution rules in the font `.fd` such that if a **bx** series got requested the **b** series got used. While this works in that particular case, it isn’t a very general solution. For example, if you happen to have a font family that has several weights you may want to typeset the whole document in a somewhat lighter or darker font but if you then modify `\mddefault` to allow for this, then of course your change only works with that particular family but not with the typewriter or sans serif family you also want to use.

A better solution was provided by the `mweights` package by Bob Tennent that offers defaults on the level of the three main font families in the document: for “rm”, “sf” and “tt” so that font packages could define defaults for the sans serif document font by providing `\bfseries@sf` which then was used when `\bfseries` got executed and the current family was the `\sffamily`.

`\DeclareFontSeriesDefault` We now support this concept directly from within L<sup>A</sup>T<sub>E</sub>X and for use in font packages (or the document preamble) we offer `\DeclareFontSeriesDefault`. This declaration takes three arguments:

**document family interface:** Can either be `rm`, `sf` or `tt`. This is optional and if not given the overall default.

**document series interface:** Can be `md` or `bf`.

**series value:** This is the value that is going to be used with the combination is requested.

For example, `\DeclareFontSeriesDefault[rm]{bf}{sb}` would use **sb** (semi-bold) when `\rmfamily \bfseries` is asked for.

If used without the optional argument, e.g., `\DeclareFontSeriesDefault{bf}{b}` then this is like redefining `\bfdefault` or `\mddefault`.

If some family specific defaults aren't given, e.g. if there are no declarations for, say, `tt` then the format defaults of `\mddefault` and `\bfdefault` are assumed. If those are later changed this is *not* reflected!<sup>37</sup>

`\DeclareFontSeriesDefault` The command to declare font series defaults for the “rm”, “sf” or “tt” family.

```

36 \let\DeclareFontSeriesDefault\undefined      % for rollback
37 \newcommand\DeclareFontSeriesDefault[3][]{%

38   \expand@font@defaults
39   \maybe@update@bfseries@defaults
40   \maybe@update@mdseries@defaults

41   \def\reserved@a{#1}%

```

No optional argument: set up general default.

```

42   \ifx\reserved@a\@empty
43     \ifcsname #2series\endcsname              % supported are
44                                           % \[md/bf]default

```

Adding `\@empty` allows us to detect if the default gets redefined with `\renewcommand` or `\def` by the user.

```

45     \expandafter\def
46       \csname #2default\endcsname{#3\@empty}%
47     \expandafter\def
48       \csname #2default@previous\endcsname{#3\@empty}%
49   \else

50     \@latex@error{Wrong syntax for \string\DeclareFontSeriesDefault}%
51     {Mandatory first argument must be 'md' or 'bf'.}

52   \fi

```

Optional argument given, set up specific default.

```

53   \else
54     \ifcsname #2series@#1\endcsname          % supported are
55                                           % \[md/bf]series@[rm/sf/tt]

56     \expandafter\edef
57       \csname #2series@#1\endcsname{#3}%

```

If the interface is used we remove the frozen kernel default. This way, we know that something was explicitly set up (even if the setup has the same value as the default).

```

58     \expandafter\let
59       \csname #2series@#1@kernel\endcsname\@undefined
60   \else
61     \@latex@error{Wrong syntax for \string\DeclareFontSeriesDefault}%
62     {Optional argument must be 'rm', 'sf', or 'tt'. \MessageBreak
63       Mandatory first argument must be 'md' or 'bf'.}

64   \fi
65 \fi
66 }

```

---

<sup>37</sup>I see no easy way to achieve this without compromising compatibility with existing packages that currently use `mweights` and directly define (some) of the `\mdseries@...` commands but not others.

(End of definition for \DeclareFontSeriesDefault.)

```
67 </2ekernel | latexrelease>
68 <latexrelease>\EndIncludeInRelease
69 <latexrelease>\IncludeInRelease{2020/02/02}%
70 <latexrelease>          {\DeclareFontSeriesDefault}{Custom series}%
71 <latexrelease>
72 <latexrelease>\let\DeclareFontSeriesDefault\@undefined      % for rollback
73 <latexrelease>\newcommand\DeclareFontSeriesDefault[3] [] {%
74 <latexrelease>  \def\reserved@a{#1}%
75 <latexrelease>  \ifx\reserved@a\@empty
76 <latexrelease>    \ifcsname #2series\endcsname          % supported are
77 <latexrelease>                                           % \[md/bf]default
78 <latexrelease>    \expandafter\def
79 <latexrelease>      \csname #2default\endcsname{#3\@empty}%
80 <latexrelease>    \expandafter\def
81 <latexrelease>      \csname #2default@previous\endcsname{#3\@empty}%
82 <latexrelease>  \else
83 <latexrelease>    \@latex@error{Wrong syntax for \string\DeclareFontSeriesDefault}%
84 <latexrelease>      {Mandatory first argument must be 'md' or 'bf'.}
85 <latexrelease>  \fi
86 <latexrelease> \else
87 <latexrelease>  \ifcsname #2series@#1\endcsname          % supported are
88 <latexrelease>                                           % \[md/bf]series@[rm/sf/tt]
89 <latexrelease>    \expandafter\edef
90 <latexrelease>      \csname #2series@#1\endcsname{#3}%
91 <latexrelease>    \expandafter\let
92 <latexrelease>      \csname #2series@#1@kernel\endcsname\@undefined
93 <latexrelease>  \else
94 <latexrelease>    \@latex@error{Wrong syntax for \string\DeclareFontSeriesDefault}%
95 <latexrelease>      {Optional argument must be 'rm', 'sf', or 'tt'. \MessageBreak
96 <latexrelease>      Mandatory first argument must be 'md' or 'bf'.}
97 <latexrelease>  \fi
98 <latexrelease> \fi
99 <latexrelease>}
100 <latexrelease>
101 <latexrelease>\EndIncludeInRelease
102 <latexrelease>\IncludeInRelease{0000/00/00}%
103 <latexrelease>          {\DeclareFontSeriesDefault}{Custom series}%
104 <latexrelease>
105 <latexrelease>\let\DeclareFontSeriesDefault\@undefined
106 <latexrelease>\let\bfseries@rm\@undefined
107 <latexrelease>\let\bfseries@sf\@undefined
108 <latexrelease>\let\bfseries@tt\@undefined
109 <latexrelease>\let\bfseries@rm@kernel\@undefined
110 <latexrelease>\let\bfseries@sf@kernel\@undefined
111 <latexrelease>\let\bfseries@tt@kernel\@undefined
112 <latexrelease>\let\mdseries@rm\@undefined
113 <latexrelease>\let\mdseries@sf\@undefined
114 <latexrelease>\let\mdseries@tt\@undefined
115 <latexrelease>\expandafter\let\csname ver@weights.sty\endcsname\@undefined
116 <latexrelease>
117 <latexrelease>\let\@meta@family@list\@undefined
118 <latexrelease>\let\prepare@family@series@update\@undefined
119 <latexrelease>\let@update@series@target@value\@undefined
```

120 <latexrelease>

This is always called in `\document` so don't make it undefined.

121 <latexrelease>\let\init@series@setup\relax

122 <latexrelease>

123 <latexrelease>\EndIncludeInRelease

124 <\*2ekernel>

125 </2ekernel>

126 <\*2ekernel | latexrelease>

127 <latexrelease>\IncludeInRelease{2020/02/02}%

128 <latexrelease> \mdseries@rm}{Custom series}%

`\mdseries@rm` We initialize the family specific default at the end of the format generation. Later on  
`\mdseries@sf` they may get overwritten in the preamble or a package via `\DeclareFontSeriesDefault`  
`\mdseries@tt` (or possibly directly).

`\bfseries@rm` Conceptual change: The `\bfdefault` will be `b` not `bx` because that is what it should  
`\bfseries@sf` be really for nearly every font except Computer/Latin Modern.

`\bfseries@tt` To account for the fact that by default we typeset in CM or LM we set up the  
`\bfseries@..` defaults to use `bx` instead.

This means that it behaves like before because if the default fonts are used then  
`\bfseries@rm` etc kick in and make `\textbf` use `bx`. However, if the font gets changed  
then `\bfdefault` will get used.

129 \def\bfseries@rm{bx}

130 \def\bfseries@sf{bx}

131 \def\bfseries@tt{bx}

Frozen version of the kernel defaults so we can see if they have changed.

132 \let\bfseries@rm@kernel\bfseries@rm

133 \let\bfseries@sf@kernel\bfseries@sf

134 \let\bfseries@tt@kernel\bfseries@tt

The default for the medium series is `m` and this will be interpreted as resetting both  
weight and width. To reset only one of them the virtual value `?m` and `m?` are available.

135 \def\mdseries@rm{m}

136 \def\mdseries@sf{m}

137 \def\mdseries@tt{m}

(End of definition for `\mdseries@rm` and others.)

`\series@change@debug` For debugging, but right now none of this code is extracted. The idea is to have a separate  
package with debugging code one day.

138 <\*debug>

139 \let\series@change@debug\typeout

140 \let\series@change@debug@gobble

141 </debug>

(End of definition for `\series@change@debug`.)

142 </2ekernel | latexrelease>

143 <latexrelease>\EndIncludeInRelease

144 <latexrelease>\IncludeInRelease{0000/00/00}%

145 <latexrelease> \mdseries@rm}{Custom series}%

146 <latexrelease>

147 <latexrelease>\let\bfseries@rm\@undefined

```

148 <latexrelease>\let\bfseries@sf\@undefined
149 <latexrelease>\let\bfseries@tt\@undefined
150 <latexrelease>\let\bfseries@rm@kernel\@undefined
151 <latexrelease>\let\bfseries@sf@kernel\@undefined
152 <latexrelease>\let\bfseries@tt@kernel\@undefined
153 <latexrelease>\let\mdseries@rm\@undefined
154 <latexrelease>\let\mdseries@sf\@undefined
155 <latexrelease>\let\mdseries@tt\@undefined
156 <latexrelease>\EndIncludeInRelease
157 <*2ekernel>

158 </2ekernel>
159 <*2ekernel | latexrelease>
160 <latexrelease>\IncludeInRelease{2025/11/01}%
161 <latexrelease>    {\prepare@family@series@update}{Support meta family}%

```

`\prepare@family@series@update` This is core command that prepares for the family update. The big difference to the documented code above is that the nested `\ifx` statements seem to be missing. Instead we loop through an internal list that holds the names of the three meta families. This approach allows us to extend the mechanism at a later stage to allow for additional named meta families.

Here is the current definition of that list:

```

\@meta@family@list 162 \def\@meta@family@list{\@elt{rm}\@elt{sf}\@elt{tt}}

```

This macro holds the current “meta” family. At the moment it is either `rm`, `sf`, `tt` or `??`.

`\@currentmetafamily` The latter is used if the current font family does not match any of the document meta families, defined through `\rmdefault`, `\sfdefault` or `\ttdefault`, i.e., in the case that yet another family was selected using `\fontfamily` manually.

The value gets updated by commands like `\rmfamily`, etc.

```

163 \def\@currentmetafamily{??}

164 \def\prepare@family@series@update#1#2{%

```

We start by updating the meta family.

```

165 \def\@currentmetafamily{#1}%

166 \if@forced@series
167 <+debug> \series@change@debug{No series preparation (forced \f@series)\on@line}%
168 \fontfamily#2%
169 \else
170 <+debug> \series@change@debug{Preparing for switching to #1 (#2)\on@line}%
171 \expand@font@defaults

```

We prepare for changing the current series. We have to find it before changing the family as discussed above.

```

172 \let\target@series@value\@empty

```

As the very last item in the meta family list we add `\@elt{??}` and define this pseudo meta family to be the current font family. So if none of the real meta families matched then this will match. This will cover the following case:

- `\bfseries` is called for a family using `bx` (e.g., `CMR`)
- Switch to a font family that is none of the meta families, e.g., via `\fontfamily{ptm}\allowbreak\`

- Then none of the real meta families, match but the final `\@elt{??}` will.
- Therefore if the current series is `\mddefault` or `\bfdefault` it will be detected and the corresponding target series selected.

```
173 \expandafter\edef\csname ??def@ult\endcsname{\f@family}%
```

To find it we loop over the meta family list with a suitable definition of `\@elt`.

```
174 \let\@elt\update@series@target@value
175 \@meta@family@list
```

Last resort pseudo meta family. Will only be looked at if none of the real ones have matched.

```
176 \@elt{??}%
177 \let\@elt\relax
```

That will figure out the correct series value to use without updating it. Now we can change the family.

```
178 \fontfamily#2%
```

After that we update the series. That code is again like the one above.

```
179 \ifx\target@series@value\@empty
180 <+debug> \series@change@debug{Target series still empty ...}%
181 \else
182 \ifx \f@series\target@series@value
183 <+debug> \series@change@debug{Target series unchanged:
184 <+debug> \f@series \space = \target@series@value}%
185 \else
186 \maybe@load@fontshape
187 <+debug> \series@change@debug{Target series:
188 <+debug> \f@series \space -> \target@series@value}%
```

The `\target@series@value` may contain something like `cm` (coming from a default) and so we can't directly assign it to `\f@series` we have to drop any surplus `m` first.

```
189 % \let\f@series\target@series@value
190 \series@maybe@drop@one@m\target@series@value\f@series
191 \fi
192 \fi
193 \fi
194 }
```

(End of definition for `\prepare@family@series@update`, `\@meta@family@list`, and `\@currentmetafamily`.)

`\update@series@target@value` In this macro you basically find the nested `\ifxs` from the outline above. The only difference is that it is parameterized instead of being written out. And we have only for one block of tests because the code is called repeatedly when looping over the meta family list. From the `\@meta@family@list` list we get each meta family name in turn.

```
195 \def\update@series@target@value#1{%
```

There is one additional test at the beginning, because the list contains all meta families and we need to ignore the case where current one from the list and target one are identical.

```
196 \def\reserved@a{#1}%
197 \ifx\@currentmetafamily\reserved@a % rm -> rm do nothing
198 \else
```

```

199 <+debug> \series@change@debug{Trying to match #1: \csname#1def@ult\endcsname
200 <+debug> \space = \f@family\space ?}%

```

We only “do” something if the current font family matches the current meta family.

```

201 \expandafter\ifx\csname#1def@ult\endcsname\f@family

```

If that’s the case we know that this is the block that applies (only one meta family can match). So to speed things up we change `\@elt` so that the rest of the loop gets gobbled.

```

202 \let\@elt\@gobble

```

Then we try to find the right new value for the series (as explained above). The two macros defined first are only there because we now need to use `\csname` and this way the code will be a little faster.

```

203 \expandafter\let\expandafter\reserved@b
204 \csname mdseries@\@currentmetafamily\endcsname
205 \expandafter\let\expandafter\reserved@c
206 \csname bfseries@\@currentmetafamily\endcsname
207 <+debug>\series@change@debug{Targets for mdseries and bfseries:
208 <+debug> \reserved@b\space and \reserved@c}%

```

This here is now identical to the nested `\ifx` block from the outline, except that it there appeared twice in `\rmfamily`. This is now covered by looping and stopping the loop when a match was found.

We have to sanitize the default value first because it may contain something like `mc` and that would never match `\f@series` because there it would be called `c` with the `m` dropped. It would be probably better to do that differently these days, but it is hard to adjust without causing a lot of issues, so we do the dropping in various places instead.

```

209 \expandafter\series@maybe@drop@one@m
210 \csname mdseries@#1\endcsname\reserved@d
211 \ifx\reserved@d\f@series
212 <+debug> \series@change@debug{mdseries@#1 matched -> \reserved@b}%
213 \let\target@series@value\reserved@b
214 \else

```

Again do some sanitizing.

```

215 \expandafter\series@maybe@drop@one@m
216 \csname bfseries@#1\endcsname\reserved@d
217 \ifx\reserved@d\f@series
218 <+debug> \series@change@debug{bfseries@#1 matched -> \reserved@c}%
219 \let\target@series@value\reserved@c
220 \else\ifx\f@series\mddef@ult \let\target@series@value\reserved@b
221 <+debug> \series@change@debug{mddef@ult matched -> \reserved@b}%
222 \else\ifx\f@series\bfdef@ult \let\target@series@value\reserved@c
223 <+debug> \series@change@debug{bfdef@ult matched -> \reserved@c}%
224 \fi\fi\fi\fi
225 \fi
226 \fi
227 }

```

(End of definition for `\update@series@target@value`.)

**\@restoremetafamily** In some situations it might be necessary to rerun the command that sets the current meta family, e.g., rerun `\rmfamily` if `rm` is the current meta family (for example, if the hook `rmfamily` contains some conditional code and the condition has changed at that point). The command `\@restoremetafamily` offers a simply way to do this.

```

228 \def\@restoremetafamily{%
229   \csname \@currentmetafamily family\endcsname
230 }
231
232 (End of definition for \@restoremetafamily.)
233
234 \if2ekernel\latexrelease\
235 \EndIncludeInRelease
236
237 \IncludeInRelease{2020/02/02}%
238 \prepare@family@series@update@{Custom series}%
239 \latexrelease
240 \def\@meta@family@list{\@elt{rm}\@elt{sf}\@elt{tt}}
241 \def\prepare@family@series@update#1#2{%
242 \if@forced@series
243 \fontfamily#2%
244 \else
245 \expand@font@defaults
246 \let\target@series@value\empty
247 \def\target@meta@family@value{#1}%
248 \expandafter\edef\csname ??def@ult\endcsname{\f@family}%
249 \let\@elt@update@series@target@value
250 \@meta@family@list
251 \@elt{??}%
252 \let\@elt@relax
253 \fontfamily#2%
254 \ifx\target@series@value\empty
255 \else
256 \ifx \f@series\target@series@value
257 \else
258 \maybe@load@fontshape
259 \series@maybe@drop@one@m\target@series@value\f@series
260 \fi
261 \fi
262 \fi
263 \def@update@series@target@value#1{%
264 \def\reserved@a{#1}%
265 \ifx\target@meta@family@value\reserved@a % rm -> rm do nothing
266 \else
267 \expandafter\ifx\csname#1def@ult\endcsname\f@family
268 \let\@elt@gobble
269 \expandafter\let\expandafter\reserved@b
270 \csname mdseries@\target@meta@family@value\endcsname
271 \expandafter\let\expandafter\reserved@c
272 \csname bfseries@\target@meta@family@value\endcsname
273 \expandafter\series@maybe@drop@one@m
274 \csname mdseries@#1\endcsname\reserved@d
275 \ifx\reserved@d\f@series
276 \let\target@series@value\reserved@b
277 \else
278 \expandafter\series@maybe@drop@one@m
279 \csname bfseries@#1\endcsname\reserved@d
280 \ifx\reserved@d\f@series
281 \let\target@series@value\reserved@c
282 \else\ifx\f@series\mddef@ult \let\target@series@value\reserved@b

```

```

280 <latexrelease> \else\ifx\f@series\bfdef@ult \let\target@series@value\reservedc
281 <latexrelease> \fi\fi\fi\fi
282 <latexrelease> \fi
283 <latexrelease> \fi
284 <latexrelease>}

285 <latexrelease>\EndIncludeInRelease
286 <latexrelease>\IncludeInRelease{0000/00/00}%
287 <latexrelease> {\prepare@family@series@update}{Custom series}%
288 <latexrelease>
289 <latexrelease>\let\@meta@family@list\@undefined
290 <latexrelease>\let\prepare@family@series@update\@undefined
291 <latexrelease>\let@update@series@target@value\@undefined
292 <latexrelease>
293 <latexrelease>\EndIncludeInRelease
294 <*2ekernel>

```

`\init@series@setup`

```

295 </2ekernel>
296 <*2ekernel | latexrelease>
297 <latexrelease>\IncludeInRelease{2020/02/02}%
298 <latexrelease> {\init@series@setup}{Custom series}%
    This is code to be run at begin document ...
299 \def\init@series@setup{%

```

We only want `bx` in `\bfseries@rm` if the roman font is Computer Modern or Latin Modern, otherwise it should be `b`. It was set to `bx` in the kernel so that any font use with the default families in the preamble get this value. Now at the real document start we check if the fonts have been changed. If there was a `\DeclareFontSeriesDefault` declaration or `\bfseries@rm` was directly altered then it differs from `\bfseries@rm@kernel` and we do nothing. Otherwise we check if `\rmdefault` is one of the CM/LM font families and if so we keep `bx` otherwise we change it to `b`.

This approach doesn't cover one case: CM/LM got changed to a different family that supports `bx`, but the support package for that family used `\def\bfseries@rm{bx}` instead of using `\DeclareFontSeriesDefault`. In that case the code here changes it to `b`. Solution: use the `\DeclareFontSeriesDefault` interface.

```

300 \ifx\bfseries@rm@kernel\bfseries@rm
301 \expandafter\in@\expandafter{\rmdefault}%
302 {cmr,cmss,cmtt,lcms,lcmtt,lmr,lmss,lmtt}%
303 \ifin@ \else \def\bfseries@rm{b}\fi\fi

```

Same approach for `\bfseries@sf` and `\bfseries@tt`:

```

304 \ifx\bfseries@sf@kernel\bfseries@sf
305 \expandafter\in@\expandafter{\sfdefault}%
306 {cmr,cmss,cmtt,lcms,lcmtt,lmr,lmss,lmtt}%
307 \ifin@ \else \def\bfseries@sf{b}\fi\fi
308 \ifx\bfseries@tt@kernel\bfseries@tt
309 \expandafter\in@\expandafter{\ttdefault}%
310 {cmr,cmss,cmtt,lcms,lcmtt,lmr,lmss,lmtt}%
311 \ifin@ \else \def\bfseries@tt{b}\fi\fi

```

If the document preamble has changed the `\familydefault` or if the if the `\rmdefault` contains a new font family, we may have to adjust the series defaults accordingly, before starting typesetting.

Similarly, if the user has changed the `\mddefault` or the medium series for the family selected as document font we may also have to adjust the `\seriesdefault`.

On the other hand if the document font is still CM or LM then `\bfdefault` is wrong, because it is now saying `b` and not `bx` as it should for such fonts.

To fix all this we first run `\reset@font` (the internal kernel name for `\normalfont`). This will set up the document encoding, family, series and shape based on the current values of `\encodingdefault`, `\familydefault`, `\seriesdefault` and `\shapedefault`. However, if the family (from `\familydefault`) has special medium default we should switch to that (and not use what is current value from `\seriesdefault`). This can be achieved by afterwards calling `\mediumseries` and then changing `\seriesdefault` to the now current series value (in `\f@series`).

But what should happen if `\seriesdefault` got explicitly changed? In that case the explicit change should survive and we should not alter `\seriesdefault`. This is solved by comparing the current value of `\seriesdefault` with a kernel version saved in the format and if they differ we do not call `\mdseries` or change `\seriesdefault`.

```

312 \reset@font
313 \ifx\seriesdefault\seriesdefault@kernel
314 \mdseries
315 \let\seriesdefault\f@series
316 \fi
317 }%
```

(End of definition for `\init@series@setup`.)

As the kernel code now implements the same functionality as `mweights`, albeit internally coded slightly differently, that package shouldn't be loaded any more. We therefore pretend that it already got loaded. Thus, a font package that tries to load it and then sets `\mdseries@.`, etc. will continue to work but will now use the kernel code.

Of course, mid-term such package should probably use `\DeclareFontSeriesDefault` instead of making using low-level definitions.

```

318 \expandafter\let\csname ver@mweights.sty\endcsname\fmtversion
319 </2ekernel | latexrelease>
320 <latexrelease>\EndIncludeInRelease
321 <latexrelease>\IncludeInRelease{0000/00/00}%
322 <latexrelease> \init@series@setup}{Custom series}%
```

This is always called in `\document` so don't make it undefined.

```

323 <latexrelease>\let\init@series@setup\relax
324 <latexrelease>
325 <latexrelease>\expandafter\let\csname ver@mweights.sty\endcsname\@undefined
326 <latexrelease>
327 <latexrelease>\EndIncludeInRelease
328 <*2ekernel>
329 </2ekernel>
330 <*2ekernel | latexrelease>
331 <latexrelease>\IncludeInRelease{2021/11/15}%
332 <latexrelease> \bfseries}{Custom series with hooks}%
```

`\bfseries` This document command switches to the bold series.

```

333 \DeclareRobustCommand\bfseries{%
334 \not@math@alphabet\bfseries\mathbf
```

In the original NFSS definition it then called `\fontseries` with the value `\bfdefault`. In the new scheme we have more alternatives and therefore check if the current family (`\f@family`) is the current `\rmdef@ult`, `\sfdef@ult` or `\ttdef@ult` and then select the correct family default in that case.

```

335 \expand@font@defaults
336 \maybe@update@bfseries@defaults

337 \ifx\f@family\rmdef@ult \fontseries\bfseries@rm
338 \else\ifx\f@family\sfdef@ult \fontseries\bfseries@sf
339 \else\ifx\f@family\ttdef@ult \fontseries\bfseries@tt

```

If not `\bfdefault` is used.

```

340 \else \fontseries\bfdefault
341 \fi\fi\fi

```

This hook in contrast is always executed.

```

342 \UseHook{bfseries}%
343 \selectfont
344 }

```

*(End of definition for \bfseries.)*

`\maybe@update@bfseries@defaults` If `\bfdefault` and `\bfdefault@previous` are different then the default got changed directly through the legacy interface (i.e., via `\def` or `\renewcommand`). In that case we reset all meta family defaults so that the document behaves like it was the case before the new mechanism was introduced.

```

345 \def\maybe@update@bfseries@defaults{%
346 \ifx\bfdefault\bfdefault@previous\else

```

We add `\@empty` and then let `\bfdefault@previous` to `\bfdefault` so that we can detect any further change.

```

347 \expandafter\def\expandafter\bfdefault
348 \expandafter{\bfdefault\@empty}%
349 \let\bfdefault@previous\bfdefault

```

And we reset the meta family defaults (`\bfdef@ult` is an expanded version of `\bfdefault`).

```

350 \let\bfseries@rm\bfdef@ult
351 \let\bfseries@sf\bfdef@ult
352 \let\bfseries@tt\bfdef@ult

```

Formats that set up parallel fonts, e.g., for Japanese, can use this hook to add resets here. Not that this hook is only run when resets are necessary.

```

353 \UseHook{bfseries/defaults}%
354 \fi
355 }

```

*(End of definition for \maybe@update@bfseries@defaults.)*

`\mdseries` This document command switches to the medium series.

```

356 \DeclareRobustCommand\mdseries{%
357 \not@math@alphabet\mdseries\relax
358 \expand@font@defaults
359 \maybe@update@mdseries@defaults
360 \ifx\f@family\rmdef@ult \fontseries\mdseries@rm
361 \else\ifx\f@family\sfdef@ult \fontseries\mdseries@sf
362 \else\ifx\f@family\ttdef@ult \fontseries\mdseries@tt

```

```

363     \else                                \fontseries\mddefault
364     \fi\fi\fi
365     \UseHook{mdseries}%
366     \selectfont
367 }

```

(End of definition for \mdseries.)

\maybeupdate@mdseries@defaults

```

368 \def\maybeupdate@mdseries@defaults{%
369   \ifx\mddefault\mddefault@previous\else
370     \expandafter\def\expandafter\mddefault\expandafter{\mddefault\@empty}%
371     \let\mddefault@previous\mddefault
372     \let\mdseries@rm\mddef@ult
373     \let\mdseries@sf\mddef@ult
374     \let\mdseries@tt\mddef@ult

```

Formats that set up parallel fonts, e.g., for Japanese, can use this hook to add resets here.

```

375     \UseHook{mdseries/defaults}%
376     \fi
377 }

```

(End of definition for \maybeupdate@mdseries@defaults.)

```

378 </2ekernel | latexrelease>
379 <latexrelease>\EndIncludeInRelease
380 <latexrelease>\IncludeInRelease{2020/10/01}%
381 <latexrelease>          {\bfseries}{Custom series with hooks}%
382 <latexrelease>
383 <latexrelease>\let\maybeupdate@bfseries@defaults\@undefined
384 <latexrelease>\let\maybeupdate@mdseries@defaults\@undefined
385 <latexrelease>
386 <latexrelease>\DeclareRobustCommand\bfseries{%
387 <latexrelease>  \not@math@alphabet\bfseries\mathbf
388 <latexrelease>  \expand@font@defaults
389 <latexrelease>  \ifx\bfdefault\bfdefault@previous\else
390 <latexrelease>    \expandafter\def\expandafter\bfdefault
391 <latexrelease>      \expandafter{\bfdefault\@empty}%
392 <latexrelease>    \let\bfdefault@previous\bfdefault
393 <latexrelease>    \let\bfseries@rm\bfdef@ult
394 <latexrelease>    \let\bfseries@sf\bfdef@ult
395 <latexrelease>    \let\bfseries@tt\bfdef@ult
396 <latexrelease>    \UseHook{bfseries/defaults}%
397 <latexrelease>  \fi
398 <latexrelease>    \ifx\f@family\rmdef@ult      \fontseries\bfseries@rm
399 <latexrelease>    \else\ifx\f@family\sfdef@ult  \fontseries\bfseries@sf
400 <latexrelease>    \else\ifx\f@family\ttdef@ult  \fontseries\bfseries@tt
401 <latexrelease>    \else
402 <latexrelease>      \fi\fi\fi
403 <latexrelease>  \UseHook{bfseries}%
404 <latexrelease>  \selectfont
405 <latexrelease>}
406 <latexrelease>
407 <latexrelease>\DeclareRobustCommand\mdseries{%
408 <latexrelease>  \not@math@alphabet\mdseries\relax

```

```

409 <latexrelease> \expand@font@defaults
410 <latexrelease> \ifx\mddefault\mddefault@previous\else
411 <latexrelease> \expandafter\def\expandafter\mddefault\expandafter{\mddefault\@empty}%
412 <latexrelease> \let\mddefault@previous\mddefault
413 <latexrelease> \let\mdseries@rm\mddef@ult
414 <latexrelease> \let\mdseries@sf\mddef@ult
415 <latexrelease> \let\mdseries@tt\mddef@ult
416 <latexrelease> \UseHook{mdseries/defaults}%
417 <latexrelease> \fi
418 <latexrelease> \ifx\f@family\rmdef@ult \fontseries\mdseries@rm
419 <latexrelease> \else\ifx\f@family\sfdef@ult \fontseries\mdseries@sf
420 <latexrelease> \else\ifx\f@family\ttdef@ult \fontseries\mdseries@tt
421 <latexrelease> \else \fontseries\mddefault
422 <latexrelease> \fi\fi\fi
423 <latexrelease> \UseHook{mdseries}%
424 <latexrelease> \selectfont
425 <latexrelease>}
426 <latexrelease>\EndIncludeInRelease
427 <latexrelease>\IncludeInRelease{2020/02/02}%
428 <latexrelease> {\bfseries}{Custom series with hooks}%
429 <latexrelease>
430 <latexrelease>
431 <latexrelease>\DeclareRobustCommand\bfseries{%
432 <latexrelease> \not@math@alphabet\bfseries\mathbf
433 <latexrelease> \expand@font@defaults
434 <latexrelease> \ifx\f@family\rmdef@ult \fontseries\bfseries@rm
435 <latexrelease> \else\ifx\f@family\sfdef@ult \fontseries\bfseries@sf
436 <latexrelease> \else\ifx\f@family\ttdef@ult \fontseries\bfseries@tt
437 <latexrelease> \else \fontseries\bfdefault
438 <latexrelease> \fi\fi\fi
439 <latexrelease> \selectfont
440 <latexrelease>}
441 <latexrelease>
442 <latexrelease>\DeclareRobustCommand\mdseries{%
443 <latexrelease> \not@math@alphabet\mdseries\relax
444 <latexrelease> \expand@font@defaults
445 <latexrelease> \ifx\f@family\rmdef@ult \fontseries\mdseries@rm
446 <latexrelease> \else\ifx\f@family\sfdef@ult \fontseries\mdseries@sf
447 <latexrelease> \else\ifx\f@family\ttdef@ult \fontseries\mdseries@tt
448 <latexrelease> \else \fontseries\mddefault
449 <latexrelease> \fi\fi\fi
450 <latexrelease> \selectfont
451 <latexrelease>}
452 <latexrelease>
453 <latexrelease>
454 <latexrelease>
455 <latexrelease>\EndIncludeInRelease
456 <latexrelease>\IncludeInRelease{0000/00/00}%
457 <latexrelease> {\bfseries}{Custom series with hooks}%
458 <latexrelease>
459 <latexrelease>\DeclareRobustCommand\bfseries
460 <latexrelease> {\not@math@alphabet\bfseries\mathbf
461 <latexrelease> \fontseries\bfdefault\selectfont}
462 <latexrelease>\DeclareRobustCommand\mdseries

```

```

463 <latexrelease>          {\not@math@alphabet\mdseries\relax
464 <latexrelease>          \fontseries\mddefault\selectfont}
465 <latexrelease>
466 <latexrelease>\EndIncludeInRelease
467 <*2ekernel>
468
469
470
471
472 </2ekernel>
473 <*2ekernel | latexrelease>
474 <latexrelease> \IncludeInRelease{2020/10/01}%
475 <latexrelease>          {\expand@font@defaults}{Custom series with hooks}%

```

`\expand@font@defaults` The family specific defaults are fully expanded, i.e., they are defined via `\edef` inside `\rm@def@ult` `\DeclareFontSeriesDefault`. However, the overall defaults, e.g., `\bfdefault` may have been redefined by the user and thus may not be fully expanded. So to enable reliable comparison we make expanded versions of them. That we rerun each time. The alternative would be to only allow for changes before begin document.

```

\sf@def@ult
\tt@def@ult
\md@def@ult
\bf@def@ult
476 \def\expand@font@defaults{%
477   \edef\rmdef@ult{\rmdefault}%
478   \edef\sfdef@ult{\sfdefault}%
479   \edef\ttdef@ult{\ttdefault}%

```

The series defaults may contain some surplus `m` that we need to drop here.

```

480   \series@maybe@drop@one@m\bfdefault\bfdef@ult
481   \series@maybe@drop@one@m\mddefault\mddef@ult

```

Formats that set up parallel fonts, e.g., for Japanese, can use this hook to add additional code here.

```

482   \UseHook{expand@font@defaults}%
483 }

```

(End of definition for `\expand@font@defaults` and others.)

`\rmfamily` Here are the document level commands for changing the main font families, or rather, here is a documented outline of the code, the actual code is then streamlined and somewhat generalized.

```

DeclareRobustCommand\rmfamily{%
  \not@math@alphabet\rmfamily\mathrm

```

If families are changed then we have to do a bit more work. In the original NFSS implementation a family change kept encoding, series shape and size unchanged but now we can't any longer simply reuse the current series value. Instead we may have to change it from one family default to the next.

```

\expand@font@defaults

```

We have to do the testing while the current family is still unchanged but we have to do the adjustment of the series after it got changed (because the new family might have different sets of shapes available and we certainly don't want to see substitution going on. So we use `\target@series@value` to hold the target series (if any).

```

\let\target@series@value\@empty

```

Thus, if the current family is the sans family

```
\ifx\f@family\sfdef@ult
```

and if we using the medium series of the sans family

```
\ifx\f@series\mdseries@sf
```

then lets switch to the medium series for the serif family

```
\let\target@series@value\mdseries@rm
```

and if we use the bold series of the sans family switch to the bold default of the serif family:

```
\else\ifx\f@series\bfseries@sf \let\target@series@value\bfseries@rm
```

However, the sans family may not have any specific defaults set, so we also compare with the overall defaults.

```
\else\ifx\f@series\mddef@ult \let\target@series@value\mdseries@rm
\else\ifx\f@series\bfdef@ult \let\target@series@value\bfseries@rm
```

If neither test was true we leave the series alone. This way a special manual setting such as `\fontseries{lc}` is not undone if the family changes (of course there may not be any support for it in the new family but then the NFSS substitution kicks in and sorts it out).

```
\fi\fi\fi\fi
```

We need to do the same if the current family is the typewriter family:

```
\else\ifx\f@family\ttdef@ult
\ifx\f@series\mdseries@tt \let\target@series@value\mdseries@rm
\else\ifx\f@series\bfseries@tt \let\target@series@value\bfseries@rm
\else\ifx\f@series\mddef@ult \let\target@series@value\mdseries@rm
\else\ifx\f@series\bfdef@ult \let\target@series@value\bfseries@rm
\fi\fi\fi\fi
\fi\fi
```

With these preparations for series out of the way we can now change the font family to `\rmdefault`.

```
\fontfamily\rmdefault
```

If `\target@series@value` is still empty there is nothing more to do other than selecting the new family. However, if not then we should update the font series now as well. But there is one further subtle issue. We may not have loaded an `.fd` file for our target font family yet. In the past that was done in `\selectfont` if necessary but since we are now doing all the comparisons in `\fontseries` we need to make sure that the font family specifications are already loaded prior to calling `\fontseries`.

```
\ifx\target@series@value\@empty \else
\maybe@load@fontshape
```

Updating the series in this case means directly changing `\f@series` to the target value. We don't want to go through `\fontseries` because that would apply the mappings and then `bx + b` would keep `bx` instead of changing to `b` as desired. as

```
\let\f@series\target@series@value
\fi
\selectfont}
```

So now for the real definition: most of the code above gets delegated to a helper command `\prepare@family@series@update` so that the definition becomes again fairly short. In addition we add a hook, mainly for our Japanese friends so that the code can be extended prior to the call to `\selectfont`.

```
484 \DeclareRobustCommand\rmfamily{%
485   \not@math@alphabet\rmfamily\mathrm
```

This holds all the code discussed above, first argument is the meta family, i.e., `rm` in this case, and second argument is the default family name, e.g., `cmr` indirectly accessed via `\rmdefault`. This is calling `\fontfamily` and if necessary `\fontseries` as outline above.

```
486   \prepare@family@series@update{rm}\rmdefault
```

Then comes the hook code (by default a no-op) and finally the call to `\selectfont`.

```
487   \UseHook{rmfamily}%
488   \selectfont}
```

The definitions for `\sffamily` and `\ttfamily` are similar, the differences are only in what font families get checked.

```
\sffamily
\ttfamily
489 \DeclareRobustCommand\sffamily{%
490   \not@math@alphabet\sffamily\mathsf
491   \prepare@family@series@update{sf}\sfdefault
492   \UseHook{sffamily}%
493   \selectfont}

494 \DeclareRobustCommand\ttfamily{%
495   \not@math@alphabet\ttfamily\mathtt
496   \prepare@family@series@update{tt}\ttdefault
497   \UseHook{ttfamily}%
498   \selectfont}
```

*(End of definition for \rmfamily, \sffamily, and \ttfamily.)*

```
rmfamily  Declare the hooks used above.
sffamily  499 \NewHook{rmfamily}
ttfamily  500 \NewHook{sffamily}
normalfont 501 \NewHook{ttfamily}
expand@font@defaults 502 \NewHook{normalfont}
bfseries  503 \NewHook{expand@font@defaults}
bfseries/defaults 504 \NewHook{bfseries}
mdseries  505 \NewHook{bfseries/defaults}
mdseries/defaults 506 \NewHook{mdseries}
507 \NewHook{mdseries/defaults}
```

*(End of definition for rmfamily and others.)*

```

\@rmfamilyhook These four hooks have legacy versions used in 2020/02/02 so we should support them
\@sffamilyhook until they aren't any longer used.
\@ttfamilyhook By default the hooks do nothing and in new code they should not any longer be
\@defaultfamilyhook used. Instead use the standard hook system and the hook names rmfamily, sffamily,
                    ttfamily. Instead of \@defaultfamilyhook use normalfont.

508 \let\@rmfamilyhook\@empty
509 \let\@sffamilyhook\@empty
510 \let\@ttfamilyhook\@empty
511 \let\@defaultfamilyhook\@empty

(End of definition for \@rmfamilyhook and others.)

512 </2ekernel | latexrelease>
513 <latexrelease>\EndIncludeInRelease
514 <latexrelease>\IncludeInRelease{2020/02/02}%
515 <latexrelease>                {\expand@font@defaults}{Custom series with hooks}%
516 <latexrelease>
517 <latexrelease>\def\expand@font@defaults{%
518 <latexrelease>  \edef\rmdef@ult{\rmdefault}%
519 <latexrelease>  \edef\sffdef@ult{\sffdefault}%
520 <latexrelease>  \edef\ttdef@ult{\ttdefault}%
521 <latexrelease>  \edef\bfdef@ult{\bfdefault}%
522 <latexrelease>  \edef\mddef@ult{\mddefault}%
523 <latexrelease>  \edef\famdef@ult{\familydefault}%
524 <latexrelease>}%
525 <latexrelease>
526 <latexrelease>
527 <latexrelease>\DeclareRobustCommand\rmfamily{%
528 <latexrelease>  \not@math@alphabet\rmfamily\mathrm
529 <latexrelease>  \prepare@family@series@update{rm}\rmdefault
530 <latexrelease>  \@rmfamilyhook
531 <latexrelease>  \selectfont}
532 <latexrelease>\DeclareRobustCommand\sffamily{%
533 <latexrelease>  \not@math@alphabet\sffamily\mathsf
534 <latexrelease>  \prepare@family@series@update{sf}\sffdefault
535 <latexrelease>  \@sffamilyhook
536 <latexrelease>  \selectfont}
537 <latexrelease>\DeclareRobustCommand\ttfamily{%
538 <latexrelease>  \not@math@alphabet\ttfamily\mathtt
539 <latexrelease>  \prepare@family@series@update{tt}\ttdefault
540 <latexrelease>  \@ttfamilyhook
541 <latexrelease>  \selectfont}
542 <latexrelease>\let\@rmfamilyhook\@empty
543 <latexrelease>\let\@sffamilyhook\@empty
544 <latexrelease>\let\@ttfamilyhook\@empty
545 <latexrelease>
546 <latexrelease>
547 <latexrelease>\EndIncludeInRelease
548 <latexrelease>\IncludeInRelease{0000/00/00}%
549 <latexrelease>                {\expand@font@defaults}{Custom series with hooks}%
550 <latexrelease>
551 <latexrelease>\let\expand@font@defaults\@undefined
552 <latexrelease>
553 <latexrelease>\DeclareRobustCommand\bfseries

```

```

554 <latexrelease>          {\not@math@alphabet\bfseries\mathbf
555 <latexrelease>          \fontseries\bfdefault\selectfont}
556 <latexrelease>\DeclareRobustCommand\mdseries
557 <latexrelease>          {\not@math@alphabet\mdseries\relax
558 <latexrelease>          \fontseries\mddefault\selectfont}
559 <latexrelease>\DeclareRobustCommand\rmfamily
560 <latexrelease>          {\not@math@alphabet\rmfamily\mathrm
561 <latexrelease>          \fontfamily\rmdefault\selectfont}
562 <latexrelease>\DeclareRobustCommand\sffamily
563 <latexrelease>          {\not@math@alphabet\sffamily\mathsf
564 <latexrelease>          \fontfamily\sfdefault\selectfont}
565 <latexrelease>\DeclareRobustCommand\ttfamily
566 <latexrelease>          {\not@math@alphabet\ttfamily\mathtt
567 <latexrelease>          \fontfamily\ttdefault\selectfont}
568 <latexrelease>
569 <latexrelease>\let\@rmfamilyhook\@undefined
570 <latexrelease>\let\@sffamilyhook\@undefined
571 <latexrelease>\let\@ttfamilyhook\@undefined
572 <latexrelease>
573 <latexrelease>\EndIncludeInRelease
574 <*2ekernel>

```

`\IfFontSeriesContextTF` With the ability for `\bfseries` or `\mdseries` to be mapped to different NFSS axis values it becomes important to have the ability to determine the current context as we can no longer look at `\fontseries` to answer a question such as “am I currently typesetting in a bold typeface?”

This is provided by the test `\IfFontSeriesContextTF`. It takes three arguments:

- The context we try to check (either `bf` for bold or `md` for medium, i.e., the same that can go into the first mandatory argument of `\DeclareFontSeriesDefault`),
- what to do if we are in this context (true case) and
- what to do if we are not (false case).

This allows you to define commands like `\IfBold`, e.g.,

```
\NewDocumentCommand\IfBold{mm}{\IfFontSeriesContextTF{bf}{#1}{#2}}
```

and then do

```
This is \IfBold{bold}{non-bold} text.
```

and get the appropriate result.

```

575 </2ekernel>
576 <*2ekernel | latexrelease>
577 <latexrelease>\IncludeInRelease{2020/10/01}%
578 <latexrelease>          {\IfFontSeriesContextTF}{Font series context}%
579 \DeclareRobustCommand\IfFontSeriesContextTF[1]{%
580   \expand@font@defaults

```

In the beginning we haven’t found the context we are looking for.

```
581   \@font@series@contextfalse
```

We store the requested context away for use in the tests.

```
582   \def\requested@test@context{#1}%
```

The next definition is there to ensure that get a final match during testing even if the current family is non of the meta families (`rm`, `sf` or `tt`). This will then basically tests if the current font family matches the overall default.

```
583 \expandafter\edef\csname ??def@ult\endcsname{\f@family}%
```

Then we run through the meta family list (currently containing just the three values) followed by the artificial meta family `??` and test each of them in turn using `\test@font@series@context` as the testing command.

```
584 \let\@elt\test@font@series@context
585 \@meta@family@list
586 \@elt{??}%
587 \let\@elt\relax
```

Following that we evaluate the status of `\if@font@series@context` to determine which of the remaining arguments (true/false case) we have to execute.

```
588 \if@font@series@context
589 \expandafter\@firstoftwo
590 \else
591 \expandafter\@secondoftwo
592 \fi
593 }
```

The T/F variants were introduced in 2025 but to simplify rollback we pretend that this happened at the same time as `\IfFontSeriesContextTF`.

```
594 \long\def\IfFontSeriesContextT#1{\IfFontSeriesContextTF{#1}{}}
595 \def\IfFontSeriesContextF{\IfFontSeriesContextTF{}}
```

*(End of definition for \IfFontSeriesContextTF.)*

`\test@font@series@context` This tests the context (stored in `\requested@test@context`) and updates the boolean if the right context is found.

```
596 \def\test@font@series@context#1{%
```

First task is to figure out whether the current family matches `\rmfamily`, `\sffamily`, etc. so in `\reserved@a` we store the value of `\rmdef@ult` (or whatever the given meta family is) and compare that to `\f@family`.

```
597 \edef\reserved@a{\csname #1def@ult\endcsname}%
598 \ifx\f@family\reserved@a
```

If they match we have found the right meta family so we don't need to test any of the remaining meta family and therefore change `\@elt` to `\@gobble`.

```
599 \let\@elt\@gobble
```

Now we have to test if `\f@series` matches the requested context (e.g., whether `\bfseries@rm` has that value if the current meta family is `rm` and we are looking for the `bf` context).

```
600 \expandafter\ifx
601 \csname\requested@test@context series@#1\endcsname\f@series
```

If yes we change the boolean and are done.

```
602 \@font@series@contexttrue
```

If not then maybe the reason is that nothing special was set up for that meta family so we also check now check if `\f@series` matches the overall default (e.g., `\bfdef@ult` if we are looking for the bold context). If that matches we change the boolean.

```

603     \else
604         \expandafter\ifx
605             \csname\requested@test@context def@ult\endcsname\f@series
606             \@font@series@contexttrue
607     \fi\fi\fi
608 }

```

(End of definition for `\test@font@series@context`.)

`\if@font@series@context` The boolean to signal if we found the requested font series context.

```

609 \newif\if@font@series@context
610
611 (End of definition for \if@font@series@context.)
612
613 </2ekernel | latexrelease>
614 <latexrelease>\EndIncludeInRelease
615 <latexrelease>\IncludeInRelease{0000/00/00}%
616 <latexrelease>          {\IfFontSeriesContextTF}{Font series context}%
617 <latexrelease>
618 <latexrelease>\let\IfFontSeriesContextTF\@undefined
619 <latexrelease>\let\IfFontSeriesContextT\@undefined
620 <latexrelease>\let\IfFontSeriesContextF\@undefined
621 <latexrelease>\let\test@font@series@context\@undefined
622 <latexrelease>\let\if@font@series@context\@undefined
623 <latexrelease>\let\@font@series@contexttrue\@undefined
624 <latexrelease>\let\@font@series@contextfalse\@undefined
625 <latexrelease>\EndIncludeInRelease
626 <*2ekernel>

```

### 3 Supporting nested emphasis

By default L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> supports two levels of nested emphasis: if the current font has an upright shape then it switches to `\itshape` otherwise to `\eminnershape` (which defaults to `\upshape`). This means nested emphasis will oscillate between italic and upright shapes.

Sometimes it would be nice to allow for a more lengthy sequence, but instead of providing a fixed one L<sup>A</sup>T<sub>E</sub>X now offers a general mechanism that allows to define arbitrary sequences.

`\DeclareEmphSequence`

`\emforce`

This declaration expects a comma separated list of (font) change declarations corresponding to increasing levels of emphasis. The mechanism tries to be “smart” and verifies that the declarations actually alter the font. If not it will ignore this level and tries the next one—the assumption being that there was a manual font change in the document to the font that is now supposed to be used for emphasis. Of course, this only works if the declarations in the list actually change the font and not, say, just the color. In such a case one has to use `\emforce` to which directs the mechanism to use the level even if the font attributes haven’t changed.

`\emreset`

If the nesting is so deep, that the specified levels are exhausted then `\emreset` is used as a final set of declarations (which by default returns back to the upright shape). Any additional nesting levels will then reuse the list from its beginning.

`\DeclareEmphSequence` `\DeclareEmphSequence` expects a clist of declaration. Spaces in the argument are dropped to avoid spurious spaces in the output. The declarations are additive. At the very end the shape is reset using `\emreset` and `\emforce` so that this case is never skipped.<sup>38</sup> Further nested calls restart at the beginning.

```

624 </2ekernel>
625 <*2ekernel|latexrelease>
626 <latexrelease>\IncludeInRelease{2020/02/02}%
627 <latexrelease>{\DeclareEmphSequence}{Nested emph}%
628 \def\DeclareEmphSequence#1{%
629   \protected@edef\emfontdeclare@clist{\zap@space#1, \@empty\emforce\emreset}%
630 }

```

By default the it is empty, in which case `\emminnershape` is used by L<sup>A</sup>T<sub>E</sub>X.

```

631 \let\emfontdeclare@clist\@empty

```

*(End of definition for \DeclareEmphSequence.)*

`\emrest` Reset the font to upright and upper/lower case. With the default rules using `\shapedefault` does that for us but to be on the safe side we do it like this:

```

632 \DeclareRobustCommand\emreset{\upshape\ulcshape}

```

*(End of definition for \emrest.)*

`\em` The new definition for `\em` (and implicitly `\emph`) is the same as before as long as `\emfontdeclare@clist` is empty.

```

633 \DeclareRobustCommand\em{%
634   \@nomath\em
635   \ifx\emfontdeclare@clist\@empty
636     \ifdim \fontdimen\@ne\font >\z@
637       \emminnershape \else \itshape \fi
638   \else

```

But if not we use the list to decide how to do emphasis.

We use the current font to check if the declarations have any effect, so even a size change is allowed and identified as a modification (but a color change, for example, isn't). So first we save the current status.

```

639   \edef\em@currfont{\csname\curr@fontshape/\f@size\endcsname}%

```

Then we grab the next element from the list and check if it can be used.

```

640   \expandafter\do@emfont@update\emfontdeclare@clist\do@emfont@update
641   \fi
642 }
643 \def\emminnershape{\upshape}

```

*(End of definition for \em.)*

`\do@emfont@update` We know that the list (if not empty) has at least 2 elements separated by a comma, so we pick up the first in #1 and the rest in #2.

```

644 \def\do@emfont@update#1,#2\do@emfont@update{%

```

First action is to alter the list and move the first entry to the end

```

645   \def\emfontdeclare@clist{#2,#1}%

```

<sup>38</sup>Maybe we should not add `\emforce` but allow that case to be skipped as well. Of course, that might result in an endless loop if somebody defines a sequence without any font change and without `\emforce` but ...

Then we execute the current declaration. Appending `\selectfont` means one can write just `\fontshape{it}` and that works then too.

```
646 % \typeout{Use: \detokenize{#1}}%
647 #1\selectfont
```

We then compare the current font with our saved version, but with a slight twist: we add `\em@force` at the end of the name. Normally this is empty so has no effect but if there was an `\emforce` as part of `#1` it will append a `/` to the font name (making it invalid) thus this will then always fail the test.

If the test fails we are done and the declarations will be used. Otherwise we will try the next declaration in the sequence.

```
648 \expandafter\ifx\csname \curr@fontshape/\f@size\em@force
```

For the comparison with `\ifx` we have to expand `\em@currfont` once as the relevant info is inside.

```
649 \expandafter\endcsname
650 \em@currfont
651 \expandafter\do@emfont@update\emfontdeclare@clist\do@emfont@update
```

If `\emforce` was used, we have to undo its effect:

```
652 \else
653 \let\em@force\@empty
654 \fi
655 }
```

(End of definition for `\do@emfont@update`.)

`\emforce` The definition of `\emforce` is simple: change `\em@force` to make the above test always  
`\em@force` invalid.

```
656 \protected\def\emforce{\def\em@force{}}
657 \let\em@force\@empty
658 </2ekernel | latexrelease>
659 <latexrelease>\EndIncludeInRelease
```

(End of definition for `\emforce` and `\em@force`.)

`\em` These are the older definitions for `\em`, prior to 2020.

`\emminnershape` We also have to define the *emphasize* font change command (i.e. `\em`). This command will look is the current font is sloped (i.e. has a positive `\fontdimen1`) and will then select either `\upshape` or `\itshape`.

```
660 <latexrelease>\IncludeInRelease{2015/01/01}{\DeclareEmphSequence}{Nested emph}%
661 <latexrelease>\let\DeclareEmphSequence\@undefined
662 <latexrelease>\let\emfontdeclare@clist\@undefined
663 <latexrelease>\let\emreset\@undefined
664 <latexrelease>\let\do@emfont@update\@undefined
665 <latexrelease>\let\emforce\@undefined
666 <latexrelease>\let\em@force\@undefined
667 <latexrelease>
668 <latexrelease>\DeclareRobustCommand\em
669 <latexrelease>{\@nomath\em \ifdim \fontdimen\@ne\font >\z@
670 <latexrelease>\emminnershape \else \itshape \fi}%
671 <latexrelease>\EndIncludeInRelease
672 <latexrelease>
673 <latexrelease>\IncludeInRelease{0000/00/00}{\DeclareEmphSequence}{Nested emph}%
```

```

674 <latexrelease>\DeclareRobustCommand\em
675 <latexrelease>          {\@nomath\em \ifdim \fontdimen\@ne\font >\z@
676 <latexrelease>          \upshape \else \itshape \fi}%
677 <latexrelease>\let\eminnershape\@undefined
678 <latexrelease>\EndIncludeInRelease
679 <*2ekernel>

```

*(End of definition for \em and \eminnershape.)*

**\not@math@alphabet** This function generates an error message when it is called in math mode. The same function should be defined in `newfont.sty`.

```

680 \def\not@math@alphabet#1#2{%
681     \relax
682     \ifmmode
683         \@latex@error{Command \noexpand#1invalid in math mode}%
684         {%
685             Please
686             \ifx#2\relax
687                 define a new math alphabet^^J%
688                 if you want to use a special font in math mode%
689             \else

```

We have to a `\noexpand` below to prevent expansion of `#2`. In case of `#1` we can omit this (due to the current definition of robust commands since they do come out right there :-).

```

690             use the math alphabet \noexpand#2instead of
691             the #1command%
692         \fi
693         .
694     }%
695 \fi}

```

*(End of definition for \not@math@alphabet.)*

Finally we provide two abbreviations to switch to the L<sup>A</sup>T<sub>E</sub>X *versions*.

```

696 \DeclareRobustCommand\boldmath{\@nomath\boldmath
697         \mathversion{bold}}
698 \DeclareRobustCommand\unboldmath{\@nomath\unboldmath
699         \mathversion{normal}}

```

Here we switch to the default math version by defining the internal macro `\math@version`. We dare not to call `\mathversion` at this place because this would call `\glb@settings`.

```

700 \def\math@version{normal}

```

### 3.1 Legacy

We start by defining a few macros that are part of standard L<sup>A</sup>T<sub>E</sub>X's user interface. The use of these functions is not encouraged, but they will allow to process older documents without changes to the source.

**\newfont**

```

701 \def\newfont#1#2{\@ifdefinable#1{\font#1=#2\relax}}

```

*(End of definition for \newfont.)*

`\symbol`

```
702 </2ekernel>
703 <*2ekernel | latexrelease>
704 <latexrelease>\IncludeInRelease{2020/10/01}%
705 <latexrelease>{\symbol}{XeTeX change for math}%
706 \ifdefined\XeTeXversion
707 \DeclareRobustCommand\symbol[1]{\Ucharcat#1 12\relax}
708 \else
709 \DeclareRobustCommand\symbol[1]{\char#1\relax}
710 \fi
711 </2ekernel | latexrelease>
712 <latexrelease>\EndIncludeInRelease
713 <latexrelease>\IncludeInRelease{0000/00/00}%
714 <latexrelease>{\symbol}{XeTeX change for math}%
715 <latexrelease>
716 <latexrelease>\DeclareRobustCommand\symbol[1]{\char#1\relax}
717 <latexrelease>
718 <latexrelease>\EndIncludeInRelease
719 <*2ekernel>
```

*(End of definition for \symbol.)*

## 3.2 Miscellaneous

`\@setfontsize` This abbreviation is used by L<sup>A</sup>T<sub>E</sub>X's user level size changing commands, such as `\large`.

`\@setsize` 720 `\def\@setfontsize#1#2#3{\@nomath#1%`

For the benefit of people relying on keeping the name of the current font command saved in `\@currsize` we define it. To ensure that `\@setfontsize` keeps being robust we omit this assignment during times where `\protect` differs from `\@typeset@protect`.

```
721 \ifx\protect\@typeset@protect
722 \let\@currsize#1%
723 \fi
724 \fontsize{#2}{#3}\selectfont}
```

For compatibility we also define `\@setsize` the 209 command

```
725 <*compat>
726 \def\@setsize#1#2#3#4{\@setfontsize#1{#4}{#2}}
727 </compat>
```

*(End of definition for \@setfontsize and \@setsize.)*

`\hexnumber@` To set up L<sup>A</sup>T<sub>E</sub>X's special math character definitions we first provide a macro to generate hexadecimal numbers. It is a rather simple `\ifcase`.

```
728 \def\hexnumber@#1{\ifcase\number#1
729 0\or 1\or 2\or 3\or 4\or 5\or 6\or 7\or 8\or
730 9\or A\or B\or C\or D\or E\or F\fi}
```

*(End of definition for \hexnumber@.)*

`\nfss@text` In its simplest form `\nfss@text` is an `\mbox`. This will produce unbreakable text outside math and inside math you will get text with the same fonts as outside. The only drawback is that such item won't change sizes in subscripts. But this behavior can be easily changed.

With the `amstex` style option one will get a sub style called `amstext` which will redefine the `\nfss@text` macro to produce correct text in all sizes.

We have to use `\def` instead of the shorter `\let` since `\mbox` is undefined when we reach this point.

```
731 \def\nfss@text#1{\mbox{#1}}
```

(End of definition for `\nfss@text`.)

`\copyright` The definition of `\copyright` was changed so that it works in other type styles, and to make it robust. We leave the family untouched so that the copyright notice will come out differently if a different font family is in use. This command is commented out, since it is now defined in `ltoutenc.dtx`.

```
732 %\DeclareRobustCommand\copyright
733 %    {\ooalign{\hfil
734 %        \raise.07ex\hbox{\mdseries\upshape c}\hfil\crcr
735 %        \mathhexbox20D}}}
```

(End of definition for `\copyright`.)

`\normalfont` The macro `\reset@font` is used in L<sup>A</sup>T<sub>E</sub>X to switch to a standard font, in order to initialize the current font in situations where typesetting is done in a new visual context (e.g. in a footnote). We define it here to allow the test for the new L<sup>A</sup>T<sub>E</sub>X version above but nevertheless are able to run all kind of mixtures.

The user interface name for `\reset@font` is `\normalfont`:

```
736 </2ekernel>
737 <*2ekernel|latexrelease>
738 <latexrelease>\IncludeInRelease{2025/11/01}%
739 <latexrelease>          {\normalfont}{Support meta family}%
740 \DeclareRobustCommand\normalfont{%
```

Instead of calling `\usefont`, as it was done in the past, we inline the code from `\usefont` as we want to add the hook before `\selectfont`, but after all the font attributes are set.

```
741 \fontencoding\encodingdefault
742 \edef\f@family{\familydefault}%
743 \edef\f@series{\seriesdefault}%
744 \edef\f@shape{\shapedefault}%
```

Now that `\f@family` is set we can update the meta family macro.

```
745 \set@current@meta@family
```

Any earlier `\fontseries`, etc. should be canceled and we should switch unconditionally to the requested font face so we drop any code that may have been stored in `\delayed@f@adjustment`.

```
746 \let\delayed@f@adjustment\@empty
747 \UseHook{normalfont}%
748 \selectfont}
749 \let\reset@font\normalfont
```

(End of definition for `\normalfont` and `\reset@font`.)

`\set@current@meta@family` This macros determines the current meta family by comparing the current family in `\f@family` with the various document font defaults, e.g., `\rmdefault`.

```
750 \def\set@current@meta@family {%
```

Because these defaults can be set by the user and may contain the family name indirectly, we first expand them to ensure we do not get false negatives.

```

751 \edef\rmdef@ult{\rmdefault}%
752 \ifx\f@family\rmdef@ult
753 \def\@currentmetafamily{rm}%
754 \else
755 \ifx\f@family\sfdef@ult
756 \def\@currentmetafamily{sf}%
757 \else
758 \ifx\f@family\ttdef@ult
759 \def\@currentmetafamily{tt}%
760 \else
761 \def\@currentmetafamily{??}%
762 \fi
763 \fi
764 \fi
765 }

```

(End of definition for \set@current@meta@family.)

```

766 % \changes{v3.2g}{2021/03/18}
767 % {Add missing 2020/02/02 latexrelease entry.}
768 </2ekernel | latexrelease>
769 <latexrelease>\EndIncludeInRelease
770 <latexrelease>\IncludeInRelease{2021/06/01}%
771 <latexrelease> \{\normalfont\}{Cancel delayed actions}%
772 <latexrelease>
773 <latexrelease>\DeclareRobustCommand\normalfont{%
774 <latexrelease> \fontencoding\encodingdefault
775 <latexrelease> \edef\f@family{\familydefault}%
776 <latexrelease> \edef\f@series{\seriesdefault}%
777 <latexrelease> \edef\f@shape{\shapedefault}%
778 <latexrelease> \let\delayed@f@adjustment\@empty
779 <latexrelease> \UseHook{normalfont}%
780 <latexrelease> \@defaultfamilyhook % hookname from 2020/02 will vanish
781 <latexrelease> \selectfont}
782 <latexrelease>\let\reset@font\normalfont
783 <latexrelease>
784 <latexrelease>\let\set@current@meta@family\undefined
785 <latexrelease>\EndIncludeInRelease

786 <latexrelease>\IncludeInRelease{2020/10/01}%
787 <latexrelease> \{\normalfont\}{Add hook to \normalfont}%
788 <latexrelease>
789 <latexrelease>\DeclareRobustCommand\normalfont{%
790 <latexrelease> \fontencoding\encodingdefault
791 <latexrelease> \edef\f@family{\familydefault}%
792 <latexrelease> \edef\f@series{\seriesdefault}%
793 <latexrelease> \edef\f@shape{\shapedefault}%
794 <latexrelease> \UseHook{normalfont}%
795 <latexrelease> \@defaultfamilyhook % hookname from 2020/02 will vanish
796 <latexrelease> \selectfont}
797 <latexrelease>
798 <latexrelease>\let\reset@font\normalfont
799 <latexrelease>

```

```

800 <latexrelease>\EndIncludeInRelease
801 <latexrelease>
802 <latexrelease>\IncludeInRelease{2020/02/02}%
803 <latexrelease>          {\normalfont}{Add hook to \normalfont}%
804 <latexrelease>
805 <latexrelease>\DeclareRobustCommand\normalfont{%
806 <latexrelease>    \fontencoding\encodingdefault
807 <latexrelease>    \edef\f@family{\familydefault}%
808 <latexrelease>    \edef\f@series{\seriesdefault}%
809 <latexrelease>    \edef\f@shape{\shapedefault}%
810 <latexrelease>    \@defaultfamilyhook
811 <latexrelease>    \selectfont}
812 <latexrelease>
813 <latexrelease>\let\reset@font\normalfont
814 <latexrelease>
815 <latexrelease>\let\@defaultfamilyhook\@empty
816 <latexrelease>
817 <latexrelease>\EndIncludeInRelease
818 <latexrelease>
819 <latexrelease>\IncludeInRelease{0000/00/00}%
820 <latexrelease>          {\normalfont}{Add hook to \normalfont}%
821 <latexrelease>
822 <latexrelease>\DeclareRobustCommand\normalfont
823 <latexrelease>          {\usefont\encodingdefault
824 <latexrelease>              \familydefault
825 <latexrelease>              \seriesdefault
826 <latexrelease>              \shapedefault
827 <latexrelease>              \relax}
828 <latexrelease>\let\reset@font\normalfont
829 <latexrelease>
830 <latexrelease>\let\@defaultfamilyhook\@undefined
831 <latexrelease>
832 <latexrelease>\EndIncludeInRelease
833 <*2ekernel>

```

`\fontfamily` One place where the current meta family should be set is `\fontfamily`, which is why we defined it here after the definition of `\set@current@meta@family` in this file.

```

834 </2ekernel>
835 <*2ekernel | latexrelease>
836 <latexrelease>\IncludeInRelease{2025/11/01}%
837 <latexrelease>          {\fontfamily}{Set meta family}%
838 \DeclareRobustCommand\fontfamily[1]
839   {\edef\f@family{#1}\set@current@meta@family}
840 </2ekernel | latexrelease>
841 <latexrelease>\EndIncludeInRelease
842 <latexrelease>\IncludeInRelease{0000/00/00}%
843 <latexrelease>          {\fontfamily}{Set meta family}%
844 <latexrelease>
845 <latexrelease>\DeclareRobustCommand\fontfamily[1]{\edef\f@family{#1}}
846 <latexrelease>\EndIncludeInRelease
847 <*2ekernel>

```

*(End of definition for \fontfamily.)*

We left out the special L<sup>A</sup>T<sub>E</sub>X fonts which are not automatically included in the base version of the font selection since these fonts contain only a few characters which are also included in the AMS fonts so anybody who is using these fonts doesn't need them. But for compatibility reasons we will define these symbols.

```

848 \def\not@base#1{\@latex@error
849   {Command \noexpand#1not provided in base LaTeX2e}%
850   {Load the latexsym or the amsfonts package to
851     define this symbol}}
852 \def\mho{\not@base\mho}
853 \def\Join{\not@base\Join}
854 \def\Box{\not@base\Box}
855 \def\Diamond{\not@base\Diamond}
856 \def\leadsto{\not@base\leadsto}
857 \def\squsubset{\not@base\squsubset}
858 \def\sqsupset{\not@base\sqsupset}
859 \def\lhd{\not@base\lhd}
860 \def\unlhd{\not@base\unlhd}
861 \def\rhd{\not@base\rhd}
862 \def\unrhd{\not@base\unrhd}

```

We now initialize all variables set by `\DeclareErrorFont`. These values are not really important since they will be overwritten later on by the definition in `fontdef.ltx`.

However, if `fontdef.cfg` is corrupted then at least a hopefully suitable error font is present.

```

863 \DeclareErrorFont{OT1}{cmr}{m}{n}{10}  %% don't modify this setting
864                                         %% overwrite it in fontdef.cfg
865                                         %% if necessary

```

We also set some default values for `\f@family` etc. Note that we don't yet have any encodings that comes later. In the past this was implicitly done by `\DeclareErrorFont`.

```

866 \def\f@family{cmr}                    % can't use \fontfamily at this point as
867                                         % defaults aren't set up yet

```

Previously the default values for series and shape were set by calling `\fontseries` and `\fontshape`, but their action is now delayed until `\selectfont` which isn't called inside the format (to avoid unnecessarily loading a font that may never get used). We therefore have to set `\f@series` and `\f@shape` directly instead.

```

868 \def\f@series{m}                      % \fontseries{m}
869 \def\f@shape{n}                       % \fontshape{n}
870 \fontsize{10}{10}

```

The initial `fontenc` package load list. This will get overwritten in `fonttext` and is only provided in case an old `fonttext.cfg` does not define the command:

```

871 \def\@fontenc@load@list{\@elt{T1,OT1}}

```

We now load the customizable parts of NFSS.

```

872 \InputIfFileExists{fonttext.cfg}
873   {\typeout{=====^^J%
874             ^^J%
875             Local config file fonttext.cfg used^^J%
876             ^^J%
877             =====}%}

```

```

878         \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
879     }
880     {\input{fonttext.ltx}}
881 \let\@addtofilelist\@gobble

Ditto for math although I don't think that we will get a lot of customization :-)
882 \InputIfFileExists{fontmath.cfg}
883     {\typeout{=====^^J%
884             ^^J%
885             Local config file fontmath.cfg used^^J%
886             ^^J%
887             =====}%
888     \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
889     }
890     {\input{fontmath.ltx}}
891 \let\@addtofilelist\@gobble

```

Then we preload several fonts. This file might be customized *without* changing the behavior of the format (i.e. necessary font definitions will be loaded at runtime if they are not preloaded). This is done in the file `preload.ltx`.

```

892 \InputIfFileExists{preload.cfg}
893     {\typeout{=====^^J%
894             ^^J%
895             Local config file preload.cfg used^^J%
896             ^^J%
897             =====}%
898     \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
899     }
900     {\input{preload.ltx}}
901 \let\@addtofilelist\@gobble

```

`\seriesdefault` After `\seriesdefault` got defined inside `fonttext.ltx` or a `.cfg` file overwriting it, we alter its value by appending `\@empty` to it. This will vanish if expanded but allows us to check if the default gets altered (even to the same value) in the document preamble. All we have to do is to save the current value somewhere and later compare the two. For this we use `\seriesdefault@kernel`.

```

902 \expandafter\def\expandafter\seriesdefault\expandafter{\seriesdefault\@empty}
903 \let\seriesdefault@kernel\seriesdefault

```

(End of definition for `\seriesdefault` and `\seriesdefault@kernel`.)

`\@acci` We also save the values of some accents in `\@acci`, `\@accii` and `\@acciii` so they can  
`\@accii` be restored by a `minipage` inside a `tabbing` environment.  
`\@acciii` 904 \let\@acci\ ' \let\@accii\ ' \let\@acciii\=

(End of definition for `\@acci`, `\@accii`, and `\@acciii`.)

`\cal` Here were the two old `\alphabet identifiers`.

`\mit` (End of definition for `\cal` and `\mit`.)

```

905 \</2ekernel>

```

# File 30

## fontdef.dtx

### 1 Introduction

This file is used to generate the files `fonttext.ltx` (text font declarations) and `fontmath.ltx` (math font declarations), which are used during the format generation. It contains the declaration of the standard text encodings used at the site as well as a minimal subset of font shape groups that NFSS will look at to ensure that the specified encodings are valid.

The math part contains the setup for math encodings as well as the default math symbol declarations that belong to the encoding.

It is possible to change this setup (by using other fonts, or defaults) without losing the ability to process documents written at other sites. Portability in this sense means that a document will compile without errors. It does not mean, however, that identical output will be produced. For this it is necessary that the distributed setup is used at both installations.

### 2 Customization

You are not allowed to change this source file! If you want to change the default encodings and/or the font shape groups preloaded you should create a copy of `fonttext.ltx` under the name `fonttext.cfg` and change this copy. If  $\text{\LaTeX}$  2<sub>ε</sub> finds a file of this name it will use it, otherwise it uses the standard file which is `fontdef.ltx`.

If you don't plan to use Computer Modern much or at all, it might (!) be a good idea to make your own `fonttext.cfg`. Look at the comments below (docstrip module 'text') to see what should go into such a file.

To change the math font setup use a copy of `fontmath.ltx` under the name `fontmath.cfg` and change this copy. However, dealing with this interface is even more a job for an expert than changing the text font setup — in short, we don't encourage either.

**Warning:** please note that we don't support customised  $\text{\LaTeX}$  versions. Thus, before sending in a bug report please try your test file with a  $\text{\LaTeX}$  format which is not customised and send in the log from that version (unless the problem goes away).

Please note: the following standard encodings have to be defined in all local variants of `font....cfg` to guarantee that all  $\text{\LaTeX}$  installations behave in the same way.

T1	Cork $\text{\TeX}$ text encoding
OT1	old $\text{\TeX}$ text encoding
U	unknown encoding
OML	old $\text{\TeX}$ math letters encoding
OMS	old $\text{\TeX}$ math symbols encoding
OMX	old $\text{\TeX}$ math extension symbols encoding
TU	Unicode

Notice that some of these encodings are ‘old’ in the sense that we hope that they will be superseded soon by encoding standards defined by the T<sub>E</sub>X user community. Therefore this set of default encodings may change in the future.

The first candidate is OT1 which will soon be replaced by T1, the official T<sub>E</sub>X text encoding.

**Warning:** If you add additional encodings to this file there is no guarantee any longer that files processable at your installation will also be processable at other installations. Thus, if you make use of such an encoding in your document, e.g. if you intend to typeset in Cyrillic (OT2 encoding), you need to specify this encoding in the preamble of your document prior to sending it to another installation. Once the encoding is specified in that place in your document, the document is processable at all L<sup>A</sup>T<sub>E</sub>X installations (provided they have suitable fonts installed).

For this reason we suggest that you define a short package file that sets up an additional encoding used at your site (rather than putting the encoding into this file) since this package can easily be shipped with your document.

### 3 The docstrip modules

The following modules are used to direct **docstrip** in generating external files:

driver	produce a documentation driver file
text	produce the file <b>fonttext.ltx</b>
math	produce the file <b>fontmath.ltx</b>
cfgtext	produce a dummy <b>fonttext.cfg</b> file
cfgmath	produce a dummy <b>fontmath.cfg</b> file

A typical **docstrip** command file would then have entries like:

```
generateFile{fonttext.ltx}{t}{\from{fontdef.dtx}{text}}
```

### 4 A driver for this document

The next bit of code contains the documentation driver file for T<sub>E</sub>X, i.e. the file that will produce the documentation you are currently reading. It will be extracted from this file by the DOCSTRIP program.

```
1 <*driver>
2 \documentclass{ltxdoc}
3 \GetFileInfo{fontdef.dtx}
4 \begin{document}
5   \DocInput{fontdef.dtx}
6 \end{document}
7 </driver>
```

### 5 The fonttext.ltx file

The identification is done earlier on with a \ProvidesFile declaration.

```
8 <*text>
9 \typeout{=== Don't modify this file, use a .cfg file instead ===^~J}
```

## 5.1 Encodings

This file declares the standard encodings for text and math fonts. All others should be declared in packages or in the documents directly.

For every text encoding there are normally a number of encoding specific commands, e.g. accents, special characters, etc. (The definition for such a command might have to change when the encoding is changed, because the character is in a different position, or not available at all, or the accent is produced in a different way.) This is handled by a general mechanism which is described in `ltoutenc.dtx`.

By convention, text encoding specific declarations, including the `\DeclareFontEncoding` declaration, are kept in separate file of the form `<enc>enc.def`, e.g. `ot1enc.def`. This allows other applications to make use of the declarations as well.

Similar to the default encoding, the loading of the encoding files for the two major text encodings shouldn't be changed. In particular, the `inputenc` package depends on this.

```
10 \input {omlenc.def}
11 \input {omsenc.def}
```

Documents containing a lot of accented characters should really be using T1 fonts. We therefore load this after OT1 so that T1 encoding specific commands are executed as fast as possible (encoding files are no longer reloaded in `fontenc`).

```
12 \input {ot1enc.def}
13 \input {t1enc.def}
14 \input {ts1enc.def}

15 \ifx\Umathcode\@undefined
```

We then set the default text font encoding. This will hopefully change some day to T1. This setting should *not* be changed to produce a portable format.

```
16 \fontencoding{OT1}

The initial fontenc package load list if an 8-bit TEX engine is used:
17 \def\@fontenc@load@list{\@elt{T1,OT1}}
18 \def\rmsubstdefault{cmr}
19 \def\sfsubstdefault{cmss}
20 \def\ttsubstdefault{cmtt}
21 \LoadFontDefinitionFile{TS1}{cmr}

22 \else
```

Unicode.

```
23 \input {tuenc.def}
24 \fontencoding{TU}

The initial fontenc package load list if a Unicode engine is used:
25 \def\@fontenc@load@list{\@elt{TU}}
26 \DeclareFontSubstitution{TU}{lmr}{m}{n}
27 \LoadFontDefinitionFile{TU}{lmr}
28 \LoadFontDefinitionFile{TU}{lmss}
29 \LoadFontDefinitionFile{TU}{lmtt}

30 \def\rmsubstdefault{lmr}
31 \def\sfsubstdefault{lmss}
32 \def\ttsubstdefault{lmtt}
33 \LoadFontDefinitionFile{TS1}{lmr}
```

```
34 \DeclareFontSubstitution{TU}{lmr}{m}{n}
```

End of Unicode branch.

```
35 \fi
```

If different encodings for text fonts are in use one could put the common setup into `\DeclareFontEncodingDefaults`. There is now a better mechanism so using this interface is discouraged!

```
36 \DeclareFontEncodingDefaults{}{}
```

The default font substitution for an encoding is defined in the corresponding `...enc.def` file so for OT1, T1, and TS1 this is already defined.

```
37 %\DeclareFontSubstitution{T1}{cmr}{m}{n}
```

```
38 %\DeclareFontSubstitution{OT1}{cmr}{m}{n}
```

```
39 %\DeclareFontSubstitution{TS1}{cmr}{m}{n}
```

This release of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> assumes that the ec fonts are available. It is possible to change this to point to some other font family (e.g., Times with the appropriate encoding if it is available) without making documents non-portable. However, in such a case documents will produce different page breaks at other sites. The substitution defaults can all be changed without losing portability as long as there are font shape definitions for the selected substitutions.

For every encoding declaration, L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> will try to verify that the given substitution information makes sense, i.e. that it is impossible to go into an endless loop if font substitution happens. This is done at the moment the `\begin{document}` is encountered. L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> will then check that for every encoding the substitution defaults form a valid font shape group, which means that it will check if there is a `\DeclareFontShape` declaration for this combination. We will therefore load the corresponding `.fd` files now. If we don't do this they would be loaded at verification time (i.e. at `\begin{document}`) which would delay processing unnecessarily.

**Warning:** Please note that this means that you have to regenerate the format whenever you change any of these `.fd` files since L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> will not read `.fd` files if it already knows about the encoding/family combination.

The `\nfss@catcodes` ensures that white space is ignored in any definitions made in the fd files.

```
40 \begingroup
```

```
41 \nfss@catcodes
```

```
42 \input {t1cmr.fd}
```

```
43 \input {ot1cmr.fd}
```

```
44 \input {ts1cmr.fd}
```

```
45 \endgroup
```

We also load some other font definition files which are normally needed in a document. This is only done for processing speed and you can comment the next two lines out to save some memory. If necessary these files are then loaded when your document is processed. (Loading `.fd` files is a less drastic step compared to preloading fonts because the number of fonts is limited 255 at (nearly) every T<sub>E</sub>X installation, while the amount of main memory is not a limiting factor at most installations.)

```
46 \begingroup
```

```
47 \nfss@catcodes
```

```
48 \input {t1cmss.fd}
```

```

49 \input {t1cmtt.fd}
50 \input {ot1cmss.fd}
51 \input {ot1cmtt.fd}

52 \input {ts1cmss.fd}
53 \input {ts1cmtt.fd}
54 \endgroup

```

Even though Unicode engines default to `lm` load `ts1cmr` as this may be used for fallback for TS1 encoding.

We now load it in all engines above, so the next lines are no longer necessary. We keep them here if we stop loading other `fd` files in Unicode engines.

```

55 %\ifx\Umathcode\@undefined\else
56 %\begingroup
57 %\nfss@catcodes
58 %\input {ts1cmr.fd}
59 %\endgroup
60 %\fi

```

Even with all the precautions it is still possible that NFSS will run into problems, for example, when a `.fd` file contains corrupted data. To guard against such cases NFSS has a very low-level fallback font that is installed with the following line.

```

61 \DeclareErrorFont{OT1}{cmr}{m}{n}{10}

```

This means, “if everything else fails use Computer Modern Roman normal shape at 10pt in the old text encoding”. You can change the font used but the encoding should be the same as the one specified with `\fontencoding` above.

## 5.2 Defaults

To allow the use of `\rmfamily`, `\sffamily`, etc. in documents even if non-standard families are used we provide nine macros which hold the name of the corresponding families, series, and so on. This makes it easy to use other font families (like Times Roman, etc.). One simply has to redefine these defaults.

All these hooks have to be defined in this file but you can change their meaning (except for `\encodingdefault`) without making documents non-portable.

```

\encodingdefault The following three definitions set up the meaning for \rmfamily, \sffamily, and
\rmdefault      \ttfamily.
\sfdefault
\ttdefault
62 \ifx\Umathcode\@undefined
63 \newcommand\encodingdefault{OT1}
64 \newcommand\rmdefault{cmr}
65 \newcommand\sfdefault{cmss}
66 \newcommand\ttdefault{cmtt}
67 \else
68 \newcommand\encodingdefault{TU}
69 \newcommand\rmdefault{lmr}
70 \fontfamily{\rmdefault}
71 \newcommand\sfdefault{lmss}
72 \newcommand\ttdefault{lmtt}
73 \fi
74 \</text>
75 \<latexrelease>\IncludeInRelease{2017/01/01}%
76 \<latexrelease>          {\encodingdefault}{TU encoding default}%

```

```

77 <latexrelease>\ifx\Umathcode\@undefined
78 <latexrelease>\renewcommand\encodingdefault{OT1}
79 <latexrelease>\fontencoding{\encodingdefault}
80 <latexrelease>\renewcommand\rmdefault{cmr}
81 <latexrelease>\fontfamily{\rmdefault}
82 <latexrelease>\renewcommand\sfddefault{cmss}
83 <latexrelease>\renewcommand\ttdefault{cmtt}
84 <latexrelease>\else
85 <latexrelease>\renewcommand\encodingdefault{TU}
86 <latexrelease>%done in everyjob\fontencoding{\encodingdefault}
87 <latexrelease>\renewcommand\rmdefault{lmr}
88 <latexrelease>\fontfamily{\rmdefault}
89 <latexrelease>\renewcommand\sfddefault{lmss}
90 <latexrelease>\renewcommand\ttdefault{lmtt}
91 <latexrelease>\fi
92 <latexrelease>\EndIncludeInRelease
93 <latexrelease>\IncludeInRelease{0000/00/00}%
94 <latexrelease>          {\encodingdefault}{TU encoding default}%
95 <latexrelease>\fontencoding{OT1}
96 <latexrelease>\renewcommand\encodingdefault{OT1}
97 <latexrelease>\fontencoding{\encodingdefault}
98 <latexrelease>\renewcommand\rmdefault{cmr}
99 <latexrelease>\fontfamily{\rmdefault}
100 <latexrelease>\renewcommand\sfddefault{cmss}
101 <latexrelease>\renewcommand\ttdefault{cmtt}
102 <latexrelease>\EndIncludeInRelease
103 <*text>

```

*(End of definition for \encodingdefault and others.)*

```

\bfdefault Series changing commands are influenced by the following hooks.
\mddefault
104 \newcommand\bfdefault{b} % overwritten below (for rollback)
105 \newcommand\mddefault{m} % overwritten below (for rollback)

```

*(End of definition for \bfdefault and \mddefault.)*

```

\itdefault Shape changing commands use the following hooks.
\sldefault
\scdefault
\updefault
106 \newcommand\itdefault{it}
107 \newcommand\sldefault{sl}
108 \newcommand\scdefault{sc}
109 \newcommand\updefault{up} % overwritten below (for rollback)

```

*(End of definition for \itdefault and others.)*

```

110 </text>
111 <*text | latexrelease>
112 <latexrelease>\IncludeInRelease{2020/02/02}%
113 <latexrelease>          {\updefault}{font defaults change}%
114 \renewcommand\updefault{up}

```

We append \@empty to the series value so that we can detect if it got changed via \def or \renewcommand later.

```

115 \renewcommand\bfdefault{b\@empty}
116 \renewcommand\mddefault{m\@empty}

```

```

117 \let\bfdefault@previous\bfdefault
118 \let\mddefault@previous\mddefault
119 </text | latexrelease>
120 <latexrelease>\EndIncludeInRelease
121 <latexrelease>\IncludeInRelease{0000/00/00}%
122 <latexrelease>                {\updefault}{font defaults change}%
123 <latexrelease>
124 <latexrelease>\renewcommand\updefault{n}
125 <latexrelease>\renewcommand\bfdefault{bx}
126 <latexrelease>
127 <latexrelease>\let\bfdefault@previous\undefined
128 <latexrelease>\let\mddefault@previous\undefined
129 <latexrelease>\EndIncludeInRelease
130 <*text>

```

`\familydefault` Finally we have the hooks that describe the behaviour of the `\normalfont` command.  
`\seriesdefault` To stay portable, the definition of `\encodingdefault` should *not* be changed and should  
`\shapedefault` match the setting above for `\fontencoding`. All other values can be set according to your taste.

```

131 \newcommand\familydefault{\rmdefault}
132 \newcommand\seriesdefault{\mddefault}

```

In previous releases `\shapedefault` pointed to `\updefault` which resolved to `n`, but these days that is no longer the case (and `up` is wrong when you want to do a reset. So we now use `n` explicitly.

```

133 \newcommand\shapedefault{n}

```

(End of definition for `\familydefault`, `\seriesdefault`, and `\shapedefault`.)

This finishes the low-level setup in `fonttext.ltx`.

```

134 </text>

```

## 6 The fontmath.ltx file

The identification is done earlier on with a `\ProvidesFile` declaration.

```

135 <*math>
136 \typeout{=== Don't modify this file, use a .cfg file instead ===^J}

```

### 6.1 The font encodings used

```

137 \DeclareFontEncoding{OML}{-}{-}
138 \DeclareFontEncoding{OMS}{-}{-}
139 \DeclareFontEncoding{OMX}{-}{-}

```

Finally a declaration for `U` encoding which serves for all fonts that do not fit standard encodings. For math this sets up `\noaccents@` providing for AMS- $\LaTeX$ . This macro is used therein to handle accented characters if they are not supported by the font. In other words, if fonts with `U` encoding are used in math, all accents (like from `\breve`) are obtained from some other font that has them.

```

140 \DeclareFontEncoding{U}{-}{\noaccents@}

```

The encodings for math are next:

```

141 \DeclareFontSubstitution{OML}{cmm}{m}{it}
142 \DeclareFontSubstitution{OMS}{cmsy}{m}{n}

```

```

143 \DeclareFontSubstitution{OMX}{cmex}{m}{n}
144 \DeclareFontSubstitution{U}{cmr}{m}{n}
145 \begingroup
146 \nfss@catcodes
147 \input {omlcmm.fd}
148 \input {omscmsy.fd}
149 \input {omxcmex.fd}
150 \input {ucmr.fd}
151 \endgroup

```

### 6.1.1 Symbolfont and Alphabet declarations

We now define the basic symbol fonts used by L<sup>A</sup>T<sub>E</sub>X. These four symbol fonts must be defined by this file.

It is possible to make the symbol fonts point to other external fonts without losing the ability to process documents written at other sites, as long as one defines the same symbol font names with the same encodings, e.g. `operators` with `OT1` etc. If other encodings are used documents become non-portable. Such a change should therefore be done in a package file.

```

152 \DeclareSymbolFont{operators} {OT1}{cmr} {m}{n}
153 \DeclareSymbolFont{letters} {OML}{cmm} {m}{it}
154 \DeclareSymbolFont{symbols} {OMS}{cmsy}{m}{n}
155 \DeclareSymbolFont{largesymbols}{OMX}{cmex}{m}{n}
156 \SetSymbolFont{operators}{bold}{OT1}{cmr} {bx}{n}
157 \SetSymbolFont{letters} {bold}{OML}{cmm} {b}{it}
158 \SetSymbolFont{symbols} {bold}{OMS}{cmsy}{b}{n}

```

Below are the seven math alphabets which are defined by NFSS. Again they must be defined by this file. However, as before you can change the fonts used without losing portability, but you should be careful when changing the encoding since that may make documents come out wrong.

```

159 \DeclareSymbolFontAlphabet{\mathrm} {operators}
160 \DeclareSymbolFontAlphabet{\mathnormal}{letters}
161 \DeclareSymbolFontAlphabet{\mathcal} {symbols}
162 \DeclareMathAlphabet {\mathbf} {OT1}{cmr}{bx}{n}
163 \DeclareMathAlphabet {\mathsf} {OT1}{cmss}{m}{n}
164 \DeclareMathAlphabet {\mathit} {OT1}{cmr}{m}{it}
165 \DeclareMathAlphabet {\mathtt} {OT1}{cmtt}{m}{n}

```

Given the currently available fonts we cannot bold-en `\mathbf` and `\mathtt` but in principle one could use ‘ultra bold’ or something. The alphabets defined via `\DeclareSymbolFontAlphabet` will change automatically in a new math version if the corresponding symbol font changes.

```

166 \SetMathAlphabet\mathsf{bold}{OT1}{cmss}{bx}{n}
167 \SetMathAlphabet\mathit{bold}{OT1}{cmr}{bx}{it}

```

## 6.2 Math font sizes

The declarations below declare the text, script and scriptscript size to be used for each text font size.

All occurrences of sizes longer than a single character are replaced with the macro name that holds them, saving a number of tokens (but losing a bit of speed, so this may not stay this way).

```

168 \DeclareMathSizes{5}{5}{5}{5}
169 \DeclareMathSizes{6}{6}{5}{5}
170 \DeclareMathSizes{7}{7}{5}{5}
171 \DeclareMathSizes{8}{8}{6}{5}
172 \DeclareMathSizes{9}{9}{6}{5}
173 \DeclareMathSizes{\@xpt}{\@xpt}{7}{5}
174 \DeclareMathSizes{\@xipt}{\@xipt}{8}{6}
175 \DeclareMathSizes{\@xipt}{\@xipt}{8}{6}
176 \DeclareMathSizes{\@xivpt}{\@xivpt}{\@xpt}{7}
177 \DeclareMathSizes{\@xvipt}{\@xvipt}{\@xipt}{\@xpt}
178 \DeclareMathSizes{\@xxpt}{\@xxpt}{\@xivpt}{\@xipt}
179 \DeclareMathSizes{\@xxvpt}{\@xxvpt}{\@xxpt}{\@xvipt}

```

### 6.3 The math symbol assignments

We start by setting up math codes for most of the characters typed in directly from the keyboard. Most of them are normally already setup up in the same way by `IniTeX`. However, we repeat them here to have a complete setup which can be exchanged with another if desired.

#### 6.3.1 The letters

```

180 \DeclareMathSymbol{a}{\mathalpha}{letters}{'a}
181 \DeclareMathSymbol{b}{\mathalpha}{letters}{'b}
182 \DeclareMathSymbol{c}{\mathalpha}{letters}{'c}
183 \DeclareMathSymbol{d}{\mathalpha}{letters}{'d}
184 \DeclareMathSymbol{e}{\mathalpha}{letters}{'e}
185 \DeclareMathSymbol{f}{\mathalpha}{letters}{'f}
186 \DeclareMathSymbol{g}{\mathalpha}{letters}{'g}
187 \DeclareMathSymbol{h}{\mathalpha}{letters}{'h}
188 \DeclareMathSymbol{i}{\mathalpha}{letters}{'i}
189 \DeclareMathSymbol{j}{\mathalpha}{letters}{'j}
190 \DeclareMathSymbol{k}{\mathalpha}{letters}{'k}
191 \DeclareMathSymbol{l}{\mathalpha}{letters}{'l}
192 \DeclareMathSymbol{m}{\mathalpha}{letters}{'m}
193 \DeclareMathSymbol{n}{\mathalpha}{letters}{'n}
194 \DeclareMathSymbol{o}{\mathalpha}{letters}{'o}
195 \DeclareMathSymbol{p}{\mathalpha}{letters}{'p}
196 \DeclareMathSymbol{q}{\mathalpha}{letters}{'q}
197 \DeclareMathSymbol{r}{\mathalpha}{letters}{'r}
198 \DeclareMathSymbol{s}{\mathalpha}{letters}{'s}
199 \DeclareMathSymbol{t}{\mathalpha}{letters}{'t}
200 \DeclareMathSymbol{u}{\mathalpha}{letters}{'u}
201 \DeclareMathSymbol{v}{\mathalpha}{letters}{'v}
202 \DeclareMathSymbol{w}{\mathalpha}{letters}{'w}
203 \DeclareMathSymbol{x}{\mathalpha}{letters}{'x}
204 \DeclareMathSymbol{y}{\mathalpha}{letters}{'y}
205 \DeclareMathSymbol{z}{\mathalpha}{letters}{'z}

206 \DeclareMathSymbol{A}{\mathalpha}{letters}{'A}
207 \DeclareMathSymbol{B}{\mathalpha}{letters}{'B}
208 \DeclareMathSymbol{C}{\mathalpha}{letters}{'C}
209 \DeclareMathSymbol{D}{\mathalpha}{letters}{'D}
210 \DeclareMathSymbol{E}{\mathalpha}{letters}{'E}

```

```

211 \DeclareMathSymbol{F}{\mathalpha}{letters}{'F}
212 \DeclareMathSymbol{G}{\mathalpha}{letters}{'G}
213 \DeclareMathSymbol{H}{\mathalpha}{letters}{'H}
214 \DeclareMathSymbol{I}{\mathalpha}{letters}{'I}
215 \DeclareMathSymbol{J}{\mathalpha}{letters}{'J}
216 \DeclareMathSymbol{K}{\mathalpha}{letters}{'K}
217 \DeclareMathSymbol{L}{\mathalpha}{letters}{'L}
218 \DeclareMathSymbol{M}{\mathalpha}{letters}{'M}
219 \DeclareMathSymbol{N}{\mathalpha}{letters}{'N}
220 \DeclareMathSymbol{O}{\mathalpha}{letters}{'O}
221 \DeclareMathSymbol{P}{\mathalpha}{letters}{'P}
222 \DeclareMathSymbol{Q}{\mathalpha}{letters}{'Q}
223 \DeclareMathSymbol{R}{\mathalpha}{letters}{'R}
224 \DeclareMathSymbol{S}{\mathalpha}{letters}{'S}
225 \DeclareMathSymbol{T}{\mathalpha}{letters}{'T}
226 \DeclareMathSymbol{U}{\mathalpha}{letters}{'U}
227 \DeclareMathSymbol{V}{\mathalpha}{letters}{'V}
228 \DeclareMathSymbol{W}{\mathalpha}{letters}{'W}
229 \DeclareMathSymbol{X}{\mathalpha}{letters}{'X}
230 \DeclareMathSymbol{Y}{\mathalpha}{letters}{'Y}
231 \DeclareMathSymbol{Z}{\mathalpha}{letters}{'Z}

```

### 6.3.2 The digits

```

232 \DeclareMathSymbol{0}{\mathalpha}{operators}{'0}
233 \DeclareMathSymbol{1}{\mathalpha}{operators}{'1}
234 \DeclareMathSymbol{2}{\mathalpha}{operators}{'2}
235 \DeclareMathSymbol{3}{\mathalpha}{operators}{'3}
236 \DeclareMathSymbol{4}{\mathalpha}{operators}{'4}
237 \DeclareMathSymbol{5}{\mathalpha}{operators}{'5}
238 \DeclareMathSymbol{6}{\mathalpha}{operators}{'6}
239 \DeclareMathSymbol{7}{\mathalpha}{operators}{'7}
240 \DeclareMathSymbol{8}{\mathalpha}{operators}{'8}
241 \DeclareMathSymbol{9}{\mathalpha}{operators}{'9}

```

### 6.3.3 Punctuation, brace, etc. keys

```

242 \DeclareMathSymbol{!}{\mathclose}{operators}{"21}
243 \DeclareMathSymbol{*}{\mathbin}{symbols}{"03} % \ast
244 \DeclareMathSymbol{+}{\mathbin}{operators}{"2B}
245 \DeclareMathSymbol{,}{\mathpunct}{letters}{"3B}
246 \DeclareMathSymbol{-}{\mathbin}{symbols}{"00}
247 \DeclareMathSymbol{.}{\mathord}{letters}{"3A}
248 \DeclareMathSymbol{:}{\mathrel}{operators}{"3A}
249 \DeclareMathSymbol{;}{\mathpunct}{operators}{"3B}
250 \DeclareMathSymbol{=}{\mathrel}{operators}{"3D}
251 \DeclareMathSymbol{?}{\mathclose}{operators}{"3F}

```

The following symbols are defined as delimiters below which automatically defines them as math symbols.

```

252 %\DeclareMathSymbol{({\mathopen}{operators}{"28}
253 %\DeclareMathSymbol{)}{\mathclose}{operators}{"29}
254 %\DeclareMathSymbol{/}{\mathord}{letters}{"3D}
255 %\DeclareMathSymbol{[}{\mathopen}{operators}{"5B}
256 %\DeclareMathSymbol{]}{\mathclose}{operators}{"5D}
257 %\DeclareMathSymbol{|}{\mathord}{symbols}{"6A}

```

```

258 %\DeclareMathSymbol{<}{\mathrel}{letters}{"3C}
259 %\DeclareMathSymbol{>}{\mathrel}{letters}{"3E}

```

Should all of the following being activated by default? Probably not.

```

260 %\DeclareMathSymbol{\{}{\mathopen}{symbols}{"66}
261 %\DeclareMathSymbol{\}}{\mathclose}{symbols}{"67}
262 %\DeclareMathSymbol{\}\}{\mathord}{symbols}{"6E} % \backslash
263 \mathcode'\ =8000 % \space
264 \mathcode'\ ' =8000 % ^\prime
265 \mathcode'\_ =8000 % \_

```

### 6.3.4 Delimitercodes for characters

[to be completed]

Finally,  $\text{\texttt{Init\TeX}}$  sets all  $\text{\texttt{\delcode}}$  values to -1, except  $\text{\texttt{\delcode' =0}}$

```

266 \DeclareMathDelimiter{()}{\mathopen}{operators}{"28}{largesymbols}{"00}
267 \DeclareMathDelimiter{)}{\mathclose}{operators}{"29}{largesymbols}{"01}
268 \DeclareMathDelimiter{[]}{\mathopen}{operators}{"5B}{largesymbols}{"02}
269 \DeclareMathDelimiter{[]}{\mathclose}{operators}{"5D}{largesymbols}{"03}

```

The next two are considered to be relations when not used in the context of a delimiter! And worse, they do even represent different glyphs when being used as delimiter and not as delimiter. This is a user level syntax inherited from plain  $\text{\texttt{T\TeX}}$ . Therefore we explicitly redefine the math symbol definitions for these symbols afterwards.

```

270 \DeclareMathDelimiter{<}{\mathopen}{symbols}{"68}{largesymbols}{"0A}
271 \DeclareMathDelimiter{>}{\mathclose}{symbols}{"69}{largesymbols}{"0B}
272 \DeclareMathSymbol{<}{\mathrel}{letters}{"3C}
273 \DeclareMathSymbol{>}{\mathrel}{letters}{"3E}

```

And here is another case where the non-delimiter version produces a glyph different from the delimiter version.

```

274 \DeclareMathDelimiter{/}{\mathord}{operators}{"2F}{largesymbols}{"0E}
275 \DeclareMathSymbol{/}{\mathord}{letters}{"3D}

276 \DeclareMathDelimiter{|}{\mathord}{symbols}{"6A}{largesymbols}{"0C}
277 \expandafter\DeclareMathDelimiter\@backslashchar
278 \mathord}{symbols}{"6E}{largesymbols}{"0F}

```

N.B. { and } should NOT get delcodes; otherwise parameter grouping fails!

## 6.4 Symbols accessed via control sequences

### 6.4.1 Greek letters

```

279 \DeclareMathSymbol{\alpha}{\mathord}{letters}{"0B}
280 \DeclareMathSymbol{\beta}{\mathord}{letters}{"0C}
281 \DeclareMathSymbol{\gamma}{\mathord}{letters}{"0D}
282 \DeclareMathSymbol{\delta}{\mathord}{letters}{"0E}
283 \DeclareMathSymbol{\epsilon}{\mathord}{letters}{"0F}
284 \DeclareMathSymbol{\zeta}{\mathord}{letters}{"10}
285 \DeclareMathSymbol{\eta}{\mathord}{letters}{"11}
286 \DeclareMathSymbol{\theta}{\mathord}{letters}{"12}
287 \DeclareMathSymbol{\iota}{\mathord}{letters}{"13}
288 \DeclareMathSymbol{\kappa}{\mathord}{letters}{"14}
289 \DeclareMathSymbol{\lambda}{\mathord}{letters}{"15}
290 \DeclareMathSymbol{\mu}{\mathord}{letters}{"16}
291 \DeclareMathSymbol{\nu}{\mathord}{letters}{"17}

```

```

292 \DeclareMathSymbol{\xi}{\mathord}{letters}{18}
293 \DeclareMathSymbol{\pi}{\mathord}{letters}{19}
294 \DeclareMathSymbol{\rho}{\mathord}{letters}{1A}
295 \DeclareMathSymbol{\sigma}{\mathord}{letters}{1B}
296 \DeclareMathSymbol{\tau}{\mathord}{letters}{1C}
297 \DeclareMathSymbol{\upsilon}{\mathord}{letters}{1D}
298 \DeclareMathSymbol{\phi}{\mathord}{letters}{1E}
299 \DeclareMathSymbol{\chi}{\mathord}{letters}{1F}
300 \DeclareMathSymbol{\psi}{\mathord}{letters}{20}
301 \DeclareMathSymbol{\omega}{\mathord}{letters}{21}
302 \DeclareMathSymbol{\varepsilon}{\mathord}{letters}{22}
303 \DeclareMathSymbol{\vartheta}{\mathord}{letters}{23}
304 \DeclareMathSymbol{\varpi}{\mathord}{letters}{24}
305 \DeclareMathSymbol{\varrho}{\mathord}{letters}{25}
306 \DeclareMathSymbol{\varsigma}{\mathord}{letters}{26}
307 \DeclareMathSymbol{\varphi}{\mathord}{letters}{27}
308 \DeclareMathSymbol{\Gamma}{\mathalpha}{operators}{00}
309 \DeclareMathSymbol{\Delta}{\mathalpha}{operators}{01}
310 \DeclareMathSymbol{\Theta}{\mathalpha}{operators}{02}
311 \DeclareMathSymbol{\Lambda}{\mathalpha}{operators}{03}
312 \DeclareMathSymbol{\Xi}{\mathalpha}{operators}{04}
313 \DeclareMathSymbol{\Pi}{\mathalpha}{operators}{05}
314 \DeclareMathSymbol{\Sigma}{\mathalpha}{operators}{06}
315 \DeclareMathSymbol{\Upsilon}{\mathalpha}{operators}{07}
316 \DeclareMathSymbol{\Phi}{\mathalpha}{operators}{08}
317 \DeclareMathSymbol{\Psi}{\mathalpha}{operators}{09}
318 \DeclareMathSymbol{\Omega}{\mathalpha}{operators}{0A}

```

#### 6.4.2 Ordinary symbols

```

319 \DeclareMathSymbol{\aleph}{\mathord}{symbols}{40}
320 \DeclareMathSymbol{\imath}{\mathord}{letters}{7B}
321 \DeclareMathSymbol{\jmath}{\mathord}{letters}{7C}
322 \DeclareMathSymbol{\ell}{\mathord}{letters}{60}
323 \DeclareMathSymbol{\wp}{\mathord}{letters}{7D}
324 \DeclareMathSymbol{\Re}{\mathord}{symbols}{3C}
325 \DeclareMathSymbol{\Im}{\mathord}{symbols}{3D}
326 \DeclareMathSymbol{\partial}{\mathord}{letters}{40}
327 \DeclareMathSymbol{\infty}{\mathord}{symbols}{31}
328 \DeclareMathSymbol{\prime}{\mathord}{symbols}{30}
329 \DeclareMathSymbol{\emptyset}{\mathord}{symbols}{3B}
330 \DeclareMathSymbol{\nabla}{\mathord}{symbols}{72}
331 \DeclareMathSymbol{\top}{\mathord}{symbols}{3E}
332 \DeclareMathSymbol{\bot}{\mathord}{symbols}{3F}
333 \DeclareMathSymbol{\triangle}{\mathord}{symbols}{34}
334 \DeclareMathSymbol{\forall}{\mathord}{symbols}{38}
335 \DeclareMathSymbol{\exists}{\mathord}{symbols}{39}
336 \DeclareMathSymbol{\neg}{\mathord}{symbols}{3A}

```

Alias:

```

337 % \let\not=\neg
338 \DeclareMathSymbol{\not}{\mathord}{symbols}{3A}
339 \DeclareMathSymbol{\flat}{\mathord}{letters}{5B}
340 \DeclareMathSymbol{\natural}{\mathord}{letters}{5C}
341 \DeclareMathSymbol{\sharp}{\mathord}{letters}{5D}

```

```

342 \DeclareMathSymbol{\clubsuit}{\mathord}{symbols}{"7C}
343 \DeclareMathSymbol{\diamondsuit}{\mathord}{symbols}{"7D}
344 \DeclareMathSymbol{\heartsuit}{\mathord}{symbols}{"7E}
345 \DeclareMathSymbol{\spadesuit}{\mathord}{symbols}{"7F}

346 \DeclareRobustCommand\hbar{{\mathchar'26\mkern-9mu}}
347 \DeclareRobustCommand\surd{{\mathchar"1270}}
348 \DeclareRobustCommand\angle{{\vbox{\ialign{$\m@th\scriptstyle##$\crrc
349     \not\mathrel{\mkern14mu}\crrc
350     \noalign{\nointerlineskip}
351     \mkern2.5mu\leaders\hrule \@height.34pt\hfill\mkern2.5mu\crrc}}}}

```

### 6.4.3 Large Operators

```

352 \DeclareMathSymbol{\coprod}{\mathop}{largesymbols}{"60}
353 \DeclareMathSymbol{\bigvee}{\mathop}{largesymbols}{"57}
354 \DeclareMathSymbol{\bigwedge}{\mathop}{largesymbols}{"56}
355 \DeclareMathSymbol{\biguplus}{\mathop}{largesymbols}{"55}
356 \DeclareMathSymbol{\bigcap}{\mathop}{largesymbols}{"54}
357 \DeclareMathSymbol{\bigcup}{\mathop}{largesymbols}{"53}
358 \DeclareMathSymbol{\intop}{\mathop}{largesymbols}{"52}
359 \DeclareRobustCommand\int{\intop\nolimits}
360 \DeclareMathSymbol{\prod}{\mathop}{largesymbols}{"51}
361 \DeclareMathSymbol{\sum}{\mathop}{largesymbols}{"50}
362 \DeclareMathSymbol{\bigotimes}{\mathop}{largesymbols}{"4E}
363 \DeclareMathSymbol{\bigoplus}{\mathop}{largesymbols}{"4C}
364 \DeclareMathSymbol{\bigodot}{\mathop}{largesymbols}{"4A}
365 \DeclareMathSymbol{\ointop}{\mathop}{largesymbols}{"48}
366 \DeclareRobustCommand\oint{\ointop\nolimits}
367 \DeclareMathSymbol{\bigsqcup}{\mathop}{largesymbols}{"46}
368 \DeclareMathSymbol{\smallint}{\mathop}{symbols}{"73}

```

### 6.4.4 Binary symbols

```

369 \DeclareMathSymbol{\triangleleft}{\mathbin}{letters}{"2F}
370 \DeclareMathSymbol{\triangleright}{\mathbin}{letters}{"2E}
371 \DeclareMathSymbol{\bigtriangleup}{\mathbin}{symbols}{"34}
372 \DeclareMathSymbol{\bigtriangledown}{\mathbin}{symbols}{"35}

```

Alias:

```

373 % \let \varbigtriangledown \bigtriangledown
374 % \let \varbigtriangleup \bigtriangleup
375 \DeclareMathSymbol{\varbigtriangleup}{\mathbin}{symbols}{"34}
376 \DeclareMathSymbol{\varbigtriangledown}{\mathbin}{symbols}{"35}

```

These last two synonyms are needed because the `stmaryrd` package redefines them as Operators.

```

377 \DeclareMathSymbol{\wedge}{\mathbin}{symbols}{"5E}
378 \DeclareMathSymbol{\vee}{\mathbin}{symbols}{"5F}

```

Alias:

```

379 % \let \land=\wedge
380 % \let \lor=\vee
381 \DeclareMathSymbol{\land}{\mathbin}{symbols}{"5E}
382 \DeclareMathSymbol{\lor}{\mathbin}{symbols}{"5F}
383 \DeclareMathSymbol{\cap}{\mathbin}{symbols}{"5C}
384 \DeclareMathSymbol{\cup}{\mathbin}{symbols}{"5B}
385 \DeclareMathSymbol{\ddagger}{\mathbin}{symbols}{"7A}

```

```

386 \DeclareMathSymbol{\dagger}{\mathbin}{symbols}{"79}
387 \DeclareMathSymbol{\sqcap}{\mathbin}{symbols}{"75}
388 \DeclareMathSymbol{\sqcup}{\mathbin}{symbols}{"74}
389 \DeclareMathSymbol{\uplus}{\mathbin}{symbols}{"5D}
390 \DeclareMathSymbol{\amalg}{\mathbin}{symbols}{"71}
391 \DeclareMathSymbol{\diamond}{\mathbin}{symbols}{"05}
392 \DeclareMathSymbol{\bullet}{\mathbin}{symbols}{"0F}
393 \DeclareMathSymbol{\wr}{\mathbin}{symbols}{"6F}
394 \DeclareMathSymbol{\div}{\mathbin}{symbols}{"04}
395 \DeclareMathSymbol{\odot}{\mathbin}{symbols}{"0C}
396 \DeclareMathSymbol{\oslash}{\mathbin}{symbols}{"0B}
397 \DeclareMathSymbol{\otimes}{\mathbin}{symbols}{"0A}
398 \DeclareMathSymbol{\ominus}{\mathbin}{symbols}{"09}
399 \DeclareMathSymbol{\oplus}{\mathbin}{symbols}{"08}
400 \DeclareMathSymbol{\mp}{\mathbin}{symbols}{"07}
401 \DeclareMathSymbol{\pm}{\mathbin}{symbols}{"06}
402 \DeclareMathSymbol{\circ}{\mathbin}{symbols}{"0E}
403 \DeclareMathSymbol{\bigcirc}{\mathbin}{symbols}{"0D}
404 \DeclareMathSymbol{\setminus}{\mathbin}{symbols}{"6E}
405 \DeclareMathSymbol{\cdot}{\mathbin}{symbols}{"01}
406 \DeclareMathSymbol{\ast}{\mathbin}{symbols}{"03}
407 \DeclareMathSymbol{\times}{\mathbin}{symbols}{"02}
408 \DeclareMathSymbol{\star}{\mathbin}{letters}{"3F}

```

#### 6.4.5 Relations

```

409 \DeclareMathSymbol{\propto}{\mathrel}{symbols}{"2F}
410 \DeclareMathSymbol{\sqsubseteq}{\mathrel}{symbols}{"76}
411 \DeclareMathSymbol{\sqsupseteq}{\mathrel}{symbols}{"77}
412 \DeclareMathSymbol{\parallel}{\mathrel}{symbols}{"6B}
413 \DeclareMathSymbol{\mid}{\mathrel}{symbols}{"6A}
414 \DeclareMathSymbol{\dashv}{\mathrel}{symbols}{"61}
415 \DeclareMathSymbol{\vdash}{\mathrel}{symbols}{"60}
416 \DeclareMathSymbol{\nearrow}{\mathrel}{symbols}{"25}
417 \DeclareMathSymbol{\searrow}{\mathrel}{symbols}{"26}
418 \DeclareMathSymbol{\nwarrow}{\mathrel}{symbols}{"2D}
419 \DeclareMathSymbol{\swarrow}{\mathrel}{symbols}{"2E}
420 \DeclareMathSymbol{\Leftrightarrow}{\mathrel}{symbols}{"2C}
421 \DeclareMathSymbol{\Leftrightarrow}{\mathrel}{symbols}{"28}
422 \DeclareMathSymbol{\Rightarrow}{\mathrel}{symbols}{"29}
423 \DeclareRobustCommand\neq{\not=}

```

As `\neq` is robust we should not use `\let` to define `\ne` as then it would change if `\neq` changes.

```

424 \DeclareRobustCommand\ne{\not=}

```

It would ok to use `\let` for those declared by `\DeclareMathSymbol` but for a cleaner interface we avoid it always (just in case the internals change).

```

425 \DeclareMathSymbol{\leq}{\mathrel}{symbols}{"14}
426 \DeclareMathSymbol{\geq}{\mathrel}{symbols}{"15}

```

Alias:

```

427 % \let\le=\leq
428 % \let\ge=\geq
429 \DeclareMathSymbol{\le}{\mathrel}{symbols}{"14}
430 \DeclareMathSymbol{\ge}{\mathrel}{symbols}{"15}

```

```

431 \DeclareMathSymbol{\succ}{\mathrel}{symbols}{"1F}
432 \DeclareMathSymbol{\prec}{\mathrel}{symbols}{"1E}
433 \DeclareMathSymbol{\approx}{\mathrel}{symbols}{"19}
434 \DeclareMathSymbol{\succeq}{\mathrel}{symbols}{"17}
435 \DeclareMathSymbol{\preceq}{\mathrel}{symbols}{"16}
436 \DeclareMathSymbol{\supset}{\mathrel}{symbols}{"1B}
437 \DeclareMathSymbol{\subset}{\mathrel}{symbols}{"1A}
438 \DeclareMathSymbol{\supseteq}{\mathrel}{symbols}{"13}
439 \DeclareMathSymbol{\subseteq}{\mathrel}{symbols}{"12}
440 \DeclareMathSymbol{\in}{\mathrel}{symbols}{"32}
441 \DeclareMathSymbol{\ni}{\mathrel}{symbols}{"33}

```

Alias:

```

442 % \let\owns=\ni
443 \DeclareMathSymbol{\owns}{\mathrel}{symbols}{"33}
444 \DeclareMathSymbol{\gg}{\mathrel}{symbols}{"1D}
445 \DeclareMathSymbol{\ll}{\mathrel}{symbols}{"1C}
446 \DeclareMathSymbol{\not}{\mathrel}{symbols}{"36}
447 \DeclareMathSymbol{\leftrightharpoonup}{\mathrel}{symbols}{"24}
448 \DeclareMathSymbol{\leftarrow}{\mathrel}{symbols}{"20}
449 \DeclareMathSymbol{\rightarrow}{\mathrel}{symbols}{"21}

```

Alias:

```

450 % \let\gets=\leftarrow
451 % \let\to=\rightarrow
452 \DeclareMathSymbol{\gets}{\mathrel}{symbols}{"20}
453 \DeclareMathSymbol{\to}{\mathrel}{symbols}{"21}
454 \DeclareMathSymbol{\mapstochar}{\mathrel}{symbols}{"37}
455 \DeclareRobustCommand\mapsto{\mapstochar\rightarrow}
456 \DeclareMathSymbol{\sim}{\mathrel}{symbols}{"18}
457 \DeclareMathSymbol{\simeq}{\mathrel}{symbols}{"27}
458 \DeclareMathSymbol{\perp}{\mathrel}{symbols}{"3F}
459 \DeclareMathSymbol{\equiv}{\mathrel}{symbols}{"11}
460 \DeclareMathSymbol{\asymp}{\mathrel}{symbols}{"10}
461 \DeclareMathSymbol{\smile}{\mathrel}{letters}{"5E}
462 \DeclareMathSymbol{\frown}{\mathrel}{letters}{"5F}
463 \DeclareMathSymbol{\leftharpoonup}{\mathrel}{letters}{"28}
464 \DeclareMathSymbol{\leftharpoondown}{\mathrel}{letters}{"29}
465 \DeclareMathSymbol{\rightharpoonup}{\mathrel}{letters}{"2A}
466 \DeclareMathSymbol{\rightharpoondown}{\mathrel}{letters}{"2B}

```

Here cometh much profligate robustification of math constructs. Warning: some of these commands may become non-robust if an AMS package is loaded.

Further potential problems: some math font packages may make unfortunate assumptions about some of these definitions that are not true of the robust versions we need.

```

467 \DeclareRobustCommand
468 \cong{\mathrel{\mathpalette\@vereq\sim}} % congruence sign
469 \def\@vereq#1#2{\lower.5p@\vbox{\lineskiplimit\maxdimen\lineskip-.5p@
470 \ialign{${\m@th#1\hfil##\hfil$\crrc#2\crrc=\crrc$}}{}}
471 \DeclareRobustCommand
472 \notin{\mathrel{\m@th\mathpalette\c@ncel\in}}
473 \def\c@ncel#1#2{\m@th\oalign{${\hfil#1\mkern1mu\hfil$\crrc$#1#2$}}
474 \DeclareRobustCommand
475 \rightleftharpoons{\mathrel{\mathpalette\rlh@{}}}

```

```

476 \def\rhlh@#1{\vcenter{\m@th\hbox{\ooalign{\raise2pt
477 \hbox{$#1\rightarrow$}\cr
478 \hbox{$#1\leftarrow$}\cr}}}
479 \DeclareRobustCommand
480 \doteq{\buildrel\textstyle.\over=}

```

#### 6.4.6 Arrows

```

481 \DeclareRobustCommand
482 \joinrel{\mathrel{\mkern-3mu}}
483 \DeclareRobustCommand
484 \relbar{\mathrel{\smash-}} % \smash, because -
485 % has the same height as +

```

In contrast to `plain.tex` `\Relbar` got braces around the equal sign to guard against it being “math active” expanding to `\futurelet...`. This might be the case when packages are implementing shorthands for math, e.g. `=>` meaning `\Rightarrow` etc. It would actually be better not to use `=` in such definitions but instead define something like `\mathequalsign` and use this. However we can’t do this now as it would break other math layouts where characters are in different places (since those wouldn’t know about the need for a new command name).

```

486 \DeclareRobustCommand
487 \Relbar{\mathrel{=}}
488 \DeclareMathSymbol{\lhook}{\mathrel}{letters}{"2C}
489 \DeclareRobustCommand\hookrightarrow{\lhook\joinrel\rightarrow}
490 \DeclareMathSymbol{\rhook}{\mathrel}{letters}{"2D}
491 \DeclareRobustCommand\hookleftarrow{\leftarrow\joinrel\rhook}
492 \DeclareRobustCommand
493 \bowtie{\mathrel{\triangleright}\joinrel\mathrel{\triangleleft}}
494 \DeclareRobustCommand
495 \models{\mathrel{||}\joinrel\Relbar}
496 \DeclareRobustCommand
497 \Longrightarrow{\Relbar\joinrel\rightarrow}

```

LaTeX Change: `\longrightarrow` and `\longleftarrow` redefined to make them robust.

```

498 \DeclareRobustCommand\longrightarrow
499 {\relbar\joinrel\rightarrow}
500 \DeclareRobustCommand\longleftarrow
501 {\leftarrow\joinrel\relbar}
502 \DeclareRobustCommand
503 \Longleftarrow{\Leftarrow\joinrel\Relbar}
504 \DeclareRobustCommand
505 \longmapsto{\mapstochar\longrightarrow}
506 \DeclareRobustCommand
507 \longlefttrightarrow{\leftarrow\joinrel\rightarrow}
508 \DeclareRobustCommand
509 \Longlefttrightarrow{\Leftarrow\joinrel\rightarrow}
510 \DeclareRobustCommand
511 \iff{\;\Longlefttrightarrow\;}

```

#### 6.4.7 Punctuation symbols

```

512 \DeclareMathSymbol{\ldotp}{\mathpunct}{letters}{"3A}
513 \DeclareMathSymbol{\cdotp}{\mathpunct}{symbols}{"01}
514 \DeclareMathSymbol{\colon}{\mathpunct}{operators}{"3A}

```

This is commented out, since `\ldots` is now defined in `ltoutenc.dtx`.

```

515 %\def\@ldots{\mathinner{\ldotp\ldotp\ldotp}}
516 %\DeclareRobustCommand\ldots
517 %      {\relax\ifmmode\@ldots\else\mbox{$\m@th\@ldots$,}\fi}
518 \DeclareRobustCommand
519   \cdots{\mathinner{\cdotp\cdotp\cdotp}}
520 \DeclareRobustCommand
521   \vdots{\vbox{\baselineskip4\p@ \lineskiplimit\z@
522     \kern6\p@\hbox{.}\hbox{.}\hbox{.}}}
523 \DeclareRobustCommand
524   \ddots{\mathinner{\mkern1mu\raise7\p@
525     \vbox{\kern7\p@\hbox{.}}\mkern2mu
526     \raise4\p@\hbox{.}\mkern2mu\raise\p@\hbox{.}\mkern1mu}}

```

#### 6.4.8 Math accents

```

527 \DeclareMathAccent{\acute}{\mathalpha}{operators}{13}
528 \DeclareMathAccent{\grave}{\mathalpha}{operators}{12}
529 \DeclareMathAccent{\ddot}{\mathalpha}{operators}{7F}
530 \DeclareMathAccent{\tilde}{\mathalpha}{operators}{7E}
531 \DeclareMathAccent{\bar}{\mathalpha}{operators}{16}
532 \DeclareMathAccent{\breve}{\mathalpha}{operators}{15}
533 \DeclareMathAccent{\check}{\mathalpha}{operators}{14}
534 \DeclareMathAccent{\hat}{\mathalpha}{operators}{5E}
535 \DeclareMathAccent{\vec}{\mathord}{letters}{7E}
536 \DeclareMathAccent{\dot}{\mathalpha}{operators}{5F}
537 \DeclareMathAccent{\widetilde}{\mathord}{largesymbols}{65}
538 \DeclareMathAccent{\widehat}{\mathord}{largesymbols}{62}

```

For some reason plain  $\TeX$  never bothered to provide a ring accent in math (although it is available in the fonts), but since we got a request for it here we go:

```

539 \DeclareMathAccent{\mathring}{\mathalpha}{operators}{17}

```

#### 6.4.9 Radicals

```

540 \DeclareMathRadical{\sqrtsign}{symbols}{70}{largesymbols}{70}

```

#### 6.4.10 Over and under something, etc

```

541 \DeclareRobustCommand\overrightarrow[1]{\vbox{\m@th\ialign{##\crrc
542   \rightarrowfill\crrc\noalign{\kern-\p@\nointerlineskip}
543   $\hfil\displaystyle{#1}\hfil$\crrc}}}
544 \DeclareRobustCommand\overleftarrow[1]{\vbox{\m@th\ialign{##\crrc
545   \leftarrowfill\crrc\noalign{\kern-\p@\nointerlineskip}%
546   $\hfil\displaystyle{#1}\hfil$\crrc}}}
547 \DeclareRobustCommand\overbrace[1]
548   {\mathop{\vbox{\m@th\ialign{##\crrc\noalign{\kern3\p@}%
549     \downbracefill\crrc\noalign{\kern3\p@\nointerlineskip}%
550     $\hfil\displaystyle{#1}\hfil$\crrc}}}\limits}
551 \DeclareRobustCommand\underbrace[1]{\mathop{\vtop{\m@th\ialign{##\crrc
552   $\hfil\displaystyle{#1}\hfil$\crrc
553   \noalign{\kern3\p@\nointerlineskip}%
554   \upbracefill\crrc\noalign{\kern3\p@}}}\limits}

```

(quite a waste of tokens, IMHO — Frank)

```

555 \DeclareRobustCommand\skew[3]
556   {\{\muskip\z@#1mu\divide\muskip\z@ \tw@ \mkern\muskip\z@
557   #2{\mkern-\muskip\z@#3}\mkern\muskip\z@}\mkern-\muskip\z@}\}

```

```

558 \DeclareRobustCommand\rightarrowfill{$\m@th\smash-\mkern-7mu%
559 \cleaders\hbox{$\mkern-2mu\smash-\mkern-2mu$}\hfill
560 \mkern-7mu\mathord\rightarrow$}
561 \DeclareRobustCommand\leftarrowfill{$\m@th\mathord\leftarrow\mkern-7mu%
562 \cleaders\hbox{$\mkern-2mu\smash-\mkern-2mu$}\hfill
563 \mkern-7mu\smash-$}
564 \DeclareMathSymbol{\braceld}{\mathord}{largesymbols}{7A}
565 \DeclareMathSymbol{\bracerd}{\mathord}{largesymbols}{7B}
566 \DeclareMathSymbol{\bracelu}{\mathord}{largesymbols}{7C}
567 \DeclareMathSymbol{\braceru}{\mathord}{largesymbols}{7D}
568 \DeclareRobustCommand\downbracefill{$\m@th\setbox\z@\hbox{$\braceld$}%
569 \braceld\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\braceru
570 \bracelu\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\bracerd$}
571 \DeclareRobustCommand\upbracefill{$\m@th\setbox\z@\hbox{$\bracerd$}%
572 \bracelu\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\bracerd
573 \braceld\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\braceru$}

```

#### 6.4.11 Delimiters

```

574 \DeclareMathDelimiter{\lmoustache} % top from (, bottom from )
575 {\mathopen}{largesymbols}{7A}{largesymbols}{40}
576 \DeclareMathDelimiter{\rmoustache} % top from ), bottom from (
577 {\mathclose}{largesymbols}{7B}{largesymbols}{41}
578 \DeclareMathDelimiter{\arrowvert} % arrow without arrowheads
579 {\mathord}{symbols}{6A}{largesymbols}{3C}
580 \DeclareMathDelimiter{\Arrowvert} % double arrow without arrowheads
581 {\mathord}{symbols}{6B}{largesymbols}{3D}
582 \DeclareMathDelimiter{\Vert}
583 {\mathord}{symbols}{6B}{largesymbols}{0D}

```

`\DeclareMathDelimiter` produces a command that is robust (with an internal macro containing the payload) so we should not use `\let` for making an alias

```

584 %\let\l=\Vert
585 \DeclareMathDelimiter{\l}
586 {\mathord}{symbols}{6B}{largesymbols}{0D}
587 \DeclareMathDelimiter{\v}
588 {\mathord}{symbols}{6A}{largesymbols}{0C}
589 \DeclareMathDelimiter{\uparrow}
590 {\mathrel}{symbols}{22}{largesymbols}{78}
591 \DeclareMathDelimiter{\downarrow}
592 {\mathrel}{symbols}{23}{largesymbols}{79}
593 \DeclareMathDelimiter{\updownarrow}
594 {\mathrel}{symbols}{6C}{largesymbols}{3F}
595 \DeclareMathDelimiter{\Uparrow}
596 {\mathrel}{symbols}{2A}{largesymbols}{7E}
597 \DeclareMathDelimiter{\Downarrow}
598 {\mathrel}{symbols}{2B}{largesymbols}{7F}
599 \DeclareMathDelimiter{\Updownarrow}
600 {\mathrel}{symbols}{6D}{largesymbols}{77}
601 \DeclareMathDelimiter{\backslash} % for double coset G\backslash H
602 {\mathord}{symbols}{6E}{largesymbols}{0F}
603 \DeclareMathDelimiter{\rangle}
604 {\mathclose}{symbols}{69}{largesymbols}{0B}
605 \DeclareMathDelimiter{\langle}
606 {\mathopen}{symbols}{68}{largesymbols}{0A}

```

```

607 \DeclareMathDelimiter{\rbrace
608     {\mathclose}{symbols}{"67}{largesymbols}{"09}
609 \DeclareMathDelimiter{\lbrace
610     {\mathopen}{symbols}{"66}{largesymbols}{"08}
611 \DeclareMathDelimiter{\rceil}
612     {\mathclose}{symbols}{"65}{largesymbols}{"07}
613 \DeclareMathDelimiter{\lceil}
614     {\mathopen}{symbols}{"64}{largesymbols}{"06}
615 \DeclareMathDelimiter{\rfloor}
616     {\mathclose}{symbols}{"63}{largesymbols}{"05}
617 \DeclareMathDelimiter{\lfloor}
618     {\mathopen}{symbols}{"62}{largesymbols}{"04}

```

`\lgroup` There are three plain  $\TeX$  delimiters which are not fully supported by NFSS, since they partly point into a bold `cmr` font. Allocating a full symbol font, just to have three delimiters seems a bit too much given the limited space available. For this reason only the extensible sizes are supported. If this is not desired one can use, without losing portability, define `\mathbf` and `\mathtt` as font symbol alphabet (setting up `cmr/bx/n` and `cmtt/m/n` as symbol fonts first) and modify the delimiter declarations to point with their small variant to those symbol fonts. (This is done in `oldlfont.dtx` so look there for examples.)

```

619 \DeclareMathDelimiter{\lgroup} % extensible ( with sharper tips
620     {\mathopen}{largesymbols}{"3A}{largesymbols}{"3A}
621 \DeclareMathDelimiter{\rgroup} % extensible ) with sharper tips
622     {\mathclose}{largesymbols}{"3B}{largesymbols}{"3B}
623 \DeclareMathDelimiter{\bracevert} % the vertical bar that extends braces
624     {\mathord}{largesymbols}{"3E}{largesymbols}{"3E}

```

*(End of definition for `\lgroup`, `\rgroup`, and `\bracevert`.)*

## 6.5 Math versions of text commands

The `\mathunderscore` here is really a text definition, so it has been put back into `loutenc.dtx` (by Chris, 30/04/97) and should be removed from here.

These symbols are the math versions of text commands such as `\P`, `\$`, etc.

```

\mathparagraph These math symbols are not in plain  $\TeX$ .
\mathsection    625 \DeclareMathSymbol{\mathparagraph}{\mathord}{symbols}{"7B}
\mathdollar     626 \DeclareMathSymbol{\mathsection}{\mathord}{symbols}{"78}
\mathsterling   627 \DeclareMathSymbol{\mathdollar}{\mathord}{operators}{"24}
\mathunderscore 628 \DeclareRobustCommand\mathsterling{\mathit{\mathchar"7024}}
                629 \DeclareRobustCommand\mathunderscore{\kern.06em\vbox{\hrule\@width.3em}}

```

*(End of definition for `\mathparagraph` and others.)*

`\mathellipsis` This is plain  $\TeX$ 's `\ldots`.

```

630 \DeclareRobustCommand\mathellipsis{\mathinner{\ldotp\ldotp\ldotp}}%

```

*(End of definition for `\mathellipsis`.)*

## 6.6 Other special functions and parameters

### 6.6.1 Biggggg

```
631 </math>
632 <*math | latexrelease>
633 <latexrelease>\IncludeInRelease{2018/12/01}%
634 <latexrelease>          {\Big}{Start LR-mode}%
635 \DeclareRobustCommand\big[1]{\leavevmode@ifvmode
636   {\hbox{$\left#1\ vbox to8.5\p@{} \right.\n@space$}}}
637 \DeclareRobustCommand\Big[1]{\leavevmode@ifvmode
638   {\hbox{$\left#1\ vbox to11.5\p@{} \right.\n@space$}}}
639 \DeclareRobustCommand\bigg[1]{\leavevmode@ifvmode
640   {\hbox{$\left#1\ vbox to14.5\p@{} \right.\n@space$}}}
641 \DeclareRobustCommand\Bigg[1]{\leavevmode@ifvmode
642   {\hbox{$\left#1\ vbox to17.5\p@{} \right.\n@space$}}}
643 </math | latexrelease>
644 <latexrelease>\EndIncludeInRelease
645 <latexrelease>\IncludeInRelease{0000/00/00}%
646 <latexrelease>          {\Big}{Start LR-mode}%
647 <latexrelease>\def\big#1{{\hbox{$\left#1\ vbox to8.5\p@{} \right.\n@space$}}}
648 <latexrelease>\def\Big#1{{\hbox{$\left#1\ vbox to11.5\p@{} \right.\n@space$}}}
649 <latexrelease>\def\bigg#1{{\hbox{$\left#1\ vbox to14.5\p@{} \right.\n@space$}}}
650 <latexrelease>\def\Bigg#1{{\hbox{$\left#1\ vbox to17.5\p@{} \right.\n@space$}}}
651 <latexrelease>\EndIncludeInRelease
652 <*math>

653 \def\n@space{\null\delimiterspace\z@ \m@th}
```

### 6.6.2 The log-like functions

`\operator@font` The `\operator@font` determines the symbol font used for log-like functions.

```
654 \def\operator@font{\mathgroup\symoperators}
```

*(End of definition for \operator@font.)*

### 6.6.3 Parameters

```
655 \thinmuskip=3mu
656 \medmuskip=4mu plus 2mu minus 4mu
657 \thickmuskip=5mu plus 5mu
```

This finishes the low-level setup in `fontmath.ltx`.

```
658 </math>
```

## 7 Default cfg files

We provide default `cfg` files here to ensure that on installations that search large file trees we do not pick up some strange customisation files from somewhere.

```
659 <*cfgtext | cfgmath | cfgprel>
660 %%
661 %%
662 %%
663 %% Load the standard setup:
664 %%
665 <+cfgtext>\input{fonttext.ltx}
```

```

666 <+cfgmath>\input{fontmath.ltx}
667 <+cfgprel>\input{preload.ltx}
668 %%
669 %% Small changes could go here; see documentation in cfgguide.tex for
670 %% allowed modifications.
671 %%
672 %% In particular it is not allowed to misuse this configuration file
673 %% to modify internal LaTeX commands!
674 %%
675 %% If you use this file as the basis for configuration please change
676 %% the \ProvidesFile lines to clearly identify your modification, e.g.,
677 %%
678 <+cfgtext>%% \ProvidesFile{fonttext.cfg}[2001/06/01
679 <+cfgmath>%% \ProvidesFile{fonttext.cfg}[2001/06/01
680 <+cfgprel>%% \ProvidesFile{preload.cfg}[2001/06/01
681 %% Customised local font setup]
682 %%
683 %%
684 </cfgtext | cfgmath | cfgprel>

```

## File 31

# preload.dtx

## 1 Overview

This file contains an number of possible settings for preloading fonts during installation of NFSS2 (which is used by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>). It will be used to generate the following files:

preload.min	minimal subset of fonts necessary to run NFSS2
preload.ori	preload of CM fonts similar to the old <code>lfonts.tex</code>
preload.ltx	The standard selection of preloads
cmpreload.xpt	preload of CM fonts for 10pt document size
cmpreload.xip	preload of CM fonts for 11pt document size
cmpreload.xii	preload of CM fonts for 12pt document size
dcpreload.xpt	preload of DC fonts for 10pt size
dcpreload.xip	preload of DC fonts for 11pt size
dcpreload.xii	preload of DC fonts for 12pt size

These files are for installations that make use of Computer Modern fonts either old encoding (OT1) or Cork encoding (T1). The Computer Modern fonts with Cork encoding are known as DC-fonts.

Most important is `preload.ltx` which is used during format generation. You are *not* allowed to change this file.

## 2 Customization

You can customize the preloaded fonts in your L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> system by installing a file with the name `preload.cfg`. If this file exists it will be used in place of the system file `preload.ltx`. You can, for example, copy one of the files mentioned above (that can be generated from this source) to `preload.cfg`.

Or you can define completely other preloads. In that case start from `preload.min` since that contains the fonts that have to be preloaded by *\*all\** L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> systems.

Avoid using `preload.ori`, it will load so many fonts that on most installations it is nearly impossible to load other font families afterwards. This file is only generated to show what fonts have been preloaded by L<sup>A</sup>T<sub>E</sub>X 2.09.

If you normally use other fonts than Computer Modern `preload.min` might be best.

**Warning:** If you preload fonts with encodings other than the normally supported encodings you have to declare that encoding in a `fontdef.cfg` configuration file (see the documentation in the file `fontdef.dtx`). Adding an extra encoding to the format might produce non-portable documents, thus this should be avoided if possible.

## 3 Module switches for the DOCSTRIP program

The DOCSTRIP will generate the above file from this source using the following module directives:

driver	produce a documentation driver file
preload	produce a preload... file
cm	for OT1 encoded Computer Modern
dc	for T1 encoded Computer Modern
min	produce minimal subset
xpt	produce 10pt preloads
xipt	produce 11pt preloads
xipt	produce 12pt preloads
ori	produce preloads similar to old <code>lfonts.tex</code>
tex	produce <code>preload.ltx</code>

A typical DOCSTRIP command file would then have entries like:

```
generateFile{preload.min}{t}{\from{preload.dtx}{preload,min}}
```

for generating preload files.

## 4 A driver for this document

The next bit of code contains the documentation driver file for T<sub>E</sub>X, i.e., the file that will produce the documentation you are currently reading. It will be extracted from this file by the DOCSTRIP program.

```

1 <*driver>
2 \documentclass{ltxdoc}
3 %\OnlyDescription % comment out for implementation details
4 \begin{document}
5   \DocInput{preload.dtx}
6 \end{document}
7 </driver>
```

## 5 The code

We begin by loading the math extension font (cmex10) and the L<sup>A</sup>T<sub>E</sub>X line and circle fonts. It is necessary to do this explicitly since these are used by the L<sup>A</sup>T<sub>E</sub>X format. Since the internal font name contains / characters and digits we construct the name via `\csname`. These are the only fonts (!) that must be loaded in this file.

All `\DeclarePreloadSizes` can be removed or others can be added, they only influence the processing speed.

```

8 \expandafter\font\csname OMX/cmex/m/n/10\endcsname=cmex10\relax
9 \font\tenln =line10 \font\tenlnw =linew10\relax
10 \font\tencirc=lcircle10 \font\tencircw=lcirclew10\relax
```

The above fonts should not be touched but anything below this point here in the preload suggestions can be modified without any problems.

```

11 <-tex>%*****
12 <-tex>% Start any modification below this point **
13 <-tex>%*****
14 <-tex>
15 %%
16 %% Computer Modern Roman:
17 %%-----
```

```

18 <*ori>
19 \DeclarePreloadSizes{OT1}{cmr}{m}{n}
20     {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74,24.88}
21 \DeclarePreloadSizes{OT1}{cmr}{bx}{n}{9,10,10.95,12,14.4,17.28}
22 \DeclarePreloadSizes{OT1}{cmr}{m}{sl}{10,10.95,12}
23 \DeclarePreloadSizes{OT1}{cmr}{m}{it}{7,8,9,10,10.95,12}
24 </ori>
25 <+xpt & cm> \DeclarePreloadSizes{OT1}{cmr}{m}{n}{5,7,10}
26 <+xpt & dc> \DeclarePreloadSizes{T1}{cmr}{m}{n}{5,7,10}
27 <+xipt & cm> \DeclarePreloadSizes{OT1}{cmr}{m}{n}{6,8,10.95}
28 <+xipt & dc> \DeclarePreloadSizes{T1}{cmr}{m}{n}{6,8,10.95}
29 <+xipt & cm> \DeclarePreloadSizes{OT1}{cmr}{m}{n}{6,8,12}
30 <+xipt & dc> \DeclarePreloadSizes{T1}{cmr}{m}{n}{6,8,12}
31 %%
32 %% Computer Modern Sans:
33 %%-----
34 <+ori> \DeclarePreloadSizes{OT1}{cmss}{m}{n}{10,10.95,12}
35 %%
36 %% Computer Modern Typewriter:
37 %%-----
38 <+ori> \DeclarePreloadSizes{OT1}{cmtt}{m}{n}{9,10,10.95,12}
39 %%
40 %% Computer Modern Math:
41 %%-----
42 <*ori>
43 \DeclarePreloadSizes{OML}{cmm}{m}{it}
44     {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
45 \DeclarePreloadSizes{OMS}{cmsy}{m}{n}
46     {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
47 </ori>

```

The math fonts are the same for both DC and CM fonts. So far there isn't an agreed on standard.

```

48 <*xpt>
49 \DeclarePreloadSizes{OML}{cmm}{m}{it}{5,7,10}
50 \DeclarePreloadSizes{OMS}{cmsy}{m}{n}{5,7,10}
51 </xpt>
52 <*xipt>
53 \DeclarePreloadSizes{OML}{cmm}{m}{it}{6,8,10.95}
54 \DeclarePreloadSizes{OMS}{cmsy}{m}{n}{6,8,10.95}
55 </xipt>
56 <*xipt>
57 \DeclarePreloadSizes{OML}{cmm}{m}{it}{6,8,12}
58 \DeclarePreloadSizes{OMS}{cmsy}{m}{n}{6,8,12}
59 </xipt>
60 %%
61 %% LaTeX symbol fonts:
62 %%-----
63 <*ori>
64 \DeclarePreloadSizes{U}{lasy}{m}{n}
65     {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
66 </ori>
67 </preload>

```

# File 32

## lftntcmd.dtx

### Abstract

The commands defined in this file `lftntcmd` are part of the kernel code for  $\text{\LaTeX 2}_{\epsilon}/\text{NFSS2}$ .

It is also meant to serve as documentation for package writers since it demonstrates how to define high-level font changing commands using a small number of creator functions.

## 1 Introduction

Font changes such as `\bfseries`, `\sffamily`, etc. are declarations; this means that their scope is delimited by the grouping structure, either by the next `\end` of some environment or by explicitly using a group, e.g., writing something like `{\bfseries...}` in the source. If you make the mistake of writing `\bfseries{...}` (thinking of `\bfseries` as a command with one argument) then the result is rather striking.

Font declarations are an artifact of the  $\text{\TeX}$  system and for several reasons it is better to avoid them on the user level whenever possible. In  $\text{\LaTeX 3}$  they will probably all be replaced by environments and by font commands taking one argument.

This file defines a creator function for such declarative font switches. This function creates commands which can be used in both math and text.

This file also defines a number of high-level commands (all starting with `\text..`) that have one argument and typeset this argument in the requested way. Thus these commands are for typesetting short pieces of text in a specific family, series or shape. These are all produced as examples of the use of a creator function which is itself also defined in this file.

Table 3 shows all these high-level commands in action. A further advantage of using these commands is that they automatically take care of any necessary italic correction on either side of their argument.

Thus, when using such commands, one does not have to worry about forgetting the italic correction when changing fonts. Only in very few situations is this additional space wrong but, for example, most typographers recommend omitting the italic correction if a small punctuation character, like a comma, directly follows the font change. Since the amount of correction required is partly a matter of taste, you can define in what situations the italic correction should be suppressed. This is done by putting the characters that should cancel a preceding italic correction in the list `\nocorrlist`.<sup>39</sup> The default definition for this list is produced by the following.

```
\newcommand \nocorrlist {,.}
```

It is best to declare the most often used characters first, because this will make the processing slightly faster. For example,

```
\emph{When using the \NFSS{} high-level commands,  
the \emph{proper} use of italic corrections is  
automatically taken care of}. Only
```

---

<sup>39</sup>Any package that changes the `\catcode` of a character inside `\nocorrlist` must then explicitly reset the list. Otherwise the changed character will no longer be recognized by the suppression algorithm.

<i>Command</i>	<i>Corresponds to</i>	<i>Action</i>
<code>\textnormal{..}</code>	<code>\normalfont</code>	Typeset argument in normal family
<code>\textrm{..}</code>	<code>\rmfamily</code>	Typeset argument in roman family
<code>\textsf{..}</code>	<code>\sffamily</code>	Typeset argument in <b>sans serif</b> family
<code>\texttt{..}</code>	<code>\ttfamily</code>	Typeset argument in <b>typewriter</b> family
<code>\textmd{..}</code>	<code>\mdseries</code>	Typeset argument in medium series
<code>\textbf{..}</code>	<code>\bfseries</code>	Typeset argument in <b>bold</b> series
<code>\textup{..}</code>	<code>\upshape</code>	Typeset argument in normal shape
<code>\textit{..}</code>	<code>\itshape</code>	Typeset argument in <i>italic</i> shape
<code>\textsl{..}</code>	<code>\slshape</code>	Typeset argument in <i>slanted</i> shape
<code>\textsc{..}</code>	<code>\scshape</code>	Typeset argument in SMALL CAPS shape
<code>\emph{..}</code>	<code>\em</code>	Typeset argument <i>emphasized</i>

Table 3: Font-change commands with arguments

The font change commands provided here all start with `\text..` to emphasize that they are for use in normal text and to be easily memorable. They automatically take care of any necessary italic correction on either side of the argument.

`\emph{sometimes}` one has to help `\LaTeX{}` by adding a `\verb=\nocorr=` command.

which results in:

*When using the NFSS high-level commands, the proper use of italic corrections is automatically taken care of. Only sometimes one has to help L<sup>A</sup>T<sub>E</sub>X by adding a `\nocorr` command.*

In contrast, the use of the declaration forms is often more appropriate when you define your own commands or environments.

```
\newenvironment{bfitemize}{\begin{itemize}\normalfont\bfseries}
                          {\end{itemize}}
\begin{bfitemize}
\item This environment produces boldface items.
\item It is defined in terms of \LaTeX's
      \texttt{itemize} environment and NFSS
      declarations.
\end{bfitemize}
```

This gives:

- **This environment produces boldface items.**
- **It is defined in terms of L<sup>A</sup>T<sub>E</sub>X's `itemize` environment and NFSS declarations.**

In addition to global customization of when to insert the italic correction, it is of course sometimes necessary to explicitly insert one with `\/`.

It is also possible to suppress the italic correction in individual instances. For this, the command `\nocorr` is provided.

The `\nocorr` must appear as the first or last token inside the braces of the argument of the `\text...` commands, at that end of the text where you wish to suppress the italic correction.

It is worth pointing out here that inserting a `\/` in places where it can have no function (i.e. anywhere except immediately after a slanted letter) is not an error—it will just be silently ignored. Unfortunately this is not true if the redefinition of `\/` in `amstex.sty` is used as this version can cause space to be removed immediately before the `\/`.

## 2 The implementation

`\DeclareTextFontCommand` This is the creator function for `\text..` commands. It gives a warning if `\foo` or `\fragfoo` is already defined.

In math mode it simply puts the font declaration and text into a box (possibly an automagically sized one).

Otherwise it first scans the text to see where `\nocorr` occurs within it. This sets the `\check@ic` commands to do what is necessary concerning the italic correction at both ends.

The algorithm for deciding whether to put in an italic correction is not very subtle: one is added whenever the newly current font is not itself positively sloped, unless the next token is a character in the ‘nocorr’ list. At the end of the text this is done after closing the group so as to check the ‘outer font’. Note that this will often result in adding an italic correction token after a character in an unsloped font; we believe (in early 2003) that this is perhaps inefficient but not dangerous.

It also now checks for empty contents of the text command and optimizes this case. Some care is also taken to check that doing dangerous things in vertical mode is avoided.

The italic correction token is added to the horizontal list before (in the list) an immediately preceding non-zero glob of glue (skip) and any non-zero penalty preceding that since, in the typical case, this puts it immediately after the last character in the preceding word.

Note that it is necessary to put in the `\aftergroup\maybe@ic` at the end of the group so that it comes after any other aftergroup tokens and immediately before the following tokens. It is also necessary to remove the `\fi` from the token list before the group ends; this is done by adding an `\expandafter` just before the closing brace.

```

1  \<2kernel>
2  \def \DeclareTextFontCommand #1#2{%
3    \DeclareRobustCommand#1[1]{%
4      \ifmmode
5        \nfss@text{#2##1}%
6      \else
7        \hmode\bgroup
8        \text@command{##1}%
9        #2\check@icl ##1\check@icr
10       \expandafter
11       \egroup
12       \fi
13           }%
14 }

```

(End of definition for `\DeclareTextFontCommand`.)

```

\textrm Now we define the \text<family> commands in terms of the above; \textttt does not
\textsf look very nice!
\texttt 15 \DeclareTextFontCommand{\textrm}{\rmfamily}
\textnormal 16 \DeclareTextFontCommand{\textsf}{\sffamily}
          17 \DeclareTextFontCommand{\texttt}{\ttfamily}
          18 \DeclareTextFontCommand{\textnormal}{\normalfont}

```

(End of definition for `\textrm` and others.)

```

\textbf For the series attribute:
\textmd 19 \DeclareTextFontCommand{\textbf}{\bfseries}
          20 \DeclareTextFontCommand{\textmd}{\mdseries}

```

(End of definition for `\textbf` and `\textmd`.)

```

\textit And for the shapes:
\textsl 21 \DeclareTextFontCommand{\textit}{\itshape}
\textsc 22 \DeclareTextFontCommand{\textsl}{\slshape}
\textup 23 \DeclareTextFontCommand{\textsc}{\scshape}
          24 \DeclareTextFontCommand{\textup}{\upshape}

```

(End of definition for `\textit` and others.)

```

\textulc
\textsw 25 </2ekernel>
\textssc 26 <*2ekernel | latexrelease>
          27 <latexrelease>\IncludeInRelease{2020/02/02}%
          28 <latexrelease>          {\textulc}{Additional text commands}%
          29 \DeclareTextFontCommand{\textulc}{\ulcshape}
          30 \DeclareTextFontCommand{\textsw}{\swshape}
          31 \DeclareTextFontCommand{\textssc}{\sscshape}
          32 </2ekernel | latexrelease>
          33 <latexrelease>\EndIncludeInRelease
          34 <latexrelease>\IncludeInRelease{0000/00/00}%
          35 <latexrelease>          {\textulc}{Additional text commands}%
          36 <latexrelease>
          37 <latexrelease>\let\textulc\@undefined
          38 <latexrelease>\let\textsw\@undefined
          39 <latexrelease>\let\textssc\@undefined
          40 <latexrelease>\EndIncludeInRelease
          41 <*2ekernel>

```

(End of definition for `\textulc`, `\textsw`, and `\textssc`.)

`\emph` Finally we have the `\em` font change declaration of L<sup>A</sup>T<sub>E</sub>X. The corresponding definition with argument is

```
42 \DeclareTextFontCommand{\emph}{\em}
```

(End of definition for `\emph`.)

`\nocorr` This is just a label, so it does nothing; it should also be unexpandable.

```
43 \let \nocorr \relax
```

(End of definition for `\nocorr`.)

`\check@ic1` We define these defaults in case some error causes them to be expanded at the wrong  
`\check@icr` time.

```
44 \let \check@ic1 \@empty
45 \let \check@icr \@empty
```

(End of definition for `\check@ic1` and `\check@icr`.)

`\text@command` This checks for a `\nocorr` as the first token in its argument and also for one in any other  
`\check@nocorr@` position not protected within braces (the latter is treated as if it were at the end of the argument).

Is this the correct action in the ‘empty’ case? It is efficient but typographically it is, strictly, incorrect!

```
46 \def \text@command #1{%
47   \edef \reserved@a {\unexpanded{#1}}%
48   \ifx \reserved@a \@empty
49     \let \check@ic1 \@empty
50     \let \check@icr \@empty
51   \else
```

`\space` is a reserved word in L<sup>A</sup>T<sub>E</sub>X or actually already in plain T<sub>E</sub>X. If somebody really redefines it so many things will break that I don’t see any reason to make this routine here slower than necessary.

```
52 %   \def \reserved@b { }%
53 %   \ifx \reserved@a \reserved@b
54   \ifx \reserved@a \space
55     \let \check@ic1 \@empty
56     \let \check@icr \@empty
57   \else
58     \check@nocorr@ #1\nocorr\@nil
59   \fi
60 \fi
61 }
62 \def \check@nocorr@ #1#2\nocorr#3\@nil {%
```

The two checks are initialised here to their values in the normal case.

```
63 \let \check@ic1 \maybe@ic
64 \def \check@icr {\ifvmode \else \aftergroup \maybe@ic \fi}%
65 \def \reserved@a {\nocorr}%
66 \def \reserved@b {#1}%
67 \def \reserved@c {#3}%
68 \ifx \reserved@a \reserved@b
69   \ifx \reserved@c \@empty
```

In this case there is a `\nocorr` at the start but not at the end, so `\check@ic1` should be empty.

```
70   \let \check@ic1 \@empty
71   \else
```

Otherwise there is a `\nocorr` both at the start and elsewhere, so no italic corrections should be added.

```
72   \let \check@ic1 \@empty
73   \let \check@icr \@empty
74 \fi
```

```

75     \else
76     \ifx \reserved@c \@empty

```

In this case there is no `\nocorr` anywhere, so we need to check for an italic correction at both the beginning and the end. This has been set up as the default so no code is needed here.

```

77     \else

```

In this case there is no `\nocorr` at the start but there is one elsewhere, so no `\aftergroup` is needed.

```

78         \let \check@icr \@empty
79     \fi
80 \fi
81 }

```

*(End of definition for \text@command and \check@nocorr@.)*

`\ifmaybe@ic` Switch used solely within `\maybe@ic` not interfering with other switches.

```

82 \newif\ifmaybe@ic

```

*(End of definition for \ifmaybe@ic.)*

`\maybe@ic` These macros implement the italic correction.

```

\maybe@ic@
83 \def \maybe@ic {\futurelet \@let@token \maybe@ic@}
84 \def \maybe@ic@ {%

```

We first check to see if the current font is positively sloped. (But do not forget the message Rainer sent about an upright font with non-zero slope! Or is this an urban myth?) It has been suggested that this should test against a small positive value, but what?

```

85     \ifdim \fontdimen\@ne\font>\z@
86     \else
87     \maybe@ictrue

```

It would be possible, but probably not worthwhile, to continue the forward scan beyond any closing braces.

```

88     \expandafter \@tfor \expandafter \reserved@a \expandafter : \expandafter = %
89     \nocorrlist

```

We have to hide the `\@let@token` in the macro `\t@st@ic` rather than testing it directly in the loop since it might be `\let` to a `\fi` or `\else`, which would result in chaos.

```

90     \do \t@st@ic

```

Frank thinks that the next bit is inefficient if done after the second change. Chris thinks that most all of this is inefficient for the commonest cases: but that is the price of a cleverer algorithm. It is certainly needed to deal with the use of `\nolinebreak`.

```

91     \ifmaybe@ic \sw@slant \fi
92 \fi
93 }

```

*(End of definition for \maybe@ic and \maybe@ic@.)*

`\t@st@ic` The next token in the input stream is stored in `\@let@token` via a `\let`, the current token from `\nocorrlist` is stored via `\def` in `\reserved@a`. To compare them we have to fiddle around a bit.

If the only things to check were characters then this could be done via an `\if` thus their catcodes would not matter; but this will not work whilst `\futurelet` is used above.

```

94 \def \t@st@ic {%
95   \expandafter\let\expandafter\reserved@b\expandafter=\reserved@a\relax
96   \ifx\reserved@b\@let@token

```

If they are the same we record the fact and jump out of the loop.

```

97     \maybe@icfalse
98     \@break@tfor
99   \fi
100 }

```

*(End of definition for \t@st@ic.)*

`\sw@slant` The definition of the mysterious `\sw@slant` command is as follows.  
`\fix@penalty`

```

101 \def \sw@slant {%

```

It is surely correct to put in an italic correction when there is no skip. If the last thing on the list is actually a zero skip (including things whose dimension part is zero, such as `\hfill`), or anything other than a character, then the italic correction will have no effect.

In order to work correctly with unbreakable spaces from `~` (and other common forms of line-breaking control) we also move back across a penalty before the glue.

```

102   \ifdim \lastskip=\z@
103     \fix@penalty
104   \else
105     \skip@ \lastskip
106     \unskip
107     \fix@penalty
108     \hskip \skip@
109   \fi
110 }

```

The above code means: “If there is a non-zero space just before the current position (`\ifdim...`) save the amount of that space (`\skip@\lastskip`), remove it (`\unskip`), then do a similar thing if there is a penalty just before the skip, and finally put the space back in.”

Since zero glue cannot be distinguished in this context from no glue, we dare not put in an `\hskip` in this case as this may produce an unwanted breakpoint. This is not satisfactory.

The penalty before the glue is handled similarly, with the same caveats concerning the zero case. Is this the first recorded use of `\unpenalty` in standard L<sup>A</sup>T<sub>E</sub>X code?

```

111 \def \fix@penalty {%
112   \ifnum \lastpenalty=\z@
113     @@italiccorr
114   \else
115     \count@ \lastpenalty
116     \unpenalty
117     @@italiccorr

```

```

118     \penalty \count@
119     \fi
120 }

```

(End of definition for `\sw@slant` and `\fix@penalty`.)

**\nocorrlist** This holds the list of characters that should prevent italic correction. They should be ordered by decreasing frequency of use. If any such character is made active later on one needs to redefine the list so that the active character becomes part of it.

```

121 \def \nocorrlist {,.}

```

(End of definition for `\nocorrlist`.)

**\nfss@text** This command will by default behave like a L<sup>A</sup>T<sub>E</sub>X `\mbox` but may be redefined by packages such as `amstext.sty` to be a bit cleverer.

```

122 \ifx \nfss@text\undefined
123   \def \nfss@text {\leavevmode\hbox}
124 \fi

```

(End of definition for `\nfss@text`.)

**\DeclareOldFontCommand** This is the function used to create declarative font-changing commands that can also be used to change alphabets in math-mode.

Usage: `\DeclareOldFontCommand \fn{<font-change decls>} <math-alphabet>`

Here `\fn` is the font-declaration command being defined, `<font-change decls>` is the declaration it will expand to in text-mode, and `<math-alphabet>` is the (single) math alphabet specifier which is to be used in math-mode.

It does not care whether the command being defined already exists but it does give a warning if it redefines anything.

Here are some typical examples of its use in conjunction with more basic NFSS2 font commands.

```

\DeclareOldFontCommand{\rm}{\normalfont\rmfamily}{\mathrm}
\DeclareOldFontCommand{\sf}{\normalfont\sffamily}{\mathsf}
\DeclareOldFontCommand{\tt}{\normalfont\ttfamily}{\mathtt}

```

```

125 \def \DeclareOldFontCommand #1#2#3{%
126   \DeclareRobustCommand #1{\@fontswitch {#2}{#3}}%
127 }

```

(End of definition for `\DeclareOldFontCommand`.)

**\@fontswitch** **\@math@egroup** These two commands actually do the necessary tests and declarative font- or alphabet-changing.

```

\@math@egroup
\@math@egroup
128 \def \@fontswitch #1#2{%
129   \ifmmode
130     \let \math@bgroup \relax
131     \def \math@egroup {\let \math@bgroup \@math@bgroup
132                       \let \math@egroup \@math@egroup}%

```

We need to have a `\relax` in the following line in case the `#2` is something like `\mathsf` grabbing the next token as an argument. For this reason the code also uses explicit arguments again (see pr/1275).

```

133     #2\relax
134   \else
135     #1%
136   \fi
137 }
138 \let \@@math@bgroup \math@bgroup
139 \let \@@math@egroup \math@egroup

(End of definition for \@fontswitch, \@@math@egroup, and \@@math@egroup.)
These commands are available only in the preamble.

140 \@onlypreamble \DeclareTextFontCommand
141 \@onlypreamble \DeclareOldFontCommand

```

### 3 Initialization

```

\normalsize This is defined to produce an error.

142 \def\normalsize{%
143   \@latex@error {The font size command \protect\normalsize\space
144                 is not defined:\MessageBreak
145                 there is probably something wrong with
146                 the class file}\@eha
147 }
148 \</2ekernel>

(End of definition for \normalsize.)

```

## File 33

# ltxtextcomp.dtx

This file contains the implementation for accessing the glyphs provided by the TS1 encoding (Text Companion Encoding). This is now offered as part of the kernel and so the `textcomp` package which used to provide the definitions is now mainly needed for compatibility reasons (and doesn't do much any more).

```
1 <*2ekernel | latexrelease>
2 <latexrelease>\NewModuleRelease{2020/02/02}{ltxtextcomp}
3 <latexrelease>                                {Text Companion symbols}
```

`\oldstylenums`  
`\legacyoldstylenums`

Preserve the old definition of `\oldstylenums` under a different name.

This macro implements old style numerals but only works if we assume that the standard math fonts are used. Thus it needs changing in case other math encodings are used.

```
4 \DeclareRobustCommand\legacyoldstylenums[1]{%
5   \begingroup
```

Provide spacing using the interword space of the current font.

```
6   \spaceskip\fontdimen\tw@\font
```

Then switch to the math italic font. We don't change the current value of `\f@series` which means that you can use bold numerals if `\bfseries` is in force. As family we use `\rmdefault` which means that this only works if there exist an OML encoded version of that font or rather a corresponding .fd file (which is the case for standard L<sup>A</sup>T<sub>E</sub>X fonts even though they only contain substitutions).

```
7   \usefont{OML}{\rmdefault}{\f@series}{it}%
8   \mathgroup\symletters #1%
9   \endgroup
10 }
```

And here is the improved one that adjusts depending on surroundings.

```
11 \DeclareRobustCommand\oldstylenums[1]{%
12   \begingroup
13   \ifmmode
14     \mathgroup\symletters #1%
15   \else
```

The `\CheckEncodingSubset` is discussed below.

```
16   \CheckEncodingSubset\@use@text@encoding{TS1}{\tc@oldstylesubst2{{#1}}}%
17   \fi
18   \endgroup
19 }
```

The helper to select the substitution if needed.

```
20 \def\tc@oldstylesubst#1{%
21   \tc@errorwarn
22     {Oldstyle digits unavailable for
23     family \f@family.\MessageBreak
24     Default oldstyle digits used instead}\@eha
25   \bgroup
26   \expand@font@defaults
```

The substitution defaults are provided in the file `fonttext.ltx`.

```

27     \ifx\f@family\rmdef@ult
28         \fontfamily\rmsubstdefault
29     \else\ifx\f@family\sfddef@ult
30         \fontfamily\sfsbstdefault
31     \else\ifx\f@family\ttdef@ult
32         \fontfamily\ttsbstdefault
33     \else
34         \fontfamily\textcompsubstdefault
35     \fi\fi\fi
36     \fontencoding{TS1}\selectfont#1%
37 \egroup
38 }

```

*(End of definition for \oldstylenums and \legacyoldstylenums.)*

`\textcompsubstdefault` Here is the default for the “unknown” case:

```

39 \def\textcompsubstdefault{\rmsubstdefault}

```

*(End of definition for \textcompsubstdefault.)*

To set up the glyphs for the subsets we need a number helpers.

`\tc@errorwarn` To we produce errors, warnings, or only info in the transcripts if glyphs require substitutions? By default it is “info” only. With the `textcomp` package that can be changed.

```

40 \def\tc@errorwarn#1#2{\@latex@info{#1}}

```

*(End of definition for \tc@errorwarn.)*

`\tc@subst`

```

41 \def\tc@subst#1{%
42     \tc@errorwarn
43     {Symbol \string#1 not provided by\MessageBreak
44     font family \f@family\space
45     in TS1 encoding.\MessageBreak Default family used instead}\@eha
46 \bgroup
47     \expand@font@defaults
48     \ifx\f@family\rmdef@ult
49         \fontfamily\rmsubstdefault
50     \else\ifx\f@family\sfddef@ult
51         \fontfamily\sfsbstdefault
52     \else\ifx\f@family\ttdef@ult
53         \fontfamily\ttsbstdefault
54     \else
55         \fontfamily\textcompsubstdefault
56     \fi\fi\fi

```

Whatever default was chosen, we claim now (locally hopefully) that it can handle all slots (even if not true) to avoid looping in certain situations, e.g., when something was set up incorrectly.

```

57     \@namedef{TS1:\f@family}{0}%
58     \selectfont#1%
59 \egroup
60 }

```

*(End of definition for \tc@subst.)*

`\tc@fake@euro` `\tc@fake@euro` is an example of a “fake” definition to use in arg #3 of the command `\CheckEncodingSubset` when a symbol is not available in a certain font family. Here we produce a poor man’s Euro symbol by combining a “C” with a “=”.

```

61 \def\tc@fake@euro#1{%
62   \leavevmode
63   \@font@info{Faking \noexpand#1for font family
64               \f@family\MessageBreak in TS1 encoding}%
65   \valign{##\cr
66     \vfil\hbox to 0.07em{\dimen@\f@size\p@
67                         \math@fontsfalse
68                         \fontsize{.7\dimen@}\z@\selectfont=\hss}%
69     \vfil\cr%
70     \hbox{C}\crrcr
71   }%
72 }
```

*(End of definition for \tc@fake@euro.)*

`\tc@check@symbol` These are two abbreviations that we use below to check symbols and accents in TS1.  
`\tc@check@accent` Only there to save some space, e.g., we can then write

```
DeclareTextCommandDefault{\textcurrency}{\tc@check@symbol3\textcurrency}
```

to ensure that `\textcurrency` is only typeset if the current font has a TS1 subset id of less than 3. Otherwise `\tc@error` is called telling the user that for this font family `\textcurrency` is not available.

```
73 \def\tc@check@symbol{\CheckEncodingSubset\UseTextSymbol{TS1}\tc@subst}
```

Accents have been made an error in the `textcomp` package when not available. Now that we provide the functionality in the kernel we avoid the error by swapping in a T1 accent if the TS1 accent is not available.

```

74 %\def\tc@check@accent{\CheckEncodingSubset\UseTextAccent{TS1}\tc@error}
75 \def\tc@check@accent#1{\CheckEncodingSubset\UseTextAccent
76                       {TS1}{\tc@swap@accent#1}}
77 \def\tc@swap@accent#1#2{\UseTextAccent{T1}#1}
```

*(End of definition for \tc@check@symbol and \tc@check@accent.)*

## 1 Sub-encodings

Here are the default definitions for the TS1 symbols. First those that we assume are always available if a font implements TS1.

```

78 \DeclareTextSymbolDefault{\textdollar}{TS1}
79 \UndeclareTextCommand{\textdollar}{OT1} % don't use the OT1 def any longer
80 \DeclareTextSymbolDefault{\textsterling}{TS1}
81 \UndeclareTextCommand{\textsterling}{OT1}% don't use the OT1 def any longer
82 \DeclareTextSymbolDefault{\textperthousand}{TS1}
83 \UndeclareTextCommand{\textperthousand}{T1} % don't use the T1 def
```

Using `\UndeclareTextCommand` above is enough only if the encoding definition files are not reloaded afterwards. In the past that happened if `fontenc` was used in the document preamble (not any longer). So in some sense it is better to fully remove them from the encoding files, but for rollbacks it is easier to keep them in for now.

These are the standard `itemize` and footnote symbols originally taken from OMS and now from TS1:

```
84 \DeclareTextSymbolDefault{\textasteriskcentered}{TS1}
85 \DeclareTextSymbolDefault{\textbullet}{TS1}
86 \DeclareTextSymbolDefault{\textdaggerdbl}{TS1}
87 \DeclareTextSymbolDefault{\textdagger}{TS1}
88 \DeclareTextSymbolDefault{\textparagraph}{TS1}
89 \DeclareTextSymbolDefault{\textperiodcentered}{TS1}
90 \DeclareTextSymbolDefault{\textsection}{TS1}
```

And here are the other TS1 glyphs that are implemented by every font (or nearly every)—a few are commented out and moved to sub-encoding 9, because they aren't around in some fonts.

```
91 %%\DeclareTextSymbolDefault{\textbardbl}{TS1} % subst in sub-enc 9 above
92 \DeclareTextSymbolDefault{\textbrokenbar}{TS1}
93 %%\DeclareTextSymbolDefault{\textcelsius}{TS1} % subst in sub-enc 9 above
94 \DeclareTextSymbolDefault{\textcent}{TS1}
95 \DeclareTextSymbolDefault{\textcopyright}{TS1}
96 \DeclareTextSymbolDefault{\textdegree}{TS1}
97 \DeclareTextSymbolDefault{\textdiv}{TS1}
98 \DeclareTextSymbolDefault{\textlnot}{TS1}
99 \DeclareTextSymbolDefault{\textonehalf}{TS1}
100 \DeclareTextSymbolDefault{\textonequarter}{TS1}
101 %%\DeclareTextSymbolDefault{\textonesuperior}{TS1} % subst in sub-enc 9 above
102 \DeclareTextSymbolDefault{\textordfeminine}{TS1}
103 \DeclareTextSymbolDefault{\textordmasculine}{TS1}
104 \DeclareTextSymbolDefault{\textpm}{TS1}
105 \DeclareTextSymbolDefault{\textquotesingle}{TS1}
106 \DeclareTextSymbolDefault{\textquotestraightbase}{TS1}
107 \DeclareTextSymbolDefault{\textquotestraightdblbase}{TS1}
108 \DeclareTextSymbolDefault{\textregistered}{TS1}
109 %%\DeclareTextSymbolDefault{\textthreequartersemdash}{TS1} % subst in sub-enc 9 above
110 \DeclareTextSymbolDefault{\textthreequarters}{TS1}
111 %%\DeclareTextSymbolDefault{\textthreesuperior}{TS1} % subst in sub-enc 9 above
112 \DeclareTextSymbolDefault{\texttimes}{TS1}
113 \DeclareTextSymbolDefault{\texttrademark}{TS1}
114 %%\DeclareTextSymbolDefault{\texttwelveudash}{TS1} % subst in sub-enc 9 above
115 %%\DeclareTextSymbolDefault{\texttwosuperior}{TS1} % subst in sub-enc 9 above
116 \DeclareTextSymbolDefault{\textyen}{TS1}

117 \DeclareTextSymbolDefault{\textcapitalcompwordmark}{TS1}
118 \DeclareTextSymbolDefault{\textascendercompwordmark}{TS1}
```

In the following sections the remaining default definitions are ordered by sub-encoding in which they are become **unavailable**, i.e., they are not provided in the sub-encoding with that number and all sub-encodings with higher numbers.

Thus the symbols that are available in sub-encoding  $x$  are the symbols above (always available) and the symbols listed as becoming unavailable in sub-encodings  $x + 1$  and higher.

## 1.1 Unavailable in sub-encoding 1 and higher (drop symbols not working in Latin Modern)

The `\textcircled` is available but the glyph is simply too small so we keep using the OMS glyph.

```
119 \DeclareTextCommandDefault{\textcircled}
120 {\CheckEncodingSubset\UseTextAccent{TS1}{\UseTextAccent{OMS}}1\textcircled}
```

## 1.2 Unavailable in sub-encoding 2 (majority of new OTF fonts via autost) and higher

```
121 \DeclareTextCommandDefault{\t}
122 {\CheckEncodingSubset\UseTextAccent{TS1}{\UseTextAccent{OML}}2\t}
```

Capital accents are really only very seldom implemented, so from sub-encoding 2 onwards we use the normal T1 accents if they are asked for in the document.

In Unicode engines we don't implement them at all but always use the basic accents instead. whether that works or not really depends on the font, something like `\"X` usually comes out wrong in Unicode engines.

```
123 \ifx\Umathcode\@undefined
124 \DeclareTextCommandDefault{\capitalacute}
125 {\tc@check@accent{\'}2\capitalacute}
126 \DeclareTextCommandDefault{\capitalbreve}
127 {\tc@check@accent{\u}2\capitalbreve}
128 \DeclareTextCommandDefault{\capitalcaron}
129 {\tc@check@accent{\v}2\capitalcaron}
130 \DeclareTextCommandDefault{\capitalcedilla}
131 {\tc@check@accent{\c}2\capitalcedilla}
132 \DeclareTextCommandDefault{\capitalcircumflex}
133 {\tc@check@accent{\^}2\capitalcircumflex}
134 \DeclareTextCommandDefault{\capitaldieresis}
135 {\tc@check@accent{\"}2\capitaldieresis}
136 \DeclareTextCommandDefault{\capitaldotaccent}
137 {\tc@check@accent{\.}2\capitaldotaccent}
138 \DeclareTextCommandDefault{\capitalgrave}
139 {\tc@check@accent{\`}2\capitalgrave}
140 \DeclareTextCommandDefault{\capitalhungarumlaut}
141 {\tc@check@accent{\H}2\capitalhungarumlaut}
142 \DeclareTextCommandDefault{\capitalmacron}
143 {\tc@check@accent{\=}2\capitalmacron}
144 \DeclareTextCommandDefault{\capitalogonek}
145 {\tc@check@accent{\k}2\capitalogonek}
146 \DeclareTextCommandDefault{\capitalring}
147 {\tc@check@accent{\r}2\capitalring}
148 \DeclareTextCommandDefault{\capitaltie}
149 {\tc@check@accent{\t}2\capitaltie}
150 \DeclareTextCommandDefault{\capitaltilde}
151 {\tc@check@accent{\~}2\capitaltilde}
```

For `\newtie` and `\capitalnewtie` this is actually wrong, they should pick up the accent from the substitution font (not done yet).

```
152 \DeclareTextCommandDefault{\newtie}
153 {\tc@check@accent{\t}2\newtie}
154 \DeclareTextCommandDefault{\capitalnewtie}
```

```
155                                {\tc@check@accent{\t}2\capitalnewtie}
```

In Unicode engines we just execute the simple accents:

```
156 \else
157   \DeclareTextCommandDefault\capitalacute{\@tabacckludge'}
158   \DeclareTextCommandDefault\capitalbreve{\u}
159   \DeclareTextCommandDefault\capitalcaron{\v}
160   \DeclareTextCommandDefault\capitalcedilla{\c}
161   \DeclareTextCommandDefault\capitalcircumflex{\^}
162   \DeclareTextCommandDefault\capitaldieresis{"}
163   \DeclareTextCommandDefault\capitaldotaccent{.}
164   \DeclareTextCommandDefault\capitalgrave{\@tabacckludge`}
165   \DeclareTextCommandDefault\capitalhungarumlaut{\H}
166   \DeclareTextCommandDefault\capitalmacron{\@tabacckludge=}
167   \DeclareTextCommandDefault\capitalnewtie{\t}
168   \DeclareTextCommandDefault\capitalogonek{\k}
169   \DeclareTextCommandDefault\capitalring{\r}
170   \DeclareTextCommandDefault\capitaltie{\t}
171   \DeclareTextCommandDefault\capitaltilde{\~}
172   \DeclareTextCommandDefault\newtie{\t}
173 \fi
```

The next two symbols exist in some fonts (faked?), but we ignore that to keep the subsets reasonable compact and most important linear.

```
174 \DeclareTextCommandDefault{\textlbrackdbl}
175                                {\tc@check@symbol2\textlbrackdbl}
176 \DeclareTextCommandDefault{\textrbrackdbl}
177                                {\tc@check@symbol2\textrbrackdbl}
```

Old style numerals are again in some fonts but using -OsF, etc. is the better approach to get them, so we claim they aren't in sub-encoding 2 as that's true for most fonts.

```
178 \DeclareTextCommandDefault{\texteightoldstyle}
179                                {\tc@check@symbol2\texteightoldstyle}
180 \DeclareTextCommandDefault{\textfiveoldstyle}
181                                {\tc@check@symbol2\textfiveoldstyle}
182 \DeclareTextCommandDefault{\textfouroldstyle}
183                                {\tc@check@symbol2\textfouroldstyle}
184 \DeclareTextCommandDefault{\textnineoldstyle}
185                                {\tc@check@symbol2\textnineoldstyle}
186 \DeclareTextCommandDefault{\textoneoldstyle}
187                                {\tc@check@symbol2\textoneoldstyle}
188 \DeclareTextCommandDefault{\textsevenoldstyle}
189                                {\tc@check@symbol2\textsevenoldstyle}
190 \DeclareTextCommandDefault{\textsixoldstyle}
191                                {\tc@check@symbol2\textsixoldstyle}
192 \DeclareTextCommandDefault{\textthreeoldstyle}
193                                {\tc@check@symbol2\textthreeoldstyle}
194 \DeclareTextCommandDefault{\texttwooldstyle}
195                                {\tc@check@symbol2\texttwooldstyle}
196 \DeclareTextCommandDefault{\textzerooldstyle}
197                                {\tc@check@symbol2\textzerooldstyle}
```

The next set of glyphs is special to T<sub>E</sub>X fonts (and available with a few older PS fonts supported through virtual fonts), but not any longer in the majority of fonts provided through autost, so we pretend there aren't available in sub-encoding 2 and below.

```
198 \DeclareTextCommandDefault{\textacutedbl}
```

```

199             {\tc@check@symbol2\textacutedbl}
200 \DeclareTextCommandDefault{\textasciiacute}
201             {\tc@check@symbol2\textasciiacute}
202 \DeclareTextCommandDefault{\textasciibreve}
203             {\tc@check@symbol2\textasciibreve}
204 \DeclareTextCommandDefault{\textasciicaron}
205             {\tc@check@symbol2\textasciicaron}
206 \DeclareTextCommandDefault{\textasciidieresis}
207             {\tc@check@symbol2\textasciidieresis}
208 \DeclareTextCommandDefault{\textasciigrave}
209             {\tc@check@symbol2\textasciigrave}
210 \DeclareTextCommandDefault{\textasciimacron}
211             {\tc@check@symbol2\textasciimacron}
212 \DeclareTextCommandDefault{\textgravedbl}
213             {\tc@check@symbol2\textgravedbl}
214 \DeclareTextCommandDefault{\texttildelow}
215             {\tc@check@symbol2\texttildelow}

```

Finally those below are only available in CM-based fonts but in no font that has its origin outside of the T<sub>E</sub>X world.

```

216 \DeclareTextCommandDefault{\textbaht}
217             {\tc@check@symbol2\textbaht}
218 \DeclareTextCommandDefault{\textbigcircle}
219             {\tc@check@symbol2\textbigcircle}
220 \DeclareTextCommandDefault{\textborn}
221             {\tc@check@symbol2\textborn}
222 \DeclareTextCommandDefault{\textcentoldstyle}
223             {\tc@check@symbol2\textcentoldstyle}
224 \DeclareTextCommandDefault{\textcircledP}
225             {\tc@check@symbol2\textcircledP}
226 \DeclareTextCommandDefault{\textcopyleft}
227             {\tc@check@symbol2\textcopyleft}
228 \DeclareTextCommandDefault{\textdblhyphenchar}
229             {\tc@check@symbol2\textdblhyphenchar}
230 \DeclareTextCommandDefault{\textdblhyphen}
231             {\tc@check@symbol2\textdblhyphen}
232 \DeclareTextCommandDefault{\textdied}
233             {\tc@check@symbol2\textdied}
234 \DeclareTextCommandDefault{\textdiscount}
235             {\tc@check@symbol2\textdiscount}
236 \DeclareTextCommandDefault{\textdivorced}
237             {\tc@check@symbol2\textdivorced}
238 \DeclareTextCommandDefault{\textdollaroldstyle}
239             {\tc@check@symbol2\textdollaroldstyle}
240 \DeclareTextCommandDefault{\textguarani}
241             {\tc@check@symbol2\textguarani}
242 \DeclareTextCommandDefault{\textleaf}
243             {\tc@check@symbol2\textleaf}
244 \DeclareTextCommandDefault{\textlquill}
245             {\tc@check@symbol2\textlquill}
246 \DeclareTextCommandDefault{\textmarried}
247             {\tc@check@symbol2\textmarried}
248 \DeclareTextCommandDefault{\textmho}
249             {\tc@check@symbol2\textmho}
250 \DeclareTextCommandDefault{\textmusicalnote}

```

```

251             {\tc@check@symbol2\textmusicalnote}
252 \DeclareTextCommandDefault{\textnaira}
253             {\tc@check@symbol2\textnaira}
254 \DeclareTextCommandDefault{\textopenbullet}
255             {\tc@check@symbol2\textopenbullet}
256 \DeclareTextCommandDefault{\textpeso}
257             {\tc@check@symbol2\textpeso}
258 \DeclareTextCommandDefault{\textpildcrow}
259             {\tc@check@symbol2\textpildcrow}
260 \DeclareTextCommandDefault{\textrecipe}
261             {\tc@check@symbol2\textrecipe}
262 \DeclareTextCommandDefault{\textreferencemark}
263             {\tc@check@symbol2\textreferencemark}
264 \DeclareTextCommandDefault{\textrquill}
265             {\tc@check@symbol2\textrquill}
266 \DeclareTextCommandDefault{\textservicemark}
267             {\tc@check@symbol2\textservicemark}
268 \DeclareTextCommandDefault{\textsurd}
269             {\tc@check@symbol2\textsurd}

```

The `\textpertenthousand` also belongs in this group but here we have a choice: in T1 there is a definition for `\textpertenthousand` making the symbol up from % and `\char 24` (twice) but in many fonts that char doesn't exist and the slot is reused for random ligatures. So better not use it because often it is wrong. But pointing to TS1 is also not great as only a few fonts have it as a real symbol, so we get a substitution to CM or LM.

Alternatively we could just state that the symbol is unavailable in those fonts. For now I substitute.

```

270 \DeclareTextCommandDefault{\textpertenthousand}
271             {\tc@check@symbol2\textpertenthousand}
272 \UndeclareTextCommand{\textpertenthousand}{T1}

```

### 1.3 Unavailable in sub-encoding 3 and higher

Sub-encoding 2 is the one where we loose many symbols. In the higher-numbered sub-encodings we see only a few dropped additionally.

```

273 \DeclareTextCommandDefault{\textlangle}
274             {\tc@check@symbol3\textlangle}
275 \DeclareTextCommandDefault{\textrangle}
276             {\tc@check@symbol3\textrangle}

```

### 1.4 Unavailable in sub-encoding 4 and higher

```

277 \DeclareTextCommandDefault{\textcolonmonetary}
278             {\tc@check@symbol4\textcolonmonetary}
279 \DeclareTextCommandDefault{\textdong}
280             {\tc@check@symbol4\textdong}
281 \DeclareTextCommandDefault{\textdownarrow}
282             {\tc@check@symbol4\textdownarrow}
283 \DeclareTextCommandDefault{\textleftarrow}
284             {\tc@check@symbol4\textleftarrow}
285 \DeclareTextCommandDefault{\textlira}
286             {\tc@check@symbol4\textlira}
287 \DeclareTextCommandDefault{\textrightarrow}

```

```

288             {\tc@check@symbol4\textrightarrow}
289 \DeclareTextCommandDefault{\textuparrow}
290             {\tc@check@symbol4\textuparrow}
291 \DeclareTextCommandDefault{\textwon}
292             {\tc@check@symbol4\textwon}

```

## 1.5 Unavailable in sub-encoding 5 (most older PS fonts) and higher

Most older PS fonts (supported in T<sub>E</sub>X since the early nineties when virtual fonts became available) are sorted under this sub-encoding. But in reality, many of them don't have all glyphs that should be available in sub-encoding 5. Instead they show little squares, i.e., they produce “tofu” if you are unlucky.

But the coverage is so random that it is impossible to sort them properly and if we tried to ensure that they only typeset those glyphs that are really always available, we would have to put them all into sub-encoding 9; so putting them into 5 is really a compromise.

Modern fonts usually don't typeset a tofu character if a glyph is missing. They are therefore only classified as sub-encoding 5 if they really support its glyph set completely.

```

293 \DeclareTextCommandDefault{\textestimated}
294             {\tc@check@symbol5\textestimated}
295 \DeclareTextCommandDefault{\textnumero}
296             {\tc@check@symbol5\textnumero}

```

## 1.6 Unavailable in sub-encoding 6 and higher

```

297 \DeclareTextCommandDefault{\textflorin}
298             {\tc@check@symbol6\textflorin}
299 \DeclareTextCommandDefault{\textcurrency}
300             {\tc@check@symbol6\textcurrency}

```

## 1.7 Unavailable in sub-encoding 7 and higher

```

301 \DeclareTextCommandDefault{\textfractionsolidus}
302             {\tc@check@symbol7\textfractionsolidus}
303 \DeclareTextCommandDefault{\textohm}
304             {\tc@check@symbol7\textohm}
305 \DeclareTextCommandDefault{\textmu}
306             {\tc@check@symbol7\textmu}
307 \DeclareTextCommandDefault{\textminus}
308             {\tc@check@symbol7\textminus}

```

## 1.8 Unavailable in sub-encoding 8 and higher

```

309 \DeclareTextCommandDefault{\textblank}
310             {\tc@check@symbol{8}\textblank}
311 \DeclareTextCommandDefault{\textinterrobangdown}
312             {\tc@check@symbol{8}\textinterrobangdown}
313 \DeclareTextCommandDefault{\textinterrobang}
314             {\tc@check@symbol{8}\textinterrobang}

```

Fonts with this sub-encoding don't have a Euro symbol, but instead of substituting we fake it.

```

315 \DeclareTextCommandDefault{\texteuro}
316     {\CheckEncodingSubset\UseTextSymbol{TS1}\tc@fake@euro{8}\texteuro}

```

## 1.9 Unavailable in Sub-encoding 9 (most missing)

```
317 \DeclareTextCommandDefault{\textcelsius}
318         {\tc@check@symbol{9}\textcelsius}
319 \DeclareTextCommandDefault{\textonesuperior}
320         {\tc@check@symbol{9}\textonesuperior}
321 \DeclareTextCommandDefault{\textthreequartersemdash}
322         {\tc@check@symbol{9}\textthreequartersemdash}
323 \DeclareTextCommandDefault{\textthreesuperior}
324         {\tc@check@symbol{9}\textthreesuperior}
325 \DeclareTextCommandDefault{\texttwelveudash}
326         {\tc@check@symbol{9}\texttwelveudash}
327 \DeclareTextCommandDefault{\texttwosuperior}
328         {\tc@check@symbol{9}\texttwosuperior}
329 \DeclareTextCommandDefault{\textbardbl}
330         {\tc@check@symbol{9}\textbardbl}
```

## 2 Unicode engine specials

If we are using a unicode engine we handle some glyphs differently, so this here are the definitions for the Unicode encoding (overwriting the defaults above).

```
331 \ifx \Umathcode\@undefined \else
```

This set should be taken from TS1 encoding even if it means you get it from the default font for that encoding.

```
332 %\DeclareTextSymbol{\textcopyright}{TS1}{171}
333 %\DeclareTextSymbol{\textdblhyphen}{TS1}{45}
334 %\DeclareTextSymbol{\textdblhyphenchar}{TS1}{127}
335 %\DeclareTextSymbol{\textquotestraightbase}{TS1}{13}
336 %\DeclareTextSymbol{\textquotestraightdblbase}{TS1}{18}
337 %\DeclareTextSymbol{\textleaf}{TS1}{108}
338 %\DeclareTextSymbol{\texttwelveudash}{TS1}{21}
339 %\DeclareTextSymbol{\textthreequartersemdash}{TS1}{22}
```

If oldstyle numerals are asked for we just use \oldstylenums.

```
340 \DeclareTextCommand{\textzerooldstyle} \UnicodeEncodingName{\oldstylenums{0}}
341 \DeclareTextCommand{\textoneoldstyle} \UnicodeEncodingName{\oldstylenums{1}}
342 \DeclareTextCommand{\texttwooldstyle} \UnicodeEncodingName{\oldstylenums{2}}
343 \DeclareTextCommand{\textthreeoldstyle} \UnicodeEncodingName{\oldstylenums{3}}
344 \DeclareTextCommand{\textfouroldstyle} \UnicodeEncodingName{\oldstylenums{4}}
345 \DeclareTextCommand{\textfiveoldstyle} \UnicodeEncodingName{\oldstylenums{5}}
346 \DeclareTextCommand{\textsixoldstyle} \UnicodeEncodingName{\oldstylenums{6}}
347 \DeclareTextCommand{\textsevenoldstyle} \UnicodeEncodingName{\oldstylenums{7}}
348 \DeclareTextCommand{\texteightoldstyle} \UnicodeEncodingName{\oldstylenums{8}}
349 \DeclareTextCommand{\textnineoldstyle} \UnicodeEncodingName{\oldstylenums{9}}
```

These have Unicode slots so this should be integrated into TU explicitly

```
350 \DeclareTextSymbol{\textpilcrow} \UnicodeEncodingName{"00B6}
351 \DeclareTextSymbol{\textborn} \UnicodeEncodingName{"002A}
352 \DeclareTextSymbol{\textdied} \UnicodeEncodingName{"2020}
353 \DeclareTextSymbol{\textlbrackdbl} \UnicodeEncodingName{"27E6}
354 \DeclareTextSymbol{\textrbrackdbl} \UnicodeEncodingName{"27E7}
355 \DeclareTextSymbol{\textguarani} \UnicodeEncodingName{"20B2}
```

We could make `\textcentoldstyle` and `\textdollaroldstyle` point to dollar and cent in the Unicode encoding

```
356 %\DeclareTextSymbol{\textcentoldstyle} \UnicodeEncodingName{"00A2}
357 %\DeclareTextSymbol{\textdollaroldstyle}\UnicodeEncodingName{"0024}
```

but I think it is better to pick them up from TS1 even if that usually means LMR fonts

```
358 \DeclareTextSymbol{\textdollaroldstyle}{TS1}{138}
359 \DeclareTextSymbol{\textcentoldstyle} {TS1}{139}

360 \fi % --- END of Unicode engines specials
```

### 3 Font family sub-encodings setup

We declare the subsets for a good number of fonts in the kernel ...

But first the default for anything that is not declared. We use 9 which is most likely much too conservative, but with the advantage that we aren't getting missing glyphs (or at least that this is very unlikely). For nearly all font in the T<sub>E</sub>X Live distribution of 2019 “correct” classifications are given below, so that this default is only used for new font families, and over time the right classifications can be added here too.

```
361 \DeclareEncodingSubset{TS1}{?}{9}
```

This first block contains the fonts that have been already supported by the `textcomp` package way back, i.e., the font families that have T<sub>E</sub>X support since the mid-nineties.

```
362 \DeclareEncodingSubset{TS1}{ccr} {0}
363 \DeclareEncodingSubset{TS1}{cmbr} {0}
```

The following 4 declarations are now part of the corresponding `.fd` file, hopefully other will follow so that this list of declarations can eventually be removed from the kernel (where it doesn't belong).

```
364 %\DeclareEncodingSubset{TS1}{cmr} {0}
365 %\DeclareEncodingSubset{TS1}{cmss} {0}
366 %\DeclareEncodingSubset{TS1}{cmtt} {0}
367 %\DeclareEncodingSubset{TS1}{cmvtt} {0}

368 \DeclareEncodingSubset{TS1}{cmtl} {0}
369 \DeclareEncodingSubset{TS1}{pxr} {0}
370 \DeclareEncodingSubset{TS1}{pxss} {0}
371 \DeclareEncodingSubset{TS1}{pxtt} {0}
372 \DeclareEncodingSubset{TS1}{qag} {0}
373 \DeclareEncodingSubset{TS1}{qbk} {0}
374 \DeclareEncodingSubset{TS1}{qcr} {0}
375 \DeclareEncodingSubset{TS1}{qcs} {0}
376 \DeclareEncodingSubset{TS1}{qhvc} {0}
377 \DeclareEncodingSubset{TS1}{qhv} {0}
378 \DeclareEncodingSubset{TS1}{qpl} {0}
379 \DeclareEncodingSubset{TS1}{qtm} {0}
380 \DeclareEncodingSubset{TS1}{qzc} {0}
381 \DeclareEncodingSubset{TS1}{txr} {0}
382 \DeclareEncodingSubset{TS1}{txss} {0}
383 \DeclareEncodingSubset{TS1}{txtt} {0}

384 \DeclareEncodingSubset{TS1}{lmr} {1}
385 \DeclareEncodingSubset{TS1}{lmdh} {1}
386 \DeclareEncodingSubset{TS1}{lmss} {1}
387 \DeclareEncodingSubset{TS1}{lmssq} {1}
```

```
388 \DeclareEncodingSubset{TS1}{lmvtt} {1}
```

The lmtt family is missing TM, SM, and perthousand for some reason, so the first safe sub-encoding would be 2, but that is then missing out a huge number of glyphs that are available, so we claim it is sub-encoding 1 even if this can lead to missing glyphs.

```
389 \DeclareEncodingSubset{TS1}{lmtt} {1} % missing TM, SM and pertenthousand
```

The next three families have been removed from TeX Live, but we keep the definitions

```
390 \DeclareEncodingSubset{TS1}{ptmx} {2}
```

```
391 \DeclareEncodingSubset{TS1}{ptmj} {2}
```

```
392 \DeclareEncodingSubset{TS1}{ul8} {2}
```

The next set are the early PostScript font implementations, these days there are better alternatives, but .... Note that, their virtual fonts contain a lot of “tofu” in form of black squares, thus they don’t even give a missing character warning if you select such a glyph. This is why they are set as sub-encoding 5.

```
393 \DeclareEncodingSubset{TS1}{bch} {5} % tofu for blank, ohm
```

```
394 \DeclareEncodingSubset{TS1}{futj} {5} % tofu for blank, interrobang/down, ohm
```

```
395 \DeclareEncodingSubset{TS1}{futs} {5} % tofu for blank, ohm
```

```
396 \DeclareEncodingSubset{TS1}{futx} {5} % probably (currently broken distrib)
```

```
397 \DeclareEncodingSubset{TS1}{pag} {5} % tofu for blank, interrobang/down, ohm
```

```
398 \DeclareEncodingSubset{TS1}{pbk} {5} % tofu for blank, interrobang/down, ohm
```

```
399 \DeclareEncodingSubset{TS1}{pcr} {5} % tofu for blank, interrobang/down, ohm
```

```
400 \DeclareEncodingSubset{TS1}{phv} {5} % tofu for blank, interrobang/down, ohm
```

```
401 \DeclareEncodingSubset{TS1}{pnc} {5} % tofu for blank, interrobang/down, ohm
```

```
402 \DeclareEncodingSubset{TS1}{pplj} {5} % tofu for blank
```

```
403 \DeclareEncodingSubset{TS1}{pplx} {5} % tofu for blank
```

```
404 \DeclareEncodingSubset{TS1}{ppl} {5} % tofu for blank interrobang/down
```

```
405 \DeclareEncodingSubset{TS1}{ptm} {5} % tofu for blank, interrobang/down, ohm
```

```
406 \DeclareEncodingSubset{TS1}{pzc} {5} % tofu for blank, interrobang/down, ohm
```

```
407 \DeclareEncodingSubset{TS1}{ul9} {5} % tofu for blank, interrobang/down, ohm
```

The next set suffers from the same problem and they contain even fewer real glyphs.

```
408 \DeclareEncodingSubset{TS1}{dayroms} {6} % tofu for blank, interrobang/down, ohm
```

```
409 \DeclareEncodingSubset{TS1}{dayrom} {6} % tofu for blank, interrobang/down, ohm
```

```
410 \DeclareEncodingSubset{TS1}{augie} {8} % really only missing euro
```

```
411 \DeclareEncodingSubset{TS1}{put} {8}
```

```
412 \DeclareEncodingSubset{TS1}{uag} {8} % probably (currently broken distrib)
```

```
413 \DeclareEncodingSubset{TS1}{ugq} {8}
```

```
414 \DeclareEncodingSubset{TS1}{zi4} {9}
```

LucidaBright (sold through TUG) probably not quite correct, I guess as I have the older fonts ...

```
415 \DeclareEncodingSubset{TS1}{hls} {5}
```

```
416 \DeclareEncodingSubset{TS1}{hlst} {5}
```

```
417 \DeclareEncodingSubset{TS1}{hlct} {5}
```

```
418 \DeclareEncodingSubset{TS1}{hlh} {5}
```

```
419 \DeclareEncodingSubset{TS1}{hlx} {8}
```

```
420 \DeclareEncodingSubset{TS1}{hlce} {8}
```

```
421 \DeclareEncodingSubset{TS1}{hlcn} {8}
```

```
422 \DeclareEncodingSubset{TS1}{hlcw} {8}
```

```
423 \DeclareEncodingSubset{TS1}{hlcf} {8}
```

Below are the newer fonts that have support files for L<sup>A</sup>T<sub>E</sub>X. With very few exceptions the classifications are done so that all characters are correctly produced (either being available in the font or substituted).

There are a few fonts that contain “tofu” squares in places (instead of a real glyph) and in a few cases some really seldom needed chars are unavailable, i.e., produce missing glyphs (to avoid that a large number of available chars are unnecessarily substituted).

Encoding declarations for these font families shouldn’t really be in the kernel, but part of the .fd files for the family. When we introduced the concept in 2021 we had some hope that this would happen over time and that we could take the declarations out—after all it is nearly impossible to maintain it correctly in the kernel, given that fonts may get new glyphs added (happened for several of them in the recent year) which is something we wouldn’t notice. However, so far this hasn’t happened, so in 2024, I went through the current set and adjusted the declarations in several places.

Next four are wrong and still need adjustment:

```

424 \DeclareEncodingSubset{TS1}{lato-*}      {0} % with a bunch of tofu inside
425 \DeclareEncodingSubset{TS1}{opensans-*}  {0} % with a bunch of tofu inside
426 \DeclareEncodingSubset{TS1}{cantarell-*} {0} % with a bunch of tofu inside
427 \DeclareEncodingSubset{TS1}{tli}         {1} % with lots of tofu inside
428 \DeclareEncodingSubset{TS1}{fbb-*}       {2} % missing centoldstyle

429 \DeclareEncodingSubset{TS1}{Alegreya-*}  {2}
430 \DeclareEncodingSubset{TS1}{AlegreyaSans-*} {2}
431 \DeclareEncodingSubset{TS1}{BaskervilleF-*} {2}
432 \DeclareEncodingSubset{TS1}{DejaVuSans-TLF} {2}
433 \DeclareEncodingSubset{TS1}{DejaVuSansCondensed-TLF} {2}

```

Next one is missing \textfractionsolidus but is otherwise completely sub-encoding 2 so we use that sub-encoding.

```

434 \DeclareEncodingSubset{TS1}{DejaVuSansMono-TLF} {2}

435 \DeclareEncodingSubset{TS1}{EBGaramond-*} {2}
436 \DeclareEncodingSubset{TS1}{Merriwthr-OsF} {2}
437 \DeclareEncodingSubset{TS1}{MerriwthrSans-OsF} {2}
438 \DeclareEncodingSubset{TS1}{Montserrat-*} {2}
439 \DeclareEncodingSubset{TS1}{MontserratAlternates-*} {2}
440 \DeclareEncodingSubset{TS1}{NotoSansMono-TLF} {2}
441 \DeclareEncodingSubset{TS1}{NotoSansMono-TOsF} {2}
442 \DeclareEncodingSubset{TS1}{Tempora-TLF} {2}
443 \DeclareEncodingSubset{TS1}{Tempora-TOsF} {2}
444 \DeclareEncodingSubset{TS1}{XCharter-TLF} {2}
445 \DeclareEncodingSubset{TS1}{XCharter-TOsF} {2}
446 \DeclareEncodingSubset{TS1}{erewhon-*} {2}

447 \DeclareEncodingSubset{TS1}{Arimo-TLF} {3}
448 \DeclareEncodingSubset{TS1}{Crlt-*} {3}
449 \DeclareEncodingSubset{TS1}{IBMPlexMono-TLF} {3}
450 \DeclareEncodingSubset{TS1}{IBMPlexSans-TLF} {3}
451 \DeclareEncodingSubset{TS1}{IBMPlexSerif-TLF} {3}
452 \DeclareEncodingSubset{TS1}{SourceCodePro-TLF} {3}
453 \DeclareEncodingSubset{TS1}{SourceCodePro-TOsF} {3}
454 \DeclareEncodingSubset{TS1}{SourceSansPro-*} {3}
455 \DeclareEncodingSubset{TS1}{SourceSerifPro-*} {3}
456 \DeclareEncodingSubset{TS1}{Tinos-TLF} {3}

```

```

457 \DeclareEncodingSubset{TS1}{AccanthisADFStdNoThree-LF}{4}
458 \DeclareEncodingSubset{TS1}{Cabin-TLF} {4}
459 \DeclareEncodingSubset{TS1}{Caladea-TLF} {4}
460 \DeclareEncodingSubset{TS1}{Chivo-*} {4}
461 \DeclareEncodingSubset{TS1}{ClearSans-TLF} {4}
462 \DeclareEncodingSubset{TS1}{Coelacanth-LF} {4}
463 \DeclareEncodingSubset{TS1}{CrimsonPro-*} {4}
464 \DeclareEncodingSubset{TS1}{FiraMono-TLF} {4}
465 \DeclareEncodingSubset{TS1}{FiraMono-TOf} {4}
466 \DeclareEncodingSubset{TS1}{FiraSans-*} {4}
467 \DeclareEncodingSubset{TS1}{Go-TLF} {4}
468 \DeclareEncodingSubset{TS1}{GoMono-TLF} {4}
469 \DeclareEncodingSubset{TS1}{InriaSans-*} {4}
470 \DeclareEncodingSubset{TS1}{InriaSerif-*} {4}
471 \DeclareEncodingSubset{TS1}{LibertinusSans-*} {4}
472 \DeclareEncodingSubset{TS1}{LibertinusSerif-*} {4}
473 \DeclareEncodingSubset{TS1}{LibreBodoni-TLF} {4}
474 \DeclareEncodingSubset{TS1}{LibreFranklin-TLF} {4}
475 \DeclareEncodingSubset{TS1}{LinguisticsPro-LF} {4}
476 \DeclareEncodingSubset{TS1}{LinguisticsPro-Of} {4}
477 \DeclareEncodingSubset{TS1}{LinuxBiolumT-*} {4}
478 \DeclareEncodingSubset{TS1}{LinuxLibertineT-*} {4}
479 \DeclareEncodingSubset{TS1}{MintSpirit-*} {4}
480 \DeclareEncodingSubset{TS1}{MintSpiritNoTwo-*} {4}
481 \DeclareEncodingSubset{TS1}{PTMono-TLF} {4}
482 \DeclareEncodingSubset{TS1}{PTSans-TLF} {4}
483 \DeclareEncodingSubset{TS1}{PTSansCaption-TLF} {4}
484 \DeclareEncodingSubset{TS1}{PTSansNarrow-TLF} {4}
485 \DeclareEncodingSubset{TS1}{PTSerif-TLF} {4}
486 \DeclareEncodingSubset{TS1}{PTSerifCaption-TLF} {4}
487 \DeclareEncodingSubset{TS1}{Raleway-TLF} {4}
488 \DeclareEncodingSubset{TS1}{Raleway-TOf} {4}
489 \DeclareEncodingSubset{TS1}{Roboto-*} {4}
490 \DeclareEncodingSubset{TS1}{RobotoMono-TLF} {4}
491 \DeclareEncodingSubset{TS1}{RobotoSlab-TLF} {4}
492 \DeclareEncodingSubset{TS1}{Rosario-*} {4}
493 \DeclareEncodingSubset{TS1}{SticksTooText-*} {4}
494 \DeclareEncodingSubset{TS1}{UniversalisADFStd-LF} {4}

495 \DeclareEncodingSubset{TS1}{Almndr-Of} {5}
496 \DeclareEncodingSubset{TS1}{Baskervalex-*} {5}
497 \DeclareEncodingSubset{TS1}{Bttr-TLF} {5}
498 \DeclareEncodingSubset{TS1}{Cinzel-LF} {5}
499 \DeclareEncodingSubset{TS1}{CinzelDecorative-LF} {5}
500 \DeclareEncodingSubset{TS1}{Cochineal-*} {5}
501 \DeclareEncodingSubset{TS1}{DejaVuSerif-TLF} {5}
502 \DeclareEncodingSubset{TS1}{DejaVuSerifCondensed-TLF} {5}
503 \DeclareEncodingSubset{TS1}{GilliusADF-LF} {5}
504 \DeclareEncodingSubset{TS1}{GilliusADFCond-LF} {5}
505 \DeclareEncodingSubset{TS1}{GilliusADFNoTwo-LF} {5}
506 \DeclareEncodingSubset{TS1}{GilliusADFNoTwoCond-LF} {5}
507 \DeclareEncodingSubset{TS1}{OldStandard-TLF} {5}
508 \DeclareEncodingSubset{TS1}{PlyfrDisplay-TLF} {5}
509 \DeclareEncodingSubset{TS1}{PlyfrDisplay-TOf} {5}
510 \DeclareEncodingSubset{TS1}{TheanoDidot-TLF} {5}

```

```

511 \DeclareEncodingSubset{TS1}{TheanoDidot-T0sF}      {5}
512 \DeclareEncodingSubset{TS1}{TheanoModern-TLF}      {5}
513 \DeclareEncodingSubset{TS1}{TheanoModern-T0sF}     {5}
514 \DeclareEncodingSubset{TS1}{TheanoOldStyle-TLF}    {5}
515 \DeclareEncodingSubset{TS1}{TheanoOldStyle-T0sF}   {5}
516 \DeclareEncodingSubset{TS1}{charssil-TLF}          {5}

517 \DeclareEncodingSubset{TS1}{Crimson-TLF}           {6}
518 \DeclareEncodingSubset{TS1}{LibertinusSerifDisplay-LF} {6}
519 \DeclareEncodingSubset{TS1}{LinuxLibertineDisplayT-*} {6}
520 \DeclareEncodingSubset{TS1}{LinuxLibertineMonoT-LF} {6}
521 \DeclareEncodingSubset{TS1}{LinuxLibertineMonoT-TLF} {6}
522 \DeclareEncodingSubset{TS1}{Ovr1ck-LF}             {6}

523 \DeclareEncodingSubset{TS1}{ComicNeue-TLF}         {7}
524 \DeclareEncodingSubset{TS1}{ComicNeueAngular-TLF}  {7}
525 \DeclareEncodingSubset{TS1}{CormorantGaramond-*}   {7}
526 \DeclareEncodingSubset{TS1}{Heuristica-TLF}        {7}
527 \DeclareEncodingSubset{TS1}{Heuristica-T0sF}       {7}
528 \DeclareEncodingSubset{TS1}{IMFELLEnglish-TLF}    {7}
529 \DeclareEncodingSubset{TS1}{LibreBskrvl-TLF}       {7}
530 \DeclareEncodingSubset{TS1}{LibreCsln-*}           {7}
531 \DeclareEncodingSubset{TS1}{Lbstr-LF}               {7}
532 \DeclareEncodingSubset{TS1}{Mrcls-LF}              {7}

```

Strangely enough NotoSerif and NotoSans are sub-encoding 7 as they are missing `\textminus` and several other glyphs. In contrast, the NotoSansMono is far more complete.

```

533 \DeclareEncodingSubset{TS1}{NotoSans-*}            {7}
534 \DeclareEncodingSubset{TS1}{NotoSerif-*}           {7}
535 \DeclareEncodingSubset{TS1}{Quattro-LF}            {7}
536 \DeclareEncodingSubset{TS1}{QuattroSans-LF}        {7}
537 \DeclareEncodingSubset{TS1}{Frm-LF}                {7} % the superiors are missing

538 \DeclareEncodingSubset{TS1}{LibertinusMono-TLF}    {8}
539 \DeclareEncodingSubset{TS1}{AlgolRevived-TLF}      {9}

```

## 4 Legacy symbol support for lists and footnote symbols

`\UseLegacyTextSymbols`

```

540 \def\UseLegacyTextSymbols{%
541   \DeclareTextSymbolDefault{\textasteriskcentered}{OMS}%
542   \DeclareTextSymbolDefault{\textbardbl}{OMS}%
543   \DeclareTextSymbolDefault{\textbullet}{OMS}%
544   \DeclareTextSymbolDefault{\textdaggerdbl}{OMS}%
545   \DeclareTextSymbolDefault{\textdagger}{OMS}%
546   \DeclareTextSymbolDefault{\textparagraph}{OMS}%
547   \DeclareTextSymbolDefault{\textperiodcentered}{OMS}%
548   \DeclareTextSymbolDefault{\textsection}{OMS}%
549   \UndeclareTextCommand{\textsection}{T1}%
550   \expandafter\let\csname oldstylenums \expandafter\endcsname
551     \csname legacyoldstylenums \endcsname
552 }

```

(End of definition for \UseLegacyTextSymbols.)

\textlegacyasteriskcentered Here are new names for the legacy symbols that L<sup>A</sup>T<sub>E</sub>X used to pick up from the OMS encoded fonts (and used for itemize lists or footnote symbols).

\textlegacybardbl We go the roundabout way via separate OMS declarations so that

\textlegacybullet \renewcommand\textbullet{\textlegacybullet}

\textlegacydaggerdbl doesn't produce an endless loop.

\textlegacydagger \textlegacyparagraph  
\textlegacyperiodcentered  
\textlegacysection

```

553 \DeclareTextSymbol{\textlegacyasteriskcentered}{OMS}{3} % "03
554 \DeclareTextSymbol{\textlegacybardbl}{OMS}{107} % "6B
555 \DeclareTextSymbol{\textlegacybullet}{OMS}{15} % "0F
556 \DeclareTextSymbol{\textlegacydaggerdbl}{OMS}{122} % "7A
557 \DeclareTextSymbol{\textlegacydagger}{OMS}{121} % "79
558 \DeclareTextSymbol{\textlegacyparagraph}{OMS}{123} % "7B
559 \DeclareTextSymbol{\textlegacyperiodcentered}{OMS}{1} % "01
560 \DeclareTextSymbol{\textlegacysection}{OMS}{120} % "78

561 \DeclareTextSymbolDefault{\textlegacyasteriskcentered}{OMS}
562 \DeclareTextSymbolDefault{\textlegacybardbl}{OMS}
563 \DeclareTextSymbolDefault{\textlegacybullet}{OMS}
564 \DeclareTextSymbolDefault{\textlegacydaggerdbl}{OMS}
565 \DeclareTextSymbolDefault{\textlegacydagger}{OMS}
566 \DeclareTextSymbolDefault{\textlegacyparagraph}{OMS}
567 \DeclareTextSymbolDefault{\textlegacyperiodcentered}{OMS}
568 \DeclareTextSymbolDefault{\textlegacysection}{OMS}

```

(End of definition for \textlegacyasteriskcentered and others.)

Supporting rollback ...

```

569 </2ekernel | latexrelease>
570 <latexrelease>
571 <latexrelease>\IncludeInRelease{0000/00/00}%
572 <latexrelease>    {ltxtextcomp}{\Undefine text companion symbols}%
573 <latexrelease>
574 <latexrelease>\DeclareRobustCommand\oldstylenums[1]{%
575 <latexrelease>    \begingroup
576 <latexrelease>    \spaceskip\fontdimen\tw@font
577 <latexrelease>    \usefont{OML}{\rmdefault}{\f@series}{it}%
578 <latexrelease>    \mathgroup\symletters #1%
579 <latexrelease>    \endgroup
580 <latexrelease>}
581 <latexrelease>\let\legacyoldstylenums\@undefined
582 <latexrelease>\def\textcompsubstdefault{cmr}
583 <latexrelease>
584 <latexrelease>\let\DeclareEncodingSubset\@undefined
585 <latexrelease>\let\CheckEncodingSubset\@undefined
586 <latexrelease>
587 <latexrelease>\DeclareTextSymbolDefault{\textdollar}{OT1}
588 <latexrelease>\DeclareTextSymbolDefault{\textsterling}{OT1}
589 <latexrelease>\DeclareTextCommand{\textdollar}{OT1}{\hmode\bgroup
590 <latexrelease>    \ifdim \fontdimen\@ne\font >\z@
591 <latexrelease>        \slshape
592 <latexrelease>    \else
593 <latexrelease>        \upshape
594 <latexrelease>    \fi

```

```

595 <latexrelease> \char'{$\egroup}
596 <latexrelease>\DeclareTextCommand{\textsterling}{OT1}{\hmode@bgroup
597 <latexrelease> \ifdim \fontdimen\@ne\font >\z@
598 <latexrelease> \itshape
599 <latexrelease> \else
600 <latexrelease> \fontshape{ui}\selectfont
601 <latexrelease> \fi
602 <latexrelease> \char'{$\egroup}
603 <latexrelease>\DeclareTextCommand{\textperthousand}{T1}
604 <latexrelease> {\%\char 24 }
605 <latexrelease>
606 <latexrelease>\DeclareTextSymbolDefault{\textasteriskcentered}{OMS}
607 <latexrelease>\DeclareTextSymbolDefault{\textbullet}{OMS}
608 <latexrelease>\DeclareTextSymbolDefault{\textdaggerdbl}{OMS}
609 <latexrelease>\DeclareTextSymbolDefault{\textdagger}{OMS}
610 <latexrelease>\DeclareTextSymbolDefault{\textparagraph}{OMS}
611 <latexrelease>\DeclareTextSymbolDefault{\textperiodcentered}{OMS}
612 <latexrelease>\DeclareTextSymbolDefault{\textsection}{OMS}
613 <latexrelease>
614 <latexrelease>\DeclareTextSymbolDefault{\textbardbl}{OMS}
615 <latexrelease>\let\textbrokenbar\@undefined
616 <latexrelease>\let\textcelsius\@undefined
617 <latexrelease>\let\textcent\@undefined
618 <latexrelease>\DeclareTextCommandDefault{\textcopyright}
619 <latexrelease> {\textcircled{c}}
620 <latexrelease>\let\textdegree\@undefined
621 <latexrelease>\let\textdiv\@undefined
622 <latexrelease>\let\textlnot\@undefined
623 <latexrelease>\let\textonehalf\@undefined
624 <latexrelease>\let\textonequarter\@undefined
625 <latexrelease>\let\textonesuperior\@undefined
626 <latexrelease>\DeclareTextCommandDefault{\textordfeminine}
627 <latexrelease> {\textsuperscript{a}}
628 <latexrelease>\DeclareTextCommandDefault{\textordmasculine}
629 <latexrelease> {\textsuperscript{o}}
630 <latexrelease>\let\textpm\@undefined
631 <latexrelease>\let\textquotesingle\@undefined
632 <latexrelease>\let\textquotestraightbase\@undefined
633 <latexrelease>\let\textquotestraightdblbase\@undefined
634 <latexrelease>\DeclareTextCommandDefault{\textregistered}
635 <latexrelease> {\textcircled{%
636 <latexrelease> \check@mathfonts\fontsize\sf@size\z@
637 <latexrelease> \math@fontsfalse\selectfont R}}
638 <latexrelease>\let\textthreequartersemdash\@undefined
639 <latexrelease>\let\textthreequarters\@undefined
640 <latexrelease>\let\textthreesuperior\@undefined
641 <latexrelease>\let\texttimes\@undefined
642 <latexrelease>\DeclareTextCommandDefault{\texttrademark}
643 <latexrelease> {\textsuperscript{TM}}
644 <latexrelease>\let\texttwelveudash\@undefined
645 <latexrelease>\let\texttwosuperior\@undefined
646 <latexrelease>\let\textyen\@undefined
647 <latexrelease>
648 <latexrelease>\let\textcapitalcompwordmark\@undefined

```

```

649 <latexrelease>\let\textascendercompwordmark\@undefined
650 <latexrelease>
651 <latexrelease>\DeclareTextAccentDefault{\textcircled}{OMS}
652 <latexrelease>\DeclareTextAccentDefault{\t}{OML}
653 <latexrelease>
654 <latexrelease>\let\capitalacute\@undefined
655 <latexrelease>\let\capitalbreve\@undefined
656 <latexrelease>\let\capitalcaron\@undefined
657 <latexrelease>\let\capitalcedilla\@undefined
658 <latexrelease>\let\capitalcircumflex\@undefined
659 <latexrelease>\let\capitaldieresis\@undefined
660 <latexrelease>\let\capitaldotaccent\@undefined
661 <latexrelease>\let\capitalgrave\@undefined
662 <latexrelease>\let\capitalhungarumlaut\@undefined
663 <latexrelease>\let\capitalmacron\@undefined
664 <latexrelease>\let\capitalnewtie\@undefined
665 <latexrelease>\let\capitalogonek\@undefined
666 <latexrelease>\let\capitalring\@undefined
667 <latexrelease>\let\capitaltie\@undefined
668 <latexrelease>\let\capitaltilde\@undefined
669 <latexrelease>\let\newtie\@undefined
670 <latexrelease>
671 <latexrelease>\let\textlbrackdbl\@undefined
672 <latexrelease>\let\textrrackdbl\@undefined
673 <latexrelease>
674 <latexrelease>\let\texteightoldstyle\@undefined
675 <latexrelease>\let\textfiveoldstyle\@undefined
676 <latexrelease>\let\textfouroldstyle\@undefined
677 <latexrelease>\let\textnineoldstyle\@undefined
678 <latexrelease>\let\textoneoldstyle\@undefined
679 <latexrelease>\let\textsevenoldstyle\@undefined
680 <latexrelease>\let\textsixoldstyle\@undefined
681 <latexrelease>\let\textthreeoldstyle\@undefined
682 <latexrelease>\let\texttwooldstyle\@undefined
683 <latexrelease>\let\textzerooldstyle\@undefined
684 <latexrelease>
685 <latexrelease>\let\textacutedbl\@undefined
686 <latexrelease>\let\textasciicute\@undefined
687 <latexrelease>\let\textasciibreve\@undefined
688 <latexrelease>\let\textasciicaron\@undefined
689 <latexrelease>\let\textasciidieresis\@undefined
690 <latexrelease>\let\textasciigrave\@undefined
691 <latexrelease>\let\textasciimacron\@undefined
692 <latexrelease>\let\textgravedbl\@undefined
693 <latexrelease>\let\texttildelow\@undefined
694 <latexrelease>
695 <latexrelease>\let\textbaht\@undefined
696 <latexrelease>\let\textbigcircle\@undefined
697 <latexrelease>\let\textborn\@undefined
698 <latexrelease>\let\textcentoldstyle\@undefined
699 <latexrelease>\let\textcircledP\@undefined
700 <latexrelease>\let\textcopyleft\@undefined
701 <latexrelease>\let\textdblhyphenchar\@undefined
702 <latexrelease>\let\textdblhyphen\@undefined

```

```

703 <latexrelease>\let\textdied\@undefined
704 <latexrelease>\let\textdiscount\@undefined
705 <latexrelease>\let\textdivorced\@undefined
706 <latexrelease>\let\textdollaroldstyle\@undefined
707 <latexrelease>\let\textguarani\@undefined
708 <latexrelease>\let\textleaf\@undefined
709 <latexrelease>\let\textlquill\@undefined
710 <latexrelease>\let\textmarried\@undefined
711 <latexrelease>\let\textmho\@undefined
712 <latexrelease>\let\textmusicalnote\@undefined
713 <latexrelease>\let\textnaira\@undefined
714 <latexrelease>\let\textopenbullet\@undefined
715 <latexrelease>\let\textpeso\@undefined
716 <latexrelease>\let\textpilcrow\@undefined
717 <latexrelease>\let\textrecipe\@undefined
718 <latexrelease>\let\textreferencemark\@undefined
719 <latexrelease>\let\textarquill\@undefined
720 <latexrelease>\let\textservicemark\@undefined
721 <latexrelease>\let\textsurd\@undefined
722 <latexrelease>
723 <latexrelease>\DeclareTextCommand{\textpertenthousand}{T1}
724 <latexrelease>                {\%\char 24\char 24 }
725 <latexrelease>
726 <latexrelease>\let\textlangle\@undefined
727 <latexrelease>\let\extrangle\@undefined
728 <latexrelease>
729 <latexrelease>\let\textcolonmonetary\@undefined
730 <latexrelease>\let\textdong\@undefined
731 <latexrelease>\let\textdownarrow\@undefined
732 <latexrelease>\let\textleftarrow\@undefined
733 <latexrelease>\let\textlira\@undefined
734 <latexrelease>\let\textrightarrow\@undefined
735 <latexrelease>\let\textuparrow\@undefined
736 <latexrelease>\let\textwon\@undefined
737 <latexrelease>
738 <latexrelease>\let\textestimated\@undefined
739 <latexrelease>\let\textnumero\@undefined
740 <latexrelease>
741 <latexrelease>\let\textflorin\@undefined
742 <latexrelease>\let\textcurrency\@undefined
743 <latexrelease>
744 <latexrelease>\let\textfractionsolidus\@undefined
745 <latexrelease>\let\textohm\@undefined
746 <latexrelease>\let\textmu\@undefined
747 <latexrelease>\let\textminus\@undefined
748 <latexrelease>
749 <latexrelease>\let\textblank\@undefined
750 <latexrelease>\let\textinterrobangdown\@undefined
751 <latexrelease>\let\textinterrobang\@undefined
752 <latexrelease>
753 <latexrelease>\let\texteuro\@undefined
754 <latexrelease>
755 <latexrelease>\let\textcelsius\@undefined
756 <latexrelease>\let\tonesuperior\@undefined

```

```

757 \let\textthreequartersemdash\@undefined
758 \let\textthreesuperior\@undefined
759 \let\texttwelveudash\@undefined
760 \let\texttwosuperior\@undefined
761 \let\textbardbl\@undefined
762 \let\@undefined\@undefined
763 \let\UseLegacyTextSymbols\@undefined
764 \let\textlegacyasteriskcentered\@undefined
765 \let\textlegacybardbl\@undefined
766 \let\textlegacybullet\@undefined
767 \let\textlegacydaggerdbl\@undefined
768 \let\textlegacydagger\@undefined
769 \let\textlegacyparagraph\@undefined
770 \let\textlegacyperiodcentered\@undefined
771 \let\textlegacysection\@undefined
772 \let\@undefined\@undefined
773 \EndModuleRelease

```

## 5 The textcomp package

For any rollback request before 2018-08-11 we make an attempt by loading the 2018 version.

```

774 \*TS1sty
775 \DeclareRelease{1997-12-01}{textcomp-2018-08-11.sty}
776 \DeclareRelease{2018-08-11}{textcomp-2018-08-11.sty}
777 \DeclareCurrentRelease{2020-02-02}
778
779 \ProvidesPackage{textcomp}
780 [2024/04/24 v2.1b Standard LaTeX package]

```

A precaution in case this is used without rebuilding the format.

```

781 \NeedsTeXFormat{LaTeX2e}[2020/02/02]

```

This is implemented by defining the default subset:

```

782 \DeclareOption{full}{\DeclareEncodingSubset{TS1}{?}{0}}
783 \DeclareOption{almostfull}{\DeclareEncodingSubset{TS1}{?}{1}}
784 \DeclareOption{euro}{\DeclareEncodingSubset{TS1}{?}{8}}
785 \DeclareOption{safe}{\DeclareEncodingSubset{TS1}{?}{9}}

```

The default is set up in the kernel is “safe” these days for unknown fonts but LaTeX has definitions for most families so it seldom applies.

If a different default is used then one needs to check the results to ensure that there aren’t “missing glyphs”.

The next set of options define the warning level (default in the kernel is info only). Using the package options you can change this behavior.

```

786 \DeclareOption{error}
787 {\gdef\tc@errorwarn{\PackageError{textcomp}}}
788 \DeclareOption{warn}
789 {\gdef\tc@errorwarn#1#2{\PackageWarning{textcomp}{#1}}}
790 \DeclareOption{info}
791 {\gdef\tc@errorwarn#1#2{\PackageInfo{textcomp}{#1}}}
792 \DeclareOption{quiet}{\gdef\tc@errorwarn#1#2{}}

```

The “force” option basically changes the sub-encoding to that of the default (which, unless changes, is 9 these days), i.e., it no longer depends on the font in use. This is mainly there because it might have been used in older documents, but not something that is recommended.

```

793 \DeclareOption{force}{%
794   \def\CheckEncodingSubset#1#2#3#4#5{%
795     \ifnum #4>%
796       0\csname #2:?\endcsname
797       \relax
798     \expandafter\@firstoftwo
799   \else
800     \expandafter\@secondoftwo
801   \fi
802   {#1{#2}}{#3}%
803   #5}%
804 }

805 \ProcessOptions\relax

```

There is not much else to do nowadays, because everything is already set up in the L<sup>A</sup>T<sub>E</sub>X kernel.

```

806 \InputIfFileExists{textcomp.cfg}
807 {\PackageInfo{textcomp}{Local configuration file used}}{}
808 </TS1sty>

```

## 5.1 The old textcomp package code

This section contains the old code for the textcomp package and its documentation. It is only used if we roll back prior to 2020. Thus all the rest is mainly for historians. Note that the old code categorized in the sub-encodings only into 6 classes not 10.

```

809 <*TS1oldsty>
810 \ProvidesPackage{textcomp}
811 [2018/08/11 v2.0j Standard LaTeX package]

```

This one is for the TS1 encoding which contains text symbols for use with the T1-encoded text fonts. It therefore first inputs the file `TS1enc.def` and then sets (or resets) the defaults for the symbols it contains. The result of this is that when one of these symbols is accessed and the current encoding does not provide it, the symbol will be supplied by a silent, local change to this encoding.

Since many PostScript fonts only implement a subset of TS1 many commands only produce black blobs of ink. To resolve the resulting problems a number of options have been introduced and some code has been developed to distinguish sub-encodings.

The sub-encodings have a numerical id and are defined as follows for TS1:

**#5** those TS1 symbols that are also in the ISO-Adobe character set; without `textcurrency`, which is often misused for the Euro. Older Type1 fonts from the non-T<sub>E</sub>X world provide only this subset.

**#4** = #5 + `\texteuro`. Most newer fonts provide this.

**#3** = #4 + `\textomega`. Can also be described as  $TS1 \cap (ISO-Adobe \cup MacRoman)$ . (Except for the missing “currency”.)

**#2** = **#3** + `\textestimated` + `\textcurrency`. Can also be described as `TS1`  $\cap$  Adobe-Western-2. This may be relevant for OpenType fonts, which usually show the Adobe-Western-2 character set.

**#1** = `TS1` without `\textcircled` and `\t`. These two glyphs are often not implemented and if their kernel defaults are changed commands like `\copyright` unnecessarily fail.

**#0** = full `TS1`

And here a summary to go in the transcript file:

```

812 \PackageInfo{textcomp}{Sub-encoding information:\MessageBreak
813   \space\space 5 = only ISO-Adobe without
814                     \string\textcurrency\MessageBreak
815   \space\space 4 = 5 + \string\texteuro\MessageBreak
816   \space\space 3 = 4 + \string\textohm\MessageBreak
817   \space\space 2 = 3 + \noexpand\textestimated+
818                     \string\textcurrency\MessageBreak
819   \space\space 1 = TS1 - \noexpand\textcircled-
820                     \string\t\MessageBreak
821   \space\space 0 = TS1 (full)\MessageBreak
822   Font families with sub-encoding setting implement\MessageBreak
823   only a restricted character set as indicated.\MessageBreak
824   Family '?' is the default used for unknown fonts.\MessageBreak
825   See the documentation for details\@gobble}

```

`\DeclareEncodingSubset` An encoding subset to which a font family belongs is declared by the command `\DeclareEncodingSubset` that takes the major encoding as the first argument (e.g., `TS1`), the family name as the second argument (e.g., `cmr`), and the subset encoding id as a third, (e.g., 0 for `cmr`).

The default encoding subset to use when nothing is known about the current font family is named `?`.

```

826 \def\DeclareEncodingSubset#1#2#3{%
827   \@ifundefined{#1:#2}%
828     {\PackageInfo{textcomp}{Setting #2 sub-encoding to #1/#3}}%
829     {\PackageInfo{textcomp}{Changing #2 sub-encoding to #1/#3}}%
830   \@namedef{#1:#2}{#3}}

```

In the original code this was only allowed in the preamble but now `.fds` might contain it so that even in a rollback situation it is necessary to allow it everywhere in the document.

```

831 %\@onlypreamble\DeclareEncodingSubset

```

(End of definition for `\DeclareEncodingSubset`.)

The options for the package are the following:

**safe** for unknown font families enables only symbols that are also in the ISO-Adobe character set; without "currency", which is often misused for the Euro. Older Type1 fonts from the non-TeX world provide only this subset.

**euro** enables the “safe” symbols plus the `\texteuro` command. Most newer fonts provide this.

**full** enables all `TS1` commands; useful only with fonts like EC or CM bright.

**almostfull** same as “full”, except that `\textcircled` and `\t` are *not* redefined from their defaults to avoid that commands like `\copyright` suddenly no longer work.

**force** ignore all subset encoding definitions stored in the package itself or in the configuration file and always use the default subset as specified by one of the other options (seldom useful, only dangerous).

`\iftc@forced` Switch used to implement the **force** option

```
832 \newif\iftc@forced \tc@forcedfalse
```

(End of definition for `\iftc@forced`.)

This is implemented by defining the default subset:

```
833 \DeclareOption{full}{\DeclareEncodingSubset{TS1}{?}{0}}
```

```
834 \DeclareOption{almostfull}{\DeclareEncodingSubset{TS1}{?}{1}}
```

```
835 \DeclareOption{euro}{\DeclareEncodingSubset{TS1}{?}{4}}
```

```
836 \DeclareOption{safe}{\DeclareEncodingSubset{TS1}{?}{5}}
```

The default is “almostfull” which means that old documents will work except that `\textcircled` and `\t` will use the kernel defaults (with the advantage that this also works if the current font, as often the case, doesn’t implement these glyphs).

The “force” option simply sets the switch to true.

```
837 \DeclareOption{force}{\tc@forcedtrue}
```

The suggestions to user is to use the “safe” option always unless that balks in which case they could switch to “almostfull” but then better check their output manually.

```
838 \def\tc@errorwarn{\PackageError}
```

```
839 \DeclareOption{warn}{\gdef\tc@errorwarn#1#2#3{\PackageWarning{#1}{#2}}}
```

```
840 \DeclareOption{quiet}{\gdef\tc@errorwarn#1#2#3{}}
```

```
841 \ExecuteOptions{almostfull}
```

```
842 \ProcessOptions\relax
```

`\CheckEncodingSubset` The command `\CheckEncodingSubset` will check if the current font family has the right encoding subset to typeset a certain command. It takes five arguments as follows: first argument is either `\UseTextSymbol`, `\UseTextAccent` depending on whether or not the symbol is a text symbol or a text accent.

The second argument is the encoding from which this symbol should be fetched.

The third argument is either a fake accessor command or an error message. the code in that argument (if ever executed) receives two arguments: **#2** and **#5** of `\CheckEncodingSubset`.

Argument four is the subset encoding id to test against: if this value is higher than the subset id of the current font family then we typeset the symbol, i.e., execute **#1{#2}#5** otherwise it runs **#3#5**, e.g., to produce an error message or fake the glyph somehow.

Argument five is the symbol or accent command that is being checked.

For usage examples see definitions below.

```
843 \iftc@forced
```

If the “force” option was given we always use the default for testing against.

```
844 \def\CheckEncodingSubset#1#2#3#4#5{%
```

```
845   \ifnum #4>%
```

```
846     0\csname #2:\endcsname
```

```
847     \relax
```

```
848   \expandafter\@firstoftwo
```

```
849   \else
```

```

850 \expandafter\@secondoftwo
851 \fi
852 {#1{#2}}{#3}%
853 #5%
854 }

```

In normal circumstances the test is a bit more complicated: first check if there exists a macro `\(arg2):⟨current-family⟩` and if so use that value to test against, otherwise use the default to test against.

```

855 \else
856 \def\CheckEncodingSubset#1#2#3#4#5{%
857   \ifnum #4>%
858     \expandafter\ifx\csname #2:\f@family\endcsname\relax
859       0\csname #2:?\endcsname
860     \else
861       \csname #2:\f@family\endcsname
862     \fi
863   \relax
864   \expandafter\@firstoftwo
865 \else
866   \expandafter\@secondoftwo
867 \fi
868 {#1{#2}}{#3}%
869 #5%
870 }
871 \fi

```

*(End of definition for \CheckEncodingSubset.)*

`\tc@subst`

```

872 \def\tc@subst#1{%
873   \tc@errorwarn{textcomp}%
874   {Symbol \string#1 not provided by\MessageBreak
875     font family \f@family\space
876     in TS1 encoding.\MessageBreak Default family used instead}\@eha
877   \bgroup\fontfamily\textcompsubstdefault\selectfont#1\egroup
878 }

```

*(End of definition for \tc@subst.)*

`\tc@error` `\tc@error` is going to be used in arg #3 of `\CheckEncodingSubset` when a symbol is not available in a certain font family. It gets pass the encoding it normally lives in (arg one) and the name of the symbol or accent that has a problem.

```

879 % error commands take argument:
880 % #1 symbol to be used
881 \def\tc@error#1{%
882   \PackageError{textcomp}% % should be latex error if general
883   {Accent \string#1 not provided by\MessageBreak
884     font family \f@family\space
885     in TS1 encoding}\@eha
886 }

```

*(End of definition for \tc@error.)*

`\tc@fake@euro` `\tc@fake@euro` is an example of a “fake” definition to use in arg #3 of `\CheckEncodingSubset` when a symbol is not available in a certain font family. Here we produce an Euro symbol by combining a “C” with a “=”.

```

887 \def\tc@fake@euro#1{%
888   \leavevmode
889   \PackageInfo{textcomp}{Faking \noexpand#1for font family
890                                     \f@family\MessageBreak in TS1 encoding}%
891   \valign{##\cr
892         \vfil\hbox to 0.07em{\dimen@\f@size\p@
893                                   \math@fontsfalse
894                                   \fontsize{.7\dimen@}\z@\selectfont=\hss}%
895         \vfil\cr%
896         \hbox{C}\crrcr
897   }%
898 }
```

*(End of definition for \tc@fake@euro.)*

`\tc@check@symbol` These are two abbreviations that we use below to check symbols and accents in TS1.  
`\tc@check@accent` Only there to save some space, e.g., we can then write

```
DeclareTextCommandDefault{\textcurrency}{\tc@check@symbol3\textcurrency}
```

to ensure that `\textcurrency` is only typeset if the current font has a TS1 subset id of less than 3. Otherwise `\tc@error` is called telling the user that for this font family `\textcurrency` is not available.

```

899 \def\tc@check@symbol{\CheckEncodingSubset\UseTextSymbol{TS1}\tc@subst}
900 \def\tc@check@accent{\CheckEncodingSubset\UseTextAccent{TS1}\tc@error}
```

*(End of definition for \tc@check@symbol and \tc@check@accent.)*

We start with the commands that are “safe” and which can be unconditionally set up, first the accents...

```

901 \DeclareTextAccentDefault{\capitalcedilla}{TS1}
902 \DeclareTextAccentDefault{\capitalogonek}{TS1}
903 \DeclareTextAccentDefault{\capitalgrave}{TS1}
904 \DeclareTextAccentDefault{\capitalacute}{TS1}
905 \DeclareTextAccentDefault{\capitalcircumflex}{TS1}
906 \DeclareTextAccentDefault{\capitaltilde}{TS1}
907 \DeclareTextAccentDefault{\capitaldieresis}{TS1}
908 \DeclareTextAccentDefault{\capitalhungarumlaut}{TS1}
909 \DeclareTextAccentDefault{\capitalring}{TS1}
910 \DeclareTextAccentDefault{\capitalcaron}{TS1}
911 \DeclareTextAccentDefault{\capitalbreve}{TS1}
912 \DeclareTextAccentDefault{\capitalmacron}{TS1}
913 \DeclareTextAccentDefault{\capitaldotaccent}{TS1}
```

...and then the other glyphs.

```

914 \DeclareTextSymbolDefault{\textcapitalcompwordmark}{TS1}
915 \DeclareTextSymbolDefault{\textascendercompwordmark}{TS1}
916 \DeclareTextSymbolDefault{\textquotestraightbase}{TS1}
917 \DeclareTextSymbolDefault{\textquotestraightdblbase}{TS1}
918 \DeclareTextSymbolDefault{\texttwelveudash}{TS1}
919 \DeclareTextSymbolDefault{\textthreequartersemdash}{TS1}
920 \DeclareTextSymbolDefault{\textdollar}{TS1}
```

```

921 \DeclareTextSymbolDefault{\textquotesingle}{TS1}
922 \DeclareTextSymbolDefault{\textasteriskcentered}{TS1}
923 \DeclareTextSymbolDefault{\textfractionsolidus}{TS1}
924 \DeclareTextSymbolDefault{\textminus}{TS1}
925 \DeclareTextSymbolDefault{\textlbrackdbl}{TS1}
926 \DeclareTextSymbolDefault{\textrbrackdbl}{TS1}
927 \DeclareTextSymbolDefault{\textasciigrave}{TS1}
928 \DeclareTextSymbolDefault{\texttildelow}{TS1}
929 \DeclareTextSymbolDefault{\textasciibreve}{TS1}
930 \DeclareTextSymbolDefault{\textasciicaron}{TS1}
931 \DeclareTextSymbolDefault{\textgravedbl}{TS1}
932 \DeclareTextSymbolDefault{\textacutedbl}{TS1}
933 \DeclareTextSymbolDefault{\textdagger}{TS1}
934 \DeclareTextSymbolDefault{\textdaggerdbl}{TS1}
935 \DeclareTextSymbolDefault{\textbardbl}{TS1}
936 \DeclareTextSymbolDefault{\textperthousand}{TS1}
937 \DeclareTextSymbolDefault{\textbullet}{TS1}
938 \DeclareTextSymbolDefault{\textcelsius}{TS1}
939 \DeclareTextSymbolDefault{\textflorin}{TS1}
940 \DeclareTextSymbolDefault{\texttrademark}{TS1}
941 \DeclareTextSymbolDefault{\textcent}{TS1}
942 \DeclareTextSymbolDefault{\textsterling}{TS1}
943 \DeclareTextSymbolDefault{\textyen}{TS1}
944 \DeclareTextSymbolDefault{\textbrokenbar}{TS1}
945 \DeclareTextSymbolDefault{\textsection}{TS1}
946 \DeclareTextSymbolDefault{\textasciidieresis}{TS1}
947 \DeclareTextSymbolDefault{\textcopyright}{TS1}
948 \DeclareTextSymbolDefault{\textordfeminine}{TS1}
949 \DeclareTextSymbolDefault{\textlnot}{TS1}
950 \DeclareTextSymbolDefault{\textregistered}{TS1}
951 \DeclareTextSymbolDefault{\textasciimacron}{TS1}
952 \DeclareTextSymbolDefault{\textdegree}{TS1}
953 \DeclareTextSymbolDefault{\textpm}{TS1}
954 \DeclareTextSymbolDefault{\texttwosuperior}{TS1}
955 \DeclareTextSymbolDefault{\textthreesuperior}{TS1}
956 \DeclareTextSymbolDefault{\textasciacute}{TS1}
957 \DeclareTextSymbolDefault{\textmu}{TS1}
958 \DeclareTextSymbolDefault{\textparagraph}{TS1}
959 \DeclareTextSymbolDefault{\textperiodcentered}{TS1}
960 \DeclareTextSymbolDefault{\textonesuperior}{TS1}
961 \DeclareTextSymbolDefault{\textordmasculine}{TS1}
962 \DeclareTextSymbolDefault{\textonequarter}{TS1}
963 \DeclareTextSymbolDefault{\textonehalf}{TS1}
964 \DeclareTextSymbolDefault{\textthreequarters}{TS1}
965 \DeclareTextSymbolDefault{\texttimes}{TS1}
966 \DeclareTextSymbolDefault{\textdiv}{TS1}

```

The `\texteuro` is only available for subsets with id 4 or less. Otherwise we fake the glyph using `\tc@fake@euro`

```

967 \DeclareTextCommandDefault{\texteuro}
968   {\CheckEncodingSubset\UseTextSymbol{TS1}\tc@fake@euro5\texteuro}

```

The `\textohm` is only available for subsets with id 3 or less. Otherwise we produce an error.

```

969 \DeclareTextCommandDefault{\textohm}{\tc@check@symbol4\textohm}

```

The `\textestimated` and `\textcurrency` are only provided for fonts with subset encoding with id 2 or less.

```

970 \DeclareTextCommandDefault{\textestimated}%
971   {\tc@check@symbol3\textestimated}
972 \DeclareTextCommandDefault{\textcurrency}%
973   {\tc@check@symbol3\textcurrency}

```

Nearly all of the remaining glyphs are provided only with fonts with id 1 or 0, i.e., are essentially complete.

```

974 \DeclareTextCommandDefault{\capitaltie}%
975   {\tc@check@accent2\capitaltie}
976 \DeclareTextCommandDefault{\newtie}%
977   {\tc@check@accent2\newtie}
978 \DeclareTextCommandDefault{\capitalnewtie}%
979   {\tc@check@accent2\capitalnewtie}
980 \DeclareTextCommandDefault{\textleftarrow}%
981   {\tc@check@symbol2\textleftarrow}
982 \DeclareTextCommandDefault{\textrightarrow}%
983   {\tc@check@symbol2\textrightarrow}
984 \DeclareTextCommandDefault{\textblank}%
985   {\tc@check@symbol2\textblank}
986 \DeclareTextCommandDefault{\textdblhyphen}%
987   {\tc@check@symbol2\textdblhyphen}
988 \DeclareTextCommandDefault{\textzerooldstyle}%
989   {\tc@check@symbol2\textzerooldstyle}
990 \DeclareTextCommandDefault{\textoneoldstyle}%
991   {\tc@check@symbol2\textoneoldstyle}
992 \DeclareTextCommandDefault{\texttwooldstyle}%
993   {\tc@check@symbol2\texttwooldstyle}
994 \DeclareTextCommandDefault{\textthreeoldstyle}%
995   {\tc@check@symbol2\textthreeoldstyle}
996 \DeclareTextCommandDefault{\textfouroldstyle}%
997   {\tc@check@symbol2\textfouroldstyle}
998 \DeclareTextCommandDefault{\textfiveoldstyle}%
999   {\tc@check@symbol2\textfiveoldstyle}
1000 \DeclareTextCommandDefault{\textsixoldstyle}%
1001   {\tc@check@symbol2\textsixoldstyle}
1002 \DeclareTextCommandDefault{\textsevenoldstyle}%
1003   {\tc@check@symbol2\textsevenoldstyle}
1004 \DeclareTextCommandDefault{\texteightoldstyle}%
1005   {\tc@check@symbol2\texteightoldstyle}
1006 \DeclareTextCommandDefault{\textnineoldstyle}%
1007   {\tc@check@symbol2\textnineoldstyle}
1008 \DeclareTextCommandDefault{\textlangle}%
1009   {\tc@check@symbol2\textlangle}
1010 \DeclareTextCommandDefault{\textrangle}%
1011   {\tc@check@symbol2\textrangle}
1012 \DeclareTextCommandDefault{\textmho}%
1013   {\tc@check@symbol2\textmho}
1014 \DeclareTextCommandDefault{\textbigcircle}%
1015   {\tc@check@symbol2\textbigcircle}
1016 \DeclareTextCommandDefault{\textuparrow}%
1017   {\tc@check@symbol2\textuparrow}
1018 \DeclareTextCommandDefault{\textdownarrow}%

```

```

1019     {\tc@check@symbol2\textdownarrow}
1020 \DeclareTextCommandDefault{\textborn}%
1021     {\tc@check@symbol2\textborn}
1022 \DeclareTextCommandDefault{\textdivorced}%
1023     {\tc@check@symbol2\textdivorced}
1024 \DeclareTextCommandDefault{\textdied}%
1025     {\tc@check@symbol2\textdied}
1026 \DeclareTextCommandDefault{\textleaf}%
1027     {\tc@check@symbol2\textleaf}
1028 \DeclareTextCommandDefault{\textmarried}%
1029     {\tc@check@symbol2\textmarried}
1030 \DeclareTextCommandDefault{\textmusicalnote}%
1031     {\tc@check@symbol2\textmusicalnote}
1032 \DeclareTextCommandDefault{\textdblhyphenchar}%
1033     {\tc@check@symbol2\textdblhyphenchar}
1034 \DeclareTextCommandDefault{\textdollaroldstyle}%
1035     {\tc@check@symbol2\textdollaroldstyle}
1036 \DeclareTextCommandDefault{\textcentoldstyle}%
1037     {\tc@check@symbol2\textcentoldstyle}
1038 \DeclareTextCommandDefault{\textcolonmonetary}%
1039     {\tc@check@symbol2\textcolonmonetary}
1040 \DeclareTextCommandDefault{\textwon}%
1041     {\tc@check@symbol2\textwon}
1042 \DeclareTextCommandDefault{\textnaira}%
1043     {\tc@check@symbol2\textnaira}
1044 \DeclareTextCommandDefault{\textguarani}%
1045     {\tc@check@symbol2\textguarani}
1046 \DeclareTextCommandDefault{\textpeso}%
1047     {\tc@check@symbol2\textpeso}
1048 \DeclareTextCommandDefault{\textlira}%
1049     {\tc@check@symbol2\textlira}
1050 \DeclareTextCommandDefault{\textrecipe}%
1051     {\tc@check@symbol2\textrecipe}
1052 \DeclareTextCommandDefault{\textinterrobang}%
1053     {\tc@check@symbol2\textinterrobang}
1054 \DeclareTextCommandDefault{\textinterrobangdown}%
1055     {\tc@check@symbol2\textinterrobangdown}
1056 \DeclareTextCommandDefault{\textdong}%
1057     {\tc@check@symbol2\textdong}
1058 \DeclareTextCommandDefault{\textpertenthousand}%
1059     {\tc@check@symbol2\textpertenthousand}
1060 \DeclareTextCommandDefault{\textpilcrow}%
1061     {\tc@check@symbol2\textpilcrow}
1062 \DeclareTextCommandDefault{\textbaht}%
1063     {\tc@check@symbol2\textbaht}
1064 \DeclareTextCommandDefault{\textnumero}%
1065     {\tc@check@symbol2\textnumero}
1066 \DeclareTextCommandDefault{\textdiscount}%
1067     {\tc@check@symbol2\textdiscount}
1068 \DeclareTextCommandDefault{\textopenbullet}%
1069     {\tc@check@symbol2\textopenbullet}
1070 \DeclareTextCommandDefault{\textservicemark}%
1071     {\tc@check@symbol2\textservicemark}
1072 \DeclareTextCommandDefault{\textlquill}%

```

```

1073 {\tc@check@symbol2\textlquill}
1074 \DeclareTextCommandDefault{\textrquill}%
1075 {\tc@check@symbol2\textrquill}
1076 \DeclareTextCommandDefault{\textcopyleft}%
1077 {\tc@check@symbol2\textcopyleft}
1078 \DeclareTextCommandDefault{\textcircledP}%
1079 {\tc@check@symbol2\textcircledP}
1080 \DeclareTextCommandDefault{\textreferencemark}%
1081 {\tc@check@symbol2\textreferencemark}
1082 \DeclareTextCommandDefault{\textsurd}%
1083 {\tc@check@symbol2\textsurd}

```

The `\textcircled` and `\t` are handled specially, unless the current font has a subset id of 0 (i.e. full TS1) we pick the symbols up from the math font encodings, i.e., the third argument to `\CheckEncodingSubset` uses `\UseTextAccent` to get them from there.

```

1084 \DeclareTextCommandDefault{\textcircled}
1085 {\CheckEncodingSubset\UseTextAccent{TS1}%
1086 {\UseTextAccent{OMS}}1\textcircled}
1087 \DeclareTextCommandDefault{\t}
1088 {\CheckEncodingSubset\UseTextAccent{TS1}%
1089 {\UseTextAccent{OML}}1\t}

```

Finally input the encoding-specific definitions for TS1 thus making the top-level definitions optimized for this encoding (and not for the default encoding).

```

1090 \input{ts1enc.def}

```

Now having the new glyphs available we also want to make sure that they are used. For most cases this will automatically happen but for some glyphs there are inferior definitions already known to L<sup>A</sup>T<sub>E</sub>X which will prevent the usage of the TS1 versions. So we better get rid of them:

```

1091 \UndeclareTextCommand{\textsterling}{OT1}
1092 \UndeclareTextCommand{\textdollar} {OT1}

```

Similar declarations should probably be made for other encodings like OT4 if they are in use.

```

1093 %\UndeclareTextCommand{\textsterling}{OT4}
1094 %\UndeclareTextCommand{\textdollar} {OT4}

```

From the T1 encoding there are two candidates for removal: `%0` and `%00` since these are both constructed from `%` followed by a tiny ‘`o`’ rather than being a single glyph. The problem with this approach is that in PostScript fonts this small zero is usually not available resulting in `%■` rather than `%0` while the real glyph (at least for `\textperthousand`) is available in the PostScript version of TS1. So for the moment we compromise by removing the T1 declaration for `\textperthousand` but keeping the one for `\textpertenthousand`. This will have the effect that with Computer Modern fonts everything will come out (although `%0` and `%00` are not taken from the same physical font) and with PostScript fonts `%00` will come out correctly while `%000` will most likely look like `%■` — which is probably an improvement over just getting a single ‘`■`’ to indicate a completely missing glyph, which would happen if we also ‘undeclared’ `\textpertenthousand`.

```

1095 \UndeclareTextCommand{\textperthousand}{T1}
1096 %\UndeclareTextCommand{\textpertenthousand}{T1}

```

### 5.1.1 Supporting oldstyle digits

```

1097 \DeclareRobustCommand\oldstylenums[1]{%
1098   \begingroup
1099   \ifmmode
1100     \mathgroup\symletters #1%
1101   \else
1102     \CheckEncodingSubset\@use@text@encoding{TS1}%
1103     {\PackageWarning{textcomp}%
1104      {Oldstyle digits unavailable for
1105       family \f@family.\MessageBreak
1106       Lining digits used instead}}%
1107     \tw@{#1}%
1108   \fi
1109   \endgroup
1110 }

```

### 5.1.2 Subset encoding defaults

For many font families commonly used in the T<sub>E</sub>X world we provide the subset encoding data here. Users can add additional font families in the file `textcomp.cfg` if they own other fonts.

However, if the option “forced” was given then all subset encoding specifications are ignored, so there is no point in setting any of them up:

```

1111 \iftc@forced \else
      Computer modern based fonts (e.g., CM, CM-Bright, Concrete):
1112 \DeclareEncodingSubset{TS1}{cmr}      {0}
1113 \DeclareEncodingSubset{TS1}{cmss}     {0}
1114 \DeclareEncodingSubset{TS1}{cmtt}     {0}
1115 \DeclareEncodingSubset{TS1}{cmvtt}    {0}
1116 \DeclareEncodingSubset{TS1}{cmbr}     {0}
1117 \DeclareEncodingSubset{TS1}{cmtl}     {0}
1118 \DeclareEncodingSubset{TS1}{ccr}      {0}
      PSNFSS fonts:
1119 \DeclareEncodingSubset{TS1}{ptm}      {4}
1120 \DeclareEncodingSubset{TS1}{pcr}      {4}
1121 \DeclareEncodingSubset{TS1}{phv}      {4}
1122 \DeclareEncodingSubset{TS1}{ppl}      {3}
1123 \DeclareEncodingSubset{TS1}{pag}      {4}
1124 \DeclareEncodingSubset{TS1}{pbk}      {4}
1125 \DeclareEncodingSubset{TS1}{pnc}      {4}
1126 \DeclareEncodingSubset{TS1}{pzc}      {4}
1127 \DeclareEncodingSubset{TS1}{bch}      {4}
1128 \DeclareEncodingSubset{TS1}{put}      {5}
      Other CTAN fonts (probably not complete):
1129 \DeclareEncodingSubset{TS1}{uag}      {5}
1130 \DeclareEncodingSubset{TS1}{ugq}      {5}
1131 \DeclareEncodingSubset{TS1}{ul8}      {4}
1132 \DeclareEncodingSubset{TS1}{ul9}      {4} % (LuxiSans, one day)
1133 \DeclareEncodingSubset{TS1}{augie}    {5}
1134 \DeclareEncodingSubset{TS1}{dayrom}   {3}
1135 \DeclareEncodingSubset{TS1}{dayroms}  {3}
1136 \DeclareEncodingSubset{TS1}{pxr}      {0}

```

```

1137 \DeclareEncodingSubset{TS1}{pxss}    {0}
1138 \DeclareEncodingSubset{TS1}{pxtt}    {0}
1139 \DeclareEncodingSubset{TS1}{txr}      {0}
1140 \DeclareEncodingSubset{TS1}{txss}     {0}
1141 \DeclareEncodingSubset{TS1}{txtt}     {0}

```

Latin Modern and TeX Gyre:

```

1142 \DeclareEncodingSubset{TS1}{lmr}      {0}
1143 \DeclareEncodingSubset{TS1}{lmdh}     {0}
1144 \DeclareEncodingSubset{TS1}{lmss}     {0}
1145 \DeclareEncodingSubset{TS1}{lmssq}    {0}
1146 \DeclareEncodingSubset{TS1}{lmvtt}    {0}
1147 \DeclareEncodingSubset{TS1}{lmtt}     {0}

1148 \DeclareEncodingSubset{TS1}{qhv}      {0}
1149 \DeclareEncodingSubset{TS1}{qag}      {0}
1150 \DeclareEncodingSubset{TS1}{qbk}      {0}
1151 \DeclareEncodingSubset{TS1}{qcr}      {0}
1152 \DeclareEncodingSubset{TS1}{qcs}      {0}
1153 \DeclareEncodingSubset{TS1}{qpl}      {0}
1154 \DeclareEncodingSubset{TS1}{qtm}      {0}
1155 \DeclareEncodingSubset{TS1}{qzc}      {0}
1156 \DeclareEncodingSubset{TS1}{qhvc}     {0}

```

Fourier-GUTenberg:

```

1157 \DeclareEncodingSubset{TS1}{futs}     {4}
1158 \DeclareEncodingSubset{TS1}{futex}    {4}
1159 \DeclareEncodingSubset{TS1}{futj}     {4}

```

Y&Y's Lucida Bright

```

1160 \DeclareEncodingSubset{TS1}{hlh}      {3}
1161 \DeclareEncodingSubset{TS1}{hls}      {3}
1162 \DeclareEncodingSubset{TS1}{hlst}     {3}

```

The remaining settings for Lucida are conservative: the following fonts contain the `\textohm` character but not the `\texteuro`, i.e., belong to neither subset 4 nor subset 3. If you want to use the `\textohm` with these fonts copy these definition to `textcomp.cfg` and change the subset to 3. However in that case make sure that you do not use the `\texteuro`.

```

1163 \DeclareEncodingSubset{TS1}{hlct}     {5}
1164 \DeclareEncodingSubset{TS1}{hlx}      {5}
1165 \DeclareEncodingSubset{TS1}{hlce}     {5}
1166 \DeclareEncodingSubset{TS1}{hlcn}     {5}
1167 \DeclareEncodingSubset{TS1}{hlcw}     {5}
1168 \DeclareEncodingSubset{TS1}{hlcf}     {5}

```

Other commercial families...

```

1169 \DeclareEncodingSubset{TS1}{pplx}     {3}
1170 \DeclareEncodingSubset{TS1}{pplj}     {3}
1171 \DeclareEncodingSubset{TS1}{ptmx}     {4}
1172 \DeclareEncodingSubset{TS1}{ptmj}     {4}

```

If the file `textcomp.cfg` exists it will be loaded at this point. This allows to define further subset encodings for font families not covered by default.

```

1173 \InputIfFileExists{textcomp.cfg}
1174 {\PackageInfo{textcomp}{Local configuration file used}}{}

```

```

1175 \fi
1176 \end{TS1oldsty}

```

## 6 The checkencodingsubset.tex file

This is a simple file that asks for a name of a font family and then displays information about the TS1 encoding for this family and recommends the right encoding subset (to be used with `\DeclareEncodingsubset`) for this family.

```

1177 (*TS1check)
1178 \ProvidesFile{checkencodingsubset.tex}
1179 [2024/10/18 v0.5b Figure out safe TS1 encoding subsets]

1180 \let\typeoutdetails\typeout
1181 %\def\typeoutdetails#1{} % alternative definition used below

```

For the purpose of this check a glyph exists if the font slot is occupied—too bad if that contains the wrong glyph or some tofu. If it “exists” we return 0 otherwise 1. This way we can call this macro several times in a row and obtain a number that is 0 if all glyphs are existing or greater than 0 if any of them is missing.

The second argument (holding the command name for a symbol) is not used during these tests.

```

1182 \def\doesglyphexist#1#2{\iffontchar\testFont #1 0\else 1\relax \fi}

```

This macro also tests and outputs some information about the symbol if it is missing. This time we make use of the second argument.

```

1183 \def\glyphmissingdetails#1#2{\iffontchar\testFont #1 \else
1184   \typeoutdetails{\space\space\space ==> \string#2 (#1) is missing}\fi}

1185 \newif\ifsafesubencodingfound
1186 \newif\ifcoremisses

```

Testing a group of symbols that belong to one sub-encoding. More precisely, the symbols that become unavailable if you change from sub-encoding  $x$  (#2) to  $x + 1$  (#3). As far as the code is concerned, the symbols that are supposed to be always available (the core) become available if we test the group -1 and 0.

The first argument contains the testing code and is supposed to return a single number greater or equal to zero.

```

1187 \def\testgroup#1#2#3{%
1188   \ifnum 0 = #1%
1189     \ifnum #2<0
1190       \typeoutdetails{All glyphs in core exist}%
1191     \else
1192       \typeoutdetails{All glyphs between sub-encoding #2 and #3 exist}%
1193     \fi
1194   \else
1195     \ifnum #2<0
1196       \typeoutdetails{*****}%
1197       \typeoutdetails{Some glyphs are missing from core:}%
1198       \coremisstrue
1199       \ifsafesubencodingfound \else
1200         \def\subencodingresult{#2}%
1201       \fi
1202     \else

```

```

1203     \typeoutdetails{Some glyphs are missing from sub-encoding #2:}%
1204     \ifsafesubencodingfound \else
1205         \def\subencodingresult{#3}%
1206     \fi
1207 \fi

```

If some glyphs are missing, we rerun the test code but this time using `\glyphmissingdetails`.

```

1208     {\let\doesglyphexist \glyphmissingdetails #1}%

```

And because we had misses we have definitely found the subset.

```

1209     \safesubencodingfoundtrue
1210 \fi
1211 }

```

The currently defined subset for the family is either stored in `\TS1:<family>` if it was declared, or it is the default subset which is stored in `\TS1:?`.

```

1212 \def\currsubencoding#1{\csname TS1:\ifcsname TS1:#1\endcsname #1\else ?\fi\endcsname}

```

If a font family is not found when declaring it with `\DeclareFixedFont` we end up with the following font. This can then be used as a simple test if we failed loading the TS1 font.

```

1213 \DeclareFixedFont\cmrFont{TS1}{cmr}{m}{n}{10pt}

```

Check for all glyphs in all encoding subsets ...

```

1214 \def\testallgroups#1{%
1215     \DeclareFixedFont\testFont{TS1}{#1}{m}{n}{10pt}%
1216     \ifx\testFont\cmrFont
1217         \typeout{***** Font family #1 not found ****}%
1218     \else

```

We haven't checked anything yet.

```

1219     \safesubencodingfoundfalse
1220     \coremissesfalse
1221     \typeoutdetails{^^J-----}%
1222     \typeoutdetails{Testing font family #1^^J(currently TS1-sub-encoding
1223         \currsubencoding{#1})}%
1224     \typeout{-----}%

```

Then we start testing the groups beginning with the glyphs between sub-encoding 8 and 9. If any of them is missing (checked with `\doesglyphexist`) then we already know that 9 is the correct answer.

```

1225     \testgroup{%
1226         \doesglyphexist{21}{\texttwelveudash}%
1227         \doesglyphexist{22}{\textthreequartersemdash}%
1228         \doesglyphexist{134}{\textbardbl}%
1229         \doesglyphexist{137}{\textcelsius}%
1230         \doesglyphexist{178}{\texttwosuperior}%
1231         \doesglyphexist{179}{\textthreesuperior}%
1232         \doesglyphexist{185}{\textonesuperior}%
1233     }{8}{9}%

```

Nevertheless we go on with further groups so that the output lists all missing glyphs.

```

1234     \testgroup{%
1235         \doesglyphexist{32}{\textblank}%
1236         \doesglyphexist{148}{\textinterrobang}%
1237         \doesglyphexist{149}{\textinterrobangdown}%
1238         \doesglyphexist{191}{\texteuro}%

```

```

1239 }{7}{8}%
1240 \testgroup{%
1241     \doesglyphexist{47}{\textfractionsolidus}%
1242     \doesglyphexist{61}{\textminus}%
1243     \doesglyphexist{87}{\textohm}%
1244     \doesglyphexist{181}{\textmu}%
1245 }{6}{7}%
1246 \testgroup{%
1247     \doesglyphexist{140}{\textflorin}%
1248     \doesglyphexist{164}{\textcurrency}%
1249 }{5}{6}%
1250 \testgroup{%
1251     \doesglyphexist{155}{\textnumero}%
1252     \doesglyphexist{157}{\textestimated}%
1253 }{4}{5}%
1254 \testgroup{%
1255     \doesglyphexist{24}{\textleftarrow}%
1256     \doesglyphexist{25}{\textrightarrow}%
1257     \doesglyphexist{94}{\textuparrow}%
1258     \doesglyphexist{95}{\textdownarrow}%
1259     \doesglyphexist{141}{\textcolonmonetary}%
1260     \doesglyphexist{142}{\textwon}%
1261     \doesglyphexist{146}{\textlira}%
1262     \doesglyphexist{150}{\textdong}%
1263 }{3}{4}%
1264 \testgroup{%
1265     \doesglyphexist{60}{\textlangle}%
1266     \doesglyphexist{62}{\textrangle}%
1267 }{2}{3}%
1268 \testgroup{%
1269     \doesglyphexist{0}{\capitalgrave}%
1270     \doesglyphexist{1}{\capitalacute}%
1271     \doesglyphexist{2}{\capitalcircumflex}%
1272     \doesglyphexist{3}{\capitaltilde}%
1273     \doesglyphexist{4}{\capitaldieresis}%
1274     \doesglyphexist{5}{\capitalhungarumlaut}%
1275     \doesglyphexist{6}{\capitalring}%
1276     \doesglyphexist{7}{\capitalcaron}%
1277     \doesglyphexist{8}{\capitalbreve}%
1278     \doesglyphexist{9}{\capitalmacron}%
1279     \doesglyphexist{10}{\capitaldotaccent}%
1280     \doesglyphexist{11}{\capitalcedilla}%
1281     \doesglyphexist{12}{\capitalogonek}%
1282     \doesglyphexist{26}{\t}%
1283     \doesglyphexist{27}{\capitaltie}%
1284     \doesglyphexist{28}{\newtie}%
1285     \doesglyphexist{29}{\capitalnewtie}%
1286     \doesglyphexist{45}{\textdblhyphen}%
1287     \doesglyphexist{48}{\textzerooldstyle}%
1288     \doesglyphexist{49}{\textoneoldstyle}%
1289     \doesglyphexist{50}{\texttwooldstyle}%
1290     \doesglyphexist{51}{\textthreeoldstyle}%
1291     \doesglyphexist{52}{\textfouroldstyle}%
1292     \doesglyphexist{53}{\textfiveoldstyle}%

```

```

1293 \doesglyphexist{54}{\textsixoldstyle}%
1294 \doesglyphexist{55}{\textsevenoldstyle}%
1295 \doesglyphexist{56}{\texteightoldstyle}%
1296 \doesglyphexist{57}{\textnineoldstyle}%
1297 \doesglyphexist{77}{\textmho}%
1298 \doesglyphexist{79}{\textbigcircle}%
1299 \doesglyphexist{91}{\textlbrackdbl}%
1300 \doesglyphexist{93}{\textrbrackdbl}%
1301 \doesglyphexist{96}{\textasciigrave}%
1302 \doesglyphexist{98}{\textborn}%
1303 \doesglyphexist{99}{\textdivorced}%
1304 \doesglyphexist{100}{\textdied}%
1305 \doesglyphexist{108}{\textleaf}%
1306 \doesglyphexist{109}{\textmarried}%
1307 \doesglyphexist{110}{\textmusicalnote}%
1308 \doesglyphexist{126}{\texttildelow}%
1309 \doesglyphexist{127}{\textdblhyphenchar}%
1310 \doesglyphexist{128}{\textasciibreve}%
1311 \doesglyphexist{129}{\textasciicaron}%
1312 \doesglyphexist{175}{\textasciimacron}%
1313 \doesglyphexist{130}{\textacutedbl}%
1314 \doesglyphexist{131}{\textgravedbl}%
1315 \doesglyphexist{138}{\textdollaroldstyle}%
1316 \doesglyphexist{139}{textcentoldstyle}%
1317 \doesglyphexist{143}{\textnaira}%
1318 \doesglyphexist{144}{\textguarani}%
1319 \doesglyphexist{145}{\textpeso}%
1320 \doesglyphexist{147}{\textrecipe}%
1321 \doesglyphexist{152}{\textpertenthousand}%
1322 \doesglyphexist{153}{\textpilcrow}%
1323 \doesglyphexist{154}{\textbaht}%
1324 \doesglyphexist{156}{\textdiscount}%
1325 \doesglyphexist{158}{\textopenbullet}%
1326 \doesglyphexist{159}{\textservicemark}%
1327 \doesglyphexist{160}{\textlquill}%
1328 \doesglyphexist{161}{\textrquill}%
1329 \doesglyphexist{168}{\textasciidieresis}%
1330 \doesglyphexist{171}{\textcopyleft}%
1331 \doesglyphexist{173}{\textcircledP}%
1332 \doesglyphexist{180}{\textasciiacute}%
1333 \doesglyphexist{184}{\textreferencemark}%
1334 \doesglyphexist{187}{\textsurd}%
1335 }{1}{2}%

```

All fonts (up to now) that belong to sub-encoding 1 do have the `\textcircled` glyph, but it is too small to be usable. So this test for this group currently doesn't do much good—but who knows maybe one day a font shows up in which this glyph is actually missing.

```

1336 \testgroup{%
1337 \doesglyphexist{79}{\textcircled}% this is not a proper test because the symbol is
1338 % usually available but not usable
1339 }{0}{1}%
1340 \testgroup{%
1341 \doesglyphexist{13}{\textquotestraightbase}%

```

```

1342 \doesglyphexist{18}{\textquotestraightdblbase}%
1343 \doesglyphexist{23}{\textcapitalcompwordmark}%
1344 \doesglyphexist{31}{\textascendercompwordmark}%
1345 \doesglyphexist{36}{\textdollar}%
1346 \doesglyphexist{39}{\textquotesingle}%
1347 \doesglyphexist{42}{\textasteriskcentered}%
1348 \doesglyphexist{132}{\textdagger}%
1349 \doesglyphexist{133}{\textdaggerdbl}%
1350 \doesglyphexist{135}{\textperthousand}%
1351 \doesglyphexist{136}{\textbullet}%
1352 \doesglyphexist{151}{\texttrademark}%
1353 \doesglyphexist{162}{\textcent}%
1354 \doesglyphexist{163}{\textsterling}%
1355 \doesglyphexist{165}{\textyen}%
1356 \doesglyphexist{166}{\textbrokenbar}%
1357 \doesglyphexist{167}{\textsection}%
1358 \doesglyphexist{169}{\textcopyright}%
1359 \doesglyphexist{170}{\textordfeminine}%
1360 \doesglyphexist{172}{\textlnot}%
1361 \doesglyphexist{174}{\textregistered}%
1362 \doesglyphexist{176}{\textdegree}%
1363 \doesglyphexist{177}{\textpm}%
1364 \doesglyphexist{182}{\textparagraph}%
1365 \doesglyphexist{183}{\textperiodcentered}%
1366 \doesglyphexist{186}{\textordmasculine}%
1367 \doesglyphexist{188}{\textonequarter}%
1368 \doesglyphexist{189}{\textonehalf}%
1369 \doesglyphexist{190}{\textthreequarters}%
1370 \doesglyphexist{214}{\texttimes}%
1371 \doesglyphexist{246}{\textdiv}%
1372 }{-1}{0}%

```

If all groups have all glyphs then we have the full encoding (subset 0).

```

1373 \ifsafesubencodingfound\else
1374 \def\subencodingresult{0}%
1375 \fi

```

If the font is missing some of the core glyphs we make a remark about this, because they will never display.

```

1376 \typeoutdetails{-----}%
1377 \typeout{TS1 encoding subset for #1\ifcoremisses \space(ignore core misses)\fi
1378 \space (\ifnum\subencodingresult =
1379 \currsubencoding{#1} ok\else bad\fi)}%
1380 \typeout{Use sub-encoding \subencodingresult
1381 \ifnum\subencodingresult = \currsubencoding{#1}\else
1382 \space (not \currsubencoding{#1})\fi}
1383 \typeout{-----^^J}%
1384 \fi
1385 }

```

This tests all declarations (or most of them) that have been added to the kernel. It is called if no family is given interactively.

```

1386 \long\def\testallkerneldefinedfamilies{%
1387 \testallgroups{ccr}% {0}
1388 \testallgroups{cmbr}% {0}

```

```

1389 %%\testallgroups{cmr}% {0} % don't test this one as it is the fallback
1390 % thus reports that the family is not found
1391 \testallgroups{cmss}% {0}
1392 \testallgroups{cmtl}% {0}
1393 \testallgroups{cmtt}% {0}
1394 \testallgroups{cmvtt}% {0}
1395 \testallgroups{pxr}% {0}
1396 \testallgroups{pxss}% {0}
1397 \testallgroups{pxtt}% {0}
1398 \testallgroups{qag}% {0}
1399 \testallgroups{qbk}% {0}
1400 \testallgroups{qcr}% {0}
1401 \testallgroups{qcs}% {0}
1402 \testallgroups{qhvc}% {0}
1403 \testallgroups{qhv}% {0}
1404 \testallgroups{qpl}% {0}
1405 \testallgroups{qtm}% {0}
1406 \testallgroups{qzc}% {0}
1407 \testallgroups{txr}% {0}
1408 \testallgroups{txss}% {0}
1409 \testallgroups{txtt}% {0}
1410 %
1411 % Next would claim to be 0 (or 2)
1412 %
1413 %%\testallgroups{lmr}% {1}
1414 %%\testallgroups{lmdh}% {1}
1415 %%\testallgroups{lms}% {1}
1416 %%\testallgroups{lmsq}% {1}
1417 %%\testallgroups{lmvtt}% {1}
1418 %%\testallgroups{lmtt}% {1} % missing TM, SM and pertenthousand so really 2
1419 %
1420 % these are no longer in TeX Live
1421 %
1422 %%\testallgroups{ptmx}% {2} % gone for a long time it seems
1423 %%\testallgroups{ptmj}% {2} % ditto
1424 %%\testallgroups{ul8}% {2} % ditto
1425 %
1426 % next block has tofu chars so results are wrong
1427 %
1428 %%\testallgroups{bch}% {5} % tofu for blank, ohm
1429 %%\testallgroups{futj}% {5} % tofu for blank, interrobang/down, ohm
1430 %%\testallgroups{futs}% {5} % tofu for blank, ohm
1431 %%\testallgroups{futz}% {5} % probably (currently broken distrib)
1432 %%\testallgroups{pag}% {5} % tofu for blank, interrobang/down, ohm
1433 %%\testallgroups{pbk}% {5} % tofu for blank, interrobang/down, ohm
1434 %%\testallgroups{pcr}% {5} % tofu for blank, interrobang/down, ohm
1435 %%\testallgroups{phv}% {5} % tofu for blank, interrobang/down, ohm
1436 %%\testallgroups{pnc}% {5} % tofu for blank, interrobang/down, ohm
1437 %%\testallgroups{pplj}% {5} % tofu for blank
1438 %%\testallgroups{pplx}% {5} % tofu for blank
1439 %%\testallgroups{ppl}% {5} % tofu for blank interrobang/down
1440 %%\testallgroups{ptm}% {5} % tofu for blank, interrobang/down, ohm
1441 %%\testallgroups{pzc}% {5} % tofu for blank, interrobang/down, ohm
1442 %%\testallgroups{ul9}% {5} % tofu for blank, interrobang/down, ohm

```

```

1443 %\testallgroups{dayroms}%{6} % tofu for blank, interrobang/down, ohm
1444 %\testallgroups{dayrom}% {6} % tofu for blank, interrobang/down, ohm
1445 %\testallgroups{augie}%{8} % really only missing euro and full of tofu
1446 %\testallgroups{put}% {8}
1447 %\testallgroups{uag}% {8} % probably (currently broken distrib)
1448 %\testallgroups{ugq}% {8}
1449 %
1450 \testallgroups{zi4}% {9}
1451 %
1452 %% not installed normally
1453 %
1454 %\testallgroups{hls}% {5}
1455 %\testallgroups{hlst}% {5}
1456 %\testallgroups{hlct}% {5}
1457 %\testallgroups{hlh}% {5}
1458 %\testallgroups{hlx}% {8}
1459 %\testallgroups{hlce}% {8}
1460 %\testallgroups{hlcn}% {8}
1461 %\testallgroups{hlcw}% {8}
1462 %\testallgroups{hlcf}% {8}
1463
1464 \testallgroups{lato-LF}% {0} % with a bunch of tofu inside --- should probably be changed
1465 \testallgroups{opensans-TLF}%{0} % with a bunch of tofu inside --- should probably be change
1466 \testallgroups{cantarell-TLF}% {0} % with a bunch of tofu inside --- should probably be cha
1467 \testallgroups{fbb-LF}% {0} % missing centoldstyle ---> 2
1468 \testallgroups{tli}% {1} % with lots of tofu inside --- should probably be changed
1469 \testallgroups{Alegreya-OsF}% {2}
1470 \testallgroups{AlegreyaSans-OsF}% {2}
1471 \testallgroups{DejaVuSans-TLF}% {2}
1472 \testallgroups{DejaVuSansCondensed-TLF}% {2}
1473 \testallgroups{DejaVuSansMono-TLF}% {2} this is missing \textfractionsolidus which makes it 7
1474 \testallgroups{EBGaramond-LF}% {2}
1475 \testallgroups{Tempora-TLF}% {2}
1476 \testallgroups{Tempora-TOfF}% {2}
1477 \testallgroups{Arimo-TLF}% {3}
1478 \testallgroups{Crlt-TLF}% {3} changed from Carlito-
1479 \testallgroups{FiraSans-LF}% {3} should be 4
1480 \testallgroups{IBMPlexSans-TLF}% {3}
1481 \testallgroups{Merriwthr-OsF}% {3} changed from Merriweather- and should be 2
1482 \testallgroups{Montserrat-LF}% {3} now 2
1483 \testallgroups{MontserratAlternates-LF}%{3} now 2
1484 \testallgroups{SourceCodePro-TLF}% {3}
1485 \testallgroups{SourceCodePro-TOfF}% {3}
1486 \testallgroups{SourceSansPro-OsF}% {3}
1487 \testallgroups{SourceSerifPro-LF}% {3}
1488 \testallgroups{Tinos-TLF}% {3}
1489 \testallgroups{AccanthisADFStdNoThree-LF}%{4}
1490 \testallgroups{Cabin-TLF}% {4}
1491 \testallgroups{Caladea-TLF}% {4}
1492 \testallgroups{Chivo-LF}% {4}
1493 \testallgroups{ClearSans-TLF}% {4}
1494 \testallgroups{Coelacanth-LF}% {4}
1495 \testallgroups{CrimsonPro-LF}% {4}
1496 \testallgroups{FiraMono-TLF}% {4}

```

```

1497 \testallgroups{FiraMono-T0sF}% {4}
1498 \testallgroups{Go-TLF}% {4}
1499 \testallgroups{GoMono-TLF}% {4}
1500 \testallgroups{InriaSans-LF}% {4}
1501 \testallgroups{InriaSerif-LF}% {4}
1502 \testallgroups{LibertinusSans-LF}% {4}
1503 \testallgroups{LibertinusSerif-LF}% {4}
1504 \testallgroups{LibreBodoni-TLF}% {4}
1505 \testallgroups{LibreFranklin-TLF}% {4}
1506 \testallgroups{LinguisticsPro-LF}% {4}
1507 \testallgroups{LinguisticsPro-0sF}% {4}
1508 \testallgroups{LinuxBiolinumT-LF}% {4}
1509 \testallgroups{LinuxLibertineT-LF}% {4}
1510 \testallgroups{MerriwthrSans-0sF}% {4} name change and now 2
1511 \testallgroups{MintSpirit-LF}% {4}
1512 \testallgroups{MintSpiritNoTwo-LF}% {4}
1513 \testallgroups{PTMono-TLF}% {4}
1514 \testallgroups{PTSans-TLF}% {4}
1515 \testallgroups{PTSansCaption-TLF}% {4}
1516 \testallgroups{PTSansNarrow-TLF}% {4}
1517 \testallgroups{PTSerif-TLF}% {4}
1518 \testallgroups{PTSerifCaption-TLF}% {4}
1519 \testallgroups{Raleway-TLF}% {4}
1520 \testallgroups{Raleway-T0sF}% {4}
1521 \testallgroups{Roboto-LF}% {4}
1522 \testallgroups{RobotoMono-TLF}% {4}
1523 \testallgroups{RobotoSlab-TLF}% {4}
1524 \testallgroups{Rosario-LF}% {4}
1525 \testallgroups{SticksTooText-LF}% {4}
1526 \testallgroups{UniversalisADFStd-LF}% {4}
1527 \testallgroups{Almndr-0sF}% {5} name change
1528 \testallgroups{Baskervaldx-LF}% {5}
1529 \testallgroups{BaskervilleF-LF}% {5} now 2
1530 \testallgroups{Bttr-TLF}% {5} name changed from Bitter-...
1531 \testallgroups{Cinzel-LF}% {5}
1532 \testallgroups{CinzelDecorative-LF}% {5}
1533 \testallgroups{DejaVuSerif-TLF}% {5}
1534 \testallgroups{DejaVuSerifCondensed-TLF}% {5}
1535 \testallgroups{GilliusADF-LF}% {5}
1536 \testallgroups{charssil-TLF}% {5} missing should be 5
1537 \testallgroups{GilliusADFCond-LF}% {5}
1538 \testallgroups{GilliusADFNoTwo-LF}% {5}
1539 \testallgroups{GilliusADFNoTwoCond-LF}% {5}
1540 \testallgroups{Lbstr-LF}% {5} name change and should be 7
1541 \testallgroups{OldStandard-TLF}% {5}
1542 \testallgroups{PlyfrDisplay-LF}% {5} name change
1543 \testallgroups{PlyfrDisplay-0sF}% {5} name change
1544 \testallgroups{TheanoDidot-TLF}% {5}
1545 \testallgroups{TheanoDidot-T0sF}% {5}
1546 \testallgroups{TheanoModern-TLF}% {5}
1547 \testallgroups{TheanoModern-T0sF}% {5}
1548 \testallgroups{TheanoOldStyle-TLF}% {5}
1549 \testallgroups{TheanoOldStyle-T0sF}% {5}
1550 \testallgroups{Crimson-TLF}% {6}

```

```

1551 \testallgroups{IBMPlexMono-TLF}% {6} now 3
1552 \testallgroups{IBMPlexSerif-TLF}% {6} now 3
1553 \testallgroups{LibertinusMono-TLF}% {6} should be 8
1554 \testallgroups{LibertinusSerifDisplay-LF}% {6}
1555 \testallgroups{LinuxLibertineDisplayT-LF}% {6}
1556 \testallgroups{LinuxLibertineMonoT-LF}% {6}
1557 \testallgroups{LinuxLibertineMonoT-TLF}% {6}
1558 \testallgroups{Ovrlck-LF}% {6} name changed
1559 \testallgroups{CormorantGaramond-LF}% {7}
1560 \testallgroups{Heuristica-TLF}% {7}
1561 \testallgroups{Heuristica-TOfF}% {7}
1562 \testallgroups{IMFELLEnglish-TLF}% {7}
1563 \testallgroups{LibreBskvl-LF}% {7} %% wrong name LibreBaskerville-TLF
1564 \testallgroups{LibreCsln-LF}% {7} changed from LibreCaslon-
1565 \testallgroups{Mrcls-LF}% {7} %% wrong name Marcellus-LF
1566 \testallgroups{NotoSans-LF}% {7}
1567 \testallgroups{NotoSansMono-TLF}% {7} now 2
1568 \testallgroups{NotoSansMono-TOfF}% {7} now 2
1569 \testallgroups{NotoSerif-LF}% {7}
1570 \testallgroups{Quattro-LF}% {7} changed from Quattrocento-
1571 \testallgroups{QuattroSans-LF}% {7} changed from QuattrocentoSans-
1572 \testallgroups{XCharter-TLF}% {7} now 2
1573 \testallgroups{XCharter-TOfF}% {7} now 2
1574 \testallgroups{erewhon-LF}% {7} now 2
1575 \testallgroups{ComicNeue-TLF}% {7}
1576 \testallgroups{ComicNeueAngular-TLF}% {7}
1577 \testallgroups{Frm-LF}% {7} % the superiors are missing; name changed from Forum-LF
1578 \testallgroups{Cochineal-TLF}% {8} now 5
1579 \testallgroups{AlgolRevived-TLF}% {9}
1580 }

```

There interaction with the user.

```

1581 \typeout{^^J=====}
1582 \typeout{[ Enter font family to check (or <enter> for kernel defined families)}
1583 \typeout{=====}
1584 \typein[\FontFamilyToCheck]{}

1585 \if!\FontFamilyToCheck!
1586 \typeout{=====}
1587 \typeout{[ Detailed output? (default no)}
1588 \typeout{=====}
1589 \typein[\Details]{}
1590 \if!\Details!
1591 \def\typeoutdetails#1{}
1592 \else
1593 \let\typeoutdetails\typeout
1594 \fi
1595 \testallkerneldefinedfamilies
1596 \else
1597 \let\typeoutdetails\typeout
1598 \testallgroups\FontFamilyToCheck
1599 \fi

1600 \stop
1601 </TS1check>

```

## File 34

# ltpageno.dtx

## 1 Page Numbering

Page numbers are produced by a page counter, used just like any other counter. The only difference is that `\c@page` contains the number of the next page to be output (the one currently being produced), rather than one minus it. Thus, it is normally initialized to 1 rather than 0. `\c@page` is defined to be `\count0`, rather than a count assigned by `\newcount`.

`\pagenumbering` The user sets the page number style with the `\pagenumbering{<foo>}` command, which sets the page counter to 1 and defines `\thepage` to be `\foo`. For example, `\pagenumbering{roman}` causes pages to be numbered i, ii, etc.

```
1 <*2ekernel>
2 \message{page nos.,}

3 \countdef\c@page=0 \c@page=1
4 \def\c1@page{}
5 \def\pagenumbering#1{%
6   \global\c@page \c@one \gdef\thepage{\csname @#1\endcsname
7     \c@page}}
8 </2ekernel>
```

## File 35

# ltxref.dtx

## 1 Cross Referencing

The user writes `\label{foo}` to define the following cross-references:

`\ref*{foo}`: value of most recently incremented referenceable counter. in the current environment. (Chapter, section, theorem, footnote and enumeration counters and other counters stepped with `\refstepcounter` are referenceable.)

`\pageref*{foo}`: page number at which `\label{foo}` command appeared. where `foo` can be any string of characters not containing `\`, `{` or `}`.

Note: The scope of the `\label` command is delimited by environments, so `\begin{theorem} \label{foo} ... \end{theorem} \label{bar}` defines `\ref{foo}` to be the theorem number and `\ref{bar}` to be the current section number.

Note: `\label` does the right thing in terms of spacing – i.e., leaving a space on both sides of it is equivalent to leaving a space on either side.

Note: the starred versions `\ref*` and `\pageref*` are provided to align with the use of `hyperref`. Without `hyperref` (or some other package using the starred form) the star is simply ignored.

Note: starting with 2023-06-01 `\label` stores also the current value of `\@currentlabelname` which should typically contain a (sanitized) title. (A reference command `\nameref` is provided by the `nameref` package.) `\label` also stores `\@currentHref` which if set should refer to a target name for links. This value is set and used by `hyperref`. Unlike the other values `\@currentHref` should be set globally. A fifth value `\@kernel@reserved@label@data` is reserved for the kernel to allow future extensions of the cross-reference system.

### 1.1 Cross Referencing

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
1 <*2ekernel>
2 \message{x-ref,}
```

This is implemented as follows. A referenceable counter `CNT` is incremented by the command `\refstepcounter{CNT}`, which sets `\@currentlabel == {CNT}{eval(\p@cnt\theCNT)}`. The command `\label{FOO}` then writes the following on file `\@auxout`:

```
\newlabel{FOO}{eval(\@currentlabel)}{eval(\thepage)}%
```

```
{eval(\@currentlabelname)}{eval(\@currentHref)}{eval(\@kernel@reserved@label@data)}
```

```
\ref{FOO} ==
BEGIN
  if \r@foo undefined
  then @refundefined := G T
  ??
  Warning: 'reference foo on page ... undefined'
```

```

        else \@car \eval(\r@F00)\@nil
      fi
    END

\pageref{foo} =
  BEGIN
    if \r@foo undefined
    then @refundundefined := G T
      ??
      Warning: 'reference foo on page ... undefined'
    else \@cdr \eval(\r@F00)\@nil
    fi
  END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

**\labelformat** A reference via **\ref** produces by default the data associated with the corresponding **\label** command (typically a number); any additional formatting has to be provided by the user. If, for example, references to equations are always to be typeset as “equation (*number*)”, one has to code “**equation** (**\ref{key}**)”. With **\labelformat** there is a possibility to generate such frills automatically without resorting to low-level coding. The command takes two arguments: the first is the name of a counter and the second is its representation when referenced. This means that for a successful usage, one has to know the counter name being used for generating the label, though in practice this should not pose a problem. The current counter number is picked up as an argument. Here are two examples:

```

\labelformat{section}{section~#1}
\labelformat{equation}{equation~( #1 )}

```

**\Ref** A side effect of using **\labelformat** is that, depending on the defined formatting, it becomes impossible to use **\ref** at the beginning of a sentence (if its replacement text starts with a lowercase letter). To overcome this problem we introduce the command **\Ref** that behave like **\ref** except that it uppercases the first token of the generated string.

To make **\Ref** work properly the very first token in the second argument of **\labelformat** has to be a simple ASCII or UTF-8 letter, otherwise the capitalization will fail or worse, you will end up with some error messages. If you actually need something more complicated in this place (e.g., an accented letter not written as a UTF-8 character) you have to explicitly surround it with braces, to identify the part that needs to be capitalized. For example, for figure references in the Hungarian language you might want to write **\labelformat{figure}{\‘a}bra~\thefigure}** or use **\labelformat{figure}{ábra~\thefigure}** which avoids the brace problem.

**\G@refundundefinedtrue** This does not save on name-space (since **\G@refundundefinedfalse** was never needed) but **\@refundundefined** it does make the implementation of such one-way switches more consistent. The extra macro to make the change is used since this change appears several times.

**Note** despite its name, **\G@refundundefinedtrue** does *not* correspond to an **\if** command, and there is no matching **...false**. It would be more natural to call the command **\G@refundundefined** (as inspection of the change log will reveal) but unfortunately such a change would break any package that had defined a **\ref**-like command that mimicked the definition of **\ref**, calling **\G@refundundefinedtrue**. Inspection of the T<sub>E</sub>X archives

revealed several such packages, and so this command has been named ...`true` so that the definition of `\ref` need not be changed, and the packages will work without change.

```

3 % \newif\ifG@refundefined
4 % \def\G@refundefinedtrue{\global\let\ifG@refundefined\iftrue}
5 % \def\G@refundefinedfalse{\global\let\ifG@refundefined\iffalse}
6 \def\G@refundefinedtrue{%
7   \gdef\@refundefined{%
8     \@latex@warning@no@line{There were undefined references}}
9 \let\@refundefined\relax

```

(End of definition for `\G@refundefinedtrue` and `\@refundefined`.)

`\ref` Referencing a `\label`. RmS 91/10/25: added a few extra `\reset@font`, as suggested by  
`\pageref` Bernd Raichle  
`\setref` RmS 92/08/14: made `\ref` and `\pageref` robust  
RmS 93/09/08: Added setting of `refundefined` switch.

```

10 </2ekernel>
11 <*2ekernel | latexrelease>
12 <latexrelease>\IncludeInRelease{2023/06/01}%
13 <latexrelease>          {\@kernel@sref}{store five arguments}%
14 \def\@setref#1#2#3{%
15   \ifx#1\relax
16     \protect\G@refundefinedtrue
17     \nfss@text{\reset@font\bfseries ??}%
18     \@latex@warning{Reference ‘#3’ on page \thepage \space
19                   undefined}%
20   \else
21     \expandafter#2#1\@empty\@empty\@empty\@empty\null
22   \fi}

23 \long\def\@firstoffive#1#2#3#4#5{#1}
24 \long\def\@secondoffive#1#2#3#4#5{#2}
25 \def\@kernel@sref#1{\expandafter\@setref\csname r@#1\endcsname\@firstoffive{#1}}
26 \def\@kernel@spageref#1{\expandafter\@setref\csname r@#1\endcsname
27   \@secondoffive{#1}}
28 <latexrelease>\EndIncludeInRelease
29 <latexrelease>\IncludeInRelease{2022/06/01}%
30 <latexrelease>          {\@kernel@sref}{store five arguments}%
31 <latexrelease>\def\@setref#1#2#3{%
32 <latexrelease>   \ifx#1\relax
33 <latexrelease>     \protect\G@refundefinedtrue
34 <latexrelease>     \nfss@text{\reset@font\bfseries ??}%
35 <latexrelease>     \@latex@warning{Reference ‘#3’ on page \thepage \space
36 <latexrelease>         undefined}%
37 <latexrelease>   \else
38 <latexrelease>     \expandafter#2#1\null
39 <latexrelease>   \fi}
40 <latexrelease>\let\@firstoffive\undefined
41 <latexrelease>\let\@secondoffive\undefined
42 <latexrelease>\def\@kernel@sref#1{\expandafter\@setref\csname r@#1\endcsname\@firstoftwo{#1}}
43 <latexrelease>\def\@kernel@spageref#1{\expandafter\@setref\csname r@#1\endcsname
44 <latexrelease>   \@secondoftwo{#1}}
45 <latexrelease>\EndIncludeInRelease
46 <latexrelease>\IncludeInRelease{0000/00/00}%

```

```

47 <latexrelease> {\@kernel@sref}{store five arguments}%
48 <latexrelease> \def\@setref#1#2#3{%
49 <latexrelease> \ifx#1\relax
50 <latexrelease> \protect\G@refundefinedtrue
51 <latexrelease> \nfss@text{\reset@font\bfseries ??}%
52 <latexrelease> \@latex@warning{Reference ‘#3’ on page \thepage \space
53 <latexrelease> undefined}%
54 <latexrelease> \else
55 <latexrelease> \expandafter#2#1\null
56 <latexrelease> \fi}
57 <latexrelease> \let\@firstoffive\undefined
58 <latexrelease> \let\@secondoffive\undefined
59 <latexrelease> \let\@kernel@sref\undefined
60 <latexrelease> \let\@kernel@spageref\undefined
61 <latexrelease> \EndIncludeInRelease
62 <latexrelease> \IncludeInRelease{2022/06/01}%
63 <latexrelease> {\ref}{Add starred reference commands}%
64 \let\@kernel@ref\@kernel@sref
65 \let\@kernel@pageref\@kernel@spageref
66 \NewDocumentCommand\ref{s}
67 {\IfBooleanTF{#1}{\@kernel@sref}{\@kernel@ref}}
68 \NewDocumentCommand\pageref{s}
69 {\IfBooleanTF{#1}{\@kernel@spageref}{\@kernel@pageref}}

```

```

70 \def\@kernel@pageref@exp#1{\csname cs_if_exist:cTF\endcsname
71   {r@#1}{\csname tl_item:cn\endcsname{r@#1}{2}}{0}}
72 \def\@kernel@ref@exp#1{\csname cs_if_exist:cTF\endcsname
73   {r@#1}{\csname tl_item:cn\endcsname{r@#1}{1}}{0}}
74 </2kernel | latexrelease>
75 <latexrelease>\EndIncludeInRelease
76 <latexrelease>\IncludeInRelease{0000/00/00}%
77 <latexrelease>          {\ref}{Add starred reference commands}%
78 <latexrelease>\def\ref#1{\expandafter\@setref\csname r@#1\endcsname\@firstoftwo{#1}}
79 <latexrelease>\def\pageref#1{\expandafter\@setref\csname r@#1\endcsname
80 <latexrelease>          \@secondoftwo{#1}}
81 <latexrelease>
82 <latexrelease>\EndIncludeInRelease
83 <*2kernel>

```

`\newlabel` This command will be written to the `.aux` file to pass label information from one run to another.

```

84 \def\@newl@bel#1#2#3{%
85   \ifundefined{#1@#2}%
86     \relax
87     {\gdef\@multiplelabels {%
88       \@latex@warning@no@line{There were multiply-defined labels}}}%

```

```

89 \latex@warning@no@line{Label ‘#2’ multiply defined}}%
90 \global\@namedef{#1@#2}{#3}}
91 \def\newlabel{\@newl@bel r}
92 \onlypreamble{\@newl@bel

```

(End of definition for \newlabel and \@newl@bel.)

`\if@multiplelabels` This is redefined to produce a warning if at least one label is defined more than once. It is executed by the `\enddocument` command.

```

93 \let \@multiplelabels \relax

```

(End of definition for \if@multiplelabels and \@multiplelabels.)

`\label` The commands `\label` and `\refstepcounter` have been changed to allow `\protect`’ed commands to work properly. For example,

```

\def\thechapter{\protect\foo{\arabic{chapter}.\roman{section}}}

```

will cause a `\label{bar}` command to define `\ref{bar}` to expand to something like `\foo{4.d}`. Change made 20 Jul 88.

```

94 \</2ekernel>
95 \<2ekernel | latexrelease>
96 \<latexrelease>\IncludeInRelease{2023/06/01}%
97 \<latexrelease> \label}{store five label arguments}%
98 \providecommand\@currentlabelname{}
99 \providecommand\@currentHref{}
100 \providecommand\@kernel@reserved@label@data{}
101 \NewHookWithArguments{label}{1}
102 \def\label#1{\@bsphack
103 \begingroup
104 \UseHookWithArguments{label}{1}{#1}%
105 \protected@write\@auxout{}%
106 \string\newlabel{#1}{\@currentlabel}{\thepage}%
107 \{\@currentlabelname}{\@currentHref}{\@kernel@reserved@label@data}}}%
108 \endgroup
109 \@esphack}
110 \<latexrelease>\EndIncludeInRelease

```

(End of definition for \label. This function is documented on page 818.)

`\refstepcounter` Saved \* for testing the argument of `\refstepcounter`.

```

111 \def\ltx@star@counter{*}

```

(End of definition for \refstepcounter.)

`\refstepcounter` Step the counter and allow for labels to point to its current value.

```

112 \<latexrelease>\IncludeInRelease{2022/06/01}%
113 \<latexrelease> {\Ref}{Add starred version}%
114 \def\@currentcounter{}
115 \<latexrelease>\EndIncludeInRelease
116 \<latexrelease>\IncludeInRelease{2024/11/01}%
117 \<latexrelease> {\@currentHref}{set theHcounter representation}%

```

`refstepcounter` (*socket*) This socket takes the whole code as argument. The default kernel plug is identity. By changing the plug `hyperref` can add a conditional and e.g. suppress the processing in a PDF context.

```
118 \NewSocket{refstepcounter}{1}
```

`refstepcounter/target` (*socket*) This socket takes an argument, the counter name, and should at least set from it the target name `\@currentHref`. With `hyperref` it sets also the actual target. This is done with a socket so that the target name is not set more than once to (possibly) different names. The socket is not used in `\@kernel@refstepcounter`. The tagging code needs the target name so it is added after this socket.

```
119 \NewSocket{refstepcounter/target}{1}
```

`(refstepcounter/target)` (*plug*)

```
120 \NewSocketPlug{refstepcounter/target}{kernel}
121 {\xdef\@currentHref {#1.\csname theH#1\endcsname}}%
122 \AssignSocketPlug{refstepcounter/target}{kernel}

123 \def\refstepcounter#1{%
124   \UseSocket{refstepcounter}{%
125     \stepcounter{#1}%
126     \edef\reserved@a{#1}%
127     \ifx\reserved@a\ltx@star@counter\else
128       \let\@currentcounter\reserved@a
129     \fi
130     \protected@edef\@currentlabel
```

By generating the second `csname` first the `\p@...` command can grab it as an argument which can be helpful for more complicated typesetting arrangements.

The trick is to ensure that `\csname the#1\endcsname` is turned into a single token before `\p@...` is expanded further. This way, if the `\p@...` command is a macro with one argument it will receive `\the...`. With the original kernel code (i.e., without the `\expandafter`) it will instead pick up `\csname` which would be disastrous.

Using `\expandafter` instead of braces delimiting the argument is better because, assuming that the `\p@...` command is not defined as a macro with one argument, the braces will stay and prohibit kerning that might otherwise happen between the glyphs generated by `\the...` and surrounding glyphs.

```
131   {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
132   \UseSocket{refstepcounter/target}{#1}%
133   \UseTaggingSocket{recordtarget}%
134   }%
135 }
```

This is a version of `\refstepcounter` which does not set and use targets.

```
\@kernel@refstepcounter 136 \def\@kernel@refstepcounter#1{%
137   \UseSocket{refstepcounter}{%
138     \stepcounter{#1}%
139     \edef\reserved@a{#1}%
140     \ifx\reserved@a\ltx@star@counter\else
141       \let\@currentcounter\reserved@a
142     \fi
143     \protected@edef\@currentlabel
144     {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}}%
```

```

145 <latexrelease>\EndIncludeInRelease
146 <latexrelease>\IncludeInRelease{2022/06/01}%
147 <latexrelease>          {\@currentHref}{set theHcounter representation}%
148 <latexrelease>\def\refstepcounter#1{\stepcounter{#1}%
149 <latexrelease>          \edef\@currentcounter{#1}%
150 <latexrelease>          \protected@edef\@currentlabel
151 <latexrelease>          {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
152 <latexrelease>}}
153 <latexrelease>\let\@kernel@refstepcounter\refstepcounter
154 <latexrelease>\EndIncludeInRelease

```

(End of definition for \refstepcounter and \@kernel@refstepcounter.)

```

155 <latexrelease>\IncludeInRelease{2022/06/01}%
156 <latexrelease>          {\Ref}{Add starred version}%

```

**\labelformat** A shortcut to set the \p@... macro for a counter. It will pick up the counter representation as an argument so that it can be specially formatted.

```

157 \def\labelformat#1{\expandafter\def\csname p@#1\endcsname##1}

```

(End of definition for \labelformat.)

**\Ref** This macro expands the result of \ref and then uppercases the first token. Only useful if the label was generated via \labelformat and contains some lower case letter at its start. If the label starts with a complicated construct (e.g., an accented letter that is provided via a command, e.g., \a instead of a UTF-8 character like ä) one has to surround everything that needs uppercasing in a brace group in the definition of \labelformat.<sup>40</sup>

```

158 % \changes{v1.1s}{2024/12/10}{Replace \cs{@tempa} with \cs{reserved@a} (gh/1579)}
159 \def\@kernel@Ref#1{\protected@edef\reserved@a{\@kernel@ref{#1}}%
160 \expandafter\MakeUppercase\reserved@a}
161 \def\@kernel@sRef#1{\protected@edef\reserved@a{\@kernel@sref{#1}}%
162 \expandafter\MakeUppercase\reserved@a}
163 \NewDocumentCommand\Ref{s}
164 {\IfBooleanTF{#1}{\@kernel@sRef}{\@kernel@Ref}}

```

(End of definition for \Ref.)

```

165 </2ekernel | latexrelease>
166 <latexrelease>\EndIncludeInRelease
167 <latexrelease>\IncludeInRelease{0000/00/00}%
168 <latexrelease>          {\label}{store five label arguments}%
169 <latexrelease>\let\@currenttitle\@undefined
170 <latexrelease>\let\@currenttarget\@undefined
171 <latexrelease>\let\@kernel@currentdata\@undefined
172 <latexrelease>\def\label#1{\@bsphack
173 <latexrelease> \protected@write\@auxout{%
174 <latexrelease>          {\string\newlabel{#1}{\@currentlabel}{\thepage}}}%
175 <latexrelease> \@esphack}
176 <latexrelease>\EndIncludeInRelease
177 <latexrelease>\IncludeInRelease{2020/10/01}%
178 <latexrelease>          {\Ref}{Add starred version}%
179 <latexrelease>\def\@currentcounter{}

```

<sup>40</sup>There is one problem with this approach: the braces are kept in a normal \ref which might spoil kerning. Perhaps one day this needs redoing.

```

180 <latexrelease>\def\refstepcounter#1{\stepcounter{#1}%
181 <latexrelease> \edef\@currentcounter{#1}%
182 <latexrelease> \protected@edef\@currentlabel
183 <latexrelease> {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
184 <latexrelease>}
185 <latexrelease>\def\labelformat#1{\expandafter\def\csname p@#1\endcsname##1}
186 <latexrelease>\DeclareRobustCommand\Ref[1]{\protected@edef\reserved@a{\ref{#1}}%
187 <latexrelease> \expandafter\MakeUppercase\reserved@a}
188 <latexrelease>\EndIncludeInRelease
189 <latexrelease>\IncludeInRelease{2019/10/01}%
190 <latexrelease> {\refstepcounter}{Add \labelformat and \Ref}%
191 <latexrelease>\let\@currentcounter\@undefined
192 <latexrelease>\def\refstepcounter#1{\stepcounter{#1}%
193 <latexrelease> \protected@edef\@currentlabel
194 <latexrelease> {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
195 <latexrelease>}
196 <latexrelease>\def\labelformat#1{\expandafter\def\csname p@#1\endcsname##1}
197 <latexrelease>\DeclareRobustCommand\Ref[1]{\protected@edef\reserved@a{\ref{#1}}%
198 <latexrelease> \expandafter\MakeUppercase\reserved@a}
199 <latexrelease>\EndIncludeInRelease
200 <latexrelease>\IncludeInRelease{0000/00/00}%
201 <latexrelease> {\refstepcounter}{Add \labelformat and \Ref}%
202 <latexrelease>
203 <latexrelease>\def\refstepcounter#1{\stepcounter{#1}%
204 <latexrelease> \protected@edef\@currentlabel
205 <latexrelease> {\csname p@#1\endcsname\csname the#1\endcsname}%
206 <latexrelease>}
207 <latexrelease>\let\labelformat\@undefined
208 <latexrelease>\let\Ref\@undefined
209 <latexrelease>
210 <latexrelease>\EndIncludeInRelease
211 <*2ekernel>

```

`\@currentlabel` Default for `\label` commands that come before any environment.

```

212 <def>\@currentlabel{}

```

*(End of definition for \@currentlabel.)*

```

213 </2ekernel>

```

## File 36

# ltproperties.dtx

### Abstract

This code implements command to record and (expandably) reference document properties. It extends the standard `\label/\ref/\pageref` commands.

## 1 Introduction

The module allows to record the “current state” of various document properties (typically the content of macros and values of counters) and to access them in other places through a label. The list of properties that can be recorded and retrieved are not fix and can be extended by the user. The values of the properties are recorded in the `.aux` file and can be retrieved at the second compilation.

The module uses the ideas of properties and labels. A label is a document reference point: a name for the user. An property is something that L<sup>A</sup>T<sub>E</sub>X can track, such as a page number, section number or name. The names of labels and properties may be arbitrary. Note that there is a single namespace for each.

## 2 Design discussion

The design here largely follows ideas from `zref`. In particular, there are two independent concepts: properties that can be recorded between runs, and labels which consist of lists of these properties. The reason for the split is that individual labels will want to record some but not all properties. For examples, a label concerned with position would track the  $x$  and  $y$  coordinates of the current point, but not for example the page number.

In the current implementation, properties share a single namespace. This allows multiple lists to re-use the same properties, for example page number, absolute page number, etc. This does mean that *changing* a standard property is an issue. However, some properties have complex definitions (again, see `zref` at present): having them in a single shared space avoids the need to copy code.

Labels could be implemented as `prop` data. That is not done at present as there is no obvious need to map to or copy the data. As such, faster performance is available using a hash table approach as in a “classical” set up. Data written to the `.aux` file uses simple paired *balanced text* not keyvals: this avoids any restrictions on names and again offers increased performance.

The `expl3` versions of the label command do not use `\@bsphack/\@esphack` to avoid double spaces, but the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> command does as it lives at the document command level.

The reference commands are expandable.

Currently the code has nearly no impact on the main `\label` and `\ref` commands as too many external packages rely on the concrete implementation. There is one exception: the label names share the same namespace. That means that if both `\label{ABC}` and `\RecordProperties{ABC}{page}` are used there is a warning Label ‘ABC’ multiply defined.

### 3 Handling unknown labels and properties

With the standard `\label/\ref` commands the requested label is either in the `.aux`-file (and so known) or not. In the first case the stored value can be used, in the second case the reference commands print two question marks.

With flexible property lists a reference commands asks for the value of a specific property stored under a label name and we have to consider more variants:

- If the requested property is unknown (not declared) the system is not correctly set up and an error is issued.
- If the label is unknown, the default of the property is used.
- If the label is known, but doesn't provide a value for the property then again the default of the property is used.
- The command `\property_ref:nnn` allows to give a local default which is used instead of the property default in the two cases before.

### 4 Rerun messages

As the reference commands are expandable they can neither issue a message that the label or the label-property combination is unknown, nor can they trigger the rerun message at the end of the  $\text{\LaTeX}$  run.

Where needed such messages must therefore be triggered manually. For this two commands are provided: `\property_ref_undefined_warn:` and `\property_ref_undefined_warn:nn`. See below for a description.

### 5 Open points

- The `xpos` and `ypos` properties require that the position is stored first but there is no (public) engine independent interface yet. Code must use `\tex_savepos:D`.

### 6 Code interfaces

---

<code>\property_new:nnnn</code>	<code>\property_new:nnnn {&lt;property&gt;} {&lt;setpoint&gt;} {&lt;default&gt;} {&lt;code&gt;}</code>
<code>\property_gset:nnnn</code>	<code>\property_gset:nnnn {&lt;property&gt;} {&lt;setpoint&gt;} {&lt;default&gt;} {&lt;code&gt;}</code>

---

$\text{\LaTeX} 2_{\epsilon}$ -interface: see `\NewProperty`, `\SetProperty`.

Sets the `<property>` to have the `<default>` specified, and at the `<setpoint>` (either `now` or `shipout`) to write the result of the `<code>` as part of a label. The `<code>` should be expandable. The expansion of `<code>` (the value of the property) is written to the `.aux` file and read back from there at the next compilation. Values should assume that the standard  $\text{\LaTeX}$  catcode régime with `@` a letter is active then.

If the property is declared within a package it is suggested that its name is build from letters, hyphens and slashes, and is always structured as follows:  
`<package-name>/<property-name>`.

---

<code>\property_record:nN</code>	<code>\property_record:nN {&lt;label&gt;} &lt;clist var&gt;</code>
<code>\property_record:nn</code>	<code>\property_record:nn {&lt;label&gt;} {&lt;clist&gt;}</code>
<code>\property_record:(nV ee)</code>	<p>LaTeX 2<sub>ε</sub>-interface: see <code>\RecordProperties</code>.</p> <p>Writes the list of properties given by the <code>&lt;clist&gt;</code> to the <code>.aux</code> file with the <code>&lt;label&gt;</code> specified.</p>

---

<code>\property_ref:nn *</code>	<code>\property_ref:nn {&lt;label&gt;} {&lt;property&gt;}</code>
<code>\property_ref:ee *</code>	<p>LaTeX 2<sub>ε</sub>-interface: see <code>\RefProperty</code>.</p> <p>Expands to the value of the <code>&lt;property&gt;</code> for the <code>&lt;label&gt;</code>, if available, and the default value of the property otherwise. If <code>&lt;property&gt;</code> has not been declared with <code>\property_new:nnnn</code> an error is issued. The command raises an internal, expandable, local flag if the reference can not be resolved.</p>

---

<code>\property_ref:nnn *</code>	<code>\property_ref:nnn {&lt;label&gt;} {&lt;property&gt;} {&lt;local default&gt;}</code>
<code>\property_ref:een *</code>	<p>LaTeX 2<sub>ε</sub>-interface: see <code>\RefProperty</code>.</p> <p>Expands to the value of the <code>&lt;property&gt;</code> for the <code>&lt;label&gt;</code>, if available, and to <code>&lt;local default&gt;</code> otherwise. If <code>&lt;property&gt;</code> has not been declared with <code>\property_new:nnnn</code> an error is issued. The command raises an internal, expandable local flag if the reference can not be resolved.</p>

---

<code>\property_ref_undefined_warn:</code>	<code>\property_ref_undefined_warn:</code>
	<p>LaTeX 2<sub>ε</sub>-interface: not provided.</p> <p>Triggers the standard warning</p> <p>LaTeX Warning: There were undefined references.</p> <p>at the end of the document if there was a recent <code>\property_ref:nn</code> or <code>\property_ref:nnn</code> which couldn't be resolved and so raised the flag. "Recent" means in the same group or in some outer group!</p>

---

<code>\property_ref_undefined_warn:n</code>	<code>\property_ref_undefined_warn:n {&lt;label&gt;}</code>
<code>\property_ref_undefined_warn:e</code>	
	<p>LaTeX 2<sub>ε</sub>-interface: not provided.</p> <p>Triggers the standard warning</p> <p>LaTeX Warning: There were undefined references.</p> <p>at the end of the document if <code>&lt;label&gt;</code> is not known. At the point where it is called it also issues the warning</p> <p>Reference '<code>&lt;label&gt;</code>' on page <code>&lt;page&gt;</code> undefined.</p>

---

<code>\property_ref_undefined_warn:nn</code>	<code>\property_ref_undefined_warn:nn {&lt;label&gt;} {&lt;property&gt;}</code>
<code>\property_ref_undefined_warn:ee</code>	
	<p>LaTeX 2<sub>ε</sub>-interface: see <code>\RefUndefinedWarn</code>.</p> <p>Triggers the standard warning</p> <p>LaTeX Warning: There were undefined references.</p> <p>at the end of the document if the reference can not be resolved. At the point where it is called it also issues the warning</p> <p>Reference '<code>&lt;label&gt;</code>' on page <code>&lt;page&gt;</code> undefined</p> <p>if the label is unknown, or the more specific</p> <p>Property '<code>&lt;property&gt;</code>' undefined for reference '<code>&lt;label&gt;</code>' on page <code>&lt;page&gt;</code></p> <p>if the label is known but doesn't provide a value for the requested property.</p>

---

<hr/>	
<code>\property_if_exist_p:n</code>	<code>* \property_if_exist_p:n {&lt;property&gt;}</code>
<code>\property_if_exist_p:e</code>	<code>* \property_if_exist:nTF {&lt;property&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\property_if_exist:nTF</code>	<code>* L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>-interface: \IfPropertyExistsTF.</code>
<code>\property_if_exist:eTF</code>	<code>* Tests if the &lt;property&gt; has been declared.</code>
<hr/>	
<code>\property_if_recorded_p:n</code>	<code>* \property_if_recorded_p:n {&lt;label&gt;}</code>
<code>\property_if_recorded_p:e</code>	<code>* \property_if_recorded:nTF {&lt;label&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\property_if_recorded:nTF</code>	<code>* </code>
<code>\property_if_recorded:eTF</code>	<code>* </code>
<hr/>	
	L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> -interface: \IfLabelExistsTF
	Tests if the <label> is known. This is also true if the label has been set with the standard \label command.
<hr/>	
<code>\property_if_recorded_p:nn</code>	<code>* \property_if_recorded_p:nn {&lt;label&gt;} {&lt;property&gt;}</code>
<code>\property_if_recorded_p:ee</code>	<code>* \property_if_recorded:nnTF {&lt;label&gt;} {&lt;property&gt;} {&lt;true code&gt;} {&lt;false code&gt;}</code>
<code>\property_if_recorded:nnTF</code>	<code>* </code>
<code>\property_if_recorded:eeTF</code>	<code>* </code>
<hr/>	
	L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> -interface: \IfPropertyRecordedTF.
	Tests if the label <label> is known and if it provides a value of the <property>.

## 7 Auxiliary file interfaces

<hr/>	
<code>\new@label@record</code>	<code>\new@label@record {&lt;label&gt;} {&lt;data&gt;}</code>
<hr/>	
	This is a command only for use in the .aux file. It loads the key–value list of <data> to be available for the <label>.

## 8 L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interface

The L<sup>A</sup>TeXe interfaces always expand label and property arguments. This means that one must be careful when using active chars or commands in the names. UTF8-chars are protected and should be safe, similar most babel shorthands.

<hr/>	
<code>\NewProperty</code>	<code>\NewProperty {&lt;property&gt;} {&lt;setpoint&gt;} {&lt;default&gt;} {&lt;code&gt;}</code>
<code>\SetProperty</code>	<code>\SetProperty {&lt;property&gt;} {&lt;setpoint&gt;} {&lt;default&gt;} {&lt;code&gt;}</code>
<hr/>	
	Sets the <property> to have the <default> specified, and at the <setpoint> (either now or shipout) to write the result of the <code> as part of a label. The <code> should be expandable. The expansion of <code> (the value of the property) is written to the .aux file and read back from there at the next compilation (at which point normally the standard L <sup>A</sup> T <sub>E</sub> X catcode régime with @ a letter is active).
<hr/>	
<code>\RecordProperties</code>	<code>\RecordProperties {&lt;label&gt;} {&lt;clist&gt;}</code>
<hr/>	
	Writes the list of properties given by the <clist> to the .aux file with the <label> specified. Similar to the standard \label command the arguments are expanded. So <clist> can be a macro containing a list of properties. Also similar to the standard \label command, the command is surrounded by an \@bsphack/\@esphack pair to preserve spacing.

<u><code>\RefProperty</code></u> ★	<code>\RefProperty</code> [ <i>⟨local default⟩</i> ] {⟨ <i>label</i> ⟩} {⟨ <i>property</i> ⟩}
	Expands to the value of the ⟨ <i>property</i> ⟩ for the ⟨ <i>label</i> ⟩, if available, and the default value of the property or – if given – to ⟨ <i>local default</i> ⟩ otherwise. If {⟨ <i>property</i> ⟩} has not been declared an error is issued.
<u><code>\IfPropertyExistsTF</code></u>	<code>\IfPropertyExistsTF</code> {⟨ <i>property</i> ⟩} {⟨ <i>true code</i> ⟩} {⟨ <i>false code</i> ⟩}
<u><code>\IfPropertyExistsT</code></u>	Tests if the ⟨ <i>property</i> ⟩ has been declared.
<u><code>\IfPropertyExistsF</code></u>	
<u><code>\IfLabelExistsTF</code></u>	<code>\IfLabelExistsTF</code> {⟨ <i>label</i> ⟩} {⟨ <i>true code</i> ⟩} {⟨ <i>false code</i> ⟩}
<u><code>\IfLabelExistsT</code></u>	Tests if the ⟨ <i>label</i> ⟩ has been recorded. This is also true if a label has been set with the standard <code>\label</code> command.
<u><code>\IfLabelExistsF</code></u>	
<u><code>\IfPropertyRecordedTF</code></u>	<code>\IfPropertyRecordedTF</code> {⟨ <i>label</i> ⟩} {⟨ <i>property</i> ⟩} {⟨ <i>true code</i> ⟩} {⟨ <i>false code</i> ⟩}
<u><code>\IfPropertyRecordedT</code></u>	Tests if the label and a value of the ⟨ <i>property</i> ⟩ for the ⟨ <i>label</i> ⟩ are both known.
<u><code>\IfPropertyRecordedF</code></u>	
<u><code>\RefUndefinedWarn</code></u>	<code>\RefUndefinedWarn</code> {⟨ <i>label</i> ⟩} {⟨ <i>property</i> ⟩}
	Triggers the standard warning LaTeX Warning: There were undefined references. at the end of the document if the reference for ⟨ <i>label</i> ⟩ and ⟨ <i>property</i> ⟩ can not be resolved. At the point where it is called it also issues the warning Reference ‘⟨ <i>label</i> ⟩’ on page ⟨ <i>page</i> ⟩ undefined if the label is unknown, or the more specific Property ‘⟨ <i>property</i> ⟩’ undefined for reference ‘⟨ <i>label</i> ⟩’ on page ⟨ <i>page</i> ⟩ if the label is known but doesn’t provide a value for the requested property.

## 9 Pre-declared properties

<u><code>abspage</code></u>	(shipout) The absolute value of the current page: starts at 1 and increases monotonically at each shipout.
<u><code>page</code></u>	(shipout) The current page as given by <code>\thepage</code> : this may or may not be a numerical value, depending on the current style. Contrast with <code>\abspage</code> . You get this value also with the standard <code>\label/\pageref</code> .
<u><code>pagenum</code></u>	(shipout) The current page as arabic number. This is suitable for integer operations and comparisons.
<u><code>label</code></u>	(now) The content of <code>\@currentlabel</code> . This is the value that you get also with the standard <code>\label/\ref</code> .

<u>title</u>	(now) The content of <code>\@currentlabelname</code> . This command is filled beside others by the <code>nameref</code> package and some classes (e.g. <code>memoir</code> ).
<u>target</u>	(now) The content of <code>\@currentHref</code> . This command is normally filled by for example <code>hyperref</code> and gives the name of the last destination it created.
<u>pagetarget</u>	(shipout) The content of <code>\@currentHpage</code> . This command is filled for example by a recent version of <code>hyperref</code> and then gives the name of the last page destination it created.
<u>counter</u>	(now) The content of <code>\@currentcounter</code> . This command contains after a <code>\refstepcounter</code> the name of the counter.
<u>xpos</u> <u>ypos</u>	(shipout) This stores the $x$ and $y$ coordinates of a point previously stored with <code>\pdfsavepos</code> / <code>\savepos</code> . E.g. (if <code>bidi</code> is used it can be necessary to save the position before and after the label):

```

\text_savepos:D
\property_record:nn{myposition}{xpos,ypos}
\text_savepos:D

```

## 10 The Implementation

```

1 <*2ekernel | latexrelease>
2 \ExplSyntaxOn
3 <@@=property>
4 <latexrelease>\NewModuleRelease{2023/11/01}{ltproperties}
5 <latexrelease>                                {Cross-referencing~properties}

```

The approach here is based closely on that from `zref`; separate out lists of properties and the properties themselves, so the latter can be used multiple times and in varying combinations. However, not everything is a straight copy. Firstly, we treat lists of properties as simple comma lists: that allows us to have either saved or dynamic lists and to avoid another data structure. The cost is that errors are detected at point-of-use, but in any real case that should be true anyway (and is true for `\zref@labelbyprop` already). Secondly, we allow properties to have arbitrary names, as the code does not require them to tokenize as control sequences.

`\property_new:nnnn` As properties can be reset, they are not constants. But they also have various pieces  
`\property_gset:nnnn` of required data. So we use the same approach as `color` and make them declarations.  
`\__property_gset:nnnn` Data-wise, we need the detail of the implementation, the default and a flag to show if  
the code works now or at shipout. This last entry is done using `text` so needs a check.  
We could use a set of `prop` here, but as we never need to map or copy the lists, we can  
gain performance using the hash table approach.

```

6 \cs_new_protected:Npn \property_new:nnnn #1#2#3#4

```

```

7   {
8     \cs_if_free:cTF { __property_code_ #1 : }
9     {
10      \exp_args:Nx \__property_gset:nnnn { \tl_to_str:n {#1} }
11      {#2} {#3} {#4}
12    }
13    {
14      \msg_error:nn { property }{ exists }{#1}
15    }
16  }
17  \cs_new_protected:Npn \property_gset:nnnn #1#2#3#4
18  {
19    \__property_gset:ennn { \tl_to_str:n {#1} }
20    {#2} {#3} {#4}
21  }
22  \cs_new_protected:Npn \__property_gset:nnnn #1#2#3#4
23  {
24    \cs_gset:cpn { __property_code_ #1 : } {#4}
25    \tl_gclear_new:c { g__property_default_ #1 _tl }
26    \tl_gset:cn { g__property_default_ #1 _tl } {#3}
27    \bool_if_exist:cF { g__property_shipout_ #1 _bool }
28    { \bool_new:c { g__property_shipout_ #1 _bool } }
29    \str_case:nnF {#2}
30    {
31      { now } { { \bool_gset_false:c { g__property_shipout_ #1 _bool } } }
32      { shipout }
33      { \bool_gset_true:c { g__property_shipout_ #1 _bool } }
34    }
35    { \msg_error:nnnn { property } { unknown-setpoint } {#1} {#2} }
36  }
37  \cs_generate_variant:Nn \__property_gset:nnnn {ennn}

```

(End of definition for \property\_new:nnnn, \property\_gset:nnnn, and \\_\_property\_gset:nnnn.  
These functions are documented on page 815.)

**\NewProperty** For consistency we expand the property name, but this doesn't warrant a variant of the  
**\SetProperty** L3-commands.

```

38  \cs_new_protected:Npn \NewProperty #1#2#3#4
39  {
40    \protected@edef\reserved@a{#1}
41    \exp_args:No \property_new:nnnn {\reserved@a} {#2}{#3}{#4}
42  }
43  \cs_new_protected:Npn \SetProperty #1#2#3#4
44  {
45    \protected@edef\reserved@a{#1}
46    \exp_args:No \property_gset:nnnn {\reserved@a} {#2}{#3}{#4}
47  }

```

(End of definition for \NewProperty and \SetProperty. These functions are documented on page 817.)

**\property\_record:nN** Writing data when it is labelled means expanding at this stage and possibly later too.  
**\property\_record:nn** That is all pretty easy using expl3: we accept a stray comma at the end of the list as  
**\property\_record:nV** that is easier to deal with than trying to tidy up, and there is no real downside.

```

48  \cs_new_protected:Npn \property_record:nN #1#2

```

```

\property_record:oo
\__property_record:nn
\__property_record:en
\__property_record_value:n
  \_property_record_value_aux:n
  \_property_record_value_aux:e

```

```

49 { \property_record:nV {#1} #2 }
50 \cs_new_protected:Npn \property_record:nn #1#2
51 { \__property_record:en { \tl_to_str:n {#1} } {#2} }
52 \cs_generate_variant:Nn \property_record:nn { nV , ee, oo }
53 \cs_new_protected:Npn \__property_record:nn #1#2
54 {
55   \protected@write \@auxout {}
56   {
57     \token_to_str:N \new@label@record
58     {#1}
59     { \clist_map_function:nN {#2} \__property_record_value:n }
60   }
61 }
62 \cs_generate_variant:Nn \__property_record:nn { e }
63 \cs_new:Npn \__property_record_value:n #1
64 { \__property_record_value_aux:e { \tl_to_str:n {#1} } }
65 \cs_new:Npn \__property_record_value_aux:n #1
66 {
67   \cs_if_exist:cTF { __property_code_ #1 : }
68   {
69     {#1}
70     {
71       \bool_if:cTF { g__property_shipout_ #1 _bool }
72       { \exp_not:c }
73       { \use:c }
74       { __property_code_ #1 : }
75     }
76   }
77   { \msg_expandable_error:nnn { property } { not-declared } {#1} }
78 }
79 \cs_generate_variant:Nn \__property_record_value_aux:n { e }

```

(End of definition for `\property_record:nN` and others. These functions are documented on page 816.)

## **\RecordProperties**

```

80 \NewDocumentCommand\RecordProperties { m m }
81 {
82   \@bsphack
83   \protected@edef\reserved@a{#1}
84   \protected@edef\reserved@b{#2}
85   \property_record:oo {\reserved@a}{\reserved@b}
86   \@esphack
87 }

```

(End of definition for `\RecordProperties`. This function is documented on page 817.)

## **10.1 Reference commands**

`l__property_ref_flag` A flag that is set if a reference couldn't be resolved.

```

88 \flag_new:n { l__property_ref_flag }

```

(End of definition for `l__property_ref_flag`.)

**\property\_ref:nn** Search for the label/property combination, and if not found fall back to the default of the property.

**\property\_ref:ee**

```

89 \cs_new:Npn \property_ref:nn #1#2
90 {
91   \__property_ref:een
92   { \tl_to_str:n {#1} }
93   { \tl_to_str:n {#2} }
94   { \tl_use:c { g__property_default_ #2 _tl } }
95 }
96 \cs_generate_variant:Nn \property_ref:nn {ee}

```

(End of definition for \property\_ref:nn. This function is documented on page 816.)

**\property\_ref:nnn** This allows to set a local default value which overrides the default value of the property.

**\property\_ref:een**

**\\_\_property\_ref:nnn**

**\\_\_property\_ref:een**

```

97 \cs_new:Npn \property_ref:nnn #1#2#3
98 {
99   \__property_ref:een
100   { \tl_to_str:n {#1} }
101   { \tl_to_str:n {#2} }
102   {#3}
103 }
104 \cs_new:Npn \__property_ref:nnn #1#2#3
105 {
106   \tl_if_exist:cTF { g__property_label_ #1 _ #2 _tl }
107   { \tl_use:c { g__property_label_ #1 _ #2 _tl } }
108   {
109     \flag_if_raised:nF
110     { l__property_ref_flag } { \flag_raise:n { l__property_ref_flag } }

```

We test for the default of the property only to check if the property has been declared.

```

111   \tl_if_exist:cTF { g__property_default_ #2 _tl }
112   { #3 }
113   { \msg_expandable_error:nnn { property } { not-declared } {#2} }
114 }
115 }
116 \cs_generate_variant:Nn \__property_ref:nnn { ee }
117 \cs_generate_variant:Nn \property_ref:nnn { een}

```

(End of definition for \property\_ref:nnn and \\_\_property\_ref:nnn. This function is documented on page 816.)

**\RefProperty** Search for the label/property combination, and if not found fall back to the default of the property or the given default.

```

118 \NewExpandableDocumentCommand \RefProperty { o m m }
119 {
120   \IfNoValueTF {#1}
121   {
122     \property_ref:ee {#2}{#3}
123   }
124   {
125     \property_ref:een {#2}{#3}{#1}
126   }
127 }

```

(End of definition for \RefProperty. This function is documented on page 818.)

```

\new@label@record A standard recursion loop.
\__property_data:nnn
128 \cs_new_protected:Npn \new@label@record #1#2
129 {
130   \tl_if_exist:cTF { r@#1 }
131   {
132     \gdef \@multiplelabels
133     { \@latex@warning@no@line { There-were-multiply-defined-labels } }
134     \@latex@warning@no@line { Label-‘#1’~multiply-defined }
135   }
136   {
137     \tl_new:c { r@#1 }
138     \tl_gset:cn { r@#1 }{#2}
139   }
140   \__property_data:nnn {#1} #2 { \q_recursion_tail } { ? } \q_recursion_stop
141 }
142 \cs_new_protected:Npn \__property_data:nnn #1#2#3
143 {
144   \quark_if_recursion_tail_stop:n {#2}
145   \tl_gclear_new:c { g__property_label_ \tl_to_str:n {#1} _ \tl_to_str:n {#2} _tl }
146   \tl_gset:cn { g__property_label_ \tl_to_str:n {#1} _ \tl_to_str:n {#2} _tl } {#3}
147   \__property_data:nnn {#1}
148 }

This command is used in \enddocument to test if some label values have changed.
149 \cs_new_protected:Npn \@kernel@new@label@record@testdef #1 #2
150 {
151   \tl_if_eq:cnF { r@#1 } {#2}
152   { \@tempwattrue }
153 }

```

(End of definition for \new@label@record and \\_\_property\_data:nnn. This function is documented on page 817.)

## 10.2 Tests and warnings

```

\property_if_exist_p:n Tests if property has been declared.
\property_if_exist:nTF
154 \prg_new_conditional:Npnn \property_if_exist:n #1 { p , T , F , TF }
155 % #1 property
156 {
157   \cs_if_exist:cTF { __property_code_ #1 : }
158   {
159     \prg_return_true:
160   }
161   {
162     \prg_return_false:
163   }
164 }
165 \prg_generate_conditional_variant:Nnn \property_if_exist:n {e} { p , T , F , TF }

(End of definition for \property_if_exist:nTF. This function is documented on page 817.)

```

```

\IfPropertyExistsTF
\IfPropertyExistsT
\IfPropertyExistsF
166 \cs_new_eq:NN \IfPropertyExistsTF \property_if_exist:eTF
167 \cs_new:Npn \IfPropertyExistsT #1#2 {\property_if_exist:eTF {#1}{#2}{}}
168 \cs_new:Npn \IfPropertyExistsF #1 {\property_if_exist:eTF {#1}{}}

```

(End of definition for `\IfPropertyExistsTF`, `\IfPropertyExistsT`, and `\IfPropertyExistsF`. These functions are documented on page 818.)

`\property_if_recorded_p:n` Tests if the label has been set. This can then be used to setup e.g. rerun messages.

```

\property_if_recorded:nTF
169 \prg_new_conditional:Npnn \property_if_recorded:n #1 { p , T , F , TF }
170   % #1 label
171   {
172     \tl_if_exist:cTF { r@#1 }
173     {
174       \prg_return_true:
175     }
176     {
177       \prg_return_false:
178     }
179   }
180 \prg_generate_conditional_variant:Nnn \property_if_recorded:n {e} { p , T , F , TF }

```

(End of definition for `\property_if_recorded:nTF`. This function is documented on page 817.)

`\IfLabelExistsTF`  
`\IfLabelExistsT`  
`\IfLabelExistsF`

```

181 \cs_new_eq:NN \IfLabelExistsTF \property_if_recorded:eTF
182 \cs_new:Npn \IfLabelExistsT #1#2 { \property_if_recorded:eTF {#1}{#2}{ } }
183 \cs_new:Npn \IfLabelExistsF #1 { \property_if_recorded:eTF {#1}{ } }

```

(End of definition for `\IfLabelExistsTF`, `\IfLabelExistsT`, and `\IfLabelExistsF`. These functions are documented on page 818.)

`\property_if_recorded_p:nn` tests if the label/property combination has been set This can then be used to setup  
`\property_if_recorded:nnTF` e.g. rerun messages.

```

184 \prg_new_conditional:Npnn \property_if_recorded:nn #1#2 { p , T , F , TF }
185   % #1 label #2 property
186   {
187     \tl_if_exist:cTF { g__property_label_ \tl_to_str:n {#1} _ \tl_to_str:n {#2} _tl }
188     {
189       \prg_return_true:
190     }
191     {
192       \prg_return_false:
193     }
194   }
195 \prg_generate_conditional_variant:Nnn \property_if_recorded:nn {ee} { p , T , F , TF }

```

(End of definition for `\property_if_recorded:nnTF`. This function is documented on page 817.)

`\IfPropertyRecordedTF`  
`\IfPropertyRecordedT`  
`\IfPropertyRecordedF`

```

196 \cs_new_eq:NN \IfPropertyRecordedTF \property_if_recorded:eeTF
197 \cs_new:Npn \IfPropertyRecordedT #1#2#3 { \property_if_recorded:eeTF {#1}{#2}{#3}{ } }
198 \cs_new:Npn \IfPropertyRecordedF #1#2#3 { \property_if_recorded:eeTF {#1}{#2}{ }{#3} }

```

(End of definition for `\IfPropertyRecordedTF`, `\IfPropertyRecordedT`, and `\IfPropertyRecordedF`. These functions are documented on page 818.)

`\property_ref_undefined_warn:` `\G@refundefinedtrue` is defined in `ltxref` and redefines a warning message.

```
199 \cs_new_protected:Npn \property_ref_undefined_warn:
200 {
201   \flag_if_raised:nT { l__property_ref_flag }
202   {
203     \G@refundefinedtrue
204   }
205 }
```

(End of definition for `\property_ref_undefined_warn:`. This function is documented on page 816.)

`\property_ref_undefined_warn:n`

```
\property_ref_undefined_warn:e
206 \cs_new_protected:Npn \property_ref_undefined_warn:n #1 %#1 label
207 {
208   \property_if_recorded:nF {#1}
209   {
210     \G@refundefinedtrue
211     \@latex@warning{Reference~‘#1’~on~page~\thepage\space undefined}%
212   }
213 }
214 \cs_generate_variant:Nn \property_ref_undefined_warn:n {e}
```

(End of definition for `\property_ref_undefined_warn:n`. This function is documented on page 816.)

`\property_ref_undefined_warn:nn`

```
\property_ref_undefined_warn:ee
\RefUndefinedWarn
215 \cs_new_protected:Npn \property_ref_undefined_warn:nn #1#2 %#1 label, #2 property
216 {
217   \property_if_recorded:nTF {#1}
218   {
219     \property_if_recorded:nnF {#1}{#2}
220     {
221       \G@refundefinedtrue
222       \@latex@warning
223       { Property~‘#2’~undefined~for~reference~‘#1’~on~page~\thepage }
224     }
225   }
226   {
227     \G@refundefinedtrue
228     \@latex@warning { Reference~‘#1’~on~page~\thepage\space undefined }%
229   }
230 }
231 \cs_generate_variant:Nn \property_ref_undefined_warn:nn {ee}
232 \cs_set_eq:NN \RefUndefinedWarn \property_ref_undefined_warn:ee
```

(End of definition for `\property_ref_undefined_warn:nn` and `\RefUndefinedWarn`. These functions are documented on page 816.)

## 10.3 Predeclared properties

`abspage`

```
233 \property_new:nnnn { abspage } { shipout }
234 { 0 } { \int_use:N \g_shipout_readonly_int }
```

(End of definition for `abspage`. This variable is documented on page 818.)

**page**

```
235 \property_new:nnnn { page } { shipout } { 0 } { \thepage }
```

*(End of definition for page. This variable is documented on page 818.)*

**pagenum**

```
236 \property_new:nnnn { pagenum } { shipout } { 0 } { \the \value { page } }
```

*(End of definition for pagenum. This variable is documented on page 818.)*

**label**

```
237 \property_new:nnnn { label } { now } { ?? } { \@currentlabel }
```

*(End of definition for label. This variable is documented on page 818.)*

**title**

```
238 \property_new:nnnn { title } { now }
```

```
239 { \exp_not:n { \textbf { ?? } } } { \@currentlabelname }
```

*(End of definition for title. This variable is documented on page 819.)*

**target**

```
240 \property_new:nnnn { target } { now } { } { \@currentHref }
```

*(End of definition for target. This variable is documented on page 819.)*

**pagetarget**

```
241 \newcommand\@currentHpage{}
```

```
242 \property_new:nnnn { pagetarget } { shipout } { } { \@currentHpage }
```

*(End of definition for pagetarget. This variable is documented on page 819.)*

**counter**

```
243 \property_new:nnnn { counter } { now } { } { \@currentcounter }
```

*(End of definition for counter. This variable is documented on page 819.)*

**xpos**

**ypos**

```
244 \property_new:nnnn { xpos } { shipout } { 0 } { \int_use:N \tex_lastxpos:D }
```

```
245 \property_new:nnnn { ypos } { shipout } { 0 } { \int_use:N \tex_lastypos:D }
```

*(End of definition for xpos and ypos. These variables are documented on page 819.)*

## 10.4 Messages

```

246 \msg_new:nnnn { property } { exists }
247   { Property~'#1'~ has~ already~ been~ declared. }
248   { There~ already~ exists~ a~ property~ declaration~ with~ this~
249     name.\\
250     Please~ use~ a~ different~ name~ for~ your~ property.}
251
252 \msg_new:nnnn { property } { not-declared }
253   { Property~'#1'~not-declared. }
254   {
255     LaTeX~has~been~asked~to~use~property~'#1',~but~this~
256     name~has~not~been~declared.
257   }
258 \msg_new:nnnn { property } { unknown-setpoint }
259   { Unknown~keyword~'#2'~for~setting~property~'#1'. }
260   {
261     LaTeX~has~been~asked~to~set~the~property~'#1',~but~the~keyword~
262     '#2'~is~not~one~of~the~two~known~values:~'now'~or~'shipout'.
263   }
264 %
265 <latexrelease>\IncludeInRelease{0000/00/00}{ltproperties}
266 <latexrelease>          {cross-referencing~properties~(undo)}%
267 <latexrelease>
268 <latexrelease>\let \NewProperty \@undefined
269 <latexrelease>\let \SetProperty \@undefined
270 <latexrelease>
271 <latexrelease>\let \RecordProperties \@undefined
272 <latexrelease>\let \RefProperty \@undefined
273 <latexrelease>\let \RefUndefinedWarn \@undefined
274 <latexrelease>
275 <latexrelease>\let \IfPropertyExistsTF \@undefined
276 <latexrelease>\let \IfLabelExistsTF \@undefined
277 <latexrelease>\let \IfPropertyRecordedTF \@undefined
278 <latexrelease>
279 <latexrelease>\let\new@label@record \@undefined
280 <latexrelease>\let\@kernel@new@label@record@testdef\@undefined
281 <latexrelease>\EndModuleRelease
282 \ExplSyntaxOff
283 </2ekernel | latexrelease>
284
285   Reset module prefix:
286   <@@=>

```

## File 37

# ltmiscen.dtx

## 1 Miscellaneous Environments

This section implements the basic environment mechanism, and also a few specific environments including `document`, The math environments and related commands, the ‘flushing’ environments, (`center`, `flushleft`, `flushright`), and `verbatim`.

```
1 <*2ekernel>
2 \message{environments,}
```

### 1.1 Environments

`\begin{foo}` and `\end{foo}` are used to delimit environment `foo`.

`\begin{foo}` starts a group and calls `\foo` if it is defined, otherwise it does nothing.

`\end{foo}` checks to see that it matches the corresponding `\begin` and if so, it calls `\endfoo` and does an `\endgroup`. Otherwise, `\end{foo}` does nothing.

If `\end{foo}` needs to ignore blanks after it, then `\endfoo` should globally set the `@ignore` switch true with `\@ignoretrue` (this will automatically be global).

NOTE: `\@@end` is defined to be the `\end` command of  $\text{\TeX}$ 82.

`\enddocument` is the user’s command for ending the manuscript file.

`\stop` is a panic button — to end  $\text{\TeX}$  in the middle.

*Historical  $\text{\LaTeX}$  2.09 comments (not necessarily accurate any more):*

```
\enddocument ==
BEGIN
  \@checkend{document}    %% checks for unmatched \begin
  \clearpage
  \begingroup
    if @filesw = true
    then close file @mainaux
    if G@refundefined = true
    then LaTeX Warning: 'There are undefined references.' fi
    if @multiplelabels = true
    then LaTeX Warning:
      'One or more label(s) multiply defined.'
    else
      \@setckpt {ARG1}{ARG2} == null
      \newlabel{LABEL}{VAL} ==
      BEGIN
        \reserved@a == VAL
        if def(\reserved@a) = def(\r@LABEL)
        else @tempswa := true          fi
      END
      \bibcite{LABEL}{VAL} == null
      BEGIN
        \reserved@a == VAL
        if def(\reserved@a) = def(\g@LABEL)
        else @tempswa := true          fi
    fi
  fi
\endgroup
```

```

                                END
                                @tempswa := false
                                make @ a letter
                                \input \jobname.AUX
                                if @tempswa = true
                                    then LaTeX Warning: 'Label may have changed.
                                                Rerun to get cross-references right.'
                                fi
                                fi
                                fi
                                \endgroup
                                finish up
                                END

                                \@writefile{EXT}{ENTRY} ==
                                    if tf@EXT undefined
                                        else \write\tf@EXT{ENTRY}
                                    fi
                                End of historical LATEX 2.09 comments.

\currentenvir The name of the current environment. Initialized to document to so that \end{document}
works correctly.
3 \def\currentenvir{document}

(End of definition for \currentenvir.)

\if@ignore
\@ignoretrue 4 \def\@ignorefalse{\global\let\if@ignore\iffalse}
\@ignorefalse 5 \def\@ignoretrue {\global\let\if@ignore\iftrue}
6 \@ignorefalse

(End of definition for \if@ignore, \@ignoretrue, and \@ignorefalse.)

\ignorespacesafterend
7 \let\ignorespacesafterend\@ignoretrue

(End of definition for \ignorespacesafterend.)

\document{document}
8 </2ekernel>
9 <*2ekernel | latexrelease>
10 <latexrelease>\IncludeInRelease{2023/11/01}%
11 <latexrelease> \enddocument}{check property labels}%
12 \def\enddocument{%

The \end{document} hook is executed first. If necessary it can contain a \clearpage to
output dangling floats first. In this position it can also contain something like \end{foo}
so that the whole document effectively starts and ends with some special environment.
However, this must be used with care, eg if two applications would use this without knowl-
edge of each other the order of the environments will be wrong after all. \AtEndDocument
is redefined at this point so that and such commands that get into the hook do not chase
their tail...

13 \@kernel@before@enddocument
14 \UseOneTimeHook{enddocument}%
15 \@kernel@after@enddocument

```

```

16 \checkend{document}%
17 \clearpage

18 \@kernel@before@enddocument@afterlastpage
19 \UseOneTimeHook{enddocument/afterlastpage}%
20 \@kernel@after@enddocument@afterlastpage
21 \begingroup
22   \if@filesw
23     \immediate\closeout\@mainaux
24     \let\@setckpt\@gobbletwo
25     \let\@newlabel\@testdef

26     \let\newlabel@record\@kernel@newlabel@record@testdef

```

The previous line is equiv to setting

```

\def\newlabel{\@testdef r}%
\def\bibcite{\@testdef b}%

```

We use \@input to load the .aux file, so that it doesn't show up in the list of files produced by \listfiles.

```

27   \@tempswafalse
28   \global\advance\c@page\@ne
29   \makeatletter \@input\jobname.aux
30   \fi
31   \UseOneTimeHook{enddocument/afteraux}%

```

Next hook is expect to contain only code for writing info messages on the terminal.

```

32   \UseOneTimeHook{enddocument/info}%
33   \endgroup
34   \UseOneTimeHook{enddocument/end}%
35   \deadcycles\z\@end}

```

The public hooks used in \enddocument:

```

36 \NewHook{enddocument}
37 \NewHook{enddocument/afterlastpage}
38 \NewHook{enddocument/afteraux}
39 \NewHook{enddocument/info}
40 \NewHook{enddocument/end}

```

This is one of the few places where we already add data and rules to a hook already in the kernel.

If we roll back we have to drop stuff before adding chunks, otherwise the code will just be appended, and thus doubled. This would result in a harmless warning during the format generation, because in that case the code chunk label doesn't exist, and therefore can't be dropped.

```

41 \<latexrelease>\RemoveFromHook{enddocument/info}[kernel/filelist]
42 \<latexrelease>\RemoveFromHook{enddocument/info}[kernel/warnings]
43 \<latexrelease>\RemoveFromHook{enddocument/info}[kernel/release]

44 \AddToHook{enddocument/info}[kernel/filelist]{\@dofilelist}
45 \AddToHook{enddocument/info}[kernel/warnings]{\@enddocument@kernel@warnings}
46 \AddToHook{enddocument/info}[kernel/release]{%
47   \let\show@release@info\wlog
48   \show@release@info{ *****}%
49   \the\LaTeXReleaseInfo

```

```

50 \show@release@info{ *****}
51
52 \DeclareHookRule{endddocument/info}{kernel/release}{before}{kernel/filelist}
53 \DeclareHookRule{endddocument/info}{kernel/filelist}{before}{kernel/warnings}

```

(End of definition for \endddocument.)

\@endddocument@kernel@warnings

```

54 \def\@endddocument@kernel@warnings{%

```

First we check for font size substitution bigger than \fontsubfuzz. The \relax is necessary because this is a macro not a register.

```

55 \ifdim \font@submax >\fontsubfuzz\relax

```

In case you wonder about the \@gobbletwo inside the message below, this is a horrible hack to remove the tokens \on@line. that are added by \@font@warning at the end.

```

56 \font@warning{Size substitutions with differences\MessageBreak
57 up to \font@submax\space have occurred.\@gobbletwo}%
58 \fi

```

The macro \@defaultsubs is initially \relax but gets redefined to produce a warning if there have been some default font substitutions.

```

59 \@defaultsubs

```

The macro \@refundefined is initially \relax but gets redefined to produce a warning if there are undefined refs.

```

60 \@refundefined

```

If a label is defined more than once, \@tempswa will always be true and thus produce a “Label(s) may ...” warning. But since a rerun will not solve that problem (unless one uses a package like varioref that generates labels on the fly), we suppress this message.

```

61 \if@files
62 \ifx \@multiplelabels \relax
63 \if@tempswa
64 \latex@warning@no@line{Label(s) may have changed.
65 Rerun to get cross-references right}%
66 \fi
67 \else
68 \@multiplelabels
69 \fi
70 \ifx \@extra@page@added \relax
71 \latex@warning@no@line{Temporary extra page added at the end.
72 Rerun to get it removed}%
73 \fi

```

We could think of adding a warning that nothing can be corrected while \nofiles is in force. In the past the warnings related to the aux file are simply suppressed in this case.

```

74 \fi
75 }

```

(End of definition for \@endddocument@kernel@warnings.)

```

76 </2kernel | latexrelease>
77 <latexrelease>\EndIncludeInRelease
78 <latexrelease>\IncludeInRelease{2020/10/01}%
79 <latexrelease> \endddocument}{Use Hooks}%

```

```

80 <latexrelease>\def\enddocument{%
81 <latexrelease>    \kernel@before@enddocument
82 <latexrelease>    \UseOneTimeHook{enddocument}%
83 <latexrelease>    \kernel@after@enddocument
84 <latexrelease>    \checkend{document}%
85 <latexrelease>    \clearpage
86 <latexrelease>    \UseOneTimeHook{enddocument/afterlastpage}%
87 <latexrelease>    \kernel@after@enddocument@afterlastpage
88 <latexrelease>    \begingroup
89 <latexrelease>        \if@filesw
90 <latexrelease>            \immediate\closeout\@mainaux
91 <latexrelease>            \let\@setckpt\@gobbletwo
92 <latexrelease>            \let\@newl@bel\@testdef
93 <latexrelease>            \@tempswafalse
94 <latexrelease>            \makeatletter \@@input\jobname.aux
95 <latexrelease>        \fi
96 <latexrelease>        \UseOneTimeHook{enddocument/afteraux}%
97 <latexrelease>        \UseOneTimeHook{enddocument/info}%
98 <latexrelease>    \endgroup
99 <latexrelease>    \UseOneTimeHook{enddocument/end}%
100 <latexrelease>    \deadcycles\z@\@@end}
101 <latexrelease>\NewHook{enddocument}
102 <latexrelease>\NewHook{enddocument/afterlastpage}
103 <latexrelease>\NewHook{enddocument/afteraux}
104 <latexrelease>\NewHook{enddocument/info}
105 <latexrelease>\NewHook{enddocument/end}

```

If we roll back we have to drop stuff before adding chunks, otherwise the code will just be appended, and thus doubled.

```

106 <latexrelease>\RemoveFromHook{enddocument/info}[kernel/filelist]
107 <latexrelease>\RemoveFromHook{enddocument/info}[kernel/warnings]
108 <latexrelease>\RemoveFromHook{enddocument/info}[kernel/release]

109 <latexrelease>\AddToHook{enddocument/info}[kernel/filelist]{\@dofilelist}
110 <latexrelease>\AddToHook{enddocument/info}[kernel/warnings]{\@enddocument@kernel@warnings}
111 <latexrelease>\AddToHook{enddocument/info}[kernel/release]{%
112 <latexrelease>    \let\show@release@info\wlog
113 <latexrelease>    \show@release@info{ *****}%
114 <latexrelease>    \the\LaTeXReleaseInfo
115 <latexrelease>    \show@release@info{ *****}}
116 <latexrelease>
117 <latexrelease>\DeclareHookRule{enddocument/info}{kernel/release}{before}{kernel/filelist}
118 <latexrelease>\DeclareHookRule{enddocument/info}{kernel/filelist}{before}{kernel/warnings}
119 <latexrelease>\def\@enddocument@kernel@warnings{%
120 <latexrelease>    \ifdim \font@submax >\fontsubfuzz\relax
121 <latexrelease>        \@font@warning{Size substitutions with differences\MessageBreak
122 <latexrelease>            up to \font@submax\space have occurred.\@gobbletwo}%
123 <latexrelease>    \fi
124 <latexrelease>    \@defaultsubs
125 <latexrelease>    \@refundefined
126 <latexrelease>    \if@filesw
127 <latexrelease>        \ifx \@multiplelabels \relax
128 <latexrelease>            \if@tempswa
129 <latexrelease>                \@latex@warning@no@line{Label(s) may have changed.
130 <latexrelease>                    Rerun to get cross-references right}%

```

```

131 <latexrelease> \fi
132 <latexrelease> \else
133 <latexrelease> \@multiplelabels
134 <latexrelease> \fi
135 <latexrelease> \ifx \@extra@page@added \relax
136 <latexrelease> \@latex@warning@no@line{Temporary extra page added at the end.
137 <latexrelease> Rerun to get it removed}%
138 <latexrelease> \fi
139 <latexrelease> \fi
140 <latexrelease>}
141 <latexrelease>\EndIncludeInRelease
142 <latexrelease>\IncludeInRelease{0000/00/00}%
143 <latexrelease> {\enddocument}{Use Hooks}%
144 <latexrelease>
145 <latexrelease>\def\enddocument{%
146 <latexrelease> \let\AtEndDocument\@firstofone
147 <latexrelease> \@enddocumenthook
148 <latexrelease> \@checkend{document}%
149 <latexrelease> \clearpage
150 <latexrelease> \begingroup
151 <latexrelease> \if@filesw
152 <latexrelease> \immediate\closeout\@mainaux
153 <latexrelease> \let\@setckpt\@gobbletwo
154 <latexrelease> \let\@newl@bel\@testdef
155 <latexrelease> \@tempswafalse
156 <latexrelease> \makeatletter \@@input\jobname.aux
157 <latexrelease> \fi
158 <latexrelease> \@dofilelist
159 <latexrelease> \ifdim \font@submax >\fontsubfuzz\relax
160 <latexrelease> \@font@warning{Size substitutions with differences\MessageBreak
161 <latexrelease> up to \font@submax\space have occurred.\@gobbletwo}%
162 <latexrelease> \fi
163 <latexrelease> \@defaultsubs
164 <latexrelease> \@refundefined
165 <latexrelease> \if@filesw
166 <latexrelease> \ifx \@multiplelabels \relax
167 <latexrelease> \if@tempswa
168 <latexrelease> \@latex@warning@no@line{Label(s) may have changed.
169 <latexrelease> Rerun to get cross-references right}%
170 <latexrelease> \fi
171 <latexrelease> \else
172 <latexrelease> \@multiplelabels
173 <latexrelease> \fi
174 <latexrelease> \fi
175 <latexrelease> \endgroup
176 <latexrelease> \deadcycles\z@\@@end}
177 <latexrelease>
178 <latexrelease>\let\@enddocument@kernel@warnings\@undefined
179 <latexrelease>
180 <latexrelease>\EndIncludeInRelease
181 <*2kernel>

```

`\@kernel@before@enddocument` The `\@kernel@before@enddocument` hook is slightly different because we initialize it with `\par` so that `\enddocument` always returns to vertical mode as its first action.

```

182 </2ekernel>
183 <*2ekernel | latexrelease>
184 <latexrelease>\IncludeInRelease{2021/06/01}%
185 <latexrelease>                {\@kernel@before@enddocument}{kernel before hook}%
186 \def\@kernel@before@enddocument{\par}
187 </2ekernel | latexrelease>
188 <latexrelease>\EndIncludeInRelease
    The rollback code renders it harmless.
189 <latexrelease>\IncludeInRelease{0000/00/00}%
190 <latexrelease>                {\@kernel@before@enddocument}{kernel before hook}%
191 <latexrelease>
192 <latexrelease>\let\@kernel@before@enddocument\@empty
193 <latexrelease>
194 <latexrelease>\EndIncludeInRelease
195 <*2ekernel>

```

*(End of definition for \@kernel@before@enddocument.)*

**\@testdef**

```

196 \def\@testdef #1#2#3{%
197   \def\reserved@a{#3}\expandafter \ifx \csname #1@#2\endcsname
198   \reserved@a \else \@tempswatrue \fi}

```

*(End of definition for \@testdef.)*

Reading data from auxiliary files (like `.toc` normally happens in vertical mode and it therefore doesn't matter if line endings are converted to spaces by  $\text{\TeX}$  during that process.

However, especially the `.toc` file might be read in L-R mode (in cases the `\tableofcontents` attempts to put, say, a list of sub-sections as a paragraph). In that case the newlines after a line like

```
\contentsline {subsubsection}{\numberline {1.1.1}A C-head}{2}
```

might result in spurious spaces (e.g., when that level is not included).

That could be fixed by reading in the file using `\endlinechar=-1` but that has the danger that it drops some valid endlines that should be converted to spaces (for example, when the user edited the TOC and then used `\nofiles` to preserve it).

So the approach taken instead is this:

- `\addcontentsline` adds the command `\protected@file@percent` to the end of the second argument of `\@writefile` that is written to the `.aux`. As the name indicates this is a protected macro so it doesn't change if it is written out.
- When the `.aux` is read back in at the end of the run, `\@writefile` is executed and writes its second argument unmodified to the file with the extension given by its first argument. Or rather that was how it was in the past.
- Instead we change `\@writefile` slightly: basically it looks at the second argument and if the last token in there is `\protected@file@percent` then it is replaced by a percent character and that is then written out. If not (for example, if the data came from a user issued `\addtocontents`, or from some package that uses `\@writefile` for writing its own files) then the command behaves exactly as before.

`\protected@file@percent` Dummy cs to be replaced by a percent sign inside `\@writefile`. If it survives (when used incorrectly) it will expand to nothing in a typsetting context.

```

199 </2ekernel>
200 <*2ekernel|latexrelease>
201 <latexrelease>\IncludeInRelease{2018/12/01}%
202 <latexrelease>          {\protected@file@percent}{Mask line endings}%
203 \protected\def\protected@file@percent{}

```

(End of definition for `\protected@file@percent`.)

`\add@percent@to@temptokena` Helper function which is used to inspect a sequence of tokens (the second argument of `\@writefile` and if the last token is `\protected@file@percent` it will replace it by a harmless percent. The result is saved in `\@temptokena` for later use.

```

204 \catcode'\^^A=9
205 \long\gdef\add@percent@to@temptokena
206   #1\protected@file@percent#2\add@percent@to@temptokena

```

When we call this macro in `\@writefile` we stick in `\@empty` at the beginning, so that in case the tokenlist consists of a single brace group the braces aren't stripped. The `\expandafter` then expands this extra token away again.

```

207   {\expandafter\ifx\expandafter X\detokenize{#2}X\expandafter\dont@add@percent@to@temptokena
208     \expandafter\do@add@percent@to@temptokena\fi{#1}}
209 \long\def\dont@add@percent@to@temptokena#1{%
210   \@temptokena\expandafter{#1}}

```

`latexrelease` will read this code in high-speed mode in certain situations. During that it will only look for `\if` tests but not actually execute the `\catcode` change above. As a result it will drop anything after the `%` character in the definition. Therefore the `\fi` needs to be on the next line and we need locally another comment character to avoid getting spaces into the definition—a weird problem :-)

```

211 \begingroup
212 \catcode'\%=12
213 \catcode'\^^A=14
214 \long\gdef\do@add@percent@to@temptokena#1{\@temptokena\expandafter{#1}\^^A

```

Can't be on the same line as the `%` — see above.

```

215   }}
216 \endgroup

```

(End of definition for `\add@percent@to@temptokena`.)

`\@writefile`

```

217 \long\def\@writefile#1#2{%
218   \@ifundefined{tf@#1}\relax
219   {%

```

If we write to the file we first prepare `#2` using `\add@percent@to@temptokena` and then write the token register out.

```

220     \add@percent@to@temptokena
221     \@empty#2\protected@file@percent
222     \add@percent@to@temptokena
223     \immediate\write\csname tf@#1\endcsname{\the\@temptokena}%
224   }%
225 }

```

```

226 </2ekernel | latexrelease>
227 <latexrelease>\EndIncludeInRelease
228 <latexrelease>\IncludeInRelease{0000/00/00}%
229 <latexrelease>          {\protected@file@percent}{Mask line endings}%
230 <latexrelease>\let\protected@file@percent\@undefined
231 <latexrelease>\let\add@percent@to@temptokena\@undefined
232 <latexrelease>\let\do@add@percent@to@temptokena\@undefined
233 <latexrelease>\let\dont@add@percent@to@temptokena\@undefined
234 <latexrelease>\long\def\@writefile#1#2{%
235 <latexrelease>  \ifundefined{tf@#1}\relax
236 <latexrelease>    {\@temptokena{#2}%
237 <latexrelease>      \immediate\write\csname tf@#1\endcsname{\the\@temptokena}%
238 <latexrelease>    }%
239 <latexrelease>}}
240 <latexrelease>\EndIncludeInRelease
241 <*2ekernel>

```

(End of definition for \@writefile.)

\stop

```

242 \def\stop{\clearpage\deadcycles\z@\let\par\@@par\@@end}

```

(End of definition for \stop.)

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

243 \everypar{\@nodocument} %% To get an error if text appears before the
244 \nullfont                %% \begin{document}

```

\begin, \end, and \@checkend changed so \end{document} will catch an unmatched \begin. Changed 24 May 89 as suggested by Frank Mittelbach and Rainer Sch\"opf.

```

\begin{NAME} ==
BEGIN
  IF \NAME undefined THEN \reserved@a == BEGIN report error END
  ELSE \reserved@a ==
    (\@currenvir :=L NAME) \NAME
  FI
  @ignore :=G F      %% Added 30 Nov 88
  \begingroup
  \@endpe := F
  \@currenvir :=L NAME
  \NAME
END

```

```

\end{NAME} ==
BEGIN
  \endNAME
  \@checkend{NAME}
  \endgroup
  IF @endpe = T      %% @endpe set True by \@endparenv

```

```

        THEN \@doendpe          %% \@doendpe redefines \par and \everypar
                                %% to suppress paragraph indentation in
        FI                      %% immediately following text
        IF @ignore = T
            THEN @ignore :=G F
                \ignorespaces
        FI
    END

\@checkend{NAME} ==
BEGIN
    IF \@currenvir = NAME
        ELSE \@badend{NAME}
    FI
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

\begin
245 </2kernel>
246 <*2kernel | latexrelease>
247 <latexrelease>\IncludeInRelease{2020/10/01}%
248 <latexrelease>          {\begin}{Use hook system}%
249 \protected\def\begin#1{%
250     \UseHook{env/#1/before}%
251     \@ifundefined{#1}%
252         {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
253         {\def\reserved@a{\def\@currenvir{#1}%
254             \edef\@currenvline{\on@line}%
255             \@execute@begin@hook{#1}%
256             \csname #1\endcsname}}}%
257     \@ignorefalse
258     \begingroup\@endpfalse\reserved@a}

```

Before the `\document` code is executed we have to first undo the `\endgroup` as there should be none for this environment to avoid that changes on top-level unnecessarily go to T<sub>E</sub>X's savestack, and we have to initialize all hooks in the hook system. So we need to test for this environment name. But once it has been found all this testing is no longer needed and so we redefine `\@execute@begin@hook` to simply use the hook.

```

259 \def\@execute@begin@hook #1{%
260     \expandafter\ifx\csname #1\endcsname\document
261         \endgroup
262         \gdef\@execute@begin@hook##1{\UseHook{env/##1/begin}}%
263         \expl@@@initialize@all@@
264     \fi

```

If this is an environment before `\begin{document}` we just run the hook so this can be outside the test.

```

265     \UseHook{env/#1/begin}%
266 }
267 </2kernel | latexrelease>
268 <latexrelease>\EndIncludeInRelease

```

```

269 <latexrelease>\IncludeInRelease{2019/10/01}%
270 <latexrelease>          {\begin}{Making \begin/\end robust}%
271 <latexrelease>\DeclareRobustCommand\begin[1]{%
272 <latexrelease>  \ifundefined{#1}%
273 <latexrelease>    {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
274 <latexrelease>    {\def\reserved@a{\def\@currentvir{#1}%
275 <latexrelease>      \edef\@currentvline{\on@line}%
276 <latexrelease>      \csname #1\endcsname}}}%
277 <latexrelease>  \ignorefalse
278 <latexrelease>  \begingroup\@endpfalse\reserved@a}
279 <latexrelease>\EndIncludeInRelease

```

A version that doesn't start out with `\relax` when in typesetting mode would be the following, but since `\begin` issues a `\begingroup` it wouldn't help much with respect to allowing things like `\noalign` or `\multicolumn` inside.

```

280 %\edef\begin
281 %  {\unexpanded{%
282 %    \ifx\protect\@typeset@protect
283 %      \expandafter\@gobble
284 %    \fi
285 %    \protect
286 %  }}%
287 %  \expandafter\noexpand\csname begin \endcsname
288 %  }
289 %\@namedef{begin }#1{%
290 %  \ifundefined{#1}%
291 %    {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
292 %    {\def\reserved@a{\def\@currentvir{#1}%
293 %      \edef\@currentvline{\on@line}%
294 %      \csname #1\endcsname}}}%
295 %  \ignorefalse
296 %  \begingroup\@endpfalse\reserved@a}
297 <latexrelease>\IncludeInRelease{0000/00/00}%
298 <latexrelease>          {\begin}{Making \begin/\end robust}%
299 <latexrelease>\def\begin#1{%
300 <latexrelease>  \ifundefined{#1}%
301 <latexrelease>    {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
302 <latexrelease>    {\def\reserved@a{\def\@currentvir{#1}%
303 <latexrelease>      \edef\@currentvline{\on@line}%
304 <latexrelease>      \csname #1\endcsname}}}%
305 <latexrelease>  \ignorefalse
306 <latexrelease>  \begingroup\@endpfalse\reserved@a}
307 <latexrelease>

```

Also undo the internal commands as some packages unfortunately test for their existence instead of using `\IfFormatAtLeastTF`.

```

308 <latexrelease>\expandafter\let\csname begin \endcsname\@undefined
309 <latexrelease>
310 <latexrelease>\EndIncludeInRelease
311 <*2ekernel>

```

*(End of definition for \begin.)*

`\end` The top level definition for `\end`.

```

312 </2ekernel>
313 <*2ekernel | latexrelease>
314 <latexrelease>\IncludeInRelease{2019/10/01}%
315 <latexrelease>          {\end}{Making \begin/\end robust}%

```

While `\begin` was made robust simply by using `\DeclareRobustCommand` we need to be a bit more subtle with `\end` as there are packages out there that try to look into the top-level contents of `\end{foo}` (that is at the expansion of `\endfoo`) to see if it contains certain macros. This is done by hitting `\end{foo}` with three `\expandafters`, the first to get

```
\csname endfoo\endcsname          \@checkend{foo}% etc.
```

the second to expand the `\csname`, i.e., to get to

```
\endfoo                          \@checkend{foo}% etc.
```

and the third to finally get to the top-level content of `\endfoo`, i.e.

```
<top-level content of \endfoo> \@checkend{foo}% etc.
```

Therefore a robust replacement should produce the same results after three expansions (there first is obviously different).

Basically the definition of `\end` should either produce `\protect\end_` (when not doing typesetting) or it should produce `\end_` (without the `\protect`) when doing typesetting. Furthermore, it should (when in typesetting mode) show exactly the same result as `\end_` (which is the original fragile definition of `\end`) when you expand either of them twice, i.e.,

```
\endfoo                          \@checkend{foo}% etc.
```

That is achieved with the code below (which is worth studying carefully).

There is some trickery involved here: in particular we use `\romannumeral` to change a single expansion into three successive expansions in one go. That primitive expands until it has scanned a number (0 in this case, so it doesn't produce any output) and so it allows us to place arbitrary many `\expandafters` inside that are all going to be executed when `\romannumeral` is hit by a single `\expandafter`.

```

316 \edef\end
317   {\unexpanded{%
318     \romannumeral
319     \ifx\protect\@typeset@protect
320       \expandafter      %1
321       \expandafter      %2
322       \expandafter      %1
323       \expandafter      %3 expands the \csname inside \end<space>
324       \expandafter      %1
325       \expandafter      %2 expands \end<space>
326       \expandafter      %1 expands the \else
327       \z@
328     \else
329       \expandafter\z@\expandafter\protect
330     \fi
331   }%
332   \expandafter\noexpand\csname end \endcsname
333 }
334 </2ekernel | latexrelease>
335 <latexrelease>\EndIncludeInRelease

```

And here is the original definition of `\end` the way it was in L<sup>A</sup>T<sub>E</sub>X for several decades now hidden in `\end_`.

```

336 <latexrelease>\IncludeInRelease{0000/00/00}%
337 <latexrelease>          {\end}{Making \begin/\end robust}%
338 <latexrelease>\def\end#1{%
339 <latexrelease>  \csname end#1\endcsname\@checkend{#1}%
340 <latexrelease>  \expandafter\endgroup\if@endpe\@doendpe\fi
341 <latexrelease>  \if@ignore\@ignorefalse\ignorespaces\fi}
342 <latexrelease>
343 <latexrelease>\EndIncludeInRelease
344 <*2ekernel>

```

(End of definition for `\end`.)

`\end\verbvisiblespace` The internal version with a space at the end.

```

345 </2ekernel>
346 <*2ekernel | latexrelease>
347 <latexrelease>\IncludeInRelease{2024/11/01}%
348 <latexrelease>          {\end!space}{New @endpe handling}%
349 \@namedef{end }#1{%
350   \romannumeral
351   \IfHookEmptyTF{env/#1/end}%
352     {\expandafter\z@}%
353     {\z@\UseHook{env/#1/end}}}%
354   \csname end#1\endcsname\@checkend{#1}%

```

We can now close the environment group and due to the new `\if@endpe` handling we no longer need to `\expandafter` out of the group.

```

355 %   \expandafter\endgroup\if@endpe\@doendpe\fi
356   \endgroup
357   \UseHook{env/#1/after}%
358   \if@ignore\@ignorefalse\ignorespaces\fi
359 }
360 </2ekernel | latexrelease>
361 <latexrelease>\EndIncludeInRelease

```

Version that adds hooks (so different from the 2019 version). It fixes tlb3722 but the change should perhaps be made in `tabularx` instead.

```

362 %   \begin{macrocode}
363 <latexrelease>\IncludeInRelease{2020/10/01}%
364 <latexrelease>          {\end!space}{Use hook system}%
365 <latexrelease>
366 <latexrelease>\@namedef{end }#1{%
367 <latexrelease>  \romannumeral
368 <latexrelease>    \IfHookEmptyTF{env/#1/end}%
369 <latexrelease>      {\expandafter\z@}%
370 <latexrelease>      {\z@\UseHook{env/#1/end}}}%
371 <latexrelease>    \csname end#1\endcsname\@checkend{#1}%
372 <latexrelease>    \expandafter\endgroup\if@endpe\@doendpe\fi
373 <latexrelease>    \UseHook{env/#1/after}%
374 <latexrelease>    \if@ignore\@ignorefalse\ignorespaces\fi
375 <latexrelease>}
376 <latexrelease>\EndIncludeInRelease

```

Version without the fix for tlb3722 for the record:

```

@namedef{end }#1{%
  \UseHook{env/#1/end}%
  \csname end#1\endcsname\@checkend{#1}%
  \expandafter\endgroup\if@endpe\@doendpe\fi
  \UseHook{env/#1/after}%
  \if@ignore\@ignorefalse\ignorespaces\fi}%

377 <latexrelease>\IncludeInRelease{2019/10/01}%
378 <latexrelease>          {\end!space}{Making \begin/\end robust}%
379 <latexrelease>
380 <latexrelease>\@namedef{end }#1{%
381 <latexrelease>  \csname end#1\endcsname\@checkend{#1}%
382 <latexrelease>  \expandafter\endgroup\if@endpe\@doendpe\fi
383 <latexrelease>  \if@ignore\@ignorefalse\ignorespaces\fi}
384 <latexrelease>\EndIncludeInRelease

385 <latexrelease>\IncludeInRelease{0000/00/00}%
386 <latexrelease>          {\end!space}{Making \begin/\end robust}%

```

Undo the internal command as some packages unfortunately test for their existence instead of using `\IfFormatAtLeastTF`.

```

387 <latexrelease>\expandafter\let\csname end \endcsname\@undefined
388 <latexrelease>
389 <latexrelease>\EndIncludeInRelease
390 <*2ekernel>

```

*(End of definition for \end\verbvisiblespace.)*

`\@checkend`

```

391 \def\@checkend#1{\def\reserved@a{#1}\ifx
392   \reserved@a\@currenvir \else\@badend{#1}\fi}

```

*(End of definition for \@checkend.)*

`\@currenvline` We do need a default value for `\@currenvline` on top-level since the document environment cancels the brace group. This means that a mismatch with `\begin{document}` will not produce a line number. Thus the outer default must be `\@empty` or we will end up with two spaces.

```

393 \let\@currenvline\@empty

```

*(End of definition for \@currenvline.)*

`\AtBeginEnvironment` We provide 4 high-level hook interfaces directly, the others only when etoolbox is loaded

```

\AtEndEnvironment 394 </2ekernel>
\BeforeBeginEnvironment 395 <*2ekernel | latexrelease>
\AfterEndEnvironment 396 <latexrelease>\IncludeInRelease{2020/10/01}%
397 <latexrelease>          {\AtBeginEnvironment}{Hooks for environments}%

398 \newcommand\AtBeginEnvironment[2][.] {\AddToHook{env/#2/begin}[#1]}
399 \newcommand\AtEndEnvironment[2][.]   {\AddToHook{env/#2/end}[#1]}
400 \newcommand\BeforeBeginEnvironment[2][.]{\AddToHook{env/#2/before}[#1]}
401 \newcommand\AfterEndEnvironment[2][.]{\AddToHook{env/#2/after}[#1]}

402 </2ekernel | latexrelease>
403 <latexrelease>\EndIncludeInRelease

```

```

404 <latexrelease>\IncludeInRelease{0000/00/00}%
405 <latexrelease>                {\AtBeginEnvironment}{Hooks for environments}%
406 <latexrelease>
407 <latexrelease>\let\AtBeginEnvironment\@undefined
408 <latexrelease>\let\AtEndEnvironment\@undefined
409 <latexrelease>\let\BeforeBeginEnvironment\@undefined
410 <latexrelease>\let\AfterEndEnvironment\@undefined
411 <latexrelease>
412 <latexrelease>\EndIncludeInRelease
413 <*2ekernel>

```

(End of definition for `\AtBeginEnvironment` and others. These functions are documented on page 225.)

## 1.2 Center, Flushright, Flushleft

```

414 \message{center,}

```

Historical *LaTeX* 2.09 comments (not necessarily accurate any more):

```

\center, \flushright and \flushleft set
  \rightskip = 0pt or \@flushglue (as appropriate)
  \leftskip  = 0pt or \@flushglue (as appropriate)
  \parindent = 0pt
  \parfillskip = 0pt. (except \flushleft)
  \\\          == \par \vskip -\parskip
  \|[LENGTH] == \\\ \vskip LENGTH
  \\\*         == \par \penalty 10000 \vskip -\parskip
  \\\*[LEN]    == \\\* \vskip LENGTH

```

They invoke the `trivlist` environment to handle vertical spacing before and after them.

`\centering`, `\raggedright` and `\raggedleft` are the declaration analogs of the above.

`\raggedright` has a more universal effect, however. It sets `\@rightskip := flushglue`. Every environment, like the list environments, that set `\rightskip` to its 'normal' value set it to `\@rightskip`

End of historical *LaTeX* 2.09 comments.

`\@centercr`

```

415 </2ekernel>
416 <*2ekernel | latexrelease>
417 <latexrelease>\IncludeInRelease{2020/02/02}%
418 <latexrelease>                {\@centercr}{Make robust}%
419 \protected\def\@centercr{\ifhmode \unskip\else \@nolnerr\fi
420   \par\@ifstar{\nobreak\@xcentercr}\@xcentercr}
421 </2ekernel | latexrelease>

```

```

422 <latexrelease>\EndIncludeInRelease
423 <latexrelease>\IncludeInRelease{0000/00/00}%
424 <latexrelease>          {\@centercr}{Make robust}%
425 <latexrelease>
426 <latexrelease>\def\@centercr{\ifhmode \unskip\else \@nolnerr\fi
427 <latexrelease>          \par\@ifstar{\nobreak\@xcentercr}\@xcentercr}
428 <latexrelease>
429 <latexrelease>\EndIncludeInRelease
430 <*2ekernel>

```

*(End of definition for \@centercr.)*

**\@xcentercr**

```

431 \def\@xcentercr{\addvspace{-\parskip}\@ifnextchar
432   [\@icentercr\ignorespaces}

```

*(End of definition for \@xcentercr.)*

**\@icentercr**

```

433 </2ekernel>
434 <*2ekernel | latexrelease>
435 <latexrelease>\IncludeInRelease{2020/10/01}%
436 <latexrelease>          {\@icentercr}{centering, etc support calc}%
437 \def\@icentercr[#1]{\@vspace@calcify{#1}\ignorespaces}
438 </2ekernel | latexrelease>
439 <latexrelease>\EndIncludeInRelease
440 <latexrelease>\IncludeInRelease{0000/00/00}%
441 <latexrelease>          {\@icentercr}{centering, etc support calc}%
442 <latexrelease>
443 <latexrelease>\def\@icentercr[#1]{\vskip #1\ignorespaces}
444 <latexrelease>\EndIncludeInRelease
445 <*2ekernel>

```

*(End of definition for \@icentercr.)*

**center** (*env.*) We use \relax to prevent \item scanning too far.

```

446 \def\center{\trivlist \centering\item\relax}
447 \def\endcenter{\endtrivlist}
448 </2ekernel>
449 <*2ekernel | latexrelease>
450 <latexrelease>\IncludeInRelease{2020/10/01}%
451 <latexrelease>          {\centering}{Set finaldhyphenemerits}%

```

**\centering**

```

452 \DeclareRobustCommand\centering{%
453   \let\\ \@centercr
454   \rightskip\@flushglue\leftskip\@flushglue
455   \finalhyphenemerits=\z@
456   \parindent\z@\parfillskip\z@skip}

```

*(End of definition for \centering.)*

`\raggedright`

```
457 \DeclareRobustCommand\raggedright{%
458   \let\\@centercr\@rightskip\@flushglue \rightskip\@rightskip
459   \finalhyphendemerits=\z@
460   \leftskip\z@skip
461   \parindent\z@}
```

*(End of definition for \raggedright.)*

`\raggedleft`

```
462 \DeclareRobustCommand\raggedleft{%
463   \let\\@centercr
464   \rightskip\z@skip\leftskip\@flushglue
465   \finalhyphendemerits=\z@
466   \parindent\z@\parfillskip\z@skip}
```

*(End of definition for \raggedleft.)*

```
467 </2ekernel | latexrelease>
468 <latexrelease>\EndIncludeInRelease
469 <latexrelease>\IncludeInRelease{2019/10/01}%
470 <latexrelease>           {\centering}{Make commands robust}%
471 <latexrelease>
472 <latexrelease>\DeclareRobustCommand\centering{%
473 <latexrelease>  \let\\@centercr
474 <latexrelease>  \rightskip\@flushglue\leftskip\@flushglue
475 <latexrelease>  \parindent\z@\parfillskip\z@skip}
476 <latexrelease>\DeclareRobustCommand\raggedright{%
477 <latexrelease>  \let\\@centercr\@rightskip\@flushglue \rightskip\@rightskip
478 <latexrelease>  \leftskip\z@skip
479 <latexrelease>  \parindent\z@}
480 <latexrelease>\DeclareRobustCommand\raggedleft{%
481 <latexrelease>  \let\\@centercr
482 <latexrelease>  \rightskip\z@skip\leftskip\@flushglue
483 <latexrelease>  \parindent\z@\parfillskip\z@skip}
484 <latexrelease>\EndIncludeInRelease
485 <latexrelease>
486 <latexrelease>\IncludeInRelease{0000/00/00}%
487 <latexrelease>           {\centering}{Make commands robust}%
488 <latexrelease>
489 <latexrelease>\kernel@make@fragile\centering
490 <latexrelease>\kernel@make@fragile\raggedright
491 <latexrelease>\kernel@make@fragile\raggedleft
492 <latexrelease>
493 <latexrelease>\EndIncludeInRelease
494 <*2ekernel>
```

`\@rightskip`

```
495 \newskip\@rightskip \@rightskip \z@skip
```

*(End of definition for \@rightskip.)*

`flushleft (env.)` We use `\relax` to prevent `\item` scanning too far.

```
496 \def\flushleft{\trivlist \raggedright\item\relax}
497 \def\endflushleft{\endtrivlist}
```

`flushright` (*env.*) We use `\relax` to prevent `\item` scanning too far.

```
498 \def\flushright{\trivlist \raggedleft\item\relax}
499 \def\endflushright{\endtrivlist}
```

### 1.3 Verbatim

```
500 \message{verbatim,}
```

The verbatim environment uses the fixed-width `\ttfamily` font, turns blanks into spaces, starts a new line for each carriage return (or sequence of consecutive carriage returns), and interprets *every* character literally. I.e., all special characters `\`, `{`, `$`, etc. are `\catcode`'d to 'other'.

The command `\verb` produces in-line verbatim text, where the argument is delimited by any pair of characters. E.g., `\verb #...#` takes '...' as its argument, and sets it verbatim in `\ttfamily` font.

The \*-variants of these commands are the same, except that spaces print as the  $\TeX$ book's space character instead of as blank spaces.

`\@vobeyspaces`

`\@vobeytabs`

```
501 </2ekernel>
502 <latexrelease>\IncludeInRelease{2023/11/01}%
503 <latexrelease>          {\@vobeytabs}{Obeyed tabs}%
504 <*2ekernel | latexrelease>
505 {\catcode'\ =\active%
506 \gdef\@vobeyspaces{\catcode'\ \active\let \@xobeysp\@vobeytabs}}
507 {\catcode'\^~I=\active
508 \gdef\@vobeytabs{\catcode'\^~I\active\let^~I\@xobeytab}%
509 \global\let^~I=\space
510 }
511 </2ekernel | latexrelease>
512 <latexrelease>\EndIncludeInRelease
513 <latexrelease>\IncludeInRelease{0000/00/00}%
514 <latexrelease>          {\@vobeytabs}{Obeyed tabs}%
515 <latexrelease>{\catcode'\ =\active%
516 <latexrelease>\gdef\@vobeyspaces{\catcode'\ \active\let \@xobeysp}}
517 <latexrelease>\let\@vobeytabs\@undefined
518 <latexrelease>\EndIncludeInRelease
519 <*2ekernel>
```

(End of definition for \@vobeyspaces and \@vobeytabs.)

`\@xobeysp`

(End of definition for \@xobeysp.)

`\@xverbatim`

`\@sxverbatim`

```
520 \begingroup \catcode '|=0 \catcode '[= 1
521 \catcode']=2 \catcode '\{=12 \catcode '\}=12
522 \catcode'\=12 |gdef|@xverbatim#1\end{verbatim}][#1|end[verbatim]]
523 |gdef|@sxverbatim#1\end{verbatim*}][#1|end[verbatim*]]
524 |endgroup
```

(End of definition for \@xverbatim and \@sxverbatim.)

`\@verbatim` Real start of verbatim environment We use `\relax` to prevent `\item` scanning too far.

```

525 </2kernel>
526 <*2kernel | latexrelease>
527 <latexrelease>\IncludeInRelease{2017-04-15}{\@verbatim}%
528 <latexrelease>          {Disable hyphenation in verbatim}%
529 \def\@verbatim{\trivlist \item\relax
530   \if@minipage\else\vskip\parskip\fi
531   \leftskip\@totalleftmargin\rightskip\z@skip
532   \parindent\z@\parfillskip\@flushglue\parskip\z@skip

```

Added `\@@par` to clear possible `\parshape` definition from a surrounding list (the verbatim guru says). Switch language when in vertical mode.

```

533   \@@par

```

Set `\language` here to suppress hyphenation. Done this way rather than setting `\hyphenchar` as that is a global setting.

```

534   \language\l@nohyphenation
535   \@tempswafalse
536   \def\par{%
537     \if@tempswa

```

A `\leavevmode` added: needed if, for example, a blank verbatim line is the first thing in a list item (wow!).

```

538       \leavevmode \null \@@par\penalty\interlinepenalty
539     \else
540       \@tempswatrue
541     \ifhmode\@@par\penalty\interlinepenalty\fi
542   \fi}%

```

To allow customization we hide the font used in a separate macro.

```

543   \let\do\@makeother \dospecials
544   \obeylines \verbatim@font \@noligs

```

To avoid a breakpoint after the labels box, we remove the penalty put there by the list macros: another use of `\unpenalty`!

```

545   \everypar \expandafter{\the\everypar \unpenalty}%
546 }
547 </2kernel | latexrelease>
548 <latexrelease>\EndIncludeInRelease
549 <latexrelease>\IncludeInRelease{0000-00-00}{\@verbatim}%
550 <latexrelease>          {Disable hyphenation in verbatim}%
551 <latexrelease>\def\@verbatim{\trivlist \item\relax
552 <latexrelease>   \if@minipage\else\vskip\parskip\fi
553 <latexrelease>   \leftskip\@totalleftmargin\rightskip\z@skip
554 <latexrelease>   \parindent\z@\parfillskip\@flushglue\parskip\z@skip
555 <latexrelease>   \@@par
556 <latexrelease>   \@tempswafalse
557 <latexrelease>   \def\par{%
558 <latexrelease>     \if@tempswa
559 <latexrelease>       \leavevmode \null \@@par\penalty\interlinepenalty
560 <latexrelease>     \else
561 <latexrelease>       \@tempswatrue
562 <latexrelease>       \ifhmode\@@par\penalty\interlinepenalty\fi
563 <latexrelease>     \fi}%
564 <latexrelease>   \let\do\@makeother \dospecials

```

```

565 <latexrelease> \obeylines \verbatim@font \@noligs
566 <latexrelease> \hyphenchar\font\m@ne
567 <latexrelease> \everypar \expandafter{\the\everypar \unpenalty}%
568 <latexrelease>}
569 <latexrelease>\EndIncludeInRelease
570 <*2ekernel>

```

*(End of definition for \@verbatim.)*

**verbatim** (RmS 93/09/19) Protected against ‘missing item’ error message triggered by empty verbatim environment.

```

571 \def\verbatim{\@verbatim \frenchspacing\@vobeyspaces \@xverbatim}
572 \def\endverbatim{\if@newlist \leavevmode\fi\endtrivlist}

```

*(End of definition for \verbatim and \endverbatim.)*

**\verbatim@font** Macro to select the font used for verbatim typesetting. It also does other work if necessary for the font used.

```

573 \def\verbatim@font{\normalfont\ttfamily}

```

*(End of definition for \verbatim@font.)*

```

574 </2ekernel>
575 <*2ekernel | latexrelease>
576 <latexrelease>\IncludeInRelease{2018/12/01}%
577 <latexrelease> \verbvisiblespace}{Setup visible space for \verb}%

```

**\asciispace** The character in slot 32, in typewriter fonts (historically) a visible space but in other fonts a real space or something else

```

578 \DeclareRobustCommand\asciispace{\char 32 }

```

*(End of definition for \asciispace.)*

**\verbvisiblespace** This defines how to get a visible space in **\verb\*** and friends. In classic T<sub>E</sub>X this is just the slot 32, but in T<sub>U</sub> encoded fonts we switch fonts and take the character from cm<sub>tt</sub>.

```

579 \ifx\Umathcode\@undefined
580   \let\verbvisiblespace\asciispace % Pdftex version
581 \else
582   \DeclareRobustCommand\verbvisiblespace
583     {\leavevmode{\usefont{OT1}{cmtt}{m}{n}\asciispace}} % xetex/luatex version
584 \fi

```

*(End of definition for \verbvisiblespace.)*

**\@verbvisiblespacebox** The box to hold the visible space character if it isn’t in slot 32 in the current typewriter font.

```

585 \newbox\@verbvisiblespacebox

```

*(End of definition for \@verbvisiblespacebox.)*

**verbatim\*** (*env.*) For **verbatim\*** we also set up the correct visible space character definition and then run **\@vobeyspaces**. As this code is not called as part of the normal verbatim environment (the method is done the other way around this time) we don’t have to check if space is already active—it shouldn’t be.

```

586 \@namedef{verbatim*}{\@verbatim
587   \@setupverbvisiblespace
588   \frenchspacing\@vobeyspaces\@sxverbatim}
589 \expandafter\let\csname endverbatim*\endcsname =\endverbatim

```

```

590 </2ekernel | latexrelease>
591 <latexrelease>\EndIncludeInRelease
592 <latexrelease>\IncludeInRelease{0000/00/00}%
593 <latexrelease>          {\verbvisiblespace}{Setup visible space for \verb}%
594 <latexrelease>
595 <latexrelease>\@namedef{verbatim*}{\@verbatim\@sxverbatim}
596 <latexrelease>
597 <latexrelease>\let\asciispace          \@undefined
598 <latexrelease>\let\verbvisiblespace    \@undefined
599 <latexrelease>\let\@setupverbvisiblespace\@undefined
600 <latexrelease>\let\@verbvisiblespacebox \@undefined
601 <latexrelease>\EndIncludeInRelease
602 <*2ekernel>

```

`\@setupverbvisiblespace` In pdfTeX a catcode 12 space will produce the character in slot 32 which is assumed to be a visible space character (in a typewriter font in OT1 or T1 encoding). In XeTeX or LuaTeX a font in TU encoding is normally used and that has a real space in this slot. So what we do in this case is this: we check the definition of `\verbvisiblespace` and if it is `\asciispace` we assume that the char32 can be used (e.g., in pdfTeX). We then redefine `\@xobeysp` so that after running `\@xobeyspaces` we get characters from slot 32 for each active space.

```

603 </2ekernel>
604 <*2ekernel | latexrelease>
605 <latexrelease>\IncludeInRelease{2023/11/01}%
606 <latexrelease>          {\@setupverbvisiblespace}{Setup visible tab for \verb}%
607 \def\@setupverbvisiblespace{%
608   \ifx\verbvisiblespace\asciispace
609     \let\@xobeysp\asciispace
610   \else

```

Otherwise we measure the width of a character in the mono-spaced current font and place a `\verbvisiblespace` into a box of the right width which we are then using as the character for a space. By default this will be the space character from OT1 cmtt but by changing `\verbvisiblespace` one could use, for example, the `\textvisiblespace` of the current typewriter font.

```

611   \setbox\z@\hbox{x}%
612   \setbox\@verbvisiblespacebox\hbox to\wd\z@{\hss\verbvisiblespace\hss}%
613   \def\@xobeysp{\leavevmode\copy\@verbvisiblespacebox}%
614 \fi
615 \@setupverbvisibletab
616 }
617 </2ekernel | latexrelease>
618 <latexrelease>\EndIncludeInRelease
619 <latexrelease>\IncludeInRelease{2018/12/01}%
620 <latexrelease>          {\@setupverbvisiblespace}{Setup visible space for \verb}%
621 <latexrelease>\def\@setupverbvisiblespace{%
622 <latexrelease>  \ifx\verbvisiblespace\asciispace
623 <latexrelease>    \let\@xobeysp\asciispace
624 <latexrelease>  \else
625 <latexrelease>    \setbox\z@\hbox{x}%
626 <latexrelease>    \setbox\@verbvisiblespacebox\hbox to\wd\z@{\hss\verbvisiblespace\hss}%
627 <latexrelease>    \def\@xobeysp{\leavevmode\copy\@verbvisiblespacebox}%
628 <latexrelease>  \fi

```

```

629 <latexrelease>}
630 <latexrelease>\EndIncludeInRelease
631 <latexrelease>\IncludeInRelease{0000/00/00}%
632 <latexrelease>{\@setupverbvisiblespace}{Setup visible space for \verb}%
633 <latexrelease>\let\@setupverbvisiblespace\@undefined
634 <latexrelease>\EndIncludeInRelease
635 <*2ekernel>

```

*(End of definition for \@setupverbvisiblespace.)*

**\@setupverbvisibletab** A redirection: just a simple wrapper.

```

636 </2ekernel>
637 <latexrelease>\IncludeInRelease{2023/11/01}%
638 <latexrelease>{\@setupverbvisibletab}{Setup visible tab for \verb}%
639 <*2ekernel | latexrelease>
640 \def\@setupverbvisibletab{\let\@xobeytab\@xobeysp}
641 </2ekernel | latexrelease>
642 <latexrelease>\EndIncludeInRelease
643 <latexrelease>\IncludeInRelease{0000/00/00}%
644 <latexrelease>{\@setupverbvisibletab}{Setup visible tab for \verb}%
645 <latexrelease>\let\@setupverbvisibletab\@undefined
646 <latexrelease>\EndIncludeInRelease
647 <*2ekernel>

```

*(End of definition for \@setupverbvisibletab.)*

**\@sverb** Definitions of \@sverb and \@verb changed so \verb+ foo+ does not lose leading blanks  
**\@@sverb** when it comes at the beginning of a line. Change made 24 May 89. Suggested by Frank Mittelbach and Rainer Schöpf.

```

648 </2ekernel>
649 <*2ekernel | latexrelease>
650 <latexrelease>\IncludeInRelease{2023/11/01}%
651 <latexrelease>{\@sverb}{Support visible tabs}%

```

If the users types \verb !~! foo then surprisingly we would get the space as the delimiter and thus “!~!foo” in the output. To avoid this scenario we check if #1 has the character code of a space, if so we recurse otherwise we call \@@sverb (which is the original definition of \@sverb).

```

652 \def\@sverb#1{\if\noexpand#1 \expandafter\@sverb\else\@@sverb{#1}\fi}

653 \def\@@sverb#1{%
654   \catcode'#1\active
655   \lccode'\~'#1%
656   \gdef\verb@balance@group{\verb@egroup
657     \@latexerror{\noexpand\verb illegal in argument}\@ehc}%
658   \aftergroup\verb@balance@group
659   \lowercase{\let~\verb@egroup}%

```

If \@sverb is called from \@verb then space is already active and supposed to produce a real space. In this case we do nothing. Otherwise we run \@setupverbvisiblespace to setup the right visible space char and afterwards \@vobeyspaces to make it the definition for the active space character.

```

660   \ifnum0%
661     \ifnum\catcode'\ =\active\else 1\fi
662     \ifnum\catcode'\~I=\active\else 1\fi

```

```

663     =0 %
664     \else \@setupverbvisiblespace \@vobeyspaces \fi
665 }

666 </2ekernel | latexrelease>
667 <latexrelease>\EndIncludeInRelease
668 <latexrelease>\IncludeInRelease{2020/10/01}%
669 <latexrelease>          {\@sverb}{Drop spaces before \verb delimiter}%
670 <latexrelease>\def\@sverb#1{%
671 <latexrelease>  \catcode'#1\active
672 <latexrelease>  \lccode'\~'#1%
673 <latexrelease>  \gdef\verb@balance@group{\verb@egroup
674 <latexrelease>    \@latex@error{\noexpand\verb illegal in argument}\@ehc}%
675 <latexrelease>  \aftergroup\verb@balance@group
676 <latexrelease>  \lowercase{\let~\verb@egroup}%
677 <latexrelease>  \ifnum\catcode'\ =\active
678 <latexrelease>  \else \@setupverbvisiblespace \@vobeyspaces \fi
679 <latexrelease>}
680 <latexrelease>\EndIncludeInRelease
681 <latexrelease>\IncludeInRelease{2018/12/01}%
682 <latexrelease>          {\@sverb}{Setup visible space for \verb}%
683 <latexrelease>
684 <latexrelease>\def\@sverb#1{%
685 <latexrelease>  \catcode'#1\active
686 <latexrelease>  \lccode'\~'#1%
687 <latexrelease>  \gdef\verb@balance@group{\verb@egroup
688 <latexrelease>    \@latex@error{\noexpand\verb illegal in command argument}\@ehc}%
689 <latexrelease>  \aftergroup\verb@balance@group
690 <latexrelease>  \lowercase{\let~\verb@egroup}%
691 <latexrelease>  \ifnum\catcode'\ =\active
692 <latexrelease>  \else \@setupverbvisiblespace \@vobeyspaces \fi
693 <latexrelease>}
694 <latexrelease>\let\@sverb\@undefined
695 <latexrelease>\EndIncludeInRelease
696 <latexrelease>
697 <latexrelease>\IncludeInRelease{0000/00/00}%
698 <latexrelease>          {\@sverb}{Setup visible space for \verb}%
699 <latexrelease>\def\@sverb#1{%
700 <latexrelease>  \catcode'#1\active
701 <latexrelease>  \lccode'\~'#1%
702 <latexrelease>  \gdef\verb@balance@group{\verb@egroup
703 <latexrelease>    \@latex@error{\noexpand\verb illegal in command argument}\@ehc}%
704 <latexrelease>  \aftergroup\verb@balance@group
705 <latexrelease>  \lowercase{\let~\verb@egroup}}%
706 <latexrelease>
707 <latexrelease>\EndIncludeInRelease
708 <*2ekernel>

```

*(End of definition for \@sverb and \@sverb.)*

**\@makeother**

```

709 \def\@makeother#1{\catcode'#112\relax}

```

*(End of definition for \@makeother.)*

`\verb@balance@group`

```
710 \let\verb@balance@group\@empty
(End of definition for \verb@balance@group.)
```

`\verb@egroup`

```
711 \def\verb@egroup{\global\let\verb@balance@group\@empty\egroup}
(End of definition for \verb@egroup.)
```

`\verb@eol@error`

```
712 \begingroup
713 \obeylines%
714 \gdef\verb@eol@error{\obeylines%
715 \def~M{\verb@egroup\@latex@error{%
716 \noexpand\verb ended by end of line}\@ehc}}%
717 \endgroup
(End of definition for \verb@eol@error.)
```

`\verb` Typesetting a small piece verbatim.

```
718 </2ekernel>
719 <*2ekernel | latexrelease>
720 <latexrelease>\IncludeInRelease{2017-04-15}{\verb}%
721 <latexrelease> {Disable hyphenation in verb}%
722 \def\verb{\relax\ifmmode\hbox\else\leavevmode\null\fi
723 \bgroup
724 \verb@eol@error \let\do\@makeoother \dospecials
725 \verbatim@font\@noligs
Set \language here to suppress hyphenation. Done this way rather than setting
\hyphenchar as that is a global setting.
726 \language\l@nohyphenation
727 \@ifstar\@sverb\@verb}
728 </2ekernel | latexrelease>
729 <latexrelease>\EndIncludeInRelease
730 <latexrelease>\IncludeInRelease{0000-00-00}{\verb}%
731 <latexrelease> {Disable hyphenation in verb}%
732 <latexrelease>\def\verb{\relax\ifmmode\hbox\else\leavevmode\null\fi
733 <latexrelease> \bgroup
734 <latexrelease> \verb@eol@error \let\do\@makeoother \dospecials
735 <latexrelease> \verbatim@font\@noligs
736 <latexrelease> \@ifstar\@sverb\@verb}
737 <latexrelease>\EndIncludeInRelease
738 <*2ekernel>
(End of definition for \verb.)
```

`\@verb`

```
739 \def\@verb{\@vobeyspaces \frenchspacing \@sverb}
(End of definition for \@verb.)
```

`\verbatim@nolig@list`

```
740 \def\verbatim@nolig@list{\do\‘\do\<\do\>\do\,\do\’\do\~}
```

*(End of definition for \verbatim@nolig@list.)*

**\do@noligs**

```
741 \def\do@noligs#1{%  
742   \catcode'#1\active  
743   \begingroup  
744     \lccode'\~'#1\relax  
745     \lowercase{\endgroup\def~{\leavevmode\kern\z@\char'#1}}}
```

*(End of definition for \do@noligs.)*

**\@noligs** To stay compatible with packages that use \@noligs we keep it.

```
746 \def\@noligs{\let\do\do@noligs \verbatim@nolig@list}
```

*(End of definition for \@noligs.)*

```
747 \</2ekernel>
```

## File 38

# ltmath.dtx

## 1 Math setup

This file contains a lot of the original plain T<sub>E</sub>X code, as well as the L<sup>A</sup>T<sub>E</sub>X environments for math. It still needs sorting out.

```
1 <*2kernel>
2 \message{math definitions,}
```

### 1.1 Math commands based on plain T<sub>E</sub>X

#### 1.1.1 The log-like functions

\log The standard operators:

```
3 \DeclareRobustCommand\log{\mathop{\operator@font log}\nolimits}
4 \DeclareRobustCommand\lg{\mathop{\operator@font lg}\nolimits}
5 \DeclareRobustCommand\ln{\mathop{\operator@font ln}\nolimits}
6 \DeclareRobustCommand\lim{\mathop{\operator@font lim}}
7 \DeclareRobustCommand\limsup{\mathop{\operator@font lim}\,sup}}
8 \DeclareRobustCommand\liminf{\mathop{\operator@font lim}\,inf}}
9 \DeclareRobustCommand\sin{\mathop{\operator@font sin}\nolimits}
10 \DeclareRobustCommand\arcsin{\mathop{\operator@font arcsin}\nolimits}
11 \DeclareRobustCommand\sinh{\mathop{\operator@font sinh}\nolimits}
12 \DeclareRobustCommand\cos{\mathop{\operator@font cos}\nolimits}
13 \DeclareRobustCommand\arccos{\mathop{\operator@font arccos}\nolimits}
14 \DeclareRobustCommand\cosh{\mathop{\operator@font cosh}\nolimits}
15 \DeclareRobustCommand\tan{\mathop{\operator@font tan}\nolimits}
16 \DeclareRobustCommand\arctan{\mathop{\operator@font arctan}\nolimits}
17 \DeclareRobustCommand\tanh{\mathop{\operator@font tanh}\nolimits}
18 \DeclareRobustCommand\cot{\mathop{\operator@font cot}\nolimits}
19 \DeclareRobustCommand\coth{\mathop{\operator@font coth}\nolimits}
20 \DeclareRobustCommand\sec{\mathop{\operator@font sec}\nolimits}
21 \DeclareRobustCommand\csc{\mathop{\operator@font csc}\nolimits}
22 \DeclareRobustCommand\max{\mathop{\operator@font max}}
23 \DeclareRobustCommand\min{\mathop{\operator@font min}}
24 \DeclareRobustCommand\sup{\mathop{\operator@font sup}}
25 \DeclareRobustCommand\inf{\mathop{\operator@font inf}}
26 \DeclareRobustCommand\arg{\mathop{\operator@font arg}\nolimits}
27 \DeclareRobustCommand\ker{\mathop{\operator@font ker}\nolimits}
28 \DeclareRobustCommand\dim{\mathop{\operator@font dim}\nolimits}
29 \DeclareRobustCommand\hom{\mathop{\operator@font hom}\nolimits}
30 \DeclareRobustCommand\det{\mathop{\operator@font det}}
31 \DeclareRobustCommand\exp{\mathop{\operator@font exp}\nolimits}
32 \DeclareRobustCommand\Pr{\mathop{\operator@font Pr}}
33 \DeclareRobustCommand\gcd{\mathop{\operator@font gcd}}
34 \DeclareRobustCommand\deg{\mathop{\operator@font deg}\nolimits}
```

*(End of definition for \log.)*

\bmod And some operators have to be done by hand:

```

35 \DeclareRobustCommand\bmod{%
36   \nonscript\mskip-\medmuskip\mkern5mu%
37   \mathbin{\operator@font mod}\penalty900\mkern5mu%
38   \nonscript\mskip-\medmuskip}

```

*(End of definition for \bmod.)*

**\pmod**

```

39 \DeclareRobustCommand\pmod[1]{%
40   \allowbreak\mkern18mu({\operator@font mod}\,\,\,#1)}

```

*(End of definition for \pmod.)*

### 1.1.2 Biggggg

**\big** Variants on **\big** and friends for use with delimiters:

```

41 \DeclareRobustCommand\bigl{\mathopen\big}
42 \DeclareRobustCommand\bigm{\mathrel\big}
43 \DeclareRobustCommand\bigg{\mathclose\big}
44 \DeclareRobustCommand\Bigl{\mathopen\Big}
45 \DeclareRobustCommand\Bigm{\mathrel\Big}
46 \DeclareRobustCommand\Bigg{\mathclose\Big}
47 \DeclareRobustCommand\biggl{\mathopen\bigg}
48 \DeclareRobustCommand\biggm{\mathrel\bigg}
49 \DeclareRobustCommand\biggr{\mathclose\bigg}
50 \DeclareRobustCommand\Biggl{\mathopen\Bigg}
51 \DeclareRobustCommand\Biggm{\mathrel\Bigg}
52 \DeclareRobustCommand\Biggr{\mathclose\Bigg}

```

*(End of definition for \big.)*

### 1.1.3 The UNSORTED Rest

The other math commands are lifted from plain T<sub>E</sub>X.

**\jot**

```

53 \newdimen\jot
54 \jot=3pt

```

*(End of definition for \jot.)*

**\interdisplaylinepenalty**

```

55 \newcount\interdisplaylinepenalty
56 \interdisplaylinepenalty=100

```

*(End of definition for \interdisplaylinepenalty.)*

**\choose**

```

57 \def\choose{\atopwithdelims()}

```

*(End of definition for \choose.)*

**\brack**

```

58 \def\brack{\atopwithdelims[]}

```

*(End of definition for \brack.)*

```

\brace
59 \def\brace{\atopwithdelims\{\}}
(End of definition for \brace.)

\mathpalette
60 \def\mathpalette#1#2{%
61   \mathchoice
62     {#1\displaystyle{#2}}%
63     {#1\textstyle{#2}}%
64     {#1\scriptstyle{#2}}%
65     {#1\scriptscriptstyle{#2}}
(End of definition for \mathpalette.)

\root
\rootbox
\root
66 \newbox\rootbox
67 \def\root#1\of{%
68   \setbox\rootbox\hbox{$\m@th\scriptscriptstyle{#1}$}%
69   \mathpalette\root
70 \def\root#1#2{%
71   \setbox\rootbox\hbox{$\m@th#1\sqrt{\scriptscriptstyle{#2}}$}%
72   \dimen@=\ht\rootbox \advance\dimen@-\dp\rootbox
73   \mkern5mu\raise.6\dimen@\copy\rootbox
74   \mkern-10mu\box\rootbox
(End of definition for \root, \rootbox, and \root.)

\phantom
\hphantom
\phantom
75 \newif\ifv@
76 \newif\ifh@
77 </2ekernel>
78 < *2ekernel | latexrelease>
79 < latexrelease> \IncludeInRelease{2019/10/01}%
80 < latexrelease> {\vphantom}{Make commands robust}%
81 \DeclareRobustCommand\vphantom{\v@true\h@false\ph@nt}
82 \DeclareRobustCommand\hphantom{\v@false\h@true\ph@nt}
83 \DeclareRobustCommand\phantom{\v@true\h@true\ph@nt}
84 \DeclareRobustCommand\mathstrut{\vphantom{}}

\mathstrut
85 < /2ekernel | latexrelease>
86 < latexrelease> \EndIncludeInRelease
87 < latexrelease> \IncludeInRelease{0000/00/00}%
88 < latexrelease> {\vphantom}{Make commands robust}%
89 < latexrelease>
90 < latexrelease> \kernel@make@fragile\vphantom
91 < latexrelease> \kernel@make@fragile\hphantom
92 < latexrelease> \kernel@make@fragile\phantom
93 < latexrelease> \kernel@make@fragile\mathstrut
94 < latexrelease>
95 < latexrelease> \EndIncludeInRelease
96 < *2ekernel>

```

```

97 \def\ph@nt{%
98   \ifmmode
99     \expandafter\mathpalette\expandafter\mathph@nt
100   \else
101     \expandafter\makeph@nt
102   \fi}

103 \def\makeph@nt#1{%
104   \setbox\z@\hbox{\color@begingroup#1\color@endgroup}\finph@nt}

105 \def\mathph@nt#1#2{%
106   \setbox\z@\hbox{$\m@th#1{#2}$}\finph@nt}

107 </2ekernel>
108 <*2ekernel | latexrelease>
109 <latexrelease>\IncludeInRelease{2018/12/01}%
110 <latexrelease>          {\finph@nt}{Start LR-mode}%
111 \def\finph@nt{%
112   \setbox\tw@\null
113   \ifv@ \ht\tw@\ht\z@ \dp\tw@\dp\z@\fi
114   \ifh@ \wd\tw@\wd\z@\fi

115   \leavevmode@ifvmode\box\tw@}
116 </2ekernel | latexrelease>
117 <latexrelease>\EndIncludeInRelease
118 <latexrelease>\IncludeInRelease{0000/00/00}%
119 <latexrelease>          {\finph@nt}{Start LR-mode}%
120 <latexrelease>\def\finph@nt{%
121 <latexrelease>   \setbox\tw@\null
122 <latexrelease>   \ifv@ \ht\tw@\ht\z@ \dp\tw@\dp\z@\fi
123 <latexrelease>   \ifh@ \wd\tw@\wd\z@\fi \box\tw@}
124 <latexrelease>\EndIncludeInRelease
125 <*2ekernel>

```

(End of definition for \phantom and others.)

\smash

```

126 \DeclareRobustCommand\smash{%
127   \relax % \relax, in case this comes first in \halign
128   \ifmmode
129     \expandafter\mathpalette\expandafter\mathsm@sh
130   \else
131     \expandafter\makesm@sh
132   \fi}

133 \def\makesm@sh#1{%
134   \setbox\z@\hbox{\color@begingroup#1\color@endgroup}\finsm@sh}

135 </2ekernel>
136 <*2ekernel | latexrelease>
137 <latexrelease>\IncludeInRelease{2022/11/01}%
138 <latexrelease>          {\mathsm@sh}{Guard against reboxing}%
139 \def\mathsm@sh#1#2{%
140   \setbox\z@\hbox{$\m@th#1{#2}$}%

```

The empty brace groups in front of the smashed box (which is placed by \finsm@sh) ensures that a \smash in math is not just producing a single box with its dimensions altered, but a box plus this second ord atom. The reason is that T<sub>E</sub>X sometimes reboxes

a box if its the only thing in a place like the denominator of a fraction. This would then undo the smashing and the additional ord atom prevents that. Two ord atoms in a row do not alter the horizontal spacing in a formula so this is otherwise transparent.

```

141   {} \finsm@sh}

142 </2ekernel | latexrelease>
143 <latexrelease> \EndIncludeInRelease
144 <latexrelease> \IncludeInRelease{0000/00/00}%
145 <latexrelease>           {\mathsm@sh}{Guard against reboxing}%
146 <latexrelease> \def\mathsm@sh#1#2{%
147 <latexrelease>   \setbox\z@\hbox{$\m@th#1{#2}$} \finsm@sh}
148 <latexrelease> \EndIncludeInRelease
149 <*2ekernel>

```

```

150 </2ekernel>
151 <*2ekernel | latexrelease>
152 <latexrelease> \IncludeInRelease{2018/12/01}%
153 <latexrelease>           {\finsm@sh}{Start LR-mode}%
154 \def\finsm@sh{\ht\z@\z@ \dp\z@\z@ \leavevmode@ifvmode\box\z@}
155 </2ekernel | latexrelease>
156 <latexrelease> \EndIncludeInRelease
157 <latexrelease> \IncludeInRelease{0000/00/00}%
158 <latexrelease>           {\finsm@sh}{Start LR-mode}%
159 <latexrelease> \def\finsm@sh{\ht\z@\z@ \dp\z@\z@ \box\z@}
160 <latexrelease> \EndIncludeInRelease
161 <*2ekernel>

```

(End of definition for \smash.)

\buildrel

```

162 \def\buildrel#1\over#2{\mathrel{\mathop{\kern\z@#2}\limits^{#1}}}

```

(End of definition for \buildrel.)

```

163 </2ekernel>
164 <*2ekernel | latexrelease>
165 <latexrelease> \IncludeInRelease{2019/10/01}%
166 <latexrelease>           {\cases}{Make commands robust}%

```

\cases

```

167 \DeclareRobustCommand*\cases[1]{\left\{\!,\vcenter{\normalbaselines\m@th
168   \ialign{##\hfil$&\quad{##}\hfil\crr#1\crr}\right.}

```

(End of definition for \cases.)

\matrix

```

169 \DeclareRobustCommand*\matrix[1]{\null\!,\vcenter{\normalbaselines\m@th
170   \ialign{\hfil$##$\hfil&\quad\hfil$##$\hfil\crr
171     \mathstrut\crr\noalign{\kern-\baselineskip}
172     #1\crr\mathstrut\crr\noalign{\kern-\baselineskip}}}\!,}

```

(End of definition for \matrix.)

\pmatrix

```

173 \DeclareRobustCommand*\pmatrix[1]{\left(\matrix{#1}\right)}

```

(End of definition for `\pmatrix`.)

```

174 \endkernel | latexrelease)
175 \latexrelease\EndIncludeInRelease
176 \latexrelease\IncludeInRelease{0000/00/00}%
177 \latexrelease\cases\{Make commands robust}%
178 \latexrelease
179 \latexrelease\kernel@make@fragile\cases
180 \latexrelease\kernel@make@fragile\matrix
181 \latexrelease\kernel@make@fragile\pmatrix
182 \latexrelease
183 \latexrelease\EndIncludeInRelease
184 \endkernel

```

`\bordermatrix`

```

185 \def\bordermatrix#1{\begingroup \m@th
186   \@tempdima 8.75\p@
187   \setbox\z@\vbox{%
188     \def\crr{\crr\noalign{\kern2\p@\global\let\crr\endline}}%
189     \ialign{##$\hfil\kern2\p@\kern\@tempdima&\thinspace\hfil$##$\hfil
190       &&\quad\hfil$##$\hfil\crr
191       \omit\strut\hfil\crr\noalign{\kern-\baselineskip}%
192       #1\crr\omit\strut\crr}%
193   \setbox\tw@\vbox{\unvcopy\z@\global\setbox\@ne\lastbox}%
194   \setbox\th@\hbox{\unhbox\@ne\unskip\global\setbox\@ne\lastbox}%
195   \setbox\th@\hbox{$\kern\wd\@ne\kern-\@tempdima\left(\kern-\wd\@ne
196     \global\setbox\@ne\vbox{\box\@ne\kern2\p@}%
197     \vcenter{\kern-\ht\@ne\unvbox\z@\kern-\baselineskip}\,,\right)$}%
198   \null\;\vbox{\kern\ht\@ne\box\th@}\endgroup}

```

(End of definition for `\bordermatrix`.)

`\openup`

```

199 \protected\def\openup{\afterassignment\@openup\dimen@}
200 \def\@openup{\advance\lineskip\dimen@
201   \advance\baselineskip\dimen@
202   \advance\lineskiplimit\dimen@}

```

(End of definition for `\openup`.)

`\displaylines`

```

203 \newif\ifdt@p
204 \def\disply{\global\dt@ptrue\openup\jot\m@th
205   \everycr{\noalign{\ifdt@p \global\dt@pfalse \ifdim\prevdepth>-1000\p@
206     \vskip-\lineskiplimit \vskip\normallineskiplimit \fi
207     \else \penalty\interdisplaylinepenalty \fi}}}
208 \def\@lign{\tabskip\z@skip\everycr{}} % restore inside \disply
209 \def\displaylines#1{\disply \tabskip\z@skip
210   \halign{\hb@xt@\displaywidth{$\@lign\hfil\displaystyle##\hfil$}\crr
211     #1\crr}}

```

(End of definition for `\displaylines`.)

```

\sp
\sb 212 \let\sp=~
    213 \let\sb=_

    (End of definition for \sp and \sb.)

\tmspace Originally LATEX only provided a small set of spacing commands for use in text and math,
\ some of the commands like \; were only supported in math mode. amsmath normalized
\tmspace and provided all of them in text and math. This code has now been moved to the kernel
\! so that it is generally available.
\negthinspace 214 </2ekernel>
\: 215 <*2ekernel | latexrelease>
\medspace 216 <latexrelease>\IncludeInRelease{2020/10/01}%
\negmedspace 217 <latexrelease> \tmspace\amsmath spacing commands}%
\; \tmspace is really meant to be an internal command so it doesn't necessarily has to be
\tickspace robust but it was robust in amsmath so we leave it like that.
\negthickspace 218 \DeclareRobustCommand\tmspace[3]{%
    219 \ifmmode\mskip#1#2\else\leavevmode@ifvmode\kern#1#3\fi\relax}

In amsmath the text kern is .1667em. For compatibility reasons we keep the longer one.
220 \DeclareRobustCommand\,{\tmspace+\thinmuskip{.16667em}}
221 \let\thinspace\,

222 \DeclareRobustCommand\!{\tmspace-\thinmuskip{.16667em}}
223 \let\negthinspace\!

224 \DeclareRobustCommand\:{\tmspace+\medmuskip{.2222em}}
225 \let\medspace\{:

LATEX has a second name for this in its manual:
226 \let\>=\:
227 \DeclareRobustCommand\negmedspace{\tmspace-\medmuskip{.2222em}}

228 \DeclareRobustCommand\;{\tmspace+\thickmuskip{.2777em}}
229 \let\thickspace\;
230 \DeclareRobustCommand\negthickspace{\tmspace-\thickmuskip{.2777em}}
231 </2ekernel | latexrelease>
232 <latexrelease>\EndIncludeInRelease

233 <latexrelease>\IncludeInRelease{0000/00/00}%
234 <latexrelease> \tmspace\amsmath spacing commands}%
235 <latexrelease>
236 <latexrelease>\let\tmspace\@undefined
237 <latexrelease>\DeclareRobustCommand{\,,}{%
238 <latexrelease> \relax\ifmmode\mskip\thinmuskip\else\thinspace\fi}
239 <latexrelease>\DeclareRobustCommand\thinspace{\leavevmode@ifvmode\kern .16667em }
240 <latexrelease>\DeclareRobustCommand\negthinspace{\leavevmode@ifvmode\kern-.16667em }
241 <latexrelease>\def\>{\mskip\medmuskip}
242 <latexrelease>\let\:=\>
243 <latexrelease>\def\;{\mskip\thickmuskip}
244 <latexrelease>\def\!{\mskip-\thinmuskip}
245 <latexrelease>

```

```

246 <latexrelease>\let\negmedspace\@undefined
247 <latexrelease>\let\negthickspace\@undefined
248 <latexrelease>
249 <latexrelease>\EndIncludeInRelease
250 <*2ekernel>

(End of definition for \tmspace and others.)

\*
251 \DeclareRobustCommand\*{\discretionary{\thinspace\the\textfont2\char2}{-}{-}}

(End of definition for \*.)

\: Nickname for the medium space since \> is not available inside tabbing.
252 %\let\:=\>

(End of definition for \:.)

\active@math@prime This is the definition of the active math prime.
253 \def\active@math@prime{^{\bgroup\prim@s}}

(End of definition for \active@math@prime.)

\prime@s
254 {\catcode'\=' \active \global\let'\active@math@prime}
255 \def\prim@s{%
256   \prime\futurelet\@let@token\pr@m@s}
257 \def\pr@m@s{%
258   \ifx'\@let@token
259     \expandafter\pr@@@s
260   \else
261     \ifx^{\@let@token
262       \expandafter\expandafter\expandafter\pr@@@t
263     \else
264       \egroup
265     \fi
266   \fi}
267 \def\pr@@@s#1{\prim@s}
268 \def\pr@@@t#1#2{#2\egroup}

(End of definition for \prime@s.)
269 {\catcode'\_=\active \gdef\_{} } % _ in math is
270                                     % either subscript or \_

```

## 1.2 Math Environments

`\(` Produces  $\dots$  with checks that `\(` isn't used in math mode, and that `\)` is only used in math mode begun with `\(`.

```

271 \</2ekernel>
272 \<latexrelease>\IncludeInRelease{2015/01/01}{\<(){Make \< robust}%
273 \<*2ekernel | latexrelease>
274 \DeclareRobustCommand\<{%
275   \relax\ifmmode\<@badmath\else$\<fi}%
276 \DeclareRobustCommand\<{%
277   \relax\ifmmode\ifinner$\<else\<@badmath\fi\else \<@badmath\fi}%
278 \</2ekernel | latexrelease>
279 \<latexrelease>\EndIncludeInRelease
280 \<latexrelease>\IncludeInRelease{0000/00/00}{\<(){Make \< robust}%
281 \<latexrelease>\def\<{%
282 \<latexrelease> \relax\ifmmode\<@badmath\else$\<fi}%
283 \<latexrelease>\expandafter\let\csname\string( \endcsname\<undefined
284 \<latexrelease>\def\<{%
285 \<latexrelease> \relax\ifmmode\ifinner$\<else\<@badmath\fi\else \<@badmath\fi}%
286 \<latexrelease>\expandafter\let\csname\string) \endcsname\<undefined
287 \<latexrelease>\EndIncludeInRelease
288 \<*2ekernel>

```

*(End of definition for `\(` and `\)`.)*

`\dollar\dollar@begin` Two commands for starting and ending display math formulas to be used in the kernel and by packages. They are needed for tagging support and should be used by all display math environments so that these environments can be used when accessible PDFs are produced. We pretend that they have been always available, so that rollback doesn't break packages that have not set up their own rollback.

```

289 \</2ekernel>
290 \<*2ekernel | latexrelease>
291 \<latexrelease>\IncludeInRelease{2025/06/01}%
292 \<latexrelease> {\dollar\dollar@begin}{Start and end display math}%
293 \def\dollar\dollar@begin{$$$}
294 \def\dollar\dollar@end{$$$}
295 \</2ekernel | latexrelease>
296 \<latexrelease>\EndIncludeInRelease
297 \<latexrelease>\IncludeInRelease{0000/00/00}%
298 \<latexrelease> {\dollar\dollar@begin}{Start and end display math}%
299 \<latexrelease>
300 \<latexrelease>\def\dollar\dollar@begin{$$$}
301 \<latexrelease>\def\dollar\dollar@end{$$$}
302 \<latexrelease>\EndIncludeInRelease
303 \<*2ekernel>
304
305

```

*(End of definition for `\dollar\dollar@begin` and `\dollar\dollar@end`.)*

`\[` Produces  $\dots$  with checks that `\[` isn't used in math mode, and that `\]` is only used in display math mode (though there is no real test that this display math started with `\[` and not with `$$`).

```

306 </2ekernel>
307 <latexrelease>\IncludeInRelease{2015/01/01}{\[]{}{Make \[ robust}}%
308 <*2ekernel|latexrelease>
309 \DeclareRobustCommand\[%
310   \relax\ifmmode
311     \@badmath
312   \else
313     \ifvmode
314       \nointerlineskip
315       \makebox[.6\linewidth]{}%
316     \fi
317     $$$ % amsthm tries to patch this and expects a $
318 %     \dollar\dollar@begin % in the def so we can't hide it for now
319 %                               % will be adjusted when amsthm changes
320   \fi
321 ]%
322 \DeclareRobustCommand\[%
323   \relax\ifmmode
324     \ifinner
325       \@badmath
326     \else
327       \dollar\dollar@end
328     \fi
329   \else
330     \@badmath
331   \fi
332   \ignorespaces
333 ]%
334 </2ekernel|latexrelease>
335 <latexrelease>\EndIncludeInRelease
336 <latexrelease>\IncludeInRelease{2015/01/01}{\[]{}{Make \[ robust}}%
337 <latexrelease>\DeclareRobustCommand\[%
338 <latexrelease>   \relax\ifmmode
339 <latexrelease>     \@badmath
340 <latexrelease>   \else
341 <latexrelease>     \ifvmode
342 <latexrelease>       \nointerlineskip
343 <latexrelease>       \makebox[.6\linewidth]{}%
344 <latexrelease>     \fi
345 <latexrelease>     $$$%$$$ BRACE MATCH HACK
346 <latexrelease>   \fi
347 <latexrelease>}%
348 <latexrelease>\DeclareRobustCommand\[%
349 <latexrelease>   \relax\ifmmode
350 <latexrelease>     \ifinner
351 <latexrelease>       \@badmath
352 <latexrelease>     \else
353 <latexrelease>       $$$%$$$ BRACE MATCH HACK
354 <latexrelease>     \fi
355 <latexrelease>   \else
356 <latexrelease>     \@badmath
357 <latexrelease>   \fi
358 <latexrelease>   \ignorespaces

```

```

359 <latexrelease>}%
360 <latexrelease>\EndIncludeInRelease

361 <latexrelease>\IncludeInRelease{0000/00/00}{\[]{}{Make \[ robust}}%
362 <latexrelease>\def\[%
363 <latexrelease> \relax\ifmmode
364 <latexrelease> \@badmath
365 <latexrelease> \else
366 <latexrelease> \ifvmode
367 <latexrelease> \nointerlineskip
368 <latexrelease> \makebox[.6\linewidth]{}%
369 <latexrelease> \fi
370 <latexrelease> $$$%$$ BRACE MATCH HACK
371 <latexrelease> \fi
372 <latexrelease>}%
373 <latexrelease>\expandafter\let\csname\string[] \endcsname\@undefined

374 <latexrelease>\def\[%
375 <latexrelease> \relax\ifmmode
376 <latexrelease> \ifinner
377 <latexrelease> \@badmath
378 <latexrelease> \else
379 <latexrelease> $$$%$$ BRACE MATCH HACK
380 <latexrelease> \fi
381 <latexrelease> \else
382 <latexrelease> \@badmath
383 <latexrelease> \fi
384 <latexrelease> \ignorespaces
385 <latexrelease>}%
386 <latexrelease>\expandafter\let\csname\string[] \endcsname\@undefined
387 <latexrelease>\EndIncludeInRelease
388 <*2ekernel>

```

(End of definition for \[ and \].)

**math** (*env.*) Disguises for  $(\dots)$  and  $[\dots]$ .

```

displaymath (env.)
389 \let\math=\(
390 \let\endmath=\)

391 \def\displaymath{\[]
392 \def\enddisplaymath{\}\@ignoretrue}

```

**equation** (*env.*) Numbered equations, using the counter `\c@equation`. *Note:* The document style must define `\theequation` etc., and do the appropriate `\@addtoreset`. It should also redefine `\@eqnnum` if another format for the equation number is desired other than the standard (...), or to move the equation numbers to the flushleft. (See comment on the `\def` of `\@eqnnum`.)

```

393 \@definecounter{equation}
394 </2ekernel>
395 <*2ekernel | latexrelease>
396 <latexrelease>\IncludeInRelease{2025/06/01}%
397 <latexrelease> \{equation\}{Tagging support}}%
398 \def\equation{\dollar@begin
399 \refstepcounter{equation}}
400 \def\endequation{\eqno \hbox{\@eqnnum}\dollar@end\@ignoretrue}

```

```

401 </2ekernel | latexrelease>
402 <latexrelease>\EndIncludeInRelease
403 <latexrelease>\IncludeInRelease{0000/00/00}%
404 <latexrelease>{\equation}{Tagging support}%
405 <latexrelease>
406 <latexrelease>\def\equation{$$\refstepcounter{equation}}
407 <latexrelease>\def\endequation{\eqno \hbox{\@eqnnum}$$\@ignoretrue}
408 <latexrelease>\EndIncludeInRelease
409 <*2ekernel>

```

(End of definition for \c@equation.)

**\@eqnnum** Produces the equation number for equation and eqnarray environments. The following definition is for flushright numbers; for flushleft numbers, see leqno.clo. The equation number is set in black roman type even if an eqnarray environment appears in an italic environment.

```

410 \def\@eqnnum{{\normalfont \normalcolor (\theequation)}}

```

(End of definition for \@eqnnum.)

**\stackrel** A disguise for plain T<sub>E</sub>X's buildrel.

```

411 \DeclareRobustCommand\stackrel[2]{\mathrel{\mathop{#2}\limits^{#1}}}

```

(End of definition for \stackrel.)

**\frac** A disguise for plain T<sub>E</sub>X's \over.

```

412 \DeclareRobustCommand\frac[2]{\begingroup#1\endgroup\over#2}

```

(End of definition for \frac.)

**\sqrt** Add an optional argument to plain's \sqrt to give the *n*th root of an expression  $\sqrt[n]{e}$ .

**\@sqrt**

```

413 \DeclareRobustCommand\sqrt{\@ifnextchar[\@sqrt\sqrtsign}
414 \def\@sqrt[#1]{\root #1\of}

```

(End of definition for \sqrt and \@sqrt.)

**\eqnarray** Here's the eqnarray environment: Default is for left-hand side of equations to be flushright. To make them flushleft, \let\@eqnrel = \hfil.

**\@eqpen**

**\if@eqnsw**

**\@eqnrel**

```

415 \newcount\@eqcnt
416 \newcount\@eqpen
417 \newif\if@eqnsw\@eqnswtrue
418 \newskip\@centering
419 \@centering = 0pt plus 1000pt

```

To get a proper \@currentlabel we have to redefine it for the whole display. Note that we can't use \refstepcounter as this results in \@currentlabel getting restored at the wrong and thus always writing the first label to the .aux file.

```

420 </2ekernel>
421 <*2ekernel | latexrelease>
422 <latexrelease>\IncludeInRelease{2025/06/01}%
423 <latexrelease>{\eqnarray}{Support for tagging}%

```

```

424 \def\eqnarray{%
425     \stepcounter{equation}%
426     \def\@currentlabel{\p@equation\theequation}%
427     \def\@currentcounter{equation}%
428     \global\@eqnswtrue
429     \m@th
430     \global\@eqcnt\z@
431     \tabskip\@centering
432     \let\\\@eqnocr
433     \dollar\dollar\@begin\everycr{}\halign to\displaywidth\bgroup
434         \hskip\@centering$\displaystyle\tabskip\z@skip{##}$\@eqnrel
435         &\global\@eqcnt\@ne\hskip \tw@\arraycolsep \hfil${##}$\hfil
436         &\global\@eqcnt\tw@ \hskip \tw@\arraycolsep
437         $\displaystyle{##}$\hfil\tabskip\@centering
438         &\global\@eqcnt\thr@@ \hb@xt@\z@\bgroup\hss##\egroup
439         \tabskip\z@skip
440     \cr
441 }

442 \def\endeqnarray{%
443     \@@eqnocr
444     \egroup
445     \global\advance\c@equation\m@ne
446     \dollar\dollar\@end\@ignoretrue
447 }

448 </2ekernel | latexrelease>
449 <latexrelease>\EndIncludeInRelease
450 <latexrelease>\IncludeInRelease{0000/00/00}%
451 <latexrelease>          {\eqnarray}{Support for tagging}%
452 <latexrelease>
453 <latexrelease>\def\eqnarray{%
454 <latexrelease>     \stepcounter{equation}%
455 <latexrelease>     \def\@currentlabel{\p@equation\theequation}%
456 <latexrelease>     \def\@currentcounter{equation}%
457 <latexrelease>     \global\@eqnswtrue
458 <latexrelease>     \m@th
459 <latexrelease>     \global\@eqcnt\z@
460 <latexrelease>     \tabskip\@centering
461 <latexrelease>     \let\\\@eqnocr
462 <latexrelease>     $$\everycr{}\halign to\displaywidth\bgroup
463 <latexrelease>         \hskip\@centering$\displaystyle\tabskip\z@skip{##}$\@eqnrel
464 <latexrelease>         &\global\@eqcnt\@ne\hskip \tw@\arraycolsep \hfil${##}$\hfil
465 <latexrelease>         &\global\@eqcnt\tw@ \hskip \tw@\arraycolsep
466 <latexrelease>         $\displaystyle{##}$\hfil\tabskip\@centering
467 <latexrelease>         &\global\@eqcnt\thr@@ \hb@xt@\z@\bgroup\hss##\egroup
468 <latexrelease>         \tabskip\z@skip
469 <latexrelease>     \cr
470 <latexrelease>}
471 <latexrelease>\def\endeqnarray{%
472 <latexrelease>     \@@eqnocr
473 <latexrelease>     \egroup
474 <latexrelease>     \global\advance\c@equation\m@ne
475 <latexrelease>     $$\@ignoretrue
476 <latexrelease>}

```

```

477 <latexrelease>\EndIncludeInRelease
478 <*2ekernel>

479 \let\@eqnrel=\relax
(End of definition for \@eqcnt and others.)

\nonumber Switches off equation numbering.
480 \def\nonumber{\global\@eqnswfalse}
(End of definition for \nonumber.)

\@eqnrel
\@xeqnrel 481 \protected\def\@eqnrel{%
\@yeqnrel 482 {\ifnum0='}\fi
483 \@ifstar{%
484 \global\@eqpen\@M\@yeqnrel
485 }{%
486 \global\@eqpen\interdisplaylinepenalty \@yeqnrel
487 }%
488 }

489 \def\@yeqnrel{\@testopt\@xeqnrel\z@skip}

490 </2ekernel>
491 <*2ekernel | latexrelease>
492 <latexrelease>\IncludeInRelease{2020/10/01}%
493 <latexrelease> {\@xeqnrel}{eqnarray support calc syntax}%
494 \def\@xeqnrel[#1]{%
495 \ifnum0='{\fi}%
496 \@eqnrel
497 \noalign{\penalty\@eqpen\vskip\jot\@vspace@calcify{#1}}%
498 }
499 </2ekernel | latexrelease>
500 <latexrelease>\EndIncludeInRelease

501 <latexrelease>\IncludeInRelease{0000/00/00}%
502 <latexrelease> {\@xeqnrel}{eqnarray support calc syntax}%
503 <latexrelease>
504 <latexrelease>\def\@xeqnrel[#1]{%
505 <latexrelease> \ifnum0='{ \fi}%
506 <latexrelease> \@eqnrel
507 <latexrelease> \noalign{\penalty\@eqpen\vskip\jot\vskip #1\relax}%
508 <latexrelease>}
509 <latexrelease>\EndIncludeInRelease
510 <*2ekernel>

(End of definition for \@eqnrel, \@xeqnrel, and \@yeqnrel.)

\@@eqnrel
511 \def\@@eqnrel{\let\reserved@a\relax
512 \ifcase\@eqcnt \def\reserved@a{& &}\or \def\reserved@a{& &}%
513 \or \def\reserved@a{} \else
514 \let\reserved@a\empty
515 \latexerror{Too many columns in eqnarray environment}\@ehc\fi
516 \reserved@a \if@eqnsw\@eqnnum\stepcounter{equation}\fi
517 \global\@eqnswtrue\global\@eqcnt\z@\cr}

```

(End of definition for `\@eqnocr`.)

`\eqnarray@seqnocr`) Here's the `eqnarray*` environment:

```
518 \let\@seqnocr=\@eqnocr
519 \@namedef{eqnarray*}{\protected\def\@eqnocr{\nonumber\@seqnocr}\eqnarray}
520 \@namedef{endeqnarray*}{\nonumber\endeqnarray}
(End of definition for \@seqnocr.)
```

`\lefteqn` `\lefteqn{FORMULA}` typesets FORMULA in display math style flushleft in a box of width zero.

```
521 \def\lefteqn#1{\rlap{$\displaystyle #1$}}
(End of definition for \lefteqn.)
```

`\ensuremath` In math mode, `\ensuremath{text}` is equivalent to `text`; in LR or paragraph mode, it is equivalent to `$text$`. `\relax` is not needed in front of the `\ifmmode` as `\protect` will be `\let` to `\relax`. This version (due to Donald Arseneau) avoids duplicating its argument in the ‘then’ and ‘else’ part of the `\ifmath` which is necessary in nested ‘tabular’ like environments. See `amslatex/2104`.

```
522 \DeclareRobustCommand{\ensuremath}{%
523   \ifmmode
524     \expandafter\@firstofone
525   \else
526     \expandafter\@ensuredmath
527   \fi}
```

(End of definition for `\ensuremath`.)

`\@ensuredmath` The `\relax` stops `\ensuremath{}` starting display math.

```
528 \long\def\@ensuredmath#1{$\relax#1$}
(End of definition for \@ensuredmath.)
```

Lua<sub>TeX</sub> contains new math primitives to place expression over or under horizontally extensible glyphs. Before Lua<sub>TeX</sub> 1.14 these did not work correctly with the `\mathstyle` primitive and sometimes did not use cramped style in consistent ways. For newer version, we opt into the corrected behavior.

```
529 \ifx\mathdefaultsmode\undefined\else
530   \mathdefaultsmode=1
531 \fi
```

`\eqno` Ensure the (deprecated) `$$..\eqno 1 $$` ignores spaces.

```
\leqno 532 \</2kernel>
533 \<*2kernel | latexrelease>
534 \<latexrelease>\IncludeInRelease{2023/06/01}%
535 \<latexrelease>          {\eqno}{add ignorespaces to eqno}%
536 \expandafter\let\expandafter\@kernel@eqno\csname tex_eqno:D\endcsname
537 \expandafter\let\expandafter\@kernel@leqno\csname tex_leqno:D\endcsname
538 \protected\def\eqno{\@kernel@eqno\aftergroup\ignorespaces}
539 \protected\def\leqno{\@kernel@leqno\aftergroup\ignorespaces}
540 \</2kernel | latexrelease>
541 \<latexrelease>\EndIncludeInRelease
542 \<latexrelease>\IncludeInRelease{0000/00/00}%
```

```

543 <latexrelease>                {\eqno}{add ignorespaces to eqno}%
544 <latexrelease>\let\eqno\@kernel@eqno
545 <latexrelease>\let\leqno\@kernel@leqno
546 <latexrelease>\EndIncludeInRelease

```

(End of definition for \eqno and \leqno.)

## 1.3 External options to the standard document classes

### 1.3.1 Left equation numbering

**\@eqnnum** To put the equation number on the left side of an equation we have to use a little trick. The number is shifted `\displaywidth` to the left inside a box of (approximately) zero width. This fails when the equation is too wide, the equation number than may overprint the equation itself.

```

547 <*\leqno>
548 \renewcommand\@eqnnum{\hb@xt@.01\p@{}}%
549                               \rlap{\normalfont\normalcolor
550                               \hskip -\displaywidth(\theequation)}}
551 </\leqno>

```

(End of definition for \@eqnnum.)

### 1.3.2 Flush left equations

To get the displayed math environments to print the contents flush left (with an indentation) we have to redefine all of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>'s displayed math environments.

**\mathindent** The amount of indentation of the equations is stored in a register.

```

552 <*\fleqn>
553 \newskip\mathindent

```

The setting of `\mathindent` has to be deferred until the class file has been processed, because `\leftmargini` is still 0pt wide at the moment `fleqn.clo` is read in.

```

554 \AtEndOfClass{\mathindent\leftmargini}

```

(End of definition for \mathindent.)

**\[** Begin display math;

```

555 \IncludeInRelease{2015/01/01}{\[\]{Make \[ robust}%
556 \DeclareRobustCommand\[\{\relax
557                               \ifmmode\@badmath
558                               \else
559                               \begin{trivlist}%
560                               \@beginparpenalty\predisplaypenalty
561                               \@endparpenalty\postdisplaypenalty
562                               \item[]\leavevmode
563                               \hb@xt@\linewidth\bgroup $\m@th\displaystyle %$
564                               \hskip\mathindent\bgroup
565                               \fi}
566 \EndIncludeInRelease

```

```

567 \IncludeInRelease{0000/00/00}{\[]}{Make \[ robust}%
568 \renewcommand\[\relax
569     \ifmmode\@badmath
570     \else
571     \begin{trivlist}%
572     \@beginparpenalty\predisplaypenalty
573     \@endparpenalty\postdisplaypenalty
574     \item[]\leavevmode
575     \hb@xt@\linewidth\bgroup $\m@th\displaystyle %$
576     \hskip\mathindent\bgroup
577     \fi}
578 \EndIncludeInRelease

```

(End of definition for \[.)

\] end display math;

```

579 \IncludeInRelease{2015/01/01}{\[]}{Make \] robust}%
580 \DeclareRobustCommand\]\relax
581     \ifmmode
582     \egroup $\hfil% $
583     \egroup
584     \end{trivlist}%
585     \else \@badmath
586     \fi}
587 \EndIncludeInRelease

```

```

588 \IncludeInRelease{0000/00/00}{\[]}{Make \] robust}%
589 \renewcommand\]\relax
590     \ifmmode
591     \egroup $\hfil% $
592     \egroup
593     \end{trivlist}%
594     \else \@badmath
595     \fi}
596 \EndIncludeInRelease

```

(End of definition for \].)

**equation** (*env.*) The equation environment

```

597 \renewenvironment{equation}%
598 {\@beginparpenalty\predisplaypenalty
599 \@endparpenalty\postdisplaypenalty
600 \refstepcounter{equation}%
601 \trivlist \item[]\leavevmode
602 \hb@xt@\linewidth\bgroup $\m@th% $
603 \displaystyle
604 \hskip\mathindent}%

```

Ensure that there is at least a space between formula and equation number so that they don't bump in each other.

```

605 {\$ \hskip .3em minus.3em\hfil % $
606 \displaywidth\linewidth\hbox{\@eqnnum}%
607 \egroup
608 \endtrivlist}

```

`eqnarray` (*env.*) The `eqnarray` environment

```

609 \renewenvironment{eqnarray}{%
610   \stepcounter{equation}%
611   \def\@currentlabel{\p@equation\theequation}%
612   \def\@currentcounter{equation}%
613   \global\@eqnswtrue\m@th
614   \global\@eqcnt\z@
615   \tabskip\mathindent
616   \let\@=\@eqncr
617   \setlength\abovedisplayskip{\topsep}%
618   \ifvmode
619     \addtolength\abovedisplayskip{\partopsep}%
620   \fi

```

When the documentclass uses a non-zero `\parskip` setting the `\topsep` might have a negative value to compensate for that. Therefore we add `\parskip` to `\abovedisplayskip`.

```

621   \addtolength\abovedisplayskip{\parskip}%
622   \setlength\belowdisplayskip{\abovedisplayskip}%
623   \setlength\belowdisplayshortskip{\abovedisplayskip}%
624   \setlength\abovedisplayshortskip{\abovedisplayskip}%
625   \dollar\dollar@begin\everycr{}\halign to\linewidth%
626   \bgroup
627     \hskip\@centering
628     $\displaystyle\tabskip\z@skip{##}$\@eqnse1&%
629     \global\@eqcnt\@ne \hskip \tw@arraycolsep \hfil${##}$\hfil&%
630     \global\@eqcnt\tw@ \hskip \tw@arraycolsep
631     $\displaystyle{##}$\hfil \tabskip\@centering&%
632     \global\@eqcnt\thr@@
633     \hb@xt@\z@\bgroup\hss##\egroup\tabskip\z@skip\cr}%
634     {\@eqncr
635   \egroup
636   \global\advance\c@equation\m@ne\dollar\dollar@end
637   \@ignoretrue
638   }
639 \fleqn

```

## File 39

# ltlists.dtx

## 1 List, and related environments

The generic commands for creating an indented environment – `enumerate`, `itemize`, `quote`, etc – are:

```
\list{<LABEL>}{<COMMANDS>} ... \endlist
```

which can be invoked by the user as the list environment. The LABEL argument specifies item labeling. COMMANDS contains commands for changing the horizontal and vertical spacing parameters.

Each item of the environment is begun by the command `\item[ITEMLABEL]` which produces an item labeled by ITEMLABEL. If the argument is missing, then the LABEL argument of the `\list` command is used as the item label.

The label is formed by putting `\makelabel{<ITEMLABEL>}` in an hbox whose width is either its natural width or else `\labelwidth`, whichever is larger. The `\list` command defines `\makelabel` to have the default definition:

```
\makelabel{<ARG>} == BEGIN \hfil ARG END
```

which, for a label of width less than `\labelwidth`, puts the label flushright, `\labelsep` to the left of the item's text. However, `\makelabel` can be `\let` to another command by the `\list`'s COMMANDS argument.

A `\usecounter{<foo>}` command in the second argument causes the counter *foo* to be initialized to zero, and stepped by every `\item` command without an argument. (`\label` commands within the list refer to this counter.)

When you leave a list environment, returning either to an enclosing list or normal text mode, LaTeX begins a new paragraph if and only if you leave a blank line after the `\end` command. This is accomplished by the `\@endparenv` command.

Blank lines are ignored every other reasonable place–i.e.:

- Between the `\begin{list}` and the first `\item`,
- Between the `\item` and the text of that item.
- Between the end of the last item and the `\end{list}`.

For an environment like quotation, in which items are not labeled, the entire environment is a single item. It is defined by letting `\quotation == \list{}{...}\item\relax`. (Note the `\relax`, there in case the first character in the environment is a '['.) The spacing parameters provide a great deal of flexibility in designing the format, including the ability to let the indentation of the first paragraph be different from that of the subsequent ones.

The trivlist environment is equivalent to a list environment whose second argument sets the following parameter values:

`\leftmargin = 0`: causes no indentation of left margin

`\labelwidth = 0`: see below for precise effect this has.

`\itemindent = 0`: with a null label, makes first paragraph have no indentation. Succeeding paragraphs have `\parindent` indentation. To give first paragraph same indentation, set `\itemindent = \parindent` before the `\item[]`.

Every `\item` in a `trivlist` environment must have an argument—in many cases, this will be the null argument (`\item[]`). The `trivlist` environment is mainly used for paragraphing environments, like `verbatim`, in which there is no margin change. It provides the same vertical spacing as the `list` environment, and works reasonably well when it occurs immediately after an `\item` command in an enclosing list.

## 1.1 List and Trivlist

The following variables are used inside a list environment:

`\totalleftmargin` The distance that the prevailing left margin is indented from the outermost left margin,

`\linewidth` The width of the current line. Must be initialized to `\hsize`.

`\listdepth` A count for holding current list nesting depth.

`\makelabel` A macro with a single argument, used to generate the label from the argument (given or implied) of the `\item` command. Initialized to `\mklab` by the `\list` command. This command must produce some stretch—i.e., an `\hfil`.

`@inlabel` A switch that is false except between the time an `\item` is encountered and the time that `TeX` actually enters horizontal mode. Should be tested by commands that can be messed up by the list environment's use of `\everypar`.

`\box\@labels` When `@inlabel = true`, it holds the labels to be put out by `\everypar`.

`@noparitem` A switch set by `\list` when `@inlabel = true`. Handles the case of a `\list` being the first thing in an item.

`@nopalist` A switch set true for a list that begins an item. No `\topsep` space is added before or after `\item`'s such a list.

`@newlist` Set true by `\list`, set false by the first text (by `\everypar`).

`@noitemarg` Set true when executing an `\item` with no explicit argument. Used to save space. To save time, make two separate `\@item` commands.

`@nbrlist` Set true by `\usecounter` command, causes list to be numbered.

`\@listctr` `\def`'ed by `\usecounter` to name of counter.

`@noskipsec` A switch set true by a sectioning command when it is creating an in-text heading with `\everypar`.

Throughout a list environment, `\hsize` is the width of the current line, measured from the outermost left margin to the outermost right margin. Environments like `tabbing` should use `\linewidth` instead of `\hsize`.

Here are the parameters of a list that can be set by commands in the `\list's` `COMMANDS` argument. These parameters are all `TeX` skips or dimensions (defined by `\newskip` or `\newdimen`), so the usual `TeX` or `LATeX` commands can be used to set them. The commands will be executed in `vmode` if and only if the `\list` was preceded by a `\par` (or something like an `\end{list}`), so the spacing parameters can be set according to whether the list is inside a paragraph or is its own paragraph.

## 1.2 Vertical Spacing (skips)

`\topsep`: Space between first item and preceding paragraph.

`\partopsep`: Extra space added to `\topsep` when environment starts a new paragraph (is called in `vmode`).

`\itemsep`: Space between successive items.

`\parsep`: Space between paragraphs within an item – the `\parskip` for this environment.

## 1.3 Penalties

`\@beginparpenalty`: put at the beginning of a list

`\@endparpenalty`: put at end of list

`\@itempenalty`: put between items.

## 1.4 Horizontal Spacing (dimens)

`\leftmargin`: space between left margin of enclosing environment (or of page if top level list) and left margin of this list. Must be nonnegative.

`\rightmargin`: analogous.

`\listparindent`: extra indentation at beginning of every paragraph of a list except the one started by the `\item` command. May be negative! Usually, labeled lists have `\listparindent` equal to zero.

`\itemindent`: extra indentation added right BEFORE an item label.

`\labelwidth`: nominal width of box that contains the label. If the natural width of the label  $\leq$  `\labelwidth`, then the label is flushed right inside a box of width `\labelwidth` (with an `\hfil`). Otherwise, a box of the natural width is employed, which causes an indentation of the text on that line.

`\labelsep`: space between end of label box and text of first item.

## 1.5 Default Values

Defaults for the list environment are set as follows. First, `\rightmargin`, `\listparindent` and `\itemindent` are set to 0pt. Then, one of the commands `\@listi`, `\@listii`, ... , `\@listvi` is called, depending upon the current level of the list. The `\@list ...` commands should be defined by the document style. A convention that the document style should follow is to set `\leftmargin` to `\leftmargini`, ..., `\leftmarginvi` for the appropriate level. Items that aren't changed may be left alone, but everything that could possibly be changed must be reset. *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more)*:

```
\list{LABEL}{COMMANDS} ==  
  BEGIN  
    if \@listdepth > 5  
      then LaTeX error: 'Too deeply nested'  
      else \@listdepth :=G \@listdepth + 1
```

```

fi
\rightmargin      := 0pt
\listparindent    := 0pt
\itemindent       := 0pt
\eval{@list \romannumeral\the\@listdepth} %% Set default values:
\itemlabel        :=L LABEL
\makelabel        == \@mklab
@nmbrlist         :=L false
COMMANDS

\@trivlist          % commands common to \list and \trivlist

\parskip           :=L \parsep
\parindent         :=L \listparindent
\linewidth         :=L \linewidth - \rightmargin - \leftmargin
\@totalleftmargin :=L \@totalleftmargin + \leftmargin
\parshape 1 \@totalleftmargin \linewidth
\ignorespaces      % gobble space up to \item
END

\endlist == BEGIN \@listdepth :=G \@listdepth -1
              \endtrivlist
              END

\@trivlist ==
BEGIN
  if @newlist = T then \@noitemerr fi
                      %% This command removed for some forgotten reason.
  \@topsepadd :=L \topsep
  if @noskipsec then leave vertical mode fi %% Added 11 Jun 85
  if vertical mode
  then \@topsepadd :=L \@topsepadd + \partopsep
  else \unskip \par % remove glue from end of last line
  fi
  if @inlabel = true
  then @noparitem :=L true
       @noparlist :=L true
  else @noparlist :=L false
       \@topsep   :=L \@topsepadd
  fi
  \@topsep      :=L \@topsep + \parskip %% Change 4 Sep 85
  \leftskip     :=L 0pt % Restore paragraphing parameters
  \rightskip    :=L \@rightskip
  \parfillskip  :=L 0pt + 1fil

NOTE: \@setpar called on every \list in case \par has been
temporarily munged before the \list command.
\@setpar{if @newlist = false then {\@@par} fi}
\@newlist      :=G T
\@outerparskip :=L \parskip

```

```

END

\trivlist ==
BEGIN
  \parsep      := \parskip
  @nmbrlist := F
  \@trivlist
  \labelwidth := 0
  \leftmargin := 0
  \itemindent := \parindent
  \@itemlabel :=L "empty"      %% added 93/12/13
  \makelabel{LABEL} == LABEL
END

\endtrivlist ==
BEGIN
  if @inlabel = T then \indent fi
  if horizontal mode then \unskip \par fi
  if @noparlist = true
    else if \lastskip > 0
      then \@tempkipa := \lastskip
           \vskip - \lastskip
           \vskip \@tempkipa -\@outerparskip + \parskip
      fi
    \endparenv
  fi
END

\@endparenv ==
BEGIN
  \addpenalty{@endparpenalty}
  \addvspace{@topsepadd}
  \endgroup    %% ends the \begin command's \begingroup
  \par == BEGIN
    \@restorepar
    \everypar{}
    \par
  END
  \everypar == BEGIN remove \lastbox \everypar{} END
  \begingroup %% to match the \end commands \endgroup
END

\item == BEGIN if math mode then WARNING fi
          if next char = [
            then \@item
            else @noitemarg := true
                 \@item[@itemlabel]
          fi
END

\@item[LAB] ==

```

```

BEGIN
if @noperitem = true
then @noperitem := false
    % NOTE: then clause hardly every taken,
    % so made a macro \@donoperitem
    \box\@labels :=G \hbox{\hskip -\leftmargin
                        \box\@labels
                        \hskip \leftmargin }

if @minipage = false then
    \@tempskipa := \lastskip
    \vskip -\lastskip
    \vskip \@tempskipa + \@outerparskip - \parskip
fi
else if @inlabel = true
    then \indent \par % previous item empty.
    fi
    if hmode then 2 \unskip's
        % To remove any space at end of prev.
        % paragraph that could cause a blank line.
        \par
    fi
    if @newlist = T
        then if @nobreak = T % Kludge if list follows \section
            then \addvspace{\@outerparskip - \parskip}
            else \addpenalty{\@beginparpenalty}
                \addvspace{\@topsep}
                \addvspace{-\parskip} %% added 4 Sep 85
            fi
        else \addpenalty{\@itempenalty}
            \addvspace{\itemsep}
        fi
    @inlabel :=G true
fi

\everypar{ @minipage :=G F
            @newlist :=G F
            if @inlabel = true
            then @inlabel :=G false
                \hskip -\parindent
                \box\@labels
                \penalty 0
                %% 3 Oct 85 - allow line break here
                \box\@labels :=G null
            fi
            \everypar{} }

@nobreak :=G false
if @noitemarg = true
then @noitemarg := false
    if @nmbrlist
    then \refstepcounter{\@listctr}

```

```

fi      fi
\@tempboxa :=L \hbox{\makelabel{LAB}}
\box\@labels :=G \@labels \hskip \itemindent
               \hskip - (\labelwidth + \labelsep)
               if \wd \@tempboxa > \labelwidth
                   then \box\@tempboxa
                   else \hbox to \labelwidth {\unhbox\@tempboxa}
               fi
               \hskip\labelsep
\ignorespaces %gobble space up to text
END

```

```

\makelabel{LABEL} == ERROR %% default to catch lonely \item

```

```

\usecounter{CTR} == BEGIN @nmbrlist :=L true
                        \@listctr == CTR
                        \setcounter{CTR}{0}
                        END

```

DEFINE \dimen's and \count  
*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

\topsep
\partopsep 1 (*2kernel)
\itemsep    2 \newskip\topsep
\parsep     3 \newskip\partopsep
\@topsep    4 \newskip\itemsep
\@topsepadd 5 \newskip\parsep
\@outerparskip 6 \newskip\@topsep
              7 \newskip\@topsepadd
              8 \newskip\@outerparskip

```

*(End of definition for \topsep and others.)*

```

\leftmargin
\rightmargin 9 \newdimen\leftmargin
\listparindent 10 \newdimen\rightmargin
\itemindent   11 \newdimen\listparindent
\labelwidth   12 \newdimen\itemindent
\labelsep     13 \newdimen\labelwidth
\linewidth    14 \newdimen\labelsep
\@totalleftmargin 15 \newdimen\linewidth
               16 \newdimen\@totalleftmargin \@totalleftmargin=\z@

```

*(End of definition for \leftmargin and others.)*

```

\leftmargini
\leftmarginii 17 \newdimen\leftmargini
\leftmarginiii 18 \newdimen\leftmarginii
\leftmarginiv 19 \newdimen\leftmarginiii
\leftmarginv 20 \newdimen\leftmarginiv
\leftmarginvi 21 \newdimen\leftmarginv
                22 \newdimen\leftmarginvi

                (End of definition for \leftmargini and others.)

\@listdepth
\itempenalty 23 \newcount\@listdepth \@listdepth=0
\@beginparpenalty 24 \newcount\@itempenalty
\@endparpenalty 25 \newcount\@beginparpenalty
                26 \newcount\@endparpenalty

                (End of definition for \@listdepth and others.)

\@labels
                27 \newbox\@labels

                (End of definition for \@labels.)

\if@inlabel
\@inlabelfalse 28 \newif\if@inlabel \@inlabelfalse
\@inlabeltrue
                (End of definition for \if@inlabel, \@inlabelfalse, and \@inlabeltrue.)

\if@newlist
\@newlistfalse 29 \newif\if@newlist \@newlistfalse
\@newlisttrue
                (End of definition for \if@newlist, \@newlistfalse, and \@newlisttrue.)

\if@nparitem
\@nparitemfalse 30 \newif\if@nparitem \@nparitemfalse
\@nparitemtrue
                (End of definition for \if@nparitem, \@nparitemfalse, and \@nparitemtrue.)

\if@nparlist
\@nparlistfalse 31 \newif\if@nparlist \@nparlistfalse
\@nparlisttrue
                (End of definition for \if@nparlist, \@nparlistfalse, and \@nparlisttrue.)

\if@noitemarg
\@noitemargfalse 32 \newif\if@noitemarg \@noitemargfalse
\@noitemargtrue
                (End of definition for \if@noitemarg, \@noitemargfalse, and \@noitemargtrue.)

\if@newlist
\@newlistfalse 33 \newif\if@nmbolist \@nmbolistfalse
\@newlisttrue
                (End of definition for \if@newlist, \@newlistfalse, and \@newlisttrue.)

```

`list\list.)`

```

34 \def\list#1#2{%
35   \ifnum \@listdepth >5\relax
36     \toodeep
37   \else
38     \global\advance\@listdepth\@ne
39   \fi
40   \rightmargin\z@
41   \listparindent\z@
42   \itemindent\z@
43   \csname @list\romannumeral\the\@listdepth\endcsname
44   \def\@itemlabel{#1}%
45   \let\makelabel\@mklab
46   \@nmbrlistfalse
47   #2\relax
48   \@trivlist
49   \parskip\parsep
50   \parindent\listparindent
51   \advance\linewidth -\rightmargin
52   \advance\linewidth -\leftmargin
53   \advance\@totalleftmargin \leftmargin
54   \parshape \@ne \@totalleftmargin \linewidth
55   \ignorespaces}

```

*(End of definition for \list.)*

`\par@deathcycles`

```

56 \newcount\par@deathcycles

```

*(End of definition for \par@deathcycles.)*

`\@trivlist` Because `\par` is sometimes made a no-op it is possible for a missing `\item` to produce a loop that does not fill memory and so never gets trapped by T<sub>E</sub>X. We thus need to trap this here by setting `\par` to count the number of times a paragraph is called with no progress being made started.

```

57 \def\@trivlist{%
58   \if@noskipsec \leavevmode \fi
59   \@topsepadd \topsep
60   \ifvmode
61     \advance\@topsepadd \partopsep
62   \else
63     \unskip \par
64   \fi
65   \if@inlabel
66     \@nparitemtrue
67     \@nparlisttrue
68   \else
69     \if@newlist \@noitemerr \fi
70     \@nparlistfalse
71     \@topsep \@topsepadd
72   \fi
73   \advance\@topsep \parskip
74   \leftskip \z@skip
75   \rightskip \@rightskip
76   \parfillskip \@flushglue

```

```

77 \par@deathcycles \z@
78 \@setpar{\if@newlist
79         \advance\par@deathcycles \@ne
80         \ifnum \par@deathcycles >\@m
81         \@noitemerr
82         {\@@par}%
83         \fi
84         \else
85         {\@@par}%
86         \fi}%
87 \global \@newlisttrue
88 \@outerparskip \parskip}

```

(End of definition for \@trivlist.)

~~trivlist~~ **trivlist**

```

89 \def\trivlist{%
90 \parsep\parskip
91 \@nmbrlistfalse
92 \@trivlist
93 \labelwidth\z@
94 \leftmargin\z@
95 \itemindent\z@

```

We initialise \@itemlabel so that a trivlist with an \item not having an optional argument doesn't produce an error message.

```

96 \let\@itemlabel\@empty
97 \def\makelabel##1{##1}}

```

(End of definition for \trivlist.)

**\endlist**

```

98 \def\endlist{%
99 \global\advance\@listdepth\m@ne
100 \endtrivlist}

```

(End of definition for \endlist.)

The definition of \trivlist used to be in ltspc.dtx so that other commands could be 'let to it'. They now use \def.

**\endtrivlist**

```

101 \def\endtrivlist{%
102 \if@inlabel
103 \leavevmode
104 \global \@inlabelfalse
105 \fi
106 \if@newlist
107 \@noitemerr
108 \global \@newlistfalse
109 \fi
110 \ifhmode\unskip \par

```

We also check if we are in math mode and issue an error message if so (hoping that \@currenvir resolves suitably). Otherwise the usual "perhaps a missing item" error will get triggered later which is confusing.

```

111 \else

```

```

112     \inmatherr{\end{\@currenvir}}}%
113   \fi
114   \if@nolist \else
115     \ifdim\lastskip >\z@
116       \@tempskipa\lastskip \vskip -\lastskip
117       \advance\@tempskipa\parskip \advance\@tempskipa -\@outerparskip
118       \vskip\@tempskipa
119     \fi
120   \endparenv
121 \fi
122 }

```

(End of definition for `\endtrivlist`.)

`\@endparenv` To suppress the paragraph indentation in text immediately following a paragraph-making environment, `\everypar` is changed to remove the space, and `\par` is redefined to restore `\everypar`. Instead of redefining `\par` and `\everypar`, `\@endparenv` was changed to set the `@endpe` switch, letting `\end` redefine `\par` and `\everypar`.

This allows paragraph-making environments to work right when called by other environments. (Changed 27 Oct 86)

In 2024 this logic was partially replaced with a new algorithm:

- `\if@endpe` is now set globally to `true` or `false`.
- In addition `\@endpetrue` initiates an `\aftergroup` call to `\propagate@doendpe` if it is used inside a group.
- `\propagate@doendpe` in turn checks the status of `\if@endpe` and if that is `true` it calls `\@doendpe` otherwise it does nothing.
- `\@doendpe` in turn calls `\@endpetrue` and also makes the necessary changes to `\par` and `\everypar` so that they handle as before any empty line that follows the environment.
- Because of the `\@endpetrue` we get another `\aftergroup`, so the mechanism slowly migrates out of several groups if those follow immediately after the end of the environment. If, however, there is a new paragraph started or an explicit `\par` before the next group ends then this will result in a call to `\@endpefalse` and the migration stops (note that `\propagate@doendpe` is still called once after the group but does nothing).
- Using this approach something like

```

{% some customization here
\begin{equation}
  x=y
\end{equation}}
some text

```

is still correctly identified as a paragraph continuation so that there is no indentation before `some text`.

- We can get away with using global settings of `\if@endpe` even in nested situations (without keeping track of the status in a stack), because the switch change is made only at the very end of such environments, basically directly before the `\endgroup` in `\end`, and it is later set back to `false` by the next `\everypar` or the next `\par`. Even if the environment is called without using `\begin \end`, the situation doesn't change (or rather cause a problem).
- However, there is one scenario where the new approach would change the behavior. If a box is being built, e.g., with `\setbox`, we have now the case that a `\@endpetrue` inside would migrate out into a context in which it should not be true (because the box might get used elsewhere, e.g., a float). In the past, due to local switch changes, that didn't happen, i.e., `\if@endpe` would revert to `false` at the end of the box definition.
- Thus, to avoid that one has to explicitly set it back to false at the end of such constructions, just as we also need to prevent colors from migrating out. Thus the correct place to do this is in `\color@endgroup` because that is always called at that point.

```

123 \def\@endparenv{%
124   \addpenalty\@endparpenalty\addvspace\@topsepadd\@endpetrue}
125 <latexrelease>\IncludeInRelease{2015/01/01}{\@doendpe}{clubpenalty fix}%
126 \def\@doendpe{\@endpetrue
127   \def\par{\@restorepar

```

If a section heading changes `\clubpenalty` to keep lines after it together then this modification is restored via the `\everypar` mechanism at the start of the next paragraph. As we destroy the contents of this token here we explicitly set `\clubpenalty` back to its default.

```

128       \clubpenalty\@clubpenalty
129       \@endpefalse
130       \everypar{}\par}%

```

Use `\setbox0=\lastbox` instead of `\hskip -\parindent` so that a `\noindent` becomes a no-op when used before a line immediately following a list environment(23 Oct 86).

```

131   \everypar
132     {\setbox\z@\lastbox}%
133     \everypar{}\@endpefalse}}
134 <latexrelease>\EndIncludeInRelease
135 <latexrelease>\IncludeInRelease{0000/00/00}{\@doendpe}{clubpenalty fix}%
136 <latexrelease>\def\@doendpe{\@endpetrue
137 <latexrelease>   \def\par{\@restorepar\everypar{}\par\@endpefalse}\everypar
138 <latexrelease>     {\setbox\z@\lastbox}\everypar{}\@endpefalse}}
139 <latexrelease>\EndIncludeInRelease

```

*(End of definition for \@endparenv and \@doendpe.)*

```

\if@endpe As outlined above these are no longer simple switches, but we keep the name because it
\@endpefalse is used all over the place.
\@endpetrue
\propagate@doendpe 140 \newif\if@endpe

```

```

141 </2ekernel>
142 <*2ekernel | latexrelease>
143 <latexrelease>\IncludeInRelease{2024/11/01}%
144 <latexrelease>                {\@endpetrue}{New @endpe handling}%
145 \def\@endpefalse{\global\let\if@endpe\iffalse}
146 \def\@endpetrue {%
147   \global\let\if@endpe\iftrue

```

If we are inside a simple or a semi-simple group then propagate to the outside, for all other group types do nothing. Normally, we would start out in the group opened by `\begin` (type 14). When we migrate out of that we are either on top-level (type 0) or in another semi-simple group (type 14) or in some other group. Thus, the best order of tests is to first test for 14, then for 0 and finally for 1 (simple group).

```

148   \ifnum\currentgrouptype =14          % semi-simple group
149     \aftergroup\propagate@doendpe
150   \else
151     \ifnum\currentgrouptype =\z@      % no group: top-level
152     \else
153       \ifnum\currentgrouptype =\@ne  % simple group
154       \aftergroup\propagate@doendpe
155     \fi
156   \fi
157 \fi
158 }

```

If `\if@endpe` is still true after the group ends, we run `\@doendpe` that in turn runs another `\@endpetrue` (besides other things), thus propagating further if necessary. However, if the endpe situation got resolved and `\if@endpe` is false then nothing further happens.

```

159 \def\propagate@doendpe{\if@endpe \@doendpe \fi}
160 </2ekernel | latexrelease>
161 <latexrelease>\EndIncludeInRelease
162 <latexrelease>\IncludeInRelease{0000/00/00}%
163 <latexrelease>                {\@endpetrue}{New @endpe handling}%
164 <latexrelease>
165 <latexrelease>
166 <latexrelease>\def\@endpefalse{\let\if@endpe\iffalse}
167 <latexrelease>\def\@endpetrue{\let\if@endpe\iftrue}
168 <latexrelease>
169 <latexrelease>\EndIncludeInRelease
170 <*2ekernel>

```

*(End of definition for \if@endpe and others.)*

`\@mklab`

```

171 \def\@mklab#1{\hfil #1}

```

*(End of definition for \@mklab.)*

`\item`

```

172 \def\item{%
173   \@inmatherr\item
174   \@ifnextchar [\@item{\@noitemargtrue \@item[\@itemlabel]}}

```

*(End of definition for \item.)*

`\@donoparitem`

```

175 \def\@donoparitem{%
176   \@noparitemfalse
177   \global\setbox\@labels\hbox{\hskip -\leftmargin
178                                 \unhbox\@labels
179                                 \hskip \leftmargin}%
180   \if@minipage\else
181     \@tempskipa\lastskip
182     \vskip -\lastskip
183     \advance\@tempskipa\@outerparskip
184     \advance\@tempskipa -\parskip
185     \vskip\@tempskipa
186   \fi}

```

*(End of definition for \@donoparitem.)*

`\@item`

```

187 \def\@item[#1]{%
188   \if@noparitem
189     \@donoparitem
190   \else
191     \if@inlabel
192       \indent \par
193     \fi
194     \ifhmode
195       \unskip\unskip \par
196     \fi
197     \if@newlist
198       \if@nobreak
199         \@nbitem
200       \else
201         \addpenalty\@beginparpenalty
202         \addvspace\@topsep
203         \addvspace{-\parskip}%
204       \fi
205     \else
206       \addpenalty\@itempenalty
207       \addvspace\itemsep
208     \fi
209     \global\@inlabeltrue
210   \fi
211   \everypar{%
212     \@minipagefalse
213     \global\@newlistfalse

```

This `\if@inlabel` check is needed in case an item starts of inside a group so that `\everypar` does not become empty outside that group.

```

214   \if@inlabel
215     \global\@inlabelfalse

```

The paragraph indent is now removed by using `\setbox...` since this makes `\noindent` a no-op here, as it should be. Thus the following comment is redundant but is left here for the sake of future historians: this next command was changed from an `hskip` to a kern to avoid a break point after the `parindent` box: the skip could cause a line-break if a very long label occurs in `raggedright` setting. If `\noindent` was used after `\item` want

to cancel the `\itemindent` skip. This case can be detected as the indentation box will be void.

```

216      {\setbox\z@\lastbox
217       \ifvoid\z@
218        \kern-\itemindent
219       \fi}%
220      \box\@labels
221      \penalty\z@
222      \fi

```

This code is intended to prevent a page break after the first line of an item that comes immediately after a section title. It may be sensible to always forbid a page break after one line of an item? As with all such settings of `\clubpenalty` it is local so will have no effect if the item starts in a group.

Only resetting `@nobreak` when it is true is now essential since now it is sometimes set locally.

```

223      \if@nobreak
224        \@nobreakfalse
225        \clubpenalty \@M
226      \else
227        \clubpenalty \@clubpenalty
228        \everypar{}%
229      \fi}%
230      \if@noitemarg
231        \@noitemargfalse
232        \if@nmbrlist
233          \refstepcounter\@listctr
234        \fi
235      \fi

```

We use `\sbox` to support colour commands.

```

236      \sbox\@tempboxa{\makelabel{#1}}%
237      \global\setbox\@labels\hbox{%
238        \unhbox\@labels
239        \hskip \itemindent
240        \hskip -\labelwidth
241        \hskip -\labelsep
242        \ifdim \wd\@tempboxa >\labelwidth
243          \box\@tempboxa
244        \else
245          \hbox to\labelwidth {\unhbox\@tempboxa}%
246        \fi
247        \hskip \labelsep}%
248      \ignorespaces}

```

*(End of definition for \item.)*

`\makelabel`

```

249 \def\makelabel#1{%
250   \@latex@error{Lonely \string\item--perhaps a missing
251     list environment}\@ehc}

```

(End of definition for \makelabel.)

\@nbitem

```
252 \def\@nbitem{%
253   \@tempskipa\@outerparskip
254   \advance\@tempskipa -\parskip
255   \addvspace\@tempskipa}
```

(End of definition for \@nbitem.)

\usecounter

```
256 \def\usecounter#1{\@nmblisttrue\def\@listctr{#1}\setcounter{#1}\z@}
```

(End of definition for \usecounter.)

## 1.6 Itemize and Enumerate

Enumeration is done with four counters: `enumi`, `enumii`, `enumiii` and `enumiv`, where `enumN` controls the numbering of the Nth level enumeration. The label is generated by the commands `\labelenumi ... \labelenumiv`, which should be defined by the document style. Note that `\p@enumN\theenumN` defines the output of a `\ref` command. A typical definition might be:

```
\def\theenumii{\alph{enumii}}
\def\p@enumii{\theenumi}
\def\labelenumii{(\theenumii)}
```

which will print the labels as ‘(a)’, ‘(b)’, ... and print a `\ref` as ‘3a’.

The item numbers are moved to the right of the label box, so they are always a distance of `\labelsep` from the item.

`\@enumdepth` holds the current enumeration nesting depth.

Itemization is controlled by four commands: `\labelitemi`, `\labelitemii`, `\labelitemiii`, and `\labelitemiv`. To cause the second-level list to be bulleted, you just define `\labelitemii` to be `•`. `\@itemspacing` and `\@itemdepth` are the analogs of `\@enumspacing` and `\@enumdepth`.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\enumerate ==
BEGIN
  if \@enumdepth > 3
    then errormessage: “Too deeply nested”.
  else \@enumdepth :=L \@enumdepth + 1
    \@enumctr :=L eval(enum@\romannumeral\the\@enumdepth)
    \list{\label(\@enumctr)}
      {\usecounter{\@enumctr}
       \makelabel{LABEL} == \hss \llap{LABEL}}
    fi
  END
```

```
\endenumerate == \endlist
```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

\@enumdepth
257 \newcount\@enumdepth \@enumdepth = 0
(End of definition for \@enumdepth.)

\c@enumi
\c@enumii 258 \@definecounter{enumi}
\c@enumii 259 \@definecounter{enumii}
\c@enumiv 260 \@definecounter{enumiii}
261 \@definecounter{enumiv}
(End of definition for \c@enumi and others.)

enumerate (env.)
262 \def\enumerate{%
263   \ifnum \@enumdepth >\thr@@\toodeep\else
264     \advance\@enumdepth\@ne
265     \edef\@enumctr{enum\romannumeral\the\@enumdepth}%

266     \expandafter
267     \list
268       \csname label\@enumctr\endcsname
269       {\usecounter\@enumctr\def\makelabel##1{\hss\llap{##1}}}%
270   \fi}
271 \let\endenumerate =\endlist

Historical LATEX 2.09 comments (not necessarily accurate any more):
\itemize ==
BEGIN
  if \@itemdepth > 3
  then errormessage: 'Too deeply nested'.
  else \@itemdepth :=L \@itemdepth + 1
      \@itemitem == eval(labelitem\romannumeral\the\@itemdepth)
      \list{\@nameuse{\@itemitem}}
          {\makelabel{LABEL} == \hss \llap{LABEL}}
  fi
END

\enditemize == \endlist

End of historical LATEX 2.09 comments.

\@itemdepth
272 \newcount\@itemdepth \@itemdepth = 0
(End of definition for \@itemdepth.)

itemize (env.)
273 \def\itemize{%
274   \ifnum \@itemdepth >\thr@@\toodeep\else
275     \advance\@itemdepth\@ne
276     \edef\@itemitem{labelitem\romannumeral\the\@itemdepth}%

```

```

277 \expandafter
278 \list
279 \csname\@itemitem\endcsname
280 {\def\makelabel##1{\hss\llap{##1}}}%
281 \fi}

282 \let\enditemize =\endlist
283 \endkernel

```

## File 40

# ltboxes.dtx

## 1 L<sup>A</sup>T<sub>E</sub>X Box commands

`\makebox` `\makebox[ $\langle wid \rangle$ ][ $\langle pos \rangle$ ]{ $\langle obj \rangle$ }`  
Puts  $\langle obj \rangle$  in an `\hbox` of width  $\langle wid \rangle$ , positioned by  $\langle pos \rangle$ .  
The possible  $\langle pos \rangle$  are:  
s stretched,  
l flushleft,  
r flushright,  
c (default) centred.  
If  $\langle wid \rangle$  is missing, then  $\langle pos \rangle$  is also missing and  $\langle obj \rangle$  is put in an `\hbox` of its natural width.  
`\makebox( $\langle x \rangle$ , $\langle y \rangle$ )[ $\langle pos \rangle$ ]{ $\langle obj \rangle$ }`  
Puts  $\langle obj \rangle$  in an `\hbox` of width  $x * \text{\unitlength}$  and height  $y * \text{\unitlength}$ .  
 $\langle pos \rangle$  arguments are s, l, r or c (default) for stretched, flushleft, flushright or centred, and t or b for top, bottom – or combinations like tr or rb. Default for horizontal and vertical are centered. Note that in this picture mode version of `\makebox` a [b] aligns on the *bottom* of the text as documented. If you want to align on the *baseline* use `\makebox( , ) [b]{\raisebox{0pt}{\height}[0pt]{xyz}}` or `\makebox( , ) [b]{\smash{xyz}}`  
`\mbox` `\mbox{ $\langle obj \rangle$ }` The same as `\makebox{ $\langle obj \rangle$ }`, but is more efficient as no checking for optional arguments is done.  
`\newsavebox` `\newsavebox{ $\langle cmd \rangle$ }` : If  $\langle cmd \rangle$  is undefined, then defines it to be a T<sub>E</sub>X box register.  
`\savebox` `\savebox{ $\langle cmd \rangle$ }` ... :  $\langle cmd \rangle$  is defined to be a T<sub>E</sub>X box register, and the ‘...’ are any `\makebox` arguments. It is like `\makebox`, except it doesn’t produce text but saves the value in `\box  $\langle cmd \rangle$` .  
`\sbox` `\sbox{ $\langle cmd \rangle$ }{ $\langle obj \rangle$ }` is an efficient abbreviation for `\savebox{ $\langle cmd \rangle$ }{ $\langle obj \rangle$ }`.  
`lrbox (env.)` `\begin{lrbox}{ $\langle cmd \rangle$ }\text{\end{lrbox}}` is equivalent to `\sbox{ $\langle cmd \rangle$ }{ $\langle text \rangle$ }` except that any white space at the beginning and end of  $\langle text \rangle$  is ignored.  
`\framebox` `\framebox ...` : like `\makebox`, except it puts a ‘frame’ around the box. The frame is made of lines of thickness `\fboxrule`, separated by space `\fboxsep` from the text – except for `\framebox(X,Y) ...`, where the thickness of the lines is as for the picture environment, and there is no separation added.  
`\fbox` `\fbox{ $\langle obj \rangle$ }` is an abbreviation for `\framebox{ $\langle obj \rangle$ }`.  
`\parbox` `\parbox[ $\langle pos \rangle$ ][ $\langle height \rangle$ ][ $\langle inner-pos \rangle$ ]{ $\langle width \rangle$ }{ $\langle text \rangle$ }` : Makes a box with `\hsize  $\langle width \rangle$` , positioned by  $\langle pos \rangle$  as follows: c : `\vcenter` (placed in  $\$...\$$  if not in math mode) b : `\vbox` t : `\vtop` default value is c. Sets `\hsize :=  $\langle width \rangle$`  and calls `\@parboxrestore`, which does the following: Restores the original definitions of:  
`\par`  
`\`  
`\-`  
`\,`  
`\‘`  
`\=`

```

Resets the following parameters:
\parindent      = 0pt
\parskip        = 0pt
\linewidth      = \hsize
\@totalleftmargin = 0pt
\leftskip       = 0pt
\rightskip      = 0pt
\@rightskip     = 0pt
\parfillskip    = 0pt plus 1fil
\lineskip       = \normallineskip
\baselineskip   = \normalbaselineskip
Calls \sloppy
Note: \arrayparboxrestore same as \@parboxrestore but it doesn't restore \.
minipage (env.) minipage : Similar to \parbox, except it also makes this look like a page by setting
\textwidth == \columnwidth == box width
changes footnotes by redefining:
\@mpfn == mpfootnote
\thempfn == \thempfootnote
\@footnotetext == \@mpfootnotetext
resets the following list environment parameters:
\@listdepth == \@mplistdepth
where \@mplistdepth is initialized to zero,
and executes \@minipagerestore to allow the document style to reset any other
parameters it desires. It sets @minipage true, and resets \everypar to set it false. This
switch keeps \addvspace from putting space at the top of a minipage.
Change added 24 May 89: \minipage sets @minipage globally; \endminipage resets
it false.
\rule \rule[\langle raised \rangle]{\langle width \rangle}{\langle height \rangle} : Makes a \langle width \rangle * \langle height \rangle rule, raised
\langle raised \rangle.
\underline \underline{\langle text \rangle} : Makes an underlined hbox with \langle text \rangle in it.
\raisebox \raisebox{\langle distance \rangle}{\langle height \rangle}{\langle depth \rangle}{\langle box \rangle} :
Raises \langle box \rangle up by \langle distance \rangle length (down if \langle distance \rangle negative). Makes TEX think
that the new box extends \langle height \rangle above the line and \langle depth \rangle below, for a total vertical
length of \langle height \rangle + \langle depth \rangle. Default values of \langle height \rangle & \langle depth \rangle = actual height and
depth of box in new position.
1 \langle *2kernel \rangle
2 \message{boxes,}

\makebox \makebox User level command just looks for optional [ or (.
3 \langle /2kernel \rangle
4 \langle latexrelease \rangle \IncludeInRelease{2015/01/01}%
5 \langle latexrelease \rangle {\makebox}{\Make \makebox robust}%
6 \langle *2kernel | latexrelease \rangle
7 \DeclareRobustCommand\makebox{%
8 \leavevmode
9 \@ifnextchar(%)
10 \@makepicbox
11 {\@ifnextchar[\@makebox\mbox}}}%
12 \langle /2kernel | latexrelease \rangle
13 \langle latexrelease \rangle \EndIncludeInRelease

```

```

14 <latexrelease>\IncludeInRelease{0000/00/00}%
15 <latexrelease>          {\makebox}{Make \makebox robust}%
16 <latexrelease>\def\makebox{%
17 <latexrelease>  \leavevmode
18 <latexrelease>  \@ifnextchar(%)
19 <latexrelease>    \makepicbox
20 <latexrelease>    {\@ifnextchar[\@makebox\mbox}}%
21 <latexrelease>\expandafter\let\csname makebox \endcsname\@undefined
22 <latexrelease>\EndIncludeInRelease
23 <*2ekernel>

```

*(End of definition for \makebox.)*

**\mbox** The basic horizontal box command for L<sup>A</sup>T<sub>E</sub>X.

```
24 \DeclareRobustCommand\mbox[1]{\leavevmode\hbox{#1}}
```

*(End of definition for \mbox.)*

**\@makebox** Look for a possible second optional argument (defaults to c).

```

25 \def\@makebox[#1]{%
26   \@ifnextchar [{\@imakebox[#1]}{\@imakebox[#1][c]}}

```

*(End of definition for \@makebox.)*

**\@begin@tempboxa** Helper macro for supporting \height, \width etc. Grab #1 into \@tempboxa and measure it.

```

27 \long\def\@begin@tempboxa#1#2{%
28   \begingroup
29   \setbox\@tempboxa#1\color@begingroup#2\color@endgroup}%
30   \def\width{\wd\@tempboxa}%
31   \def\height{\ht\@tempboxa}%
32   \def\depth{\dp\@tempboxa}%
33   \let\totalheight\@ovri
34   \totalheight\height
35   \advance\totalheight\depth}

```

*(End of definition for \@begin@tempboxa.)*

**\@end@tempboxa** End the group started by \@begin@tempboxa, so that the scope of \height only includes the ‘length’ argument to the user-command.

```
36 \let\@end@tempboxa\endgroup
```

*(End of definition for \@end@tempboxa.)*

**\bm@c** Set up spacing.

```

\bm@l 37 \def\bm@c{\hss\unhbox\@tempboxa\hss}
\bm@r 38 \def\bm@l{\unhbox\@tempboxa\hss}\let\bm@t\bm@l
\bm@s 39 \def\bm@r{\hss\unhbox\@tempboxa}\let\bm@b\bm@r
\bm@t 40 \def\bm@s{\unhbox\@tempboxa}
\bm@b

```

*(End of definition for \bm@c and others.)*

`\@imakebox` Internal form of `\makebox`.

```

41 </2ekernel>
42 <latexrelease>\IncludeInRelease{2023/11/01}%
43 <latexrelease>          {\@imakebox}{Unknown alignment warning}%
44 <*2ekernel | latexrelease>
45 \long\def\@imakebox[#1][#2]#3{%
46   \@begin@tempboxa\hbox{#3}%
47   \setlength\@tempdima{#1}%      support calc
48   \hb@xt@\@tempdima{%
49     \expandafter\ifx\csname bm@#2\endcsname\relax
50       \bm@c
51       \@latex@warning{Unexpected alignment #2}%
52     \else
53       \csname bm@#2\endcsname
54     \fi}%
55   \@end@tempboxa}
56 </2ekernel | latexrelease>
57 <latexrelease>\EndIncludeInRelease
58 <latexrelease>\IncludeInRelease{0000/00/00}%
59 <latexrelease>          {\@imakebox}{Unknown alignment warning}%
60 <latexrelease>\long\def\@imakebox[#1][#2]#3{%
61 <latexrelease>   \@begin@tempboxa\hbox{#3}%
62 <latexrelease>   \setlength\@tempdima{#1}%      support calc
63 <latexrelease>   \hb@xt@\@tempdima{\csname bm@#2\endcsname}%
64 <latexrelease>   \@end@tempboxa}
65 <latexrelease>\EndIncludeInRelease
66 <*2ekernel>

```

*(End of definition for \@imakebox.)*

`\@makepicbox` Picture mode form of `\makebox`.

```

67 \def\@makepicbox(#1,#2){%
68   \@ifnextchar[{\@imakepicbox(#1,#2)}{\@imakepicbox(#1,#2) []}}

```

*(End of definition for \@makepicbox.)*

`\@imakepicbox` picture mode version

```

69 </2ekernel>
70 <*2ekernel | latexrelease>
71 <latexrelease>\IncludeInRelease{2020/10/01}%
72 <latexrelease>          {\@imakepicbox}{default units}%
73 \long\def\@imakepicbox(#1,#2)[#3]#4{%
74   \@defaultunitsset\@tempdimc{#2}\unitlength
75   \vbox to\@tempdimc
76   {\let\mb@b\vss \let\mb@l\hss\let\mb@r\hss
77     \let\mb@t\vss
78     \@tfor\reserved@a :=#3\do{%
79       \if s\reserved@a
80         \let\mb@l\relax\let\mb@r\relax
81       \else
82         \expandafter\let\csname mb@\reserved@a\endcsname\relax
83       \fi}%
84   \mb@t
85   \@defaultunitsset\@tempdimc{#1}\unitlength

```

```

86 \hb@xt@{\@tempdimc{\mb@l #4\mb@r}}%
87 \mb@b

```

This kern ensures that a `b` option aligns on the bottom of the text rather than the baseline. this is the documented behaviour in the L<sup>A</sup>T<sub>E</sub>X Book. The kern is removed in compatibility mode.

```

88 \kern\z@}}
89 </2ekernel | latexrelease>

90 <latexrelease>\EndIncludeInRelease
91 <latexrelease>\IncludeInRelease{0000/00/00}%
92 <latexrelease> \@imakepicbox}{default units}%
93 <latexrelease>\long\def\@imakepicbox(#1,#2)[#3]#4{%
94 <latexrelease> \vbox to#2\unitlength
95 <latexrelease> {\let\mb@b\vss \let\mb@l\hss\let\mb@r\hss
96 <latexrelease> \let\mb@t\vss
97 <latexrelease> \@tfor\reserved@a :=#3\do{%
98 <latexrelease> \if s\reserved@a
99 <latexrelease> \let\mb@l\relax\let\mb@r\relax
100 <latexrelease> \else
101 <latexrelease> \expandafter\let\csname mb@\reserved@a\endcsname\relax
102 <latexrelease> \fi}%
103 <latexrelease> \mb@t
104 <latexrelease> \hb@xt@ #1\unitlength{\mb@l #4\mb@r}%
105 <latexrelease> \mb@b
106 <latexrelease> \kern\z@}}
107 <latexrelease>\EndIncludeInRelease
108 <*2ekernel>

```

(End of definition for \@imakepicbox.)

`\set@color` This macro is initially a no-op, but the color package will redefine it to insert a `\special`.

```

109 \let\set@color\relax

```

(End of definition for \set@color.)

`\color@begingroup` In the past these macros were initially no-ops, and the color package redefined them to be `\begingroup`, `\endgroup`, `\begingroup\set@color`, `\color@setgroup` them to be `\begingroup`, `\endgroup`, `\begingroup\set@color`, `\hbox\bgroup\color@begingroup`, `\color@endgroup\egroup`. and `<set to main document color>` respectively.

`\normalcolor` Nowadays we always set the group already in the kernel as this makes the coding simpler.

`\color@hbox`

`\color@vbox`

`\color@endbox`

```

110 </2ekernel>
111 <*2ekernel | latexrelease>
112 <latexrelease>\IncludeInRelease{2021/06/01}%
113 <latexrelease> \color@begingroup}{color group settings}%
114 \let\color@begingroup\begingroup
115 \def\color@setgroup{\color@begingroup} % changed further in color package
116 \let\normalcolor\relax % remains untouched; only changed in a color package
117 \def\color@hbox{\hbox\bgroup\color@begingroup}
118 \def\color@vbox{\vbox\bgroup\color@begingroup}
119 \def\color@endbox{\color@endgroup\egroup}
120 </2ekernel | latexrelease>
121 <latexrelease>\EndIncludeInRelease

```

```

122 <latexrelease>\IncludeInRelease{0000/00/00}%
123 <latexrelease>                {\color@begingroup}{color group settings}%
124 <latexrelease>
125 <latexrelease>\let\color@begingroup\relax
126 <latexrelease>\let\color@setgroup\relax
127 <latexrelease>\let\normalcolor\relax
128 <latexrelease>\let\color@hbox\relax
129 <latexrelease>\let\color@vbox\relax
130 <latexrelease>\let\color@endbox\relax
131 <latexrelease>
132 <latexrelease>\EndIncludeInRelease
133 <*2ekernel>

```

*(End of definition for \color@begingroup and others.)*

**\color@endgroup** This macro is separated out because it received an update in 2024, so requires its own rollback.

```

134 </2ekernel>
135 <*2ekernel | latexrelease>
136 <latexrelease>\IncludeInRelease{2024/11/01}%
137 <latexrelease>                {\color@endgroup}{color group settings}%

```

Beside **\endgraf** for handling vertical boxes we also reset **\if@endpe** as we are leaving the context.

```

138 \def\color@endgroup{\endgraf\@endpefalse\endgroup}
139 <latexrelease>
140 </2ekernel | latexrelease>
141 <latexrelease>\EndIncludeInRelease
142 <latexrelease>\IncludeInRelease{2021/06/01}%
143 <latexrelease>                {\color@endgroup}{color group settings}%
144 <latexrelease>\def\color@endgroup{\endgraf\endgroup}
145 <latexrelease>
146 <latexrelease>\EndIncludeInRelease
147 <latexrelease>\IncludeInRelease{0000/00/00}%
148 <latexrelease>                {\color@endgroup}{color group settings}%
149 <latexrelease>
150 <latexrelease>\let\color@endgroup\relax
151 <latexrelease>
152 <latexrelease>\EndIncludeInRelease
153 <*2ekernel>

```

*(End of definition for \color@endgroup.)*

**\newsavebox** Allocate a new ‘savebox’.

```

154 \def\newsavebox#1{\@ifdefinable{#1}{\newbox#1}}

```

*(End of definition for \newsavebox.)*

**\savebox** Save #1 in a box register.

```

155 </2ekernel>
156 <latexrelease>\IncludeInRelease{2015/01/01}%
157 <latexrelease>                {\savebox}{Make \savebox robust}%
158 <*2ekernel | latexrelease>
159 \DeclareRobustCommand\savebox[1]{%

```



```

189         \def\noexpand\@currentvline{\on@line}}%
190     \reserved@a
191     \@endpfalse
192     \color@setgroup
193     \ignorespaces}

(End of definition for \lrbox.)

\endlrbox End the lrbox environment.
194 \def\endlrbox{\unskip\color@endgroup}

(End of definition for \endlrbox.)

\usebox unchanged
195 \DeclareRobustCommand\usebox[1]{\leavevmode\copy #1\relax}

(End of definition for \usebox.)

\frame The following definition of \frame was written by Pavel Curtis (Extra space removed 14
Jan 88) RmS 92/08/24: Replaced occurrence of \@halfwidth by \@wholewidth
196 \DeclareRobustCommand\frame[1]{%
197     \leavevmode
198     \hbox{%
199         \hskip-\@wholewidth
200         \vbox{%
201             \vskip-\@wholewidth
202             \hrule \@height\@wholewidth
203             \hbox{%
204                 \vrule\@width\@wholewidth
205                 #1%
206                 \vrule\@width\@wholewidth}%
207             \hrule\@height\@wholewidth
208             \vskip-\@wholewidth}%
209         \hskip-\@wholewidth}}

(End of definition for \frame.)

\fbxrule user level parameters,
\fbxsep
210 \newdimen\fbxrule
211 \newdimen\fbxsep

(End of definition for \fbxrule and \fbxsep.)

\fbx Abbreviated framed box command.
212 \DeclareRobustCommand\fbx[1]{%
213     \leavevmode
214     \setbox\@tempboxa\hbox{%
215         \color@begingroup
216         \kern\fbxsep{#1}\kern\fbxsep
217         \color@endgroup}%
218     \@frameb@x\relax}

(End of definition for \fbx.)

```

`\framebox` Framed version of `\makebox`.

```

219 </2ekernel>
220 <latexrelease>\IncludeInRelease{2015/01/01}%
221 <latexrelease>          {\framebox}{Make \framebox robust}%
222 <*2ekernel | latexrelease>
223 \DeclareRobustCommand\framebox{%
224   \ifnextchar(%)
225     \@framepicbox{\ifnextchar[\@framebox\fbbox}}%
226 </2ekernel | latexrelease>
227 <latexrelease>\EndIncludeInRelease
228 <latexrelease>\IncludeInRelease{0000/00/00}%
229 <latexrelease>          {\framebox}{Make \framebox robust}%
230 <latexrelease>\def\framebox{%
231 <latexrelease>  \ifnextchar(%)
232 <latexrelease>    \@framepicbox{\ifnextchar[\@framebox\fbbox}}%
233 <latexrelease>\expandafter\let\csname framebox \endcsname\undefined
234 <latexrelease>\EndIncludeInRelease
235 <*2ekernel>

(End of definition for \framebox.)

\@framebox Deal with optional arguments.

236 \def\@framebox[#1]{%
237   \ifnextchar[%]
238     {\@framebox[#1]}%
239     {\@framebox[#1][c]}}

(End of definition for \@framebox.)

\@ifframebox The handling the optional arguments. In order to set the whole box, including the
frame to the specified dimension, we first determine that dimension from the natural size
of the text, #3. calculated width.

240 </2ekernel>
241 <latexrelease>\IncludeInRelease{2023/11/01}%
242 <latexrelease>          {\@ifframebox}{Unknown alignment warning}%
243 <*2ekernel | latexrelease>
244 \long\def\@ifframebox[#1][#2]#3{%
245   \leavevmode
246   \@begin@tempboxa\hbox{#3}%
247   \setlength\@tempdima{#1}%
248   \setbox\@tempboxa\hb@xt@\@tempdima
249     {\kern\fbboxsep
250      \expandafter\ifx\csname bm@#2\endcsname\relax
251        \bm@c
252        \@latex@warning{Unexpected alignment #2}%
253      \else
254        \csname bm@#2\endcsname
255      \fi
256      \kern\fbboxsep}%
257   \@frameboxx{\kern-\fbboxrule}%
258   \@end@tempboxa}
259 </2ekernel | latexrelease>
260 <latexrelease>\EndIncludeInRelease
261 <latexrelease>\IncludeInRelease{0000/00/00}%

```

```

262 <latexrelease>                {\@iframebox}{Unknown alignment warning}%
263 <latexrelease>\long\def\@iframebox[#1][#2]#3{%
264 <latexrelease>  \leavevmode
265 <latexrelease>  \@begin@tempboxa\hbox{#3}%
266 <latexrelease>    \setlength\@tempdima{#1}%
267 <latexrelease>    \setbox\@tempboxa\hb@xt@\@tempdima
268 <latexrelease>      {\kern\fboxsep\csname bm@#2\endcsname\kern\fboxsep}%
269 <latexrelease>    \@frameb@x{\kern-\fboxrule}%
270 <latexrelease>  \@end@tempboxa}
271 <latexrelease>\EndIncludeInRelease
272 <*2ekernel>

```

*(End of definition for \@iframebox.)*

**\@frameb@x** Common part of `\framebox` and `\fbox`. #1 is a negative kern in the `\framebox` case so that the vertical rules do not add to the width of the box.

```

273 \def\@frameb@x#1{%
274   \@tempdima\fboxrule
275   \advance\@tempdima\fboxsep
276   \advance\@tempdima\dp\@tempboxa
277   \hbox{%
278     \lower\@tempdima\hbox{%
279       \vbox{%
280         \hrule\@height\fboxrule
281         \hbox{%
282           \vrule\@width\fboxrule
283           #1%
284           \vbox{%
285             \vskip\fboxsep
286             \box\@tempboxa
287             \vskip\fboxsep}%
288           #1%
289           \vrule\@width\fboxrule}%
290         \hrule\@height\fboxrule}%
291         }%
292     }%
293 }

```

*(End of definition for \@frameb@x.)*

**\@framepicbox** Picture mode version.

```

294 \def\@framepicbox(#1,#2){%
295   \ifnextchar[{\@iframepicbox(#1,#2)}{\@iframepicbox(#1,#2) []}}

```

*(End of definition for \@framepicbox.)*

**\@iframepicbox** Picture mode version.

```

296 \long\def\@iframepicbox(#1,#2)[#3]#4{%
297   \frame{\@imakepicbox(#1,#2)[#3]{#4}}

```

*(End of definition for \@iframepicbox.)*

`\parbox` The main vertical-box command for L<sup>A</sup>T<sub>E</sub>X.

```

298 </2ekernel>
299 <latexrelease>\IncludeInRelease{2015/01/01}%
300 <latexrelease>          {\parbox}{Make \parbox robust}%
301 <*2ekernel | latexrelease>
302 \DeclareRobustCommand\parbox{%
303   \@ifnextchar[%]
304     \@iparbox
305     {\@iiiparbox c\relax[s]}}%
306 </2ekernel | latexrelease>
307 <latexrelease>\EndIncludeInRelease
308 <latexrelease>\IncludeInRelease{0000/00/00}%
309 <latexrelease>          {\parbox}{Make \parbox robust}%
310 <latexrelease>\def\parbox{%
311 <latexrelease>  \@ifnextchar[%]
312 <latexrelease>    \@iparbox
313 <latexrelease>    {\@iiiparbox c\relax[s]}}%
314 <latexrelease>\expandafter\let\csname parbox \endcsname \@undefined
315 <latexrelease>\EndIncludeInRelease
316 <*2ekernel>

(End of definition for \parbox.)

\@iparbox Optional argument handling.
317 \def\@iparbox[#1]{%
318   \@ifnextchar[%]
319     {\@iparbox{#1}}%
320     {\@iiiparbox{#1}\relax[s]}}

(End of definition for \@iparbox.)

\@iiiparbox Optional argument handling.
321 \def\@iiiparbox#1[#2]{%
322   \@ifnextchar[%]
323     {\@iiiparbox{#1}{#2}}%
324     {\@iiiparbox{#1}{#2}[#1]}}

(End of definition for \@iiiparbox.)

\@iiiparbox The internal version of \parbox.
\@parboxto
325 \let\@parboxto\@empty

326 </2ekernel>
327 <latexrelease>\IncludeInRelease{2023/11/01}%
328 <latexrelease>          {\@iiiparbox}{Unknown alignment warning}%
329 <*2ekernel | latexrelease>
330 \long\def\@iiiparbox#1#2[#3]#4#5{%
331   \leavevmode
332   \@pboxswfalse
333   \setlength\@tempdima{#4}%
334   \@begin@tempboxa\vbox{\hsize\@tempdima\@parboxrestore#5\@@par}%
335     \ifx\relax#2\else
336       \setlength\@tempdimb{#2}%
337       \edef\@parboxto{to\the\@tempdimb}%
338       \fi

```

```

339 \if#1b\vbox
340 \else\if #1t\vtop
341 \else\ifmode\vcenter
342 \else\@pboxswtrue $\vcenter
343 \fi\fi\fi
344 \@parboxto{\let\hss\vss\let\unhbox\unvbox
345 \expandafter\ifx\csname bm@#3\endcsname\relax
346 \bm@c
347 \@latex@warning{Unexpected alignment #3}%
348 \else
349 \csname bm@#3\endcsname
350 \fi}%
351 \if@pboxsw \m@th$\fi
352 \@end@tempboxa}
353 </2ekernel|latexrelease>
354 <latexrelease>\EndIncludeInRelease
355 <latexrelease>\IncludeInRelease{0000/00/00}%
356 <latexrelease> \{\@iiiparbox\}{Unknown alignment warning}%
357 <latexrelease>\long\def\@iiiparbox#1#2[#3]#4#5{%
358 <latexrelease> \leavevmode
359 <latexrelease> \@pboxswfalse
360 <latexrelease> \setlength\@tempdima{#4}%
361 <latexrelease> \begin@tempboxa\vbox{\hsize\@tempdima\@parboxrestore#5\@@par}%
362 <latexrelease> \ifx\relax#2\else
363 <latexrelease> \setlength\@tempdimb{#2}%
364 <latexrelease> \edef\@parboxto{to\the\@tempdimb}%
365 <latexrelease> \fi
366 <latexrelease> \if#1b\vbox
367 <latexrelease> \else\if #1t\vtop
368 <latexrelease> \else\ifmode\vcenter
369 <latexrelease> \else\@pboxswtrue $\vcenter
370 <latexrelease> \fi\fi\fi
371 <latexrelease> \@parboxto{\let\hss\vss\let\unhbox\unvbox
372 <latexrelease> \csname bm@#3\endcsname}%
373 <latexrelease> \if@pboxsw \m@th$\fi
374 <latexrelease> \@end@tempboxa}
375 <latexrelease>\EndIncludeInRelease
376 <*2ekernel>

```

(End of definition for \@iiiparbox and \@parboxto.)

**\@arrayparboxrestore** Restore various paragraph parameters.

The rationale for allowing two normally global flags to be set locally here was stated originally by Donald Arseneau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should never appear within boxes or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in \@setnobreak; otherwise this command will be redundant.

```

377 </2ekernel>
378 <latexrelease>\IncludeInRelease{2017-04-15}%
379 <latexrelease> \{\normallineskiplimit\}
380 <latexrelease> \reset \lineskiplimit}%
381 <*2ekernel|latexrelease>

```

```

382 \def\@arrayparboxrestore{%
383   \let\if@nbreak\iffalse
384   \let\if@noskipsec\iffalse
385   \let\par\@@par
386   \let\-\@dischyph

```

Redefined accents to allow changes in font encoding

```

387   \let'\@acci\let'\@accii\let\=\@acciii
388   \parindent\z@ \parskip\z@skip
389   \everypar{}%
390   \linewidth\hsize
391   \@totalleftmargin\z@
392   \leftskip\z@skip \rightskip\z@skip \@rightskip\z@skip
393   \parfillskip\@flushglue
394   \lineskip\normallineskip

395   \lineskiplimit\normallineskiplimit
396   \baselineskip\normalbaselineskip
397   \sloppy}
398 \</2ekernel | latexrelease>

399 \<latexrelease>\EndIncludeInRelease
400 \<latexrelease>\IncludeInRelease{0000-00-00}%
401 \<latexrelease>          {\normallineskiplimit}
402 \<latexrelease>          {\reset \lineskiplimit}%
403 \<latexrelease>\def\@arrayparboxrestore{%
404 \<latexrelease>  \let\if@nbreak\iffalse
405 \<latexrelease>  \let\if@noskipsec\iffalse
406 \<latexrelease>  \let\par\@@par
407 \<latexrelease>  \let\-\@dischyph
408 \<latexrelease>  \let'\@acci\let'\@accii\let\=\@acciii
409 \<latexrelease>  \parindent\z@ \parskip\z@skip
410 \<latexrelease>  \everypar{}%
411 \<latexrelease>  \linewidth\hsize
412 \<latexrelease>  \@totalleftmargin\z@
413 \<latexrelease>  \leftskip\z@skip \rightskip\z@skip \@rightskip\z@skip
414 \<latexrelease>  \parfillskip\@flushglue \lineskip\normallineskip
415 \<latexrelease>  \baselineskip\normalbaselineskip
416 \<latexrelease>  \sloppy}
417 \<latexrelease>\EndIncludeInRelease
418 \<*2ekernel>

```

*(End of definition for \@arrayparboxrestore.)*

**\@parboxrestore** Restore various paragraph parameters, and also \.

```

419 \def\@parboxrestore{\@arrayparboxrestore\let\\\@normalcr}

```

*(End of definition for \@parboxrestore.)*

**\if@minipage** Switch that is true at the start of a minipage.

```

420 \def\@minipagefalse{\global\let\if@minipage\iffalse}
421 \def\@minipagetrue {\global\let\if@minipage\iftrue}
422 \@minipagefalse

```

*(End of definition for \if@minipage.)*

`\if@in@minipage@env`

423 `\newif\if@in@minipage@env`

*(End of definition for \if@in@minipage@env.)*

`\minipage` Essentially an environment form of `\parbox`.

424 `\def\minipage{%`  
425 `\@ifnextchar[%`  
426 `\@iminipage`  
427 `{\@iiiminipage c\relax[s]}`

*(End of definition for \minipage.)*

`\@iminipage` Optional argument handling.

428 `\def\@iminipage[#1]{%`  
429 `\@ifnextchar[%`  
430 `{\@iiiminipage{#1}}%`  
431 `{\@iiiminipage{#1}\relax[s]}`

*(End of definition for \@iminipage.)*

`\@iiiminipage` Optional argument handling.

432 `\def\@iiiminipage#1[#2]{%`  
433 `\@ifnextchar[%`  
434 `{\@iiiminipage{#1}{#2}}%`  
435 `{\@iiiminipage{#1}{#2}[#1]}`

*(End of definition for \@iiiminipage.)*

`\@iiiminipage` Internal form of minipage.

436 `\def\@iiiminipage#1#2[#3]#4{%`  
437 `\leavevmode`  
438 `\@pboxswfalse`  
439 `\setlength\@tempdima{#4}%`  
440 `\def\@mpargs{#1}{#2}{#3}{#4}%`  
441 `\setbox\@tempboxa\vbox\bgroup`  
442 `\color@begingroup`  
443 `\hsize\@tempdima`  
444 `\textwidth\hsize \columnwidth\hsize`

We check for nested minipages inside the box so that there is always a group resetting the switch even if the code does not use `\begin` to start the minipage.

445 `\if@in@minipage@env`

We only issue a warning if the outer minipage contained footnotes because that is the problematical case.

446 `\ifvoid\@mpfootins\else`  
447 `\@latex@warning{Nested minipage:`  
448 `footnotes may be misplaced}%`  
449 `\fi`  
450 `\else`  
451 `\@in@minipage@envtrue`  
452 `\fi`

```

453 \parboxrestore
454 \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
455 \let\@footnotetext\@mpfootnotetext
456 \let\@listdepth\@mplistdepth \@mplistdepth\z@
457 \@minipagerestore
458 \setminipage}

```

*(End of definition for \@iiiminipage.)*

**\@minipagerestore** Hook so that other styles can reset other commands in a minipage.

```

459 \let\@minipagerestore=\relax

```

*(End of definition for \@minipagerestore.)*

**\endminipage**

```

460 \def\endminipage{%
461   \par
462   \unskip
463   \ifvoid\@mpfootins\else
464     \vskip\skip\@mpfootins
465     \normalcolor
466     \footnoterule
467     \unvbox\@mpfootins
468   \fi
469   \@minipagefalse %% added 24 May 89
470   \color@endgroup
471   \egroup
472   \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}}

```

*(End of definition for \endminipage.)*

**\@mplistdepth** Versions of \@listdepth and \footins local to minipage.

```

\@mpfootins
473 \newcount\@mplistdepth
474 \newinsert\@mpfootins

```

*(End of definition for \@mplistdepth and \@mpfootins.)*

**\@mpfootnotetext** Minipage version of \@footnotetext.

Final \strut added 27 Mar 89, on suggestion by Don Hosek

```

475 </2ekernel>
476 <*2ekernel | latexrelease>
477 <latexrelease>\IncludeInRelease{2021/11/15}%
478 <latexrelease>{\@mpfootnotetext}{footnotetext tagging}%
479 \long\def\@mpfootnotetext#1{%
480   \global\setbox\@mpfootins\vbox{%
481     \unvbox\@mpfootins
482     \reset@font\footnotesize
483     \hsize\columnwidth
484     \parboxrestore
485     \def\@currentcounter{mpfootnote}%
486     \protected@edef\@currentlabel
487       {\csname p@mpfootnote\endcsname\@thefnmark}%
488     \color@begingroup
489     \makefntext{%
490       \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%

```

```

491 \par
492 \color@endgroup}}
493 

```

**\rule** Draw a rule of the specified size.

```

530 

```

```

540 <latexrelease>\expandafter\let\csname rule \endcsname\@undefined
541 <latexrelease>\EndIncludeInRelease
542 <*2ekernel>

(End of definition for \rule.)

\@rule Internal form of \rule.
543 \def\@rule[#1]#2#3{%
544 \leavevmode
545 \hbox{%
546 \setlength\@tempdima{#1}%
547 \setlength\@tempdimb{#2}%
548 \setlength\@tempdimc{#3}%
549 \advance\@tempdimc\@tempdima
550 \vrule\@width\@tempdimb\@height\@tempdimc\@depth-\@tempdima}}

(End of definition for \@rule.)

\@@underline Saved primitive \underline.
551 \let\@@underline\underline

(End of definition for \@@underline.)

\underline LATEX version works outside math.
552 \DeclareRobustCommand\underline[1]{%
553 \relax
554 \ifmmode\@@underline{#1}%
555 \else $\@@underline{\hbox{#1}}\m@th$\relax\fi}

(End of definition for \underline.)

\raisebox Raise a box, and change its vertical dimensions.
556 </2ekernel>
557 <latexrelease>\IncludeInRelease{2015/01/01}%
558 <latexrelease> \{\raisebox\}{Make \raisebox robust}%
559 <*2ekernel | latexrelease>
560 \DeclareRobustCommand\raisebox[1]{%
561 \leavevmode
562 \@ifnextchar[\@rsbox{#1}]{\@irsbox{#1}[]}}
563 </2ekernel | latexrelease>
564 <latexrelease>\EndIncludeInRelease
565 <latexrelease>\IncludeInRelease{0000/00/00}%
566 <latexrelease> \{\raisebox\}{Make \raisebox robust}%
567 <latexrelease>\def\raisebox#1{%
568 <latexrelease> \leavevmode
569 <latexrelease> \@ifnextchar[\@rsbox{#1}]{\@irsbox{#1}[]}}
570 <latexrelease>\expandafter\let\csname raisebox \endcsname\@undefined
571 <latexrelease>\EndIncludeInRelease
572 <*2ekernel>

(End of definition for \raisebox.)

\@rsbox Optional argument handling.
573 \def\@rsbox#1[#2]{%
574 \@ifnextchar[\@iirsbox{#1}[#2]}{\@irsbox{#1}[#2]}}

```

(End of definition for \@rsbox.)

\@argsbox ...

(End of definition for \@argsbox.)

\@irsbox Internal version of \raisebox (less than two optional args).

```

575 \long\def\@irsbox#1[#2]#3{%
576   \@begin@tempboxa\hbox{#3}%
577   \setlength\@tempdima{#1}%
578   \ifx\#2\\\else\setlength\@tempdimb{#2}\fi
579   \setbox\@tempboxa\hbox{\raise\@tempdima\box\@tempboxa}%
580   \ifx\#2\\\else\ht\@tempboxa\@tempdimb\fi
581   \box\@tempboxa
582   \@end@tempboxa}

```

(End of definition for \@irsbox.)

\@iirsbox Internal version of \raisebox (two optional args).

```

583 \long\def\@iirsbox#1[#2][#3]#4{%
584   \@begin@tempboxa\hbox{#4}%
585   \setlength\@tempdima{#1}%
586   \setlength\@tempdimb{#2}%
587   \setlength\dimen@{#3}%
588   \setbox\@tempboxa\hbox{\raise\@tempdima\box\@tempboxa}%
589   \ht\@tempboxa\@tempdimb
590   \dp\@tempboxa\dimen@
591   \box\@tempboxa
592   \@end@tempboxa}

```

(End of definition for \@iirsbox.)

\@finalstrut This macro adds a special strut the *depth* of the box given as #1, and height and width Opt. It is used for ensuring that the last line of a paragraph has the correct depth in ‘p’ columns of tables and in footnotes. In vertical mode nothing is done, as adding the strut (as done in 2.09) would start a new paragraph. It would be possible to inspect \prevdepth to check the depth of the just-completed paragraph, but we do not do that here. Actually we do even less now, skip the vmode test as it broke tabular ‘p’ columns.

The \nobreak was added (1995/10/31) to allow hyphenation of the final word of the paragraph.

In 2024 we changed the macro to account for vertical mode. In that case we use a strut produced with \hrule to avoid starting a new paragraph (resulting in spurious extra line) and also account for the \prevdepth of the previous line.

```

593 \</2ekernel>
594 \<*2ekernel | latexrelease>
595 \<latexrelease>\IncludeInRelease{2024/06/01}%
596 \<latexrelease>          {\@finalstrut}{final strut correction}%
597 \def\@finalstrut#1{%
598   \unskip
599   \ifhmode \nobreak
600   \else

```

If we are in vmode we now back up by a baseline.

```
601 \vskip-\baselineskip
602 \fi
```

Finally we unconditionally use `\vrule`.

```
603 \vrule\@width\z@\@height\z@\@depth\dp#1}
604 </2ekernel | latexrelease>
605 <latexrelease>\EndIncludeInRelease
606 <latexrelease>\IncludeInRelease{0000/00/00}%
607 <latexrelease> \{\@finalstrut\}{final strut correction}%
608 <latexrelease>\def\@finalstrut#1{%
609 <latexrelease> \unskip\ifhmode\nobreak\fi
610 <latexrelease> \vrule\@width\z@\@height\z@\@depth\dp#1}
611 <latexrelease>
612 <latexrelease>\EndIncludeInRelease
613 <*2ekernel>
```

*(End of definition for \@finalstrut.)*

## 1.1 Some low-level constructs

The following commands are basically inherited from plain T<sub>E</sub>X.

`\leftline` These macros place text on a full line either centred or left or right adjusted.

`\rightline` 614 `\def\@@line{\hb@xt@\hsize}`

`\centerline` 615 `\DeclareRobustCommand\leftline[1]{\@@line{#1\hss}}`

`\@@line` 616 `\DeclareRobustCommand\rightline[1]{\@@line{\hss#1}}`

617 `\DeclareRobustCommand\centerline[1]{\@@line{\hss#1\hss}}`

*(End of definition for \leftline and others.)*

`\rlap` These macros place text to the left or right of the current reference point without taking up space.

`\llap` 618 `\DeclareRobustCommand\rlap[1]{\hb@xt@\z@{#1\hss}}`

`\clap` 619 `\DeclareRobustCommand\llap[1]{\hb@xt@\z@{\hss#1}}`

And here is the version that centers, it was initially introduced by `mathtools`.

```
620 \DeclareRobustCommand\clap[1]{\hb@xt@\z@{\hss#1\hss}}
```

*(End of definition for \rlap, \llap, and \clap.)*

```
621 </2ekernel>
```

## File 41

# lftab.dtx

## 1 Tabbing, Tabular and Array Environments

This section deals with ‘Lining It Up in Columns’. First the `tabbing` environment is defined, and then in second part, `tabular` together with its variants, `tabular*` and `array`.

Note that the `tabular` defined here is essentially the original L<sup>A</sup>T<sub>E</sub>X 2.09 version, not the extended version described in *The L<sup>A</sup>T<sub>E</sub>X Companion*. Use the `array` package to obtain the extended version.

### 1.1 tabbing

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

`\dimen(\@firsttab + i)` = distance of tab stop `i` from left margin  
0 <= `i` <= 15 (?).

`\dimen\@firsttab` is initialized to `\@totalleftmargin`, so it starts  
at the prevailing left margin.

`\@maxtab` = number of highest defined tab register  
probably = `\@firsttab + 12`

`\@nxttabmar` = tab stop number of next line’s left margin

`\@curtabmar` = tab stop number of current line’s left margin

`\@curtab` = number of the current tab. At start of line,  
it equals `\@curtabmar`

`\@hightab` = largest tab number currently defined.

`\@tabpush` = depth of `\pushtab`’s

`\box\@curline` = contents of current line, excluding left margin  
skip, and excluding contents of current field

`\box\@curfield` = contents of current field

`@rjfield` = switch: T iff the last field of the line should  
be right-justified at the right margin.

`\tabbingsep` = distance left by the `\’` command between the  
current position and the field that is  
“left-shifted”.

#### UTILITY MACROS

`\@stopfield` : closes the current field

`\@addfield` : adds the current field to the current line.

`\@contfield` : continues the current field

`\@startfield` : begins the next field

`\@stopline` : closes the current line and outputs it

```

\@startline : starts the next line
\@ifatmargin : an \if that is true iff the current line.
                has width zero

\@startline ==
BEGIN
  \@curtabmar :=G \@nxttabmar
  \@curtab :=G \@curtabmar
  \box\@curline :=G null
  \@startfield
  \strut
END

\@stopline ==
BEGIN
  \unskip
  \@stopfield
  if @rjfield = T
    then @rjfield :=G F
      \@tempdima := \@totalleftmargin + \linewidth
      \hb@xt@ \@tempdima{\@itemfudge
                          \hskip \dimen\@curtabmar
                          \box\@curline
                          \hfil
                          \box\@curfield}
    else \@addfield
      \hbox {\@itemfudge
            \hskip \dimen\@curtabmar
            \box\@curline}
    fi
  END

\@startfield ==
BEGIN
  \box\@curfield :=G \hbox {
END

\@stopfield ==
BEGIN
  }
END

\@contfield ==
BEGIN
  \box\@curfield :=G \hbox { \unhbox\@currfield %%} brace matching
END

\@addfield ==
BEGIN
  \box\@curline :=G \unbox\@curline * \unbox\@curfield
END

```

```

\@ifatmargin ==
BEGIN
  if dim of box\@curline = 0pt then
  END

\tabbing ==
BEGIN
  \lineskip :=L 0pt
  \> == \@rtab
  \< == \@ltab
  \= == \@settab
  \+ == \@tabplus
  \- == \@tabminus
  \' == \@tabrj
  \' == \@tablab
  \\\ == BEGIN \@stopline \@startline END
  \\[DIST] == BEGIN
    \@stopline \vskip DIST \@startline\ignorespaces END
  \\\* == BEGIN \@stopline \penalty 10000 \@startline END
  \\\*[DIST] == BEGIN \@stopline \penalty 10000 \vskip DIST
    \@startline\ignorespaces END
  \@hightab := \@nxrtabmar :=G \@firsttab
  \@tabpush :=G 0
  \dimen\@firsttab := \@totalleftmargin
  @rjfield :=G F
  \trivlist \item\relax
  if @minipage = F then \vskip \parskip fi
  \box\@tabfbox = \rlap{\indent\the\everypar}
    % note: \the\everypar sets @inlabel :=G F
  \@itemfudge == BEGIN \box\@tabfbox END
  \@startline
  \ignorespaces
END

\@endtabbing ==
BEGIN
  \@stopline
  if \@tabpush > 0 then error message: "unmatched \poptabs" fi
  \endtrivlist
END

\@rtab ==
BEGIN
  \@stopfield
  \@addfield
  if \@curtab < \@hightab
    then \@curtab :=G \@curtab + 1
    else error message "Undefined Tab" fi

```

```

\@tempdima := \dimen\@curtab - \dimen\@curtabmar
              - width of box \@curline
\box\@curline :=G \hbox{\unhbox\@curline + \hskip\@tempdima}
\@startfield
END

\@settab ==
BEGIN
  \@stopfield
  \@addfield
  if \@curtab < \@maxtab
    then \@curtab :=G \@curtab+1
    else error message: "Too many tabs"    fi
  if \@curtab > \@hightab
    then \@hightab :=L \@curtab    fi
  \dimen\@curtab :=L \dimen\@curtabmar + width of \box\@curline
  \@startfield
END

\@ltab ==
BEGIN
  \@ifatmargin
  then if \@curtabmar > \@firsttab
    then \@curtab :=G \@curtab - 1
        \@curtabmar :=G \@curtabmar - 1
    else error message "Too many untab"    fi
  else error message "Left tab in middle of line"
  fi
END

\@tabplus ==
BEGIN
  if \@nxttabmar < \@hightab
    then \@nxttabmar :=G \@nxttabmar+1
    else error message "Undefined tab"
  fi
END

\@tabminus ==
BEGIN
  if \@nxttabmar > \@firsttab
    then \@nxttabmar :=G \@nxttabmar-1
    else error message "Too many untab"
  fi
END

\@tabrj ==
BEGIN \@stopfield
  \@addfield
  @rjfield :=G T

```

```

        \@startfield
    END

\@tablab ==
    BEGIN \@stopfield
        \box\@curline G:= \hbox{\box\@curline %% 'G' added 17 Jun 86
                                \hskip - width of \box\@curfield
                                \hskip -\tabbingsep
                                \box\@curfield
                                \hskip \tabbingsep }

        \@startfield
    END

\pushtabs ==
    BEGIN
        \@stopfield
        \@tabpush :=G \@tabpush + 1
        \begingroup
        \@contfield
    END

\poptabs ==
    BEGIN
        \@stopfield
        if \@tabpush > 0
            then \endgroup
                \@tabpush :=G \@tabpush - 1
            else error message: "Too many \poptabs"
            fi
        \@contfield
    END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

\a The accents \‘, \’ , and \= that have been redefined inside a tabbing environment can be called by typing \a‘, \a’ , and \a=. The macro \a is defined in `ltoutenc.dtx`.

*(End of definition for \a.)*

The ‘2ekernel’ code ensures that a `\usepackage{autotabg}` is essentially ignored if a ‘full’ format is being used that has picture mode already in the format.

```

1  \langle 2ekernel\rangle\expandafter\let\csname ver@autotabg.sty\endcsname\fmtversion

\@firsttab
\@maxtab
2  \langle *2ekernel\rangle
3  \newdimen\@gtempa
4  \chardef\@firsttab=\the\allocationnumber
5  \newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa
6  \newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa
7  \newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa
8  \newdimen\@gtempa
9  \chardef\@maxtab=\the\allocationnumber
10 \dimen\@firsttab=0pt

```

```

        (End of definition for \@firsttab and \@maxtab.)

\@nxttabmar
\@curtabmar 11 \newcount\@nxttabmar
  \@curtab 12 \newcount\@curtabmar
  \@hightab 13 \newcount\@curtab
  \@tabpush 14 \newcount\@hightab
            15 \newcount\@tabpush

        (End of definition for \@nxttabmar and others.)

\@curline
\@curfield 16 \newbox\@curline
\@tabfbox 17 \newbox\@curfield
            18 \newbox\@tabfbox

        (End of definition for \@curline, \@curfield, and \@tabfbox.)

\if@rjfield
            19 \newif\if@rjfield

        (End of definition for \if@rjfield.)

\@startline It is, in some sense, an error if the current margin tab setting is higher than the value of
            \@hightab (which is a local variable). That this is allowed is a fundamental design flaw
            which is not going to be corrected now.
            20 \def\@startline{%
            21     \ifnum \@nxttabmar >\@hightab
            22     \badtab
            23     \global\@nxttabmar \@hightab
            24     \fi
            25     \global\@curtabmar \@nxttabmar
            26     \global\@curtab \@curtabmar
            27     \global\setbox\@curline \hbox {%
            28     \@startfield
            29     \strut}

        (End of definition for \@startline.)

\@stopline
            30 \def\@stopline{%
            31     \unskip
            32     \@stopfield
            33     \if@rjfield
            34     \global\@rjfieldfalse
            35     \@tempdima\@totalleftmargin
            36     \advance\@tempdima\linewidth
            37     \hb@xt@\@tempdima{%
            38     \@itemfudge\hskip\dimen\@curtabmar
            39     \box\@curline
            40     \hfil
            41     \box\@curfield}%
            42     \else
            43     \@addfield
            44     \hbox{\@itemfudge\hskip\dimen\@curtabmar\box\@curline}%
            45     \fi}

```

```

(End of definition for \@stopline.)

\@startfield
46 \def\@startfield{%
47   \global\setbox\@curfield\hbox\bgroup\color@begingroup}

(End of definition for \@startfield.)

\@stopfield
48 \def\@stopfield{%
49   \color@endgroup\egroup}

(End of definition for \@stopfield.)

\@contfield
50 \def\@contfield{%
51   \global\setbox\@curfield\hbox\bgroup\color@begingroup
52   \unhbox\@curfield}

(End of definition for \@contfield.)

\@addfield
53 \def\@addfield{\global\setbox\@curline\hbox{\unhbox
54   \@curline\unhbox\@curfield}}

(End of definition for \@addfield.)

\@ifatmargin
55 \def\@ifatmargin{\ifdim \wd\@curline =\z@}

(End of definition for \@ifatmargin.)

\@tabcr
56 \protected\def\@tabcr{\@stopline \ifstar{\penalty \@M \@tabcr}\@tabcr}

(End of definition for \@tabcr.)

\@xtabcr
57 \def\@xtabcr{\@ifnextchar[\@itabcr{\@startline\ignorespaces}}

(End of definition for \@xtabcr.)

\@itabcr
58 \</2ekernel>
59 \< *2ekernel | latexrelease>
60 \< latexrelease>\IncludeInRelease{2020/10/01}%
61 \< latexrelease>          {\@itabcr}{Tabbing calc syntax}%
62 \def\@itabcr[#1]{\@vspace@calcify{#1}\@startline\ignorespaces}
63 \</2ekernel | latexrelease>
64 \< latexrelease>\EndIncludeInRelease
65 \< latexrelease>\IncludeInRelease{0000/00/00}%
66 \< latexrelease>          {\@itabcr}{Tabbing calc syntax}%
67 \< latexrelease>
68 \< latexrelease>\def\@itabcr[#1]{\vskip #1\@startline\ignorespaces}
69 \< latexrelease>\EndIncludeInRelease
70 \< *2ekernel>

```

tabbing (env.) We use \relax to prevent \item from scanning too far.

```
\tabbing 71 \def\tabbing{\lineskip \z@skip\let\>\@rtab\let\<\@ltab\let\=\@settab
72 \let\+\@tabplus\let\-\@tabminus\let\'\@tabrj\let\'\@tablab
73 \let\=\@tabcr
74 \@hightab\@firsttab
75 \global\@nxttabmar\@firsttab
76 \dimen\@firsttab\@totalleftmargin
77 \global\@tabpush\z@ \global\@rjfieldfalse
78 \trivlist \item\relax
79 \if@minipage\else\vskip\parskip\fi

80 \setbox\@tabfbox\hbox{%
81 \rlap{\hskip\@totalleftmargin\indent\the\everypar}}%
82 \def\@itemfudge{\box\@tabfbox}%
83 \@startline\ignorespaces}
```

```
\endtabbing 84 \def\endtabbing{%
85 \@stopline\ifnum\@tabpush >\z@ \@badpoptabs \fi\endtrivlist}
```

Omitted \global added to \@rtab 17 Jun 86

```
\@rtab 86 \def\@rtab{\@stopfield\@addfield\ifnum \@curtab<\@hightab
87 \global\advance\@curtab \@ne \else\@badtab\fi
88 \@tempdima\dimen\@curtab
89 \advance\@tempdima -\dimen\@curtabmar
90 \advance\@tempdima -\wd\@curline
91 \global\setbox\@curline\hbox{\unhbox\@curline\hskip\@tempdima}%
92 \@startfield\ignorespaces}
```

```
\@settab 93 \def\@settab{\@stopfield\@addfield
94 \ifnum \@curtab <\@maxtab
95 \ifnum\@curtab =\@hightab
96 \advance\@hightab \@ne
97 \fi
98 \global\advance\@curtab \@ne
99 \else
100 \@latexerror{Tab overflow}\@ehd
101 \fi
102 \dimen\@curtab \dimen\@curtabmar
103 \advance\dimen\@curtab \wd\@curline
104 \@startfield
105 \ignorespaces}
```

```
\@ltab 106 \def\@ltab{\@ifatmargin\ifnum\@curtabmar >\@firsttab
107 \global\advance\@curtab \m@ne \global\advance\@curtabmar\m@ne\else
108 \@badtab\fi\else
109 \@latexerror{\string\<\space in mid line}\@ehd\fi\ignorespaces}
```

```
\@tabplus 110 \def\@tabplus{%
111 \ifnum\@nxttabmar<\@hightab
```

```

112     \global\advance\@nxttabmar\@ne
113 \else
114     \@badtab
115 \fi
116 \ignorespaces}

\@tabminus 117 \def\@tabminus{%
118     \ifnum\@nxttabmar>\@firsttab
119         \global\advance\@nxttabmar\m@ne
120     \else
121         \@badtab
122     \fi
123     \ignorespaces}

\@tabrj 124 \def\@tabrj{%
125     \@stopfield\@addfield\global\@rjfieldtrue\@startfield\ignorespaces}

\setbox\@curline made \global in \@tablab. 17 Jun 86

\@tablab 126 \def\@tablab{%
127     \@stopfield
128     \global\setbox\@curline\hbox{%
129         \box\@curline
130         \hskip-\wd\@curfield \hskip-\tabbingsep
131         \box\@curfield
132         \hskip\tabbingsep}%
133     \@startfield
134     \ignorespaces}

135 </2ekernel>
136 <*2ekernel | latexrelease>
137 <latexrelease>\IncludeInRelease{2019/10/01}%
138 <latexrelease>                {\pushtabs}{Make commands robust}%

\pushtabs 139 \DeclareRobustCommand\pushtabs{%
140     \@stopfield\@addfield\global\advance\@tabpush \@ne \begingroup
141         \@contfield}

\poptabs It is, in some sense, an error if, after the endgroup, the current tab setting is higher
than the new value of \@hightab (which is a local variable). That this is allowed is a
fundamental design flaw which is not going to be corrected now.

142 \DeclareRobustCommand\poptabs{\@stopfield\@addfield
143     \ifnum \@tabpush >\z@
144         \endgroup
145         \global\advance\@tabpush \m@ne
146         \ifnum \@curtab >\@hightab
147             \global \@curtab \@hightab
148             \@badtab
149         \fi
150     \else
151         \@badpoptabs
152     \fi
153     \@contfield}

```

```

154 \DeclareRobustCommand\kill{\@stopfield\@startline\ignorespaces}
(End of definition for \@itabcr and others.)
155 </2ekernel | latexrelease>
156 <latexrelease>\EndIncludeInRelease
157 <latexrelease>\IncludeInRelease{0000/00/00}%
158 <latexrelease>                {\pushtabs}{Make commands robust}%
159 <latexrelease>
160 <latexrelease>\kernel@make@fragile\pushtabs
161 <latexrelease>\kernel@make@fragile\poptabs
162 <latexrelease>\kernel@make@fragile\kill
163 <latexrelease>
164 <latexrelease>\EndIncludeInRelease
165 <*2ekernel>

```

\tabbingsep

```

166 \newdimen\tabbingsep
(End of definition for \tabbingsep.)

```

## 1.2 array and tabular environments

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

### ARRAY PARAMETERS:

\arraycolsep  
     : half the width separating columns in an array environment  
 \tabcolsep  
     : half the width separating columns in a tabular environment  
 \arrayrulewidth  
     : width of rules  
 \doublerulesep  
     : space between adjacent rules in array or tabular  
 \arraystretch  
     : line spacing in array and tabular environments is done by  
       placing a strut in every row of height and depth  
       \arraystretch times the height and depth of the strut  
       produced by an ordinary \strut command.

### PREAMBLE:

The PREAMBLE argument of an array or tabular environment can contain the following:

l,r,c : indicate where entry is to be placed.  
 | : for vertical rule  
 @{EXP} : inserts the text EXP in every column.  
         \arraycolsep or \tabcolsep spacing is suppressed.  
 \*{N}{PRE} : equivalent to writing N copies of PRE in the preamble.  
           PRE may contain \*{N'}{EXP'} expressions.  
 p{LEN} : makes entry in parbox of width LEN.

### SPECIAL ARRAY COMMANDS:

`\multicolumn{N}{FORMAT}{ITEM}` : replaces the next N column items by ITEM, formatted according to FORMAT. FORMAT should contain at most one l,r or c. If it contains none, then ITEM is ignored.

`\vline` : draws a vertical line the height of the current row. May appear in an array element entry.

`\hline` : draws a horizontal line between rows. Must appear either before the first entry (to appear above the first row) or right after a `\\` command. If followed by another `\hline`, then adds a `\vskip` of `\doublerulesep`.

`\cline{i-j}` : draws horizontal lines between rows covering columns i through j, inclusive. Multiple commands may follow one another to provide lines covering several disjoint columns

`\extracolsep{WIDTH}` : for use inside an @ in the preamble. Causes a WIDTH space to be added between columns for the rest of the columns. This is in addition to the ordinary intercolumn space.

```

\array ==
  BEGIN
    \@acol    == \@arrayacol
    \@classz  == \@arrayclassz
    \@classiv == \@arrayclassiv
    \\        == \@arraycr
    \@halignto == NULL
    \@tabarray
  END

\endarray{NAME} == BEGIN \crrc }} END

\tabular ==
  BEGIN
    \@halignto == NULL
    \@tabular
  END

\tabular*{WIDTH} ==
  BEGIN
    \@halignto == to WIDTH
    \@tabular
  END

\@tabular ==
  BEGIN
    \leavevmode
    \hbox { $
      \@acol    == \@tabacol

```

```

\@classz == \@tabclassz
\@classiv == \@tabclassiv
\\ == \@tabularcr
\@tabarray
END

\endtabular == BEGIN \crrc}} $} END

\@tabarray == if next char = [ then \@array else \@array[c] fi

\@array[POS]{PREAMBLE} ==
BEGIN
  define \@arstrutbox to make \@arstrut produce strut of height
    and depth \arraystretch times the height and
    depth of a normal strut.
  \@mkpream{PREAMBLE}
  \@preamble == \halign \@halignto {\tabskip=0pt\@arstrut
    eval{\@preamble}\tabskip = 0pt\cr %%}
  \@startpbox == \@@startpbox
  \@endpbox == \@@endpbox
  if POS = t then \vtop
    else if POS = b then \vbox
      else \vcenter
        fi
      fi
    {
      \par ==L {} % changed 92/09/18
      \@sharp == #
      \protect == \relax
      \lineskip :=L 0pt
      \baselineskip :=L 0pt
      \@preamble
    }
  END

\@arraycr ==
BEGIN
  $ %% Prevents extra space at end of row's last entry.
  if next char = [
    then \@argarraycr
    else $ \cr %% Needed to balance $
  END

\@argarraycr[LENGTH] ==
BEGIN
  $ %% Needed to balance $ of \@arraycr
  if LENGTH > 0
    then \@tempdima := depth of \@arstrutbox + LENGTH
      \vrule height 0pt width 0pt depth \@tempdima
      \cr
    else \cr \noalign{\vskip LENGTH}
  END

```

END

`\@tabularcr` and `\@argtabularcr` same as `\@arraycr` and `\@argarraycr`  
except without the extra `$`'s.

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\extracolsep` This command needs to expand during the tabular preamble construction so can't be robust.

```
167 \def\extracolsep#1{\tabskip #1\relax}
```

*(End of definition for \extracolsep.)*

`\array`~~`\array`~~

```
168 \def\array{\let\@acol\@arrayacol \let\@classz\@arrayclassz
```

```
169 \let\@classiv\@arrayclassiv
```

```
170 \let\\\@arraycr\let\@halignto\@empty\@tabarray}
```

*(End of definition for \array.)*

`\endarray`

`\endtabular`

```
171 \def\endarray{\crcr\egroup\egroup}
```

`\endtabular*`

```
172 \def\endtabular{\crcr\egroup\egroup $\egroup}
```

```
173 \expandafter \let \csname endtabular*\endcsname = \endtabular
```

*(End of definition for \endarray, \endtabular, and \endtabular\*.)*

`\tabular`~~`\tabular`~~

```
174 \def\tabular{\let\@halignto\@empty\@tabular}
```

*(End of definition for \tabular.)*

`\tabular*` Note that the change to use `\setlength` slightly alters the timing of the expansion and use of the length in `#1` but this is very unlikely to have any practical effect.

```
175 \@namedef\tabular*#1{%
```

```
176 \setlength\dimen@{#1}%
```

```
177 \edef\@halignto{to\the\dimen@}\@tabular}
```

*(End of definition for \tabular\*.)*

`\@tabular`

```
178 \def\@tabular{\leavevmode \hbox \bgroup $\let\@acol\@tabacol
```

```
179 \let\@classz\@tabclassz
```

```
180 \let\@classiv\@tabclassiv \let\\\@tabularcr\@tabarray}
```

*(End of definition for \@tabular.)*

`\@tabarray` RmS 91/11/04 added `\m@th`.

```
181 \def\@tabarray{\m@th\@ifnextchar[\@array{\@array[c]}}
```

*(End of definition for \@tabarray.)*

RmS 1993/11/03 changed `\halign` to `\ialign` and removed superfluous `\tabskip` assignment

`\@array`

```
182 \def\@array[#1]#2{%
```

```
183 \if #1t\top \else \if#1b\vbox \else \vcenter \fi\fi
```

184    **\bgroup**

This next bit of code sets up the strut and then builds the halign and its preamble according to the specification in the second argument.

This code has been moved inside the box. A side effect of this has been to expose what was a buglet in the previous version: since the `\@arstrut` below is expanded and contains an `\ifmmode` then it could produce an unnecessary extra box in every row, thus wasting ‘lots of’ main memory.

```
185    \setbox\@arstrutbox\hbox{%
186      \vrule \@height\arraystretch\ht\strutbox
187        \@depth\arraystretch \dp\strutbox
188        \@width\z@}%
189    \@mkpream{#2}%
190    \edef\@preamble{%
191      \ialign \noexpand\@halignto
192        \bgroup \@arstrut \@preamble \tabskip\z@skip \cr}%
```

That is the end of setting up the preamble; now we reset things before executing the halign built-up in `\@preamble`. The restorations could be done by introducing an extra group, thus saving tokens.

```
193    \let\@startpbox\@startpbox \let\@endpbox\@endpbox
194    \let\@tabularnewline\%
195    \def\par{\ifnum\currentgrouptype=6 \else\@@par\fi}%
196    \let\@sharp##%
197    \set@typeset@protect
198    \lineskip\z@skip\baselineskip\z@skip
```

If the parsing of the preamble goes wrong there may be some characters left which  $\mathrm{T}_{\mathrm{E}}\mathrm{X}$  then tries to typeset, i.e., we would be in horizontal mode. That would produce an endless loop because the `\halign` expects vertical mode thus issues a `\par` but that is a no-op at this point. So we better test this case issue some error message and make a crude recovery by ending that horizontal mode with force. A better fix would be to ensure that we never pick up more than a single character token (not done).

```
199    \ifhmode \@preamerr\z@ \@@par\fi
200    \@preamble}
```

*(End of definition for \@array.)*

**\@arraycr**    Array version of `\@array`.

```
201    \protected\def\@arraycr{%
202      ${\ifnum0='}\fi\@ifstar\@xarraycr\@xarraycr}
```

*(End of definition for \@arraycr.)*

**\@arraycr**

```
203    \def\@xarraycr{\@ifnextchar[\@argarraycr{\ifnum0='{ }\fi}\cr}}
```

*(End of definition for \@arraycr.)*

**\@argarraycr**

```
204    \def\@argarraycr[#1]{%
205      \ifnum0='{ }\fi\ifdim #1>\z@ \@xargarraycr{#1}\else
206        \@yargarraycr{#1}\fi}
```

*(End of definition for \@argarraycr.)*

```

\tabularnewline Tabular version of \\.
207 \let\tabularnewline\relax

(End of definition for \tabularnewline.)

\@tabularcr
208 \protected\def\@tabularcr{%
209   {\ifnum0='{ }\fi\@ifstar\@xtabularcr\@xtabularcr}

(End of definition for \@tabularcr.)

\@xtabularcr
210 \def\@xtabularcr{\@ifnextchar[\@argtabularcr{\ifnum0='{ }\fi}\cr}}

(End of definition for \@xtabularcr.)

\@argtabularcr
211 \def\@argtabularcr[#1]{%
212   \ifnum0='{ }\fi}%
213   \ifdim #1>\z@
214     \unskip\@xargarraycr{#1}%
215   \else
216     \@yargarraycr{#1}%
217   \fi}

(End of definition for \@argtabularcr.)

\@xargarraycr
218 \def\@xargarraycr#1{\@tempdima #1\advance\@tempdima \dp \@arstrutbox
219   \vrule \@height\z@ \@depth\@tempdima \@width\z@ \cr}

(End of definition for \@xargarraycr.)

\@yargarraycr
220 \</2ekernel>
221 \<*2ekernel | latexrelease>
222 \<latexrelease>\IncludeInRelease{2020/10/01}%
223 \<latexrelease>{\@yargarraycr}{tabular support calc syntax}%
224 \def\@yargarraycr#1{\cr\noalign{\@vspace@calcify{#1}}}%
225 \</2ekernel | latexrelease>
226 \<latexrelease>\EndIncludeInRelease
227 \<latexrelease>\IncludeInRelease{0000/00/00}%
228 \<latexrelease>{\@yargarraycr}{tabular support calc syntax}%
229 \<latexrelease>
230 \<latexrelease>\def\@yargarraycr#1{\cr\noalign{\vskip #1}}
231 \<latexrelease>\EndIncludeInRelease
232 \<*2ekernel>

(End of definition for \@yargarraycr.)

```

`\multicolumn` *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

\multicolumn{NUMBER}{FORMAT}{ITEM} ==
BEGIN
\multispan{NUMBER}
\beginngroup
\@addamp == null
\@mkpream{FORMAT}
\@sharp == ITEM
\protect == \relax
\@startpbox == \@startpbox
\@endpbox == \@endpbox
\@arstrut
\@preamble
\endgroup
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

The command `\def\@addamp{}` was removed from `\multicolumn` on 6 Dec 86 because it caused embedded array environments not to work. I think that it was included originally to prevent an error message if the 2nd argument to the `\multicolumn` command had two column specifiers.

8 Feb 89 — `\hbox{}` added after `\@preamble` to correct bug that occurred if `\multicolumn` preceded `\[D]` with  $D > 0$ , caused by `\[ ]` command doing an `\unskip`, which removed `\tabcolsep` glue inserted by `\multicolumn`.

This has been made long so that, for example, a `p`-column can contain multiple paragraphs; maybe the arguments of `@`-expressions should also be able to contain multiple paragraphs.

```

233 \long\def\multicolumn#1#2#3{\multispan{#1}\beginngroup
234   \@mkpream{#2}%
235   \def\@sharp{#3}\set@typeset@protect
236   \let\@startpbox\@startpbox\let\@endpbox\@endpbox
237   \@arstrut \@preamble\hbox{\endgroup\ignorespaces}

```

*(End of definition for \multicolumn.)*

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

Codes for classes and character numbers of array, tabular and multicolumn arguments.

Character	Class	Number
c	0	0
l	0	1
r	0	2
	1	-
@	2	-
p	3	-
{@-exp}	4	-
{p-arg}	5	-

`\@testpach \foo` : expands `\foo`, which should be an array parameter

token, and sets \@chclass and \@chnum to its class and number. Uses \@lastchclass to distinguish 4 and 5

Preamble error codes

0: 'illegal character'  
 1: 'Missing @-exp'  
 2: 'Missing p-arg'

```
\@addamp ==
  BEGIN if \@firstamp = true then \@firstamp := false
        else &                                fi
  END
```

```
\@mkpream TOKENLIST ==
  BEGIN
    \@firstamp      := T
    \@lastchclass   := 6
    \@preamble      == null
    \@sharp         == \relax
    \@protect       == BEGIN \noexpand\protect\noexpand END
    \@startpbox     == \relax
    \@endpbox       == \relax
    \@expast{TOKENLIST}
    for \@nextchar := expand(\reserved@a)
      do \@testpach{\@nextchar}
        case of \@chclass
          0 -> \@classz
          1 -> \@classi
          ...
          5 -> \@classv
        end case
        \@lastchclass := \@chclass
      od
    case of \@lastchclass
      0 -> \hskip \arraycolsep           % lrc
      1 ->                                % l
      2 -> \@preamerr1 % 'Missing @-exp' % @
      3 -> \@preamerr2 % 'Missing p-arg' % p
      4 ->                                % @-exp
      5 -> \hskip \arraycolsep           % p-exp
    end case
  END
```

```
\@arrayclassz ==
  BEGIN
    \@preamble := \@preamble *
    case of \@lastchclass
      0 -> \hskip \arraycolsep \@addamp \hskip \arraycolsep
      1 -> \@addamp \hskip \arraycolsep
      2 -> % impossible
```

```

        3 -> % impossible
        4 -> \@addamp
        5 -> \hskip \arraycolsep \@addamp \hskip \arraycolsep
        6 -> \@addamp \hskip \arraycolsep
    end case
* case of \@chnum
    0 -> \hfil$\relax\@sharp$\hfil
    1 -> $\relax\@sharp$\hfil
    2 -> \hfil$\relax\@sharp$
end case

END

\@tabclassz == similar to \@arrayclassz

\@classi ==
BEGIN
    \@preamble := \@preamble *
    case of \@lastchclass
        0 -> \hskip \arraycolsep \@arrayrule
        1 -> \hskip \doublerulesep \@arrayrule
        2 -> % impossible
        3 -> % impossible
        4 -> \@arrayrule
        5 -> \hskip \arraycolsep \@arrayrule
        6 -> \@arrayrule
    end case

END

\@classii ==
BEGIN
    \@preamble := \@preamble *
    case of \@lastchclass
        0 ->
        1 -> \hskip .5\arrayrulewidth
        2 -> % impossible
        else ->
    end case

END

\@classiii ==
BEGIN
    \@preamble := \@preamble *
    case of \@lastchclass
        0 -> \hskip \arraycolsep \@addamp \hskip \arraycolsep
        1 -> \@addamp \hskip \arraycolsep
        2 -> % impossible
        3 -> % impossible
        4 -> \@addamp
        5 -> \hskip \arraycolsep \@addamp \hskip \arraycolsep
        6 -> \@addamp \hskip \arraycolsep

```

```

                                end case
END

\@arrayclassiv ==
    BEGIN \@preamble := \@preamble * $ \@nextchar$ END

\@tabclassiv == same as \@arrayclassv except without the $ ... $

\@classv ==
    BEGIN
        \@preamble :=
            \@preamble * \@startpbox{\@nextchar}\ignorespaces\@sharp
                                \@endpbox
    END

\@expast{S}:
    Sets \reserved@a := S with all instances of *{N}{STRING}
    replaced by N copies of STRING, where N > 0. An *
    appearing inside braces is ignored, but *-expressions
    inside STRING are expanded, so nested *-expressions are
    handled properly.

\@expast{S} == BEGIN \@expast S *0x\@@ END

\@expast S1 *{N}{S2} S3 \@@ ==
    BEGIN
        \reserved@a := S1
        \@tempcnta := N
        if \@tempcnta > 0
            then while \@tempcnta > 0 do \reserved@a := \reserved@a S2
                                \@tempcnta := \@tempcnta - 1 od
                \reserved@b == \@expast
            else \reserved@b == \@exnoop
            fi
        \expandafter \reserved@b \reserved@a S3 \@@
    END
End of historical LATEX 2.09 comments.

\@exnoop
238 \def\@exnoop #1\@@{}
(End of definition for \@exnoop.)

\@expast
239 \def\@expast#1{\@expast #1*0x\@@}
(End of definition for \@expast.)

```

```

\@xexpast
240 \def\@xexpast#1*#2#3#4\@@{%
241   \edef\reserved@a{#1}%
242   \@tempcnta#2\relax
243   \ifnum\@tempcnta>\z@
244     \@whilenum\@tempcnta>\z@\do
245       {\edef\reserved@a{\reserved@a#3}\advance\@tempcnta \m@ne}%
246     \let\reserved@b\@xexpast
247   \else
248     \let\reserved@b\@xexnoop
249   \fi
250   \expandafter\reserved@b\reserved@a #4\@@}

(End of definition for \@xexpast.)

\if@firstamp
  \@addamp 251 \newif\if@firstamp
252 \def\@addamp{%
253   \if@firstamp
254     \@firstampfalse
255   \else
256     \edef\@preamble{\@preamble &}%
257   \fi}

(End of definition for \if@firstamp and \@addamp.)

\@arrayacol
  \@tabacol 258 \def\@arrayacol{\edef\@preamble{\@preamble \hskip \arraycolsep}}
  \@ampacol 259 \def\@tabacol{\edef\@preamble{\@preamble \hskip \tabcolsep}}
\@acolampacol 260 \def\@ampacol{\@addamp \@acol}
261 \def\@acolampacol{\@acol\@addamp\@acol}

(End of definition for \@arrayacol and others.)

\@mkpream
262 \def\@mkpream#1{\@firstamptrue\@lastchclass6
263   \let\@preamble\@empty
264   \let\protect\@unexpandable@protect
265   \let\@sharp\relax
266   \let\@startpbox\relax\let\@endpbox\relax
267   \@expast{#1}%
268   \expandafter\@tfor \expandafter
269     \@nextchar \expandafter:\expandafter=\reserved@a\do
270     {\@testpach\@nextchar
271       \ifcase \@chclass \@classz \or \@classi \or \@classii \or \@classiii
272         \or \@classiv \or \@classv \fi\@lastchclass\@chclass}%
273   \ifcase \@lastchclass \@acol
274     \or \or \@preamerr \@ne\or \@preamerr \tw@\or \or \@acol \fi}

(End of definition for \@mkpream.)

```

`\@arrayclassz`

```
275 \def\@arrayclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
276 \or \or \@addamp \or
277 \@acolampacol \or \@firstampfalse \@acol \fi
278 \edef\@preamble{\@preamble
279 \ifcase \@chnum
280 \hfil$\relax\@sharp$\hfil \or $\relax\@sharp$\hfil
281 \or \hfil$\relax\@sharp$\fi}}
```

*(End of definition for \@arrayclassz.)*

`\@tabclassz` RmS 91/08/14 inserted extra braces around entry for NFSS

```
282 \def\@tabclassz{%
283 \ifcase\@lastchclass
284 \@acolampacol
285 \or
286 \@ampacol
287 \or
288 \or
289 \or
290 \@addamp
291 \or
292 \@acolampacol
293 \or
294 \@firstampfalse\@acol
295 \fi
296 \edef\@preamble{%
297 \@preamble{%
298 \ifcase\@chnum
299 \hfil
300 \hskip1sp%
301 \ignorespaces\@sharp\unskip\hfil
302 \or
303 \hskip1sp\ignorespaces\@sharp\unskip\hfil
304 \or
305 \hfil\hskip1sp\ignorespaces\@sharp\unskip
306 \fi}}}
```

*(End of definition for \@tabclassz.)*

`\@classi`

```
307 \def\@classi{%
308 \ifcase\@lastchclass
309 \@acol\@arrayrule
310 \or
311 \@addtopreamble{\hskip \doublerulesep}\@arrayrule
312 \or
313 \or
314 \or
315 \@arrayrule
316 \or
317 \@acol\@arrayrule
318 \or
```

```

319     \@arrayrule
320     \fi}

(End of definition for \@classi.)

\@classii

321 \def\@classii{%
322     \ifcase\@lastchclass
323     \or
324     \@addtopreamble{\hskip .5\arrayrulewidth}%
325     \fi}

(End of definition for \@classii.)

\@classiii

326 \def\@classiii{\ifcase \@lastchclass \@acolampacol \or
327     \@addamp\@acol \or
328     \or \or \@addamp \or
329     \@acolampacol \or \@ampacol \fi}

(End of definition for \@classiii.)

\@tabclassiv

330 \def\@tabclassiv{\@addtopreamble\@nextchar}

(End of definition for \@tabclassiv.)

\@arrayclassiv

331 \def\@arrayclassiv{\@addtopreamble{$\@nextchar$}}

(End of definition for \@arrayclassiv.)

\@classv

332 \def\@classv{\@addtopreamble{\@startpbox{\@nextchar}\ignorespaces
333     \@sharp\@endpbox}}

(End of definition for \@classv.)

\@addtopreamble

334 \def\@addtopreamble#1{\edef\@preamble{\@preamble #1}}

(End of definition for \@addtopreamble.)

\@chclass
\@lastchclass
\@chnum
335 \newcount\@chclass
336 \newcount\@lastchclass
337 \newcount\@chnum

(End of definition for \@chclass, \@lastchclass, and \@chnum.)

\arraycolsep
\@tabcolsep
\arrayrulewidth
\doublerulesep
338 \newdimen\arraycolsep
339 \newdimen\@tabcolsep
340 \newdimen\arrayrulewidth
341 \newdimen\doublerulesep

```

(End of definition for \arraycolsep and others.)

\arraystretch

```
342 \def\arraystretch{1} % Default value.
```

(End of definition for \arraystretch.)

\@arstrutbox

\@arstrut

```
343 \newbox\@arstrutbox
```

```
344 \def\@arstrut{%
```

```
345 \relax\ifmmode\copy\@arstrutbox\else\unhcopy\@arstrutbox\fi}
```

(End of definition for \@arstrutbox and \@arstrut.)

\@arrayrule

```
346 \def\@arrayrule{\@addtopreamble{\hskip -.5\arrayrulewidth
```

```
347 \vrule \@width \arrayrulewidth\hskip -.5\arrayrulewidth}}
```

(End of definition for \@arrayrule.)

\@testpach

```
348 \def\@testpach#1{\@chclass \ifnum \@lastchclass=\tw@ 4 \else
```

```
349 \ifnum \@lastchclass=3 5 \else
```

```
350 \z@ \if #1c\@chnum \z@ \else
```

```
351 \if #1l\@chnum \@ne \else
```

```
352 \if #1r\@chnum \tw@ \else
```

```
353 \@chclass \if #1\@ne \else
```

```
354 \if #1@\tw@ \else
```

```
355 \if #1p3 \else \z@ \@preamerr 0\fi
```

```
356 \fi \fi \fi \fi \fi \fi
```

```
357 \fi}
```

(End of definition for \@testpach.)

\hline

```
358 \def\hline{%
```

```
359 \noalign{\ifnum0='}\fi\hrule \@height \arrayrulewidth \futurelet
```

```
360 \reserved@a\@xhline}
```

(End of definition for \hline.)

\@xhline

```
361 \def\@xhline{\ifx\reserved@a\hline
```

```
362 \vskip\doublerulesep
```

Measure from the middle of the rules.

```
363 \vskip-\arrayrulewidth
```

```
364 \fi
```

```
365 \ifnum0='{ \fi}}
```

(End of definition for \@xhline.)

\vline

```
366 \def\vline{\vrule \@width \arrayrulewidth}
```

(End of definition for \vline.)

`\cline` The old L<sup>A</sup>T<sub>E</sub>X2.09 implementation of `\cline` used up quite a lot of memory and two precious count registers. This new (1995/09/14) implementation does not use any count registers. It is coded in a way that depends heavily on the definition of `\multispan` so that command has been moved here from the file `ltplain.dtx`.

These counters are no longer declared.

```
\newcount\@cla
```

```
\newcount\@clb
```

```
367 \def\cline#1{\@cline#1\@nil}
```

```
368 \def\@cline#1-#2\@nil{%
```

```
369 \omit
```

Use the counter from `\multispan`.

```
370 \@multicnt#1%
```

```
371 \advance\@multispan\m@ne
```

```
372 \ifnum\@multicnt=\@ne\@firstofone{&\omit}\fi
```

```
373 \@multicnt#2%
```

```
374 \advance\@multicnt-#1%
```

```
375 \advance\@multispan\@ne
```

The original had `\unskip` at this point, but how could a skip get here ???

```
376 \leaders\hrule\@height\arrayrulewidth\hfill
```

```
377 \cr
```

This is back spacing is fairly horrible, but it is what happened in the old version... An alternative would be to make `\cline` look ahead for a following `\cline` as does `\hline`. This would alter the spacing in existing documents so keep the old version in the kernel. Perhaps a package should do this differently.

```
378 \noalign{\vskip-\arrayrulewidth}}
```

*(End of definition for `\cline` and `\@cline`.)*

`\mscount` The `\mscount` counter is no longer declared, saving a csname and a register. It is declared in compatibility mode.

*(End of definition for `\mscount`.)*

`\multispan` Modify `\multispan` slightly from its plain T<sub>E</sub>X definition to allow more efficient code sharing with `\multicolumn`. Also share a count register with `\multipt`.

```
\@multispan \sp@n 379 \def\multispan{\omit\@multispan}
```

```
380 \def\@multispan#1{%
```

```
381 \@multicnt#1\relax
```

```
382 \loop\ifnum\@multicnt>\@ne \sp@n\repeat}
```

```
383 \def\sp@n{\span\omit\advance\@multicnt\m@ne}
```

*(End of definition for `\multispan`, `\@multispan`, and `\sp@n`.)*

`\@startpbox` Helper macros for ‘p’ columns.

```
\@endpbox \@startpbox{<width>} text \egroup is essentially \parbox{<width>}{<text>}
```

`\@endpbox` is essentially `\unskip \strut \par \egroup\hfil` (Changed 14 Jan 89)  
(changed again 1994/05/13)

```
384 \def\@startpbox#1{\vtop\bgroup \setlength\hsize{#1}\@arrayparboxrestore}
```

```
385 \def\@endpbox{\@finalstrut\@arstrutbox\par\egroup\hfil}
```

14 Jan 89: Def of \@endpbox changed from  
`\def\@endpbox{\par\vskip\dp\@arstrutbox\egroup\hfil}`  
so vertical spacing works out right if the last line of a ‘p’ entry has a descender.

*(End of definition for \@startpbox and \@endpbox.)*

`\@@startpbox`

`\@@endpbox`

```
386 \let\@@startpbox=\@startpbox
```

```
387 \let\@@endpbox=\@endpbox
```

*(End of definition for \@@startpbox and \@@endpbox.)*

```
388 </2ekernel>
```

## File 42

# ltpictur.dtx

## 1 Picture Mode

Picture mode commands. In addition to the commands available in L<sup>A</sup>T<sub>E</sub>X 2.09, This section adds the new `\qbezier` command for drawing curves.

`\qbezier`     `\qbezier[N](AX,AY)(BX,BY)(CX,CY)` plots a quadratic Bezier curve from (*AX,AY*) to (*CX,CY*), with (*BX,BY*) as the third Bezier point, using *N*+1 points equally spaced parametrically. If *N* = 0 (the default value), then a sufficient number of points are used to draw a connected curve—except that at most `\qbeziermax+1` points are drawn. A “point” is a square of side `\@wholewidth`.

`\bezier`     In addition, to be compatible with the old `bezier` package, a variant of this command, `\bezier`, is defined, in which the first argument is not optional.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

<code>\unitlength</code>	= value of dimension argument
<code>\@wholewidth</code>	= current line width
<code>\@halfwidth</code>	= half of current line width
<code>\@linefnt</code>	= font for drawing lines
<code>\@circlefnt</code>	= font for drawing circles

`\linethickness{DIM}` : Sets the width of horizontal and vertical lines in a picture to DIM. Does not change width of slanted lines or circles. Width of all lines reset by `\thinlines` and `\thicklines`

```
\picture(XSIZE,YSIZE)(XORG,YORG)
  BEGIN
    \@picht :=L YSIZE * \unitlength
    box \@picbox :=
      \hb@xt@ XSIZE * \unitlength
      {\hskip -XORG * \unitlength
       \lower YORG * \unitlength
       \hbox{
         \ignorespaces      %% added 13 June 89
       }
    }
  END
```

```
\endpicture ==
  BEGIN
    } \hss }
    height of \@picbox := \@picht
    depth of \@picbox := 0
    \mbox{\box\@picbox}    %% change 26 Aug 91
  END
```

```
\put(X, Y){OBJ} ==
  BEGIN
```

```

\@killglue
\raise Y * \unitlength \hb@xt@ 0pt { \hskip X * \unitlength
                                OBJ \hss }

\ignorespaces
END

\multiput(X,Y)(DELX,DELY){N}{OBJ} ==
BEGIN
\@killglue
\@multicnt := N
\@xdim := X * \unitlength
\@ydim := Y * \unitlength
while \@multicnt > 0
do \raise \@ydim \hb@xt@ 0pt { \hskip \@xdim
                                OBJ \hss }

\@multicnt := \@multicnt - 1
\@xdim := \@xdim + DELX * \unitlength
\@ydim := \@ydim + DELY * \unitlength
od
\ignorespaces
END

```

`\shortstack[POS]{TEXT}` : Makes a `\vbox` containing TEXT stacked as a one-column array, positioned l, r or c as indicated by POS.

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

The ‘2ekernel’ code ensures that a `\usepackage{autopict}` is essentially ignored if a ‘full’ format is being used that has picture mode already in the format.

```
1 <2ekernel>\expandafter\let\csname ver@autopict.sty\endcsname\fmtversion
```

```

\@wholewidth
\@halfwidth
2 <*2ekernel>
3 \newdimen\@wholewidth
4 \newdimen\@halfwidth

(End of definition for \@wholewidth and \@halfwidth.)

```

```

\unitlength
5 \newdimen\unitlength \unitlength =1pt

(End of definition for \unitlength.)

```

```

\@picbox
\@picht
6 \newbox\@picbox
7 \newdimen\@picht

(End of definition for \@picbox and \@picht.)

```

`\@defaultunitsset` Set a length register, #1, accepting number or an etex length expression, #2, with default unit, #3.

The register name in #1 can be prefixed by `\advance` so that the register is incremented by the supplied value.

`\@defaultunitsset{\advance\@vxx}{\textwidth-15pt}\unitlength`

#3 can be a literal unit such as `cm` or a length register such as `\unitlength`.

This is used in all `picture` commands that take picture coordinates. So `\put(2,2)` as previously but now `\put(\textwidth-5cm,0.4\textheight)` Note that you can only use expressions with lengths, `\put(1+2,0)` is not supported.

```

8 </2ekernel>
9 <*2ekernel | latexrelease>
10 <latexrelease>\IncludeInRelease{2020/10/01}%
11 <latexrelease>          {\@defaultunitsset}{default units}%
12 \def\@defaultunitsset#1#2#3{%
13   \@defaultunits#1\dimexpr#2#3\relax\relax\@nnil}
14 </2ekernel | latexrelease>

15 <latexrelease>\EndIncludeInRelease
16 <latexrelease>\IncludeInRelease{0000/00/00}%
17 <latexrelease>          {\@defaultunitsset}{default units}%
18 <latexrelease>\let\@defaultunitsset\undefined
19 <latexrelease>\EndIncludeInRelease
20 <*2ekernel>

```

*(End of definition for \@defaultunitsset.)*

`\picture` ~~`\picture`~~ #1 should be white space.

#1 should be a ( (eating any white space before the bracket),

```

\picture@
21 \long\def\picture#1{\picture@#1}
22 \def\picture@(#1){%
23   \ifnextchar({\@picture(#1)}{\@picture(#1)(0,0)}}

```

*(End of definition for \picture and \picture@.)*

`\@picture`

```

24 </2ekernel>
25 <*2ekernel | latexrelease>
26 <latexrelease>\IncludeInRelease{2020/10/01}%
27 <latexrelease>          {\@picture}{default units}%
28 \def\@picture(#1,#2)(#3,#4){%
29   \@defaultunitsset\@picht{#2}\unitlength
30   \@defaultunitsset\@tempdimc{#1}\unitlength
31   \setbox\@picbox\hbext@\@tempdimc\bgroup
32     \@defaultunitsset\@tempdimc{#3}\unitlength
33     \hskip -\@tempdimc
34     \@defaultunitsset\@tempdimc{#4}\unitlength
35     \lower\@tempdimc\hbox\bgroup
36     \ignorespaces}
37 </2ekernel | latexrelease>

```

```

38 <latexrelease>\EndIncludeInRelease
39 <latexrelease>\IncludeInRelease{0000/00/00}%
40 <latexrelease>          {\@picture}{default units}%
41 <latexrelease>\def\@picture(#1,#2)(#3,#4){%
42 <latexrelease>  \picht#2\unitlength
43 <latexrelease>  \setbox\@picbox\hb@xt@#1\unitlength\bgroup
44 <latexrelease>    \hskip -#3\unitlength
45 <latexrelease>    \lower #4\unitlength\hbox\bgroup
46 <latexrelease>    \ignorespaces}
47 <latexrelease>\EndIncludeInRelease
48 <*2ekernel>

```

(End of definition for \@picture.)

\endpicture

```

49 \def\endpicture{%
50   \egroup\hss\egroup
51   \ht\@picbox\@picht\dp\@picbox\z@
52   \mbox{\box\@picbox}}

```

(End of definition for \endpicture.)

In the definitions of \put and \multiput, \hskip was replaced by \kern just in case arg #3 = “plus”. (Bug detected by Don Knuth. changed 20 Jul 87).

```

53 </2ekernel>
54 <*2ekernel | latexrelease>
55 <latexrelease>\IncludeInRelease{2020/10/01}%
56 <latexrelease>          {\put}{default units}%
57 <latexrelease>\expandafter\let\csname put \endcsname \@undefined
58 \long\def\put(#1,#2)#3{%
59   \@killglue
60   \@defaultunitsset\@tempdimc{#2}\unitlength
61   \raise\@tempdimc
62   \hb@xt@\z@{%
63     \@defaultunitsset\@tempdimc{#1}\unitlength
64     \kern\@tempdimc
65     #3\hss}%
66   \ignorespaces}
67 </2ekernel | latexrelease>
68 <latexrelease>\EndIncludeInRelease
69 <latexrelease>\IncludeInRelease{0000/00/00}%
70 <latexrelease>          {\put}{default units}%
71 <latexrelease>\expandafter\let\csname put \endcsname \@undefined
72 <latexrelease>\long\def\put(#1,#2)#3{%
73 <latexrelease>  \@killglue\raise#2\unitlength
74 <latexrelease>  \hb@xt@\z@{\kern#1\unitlength #3\hss}%
75 <latexrelease>  \ignorespaces}
76 <latexrelease>\EndIncludeInRelease
77 <*2ekernel>

```

\multiput #3 had better be a (.

```

78 </2ekernel>
79 <*2ekernel | latexrelease>
80 <latexrelease>\IncludeInRelease{2020/10/01}%

```

```

81 <latexrelease>                {\multiput}{default units}%
82 <latexrelease>\expandafter\let\csname multiput \endcsname\@undefined
83 \def\multiput(#1,#2)#3{%
84   \@defaultunitsset\@xdim{#1}\unitlength
85   \@defaultunitsset\@ydim{#2}\unitlength
86   \@multiput{ }
87 </2ekernel | latexrelease>

88 <latexrelease>\EndIncludeInRelease
89 <latexrelease>\IncludeInRelease{0000/00/00}%
90 <latexrelease>                {\multiput}{default units}%
91 <latexrelease>\expandafter\let\csname multiput \endcsname\@undefined
92 <latexrelease>\def\multiput(#1,#2)#3{%
93 <latexrelease>   \@xdim #1\unitlength
94 <latexrelease>   \@ydim #2\unitlength
95 <latexrelease>   \@multiput{ }
96 <latexrelease>\EndIncludeInRelease
97 <*2ekernel>

```

(End of definition for \multiput.)

\@multiput

```

98 </2ekernel>
99 <*2ekernel | latexrelease>
100 <latexrelease>\IncludeInRelease{2020/10/01}%
101 <latexrelease>                {\@multiput}{default units}%
102 \long\def\@multiput(#1,#2)#3#4{%
103   \@killglue\@multicnt #3\relax
104   \@whilenum \@multicnt >\z@ \do
105     {\raise\@ydim\hb@xt@{\z@}{\kern\@xdim #4\hss}%
106     \advance\@multicnt\m@ne
107     \@defaultunitsset{\advance\@xdim}{#1}\unitlength
108     \@defaultunitsset{\advance\@ydim}{#2}\unitlength}%
109   \ignorespaces}
110 </2ekernel | latexrelease>

111 <latexrelease>\EndIncludeInRelease
112 <latexrelease>\IncludeInRelease{0000/00/00}%
113 <latexrelease>                {\@multiput}{default units}%
114 <latexrelease>\long\def\@multiput(#1,#2)#3#4{%
115 <latexrelease>   \@killglue\@multicnt #3\relax
116 <latexrelease>   \@whilenum \@multicnt >\z@ \do
117 <latexrelease>     {\raise\@ydim\hb@xt@{\z@}{\kern\@xdim #4\hss}%
118 <latexrelease>     \advance\@multicnt\m@ne
119 <latexrelease>     \advance\@xdim#1\unitlength\advance\@ydim#2\unitlength}%
120 <latexrelease>   \ignorespaces}
121 <latexrelease>\EndIncludeInRelease
122 <*2ekernel>

```

(End of definition for \@multiput.)

\@killglue

```

123 \def\@killglue{\unskip\@whiledim \lastskip >\z@ \do{\unskip}}

```

(End of definition for \@killglue.)

```

\thinlines
\thicklines
124 \DeclareRobustCommand\thinlines{\let\@linefnt\tenln
125 \let\@circlefnt\tencirc
126 \@wholewidth\fontdimen8\tenln \@halfwidth .5\@wholewidth}
127 \DeclareRobustCommand\thicklines{\let\@linefnt\tenlnw
128 \let\@circlefnt\tencircw
129 \@wholewidth\fontdimen8\tenlnw \@halfwidth .5\@wholewidth}

(End of definition for \thinlines and \thicklines.)

\linethickness

130 \DeclareRobustCommand*\linethickness[1]
131 {\@wholewidth #1\relax \@halfwidth .5\@wholewidth \ignorespaces}

(End of definition for \linethickness.)

\ishortstack

132 \def\shortstack{\@ifnextchar[\@shortstack{\@shortstack[c]}}

(End of definition for \ishortstack.)

\@ishortstack

133 \def\@shortstack[#1]{%
134 \leavevmode
135 \vbox\bgroup
136 \baselineskip-\p@ \lineskip 3\p@
137 \let\mb@l\hss\let\mb@r\hss
138 \expandafter\let\csname mb@#1\endcsname\relax
139 \let\\\@stackcr
140 \@ishortstack}

(End of definition for \@ishortstack.)

\@ishortstack

141 \def\@ishortstack#1{\ialign{\mb@l {##}\unskip\mb@r\cr #1\cr}\egroup}

(End of definition for \@ishortstack.)

\@stackcr
\@ixstackcr
142 \protected\def\@stackcr{\@ifstar\@ixstackcr\@ixstackcr}
143 \def\@ixstackcr{\@ifnextchar[\@istackcr{\cr\ignorespaces}}

(End of definition for \@stackcr and \@ixstackcr.)

\@istackcr

144 </2ekernel>
145 <*2ekernel | latexrelease>
146 <latexrelease>\IncludeInRelease{2020/10/01}%
147 <latexrelease> \@istackcr{\shortstack calc support}%
148 \def\@istackcr[#1]{\cr\noalign{\@vspace@calcify{#1}}\ignorespaces}
149 </2ekernel | latexrelease>

```

```

150 <latexrelease>\EndIncludeInRelease
151 <latexrelease>\IncludeInRelease{0000/00/00}%
152 <latexrelease>{\@istackcr}{\shortstack calc support}%
153 <latexrelease>
154 <latexrelease>\def\@istackcr[#1]{\cr\noalign{\vskip #1}\ignorespaces}
155 <latexrelease>\EndIncludeInRelease
156 <*2ekernel>

(End of definition for \@istackcr.)
Historical LATEX 2.09 comments (not necessarily accurate any more):
\line(X,Y){LEN} ==
BEGIN
  \@xarg := X
  \@yarg := Y
  \@linelen := LEN * \unitlength
  if \@xarg = 0
    then \vline
    else if \@yarg = 0
      then \hline
      else \sline
    if
  if
END

\sline ==
BEGIN
  if \@xarg < 0
    then @negarg := T
      \@xarg := -\@xarg
      \@yyarg := -\@yarg
    else @negarg := F
      \@yyarg := \@yarg
  fi
  \@tempcnta := |\@yyarg|
  if \@tempcnta > 6
    then error: 'LATEX ERROR: Illegal \line or \vector argument.'
      \@tempcnta := 0
  fi
  \box\@linechar := \hbox{\@linefont \@getlinechar(\@xarg,\@yyarg) }
  if \@yarg > 0 then \@upordown = \raise
    \@clnht := 0
  else \@upordown = \lower
    \@clnht := height of \box\@linechar
  fi
  \@clnwd := width of \box\@linechar
  if @negarg
    then \hskip - width of \box\@linechar
      \reserved@a == \hskip - 2* width of box \@linechar
    else \reserved@a == \relax
  fi
  %% Put out integral number of line segments

```

```

while \@clnwd < \@linelen
do \@upordown \@clnht \copy\@linechar
\reserved@a
\@clnht := \@clnht + ht of \box\@linechar
\@clnwd := \@clnwd + width of \box\@linechar
od

%% Put out last segment
\@clnht := \@clnht - height of \box\@linechar
\@clnwd := \@clnwd - width of \box\@linechar
\@tempdima := \@linelen - \@clnwd
\@tempdimb := \@tempdima - width of \box\@linechar
if @negarg then \hskip -\@tempdimb
else \hskip \@tempdimb
fi
\@tempdima := 1000 * \@tempdima
\@tempcnta := \@tempdima / width of \box\@linechar
\@tempdima := (\@tempcnta * ht of \box\@linechar)/1000
\@clnht := \@clnht + \@tempdima
if \@linelen < width of \box\@linechar
then \hskip width of \box\@linechar
else \hbox{\@upordown \@clnht \copy\@linechar}
fi
END

\@hline ==
BEGIN
if \@xarg < 0 then \hskip -\@linelen \fi
\vrule height \@halfwidth depth \@halfwidth width \@linelen
if \@xarg < 0 then \hskip -\@linelen \fi
END

\@vline == if \@yarg < 0 \@downline else \@upline fi

\@getlinechar(X,Y) ==
BEGIN
\@tempcnta := 8*X - 9
if Y > 0
then \@tempcnta := \@tempcnta + Y
else \@tempcnta := \@tempcnta - Y + 64
fi
\char\@tempcnta
END

\vector(X,Y){LEN} ==
BEGIN
\@xarg := X
\@yarg := Y
\@linelen := LEN * \unitlength

```

```

if \@xarg = 0
  then \@vvector
  else if \@yarg = 0
    then \@hvector
    else \@svector
  if
if
END

\@hvector ==
BEGIN
  \@hline
  {\@linefmt if \@xarg < 0 then \@getlarrow(1,0)
    else \@getrarrow(1,0)
  fi}
END

\@vvector == if \@yarg < 0 \@downvector else \@upvector fi

\@svector ==
BEGIN
  \@sline
  \@tempcnta := | \@yarg |
  if \@tempcnta < 5
    then \hskip - width of \box\@linechar
      \@upordown \@clnht \hbox
        {\@linefmt
          if @negarg then \@getlarrow(\@xarg,\@yyarg)
            else \@getrarrow(\@xarg,\@yyarg)
          fi }
    else error: 'LATEX ERROR: Illegal \line or \vector argument.'
  fi
END

\@getlarrow(X,Y) ==
BEGIN
  if Y = 0
    then \@tempcnta := '33
  else \@tempcnta := 16 * X - 9
    \@tempcntb := 2 * Y
    if \@tempcntb > 0
      then \@tempcnta := \@tempcnta + \@tempcntb
      else \@tempcnta := \@tempcnta - \@tempcntb + 64
    fi
  fi
  \char\@tempcnta
END

\@getrarrow(X,Y) ==
BEGIN

```

```

\@tempcntb := |Y|
case of \@tempcntb
  0 : \@tempcnta := '55
  1 : if X < 3
      then \@tempcnta := 24*X - 6
      else if X = 3
          then \@tempcnta := 49
          else \@tempcnta := 58 fi
      fi
  2 : if X < 3
      then \@tempcnta := 24*X - 3
      else \@tempcnta := 51 % X must = 3
      fi
  3 : \@tempcnta := 16*X - 2
  4 : \@tempcnta := 16*X + 7
endcase
if Y < 0
  then \@tempcnta := \@tempcnta + 64
  fi
\char\@tempcnta
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\if@negarg`

```

157 \newif\if@negarg

```

*(End of definition for \if@negarg.)*

`\line`

```

158 </2ekernel>
159 <*2ekernel|latexrelease>
160 <latexrelease>\IncludeInRelease{2020/10/01}%
161 <latexrelease>          {\line}{default units}%
162 <latexrelease>\expandafter\let\csname line \endcsname\@undefined
163 \def\line(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
164   \@defaultunitsset\@linelen{#3}\unitlength
165   \ifdim\@linelen<\z@\@badlinearg\else
166     \ifnum\@xarg =\z@ \@vline
167     \else \ifnum\@yarg =\z@ \@hline \else \@sline\fi
168   \fi
169   \fi}
170 </2ekernel|latexrelease>

171 <latexrelease>\EndIncludeInRelease
172 <latexrelease>\IncludeInRelease{0000/00/00}%
173 <latexrelease>          {\line}{default units}%
174 <latexrelease>\expandafter\let\csname line \endcsname\@undefined
175 <latexrelease>\def\line(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
176 <latexrelease>  \@linelen #3\unitlength
177 <latexrelease>  \ifdim\@linelen<\z@\@badlinearg\else
178 <latexrelease>    \ifnum\@xarg =\z@ \@vline
179 <latexrelease>    \else \ifnum\@yarg =\z@ \@hline \else \@sline\fi
180 <latexrelease>    \fi

```

```

181 <latexrelease> \fi}
182 <latexrelease>\EndIncludeInRelease
183 <*2ekernel>

```

(End of definition for \line.)

\@sline

```

184 \def\@sline{%
185   \ifnum\@xarg<\z@ \@negargtrue \@xarg -\@xarg \@yyarg -\@yarg
186   \else \@negargfalse \@yyarg \@yarg \fi
187   \ifnum \@yyarg >\z@ \@tempcnta\@yyarg \else \@tempcnta -\@yyarg \fi
188   \ifnum\@tempcnta>6 \@badlinearg\@tempcnta\z@ \fi
189   \ifnum\@xarg>6 \@badlinearg\@xarg \@ne \fi
190   \setbox\@linechar\hbox{\@linefnt\@getlinechar(\@xarg,\@yyarg)}%

```

If we have something like \line(5,5){30} the \@linechar will not contain a char and later on we will end in an infinite loop. So we check the width of the box and put in something as an emergency fix if necessary.

```

191 \ifdim\wd\@linechar=\z@
192   \setbox\@linechar\hbox{.}%
193   \@badlinearg
194 \fi
195 \ifnum \@yarg >\z@ \let\@upordown\raise \@clnht\z@
196   \else\let\@upordown\lower \@clnht \ht\@linechar\fi
197 \@clnwd \wd\@linechar
198 \if@negarg
199   \hskip -\wd\@linechar \def\reserved@a{\hskip -2\wd\@linechar}%
200 \else
201   \let\reserved@a\relax
202 \fi
203 \@whiledim \@clnwd <\@linelen \do
204   {\@upordown\@clnht\copy\@linechar
205     \reserved@a
206     \advance\@clnht \ht\@linechar
207     \advance\@clnwd \wd\@linechar}%
208 \advance\@clnht -\ht\@linechar
209 \advance\@clnwd -\wd\@linechar
210 \@tempdima\@linelen\advance\@tempdima -\@clnwd
211 \@tempdimb\@tempdima\advance\@tempdimb -\wd\@linechar
212 \if@negarg \hskip -\@tempdimb \else \hskip \@tempdimb \fi
213 \multiply\@tempdima \@m
214 \@tempcnta \@tempdima
215 \@tempdima \wd\@linechar \divide\@tempcnta \@tempdima
216 \@tempdima \ht\@linechar \multiply\@tempdima \@tempcnta
217 \divide\@tempdima \@m
218 \advance\@clnht \@tempdima
219 \ifdim \@linelen <\wd\@linechar
220   \hskip \wd\@linechar

```

Warn if line gets so short that it can't be printed. But don't warn if it is exactly zero since that was probably deliberate (e.g., to get a vector head only).

```

221 \ifdim \@linelen = \z@
222 \else
223   \@picture@warn
224 \fi

```

```
225 \else\@upordown\@clnht\copy\@linechar\fi}
```

(End of definition for \@sline.)

\@hline

```
226 \def\@hline{\ifnum \@xarg <\z@ \hskip -\@linelen \fi
227 \vrule \@height \@halfwidth \@depth \@halfwidth \@width \@linelen
228 \ifnum \@xarg <\z@ \hskip -\@linelen \fi}
```

(End of definition for \@hline.)

\@getlinechar

```
229 \def\@getlinechar(#1,#2){\@tempcnta#1\relax\multiply\@tempcnta 8%
230 \advance\@tempcnta -9\ifnum #2>\z@ \advance\@tempcnta #2\relax\else
231 \advance\@tempcnta -#2\relax\advance\@tempcnta 64 \fi
232 \char\@tempcnta}
```

(End of definition for \@getlinechar.)

\vector

```
233 </2ekernel>
234 <*2ekernel | latexrelease>
235 <latexrelease>\IncludeInRelease{2020/10/01}%
236 <latexrelease> \{\vector\}{default units}%
237 <latexrelease>\expandafter\let\csname vector \endcsname\@undefind
238 \def\vector(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
239 \@tempcnta \ifnum\@xarg<\z@ -\@xarg\else\@xarg\fi
240 \ifnum\@tempcnta<5\relax
241 \@defaultunitsset\@linelen{#3}\unitlength
242 \ifdim\@linelen<\z@\@badlinearg\else
243 \ifnum\@xarg =\z@ \@vvector
244 \else \ifnum\@yarg =\z@ \@hvector \else \@svector\fi
245 \fi
246 \fi
247 \else\@badlinearg\fi}
248 </2ekernel | latexrelease>
249 <latexrelease>\EndIncludeInRelease
250 <latexrelease>\IncludeInRelease{0000/00/00}%
251 <latexrelease> \{\vector\}{default units}%
252 <latexrelease>\expandafter\let\csname vector \endcsname\@undefind
253 <latexrelease>\def\vector(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
254 <latexrelease> \@tempcnta \ifnum\@xarg<\z@ -\@xarg\else\@xarg\fi
255 <latexrelease> \ifnum\@tempcnta<5\relax
256 <latexrelease> \@linelen #3\unitlength
257 <latexrelease> \ifdim\@linelen<\z@\@badlinearg\else
258 <latexrelease> \ifnum\@xarg =\z@ \@vvector
259 <latexrelease> \else \ifnum\@yarg =\z@ \@hvector \else \@svector\fi
260 <latexrelease> \fi
261 <latexrelease> \fi
262 <latexrelease> \else\@badlinearg\fi}
263 <latexrelease>\EndIncludeInRelease
264 <*2ekernel>
```

(End of definition for \vector.)

```

\@hvector
265 \def\@hvector{\@hline\hb@xt@\z@\{\@linefnt
266 \ifnum \@xarg <\z@ \@getlarrow(1,0)\hss\else
267 \hss\@getrarrow(1,0)\fi}}

(End of definition for \@hvector.)

\@vvector
268 \def\@vvector{\ifnum \@yarg <\z@ \@downvector \else \@upvector \fi}

(End of definition for \@vvector.)

\@svector
269 \def\@svector{\@sline
270 \@tempcnta\@yarg \ifnum\@tempcnta <\z@ \@tempcnta -\@tempcnta\fi
271 \ifnum\@tempcnta <5%
272 \hskip -\wd\@linechar
273 \@upordown\@clnht \hbox{\@linefnt \if@negarg
274 \@getlarrow(\@xarg,\@yyarg)\else \@getrarrow(\@xarg,\@yyarg)\fi}%
275 \else\@badlinearg\fi}

(End of definition for \@svector.)

\@getlarrow
276 \def\@getlarrow(#1,#2){\ifnum #2=\z@ \@tempcnta 27 % '33
277 \else
278 \@tempcnta #1\relax\multiply\@tempcnta \sixt@@n
279 \advance\@tempcnta -9 \@tempcntb #2\relax\multiply\@tempcntb \tw@
280 \ifnum \@tempcntb >\z@ \advance\@tempcnta \@tempcntb
281 \else\advance\@tempcnta -\@tempcntb\advance\@tempcnta 64
282 \fi\fi\char\@tempcnta}

(End of definition for \@getlarrow.)

\@getrarrow
283 \def\@getrarrow(#1,#2){\@tempcntb #2\relax
284 \ifnum\@tempcntb <\z@ \@tempcntb -\@tempcntb\relax\fi
285 \ifcase \@tempcntb\relax \@tempcnta 45 % '55
286 \or
287 \ifnum #1<\thr@@ \@tempcnta #1\relax\multiply\@tempcnta
288 24\advance\@tempcnta -6 \else \ifnum #1=\thr@@ \@tempcnta 49
289 \else\@tempcnta 58 \fi\fi\or
290 \ifnum #1<\thr@@ \@tempcnta=#1\relax\multiply\@tempcnta
291 24\advance\@tempcnta -\thr@@ \else \@tempcnta 51 \fi\or
292 \@tempcnta #1\relax\multiply\@tempcnta
293 \sixt@@n \advance\@tempcnta -\tw@ \else
294 \@tempcnta #1\relax\multiply\@tempcnta
295 \sixt@@n \advance\@tempcnta 7 \fi\ifnum #2<\z@ \advance\@tempcnta 64 \fi
296 \char\@tempcnta}

(End of definition for \@getrarrow.)

\@vline
297 \def\@vline{\ifnum \@yarg <\z@ \@downline \else \@upline\fi}

```

(End of definition for \vline.)

\@upline

```
298 \def\@upline{%
299   \hb@xt@z@{\hskip -\@halfwidth \vrule \@width \@wholewidth
300   \@height \@linelen \@depth z@\hss}}
```

(End of definition for \@upline.)

\@downline

```
301 \def\@downline{%
302   \hb@xt@z@{\hskip -\@halfwidth \vrule \@width \@wholewidth
303   \@height z@ \@depth \@linelen \hss}}
```

(End of definition for \@downline.)

\@upvector

```
304 \def\@upvector{\@upline\setbox\@tempboxa\hbox{\@linefnt\char 54}% '66
305   \raise \@linelen \hb@xt@z@{\lower \ht\@tempboxa\box\@tempboxa\hss}}
```

(End of definition for \@upvector.)

\@downvector

```
306 \def\@downvector{\@downline\lower \@linelen
307   \hb@xt@z@{\@linefnt\char 63 % '77
308   \hss}}
```

(End of definition for \@downvector.)

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\dashbox{D}(X,Y) ==
BEGIN
leave vertical mode
\hb@xt@ Opt {
  \baselineskip := Opt
  \lineskip      := Opt
%% HORIZONTAL DASHES
  \@dashdim := X * \unitlength
  \@dashcnt := \@dashdim + 200 % to prevent roundoff error
  \@dashdim := D * \unitlength
  \@dashcnt := \@dashcnt / \@dashdim
  if \@dashcnt is odd
  then \@dashdim := Opt
      \@dashcnt := (\@dashcnt + 1) / 2
  else \@dashdim := \@dashdim / 2
      \@dashcnt := \@dashcnt / 2 - 1
      \box\@dashbox := \hbox{\vrule height \@halfwidth
                             depth \@halfwidth width \@dashdim}
      \put(0,0){\copy\@dashbox}
      \put(0,Y){\copy\@dashbox}
      \put(X,0){\hskip -\@dashdim\copy\@dashbox}
      \put(X,Y){\hskip -\@dashdim\box\@dashbox}
      \@dashdim := 3 * \@dashdim
fi
```

```

\box\@dashbox := \hbox{\vrule height \@halfwidth
                        depth \@halfwidth width D * \unitlength
                        \hskip D * \unitlength}

\@tempcnta := 0
\put(0,0){\hskip \@dashdim
          while \@tempcnta < \@dashcnt
            do \copy\@dashbox
              \@tempcnta := \@tempcnta + 1
            od
          }
\@tempcnta := 0
\put(0,Y){\hskip \@dashdim
          while \@tempcnta < \@dashcnt
            do \copy\@dashbox
              \@tempcnta := \@tempcnta + 1
            od
          }

%% vertical dashes
\@dashdim := Y * \unitlength
\@dashcnt := \@dashdim + 200 % to prevent roundoff error
\@dashdim := D * \unitlength
\@dashcnt := \@dashcnt / \@dashdim
if \@dashcnt is odd
then \@dashdim := 0pt
    \@dashcnt := (\@dashcnt + 1) / 2
else \@dashdim := \@dashdim / 2
    \@dashcnt := \@dashcnt / 2 - 1
    \box\@dashbox := \hbox{\hskip -\@halfwidth
                          \vrule width \@wholewidth
                          height \@dashdim }

    \put(0,0){\copy\@dashbox}
    \put(X,0){\copy\@dashbox}
    \put(0,Y){\lower\@dashdim\copy\@dashbox}
    \put(X,Y){\lower\@dashdim\copy\@dashbox}
    \@dashdim := 3 * \@dashdim
fi
\box\@dashbox := \hbox{\vrule width \@wholewidth
                        height D * \unitlength      }

\@tempcnta := 0
\put(0,0){\hskip -\halfwidth
          \vbox{while \@tempcnta < \@dashcnt
                do \vskip D*\unitlength
                  \copy\@dashbox
                  \@tempcnta := \@tempcnta + 1
                od
                \vskip \@dashdim
              } }
\@tempcnta := 0
\put(X,0){\hskip -\halfwidth

```

```

\ vbox{while \@tempcnta < \@dashcnt
do \vskip D*\unitlength
\copy\@dashbox
\@tempcnta := \@tempcnta + 1
od
\vskip \@dashdim
}
}
% END DASHES

```

\@makepicbox(X,Y)

END

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

\dashbox

```

309 \</2kernel>
310 \<*2kernel | latexrelease>
311 \<latexrelease>\IncludeInRelease{2020/10/01}%
312 \<latexrelease>{\dashbox}{default units}%
313 \<latexrelease>\expandafter\let\csname dashbox \endcsname\undefind
314 \def\dashbox#1(#2,#3){\leavevmode\hb@xt@\z@{\baselineskip \z@skip
315 \lineskip \z@skip
316 \@defaultunitsset\@dashdim{#2}\unitlength
317 \@dashcnt \@dashdim \advance\@dashcnt 200
318 \@defaultunitsset\@dashdim{#1}\unitlength
319 \divide\@dashcnt \@dashdim
320 \ifodd\@dashcnt\@dashdim \z@
321 \advance\@dashcnt \@one \divide\@dashcnt \tw@
322 \else \divide\@dashdim \tw@ \divide\@dashcnt \tw@
323 \advance\@dashcnt \m@ne
324 \setbox\@dashbox \hbox{\vrule \@height \@halfwidth \@depth \@halfwidth
325 \@width \@dashdim}\put(0,0){\copy\@dashbox}%
326 \put(0,#3){\copy\@dashbox}%
327 \put(#2,0){\hskip-\@dashdim\copy\@dashbox}%
328 \put(#2,#3){\hskip-\@dashdim\box\@dashbox}%
329 \multiply\@dashdim \thr@@
330 \fi
331 \setbox\@dashbox \hbox{%
332 \@defaultunitsset\@tempdimc{#1}\unitlength
333 \vrule \@height \@halfwidth \@depth \@halfwidth \@width \@tempdimc
334 \hskip\@tempdimc}%
335 \@tempcnta\z@
336 \put(0,0){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
337 \do{\copy\@dashbox\advance\@tempcnta \@one }}\@tempcnta\z@
338 \put(0,#3){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
339 \do{\copy\@dashbox\advance\@tempcnta \@one }}%
340 \@defaultunitsset\@dashdim{#3}\unitlength
341 \@dashcnt \@dashdim \advance\@dashcnt 200
342 \@defaultunitsset\@dashdim{#1}\unitlength
343 \divide\@dashcnt \@dashdim
344 \ifodd\@dashcnt \@dashdim \z@
345 \advance\@dashcnt \@one \divide\@dashcnt \tw@
346 \else

```

```

347 \divide\@dashdim \tw@ \divide\@dashcnt \tw@
348 \advance\@dashcnt \m@ne
349 \setbox\@dashbox\hbox{\hskip -\@halfwidth
350 \vrule \@width \@wholewidth
351 \@height \@dashdim}\put(0,0){\copy\@dashbox}%
352 \put(#2,0){\copy\@dashbox}%
353 \put(0,#3){\lower\@dashdim\copy\@dashbox}%
354 \put(#2,#3){\lower\@dashdim\copy\@dashbox}%
355 \multiply\@dashdim \thr@@
356 \fi
357 \@defaultunitsset\@tempdimb{#1}\unitlength
358 \setbox\@dashbox\hbox{%
359 \vrule \@width \@wholewidth \@height\@tempdimb}%
360 \@tempcnta\z@
361 \put(0,0){\hskip -\@halfwidth \vbox{\@whilenum \@tempcnta <\@dashcnt
362 \do{\vskip\@tempdimb\copy\@dashbox\advance\@tempcnta \@ne }%
363 \vskip\@dashdim}}\@tempcnta\z@
364 \put(#2,0){\hskip -\@halfwidth \vbox{\@whilenum \@tempcnta<\@dashcnt
365 \do{\vskip\@tempdimb\copy\@dashbox\advance\@tempcnta \@ne }%
366 \vskip\@dashdim}}\@makepicbox(#2,#3)}
367 /2ekernel | latexrelease)

368 \latexrelease\EndIncludeInRelease
369 \latexrelease\IncludeInRelease{0000/00/00}%
370 \latexrelease \dashbox{default units}%
371 \latexrelease\expandafter\let\csname dashbox \endcsname\@undefined
372 \latexrelease\def\dashbox#1(#2,#3){%
373 \latexrelease\leavevmode\hbxt@z@{\baselineskip \z@skip
374 \latexrelease\lineskip \z@skip
375 \latexrelease\@dashdim #2\unitlength
376 \latexrelease\@dashcnt \dashdim \advance\@dashcnt 200
377 \latexrelease\@dashdim #1\unitlength\divide\@dashcnt \dashdim
378 \latexrelease\ifodd\@dashcnt\@dashdim \z@
379 \latexrelease\advance\@dashcnt \@ne \divide\@dashcnt \tw@
380 \latexrelease\else \divide\@dashdim \tw@ \divide\@dashcnt \tw@
381 \latexrelease\advance\@dashcnt \m@ne
382 \latexrelease\setbox\@dashbox \hbox{%
383 \latexrelease \vrule \@height \@halfwidth \@depth \@halfwidth
384 \latexrelease \@width \dashdim}\put(0,0){\copy\@dashbox}%
385 \latexrelease\put(0,#3){\copy\@dashbox}%
386 \latexrelease\put(#2,0){\hskip-\dashdim\copy\@dashbox}%
387 \latexrelease\put(#2,#3){\hskip-\dashdim\box\@dashbox}%
388 \latexrelease\multiply\@dashdim \thr@@
389 \latexrelease\fi
390 \latexrelease\setbox\@dashbox \hbox{%
391 \latexrelease \vrule \@height \@halfwidth \@depth \@halfwidth
392 \latexrelease \@width #1\unitlength\hskip #1\unitlength}\@tempcnta\z@
393 \latexrelease\put(0,0){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
394 \latexrelease\do{\copy\@dashbox\advance\@tempcnta \@ne }}\@tempcnta\z@
395 \latexrelease\put(0,#3){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
396 \latexrelease\do{\copy\@dashbox\advance\@tempcnta \@ne }}%
397 \latexrelease\@dashdim #3\unitlength
398 \latexrelease\@dashcnt \dashdim \advance\@dashcnt 200
399 \latexrelease\@dashdim #1\unitlength\divide\@dashcnt \dashdim
400 \latexrelease\ifodd\@dashcnt \dashdim \z@

```

```

401 <latexrelease>\advance\@dashcnt \@ne \divide\@dashcnt \tw@
402 <latexrelease>\else
403 <latexrelease>\divide\@dashdim \tw@ \divide\@dashcnt \tw@
404 <latexrelease>\advance\@dashcnt \m@ne
405 <latexrelease>\setbox\@dashbox\hbox{\hskip -\@halfwidth
406 <latexrelease>\vrule \@width \@wholewidth
407 <latexrelease>\@height \@dashdim}\put(0,0){\copy\@dashbox}%
408 <latexrelease>\put(#2,0){\copy\@dashbox}%
409 <latexrelease>\put(0,#3){\lower\@dashdim\copy\@dashbox}%
410 <latexrelease>\put(#2,#3){\lower\@dashdim\copy\@dashbox}%
411 <latexrelease>\multiply\@dashdim \thr@@
412 <latexrelease>\fi
413 <latexrelease>\setbox\@dashbox\hbox{\vrule \@width \@wholewidth
414 <latexrelease>\@height #1\unitlength}\@tempcnta\z@
415 <latexrelease>\put(0,0){%
416 <latexrelease> \hskip -\@halfwidth \vbox{\@whilenum \@tempcnta <\@dashcnt
417 <latexrelease> \do{\vskip #1\unitlength\copy\@dashbox
418 <latexrelease> \advance\@tempcnta\@ne }%
419 <latexrelease> \vskip\@dashdim}}\@tempcnta\z@
420 <latexrelease>\put(#2,0){%
421 <latexrelease> \hskip -\@halfwidth \vbox{\@whilenum \@tempcnta<\@dashcnt
422 <latexrelease> \do{\vskip #1\unitlength\copy\@dashbox
423 <latexrelease> \advance\@tempcnta \@ne }%
424 <latexrelease> \vskip\@dashdim}}\@makepicbox(#2,#3)}
425 <latexrelease>\EndIncludeInRelease
426 <*2kernel)

```

(End of definition for \dashbox.)

Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):

CIRCLES AND OVALS

USER COMMANDS:

`\circle{D}` : Produces the circle with the diameter as close as possible to  $D * \text{\unitlength}$ . `\put(X,Y){\circle{D}}` puts the circle with its center at (X,Y).

`\oval(X,Y)` : Makes an oval as round as possible that fits in the rectangle of width  $X * \text{\unitlength}$  and height  $Y * \text{\unitlength}$ . The reference point is the center.

`\oval(X,Y)[POS]` : Same as `\oval(X,Y)` except it draws only the half or quadrant of the oval indicated by POS. E.G., `\oval(X,Y)[t]` draws just the top half and `\oval(X,Y)[br]` draws just the bottom right quadrant. In all cases, the reference point is the same as the unqualified `\oval(X,Y)` command.

`\@ovvert {DELTA1} {DELTA2}` : Makes a vbox containing either the left side or the right side of the oval being constructed. The baseline will coincide with the outside bottom edge of the oval; the left side of the box will coincide with the left edge of the vertical

rule. The width of the box will be `\@tempdima`.  
`DELTA1` and `DELTA2` are added to the character number in `\@tempcnta`  
to get the characters for the top and bottom quarter circle pieces.

`\@ovhorz` : Makes an hbox containing the straight rule for either the  
top or the bottom of the oval being constructed. The baseline  
will coincide with bottom edge of the rule; the left side of  
the box will coincide with the left side of the oval.  
The width of the box will be `\@ovxx`.

`\@getcirc {DIAM}` : Sets `\@tempcnta` to the character number  
of the top-right quarter circle with the largest  
diameter less than or equal to `DIAM`.  
Sets `\@tempboxa` to an hbox containing that character.  
Sets `\@tempdima` to `\wd \@tempboxa`, which is the distance  
from the circle's left outside edge to its right  
inside edge.  
(These characters are like those described in the  
TeXbook, pp. 389-90.)

```
\@getcirc {DIAM} ==
BEGIN
  \@tempcnta      := integer coercion of (DIAM + 2pt)
                                     + 2pt added 1 Nov 88
  \@tempcnta      := \@tempcnta / integer coercion of 4pt
  if \@tempcnta > 10
    then \@tempcnta := 10 fi
  if \@tempcnta > 0
    then \@tempcnta := \@tempcnta-1
    else LaTeX Warning: Oval too small.
  fi
  \@tempcnta      := 4 * \@tempcnta
  \@tempboxa      := \hbox{\@circlefont \char \@tempcnta}
  \@tempdima      := \wd \@tempboxa
END
```

```
\@put{X}{Y}{OBJ} ==
BEGIN
  \raise Y \hb@xt@ 0pt{\hskip X OBJ \hss}
END
```

```
\@oval(X,Y)[POS] ==
BEGIN
  \beginngroup
  \boxmaxdepth := \maxdimen
  @ovt := @ovb := @ovl := @ovr := true
  for all E in POS
    do @ovE := false od
  \@ovxx      := X * \unitlength
  \@ovyy      := Y * \unitlength
```

```

\@tempdimb := min(\@ovxx,\@ovyy)
\@getcirc{\@tempdimb-2pt} %% "-2pt" added 7 Dec 89
\@ovro      := \ht \@tempboxa
\@ovri      := \dp \@tempboxa
\@ovdx      := \@ovxx - \@tempdima
\@ovdx      := \@ovdx/2
\@ovdy      := \@ovyy - \@tempdima
\@ovdy      := \@ovdy/2
\@circlefnt
\@tempboxa :=
  \hbox{
    if @ovr
      then \@ovvert{3}{2} \kern -\@tempdima
    fi
    if @ovl
      then \kern \@ovxx \@ovvert{0}{1} \kern -\@tempdima
        \kern -\@ovxx
      fi
    if @ovt
      then \@ovhorz \kern -\@ovxx
    fi
    if @ovb
      then \raise \@ovyy \@ovhorz
    fi
  }
\@ovdx := \@ovdx + \@ovro
\@ovdy := \@ovdy + \@ovro
\ht\@tempboxa := \dp\@tempboxa := 0
\@put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}
\endgroup
END

\@ovvert {DELTA1} {DELTA2} ==
BEGIN
  \vbox to \@ovyy {
    if @ovb
      then \@tempcntb := \@tempcnta + DELTA1
        \kern -\@ovro
        \hbox { \char \@tempcntb }
        \nointerlineskip
      else \kern \@ovri \kern \@ovdy
    fi
    \leaders \vrule width \@wholewidth \vfil
    \nointerlineskip
    if @ovt
      then \@tempcntb := \@tempcnta + DELTA2
        \hbox { \char \@tempcntb }
      else \kern \@ovdy \kern \@ovro
    fi
  }

```

```

END

\@ovhorz ==
BEGIN
  \hb@xt@ \ovxxx{
    \kern \ovro
    if @ovr
      then
        else \kern \ovdx
      fi
    \leaders \hrule height \@wholewidth \hfil
    if @ovl
      then
        else \kern \ovdx
      fi
    \kern \ovri
  }
END

\circle{DIAM} ==
BEGIN
  \begingroup
  \boxmaxdepth := maxdimen
  \@tempdimb := DIAM *\unitlength
  if \@tempdimb > 15.5pt
    then \@getcirc{\@tempdimb}
      \@ovro := \ht \@tempboxa
      \@tempboxa := \hbox{
        \@circlefnt
        \@tempcnta := \@tempcnta + 2
        \char \@tempcnta
        \@tempcnta := \@tempcnta - 1
        \char \@tempcnta
        \kern -2\@tempdima
        \@tempcnta := \@tempcnta + 2
        \raise \@tempdima \hbox { \char \@tempcnta }
        \raise \@tempdima \box\@tempboxa
      }
      \ht\@tempboxa := \dp\@tempboxa := 0
      \@put{-\@ovro}{-\@ovro}{\@tempboxa}
    else
      \@circ{\@tempdimb}{96}
    fi
  \endgroup
END

\circle*{DIAM} == \dot{DIAM} == \@circ{DIAM*\unitlength}{112}

\@circ{DIAM}{CHAR} ==
BEGIN

```

```

\@tempcnta := integer coercion of (DIAM + .5pt)/1pt.
if \@tempcnta > 15 then \@tempcnta := 15 fi
if \@tempcnta > 1 then \@tempcnta := \@tempcnta - 1 fi
\@tempcnta := \@tempcnta + CHAR
\@circlefnt
\char \@tempcnta
END
End of historical LATEX 2.09 comments.

\if@ovt If producing the Top Bottom Left or Right of an oval.
\if@ovb 427 \newif\if@ovt
\if@ovl 428 \newif\if@ovb
\if@ovr 429 \newif\if@ovl
430 \newif\if@ovr

(End of definition for \if@ovt and others.)

\@ovxx
\@ovyy 431 \newdimen\@ovxx
\@ovdx 432 \newdimen\@ovyy
\@ovdy 433 \newdimen\@ovdx
\@ovro 434 \newdimen\@ovdy
\@ovri 435 \newdimen\@ovro
436 \newdimen\@ovri

(End of definition for \@ovxx and others.)

\advance\@tempdima 2pt\relax added 1 Nov 88 to fix bug in which size of drawn
circle not monotonic function of argument of \circle, caused by different rounding for
dimensions of large and small circles.

\@getcirc
437 \def\@getcirc#1{\@tempdima #1\relax \advance\@tempdima 2\p@
438 \@tempcnta\@tempdima
439 \@tempdima 4\p@ \divide\@tempcnta\@tempdima
440 \ifnum \@tempcnta >10\relax
441 \@picture@warn
442 \@tempcnta 10\relax
443 \fi
444 \ifnum \@tempcnta >\z@ \advance\@tempcnta\m@ne
Warn if requirements for oval or circle can't be met.
445 \else \@picture@warn \fi
446 \multiply\@tempcnta 4\relax
447 \setbox \@tempboxa \hbox{\@circlefnt
448 \char \@tempcnta}\@tempdima \wd \@tempboxa}

(End of definition for \@getcirc.)

\@picture@warn Generic warning for lines, vectors (used in \@sline) and oval or circle (used in \@getcirc)
are not available at right size.
449 \def\@picture@warn{\@latex@warning{%
450 \string\oval, \string\circle, or \string\line\space
451 size unavailable}}

```

```

(End of definition for \@picture@warn.)

\@put
452 \def\@put#1#2#3{\raise #2\hb@xt@{z@{\hskip #1#3\hss}}
(End of definition for \@put.)

\oval
453 \def\oval(#1,#2){\@ifnextchar[{\@oval(#1,#2)}{\@oval(#1,#2) []}}
(End of definition for \oval.)

454 \</2ekernel>
455 \<latexrelease>\IncludeInRelease{2016/03/31}%
456 \<latexrelease>{\@ovhlinetrue}%
457 \<latexrelease>{Avoid almost zero length leaders}%
458 \<*2ekernel | latexrelease>

\if@ovvline Tests whether horizontal or vertical lines are needed.
\if@ovhline
459 \newif\if@ovvline \@ovvlinetrue
460 \newif\if@ovhline \@ovhlinetrue
461 \</2ekernel | latexrelease>
462 \<latexrelease>\EndIncludeInRelease
463 \<latexrelease>\IncludeInRelease{0000/00/00}%
464 \<latexrelease>{\@ovhlinetrue}%
465 \<latexrelease>{Avoid almost zero length leaders}%
466 \<latexrelease>\let\if@ovvline\@undefined
467 \<latexrelease>\let\if@ovhline\@undefined
468 \<latexrelease>\EndIncludeInRelease
469 \<*2ekernel>

(End of definition for \if@ovvline and \if@ovhline.)

\@oval
470 \</2ekernel>
471 \<*2ekernel | latexrelease>
472 \<latexrelease>\IncludeInRelease{2020/10/01}%
473 \<latexrelease>{\@oval}{default units}%
474 \def\@oval(#1,#2)[#3]{\begingroup\boxmaxdepth \maxdimen
475 \@ovttrue \@ovbtrue \@ovltrue \@ovrtrue

476 \@ovvlinefalse \@ovhlinefalse

477 \@tfor\reserved@a :=#3\do{%
478 \csname @ov\reserved@a false\endcsname}%
479 \@defaultunitsset\@ovxx{#1}\unitlength
480 \@defaultunitsset\@ovyy{#2}\unitlength

481 \@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx \@ovxx \@ovvlinetrue
482 \else \@ovyy \ifdim \@ovyy =\@ovxx \else \@ovhlinetrue \fi\fi

483 \advance \@tempdimb -2\p@
484 \@getcirc \@tempdimb
485 \@ovro \ht\@tempboxa \@ovri \dp\@tempboxa
486 \@ovdx\@ovxx \advance\@ovdx -\@tempdima \divide\@ovdx \tw@
487 \@ovdy\@ovyy \advance\@ovdy -\@tempdima \divide\@ovdy \tw@

```

```

488 \ifdim \@ovdx >\z@ \ovhlinetrue \fi
489 \ifdim \@ovdy >\z@ \ovvlinetrue \fi

490 \circlefnt \setbox\@tempboxa
491 \hbox{\if@ovr \ovvert32\kern -\@tempdima \fi
492 \if@ovl \kern \@ovxx \ovvert01\kern -\@tempdima \kern -\@ovxx \fi
493 \if@ovt \ovhorz \kern -\@ovxx \fi
494 \if@ovb \raise \@ovyy \ovhorz \fi}\advance\@ovdx\@ovro
495 \advance\@ovdy\@ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
496 \put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}%
497 \endgroup}
498 </2ekernel | latexrelease>

499 <latexrelease>\EndIncludeInRelease
500 <latexrelease>\IncludeInRelease{2016/03/31}%
501 <latexrelease> \{\@oval\}{default units}%
502 <latexrelease>\def\@oval(#1,#2)[#3]{\begingroup\boxmaxdepth \maxdimen
503 <latexrelease> \@ovttrue \@ovbtrue \@ovltrue \@ovrtrue
504 <latexrelease> \@ovvlinefalse \ovhlinefalse
505 <latexrelease> \tfor\reserved@a :=#3\do{%
506 <latexrelease> \csname @ov\reserved@a false\endcsname}%
507 <latexrelease> \@ovxx #1\unitlength
508 <latexrelease> \@ovyy #2\unitlength
509 <latexrelease> \@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx \@ovvlinetrue
510 <latexrelease> \else \@ovyy \ifdim \@ovyy =\@ovxx \else \ovhlinetrue
511 <latexrelease> \fi\fi
512 <latexrelease> \advance \@tempdimb -2\p@
513 <latexrelease> \getcirc \@tempdimb
514 <latexrelease> \@ovro \ht\@tempboxa \@ovri \dp\@tempboxa
515 <latexrelease> \@ovdx\@ovxx \advance\@ovdx -\@tempdima \divide\@ovdx \tw@
516 <latexrelease> \@ovdy\@ovyy \advance\@ovdy -\@tempdima \divide\@ovdy \tw@
517 <latexrelease> \ifdim \@ovdx >\z@ \ovhlinetrue \fi
518 <latexrelease> \ifdim \@ovdy >\z@ \ovvlinetrue \fi
519 <latexrelease> \circlefnt \setbox\@tempboxa
520 <latexrelease> \hbox{\if@ovr \ovvert32\kern -\@tempdima \fi
521 <latexrelease> \if@ovl
522 <latexrelease> \kern \@ovxx \ovvert01\kern -\@tempdima \kern -\@ovxx
523 <latexrelease> \fi
524 <latexrelease> \if@ovt \ovhorz \kern -\@ovxx \fi
525 <latexrelease> \if@ovb \raise \@ovyy \ovhorz \fi}\advance\@ovdx\@ovro
526 <latexrelease> \advance\@ovdy\@ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
527 <latexrelease> \put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}%
528 <latexrelease> \endgroup}
529 <latexrelease>\EndIncludeInRelease

530 <latexrelease>\IncludeInRelease{0000/00/00}%
531 <latexrelease> \{\@oval\}{default units}%
532 <latexrelease>\def\@oval(#1,#2)[#3]{\begingroup\boxmaxdepth \maxdimen
533 <latexrelease> \@ovttrue \@ovbtrue \@ovltrue \@ovrtrue
534 <latexrelease> \tfor\reserved@a :=#3\do
535 <latexrelease> {\csname @ov\reserved@a false\endcsname}%
536 <latexrelease> \@ovxx #1\unitlength
537 <latexrelease> \@ovyy #2\unitlength
538 <latexrelease> \@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx\else \@ovyy \fi
539 <latexrelease> \advance \@tempdimb -2\p@
540 <latexrelease> \getcirc \@tempdimb

```

```

541 <latexrelease> \ovro \ht\@tempboxa \ovri \dp\@tempboxa
542 <latexrelease> \ovdx\ovxx \advance\ovdx -\@tempdima \divide\ovdx \tw@
543 <latexrelease> \ovdy\ovyy \advance\ovdy -\@tempdima \divide\ovdy \tw@
544 <latexrelease> \circlefnt \setbox\@tempboxa
545 <latexrelease> \hbox{\if@ovr \ovvert32\kern -\@tempdima \fi
546 <latexrelease> \if@ovl
547 <latexrelease> \kern \ovxx \ovvert01\kern -\@tempdima \kern -\ovxx
548 <latexrelease> \fi
549 <latexrelease> \if@ovt \ovhorz \kern -\ovxx \fi
550 <latexrelease> \if@ovb \raise \ovyy \ovhorz \fi\advance\ovdx\ovro
551 <latexrelease> \advance\ovdy\ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
552 <latexrelease> \put{-\ovdx}{-\ovdy}{\box\@tempboxa}%
553 <latexrelease> \endgroup}
554 <latexrelease>\EndIncludeInRelease
555 (*2ekernel)

```

(End of definition for \oval.)

\@ovvert

```

556 </2ekernel>
557 <latexrelease>\IncludeInRelease{2016/03/31}%
558 <latexrelease> \ovvert{Avoid almost zero length leaders}%
559 (*2ekernel|latexrelease)
560 \def\@ovvert#1#2{\vbox to\ovyy{%
561 \if@ovb \@tempcntb \@tempcnta \advance \@tempcntb #1\relax
562 \kern -\ovro \hbox{\char \@tempcntb}\nointerlineskip
563 \else \kern \ovri \kern \ovdy \fi
564 \if@ovvline \leaders\vrule \@width \@wholewidth \fi
565 \vfil \nointerlineskip
566 \if@ovt \@tempcntb \@tempcnta \advance \@tempcntb #2\relax
567 \hbox{\char \@tempcntb}%
568 \else \kern \ovdy \kern \ovro \fi}}
569 </2ekernel|latexrelease>
570 <latexrelease>\EndIncludeInRelease
571 <latexrelease>\IncludeInRelease{0000/00/00}%
572 <latexrelease> \ovvert{Avoid almost zero length leaders}%
573 <latexrelease>\def\@ovvert#1#2{\vbox to\ovyy{%
574 <latexrelease> \if@ovb \@tempcntb \@tempcnta \advance \@tempcntb #1\relax
575 <latexrelease> \kern -\ovro \hbox{\char \@tempcntb}\nointerlineskip
576 <latexrelease> \else \kern \ovri \kern \ovdy \fi
577 <latexrelease> \leaders\vrule \@width \@wholewidth\vfil \nointerlineskip
578 <latexrelease> \if@ovt \@tempcntb \@tempcnta \advance \@tempcntb #2\relax
579 <latexrelease> \hbox{\char \@tempcntb}%
580 <latexrelease> \else \kern \ovdy \kern \ovro \fi}}
581 <latexrelease>\EndIncludeInRelease
582 (*2ekernel)

```

(End of definition for \@ovvert.)

\@ovhorz

```

583 </2ekernel>
584 <latexrelease>\IncludeInRelease{2016/03/31}%
585 <latexrelease> \ovhorz{Avoid almost zero length leaders}%

```

```

586 <*2ekernel | latexrelease>
587 \def\@ovhorz{\hb@xt@\@ovxx{\kern \@ovro
588   \if@ovr \else \kern \@ovdx \fi

589   \if@ovhline \leaders \hrule \@height \@wholewidth \fi

590   \hfil
591   \if@ovl \else \kern \@ovdx \fi
592   \kern \@ovri}}
593 </2ekernel | latexrelease>

594 <latexrelease>\EndIncludeInRelease
595 <latexrelease>\IncludeInRelease{0000/00/00}%
596 <latexrelease>          {\@ovhorz}{Avoid almost zero length leaders}%
597 <latexrelease>\def\@ovhorz{\hb@xt@\@ovxx{\kern \@ovro
598 <latexrelease>   \if@ovr \else \kern \@ovdx \fi
599 <latexrelease>   \leaders \hrule \@height \@wholewidth \hfil
600 <latexrelease>   \if@ovl \else \kern \@ovdx \fi
601 <latexrelease>   \kern \@ovri}}
602 <latexrelease>\EndIncludeInRelease
603 <*2ekernel>

```

(End of definition for \@ovhorz.)

\circle

```

604 \def\circle{\@inmatherr\circle\@ifstar\@dot\@circle}

```

(End of definition for \circle.)

\@circle

```

605 </2ekernel>
606 <*2ekernel | latexrelease>
607 <latexrelease>\IncludeInRelease{2020/10/01}%
608 <latexrelease>          {\@circle}{default units}%
609 \def\@circle#1{%
610   \begingroup \boxmaxdepth \maxdimen
611   \@defaultunitsset\@tempdimb{#1}\unitlength
612   \ifdim \@tempdimb >15.5\p@ \getcirc\@tempdimb
613     \@ovro\ht\@tempboxa
614     \setbox\@tempboxa\hbox{\@circlefnt
615       \advance\@tempcnta\tw@ \char \@tempcnta
616       \advance\@tempcnta\m@ne \char \@tempcnta \kern -2\@tempdima
617       \advance\@tempcnta\tw@
618       \raise \@tempdima \hbox{\char\@tempcnta}\raise \@tempdima
619       \box\@tempboxa}\ht\@tempboxa\z@ \dp\@tempboxa\z@
620       \@put{-\@ovro}{-\@ovro}{\box\@tempboxa}%
621     \else \@circ\@tempdimb{96}\fi\endgroup}
622 </2ekernel | latexrelease>

623 <latexrelease>\EndIncludeInRelease
624 <latexrelease>\IncludeInRelease{0000/00/00}%
625 <latexrelease>          {\@circle}{default units}%
626 <latexrelease>\def\@circle#1{%
627 <latexrelease>   \begingroup \boxmaxdepth \maxdimen \@tempdimb #1\unitlength
628 <latexrelease>   \ifdim \@tempdimb >15.5\p@ \getcirc\@tempdimb
629 <latexrelease>   \ovro\ht\@tempboxa

```

```

630 <latexrelease> \setbox\@tempboxa\hbox{\@circlefnt
631 <latexrelease> \advance\@tempcnta\tw@ \char \@tempcnta
632 <latexrelease> \advance\@tempcnta\m@ne \char \@tempcnta
633 <latexrelease> \kern -2\@tempdima
634 <latexrelease> \advance\@tempcnta\tw@
635 <latexrelease> \raise \@tempdima \hbox{\char\@tempcnta}%
636 <latexrelease> \raise \@tempdima
637 <latexrelease> \box\@tempboxa\ht\@tempboxa\z@ \dp\@tempboxa\z@
638 <latexrelease> \put{-\@ovro}{-\@ovro}{\box\@tempboxa}%
639 <latexrelease> \else \@circ\@tempdimb{96}\fi\endgroup}
640 <latexrelease>\EndIncludeInRelease
641 <*2ekernel>

```

(End of definition for \@circle.)

\@dot Internal form of \circle\*.

```

642 </2ekernel>
643 <*2ekernel | latexrelease>
644 <latexrelease>\IncludeInRelease{2020/10/01}%
645 <latexrelease> {\@dot}{default units}%
646 \def\@dot#1{%
647 \@defaultunitsset\@tempdimb{#1}\unitlength
648 \@circ\@tempdimb{112}}
649 </2ekernel | latexrelease>
650 <latexrelease>\EndIncludeInRelease
651 <latexrelease>\IncludeInRelease{0000/00/00}%
652 <latexrelease> {\@dot}{default units}%
653 <latexrelease>\def\@dot#1{\@tempdimb #1\unitlength \@circ\@tempdimb{112}}
654 <latexrelease>\EndIncludeInRelease
655 <*2ekernel>

```

(End of definition for \@dot.)

\@circ

```

656 \def\@circ#1#2{\@tempdima #1\relax \advance\@tempdima .5\p@
657 \@tempcnta\@tempdima \@tempdima \p@
658 \divide\@tempcnta\@tempdima
659 \ifnum\@tempcnta >15\relax \@tempcnta 15\relax \fi
660 \ifnum \@tempcnta >\z@ \advance\@tempcnta\m@ne\fi
661 \advance\@tempcnta #2\relax
662 \@circlefnt \char\@tempcnta}

```

(End of definition for \@circ.)

\@xarg Counters used for manipulating the ‘slope’ arguments.

```

\@yarg \newcount\@xarg
\@yyarg \newcount\@yarg
\newcount\@yyarg

```

(End of definition for \@xarg, \@yarg, and \@yyarg.)

\@multicnt Counter used in \multitup, and also \multicolumn.

```

666 \newcount\@multicnt

```

(End of definition for \@multicnt.)

```

\@xdim Length registers.
\@ydim 667 \newdimen\@xdim
        668 \newdimen\@ydim

(End of definition for \@xdim and \@ydim.)

\@linechar Box for holding a line segment character, for sloping lines.
        669 \newbox\@linechar

(End of definition for \@linechar.)

\@linelen Length of the line currently being built.
        670 \newdimen\@linelen

(End of definition for \@linelen.)

\@clnwd Height and width of current line segment.
\@clnht 671 \newdimen\@clnwd
        672 \newdimen\@clnht

(End of definition for \@clnwd and \@clnht.)

\@dashdim \dashbox internal registers.
\@dashbox 673 \newdimen\@dashdim
\@dashcnt 674 \newbox\@dashbox
        675 \newcount\@dashcnt

(End of definition for \@dashdim, \@dashbox, and \@dashcnt.)
Initialization: “\thinlines”
676 \let\@linefnt\tenln
677 \let\@circlefnt\tencirc
678 \@wholewidth\fontdimen8\tenln
679 \@halfwidth .5\@wholewidth

```

## 1.1 Curves

The new `\qbezier` command, based on the old `\bezier` defined in `bezier.sty`.  
*Historical  $\text{\LaTeX}$  2.09 comments (not necessarily accurate any more):*

```

\qbezier[N] == \bezier{N}

\bezier{N}(AX,AY)(BX,BY)(CX,CY) ==
BEGIN
  IF N = 0
  THEN \@xdima := |BX - AX|
      \@xb := |CX - BX|
      \@xa := Max(\@xa, \@xb)
      \@ya := |BY - AY|
      \@yb := |CY - BY|
      \@ya := Max(\@ya, \@yb)
      @sc := Max(\@xa, \@ya)
      %% The coefficient .5 below is the degree of overlap of
      %% successive points, where 1 is no overlap and 0 is

```

```

%% complete overlap. A coefficient of C multiplies
%% the number of points plotted by 1/C.
%%
\@xa := .5 * \@halfwidth
@sc := @sc / \@halfwidth
@sc := Max(@sc, qbeziermax)
ELSE @sc := N
@scp := @sc+1
\@xb := 2 * (BX - AX) * \unitlength
\@xa := ((CX-AX)*\unitlength - \@xb)/@sc
\@yb := 2 * (BY - AY) * \unitlength
\@ya := ((CY-AY)*\unitlength - \@yb)/@sc
\@pictdot := square rule of width \@wholewidth
\count@ := 0
WHILE \count@ < @scp
DO \@xdim := ((\count@*\@xa + @xb) / @sc) * \count@
\@ydim := ((\count@*\@ya + @yb) / @sc) * \count@
plot pt with relative coords (\@xdim,\@ydim)
\count@ := \count@+1
OD

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

**\qbeziermax** The maximum number of points to plot.

```

680 \def\qbeziermax{500}

```

*(End of definition for \qbeziermax.)*

In the code below, to save registers \@a ... are not used. Instead other registers are reused.

```

\newcounter{@sc} -> \c@multicnt
\newcounter{@scp} -> \@tempcnta
\newdimen\@xa -> \@ovxx
\newdimen\@xb -> \@ovdx
\newdimen\@ya -> \@ovyy
\newdimen\@yb -> \@ovdy
\newsavebox{\@pictdot} -> \@tempboxa

```

**\qbezier** Main user-level command to plot quadratic bezier curves. #2 should be (. .

```

681 \newcommand\qbezier[2][0]{\bezier{#1}#2}

```

*(End of definition for \qbezier.)*

**\bezier** Form of \bezier compatible with 2.09 bezier.sty, but modified to ignore spaces between its arguments. #2 should be white space, and #4 should be (. .

```

682 \def\bezier#1#2(#3)#4({\@bezier#1)(#3){}

```

```

\@bezier
683 \kernel)
684 \kernel | latexrelease)
685 \latexrelease)\IncludeInRelease{2020/10/01}%
686 \latexrelease) {\@bezier}{default units}%
687 \def\@bezier#1(#2,#3)(#4,#5)(#6,#7){%
688 \ifnum #1=\z@
689 \@defaultunitsset\@ovxx{#4}\unitlength
690 \@defaultunitsset{\advance\@ovxx}{-#2}\unitlength
691 \ifdim \@ovxx<\z@ \@ovxx -\@ovxx \fi
692 \@defaultunitsset\@ovdx{#6}\unitlength
693 \@defaultunitsset{\advance\@ovdx}{-#4}\unitlength
694 \ifdim \@ovdx<\z@ \@ovdx -\@ovdx \fi
695 \ifdim \@ovxx<\@ovdx \@ovxx \@ovdx \fi
696 \@defaultunitsset\@ovyy{#5}\unitlength
697 \@defaultunitsset{\advance\@ovyy}{-#3}\unitlength
698 \ifdim \@ovyy<\z@ \@ovyy -\@ovyy \fi
699 \@defaultunitsset\@ovdy{#7}\unitlength
700 \@defaultunitsset{\advance\@ovdy}{-#5}\unitlength
701 \ifdim \@ovdy<\z@ \@ovdy -\@ovdy \fi
702 \ifdim \@ovyy<\@ovdy \@ovyy \@ovdy \fi
703 \@multicnt
704 \ifdim \@ovxx>\@ovyy \@ovxx \else \@ovyy \fi
705 \@ovxx .5\@halfwidth \divide\@multicnt\@ovxx
706 \ifnum \qbeziermax<\@multicnt
707 \@multicnt\qbeziermax\relax
708 \fi
709 \else \@multicnt#1\relax \fi
710 \@tempcnta\@multicnt \advance\@tempcnta\@one
711 \@defaultunitsset\@ovdx{#4}\unitlength
712 \@defaultunitsset{\advance\@ovdx}{-#2}\unitlength
713 \multiply\@ovdx \tw@
714 \@defaultunitsset\@ovxx{#6}\unitlength
715 \@defaultunitsset{\advance\@ovxx}{-#2}\unitlength
716 \advance\@ovxx -\@ovdx \divide\@ovxx\@multicnt
717 \@defaultunitsset\@ovdy{#5}\unitlength
718 \@defaultunitsset{\advance\@ovdy}{-#3}\unitlength
719 \multiply\@ovdy \tw@
720 \@defaultunitsset\@ovyy{#7}\unitlength
721 \@defaultunitsset{\advance\@ovyy}{-#3}\unitlength
722 \advance\@ovyy -\@ovdy \divide\@ovyy\@multicnt

723 \setbox\@tempboxa\hbox{%
724 \hskip -\@halfwidth
725 \vrule \@height\@halfwidth
726 \@depth \@halfwidth
727 \@width \@wholewidth}%
728 \put(#2,#3){%
729 \count@\z@
730 \@whilenum{\count@<\@tempcnta}\do
731 {\@xdim\count@\@ovxx
732 \advance\@xdim\@ovdx
733 \divide\@xdim\@multicnt
734 \multiply\@xdim\count@

```

```

735 \ydim\count@\ovvy
736 \advance\ydim\ovdy
737 \divide\ydim\@multicnt
738 \multiply\ydim\count@
739 \raise \ydim
740 \hb@xt@\z@{\kern\@xdim
741 \unhcopy\@tempboxa\hss}%
742 \advance\count@\@ne}}
743 (/2ekernel | latexrelease)

744 \latexrelease\EndIncludeInRelease
745 \latexrelease\IncludeInRelease{0000/00/00}%
746 \latexrelease{\@bezier}{default units}%
747 \latexrelease\def\@bezier#1(#2,#3)(#4,#5)(#6,#7){%
748 \latexrelease \ifnum #1=\z@
749 \latexrelease \ovxx #4\unitlength
750 \latexrelease \advance\ovxx -#2\unitlength
751 \latexrelease \ifdim \ovxx<\z@ \ovxx -\ovxx \fi
752 \latexrelease \ovdx #6\unitlength
753 \latexrelease \advance\ovdx -#4\unitlength
754 \latexrelease \ifdim \ovdx<\z@ \ovdx -\ovdx \fi
755 \latexrelease \ifdim \ovxx<\ovdx \ovxx \ovdx \fi
756 \latexrelease \ovvy #5\unitlength
757 \latexrelease \advance\ovvy -#3\unitlength
758 \latexrelease \ifdim \ovvy<\z@ \ovvy -\ovvy \fi
759 \latexrelease \ovdy #7\unitlength
760 \latexrelease \advance\ovdy -#5\unitlength
761 \latexrelease \ifdim \ovdy<\z@ \ovdy -\ovdy \fi
762 \latexrelease \ifdim \ovvy<\ovdy \ovvy \ovdy \fi
763 \latexrelease \@multicnt
764 \latexrelease \ifdim \ovxx>\ovvy \ovxx \else \ovvy \fi
765 \latexrelease \ovxx .5\@halfwidth \divide\@multicnt\ovxx
766 \latexrelease \ifnum
767 \latexrelease \qbeziermax<\@multicnt \@multicnt\qbeziermax\relax
768 \latexrelease \fi
769 \latexrelease \else \@multicnt#1\relax \fi
770 \latexrelease \@tempcnta\@multicnt \advance\@tempcnta\@ne
771 \latexrelease \ovdx #4\unitlength \advance\ovdx -#2\unitlength
772 \latexrelease \multiply\ovdx \tw@
773 \latexrelease \ovxx #6\unitlength \advance\ovxx -#2\unitlength
774 \latexrelease \advance\ovxx -\ovdx \divide\ovxx\@multicnt
775 \latexrelease \ovdy #5\unitlength \advance\ovdy -#3\unitlength
776 \latexrelease \multiply\ovdy \tw@
777 \latexrelease \ovvy #7\unitlength \advance\ovvy -#3\unitlength
778 \latexrelease \advance\ovvy -\ovdy \divide\ovvy\@multicnt
779 \latexrelease \setbox\@tempboxa\hbox{%
780 \latexrelease \hskip -\@halfwidth
781 \latexrelease \vrule \@height\@halfwidth
782 \latexrelease \@depth \@halfwidth
783 \latexrelease \@width \@wholewidth}%
784 \latexrelease \put(#2,#3){%
785 \latexrelease \count@\z@
786 \latexrelease \@whilenum{\count@<\@tempcnta}\do
787 \latexrelease {\@xdim\count@\ovxx
788 \latexrelease \advance\@xdim\ovdx

```

```

789 <latexrelease>          \divide\@xdim\@multicnt
790 <latexrelease>          \multiply\@xdim\count@
791 <latexrelease>          \@ydim\count@\@ovyy
792 <latexrelease>          \advance\@ydim\@ovdy
793 <latexrelease>          \divide\@ydim\@multicnt
794 <latexrelease>          \multiply\@ydim\count@
795 <latexrelease>          \raise \@ydim
796 <latexrelease>          \hb@xt@\z@\{\kern\@xdim
797 <latexrelease>          \unhcopy\@tempboxa\hss}%
798 <latexrelease>          \advance\count@\@one}}
799 <latexrelease>\EndIncludeInRelease
800 <*2ekernel>

```

(End of definition for \bezier and \@bezier.)

As the commands above all use “picture” interface we couldn’t define them with \DeclareRobustCommand so we do that now.

```

801 </2ekernel>
802 <*2ekernel | latexrelease>
803 <latexrelease>\IncludeInRelease{2019/10/01}%
804 <latexrelease>          {\bezier}{Make commands robust}%
805 \MakeRobust\bezier
806 \MakeRobust\circle
807 \MakeRobust\dashbox
808 \MakeRobust\line
809 \MakeRobust\linethickness
810 \MakeRobust\multiput
811 \MakeRobust\oval
812 \MakeRobust\put
813 \MakeRobust\qbezier
814 \MakeRobust\shortstack
815 \MakeRobust\thinline
816 \MakeRobust\vector
817 </2ekernel | latexrelease>
818 <latexrelease>\EndIncludeInRelease
819 <latexrelease>\IncludeInRelease{0000/00/00}%
820 <latexrelease>          {\bezier}{Make commands robust}%
821 <latexrelease>
822 <latexrelease>\kernel@make@fragile\bezier
823 <latexrelease>\kernel@make@fragile\circle
824 <latexrelease>\kernel@make@fragile\dashbox
825 <latexrelease>\kernel@make@fragile\line
826 <latexrelease>\kernel@make@fragile\linethickness
827 <latexrelease>\kernel@make@fragile\multiput
828 <latexrelease>\kernel@make@fragile\oval
829 <latexrelease>\kernel@make@fragile\put
830 <latexrelease>\kernel@make@fragile\qbezier
831 <latexrelease>\kernel@make@fragile\shortstack
832 <latexrelease>\kernel@make@fragile\thinline
833 <latexrelease>\kernel@make@fragile\vector
834 <latexrelease>
835 <latexrelease>\EndIncludeInRelease
836 <*2ekernel>
837 </2ekernel>

```

## File 43

# ltthm.dtx

## 1 Theorem Environments

The user creates his own theorem-like environments with the command

`\newtheorem{<name>}{<text>}[<counter>]` or

`\newtheorem{<name>}[<oldname>]{<text>}`

This defines the environment `<name>` to be just as one would expect a theorem environment to be, except that it prints `<text>` instead of “Theorem”.

If `<oldname>` is given, then environments `<name>` and `<oldname>` use the same counter, so using a `<name>` environment advances the number of the next `<name>` environment, and vice-versa.

If `<counter>` is given, then environment `<name>` is numbered within `<counter>`.

E.g., if `<counter> = subsection`, then the first `<name>` in subsection 7.2 is numbered `<text> 7.2.1`.

The way `<name>` environments are numbered can be changed by redefining `\the<name>`.  
*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

### DOCUMENT STYLE PARAMETERS

`\@thmcounter{COUNTER}` : A command such that

`\edef\theCOUNTER{\@thmcounter{COUNTER}}`

defines `\theCOUNTER` to produce a number for a theorem environment.

The default is:

`BEGIN \noexpand\arabic{COUNTER} END`

`\@thmcountersep` : A separator placed between a theorem number and the number of the counter within which it is numbered.

E.g., to make the third theorem of section 7.2 be numbered 7.2-3, `\@thmcountersep` should be `\def`'ed to `'-'`. Its default is `''`.

`\@begintheorem{NAME}{NUMBER}` : A command that begins a theorem environment for a 'theorem' named 'NAME NUMBER' –

e.g., `\@begintheorem{Lemma}{3.7}` starts Lemma 3.7.

`\@opargbegintheorem{NAME}{NUMBER}{OPARG}` :

A command that begins a theorem environment for a 'theorem' named 'NAME NUMBER' with optional argument OPARG – e.g., `\@begintheorem{Lemma}{3.7}{Jones}` starts 'Lemma 3.7 (Jones)':.

`\@endtheorem` : A command that ends a theorem environment.

`\newtheorem{NAME}{TEXT}[COUNTER] ==`

`BEGIN`

if `\NAME` is definable

```

then \@definecounter{NAME}
  if COUNTER present
    then \@newctr{NAME}[COUNTER] fi
    \theNAME == BEGIN \theCOUNTER \@thmcountersep
                                eval\@thmcounter{NAME} END
    else \theNAME == BEGIN eval\@thmcounter{NAME} END
    \NAME == \@thm{NAME}{TEXT}
    \endNAME == \@endtheorem
  else error
fi
END

\newtheorem{NAME}[OLDNAME]{TEXT}==
BEGIN
  if counter OLDNAME nonexistent
  then ERROR
  else
    if \NAME is definable
    then BEGIN
      \theNAME == \theOLDNAME
      \NAME == \@thm{OLDNAME}{TEXT}
      \endNAME == \@endtheorem
      END
    else error
    fi
  fi
END

\@thm{NAME}{TEXT} ==
BEGIN
  \refstepcounter{NAME}
  if next char = [
    then \@ythm{NAME}{TEXT}
    else \@xthm{NAME}{TEXT}
  fi
END

\@xthm{NAME}{TEXT} ==
BEGIN
  \@begintheorem{TEXT}{\theNAME}
  \ignorespaces
END

\@ythm{NAME}{TEXT}[OPARG] ==
BEGIN
  \@opargbegintheorem{TEXT}{\theNAME}{OPARG}
  \ignorespaces
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\newtheorem` `\newtheorem` ought really be allowed only in the preamble Which would be good document style, and allow some main memory to be saved by declaring these commands to be `\onlypreamble`. Unfortunately the L<sup>A</sup>T<sub>E</sub>X book indicates that `\newtheorem` may be used anywhere in the document...

```

1 <*2ekernel>
2 \def\newtheorem#1{%
3   \ifnextchar[{\@othm{#1}}{\@nthm{#1}}}
```

(End of definition for `\newtheorem`.)

`\@nthm`

```

4 \def\@nthm#1#2{%
5   \ifnextchar[{\@xnthm{#1}{#2}}{\@ynthm{#1}{#2}}}
```

(End of definition for `\@nthm`.)

`\@xnthm` 92/09/18 RmS: Changed `\@addtoreset` to `\@newctr` to produce error message if counter #3 does not exist (to be consistent with behaviour of `\newcounter`)

```

6 \def\@xnthm#1#2[#3]{%
7   \expandafter\ifdefinable\csname #1\endcsname
8     {\@definecounter{#1}\@newctr{#1}[#3]%
9     \expandafter\xdef\csname the#1\endcsname{%
10      \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
11      \@thmcounter{#1}}}%
12   \global\@namedef{#1}{\@thm{#1}{#2}}%
13   \global\@namedef{end#1}{\@endtheorem}}}
```

(End of definition for `\@xnthm`.)

`\@ynthm`

```

14 \def\@ynthm#1#2{%
15   \expandafter\ifdefinable\csname #1\endcsname
16     {\@definecounter{#1}%
17     \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
18     \global\@namedef{#1}{\@thm{#1}{#2}}%
19     \global\@namedef{end#1}{\@endtheorem}}}
```

(End of definition for `\@ynthm`.)

`\@othm`

```

20 \def\@othm#1[#2]#3{%
21   \ifundefined{c@#2}{\@nocounterr{#2}}%
22   {\expandafter\ifdefinable\csname #1\endcsname
23     {\global\@namedef{the#1}{\@nameuse{the#2}}%
24     \global\@namedef{#1}{\@thm{#2}{#3}}%
25     \global\@namedef{end#1}{\@endtheorem}}}
```

(End of definition for `\@othm`.)

`\@thm`

```

26 </2ekernel>
27 <*2ekernel | latexrelease>
28 <latexrelease>\IncludeInRelease{2024/03/18}%
29 <latexrelease>          {\@thm}{no link target}%
30 \def\@thm#1#2{%
```

```

31 \kernel@refstepcounter{#1}%
32 \ifnextchar[{\@ythm{#1}{#2}}{\@xthm{#1}{#2}}}%
33 \<latexrelease>\EndIncludeInRelease
34 \<latexrelease>\IncludeInRelease{0000/00/00}%
35 \<latexrelease> \@thm{no link target}%
36 \<latexrelease>\def\@thm#1#2{%
37 \<latexrelease> \refstepcounter{#1}%
38 \<latexrelease> \ifnextchar[{\@ythm{#1}{#2}}{\@xthm{#1}{#2}}}%
39 \<latexrelease>\EndIncludeInRelease
40 \</2ekernel | latexrelease>

```

(End of definition for \@thm.)

```

\@xthm
\@ythm
41 \<*2ekernel>
42 \def\@xthm#1#2{%
43 \@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}
44 \def\@ythm#1#2[#3]{%
45 \@opargbegintheorem{#2}{\csname the#1\endcsname}{#3}\ignorespaces}

```

(End of definition for \@xthm and \@ythm.)

Default values

```

\@thmcounter
\@thmcountersep
46 \def\@thmcounter#1{\noexpand\arabic{#1}}
47 \def\@thmcountersep{.}

```

(End of definition for \@thmcounter and \@thmcountersep.)

```

\@begintheorem Providing theorem defaults.
\@opargbegintheorem
\@endtheorem
48 \</2ekernel>
49 \<*2ekernel | latexrelease>
50 \<latexrelease>\IncludeInRelease{2024/03/18}%
51 \<latexrelease> \@begintheorem{add link targets}%
52 \def\@begintheorem#1#2{\trivlist
53 \item[\MakeLinkTarget{\@currentcounter}\hskip \labelsep{\bfseries #1\ #2}]\itshape}
54 \def\@opargbegintheorem#1#2#3{\trivlist
55 \item[\MakeLinkTarget{\@currentcounter}\hskip \labelsep{\bfseries #1\ #2\ (#3)}]\itshape}
56 \<latexrelease>\EndIncludeInRelease
57 \<latexrelease>\IncludeInRelease{0000/00/00}%
58 \<latexrelease> \@begintheorem{add link targets}%
59 \<latexrelease>\def\@begintheorem#1#2{\trivlist
60 \<latexrelease> \item[\hskip \labelsep{\bfseries #1\ #2}]\itshape}
61 \<latexrelease>\def\@opargbegintheorem#1#2#3{\trivlist
62 \<latexrelease> \item[\hskip \labelsep{\bfseries #1\ #2\ (#3)}]\itshape}
63 \<latexrelease>\EndIncludeInRelease
64 \</2ekernel | latexrelease>
65 \<*2ekernel>
66 \def\@endtheorem{\endtrivlist}
67 \</2ekernel>

```

(End of definition for \@begintheorem, \@opargbegintheorem, and \@endtheorem.)

## File 44

# ltsect.dtx

## 1 Sectioning Commands

This file defines the declarations such as `\author` which are used by `\maketitle`. `\maketitle` itself is defined by each class, not in the L<sup>A</sup>T<sub>E</sub>X kernel.

The second part of the file defines the generic commands used for defining sectioning commands such as `\chapter`. Again the actual document level commands are defined in the class files, in terms of these commands.

```
1 <*2ekernel>
2 \message{title,}
```

### 1.1 The Title

`\title` The user defines the title and author by the declarations `\title{<name>}`, `\author{<name>}`  
`\author` Similarly the date is declared with `\date{<date>}`.  
`\date` Inside these, the `\thanks{<footnote text>}` command may be used to make acknowl-  
`\thanks` edgements, notice of address, etc. in a footnote. If there are multiple authors, they have  
`\and` to be separated with the `\and` command.  
`\maketitle` And finally, the `\maketitle` command produces the actual title, using the informa-  
tion previously saved with the other commands.

```
3 </2ekernel>
4 <*2ekernel | latexrelease>
5 <latexrelease>\IncludeInRelease{2019/10/01}%
6 <latexrelease>                {\title}{Make commands robust}%
```

**`\title`** `\title` for use in `\maketitle`. If not given `\maketitle` will produce an error message.

```
7 \DeclareRobustCommand\title[1]{\gdef\@title{#1}}
```

*(End of definition for \title. This function is documented on page 819.)*

`\author` `\author` for use in `\maketitle`. If not given `\maketitle` will produce a warning message.

```
8 \DeclareRobustCommand*\author[1]{\gdef\@author{#1}}
```

*(End of definition for \author.)*

`\date` `\date` for use in `\maketitle`. If not given `\maketitle` will produce `\today` as the default.

```
9 \DeclareRobustCommand*\date[1]{\gdef\@date{#1}}
```

*(End of definition for \date.)*

`\thanks`

```
10 \DeclareRobustCommand\thanks[1]{\footnotemark
11     \protected@xdef\@thanks{\@thanks
12         \protect\footnotetext[\the\c@footnote]{#1}}%
13 }
```

*(End of definition for \thanks.)*

`\and`

```
14 \DeclareRobustCommand\and{%    % \begin{tabular}
15   \end{tabular}}%
16   \hskip 1em \@plus.17fil%
17   \begin{tabular}[t]{c}}%    % \end{tabular}
```

*(End of definition for \and.)*

```
18 </2ekernel | latexrelease>
19 <latexrelease>\EndIncludeInRelease
20 <latexrelease>\IncludeInRelease{0000/00/00}%
21 <latexrelease>                {\title}{Make commands robust}%
22 <latexrelease>
23 <latexrelease>\kernel@make@fragile\title
24 <latexrelease>\kernel@make@fragile\author
25 <latexrelease>\kernel@make@fragile\date
26 <latexrelease>\kernel@make@fragile\thanks
27 <latexrelease>\kernel@make@fragile\and
28 <latexrelease>
29 <latexrelease>\EndIncludeInRelease
30 <*2ekernel>
```

`\@title`

```
31 \def\@title{\@latex@error{No \noexpand\title given}\@ehc}
```

*(End of definition for \@title.)*

`\@author`

```
32 \def\@author{\@latex@warning@no@line{No \noexpand\author given}}
```

*(End of definition for \@author.)*

`\@date`

```
33 \gdef\@date{\today}
```

*(End of definition for \@date.)*

`\@thanks`

```
34 \let\@thanks\@empty
```

*(End of definition for \@thanks.)*

```
35 \message{sectioning,}
```

## 1.2 Sectioning

`\@secpenalty`

```
36 \newcount\@secpenalty
37 \@secpenalty = -300
```

*(End of definition for \@secpenalty.)*

`\if@noskipsec` Way back in 1991 (08/26) FMi & RmS set the `@noskipsec` switch to true for the preamble  
`\@noskipsectrue` and to false in `\document`. This was done to trap lists and related text in the preamble  
but it does not catch everything.

```
38 \newif\if@noskipsec \@noskipsectrue
```

(End of definition for \if@noskipsec and \@noskipsectrue.)

`\@startsection` The `\@startsection{<name>}{<level>}{<indent>}{<beforeskip>}{<afterskip>}{<style>}*[<altheading>] {<heading>}` command is the mother of all the user level sectioning commands. The part after the `*`, including the `*` is optional.

**name:** e.g., 'subsection'

**level:** a number, denoting depth of section – e.g., chapter = 0, section = 1, etc.

**indent:** Indentation of heading from left margin

**beforeskip:** Absolute value = skip to leave above the heading. If negative, then paragraph indent of text following heading is suppressed.

**afterskip:** if positive, then skip to leave below heading, else negative of skip to leave to right of run-in heading.

**style:** Commands to set style. Since June 1996 release the *last* command in this argument may be a command such as `\MakeUppercase` or `\fbox` that takes an argument. The section heading will be supplied as the argument to this command. So setting #6 to, say, `\bfseries\MakeUppercase` would produce bold, uppercase headings.

If '`*`' is missing, then increment the counter. If it is present, then there should be no `[<altheading>]` argument. The command uses the counter 'secnumdepth'. It contains a pointer to the highest section level that is to be numbered.

**Warning:** The `\@startsection` command should be at the same or higher grouping level as the text that follows it. For example, you should *not* do something like

```
\def\foo{ \begingroup ...
           \paragraph{...}
           \endgroup}
```

Pseudocode for the `\@startsection` command *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments* (not necessarily accurate any more):

```
\@startsection
{NAME}{LEVEL}{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE} ==
BEGIN
  IF @noskipsec = T THEN \leavevmode FI
                                % true if previous section had no body.

  \par
  \@tempskipa := BEFORESKIP
  @afterindent := T
  IF \@tempskipa < 0 THEN \@tempskipa := -\@tempskipa
                                @afterindent := F
  FI
  IF @nobreak = true
    THEN \everypar == null
    ELSE \addpenalty{\@secpenalty}
          \addvspace{\@tempskipa}
  FI
  IF * next
```

```

        THEN \@ssect{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE}
        ELSE \@dblarg{\@sect
                    {NAME}{LEVEL}{INDENT}
                    {BEFORESKIP}{AFTERSKIP}{STYLE}}
    FI
END
End of historical LATEX 2.09 comments.

```

```

39 \def\@startsection#1#2#3#4#5#6{%
40   \if@noskipsec \leavevmode \fi
41   \par
42   \@tempskipa #4\relax
43   \@afterindenttrue
44   \ifdim \@tempskipa <\z@
45     \@tempskipa -\@tempskipa \@afterindentfalse
46   \fi
47   \if@nobreak
48     \everypar{}%
49   \else
50     \addpenalty\@secpenalty\addvspace\@tempskipa
51   \fi
52   \@ifstar
53     {\@ssect{#3}{#4}{#5}{#6}}%
54     {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}

```

*(End of definition for \@startsection.)*

**\@sect** Pseudocode for the \@sect command *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```

\@sect{NAME}{LEVEL}
      {INDENT}{BEFORESKIP}{AFTERSKIP}
      {STYLE}[ARG1]{ARG2}
      ==
BEGIN
  IF LEVEL > \@secnumdepth
    THEN \@svsec :=L null
    ELSE \refstepcounter{NAME}
         \@svsec :=L BEGIN \@seccntformat{#1}\relax END
  FI
  IF AFTERSKIP > 0
    THEN \begingroup
         STYLE
         \@hangfrom{\hskip INDENT\@svsec}
         {\interlinepenalty 10000 ARG2\par}
         \endgroup
         \NAMEmark{ARG1}
         \addcontentsline{toc}{NAME}
         { IF LEVEL > \@secnumdepth
           ELSE \protect\numberline{\theNAME} FI
           ARG1 }
    ELSE \@svsechd == BEGIN STYLE
                                   \hskip INDENT\@svsec

```

```

ARG2
\NAMEmark{ARG1}
\addcontentsline{toc}{NAME}
{ IF LEVEL > \c@secnumdepth
ELSE
\protect\numberline{\theNAME}
FI
ARG1 }

END

FI
\@xsect{AFTERSKIP}
END
End of historical LATEX 2.09 comments.

55 \def\@sect#1#2#3#4#5#6[#7]#8{%
56 \ifnum #2>\c@secnumdepth
57 \let\@svsec\@empty
58 \else
59 \refstepcounter{#1}%

Since \@secntformat might end with an improper \hskip which is scanning forward
for plus or minus we end the definition of \@svsec with \relax as a precaution.

60 \protected@edef\@svsec{\@secntformat{#1}\relax}%
61 \fi
62 \@tempskipa #5\relax
63 \ifdim \@tempskipa>\z@
64 \begingroup

This { used to be after the argument to \@hangfrom but was moved here to allow com-
mands such as \MakeUppercase to be used at the end of #6.

65 #6{%
66 \@hangfrom{\hskip #3\relax\@svsec}%
67 \interlinepenalty \@M #8\@par}%
68 \endgroup
69 \csname #1mark\endcsname{#7}%
70 \addcontentsline{toc}{#1}{%
71 \ifnum #2>\c@secnumdepth \else
72 \protect\numberline{\csname the#1\endcsname}%
73 \fi
74 #7}%
75 \else

\relax added 2 May 90

76 \def\@svsechd{%
77 #6{\hskip #3\relax
78 \@svsec #8}%
79 \csname #1mark\endcsname{#7}%
80 \addcontentsline{toc}{#1}{%
81 \ifnum #2>\c@secnumdepth \else
82 \protect\numberline{\csname the#1\endcsname}%
83 \fi
84 #7}}%
85 \fi
86 \@xsect{#5}}

```

(End of definition for \@sect.)

`\@xsect` Pseudocode for the `\@xsect` command *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
\@xsect{AFTERSKIP} ==
BEGIN
  IF AFTERSKIP > 0
    THEN \par \nobreak
         \vskip AFTERSKIP
         \@afterheading
    ELSE @nobreak :=G F
         @noskipsec :=G T
         \everypar{ IF @noskipsec = T
                     THEN @noskipsec :=G F
                         \clubpenalty := 10000 % local
                         \hskip -\parindent
                         \begingroup
                           \@svsechd
                         \endgroup
                         \unskip
                         \hskip -AFTERSKIP \relax
                                     %% relax added 14 Jan 91
                     ELSE \clubpenalty := \@clubpenalty % local
                         \everypar := NULL
                     FI
                   }
         FI
  FI
END
```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```
87 \def\@xsect#1{%
88   \@tempskipa #1\relax
89   \ifdim \@tempskipa>\z@
```

Why not combine `\@sect` and `\@xsect` and save doing the same test twice? It is not possible to change this now as these have become hooks!

This `\par` seems unnecessary.

```
90   \par \nobreak
91   \vskip \@tempskipa
92   \@afterheading
93 \else
94   \@nobreakfalse
95   \global\@noskipsectrue
96   \everypar{%
97     \if@noskipsec
98       \global\@noskipsecfalse
99       {\setbox\z@\lastbox}%
100       \clubpenalty\@M
101       \begingroup \@svsechd \endgroup
102       \unskip
103       \@tempskipa #1\relax
```

```

104      \hskip -\@tempskipa
105      \else
106        \clubpenalty \@clubpenalty
107        \everypar{}\%
108      \fi}%
109    \fi
110    \ignorespaces}

```

(End of definition for \@xsect.)

**\@secntformat** This command formats the section number including the space following it.

```

111 \def\@secntformat#1{\csname the#1\endcsname\quad}

```

(End of definition for \@secntformat.)

Pseudocode for the \@ssect command *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more)*:

```

\@ssect{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE}{ARG} ==
BEGIN
  IF AFTERSKIP > 0
    THEN \begingroup
          STYLE
          \@hangfrom{\hskip INDENT}
                {\interlinepenalty 10000 ARG\par}
        \endgroup
    ELSE \@svsechd == BEGIN STYLE
                        \hskip INDENT
                        ARG
                      END
  FI
  \@xsect{AFTERSKIP}
END

```

End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.

Pseudocode for the \@afterheading command *Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more)*:

```

\@afterheading ==
BEGIN
  @nobreak :=G true
  \everypar := BEGIN IF @nobreak = T
                  THEN @nobreak :=G false
                  \clubpenalty := 10000 % local
                  IF @afterindent = F
                    THEN remove \lastbox
                  FI
                  ELSE \clubpenalty := \@clubpenalty % local
                  \everypar := NULL
                FI
  END
END

```

End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.

`\@ssect`

```

112 \def\@ssect#1#2#3#4#5{%
113   \@tempskipa #3\relax
114   \ifdim \@tempskipa>\z@
115     \begingroup
This { used to be after the argument to \@hangfrom but was moved here to allow com-
mands such as \MakeUppercase to be used at the end of #4.
116     #4{%
117       \@hangfrom{\hskip #1}%
118       \interlinepenalty \@M #5\@par}%
119     \endgroup
120   \else
121     \def\@svsechd{#4{\hskip #1\relax #5}}%
122   \fi
123   \@xsect{#3}}

```

*(End of definition for \@ssect.)*

`\if@afterindent`  
`\@afterindenttrue`

```

124 \newif\if@afterindent \@afterindenttrue

```

*(End of definition for \if@afterindent and \@afterindenttrue.)*

`\@afterheading`

This hook is used in setting up custom-built headings in classes.dtx.

```

125 \def\@afterheading{%
126   \@nbreaktrue
127   \everypar{%
128     \if@nbreak
129       \@nbreakfalse
130       \clubpenalty \@M
131       \if@afterindent \else
132         {\setbox\z@\lastbox}%
133       \fi
134     \else
135       \clubpenalty \@clubpenalty
136     \everypar{}%
137   \fi}}

```

*(End of definition for \@afterheading.)*

`\@hangfrom` `\@hangfrom{<text>}` : Puts <text> in a box, and makes a hanging indentation of the following material up to the first `\par`. Should be used in vertical mode.

```

138 \def\@hangfrom#1{\setbox\@tempboxa\hbox{#1}}%
139   \hangindent \wd\@tempboxa\noindent\box\@tempboxa}

```

*(End of definition for \@hangfrom.)*

`\c@secnumdepth`  
`\c@tocdepth`

```

140 \newcount\c@secnumdepth
141 \newcount\c@tocdepth

```

*(End of definition for \c@secnumdepth and \c@tocdepth.)*

`\secdef \secdef{<unstarcmds>}{<unstarcmds>}{<starcmds>}`

When defining a `\chapter` or `\section` command without using `\@startsection`, you can use `\secdef` as follows:

1. `\def\chapter{ ... \secdef \<starcmd> \<unstarcmd> }`
2. `\def\<starcmd>[#1]#2{ ... } % Command to define \chapter[...]{...}`
3. `\def\<unstarcmd>#1{ ... } % Command to define \chapter*{...}`

142 `\def\secdef#1#2{\@ifstar{#2}{\@dblarg{#1}}}`

(End of definition for `\secdef`.)

### 1.2.1 Initializations

```

\sectionmark
\subsectionmark 143 \let\sectionmark\@gobble
\subsubsectionmark 144 \let\subsectionmark\@gobble
\paragraphmark 145 \let\subsubsectionmark\@gobble
\subparagraphmark 146 \let\paragraphmark\@gobble
147 \let\subparagraphmark\@gobble

```

(End of definition for `\sectionmark` and others.)

148 `\message{contents,}`

## 1.3 Table of Contents etc.

### 1.3.1 Convention

`\tf@{foo}` = file number for output for table foo. The file is opened only if `@files` = true.

### 1.3.2 Commands

A `\l@{type}{<entry>}{<page>}` Macro needs to be defined by document style for making an entry of type `<type>` in a table of contents, etc. E.g., the document style should define `\l@chapter`, `\l@section`, etc.

**Note:** When the `\protect` command is used in the `<entry>` or `<text>` of one of the commands below, it causes the following control sequence to be written on the file without being expanded. The sequence will be expanded when the table of contents entry is processed.

**Surprise:** Inside an `\addcontentsline` or `\addtocontents` command argument, the commands: `\index`, `\glossary`, and `\label` are no-ops. This could cause a problem if the user puts an `\index` or `\label` into one of the commands he writes, or into the optional 'short version' argument of a `\section` or `\caption` command.

`\@starttoc` The `\@starttoc{<ext>}` command is used to define the commands: `\tableofcontents`, `\listoffigures`, etc.

For example: `\@starttoc{lof}` is used in `\listoffigures`. This command reads the `.<ext>` file and sets up to write the new `.<ext>` file.

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

`\@starttoc{EXT} ==`

```

BEGIN
  \begingroup
  \makeatletter
  read file \jobname.EXT
  IF @filesw = true
    THEN open \jobname.EXT as file \tf@EXT
  FI
  @nobreak :=G FALSE %% added 24 May 89
\endgroup
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

149 \def\@starttoc#1{%
150   \begingroup
151   \makeatletter
152   \@input{\jobname.#1}%
153   \if@filesw
154     \expandafter\newwrite\csname tf@#1\endcsname
155     \immediate\openout \csname tf@#1\endcsname \jobname.#1\relax
156   \fi
157   \@nobreakfalse
158   \endgroup}

```

*(End of definition for \@starttoc.)*

**\addcontentsline** The `\addcontentsline{<table>}{<type>}{<entry>}` command allows the user to add his/her own entry to a table of contents, etc. The command adds the entry `\contentsline{<type>}{<entry>}{<page>}{}` to the `.<table>` file.

This macro is implemented as an application of `\addtocontents`. Note that `\thepage` is not expandable during `\protected@write` therefore one gets the page number at the time of the `\shipout`.

```

159 </2ekernel>
160 <*2ekernel | latexrelease>
161 <latexrelease>\IncludeInRelease{2020/10/01}%
162 <latexrelease>          {\addcontentsline}{fourth argument}%
163 \def\addcontentsline#1#2#3{%

```

We add an empty brace pair at the end of `\contentsline` so that the number of argument is identical in documents with and without hyperref.

```

164   \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}{}}%
165   \protected@file@percent}%
166 </2ekernel | latexrelease>
167 <latexrelease>\EndIncludeInRelease
168 <latexrelease>\IncludeInRelease{2018/12/01}%
169 <latexrelease>          {\addcontentsline}{Mask line endings}%
170 <latexrelease> \def\addcontentsline#1#2#3{%
171 <latexrelease> \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}%

```

We add `\protected@file@percent` at the end which is turned inside `\@writefile` into a percent character to mask the newline after the closing argument brace.

```

172 <latexrelease>          \protected@file@percent}}
173 <latexrelease>\EndIncludeInRelease
174 <latexrelease>\IncludeInRelease{0000/00/00}%
175 <latexrelease>          {\addcontentsline}{Mask line endings}%

```

```

176 <latexrelease>\def\addcontentsline#1#2#3{%
177 <latexrelease> \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}}
178 <latexrelease>\EndIncludeInRelease
179 <*2ekernel>

```

(End of definition for \addcontentsline.)

\@gobble@om Each of these four commands accepts an optional and a mandatory argument, possibly preceded by a star. In all cases the expansion is empty or just manipulates the spaces around the command. Used to disable commands such as \index or \label in certain situations.

```

180 </2ekernel>
181 <*2ekernel | latexrelease>
182 <latexrelease>\IncludeInRelease{2025/06/01}%
183 <latexrelease> \@gobble@som{Extended index/label}%

```

Just getting rid of the input in an expandable way is done by these two.

```

184 \DeclareExpandableDocumentCommand\@gobble@om{+o+m}{\}
185 \DeclareExpandableDocumentCommand\@gobble@som{s+o+m}{\}

```

When something needs to be suppressed during typesetting, one often also wants to ensure that this doesn't end up with two spaces (in case there is one before and one after). This can't be done expandably.

```

186 \DeclareDocumentCommand\@gobble@with@sphack@om{+o+m}{\@bsphack\@esphack}
187 \DeclareDocumentCommand\@gobble@with@sphack@som{s+o+m}{\@bsphack\@esphack}

```

(End of definition for \@gobble@om and others.)

\addtocontents The \addtocontents{<table>}{<text>} command adds <text> to the .<table> file, with no page number.

```

188 \long\def\addtocontents#1#2{%
189 \protected@write\@auxout
190 {\let\label\@gobble@om
191 \let\index\@gobble@som
192 \let\glossary\@gobble@om}%
193 {\string\@writefile{#1}{#2}}}
194 </2ekernel | latexrelease>
195 <latexrelease>\EndIncludeInRelease
196 <latexrelease>\IncludeInRelease{0000/00/00}%
197 <latexrelease> \@gobble@som{Extended index/label}%
198 <latexrelease>\long\def\addtocontents#1#2{%
199 <latexrelease> \protected@write\@auxout
200 <latexrelease> {\let\label\@gobble \let\index\@gobble \let\glossary\@gobble}%
201 <latexrelease> {\string\@writefile{#1}{#2}}}
202 <latexrelease>
203 <latexrelease>\let\@gobble@om\@undefined
204 <latexrelease>\let\@gobble@som\@undefined
205 <latexrelease>\let\@gobble@with@sphack@om\@undefined
206 <latexrelease>\let\@gobble@with@sphack@som\@undefined
207 <latexrelease>\EndIncludeInRelease
208 <*2ekernel>

```

(End of definition for \addtocontents.)

`\contentsline` The `\contentsline{<type>}{<entry>}{<page>}{}` macro produces a `<type>` entry in a table of contents, etc. It will appear in the .toc or other file. For example, the entry for subsection 1.4.3 in the table of contents, might be produced by:

```
\contentsline{subsection}
{\numberline{1.4.3}Gnats and Gnus}{22}{}
```

The `\protect` command causes command sequences to be written without expanding them.

```
209 </2ekernel>
210 <*2ekernel | latexrelease>
211 <latexrelease>\IncludeInRelease{2021/11/15}%
212 <latexrelease>{\contentsline}{Four arguments}%
```

In the toc file `\contentsline` is followed by 4 arguments these days, but only the first 3 are used in the old interface. The fourth was by default empty and only used when `hyperref` was loaded. We now pick up all 4 arguments, save the last one away in `\@contentsline@destination` and then call the old interface. This is done to simplify the interface to `hyperref` and to prepare for future changes.

```
213 \def\contentsline#1#2#3#4{\gdef\@contentsline@destination{#4}%
214 \csname l@#1\endcsname{#2}{#3}}
```

Default definition.

```
215 \let\@contentsline@destination\@empty
216 </2ekernel | latexrelease>
217 <latexrelease>\EndIncludeInRelease
218 <latexrelease>\IncludeInRelease{0000/00/00}%
219 <latexrelease>{\contentsline}{Four arguments}%
220 <latexrelease>
221 <latexrelease>\def\contentsline#1{\csname l@#1\endcsname}
222 <latexrelease>\let\@contentsline@destination\@undefined
223 <latexrelease>\EndIncludeInRelease
224 <*2ekernel>
```

*(End of definition for \contentsline.)*

`\@dottedtocline{<level>}{<indent>}{<numwidth>}{<title>}{<page>}`: Macro to produce a table of contents line with the following parameters:

**level** If `<level>` > `\c@tocdepth`, then no line produced.

**indent** Total indentation from the left margin.

**numwidth** Width of box for number if the `<title>` has a `\numberline` command. As of 25 Jan 1988, this is also the amount of extra indentation added to second and later lines of a multiple line entry.

**title** Contents of entry.

**page** Page number.

Uses the following parameters, which must be set by the document style. They should be defined with `\def`'s.

**pnumwidth** Width of box in which page number is set.

`tocrmarg` Right margin indentation for all but last line of multiple-line entries.

`dotsep` Separation between dots, in mu units. Should be `\def`'d to a number like 2 or 1.7

`\@dottedtocline`

```

225 </2ekernel>
226 <*2ekernel | latexrelease>
227 <latexrelease>\IncludeInRelease{2018/12/01}%
228 <latexrelease>                {\@dottedtocline}{Prevent protrusion}%
229 \def\@dottedtocline#1#2#3#4#5{%
230   \ifnum #1>\c@tocdepth \else
231     \vskip \z@ \@plus.2\p@
232     {\leftskip #2\relax \rightskip \@tocrmarg \parfillskip -\rightskip
233      \parindent #2\relax\@afterindenttrue
234      \interlinepenalty\@M
235      \leavevmode
236      \@tempdima #3\relax
237
238      \advance\leftskip \@tempdima \null\nobreak\hskip -\leftskip
239      {#4}\nobreak
240      \leaders\hbox{$\m@th
```

If a document uses fonts other than computer modern, the use of a dot from math can be very disturbing despite the fact that this might be the only place in a document that then uses computer modern. Therefore we surround the dot with an `\hbox` to escape to the surrounding text font.

```

240       \mkern \@dotsep mu\hbox{.}\mkern \@dotsep
241       mu$}\hfill
242       \nobreak
243       \hb@xt@\@pnumwidth{\hfil\normalfont \normalcolor #5%
```

We finish off by preventing any protrusion if that is enabled. If protrusion happens the number may shift to the right and as a result you may end up with an additional dot in the toc line in some situations.

```

244               \kern-\p@\kern\p@}%
245       \par}%
246       \fi}
```

*(End of definition for \@dottedtocline.)*

`\noptrusion` This command, if placed directly to the right (or left) of a word, will prevent protrusion of that word into the margin. It is used in the toc entry lines as they shouldn't protrude. It is implemented as to kerns that cancel each other but being there hide the word so that protrusion is not added. Note that a zero kern or an empty box would not work as the protrusion mechanism will skip over those.

```

247 \DeclareRobustCommand\noptrusion{\leavevmode\kern-\p@\kern\p@}
```

*(End of definition for \noptrusion.)*

```

248 </2ekernel | latexrelease>
249 <latexrelease>\EndIncludeInRelease
250 <latexrelease>\IncludeInRelease{0000/00/00}%
251 <latexrelease>                {\@dottedtocline}{Prevent protrusion}%
252 <latexrelease>\def\@dottedtocline#1#2#3#4#5{%
```

```

253 <latexrelease> \ifnum #1>\c@tocdepth \else
254 <latexrelease> \vskip \z@ \@plus.2\p@
255 <latexrelease> {\leftskip #2\relax \rightskip \@tocrmarg \parfillskip -\rightskip
256 <latexrelease> \parindent #2\relax\@afterindenttrue
257 <latexrelease> \interlinepenalty\@M
258 <latexrelease> \leavevmode
259 <latexrelease> \@tempdima #3\relax
260 <latexrelease> \advance\leftskip \@tempdima \null\nobreak\hskip -\leftskip
261 <latexrelease> {#4}\nobreak
262 <latexrelease> \leaders\hbox{$\m@th
263 <latexrelease> \mkern \@dotsep mu\hbox{.}\mkern \@dotsep
264 <latexrelease> mu$}\hfill
265 <latexrelease> \nobreak
266 <latexrelease> \hb@xt@\@pnumwidth{\hfil\normalfont \normalcolor #5}%
267 <latexrelease> \par}%
268 <latexrelease> \fi}
269 <latexrelease>
270 <latexrelease>\let\noprotrusion\undefined
271 <latexrelease>\EndIncludeInRelease
272 <*2ekernel>

```

**Note:** `\nobreak`'s added 7 Jan 86 to prevent bad line break that left the page number dangling by itself at left edge of a new line.

Changed 25 Jan 88 to use `\leftskip` instead of `\hangindent` so leaders of multiple-line contents entries would line up properly.

`\numberline` `\numberline{<number>}`: For use in a `\contentsline` command. It puts `<number>` flush-left in a box of width `\@tempdima` (Before 25 Jan 88 change, it also added `\@tempdima` to the hanging indentation.)

```

273 \def\numberline#1{\hb@xt@\@tempdima{#1\hfil}}
274 </2ekernel>

```

*(End of definition for \numberline.)*

## File 45

# lfloat.dtx

## 1 Floats

The different types of floats are identified by a  $\langle\textit{type}\rangle$  name, which is the name of the counter for that kind of float. For example, figures are of type ‘figure’ and tables are of type ‘table’. Each  $\langle\textit{type}\rangle$  has associated a positive  $\langle\textit{type number}\rangle$ , which is a power of two. E.g., figures might have type number 1, tables type number 2, programs type number 4, etc.

The locations where a float can go are specified by a  $\langle\textit{placement specifier}\rangle$ , which is a list of the possible locations, each denoted by a letter as follows:

h : here	— at the current location in the text.
t : top	— at the top of a text page.
b : bottom	— at the bottom of a text page.
p : page	— on a separate float page

In addition, in conjunction with these, you can use ‘!’ which means that the current values of the float positioning parameters are ignored for this float. (Has no effect on ‘p’, float page positioning.) For example, ‘pht’ specifies that the float can appear in any of three locations: page, here or top.

### 1.1 Floating Environments

```
1  $\langle*2\textit{kernel}\rangle$ 
2  $\backslash\textit{message}\{\textit{floats},\}$ 
```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

Where floats may appear on a page, and how many may appear there are specified by the following float placement parameters. The numbers are named like counters so the user can set them with the ordinary counter-setting commands.

$\backslash\textit{c@topnumber}$	: Number of floats allowed at the top of a column.
$\backslash\textit{topfraction}$	: Fraction of column that can be devoted to floats.
$\backslash\textit{c@dbltopnumber}$ , $\backslash\textit{dbltopfraction}$	: Same as above, but for double-column floats.
$\backslash\textit{c@bottomnumber}$ , $\backslash\textit{bottomfraction}$	: Same as above for bottom of page.
$\backslash\textit{c@totalnumber}$	: Number of floats allowed in a single column, including in-text floats.
$\backslash\textit{textfraction}$	: Minimum fraction of column that must contain text.
$\backslash\textit{floatpagefraction}$	: Minimum fraction of page that must be taken up by float page.
$\backslash\textit{dblfloatpagefraction}$	: Same as above, for double-column floats.

The document style must define the following.

`\fps@TYPE` : The default placement specifier for floats of type TYPE.

`\ftype@TYPE` : The type number for floats of type TYPE.

`\ext@TYPE` : The file extension indicating the file on which the contents list for float type TYPE is stored.  
For example, `\ext@figure = 'lof'`.

`\fnum@TYPE` : A macro to generate the figure number for a caption.  
For example, `\fnum@TYPE == Figure \thefigure`.

`\@makecaption{NUM}{TEXT}` :  
A macro to make a caption, with NUM the value produced by `\fnum@...` and TEXT the text of the caption. It can assume it's in a `\parbox` of the appropriate width.

`\@float{TYPE}[PLACEMENT]` : This macro begins a float environment for a single-column float of type TYPE with PLACEMENT as the placement specifier. The default value of PLACEMENT is defined by `\fps@TYPE`. The environment is ended by `\end@float`.  
E.g., `\figure == \@float{figure}, \endfigure == \end@float`.

```
\@float{TYPE}[PLACEMENT] ==
BEGIN
  if hmode then \@bsphack
    \@floatpenalty := -10002
  else \@floatpenalty := -10003
  fi
  \@captype ==L TYPE
  \@dblflset
  \@fps ==L PLACEMENT
  \@onelevel@sanitize \@fps
  add default PLACEMENT if at most ! in PLACEMENT ==
\@fpsadddefault
  if inner
    then LaTeX Error: 'Not in outer paragraph mode.'
    \@floatpenalty := 0
  else if \@freelist nonempty
    then \@currbox :=L head of \@freelist
    \@freelist :=G tail of \@freelist
    \count\@currbox :=G 32*\ftype@TYPE +
                                bits determined by PLACEMENT
    else \@floatpenalty := 0
    LaTeX Error: 'Too many unprocessed floats'
  fi
  fi
  \@currbox :=G \color@vbox
```

```

\normalcolor
\ vbox{
  %% 15 Dec 87 -
  %% removed \boxmaxdepth :=L 0pt
  %% that made box 0 depth because it screwed
  %% things up. Instead, added \vskip0pt at end
  \hsize = \columnwidth
  \@parboxrestore
  \@floatboxreset
END

```

```

\caption ==
BEGIN
  \refstepcounter{\@capttype}
  \@dblarg{\@caption{\@capttype}}
END

```

In following definition, `\par` moved from after `\addcontentsline` to before `\addcontentsline` because the `\write` could cause an extra blank line to be added to the paragraph above the caption. (Change made 12 Jun 87)

```

\@caption{TYPE}[STEXT]{TEXT} ==
BEGIN
  \par
  \addcontentsline{\ext@TYPE}{TYPE}{\numberline{\theTYPE}{STEXT}}
  \begingroup
    \@parboxrestore
    \@normalsize
    \@makecaption{\fnum@TYPE}{TEXT}
  \par
  \endgroup
END

```

`\@dblfloat{TYPE}[PLACEMENT]` : Macro to begin a float environment for a double-column float of type TYPE with PLACEMENT as the placement specifier. The default value of PLACEMENT is 'tp'

The environment is ended by `\end@dblfloat`.

E.g., `\figure* == \@dblfloat{figure}`,

`\endfigure* == \end@dblfloat`.

```

\@dblfloat{TYPE}[PLACEMENT] ==
  Identical to \@float{TYPE}[PLACEMENT] except \hsize and \linewidth
  are set to \textwidth.

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\@floatpenalty`

```

3 \newcount\@floatpenalty

```

*(End of definition for \@floatpenalty.)*

`\caption` This is set to be an error message outside a float since no `captype` is defined there; this may need to be changed by some classes.

```

4 \def\caption{%
5   \ifx\@captype\@undefined
6     \latexerror{\noexpand\caption outside float}\@ehd
7     \expandafter\@gobble
8   \else
9     \refstepcounter\@captype
10    \expandafter\@firstofone
11  \fi
12  {\@dblarg{\@caption\@captype}}%
13 }
```

*(End of definition for \caption.)*

`\@caption`

```

14 \long\def\@caption#1[#2]#3{%
15   \par
16   \addcontentsline{\csname ext@#1\endcsname}{#1}%
17   {\protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}}%
18   \begingroup
```

The paragraph setting parameters are normalised at this point, however `\@parboxrestore` resets `\everypar` which is not correct in this context so `\@setminipage` is called if needed.

The float mechanism, like `minipage`, sets the flag `@minipage` true before executing the user-supplied text. Many L<sup>A</sup>T<sub>E</sub>X constructs test for this flag and do not add vertical space when it is true. The intention is that this emulates T<sub>E</sub>X's ‘top of page’ behaviour. The flag must be set false at the start of the first paragraph. This is achieved by a redefinition of `\everypar`, but the call to `\@parboxrestore` removes that redefinition, so it is re-inserted if needed. If the flag is already false then the `\caption` was not the first entry in the float, and so some other paragraph has already activated the special `\everypar`. In this case no further action is needed.

```

19   \@parboxrestore
20   \if@minipage
21     \@setminipage
22   \fi
23   \normalsize
24   \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par
25   \endgroup
```

*(End of definition for \@caption.)*

`\@float`  
`\@dblflset`

```

26 \def\@float#1{%
27   \ifnextchar[%
28     {\@xfloat{#1}}%
29     {\edef\reserved@a{\noexpand\@xfloat{#1}[\csname fps@#1\endcsname]}}%
30     \reserved@a}}
```

*(End of definition for \@float and \@dblflset.)*

`\@dblfloat`

```

31 \def\@dblfloat{%
32   \if@twocolumn\let\reserved@a\@dblft\else\let\reserved@a\@float\fi
33   \reserved@a}
```

(End of definition for \@dblfloat.)

`\fps@dbl` Note that all double floats have default fps ‘tp’.

(End of definition for \fps@dbl.)

`\@setfps` This sets the fps, dealing with error conditions by adding the default.

(End of definition for \@setfps.)

`\@xfloat` The first part of this sets the count register that stores all the information about the type and fps of the float.

We assume here that the default specifiers already contain no active characters.

It may be better to store the defaults as numbers, rather than symbol strings.

```
34 </2ekernel>
35 <latexrelease>\IncludeInRelease{2015/01/01}%
36 <latexrelease>                {\@xfloat}{Check float options}%
37 <*2ekernel | latexrelease>
38 \def\@xfloat #1[#2]{%
39   \@nodocument
40   \def \@capytype {#1}%
41   \def \@fps {#2}%
42   \@onelevel@sanitize \@fps
43   \def \reserved@a {!}%
44   \ifx \reserved@a \@fps
45     \@fpsadddefault
46   \else
47     \ifx \@fps \@empty
48       \@fpsadddefault
49     \fi
50   \fi
51   \ifhmode
52     \@bsphack
53     \@floatpenalty -\@Mii
54   \else
55     \@floatpenalty-\@Miii
56   \fi
57   \ifinner
58     \@parmoderr\@floatpenalty\z@
59   \else
60     \@next\@currbox\@freelist
61     {%
62       \@tempcnta \sixt@@n
63       \expandafter \@tfor \expandafter \reserved@a
64       \expandafter : \expandafter =\@fps
65       \do
```

Start of changes, use a nested if structure, ending in an error.

```
66       {%
67         \if \reserved@a h%
68           \ifodd \@tempcnta
69             \else
70               \advance \@tempcnta \@ne
71             \fi
```

```

72         \else\if \reserved@a t%
73             \@setfpsbit \tw@
74         \else\if \reserved@a b%
75             \@setfpsbit 4%
76         \else\if \reserved@a p%
77             \@setfpsbit 8%
78         \else\if \reserved@a !%
79             \ifnum \@tempcnta>15
80                 \advance\@tempcnta -\sixt@@n\relax
81             \fi
82         \else
83             \@latex@error{Unknown float option ‘\reserved@a’}%
84             {Option ‘\reserved@a’ ignored and ‘p’ used.}%
85             \@setfpsbit 8%
86         \fi\fi\fi\fi\fi
87     }%

```

End of changes

```

88         \@tempcntb \csname ftype@\@capttype \endcsname
89         \multiply \@tempcntb \@xxxii
90         \advance \@tempcnta \@tempcntb
91         \global \count\@currbox \@tempcnta
92     }%
93     \@fltovf
94 \fi

```

The remainder sets up the box in which the float is typeset, and the typesetting environment to be used. It is essential to have the extra box to avoid the unwanted space that would otherwise often be put at the top of the float.

It ends with a hook; not sure how useful this is but it is needed at present to deal with double-column floats.

```

95     \global \setbox\@currbox
96         \color@vbox
97         \normalcolor
98         \vbox \bgroup
99             \hsize\columnwidth
100             \@parboxrestore
101             \@floatboxreset
102     }%
103 </2ekernel | latexrelease>
104 <latexrelease>\EndIncludeInRelease
105 <latexrelease>\IncludeInRelease{0000/00/00}%
106 <latexrelease>          {\@xfloat}{Check float options}%
107 <latexrelease>\def\@xfloat #1[#2]{%
108 <latexrelease>    \@nocument
109 <latexrelease>    \def \@capttype {#1}%
110 <latexrelease>    \def \@fps {#2}%
111 <latexrelease>    \@onelevel@sanitize \@fps
112 <latexrelease>    \def \reserved@b {!}%
113 <latexrelease>    \ifx \reserved@b \@fps
114 <latexrelease>        \@fpsadddefault
115 <latexrelease>    \else
116 <latexrelease>        \ifx \@fps \@empty
117 <latexrelease>            \@fpsadddefault

```

```

118 <latexrelease> \fi
119 <latexrelease> \fi
120 <latexrelease> \ifhmode
121 <latexrelease> \@bsphack
122 <latexrelease> \@floatpenalty -\@Mii
123 <latexrelease> \else
124 <latexrelease> \@floatpenalty-\@Miii
125 <latexrelease> \fi
126 <latexrelease> \ifinner
127 <latexrelease> \@parmoderr\@floatpenalty\z@
128 <latexrelease> \else
129 <latexrelease> \@next\@currbox\@freelist
130 <latexrelease> {%
131 <latexrelease> \@tempcnta \sixt@@n
132 <latexrelease> \expandafter \@tfor \expandafter \reserved@a
133 <latexrelease> \expandafter :\expandafter =\@fps
134 <latexrelease> \do
135 <latexrelease> {%
136 <latexrelease> \if \reserved@a h%
137 <latexrelease> \ifodd \@tempcnta
138 <latexrelease> \else
139 <latexrelease> \advance \@tempcnta \@ne
140 <latexrelease> \fi
141 <latexrelease> \fi
142 <latexrelease> \if \reserved@a t%
143 <latexrelease> \@setfpsbit \tw@
144 <latexrelease> \fi
145 <latexrelease> \if \reserved@a b%
146 <latexrelease> \@setfpsbit 4%
147 <latexrelease> \fi
148 <latexrelease> \if \reserved@a p%
149 <latexrelease> \@setfpsbit 8%
150 <latexrelease> \fi
151 <latexrelease> \if \reserved@a !%
152 <latexrelease> \ifnum \@tempcnta>15
153 <latexrelease> \advance\@tempcnta -\sixt@@n\relax
154 <latexrelease> \fi
155 <latexrelease> \fi
156 <latexrelease> }%
157 <latexrelease> \@tempcntb \csname ftype@\@capttype \endcsname
158 <latexrelease> \multiply \@tempcntb \@xxxii
159 <latexrelease> \advance \@tempcnta \@tempcntb
160 <latexrelease> \global \count\@currbox \@tempcnta
161 <latexrelease> }%
162 <latexrelease> \@fltovf
163 <latexrelease> \fi
164 <latexrelease> \global \setbox\@currbox
165 <latexrelease> \color@vbox
166 <latexrelease> \normalcolor
167 <latexrelease> \vbox \bgroup
168 <latexrelease> \hsize\columnwidth
169 <latexrelease> \@parboxrestore
170 <latexrelease> \@floatboxreset
171 <latexrelease> }%

```

```

172 \latexrelease\EndIncludeInRelease
173 \*2ekernel)

```

*(End of definition for \@xfloat.)*

**\@floatboxreset** The rational for allowing these normally global flags to be set locally here, via **\@parboxrestore**, was stated originally by Donald Arseneau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should never appear within marginals or floats or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in **\@setnobreak**; otherwise this command will be redundant.

```

174 \def \@floatboxreset {%
175     \reset@font
176     \normalsize
177     \@setminipage
178 }

```

*(End of definition for \@floatboxreset.)*

**\@setnobreak**

```

179 \def \@setnobreak{%
180     \if@nobreak
181         \let\outer@nobreak\@nobreaktrue
182         \@nobreakfalse
183     \fi
184 }

```

*(End of definition for \@setnobreak.)*

**\@setminipage**

```

185 \def \@setminipage{%
186     \@minipagetrue
187     \everypar{\@minipagefalse\everypar{}}%
188 }

```

*(End of definition for \@setminipage.)*

**\end@float**

```

189 \def\end@float{%
190     \@endfloatbox
191     \ifnum\@floatpenalty <\z@

```

We make sure that we never exceed **\textheight**, otherwise float will never get typeset (91/03/15 FMi).

```

192     \@largefloatcheck
193     \@cons\@currlist\@currbox
194     \ifnum\@floatpenalty <-\@Mii
195         \penalty -\@Miv

```

Saving and restoring **\prevdepth** added 26 May 87 to prevent extra vertical space when used in vertical mode.

```

196     \@tempdima\prevdepth
197     \vbox{}%
198     \prevdepth\@tempdima

```

```

199      \penalty\@floatpenalty

200      \else
201        \vadjust{\penalty -\@Miv \vbox{}\penalty\@floatpenalty}\@Esphack
202      \fi
203    \fi
204  }

```

(End of definition for \end@float.)

\end@dblfloat

```

205  </2ekernel>
206  <latexrelease>\IncludeInRelease{2015/01/01}%
207  <latexrelease>          {\end@dblfloat}{float order in 2-column}%
208  <*2ekernel | latexrelease>
209  \def\end@dblfloat{%
210    \if@twocolumn
211      \endfloatbox
212      \ifnum\@floatpenalty <\z@
213        \@largefloatcheck

```

Force the depth of two column float boxes.

```

214    \global\dp\@currbox1sp %

```

What follows is essentially \end@float without a starting \endfloatbox.

```

215    \@cons\@currlist\@currbox
216    \ifnum\@floatpenalty <-\@Mii
217      \penalty -\@Miv
218      \@tempdima\prevdepth
219      \vbox{}%
220      \prevdepth\@tempdima
221      \penalty\@floatpenalty
222    \else
223      \vadjust{\penalty -\@Miv \vbox{}\penalty\@floatpenalty}\@Esphack
224    \fi

225    \fi
226  \else
227    \end@float
228  \fi
229 }%

```

```

230 </2ekernel | latexrelease>
231 <latexrelease>\EndIncludeInRelease
232 <latexrelease>\IncludeInRelease{0000/00/00}%
233 <latexrelease>          {\end@dblfloat}{float order in 2-column}%
234 <latexrelease>\def\end@dblfloat{%
235 <latexrelease>\if@twocolumn
236 <latexrelease>  \endfloatbox
237 <latexrelease>  \ifnum\@floatpenalty <\z@

```

We make sure that we never exceed \textheight, otherwise float will never get typeset (91/03/15 FMi).

```

238 <latexrelease>    \@largefloatcheck
239 <latexrelease>    \@cons\@dbldeferlist\@currbox
240 <latexrelease>  \fi

```

RmS 92/03/18 changed \@esphack to \@Esphack.

```
241 \<latexrelease> \ifnum \@floatpenalty =-\@Mii \@Esphack\fi
242 \<latexrelease>\else
243 \<latexrelease> \end@float
244 \<latexrelease>\fi
245 \<latexrelease>\}%
246 \<latexrelease>\EndIncludeInRelease
247 \<*2ekernel>
```

*(End of definition for \end@dblfloat.)*

**\@endfloatbox** This macro is not intended to be a hook; it is designed to help maintain the integrity of this code, which is used twice and, as can be seen, is subject to frequent changes.

```
248 \def \@endfloatbox{%
249     \par\vskip\z@skip      %% \par\vskip\z@ added 15 Dec 87

250     \@minipagefalse
251     \outer@nobreak
252     \egroup                %% end of vbox
253     \color@endbox
254 }
```

*(End of definition for \@endfloatbox.)*

**\outer@nobreak**

```
255 \let\outer@nobreak\@empty
```

*(End of definition for \outer@nobreak.)*

**\@largefloatcheck** This calculates by how much a float is oversize for the page and prints this in a warning message.

```
256 \def \@largefloatcheck{%
257     \ifdim \ht\@currbox>\textheight
258         \@tempdima -\textheight
259         \advance \@tempdima \ht\@currbox

260         \@latex@warning {Float too large for page by \the\@tempdima}%
261         \ht\@currbox \textheight
262     \fi
263 }
```

*(End of definition for \@largefloatcheck.)*

**\@dbflt**

**\@xdblfloat**

```
264 \def\@dbflt#1{\@ifnextchar[{\@xdblfloat{#1}}{\@xdblfloat{#1}[tp]}}
265 \def\@xdblfloat#1[#2]{%
266     \@xfloat{#1}[#2]\hsize\textwidth\linewidth\textwidth}
```

*(End of definition for \@dbflt and \@xdblfloat.)*

Moved to ltoutput 93/12/16

```
267 %\newcount\c@topnumber
268 %\newcount\c@dbltopnumber
269 %\newcount\c@bottomnumber
270 %\newcount\c@totalnumber
```

`\@floatplacement` An analysis of `\@floatplacement`:  
This should be called whenever `\@colht` has been set.

```

271 \def\@floatplacement{\global\@topnum\c@topnumber
272   % Textpage bit, global:
273   \global\@toproom \topfraction\@colht
274   \global\@botnum \c@bottomnumber
275   \global\@botroom \bottomfraction\@colht
276   \global\@colnum \c@totalnumber
277   % Floatpage bit, local:
278   \@fpmin \floatpagefraction\@colht}
279 \endkernel

```

*(End of definition for \@floatplacement.)*

`\@dblfloatplacement` This should be called only within a group. Now changed to provide extra checks in `\@addtodblcol`, needed when processing a BANG float.

```

280 \latexrelease\IncludeInRelease{2015/01/01}%
281 \latexrelease \def\@dblfloatplacement{\float order in 2-column}%
282 \endkernel\latexrelease

```

When making two column float area, look for floats with 1sp depth.

```

283 \def\@dblfloatplacement{\global\@dbltopnum\c@dbltopnumber
284   \global\@dbltoproom \dbltopfraction\@colht
285   \@textmin \@colht
286   \advance \@textmin -\@dbltoproom
287   \@fpmin \dblfloatpagefraction\textheight
288   \fptop \@dblftop
289   \fpsep \@dblfpsep
290   \fpbot \@dblfpbot

```

`\f@depth` is used in `\@testwrongwidth` to look for either column or dbl-column floats. A value of 1sp signals the latter. Because of this setting here, `\@dblfloatplacement` needs to be called inside a group which is a questionable design.

```

291 \def\f@depth{1sp}%
292 \endkernel\latexrelease
293 \latexrelease\EndIncludeInRelease
294 \latexrelease\IncludeInRelease{0000/00/00}%
295 \latexrelease \def\@dblfloatplacement{\float order in 2-column}%
296 \latexrelease\def \@dblfloatplacement {%

```

Textpage bit: global, but need not be.

```

297 \latexrelease \global \@dbltopnum \c@dbltopnumber
298 \latexrelease \global \@dbltoproom \dbltopfraction\@colht

```

This new bit uses `\@textmin` to locally store the amount of extra room in the column.

```

299 \latexrelease \@textmin \@colht
300 \latexrelease \advance \@textmin -\@dbltoproom

```

Floatpage bit: must be local.

```

301 \latexrelease \@fpmin \dblfloatpagefraction\textheight
302 \latexrelease \fptop \@dblftop
303 \latexrelease \fpsep \@dblfpsep
304 \latexrelease \fpbot \@dblfpbot
305 \latexrelease}%
306 \latexrelease\EndIncludeInRelease
307 \endkernel

```

(End of definition for `\@dblfloatplacement`.)

Historical *LaTeX* 2.09 comments (not necessarily accurate any more):

MARGINAL NOTES:

Marginal notes use the same mechanism as floats to communicate with the `\output` routine. Marginal notes are distinguished from floats by having a negative placement specification. The command `\marginpar [LTEXT]{RTEXT}` generates a marginal note in a parbox, using LTEXT if it's on the left and RTEXT if it's on the right. (Default is RTEXT = LTEXT.) It uses the following parameters.

`\marginparwidth` : Width of marginal notes.  
`\marginparsep` : Distance between marginal note and text.  
the page layout to determine how to move the marginal  
note into the margin. E.g., `\@leftmargin skip ==`  
`\hskip -\marginparwidth \hskip -\marginparsep` .  
`\marginparpush` : Minimum vertical separation between `\marginpar`'s

Marginal notes are normally put on the outside of the page if `@mparswitch = true`, and on the right if `@mparswitch = false`. The command `\reversemarginpar` reverses the side where they are put. `\normalmarginpar` undoes `\reversemarginpar`. These commands have no effect for two-column output.

SURPRISE: if two marginal notes appear on the same line of text, then the second one could appear on the next page, in a funny position.

```
\marginpar [LTEXT]{RTEXT} ==
BEGIN
  if hmode then \@bsphack
    \@floatpenalty := -10002
  else \@floatpenalty := -10003
  fi
  if inner
    then LaTeX Error: 'Not in outer paragraph mode.'
    \@floatpenalty := 0
  else if \@freelist has two elements:
    then get \@marbox, \@currbox from \@freelist
    \count\@marbox :=G -1
  else \@floatpenalty := 0
    LaTeX Error: 'Too many unprocessed floats'
    \@currbox, \@marbox := \@tempboxa %%use \def
  fi
fi
if optional argument
then %% \@xmpar ==
  \@savemarbox\@marbox{LTEXT}
  \@savemarbox\@currbox{RTEXT}
```

```

        else %% \@ympar ==
            \@savemarbox\@marbox{RTEXT}
            \box\@currbox :=G \box\@marbox
        fi
    \@xympar
END

\reversemarginpar == BEGIN \@mparbottom :=G 0
                        @reversemargin :=G true
                        END

\normalmarginpar == BEGIN \@mparbottom :=G 0
                        @reversemargin :=G false
                        END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

**\marginpar**

```

308 \def\marginpar{%
309   \ifhmode
310     \@bsphack
311     \@floatpenalty -\@Mii
312   \else
313     \@floatpenalty-\@Miii
314   \fi
315   \ifinner
316     \@parmoderr
317     \@floatpenalty\z@
318   \else
319     \@next\@currbox\@freelist{}\{}%
320     \@next\@marbox\@freelist{\global\count\@marbox\m@ne}%
321     {\@floatpenalty\z@
322       \@fltovf\def\@currbox{\@tempboxa}\def\@marbox{\@tempboxa}}}%
323   \fi
324   \@ifnextchar [\@xmpar\@ympar}

```

*(End of definition for \marginpar.)*

**\@xmpar**

```

325 \long\def\@xmpar[#1]#2{%
326   \@savemarbox\@marbox{#1}%
327   \@savemarbox\@currbox{#2}%
328   \@xympar}

```

*(End of definition for \@xmpar.)*

**\@ympar**

```

329 \long\def\@ympar#1{%
330   \@savemarbox\@marbox{#1}%
331   \global\setbox\@currbox\copy\@marbox
332   \@xympar}

```

*(End of definition for \@ympar.)*

`\@savemarbox`

```

333 </2ekernel>
334 <*2ekernel | latexrelease>
335 <latexrelease>\IncludeInRelease{2021/06/01}%
336 <latexrelease>          {\@savemarbox}{Explicit par for marginpar}%
337 \long\def \@savemarbox #1#2{%
338   \global\setbox #1%
339     \color@vbox
340     \vtop{%
341       \hsize\marginparwidth
342       \@parboxrestore
343       \@marginparreset
344       #2\par
345       \@minipagefalse
346       \outer@nobreak
347     }%
348   \color@endbox
349 }
350 </2ekernel | latexrelease>
351 <latexrelease>\EndIncludeInRelease
352 <latexrelease>\IncludeInRelease{0000/00/00}%
353 <latexrelease>          {\@savemarbox}{Explicit par for marginpar}%
354 <latexrelease>
355 <latexrelease>\long\def \@savemarbox #1#2{%
356 <latexrelease>  \global\setbox #1%
357 <latexrelease>    \color@vbox
358 <latexrelease>    \vtop{%
359 <latexrelease>      \hsize\marginparwidth
360 <latexrelease>      \@parboxrestore
361 <latexrelease>      \@marginparreset
362 <latexrelease>      #2%
363 <latexrelease>      \@minipagefalse
364 <latexrelease>      \outer@nobreak
365 <latexrelease>    }%
366 <latexrelease>    \color@endbox
367 <latexrelease>}
368 <latexrelease>\EndIncludeInRelease
369 <*2ekernel>

```

*(End of definition for \@savemarbox.)*

`\@marginparreset` The rationale for allowing these normally global flags to be set locally here, via `\@parboxrestore` was stated originally by Donald Arseneau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should never appear within marginals or floats or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in `\@setnobreak`; otherwise this command will be redundant.

```

370 \def \@marginparreset {%
371   \reset@font
372   \normalsize
373 %   \let@if@nobreak\iffalse
374 %   \let@if@noskipsec\iffalse

```

```

375 %          \@setnobreak
376          \@setminipage
377 }

```

(End of definition for \@marginparreset.)

\@xympar

Setting the box here is done only because the code uses \end@float; it will be empty and gets discarded.

```

378 \def \@xympar{%
379   \ifnum \@floatpenalty < \z@ \@cons \@currlist \@marbox \fi
380   \setbox \@tempboxa
381     \color@vbox
382     \vbox \bgroup
383   \end@float
384   \@ignorefalse
385   \@esphack
386 }

```

(End of definition for \@xympar.)

\reversemarginpar

\normalmarginpar

```

387 \def \reversemarginpar {\global \@parbottom \z@ \@reversemargintrue}
388 \def \normalmarginpar {\global \@parbottom \z@ \@reversemarginfalse}

```

(End of definition for \reversemarginpar and \normalmarginpar.)

```

389 \message{footnotes,}

```

## 1.2 Footnotes

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

\footnote{NOTE} : User command to insert a footnote.

\footnote[*NUM*]{NOTE}: User command to insert a footnote numbered *NUM*, where *NUM* is a number – 1, 2, etc. For example, if footnotes are numbered \*, \*\*, etc. within pages, then \footnote[2]{...} produces footnote '\*\*'. This command does not step the footnote counter.

\footnotemark[*NUM*] : Command to produce just the footnote mark in the text, but no footnote. With no argument, it steps the footnote counter before generating the mark.

\footnotetext[*NUM*]{TEXT} : Command to produce the footnote but no mark. \footnote is equivalent to \footnotemark \footnotetext .

As in PLAIN, footnotes use \insert\footins, and the following parameters:

`\footnotesize` : Size-changing command for footnotes.

`\footnotesep` : The height of a strut placed at the beginning of every footnote.

`\skip\footins` : Space between main text and footnotes. The rule separating footnotes from text occurs in this space. This space lies above the strut of height `\footnotesep` which is at the beginning of the first footnote.

`\footnoterule` : Macro to draw the rule separating footnotes from text. It is executed right after a `\vspace` of `\skip\footins`. It should take zero vertical space—i.e., it should to a negative skip to compensate for any positive space it occupies. (See PLAIN.TEX.)

`\interfootnotelinepenalty` : Interline penalty for footnotes.

`\thefootnote` : In usual LaTeX style, produces the footnote number. If footnotes are to be numbered within pages, then the document style file must include an `\@addtoreset` command to cause the footnote counter to be reset when the page counter is stepped. This is not a good idea, though, because the counter will not always be reset in time to ensure that the first footnote on a page is footnote number one.

`\@thefnmark` : Holds the current footnote’s mark—e.g., `\dag` or `'1'` or `'a'`.

`\@mpfnnumber` : A macro that generates the numbers for `\footnote` and `\footnotemark` commands. It == `\thefootnote` outside a minipage environment, but can be changed inside to generate numbers for `\footnote`’s.

`\@makefnmark` : A macro to generate the footnote marker from `\@thefnmark`. The default definition was `\hbox{$\@thefnmark$}`.

This is now replaced by  
`\textsuperscript{\@thefnmark}`

`\@makefntext{NOTE}` :  
 Must produce the actual footnote, using `\@thefnmark` as the mark of the footnote and NOTE as the text. It is called when effectively inside a `\parbox`, with `\hsize = \columnwidth`.  
 For example, it might be as simple as  
`$\@thefnmark$ NOTE`

In a minipage environment, `\footnote` and `\footnotetext` are redefined so that

- (a) they use the counter `mpfootnote`
- (b) the footnotes they produce go at the bottom of the minipage.

The switch is accomplished by letting `\@mpfn == footnote` or `mpfootnote` and `\thempfn == \thefootnote` or `\thempfootnote`, and by redefining `\@footnotetext` to be `\@mpfootnotetext` in the minipage.

```

\footnote{NOTE} ==
BEGIN
  \stepcounter{\@mpfn}
  begingroup
    \protect == \noexpand
    \@thefnmark :=G eval (\thempfn)
  endgroup
  \@footnotemark
  \@footnotetext{NOTE}
END

\footnote[NUM]{NOTE} ==
BEGIN
  begingroup
    \protect == \noexpand
    counter \@mpfn :=L NUM
    \@thefnmark :=G eval (\thempfn)
  endgroup
  \@footnotemark
  \@footnotetext{NOTE}
END

\footnotemark ==
BEGIN \stepcounter{footnote}
  begingroup
    \protect == \noexpand
    \@thefnmark :=G eval(\thefootnote)
  endgroup
  \@footnotemark
END

\footnotemark[NUM] ==
BEGIN
  begingroup
    footnote counter :=L NUM
    \protect == \noexpand
    \@thefnmark :=G eval(\thefootnote)
  endgroup
  \@footnotemark
END

```

```

\@footnotemark ==
  BEGIN
    \leavevmode
    IF hmode THEN \@x@sf := \the\spacefactor FI
    \@makefnmark      % put number in main text
    IF hmode THEN \spacefactor := \@x@sf FI
  END

\footnotetext      ==
  BEGIN begingroup \protect == \noexpand
    \@thefnmark :=G eval (\thempfn)
  endgroup
  \@footnotetext
  END

\footnotetext[NUM] ==
  BEGIN begingroup counter \@mpfn :=L NUM
    \protect == \noexpand
    \@thefnmark :=G eval (\thempfn)
  endgroup
  \@footnotetext
  END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

`\footins` L<sup>A</sup>T<sub>E</sub>X does use the same insert for footnotes as PLAIN.

```

390 \newinsert\footins

```

L<sup>A</sup>T<sub>E</sub>X leaves these initializations for the `\footins` insert.

```

391 \skip\footins=\bigskipamount % space added when footnote is present
392 \count\footins=1000 % footnote magnification factor (1 to 1)
393 \dimen\footins=8in % maximum footnotes per page

```

*(End of definition for \footins.)*

`\footnoterule` L<sup>A</sup>T<sub>E</sub>X keeps PLAIN T<sub>E</sub>X's `\footnoterule` as the default.

```

394 \def\footnoterule{\kern-3\p@
395   \hrule \@width 2in \kern 2.6\p@} % the \hrule is .4pt high

```

*(End of definition for \footnoterule.)*

`\thefootnote`

```

396 \@definecounter{footnote}
397 \def\thefootnote{\@arabic\c@footnote}

```

*(End of definition for \thefootnote.)*

`\thempfootnote` The default display for the footnote counter in minipages is to use italic letters. We use `\itshape` not `\textit` as the latter would add an italic correction.

```

398 \@definecounter{mpfootnote}
399 \def\thempfootnote{{\itshape\@alph\c@mpfootnote}}

```

*(End of definition for \thempfootnote.)*

`\@makefnmark` Default definition.

```
400 %\def\@makefnmark{\hbox{$\sim\@thefnmark}\m@th$}%
401 \def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}
```

*(End of definition for \@makefnmark.)*

`\textsuperscript` This command provides superscript characters in the current text font. It's implementation might change!!!

```
402 \DeclareRobustCommand*\textsuperscript[1]{%
403   \@textsuperscript{\selectfont#1}}
```

*(End of definition for \textsuperscript.)*

`\@textsuperscript` This command should not be used directly, but may be used to define other commands `\textsuperscript`, `\@makefnmark`. #1 should always start with a font selection command, to activate the font size switch.

```
404 \</2ekernel>
405 \<*2ekernel | latexrelease>
406 \<latexrelease>\IncludeInRelease{2020/10/01}%
407 \<latexrelease>          {\@textsuperscript}{superscript baseline}%
408 \def\@textsuperscript#1{%
409   {\m@th\ensuremath{\sim\hbox{\fontsize\sf@size\sf@size#1}}}}
410 \</2ekernel | latexrelease>
411 \<latexrelease>\EndIncludeInRelease
412 \<latexrelease>\IncludeInRelease{0000/00/00}%
413 \<latexrelease>          {\@textsuperscript}{superscript baseline}%
414 \<latexrelease>
415 \<latexrelease>\def\@textsuperscript#1{%
416 \<latexrelease>   {\m@th\ensuremath{\sim\hbox{\fontsize\sf@size\z@#1}}}}
417 \<latexrelease>\EndIncludeInRelease
418 \<*2ekernel>
```

*(End of definition for \@textsuperscript.)*

`\textsubscript`

```
419 \</2ekernel>
420 \<latexrelease>\IncludeInRelease{2015/01/01}%
421 \<latexrelease>          {\textsubscript}{\textsubscript}%
422 \<*2ekernel | latexrelease>
423 \DeclareRobustCommand*\textsubscript[1]{%
424   \@textsubscript{\selectfont#1}}%
425 \</2ekernel | latexrelease>
426 \<latexrelease>\EndIncludeInRelease
427 \<latexrelease>\IncludeInRelease{0000/00/00}%
428 \<latexrelease>          {\textsubscript}{\textsubscript}%
429 \<latexrelease>\let\textsubscript\@undefined
430 \<latexrelease>\EndIncludeInRelease
431 \<*2ekernel>
```

*(End of definition for \textsubscript.)*

`\@textsubscript`

```
432 </2ekernel>
433 <*2ekernel | latexrelease>
434 <latexrelease>\IncludeInRelease{2020/10/01}%
435 <latexrelease>          {\@textsubscript}{subscript baseline}%
436 \def\@textsubscript#1{%
437   {\m@th\ensuremath{_{\mbox{\fontsize\sf@size\sf@size#1}}}}
438 </2ekernel | latexrelease>
439 <latexrelease>\EndIncludeInRelease

440 <latexrelease>\IncludeInRelease{2015/01/01}%
441 <latexrelease>          {\@textsubscript}{subscript baseline}%
442 <latexrelease>
443 <latexrelease>\def\@textsubscript#1{%
444 <latexrelease>   {\m@th\ensuremath{_{\mbox{\fontsize\sf@size\z@#1}}}}
445 <latexrelease>\EndIncludeInRelease
446 <latexrelease>\IncludeInRelease{0000/00/00}%
447 <latexrelease>          {\@textsubscript}{subscript baseline}%
448 <latexrelease>\let\@textsubscript\@undefined
449 <latexrelease>\EndIncludeInRelease
450 <*2ekernel>

(End of definition for \@textsubscript.)
```

`\footnotesep`

```
451 \newdimen\footnotesep

(End of definition for \footnotesep.)
```

`\footnote`

```
452 \def\footnote{\@ifnextchar[\@xfootnote{\stepcounter\@mpfn
453   \protected@xdef\@thefnmark{\thempfn}%
454   \@footnotemark\@footnotetext}}

(End of definition for \footnote.)
```

`\@xfootnote`

```
455 \def\@xfootnote[#1]{%
456   \begingroup
457   \csname c@\@mpfn\endcsname #1\relax
458   \unrestored@protected@xdef\@thefnmark{\thempfn}%
459   \endgroup
460   \@footnotemark\@footnotetext}

(End of definition for \@xfootnote.)
```

`\@footnotetext`

```
461 </2ekernel>
462 <*2ekernel | latexrelease>
463 <latexrelease>\IncludeInRelease{2021/11/15}%
464 <latexrelease>          {\@footnotetext}{footnotetext tagging}%
465 \long\def\@footnotetext#1{\insert\footins{%
466   \reset@font\footnotesize
467   \interlinepenalty\interfootnotelinepenalty
468   \splittopskip\footnotesep
```

```

469 \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
470 \hsize\columnwidth \@parboxrestore
471 \def\@currentcounter{footnote}%
472 \protected@edef\@currentlabel{%
473 \csname p@footnote\endcsname\@thefnmark
474 }%
475 \color@begingroup
476 \makefnintext{%
477 \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
478 \par
479 \color@endgroup}}}%
480 </2ekernel | latexrelease>
481 <latexrelease>\EndIncludeInRelease

482 <latexrelease>\IncludeInRelease{2021/06/01}%
483 <latexrelease> \{\@footnotetext\}{footnotetext tagging}%
484 <latexrelease>\long\def\@footnotetext#1{\insert\footins{%
485 <latexrelease> \reset@font\footnotesize
486 <latexrelease> \interlinepenalty\interfootnotelinepenalty
487 <latexrelease> \splittopskip\footnotesep
488 <latexrelease> \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
489 <latexrelease> \hsize\columnwidth \@parboxrestore
490 <latexrelease> \protected@edef\@currentlabel{%
491 <latexrelease> \csname p@footnote\endcsname\@thefnmark
492 <latexrelease> }%
493 <latexrelease> \color@begingroup
494 <latexrelease> \makefnintext{%
495 <latexrelease> \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
496 <latexrelease> \par
497 <latexrelease> \color@endgroup}}}%
498 <latexrelease>\EndIncludeInRelease

499 <latexrelease>\IncludeInRelease{0000/00/00}%
500 <latexrelease> \{\@footnotetext\}{footnotetext tagging}%
501 <latexrelease>
502 <latexrelease>\long\def\@footnotetext#1{\insert\footins{%
503 <latexrelease> \reset@font\footnotesize
504 <latexrelease> \interlinepenalty\interfootnotelinepenalty
505 <latexrelease> \splittopskip\footnotesep
506 <latexrelease> \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
507 <latexrelease> \hsize\columnwidth \@parboxrestore
508 <latexrelease> \protected@edef\@currentlabel{%
509 <latexrelease> \csname p@footnote\endcsname\@thefnmark
510 <latexrelease> }%
511 <latexrelease> \color@begingroup
512 <latexrelease> \makefnintext{%
513 <latexrelease> \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
514 <latexrelease> \color@endgroup}}}%
515 <latexrelease>
516 <latexrelease>\EndIncludeInRelease
517 <*2ekernel>

```

*(End of definition for \@footnotetext.)*

**\footnotemark**

```

518 \def\footnotemark{%
519   \@ifnextchar[\@xfootnotemark
520     {\stepcounter{footnote}%
521     \protected@xdef\@thefnmark{\thefootnote}%
522     \@footnotemark}}

```

*(End of definition for \footnotemark.)*

**\@xfootnotemark**

```

523 \def\@xfootnotemark[#1]{%
524   \begingroup
525     \c@footnote #1\relax
526     \unrestored@protected@xdef\@thefnmark{\thefootnote}%
527   \endgroup
528   \@footnotemark}

```

*(End of definition for \@xfootnotemark.)*

**\@footnotemark**

```

529 \def\@footnotemark{%
530   \leavevmode
531   \ifhmode\edef\x@sf{\the\spacefactor}\nobreak\fi
532   \@makefnmark
533   \ifhmode\spacefactor\x@sf\fi
534   \relax}

```

*(End of definition for \@footnotemark.)*

**\footnotetext**

```

535 \def\footnotetext{%
536   \@ifnextchar [\@xfootnotenext
537     {\protected@xdef\@thefnmark{\thempfn}%
538     \@footnotetext}}

```

*(End of definition for \footnotetext.)*

**\@xfootnotenext**

```

539 \def\@xfootnotenext[#1]{%
540   \begingroup
541     \csname c@\@mpfn\endcsname #1\relax
542     \unrestored@protected@xdef\@thefnmark{\thempfn}%
543   \endgroup
544   \@footnotetext}

```

*(End of definition for \@xfootnotenext.)*

**\thempfn**

**\@mpfn**

```

545 \def\@mpfn{footnote}
546 \def\thempfn{\thefootnote}

```

*(End of definition for \thempfn and \@mpfn.)*

`\footref` This command generates a footnote mark. The value is produced by referencing a `\label` placed into a `\footnote` elsewhere (can be one in the main galley or in a minipage).

```

547 </2ekernel>
548 <*2ekernel | latexrelease>
549 <latexrelease>\IncludeInRelease{2021/06/01}%
550 <latexrelease>                {\footref}{Add footref}%
551 \def\footref#1{%
552   \begingroup
553     \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
554   \endgroup
555   \@footnotemark
556 }
557 </2ekernel | latexrelease>
558 <latexrelease>\EndIncludeInRelease

```

We don't remove it when rolling back so that packages offered it in the past do not need to alter their behavior in a rollback situation.

```

559 <latexrelease>\IncludeInRelease{0000/00/00}%
560 <latexrelease>                {\footref}{Add footref}%
561 <latexrelease>
562 <latexrelease> % \let\footref\@undefined
563 <latexrelease>
564 <latexrelease>\EndIncludeInRelease
565 <*2ekernel>

```

*(End of definition for \footref.)*

```

566 </2ekernel>

```

## File 46

# ltidxglo.dtx

## 1 Index and Glossary Generation

Index and Glossary commands.

```
\makeindex      A preamble command to turn on indexing.
\makeglossary    A preamble command to turn on making glossary entries.
  \index         Make an index entry for #1.
  \glossary      Make a glossary entry for #1.
Historical LATEX 2.09 comments (not necessarily accurate any more):
\makeindex ==
  BEGIN
    \index == BEGIN \@bsphack
              \begingroup
              \protect{X} == \string X\space
              %% added 3 Feb 87 for \index commands
              %% in \footnotes
              re-\catcode special characters
              to 'other'
              \@wrindex

  END

\@wrindex{ITEM} ==
  BEGIN
    write of {\indexentry{ITEM}{page number}}
  \endgroup
  \@esphack
  END

INITIALIZATION:

\index == BEGIN \@bsphack
          \begingroup
          re-\catcode special characters (in case '%' there)
          \@index

  END

\@index{ITEM} == BEGIN \endgroup \@esphack END

Changes made 14 Apr 89 to write \glossaryentry's instead of
\indexentry's on the .glo file.
End of historical LATEX 2.09 comments.
1 ⟨*2ekernel⟩
2 \message{index,}
```

`\makeindex`

```
3 \def\makeindex{%
4   \newwrite\@indexfile
5   \immediate\openout\@indexfile=\jobname.idx
6   \def\index{\@bsphack\beginingroup
7     \@sanitize
8     \@wrindex}\typeout
9     {Writing index file \jobname.idx}}%
```

Opening the write channel should be done only once since on some OS multiple opens are forbidden and in any case it is useless. So we turn this into a no-op after use.

```
10 \let\makeindex\@empty
11 }
12 \@onlypreamble\makeindex
```

*(End of definition for \makeindex.)*

`\@wrindex`

```
13 \def\@wrindex#1{%
14   \protected@write\@indexfile{}%
15   {\string\indexentry{#1}{\thepage}}%
16   \endgroup
17   \@esphack}
```

*(End of definition for \@wrindex.)*

`\index`

```
18 \def\index{\@bsphack\beginingroup \@sanitize\@index}
```

*(End of definition for \index.)*

`\@index`

```
19 \def\@index#1{\endgroup\@esphack}
```

*(End of definition for \@index.)*

`\makeglossary`

```
20 \def\makeglossary{%
21   \newwrite\@glossaryfile
22   \immediate\openout\@glossaryfile=\jobname.glo
23   \def\glossary{\@bsphack\beginingroup
24     \@sanitize
25     \@wrglossary}\typeout
26     {Writing glossary file \jobname.glo }}%
```

Opening the write channel should be done only once since on some OS multiple opens are forbidden and in any case it is useless. So we turn this into a no-op after use.

```
27 \let\makeglossary\@empty
28 }
29 \@onlypreamble\makeglossary
```

*(End of definition for \makeglossary.)*

`\@wrglossary`

```
30 \def\@wrglossary#1{%  
31   \protected@write\@glossaryfile{%  
32     {\string\glossaryentry{#1}{\thepage}}}%  
33   \endgroup  
34   \@esphack}
```

*(End of definition for \@wrglossary.)*

`\glossary`

```
35 \def\glossary{\@bsphack\begin@group\@sanitizel\@index}
```

*(End of definition for \glossary.)*

```
36 \endkernel
```

## File 47

# ltbibl.dtx

## 1 Bibliography Generation

A bibliography is created by the `thebibliography` environment, which generates a title such as “References”, and a list of entries. The `BIBTEX` program will create a file containing such an environment, which will be read in by the `\bibliography` command. With `BIBTEX`, the following commands will be used.

`\bibliography`      `\bibliography{<file1,file2, ...,filen>}` : specifies the bibdata files. Writes a `\bibdata` entry on the `.aux` file and tries to read in `mainfile.bbl`.

`\bibliographystyle`      `\bibliographystyle{<style>}` : Writes a `\bibstyle` entry on the `.aux` file.

`thebibliography (env.)`      The `thebibliography` environment is a list environment. To save the use of an extra counter, it should use `enumiv` as the item counter. Instead of using `\item`, items in the bibliography are produced by the following commands:

`\bibitem{<name>}` : Produces a numbered entry cited as `<name>`.

`\bibitem[<label>]{<name>}` : Produces an entry labeled by `<Label>` and cited by `<name>`.

    The former is used for bibliographies with citations like [1], [2], etc.; the latter is used for citations like [Knuth82].

    The document class must define the `thebibliography` environment. This environment has a single argument, which is the widest bibliography label— e.g., if the [Knuth67] is the widest entry, then this argument will be Knuth67. The `\thebibliography` command must begin a list environment, which the `\endthebibliography` command ends.

`\cite`      Entries are cited by the command `\cite{<name>}`.

`\nocite`      `\nocite{< citations >}` puts information on the `.aux` file that causes `BIBTEX` to include the `{< citations >}` list in the bibliography, but puts nothing in the text.

`\nocite{*}` is special: it tells `BIBTEX` to put the whole of a collection of references into the bibliography.

```
1 <*2ekernel>
2 \message{bibliography,}
```

*Historical  $\LaTeX$  2.09 comments (not necessarily accurate any more):*

### PARAMETERS

`@cite` : A macro such that `\@cite{LABEL1,LABEL2}{NOTE}` produces the output for a `\cite[NOTE]{FOO1,FOO2}` command, where entry `FOOi` is defined by `\bibitem[LABELi]{FOOi}`. The switch `@tempswa` is true if the optional `NOTE` argument is present. The default definition is :

```
\@cite{LABELS}{NOTE} ==
  BEGIN [LABELS
    IF @tempswa = T THEN , NOTE FI
  ]
END
```

`@biblabel` : A macro to produce the label in the bibliography entry. For `\bibitem[LABEL]{NAME}`, the label is

generated by \@biblabel{LABEL}. It has the default definition \@biblabel{LABEL} -> [LABEL].

#### CONVENTION

\b@F00 : The name or number of the reference created by \cite{FOO}  
E.g., if \cite{FOO} -> [17] , then \b@F00 -> 17.

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

\bibitem

```
3 \def\bibitem{\@ifnextchar[\@lbibitem\bibitem}
```

*(End of definition for \bibitem.)*

\@lbibitem

```
4 \def\@lbibitem[#1]#2{\item[\@biblabel{#1}\hfill]\if@filesw
5     {\let\protect\noexpand
6      \immediate
7      \write\@auxout{\string\bibcite{#2}{#1}}}\fi\ignorespaces}
```

*(End of definition for \@lbibitem.)*

\@bibitem

```
8 \def\@bibitem#1{\item\if@filesw \immediate\write\@auxout
9     {\string\bibcite{#1}{\the\value{\@listctr}}}\fi\ignorespaces}
```

*(End of definition for \@bibitem.)*

\bibcite

```
10 \def\bibcite{\@newlabel b}
```

*(End of definition for \bibcite.)*

\citation

```
11 \let\citation\@gobble
```

*(End of definition for \citation.)*

\cite

```
12 \</2ekernel>
13 \< *2ekernel | latexrelease>
14 \< latexrelease> \IncludeInRelease{2022/06/01}%
15 \< latexrelease> {\cite}{check for blank}%
16 \DeclareRobustCommand\cite{%
17     \@ifnextchar [{\@tempswatrue\@citex@checkblank}{\@tempswafalse\@citex@checkblank[]}]}
```

Due to the way \@for as used in \@citex behaves an empty argument to \cite did not produce any warning for a missing citation. So we now inject a command before calling \@citex that does the checking for us. It is not done in \@citex directly, because that command is altered by a number of packages/classes and this way it is more likely that the check survives.

```
18 \def\@citex@checkblank[#1]#2{%
19     \IfBlankTF {#2}%
20     {\@citex[#1]{\space}}%
21     {\@citex[#1]{#2}}%
22 }
23 \</2ekernel | latexrelease>
```

```

24 <latexrelease>\EndIncludeInRelease
25 <latexrelease>\IncludeInRelease{0000/00/00}%
26 <latexrelease>          {\cite}{check for blank}%
27 <latexrelease>
28 <latexrelease>\DeclareRobustCommand\cite{%
29 <latexrelease> \ifnextchar [{\@tempswattrue\@citex}{\@tempswafalse\@citex[]}}
30 <latexrelease>\let\@citex@checkblank\@undefined
31 <latexrelease>
32 <latexrelease>\EndIncludeInRelease
33 <*2ekernel>

```

(End of definition for \cite.)

\@citex \penalty\@m added to definition of \@citex to allow a line break after the ‘,’ in citations like [Jones80,Smith77] (Added 23 Oct 86)  
space added after the ‘,’ (21 Nov 87)

```

34 \def\@citex[#1]#2{\leavevmode
35   \let\@citea\@empty
36   \@cite{\@for\@citeb:=#2\do
37     {\@citea\def\@citea{,\penalty\@m\ }%
38     \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}}%
39   \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi

```

Using \hbox instead of \mbox is fine because of the \leavevmode above. In fact the use of a box around the citation contents is more than questionable in my view (FMi), but within 2e I have to keep that for compatibility reasons as it would probably change too many existing documents. Its main reason is to avoid hyphenation of labels such as [FOOB89] into [FOO- B89] so in certain styles it makes sense; but, for example, in author year citations it becomes more than questionable.

So Chris added yet another hook here, as suggested by, at least, Donald Arseneau. Note that this one is inside the first argument of the \@cite hook. This decouples the top-level typesetting of the citation from the details of the other business conducted here. All this really needs a complete rethink to get the right modularity.

```

40   \ifundefined{b@\@citeb}{\hbox{\reset@font\bfseries ?}}%
41   \G@refundefinedtrue
42   \@latex@warning
43     {Citation ‘\@citeb’ on page \thepage \space undefined}}%
44   {\@cite@ofmt{\csname b@\@citeb\endcsname}}}{#1}}

```

(End of definition for \@citex.)

```

\@bibdata
\@bibstyle
45 \let\@bibdata=\@gobble
46 \let\@bibstyle=\@gobble

```

(End of definition for \bibdata and \bibstyle.)

```

\bibliography
47 \def\bibliography#1{%
48   \if@filesw
49     \immediate\write\@auxout{\string\bibdata{\zap@space#1 \@empty}}%
50   \fi
51   \@input{\jobname.bbl}}

```

(End of definition for \bibliographystyle.)

\bibliographystyle

```
52 \def\bibliographystyle#1{%  
53   \ifx\@begindocumenthook\@undefined\else  
54     \expandafter\AtBeginDocument  
55   \fi  
56   {\if@filesw  
57     \immediate\write\@auxout{\string\bibstyle{#1}}%  
58   \fi}}
```

(End of definition for \bibliographystyle.)

\nocite (Added 14 Jun 85)

This puts information on the .aux file that causes BibTeX to include the citation list in the bibliography, but puts nothing in the text.

RmS 93/08/06: Made loop for \nocite like that for \citex, to get rid of leading spaces.

```
59 \</2ekernel>  
60 \<*2ekernel | latexrelease>  
61 \<latexrelease>\IncludeInRelease{2021/06/01}%  
62 \<latexrelease>          {\nocite}{Allow nocite in preamble}%  
63 \def\nocite#1{\@bsphack
```

With the implementation designed already in L<sup>A</sup>T<sub>E</sub>X 2.09 the \nocite command will not work before \begin{document} since it tries to write to the .aux file which is not open before that point. As a result the “reference” will appear on the terminal and nothing else will happen.

[This would be easy to fix, but then a document using the fix will silently fail on an older release of L<sup>A</sup>T<sub>E</sub>X, missing all citations done with \nocite. Thus we do only generate an error message and leave the fix for a L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> successor.]

Given that we are now a quarter century into using L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> there is no good reason any more do limit ourself to 2.09 considerations. So we now simply delay the \nocite if it is issued in the preamble.

```
64   \ifx\@onlypreamble\document
```

Since we are after \begin{document} we can do the citations:

```
65   \@for\@citeb:=#1\do{%  
66     \edef\@citeb{\expandafter\@firstofone\@citeb}%  
67     \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi  
68     \@ifundefined{b@\@citeb}{\G@refundefinedtrue  
69       \@latex@warning{Citation ‘\@citeb’ undefined}}{}%  
70   \else
```

But before \begin{document} we raised an error message in the past but as of 2021/05 not any longer.

```
71 %   \@latex@error{Cannot be used in preamble}\@eha
```

Instead we delay the declaration to the start of the document. We have to use a late hook for this, so that it comes after the .aux file is open for writing and after \@preamblecmds was executed to change the above test. Therefore \AtBeginDocument would still be too early.

```
72   \AddToHook{begindocument/end}[kernel]{\nocite{#1}}%  
73   \fi
```

```

74 \esphack}
75 </2ekernel | latexrelease>
76 <latexrelease>\EndIncludeInRelease

77 <latexrelease>\IncludeInRelease{0000/00/00}%
78 <latexrelease> \nocite}{Allow nocite in preamble}%
79 <latexrelease>
80 <latexrelease>\def\nocite#1{\@bsphack
81 <latexrelease> \ifx\@onlypreamble\document
82 <latexrelease> \for\citeb:=#1\do{%
83 <latexrelease> \edef\citeb{\expandafter\@firstofone\citeb}%
84 <latexrelease> \if@filesw\immediate\write\@auxout{\string\citation{\citeb}}\fi
85 <latexrelease> \ifundefined{b@\citeb}{\Grefundefinedtrue
86 <latexrelease> \@latex@warning{Citation ‘\citeb’ undefined}}{}}%
87 <latexrelease> \else
88 <latexrelease> \@latex@error{Cannot be used in preamble}\@eha
89 <latexrelease> \fi
90 <latexrelease> \esphack}
91 <latexrelease>
92 <latexrelease>\EndIncludeInRelease
93 <*2ekernel>

```

Since `\nocite{*}` should not produce a warning about undefined citation keys (see PR 557), we need to set the control sequence `‘b@*’` to something other than `\relax`. As a result `\cite{*}` will not warn either (but that never worked with BibTeX in the first place).

```

94 \expandafter\let\csname b@*\endcsname\@empty

```

*(End of definition for \nocite.)*

## 1.1 Default definitions

This hook determines the ‘relative formatting’ of the two logical parts of a citation with comment.

```

\@cite
95 \def\@cite#1#2{[#1\if@tempswa , #2\fi]}

```

*(End of definition for \@cite.)*

`\@cite@ofmt` This is, in general, a command that appears to have one argument whose value is, in the kernel, a single cs whose name is the expansion of `b@\@citeb`; the expansion of this cs will typically be some hmode material that produces the detailed typeset form of just the citations themselves.

```

96 \let\@cite@ofmt\hbox

```

*(End of definition for \@cite@ofmt.)*

```

\@biblabel
97 \def\@biblabel#1{[#1]}
98 </2ekernel>

```

*(End of definition for \@biblabel.)*

## File 48

# ltmarks.dtx

### Abstract

Marks are used to communicate information about the content of a page to the output routine. For example, in order to construct running headers, the output routine needs information about which section names are present on a page, and this information is passed to it through the mark system. However, marks may also be used for other purposes. This module provides a generalized mechanism for marks of independent classes.

## 1 Introduction

The  $\text{\TeX}$  engines offer a low-level mark mechanism to communicate information about the content of the current page to the asynchronous operating output routine. It works by placing `\mark` commands into the source document. When the material for the current page is assembled in box 255,  $\text{\TeX}$  scans for such marks and sets the commands `\topmark`, `\firstmark` and `\botmark`. The `\firstmark` receives the content of the first `\mark` seen in box 255 and `\botmark` the content of the last mark seen. The `\topmark` holds the content of the last mark seen on the previous page or more exactly the value of `\botmark` from the previous page. If there are no marks on the current page then all three are made equal to the `\botmark` from the previous page.

This mechanism works well for simple formats (such as plain  $\text{\TeX}$ ) whose output routines are only called to generate pages. It fails, however, in  $\text{\LaTeX}$  (and other more complex formats), because here the output routine is sometimes called without producing a page, e.g., when encountering a float and placing it into one of the float regions. In that case the output routine is called, determines where to place the float, alters the goal for assembling text material (if the float was added to the top or bottom region) and then it resumes collecting textual material.

As a result the `\botmark` gets updated and so `\topmark` no longer reflects the situation at the top of the next page when that page is finally boxed.

Another problem for  $\text{\LaTeX}$  was that it wanted to use several “independent” marks and in the early implementations of  $\text{\TeX}$  there was only a single `\mark` command available. For that reason  $\text{\LaTeX}$  implemented its own mark mechanism where the marks always contained two parts with their own interfaces: `\markboth` and `\markright` to set marks and `\leftmark` and `\rightmark` to retrieve them.

However, this extended mechanism (while supporting scenarios such as chapter/section marks) was far from general. The mark situation at the top of a page (i.e., `\topmark`) remained unusable and the two marks offered were not really independent of each other because `\markboth` (as the name indicates) was always setting both.

The new mechanism overcomes both issues:

- It provides arbitrarily many, fully independent named marks, that can be allocated and, from that point onwards, used.
- It offers access for each such marks to retrieve its top, first, and bottom values separately.
- Furthermore, the mechanism is augmented to give access to marks in different “regions” which may not be just full pages.

## 2 Design-level and code-level interfaces

The interfaces are mainly meant for package developers, but they are usable (with appropriate care) also in the document preamble, for example, when setting up special running headers with `fancyhdr`, etc. They are therefore available both as CamelCase commands as well as commands for use in the L3 programming layer. Both are described together below.

---

<code>\NewMarkClass</code>	<code>\NewMarkClass {&lt;class&gt;}</code>
<code>\mark_new_class:n</code>	<code>\mark_new_class:n {&lt;class&gt;}</code>

---

Declares a new `<class>` of marks to be tracked by L<sup>A</sup>T<sub>E</sub>X. Each `<class>` must be declared before it is used.

Mark classes can only be declared before `\begin{document}`.

---

<code>\InsertMark</code>	<code>\InsertMark {&lt;class&gt;} {&lt;text&gt;}</code>
<code>\mark_insert:nn</code>	<code>\mark_insert:nn {&lt;class&gt;} {&lt;text&gt;}</code>

---

Adds a mark to the current galley for the `<class>`, containing the `<text>`.

It has no effect in places in which you can't place floats, e.g., a mark inside a box or inside a footnote never shows up anywhere.

If used in vertical mode it obeys L<sup>A</sup>T<sub>E</sub>X's internal `@nobreak` switch, i.e., it does not introduce a breakpoint if used after a heading. If used in horizontal mode it doesn't handle spacing (like, for example, `\index` or `\label` does, so it should be attached to material that is typeset.

---

<code>insertmark</code>	<code>\AddToHook {insertmark} {&lt;code&gt;}</code>
-------------------------	---

---

When marks are inserted, the mark content may need some special treatment, e.g., by default `\label`, `\index`, and `\glossary` do not expand at this time (but only later if and when the mark content is actually used. In order to allow packages to augment or alter this setup there is a public hook `insertmark` that is executed at this point. It runs in a group so local modification to commands are only applied to the `<text>` argument of `\InsertMark` or `\mark_insert:nn`.

---

<code>\TopMark</code>	<code>* \TopMark</code>	<code>[(\region)]</code>	<code>{\class}</code>
<code>\FirstMark</code>	<code>* \FirstMark</code>	<code>[(\region)]</code>	<code>{\class}</code>
<code>\LastMark</code>	<code>* \LastMark</code>	<code>[(\region)]</code>	<code>{\class}</code>
<code>\mark_use_top:nn</code>	<code>* \mark_use_top:nn</code>	<code>{\region}</code>	<code>{\class}</code>
<code>\mark_use_first:nn</code>	<code>* \mark_use_first:nn</code>	<code>{\region}</code>	<code>{\class}</code>
<code>\mark_use_last:nn</code>	<code>* \mark_use_last:nn</code>	<code>{\region}</code>	<code>{\class}</code>

---

These functions expand to the appropriate mark `<text>` for the given `<class>` in the specified `<region>`. The default `<region>` in the design-level commands is `page`. Note that with the L3 layer commands there are no optional arguments, i.e., both arguments have to be provided.

**TeXhackers note:** The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the `<text>` does not expand further when appearing in an `x`-type or `e`-type argument expansion.

The “first” and “last” marks are those seen first and last in the current region/page, respectively. The “top” mark is the last mark of the `<class>` seen in an earlier region, i.e., the `<text>` what would be “current” at the very top of the region.

### Important!

The commands are only meaningful inside the output routine, in other places their result is (while not random) unpredictable due to the way L<sup>A</sup>T<sub>E</sub>X cuts text material into pages. There is, however, one exception: if you produce multiple columns using the `multicol` package, it is possible to retrieve mark values from the regions `first-column`, `last-column`, `mcol-1`, `mcol-2`,... directly after the environment has ended. This can, for example, be useful if a `multicols` has been used inside a box.

Currently, `<region>` is one of `page`, `previous-page`, `column`, `previous-column`, `first-column`, `last-column`, and `mcol-1` (first column in a `multicols`), `mcol-2` (second column in a `multicols`), up to `mcol-20` (twentieth column in a `multicols`). See section 2.2 for discussion of how these regions behave and how one can make use of them.

---

<code>\IfMarksEqualTF</code>	<code>* \IfMarksEqualTF</code>	<code>[(\region)]</code>	<code>{\class}</code>	<code>{\pos<sub>1</sub>}</code>	<code>{\pos<sub>2</sub>}</code>	<code>{\true}</code>	<code>{\false}</code>
<code>\IfMarksEqualT</code>	<code>* \mark_if_eq:nnnnTF</code>	<code>{\region}</code>	<code>{\class}</code>	<code>{\pos<sub>1</sub>}</code>	<code>{\pos<sub>2</sub>}</code>	<code>{\true}</code>	<code>{\false}</code>
<code>\IfMarksEqualF</code>	<code>* \mark_if_eq:nnnnnnTF</code>	<code>{\region<sub>1</sub>}</code>	<code>{\class<sub>1</sub>}</code>	<code>{\pos<sub>1</sub>}</code>			
<code>\mark_if_eq:nnnnTF</code>	<code>*</code>	<code>{\region<sub>2</sub>}</code>	<code>{\class<sub>2</sub>}</code>	<code>{\pos<sub>2</sub>}</code>	<code>{\true}</code>	<code>{\false}</code>	
<code>\mark_if_eq:nnnnnnTF</code>	<code>*</code>						

---

These conditionals allow you to compare the content of two marks and act based on the result. The commands work in an expansion context, if necessary.

It is quite common when programming with marks to need to interrogate conditions such as whether marks have appeared on a previous page, or if there are multiple marks present on the current page, and so on. The tests above allow for the construction of a variety of typical test scenarios, with three examples presented below.

The first two conditionals cover only the common scenarios. Both marks are picked up from the same `<region>` (by default `page`) and they have to be of the same `<class>`.<sup>41</sup> The `<posi>` argument can be either `top`, `first`, or `last`.

Important to note is that the comparison is not with respect to the textual content of the marks but whether or not they originated from the same `\InsertMark` command (or the L3 layer version `\mark_insert:nn`).

If you wish to compare marks across different regions or across different classes, you have to do it using the generic test only available in the L3 programming layer or do it manually, i.e., get the marks and then compare the values yourself.<sup>42</sup>

<sup>41</sup>If an undeclared mark class is used the tests return `true` (not an error).

<sup>42</sup>If two undeclared mark classes are compared the result is always `true`; if a declared and an undeclared

## 2.1 Use cases for conditionals

However, the basic version is enough for the following typical use cases:

**Test for at most one mark of class `myclass` on current page:** If the first and last mark in a region are the same then either there was no mark at all, or there was at most one. To test this on the current page:

```
\NewMarkClass{myclass}
\IfMarksEqualTF{myclass}{first}{last}
{ <zero or one mark> }{ <two or more marks> }
```

**Test for no mark of class `myclass` in the previous page:** If the top mark is the same as the first mark, there is no mark in the region at all. If we wanted to do this test for the previous page:

```
\IfMarksEqualTF[previous-page]{myclass}{top}{first}
{ <no marks> }{ <at least one mark> }
```

Comparing top and last would give you the same result.

**Test for zero, one, or more than one:** Combining the two tests from above you can test for zero, one or more than one mark.

```
\IfMarksEqualTF{myclass}{top}{first}
{ <no marks> }
{\IfMarksEqualTF{myclass}{first}{last}
{ <exactly one mark> }{ <more than one mark> }}
```

If you need one of such tests more often (or if you want a separate command for it for readability), then consider defining:

```
\providecommand\IfNoMarkTF[2][page]{\IfMarksEqualTF[#1]{#2}{first}{last}}
```

## 2.2 Understanding regions

If a page has just been finished then the region `page` refers to the current page and `previous-page`, as the name indicates, refers to the page before the current page. This means you are able to access mark information for the current page as well as for the page before (as long as you are inside the output routine) without the need to explicitly save that information beforehand. The `page` region is the region that is most often queried, which is why commands like `\FirstMark` use that region by default.

In single column documents the `column` is the same as the `page` region, but in two-column documents (if not produced by `multicols`), `column` refers to the current column that just got finished and `previous-column` to the one previously finished. Code for running headers is (in standard L<sup>A</sup>T<sub>E</sub>X) evaluated only after both columns have been assembled, which is another way of saying that in that case `previous-column` refers to the left column and `column` to the right column. However, to make these somewhat easier to use, there are also aliased names for these two regions: `first-column` and `last-column`.<sup>43</sup>

---

mark class is used it is always *false*.

<sup>43</sup>The region is called “last-column” not “second-column” in anticipation of extending the mechanism to multiple columns, where first and last would still make sense. There aren’t any `previous-first-column` and `previous-last-column` regions to access the corresponding columns from the previous page.

Note that you can only look backwards at already processed regions, e.g., in a `twoside` document finishing a recto (odd, right-hand) page you can access the data from the facing verso (left-hand) page, but if you are finishing a left-hand page you can't integrate data from the upcoming right-hand page. If such a scenario needs to be realized then it is necessary to save the left-hand page temporarily instead of finalizing it, process material for the right-hand page and once both are ready, attach running headers and footers and shipout out both in one go.<sup>44</sup>

The situation starts getting rather complex if you allow for multiple columns in the way they are supported by the `multicol` package. In this case you might have a variable number of “columns” on a single page to be shipped out. And even if not, then a `multicols` might start or end in the middle of the page; in either case, the regions `column` and `previous-column` become rather meaningless and you should therefore not use them.<sup>45</sup> Instead, the algorithm offers `mcol-1`, `mcol-2`, `mcol-3`, etc., to represent the columns in the `multicols` on the current page to be shipped out. If there is more than one `multicols` on the current page then in the output routine only the columns of the last one will be accessible.

These provisions cover, out of the box, a number of layouts and use cases, but obviously not all. However, more cases can be supported by storing away mark information during the processing. Here is the full algorithm:

- The `column` region is used by the “current column” that is being built (moving through all columns with `previous-column` trailing behind (to handle top marks properly).
- When the `multicols` starts, the `column` region is cleared, i.e., from that point on it looks as if there have not been any marks so far. This will make sure that the top mark in the first column is always empty.
- If the `multicols` extends beyond the current page, then the material designated for the current page is split into columns. The `column` region is used to represent each column in turn.
  - First we copy the current data from `column` to `previous-column`. Then the mark data from the current column is placed into the `column` region. Then we alias `column` to `mcol-1`.
  - These steps are repeated for all columns of the `multicols` environment.
  - Finally, the first and the last column of that page is also made available as `first-column` and `last-column`, respectively.
- All those marks inside any of the columns are also available in the `page` region. Thus, if you are interested in the top, first, or last mark of a specific class on the whole page you simply need to query for it in the `page` region.
- If the `multicols` continues across several pages then this algorithm above is repeated for each page, except that the `column` region is not cleared again. This means that the top mark of the first column of the next page will be the last mark of the last column from the previous page.

<sup>44</sup>As of now that scenario is not (yet) officially supported but it would be possible to achieve this using the shipout hooks to store the verso page and then on the next shipout use the hook to shipout both with running headers and footers attached.

<sup>45</sup>They return something, because they represent the last two columns of the `multicols` when you are inside the output routine, but that is obviously of little use.

- When the `multicols` finishes the remaining material for the current page is balanced to produce columns of roughly equal height.
- Again `column` and `previous-column` are used while this balancing happens and `mcol-1`, `mcol-2`, etc., are used to represent the column regions and `first-column` and `last-column` are set appropriately.
- Then the balanced set of columns is returned back to the page (since there may be space for further material). In addition, all marks inside that material are reinserted so that they become available in the `page` region.
- As a side effect, it is possible (and useful in certain circumstances) to query for mark classes directly after the `multicols` has ended without the need to be inside the output routine. The regions that can be queried this way are `mcol-1`, `mcol-2`, etc. (up to the number of columns the multicol had) and `first-column` and `last-column`.

## 2.3 Debugging mark code

---

<code>\DebugMarksOn</code>	<code>\DebugMarksOn ... \DebugMarksOff</code>
<code>\DebugMarksOff</code>	
<code>\mark_debug_on:</code>	Commands to turn the debugging of mark code on or off. The debugging output is
<code>\mark_debug_off:</code>	rather coarse and not really intended for normal use at this point in time.

---

## 3 Application examples

If you want to figure out if a break was taken at a specific point, e.g., whether a heading appears at the top of the page, you can do something like this:

```
\newcounter{breakcounter}
\NewMarkClass{break}
\newcommand\markedbreak[1]{\stepcounter{breakcounter}%
                           \InsertMark{break}{\arabic{breakcounter}}%
                           \penalty #1\relax
                           \InsertMark{break}{-\arabic{breakcounter}}}
```

To test if the break was taken you can test if `\TopMark{break}` is positive (taken) or negative (not taken) or zero (there was never any marked break so far). The absolute value can be used to keep track of which break it was (with some further coding).

*to be extended with additional application examples*

## 4 Legacy L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interface

Here we describe the interfaces that L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> offered since the early nineties and some minor extensions.

## 4.1 Legacy design-level and document-level interfaces

---

<code>\markboth</code>	<code>\markboth {&lt;left&gt;} {&lt;right&gt;}</code>
<code>\markright</code>	<code>\markright {&lt;right&gt;}</code>

---

L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> uses two marks which aren't fully independent. A “left” mark generated by the first argument of `\markboth` and a “right” mark generated by the second argument of `\markboth` or by the only argument of `\markright`. The command `\markboth` and `\markright` are in turn called from heading commands such as `\chaptermark` or `\sectionmark` and their behavior is controlled by the document class.

For example, in the `article` class with `twoside` in force the `\sectionmark` will issue `\markboth` with an empty second argument and `\subsectionmark` will issue `\markright`. As a result the left mark will contain chapter titles and the right mark subsection titles.

Note, however, that in one-sided documents the standard behavior is that only `\markright` is used, i.e., there will only be right-marks but no left marks!

---

<code>\leftmark</code>	<code>* \leftmark</code>
<code>\rightmark</code>	<code>* \rightmark</code>

---

These functions return the appropriate mark value from the current page and work as before, that is `\leftmark` will get the last (!) left mark from the page and `\rightmark` the first (!) right mark.

In other words they work reasonably well if you want to show the section title that is current when you are about to turn the page and also show the first subsection title on the current page (or the last from the previous page if there wasn't one). Other combinations can't be shown using this interface.

The commands are fully expandable, because this is how they have been always defined in L<sup>A</sup>T<sub>E</sub>X. However, this is of course only true if the content of the mark they return is itself expandable and does not contain any fragile material. Given that this can't be guaranteed for arbitrary content, a programmer using them in this way should use `\protected@edef` and *not* `\edef` to avoid bad surprises as far as this is possible, or use the new interfaces (`\TopMark`, `\FirstMark`, and `\LastMark`) which return the `<text>` in `\exp_not:n` to prevent uncontrolled expansion.

## 4.2 Legacy interface extensions

The new implementation adds three mark classes: `2e-left`, `2e-right` and `2e-right-nonempty` and patches `\markboth` and `\markright` slightly so that they also update these new mark classes, so that the new classes work with existing document classes.

As a result you can use `\LastMark{2e-left}` and `\FirstMark{2e-right}` instead of `\leftmark` and `\rightmark`. But more importantly, you can use any of the other retrieval commands to get a different status value from those marks, e.g., `\LastMark{2e-right}` would return the last subsection on the page (instead of the first as returned by `\rightmark`).

The difference between `2e-right` and `2e-right-nonempty` is that the latter will only be updated if the material for the mark is not empty. Thus `\markboth{title}{}` as issued by, say, `\sectionmark`, sets a `2e-left` mark with `title` and a `2e-right` mark with the empty string but does not add a `2e-right-nonempty` mark.

Thus, if you have a section at the start of a page and you would ask for `\FirstMark{2e-right}` you would get an empty string even if there are subsections on that page. But `2e-right-nonempty` would then give you the first or last subsection

on that page. Of course, nothing is simple. If there are no subsections it would tell you the last subsection from an earlier page. We therefore need comparison tools, e.g., if top and first are identical you know that the value is bogus, i.e., a suitable implementation would be

```
\IfMarksEqualTF{2e-right-nonempty}{top}{first}
{ <appropriate action if there was no real mark> }
{\FirstMark{2e-right-nonempty}}
```

## 5 Notes on the mechanism

In contrast to vanilla  $\text{\TeX}$ ,  $\varepsilon\text{-}\text{\TeX}$  extends the mark system to allow multiple independent marks. However, it does not solve the `\topmark` problem which means that  $\text{\LaTeX}$  still needs to manage marks almost independently of  $\text{\TeX}$ . The reason for this is that the more complex output routine used by  $\text{\LaTeX}$  to handle floats (and related structures) means that `\topmark(s)` remain unreliable. Each time the output routine is fired up,  $\text{\TeX}$  moves `\botmark` to `\topmark`, and while  $\varepsilon\text{-}\text{\TeX}$  extends this to multiple registers the fundamental concept remains the same. That means that the state of marks needs to be tracked by  $\text{\LaTeX}$  itself. An early implementation of this package used  $\text{\TeX}$ 's `\botmark` only to ensure the correct interaction with the output routine (this was before the  $\varepsilon\text{-}\text{\TeX}$  mechanism was even available). However, other than in a prototype implementation for  $\text{\LaTeX}3$ , this package was never made public.

The new implementation now uses  $\varepsilon\text{-}\text{\TeX}$ 's marks as they have some advantages, because with them we can leave the mark text within the galley and only extract the marks during the output routine when we are finally shipping out a page or storing away a column for use in the next page. That means we do not have to maintain a global data structure that we have to keep in sync with informational marks in the galley but can rely on everything being in one place and thus manipulations (e.g. reordering of material) will take the marks with them without a need for updating a fragile linkage.

To allow for completely independent marks we use the following procedure:

- For every type of marks we allocate a mark class so that in the output routine  $\text{\TeX}$  can calculate for each class the current top, first, and bottom mark independently. For this we use `\newmarks`, i.e., one marks register per class.
- As already mentioned firing up an output routine without shipping out a page means that  $\text{\TeX}$ 's top marks get wrong so it is impossible to rely on  $\text{\TeX}$ 's approach directly. What we do instead is to keep track of the real marks (for the last page or more generally last region) in some global variables.
- These variables are updated in the output routine at defined places, i.e., when we do real output processing but not if we use special output routines to do internal housekeeping.
- The trick we use to get correctly updated variables is the following: the material that contains new marks (for example the page to be shipped out) is stored in a box. We then use  $\text{\TeX}$  primitive box splitting functions by splitting off the largest amount possible (which should be the whole box if nothing goes really wrong). While that seems a rather pointless thing to do, it has one important side effect:  $\text{\TeX}$  sets up first and bottom marks for each mark class from the material it has split off. This way we get the first and last marks (if there have been any) from the material in the box.

- The top marks are simply the last marks from the previous page or region. And if there hasn't been a first or bottom mark in the box then the new top mark also becomes new first and last mark for that class.
- That mark data is then stored in global token lists for use during the output routine and legacy commands such as `\leftmark` or new commands such as `\TopMark` simply access the data stored in these token lists.

That's about it in a nutshell. Of course, there are some details to be taken care of—those are discussed in the implementation sections.

## 6 Public interfaces for packages such as **multicol**

The functions in this section are public so that packages can make use of them. However, this must be done with great care, e.g., `\mark_update_structure_from_material:nn` updates the global mark structure and can therefore be used only in places where such an update is meaningful, e.g., in special output routines. Elsewhere, a change to the mark structure would break the whole mechanism and querying the marks would return incorrect data.

---

```
\mark_update_structure_from_material:nn \mark_update_structure_from_material:nn {<region>} {<material with
marks>}
```

---

Helper function that inspects the marks inside the second argument and assigns new mark values based on that to the `<region>` given in the first argument. For this it first copies the mark structure from `<region>` to `previous-<region>` and then takes all last mark values currently in the region and makes them the new top mark values. Finally it assigns new first and last values for all mark classes based on what was found in the second argument.

As a consequence, the allowed values for `<region>` are `page` and `column` because only they have `previous-...` counterparts.

Another important aspect to keep in mind is that marks are recognized only if they appear on the top level, e.g., if we want to process material stored in boxes we need to put it unboxed (using `\unvcopy` etc.) into the second argument.

---

```
\mark_copy_structure:nn \mark_copy_structure:nn {<alias>} {<source>}
```

---

Helper function that copies all mark values in the `<source>` region to `<alias>`, i.e., make the structures identical. Used to update the `previous-...` structures inside `\mark_update_structure_from_material:nn` and `first-column` and `last-column` structures inside the internal commands `\__mark_update_singlecol_structures:` or `\__mark__update_dbcol_structures:`.

---

```
\mark_set_structure_to_err:n \mark_set_structure_to_err:n {<region>}
```

---

Helper function that sets all mark values in the `<region>` to an error message. This is currently used for `last-column` at times where using marks from it would be questionable/wrong, i.e., when we have just processed the first column in a two-column document.

---

```
\mark_clear_structure:n \mark_clear_structure:n {\region}
```

---

Helper function that sets all mark values in the  $\langle\textit{region}\rangle$  to empty. This is currently used for `column` when a multicol environment starts; this is because it wouldn't make sense if the top mark in the first column returned the last mark from a previous multicol (which may have been much earlier, with intermediate material).

---

```
\mark_get_marks_for_reinsertion:nnn \mark_get_marks_for_reinsertion:nnn {\source}
                                     \token-list-var for collecting first marks
                                     \token-list-var for collecting last marks
```

---

Helper function for extracting marks that would otherwise get lost, for example when they are hidden inside a box. This helper does not update mark structures and can therefore be used outside the output routine as well.

It collects all the top-level marks from inside the  $\langle\textit{source}\rangle$  and then adds suitable `\mark_insert:nn` commands to each of the two token lists. These token lists can then be executed at the right place to reinsert the marks, e.g., directly after the box. This is, for example, going to be used<sup>46</sup> by `multicol` when a short balanced `multicols` is returned to the galley for typesetting.

If the  $\langle\textit{source}\rangle$  consists of a single vertical box (plus possibly followed by some glue but nothing else) then the box is unpacked and the top-level marks are collected from its content. However, if it is not a vertical box or there are other data then nothing is unpacked and you have to do the unpacking yourself to get at the marks inside.

It is quite likely that one only needs a single token list for returning the `\mark_insert:nn` statements. If that is the case this command may change to take only two arguments.

## 7 Internal functions for the standard output routine of L<sup>A</sup>T<sub>E</sub>X

The functions in this section are tied to the output routine and used in the interface to L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> and perhaps at some later time within a new output routine for L<sup>A</sup>T<sub>E</sub>X. They are not (yet) meant for general use and are therefore made internal, even though we already use them in `multicol`. Internal means that `@@` automatically gets replaced in the code (and in the documentation) so we have to give it a suitable value.

<sub>1</sub>  $\langle\textit{@@=mark}\rangle$

---

```
\__mark_update_singlecol_structures: \__mark_update_singlecol_structures:
```

---

L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> integration function in case we are doing single column layouts. It assumes that the page content is already stored in `\@outputbox` and processes the marks inside that box. It is called as part of `\@opcol`.

---

```
\__mark_update_dbcol_structures: \__mark_update_singlecol_structures:
```

---

L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> integration function mark used when we are doing double column documents. It assumes that the page content is already stored in `\@outputbox` and processes the marks inside that box. It then does different post-processing depending on the start of the switch `\if@firstcolumn`. If we are in the second column it also has to update page marks, otherwise it only updates column marks. It too is called as part of `\@opcol`.

---

<sup>46</sup>Probably not before 2025, though.

## 8 The Implementation

```

2 <*2ekernel | latexrelease>
3 \ExplSyntaxOn
4 <latexrelease>\NewModuleRelease{2022/06/01}{ltmarks}
5 <latexrelease>                {Marks-handling}

```

### 8.1 Allocating new mark classes

---

`\g__mark_classes_seq` A list holding all the mark classes that have been declared.

```

6 \seq_new:N \g__mark_classes_seq

```

`\mark_new_class:n` A mark class is created by initializing a number of data structures. First, we get a register number to refer to the mark class. The new mark class is then added to the `\g__mark_classes_seq` sequence to be able to easily loop over all classes. Finally a number of top-level global token lists are declared that hold various versions of the mark for access.

`\__mark_new_class:nn`

```

7 \cs_new_protected:Npn \mark_new_class:n #1
8 {
9   \seq_if_in:NnTF \g__mark_classes_seq {#1}
10     {
11       \msg_error:nnn { mark } { class-already-defined }
12       {#1}
13     }
14     { \__mark_new_class:nn {#1} }
15 }

```

This is only available in the preamble.

```

16 \@onlypreamble \mark_new_class:n

```

The internal command carries out the necessary allocations.

```

17 \cs_new_protected:Npn \__mark_new_class:nn #1
18 {
19   <*trace>
20   \__mark_debug:n { \iow_term:x { Marks:~new~mark:~#1~\msg_line_context: } }
21   </trace>

```

Use the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interface for now as the L3 programming layer doesn't have one for marks yet.

```

22 \exp_args:Nc \newmarks {c__mark_class_ #1 _mark}

```

Remember the new class in the sequence.

```

23 \seq_gput_right:Nn \g__mark_classes_seq {#1}
24 \__mark_init_region:nn {page}{#1}

```

For the page region we also keep track of the previous-page.

```

25 \__mark_init_region:nn {previous-page}{#1}

```

Same game for column and previous-column

```

26 \__mark_init_region:nn {column}{#1}
27 \__mark_init_region:nn {previous-column}{#1}

```

But for columns we also allocate token lists for the alias regions `first-column` and `last-column`.

```
28 \__mark_init_region:nn {first-column}{#1}
29 \__mark_init_region:nn {last-column}{#1}
```

To support multiple columns produced by the `multicol` package, we preallocate twenty alias regions (since this is the number of columns that `multicol` supports as a maximum). They are filled by copying the current column into the appropriate `mcol-...`

```
30 %fmi \__mark_init_region:nn {mcol}{#1}
31 %fmi \__mark_init_region:nn {previous-mcol}{#1}
32 \__mark_init_region:nn {mcol-1}{#1}
33 \__mark_init_region:nn {mcol-2}{#1}
34 \__mark_init_region:nn {mcol-3}{#1}
35 \__mark_init_region:nn {mcol-4}{#1}
36 \__mark_init_region:nn {mcol-5}{#1}
37 \__mark_init_region:nn {mcol-6}{#1}
38 \__mark_init_region:nn {mcol-7}{#1}
39 \__mark_init_region:nn {mcol-8}{#1}
40 \__mark_init_region:nn {mcol-9}{#1}
41 \__mark_init_region:nn {mcol-10}{#1}
42 \__mark_init_region:nn {mcol-11}{#1}
43 \__mark_init_region:nn {mcol-12}{#1}
44 \__mark_init_region:nn {mcol-13}{#1}
45 \__mark_init_region:nn {mcol-14}{#1}
46 \__mark_init_region:nn {mcol-15}{#1}
47 \__mark_init_region:nn {mcol-16}{#1}
48 \__mark_init_region:nn {mcol-17}{#1}
49 \__mark_init_region:nn {mcol-18}{#1}
50 \__mark_init_region:nn {mcol-19}{#1}
51 \__mark_init_region:nn {mcol-20}{#1}
```

We also have to initialize the `saved-column` region that is used in `multicol`. Perhaps we should have a `\NewMarkRegion` so that it would be possible for other packages to add further regions. But let's wait and see if there is a real use case for new regions before making the interface more general.

```
52 \__mark_init_region:nn {saved-column}{#1}
53 }
```

*(End of definition for `\mark_new_class:n` and `\__mark_new_class:nn`. This function is documented on page 1015.)*

`\__mark_init_region:nn` For each class (#2) and region (#1), we need three token lists: one for top, first, and last.  
`\c__mark_empty_tl` The default value to be returned is “empty”.

```
54 \cs_new_protected:Npn \__mark_init_region:nn #1 #2 {
55 \tl_new:c { g__mark_#1_top_ #2 _tl }
56 \tl_new:c { g__mark_#1_first_ #2 _tl }
57 \tl_new:c { g__mark_#1_last_ #2 _tl }
58 \tl_gset_eq:cN { g__mark_#1_top_ #2 _tl } \c__mark_empty_tl
59 \tl_gset_eq:cN { g__mark_#1_first_ #2 _tl } \c__mark_empty_tl
60 \tl_gset_eq:cN { g__mark_#1_last_ #2 _tl } \c__mark_empty_tl
61 }
```

All marks will have an identification in the form of a number<sup>47</sup> that is incremented each time a mark insertion happens; therefore the initial empty values should also have such a number, so that data extraction will be uniform.

```
62 \tl_const:Nn \c__mark_empty_tl { \__mark_value:nn{0}{} }
```

(End of definition for `\__mark_init_region:nn` and `\c__mark_empty_tl`.)

## 8.2 Updating mark structures

```
\l__mark_box
\l__mark_ii_box
\g__mark_tmp_tl
\g__mark_new_top_tl
```

For some operations we need two temporary private boxes and two private global token lists.

```
63 \box_new:N \l__mark_box
64 \box_new:N \l__mark_ii_box
65 \tl_new:N \g__mark_tmp_tl
66 \tl_new:N \g__mark_new_top_tl
```

(End of definition for `\l__mark_box` and others.)

```
\__mark_extract_and_handle_marks:nn
```

This is the main macro to extract and handle marks inside some vertical material. It is used by `\mark_update_structure_from_material:nn` (for updating the mark structure for a region based on the marks found) and by `\mark_get_marks_for_reinsertion:nnn` (for extracting marks from some material and prepare for reinserting them later (e.g., out of a box that is placed as a box into the main galley)).

```
67 \cs_new_protected:Npn \__mark_extract_and_handle_marks:nn #1#2 {
```

This macro expects code to handle extracted marks in its first argument and vertical material (not boxed or just consisting of a single vertical box) as its second. It extracts top-level mark information from `#2`, stores them as split marks and then calls `#1` to make use of this information.

If it finds a forced break in the material it removes it and then restarts the attempt without it.

We start with a group to keep most changes local.

```
68 \group_begin:
```

Getting the first and last marks out of the material in `#2` is done by putting the material in a box and then doing a split operation to the maximum size possible (which hopefully gets us all of the content).<sup>48</sup> Because this action is used only to get the mark values, we don't want any underfull box warnings so we (locally) turn those off.

```
69 \dim_set_eq:NN \tex_splitmaxdepth:D \c_max_dim
70 \int_set_eq:NN \tex_vbadness:D \c_max_int
71 \dim_set_eq:NN \tex_vfuzz:D \c_max_dim
```

There is a further complication: if the material contains infinite shrinking glue then a `\vsplit` operation will balk with a low-level error. Now pages or columns, which are our main concern here, can't have such infinite shrinkage if they are cut straight from the galley, however the use of `\enlargethispage` actually does add some at the very bottom (and also wraps the whole page into a box by itself, so if we leave it this way then a) we get this error and b) we don't see any marks because they are hidden one level down).

<sup>47</sup>There are a few cases where special identification strings are used, e.g., `2.09-compat`.

<sup>48</sup>With normal column material cut from the main galley we should always get all material in one go, but in certain situations, for example, in a `multicols` environment that contains some `\columnbreaks` a single split operation will not be enough. Thus, this is something we need to handle.

Another possible issue are packages or user code that place stray `\vboxes` directly into the main galley (an example is `marginnote` that attaches its marginals in this way). If such boxes end up as the last item on the page we should not unpack them.

All these issues need to be handled, which is done in `\__mark_prepare_and_extract:nn`.

```
72 \__mark_prepare_and_extract:nn {#1} {#2}
```

Once all mark classes have been processed, the data structures are updated and we can close the group, which undoes our local changes and retains only the global ones.

```
73 \group_end:
74 }
```

(End of definition for `\__mark_extract_and_handle_marks:nn`.)

`\__mark_prepare_and_extract:nn` This macro does the dirty work. It is not directly integrated in `\__mark_extract_and_handle_marks:nn` because we may have to call it recursively if we find forced breaks.

```
75 \cs_new_protected:Npn \__mark_prepare_and_extract:nn #1#2 {
```

To handle the `\enlargethispage` case we do an `\unskip` to get rid of any glue that is present at the very end of the material and also check if we have then a `\vbox` as the last item and if so unpack that too, but only under certain conditions, see below. All this is temporary done in a group, just for getting the marks out, so it doesn't affect the final page production.

```
76 \vbox_set:Nn \l__mark_box
77 {
78   #2
79   \tex_unskip:D
80   \box_set_to_last:N \l__mark_box
```

After having removed the last box from the current list (if there was one) we check whether the vertical list is now empty. If not, then the last box is definitely not the one from `\enlargethispage` and so we can, and should, leave it alone. Otherwise we check if this last box is a `\vbox`.

```
81 \int_compare:nNnT \tex_lastnodetype:D < 0
82 {
83   \box_if_vertical:NT \l__mark_box
```

If it is, we unpack the box.

```
84 { \vbox_unpack:N \l__mark_box }
85 }
```

If it wasn't a `\vbox`, it was either an `\hbox` or there was no box. Given that we are only interested in the marks we don't need put it back in that case.

```
86 }
```

We are now ready to `\vsplit` the box to get at the marks. If the box contains some infinite negative glue the `TEX` will produce an error complaining about it but it will correctly find the split marks. Given that we can't prevent that error, we hide it from the user and ensure that `TEX` doesn't stop. The error message still shows in the log, but even that is mitigated as best as possible—see the definition of `\__mark_vbox_set_split_to_maxdimen:NN` for the tricks employed.

```
87 \__mark_vbox_set_split_to_maxdimen:NN \l__mark_ii_box \l__mark_box
```

After splitting we check if there is anything left in `\l__mark_box`. If not then the above split has set some split marks that we can then use to finish the extraction:

```

88   \box_if_empty:NTF \l__mark_box
89   { #1 }

If we have a remainder after the split then this means that there was some forced break
in the material. We get rid of that by combining the content of the two boxes and restart.

90   {
91   (*trace)
92   \__mark_debug:n { \iow_term:x
93   { Marks:~ mark~ extraction~needs~ recursion~
94   \msg_line_context: } }
95   (/trace)
96   \__mark_prepare_and_extract:nn {#1}
97   { \vbox_unpack:N \l__mark_ii_box
98   \vbox_unpack:N \l__mark_box }
99   }
100  }
```

(End of definition for `\__mark_prepare_and_extract:nn`.)

`\__mark_vbox_set_split_to_maxdimen:NN`

Split a box to get at its marks without pausing even if T<sub>E</sub>X is producing an error message because of infinite negative glue in the box. If there is such an error we ensure that it only shows up in the log but not on the terminal.

With a recent T<sub>E</sub>X engine that knows the primitive `\ignoreprimitiveerror` we can turn this error into a warning (simply by setting this primitive to the value 1).

```

101 \if_cs_exist:N \tex_ignoreprimitiveerror:D

102 \cs_new_protected:Npn \__mark_vbox_set_split_to_maxdimen:NN #1#2 {
103   \tl_set:Nc \l__mark_saved_parameters_tl
104   { \tex_ignoreprimitiveerror:D
105     \int_use:N \tex_ignoreprimitiveerror:D
106     \scan_stop:
107   }
108   \tex_ignoreprimitiveerror:D 1 \scan_stop:
109   \vbox_set_split_to_ht:NNn #1 #2 { \c_max_dim }
110   \l__mark_saved_parameters_tl
111 }
```

With older T<sub>E</sub>X engines we have to make use of David's hack below to render the error (fairly) harmless and prevent T<sub>E</sub>X from stopping. But, of course, the above solution is better because jumping over the error with a local change to the interaction mode still means that T<sub>E</sub>X thinks there was an error in the run so the return code is no longer 0 (and that might affect workflows that want to test for this).

```

112 \else:
```

The nice low-level hack by DPC records in the `.log` that a glue shrinkage error is harmless.

We disguise `\c_max_dim` in an odd looking csname, which then shows up as part of the display of an error message if that error happens. This csname forms part of the error display so what you get is something like

```

! Infinite glue shrinkage found in box being split.
<argument> Infinite shrink error above ignored !
1. ... }
```

which hopefully makes it clear that the error is harmless and should be ignored by the reader of the .log.

```
113 \cs_set_eq:cN {\Infinite~shrink~error~above~ignored~!}\c_max_dim
```

The whole definition of `\__mark_vbox_set_split_to_maxdimen:NN` below is fully expanded, so we have to use a lot of `\exp_not:N` commands to prevent expansion where necessary.

```
114 \cs_new_protected:Npx \__mark_vbox_set_split_to_maxdimen:NN #1#2 {
```

We start by saving the current interaction and escape char settings.

```
115   \tl_set:Nc \exp_not:N \l__mark_saved_parameters_tl
116   {
117     \tex_interactionmode:D
118     \exp_not:N \int_use:N \tex_interactionmode:D \scan_stop:
119     \tex_escapechar:D
120     \exp_not:N \int_use:N \tex_escapechar:D \scan_stop:
121   }
```

Then we change them so that no escape char is printed in the error message (accounts for the missing backslash in front of `Infinite shrink ...`) and we set the interaction to `\nonstopmode` so that the error (if any) just goes into the .log file and T<sub>E</sub>X doesn't stop at that point.

```
122   \tex_escapechar:D      -1 \scan_stop:
123   \tex_interactionmode:D 0 \scan_stop:
```

Then we do the splitting of the box to `\c_max_dim` to get at the marks. This may generate the error we are worried about, i.e., if the box contains infinite negative glue. However, T<sub>E</sub>X makes this glue finite and continues, which means we get our split marks which is really all we care about.

```
124   \tex_setbox:D #1 \tex_vsplit:D #2 to
```

The `\use:n` may seem pointless, and it is to some extent, but we need it to get our disguised `\c_max_dim` displayed properly as part of the error message if there is one. Without it, the display would show only part of what we want it to show (try it).

```
125     \exp_not:N \use:n {
126       \use:c{\Infinite~shrink~error~above~ignored~!}
127     }
```

Finally, we change the escape char and the interaction mode back to what it was before:

```
128   \exp_not:N \l__mark_saved_parameters_tl
129 }
130 \fi:
```

*(End of definition for \\_\_mark\_vbox\_set\_split\_to\_maxdimen:NN.)*

`\l__mark_saved_parameters_tl` The temporary variable used for resetting escape char and interaction mode.

```
131 \tl_new:N \l__mark_saved_parameters_tl
```

*(End of definition for \l\_\_mark\_saved\_parameters\_tl.)*

`\mark_update_structure_from_material:nn` This function updates the mark structures of a region. The first argument is the region to update and second argument receives the material that holds the marks. Out of this material we extract the first and last marks for all classes (if there are any) to do the assignments.

```
132 \cs_new_protected:Npn \mark_update_structure_from_material:nn #1#2 {
133   \__mark_extract_and_handle_marks:nn
```

Once the marks can be extracted we update the structure from the split marks (code in `\_mark_update_structure_from_splitmarks:n`).

```

134     { \_mark_update_structure_from_splitmarks:n {#1} }
135     { #2 }
136 }

```

(End of definition for `\mark_update_structure_from_material:nn`. This function is documented on page 1022.)

This macro is called after we have done a `\tex_vsplit:D` operation and the mark data is in the split marks.

```

137 \cs_new_protected:Npn \_mark_update_structure_from_splitmarks:n #1 {

```

The first thing we do is to copy the current region structure to `previous-...`; this leaves the current structure untouched so we can update it class by class (as is necessary).

```

138   \mark_copy_structure:nn { previous-#1 } {#1}

```

After this action we can get first and last marks of the various classes through `\tex_splitfirstmarks:D` and `\tex_splitbotmarks:D`. So now we loop over all classes stored in `\g__mark_classes_seq`.

```

139   \seq_map_inline:Nn \g__mark_classes_seq
140   {

```

First action: get the last mark from the previous region, i.e., `previous-#1`. But because it is also still inside `#1`, at the moment we use that to construct the name because this is a tiny bit faster. Given that we need this value in various assignments we store it away which avoids unnecessary further csname generations.

```

141       \tl_gset_eq:Nc \g__mark_new_top_tl { g__mark_#1_last_##1_tl }

```

This will first of all become the new top mark for the current class.

```

142       \tl_gset_eq:cN { g__mark_#1_top_##1_tl } \g__mark_new_top_tl

```

Next action is to get ourselves the new last mark from the material supplied.

```

143       \tl_gset:Nc \g__mark_tmp_tl
144       { \tex_splitbotmarks:D \use:c { c__mark_class_##1_mark } }

```

If this mark doesn't exist then obviously neither does the first mark, so both become the last mark from the previous region. We have to be a little careful here: something like `\mark_insert:nn{foo}{}` adds an “empty” mark that should not be confused with no mark at all. But no mark in our material will result in `\g__mark_tmp_tl` being fully empty. This is why we have to make sure that “empty” from `\mark_insert:nn` only appears to be empty when typeset but fails the next test (see below how this is done).

```

145       \tl_if_empty:NTF \g__mark_tmp_tl
146       {
147           \tl_gset_eq:cN { g__mark_#1_last_ ##1_tl }
148           \g__mark_new_top_tl
149           \tl_gset_eq:cN { g__mark_#1_first_##1_tl }
150           \g__mark_new_top_tl
151       }

```

If it wasn't empty, i.e., if it had a real value then we use this value for our new last mark instead.

```

152       {
153           \tl_gset_eq:cN { g__mark_#1_last_##1_tl } \g__mark_tmp_tl

```

Because we had a last mark we also have a first mark (which might be the same, but might be not), so we pick that up and assign it to the appropriate token list. This explains why we first checked for the last mark because that makes the processing faster in case there is none.

```

154         \tl_gset:co { g__mark_#1_first_##1_tl }
155         {
156             \tex_splitfirstmarks:D
157             \use:c { c__mark_class_##1_mark }
158         }
159     }
160 }
161 }

```

(End of definition for `\__mark_update_structure_from_splitmarks:n`.)

`\mark_get_marks_for_reinsertion:nNN`

This function extracts the marks from the material in the first argument but it does not update any the mark structures. Instead, it collects the marks in the token lists given as the second and third argument, in such a way that they can be reinserted by just executing the token lists.<sup>49</sup>

```

162 \cs_new_protected:Npn \mark_get_marks_for_reinsertion:nNN #1#2#3 {

```

First we clear the temporary token lists as we haven't seen any marks yet.

```

163   \tl_gclear:N \g__mark_first_marks_tl
164   \tl_gclear:N \g__mark_last_marks_tl

```

Then we extract all top-level marks, thereby filling the token lists with suitable `\mark_insert:nn` calls.

```

165   \__mark_extract_and_handle_marks:nn

```

The first argument holds the code used for filling the token lists and the second holds the material from which all marks should be extracted.

```

166   \__mark_get_from_splitmarks:
167   { #1 }

```

Finally, we copy the updated (or not updated) temporary token lists to the two that have been supplied when the function was called. By convention “get” operations return their values in local variables and `\__mark_extract_and_handle_marks:nn` runs in a group, which is why we have to use global temporary variables for collecting.

```

168   \tl_set_eq:NN #2 \g__mark_first_marks_tl
169   \tl_set_eq:NN #3 \g__mark_last_marks_tl
170 }

```

(End of definition for `\mark_get_marks_for_reinsertion:nNN`. This function is documented on page 1023.)

`\__mark_get_from_splitmarks:`

This function is called after we have done a `\vsplit` to update the split marks. It loops through all mark classes to find out if there are marks for this class and if so updates the global tls used for collecting.

```

171 \cs_new_protected:Npn \__mark_get_from_splitmarks: {
172   \seq_map_inline:Nn \g__mark_classes_seq
173   {

```

<sup>49</sup>It is probably enough to collect everything in a single token list as long as we put the first marks first and the last marks last). But for extra flexibility, I currently use 2 token lists. This might change when it is really clear that this is never needed.

First we to get the last mark for the current class from the material supplied.

```

174 \tl_gset:No \g__mark_tmp_tl
175 { \tex_splitbotmarks:D \use:c { c__mark_class_##1_mark } }

```

If this mark doesn't exist then obviously first mark doesn't either, so we do nothing (other than issuing some debugging info).

We have to be a little careful here: something like `\mark_insert:nn{foo}{}` adds an “empty” mark that we should not confuse with the case where there is no mark at all.

When there is no mark at all we get a truly empty `\g__mark_tmp_tl` as a result. This is why we have to make sure that an “empty” mark generated with `\mark_insert:nn` only appears to be empty when it is typeset, but fails the next test (see below how this is done).

```

176 \tl_if_empty:NTF \g__mark_tmp_tl
177 {
178   (*trace)
179   \__mark_debug:n { \iow_term:x { Marks:~no~ marks~
180     for~ class~ '##1'~\msg_line_context: } }
181   </trace>
182 }

```

If it wasn't empty, i.e., if it had a real value then we use this value for our new last mark instead. This means we put an appropriate `\mark_insert:nn` statement into `\g__mark_last_marks_tl`.

```

183 {
184   (*trace)
185   \__mark_debug:n { \iow_term:x { Marks:~ extract~ last~

```

The mark content in `\g__mark_tmp_tl` may contain arbitrary code that may react badly if it is expanded in a write. So we better avoid that expansion, otherwise debugging might generate spurious errors when turned on.

```

186   mark~ for~ class~ '##1'~ =~ \exp_not:o \g__mark_tmp_tl } }
187 </trace>
188 \tl_gput_right:Ne \g__mark_last_marks_tl
189 { \mark_insert:nn {##1} { \__mark_drop_id:o { \g__mark_tmp_tl } } }

```

Because we had a last mark we also have a first mark (which might be the same, but might not be), so we pick that up and add it to the `\g__mark_first_marks_tl` token list. This explains why we first checked for the last mark because that makes the processing faster in case there is none.

```

190 (*trace)
191 \__mark_debug:n { \iow_term:x {
192   Marks:~ extract~ first~ mark~ for~ class~ '##1'~ =~

```

Again no expansion for the mark content.

```

193   \exp_not:o {
194     \tex_splitfirstmarks:D
195     \use:c { c__mark_class_##1_mark }
196   }
197 } }
198 </trace>
199 \tl_gput_right:Ne \g__mark_first_marks_tl
200 { \mark_insert:nn {##1}
201   {

```

We better drop the id from the returned value otherwise they will accumulate in the marks when reinserted.

```

202             \__mark_drop_id:o {
203                 \tex_splitfirstmarks:D
204                 \use:c { c__mark_class_##1_mark }
205             }
206         }
207     }
208 }
209 }
210 }

```

(End of definition for \\_\_mark\_get\_from\_splitmarks:.)

\g\_\_mark\_first\_marks\_tl These are two global temporary variables used in the code above.  
\g\_\_mark\_last\_marks\_tl

```

211 \tl_new:N \g__mark_first_marks_tl
212 \tl_new:N \g__mark_last_marks_tl

```

(End of definition for \g\_\_mark\_first\_marks\_tl and \g\_\_mark\_last\_marks\_tl.)

**\mark\_copy\_structure:nn** This function copies the structure for one region to another, e.g., from page to previous-page above, or later from column to first-column, etc.

```

213 \cs_new_protected:Npn \mark_copy_structure:nn #1#2 {

```

This requires a simple loop through all mark classes copying the token list from one name to the next.

```

214   \seq_map_inline:Nn \g__mark_classes_seq
215   {
216       \tl_gset_eq:cc { g__mark_ #1_top_   ##1_tl }
217                   { g__mark_ #2_top_   ##1_tl }
218       \tl_gset_eq:cc { g__mark_ #1_first_ ##1_tl }
219                   { g__mark_ #2_first_ ##1_tl }
220       \tl_gset_eq:cc { g__mark_ #1_last_  ##1_tl }
221                   { g__mark_ #2_last_  ##1_tl }
222   }
223 }

```

(End of definition for \mark\_copy\_structure:nn. This function is documented on page 1022.)

**\mark\_clear\_structure:n** This function sets the structure of one region back to an initial state, so that all classes return an empty value if queried.

```

224 \cs_new_protected:Npn \mark_clear_structure:n #1 {

```

This requires a simple loop through all mark classes.

```

225   \seq_map_inline:Nn \g__mark_classes_seq
226   {
227       \tl_gset_eq:cN { g__mark_ #1_top_   ##1_tl }
228                   \c__mark_empty_tl
229       \tl_gset_eq:cN { g__mark_ #1_first_ ##1_tl }
230                   \c__mark_empty_tl
231       \tl_gset_eq:cN { g__mark_ #1_last_  ##1_tl }
232                   \c__mark_empty_tl
233   }
234 }

```

(End of definition for `\mark_clear_structure:n`. This function is documented on page 1023.)

```
\mark_set_structure_to_err:n A slight variation is to install a fixed error message as the value.
  \__mark_error:n
235 \cs_new_protected:Npn \mark_set_structure_to_err:n #1 {
236   \seq_map_inline:Nn \g__mark_classes_seq
237     {
238     \tl_gset:ce { g__mark_ #1 _top_   ##1 _tl } { \__mark_value:nn{?}{\__mark_error:nn {#1}}
239     \tl_gset:ce { g__mark_ #1 _first_ ##1 _tl } { \__mark_value:nn{?}{\__mark_error:nn {#1}}
240     \tl_gset:ce { g__mark_ #1 _last_  ##1 _tl } { \__mark_value:nn{?}{\__mark_error:nn {#1}}
241     }
242 }
```

Given that this is used in only one place, we could hardwire the argument which would be a bit more compact, but who knows, perhaps we end up with another reason to use this error command elsewhere, so for now we keep the argument.

```
243 \cs_new_protected:Npn \__mark_error:nn #1#2 {
244   \msg_error:nnnn { mark } { invalid-use } {#1} {#2}
245 }
```

(End of definition for `\mark_set_structure_to_err:n` and `\__mark_error:n`. This function is documented on page 1022.)

### 8.3 Placing and retrieving marks

`\mark_insert:nn` This function puts a mark for some `<class>` at the current point.

```
246 \cs_new_protected:Npn \mark_insert:nn #1#2
247 {
248   \seq_if_in:NnTF \g__mark_classes_seq {#1}
249   {
```

We need to pass the evaluated argument into the mark but protected commands should not expand including those protected using the `\protect` approach of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. We also disable `\label` and the like.<sup>50</sup>

At this point the code eventually should get a public (and a kernel) hook instead of a set of hardwired settings.

```
250     \group_begin:
```

Within the group we alter some comments, e.g. `\label` or `\index`, to do the right at this point. This is done in the kernel hook `\@kernel@before@insertmark` which is followed by the public hook `insertmark` that can be used by packages to augment or alter that setup as necessary.

```
251     \@kernel@before@insertmark
252     \hook_use:n { insertmark }
253     \unrestored@protected@xdef \g__mark_tmp_tl
254     {
```

To ensure that marks are unique we insert a hidden sequence marker at the beginning of the content of the mark containing the sequence number of the mark.

```
255         \__mark_value:nn{ \int_use:N\g__mark_int }{#2}
256     }
257 < *trace>
258     \__mark_debug:n{ \iow_term:x { Marks:~ set~#1~<--
```

<sup>50</sup>Straight copy from `latex.ltx` but is this even correct? At least a label in a running header makes little sense if it get set several times! Maybe that needs looking at in the 2e kernel.

```

259         '\tl_to_str:V \g__mark_tmp_tl' ~ \msg_line_context: } }
260 \trace>
261 \tex_marks:D \use:c { c__mark_class_ #1 _mark }
262 {

```

Here is the trick to avoid truly empty marks: if the result from the above processing is empty we add something which eventually becomes empty, but not immediately; otherwise we just put `\g__mark_tmp_tl` in.

```

263 % This is no longer needed with 1.0f
264 % \tl_if_empty:NTF \g__mark_tmp_tl
265 % { \exp_not:n { \prg_do_nothing: } }
266 % { \exp_not:o { \g__mark_tmp_tl } }
267 \exp_not:o { \g__mark_tmp_tl }
268 }
269 \group_end:

```

A mark introduces a possible break point and in certain situations that should not happen in vertical mode in L<sup>A</sup>T<sub>E</sub>X. This may need some checking and possibly cleanup ....

```

270 \if@nobreak\ifvmode\nobreak\fi\fi
271 }

```

If the mark class was not known, raise an error.

```

272 {
273 \msg_error:nnx { mark } { unknown-class }
274 { \tl_to_str:n {#1} }
275 }
276 }

```

*(End of definition for `\mark_insert:nn`. This function is documented on page 1015.)*

`\__mark_value:nn` A hidden marker is placed into every mark added by `\mark_insert:nn`. It will not show up in the output but its argument (a counter value that is incremented) makes all marks unique so the test for “equal” is not fooled by two different marks having the same mark text.

```

277 \cs_new_protected:Npn \__mark_value:nn #1#2 { #2 }

```

*(End of definition for `\__mark_value:nn`.)*

`\@kernel@before@insertmark` By default `\label`, `\index`, and `\glossary` do nothing when the mark is inserted.

```

insertmark 278 \int_new:N \g__mark_int
279 \cs_new:Npn \@kernel@before@insertmark {
280 \cs_set_eq:NN \label \scan_stop:
281 \cs_set_eq:NN \index \scan_stop:
282 \cs_set_eq:NN \glossary \scan_stop:

```

We count each mark and use that to place a hidden marker in front of the mark text. To ensure that there is no overflow (very unlikely but you never know) we restart every 100000 marks. Thus, if somebody puts more than that number of marks on a single page you could construct a scenario in which that approach fails.

```

283 \int_compare:nNnTF \g__mark_int < {99999}
284 { \int_gincr:N \g__mark_int }
285 { \int_gzero:N \g__mark_int }
286
287 }

```

The public hook to augment the setup.

```
288 \hook_new:n {insertmark}
```

(End of definition for \@kernel@before@insertmark and insertmark.)

`\mark_use_top:nn` To retrieve the first, last or top region mark, we grab the appropriate value stored in the corresponding token list variable and pass its contents back. These functions should be used only in output routines and only after `\mark_update_structure_from_material:nn` has acted, otherwise their value will be wrong.

```
289 \cs_new:Npn \mark_use_first:nn #1#2 { \__mark_use_check:nnn { g__mark_#1_first_#2_tl } {#1} {#2} }
290 \cs_new:Npn \mark_use_last:nn #1#2 { \__mark_use_check:nnn { g__mark_#1_last_#2_tl } {#1} {#2} }
291 \cs_new:Npn \mark_use_top:nn #1#2 { \__mark_use_check:nnn { g__mark_#1_top_#2_tl } {#1} {#2} }
```

If used with an unknown class or region these commands will generate an error. If that happens in an expandable context then the error generation is delayed (e.g., if used in a `\section`) and happens when the code is finally used in typesetting, e.g., in the TOC or a running header. If used in a `\typeout` you only see something like `\__mark_error:n{page}`. This is not too good, but probably better than low-level errors, I guess, and I don't want to use an expandable error because of the size restrictions in such error messages.

```
292 \cs_new:Npn \__mark_use_check:nnn #1#2#3 {
293   \tl_if_eq:cNTF {#1} \relax
294     { \__mark_error:nn {#2} {#3} }
295     { \__mark_drop_id:v {#1} }
296 }
```

Each mark starts with an id and while the id does not print it is nevertheless better to remove it when returning the mark, so that downstream manipulation of the data doesn't have to deal with it. This is what the `\exp_not:o` accomplishes.

```
297 \cs_new:Npn \__mark_drop_id:n #1 { \exp_not:o { #1 } }
298 \cs_generate_variant:Nn \__mark_drop_id:n { o, v }
```

(End of definition for `\mark_use_top:nn`, `\mark_use_first:nn`, and `\mark_use_last:nn`. These functions are documented on page 1016.)

## 8.4 Comparing mark values

`\mark_if_eq:nnnnTF` Test if in a given region (`#1`) for a given class (`#2`) the marks in position `#3` and `#4` (top, first, or last) are identical

```
299 \prg_new_conditional:Npnn \mark_if_eq:nnnn #1#2#3#4 { T , F , TF }
300 {
301   \tl_if_eq:ccTF { g__mark_ #1 _#3_ #2 _tl }
302     { g__mark_ #1 _#4_ #2 _tl }
303     \prg_return_true:
304     \prg_return_false:
305 }
```

The fully general test (with two triplets of the form `<region>`, `<class>`, and `<position>`) is this:

```
306 \prg_new_conditional:Npnn \mark_if_eq:nnnnnn #1#2#3#4#5#6 { T , F , TF }
307 {
308   \tl_if_eq:ccTF { g__mark_ #1 _#3_ #2 _tl }
309     { g__mark_ #4 _#6_ #5 _tl }
310     \prg_return_true:
311 }
```

```

311             \prg_return_false:
312     }

```

(End of definition for `\mark_if_eq:nnnnTF` and `\mark_if_eq:nnnnnnTF`. These functions are documented on page [1016](#).)

## 8.5 Messages

Mark errors are L<sup>A</sup>T<sub>E</sub>X kernel errors:

```

313 \prop_gput:Nnn \g_msg_module_type_prop { mark } { LaTeX }
314 \msg_new:nnnn { mark } { class-already-defined }
315   { Mark~class~'#1'~already~defined }
316   {
317     \c__msg_coding_error_text_tl
318     LaTeX~was~asked~to~define~a~new~mark~class~called~'#1':~
319     this~mark~class~already~exists.
320     \c__msg_return_text_tl
321   }
322 \msg_new:nnnn { mark } { unknown-class }
323   { Unknown~mark~class~'#1'. }
324   {
325     \c__msg_coding_error_text_tl
326     LaTeX~was~asked~to~manipulate~a~mark~of~class~'#1',~
327     but~this~class~of~marks~does~not~exist.
328   }

```

The next error can also happen if the mark class is unknown, so this should perhaps be separated into two different errors.

```

329 \msg_new:nnnn { mark } { invalid-use }
330   { Mark~region~'#1'~not~usable~or~class~'#2'~unknown }
331   {
332     \c__msg_coding_error_text_tl
333     The~region~'#1'~is~either~not~known~or~data~for~it~
334     still~needs~to~be~assembled,~e.g.,~last~column~
335     while~building~the~first~column.~
336     Also~possible:~the~class~name~'#2'~is~misspelled.
337     \c__msg_return_text_tl
338   }

```

## 8.6 Debugging the mark structures

Code and commands in this section are not final, it needs more experimentation to see what kind of tracing information is going to be useful in practice. For now the tracing is mainly meant to be used for code testing and not so much for application testing.

It is quite likely that the commands and the behavior of the tracing might change in the future once we gained some experience with it.

```

\g__mark_debug_bool Holds the current debugging state.
339 \bool_new:N \g__mark_debug_bool

```

(End of definition for `\g__mark_debug_bool`.)

```

\mark_debug_on: Turns debugging on and off by redefining \__mark_debug:n.
\mark_debug_off:
\__mark_debug:n
\__mark_debug_gset:
340 \cs_new_eq:NN \__mark_debug:n \use_none:n
341 \cs_new_protected:Npn \mark_debug_on:
342 {
343   \bool_gset_true:N \g__mark_debug_bool
344   \__mark_debug_gset:
345 }
346 \cs_new_protected:Npn \mark_debug_off:
347 {
348   \bool_gset_false:N \g__mark_debug_bool
349   \__mark_debug_gset:
350 }
351 \cs_new_protected:Npn \__mark_debug_gset:
352 {
353   \cs_gset_protected:Npx \__mark_debug:n ##1
354   { \bool_if:NT \g__mark_debug_bool {##1} }
355 }

```

(End of definition for \mark\_debug\_on: and others. These functions are documented on page 1019.)

\DebugMarksOn CamelCase commands for debugging.

```

\DebugMarksOff
356 \cs_new_eq:NN \DebugMarksOn \mark_debug_on:
357 \cs_new_eq:NN \DebugMarksOff \mark_debug_off:

```

(End of definition for \DebugMarksOn and \DebugMarksOff. These functions are documented on page 1019.)

\\_\_mark\_class\_status:nnn Shows the mark values across all regions for one mark class (#2).

The first argument gives some *info* to help in identifying where the command was called, the second is the class and the third holds the number of mcol-... we should display: inside a multicols environment this will be \col@number, in L<sup>A</sup>T<sub>E</sub>X's normal output routines it will be 0.

```

358 <*trace>
359 \cs_new_protected:Npn \__mark_class_status:nnn #1#2#3 {
360   \typeout{ Marks:~#2~ #1:}
361   \__mark_region_status:nnn {#2}{ page~ (previous) } { previous-page }
362   \__mark_region_status:nnn {#2}{ page~ (current)~ } { page }
363   \__mark_region_status:nnn {#2}{ column~ (previous) }{ previous-column }
364   \__mark_region_status:nnn {#2}{ column~ (current)~ }{ column }
365   \__mark_region_status:nnn {#2}{ column~ (first) } { first-column }
366   \__mark_region_status:nnn {#2}{ column~ (last)~ } { last-column }

```

Then finish by displaying a subset of the mcol-... regions: none (0) in the standard L<sup>A</sup>T<sub>E</sub>X output routine and \col@number within a multicols environment.

```

367   \int_step_inline:nn {#3}
368   {
369     \__mark_region_status:nnn {#2}{ column~ (##1)~ } { mcol-##1 }
370   }
371 }

```

(End of definition for \\_\_mark\_class\_status:nnn.)

`\__mark_region_status:nnn` Display the top, first, and last mark of a region unless none of them exist or all of them are empty.

```

372 \cs_new_protected:Npn \__mark_region_status:nnn #1#2#3 {
373   \group_begin:
374   \cs_set:Npn \__mark_value:nn ##1##2{ \exp_not:n{ {##1} ~ ##2 } }
375   \tl_if_exist:cT { g__mark_#3_last_ #1 _tl }
376   {
377     \tl_if_eq:cNF { g__mark_#3_last_ #1 _tl } \c__mark_empty_tl
378     {
379       \typeout{\@spaces #2 =
380         ~|~ \use:c { g__mark_#3_top_ #1 _tl } ~|~
381         \use:c { g__mark_#3_first_ #1 _tl } ~|~
382         \use:c { g__mark_#3_last_ #1 _tl } ~|
383       }
384     }
385   }
386   \group_end:
387 }

```

*(End of definition for \\_\_mark\_region\_status:nnn.)*

`\__mark_status:nn` Show a snapshot of all mark class values across all regions. The first argument is a string to identify the output, the second argument is the number of `mcol-...` regions to show. Outside of a `multicols` environment this is normally set to 0.

```

388 \cs_new_protected:Npn \__mark_status:nn #1#2
389 {
390   \seq_map_inline:Nn \g__mark_classes_seq
391   { \__mark_class_status:nnn {#1} {##1} {#2} }
392 }
393 </trace>

```

*(End of definition for \\_\_mark\_status:nn.)*

`\ShowMarksAt` Debugging helper that displays a snapshot of all known mark structures. The first argument is a text string that is displayed to help identifying when the snapshot was made. The optional second one determines how many `mcol-...` regions are displayed (by default 4).

This may not stay like this (or at all), which is why it isn't yet documented as an official command.

```

394 \NewDocumentCommand \ShowMarksAt {m O{4}} { {
395   <*trace>
396   \__mark_debug:n { \__mark_status:nn {#1}{#2} }
397   </trace>
398 }

```

*(End of definition for \ShowMarksAt.)*

## 8.7 Designer-level interfaces

`\NewMarkClass` These two are identical to the L3 programming layer commands.

`\InsertMark`

```

399 \cs_new_eq:NN \NewMarkClass \mark_new_class:n
400 \@onlypreamble \NewMarkClass
401 \cs_new_eq:NN \InsertMark \mark_insert:nn

```

(End of definition for `\NewMarkClass` and `\InsertMark`. These functions are documented on page 1015.)

`\TopMark` `\FirstMark` `\LastMark` The following commands take an optional argument that defaults to page. There is no checking that the region is actually valid. If not there is simply an empty return.

```

402 \NewExpandableDocumentCommand \FirstMark { 0{page} m }
403     { \mark_use_first:nn {#1}{#2} }
404 \NewExpandableDocumentCommand \LastMark { 0{page} m }
405     { \mark_use_last:nn {#1}{#2} }
406 \NewExpandableDocumentCommand \TopMark { 0{page} m }
407     { \mark_use_top:nn {#1}{#2} }

```

(End of definition for `\TopMark`, `\FirstMark`, and `\LastMark`. These functions are documented on page 1016.)

`\IfMarksEqualTF` `\IfMarksEqualT` `\IfMarksEqualF` We only provide CamelCase commands for the case with one region (optional) and one class. One could think of also providing a version for the general case with several optional arguments, but use cases for this are most likely rare, so not done yet.

```

408 \NewExpandableDocumentCommand \IfMarksEqualTF {0{page}mmm} {
409     \mark_if_eq:nnnnTF {#1}{#2}{#3}{#4}
410 }
411 \NewExpandableDocumentCommand \IfMarksEqualT {0{page}mmm} {
412     \mark_if_eq:nnnnT {#1}{#2}{#3}{#4}
413 }
414 \NewExpandableDocumentCommand \IfMarksEqualF {0{page}mmm} {
415     \mark_if_eq:nnnnF {#1}{#2}{#3}{#4}
416 }

```

(End of definition for `\IfMarksEqualTF`, `\IfMarksEqualT`, and `\IfMarksEqualF`. These functions are documented on page 1016.)

## 9 L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> integration

### 9.1 Core L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> integration

`\_mark\_update\_singlecol\_structures:` This command updates the mark structures if we are producing a single column document.

```

417 \cs_new_protected:Npn \_mark\_update\_singlecol\_structures: {

```

First we update the page region (which also updates the previous-page).

The `\@outputbox` is normally in `\vbox` in L<sup>A</sup>T<sub>E</sub>X but we can't take that for granted (an `amsmath` test document changed it to an `\hbox` just to trip me up) so we are a little careful with unpack now.

```

418     \box_if_vertical:NTF \@outputbox
419     {
420         \mark_update_structure_from_material:nn {page}
421         { \vbox_unpack:N \@outputbox }
422     }
423     {
424         \mark_update_structure_from_material:nn {page}
425         { \hbox_unpack:N \@outputbox }
426     }

```

Then we provide the necessary updates for the aliases.

```

427 \mark_copy_structure:nn {previous-column}{previous-page}
428 \mark_copy_structure:nn {column}{page}
429 \mark_copy_structure:nn {first-column}{page}
430 \mark_copy_structure:nn {last-column}{page}
431 <{*trace}
432 % move this into status itself?
433 \__mark_debug:n
434 {
435     \__mark_status:nn
436     { in~ OR~ (
437         \legacy_if:nTF {@twoside}
438         { twoside-
439             \int_if_odd:nTF \c@page
440             { odd }{ even }
441         }
442         { oneside }
443     )
444 }
445 {0}
446 }
447 </trace>
448 }

```

(End of definition for \\_\_mark\_update\_singlecol\_structures:.)

\\_\_mark\_update\_dbcol\_structures: This commands handles the updates if we are doing two-column pages.

```

449 \cs_new_protected:Npn \__mark_update_dbcol_structures: {

```

First we update the column and previous-column regions using the material assembled in \@outputbox.

```

450 \box_if_vertical:NTF \@outputbox
451 {
452     \mark_update_structure_from_material:nn {column}
453     { \vbox_unpack:N \@outputbox }
454 }
455 {
456     \mark_update_structure_from_material:nn {column}
457     { \hbox_unpack:N \@outputbox }
458 }

```

How we have to update the alias regions depends on whether or not \@opcol was called to process the first column or to produce the completed page

```

459 \legacy_if:nTF {@firstcolumn}
460 {

```

If we are processing the first column then column is our first-column and there is no last-column yet, so we make those an error.

```

461     \mark_copy_structure:nn {first-column}{column}
462     \mark_set_structure_to_err:n {last-column}
463 }
464 {

```

If we produce the completed page then the `first-column` is the same as the new `previous-column`. However, the structure should already be correct if you think about it (because it was set to `column` last time which is now the `previous-column`), thus there is no need to make an update.

```
465 % \mark_copy_structure:nn {first-column}{previous-column}
```

However, we now have a proper `last-column` so we assign that.

```
466 \mark_copy_structure:nn {last-column}{column}
```

What now remains doing is to update the `page` and `previous-page` regions. For this we have to copy the settings in `page` into `previous-page` and then update `page` such that the top and first marks are taken from the `first-column` region and the last marks are taken from the `last-column` region. All this has to be done for all mark classes so we loop over our sequence.

Note that one loop is needed if we arrange the copy statements in a suitable way.

```
467 \seq_map_inline:Nn \g__mark_classes_seq
468 {
```

The `previous-page` updates need to come before the updates for `page` region because otherwise the values to copy are already overwritten. necessary values.

```
469 \tl_gset_eq:cc { g__mark_previous-page_top_ ##1 _tl }
470 { g__mark_page_top_ ##1 _tl }
471 \tl_gset_eq:cc { g__mark_previous-page_first_ ##1 _tl }
472 { g__mark_page_first_ ##1 _tl }
473 \tl_gset_eq:cc { g__mark_previous-page_last_ ##1 _tl }
474 { g__mark_page_last_ ##1 _tl }
```

To update the top we only have to copy what is in `first-column`:

```
475 \tl_gset_eq:cc { g__mark_page_top_ ##1 _tl }
476 { g__mark_first-column_top_ ##1 _tl }
477
```

Updating the `first` mark for the `page` region is more complicated. We first have to find out if there is any mark in the first column (this can be done by comparing the top and the `first` mark of that region).

```
478 \tl_if_eq:ccTF { g__mark_first-column_top_ ##1 _tl }
479 { g__mark_first-column_first_ ##1 _tl }
480 {
```

If there is no mark in the first column we copy the first mark of the last column. If that doesn't contain a mark we still get the right result because the first mark is then equal to the top mark.

```
481 \tl_gset_eq:cc { g__mark_page_first_ ##1 _tl }
482 { g__mark_last-column_first_ ##1 _tl }
483 }
484 {
```

On the other hand, if there is a mark in the first column we copy over the `first` mark from that column.

```
485 \tl_gset_eq:cc { g__mark_page_first_ ##1 _tl }
486 { g__mark_first-column_first_ ##1 _tl }
487 }
```

The logic for the `last` page mark is again simple, we can just copy the value in the `last` mark of the last column. If that column doesn't contain any marks, then the value in `last` will be automatically the same as the `last` from the first column.

```

488         \tl_gset_eq:cc { g__mark_page_last_      ##1 _tl }
489                     { g__mark_last-column_last_ ##1 _tl }
490     }
491 }
492 < *trace >
493     \__mark_debug:n
494     {
495         \__mark_status:nn
496         { in~ OR~ (
497             \legacy_if:nTF {@twoside}
498             { twoside-
499                 \int_if_odd:nTF \c@page
500                 { odd }{ even }
501             }
502             { oneside }
503             \space
504             \legacy_if:nTF {@firstcolumn}
505             { first~ }{ second~ }
506             column )
507         }
508         {0}
509     }
510 < /trace >
511 }

```

(End of definition for `\__mark_update_dbcol_structures:.`)

## 9.2 Other L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> output routines

This section will cover support for packages that alter the L<sup>A</sup>T<sub>E</sub>X output routine (as necessary). The support for multicols (for now) is handled directly in that package.

```

512 < @@= >

```

`\@expl@@mark@update@singlecol@structures@@`

```

513 \cs_new_eq:NN \@expl@@mark@update@singlecol@structures@@
514 \__mark_update_singlecol_structures:

```

(End of definition for `\@expl@@mark@update@singlecol@structures@@.`)

`\@expl@@mark@update@dblcol@structures@@`

```

515 \cs_new_eq:NN \@expl@@mark@update@dblcol@structures@@
516 \__mark_update_dbcol_structures:

```

(End of definition for `\@expl@@mark@update@dblcol@structures@@.`)

### 9.3 Rollback information

```
517 <latexrelease>\IncludeInRelease{0000/00/00}{ltmarks}%  
518 <latexrelease>                                {Undo~Marks~handling}  
519 <latexrelease>
```

We keep the interface commands around even if we roll back in case they are used in packages that don't roll back. Not likely to do a lot of good, but then there is not much we can do, but this at least they won't give unknown csname errors.

```
520 <latexrelease>\DeclareRobustCommand \NewMarkClass[1]{}  
521 <latexrelease>\DeclareRobustCommand \InsertMark[2]{}  
522 <latexrelease>\RenewExpandableDocumentCommand \FirstMark { 0{ } m } { }  
523 <latexrelease>\RenewExpandableDocumentCommand \LastMark { 0{ } m } { }  
524 <latexrelease>\RenewExpandableDocumentCommand \TopMark { 0{ } m } { }  
525 <latexrelease>\RenewExpandableDocumentCommand \IfMarksEqualTF { 0{ } mmm }{ }  
526 <latexrelease>
```

Same here, this avoided extra roll back code in the OR.

```
527 <latexrelease>\let \@expl@@mark@update@singlecol@structures@@ \relax  
528 <latexrelease>\let \@expl@@mark@update@dblcol@structures@@ \relax  
529 <latexrelease>  
530 <latexrelease>  
531 <latexrelease>\EndModuleRelease  
532 \ExplSyntaxOff  
533 </2ekernel | latexrelease>  
  
Reset module prefix:  
534 <@@=>
```

## File 49

# ltpage.dtx

## 1 Page styles and related commands

### 1.1 Page Style Commands

`\pagestyle{<style>}` : sets the page style of the current and succeeding pages to *style*

`\thispagestyle{<style>}` : sets the page style of the current page only to *style*.

To define a page style *style*, you must define `\ps@style` to set the page style parameters.

### 1.2 How a page style makes running heads and feet

The `\ps@...` command defines the macros `\@oddhead`, `\@oddfoot`, `\@evenhead`, and `\@evenfoot` to define the running heads and feet. (See output routine.) To make headings determined by the sectioning commands, the page style defines the commands `\chaptermark`, `\sectionmark`, etc., where `\chaptermark{<text>}` is called by `\chapter` to set a mark. The `\...mark` commands and the `\...head` macros are defined with the help of the following macros.

(All the `\...mark` commands should be initialized to no-ops.)

### 1.3 marking conventions

L<sup>A</sup>T<sub>E</sub>X extends T<sub>E</sub>X's `\mark` facility by producing two kinds of marks a 'left' and a 'right' mark, using the following commands:

`\markboth{<left>}{<right>}` : Adds both marks.

`\markright{<right>}` : Adds a 'right' mark.

`\leftmark` : Used in the output routine, gets the current 'left' mark. Works like T<sub>E</sub>X's `\botmark`.

`\rightmark` : Used in the output routine, gets the current 'right' mark. Works like T<sub>E</sub>X's `\firstmark`. The marking commands work reasonably well for right marks 'numbered within' left marks—e.g., the left mark is changed by a `\chapter` command and the right mark is changed by a `\section` command. However, it does produce somewhat anomalous results if 2 `\markboth`'s occur on the same page.

Commands like `\tableofcontents` that should set the marks in some page styles use a `\@mkboth` command, which is `\let` by the `\pagestyle` command (`\ps@...`) to `\markboth` for setting the heading or to `\@gobbletwo` to do nothing.

1 <\*2ekernel>

`\pagestyle` User command to set the page style for this and following pages.

```
2 \def\pagestyle#1{%
3   \@ifundefined{ps@#1}%
4     \undefinedpagestyle
5     {\@nameuse{ps@#1}}}
```

(End of definition for `\pagestyle`.)

`\thispagestyle` User command to set the page style for this page only.

```

6 \def\thispagestyle#1{%
7   \ifundefined{ps@#1}%
8     \undefinedpagestyle
9     {\global\@specialpagetrue\gdef\@specialstyle{#1}}}
```

*(End of definition for \thispagestyle.)*

`\ps@empty` The empty page style: No head or foot line.

```

10 \def\ps@empty{%
11   \let\@mkboth\@gobbletwo\let\@oddhead\@empty\let\@oddfoot\@empty
12   \let\@evenhead\@empty\let\@evenfoot\@empty}
```

*(End of definition for \ps@empty.)*

`\ps@plain` The plain page style: No head, centred page number in foot.

```

13 \def\ps@plain{\let\@mkboth\@gobbletwo
14   \let\@oddhead\@empty\def\@oddfoot{\reset@font\hfil\thepage
15   \hfil}\let\@evenhead\@empty\let\@evenfoot\@oddfoot}
```

*(End of definition for \ps@plain.)*

`\@leftmark` We implement `\@leftmark` and `\@rightmark` in terms of already defined commands to  
`\@rightmark` save token space. We can't get rid of them since they are sometimes used in applications.

```

16 \let\@leftmark\@firstoftwo
17 \let\@rightmark\@secondoftwo
```

*(End of definition for \@leftmark and \@rightmark.)*

```

18 </2ekernel>
19 <*2ekernel | latexrelease>
20 <latexrelease>\IncludeInRelease{2025/06/01}%
21 <latexrelease>          {\markboth}{Drop legacy mark support}%
```

`\markboth` User commands for setting L<sup>A</sup>T<sub>E</sub>X marks.

`\markright` Test for `@nobreak` added 15 Apr 86 in `\markboth` and `\markright` letting `\label` and `\index` to `\relax` added 22 Feb 86 so these commands can appear in sectioning command arguments RmS 91/06/21 Same for `\glossary`

```

22 \ExplSyntaxOn
23 \DeclareRobustCommand*\markboth[2]{%
24   \mark_insert:nn{2e-left}{#1}
25   \mark_insert:nn{2e-right}{#2}
26   \tl_if_empty:nF{#2}{ \mark_insert:nn{2e-right-nonempty}{#2} }
27 }

28 \DeclareRobustCommand*\markright[1]{%
29   \mark_insert:nn{2e-right}{#1}
30   \tl_if_empty:nF{#1}{ \mark_insert:nn{2e-right-nonempty}{#1} }
31 }
32 \ExplSyntaxOff
```

(End of definition for \markboth and \markright. These functions are documented on page 1020.)

```

33 </2ekernel | latexrelease>
34 <latexrelease>\EndIncludeInRelease
35 <latexrelease>\IncludeInRelease{2022/06/01}%
36 <latexrelease>          {\markboth}{New mark support}%
37 <latexrelease>\ExplSyntaxOn
38 <latexrelease>\DeclareRobustCommand*\markboth[2]{%
39 <latexrelease>  \begingroup
40 <latexrelease>    \let\label\relax \let\index\relax \let\glossary\relax
41 <latexrelease>    \unrestored@protected@xdef\@themark {{#1}{#2}}%
42 <latexrelease>    \@temptokena \expandafter{\@themark}%
43 <latexrelease>    \mark_insert:nn{2e-left}{#1}
44 <latexrelease>    \mark_insert:nn{2e-right}{#2}
45 <latexrelease>    \tl_if_empty:nF{#2}{ \mark_insert:nn{2e-right-nonempty}{#2} }
46 <latexrelease>    \mark{\the\@temptokena}%
47 <latexrelease>  \endgroup
48 <latexrelease>  \if@nobreak\ifvmode\nobreak\fi\fi}
49 <latexrelease>\DeclareRobustCommand*\markright[1]{%
50 <latexrelease>  \begingroup
51 <latexrelease>    \let\label\relax \let\index\relax \let\glossary\relax
52 <latexrelease>    \expandafter\@markright\@themark {#1}%
53 <latexrelease>    \@temptokena \expandafter{\@themark}%
54 <latexrelease>    \mark_insert:nn{2e-right}{#1}
55 <latexrelease>    \tl_if_empty:nF{#1}{ \mark_insert:nn{2e-right-nonempty}{#1} }
56 <latexrelease>    \mark{\the\@temptokena}%
57 <latexrelease>  \endgroup
58 <latexrelease>  \if@nobreak\ifvmode\nobreak\fi\fi}
59 <latexrelease>\ExplSyntaxOff
60 <latexrelease>\EndIncludeInRelease
61 <latexrelease>\IncludeInRelease{2019/10/01}%
62 <latexrelease>          {\markboth}{Make commands robust}%
63 <latexrelease>
64 <latexrelease>\DeclareRobustCommand*\markboth[2]{%
65 <latexrelease>  \begingroup
66 <latexrelease>    \let\label\relax \let\index\relax \let\glossary\relax
67 <latexrelease>    \unrestored@protected@xdef\@themark {{#1}{#2}}%
68 <latexrelease>    \@temptokena \expandafter{\@themark}%
69 <latexrelease>    \mark{\the\@temptokena}%
70 <latexrelease>  \endgroup
71 <latexrelease>  \if@nobreak\ifvmode\nobreak\fi\fi}
72 <latexrelease>\DeclareRobustCommand*\markright[1]{%
73 <latexrelease>  \begingroup
74 <latexrelease>    \let\label\relax \let\index\relax \let\glossary\relax
75 <latexrelease>    \expandafter\@markright\@themark {#1}%
76 <latexrelease>    \@temptokena \expandafter{\@themark}%
77 <latexrelease>    \mark{\the\@temptokena}%
78 <latexrelease>  \endgroup
79 <latexrelease>  \if@nobreak\ifvmode\nobreak\fi\fi}
80 <latexrelease>
81 <latexrelease>\EndIncludeInRelease
82 <latexrelease>\IncludeInRelease{0000/00/00}%
83 <latexrelease>          {\markboth}{Make commands robust}%
84 <latexrelease>

```

Using `\kernel@make@fragile` doesn't really work if there are more redefinitions later on, so we have to repeat the above definition first and then undo it (or use `\def` directly).

```

85 <latexrelease>%\kernel@make@fragile\markboth
86 <latexrelease>%\kernel@make@fragile\markright
87 <latexrelease>\def\markboth#1#2{%
88 <latexrelease> \begingroup
89 <latexrelease> \let\label\relax \let\index\relax \let\glossary\relax
90 <latexrelease> \unrestored@protected@xdef\@themark {{#1}{#2}}%
91 <latexrelease> \@temptokena \expandafter{\@themark}%
92 <latexrelease> \mark{\the\@temptokena}%
93 <latexrelease> \endgroup
94 <latexrelease> \if@nbreak\ifvmode\nobreak\fi\fi}
95 <latexrelease>\def\markright#1{%
96 <latexrelease> \begingroup
97 <latexrelease> \let\label\relax \let\index\relax \let\glossary\relax
98 <latexrelease> \expandafter\@markright\@themark {#1}%
99 <latexrelease> \@temptokena \expandafter{\@themark}%
100 <latexrelease> \mark{\the\@temptokena}%
101 <latexrelease> \endgroup
102 <latexrelease> \if@nbreak\ifvmode\nobreak\fi\fi}
103 <latexrelease>
104 <latexrelease>\EndIncludeInRelease
105 <*2ekernel>

\leftmark
\rightmark
106 </2ekernel>
107 <*2ekernel | latexrelease>
108 <latexrelease>\IncludeInRelease{2025/06/01}%
109 <latexrelease> \{\leftmark\}{Use new mark mechanism}%
110 \ExplSyntaxOn
111 \cs_new:Npn \leftmark {\mark_use_last:nn{page}{2e-left}}
112 \cs_new:Npn \rightmark {\mark_use_first:nn{page}{2e-right}}
113 \ExplSyntaxOff
114 </2ekernel | latexrelease>
115 <latexrelease>\EndIncludeInRelease
116 <latexrelease>\IncludeInRelease{0000/00/00}%
117 <latexrelease> \{\leftmark\}{Use new mark mechanism}%
118 <latexrelease>
119 <latexrelease>\def\leftmark{\expandafter\@leftmark\botmark\@empty\@empty}
120 <latexrelease>\def\rightmark{\expandafter\@rightmark\firstmark\@empty\@empty}

121 <latexrelease>\def\@themark{{}{}}
\markright 122 <latexrelease>\def\@markright#1#2#3{\@temptokena {#1}%
\mark 123 <latexrelease>\unrestored@protected@xdef\@themark{{\the\@temptokena}{#3}}}
124 <latexrelease>\EndIncludeInRelease
125 <*2ekernel>

```

(End of definition for `\leftmark` and others. These functions are documented on page 1020.)

`\raggedbottom` `\raggedbottom` typesets pages with no vertical stretch, so they have their natural height instead of all being exactly the same height. (Uses a space of .0001fil to avoid interfering with the 1fil space of `\newpage`.)

```

126 \DeclareRobustCommand\raggedbottom{%
127   \def\@textbottom{\vskip \z@ \@plus.0001fil}\let\@texttop\relax}

(End of definition for \raggedbottom.)

\flushbottom \flushbottom: Inverse of \raggedbottom — makes all pages the same height.
128 \DeclareRobustCommand\flushbottom{%
129   \let\@textbottom\relax \let\@texttop\relax}

(End of definition for \flushbottom.)

\sloppy \sloppy will never (well, hardly ever) produce overfull boxes, but may produce underfull
ones. (14 June 85)
130 \DeclareRobustCommand\sloppy{%
131   \tolerance 9999%
132   \emergencystretch 3em%
133   \hfuzz .5\p@
134   \vfuzz\hfuzz}

(End of definition for \sloppy.)

sloppypar (env.) A sloppypar environment is equivalent to {\par \sloppy ... \par}.
135 \def\sloppypar{\par\sloppy}
136 \def\endsloppypar{\par}

\fussy Resets TeX's parameters to their normal finicky values.
137 \DeclareRobustCommand\fussy{%
138   \emergencystretch\z@
139   \tolerance 200%
140   \hfuzz .1\p@
141   \vfuzz\hfuzz}

(End of definition for \fussy.)

\overfullrule LATEX default is no overfull box rule. Changed by document class option.
142 \overfullrule 0pt

(End of definition for \overfullrule.)
143 </2ekernel>

```

## File 50

# ltclass.dtx

## 1 Introduction

This file implements the following declarations, which replace `\documentstyle` in  $\text{\LaTeX 2}_\epsilon$  documents.

Note that old documents containing `\documentstyle` will be run using a compatibility option—thus keeping everyone happy, we hope!

The overall idea is that there are two types of ‘style files’: ‘class files’ which define elements and provide a default formatting for them; and ‘packages’ which provide extra functionality. One difference between  $\text{\LaTeX 2}_\epsilon$  and  $\text{\LaTeX 2.09}$  is that  $\text{\LaTeX 2}_\epsilon$  packages may have options. Note that options to classes/packages may be implemented such that they input files, but these file names are not necessarily directly related to the option name.

## 2 User interface

```
\documentclass[<main-option-list>]{<class>}[<version>]
```

There must be exactly one such declaration, and it must come first. The *<main-option-list>* is a list of options which can modify the formatting of elements which are defined in the *<class>* file as well as in all following `\usepackage` declarations (see below). The *<version>* is a version number, beginning with a date in the format YYYY/MM/DD. If an older version of the class is found, a warning is issued.

```
\documentstyle[<main-option-list>]{<class>}[<version>]
```

The `\documentstyle` declaration is kept in order to maintain upward compatibility with  $\text{\LaTeX 2.09}$  documents. It is similar to `\documentclass`, but it causes all options in *<main-option-list>* that the *<class>* does not use to be passed to `\RequirePackage` after the options have been processed. This maintains compatibility with the 2.09 behaviour. Also a flag is set to indicate that the document is to be processed in  $\text{\LaTeX 2.09}$  compatibility mode. As far as most packages are concerned, this only affects the warnings and errors  $\text{\LaTeX}$  generates. This flag does affect the definition of font commands, and `\sloppy`.

```
\usepackage[<package-option-list>]{<package-list>}[<version>]
```

There can be any number of these declarations. All packages in *<package-list>* are called with the same options.

Each *<package>* file defines new elements (or modifies those defined in the *<class>*), and thus extends the range of documents which can be processed. The *<package-option-list>* is a list of options which can modify the formatting of elements defined in the *<package>* file. The *<version>* is a version number, beginning with a date in the format YYYY/MM/DD. If an older version of the package is found, a warning is issued.

Each package is loaded only once. If the same package is requested more than once, nothing happens, unless the package has been requested with options that were not given the first time it was loaded, in which case an error is produced.

As well as processing the options given in the  $\langle\text{package-option-list}\rangle$ , each package processes the  $\langle\text{main-option-list}\rangle$ . This means that options that affect all of the packages can be given globally, rather than repeated for every package.

Note that class files have the extension `.cls`, packages have the extension `.sty`.

`filecontents` (*env.*)

The environment `filecontents` is intended for passing the contents of packages, options, or other files along with a document in a single file. It has one argument, which is the name of the file to create. If that file already exists (maybe only in the current directory if the OS supports a notion of a ‘current directory’ or ‘default directory’) then nothing happens (except for an information message) and the body of the environment is bypassed. Otherwise, the body of the environment is written verbatim to the file name given as the first argument, together with some comments about how it was produced.

The environment can also be called with an optional argument which is used to alter some of its behavior: option `force` or `overwrite` will allow for overwriting existing files, option `nosearch` will only check the current directory when looking if the file exists. This can be useful if you want to generate a local (modified) copy of some file that is already in the search tree of  $\text{\TeX}$ . Finally, you can use `noheader` to prevent it from writing the standard blurb at the top of the file (this is actually the same as using the star form of the environment).

As the environment is intended to be used on document level to bundle different files together, by default it refuses to overwrite files. If the option `force` is used then it always writes the file, but it generates a warning if it overwrites (or might overwrite) an existing file.<sup>51</sup> If necessary, this warning can be suppressed by also using the option `nowarn` but for most use cases we recommend informing the user when an overwrite happens and therefore to not add this option.

The environment is now allowed anywhere in the document, but to ensure that all the necessary packages and options are available when the document is run, it is normally best to place it at the top of your file (before `\documentclass`). A possible use case for using it inside the document body is if you want to reuse some text several times in the document you could then write it and later use `\input` to retrieve it where needed.

The begin and end tags should each be on a line by itself.

## 2.1 Option processing

When the options are processed, they are divided into two types: *local* and *global*:

- For a class, the options in the `\documentclass` command are local.
- For a package, the options in the `\usepackage` command are local, and the options in the `\documentclass` command are global.

The options for `\documentclass` and `\usepackage` are processed in the following way:

1. The local and global options that have been declared (using `\DeclareOption` as described below) are processed first.

In the case of `\ProcessOptions`, they are processed in the order that they were declared in the class or package.

In the case of `\ProcessOptions*`, they are processed in the order that they appear in the option-lists. First the global options, and then the local ones.

---

<sup>51</sup> $\text{\TeX}$  might see a file in the `texmf/` tree that is not in current directory, in which case no overwrite happens; but it can’t distinguish that case from the one in which an overwrite takes place.

2. Any remaining local options are dealt with using the default option (declared using the `\DeclareOption*` declaration described below). For document classes, this usually does nothing, but records the option on a list of unused options. For packages, this usually produces an error.

Finally, when `\begin{document}` is reached, if there are any global options which have not been used by either the class or any package, the system will produce a warning.

## 3 Class and Package interface

### 3.1 Class name and version

`\ProvidesClass` A class can identify itself with the `\ProvidesClass{<name>}[<version>]` command. The `<version>` should begin with a date in the format `YYYY/MM/DD`.

### 3.2 Package name and version

`\ProvidesPackage` A package can identify itself with the `\ProvidesPackage{<name>}[<version>]` command. The `<version>` should begin with a date in the format `YYYY/MM/DD`.

### 3.3 Requiring other packages

`\RequirePackage` Packages or classes can load other packages using `\RequirePackage[<options>]{<name>}[<version>]`. If the package has already been loaded, then nothing happens unless the requested options are not a subset of the options with which it was loaded, in which case an error is called.

`\LoadClass` Similar to `\RequirePackage`, but for classes, may not be used in package files.

`\PassOptionsToPackage` Packages can pass options to other packages using:

`\PassOptionsToPackage{<options>}{<package>}`.

`\PassOptionsToClass` This adds the `<options>` to the options list of any future `\RequirePackage` or `\usepackage` command. For example:

```
\PassOptionsToPackage{foo,bar}{fred}
```

is the same as:

```
\RequirePackage[foo,bar,baz]{fred}
```

`\LoadClassWithOptions` `\LoadClassWithOptions{<name>}[<version>]:`

This is similar to `\LoadClass`, but it always calls class `<name>` with exactly the same option list that is being used by the current class, rather than an option explicitly supplied or passed on by `\PassOptionsToClass`. `\RequirePackageWithOptions` is the analogous command for packages.

This is mainly intended to allow one class to simply build on another, for example:

```
\LoadClassWithOptions{article}
```

This should be contrasted with the slightly different construction

```
\DeclareOption*{\PassOptionsToClass{CurrentOption}{article}}
\ProcessOptions
\LoadClass{article}
```

As used here, the effects are more or less the same, but the version using `\LoadClassWithOptions` is slightly quicker (and less to type). If, however, the class declares options of its own then the two constructions are different; compare, for example:

```
\DeclareOption{landscape}{...}
\ProcessOptions
\LoadClassWithOptions{article}
```

with:

```
\DeclareOption{landscape}{...}
\DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
\ProcessOptions
\LoadClass{article}
```

In the first case, the `article` class will be called with option `landscape` precisely when the current class is called with this option; but in the second example it will not as in that case `article` is only passed options by the default option handler, which is not used for `landscape` as that option is explicitly declared.

```
\IfPackageLoadedTF      To find out if a package has already been loaded, use
  \IfClassLoadedTF
  \@ifpackageloaded      \IfPackageLoadedTF{<package>}{<true>}{<false>}
  \@ifclassloaded
```

or the old name `\@ifpackageloaded`.

```
\IfPackageAtLeastTF     To find out if a package has already been loaded with a version equal to or more
  \IfClassAtLeastTF      recent than <date>, use
  \IfFileAtLeastTF
  \ifpackagelater        \IfPackageAtLeastTF{<package>}{<date>}{<true>}{<false>}
  \@ifclasslater         or the old name \@ifpackagelater.
  \IfFormatAtLeastTF     To test the format date use
                        \IfFormatAtLeastTF{<date>}{<true>}{<false>}
```

```
\IfPackageLoadedWithOptionsTF  To find out if a package has already been loaded with at least the options <options>,
\IfClassLoadedWithOptionsTF use
  \@ifpackagewith        \IfPackageLoadedWithOptionsTF{<package>}{<options>}{<true>}{<false>}
  \@ifclasswith
```

or the old name `\@ifpackagewith`.

There exists one package that can't be tested with the above commands: the `fontenc` package pretends that it was never loaded to allow for repeated reloading with different options (see `ltoutenc.dtx` for details).

```
\NeedsDocumentMetadata  To require that a document starts with \DocumentMetadata use
                        \NeedsDocumentMetadata
```

### 3.4 Declaring new options

Options for classes and packages are built using the same macros.

<code>\DeclareOption</code>	To define a builtin option, use <code>\DeclareOption{&lt;name&gt;}{&lt;code&gt;}</code> .
<code>\DeclareOption*</code>	To define the default action to perform for local options which have not been declared, use <code>\DeclareOption*{&lt;code&gt;}</code> .

*Note:* there should be no use of `\RequirePackage`, `\DeclareOption`, `\DeclareOption*` or `\ProcessOptions` inside `\DeclareOption` or `\DeclareOption*`.

Possible uses for `\DeclareOption*` include:

```
\DeclareOption*{}
Do nothing. Silently accept unknown options. (This suppresses the usual warnings.)
\DeclareOption*{\@unkownoptionerror}
Complain about unknown local options. (The initial setting for package files.)
\DeclareOption*{\PassOptionsToPackage{\CurrentOption}{<pkg-name>}}
Handle the current option by passing it on to the package <pkg-name>, which will pre-
sumably be loaded via \RequirePackage later in the file. This is useful for building
‘extension’ packages, that perhaps handle a couple of new options, but then pass every-
thing else on to an existing package.
\DeclareOption*{\InputIfFileExists{xx-\CurrentOption.yyy}%
{}%
{\OptionNotUsed}}
```

Handle the option foo by loading the file `xx-foo.yyy` if it exists, otherwise do nothing, but declare that the option was not used. Actually the `\OptionNotUsed` declaration is only needed if this is being used in class files, but does no harm in package files.

### 3.5 Safe Input Macros

<code>\InputIfFileExists</code>	<code>\InputIfFileExists{&lt;file&gt;}{&lt;then&gt;}{&lt;else&gt;}</code> Inputs <code>&lt;file&gt;</code> if it exists. Immediately before the input, <code>&lt;then&gt;</code> is executed. Otherwise <code>&lt;else&gt;</code> is executed.
<code>\IfFileExists</code>	As above, but does not input the file. One thing you might like to put in the <code>&lt;else&gt;</code> clause is
<code>\@missingfileerror</code>	This starts an interactive request for a filename, supplying default extensions. Just hitting return causes the whole input to be skipped and entering <code>x</code> quits the current run,
<code>\input</code>	This has been redefined from the L <sup>A</sup> T <sub>E</sub> X2.09 definition, in terms of the new commands <code>\InputIfFileExists</code> and <code>\@missingfileerror</code> .
<code>\listfiles</code>	Giving this declaration in the preamble causes a list of all files input via the ‘safe input’ commands to be listed at the end. Any strings specified in the optional argument to <code>\ProvidesPackage</code> are listed alongside the file name. So files in standard (and other non-standard) distributions can put informative strings in this argument.

## 4 Implementation

<sup>1</sup> `<*2kernel>`

<code>\if@compatibility</code>	The flag for compatibility mode.
--------------------------------	----------------------------------

<sup>2</sup> `\newif\if@compatibility`

*(End of definition for \if@compatibility.)*

`\@documentclasshook` This legacy hook is called after the first `\documentclass` command. It is *not* integrated with the new 2020 hook management system! By default this checks to see if `\@normalsize` is undefined, and if so, sets it to `\normalsize`.

```

3 \def\@documentclasshook{%
4   \ifx\@normalsize\undefined
5     \let\@normalsize\normalsize
6   \fi
7 }

```

(End of definition for `\@documentclasshook`.)

`\@declaredoptions` This list is automatically built by `\DeclareOption`. It is the list of options (separated by commas) declared in the class or package file and it defines the order in which the corresponding `\ds<option>` commands are executed. All local `<option>`s which are not declared will be processed in the order defined by the optional argument of `\documentclass` or `\usepackage`.

```

8 \let\@declaredoptions\@empty

```

(End of definition for `\@declaredoptions`.)

`\@classoptionslist` List of options of the main class.

```

9 \let\@classoptionslist\relax
10 %\@onlypreamble\@classoptionslist

```

(End of definition for `\@classoptionslist`.)

`\@raw@classoptionslist` List of options of the main class (unprocessed).

```

11 \let\@raw@classoptionslist\relax

```

(End of definition for `\@raw@classoptionslist`.)

`\@unusedoptionlist` List of options of the main class that haven't been declared or loaded as class option files.

```

12 \let\@unusedoptionlist\@empty
13 %\@onlypreamble\@unusedoptionlist

```

(End of definition for `\@unusedoptionlist`.)

`\CurrentOption` Name of current package or option.

```

14 \let\CurrentOption\@empty

```

(End of definition for `\CurrentOption`.)

`\@currpath` Path to the current file if explicitly given.

```

15 </2ekernel>
16 <*2ekernel | latexrelease>
17 <latexrelease>
18 <latexrelease>\IncludeInRelease{2020/10/01}{\@currpath}%
19 <latexrelease> {Add \@currpath}%
20 \let\@currpath\@empty
21 <latexrelease>\EndIncludeInRelease
22 %
23 <latexrelease>\IncludeInRelease{0000/00/00}{\@currpath}%
24 <latexrelease> {Add \@currpath}%
25 <latexrelease>\let\@currpath\@undefined

```

```

26 <latexrelease>\EndIncludeInRelease
27 </2ekernel | latexrelease>
28 <*2ekernel>

```

(End of definition for \@currpath.)

**\@currname** Name of current package or option.

```

29 \let\@currname\@empty

```

(End of definition for \@currname.)

**\@currentt** The current file extension.

```

30 \global\let\@currentt=\@empty

```

(End of definition for \@currentt.)

**\@clsextension** The two possible values of \@currentt.

```

\@pkgextension
31 \def\@clsextension{cls}
32 \def\@pkgextension{sty}

```

(End of definition for \@clsextension and \@pkgextension.)

**\@pushfilename** Commands to push and pop the file name and extension.

**\@popfilename** #1 current name.

**\@currnamestack** #2 current extension.

#3 current catcode of @.

#4 Rest of the stack.

```

33 </2ekernel>
34 <*2ekernel | latexrelease>
35 <latexrelease>
36 <latexrelease>\IncludeInRelease{2020/10/01}{\@pushfilename}%
37 <latexrelease> {Add \@expl@push@filename@@ and \@expl@push@filename@aux@@}%
38 \def\@pushfilename{%

```

The push and pop macros are injected in \@pushfilename and \@popfilename so that they correctly keep track of the hook labels.

This needs cleanup with the expl3 interfaces also playing here, e.g., \@expl@push@filename@@ needs cleanup and (and should probably not have this name either).

```

39 \@expl@push@filename@@
40 \xdef\@currnamestack{%
41   {\@currname}%
42   {\@currentt}%
43   {\the\catcode'\@}%
44   \@currnamestack}%

```

Temporarily add a stack for \@currpath here. This should be integrated in the main file stack eventually, but other packages rely on \@currnamestack having three elements per file, so that isn't a trivial change. The prefix \@kernel@... hopefully discourages people from using it.

```

45 \xdef\@kernel@currpathstack{%
46   {\@currpath}%
47   \@kernel@currpathstack}%
48 \@expl@push@filename@aux@@
49 <latexrelease>\EndIncludeInRelease

```

The following version of `\@pushfilename` didn't formally exist in this file, but in the 2020/02/02 release, `expl3` was preloaded and it patched `\@pushfilename` (and `\@popfilename`) by adding some hooks in there. But rolling back to 2020/02/02, `expl3` doesn't patch these macros again, so rolling back has to take those hooks into account. Same goes for `\@popfilename`.

```

50 <latexrelease>
51 <latexrelease>\IncludeInRelease{2020/02/02}{\@pushfilename}%
52 <latexrelease> {Add \@expl@push@filename@@}%
53 <latexrelease>\def\@pushfilename{%
54 <latexrelease> \@expl@push@filename@@
55 <latexrelease> \xdef\@currnamestack{%
56 <latexrelease> {\@currname}%
57 <latexrelease> {\@current}%
58 <latexrelease> {\the\catcode'\@}%
59 <latexrelease> \@currnamestack}%
60 <latexrelease> \@expl@push@filename@aux@@}
61 <latexrelease>\EndIncludeInRelease
62 <latexrelease>

```

When we roll back from a release that has `expl3` preloaded, the definitions of `\@pushfilename` and `\@popfilename` can't be completely rolled back otherwise `expl3`-based packages won't have the automatic `\ExplSyntaxOff` at the end. Here and below for `\@popfilename`, we don't roll back all the way through if coming from `LATEX > 2020-02-02`.

```

63 <latexrelease>\IncludeInRelease{0000/00/00}{\@pushfilename}%
64 <latexrelease> {Add \@expl@push@filename@@ and \@expl@push@filename@aux@@}%
65 <latexrelease>\ifnum\sourceLaTeXdate<20200202\relax
66 <latexrelease> \GenericInfo{}\{Defining 00-00-00\string\@pushfilename.\}
67 <latexrelease>\def\@pushfilename{%
68 <latexrelease> \xdef\@currnamestack{%
69 <latexrelease> {\@currname}%
70 <latexrelease> {\@current}%
71 <latexrelease> {\the\catcode'\@}%
72 <latexrelease> \@currnamestack}%
73 <latexrelease>\else
74 <latexrelease> \GenericInfo{}\{Defining 2020-02-02\string\@pushfilename.\}
75 <latexrelease>\def\@pushfilename{%
76 <latexrelease> \@expl@push@filename@@
77 <latexrelease> \xdef\@currnamestack{%
78 <latexrelease> {\@currname}%
79 <latexrelease> {\@current}%
80 <latexrelease> {\the\catcode'\@}%
81 <latexrelease> \@currnamestack}%
82 <latexrelease> \@expl@push@filename@aux@@}
83 <latexrelease>\fi
84 <latexrelease>\EndIncludeInRelease
85 \@onlypreamble\@pushfilename

86 <latexrelease>
87 <latexrelease>\IncludeInRelease{2020/10/01}{\@popfilename}%
88 <latexrelease> {Add \@expl@pop@filename@@}%
89 <latexrelease>\def\@popfilename{\@expl@@@hook@curr@name@pop@@
90 \expandafter\@p@filename\@currnamestack\@nil

```

Same for popping:

```

91 \expandafter\@p@pfilepath\@kernel@currpathstack\@nil
92 \@expl@pop@filename@@}
93 <latexrelease>\EndIncludeInRelease
94 <latexrelease>
95 <latexrelease>\IncludeInRelease{2020/02/02}{\@popfilename}%
96 <latexrelease> {Add \@expl@push@filename@@}%
97 <latexrelease>\def\@popfilename{\expandafter\@p@pfilename\@currnamestack\@nil}
98 <latexrelease> \@expl@pop@filename@@}
99 <latexrelease>\EndIncludeInRelease
100 <latexrelease>

101 <latexrelease>\IncludeInRelease{0000/00/00}{\@popfilename}%
102 <latexrelease> {Add \@expl@push@filename@@ and \@expl@push@filename@aux@@}%
103 <latexrelease>\ifnum\sourceLaTeXdate<20200202\relax
104 <latexrelease> \GenericInfo{}\{Defining 00-00-00\string\@popfilename.\}
105 <latexrelease>\def\@popfilename{\expandafter\@p@pfilename\@currnamestack\@nil}
106 <latexrelease>\else
107 <latexrelease> \GenericInfo{}\{Defining 2020-02-02\string\@popfilename.\}
108 <latexrelease>\def\@popfilename{\expandafter\@p@pfilename\@currnamestack\@nil}
109 <latexrelease> \@expl@pop@filename@@}
110 <latexrelease>\fi
111 <latexrelease>\EndIncludeInRelease
112 \@onlypreamble\@popfilename

113 </2ekernel | latexrelease>
114 <*2ekernel>

115 \def\@p@pfilename#1#2#3#4\@nil{%
116 \gdef\@currname{#1}%
117 \gdef\@currentext{#2}%
118 \catcode'\@#3\relax
119 \gdef\@currnamestack{#4}}
120 \@onlypreamble\@p@pfilename

121 \gdef\@currnamestack{}
122 \@onlypreamble\@currnamestack

```

*(End of definition for \@pushfilename, \@popfilename, and \@currnamestack.)*

**\@kernel@currpathstack** Path to the current file if explicitly given. The auxiliary is needed here to insert a \@empty to prevent the loss of braces.

```

123 </2ekernel>
124 <*2ekernel | latexrelease>
125 <latexrelease>
126 <latexrelease>\IncludeInRelease{2020/10/01}{\@kernel@currpathstack}%
127 <latexrelease> {Add \@kernel@currpathstack}%

```

If rolling backwards to this release, \@kernel@currpathstack will be defined, so the \gdef line should not be executed, thus the \@gobblethree will take it out, so the satch isn't touched.

```

128 <latexrelease>\@ifundefined{\kernel@currpathstack}{\@gobblethree}
129 \gdef\@kernel@currpathstack{}%

```

If rolling forward to this release, then the \gdef line above will define the path stack to be empty (which it can't be, inside a file), so the code below will traverse the \@currnamestack, and add as many empty items to \@kernel@currpathstack as there

are items in `\@currnamestack`, so both are back in sync. Most of the time `latexrelease` is loaded on top-level, so only one item is needed, but `platexrelease` loads it internally, so the more complicated loop is needed.

```

130 <latexrelease>\ifx\@kernel@currpathstack\@empty
131 <latexrelease> \def\reserved@a#1#2#3{%
132 <latexrelease> \ifx\relax#3\else
133 <latexrelease> \g@addto@macro\@kernel@currpathstack{#3}%
134 <latexrelease> \expandafter\reserved@a
135 <latexrelease> \fi}%
136 <latexrelease> \expandafter\reserved@a\@currnamestack{#1}\relax}%
137 <latexrelease>\fi
138 \def\@p@pfilepath#1{%
139 \gdef\@currpath{#1}\@p@pfilepath@aux\@empty}
140 \def\@p@pfilepath@aux#1\@nil{%
141 \xdef\@kernel@currpathstack{#1}}
142 <latexrelease>\EndIncludeInRelease
143 %
144 <latexrelease>\IncludeInRelease{0000/00/00}{\@kernel@currpathstack}%
145 <latexrelease> {Add \@kernel@currpathstack}%
146 <latexrelease>\let\@kernel@currpathstack\undefined
147 <latexrelease>\let\@p@pfilepath\undefined
148 <latexrelease>\let\@p@pfilepath@aux\undefined
149 <latexrelease>\EndIncludeInRelease
150 </2ekernel | latexrelease>
151 <*2ekernel>

```

*(End of definition for \@kernel@currpathstack.)*

`\@optionlist` Returns the option list of the file.

```

152 \def\@optionlist#1{%
153 \ifundefined{opt@#1}\@empty{\csname opt@#1\endcsname}}
154 %\onlypreamble\@optionlist

```

*(End of definition for \@optionlist.)*

`\@ifpackageloaded` `\@ifpackageloaded{<name>}` Checks to see whether a file has been loaded.

```

\@ifclassloaded
155 \def\@ifpackageloaded{\@ifl@aded\@pkgextension}
156 \def\@ifclassloaded{\@ifl@aded\@clsextension}

157 \def\@ifl@aded#1#2{%
158 \expandafter\ifx\csname ver@#2.#1\endcsname\relax
159 \expandafter\@secondoftwo
160 \else
161 \expandafter\@firstoftwo
162 \fi}

```

*(End of definition for \@ifpackageloaded and \@ifclassloaded.)*

`\@ifpackagelater` `\@ifpackagelater{<name>}{YYYY/MM/DD}{<true code>}{<false code>}` Checks that the package loaded is more recent or equal to the given date. A better name for it would therefore been `\@ifpackagelaterorequal` but it is in use for more than 30 years, so ...

```

163 \def\@ifpackagelater{\@ifl@ter\@pkgextension}
164 \def\@ifclasslater{\@ifl@ter\@clsextension}

```

(End of definition for \ifpackagelater and \ifclasslater.)

\IfPackageAtLeastTF \IfFormatAtLeastTF{YYYY/MM/DD}{\true code}{\false code} Test if the format is later or equal to the given date.

```

\IfClassAtLeastTF
\IfFileAtLeastTF
\IfFormatAtLeastTF
165 \endkernel
166 \*2kernel | latexrelease
167 \latexrelease\IncludeInRelease{2020/10/01}%
168 \latexrelease \IfFormatAtLeastTF{Test format date}%
169 \def\IfFormatAtLeastTF{\@ifl@t@r\fmtversion}
170 \let\IfPackageAtLeastTF\ifpackagelater
171 \let\IfClassAtLeastTF\ifclasslater
172 \def\IfFileAtLeastTF#1{\expandafter\@ifl@t@r\csname ver@#1\endcsname}

```

For rollback pretend it was available since the beginning of dawn.

```

173 \endkernel | latexrelease
174 \latexrelease\EndIncludeInRelease
175 \latexrelease\IncludeInRelease{0000/00/00}%
176 \latexrelease \IfFormatAtLeastTF{Test format date}%
177 \latexrelease\def\IfFormatAtLeastTF{\@ifl@t@r\fmtversion}
178 \latexrelease\let\IfPackageAtLeastTF\ifpackagelater
179 \latexrelease\let\IfClassAtLeastTF\ifclasslater
180 \latexrelease\def\IfFileAtLeastTF#1{\expandafter\@ifl@t@r\csname ver@#1\endcsname}
181 \latexrelease\EndIncludeInRelease
182 \*2kernel

```

(End of definition for \IfPackageAtLeastTF and others.)

\@ifl@ter

```

183 \def\@ifl@ter#1#2{%
184   \expandafter\@ifl@t@r
185   \csname ver@#2.#1\endcsname}
186 \endkernel

This internal macro is also used in \NeedsTeXFormat.

187 \latexrelease\IncludeInRelease{2018/04/01}%
188 \latexrelease \@ifl@t@r{Guard against bad input}%
189 \*2kernel | latexrelease
190 \def\@ifl@t@r#1#2{%
191   \ifnum\expandafter\@parse@version@#1//00\@nil<%
192     \expandafter\@parse@version@#2//00\@nil
193     \expandafter\@secondoftwo
194   \else
195     \expandafter\@firstoftwo
196   \fi}
197 \def\@parse@version@#1{\@parse@version0#1}
198 \endkernel | latexrelease
199 \latexrelease\EndIncludeInRelease
200 \latexrelease\IncludeInRelease{0000/00/00}%
201 \latexrelease \@ifl@t@r{Guard against bad input}%
202 \latexrelease\def\@ifl@t@r#1#2{%
203 \latexrelease \ifnum\expandafter\@parse@version@#1//00\@nil<%
204 \latexrelease \expandafter\@parse@version@#2//00\@nil
205 \latexrelease \expandafter\@secondoftwo
206 \latexrelease \else
207 \latexrelease \expandafter\@firstoftwo

```

```

208 <latexrelease> \fi}
209 <latexrelease>\let\@parse@version@\@undefined
210 <latexrelease>\EndIncludeInRelease
211 <*2ekernel>

```

(End of definition for \ifl@ter.)

```

212 </2ekernel>
213 <*2ekernel | latexreleasefirst>
214 \def\@parse@version#1/#2/#3#4#5\@nil{%
215 \@parse@version@dash#1-#2-#3#4\@nil
216 }

```

The \if test here ensures that an argument with no / or - produces 0 (actually 00).

```

217 \def\@parse@version@dash#1-#2-#3#4#5\@nil{%
218 \if\relax#2\relax\else#1\fi#2#3#4 }
219 </2ekernel | latexreleasefirst>
220 <*2ekernel>

```

\@ifpackagewith \@ifpackagewith{<name>}{<option-list>} Checks that <option-list> is a subset of the options with which <name> was loaded.

```

221 \def\@ifpackagewith{\@ifoptions\@pkgextension}
222 \def\@ifclasswith{\@ifoptions\@clsextension}
223 \def\@ifoptions#1#2{%
224 \expandtwoargs\@ifpti@ns{\@optionlist{#2.#1}}

```

Probably shouldn't use \CurrentOption here... (changed to \reserved@b.)

```

225 </2ekernel>
226 <latexrelease>\IncludeInRelease{2017/01/01}%
227 <latexrelease> \if@pti@ns{Spaces in option clash check}%
228 <*2ekernel | latexrelease>
229 \def\@ifpti@ns#1#2{%
230 \let\reserved@a\@firstoftwo

231 \edef\reserved@b{\zap@space#2 \@empty}%
232 \@for\reserved@b:=\reserved@b\do{%
233 \ifx\reserved@b\@empty
234 \else
235 \expandafter\in@\expandafter{\expandafter,\reserved@b,}{, #1,}%
236 \ifin@
237 \else
238 \let\reserved@a\@secondoftwo
239 \fi
240 \fi
241 }%
242 \reserved@a}
243 </2ekernel | latexrelease>
244 <latexrelease>\EndIncludeInRelease
245 <latexrelease>\IncludeInRelease{0000/00/00}%
246 <latexrelease> \if@pti@ns{Spaces in option clash check}%
247 <latexrelease>\def\@ifpti@ns#1#2{%
248 <latexrelease> \let\reserved@a\@firstoftwo
249 <latexrelease> \@for\reserved@b:=#2\do{%
250 <latexrelease> \ifx\reserved@b\@empty
251 <latexrelease> \else

```

```

252 <latexrelease> \expandafter\in@\expandafter
253 <latexrelease> {\expandafter,\reserved@b,}{, #1,}%
254 <latexrelease> \ifin@
255 <latexrelease> \else
256 <latexrelease> \let\reserved@a\@secondoftwo
257 <latexrelease> \fi
258 <latexrelease> \fi
259 <latexrelease> }%
260 <latexrelease> \reserved@a}
261 <latexrelease>\EndIncludeInRelease
262 <*2ekernel>

```

(End of definition for \@ifpackagewith and \@ifclasswith.)

\IfPackageLoadedTF More public names for the commands already available for a long time.

```

\IfPackageLoadedWithOptionsTF 263 </2ekernel>
\IfClassLoadedTF 264 <*2ekernel | latexrelease>
\IfClassLoadedWithOptionsTF 265 <latexrelease>\IncludeInRelease{2024/06/01}%
266 <latexrelease> {\IfPackageLoadedTF}{Test package loading}%
267 \let \IfPackageLoadedTF \ifpackageloaded
268 \let \IfClassLoadedTF \ifclassloaded
269 \let \IfPackageLoadedWithOptionsTF \ifpackagewith
270 \let \IfClassLoadedWithOptionsTF \ifclasswith

```

For rollback/rollforward pretend everything was available since the beginning of dawn.

```

271 </2ekernel | latexrelease>
272 <latexrelease>\EndIncludeInRelease
273 <latexrelease>\IncludeInRelease{0000/00/00}%
274 <latexrelease> {\IfPackageLoadedTF}{Test package loading}%
275 <latexrelease>
276 <latexrelease>\let \IfPackageLoadedTF \ifpackageloaded
277 <latexrelease>\let \IfClassLoadedTF \ifclassloaded
278 <latexrelease>\let \IfPackageLoadedWithOptionsTF \ifpackagewith
279 <latexrelease>\let \IfClassLoadedWithOptionsTF \ifclasswith
280 <latexrelease>
281 <latexrelease>\EndIncludeInRelease
282 <*2ekernel>

```

(End of definition for \IfPackageLoadedTF and others.)

\IfPackageLoadedT A few more conditionals for convenience

```

\IfPackageLoadedF 283 </2ekernel>
\IfPackageAtLeastT 284 <*2ekernel | latexrelease>
\IfPackageAtLeastF 285 <latexrelease>\IncludeInRelease{2024/06/01}%
\IfClassAtLeastT 286 <latexrelease> {\IfPackageLoadedT}{More conditionals}%
\IfClassAtLeastF 287 \def\IfPackageLoadedT #1{\IfPackageLoadedTF{#1}\@firstofone\@gobble}
\IfFileAtLeastT 288 \def\IfPackageLoadedF #1{\IfPackageLoadedTF{#1}{}}
\IfFileAtLeastF 289 \def\IfClassLoadedT #1{\IfClassLoadedTF{#1}\@firstofone\@gobble}
\IfFormatAtLeastT 290 \def\IfClassLoadedF #1{\IfClassLoadedTF{#1}{}}
\IfFormatAtLeastF 291 \def\IfPackageAtLeastT#1#2{\IfPackageAtLeastTF{#1}{#2}\@firstofone\@gobble}
\IfPackageLoadedWithOptionsT 292 \def\IfPackageAtLeastF#1#2{\IfPackageAtLeastTF{#1}{#2}{}}
\IfPackageLoadedWithOptionsF 293 \def\IfClassAtLeastT #1#2{\IfClassAtLeastTF{#1}{#2}\@firstofone\@gobble}
\IfClassLoadedT 294 \def\IfClassAtLeastF #1#2{\IfClassAtLeastTF{#1}{#2}{}}
\IfClassLoadedF 295 \def\IfFileAtLeastT #1#2{\IfFileAtLeastTF{#1}{#2}\@firstofone\@gobble}
\IfClassLoadedWithOptionsF 296 \def\IfFileAtLeastF #1#2{\IfFileAtLeastTF{#1}{#2}{}}
\IfClassLoadedWithOptionsTF

```

```

297 \def\IfFormatAtLeastT #1{\IfFormatAtLeastTF{#1}\@firstofone\@gobble}
298 \def\IfFormatAtLeastF #1{\IfFormatAtLeastTF{#1}{}}
299 \def\IfPackageLoadedWithOptionsT #1#2{\IfPackageLoadedWithOptionsTF{#1}{#2}\@firstofone\@gobble}
300 \def\IfPackageLoadedWithOptionsF #1#2{\IfPackageLoadedWithOptionsTF{#1}{#2}{}}
301 \def\IfClassLoadedWithOptionsT #1#2{\IfClassLoadedWithOptionsTF{#1}{#2}\@firstofone\@gobble}
302 \def\IfClassLoadedWithOptionsF #1#2{\IfClassLoadedWithOptionsTF{#1}{#2}{}}

```

These three commands haven't been there at all in the past.

```

303 \def\IfFileLoadedTF#1{%
304   \expandafter\ifx\csname ver@#1\endcsname\relax
305     \expandafter\@secondoftwo
306   \else
307     \expandafter\@firstoftwo
308   \fi}
309 \def\IfFileLoadedT #1{\IfFileLoadedTF{#1}\@firstofone\@gobble}
310 \def\IfFileLoadedF #1{\IfFileLoadedTF{#1}{}}

```

For rollback/rollforward pretend everything was available since the beginning of dawn.

```

311 </2ekernel | latexrelease>
312 <latexrelease>\EndIncludeInRelease
313 <latexrelease>\IncludeInRelease{0000/00/00}%
314 <latexrelease>          {\IfPackageLoadedT}{More conditionals}%
315 <latexrelease>
316 <latexrelease>\def\IfPackageLoadedT #1#2{\IfPackageLoadedTF{#1}{#2}{}}
317 <latexrelease>\def\IfPackageLoadedF #1{\IfPackageLoadedTF{#1}{}}
\IfFileLoadedTF
\IfFileLoadedT
\IfFileLoadedF
318 <latexrelease>\def\IfClassLoadedT #1#2{\IfClassLoadedTF{#1}{#2}{}}
319 <latexrelease>\def\IfClassLoadedF #1{\IfClassLoadedTF{#1}{}}
320 <latexrelease>\def\IfPackageAtLeastT#1#2#3{\IfPackageAtLeastTF{#1}{#2}{#3}{}}
321 <latexrelease>\def\IfPackageAtLeastF #1#2{\IfPackageAtLeastTF{#1}{#2}{}}
322 <latexrelease>\def\IfClassAtLeastT #1#2#3{\IfClassAtLeastTF{#1}{#2}{#3}{}}
323 <latexrelease>\def\IfClassAtLeastF #1#2{\IfClassAtLeastTF{#1}{#2}{}}
324 <latexrelease>\def\IfFileAtLeastT #1#2#3{\IfFileAtLeastTF{#1}{#2}{#3}{}}
325 <latexrelease>\def\IfFileAtLeastF #1#2{\IfFileAtLeastTF{#1}{#2}{}}
326 <latexrelease>\def\IfFormatAtLeastT #1#2{\IfFormatAtLeastTF{#1}{#2}{}}
327 <latexrelease>\def\IfFormatAtLeastF #1{\IfFormatAtLeastTF{#1}{}}
328 <latexrelease>\def\IfPackageLoadedWithOptionsT #1#2#3{\IfPackageLoadedWithOptionsTF{#1}{#2}{#3}{}}
329 <latexrelease>\def\IfPackageLoadedWithOptionsF #1#2{\IfPackageLoadedWithOptionsTF{#1}{#2}{}}
330 <latexrelease>\def\IfClassLoadedWithOptionsT #1#2#3{\IfClassLoadedWithOptionsTF{#1}{#2}{#3}{}}
331 <latexrelease>\def\IfClassLoadedWithOptionsF #1#2{\IfClassLoadedWithOptionsTF{#1}{#2}{}}
332 <latexrelease>
333 <latexrelease>\def\IfFileLoadedTF#1{%
334 <latexrelease>   \expandafter\ifx\csname ver@#1\endcsname\relax
335 <latexrelease>     \expandafter\@secondoftwo
336 <latexrelease>   \else
337 <latexrelease>     \expandafter\@firstoftwo
338 <latexrelease>   \fi}
339 <latexrelease>\def\IfFileLoadedT#1#2{\IfFileLoadedTF{#1}{#2}{}}
340 <latexrelease>\def\IfFileLoadedF #1{\IfFileLoadedTF{#1}{}}
341 <latexrelease>
342 <latexrelease>\EndIncludeInRelease
343 <*2ekernel>

```

*(End of definition for \IfPackageLoadedT and others.)*

`\ProvidesPackage` Checks that the current filename is correct, and defines `\ver@filename`.

```

344 </2ekernel>
345 <latexrelease>\IncludeInRelease{2020/10/01}%
346 <latexrelease> {\ProvidesPackage}{Check name with \strcmp}%
347 <*2ekernel | latexrelease>
348 \def\ProvidesPackage#1{%
349   \xdef\@gtempa{#1}%

```

Here `\@currpath` is explicitly added to the file name to report when a package or class is loaded using an explicit path. Loading using a path in the argument is supported but not encouraged.

```

350   \@expandtwoargs\@expl@str@if@eq@nnTF
351   {\@gtempa}{\@currpath\@currname}{}%
352   \@latex@warning@no@line{You have requested
353     \@cls@pkg\space'\@currpath\@currname',\MessageBreak
354     but the \@cls@pkg\space provides '#1'}%
355   }%
356   \@ifnextchar[\@pr@videpackage{\@pr@videpackage[]}]%
357 \onlypreamble\ProvidesPackage
358 </2ekernel | latexrelease>
359 <latexrelease>\EndIncludeInRelease
360 %
361 <latexrelease>\IncludeInRelease{0000/00/00}%
362 <latexrelease> {\ProvidesPackage}{Undo: check name with \strcmp}%
363 <latexrelease>\def\ProvidesPackage#1{%
364 <latexrelease>   \xdef\@gtempa{#1}%
365 <latexrelease>   \ifx\@gtempa\@currname\else
366 <latexrelease>     \@latex@warning@no@line{You have requested
367 <latexrelease>       \@cls@pkg\space'\@currname',\MessageBreak
368 <latexrelease>       but the \@cls@pkg\space provides '#1'}%
369 <latexrelease>   \fi
370 <latexrelease>   \@ifnextchar[\@pr@videpackage{\@pr@videpackage[]}]%
371 <latexrelease>\EndIncludeInRelease
372 <*2ekernel>

```

*(End of definition for \ProvidesPackage.)*

`\@pr@videpackage` This is the helper command for `\ProvidesPackage`. It tries to be cautious when handling the identification string in case it contains UTF-8 characters.

```

373 </2ekernel>
374 <*2ekernel | latexrelease>
375 <latexrelease>\IncludeInRelease{2020/10/01}%
376 <latexrelease> {\@pr@videpackage}{Allow for package substitution}%
377 \def\@pr@videpackage[#1]{%
378   \expandafter\protected\xdef          %    <-- protected...
379   \csname ver@\@currname.\@current\endcsname{#1}% Loaded package
380   \expandafter\let
381   \csname ver@\@currpkg@reqd\expandafter\endcsname % Requested package
382   \csname ver@\@currname.\@current\endcsname
383   \ifx\@current\@clsextension
384     \typeout{Document Class: \@gtempa\space#1}%
385   \else
386     \protected@wlog{Package: \@gtempa\space#1}%    <--- protected
387   \fi}

```

(End of definition for \@pr@videpackage.)

`\protected@wlog` This is like plain T<sub>E</sub>X's `\wlog` but gracefully handles protected commands.

```
388 \long\def\protected@wlog#1{\begingroup
389   \set@display@protect
390   \immediate \write \m@ne {#1}\endgroup }
```

(End of definition for `\protected@wlog`.)

```
391 </2ekernel | latexrelease>
392 <latexrelease>\EndIncludeInRelease
393 <latexrelease>\IncludeInRelease{2020/02/02}%
394 <latexrelease>          {\@pr@videpackage}{Protection for package info}%
395 <latexrelease>
396 <latexrelease>\def\@pr@videpackage[#1]{%
397 <latexrelease>  \expandafter\protected@xdef          %      <-- protected...
398 <latexrelease>    \csname ver@%currname.\@currentx\endcsname{#1}%
399 <latexrelease>\ifx\@currentx\@clsextension
400 <latexrelease>  \typeout{Document Class: \@gtempa\space#1}%
401 <latexrelease>  \else
402 <latexrelease>    \protected@wlog{Package: \@gtempa\space#1}%  <--- protected
403 <latexrelease>  \fi}
404 <latexrelease>
405 <latexrelease>\EndIncludeInRelease
406 <latexrelease>\IncludeInRelease{0000/00/00}%
407 <latexrelease>          {\@pr@videpackage}{Protection for package info}%
408 <latexrelease>
409 <latexrelease>\def\@pr@videpackage[#1]{%
410 <latexrelease>  \expandafter\xdef\csname ver@%currname.\@currentx\endcsname{#1}%
411 <latexrelease>  \ifx\@currentx\@clsextension
412 <latexrelease>    \typeout{Document Class: \@gtempa\space#1}%
413 <latexrelease>  \else
414 <latexrelease>    \wlog{Package: \@gtempa\space#1}%
415 <latexrelease>  \fi}
416 <latexrelease>\let\protected@wlog\@undefined
417 <latexrelease>
418 <latexrelease>\EndIncludeInRelease
419 <*2ekernel>
420 \@onlypreamble\@pr@videpackage
```

`\ProvidesClass` Like `\ProvidesPackage`, but for classes. This needs a dummy `latexrelease` block to copy the definition of `\ProvidesPackage` as it changes across releases.

```
421 </2ekernel>
422 <latexrelease>\IncludeInRelease{0000/00/00}%
423 <latexrelease>  {\ProvidesClass}{Track \ProvidesPackage}%
424 <*2ekernel | latexrelease>
425 \let\ProvidesClass\ProvidesPackage
426 \@onlypreamble\ProvidesClass
427 </2ekernel | latexrelease>
428 <latexrelease>\EndIncludeInRelease
429 <*2ekernel>
```

(End of definition for `\ProvidesClass`.)

`\ProvidesFile` Like `\ProvidesPackage`, but for arbitrary files. Do not apply `\@onlypreamble` to these, as we may want to label files input during the document.

```
\@providesfile 430 \def\ProvidesFile#1{%
431   \begingroup
432   \catcode'\ 10 %
433   \ifnum \endlinechar<256 %
434     \ifnum \endlinechar>\m@ne
435       \catcode\endlinechar 10 %
436     \fi
437   \fi
438   \@makeother\/%
439   \@makeother\&%
440   \kernel@ifnextchar[{\@providesfile{#1}}{\@providesfile{#1}[]}]}
```

During initex a special version of `\@providesfile` is used. The real definition is installed right at the end, in `ltfinal.dtx`.

```
def\@providesfile#1[#2]{%
  \wlog{File: #1 #2}%
  \expandafter\xdef\csname ver@#1\endcsname{#2}%
  \endgroup}
```

*(End of definition for \ProvidesFile and \@providesfile.)*

`\PassOptionsToPackage` If the package has been loaded, we check that it was first loaded with the options.  
`\PassOptionsToClass` Otherwise we add the option list to that of the package.

```
441 </2ekernel>
442 <latexrelease>\IncludeInRelease{2021/06/01}%
443 <latexrelease>          {\@passOptions}{Raw option lists}%
444 <*2ekernel | latexrelease>
445 \def\@passOptions#1#2#3{%
446   \@expl@@@filehook@set@curr@file@@nNN
447   {\@expl@@@filehook@resolve@file@subst@@w #3.#1\@nil}%
448   \reserved@a\reserved@b
449   \@expl@@@filehook@clear@replacement@flag@@
450   \expandafter\protected\xdef\csname opt@\reserved@a\endcsname{%
451     \@ifundefined{opt@\reserved@a}\@empty
452     {\csname opt@\reserved@a\endcsname,}%
453     \zap@space#2 \@empty}%
454   \expandafter\let
455     \csname opt@#3.#1\expandafter\endcsname
456     \csname opt@\reserved@a\endcsname
457   \ifundefined{@raw@opt@#3.#1}%
458     {\expandafter\gdef\csname @raw@opt@#3.#1\expandafter\endcsname
459       \expandafter{#2}}%
460     {\expandafter\g@addto@macro\csname @raw@opt@#3.#1\expandafter\endcsname
461       \expandafter{\expandafter,#2}}%
462   }
463 </2ekernel | latexrelease>
464 <latexrelease>\EndIncludeInRelease
```

```

465 <latexrelease>\IncludeInRelease{2020/10/01}{\@pass@options}
466 <latexrelease> {Add file replacement in \@pass@options}%
467 <latexrelease>
468 <latexrelease>\def\@pass@options#1#2#3{%
469 <latexrelease> \expl@@@filehook@set@curr@file@@nNN
470 <latexrelease> {\expl@@@filehook@resolve@file@subst@@w #3.#1\@nil}%
471 <latexrelease> \reserved@a\reserved@b
472 <latexrelease> \expl@@@filehook@clear@replacement@flag@@
473 <latexrelease> \expandafter\xdef\csname opt@\reserved@a\endcsname{%
474 <latexrelease> \ifundefined{opt@\reserved@a}\@empty
475 <latexrelease> {\csname opt@\reserved@a\endcsname,}%
476 <latexrelease> \zap@space#2 \@empty}%
477 <latexrelease> \expandafter\let
478 <latexrelease> \csname opt@#3.#1\expandafter\endcsname
479 <latexrelease> \csname opt@\reserved@a\endcsname}
480 <latexrelease>\EndIncludeInRelease

481 <latexrelease>\IncludeInRelease{0000/00/00}{\@pass@options}
482 <latexrelease> {\@pass@options}%
483 <latexrelease>
484 <latexrelease>\def\@pass@options#1#2#3{%
485 <latexrelease> \expandafter\xdef\csname opt@#3.#1\endcsname{%
486 <latexrelease> \ifundefined{opt@#3.#1}\@empty
487 <latexrelease> {\csname opt@#3.#1\endcsname,}%
488 <latexrelease> \zap@space#2 \@empty}}
489 <latexrelease>\EndIncludeInRelease
490 <*2ekernel>

491 \@onlypreamble\@pass@options

492 \def\PassOptionsToPackage{\@pass@options\@pkgextension}
493 \def\PassOptionsToClass{\@pass@options\@clsextension}
494 \@onlypreamble\PassOptionsToPackage
495 \@onlypreamble\PassOptionsToClass

```

*(End of definition for \PassOptionsToPackage and \PassOptionsToClass.)*

**\DeclareOption** Adds an option as a `\ds@` command, or the default `\default@ds` command.

```

\DeclareOption*
496 \def\DeclareOption{%
497 \let\@fileswith@ptions\@badrequireerror
498 \ifstar\@defdefault@ds\@declareoption}
499 \long\def\@declareoption#1#2{%
500 \xdef\@declaredoptions{\@declaredoptions,#1}%
501 \toks@{#2}%
502 \expandafter\edef\csname ds@#1\endcsname{\the\toks@}
503 \long\def\@defdefault@ds#1{%
504 \toks@{#1}%
505 \edef\default@ds{\the\toks@}}
506 \@onlypreamble\DeclareOption
507 \@onlypreamble\@declareoption
508 \@onlypreamble\@defdefault@ds

```

*(End of definition for \DeclareOption and \DeclareOption\*.)*

**\OptionNotUsed** If we are in a class file, add `\CurrentOption` to the list of unused options. Otherwise, in  
**\@remove@eq@value** a package file do nothing.

```

509 </2ekernel>
510 <latexrelease>\IncludeInRelease{2021/06/01}%
511 <latexrelease>          {\OptionNotUsed}{filter unused option list}%
512 <*2ekernel | latexrelease>
513 \ExplSyntaxOn
514 \def\@remove@eq@value#1=#2\@nil{\tl_trim_spaces:n{#1}}
515 \ExplSyntaxOff
516 \def\OptionNotUsed{%
517   \ifx\@currentx\@clsextension
518     \xdef\@unusedoptionlist{%
519       \ifx\@unusedoptionlist\@empty\else\@unusedoptionlist,\fi
520       \expandafter\@remove@eq@value\CurrentOption=\@nil}%
521   \fi}
522 </2ekernel | latexrelease>
523 <latexrelease>\EndIncludeInRelease
524 <latexrelease>\IncludeInRelease{0000/00/00}%
525 <latexrelease>          {\OptionNotUsed}{filter unused option list}%
526 <latexrelease>\let\@remove@eq@value\@undefined
527 <latexrelease>\def\OptionNotUsed{%
528 <latexrelease>   \ifx\@currentx\@clsextension
529 <latexrelease>     \xdef\@unusedoptionlist{%
530 <latexrelease>       \ifx\@unusedoptionlist\@empty\else\@unusedoptionlist,\fi
531 <latexrelease>       \CurrentOption}%
532 <latexrelease>   \fi}
533 <latexrelease>\EndIncludeInRelease
534 <*2ekernel>
535 \@onlypreamble\OptionNotUsed

```

*(End of definition for \OptionNotUsed and \@remove@eq@value.)*

**\default@ds** The default option code. Set by \@onefilewithoptions to either \OptionNotUsed for classes, or \@unknownoptionerror for packages. This may be reset in either case with \DeclareOption\*.

```
536 % \let\default@ds\OptionNotUsed
```

*(End of definition for \default@ds.)*

**\ProcessOptions** \ProcessOptions calls \ds@option for each known package option, then calls \default@ds for each option on the local options list. Finally resets all the declared options to \relax. The empty option does nothing, this has to be reset on the off chance it's set to \relax if an empty element gets into the \@declaredoptions list.

The star form is similar but executes options given in the order specified in the document, not the order they are declared in the file. In the case of packages, global options are executed before local ones.

```

537 \def\ProcessOptions{%
538   \let\ds@\@empty
539   \protected@edef\@curroptions{\@optionlist{\@currname.\@currentx}}%
540   \@ifstar\@xprocessoptions\@processoptions}
541 \@onlypreamble\ProcessOptions

```

```

542 \def\@process@ptions{%
543   \for\CurrentOption:=\@declaredoptions\do{%
544     \ifx\CurrentOption\@empty\else
545       \@expandtwoargs\in@{,\CurrentOption,}{%
546         ,\ifx\@current\@clsextension\else\@classoptionslist,\fi
547         \@curroptions,}%
548     \ifin@
549       \@use@option
550       \expandafter\let\csname ds@\CurrentOption\endcsname\@empty
551     \fi
552   \fi}%
553 \@process@ptions}
554 \@onlypreamble\@process@ptions

555 </2ekernel>
556 <latexrelease>\IncludeInRelease{2021/06/01}%
557 <latexrelease>           {\@xprocess@ptions}{safer \@xprocess@ptions}%
558 <*2ekernel | latexrelease>
559 \def\@xprocess@ptions{%
560   \ifx\@current\@clsextension\else
561     \ifx\@classoptionslist\relax\else
562       \for\CurrentOption:=\@classoptionslist\do{%
563         \ifx\CurrentOption\@empty\else
564           \ifundefined{ds@\detokenize\expandafter{\CurrentOption}}{ }{%
565             \@use@option
566             \expandafter\let\csname ds@\CurrentOption\endcsname\@empty
567           }%
568         \fi}%
569   \fi
570   \fi
571   \@process@ptions}
572 </2ekernel | latexrelease>
573 <latexrelease>\EndIncludeInRelease
574 <latexrelease>\IncludeInRelease{0000/00/00}%
575 <latexrelease>           {\@xprocess@ptions}{safer \@xprocess@ptions}%
576 <latexrelease>\let\@remove@eq@value\@undefined

577 <latexrelease>\def\@xprocess@ptions{%
578 <latexrelease>   \ifx\@current\@clsextension\else
579 <latexrelease>     \@for\CurrentOption:=\@classoptionslist\do{%
580 <latexrelease>       \ifx\CurrentOption\@empty\else
581 <latexrelease>         \@expandtwoargs\in@{,\CurrentOption,}{,\@declaredoptions,}%
582 <latexrelease>       \ifin@
583 <latexrelease>         \@use@option
584 <latexrelease>         \expandafter\let\csname ds@\CurrentOption\endcsname\@empty
585 <latexrelease>       \fi
586 <latexrelease>     \fi}%
587 <latexrelease>   \fi
588 <latexrelease>   \@process@ptions}
589 <latexrelease>\EndIncludeInRelease
590 <*2ekernel>

591 \@onlypreamble\@xprocess@ptions

    The common part of \ProcessOptions and \ProcessOptions*.
592 </2ekernel>

```

```

593 <*2ekernel | latexrelease>
594 <latexrelease>\IncludeInRelease{2020/10/01}%
595 <latexrelease>          {\process@pti@ns}{Unused options issue}%
596 \def\@process@pti@ns{%
597   \@for\CurrentOption:=\@curroptions\do{%
598     \ifundefined{ds@\detokenize\expandafter\CurrentOption}}%
599     {\@use@ption
600      \default@ds}%

```

There should not be any non-empty definition of `\CurrentOption` at this point, as all the declared options were executed earlier. This is for compatibility with 2.09 styles which use `\def\ds@...` directly, and so have options which do not appear in `\@declaredoptions`.

```

601   \@use@ption}%

```

Clear all the definitions for option code. First set all the declared options to `\relax`, then reset the ‘default’ and ‘empty’ options. and the list of declared options.

```

602   \@for\CurrentOption:=\@declaredoptions\do{%
603     \expandafter\let\csname ds@\CurrentOption\endcsname\relax}%

604   \let\CurrentOption\@empty
605   \let\@fileswith@pti@ns\@fileswith@pti@ns
606   \AtEndOfPackage{\expandafter\let
607     \csname unprocessedoptions-\@currname.\@current\endcsname
608     \relax}}
609 \@onlypreamble\@process@pti@ns
610 </2ekernel | latexrelease>
611 <latexrelease>\EndIncludeInRelease
612 <latexrelease>\IncludeInRelease{0000/00/00}%
613 <latexrelease>          {\process@pti@ns}{Unused options issue}%
614 <latexrelease>
615 <latexrelease>\def\@process@pti@ns{%
616 <latexrelease>   \@for\CurrentOption:=\@curroptions\do{%
617 <latexrelease>     \ifundefined{ds@\CurrentOption}%
618 <latexrelease>       {\@use@ption
619 <latexrelease>        \default@ds}%
620 <latexrelease>       \@use@ption}%
621 <latexrelease>   \@for\CurrentOption:=\@declaredoptions\do{%
622 <latexrelease>     \expandafter\let\csname ds@\CurrentOption\endcsname\relax}%
623 <latexrelease>   \let\CurrentOption\@empty
624 <latexrelease>   \let\@fileswith@pti@ns\@fileswith@pti@ns
625 <latexrelease>   \AtEndOfPackage{\let\@unprocessedoptions\relax}}
626 <latexrelease>\EndIncludeInRelease
627 <*2ekernel>

```

*(End of definition for \ProcessOptions and \ProcessOptions\*.)*

**\@options** `\@options` is a synonym for `\ProcessOptions*` for upward compatibility with L<sup>A</sup>T<sub>E</sub>X 2.09 style files.

```

628 \def\@options{\ProcessOptions*}
629 \@onlypreamble\@options

```

*(End of definition for \@options.)*

**\@use@ption** Execute the code for the current option.

```

630 </2ekernel>

```

```

631 <latexrelease>\IncludeInRelease{2021/06/01}%
632 <latexrelease>                {\@use@option}{filter unused option list}%
633 <*2ekernel | latexrelease>
634 \def\@use@option{%
635   \@expandtwoargs\@removeelement
636     {\expandafter\@remove@eq@value\CurrentOption=\@nil}%
637   \@unusedoptionlist\@unusedoptionlist
638   \csname ds@\detokenize\expandafter{\CurrentOption}\endcsname}
639 </2ekernel | latexrelease>
640 <latexrelease>\EndIncludeInRelease
641 <latexrelease>\IncludeInRelease{0000/00/00}%
642 <latexrelease>                {\@use@option}{filter unused option list}%
643 <latexrelease>\def\@use@option{%
644 <latexrelease>   \@expandtwoargs\@removeelement\CurrentOption
645 <latexrelease>   \@unusedoptionlist\@unusedoptionlist
646 <latexrelease>   \csname ds@\CurrentOption\endcsname}
647 <latexrelease>\EndIncludeInRelease
648 <*2ekernel>
649 \@onlypreamble\@use@option

```

(End of definition for \@use@option.)

**\ExecuteOptions** **\ExecuteOptions{<option-list>}** executes the code declared for each option.

```

650 </2ekernel>
651 <latexrelease>\IncludeInRelease{2017/01/01}%
652 <latexrelease>                {\ExecuteOptions}{Spaces in \ExecuteOptions}%
653 <*2ekernel | latexrelease>
654 \def\ExecuteOptions#1{%

```

Use \@fortmp here as it is anyway cleared during \@for loop so does not change any existing names.

```

655   \edef\@fortmp{\zap@space#1 \@empty}%
656   \def\reserved@a##1\@nil{%
657     \@for\CurrentOption:=\@fortmp\do
658       {\csname ds@\CurrentOption\endcsname}%
659     \edef\CurrentOption{##1}}%
660   \expandafter\reserved@a\CurrentOption\@nil}
661 </2ekernel | latexrelease>
662 <latexrelease>\EndIncludeInRelease
663 <latexrelease>\IncludeInRelease{0000/00/00}%
664 <latexrelease>                {\ExecuteOptions}{Spaces in \ExecuteOptions}%
665 <latexrelease>\def\ExecuteOptions#1{%
666 <latexrelease>   \def\reserved@a##1\@nil{%
667 <latexrelease>     \@for\CurrentOption:=#1\do
668 <latexrelease>       {\csname ds@\CurrentOption\endcsname}%
669 <latexrelease>     \edef\CurrentOption{##1}}%
670 <latexrelease>   \expandafter\reserved@a\CurrentOption\@nil}
671 <latexrelease>\EndIncludeInRelease
672 <*2ekernel>
673 \@onlypreamble\ExecuteOptions

```

(End of definition for \ExecuteOptions.)

The top-level commands, which just set some parameters then call the internal command, \@fileswithoptions.

`\documentclass` The main new-style class declaration.

```

674 \def\documentclass{%
675   \let\documentclass\@twoclasseserror
676   \if@compatibility\else\let\usepackage\RequirePackage\fi
677   \@fileswithoptions\@clsextension}
678 \@onlypreamble\documentclass
(End of definition for \documentclass.)

```

`\documentstyle` 2.09 style class ‘style’ declaration.

```

679 \def\documentstyle{%
680   \makeatletter\input{latex209.def}\makeatother
681   \documentclass}
682 \@onlypreamble\documentstyle
(End of definition for \documentstyle.)

```

`\RequirePackage` Load package if not already loaded.

```

683 \def\RequirePackage{%
684   \@fileswithoptions\@pkgextension}
685 \@onlypreamble\RequirePackage
(End of definition for \RequirePackage.)

```

`\LoadClass` Load class.

```

686 \def\LoadClass{%
687   \ifx\@current\@pkgextension
688     \@latex@error
689     {\noexpand\LoadClass in package file}%
690     {You may only use \noexpand\LoadClass in a class file.}%
691   \fi
692   \@fileswithoptions\@clsextension}
693 \@onlypreamble\LoadClass
(End of definition for \LoadClass.)

```

`\@loadwithoptions` Pass the current option list on to a class or package. #1 is `\@cls-or-pkgextension`, #2 is `\RequirePackage` or `\LoadClass`, #3 is the class or package to be loaded.

```

694 \</2kernel>
695 \<latexrelease>\IncludeInRelease{2021/06/01}%
696 \<latexrelease>          {\@loadwithoptions}{Raw option lists load with options}%
697 \<*2kernel | latexrelease>
698 \def\@loadwithoptions#1#2#3{%
699   \expandafter\let\csname opt@#3.#1\expandafter\endcsname
700     \csname opt@\@currname.\@current\endcsname
701   \expandafter\let\csname @raw@opt@#3.#1\expandafter\endcsname
702     \csname @raw@opt@\@currname.\@current\endcsname
703   #2{#3}}
704 \</2kernel | latexrelease>
705 \<latexrelease>\EndIncludeInRelease

```

```

706 <latexrelease>\IncludeInRelease{0000/00/00}
707 <latexrelease>                {\@loadwithoptions}{Raw option lists load with options}%
708 <latexrelease>\def\@loadwithoptions#1#2#3{%
709 <latexrelease>  \expandafter\let\csname opt@#3.#1\expandafter\endcsname
710 <latexrelease>        \csname opt@#@currname.\@current\endcsname
711 <latexrelease>    #2{#3}}
712 <latexrelease>\EndIncludeInRelease
713 <*2ekernel>

714 \@onlypreamble\@loadwithoptions

(End of definition for \@loadwithoptions.)

```

**\LoadClassWithOptions** Load class ‘#1’ with the current option list.

```

715 \def\LoadClassWithOptions{%
716   \@loadwithoptions\@clsextension\LoadClass}
717 \@onlypreamble\LoadClassWithOptions

(End of definition for \LoadClassWithOptions.)

```

**\RequirePackageWithOptions** Load package ‘#1’ with the current option list.

```

718 </2ekernel>
719 <*2ekernel | latexrelease>
720 <latexrelease>\IncludeInRelease{2020/10/01}%
721 <latexrelease>                {\RequirePackageWithOptions}{Unused options issue}%
722 \def\RequirePackageWithOptions{%

```

The resetting of the unprocessed options is now done on a par package basis.

```

723   \AtEndOfPackage{\expandafter\let
724                   \csname unprocessedoptions-\@currname.\@current\endcsname
725                   \relax}%
726   \@loadwithoptions\@pkgextension\RequirePackage}
727 \@onlypreamble\RequirePackageWithOptions
728 </2ekernel | latexrelease>
729 <latexrelease>\EndIncludeInRelease

730 <latexrelease>\IncludeInRelease{0000/00/00}%
731 <latexrelease>                {\RequirePackageWithOptions}{Unused options issue}%
732 <latexrelease>
733 <latexrelease>\def\RequirePackageWithOptions{%
734 <latexrelease>  \AtEndOfPackage{\let\@unprocessedoptions\relax}%
735 <latexrelease>  \@loadwithoptions\@pkgextension\RequirePackage}
736 <latexrelease>\EndIncludeInRelease
737 <*2ekernel>

```

(End of definition for \RequirePackageWithOptions.)

**\usepackage** To begin with, \usepackage produces an error. This is reset by \documentclass.

```

738 \def\usepackage#1#{%
739   \@latex@error
740   {\noexpand \usepackage before \string\documentclass}%
741   {\noexpand \usepackage may only appear in the document
742    preamble, i.e.,\MessageBreak
743    between \noexpand\documentclass and
744    \string\begin{document}.}%
745   \@gobble}
746 \@onlypreamble\usepackage

```

(End of definition for \usepackage.)

**\NeedsTeXFormat** Check that the document is running on the correct system.

```
747 \def\NeedsTeXFormat#1{%
748   \def\reserved@a{#1}%
749   \ifx\reserved@a\fmtname
750     \expandafter\@needsformat
751   \else
752     \@latex@error{This file needs format ‘\reserved@a’%
753       \MessageBreak but this is ‘\fmtname’}{%
754       The current input file will not be processed
755       further,\MessageBreak
756       because it was written for some other flavor of
757       TeX.\MessageBreak\@ehd}%
```

If the file is not meant to be processed by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> we stop inputting it, but we do not end the run. We just end inputting the current file.

```
758   \endinput \fi}
759 \@onlypreamble\NeedsTeXFormat

760 \def\@needsformat{%
761   \@ifnextchar[%
762     \@needsformat
763   {}
764 \@onlypreamble\@needsformat

765 \def\@needsformat[#1]{%
766   \ifl@t@r\fmtversion{#1}{}%
767   {\@latex@warning@ono@line
768     {You have requested release ‘#1’ of LaTeX,\MessageBreak
769     but only release ‘\fmtversion’ is available}}
770 \@onlypreamble\@needsformat
```

(End of definition for \NeedsTeXFormat.)

**\NeedsDocumentMetadata** Check that \DocumentMetadata has been used.

```
771 \protected\def\NeedsDocumentMetadata{%
772   \IfDocumentMetadataF{%
773     \@latex@error{This file needs \string\DocumentMetadata}%
774     {The current input file will not be processed
775     further,\MessageBreak
776     because the document didn’t start with \string\DocumentMetadata.%
777     \MessageBreak\@ehd}}
778   \IfDocumentMetadataF{\endinput}}%
```

(End of definition for \NeedsDocumentMetadata.)

**\zap@space** \zap@space foo⟨space⟩\@empty removes all spaces from foo that are not protected by { } groups.

```
779 \def\zap@space#1 #2{%
780   #1%
781   \ifx#2\@empty\else\expandafter\zap@space\fi
782   #2}
```

(End of definition for \zap@space.)

`\@fileswithoptions` The common part of `\documentclass` and `\usepackage`.

```

783 </2ekernel>
784 <latexrelease>\IncludeInRelease{2024/06/01}%
785 <latexrelease>          {\@fileswithoptions}{Check Group}%
786 <*2ekernel | latexrelease>
787 \def\@fileswithoptions#1{%
788     \ifnum\currentgrouplevel>\z@
789     \latex@error
790     {Loading a class or package in a group}%
791     {Classes and packages should only be loaded at the top level}%
792     \fi
793     \@ifnextchar[%]
794     {\@fileswith@ptions#1}%
795     {\@fileswith@ptions#1[]}}
796 </2ekernel | latexrelease>
797 <latexrelease>\EndIncludeInRelease
798 <latexrelease>\IncludeInRelease{0000/00/00}%
799 <latexrelease>          {\@fileswithoptions}{Check Group}%
800 <latexrelease>\def\@fileswithoptions#1{%
801 <latexrelease>  \@ifnextchar[%]
802 <latexrelease>    {\@fileswith@ptions#1}%
803 <latexrelease>    {\@fileswith@ptions#1[]}}
804 <latexrelease>\EndIncludeInRelease
805 <*2ekernel>
806 \@onlypreamble\@fileswithoptions

807 \def\@fileswith@ptions#1[#2]#3{%
808     \@ifnextchar[%]
809     {\@fileswith@ptions#1[#{#2}]#3}%
810     {\@fileswith@ptions#1[#{#2}]#3[]}}
811 \@onlypreamble\@fileswith@ptions

```

Then we do some work.

First of all, we define the global variables. Then we look to see if the file has already been loaded. If it has, we check that it was first loaded with at least the current options. If it has not, we add the current options to the package options, set the default version to be 0000/00/00, and load the file if we can find it. Then we check the version number.

Finally, we restore the old file name, reset the default option, and we set the catcode of `@`.

For classes, we can immediately process the file. For other types, `#2` could be a comma separated list, so loop through, processing each one separately.

```

812 </2ekernel>
813 <latexrelease>\IncludeInRelease{2020/10/01}%
814 <latexrelease>          {\@fileswith@ptions}{ifx tests in \@fileswith@ptions}%
815 <*2ekernel | latexrelease>
816 \def\@fileswith@ptions#1[#2]#3[#4]{%
817     \ifx#1\@clsextension
818     \ifx\@classoptionslist\relax
819     \protected@xdef\@classoptionslist{\zap@space#2 \@empty}%

```

Save raw class list.

```

820     \gdef\@raw@classoptionslist{#2}%

```

```

821     \def\reserved@a{%
822         \@onefilewithoptions#3[#{#2}][#{#4}]#1%
823         \@documentclasshook}%
824     \else
825         \def\reserved@a{%
826             \@onefilewithoptions#3[#{#2}][#{#4}]#1%
827         \fi
828     \else

```

build up a list of calls to `\@onefilewithoptions` (one for each package) without thrashing the parameter stack.

```

829     \def\reserved@b##1,{%

```

If `#1` is `\@nnil` we have reached the end of the list (older version used `\@nil` here but `\@nil` is undefined so `\ifx` equal to all undefined commands)

```

830     \ifx\@nnil##1\relax\else

```

If `\ifx\@nnil##1\@nnil` is true then `#1` is (presumably) empty (Older code used `\relax` which is slightly easier to get into `#1` by mistake, which would spoil this test.)

```

831     \ifx\@nnil##1\@nnil\else

832         \noexpand\@onefilewithoptions##1[{\unexpanded{#2}}][#{#4}]%
833         \noexpand\@pkgextension
834     \fi
835     \expandafter\reserved@b
836 \fi}%
837 \edef\reserved@a{\zap@space#3 \@empty}%
838 \edef\reserved@a{\expandafter\reserved@b\reserved@a,\@nnil,}%
839 \fi
840 \reserved@a}
841 </2ekernel | latexrelease>
842 <latexrelease>\EndIncludeInRelease
843 <latexrelease>\IncludeInRelease{2017/01/01}%
844 <latexrelease>    {\@fileswith@pti@ns}{\ifx tests in \@fileswith@pti@ns}%
845 <latexrelease>\def\@fileswith@pti@ns#1[#2]#3[#4]{%
846 <latexrelease>    \ifx#1\@clsextension
847 <latexrelease>        \ifx\@classoptionslist\relax
848 <latexrelease>            \xdef\@classoptionslist{\zap@space#2 \@empty}%
849 <latexrelease>            \def\reserved@a{%
850 <latexrelease>                \@onefilewithoptions#3[#{#2}][#{#4}]#1%
851 <latexrelease>                \@documentclasshook}%
852 <latexrelease>        \else
853 <latexrelease>            \def\reserved@a{%
854 <latexrelease>                \@onefilewithoptions#3[#{#2}][#{#4}]#1%
855 <latexrelease>            \fi
856 <latexrelease>        \else
857 <latexrelease>            \def\reserved@b##1,{%
858 <latexrelease>                \ifx\@nnil##1\relax\else
859 <latexrelease>                    \ifx\@nnil##1\@nnil\else
860 <latexrelease>                        \noexpand\@onefilewithoptions##1[#{#2}][#{#4}]%
861 <latexrelease>                        \noexpand\@pkgextension
862 <latexrelease>                    \fi
863 <latexrelease>                    \expandafter\reserved@b
864 <latexrelease>                \fi}%
865 <latexrelease>            \edef\reserved@a{\zap@space#3 \@empty}%

```

```

866 <latexrelease> \edef\reserved@a{\expandafter\reserved@b\reserved@a,\@nnil,}%
867 <latexrelease> \fi
868 <latexrelease> \reserved@a}

869 <latexrelease>\EndIncludeInRelease
870 <latexrelease>\IncludeInRelease{0000/00/00}%
871 <latexrelease> {\@fileswith@pti@ns}{ifx tests in \@fileswith@pti@ns}%
872 <latexrelease>\def\@fileswith@pti@ns#1[#2]#3[#4]{%
873 <latexrelease> \ifx#1\@clsextension
874 <latexrelease> \ifx\@classoptionslist\relax
875 <latexrelease> \xdef\@classoptionslist{\zap@space#2 \@empty}%
876 <latexrelease> \def\reserved@a{%
877 <latexrelease> \@onefilewithoptions#3[{#2}][{#4}]#1%
878 <latexrelease> \@documentclasshook}%
879 <latexrelease> \else
880 <latexrelease> \def\reserved@a{%
881 <latexrelease> \@onefilewithoptions#3[{#2}][{#4}]#1}%
882 <latexrelease> \fi
883 <latexrelease> \else
884 <latexrelease> \def\reserved@b##1,{%
885 <latexrelease> \ifx\@nil##1\relax\else
886 <latexrelease> \ifx\relax##1\relax\else
887 <latexrelease> \noexpand\@onefilewithoptions##1[{#2}][{#4}]%
888 <latexrelease> \noexpand\@pkgextension
889 <latexrelease> \fi
890 <latexrelease> \expandafter\reserved@b
891 <latexrelease> \fi}%
892 <latexrelease> \edef\reserved@a{\zap@space#3 \@empty}%
893 <latexrelease> \edef\reserved@a{%
894 <latexrelease> \expandafter\reserved@b\reserved@a,\@nil,}%
895 <latexrelease> \fi
896 <latexrelease> \reserved@a}
897 <latexrelease>\EndIncludeInRelease
898 <*2ekernel>

899 \@onlypreamble\@fileswith@pti@ns

```

This macro is used when loading packages or classes.

`\load@onefilewithoptions` Have the main argument as #1, so we only need one `\expandafter` above.

```

900 </2ekernel>
901 <*2ekernel | latexrelease>
902 <latexrelease>\IncludeInRelease{2020/10/01}%
903 <latexrelease> {\@onefilewithoptions}{Hooks and unused options issue}%

```

Here this macro is called `\@onefilewithoptions`, but further ahead in this file it is renamed to `\load@onefilewithoptions`, and `\@onefilewithoptions` becomes a wrapper around this, used for bookkeeping when rolling back. Therefore, when in `latexrelease`, we need to define `\load@onefilewithoptions` instead, thus the extra guarded `\def` line below:

```

904 <*2ekernel>
905 \def\@onefilewithoptions#1[#2][#3]#4{%
906 </2ekernel>
907 <latexrelease>\def\load@onefilewithoptions#1[#2][#3]#4{%

```

We have to sanitise file names, so that something like

```

\usepackage{some/local/path/array}
\usepackage{array}

```

won't load `array.sty` twice. It is remotely possible that those are two different files, but as a matter of principles, we will consider that the base file name uniquely identifies a package, regardless of where it lives. This assumption already holds for file hooks, for example, which address the hook to a file by its base name only.

We'll use `\@expl@@@filehook@set@curr@file@@nNN{#1.#4}\reserved@a\reserved@b` to parse the file name and return the `<path>` and `<base+ext>` in separate token lists. Further ahead, most operations use `\@currname` which doesn't have a path attached to it; only few actions prepend `\@currpath` to `\@currname` (namely loading, as we have to respect the given path).

A file substitution isn't followed just yet because at this point we are parsing user input, so the file is still what the user asked for, and not the file actually loaded.

```

908 \@expl@@@filehook@set@curr@file@@nNN{#1.#4}\reserved@a\reserved@b
909 \edef\reserved@c{\def\noexpand\reserved@c####1%
910 \detokenize\expandafter{\expanded{.#4}}}%
911 \noexpand\@nil{\def\noexpand\reserved@a{####1}}\reserved@c
912 \expandafter\reserved@c\reserved@a\@nil
913 \@pushfilename
914 \xdef\@currname{\string@makeletter\reserved@a}%
915 \xdef\@currpath{\ifx\reserved@b\@empty\else\reserved@b\fi}%
916 \global\let\@currentx#4%

```

The command `\ver@<file>.<ext>` is used to signal that a package is already loaded, either because it is in fact loaded, or because its loading was suppressed. In minimal installations, said package may not exist but still have its loading suppressed with `\ver@<file>.<ext>`, so before checking if the file exists we have to check that we do need to load it with `\@ifl@aded`. If we don't, then there's no point in checking for a typo or load-disabling.

```

917 \@ifl@aded\@currentx\@currname

```

In the current preferred approach, a key family name will exist for processing using `ltkeys`. In that case, we replace the previous package options with the new ones, then call the key handler. Otherwise, we use the more classical clash handler.

```

918 {%
919 \@ifundefined{opt@handler@\@currname.\@currentx}
920 {\@onefilewithoptions@clashchk{#2}}
921 {%
922 \expandafter\protected@edef
923 \csname opt@\@currname.\@currentx\endcsname
924 {\zap@space#2 \@empty}%
925 \expandafter\def
926 \csname @raw@opt@\@currname.\@currentx\expandafter\endcsname
927 \expandafter{#2}%
928 \@nameuse{opt@handler@\@currname.\@currentx}%
929 }%
930 }%
931 {\makeatletter

```

The next line seems to be necessary for 2.09 compatibility (the way the code is written there) This seems questionable and should be look at as in 2e it is definitely unnecessary at this point!

```

932 \@reset@ptions

```

First we take the  $\langle name \rangle$  and  $\langle ext \rangle$  given in the argument and check if the file exists, and issue an error otherwise asking for a correction with  $\backslash@missingfileerror$ . For checking if the file exists we use  $\backslash@currpath$  (usually empty) before  $\backslash@currname$ .

```
933      \IfFileExists{\@currpath\@currname.\@currentext}{}%
934      {\@missingonefilewithoptions{#2}}%
```

If  $\backslash@currname$  is empty (the user replied to the “Enter file name” prompt with  $\langle RETURN \rangle$ ), so stop here (do  $\backslash@popfilename$  to pop the item just added above).

This  $\backslash@gobble$  omits the date check at the end.

```
935      \ifx\@currname\@empty
936      \expandafter\@gobble
937      \else
```

If the file exists, check if it was load-prevented, and otherwise do the bookkeeping with  $\backslash@filehook@file@push$  then call  $\backslash@set@curr@file$  to set  $\backslash@curr@file$  (and do any required substitution), then actually load the class/package with  $\backslash@load@onefile@withoptions$ .  $\backslash@set@curr@file$  also needs the file path.

```
938      \@disable@packageload@do{\@currname.\@currentext}%
939      {\@expl@@@filehook@file@push@@
940      \set@curr@file{\@currpath\@currname.\@currentext}%
941      \@filehook@set@CurrentFile
```

The  $\backslash@set@curr@file$  line above might have replaced the file, so  $\backslash@currname$  and  $\backslash@currentext$  may no longer hold the actual package being loaded, so in that case we need to update these two token lists ( $\backslash@curr@file$  holds the file name after replacement, so we parse that).

The requested file is saved in  $\backslash@currpkg@reqd$  to be used in  $\backslash@InputIfFileExists$  later: if the updated  $\backslash@currname$  and  $\backslash@currentext$  are used we lose track of the substitution, so  $\backslash@CurrentFile$  and  $\backslash@CurrentFileUsed$  will be (incorrectly) the same.

```
942      \expandafter\@swaptwoargs\expandafter
943      {\@expandafter{\@currpkg@reqd}}%
944      {% <
```

$\backslash@currpkg@reqd$  doesn’t take a path because it is used later to assign  $\backslash@opt@...$  and  $\backslash@ver@...$

```
945      \edef\@currpkg@reqd{\@currname.\@currentext}%
946      \ifx\CurrentFile\CurrentFileUsed
947      \else
948      \filename@parse\@curr@file
949      \edef\@currpath{\string@makeletter\filename@area}%
950      \edef\@currname{\string@makeletter\filename@base}%
951      \edef\@currentext{\string@makeletter\filename@ext}%
952      \fi
953      \load@onefile@withoptions{#2}%
954      \def\@currpkg@reqd%\@currpkg@reqd%
955      }% >
```

Now just clean up and exit.

```
956      \@expl@@@filehook@file@pop@@}%
957      \expandafter\@firstofone
958      \fi}%
```

Except in the case where \@currname is empty, the date is checked against the date marked in the package file:

```

959 {\ifl@ter\@currentx{\@currname}{#3}{}%
960 {\@latex@warning@no@line
961 {You have requested,\on@line,
962 version\MessageBreak
963 '#3' of \@cls@pkg\space \@currname,\MessageBreak
964 but only version\MessageBreak
965 '\csname ver@\@currname.\@currentx\endcsname'\MessageBreak
966 is available}}}%

967 \ifx\@currentx\@clsextension\let\LoadClass\@twoloadclasserror\fi}%
968 \@popfilename
969 \@reset@options}

```

If the package is already loaded, check that there were no option clashes.

```

\@onefilewithoptions@clashchk
970 \def\@onefilewithoptions@clashchk#1{%
971 \if@options\@currentx{\@currname}{#1}{}%
972 {\@latex@error
973 {Option clash for \@cls@pkg\space \@currname}%
974 {The package \@currname\space has already been loaded
975 with options:\MessageBreak
976 \space\space[\@optionlist{\@currname.\@currentx}]\MessageBreak
977 There has now been an attempt to load it
978 with options\MessageBreak
979 \space\space[#1]\MessageBreak
980 Adding the global options:\MessageBreak
981 \space\space
982 \@optionlist{\@currname.\@currentx},#1\MessageBreak
983 to your \noexpand\documentclass declaration may fix this.%
984 \MessageBreak
985 Try typing \space <return> \space to proceed.}}%
986 \@firstofone}

987 \let\@currpkg@reqd\@empty
988 \@onlypreamble\@onefilewithoptions
989 \let\@unprocessedoptions\@undefined

```

Now the action taken when a file is not found. Path must be included here as it eventually leads to a file lookup.

```

990 \def\@missing@onefilewithoptions#1{%
991 \@missingfileerror{\@currpath\@currname}\@currentx
992 \global\let\@currpath\@missingfile@area
993 \global\let\@currname\@missingfile@base
994 \global\let\@currentx\@missingfile@ext}

```

Now the code that actually does the file loading:

```

\load@onefile@withoptions
995 \def\load@onefile@withoptions#1{%
996 \let\CurrentOption\@empty
997 \@reset@options

```

Grab everything in a macro, so the parameter stack is popped before any processing begins.

```

998 \def\reserved@a{%
999 \pass@options\@currentx{#1}\@currname}%

1000 \expandafter\let
1001 \csname opt@\@currpkg@reqd\expandafter\endcsname
1002 \csname opt@\@currname.\@currentx\endcsname
1003 \expandafter\let
1004 \csname @raw@opt@\@currpkg@reqd\expandafter\endcsname
1005 \csname @raw@opt@\@currname.\@currentx\endcsname
1006 \global\expandafter
1007 \let\csname ver@\@currname.\@currentx\endcsname\@empty

```

We initialize `\...-h@@k` here and only if we load the file so that it remains undefined otherwise.

```

1008 \expandafter\let\csname\@currname.\@currentx-h@@k\endcsname\@empty

```

When the current extension is `\@pkgextension` we are loading a package otherwise, if it is `\@clsextension`, a class, so depending on that we execute different hooks. If the extension is neither, then it is another type of file without special hooks.

```

1009 %-----
1010 \ifx\@currentx\@pkgextension
1011 \UseHook{package/before}%
1012 \UseOneTimeHook{package/\@currname/before}%
1013 \else
1014 \ifx\@currentx\@clsextension
1015 \UseHook{class/before}%
1016 \UseOneTimeHook{class/\@currname/before}%
1017 \fi
1018 \fi

```

Now actually load the file (at this point we are certain it exists, but use `\InputIfFileExists` so that file hooks are executed). `\@currpath` is needed here too.

```

1019 \InputIfFileExists{\@currpath\@currpkg@reqd}{}%
1020 {\@latex@error
1021 {The \@cls@pkg\space\@currpkg@reqd\space failed to load}\@ehd}%
1022 %-----

```

In older versions of the code `\@unprocessedoptions` would generate an error for each specified option in a package unless a `\ProcessOptions` has appeared in the package file.

This has changed in 2020. We now use a separate macro per package to avoid interference in case of nested packages. The whole code for handling this issue (GitHub 22) was provided by Hironobu Yamashita, thanks for that.

```

1023 \expandafter\let\csname unprocessedoptions-\@currname.\@currentx\endcsname
1024 \@@unprocessedoptions
1025 \csname\@currname.\@currentx-h@@k\endcsname
1026 \expandafter\let\csname\@currname.\@currentx-h@@k\endcsname
1027 \undefined

```

Catch the case where the packages has handled the options and redefined `\@unprocessedoptions` to `\relax` (old interface). In that case no error should be produced.

```

1028 \ifx\@unprocessedoptions\relax
1029 \let\@unprocessedoptions\undefined

```

Otherwise run the per package set of unused options.

```

1030 \else
1031 \csname unprocessedoptions-\@currname.\@current\endcsname
1032 \fi

```

In either case we drop the macro afterwards as it is no longer needed.

```

1033 \expandafter\let
1034 \csname unprocessedoptions-\@currname.\@current\endcsname
1035 \@undefined

```

And same procedure, James, when we are finished loading, except that the hook order is now reversed.

```

1036 %-----
1037 \ifx\@current\@pkgextension
1038 \UseOneTimeHook{package/\@currname/after}%
1039 \UseHook{package/after}%
1040 \else
1041 \ifx\@current\@clsextension
1042 \UseOneTimeHook{class/\@currname/after}%
1043 \UseHook{class/after}%
1044 \fi
1045 \fi}%
1046 %-----
1047 \@ifl@aded\@current\@currname{}\reserved@a{}

```

Now declare the non-generic package and class hooks used above:

```

1048 \NewHook{package/before}
1049 \NewHook{class/before}
1050 \NewReversedHook{package/after}
1051 \NewReversedHook{class/after}

1052 </2ekernel | latexrelease>
1053 <latexrelease>\EndIncludeInRelease
1054 <latexrelease>\IncludeInRelease{0000/00/00}%
1055 <latexrelease> \{\@onefilewithoptions\}{Hooks and unused options issue}%
1056 <latexrelease>

```

Because of the way \@onfilewithoptions is changed for rollback handling below we have to define \load@onefilewithoptions when rolling back!

```

1057 <latexrelease>\def\load@onefilewithoptions#1[#2][#3]#4{%
1058 <latexrelease> \@pushfilename
1059 <latexrelease> \xdef\@currname{#1}%
1060 <latexrelease> \global\let\@current#4%
1061 <latexrelease> \let\CurrentOption\@empty
1062 <latexrelease> \@reset@ptions
1063 <latexrelease> \makeatletter
1064 <latexrelease> \def\reserved@a{%
1065 <latexrelease> \@ifl@aded\@current{#1}%
1066 <latexrelease> \{\@if@ptions\@current{#1}#{2}\}%
1067 <latexrelease> \{\@latex@error
1068 <latexrelease> \{Option clash for \@cls@pkg\space #1\}%
1069 <latexrelease> \{The package #1 has already been loaded
1070 <latexrelease> \space\space\@optionlist{#1.\@current}\}\MessageBreak
1071 <latexrelease> \space\space\@optionlist{#1.\@current}\}\MessageBreak
1072 <latexrelease> \{There has now been an attempt to load it

```

```

1073 <latexrelease>          with options\MessageBreak
1074 <latexrelease>          \space\space[#2]\MessageBreak
1075 <latexrelease>          Adding the global options:\MessageBreak
1076 <latexrelease>          \space\space
1077 <latexrelease>          \@optionlist{#1.\@current},#2\MessageBreak
1078 <latexrelease>          to your \noexpand\documentclass declaration may fix this.%
1079 <latexrelease>          \MessageBreak
1080 <latexrelease>          Try typing \space <return> \space to proceed.}}}%
1081 <latexrelease>          {\@pass@options\@current{#2}{#1}%
1082 <latexrelease>          \global\expandafter
1083 <latexrelease>          \let\csname ver@\@currname.\@current\endcsname\@empty
1084 <latexrelease>          \expandafter\let\csname\@currname.\@current-h@@k\endcsname\@empty
1085 <latexrelease>          \InputIfFileExists
1086 <latexrelease>          {\@currname.\@current}%
1087 <latexrelease>          {}%
1088 <latexrelease>          {\@missingfileerror\@currname\@current}%
1089 <latexrelease>          \let\@unprocessedoptions\@unprocessedoptions
1090 <latexrelease>          \csname\@currname.\@current-h@@k\endcsname
1091 <latexrelease>          \expandafter\let\csname\@currname.\@current-h@@k\endcsname
1092 <latexrelease>          \undefined
1093 <latexrelease>          \@unprocessedoptions}%
1094 <latexrelease>          \@ifl@ter\@current{#1}{#3}{}%
1095 <latexrelease>          {\@latex@warning@no@line
1096 <latexrelease>          {You have requested,\on@line,
1097 <latexrelease>          version\MessageBreak
1098 <latexrelease>          ‘#3’ of \cls@pkg\space #1,\MessageBreak
1099 <latexrelease>          but only version\MessageBreak
1100 <latexrelease>          ‘\csname ver@#1.\@current\endcsname’\MessageBreak
1101 <latexrelease>          is available}}}%
1102 <latexrelease>          \ifx\@current\@clsextension\let\LoadClass\@twoloadclasserror\fi
1103 <latexrelease>          \popfilename
1104 <latexrelease>          \@reset@options}%
1105 <latexrelease>          \reserved@a}
1106 <latexrelease>
1107 <latexrelease>\let \load@onefile@withoptions \undefined
1108 <latexrelease>\let \@missing@onefilewithoptions \undefined
1109 <latexrelease>
1110 <latexrelease>\EndIncludeInRelease
1111 <*2ekernel>

```

*(End of definition for \@fileswithoptions and others.)*

**\@@fileswith@pti@ns** Save the definition (for error checking).

```

1112 \let\@@fileswith@pti@ns\@fileswith@pti@ns
1113 \@onlypreamble\@@fileswith@pti@ns

```

*(End of definition for \@@fileswith@pti@ns.)*

**\@reset@ptions** Reset the default option, and clear lists of declared options.

```

1114 \def\@reset@ptions{%
1115   \global\ifx\@current\@clsextension
1116     \let\default@ds\OptionNotUsed
1117   \else
1118     \let\default@ds\unknownoptionerror
1119   \fi

```

```

1120 \global\let\ds@\empty
1121 \global\let\@declaredoptions\empty}
1122 \@onlypreamble\@resetoptions

```

(End of definition for \@resetoptions.)

## 4.1 Hooks

Allow code to be saved to be executed at specific later times.

Here we save things in macros. I considered using toks registers (and \addto@hook from the NFSS code), but that would require stacking the contents in the case of required packages, so just generate a new macro for each package.

\@begindocumenthook Stuff to appear at the beginning or end of the document.

```

\@enddocumenthook
1123 \ifx\@begindocumenthook\undefined
1124 \let\@begindocumenthook\empty
1125 \fi
1126 \let\@enddocumenthook\empty

```

(End of definition for \@begindocumenthook and \@enddocumenthook.)

\AtEndOfPackage The access functions.

```

\AtEndOfClass
\AtBeginDocument
\AtEndDocument
1127 \def\AtEndOfPackage{%
1128 \expandafter\g@addto@macro\csname\@currname.\@current-h@@k\endcsname}
1129 \let\AtEndOfClass\AtEndOfPackage
1130 \@onlypreamble\AtEndOfPackage
1131 \@onlypreamble\AtEndOfClass
1132 \</2ekernel>
1133 \<*2ekernel | latexrelease>
1134 \<latexrelease>\IncludeInRelease{2020/10/01}%
1135 \<latexrelease> \{\AtBeginDocument\}{Use hook system}%
1136 \DeclareRobustCommand\AtBeginDocument{\AddToHook{begindocument}}
1137 \DeclareRobustCommand\AtEndDocument {\AddToHook{enddocument}}
1138 %\DeclareRobustCommand\AtEndDocument {\AddToHook{env/document/end}} % alternative impl
1139 \</2ekernel | latexrelease>
1140 \<latexrelease>\EndIncludeInRelease
1141 \<latexrelease>\IncludeInRelease{0000/00/00}%
1142 \<latexrelease> \{\AtBeginDocument\}{Use hook system}%
1143 \<latexrelease>
1144 \<latexrelease>\DeclareRobustCommand\AtBeginDocument{\g@addto@macro\@begindocumenthook}
1145 \<latexrelease>\DeclareRobustCommand\AtEndDocument{\g@addto@macro\@enddocumenthook}
1146 \<latexrelease>
1147 \<latexrelease>\EndIncludeInRelease
1148 \<*2ekernel>

```

In its initial implementation (not using the hook system) \AtBeginDocument was made \@onlypreamble because using it later had no effect whatsoever, thus was most certainly an unintended programming error. With the reimplementaion, using the begindocument hook internally, this has changed because adding to a onetime hook after it has already been used simply executes the additional code immediately. We therefore no longer generate an error if it is used inside the document so that \AddToHook{begindocument} and \AtBeginDocument are truly equivalent (as claimed in the hook documentation).

```

1149 %\@onlypreamble\AtBeginDocument

```

(End of definition for \AtEndOfPackage and others.)

\@cls@pkg The current file type.

```
1150 </2ekernel>
1151 < *2ekernel | latexrelease>
1152 < latexrelease> \IncludeInRelease{2024/11/01}%
1153 < latexrelease> { \@cls@pkg } { Allow for more extensions }%
1154 \def \@cls@pkg {%
1155   \ifx \@currentx \@clsextension
1156     document class%
1157   \else
1158     \ifx \@currentx \@pkgextension
1159       package%
1160     \else
1161       file%
1162     \fi
1163   \fi}
1164 < /2ekernel | latexrelease>
1165 < latexrelease> \EndIncludeInRelease
1166 < latexrelease> \IncludeInRelease{0000/00/00}%
1167 < latexrelease> { \@cls@pkg } { Allow for more extensions }%
1168 < latexrelease>
1169 < latexrelease> \def \@cls@pkg {%
1170 < latexrelease>   \ifx \@currentx \@clsextension
1171 < latexrelease>     document class%
1172 < latexrelease>   \else
1173 < latexrelease>     package%
1174 < latexrelease>   \fi}
1175 < latexrelease> \EndIncludeInRelease
1176 < *2ekernel>
1177 \@onlypreamble \@cls@pkg
```

(End of definition for \@cls@pkg.)

\@unknownoptionerror Bad option.

```
1178 \def \@unknownoptionerror {%
1179   \latexerror
1180     {Unknown option '\CurrentOption' for \@cls@pkg\space'\@currname'}%
1181     {The option '\CurrentOption' was not declared in
1182       \@cls@pkg\space'\@currname', perhaps you\MessageBreak
1183       misspelled its name.
1184       Try typing \space <return>
1185       \space to proceed.}}
1186 \@onlypreamble \@unknownoptionerror
```

(End of definition for \@unknownoptionerror.)

\@@unprocessedoptions Declare an error for each option, unless a \ProcessOptions occurred.

```
1187 \def \@@unprocessedoptions {%
1188   \ifx \@currentx \@pkgextension
1189     \protected@edef \@curroptions { \optionlist { \@currname . \@currentx } }%
1190     \@for \CurrentOption : = \@curroptions \do {%
1191       \ifx \CurrentOption \@empty \else \@unknownoptionerror \fi}%
1192   \fi}
```

```

1192 \fi}
1193 \@onlypreamble\@unprocessedoptions
1194 \@onlypreamble\@unprocessedoptions

```

*(End of definition for \@unprocessedoptions.)*

`\@badrequireerror` `\RequirePackage` or `\LoadClass` occurs in the options section.

```

1195 \def\@badrequireerror#1[#2]#3[#4]{%
1196 \latexerror
1197 {\noexpand\RequirePackage or \noexpand\LoadClass
1198 in Options Section}%
1199 {The \@cls@pkg\space '@\currname' is defective.\MessageBreak
1200 It attempts to load '#3' in the options section, i.e.,\MessageBreak
1201 between \noexpand\DeclareOption and \string\ProcessOptions.}}
1202 \@onlypreamble\@badrequireerror

```

*(End of definition for \@badrequireerror.)*

`\@twoloadclasserror` Two `\LoadClass` in a class.

```

1203 \def\@twoloadclasserror{%
1204 \latexerror
1205 {Two \noexpand\LoadClass commands}%
1206 {You may only use one \noexpand\LoadClass in a class file}}
1207 \@onlypreamble\@twoloadclasserror

```

*(End of definition for \@twoloadclasserror.)*

`\@twoclasseserror` Two `\documentclass` or `\documentstyle`.

```

1208 \def\@twoclasseserror#1#{%
1209 \latexerror
1210 {Two \noexpand\documentclass or \noexpand\documentstyle commands}%
1211 {The document may only declare one class.}\@gobble}
1212 \@onlypreamble\@twoclasseserror

```

*(End of definition for \@twoclasseserror.)*

## 4.2 Providing shipment

`\two@digits` Prefix a number less than 10 with '0'.

```

1213 \def\two@digits#1{\ifnum#1<10 0\fi\number#1}

```

*(End of definition for \two@digits.)*

`\filecontents*` This environment implements inline files. The star-form does not write extra comments

`\endfilecontents` into the file.

```

1214 </2ekernel>
1215 <*2ekernel | latexrelease>
1216 <latexrelease>\IncludeInRelease{2020/10/01}%
1217 <latexrelease> \filecontents*{Define \@curr@file directly (gh/220)}%
1218 %

```

We use `@tempswa` to mean no preamble writing and reuse `@filesw` to indicate no overwriting:

```

1219 \def\filecontents{\@tempswatrue\@fileswtrue
1220 \ifnextchar[\filec@ntents@opt\filec@ntents
1221 }
1222 \@namedef{filecontents*}{\@tempswafalse\@fileswtrue
1223 \ifnextchar[\filec@ntents@opt\filec@ntents
1224 }

```

To handle the optional argument we execute for each option the command `\filec@ntents@OPTION` if it exist or complain about unknown option.

```

1225 \def\filec@ntents@opt[#1]{%
1226 \edef\@fortmp{\zap@space#1 \@empty}%
1227 \@for\reserved@a:=\@fortmp\do{%
1228 \ifcsname filec@ntents@\reserved@a\endcsname
1229 \csname filec@ntents@\reserved@a\endcsname
1230 \else
1231 \@latex@error{Unknown filecontents option \reserved@a}%
1232 {Valid options are force (or overwrite), nosearch, noheader, nowarn}%
1233 \fi}%
1234 \filec@ntents
1235 }

```

Option `force` (or `overwrite`) changes the overwriting switch

```

1236 \let\filec@ntents@force\@fileswfalse
1237 \let\filec@ntents@overwrite\@fileswfalse % alternative name

```

and option `noheader` the preamble switch (which is equivalent to using the star form of the environment).

```

1238 \let\filec@ntents@noheader\@tempswafalse

```

Option `nosearch` only checks the current directory not the whole T<sub>E</sub>X tree for the existence of the file to write.

```

1239 \def\filec@ntents@nosearch{%
1240 \let\filec@ntents@checkdir\@currdir
1241 \def\filec@ntents@where{in current directory}}

```

By default we search the whole tree:

```

1242 \let\filec@ntents@checkdir\@empty
1243 \def\filec@ntents@where{exists on the system}

```

Option `nowarn` does not show any warning on the terminal but still writes it to the `.log`.

```

1244 \def\filec@ntents@nowarn{%
1245 \let\filec@ntents@warning\@latex@note@no@line
1246 }

```

By default we show terminal warnings.

```

1247 \let\filec@ntents@warning\@latex@warning@no@line
1248 \begingroup%
1249 \@tempcnta=1
1250 \loop
1251 \catcode\@tempcnta=12 %
1252 \advance\@tempcnta\@ne %
1253 \ifnum\@tempcnta<32 %
1254 \repeat %

```

```

1255 \catcode'\*=11 %
1256 \catcode'\^^M\active%
1257 \catcode'\^^L\active\let^^L\relax%
1258 \catcode'\^^I\active%

1259 \gdef\filec@ntents#1{%
1260   \set@curr@file{\filec@ntents@checkdir#1}%
1261   \edef\q@curr@file{"\@curr@file"}%

   LuaTeX has more writes (and 18 is safe here).

1262   \chardef\reserved@c\ifx\directlua\@undefined 15 \else 127 \fi%
1263   \openin\@inputcheck\q@curr@file \space %
1264   \ifeof\@inputcheck%
1265     \@latex@note@no@line%
1266     {Writing file '\@currdir\@curr@file'}%

1267   \ch@ck7\reserved@c\write\relax%
1268   \immediate\openout\reserved@c\q@curr@file\relax%
1269   \else%

1270   \if@filesw%
1271     \@latex@note@no@line%
1272     {File '\@curr@file' already \filec@ntents@where.\MessageBreak%
1273     Not generating it from this source}%
1274     \let\write\@gobbles%
1275     \let\closeout\@gobble%
1276   \else%

```

If we are overwriting, we try to make sure that the user is not by mistake overwriting the input file (`\jobname`). Of course, this only works for input files ending in `.tex`. If a different extension is used there is no way to see that we are overwriting ourselves!

```

1277   \edef\reserved@b{\detokenize\expandafter{\jobname}}%
1278   \ifx\@curr@file\reserved@b%
1279     \@fileswtrue%
1280   \else%
1281     \edef\reserved@b{\reserved@b\detokenize{.tex}}%
1282     \ifx\@curr@file\reserved@b
1283       \@fileswtrue%
1284     \fi%
1285   \fi%

```

We allocate a write channel but we open it only if it is (hopefully) safe. If not opened that means we are going to write on the terminal.

```

1286   \ch@ck7\reserved@c\write\relax%
1287   \if@filesw% % Foul ... trying to overwrite \jobname!
1288   \@latex@error{Trying to overwrite '\jobname.tex'}{You can't %
1289     write to the file you are reading from!\MessageBreak%
1290     Data is written to screen instead.}%
1291   \else%
1292     \filec@ntents@warning%
1293     {Writing or overwriting file '\@curr@file'}%
1294     \immediate\openout\reserved@c\q@curr@file\relax%
1295   \fi%
1296   \fi%
1297   \fi%

```

Closing the \@inputcheck is done here to avoid having to do this in each branch.

```

1298 \closein\@inputcheck%
1299 \if@tempswa%

1300 \immediate\write\reserved@c{%
1301 \@percentchar\@percentchar\space%
1302 \expandafter\@gobble\string\LaTeX2e file '@curr@file'^^J%
1303 \@percentchar\@percentchar\space generated by the %
1304 '@currentvir' \expandafter\@gobblefour\string\newenvironment^^J%
1305 \@percentchar\@percentchar\space from source 'jobname' on %
1306 \number\year/\two@digits\month/\two@digits\day.^^J%
1307 \@percentchar\@percentchar}%
1308 \fi%
1309 \let\do\@makeother\dospecials%

```

If there are active characters in the upper half (e.g., from inputenc) there would be confusion so we render everything harmless.

```

1310 \count@ 128\relax%
1311 \loop%
1312 \catcode\count@ 11\relax%
1313 \advance\count@ \@ne%
1314 \ifnum\count@<\@cclvi%
1315 \repeat%

1316 \edef\E{\@backslashchar end\string{\@currentvir\string}}%
1317 \edef\reserved@b{%
1318 \def\noexpand\reserved@b%
1319 #####1\E####2\E####3\relax}%
1320 \reserved@b{%
1321 \ifx\relax##3\relax%

```

There was no \end{filecontents}

```

1322 \immediate\write\reserved@c{##1}%
1323 \else%

```

There was a \end{filecontents}, so stop this time.

```

1324 \edef^^M{\noexpand\end{\@currentvir}}%
1325 \ifx\relax##1\relax%
1326 \else%

```

Text before the \end, write it with a warning.

```

1327 \latex@warning{Writing text '##1' before %
1328 \string\end{\@currentvir}\MessageBreak
1329 as last line of \@curr@file}%
1330 \immediate\write\reserved@c{##1}%
1331 \fi%
1332 \ifx\relax##2\relax%
1333 \else%

```

Text after the \end, ignore it with a warning.

```

1334 \latex@warning{%
1335 Ignoring text '##2' after \string\end{\@currentvir}}%
1336 \fi%
1337 \fi%
1338 ^^M}%

```

```

1339 \catcode'\^L\active%
1340 \let\L\@undefined%
1341 \def^^L{\expandafter\ifx\csname L\endcsname\relax\fi ^^J^^J}%
1342 \catcode'\^I\active%
1343 \let\I\@undefined%
1344 \def^^I{\expandafter\ifx\csname I\endcsname\relax\fi\space}%
1345 \catcode'\^M\active%
1346 \edef^^M##1^^M{%
1347 \noexpand\reserved@b##1\E\E\relax}}%
1348 \endgroup%

1349 </2ekernel | latexrelease>
1350 <latexrelease>\EndIncludeInRelease
1351 <latexrelease>\IncludeInRelease{2019/10/01}%
1352 <latexrelease> \{filec@ntents\}{Spaces in file names + optional arg}%
1353 <latexrelease>
1354 <latexrelease>\def\filecontents{\@tempswatrue\@fileswtrue
1355 <latexrelease> \@ifnextchar[\filec@ntents@opt\filec@ntents
1356 <latexrelease>}}
1357 <latexrelease>\@namedef{filecontents*}{\@tempswafalse\@fileswtrue
1358 <latexrelease> \@ifnextchar[\filec@ntents@opt\filec@ntents
1359 <latexrelease>}}
1360 <latexrelease>\def\filec@ntents@opt[#1]{%
1361 <latexrelease> \edef\@fortmp{\zap@space#1 \@empty}%
1362 <latexrelease> \@for\reserved@a:=\@fortmp\do{%
1363 <latexrelease> \ifcsname filec@ntents@\reserved@a\endcsname
1364 <latexrelease> \csname filec@ntents@\reserved@a\endcsname
1365 <latexrelease> \else
1366 <latexrelease> \@latex@error{Unknown filecontents option \reserved@a}%
1367 <latexrelease> {Valid options are force (or overwrite), nosearch, noheader}%
1368 <latexrelease> \fi}%
1369 <latexrelease> \filec@ntents
1370 <latexrelease>}}
1371 <latexrelease>\let\filec@ntents@force\@fileswfalse
1372 <latexrelease>\let\filec@ntents@overwrite\@fileswfalse % alternative name
1373 <latexrelease>\let\filec@ntents@noheader\@tempswafalse
1374 <latexrelease>\def\filec@ntents@nosearch{%
1375 <latexrelease> \let\filec@ntents@checkdir\@currdir
1376 <latexrelease> \def\filec@ntents@where{in current directory}}
1377 <latexrelease>\let\filec@ntents@checkdir\@empty
1378 <latexrelease>\def\filec@ntents@where{exists on the system}
1379 <latexrelease>\begingroup%
1380 <latexrelease>\@tempcnta=1
1381 <latexrelease>\loop
1382 <latexrelease> \catcode\@tempcnta=12 %
1383 <latexrelease> \advance\@tempcnta\@ne %
1384 <latexrelease>\ifnum\@tempcnta<32 %
1385 <latexrelease>\repeat %
1386 <latexrelease>\catcode'\*=11 %
1387 <latexrelease>\catcode'\^M\active%
1388 <latexrelease>\catcode'\^L\active\let^^L\relax%
1389 <latexrelease>\catcode'\^I\active%
1390 <latexrelease>\gdef\filec@ntents#1{%
1391 <latexrelease> \set@curr@file{\filec@ntents@checkdir#1}%
1392 <latexrelease> \edef\q@curr@file{\expandafter\quote@name\expandafter{\@curr@file}}%

```

```

1393 <latexrelease> \chardef\reserved@c\ifx\directlua\@undefined 15 \else 127 \fi%
1394 <latexrelease> \openin\@inputcheck\q@curr@file \space %
1395 <latexrelease> \ifeof\@inputcheck%
1396 <latexrelease> \@latex@warning@no@line%
1397 <latexrelease> {Writing file '\@currdir\@curr@file'}%
1398 <latexrelease> \ch@ck7\reserved@c\write\relax%
1399 <latexrelease> \immediate\openout\reserved@c\q@curr@file\relax%
1400 <latexrelease> \else%
1401 <latexrelease> \if@filesw%
1402 <latexrelease> \@latex@warning@no@line%
1403 <latexrelease> {File '\@curr@file' already \filecontentswhere.\MessageBreak%
1404 <latexrelease> Not generating it from this source}%
1405 <latexrelease> \let\write\@gobbletwo%
1406 <latexrelease> \let\closeout\@gobble%
1407 <latexrelease> \else%
1408 <latexrelease> \edef\reserved@a{\detokenize\expandafter{\reserved@a}}%
1409 <latexrelease> \edef\reserved@a{\detokenize\expandafter{\reserved@a}}%
1410 <latexrelease> \edef\reserved@b{\detokenize\expandafter{\jobname}}%
1411 <latexrelease> \ifx\reserved@a\reserved@b%
1412 <latexrelease> \@fileswtrue%
1413 <latexrelease> \else%
1414 <latexrelease> \edef\reserved@b{\reserved@b\detokenize{.tex}}%
1415 <latexrelease> \ifx\reserved@a\reserved@b
1416 <latexrelease> \@fileswtrue%
1417 <latexrelease> \fi%
1418 <latexrelease> \fi%
1419 <latexrelease> \ch@ck7\reserved@c\write\relax%
1420 <latexrelease> \if@filesw% % Foul ... trying to overwrite \jobname!
1421 <latexrelease> \@latex@error{Trying to overwrite '\jobname.tex'}{You can't %
1422 <latexrelease> write to the file you are reading from!\MessageBreak%
1423 <latexrelease> Data is written to screen instead.}%
1424 <latexrelease> \else%
1425 <latexrelease> \@latex@warning@no@line%
1426 <latexrelease> {Writing or overwriting file '\@currdir\@curr@file'}%
1427 <latexrelease> \immediate\openout\reserved@c\q@curr@file\relax%
1428 <latexrelease> \fi%
1429 <latexrelease> \fi%
1430 <latexrelease> \fi%
1431 <latexrelease> \closein\@inputcheck%
1432 <latexrelease> \if@tempswa%
1433 <latexrelease> \immediate\write\reserved@c{%
1434 <latexrelease> \@percentchar\@percentchar\space%
1435 <latexrelease> \expandafter\@gobble\string\LaTeX2e file '\@curr@file'^^J%
1436 <latexrelease> \@percentchar\@percentchar\space generated by the %
1437 <latexrelease> '\@currenvir' \expandafter\@gobblefour\string\newenvironment^^J%
1438 <latexrelease> \@percentchar\@percentchar\space from source '\jobname' on %
1439 <latexrelease> \number\year/\two@digits\month/\two@digits\day.^^J%
1440 <latexrelease> \@percentchar\@percentchar}%
1441 <latexrelease> \fi%
1442 <latexrelease> \let\do\@makeoother\dospecials%
1443 <latexrelease> \count@ 128\relax%
1444 <latexrelease> \loop%
1445 <latexrelease> \catcode\count@ 11\relax%
1446 <latexrelease> \advance\count@ \one%

```

```

1447 <latexrelease> \ifnum\count@<\@cclvi%
1448 <latexrelease> \repeat%
1449 <latexrelease> \edef\E{\@backslashchar end\string{\@currentvir\string}}%
1450 <latexrelease> \edef\reserved@b{%
1451 <latexrelease> \def\noexpand\reserved@b%
1452 <latexrelease> #####1\E####2\E####3\relax}%
1453 <latexrelease> \reserved@b{%
1454 <latexrelease> \ifx\relax##3\relax%
1455 <latexrelease> \immediate\write\reserved@c{##1}%
1456 <latexrelease> \else%
1457 <latexrelease> \edef^^M{\noexpand\end{\@currentvir}}%
1458 <latexrelease> \ifx\relax##1\relax%
1459 <latexrelease> \else%
1460 <latexrelease> \@latex@warning{Writing text ‘##1’ before %
1461 <latexrelease> \string\end{\@currentvir}\MessageBreak as last line of \@curr@file}%
1462 <latexrelease> \immediate\write\reserved@c{##1}%
1463 <latexrelease> \fi%
1464 <latexrelease> \ifx\relax##2\relax%
1465 <latexrelease> \else%
1466 <latexrelease> \@latex@warning{%
1467 <latexrelease> Ignoring text ‘##2’ after \string\end{\@currentvir}}%
1468 <latexrelease> \fi%
1469 <latexrelease> \fi%
1470 <latexrelease> ^^M}%
1471 <latexrelease> \catcode'\^^L\active%
1472 <latexrelease> \let\L\@undefined%
1473 <latexrelease> \def^^L{\expandafter\ifx\csname L\endcsname\relax\fi ^^J^^J}%
1474 <latexrelease> \catcode'\^^I\active%
1475 <latexrelease> \let\I\@undefined%
1476 <latexrelease> \def^^I{\expandafter\ifx\csname I\endcsname\relax\fi\space}%
1477 <latexrelease> \catcode'\^^M\active%
1478 <latexrelease> \edef^^M##1^^M{%
1479 <latexrelease> \noexpand\reserved@b##1\E\E\relax}}%
1480 <latexrelease> \endgroup%
1481 <latexrelease> \EndIncludeInRelease
1482 <latexrelease> \IncludeInRelease{0000/00/00}%
1483 <latexrelease> {\filecontents}{Spaces in file names + optional arg}%
1484 <latexrelease>
1485 <latexrelease> \let\filecontents@opt \@undefined
1486 <latexrelease> \let\filecontents@force \@undefined
1487 <latexrelease> \let\filecontents@overwrite \@undefined
1488 <latexrelease> \let\filecontents@noheader \@undefined
1489 <latexrelease> \let\filecontents@nosearch \@undefined
1490 <latexrelease> \let\filecontents@checkdir \@undefined
1491 <latexrelease> \let\filecontents@where \@undefined
1492 <latexrelease>
1493 <latexrelease> \begingroup%
1494 <latexrelease> \@tempcnta=1
1495 <latexrelease> \loop
1496 <latexrelease> \catcode\@tempcnta=12 %
1497 <latexrelease> \advance\@tempcnta\@ne %
1498 <latexrelease> \ifnum\@tempcnta<32 %
1499 <latexrelease> \repeat %
1500 <latexrelease> \catcode'\*=11 %

```

```

1501 <latexrelease>\catcode'\^~M\active%
1502 <latexrelease>\catcode'\^~L\active\let^~L\relax%
1503 <latexrelease>\catcode'\^~I\active%
1504 <latexrelease>
1505 <latexrelease>\gdef\filecontents#1{%
1506 <latexrelease> \openin\@inputcheck#1 %
1507 <latexrelease> \ifeof\@inputcheck%
1508 <latexrelease> \@latex@warning@no@line%
1509 <latexrelease> {Writing file '\@currdir#1'}%
1510 <latexrelease> \chardef\reserved@c15 %
1511 <latexrelease> \ch@ck7\reserved@c\write%
1512 <latexrelease> \immediate\openout\reserved@c#1\relax%
1513 <latexrelease> \else%
1514 <latexrelease> \closein\@inputcheck%
1515 <latexrelease> \@latex@warning@no@line%
1516 <latexrelease> {File '#1' already exists on the system.\MessageBreak%
1517 <latexrelease> Not generating it from this source}%
1518 <latexrelease> \let\write\@gobbletwo%
1519 <latexrelease> \let\closeout\@gobble%
1520 <latexrelease> \fi%
1521 <latexrelease> \if@tempswa%
1522 <latexrelease> \immediate\write\reserved@c{%
1523 <latexrelease> \@percentchar\@percentchar\space%
1524 <latexrelease> \expandafter\@gobble\string\LaTeX2e file '#1'^~J%
1525 <latexrelease> \@percentchar\@percentchar\space generated by the %
1526 <latexrelease> '\@currenvir' \expandafter\@gobblefour\string\newenvironment^~J%
1527 <latexrelease> \@percentchar\@percentchar\space from source '\jobname' on %
1528 <latexrelease> \number\year/\two@digits\month/\two@digits\day.^~J%
1529 <latexrelease> \@percentchar\@percentchar}%
1530 <latexrelease> \fi%
1531 <latexrelease> \let\do\@makeoother\dospecials%
1532 <latexrelease> \count@ 128\relax%
1533 <latexrelease> \loop%
1534 <latexrelease> \catcode\count@ 11\relax%
1535 <latexrelease> \advance\count@ \@ne%
1536 <latexrelease> \ifnum\count@<\ccclvi%
1537 <latexrelease> \repeat%
1538 <latexrelease> \edef\Ef{\@backslashchar end\string{\@currenvir\string}}%
1539 <latexrelease> \edef\reserved@b{%
1540 <latexrelease> \def\noexpand\reserved@b%
1541 <latexrelease> #####1\E####2\E####3\relax}%
1542 <latexrelease> \reserved@b{%
1543 <latexrelease> \ifx\relax##3\relax%
1544 <latexrelease> \immediate\write\reserved@c{##1}%
1545 <latexrelease> \else%
1546 <latexrelease> \edef^~M{\noexpand\end{\@currenvir}}%
1547 <latexrelease> \ifx\relax##1\relax%
1548 <latexrelease> \else%
1549 <latexrelease> \@latex@warning{Writing text '##1' before %
1550 <latexrelease> \string\end{\@currenvir}\MessageBreak as last line of #1}%
1551 <latexrelease> \immediate\write\reserved@c{##1}%
1552 <latexrelease> \fi%
1553 <latexrelease> \ifx\relax##2\relax%
1554 <latexrelease> \else%

```

```

1555 <latexrelease> \latex@warning{%
1556 <latexrelease> Ignoring text '##2' after \string\end{@currenvir}}%
1557 <latexrelease> \fi%
1558 <latexrelease> \fi%
1559 <latexrelease> ^^M}%
1560 <latexrelease>
1561 <latexrelease> \catcode'\^^L\active%
1562 <latexrelease> \let\L\@undefined%
1563 <latexrelease> \def^^L{\expandafter\ifx\csname L\endcsname\relax\fi ^^J^^J}%
1564 <latexrelease> \catcode'\^^I\active%
1565 <latexrelease> \let\I\@undefined%
1566 <latexrelease> \def^^I{\expandafter\ifx\csname I\endcsname\relax\fi\space}%
1567 <latexrelease> \catcode'\^^M\active%
1568 <latexrelease> \edef^^M##1^^M{%
1569 <latexrelease> \noexpand\reserved@b##1\E\E\relax}}%
1570 <latexrelease>\endgroup%
1571 <latexrelease>\EndIncludeInRelease
1572 <*2ekernel>

1573 \begingroup
1574 \catcode'\|=\catcode'\%
1575 \catcode'\%=12
1576 \catcode'\*=11
1577 \gdef\@percentchar{%}
1578 \gdef\endfilecontents{|
1579 \immediate\closeout\reserved@c
1580 \def\T##1##2##3{|
1581 \ifx##1\@undefined\else
1582 \latex@warning@no@line{##2 has been converted to Blank ##3e}|
1583 \fi}|
1584 \T\L{Form Feed}{Lin}|
1585 \T\I{Tab}{Spac}|
1586 \immediate\write\@unused{}}
1587 \global\let\endfilecontents*\endfilecontents

```

We no longer prevent the code to be used after begin document (no rollback needed for this change).

```

1588 %\@onlypreamble\filecontents
1589 %\@onlypreamble\endfilecontents
1590 %\@onlypreamble\filecontents*
1591 %\@onlypreamble\endfilecontents*
1592 \endgroup
1593 %\@onlypreamble\filecontents

```

(End of definition for \filecontents and \endfilecontents.)

## 5 Package/class rollback mechanism

```

1594 </2ekernel>
1595 <*2ekernel | latexreleasefirst>

```

\pkgcls@debug For testing we have a few extra lines of code that by default do nothing but one can set \pkgcls@debug to \typeout to get extra info. Sometime in the future this will be dropped.

```

1596 <*tracerollback>

```

```

1597 %\let\pkgcls@debug\typeout
1598 \let\pkgcls@debug@gobble
1599 </tracerollback>

```

*(End of definition for \pkgcls@debug.)*

**\requestedLaTeXdate** The macro (!) **\requestedLaTeXdate** holds the globally requested rollback date (via **latexrelease**) or zero if no such request was made.

```

1600 \def\requestedLaTeXdate{0}

```

*(End of definition for \requestedLaTeXdate.)*

**\pkgcls@targetdate** If a rollback for a package or class is requested then **\pkgcls@targetdate** holds the requested date as a number YYYYMMDD (if there was one, otherwise the value of **\requestedLaTeXdate**) and **\pkgcls@targetlabel** will be empty. If there was a request for a named version then **\pkgcls@targetlabel** holds the version name and **\pkgcls@targetdate** is set to 1.

**\pkgcls@targetdate=0** is used to indicate that there was no rollback request. While loading an old release **\pkgcls@targetdate** is also reset to zero so that **\DeclareRelease** declarations are bypassed.

In contrast **\pkgcls@innerdate** will always hold the requested date (in a macro not a counter) if there was one, otherwise, e.g., if there was no request or a request to a version name it will contain T<sub>E</sub>X largest legal number. While loading a file this can be used to provide conditionals that select code based on the request.

```

1601 \ifx\pkgcls@targetdate\@undefined
1602   \newcount\pkgcls@targetdate
1603   \fi
1604 \let\pkgcls@targetlabel\@empty
1605 \def\pkgcls@innerdate{\maxdimen}

```

*(End of definition for \pkgcls@targetdate, \pkgcls@targetlabel, and \pkgcls@innerdate.)*

**\pkgcls@candidate** When looping through the **\DeclareRelease** declarations we record if the release is the best candidate we have seen so far. This is recorded in **\pkgcls@candidate** and we update it whenever we see a better one.

In **\pkgcls@releasedate** we keep track of the release date of that candidate.

```

1606 \let\pkgcls@candidate\@empty
1607 \let\pkgcls@releasedate\@empty

```

*(End of definition for \pkgcls@candidate and \pkgcls@releasedate.)*

**\load@onefilewithoptions** the best place to add the rollback code is at the point where **\@onefilewithoptions** is called to load a single class or package.

To make things easy we save the old definition as **\load@onefilewithoptions** and then provide a new interface.

Important: as this code is also unconditionally placed into **latexrelease** we can only do this name change once otherwise both macros will contain the same code.

```

1608 \ifx\load@onefilewithoptions\@undefined
1609   \let\load@onefilewithoptions\@onefilewithoptions
1610   \def\@onefilewithoptions#1[#2][#3]#4{%

```

First a bit of tracing normally disabled.

```

1611 (*tracerollback)
1612 \pkgcls@debug{--- File loaded request (\noexpand\usepackage or ...)}%
1613 \pkgcls@debug{\@spaces 1: #1}%
1614 \pkgcls@debug{\@spaces 2: #2}%
1615 \pkgcls@debug{\@spaces 3: #3}%
1616 \pkgcls@debug{\@spaces 4: #4}%
1617 /tracerollback)

```

Three of the arguments are needed later on in error/warning messages so we save them.

```

1618 \def\pkgcls@name{#1}%           % for info message
1619 \def\pkgcls@arg {#3}%           % for info message
1620 \edef\pkgcls@ext{%
1621   \ifx#4\@clsextension document class\else
1622     \ifx#4\@pkgextension package\else
1623       file
1624     \fi
1625   \fi
1626 }%                               % for info message

```

then we parse the final optional argument to determine if there is a specific rollback request for the current file. This will set `\pkgcls@targetdate`, `\pkgcls@targetlabel` and `\pkgcls@mindate`.

```

1627 \pkgcls@parse@date@arg{#3}%

```

When determining the correct release to load we keep track of candidates in `\pkgcls@candidate` and initially we don't have any:

```

1628 \let\pkgcls@candidate\@empty

```

If we had a rollback request then #3 may contain data but not necessarily a “minimal date” so instead of passing it on we pass on the content of `\pkgcls@mindate`. We need to pass the value not the command, otherwise nested packages may pick up the wrong information.

```

1629 \begingroup
1630 \edef\reserved@a{%
1631   \endgroup
1632   \unexpanded{\load@onefilewithoptions#1[#2]}%
1633   [\pkgcls@mindate]%
1634   \unexpanded{#4}}%
1635 \reserved@a
1636 }
1637 \fi

```

*(End of definition for \load@onefilewithoptions and \onefilewithoptions.)*

`\pkgcls@parse@date@arg` The `\pkgcls@parse@date@arg` command parses the second optional argument of `\usepackage`, `\RequirePackage` or `\documentclass` for a rollback request setting the values of `\pkgcls@targetdate` and `\pkgcls@targetlabel`.

This optional argument has a dual purpose: If it just contains a date string then this means that the package should have at least that date (to ensure that a certain feature is actually available, or a certain bug has been fixed). When the package gets loaded the information in `\Provides...` will then be checked against this request.

But if it starts with an equal sign followed by a date string or followed by a version name then this means that we should roll back to the state of the package at that date or to the version with the requested name.

If there was no optional argument or the optional argument does not start with “=” then the `\pkgcls@targetdate` is set to the date of the overall rollback request (via `latexrelease`) or if that was not given it is set to 0. In either case `\pkgcls@targetlabel` will be made empty.

If the argument doesn’t start with “=” then it is supposed to be a “minimal date” and we therefore save the value in `\pkgcls@mindate`, otherwise this macro is made empty.

So in summary we have:

Input	<code>\pkgcls@targetdate</code>	<code>\pkgcls@targetlabel</code>	<code>\pkgcls@mindate</code>
<code>&lt;empty&gt;</code>	→ <code>&lt;global-rollbackdate-as-number&gt;</code>	<code>&lt;empty&gt;</code>	<code>&lt;empty&gt;</code>
<code>&lt;date&gt;</code>	→ <code>&lt;global-rollbackdate-as-number&gt;</code>	<code>&lt;empty&gt;</code>	<code>&lt;date&gt;</code>
<code>=&lt;date&gt;</code>	→ <code>&lt;date-as-number&gt;</code>	<code>&lt;empty&gt;</code>	<code>&lt;empty&gt;</code>
<code>=&lt;version&gt;</code>	→ 1	<code>&lt;version&gt;</code>	<code>&lt;empty&gt;</code>
<code>&lt;other&gt;</code>	→ <code>&lt;global-rollbackdate-as-number&gt;</code>	<code>&lt;empty&gt;</code>	<code>&lt;other&gt;</code>

where `<global-rollbackdate-as-number>` is a date request given via `latexrelease` or if there wasn’t one 0.

```
1638 \def\pkgcls@parse@date@arg #1{%
```

If the argument is empty we use the rollback date from `latexrelease` which has the value of zero if there was no rollback request. The label and the minimal date is made empty in that case.

```
1639 \ifx\@nil#1\@nil
1640 \pkgcls@targetdate\requestedLaTeXdate\relax
1641 \let\pkgcls@targetlabel\@empty
1642 \let\pkgcls@mindate\@empty
```

Otherwise we parse the argument further, checking for a = as the first character. We append a = at the end so that there is at least one such character in the argument.

```
1643 \else
1644 \pkgcls@parse@date@arg@#1=\@nil\relax
1645 \fi
1646 }
```

The actual parsing work then happens in `\pkgcls@parse@date@arg@:`

```
1647 \def\pkgcls@parse@date@arg@#1=#2\@nil{%
```

We set `\pkgcls@targetdate` depending on the parsing result; the code is expandable so we can do the parsing as part of the assignment.

```
1648 \pkgcls@targetdate
```

If a = was in first position then #1 will be empty. In that case #2 will be the original argument with a = appended.

This can be parsed with `\@parse@version`, the trailing character is simply ignored. This macro returns the parsed date as a number (or zero if it wasn’t a date) and accepts both YYYY/MM/DD and YYYY-MM-DD formats.

```
1649 \ifx\@nil#1\@nil
1650 \@parse@version0#2//00\@nil\relax
```

Whatever is returned is thus assigned to `\pkgcls@targetdate` and therefore we can now test its value. If the value is zero we assume that the remaining argument string represents a version and change `\pkgcls@targetdate` and set `\pkgcls@targetlabel` to the version name (after stripping off the trailing =).

```
1651 \ifnum \pkgcls@targetdate=\z@
```

```

1652     \pkgcls@targetdate\@ne
1653     \def\pkgcls@innerdate{\maxdimen}%
1654     \pkgcls@parse@date@arg@version#2%
1655     \else
1656     \edef\pkgcls@innerdate{\the\pkgcls@targetdate}%
1657     \fi
1658     \let\pkgcls@mindate\@empty
1659     \else

```

If #1 was not empty then there wasn't a = character in first position so we are dealing either with a “minimum date” or with some incorrect data. We assume the former and make the following assignments (the first one finishing the assignment of \pkgcls@targetdate):

```

1660     \requestedLaTeXdate\relax
1661     \let\pkgcls@targetlabel\@empty
1662     \def\pkgcls@innerdate{\maxdimen}%
1663     \def\pkgcls@mindate{#1}%

```

If the min-date is after the requested rollback date (if there is any, i.e., if it is not zero) then we have a conflict and therefore issue a warning.

```

1664     \ifnum \pkgcls@targetdate > \z@
1665     \ifnum \@parse@version0#1//00\@nil > \pkgcls@targetdate
1666     \@latex@warning@no@line{Suspicious rollback/min-date date given\MessageBreak
1667     A minimal date of #1 has been specified for
1668     \pkgcls@ext\MessageBreak '\pkgcls@name'.\MessageBreak
1669     But this is in conflict
1670     with a rollback request to \requestedpatchdate}
1671     \fi
1672     \fi
1673     \fi
1674 }

```

Strip off the trailing = and assign the version name to \pkgcls@targetlabel.

```

1675 \def\pkgcls@parse@date@arg@version#1={%
1676   \def\pkgcls@targetlabel{#1}}

```

(End of definition for \pkgcls@parse@date@arg.)

**\DeclareRelease** First argument is the “name” of the release and it can be left empty if one doesn't like to give a name to the release. The second argument is that from which on this release was available (or should be used in case of minor updates). The final argument is the external file name of this release, by convention this should be `<pkg/cls-name>-<date>.<extension>` but this is not enforced and through this argument one can overwrite it.

```

1677 \def\DeclareRelease#1#2#3{%
1678   \ifnum\pkgcls@targetdate>\z@ % some sort of rollback request
1679   <*tracerollback>
1680     \pkgcls@debug{---\string\DeclareRelease:}%
1681     \pkgcls@debug{\@spaces 1: #1}%
1682     \pkgcls@debug{\@spaces 2: #2}%
1683     \pkgcls@debug{\@spaces 3: #3}%
1684   </tracerollback>

```

If the date argument #2 is empty we are dealing with a special release that should be only accessible via its name; a typical use case would be a “beta” release. So if we are currently processing a date request we ignore it and otherwise we check if we can match the name and if so load the corresponding release file.

```

1685 \ifx\@nil#2\@nil
1686 \ifnum\pkgcls@targetdate=\@ne % named request
1687 \def\reserved@a{#1}%
1688 \ifx\pkgcls@targetlabel\reserved@a
1689 \pkgcls@use@this@release{#3}{}%
1690 (*tracereollback)
1691 \else
1692 \pkgcls@debug{Label doesn't match}%
1693 (/tracereollback)
1694 \fi
1695 (*tracereollback)
1696 \else
1697 \pkgcls@debug{Date request: ignored}%
1698 (/tracereollback)
1699 \fi
1700 \else

```

If the value of \pkgcls@targetdate is greater than 1 (or in reality greater than something like 19930101) we are dealing with a rollback request to a specific date.

```

1701 \ifnum\pkgcls@targetdate>\@ne % a real request

```

So we parse the date of this release to check if it is before or after the request date.

```

1702 \ifnum\@parse@version#2//00\@nil
1703 >\pkgcls@targetdate

```

If it is after we have to distinguish between two cases: If there was an earlier candidate we use that one because the other is too late, but if there wasn't one (i.e., if current release is the oldest that exists) we use it as the best choice. However in that case something is wrong (as there shouldn't be a rollback to a date when a package used didn't yet exists). So we make a complained to the user.

```

1704 \ifx\pkgcls@candidate\@empty
1705 \pkgcls@rollbackdate@error{#2}%
1706 \pkgcls@use@this@release{#3}{#2}%
1707 \else
1708 \pkgcls@use@this@release\pkgcls@candidate
1709 \pkgcls@releasedate
1710 \fi
1711 \else

```

Otherwise, if the release date of this version is before the target rollback and we record it as a candidate. But we don't use it yet as there may be another release which is still before the target rollback.

```

1712 \def\pkgcls@candidate{#3}%
1713 \def\pkgcls@releasedate{#2}%
1714 (*tracereollback)
1715 \pkgcls@debug{New candidate: #3}%
1716 (/tracereollback)
1717 \fi
1718 \else

```

If we end up in this branch we have a named version request. So we check if `\pkgcls@targetlabel` matches the current name and if yes we use this release immediately, otherwise we do nothing as a later declaration may match it.

```

1719     \def\reserved@a{#1}%
1720     \ifx\pkgcls@targetlabel\reserved@a
1721       \pkgcls@use@this@release{#3}{#2}%
1722   \<traceroollback>
1723     \else
1724       \pkgcls@debug{Label doesn't match}%
1725   \</traceroollback>
1726     \fi
1727   \fi
1728 \fi
1729 \fi
1730 }
```

*(End of definition for \DeclareRelease.)*

**\pkgcls@use@this@release** If a certain release has been selected (stored in the external file given in #1) we need to input it and afterwards stop reading the current file.

```

1731 \def\pkgcls@use@this@release#1#2{%
```

Before that we record the selection made inside the transcript.

```

1732   \pkgcls@show@selection{#1}{#2}%
```

We then set the `\pkgcls@targetdate` to zero so that any `\DeclareRelease` or `\DeclareCurrentRelease` in the file we now load are bypassed<sup>52</sup> and then we finally load the correct release.

After loading that file we need to stop reading the current file so we issue `\endinput`. Note that the `\relax` before that is essential to ensure that the `\endinput` is only happening after the file has been fully processed, otherwise it would act after the first line of the `@@input`!

```

1733   \pkgcls@targetdate\z@
1734   \@addtofilelist{#1}%
1735   @@input #1\relax
1736   \endinput
1737 }
```

*(End of definition for \pkgcls@use@this@release.)*

**\pkgcls@show@selection** This command records what selection was made. As that is needed in two places (and it is rather lengthy) it was placed in a separate command. The first argument is the name of the external file that is being loaded and is only needed for debugging. The second argument is the date that corresponds to this file and it is used as part of the message.

```

1738 \def\pkgcls@show@selection#1#2{%
1739 \<traceroollback>
1740   \pkgcls@debug{Result: use #1}%
1741 \</traceroollback>
1742   \GenericInfo
1743     {\@spaces\@spaces\space}{Rollback for
1744     \@cls@pkg\space'\@currname' requested ->
```

<sup>52</sup>The older release may also have such declarations inside if it was a simply copy of the `.sty` or `.cls` file current at that date. Removing these declarations would make the file load a tiny bit faster, but this way it works in any case.

```

1745 \ifnum\pkgcls@targetdate>\@ne
1746     date
1747     \ifnum\requestedLaTeXdate=\pkgcls@targetdate
1748         \requestedpatchdate
1749     \else
1750         \expandafter\@gobble\pkgcls@arg
1751     \fi.\MessageBreak

```

Instead of “best approximation” we could say that we have been able to exactly match the date (if it is exact), but that would mean extra tests without much gain, so not done.

```

1752     Best approximation is
1753 \else
1754     version '\pkgcls@targetlabel'.\MessageBreak
1755     This corresponds to
1756 \fi
1757 \ifx\@nil#2\@nil
1758     a special release%
1759 \else
1760     the release introduced on #2%
1761 \fi
1762 \@gobble}%
1763 }

```

(End of definition for \pkgcls@show@selection.)

**\pkgcls@rollbackdate@error** This is called if the requested rollback date is earlier than the earliest known release of a package or class.

A similar error is given if global rollback date and min-date on a specific package conflict with each other, but that case is happens only once so it is inlined.

```

1764 \def\pkgcls@rollbackdate@error#1{%
1765     \@latex@error{Suspicious rollback date given}%
1766     {The \@cls@pkg\space'\@currname' has no rollback data
1767     before #1 which\MessageBreak
1768     is after your requested rollback date --- so
1769     something may be wrong here.\MessageBreak
1770     Continue and we use the earliest known release.}}

```

(End of definition for \pkgcls@rollbackdate@error.)

**\DeclareCurrentRelease** This declares the date (and possible name) of the current version of a package or class.

```

1771 \def\DeclareCurrentRelease#1#2{%

```

First we test if \pkgcls@targetdate is greater than zero, otherwise this code is bypassed (as there is no rollback request).

```

1772 \ifnum\pkgcls@targetdate>\z@ % some sort of rollback request
1773 {*tracerollback}
1774     \pkgcls@debug{---DeclareCurrentRelease}%
1775     \pkgcls@debug{ 1: #1}%
1776     \pkgcls@debug{ 2: #2}%
1777 \}
```

If the value is greater than 1 we have to deal with a date request, so we parse #2 as a date and compare it with \pkgcls@targetdate.

```

1778 \ifnum\pkgcls@targetdate>\@ne % a date request
1779     \ifnum\@parse@version#2//00\@nil
1780         >\pkgcls@targetdate

```

If it is greater that means the release date if this file is later than the requested rollback date. Again we have two cases: If there was a previous candidate release we use that one as the current release is too young, but if there wasn't we have to use this release nevertheless as there isn't any alternative.

However this case can only happen if there is a `\DeclareCurrentRelease` but no declared older releases (so basically the use of the declaration is a bit dubious).

```

1781     \ifx\pkgcls@candidate\empty
1782     \pkgcls@rollbackdate@error{#2}%
1783     \else
1784     \pkgcls@use@this@release\pkgcls@candidate
1785     \pkgcls@releasedate
1786     \fi

```

Otherwise the current file is the right release, so we record that in the transcript and then carry on.

```

1787     \else
1788     \pkgcls@show@selection{current version}{#2}%
1789     \fi
1790     \else % a label request

```

Otherwise we have a rollback request to a named version so we check if that fits the current name and if not give an error as this was the last possible opportunity.

```

1791     \def\reserved@a{#1}%
1792     \ifx\pkgcls@targetlabel\reserved@a
1793     \pkgcls@show@selection{current version}{#2}%
1794     \else
1795     \@latex@error{Requested version '\pkgcls@targetlabel' for
1796     \cls@pkg\space'\@currname' is unknown}\@ehc
1797     \fi
1798     \fi
1799     \fi
1800 }

```

*(End of definition for \DeclareCurrentRelease.)*

**\IfTargetDateBefore** This enables a simple form of conditional code inside a class or package file. If there is a date request and the request date is earlier than the first argument the code in the second argument is processed otherwise the code in the third argument is processed. If there was no date request then we also execute the third argument, i.e., we will get the “latest” version of the file.

Most often the second argument (before-date-code) will be empty.

```

1801 \DeclareRobustCommand\IfTargetDateBefore[1]{%
1802   \ifnum\pkgcls@innerdate <%
1803   \expandafter\@parse@version\expandafter0#1//00\@nil
1804   \typeout{Exclude code introduced on #1}%
1805   \expandafter\@firstoftwo
1806   \else
1807   \typeout{Include code introduced on #1}%
1808   \expandafter\@secondoftwo
1809   \fi
1810 }

```

*(End of definition for \IfTargetDateBefore.)*

```

1811 </2ekernel | latexreleasefirst>

```

## 6 After Preamble

Finally we declare a package that allows all the commands declared above to be `\@onlypreamble` to be used after `\begin{document}`.

```
1812 <*afterpreamble>
1813 \NeedsTeXFormat{LaTeX2e}
1814 \ProvidesPackage{pkgindoc}
1815         [2020-08-08 v1.3m Package Interface in Document (DPC)]
1816 \def\reserved@a#1\do\@classoptionslist#2\do\filecontents#3\relax{%
1817     \gdef\@preamblecmds{#1#3}}
1818 \expandafter\reserved@a\@preamblecmds\relax
1819 </afterpreamble>
```

File 51

## ltkeys.dtx

### 1 Creating and using keyval options

As with any key–value input, using key–value pairs as package or class options has two parts: creating the key options and setting (using) them. Options created in this way *may* be used after package loading as general key–value settings: this will depend on the nature of the underlying code.

---

`\DeclareKeys` `\DeclareKeys [<family>] {<declarations>}`

---

Creates a series of options from a comma-separated *<declarations>* list. The *<family>* is a namespace for the keys; if not given, the basename of the current class or package is used. Each entry in the *<declarations>* (a commas-separated list) is a key–value pair, with the *<key>* having one or more *<properties>*. A small number of “basic” *<properties>* are described below. The full range of properties, provided by `l3keys`, can also be used for more powerful processing. See `interface3` for the full details.

The basic properties provided here are

- `.code` — execute arbitrary code
- `.if` — sets a TeX `\if...` switch
- `.ifnot` — sets an inverted TeX `\if...` switch
- `.pass-to-packages` — for class options, this specifies whether the option should be treated “global” (read by packages from the global list); for package options this property has no effect
- `.store` — stores a value in a macro
- `.usage` — defines whether the option can be given only when loading (`load`), in the preamble (`preamble`) or has no limitation on scope (`general`)

The part of the *<key>* before the *<property>* is the *<name>*, with the *<value>* working with the *<property>* to define the behaviour of the option.

For example, with

```
\DeclareKeys[mypkg]
{
  draft.if           = @mypkg@draft      ,
  draft.usage        = preamble          ,
  name.store          = \@mypkg@name      ,
  name.usage          = load              ,
  second-name.store = \@mypkg@other@name
}
```

three options would be create. The option `draft` can be given anywhere in the preamble, and will set a switch called `\if@mypkg@draft`. The option `name` can only be given during package loading, and will save whatever value it is given in `\@mypkg@name`. Finally, the option `second-name` can be given anywhere, and will save its value in `\@mypkg@other@name`.

Keys created *before* the use of `\ProcessKeyOptions` act as package options.

---

`\DeclareUnknownKeyHandler` `\DeclareUnknownKeyHandler [<family>] {<code>}`

---

The function `\DeclareUnknownKeyHandler` may be used to define the behavior when an undefined key is encountered. The *<code>* will receive the unknown key name as `#1` and the value as `#2`. These can then be processed as appropriate, e.g. by forwarding to another package.

---

**\ProcessKeyOptions** \ProcessKeyOptions [*<families>*]

---

The `\ProcessKeyOptions` function is used to check the current option list against the keys defined for *<families>* (a comma-separated list). Global (class) options and local (package) options are checked when this function is called in a package. Where there is more than one *<family>* in the list of *<families>*, processing takes place in the order of the *<families>*. Every key known in a *<family>* is passed for processing, thus a key defined in more than one *<family>* will be processed several times, and if the code paths are shared, the outcome will be determined by the last entry in the list of *<families>*.

---

**\SetKeys** \SetKeys [*<family>*] {*<keyvals>*}

---

Sets (applies) the explicit list of *<keyvals>* for the *<family>*: if the latter is not given, the value of `\@currname` is used. This command may be used within a package to set options before or after using `\ProcessKeyOptions`.

## 1.1 Implementation of `ltkeys`

```

1 <@=keys>
2 <*2ekernel>
3 \ExplSyntaxOn

```

## 1.2 Key properties

```

.code
  .if      4 \group_begin:
  .ifnot   5 \cs_set_protected:Npn \__keys_tmp:nn #1#2
  .store   6 {
  .usage   7 \quark_if_recursion_tail_stop:n {#1}
           8 \cs_new_eq:cc
           9 { \c__keys_props_root_str . #2 }
          10 { \c__keys_props_root_str . #1 }
          11 \__keys_tmp:nn
          12 }
          13 \__keys_tmp:nn
          14 { code:n } { code }
          15 { legacy_if_set:n } { if }
          16 { legacy_if_set_inverse:n } { ifnot }
          17 { tl_set:N } { store }
          18 { usage:n } { usage }
          19 { \q_recursion_tail } { }
          20 \q_recursion_stop
          21 \group_end:

```

(End of definition for `.code` and others.)

**.pass-to-packages** Used to force options to be global: as this property (uniquely) has an *optional* value, there is a bit of work to do.

```

\__keys_scope:n
\__keys_scope:N 22 \cs_new_protected:cpn { \c__keys_props_root_str .pass-to-packages }
                23 {
                24 \bool_if:NTF \l__keys_no_value_bool
                25 { \__keys_scope:n { true } }
                26 { \__keys_scope:n }

```

```

27 }
28 \cs_new_protected:Npn \__keys_scope:n #1
29 {
30   \str_case:nnF {#1}
31   {
32     { true }
33     { \__keys_scope:N \clist_put_right:NV }
34     { false }
35     { \__keys_scope:N \clist_remove_all:NV }
36   }
37   {
38     \msg_error:nnnn { keys }
39     { choice-unknown }
40     { .pass-to-packages }
41     {#1}
42   }
43 }
44 \cs_new_protected:Npn \__keys_scope:N #1
45 {
46   \exp_after:wN \__keys_find_key_module:wNN
47   \l_keys_path_str \s_keys_stop
48   \l_keys_key_tl \l_keys_key_str
49   #1 \l__keys_forced_global_clist \l_keys_key_str
50 }

```

(End of definition for `.pass-to-packages`, `\__keys_scope:n`, and `\__keys_scope:N`.)

### 1.3 Main mechanism

```

51 \cs_generate_variant:Nn \clist_if_in:NnT { Ne }
52 \cs_generate_variant:Nn \clist_if_in:NnTF { Ne }
53 \cs_generate_variant:Nn \clist_put_right:Nn { Nv }

```

`\l__keys_class_only_clist` Used to track class-only options.

```
54 \clist_new:N \l__keys_class_only_clist
```

(End of definition for `\l__keys_class_only_clist`.)

`\l__keys_forced_global_clist` Used to force options to be global.

```
55 \clist_new:N \l__keys_forced_global_clist
```

(End of definition for `\l__keys_forced_global_clist`.)

`\l__keys_options_clist` A single list is used for all options, into which they are collected before processing.

```
56 \clist_new:N \l__keys_options_clist
```

(End of definition for `\l__keys_options_clist`.)

`\l__keys_local_clist` Holds the local options when appropriate: otherwise empty. Needed as the  $\text{\LaTeX} 2_{\epsilon}$  setup here can be equal to `\scan_stop:`, which is not generally supported.

```
57 \clist_new:N \l__keys_local_clist
```

(End of definition for \l\_\_keys\_local\_clist.)

---

\l\_\_keys\_options\_loading\_bool

---

Used to indicate we are in the loading phase: controls the outcome of warnings.

```
58 \bool_new:N \l__keys_options_loading_bool
```

```
\__keys_options:n
\__keys_options_aux:n
```

The main function calls functions to collect up the global and local options into \l\_\_keys\_options\_clist before calling the underlying functions to actually do the processing. So that a suitable message is produced if the option is unknown, the special **unknown** key is set if it does not already exist for the current family, and is cleaned up afterwards if required. To allow the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> layer to know this mechanism is active, and to deal with the key family not matching the file name, we store the family in all cases. Global options are only considered the first time a package is loaded: this is tracked using `opt@handler@ \currname . \currentx`, as this is defined once keyval processing has been applied for the first time.

```
59 \cs_new_protected:Npn \__keys_options:n #1
60 { \__keys_options_expand_module:Nn \__keys_options_aux:n {#1} }
61 \cs_new_protected:Npn \__keys_options_aux:n #1
62 {
63   \__keys_options_local:
64   \clist_map_inline:nn {#1}
65   {
66     \clist_clear:N \l__keys_options_clist
67     \cs_if_exist:cF { opt@handler@ \currname . \currentx }
68     { \__keys_options_global:n {##1} }
69     \__keys_options_local:n {##1}
70     \bool_set_true:N \l__keys_options_loading_bool
71     \clist_map_variable:NNn \l__keys_options_clist \CurrentOption
72     { \keys_set:nV {#1} \CurrentOption }
73     \bool_set_false:N \l__keys_options_loading_bool
74     \__keys_options_loaded:n {##1}
75   }
76   \clist_if_empty:NF \l__keys_unused_clist
77   {
78     \clist_map_inline:Nn \l__keys_unused_clist
79     {
80       \msg_error:nnxx { keys } { option-unknown }
81       {##1} { \currname }
82     }
83   }
84   \cs_if_exist:cF { opt@handler@ \currname . \currentx }
85   {
86     \cs_gset_protected:cpn { opt@handler@ \currname . \currentx }
87     { \ProcessKeyOptions [ {#1} ] }
88   }
89   \AtEndOfPackage { \cs_set_eq:NN \unprocessedoptions \scan_stop: }
90 }

91 \msg_new:nnnn { keys } { option-unknown }
92 { Unknown-option~'#1'~for~package~#2. }
93 {
94   LaTeX-has-been-asked-to-set-an-option-called~'#1'~
```

```

95     but~the~package~"\msg_module_name:n {#2}"~has~not~created~an~option~with~this~name.
96   }

```

(End of definition for `\__keys_options:n` and `\__keys_options_aux:n`.)

`\__keys_options_global:n` Global (class) options are handled differently for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> packages and classes. Hence this function is essentially a check on the current file type. The initial test is needed as L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> allows variables to be equal to `\scan_stop:`, which is usually forbidden in expl3 code.

```

97 \cs_new_protected:Npn \__keys_options_global:n #1
98 {
99   \cs_if_eq:NNF \@raw@classoptionslist \scan_stop:
100   {
101     \cs_if_eq:NNTF \@currentx \@clsextension
102     { \__keys_options_class:n {#1} }
103     { \__keys_options_package:n {#1} }
104   }
105 }

```

(End of definition for `\__keys_options_global:n`.)

`\__keys_options_class:n` For classes, each option (stripped of any content after =) is checked for existence as a key. `\__keys_options_class:nnn` If found, the option is added to the combined list for processing. On the other hand, unused options are stored up in `\@unusedoptionlist`. An earlier version of this code checked for the `unknown` key just once and if found short-cutted the loop: that though makes handling more complex situations harder, so we take the performance hit instead. `\__keys_options_class:nn` Options used by classes are tracked but the catch-all `unknown` is excluded (hence not using a lazy evaluation for the key testing).

```

106 \cs_new_protected:Npn \__keys_options_class:n #1
107 {
108   \cs_if_free:cF { \@raw@opt@ \@currname . \@currentx }
109   {
110     \clist_map_inline:cn { \@raw@opt@ \@currname . \@currentx }
111     {
112       \exp_args:Ne \__keys_options_class:nnn
113       { \tl_trim_spaces:e { \__keys_remove_equals:n {##1} } }
114       {##1} {#1}
115     }
116   }
117 }
118 \cs_new_protected:Npn \__keys_options_class:nnn #1#2#3
119 {
120   \keys_if_exist:nnTF {#3} {#1}
121   {
122     \__keys_options_class:nn {#1} {#2}
123     \clist_put_right:Ne \l__keys_class_only_clist { \tl_to_str:n {#1} }
124   }
125   {
126     \keys_if_exist:nnTF {#3} { unknown }
127     { \__keys_options_class:nn {#1} {#2} }
128     {
129       \clist_if_in:NnF \@unusedoptionlist {#1}
130       { \clist_put_right:Nn \@unusedoptionlist {#1} }
131     }
132   }
133 }

```

```

132     }
133   }
134   \cs_new_protected:Npn \__keys_options_class:nn #1#2
135   {
136     \clist_remove_all:Nn \@unusedoptionlist {#1}
137     \clist_put_right:Nn \l__keys_options_clist {#2}
138   }

(End of definition for \__keys_options_class:n, \__keys_options_class:nnn, and
 \__keys_options_class:nn.)

```

`\__keys_options_package:n` For global options when processing a package, the tasks are slightly different from those for a class. The check is the same, but here there is nothing to do if the option is not applicable. Each valid option also needs to be removed from `\@unusedoptionlist`.

```

139   \cs_new_protected:Npn \__keys_options_package:n #1
140   {
141     \clist_map_inline:Nn \@raw@classoptionslist
142     {
143       \exp_args:Ne \__keys_options_package:nnn
144       { \tl_trim_spaces:e { \__keys_remove_equals:n {##1} } }
145       {##1} {#1}
146     }
147   }

```

The forced-global test here needs to use `\tl_to_str:n` as the data come from a key name, which is always a string.

```

148   \cs_new_protected:Npn \__keys_options_package:nnn #1#2#3
149   {
150     \keys_if_exist:nnT {#3} {#1}
151     {
152       \clist_if_in:NeTF \l__keys_class_only_clist { \tl_to_str:n {#1} }
153       {
154         \clist_if_in:NeT \l__keys_forced_global_clist { \tl_to_str:n {#1} }
155         { \__keys_options_package:nn {#1} {#2} }
156       }
157       { \__keys_options_package:nn {#1} {#2} }
158     }
159   }
160   \cs_new_protected:Npn \__keys_options_package:nn #1#2
161   {
162     \clist_put_right:Nn \l__keys_options_clist {#2}
163     \clist_remove_all:Nn \@unusedoptionlist {#1}
164   }

```

(End of definition for `\__keys_options_package:n`, `\__keys_options_package:nnn`, and `\__keys_options_package:nn`.)

`\__keys_options_local:` If local options are found, they are added to the processing list. L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> stores options for each file in a macro which may or may not exist, hence the need to use `\cs_if_exist:c`. For tracking the unused options, we need to hold only the option name, hence needing a mapping.

```

165   \cs_new_protected:Npn \__keys_options_local:
166   {
167     \clist_clear:N \l__keys_local_clist
168     \cs_if_eq:NNF \@currentt \cclsextension

```

```

169     {
170       \cs_if_exist:cT { @raw@opt@ \@currname . \@currentx }
171       {
172         \clist_set_eq:Nc \l__keys_local_clist
173           { @raw@opt@ \@currname . \@currentx }
174       }
175     }
176     \clist_map_inline:Nn \l__keys_local_clist
177     {
178       \clist_put_right:Ne \l__keys_unused_clist
179       { \tl_trim_spaces:e { \__keys_remove_equals:n {##1} } }
180     }
181   }

```

*(End of definition for \\_\_keys\_options\_local:.)*

\\_\_keys\_options\_local:n    A simpler version of the code used for package options: we stack up those that are known,  
 \\_\_keys\_options\_local:nnn unless the family supports unknown keys in which case we hover up everything.

```

182 \cs_new_protected:Npn \__keys_options_local:n #1
183 {
184   \keys_if_exist:nnTF {#1} { unknown }
185   {
186     \clist_put_right:NV \l__keys_options_clist \l__keys_local_clist
187     \clist_clear:N \l__keys_unused_clist
188   }
189   {
190     \clist_map_inline:Nn \l__keys_local_clist
191     {
192       \exp_args:Ne \__keys_options_local:nnn
193       { \tl_trim_spaces:e { \__keys_remove_equals:n {##1} } }
194       {##1} {#1}
195     }
196   }
197 }
198 \cs_new_protected:Npn \__keys_options_local:nnn #1#2#3
199 {
200   \keys_if_exist:nnT {#3} {#1}
201   {
202     \clist_put_right:Nn \l__keys_options_clist {#2}
203     \clist_remove_all:Nn \l__keys_unused_clist {#1}
204   }
205 }

```

*(End of definition for \\_\_keys\_options\_local:n and \\_\_keys\_options\_local:nnn.)*

\\_\_keys\_remove\_equals:n    As the name suggests, this is a simple function to remove an equals sign from the input.  
 \\_\_keys\_remove\_equals:w    This is all wrapped up in an n function so that there will always be a sign available.

```

206 \cs_new:Npn \__keys_remove_equals:n #1
207   { \__keys_remove_equals:w #1 = \s__keys_stop }
208 \cs_new:Npn \__keys_remove_equals:w #1 = #2 \s__keys_stop { \exp_not:n {#1} }

```

*(End of definition for \\_\_keys\_remove\_equals:n and \\_\_keys\_remove\_equals:w.)*

## 1.4 The document interfaces

```
209 \cs_generate_variant:Nn \keys_define:nn { nx }
```

`\__keys_options_expand_module:Nn`

`\__keys_options_expand_module:nN`

To deal with active characters inside the module argument whilst also expanding that argument, we use a combination of `c`- and `f`-type expansion. This works as the definitions for active UTF-8 bytes contain an `\ifincsname` test.

```
210 \cs_new_protected:Npn \__keys_options_expand_module:Nn #1#2
211 {
212   \cs:w __keys_options_expand_module:nN \use:e { \cs_end: {#2} } #1
213 }
214 \cs_new_protected:Npn \__keys_options_expand_module:nN #1#2
215 { #2 {#1} }
```

(End of definition for `\__keys_options_expand_module:Nn` and `\__keys_options_expand_module:nN`.)

### `\DeclareKeys`

Defining key options is quite straight-forward: we have an intermediate function to allow for potential set-up steps.

```
216 \NewDocumentCommand \DeclareKeys { 0 { \@currname } +m }
217 { \__keys_options_expand_module:Nn \keys_define:nn {#1} {#2} }
```

(End of definition for `\DeclareKeys`. This function is documented on page 1105.)

### `\DeclareUnknownKeyHandler`

```
218 \NewDocumentCommand \DeclareUnknownKeyHandler { 0 { \@currname } +m }
219 {
220   \cs_set_protected:cpn { __keys_unknown_handler_ #1 :nn } ##1##2 {#2}
221   \__keys_options_expand_module:Nn \keys_define:nx {#1}
222   {
223     unknown .code:n =
224       \exp_not:N \exp_args:NV
225       \exp_not:c { __keys_unknown_handler_ #1 :nn }
226       \exp_not:N \l_keys_key_str {###1}
227   }
228 }
```

(End of definition for `\DeclareUnknownKeyHandler`. This function is documented on page 1105.)

### `\ProcessKeyOptions`

We need to deal with the older interface from `l3keys2e` here: it had a mandatory argument. We can mop that up using a look-ahead, and then exploit that information to determine whether the package option handling is set up for the new approach for clash handling.

```
229 \NewDocumentCommand \ProcessKeyOptions { 0 { \@currname } }
230 { \__keys_options:n {#1} }
231 \@onlypreamble \ProcessKeyOptions
```

(End of definition for `\ProcessKeyOptions`. This function is documented on page 1106.)

## 1.5 Option usage scope

`\_keys_options_loaded:n` Indicates that the load-time options for a package have been processed: once this has happened, make them unavailable either with a warning or an error.

```

232 \cs_new_protected:Npn \_keys_options_loaded:n #1
233 {
234   \prop_get:NnNT \l_keys_usage_load_prop {#1} \l_keys_tmpa_tl
235   {
236     \clist_map_inline:Nn \l_keys_tmpa_tl
237     {
238       \keys_define:nn {#1}
239       {
240         ##1 .code:n =
241           \_keys_options_loaded:nn {#1} {##1}
242       }
243     }
244   }
245 }
246 \cs_new_protected:Npn \_keys_options_loaded:nn #1#2
247 {
248   \bool_if:NTF \l_keys_options_loading_bool
249   { \msg_warning:nnnn { keys } { load-option-ignored } }
250   { \msg_error:nnnn { keys } { load-only } }
251   {#1} {#2}
252 }
253 \msg_new:nnn { keys } { load-option-ignored }
254 {
255   Package~"\msg_module_name:n {#1}"~has~already~been~loaded:~
256   ignoring~load-time~option~"#2".
257 }
258 \msg_new:nnnn { keys } { load-only }
259 {
260   Key~"#2"~may~only~be~used~during~loading~of~package~
261   "\msg_module_name:n {#1}".
262 }
263 {
264   LaTeX~was~asked~to~set~a~key~called~"#2",~but~this~is~only~allowed~
265   in~the~optional~argument~when~loading~package~"\msg_module_name:n {#1}".
266 }

```

(End of definition for `\_keys_options_loaded:n` and `\_keys_options_loaded:nn`.)

Disable all preamble options in one shot.

```

267 \tl_gput_left:Nn \@kernel@after@begindocument
268 {
269   \prop_map_inline:Nn \l_keys_usage_preamble_prop
270   {
271     \clist_map_inline:nn {#2}
272     {
273       \keys_define:nn {#1}
274       {
275         ##1 .code:n =
276           \msg_error:nnn { keys } { preamble-only } {##1}
277       }

```

```

278     }
279   }
280 }
281 \msg_new:nnnn { keys } { preamble-only }
282 { Key~"#1"~may~only~be~used~in~the~preamble. }
283 {
284   LaTeX~was~asked~to~set~a~key~called~"#1",~but~this~is~only~allowed~
285   before~\begin{document}.~You~will~need~to~set~the~key~earlier.
286 }

```

## 1.6 General key setting

**\SetKeys** A simple wrapper.

```

287 \NewDocumentCommand \SetKeys { 0 { \@currname } +m }
288 { \__keys_options_expand_module:Nn \keys_set:nn {#1} {#2} }

```

*(End of definition for \SetKeys. This function is documented on page [1106](#).)*

```

289 \ExplSyntaxOff
290 </2ekernel>

```

## File 52

# ltfilehook.dtx

## 1 Introduction

### 1.1 Provided hooks

The code offers a number of hooks into which packages (or the user) can add code to support different use cases. Many hooks are offered as pairs (i.e., the second hook is reversed). Also important to know is that these pairs are properly nested with respect to other pairs of hooks.

There are hooks that are executed for all files of a certain type (if they contain code), e.g., for all “include files” or all “packages”, and there are also hooks that are specific to a single file, e.g., do something after the package `foo.sty` has been loaded.

### 1.2 General hooks for file reading

There are four hooks that are called for each file that is read using document-level commands such as `\input`, `\include`, `\usepackage`, etc. They are not called for files read using internal low-level methods, such as `\@input` or `\openin`.

<code>file/before</code> <code>file/.../before</code> <code>file/.../after</code> <code>file/after</code>	These are:  <b><code>file/before</code>, <code>file/⟨file-name⟩/before</code></b> These hooks are executed in that order just before the file is loaded for reading. The code of the first hook is used with every file, while the second is executed only for the file with matching <code>⟨file-name⟩</code> allowing you to specify code that only applies to one file.
--	--

**`file/⟨file-name⟩/after`, `file/after`** These hooks are executed after the file with name `⟨file-name⟩` has been fully consumed. The order is swapped (the specific one comes first) so that the `/before` and `/after` hooks nest properly, which is important if any of them involve grouping (e.g., contain environments, for example). Furthermore both hooks are reversed hooks to support correct nesting of different packages adding code to both `/before` and `/after` hooks.

So the overall sequence of hook processing for any file read through the user interface commands of L<sup>A</sup>T<sub>E</sub>X is:

```
\UseHook{file/before}
\UseHook{file/⟨file name⟩/before}
  ⟨file contents⟩
\UseHook{file/⟨file name⟩/after}
\UseHook{file/after}
```

The file hooks only refer to the file by its name and extension, so the `⟨file name⟩` should be the file name as it is on the filesystem with extension (if any) and without paths. Different from `\input` and similar commands, the `.tex` extension is not assumed in hook `⟨file name⟩`, so `.tex` files must be specified with their extension to be recognized. Files within subfolders should also be addressed by their name and extension only.

Extensionless files also work, and should then be given without extension. Note however that T<sub>E</sub>X prioritizes `.tex` files, so if two files `foo` and `foo.tex` exist in the search path, only the latter will be seen.

When a file is input, the `<file name>` is available in `\CurrentFile`, which is then used when accessing the `file/<file name>/before` and `file/<file name>/after`.

---

<code>\CurrentFile</code>	The name of the file about to be read (or just finished) is available to the hooks through <code>\CurrentFile</code> (there is no <code>expl3</code> name for it for now). The file is always provided with its extension, i.e., how it appears on your hard drive, but without any specified path to it. For example, <code>\input{sample}</code> and <code>\input{app/sample.tex}</code> would both have <code>\CurrentFile</code> being <code>sample.tex</code> .
---------------------------	--

---

<code>\CurrentFilePath</code>	The path to the current file (complement to <code>\CurrentFile</code> ) is available in <code>\CurrentFilePath</code> if needed. The paths returned in <code>\CurrentFilePath</code> are only user paths, given through <code>\input@path</code> (or <code>expl3</code> 's equivalent <code>\l_file_search_path_seq</code> ) or by directly typing in the path in the <code>\input</code> command or equivalent. Files located by <code>kpsewhich</code> get the path added internally by the T <sub>E</sub> X implementation, so at the macro level it looks as if the file were in the current folder, so the path in <code>\CurrentFilePath</code> is empty in these cases (package and class files, mostly).
-------------------------------	--

---

<code>\CurrentFileUsed</code> <code>\CurrentFilePathUsed</code>	In normal circumstances these are identical to <code>\CurrentFile</code> and <code>\CurrentFilePath</code> . They will differ when a file substitution has occurred for <code>\CurrentFile</code> . In that case, <code>\CurrentFileUsed</code> and <code>\CurrentFilePathUsed</code> will hold the actual file name and path loaded by L <sup>A</sup> T <sub>E</sub> X, while <code>\CurrentFile</code> and <code>\CurrentFilePath</code> will hold the names that were <i>asked for</i> . Unless doing very specific work on the file being read, <code>\CurrentFile</code> and <code>\CurrentFilePath</code> should be enough.
--	---

### 1.3 Hooks for package and class files

Commands to load package and class files (e.g., `\usepackage`, `\RequirePackage`, `\LoadPackageWithOptions`, etc.) offer the hooks from section 1.2 when they are used to load a package or class file, e.g., `file/array.sty/after` would be called after the `array` package got loaded. But as packages and classes form as special group of files, there are some additional hooks available that only apply when a package or class is loaded.

---

<code>package/before</code> <code>package/after</code> <code>package/.../before</code> <code>package/.../after</code> <code>class/before</code> <code>class/after</code> <code>class/.../before</code> <code>class/.../after</code>	<p>These are:</p> <p><b><code>package/before</code>, <code>package/after</code></b> These hooks are called for each package being loaded.</p> <p><b><code>package/&lt;name&gt;/before</code>, <code>package/&lt;name&gt;/after</code></b> These hooks are additionally called if the package name is <code>&lt;name&gt;</code> (without extension).</p> <p><b><code>class/before</code>, <code>class/after</code></b> These hooks are called for each class being loaded.</p> <p><b><code>class/&lt;name&gt;/before</code>, <code>class/&lt;name&gt;/after</code></b> These hooks are additionally called if the class name is <code>&lt;name&gt;</code> (without extension).</p>
--	---

All `/after` hooks are implemented as reversed hooks.

The overall sequence of execution for `\usepackage` and friends is:

```
\UseHook{package/before}
\UseOneTimeHook{package/<package name>/before}

  \UseHook{file/before}
  \UseHook{file/<package name>.sty/before}
  <package contents>
  \UseHook{file/<package name>.sty/after}
  \UseHook{file/after}

code from \AtEndOfPackage if used inside the package

\UseOneTimeHook{package/<package name>/after}
\UseHook{package/after}
```

and similar for class file loading, except that `package/` is replaced by `class/` and `\AtEndOfPackage` by `\AtEndOfClass`.

If a package or class is not loaded none of the hooks are executed!

All class or package hooks involving the name of the class or package are implemented as one-time hooks, whereas all other such hooks are normal hooks. This allows for the following use case

```
\AddToHook{package/varioref/after}
{ ... apply my customizations if the package gets
  loaded (or was loaded already) ... }
```

without the need to first test if the package is already loaded.

## 1.4 Hooks for `\include` files

To manage `\include` files, L<sup>A</sup>T<sub>E</sub>X issues a `\clearpage` before and after loading such a file. Depending on the use case one may want to execute code before or after these `\clearpages` especially for the one that is issued at the end.

Executing code before the final `\clearpage`, means that the code is processed while the last page of the included material is still under construction. Executing code after it means that all floats from inside the include file are placed (which might have added further pages) and the final page has finished.

Because of these different scenarios we offer hooks in three places.<sup>53</sup> None of the hooks are executed when an `\include` file is bypassed because of an `\includeonly` declaration. They are, however, all executed if L<sup>A</sup>T<sub>E</sub>X makes an attempt to load the `\include` file (even if it doesn't exist and all that happens is “No file `<filename>.tex`”).

---

<sup>53</sup>If you want to execute code before the first `\clearpage` there is no need to use a hook—you can write it directly in front of the `\include`.

<code>include/before</code>	These are:
<code>include/.../before</code>	
<code>include/end</code>	<b><code>include/before, include/&lt;name&gt;/before</code></b> These hooks are executed (in that order) after the initial <code>\clearpage</code> and after <code>.aux</code> file is changed to use <code>&lt;name&gt;.aux</code> , but
<code>include/.../end</code>	before the <code>&lt;name&gt;.tex</code> file is loaded. In other words they are executed at the very
<code>include/after</code>	beginning of the first page of the <code>\include</code> file.
<code>include/.../after</code>	

**`include/<name>/end, include/end`** These hooks are executed (in that order) after `LATEX` has stopped reading from the `\include` file, but before it has issued a `\clearpage` to output any deferred floats.

**`include/<name>/after, include/after`** These hooks are executed (in that order) after `LATEX` has issued the `\clearpage` but before it has switched back writing to the main `.aux` file. Thus technically we are still inside the `\include` and if the hooks generate any further typeset material including anything that writes to the `.aux` file, then it would be considered part of the included material and bypassed if it is not loaded because of some `\includeonly` statement.<sup>54</sup>

**`include/excluded, include/<name>/excluded`** The above hooks for `\include` files are only executed when the file is loaded (or more exactly the load is attempted). If, however, the `\include` file is explicitly excluded (through an `\includeonly` statement) the above hooks are bypassed and instead the `include/excluded` hook followed by the `include/<name>/excluded` hook are executed. This happens after `LATEX` has loaded the `.aux` file for this include file, i.e., after `LATEX` has updated its counters to pretend that the file was seen.

All `include` hooks involving the name of the included file are implemented as one-time hooks (whereas all other such hooks are normal hooks).

If you want to execute code that is run for every `\include` regardless of whether or not it is excluded, use the `cmd/include/before` or `cmd/include/after` hooks.

## 1.5 High-level interfaces for `LATEX`

We do not provide any additional wrappers around the hooks (like `filehook` or `scrfile` do) because we believe that for package writers the high-level commands from the hook management, e.g., `\AddToHook`, etc. are sufficient and in fact easier to work with, given that the hooks have consistent naming conventions.

<sup>54</sup>For that reason another `\clearpage` is executed after these hooks which normally does nothing, but starts a new page if further material got added this way.

## 1.6 Kernel, class, and package interfaces for L<sup>A</sup>T<sub>E</sub>X

---

<code>\declare@file@substitution</code>	<code>\declare@file@substitution</code>	<code>{\file}</code>	<code>{\replacement-file}</code>
<code>\undeclare@file@substitution</code>	<code>\undeclare@file@substitution</code>	<code>{\file}</code>	

---

If `\file` is requested for loading replace it with `\replacement-file`. `\CurrentFile` remains pointing to `\file` but `\CurrentFileUsed` will show the file actually loaded.

The main use case for this declaration is to provide a corrected version of a package that can't be changed (due to its license) but no longer functions because of L<sup>A</sup>T<sub>E</sub>X kernel changes, for example, or to provide a version that makes use of new kernel functionality while the original package remains available for use with older releases. As such it is mainly meant for use in the L<sup>A</sup>T<sub>E</sub>X kernel but other use cases are conceivable.

The `\undeclare@file@substitution` declaration undoes a substitution made earlier.

*Please do not misuse this functionality and replace a file with another unless if really needed and only if the new version is implementing the same functionality as the original one!*

---

<code>\disable@package@load</code>	<code>\disable@package@load</code>	<code>{\package}</code>	<code>{\alternate-code}</code>
<code>\reenable@package@load</code>	<code>\reenable@package@load</code>	<code>{\package}</code>	

---

If `\package` is requested, do not load it but instead run `\alternate-code` which could issue a warning, error or any other code.

The main use case is for classes that want to restrict the set of supported packages or contain code that make the use of some packages impossible. So rather than waiting until the document breaks they can set up informative messages why certain packages are not available.

The function is only implemented for packages not for arbitrary files and again it should only be applied if there are good reasons for doing this.<sup>55</sup>

## 1.7 A sample package for structuring the log output

As an application we provide the package `structuredlog` that adds lines to the `.log` when a file is opened and closed for reading keeping track of nesting level as well. For example, for the current document it adds the lines

```
= (LEVEL 1 START) t1lmr.fd
= (LEVEL 1 STOP) t1lmr.fd
= (LEVEL 1 START) supp-pdf.mkii
= (LEVEL 1 STOP) supp-pdf.mkii
= (LEVEL 1 START) nameref.sty
== (LEVEL 2 START) refcount.sty
== (LEVEL 2 STOP) refcount.sty
== (LEVEL 2 START) gettitlestring.sty
== (LEVEL 2 STOP) gettitlestring.sty
= (LEVEL 1 STOP) nameref.sty
= (LEVEL 1 START) ltfilehook-doc.out
```

---

<sup>55</sup>Just to be sure: “I don’t like this package by somebody else” is not a good one :-)

```

= (LEVEL 1 STOP) ltfilehook-doc.out
= (LEVEL 1 START) ltfilehook-doc.out
= (LEVEL 1 STOP) ltfilehook-doc.out
= (LEVEL 1 START) ltfilehook-doc.hd
= (LEVEL 1 STOP) ltfilehook-doc.hd
= (LEVEL 1 START) ltfilehook.dtx
== (LEVEL 2 START) otllmr.fd
== (LEVEL 2 STOP) otllmr.fd
== (LEVEL 2 START) omllmm.fd
== (LEVEL 2 STOP) omllmm.fd
== (LEVEL 2 START) omslmsy.fd
== (LEVEL 2 STOP) omslmsy.fd
== (LEVEL 2 START) omxlmex.fd
== (LEVEL 2 STOP) omxlmex.fd
== (LEVEL 2 START) umsa.fd
== (LEVEL 2 STOP) umsa.fd
== (LEVEL 2 START) umsb.fd
== (LEVEL 2 STOP) umsb.fd
== (LEVEL 2 START) tsllmr.fd
== (LEVEL 2 STOP) tsllmr.fd
== (LEVEL 2 START) tllmss.fd
== (LEVEL 2 STOP) tllmss.fd
= (LEVEL 1 STOP) ltfilehook.dtx

```

Thus if you inspect an issue in the .log it is easy to figure out in which file it occurred, simply by searching back for LEVEL and if it is a STOP then remove 1 from the level value and search further for LEVEL with that value which should then be the START level of the file you are in.

## 2 The Implementation

```

1 <*2kernel>
2 <@@=filehook>

```

### 2.1 Document and package-level commands

**\CurrentFile** User-level macros that hold the current file name and file path. These are used internally as well because the code takes care to protect against a possible redefinition of these macros in the loaded file (it's necessary anyway to make hooks work with nested \input).  
**\CurrentFilePath** The versions \...Used hold the *actual* file name and path that is loaded by L<sup>A</sup>T<sub>E</sub>X, whereas the other two hold the name as requested. They will differ in case there's a file substitution.  
**\CurrentFileUsed**  
**\CurrentFilePathUsed**

```

3 </2kernel>
4 <*2kernel | latexrelease>
5 <latexrelease>\IncludeInRelease{2020/10/01}%
6 <latexrelease>          {\CurrentFile}{Hook management file}%
7 \ExplSyntaxOn
8 \tl_new:N \CurrentFile
9 \tl_new:N \CurrentFilePath
10 \tl_new:N \CurrentFileUsed
11 \tl_new:N \CurrentFilePathUsed

```

```

12 \ExplSyntaxOff
13 </2ekernel | latexrelease>
14 <latexrelease>\EndIncludeInRelease

15 <latexrelease>\IncludeInRelease{0000/00/00}%
16 <latexrelease>                {\CurrentFile}{Hook management file}%
17 <latexrelease>
18 <latexrelease>\let \CurrentFile          \@undefined
19 <latexrelease>\let \CurrentFilePath      \@undefined
20 <latexrelease>\let \CurrentFileUsed     \@undefined
21 <latexrelease>\let \CurrentFilePathUsed \@undefined
22 <latexrelease>
23 <latexrelease>\EndIncludeInRelease
24 <*2ekernel>

```

(End of definition for `\CurrentFile` and others. These functions are documented on page 1116.)

## 2.2 expl3 helpers

```

25 </2ekernel>
26 <*2ekernel | latexrelease>
27 <latexrelease>\IncludeInRelease{2020/10/01}%
28 <latexrelease>                {\__filehook_file_parse_full_name:nN}{File helpers}%
29 \ExplSyntaxOn

```

`\__filehook_file_parse_full_name:nN`  
`\__filehook_full_name:nn`

A utility macro to trigger expl3's file-parsing and lookup, and return a normalized representation of the file name. If the queried file doesn't exist, no normalization takes place. The output of `\__filehook_file_parse_full_name:nN` is passed on to the #2—a 3-argument macro that takes the `<path>`, `<base>`, and `<ext>` parts of the file name.

```

30 \cs_new:Npn \__filehook_file_parse_full_name:nN #1
31 {
32   \exp_args:Nf \file_parse_full_name_apply:nN
33   {
34     \exp_args:Nf \__filehook_full_name:nn
35     { \file_full_name:n {#1} } {#1}
36   }
37 }
38 \cs_new:Npn \__filehook_full_name:nn #1 #2
39 {
40   \tl_if_empty:nTF {#1}
41   { \tl_trim_spaces:n {#2} }
42   { \tl_trim_spaces:n {#1} }
43 }

```

(End of definition for `\__filehook_file_parse_full_name:nN` and `\__filehook_full_name:nn`.)

`\__filehook_if_no_extension:nTF`  
`\__filehook_drop_extension:N`

Some actions depend on whether the file extension was explicitly given, and sometimes the extension has to be removed. The macros below use `\__filehook_file_parse_full_name:nN` to split up the file name and either check if `<ext>` (#3) is empty, or discard it.

```

44 \cs_new:Npn \__filehook_if_no_extension:nTF #1
45 {
46   \exp_args:Ne \tl_if_empty:nTF
47   { \file_parse_full_name_apply:nN {#1} \use_iii:nnn }
48 }

```

```

49 \cs_new_protected:Npn \__filehook_drop_extension:N #1
50 {
51   \tl_gset:Nx #1
52   {
53     \exp_args:NV \__filehook_file_parse_full_name:nN #1
54     \__filehook_drop_extension_aux:nnn
55   }
56 }
57 \cs_new:Npn \__filehook_drop_extension_aux:nnn #1 #2 #3
58 { \tl_if_empty:nF {#1} { #1 / } #2 }

```

(End of definition for \\_\_filehook\_if\_no\_extension:nTF and \\_\_filehook\_drop\_extension:N.)

\g\_\_filehook\_input\_file\_seq Yet another stack, to keep track of \CurrentFile and \CurrentFilePath with nested  
\l\_\_filehook\_internal\_tl \inputs. At the beginning of \InputIfFileExists, the current value of \CurrentFilePath  
\\_\_filehook\_file\_push: and \CurrentFile is pushed to \g\_\_filehook\_input\_file\_seq, and at the end, it is  
\\_\_filehook\_file\_pop: popped and the value reassigned. Some other places don't use \InputIfFileExists di-  
\\_\_filehook\_file\_pop\_assign:nnnn rectly (\include) or need \CurrentFile earlier (\@onefilewithoptions), so these are  
manually used elsewhere as well.

```

59 \tl_new:N \l__filehook_internal_tl
60 \seq_if_exist:NF \g__filehook_input_file_seq
61 { \seq_new:N \g__filehook_input_file_seq }
62 \cs_new_protected:Npn \__filehook_file_push:
63 {
64   \seq_gpush:Nx \g__filehook_input_file_seq
65   {
66     { \CurrentFilePathUsed } { \CurrentFileUsed }
67     { \CurrentFilePath      } { \CurrentFile      }
68   }
69 }
70 \cs_new_protected:Npn \__filehook_file_pop:
71 {
72   \seq_gpop:NNTF \g__filehook_input_file_seq \l__filehook_internal_tl
73   { \exp_after:wN \__filehook_file_pop_assign:nnnn \l__filehook_internal_tl }
74   {
75     \msg_error:nnn { latex2e } { should-not-happen }
76     { Tried-to-pop-from-an-empty-file-name-stack. }
77   }
78 }
79 \cs_new_protected:Npn \__filehook_file_pop_assign:nnnn #1 #2 #3 #4
80 {
81   \tl_set:Nn \CurrentFilePathUsed {#1}
82   \tl_set:Nn \CurrentFileUsed     {#2}
83   \tl_set:Nn \CurrentFilePath     {#3}
84   \tl_set:Nn \CurrentFile         {#4}
85 }
86 \ExplSyntaxOff

```

(End of definition for \g\_\_filehook\_input\_file\_seq and others.)

```

87 </2ekernel|latexrelease>
88 <latexrelease>\EndIncludeInRelease

```

When rolling forward the following expl3 functions may not be defined. If we roll back the code does nothing.

```

89 <latexrelease>\IncludeInRelease{2020/10/01}%
90 <latexrelease>          {\file_parse_full_name_apply:nN}{Roll forward help}%
91 <latexrelease>
92 <latexrelease>\ExplSyntaxOn
93 <latexrelease>\cs_if_exist:NF\file_parse_full_name_apply:nN
94 <latexrelease>{
95 <latexrelease>\cs_new:Npn \file_parse_full_name_apply:nN #1
96 <latexrelease> {
97 <latexrelease>   \exp_args:Ne \__file_parse_full_name_auxi:nN
98 <latexrelease>   { \__kernel_file_name_sanitiz:n {#1} }
99 <latexrelease> }
100 <latexrelease>\cs_new:Npn \__file_parse_full_name_auxi:nN #1
101 <latexrelease> {
102 <latexrelease>   \__file_parse_full_name_area:nw { } #1
103 <latexrelease>   / \s__file_stop
104 <latexrelease> }
105 <latexrelease>\cs_new:Npn \__file_parse_full_name_area:nw #1 #2 / #3 \s__file_stop
106 <latexrelease> {
107 <latexrelease>   \tl_if_empty:nTF {#3}
108 <latexrelease>   { \__file_parse_full_name_base:nw { } #2 . \s__file_stop {#1} }
109 <latexrelease>   { \__file_parse_full_name_area:nw { #1 / #2 }
110 <latexrelease>           #3 \s__file_stop }
111 <latexrelease> }
112 <latexrelease>\cs_new:Npn \__file_parse_full_name_base:nw #1 #2 . #3 \s__file_stop
113 <latexrelease> {
114 <latexrelease>   \tl_if_empty:nTF {#3}
115 <latexrelease>   {
116 <latexrelease>     \tl_if_empty:nTF {#1}
117 <latexrelease>     {
118 <latexrelease>       \tl_if_empty:nTF {#2}
119 <latexrelease>       { \__file_parse_full_name_tidy:nnnN { } { } }
120 <latexrelease>       { \__file_parse_full_name_tidy:nnnN { .#2 } { } }
121 <latexrelease>     }
122 <latexrelease>     { \__file_parse_full_name_tidy:nnnN {#1} { .#2 } }
123 <latexrelease>   }
124 <latexrelease>   { \__file_parse_full_name_base:nw { #1 . #2 }
125 <latexrelease>           #3 \s__file_stop }
126 <latexrelease> }
127 <latexrelease>\cs_new:Npn \__file_parse_full_name_tidy:nnnN #1 #2 #3 #4
128 <latexrelease> {
129 <latexrelease>   \exp_args:Nee #4
130 <latexrelease>   {
131 <latexrelease>     \str_if_eq:nnF {#3} { / } { \use_none:n }
132 <latexrelease>     #3 \prg_do_nothing:
133 <latexrelease>   }
134 <latexrelease>   { \use_none:n #1 \prg_do_nothing: }
135 <latexrelease>   {#2}
136 <latexrelease> }
137 <latexrelease>}
138 <latexrelease>\ExplSyntaxOff
139 <latexrelease>
140 <latexrelease>\EndIncludeInRelease
141 <*2ekernel>
142 <@@=>

```

## 2.3 Declaring the file-related hooks

These hooks have names with three-parts that start with `file/`, `include/`, `class/` or `package/` and end with `/before` or `/after` (or `/end` in the case of `include/`). They are all generic hooks so will be declared only if code is added to them; this declaration is done for you automatically and, indeed, they should not be declared explicitly.

Those named `.../after` and `include/.../end` are, when code is added, declared as reversed hooks.

## 2.4 Patching L<sup>A</sup>T<sub>E</sub>X’s `\InputIfFileExists` command

Most of what we have to do is adding `\UseHook` into several L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> core commands, because of some circular dependencies in the kernel we do this only now and not in `ltfiles`.

`\InputIfFileExists` `\InputIfFileExists` loads any file if it is available so we have to add the hooks `file/before` and `file/after` in the right places. If the file doesn’t exist no hooks should be executed.

```

143 </2ekernel>
144 <latexrelease>\IncludeInRelease{2020/10/01}%
145 <latexrelease>          {\InputIfFileExists}{Hook management (files)}%
146 <*2ekernel|latexrelease>

147 \let\InputIfFileExists\@undefined
148 \DeclareRobustCommand \InputIfFileExists[2]{%
149   \IfFileExists{#1}%
150   {%
151     \@expl@@@filehook@file@push@@
152     \@filehook@set@CurrentFile

```

We pre-expand `\@filef@und` so that in case another file is loaded in the true branch of `\InputIfFileExists`, these don’t change their value meanwhile. This isn’t a worry with `\CurrentFile...` because they are kept in a stack.

```

153   \expandafter\@swaptwoargs\expandafter
154   {\expandafter\@input@file@exists@with@hooks
155     \expandafter{\@filef@und}}%
156   {#2}%
157   \@expl@@@filehook@file@pop@@
158 }%
159 }
160 \def\@input@file@exists@with@hooks#1{%

```

If the file exists then `\CurrentFile` holds its name. But we can’t rely on that still being true after the file has been processed. Thus for using the name in the file hooks we need to preserve the name and then restore it for the `file/.../after` hook.

The hook always refers to the file requested by the user. The hook is *always* loaded for `\CurrentFile` which usually is the same as `\CurrentFileUsed`. In the case of a file replacement, the `\CurrentFileUsed` holds the actual file loaded. In any case the file names are normalized so that the hooks work on the real file name, rather than what the user typed in.

`expl3`’s `\file_full_name:n` normalizes the file name (to factor out differences in the `.tex` extension), and then does a file lookup to take into account a possible path from `\l_file_search_path_seq` and `\input@path`. However only the file name and extension

are returned so that file hooks can refer to the file by their name only. The path to the file is returned in `\CurrentFilePath`.

```

161 \edef\reserved@a{%
162   \@expl@@@filehook@file@pop@assign@@nnnn
163   {\CurrentFilePathUsed}%
164   {\CurrentFileUsed}%
165   {\CurrentFilePath}%
166   {\CurrentFile}}%
167 \expandafter\@swaptwoargs\expandafter{\reserved@a}%

```

Before adding to the file list we need to make all (letter) characters catcode 11, because several packages use constructions like

```

\filename@parse{<filename>}
\ifx\filename@ext\@clsextension
...
\fi

```

and that doesn't work if `\filename@ext` is `\detokenized`. Making `\@clsextension` a string doesn't help much because some packages define their own `\<prefix>@someextension` with normal catcodes. This is not entirely correct because packages loaded (somehow) with catcode 12 alphabetic tokens (say, as the result of a `\string` or `\detokenize` command, or from a T<sub>E</sub>X string like `\jobname`) will have these character tokens incorrectly turned into letter tokens. This however is rare, so we'll go for the all-letters approach (grepping the packages in T<sub>E</sub>X Live didn't bring up any obvious candidate for breaking with this catcode change).

```

168 {\edef\reserved@a{\unqu@tefilef@und#1\@nil}%
169  \addtofilelist{\string@makeletter\reserved@a}%
170  \UseHook{file/before}%

```

The current file name is available in `\CurrentFile` so we use that in the specific hook.

```

171  \UseHook{file/\CurrentFile/before}%
172  \@input #1% <- trailing space comes from \@filef@und
173  }%

```

And here, `\CurrentFile` is restored (by `\@expl@@@filehook@file@pop@assign@@nnnn`) so we can use it once more.

```

174  \UseHook{file/\CurrentFile/after}%
175  \UseHook{file/after}}
176 \def\unqu@tefilef@und"#1" \@nil{#1}

```

Now declare the non-generic file hooks used above:

```

177 \NewHook{file/before}
178 \NewReversedHook{file/after}
179 \<latexrelease>\EndIncludeInRelease
180 \</2ekernel|latexrelease>

```

Now define `\InputIfFileExists` to input #1 if it seems to exist. Immediately prior to the input, #2 is executed. If the file #1 does not exist, execute '#3'.

```

181 \<latexrelease>\IncludeInRelease{2019/10/01}%
182 \<latexrelease>      {\InputIfFileExists}{Hook management (files)}%
183 \<latexrelease>
184 \<latexrelease>\DeclareRobustCommand \InputIfFileExists[2]{%
185 \<latexrelease>  \IfFileExists{#1}%
186 \<latexrelease>    {%

```

```

187 <latexrelease> \expandafter\@swaptwoargs\expandafter
188 <latexrelease> {\@filef@und}{#2\@addtofilelist{#1}\@input}}
189 <latexrelease>\let\@input@file@exists@with@hooks\@undefined
190 <latexrelease>\let\unqu@tefilef@und\@undefined
191 <latexrelease>\EndIncludeInRelease

192 <latexrelease>\IncludeInRelease{0000/00/00}%
193 <latexrelease> {\InputIfFileExists}{Hook management (files)}%
194 <latexrelease>\long\def \InputIfFileExists#1#2{%
195 <latexrelease> \IfFileExists{#1}%
196 <latexrelease> {#2\@addtofilelist{#1}\@input \@filef@und}}

```

Also undo the internal command as some packages unfortunately test for their existence instead of using `\IfFormatAtLeastTF`.

```

197 <latexrelease>\expandafter\let\csname InputIfFileExists \endcsname\@undefined
198 <latexrelease>\let\@input@file@exists@with@hooks\@undefined
199 <latexrelease>\let\unqu@tefilef@und\@undefined
200 <latexrelease>\EndIncludeInRelease
201 <*2ekernel>

```

(End of definition for `\InputIfFileExists`, `\@input@file@exists@with@hooks`, and `\unqu@tefilef@und`.)

## 2.5 Declaring a file substitution

```

202 <@=filehook>
203 </2ekernel>
204 <*2ekernel | latexrelease>
205 <latexrelease>\IncludeInRelease{2020/10/01}%
206 <latexrelease> {\_filehook_subst_add:nn}{Declaring file substitution}%
207 \ExplSyntaxOn

```

`\_filehook_subst_add:nn` `\_filehook_subst_add:nn` declares a file substitution by doing a (global) definition of the form `\def\@file-subst@{file}{replacement}`. The file names are properly sanitised, and normalized with the same treatment done for the file hooks. That is, a file replacement is declared by using the file name (and extension, if any) only, and the file path should not be given. If a file name is empty it is replaced by `.tex` (the empty `csname` is used to check that).

```

208 \cs_new_protected:Npn \_filehook_subst_add:nn #1 #2
209 {
210   \group_begin:
211     \cs_set:cpx { } { \exp_not:o { \cs:w\cs_end: } }
212     \int_set:Nn \tex_escapechar:D { -1 }
213     \cs_gset:cpx
214     {
215       @file-subst@
216       \_filehook_subst_file_normalize:Nn \use_ii_iii:nnn {#1}
217     }
218     { \_filehook_subst_file_normalize:Nn \_filehook_file_name_compose:nnn
219       {#2} }
220   \group_end:
221 }
222 \cs_new_protected:Npn \_filehook_subst_remove:n #1
223 {

```

```

224 \group_begin:
225 \cs_set:cpx { } { \exp_not:o { \cs:w\cs_end: } }
226 \int_set:Nn \tex_escapechar:D { -1 }
227 \cs_undefine:c
228 {
229 @file-subst@
230 \__filehook_subst_file_normalize:Nn \use_ii_iii:nnn {#1}
231 }
232 \group_end:
233 }
234 \cs_new:Npn \__filehook_subst_file_normalize:Nn #1 #2
235 {
236 \exp_after:wN \__filehook_subst_empty_name_chk:NN
237 \cs:w \exp_after:wN \cs_end:
238 \cs:w \__filehook_file_parse_full_name:nN {#2} #1 \cs_end:
239 }
240 \cs_new:Npn \__filehook_subst_empty_name_chk:NN #1 #2
241 { \if_meaning:w #1 #2 .tex \else: \token_to_str:N #2 \fi: }

```

(End of definition for `\__filehook_subst_add:nn` and others.)

`\use_ii_iii:nnn` A variant of `\use_...` to discard the first of three arguments.

*Todo: this should move to `expl3`*

```

242 \cs_gset:Npn \use_ii_iii:nnn #1 #2 #3 {#2 #3}

```

(End of definition for `\use_ii_iii:nnn`.)

```

243 \ExplSyntaxOff
244 </2ekernel | latexrelease>
245 <latexrelease>\EndIncludeInRelease
246 <*2ekernel>

```

`\declare@file@substitution` For two internals we provide L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> names so that we can use them elsewhere in the kernel (and so that they can be used in packages if really needed, e.g., `scrfile`).

`\undecclare@file@substitution`

```

247 </2ekernel>
248 <*2ekernel | latexrelease>
249 <latexrelease>\IncludeInRelease{2020/10/01}%
250 <latexrelease> \declare@file@substitution{File substitution}%
251 \ExplSyntaxOn
252 \cs_new_eq:NN \declare@file@substitution \__filehook_subst_add:nn
253 \cs_new_eq:NN \undecclare@file@substitution \__filehook_subst_remove:n
254 \ExplSyntaxOff
255 </2ekernel | latexrelease>
256 <latexrelease>\EndIncludeInRelease

```

We are not fully rolling back the file substitutions in case a rollback encounters a package that contains them, but is itself not setup for rollback. So we just bypass them and hope for the best.

```

257 <latexrelease>\IncludeInRelease{0000/00/00}%
258 <latexrelease> \declare@file@substitution{File substitution}%
259 <latexrelease>
260 <latexrelease>\let \declare@file@substitution \@gobbletwo
261 <latexrelease>\let \undecclare@file@substitution \@gobble
262 <latexrelease>

```

```

263 <latexrelease>\EndIncludeInRelease
264 <*2ekernel>

```

(End of definition for \declare@file@substitution and \undeclear@file@substitution. These functions are documented on page 1119.)

```

265 <@@=>

```

## 2.6 Selecting a file (\set@curr@file)

\set@curr@file Now we hook into \set@curr@file to resolve a possible file substitution, and add \set@curr@file@nosearch \@expl@@@filehook@set@curr@file@@nNN at the end, after \@curr@file is set.

\curr@file A file name is built using \expandafter\string\csize{filename}\endcsname to avoid expanding utf8 active characters. The \csize expands the normalization machinery and the routine to resolve a file substitution, returning a control sequence with the same name as the file.

It happens that when {filename} is empty, the generated control sequence is \csize\endcsname, and doing \string on that results in the file csizeendcsname.tex. To guard against that we \ifx-compare the generated control sequence with the empty csize. To do so, \csize\endcsname has to be defined, otherwise it would be equal to \relax and we would have false positives. Here we define \csize\endcsname to expand to itself to avoid it matching the definition of some other control sequence.

```

266 </2ekernel>
267 <*2ekernel | latexrelease>
268 <latexrelease>\IncludeInRelease{2022/06/01}%
269 <latexrelease>          {\set@curr@file}{Setting current file name}%
270 \def\set@curr@file{%
271   \begingroup
272     \set@curr@file@aux}
273 \edef\set@curr@file@nosearch{%
274   \begingroup
275     \let\noexpand\input@path\noexpand\@empty
276     \csize seq_clear:N\endcsname
277     \expandafter\noexpand\csize l_file_search_path_seq\endcsname
278     \noexpand\set@curr@file@aux}
279 \def\set@curr@file@aux#1{%
280   \escapechar\m@ne
281   \let\protect\string
282   \edef~{\string~}%
283   \expandafter\def\csize\expandafter\endcsname
284   \expandafter{\csize\endcsname}%

```

Two file names are set here: \@curr@file@reqd which is the file requested by the user, and \@curr@file which should be the same, except when we have a file substitution, in which case it holds the actual loaded file. \@curr@file is resolved first, to check if a substitution happens. If it doesn't, \@expl@@@filehook@if@file@replaced@@TF short-cuts and just copies \@curr@file, otherwise the full normalization procedure is executed.

At this stage the file name is parsed and normalized, but if the input doesn't have an extension, the default .tex is *not* added to \@curr@file because for applications other than \input (graphics, for example) the default extension may not be .tex. First check if the input has an extension, then if the input had no extension, call

\@expl@@@filehook@drop@extension@@N. In case of a file substitution, \@curr@file will have an extension.

```

285 \@@expl@@@filehook@if@no@extension@@nTF{#1}%
286 {\@tempwattrue}{\@tempwafalse}%
287 \@kernel@make@file@csname\@curr@file
288 \@expl@@@filehook@resolve@file@subst@@w {#1}%
289 \@expl@@@filehook@if@file@replaced@@TF
290 {\@kernel@make@file@csname\@curr@file@reqd
291 \@expl@@@filehook@normalize@file@name@@w{#1}%
292 \if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file@reqd \fi}%
293 {\if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file \fi
294 \global\let\@curr@file@reqd\@curr@file}%
295 \@expl@@@filehook@clear@replacement@flag@@
296 \endgroup}
297 /2kernel | latexrelease)
298 (latexrelease)\EndIncludeInRelease

299 (latexrelease)\IncludeInRelease{2021/06/01}%
300 (latexrelease) {\set@curr@file}{Setting current file name}%
301 (latexrelease)\def\set@curr@file#1{%
302 (latexrelease) \begingroup
303 (latexrelease) \escapechar\m@ne
304 (latexrelease) \let\protect\string
305 (latexrelease) \edef~{\string~}%
306 (latexrelease) \expandafter\def\csname\expandafter\endcsname
307 (latexrelease) \expandafter{\csname\endcsname}%
308 (latexrelease) \@expl@@@filehook@if@no@extension@@nTF{#1}%
309 (latexrelease) {\@tempwattrue}{\@tempwafalse}%
310 (latexrelease) \@kernel@make@file@csname\@curr@file
311 (latexrelease) \@expl@@@filehook@resolve@file@subst@@w {#1}%
312 (latexrelease) \@expl@@@filehook@if@file@replaced@@TF
313 (latexrelease) {\@kernel@make@file@csname\@curr@file@reqd
314 (latexrelease) \@expl@@@filehook@normalize@file@name@@w{#1}%
315 (latexrelease) \if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file@reqd \fi}%
316 (latexrelease) {\if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file \fi
317 (latexrelease) \global\let\@curr@file@reqd\@curr@file}%
318 (latexrelease) \@expl@@@filehook@clear@replacement@flag@@
319 (latexrelease) \endgroup}
320 (latexrelease)\let\set@curr@file@nosearch\@undefined
321 (latexrelease)\EndIncludeInRelease

322 (latexrelease)\IncludeInRelease{2020/10/01}%
323 (latexrelease) {\set@curr@file}{Setting current file name}%
324 (latexrelease)\def\set@curr@file#1{%
325 (latexrelease) \begingroup
326 (latexrelease) \escapechar\m@ne
327 (latexrelease) \expandafter\def\csname\expandafter\endcsname
328 (latexrelease) \expandafter{\csname\endcsname}%
329 (latexrelease) \@expl@@@filehook@if@no@extension@@nTF{#1}%
330 (latexrelease) {\@tempwattrue}{\@tempwafalse}%
331 (latexrelease) \@kernel@make@file@csname\@curr@file
332 (latexrelease) \@expl@@@filehook@resolve@file@subst@@w {#1}%
333 (latexrelease) \@expl@@@filehook@if@file@replaced@@TF
334 (latexrelease) {\@kernel@make@file@csname\@curr@file@reqd
335 (latexrelease) \@expl@@@filehook@normalize@file@name@@w{#1}%

```

```

336 <latexrelease> \if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file@reqd \fi}%
337 <latexrelease> {\if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file \fi
338 <latexrelease> \global\let\@curr@file@reqd\@curr@file}%
339 <latexrelease> \@expl@@@filehook@clear@replacement@flag@@
340 <latexrelease> \endgroup}
341 <latexrelease>\let\set@curr@file@nosearch\@undefined
342 <latexrelease>\EndIncludeInRelease

343 <latexrelease>\IncludeInRelease{2019/10/01}%
344 <latexrelease> {\set@curr@file}{Setting current file name}%
345 <latexrelease>\def\set@curr@file#1{%
346 <latexrelease> \begingroup
347 <latexrelease> \escapechar\m@ne
348 <latexrelease> \xdef\@curr@file{%
349 <latexrelease> \expandafter\expandafter\expandafter\unquote@name
350 <latexrelease> \expandafter\expandafter\expandafter{%
351 <latexrelease> \expandafter\string
352 <latexrelease> \csname\@firstofone#1\@empty\endcsname}}%
353 <latexrelease> \endgroup
354 <latexrelease>}}
355 <latexrelease>\let\set@curr@file@nosearch\@undefined
356 <latexrelease>\EndIncludeInRelease

357 <latexrelease>\IncludeInRelease{0000/00/00}%
358 <latexrelease> {\set@curr@file}{Setting current file name}%
359 <latexrelease>\let\set@curr@file\@undefined
360 <latexrelease>\let\set@curr@file@nosearch\@undefined
361 <latexrelease>\EndIncludeInRelease
362 <*2ekernel>

```

(End of definition for \set@curr@file and others.)

```

\@filehook@set@CurrentFile      Todo: This should get internalized using @expl@ names
\@kernel@make@file@csname
\@set@curr@file@aux
363 </2ekernel>
364 <*2ekernel | latexrelease>
365 <latexrelease>\IncludeInRelease{2020/10/01}%
366 <latexrelease> {\@kernel@make@file@csname}{Make file csname}%
367 \def\@kernel@make@file@csname#1#2#3{%
368 \xdef#1{\expandafter\@set@curr@file@aux
369 \csname\expandafter#2\@firstofone#3\@nil\endcsname}}

```

This auxiliary compares \<filename> with \csname\endcsname to check if the empty .tex file was requested.

```

370 \long\def\@set@curr@file@aux#1{%
371 \expandafter\ifx\csname\endcsname#1%
372 .tex\else\string#1\fi}

```

Then we call \@expl@@@filehook@set@curr@file@@nNN once for \@curr@file to set \CurrentFile(Path)Used and once for \@curr@file@reqd to set \CurrentFile(Path). Here too the slower route is only used if a substitution happened, but here \@expl@@@filehook@if@file@replaced@@TF can't be used because the flag is reset at the \endgroup above, so we check if \@curr@file and \@curr@file@reqd differ. This macro is issued separate from \set@curr@file because it changes \CurrentFile, and side-effects would quickly get out of control.

```

373 \def\@filehook@set@CurrentFile{%

```

```

374 \@@expl@@@filehook@set@curr@file@@nNN{\@curr@file}%
375 \CurrentFileUsed\CurrentFilePathUsed
376 \ifx\@curr@file@reqd\@curr@file
377 \let\CurrentFile\CurrentFileUsed
378 \let\CurrentFilePath\CurrentFilePathUsed
379 \else
380 \@@expl@@@filehook@set@curr@file@@nNN{\@curr@file@reqd}%
381 \CurrentFile\CurrentFilePath
382 \fi}
383 </2ekernel | latexrelease>
384 <latexrelease>\EndIncludeInRelease
385 <*2ekernel>

(End of definition for \@filehook@set@CurrentFile, \@kernel@make@file@csname, and
\@set@curr@file@aux.)

386 <@@=filehook>

```

`\_filehook_set_curr_file:nNN`  
`\_filehook_set_curr_file_assign:nnnNN`

When inputting a file, `\set@curr@file` does a file lookup (in `\input@path` and `\l_file_search_path_seq`) and returns the actual file name (`<base>` plus `<ext>`) in `\CurrentFileUsed`, and in case there's a file substitution, the requested file in `\CurrentFile` (otherwise both are the same). Only the base and extension are returned, regardless of the input (both `path/to/file.tex` and `file.tex` end up as `file.tex` in `\CurrentFile`). The path is returned in `\CurrentFilePath`, in case it's needed.

```

387 </2ekernel>
388 <*2ekernel | latexrelease>
389 <latexrelease>\IncludeInRelease{2020/10/01}%
390 <latexrelease> \{\_filehook_set_curr_file:nNN\}{Set curr file}%
391 \ExplSyntaxOn
392 \cs_new_protected:Npn \_filehook_set_curr_file:nNN #1
393 {
394 \exp_args:Nf \_filehook_file_parse_full_name:nN {#1}
395 \_filehook_set_curr_file_assign:nnnNN
396 }
397 \cs_new_protected:Npn \_filehook_set_curr_file_assign:nnnNN #1 #2 #3 #4 #5
398 {
399 \str_set:Nn #5 {#1}
400 \str_set:Nn #4 {#2#3}
401 }
402 \ExplSyntaxOff
403 </2ekernel | latexrelease>
404 <latexrelease>\EndIncludeInRelease
405 <*2ekernel>

(End of definition for \_filehook_set_curr_file:nNN and
\_filehook_set_curr_file_assign:nnnNN.)

```

## 2.7 Replacing a file and detecting loops

`\_filehook_resolve_file_subst:w`  
`\_filehook_normalize_file_name:w`  
`\_filehook_file_name_compose:nnn`

Start by sanitizing the file with `\_filehook_file_parse_full_name:nN` then do `\_filehook_file_subst_begin:nnn{\<path>}{\<name>}{\<ext>}`.

```

406 </2ekernel>
407 <*2ekernel | latexrelease>
408 <latexrelease>\IncludeInRelease{2020/10/01}%

```

```

409 <latexrelease>      {\_filehook_resolve_file_subst:w}{Replace files detect loops}%
410 \ExplSyntaxOn
411 \cs_new:Npn \_filehook_resolve_file_subst:w #1 \@nil
412   { \_filehook_file_parse_full_name:nN {#1} \_filehook_file_subst_begin:nnn }
413 \cs_new:Npn \_filehook_normalize_file_name:w #1 \@nil
414   { \_filehook_file_parse_full_name:nN {#1} \_filehook_file_name_compose:nnn }
415 \cs_new:Npn \_filehook_file_name_compose:nnn #1 #2 #3
416   { \tl_if_empty:nF {#1} { #1 / } #2#3 }

```

```

\_filehook_file_replaced
\_filehook_if_file_replaced:TF
\_filehook_clear_replacement_flag:

```

Since the file replacement is done expandably in a `\csname`, use a flag to remember if a substitution happened. We use this in `\set@curr@file` to short-circuit some of it in case no substitution happened (by far the most common case, so it's worth optimizing). The flag raised during the file substitution algorithm must be explicitly cleared after the `\_filehook_if_file_replaced:TF` conditional is no longer needed, otherwise further uses of `\_filehook_if_file_replaced:TF` will wrongly return true.

```

417 \flag_new:n { \_filehook_file_replaced }
418 \cs_new:Npn \_filehook_if_file_replaced:TF #1 #2
419   { \flag_if_raised:nTF { \_filehook_file_replaced } {#1} {#2} }
420 \cs_new_protected:Npn \_filehook_clear_replacement_flag:
421   { \flag_clear:n { \_filehook_file_replaced } }

```

```

\_filehook_file_subst_begin:nnn

```

First off, start by checking if the current file (`\langle name \rangle + \langle ext \rangle`) has a declared substitution. If not, then just put that as the name (including a possible `\langle path \rangle` in this case): this is the default case with no substitutions, so it's the first to be checked. The auxiliary `\_filehook_file_subst_tortoise_hare:nn` sees that there's no replacement for `#2#3` and does nothing else.

```

422 \cs_new:Npn \_filehook_file_subst_begin:nnn #1 #2 #3
423   {
424     \_filehook_file_subst_tortoise_hare:nn { #2#3 } { #2#3 }
425     { \_filehook_file_name_compose:nnn {#1} {#2} {#3} }
426   }
427 \ExplSyntaxOff
428 </2ekernel|latexrelease>
429 <latexrelease>\EndIncludeInRelease
430 <*2ekernel>

```

### 2.7.1 The Tortoise and Hare algorithm

```

\_filehook_file_subst_tortoise_hare:nn
\_filehook_file_subst_loop:NN
\_filehook_file_subst_loop:cc

```

If there is a substitution (`\langle true \rangle` in the first `\cs_if_exist:cTF` below), then first check if there is no substitution down the line: this should be the second most common case, of one file replaced by another. In that case just leave the substitution there and the job is done. If any substitution happens, then the `\flag \_filehook_file_replaced` is raised (conditionally, because checking if a flag is raised is much faster than raising it over and over again).

If, however there are more substitutions, then we need to check for a possible loop in the substitutions, which would otherwise put  $\text{\TeX}$  in an infinite loop if just an exhaustive expansion was used.

To detect a loop, the *Tortoise and Hare* algorithm is used. The name of the algorithm is an analogy to Aesop's fable, in which the Hare outruns a Tortoise. The two pointers here are the csnames which contains each file replacement, both of which start at the position zero, which is the file requested. In the inner part of the macro below, `\_filehook_file_subst_loop:cc` is called with `\@file-subst@<file>` and

`\@file-subst@\@file-subst@<file>`; that is, the substitution of `<file>` and the substitution of that substitution: the Tortoise walks one step while the Hare walks two.

Within `\__filehook_file_subst_loop:NN` the two substitutions are compared, and if they lead to the same file it means that there is a loop in the substitutions. If there's no loop, `\__filehook_file_subst_tortoise_hare:nn` is called again with the Tortoise at position 1 and the hare at 2. Again, the substitutions are checked ahead of the Hare pointer to check that it won't run too far; in case there is no loop in the declarations, eventually one of the `\cs_if_exist:cTF` below will go `<false>` and the algorithm will end; otherwise it will run until the Hare reaches the same spot as the tortoise and a loop is detected.

```

431 </2ekernel>
432 <*2ekernel|latexrelease>
433 <latexrelease>\IncludeInRelease{2020/10/01}%
434 <latexrelease> {\__filehook_file_subst_tortoise_hare:nn}{Tortoise and Hare}%
435 \ExplSyntaxOn
436 \cs_new:Npn \__filehook_file_subst_tortoise_hare:nn #1 #2 #3
437 {
438   \cs_if_exist:cTF { @file-subst@ #2 }
439   {
440     \flag_if_raised:nF { __filehook_file_replaced }
441     { \flag_raise:n { __filehook_file_replaced } }
442     \cs_if_exist:cTF { @file-subst@ \use:c { @file-subst@ #2 } }
443     {
444       \__filehook_file_subst_loop:cc
445       { @file-subst@ #1 }
446       { @file-subst@ \use:c { @file-subst@ #2 } }
447     }
448     { \use:c { @file-subst@ #2 } }
449   }
450   { #3 }
451 }

```

This is just an auxiliary to check if a loop was found, and continue the algorithm otherwise. If a loop is found, the `.tex` file is used as fallback and `\__filehook_file_subst_cycle_error:cN` is called to report the error.

```

452 \cs_new:Npn \__filehook_file_subst_loop:NN #1 #2
453 {
454   \token_if_eq_meaning:NNTF #1 #2
455   {
456     .tex
457     \__filehook_file_subst_cycle_error:cN { @file-subst@ #1 } #1
458   }
459   { \__filehook_file_subst_tortoise_hare:nn {#1} {#2} {#2} }
460 }
461 \cs_generate_variant:Nn \__filehook_file_subst_loop:NN { cc }

```

Showing this type of error expandably is tricky, as we have a very limited amount of characters to show and a potentially large list. As a work around, several errors are printed, each showing one step of the loop, until all the error messages combined show the loop.

```

462 \cs_new:Npn \__filehook_file_subst_cycle_error:NN #1 #2
463 {
464   \msg_expandable_error:nnff { latex2e } { file-cycle }

```

```

465 {#1} { \use:c { @file-subst@ #1 } }
466 \token_if_eq_meaning:NNF #1 #2
467 { \__filehook_file_subst_cycle_error:cN { @file-subst@ #1 } #2 }
468 }
469 \cs_generate_variant:Nn \__filehook_file_subst_cycle_error:NN { c }
And the error message:
470 \msg_new:nnn { latex2e } { file-cycle }
471 { File~loop!~#1~replaced~by~#2... }

(End of definition for \__filehook_resolve_file_subst:w and others.)

472 \ExplSyntaxOff
473 </2ekernel | latexrelease>
474 <latexrelease>\EndIncludeInRelease
475 <*2ekernel>
476 <@@=>

```

## 2.8 Preventing a package from loading

We support the use case of preventing a package from loading but not any other type of files (e.g., classes).

`\disable@package@load` defines `\@pkg-disable@<package>` to expand to some code #2 instead of loading the package.

```

477 </2ekernel>
478 <*2ekernel | latexrelease>
479 <latexrelease>\IncludeInRelease{2020/10/01}%
480 <latexrelease> { \disable@package@load } { Disable packages } %
481 \def \disable@package@load #1 #2 { %
482   \global \namedef { \@pkg-disable@ #1 . \@pkgextension } { #2 } }

```

Here we check if a control sequence named `\@pkg-disable@<name>.sty` is defined, and if so don't use the package loading code #2, but use the replacement code stored in that control sequence, write something to the log, and then prevent `\@onefilewithoptions` from sanity-checking the requested package date (the `\expandafter` here triggers one in `\@onefilewithoptions` that ends a conditional there, and the `\@gobbletwo` removes the date checking code from the input stream).

```

483 \def \disable@package@load #1 #2 { %
484   \ifundefined { \@pkg-disable@ #1 } %
485     { #2 } %
486     { \@nameuse { \@pkg-disable@ #1 } %
487       \@latex@info { Package ' #1 ' has been disabled . %
488         \MessageBreak Load request ignored } %
489       \expandafter \@gobbletwo } }

```

`\reenable@package@load` undefines `\@pkg-disable@<package>` to realow loading a package.

```

490 \def \reenable@package@load #1 { %
491   \global \expandafter \let
492   \csname \@pkg-disable@ #1 . \@pkgextension \endcsname \@undefined }

```

```

493 </2ekernel | latexrelease>
494 <latexrelease>\EndIncludeInRelease
495 <latexrelease>\IncludeInRelease{0000/00/00}%
496 <latexrelease>      {\disable@package@load}{Disable packages}%
497 <latexrelease>
498 <latexrelease>\let\disable@package@load \undefined
499 <latexrelease>\let\@disable@packageload@do\undefined
500 <latexrelease>\let\reenable@package@load \undefined
501 <latexrelease>\EndIncludeInRelease
502 <*2ekernel>

```

(End of definition for \disable@package@load, \reenable@package@load, and  
\@disable@packageload@do. These functions are documented on page 1119.)

## 2.9 High-level interfaces for L<sup>A</sup>T<sub>E</sub>X

None so far and the general feeling for now is that the hooks are enough. Packages like filehook, etc., may use them to set up their interfaces (samples are given below) but for the now the kernel will not provide any.

### 2.10 Internal commands needed elsewhere

Here we set up a few horrible (but consistent) L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> names to allow for internal commands to be used outside this module (and in parts that still use L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> syntax. We have to unset the @@ since we want double “at” sign in place of double underscores.

```

503 <@@= >
504 </2ekernel>
505 <*2ekernel | latexrelease>
506 <latexrelease>\IncludeInRelease{2020/10/01}%
507 <latexrelease>      {\@expl@@@filehook@if@no@extension@@nTF}{2e tmp interfaces}%
508 \ExplSyntaxOn
509 \cs_new_eq:NN \@expl@@@filehook@if@no@extension@@nTF
510               \__filehook_if_no_extension:nTF
511 \cs_new_eq:NN \@expl@@@filehook@set@curr@file@@nNN
512               \__filehook_set_curr_file:nNN
513 \cs_new_eq:NN \@expl@@@filehook@resolve@file@subst@@w
514               \__filehook_resolve_file_subst:w
515 \cs_new_eq:NN \@expl@@@filehook@normalize@file@name@@w
516               \__filehook_normalize_file_name:w
517 \cs_new_eq:NN \@expl@@@filehook@if@file@replaced@@TF
518               \__filehook_if_file_replaced:TF
519 \cs_new_eq:NN \@expl@@@filehook@clear@replacement@flag@@
520               \__filehook_clear_replacement_flag:
521 \cs_new_eq:NN \@expl@@@filehook@drop@extension@@N
522               \__filehook_drop_extension:N
523 \cs_new_eq:NN \@expl@@@filehook@file@push@@
524               \__filehook_file_push:
525 \cs_new_eq:NN \@expl@@@filehook@file@pop@@
526               \__filehook_file_pop:

```

```

527 \cs_new_eq:NN \@expl@@@filehook@file@pop@assign@@nnnn
528         \__filehook_file_pop_assign:nnnn
529 \ExplSyntaxOff

```

This one specifically has to be undefined because it is left over in the input stream from `\InputIfFileExists` and executed when `latexrelease` is loaded. It cannot be `\let` to `\undefined` otherwise it would error as well, so it is `\let` to `\relax` to be silently ignored when loading `\latexrelease`.

```

530 </2ekernel | latexrelease>
531 <latexrelease>\EndIncludeInRelease
532 <latexrelease>
533 <latexrelease>\IncludeInRelease{0000/00/00}%
534 <latexrelease>    {\@expl@@@filehook@if@no@extension@@nTF}{2e tmp interfaces}%
535 <latexrelease>\let\@expl@@@filehook@file@pop@@\relax
536 <latexrelease>\EndIncludeInRelease
537 <*2ekernel>

```

This ends the kernel code in this file.

```

538 </2ekernel>

```

### 3 A sample package for structuring the log output

```

539 <*structuredlog>
540 <@@=filehook>

541 \ProvidesExplPackage
542     {structuredlog}{\ltfilehookdate}{\ltfilehookversion}
543     {Structuring the TeX transcript file}

```

`\g_filehook_nesting_level_int` Stores the current package nesting level.

```

544 \int_new:N \g__filehook_nesting_level_int

```

Initialise the counter with the number of files in the `\@currnamestack` (the number of items divided by 3) minus one, because this package is skipped when printing to the log.

```

545 \int_gset:Nn \g__filehook_nesting_level_int
546     { ( \tl_count:N \@currnamestack ) / 3 - 1 }

```

*(End of definition for `\g__filehook_nesting_level_int`.)*

`\_filehook_log_file_record:n` This macro is responsible for increasing and decreasing the file nesting level, as well as printing to the log. The argument is either `STOPTART` or `STOP` and the action it takes on the nesting integer depends on that.

```

547 \cs_new_protected:Npn \_filehook_log_file_record:n #1
548 {
549     \str_if_eq:nnT {#1} {START} { \int_gincr:N \g__filehook_nesting_level_int }
550     \iow_term:x
551     {
552         \prg_replicate:nn { \g__filehook_nesting_level_int } { = } ~
553         ( LEVEL ~ \int_use:N \g__filehook_nesting_level_int \c_space_tl #1 ) ~
554         \CurrentFileUsed

```

If there was a file replacement, show that as well:

```

555     \str_if_eq:NNF \CurrentFileUsed \CurrentFile
556     { ~ ( \CurrentFile \c_space_tl requested ) }
557     \iow_newline:
558   }
559   \str_if_eq:nnT {#1} {STOP} { \int_gdecr:N \g__filehook_nesting_level_int }
560 }

```

Now just hook the macro above in the generic file/before...

```

561 \AddToHook{file/before}{ \__filehook_log_file_record:n { START } }
...and file/after hooks. We don't want to install the file/after hook immediately,
because that would mean it is the first time executed when the package finishes. We
therefore put the declaration inside \AddToHookNext so that it gets only installed when
we have left this package.

```

```

562 \AddToHookNext{file/after}
563 { \AddToHook{file/after}{ \__filehook_log_file_record:n { STOP } } }

```

(End of definition for \\_\_filehook\_log\_file\_record:n.)

```

564 <@@=
565 </structuredlog>

```

## 4 Package emulations

### 4.1 Package atveryend emulation

With the new hook management and the hooks in \enddocument all of atveryend is taken care of. We can make an emulation only here after the substitution functionality is available:

```

566 <*2ekernel>
567 \declare@file@substitution{atveryend.sty}{atveryend-ltx.sty}
568 </2ekernel>

```

Here is the package file we point to:

```

569 <*atveryend-ltx>
570 \ProvidesPackage{atveryend-ltx}
571 [2020/08/19 v1.0a
572 Emulation of the original atveryend package^^Jwith kernel methods]

```

Here are new definitions for its interfaces now pointing to the hooks in \enddocument

```

573 \newcommand\AfterLastShipout {\AddToHook{enddocument/afterlastpage}}
574 \newcommand\AtVeryEndDocument {\AddToHook{enddocument/afteraux}}

```

Next one is a bit of a fake, but the result should normally be as expected. If not, one needs to add a rule to sort the code chunks in enddocument/info.

```

575 \newcommand\AtEndAfterFileList{\AddToHook{enddocument/info}}
576 \newcommand\AtVeryVeryEnd {\AddToHook{enddocument/end}}

```

**\BeforeClearDocument** This one is the only one we don't implement or rather don't have a dedicated hook in the code.

```

577 \ExplSyntaxOn
578 \newcommand\BeforeClearDocument[1]
579 { \AtEndDocument{#1}
580   \atveryend@DEPRECATED{BeforeClearDocument \tl_to_str:n{#1}}
581 }

```

```

582 \cs_new:Npn\atveryend@DEPRECATED #1
583   {\iow_term:x{=====~DEPRECATED~USAGE~#1~=====}}
584 \ExplSyntaxOff

(End of definition for \BeforeClearDocument.)

585 \atveryend-ltx)

```

## File 53

# ltshipout.dtx

## 1 Introduction

The code provides an interface to the `\shipout` primitive of  $\mathrm{T\!E\!X}$  which is called when a finished pages is finally “shipped out” to the target output file, e.g., the `.dvi` or `.pdf` file. A good portion of the code is based on ideas by Heiko Oberdiek implemented in his packages `atbegshi` and `atenddvi` even though the interfaces are somewhat different.<sup>56</sup>

### 1.1 Overloading the `\shipout` primitive

---

**`\shipout`** With this implementation  $\mathrm{T\!E\!X}$ ’s `shipout` primitive is no longer available for direct use. Instead `\shipout` is running some (complicated) code that picks up the box to be shipped out regardless of how that is done, i.e., as a constructed `\vbox` or `\hbox` or as a box register.

It then stores it in a named box register. This box can then be manipulated through a set of hooks after which it is shipped out for real.

Each shipout that actually happens (i.e., where the material is not discarded for one or the other reason) is recorded and the total number is available in a readonly variable and in a  $\mathrm{L\!A\!T\!E\!X}$  counter.

---

**`\RawShipout`** This command implements a simplified shipout that bypasses the foreground and background hooks, e.g., only `shipout/firstpage` and `shipout/lastpage` are executed and the total shipout counters are incremented.

The command doesn’t use `\ShipoutBox` but its own private box register so that it can be used inside of shipout hooks to do some additional shipouts while already in the output routine with the current page being stored in `\ShipoutBox`. It does have access to `\ShipoutBox` if it is used in `shipout/before` (or `shipout/after`) and can use its content.

It is safe to use it in `shipout/before` or `shipout/after` but not necessarily in the other `shipout/...` hooks as they are intended for special processing.

---

<sup>56</sup>Heiko’s interfaces are emulated by the kernel code, if a document requests his packages, so older documents will continue to work.

---

<code>\ShipoutBox</code> <code>\l_shipout_box</code>	This box register is called <code>\ShipoutBox</code> (alternatively available via the L3 name <code>\l_shipout_box</code> ).
---	--

---

This box is a “local” box and assignments to it should be done only locally. Global assignments (as done by some packages with older code where this box is known as 255) may work but they are conceptually wrong and may result in errors under certain circumstances.

During the execution of `shipout/before` this box contains the accumulated material for the page, but not yet any material added by other shipout hooks. During execution of `shipout/after`, i.e., after the shipout has happened, the box also contains any background or foreground material.

Material from the hooks `shipout/firstpage` or `shipout/lastpage` is not included (but only used during the actual shipout) to facilitate reuse of the box data (e.g., `shipout/firstpage` material should never be added to a later page of the output).

---

<code>\l_shipout_box_ht_dim</code> <code>\l_shipout_box_dp_dim</code> <code>\l_shipout_box_wd_dim</code> <code>\l_shipout_box_ht_plus_dp_dim</code>
--

---

The shipout box dimensions are available in the L3 registers `\l_shipout_box_ht_dim`, etc. (there are no L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> names).<sup>57</sup> These variables can be used inside the hook code for `shipout/before`, `shipout/foreground` and `shipout/background` if needed.

## 1.2 Provided hooks

---

<code>shipout/before</code> <code>shipout/after</code> <code>shipout/foreground</code> <code>shipout/background</code> <code>shipout/firstpage</code> <code>shipout/lastpage</code>
--

---

The code for `\shipout` offers a number of hooks into which packages (or the user) can add code to support different use cases. These are:

**shipout/before** This hook is executed after the finished page has been stored in `\ShipoutBox` / `\l_shipout_box`. It can be used to alter that box content or to discard it completely (see `\DiscardShipoutBox` below).

You can use `\RawShipout` inside this hook for special use cases. It can make use of `\ShipoutBox` (which doesn’t yet include the background and foreground material).

**Note:** It is not possible (or say advisable) to try and use this hook to typeset material with the intention to return it to main vertical list, it will go wrong and give unexpected results in many cases—for starters it will appear after the current page not before or it will vanish or the vertical spacing will be wrong!

**shipout/background** This hook adds a picture environment into the background of the page with the (0,0) coordinate in the top-left corner using a `\unitlength` of 1pt.

It should therefore only receive `\put` commands or other commands suitable in a `picture` environment and the vertical coordinate values would normally be negative.

---

<sup>57</sup>Might need changing, but HO’s version as strings is not really helpful I think).

Technically this is implemented by adding a zero-sized `\hbox` as the very first item into the `\ShipoutBox` containing that `picture` environment. Thus the rest of the box content will overprint what ever is typeset by that hook.

**shipout/foreground** This hook adds a picture environment into the foreground of the page with the (0,0) coordinate in the top-left corner using a `\unitlength` of 1pt. Technically this is implemented by adding a zero-sized `\hbox` as the very last item into the `\ShipoutBox` and raising it up so that it still has its (0,0) point in the top-left corner. But being placed after the main box content it will be typeset later and thus overprints it (i.e., is in the foreground).

**shipout** This hook is executed after foreground and/or background material has been added, i.e., just in front of the actual shipout operation. Its purpose is to allow manipulation of the finalized box (stored in `\ShipoutBox`) with the extra material also in place (which is not yet the case in `shipout/before`).

It cannot be used to cancel the shipout operation via `\DiscardShipoutBox` (that has to happen in `shipout/before`, if desired!

**shipout/firstpage** The material from this hook is executed only once at the very beginning of the first output page that is shipped out (i.e., not discarded at the last minute). It should only contain `\special` or similar commands needed to direct post processors handling the .dvi or .pdf output.<sup>58</sup>

This hook is added to the very first page regardless of how it is shipped out (i.e., with `\shipout` or `\RawShipout`).

**shipout/lastpage** The corresponding hook to add `\specials` at the very end of the output file. It is only executed on the very last page of the output file — or rather on the page that  $\text{\LaTeX}$  believes is the last one. Again it is executed regardless of the shipout method.

It may not be possible for  $\text{\LaTeX}$  to correctly determine which page is the last one without several reruns. If this happens and the hook is non-empty then  $\text{\LaTeX}$  will add an extra page to place the material and also request a rerun to get the correct placement sorted out.

**shipout/after** This hook is executed after a shipout has happened. If the shipout box is discarded this hook is not looked at.

You can use `\RawShipout` inside this hook for special use cases and the main `\ShipoutBox` is still available at this point (but in contrast to `shipout/before` it now includes the background and foreground material).

**Note:** Just like `shipout/before` this hook is not meant to be used for adding typeset material back to the main vertical list—it might vanish or the vertical spacing will be wrong!

As mentioned above the hook `shipout/before` is executed first and can manipulate the prepared shipout box stored in `\ShipoutBox` or set things up for use in `\write` during the actual shipout. It is even run if there was a `\DiscardShipoutBox` request in the document.

The other hooks (except `shipout` and `shipout/after`) are added inside `hboxes` to the box being shipped out in the following order:

---

<sup>58</sup>In  $\text{\LaTeX} 2_\epsilon$  that was already existing, but implemented using a box register with the name `\@begindivibox`.

<code>shipout/firstpage</code>	only on the first page
<code>shipout/background</code>	
<code>&lt;boxed content of \ShipoutBox&gt;</code>	
<code>shipout/foreground</code>	
<code>shipout/lastpage</code>	only on the last page

If any of the hooks has no code then the corresponding box is added at that point.

Once the (page) box has got the above extra content it can again be manipulated using the `shipout` hook and then is shipped out for real.

Once the (page) box has been shipped out the `shipout/after` hook is called (while you are still inside the output routine). It is not called if the shipout box was discarded.

In a document that doesn't produce pages, e.g., only makes `\typeouts`, none of the hooks are ever executed (as there is no `\shipout`) not even the `shipout/lastpage` hook.

If `\RawShipout` is used instead of `\shipout` then only the hooks `shipout/firstpage` and `shipout/lastpage` are executed (on the first or last page), all others are bypassed.

### 1.3 Legacy L<sup>A</sup>T<sub>E</sub>X commands

---

<code>\AtBeginDvi</code>	<code>\AtBeginDvi {&lt;code&gt;}</code>
--------------------------	---

---

<code>\AtEndDvi</code>	
------------------------	--

`\AtBeginDvi` is the existing L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interface to fill the `shipout/firstpage` hook. This is not really a good name as it is not just supporting `.dvi` but also `.pdf` output or `.xdv`.

`\AtEndDvi` is the counterpart that was not available in the kernel but only through the package `atenddvi`. It fills the `shipout/lastpage` hook.

Neither interface can set a code label but uses the current default label.

As these two wrappers have been available for a long time we continue offering them (but not enhancing them, e.g., by providing support for code labels).

For new code we strongly suggest using the high-level hook management commands directly instead of “randomly-named” wrappers. This will lead to code that is easier to understand and to maintain and it also allows you to set code labels if needed.

For this reason we do not provide any other “new” wrapper commands for the above hooks in the kernel, but only keep the existing ones for backward compatibility.

## 1.4 Special commands for use inside the hooks

---

<code>\DiscardShipoutBox</code> <code>\shipout_discard:</code>	<code>\AddToHookNext {shipout/before} {...\DiscardShipoutBox...}</code>
---	---

---

The `\DiscardShipoutBox` declaration (L3 name `\shipout_discard:`) requests that on the next shipout the page box is thrown away instead of being shipped to the `.dvi` or `.pdf` file.

Typical applications wouldn't do this unconditionally, but have some processing logic that decides to use or not to use the page.

Note that if this declaration is used directly in the document it may depend on the placement to which page it applies, given that  $\text{\LaTeX}$  output routine is called in an asynchronous manner! Thus normally one would use this only as part of the `shipout/before` code.

*Todo: Once we have a new mark mechanism available we can improve on that and make sure that the declaration applies to the page that contains it — not done (yet)*

`\DiscardShipoutBox` cannot be used in any of the `shipout/...` hooks other than `shipout/before`.

In the `atbegshi` package there are a number of additional commands for use inside the `shipout/before` hook. They should normally not be needed any more as one can instead simply add code to the hooks `shipout/before`, `shipout`, `shipout/background` or `shipout/foreground`.<sup>59</sup> If `atbegshi` gets loaded then those commands become available as public functions with their original names as given below.

## 1.5 Provided $\text{\LaTeX}$ callbacks

---

<code>pre_shipout_filter</code>	Under $\text{\LaTeX}$ the <code>pre_shipout_filter</code> Lua callback is provided which gets called directly after the <code>shipout</code> hook, immediately before the shipout primitive gets invoked. The signature is
---------------------------------	--

---

```
function(<node> head)
  return true
end
```

The `head` is the list node corresponding to the box to be shipped out. The return value should always be `true`.

---

<sup>59</sup>If that assumption turns out to be wrong it would be trivial to change them to public functions (right now they are private).

## 1.6 Information counters

---

<code>\ReadonlyShipoutCounter</code>	<code>\ifnum\ReadonlyShipoutCounter=...</code>
<code>\g_shipout_readonly_int</code>	<code>\int_use:N \g_shipout_readonly_int % expl3 usage</code>

---

This integer holds the number of pages shipped out up to now (including the one to be shipped out when inside the output routine). More precisely, it is incremented only after it is clear that a page will be shipped out, i.e., after the `shipout/before` hook (because that might discard the page)! In contrast `shipout/after` sees the incremented value.

Just like with the `page` counter its value is only accurate within the output routine. In the body of the document it may be off by one as the output routine is called asynchronously!

Also important: it *must not* be set, only read. There are no provisions to prevent that restriction, but if you manipulate it, chaos will be the result. To emphasize this fact it is not provided as a  $\text{\LaTeX}$  counter but as a  $\text{\TeX}$  counter (i.e., a command), so `\Alph{\ReadonlyShipoutCounter}` etc, would not work.

---

<code>totalpages</code>	<code>\arabic{totalpages}</code>
<code>\g_shipout_totalpages_int</code>	<code>\int_use:N \g_shipout_totalpage_int % expl3 usage</code>

---

In contrast to `\ReadonlyShipoutCounter`, the `totalpages` counter is a  $\text{\LaTeX}$  counter and incremented for each shipout attempt including those pages that are discarded for one or the other reason. Again `shipout/before` sees the counter before it is incremented. In contrast `shipout/after` sees the incremented value.

Furthermore, while it is incremented for each page, its value is never used by  $\text{\LaTeX}$ . It can therefore be freely reset or changed by user code, for example, to additionally count a number of pages that are not build by  $\text{\LaTeX}$  but are added in a later part of the process, e.g., cover pages or picture pages made externally.

Important: as this is a page-related counter its value is only reliable inside the output routine!

---

<code>\PreviousTotalPages</code>	<code>\PreviousTotalPages</code>
----------------------------------	----------------------------------

---

Command that expands to the number of total pages from the previous run. If there was no previous run or if used in the preamble it expands to 0. Note that this is a command and not a counter, so in order to display the number in, say, Roman numerals you have to assign its value to a counter and then use `\Roman` on that counter.

## 1.7 Debugging shipout code

---

<code>\DebugShipoutsOn</code>	<code>\DebugShipoutsOn</code>
<code>\DebugShipoutsOff</code>	
<code>\shipout_debug_on:</code>	Turn the debugging of shipout code on or off. This displays changes made to the shipout data structures.
<code>\shipout_debug_off:</code>	

---

*Todo: This needs some rationalizing and may not stay this way.*

## 2 Emulating commands from other packages

The packages in this section are no longer necessary, but as they are used by other packages, they are emulated when they are explicitly loaded with `\usepackage` or `\RequirePackage`.

Please note that the emulation only happens if the package is explicitly requested, i.e., the commands documented below are not automatically available in the L<sup>A</sup>T<sub>E</sub>X kernel! If you write a new package we suggest to use the appropriate kernel hooks directly instead of loading the emulation.

### 2.1 Emulating atbegshi

---

<code>\AtBeginShipoutUpperLeft</code>	<code>\AddToHook {shipout/before} {...\AtBeginShipoutUpperLeft{&lt;code&gt;}...}</code>
<code>\AtBeginShipoutUpperLeftForeground</code>	

---

This adds a `picture` environment into the background of the shipout box expecting `<code>` to contain `picture` commands. The same effect can be obtained by simply using kernel features as follows:

`\AddToHook{shipout/background}{<code>}`

There is one technical difference: if `\AtBeginShipoutUpperLeft` is used several times each invocation is put into its own box inside the shipout box whereas all `<code>` going into `shipout/background` ends up all in the same box in the order it is added or sorted based on the rules for the hook chunks.

`\AtBeginShipoutUpperLeftForeground` is similar with the difference that the `picture` environment is placed in the foreground. To model it with the kernel functions use the hook `shipout/foreground` instead.

---

<code>\AtBeginShipoutAddToBox</code>	<code>\AddToHook {shipout/before} {...\AtBeginShipoutAddToBox{&lt;code&gt;}...}</code>
<code>\AtBeginShipoutAddToBoxForeground</code>	

---

These work like `\AtBeginShipoutUpperLeft` and `\AtBeginShipoutUpperLeftForeground` with the difference that `<code>` is directly placed into an `\hbox` inside the shipout box and not surrounded by a `picture` environment.

To emulate them using `shipout/background` or `shipout/foreground` you may have to wrap `<code>` into a `\put` statement but if the code is not doing any typesetting just adding it to the hook should be sufficient.

---

<code>\AtBeginShipoutBox</code>	This is the name of the shipout box as <code>atbegshi</code> knows it.
---------------------------------	--

---



---

<code>\AtBeginShipoutOriginalShipout</code>	
---	--

---

This is the name of the `\shipout` primitive as `atbegshi` knows it. This bypasses all the mechanisms set up by the L<sup>A</sup>T<sub>E</sub>X kernel and there are various scenarios in which it can therefore fail. It should only be used to run existing legacy `atbegshi` code but not in newly developed applications.

The kernel alternative is `\RawShipout` which is integrated with the L<sup>A</sup>T<sub>E</sub>X mechanisms and updates, for example, the `\ReadonlyShipoutCounter` counter. Please use `\RawShipout` for new code if you want to bypass the before, foreground and background hooks.

<hr/> <hr/>	<code>\AtBeginShipoutInit</code>	By default <code>atbegshi</code> delayed its action until <code>\begin{document}</code> . This command was forcing it in an earlier place. With the new concept it does nothing.
<hr/> <hr/>	<code>\AtBeginShipout</code> <code>\AtBeginShipoutNext</code>	<code>\AtBeginShipout{&lt;code&gt;} ≡ \AddToHook{shipout/before}{&lt;code&gt;}</code> <code>\AtBeginShipoutNext{&lt;code&gt;} ≡ \AddToHookNext{shipout/before}{&lt;code&gt;}</code> This is equivalent to filling the <code>shipout/before</code> hook by either using <code>\AddToHook</code> or <code>\AddToHookNext</code> , respectively.
<hr/> <hr/>	<code>\AtBeginShipoutFirst</code> <code>\AtBeginShipoutDiscard</code>	The <code>atbegshi</code> names for <code>\AtBeginDvi</code> and <code>\DiscardShipoutBox</code> .

## 2.2 Emulating everyshi

The `everyshi` package is providing commands to run arbitrary code just before the shipout starts. One point of difference: in the new shipout hooks the page is available as `\ShipoutBox` for inspection of change, one should not manipulate box 255 directly inside `shipout/before`, so old code doing this would change to use `\ShipoutBox` instead of 255 or `\@cclv`.

<hr/> <hr/>	<code>\EveryShipout</code>	<code>\EveryShipout{&lt;code&gt;} ≡ \AddToHook{shipout/before}{&lt;code&gt;}</code>
<hr/> <hr/>	<code>\AtNextShipout</code>	<code>\AtNextShipout{&lt;code&gt;} ≡ \AddToHookNext{shipout/before}{&lt;code&gt;}</code>

However, most use cases for `everyshi` are attempts to put some picture or text into the background or foreground of the page and that can be done today simply by using the `shipout/background` and `shipout/foreground` hooks without any need to coding.

## 2.3 Emulating atenddvi

The `atenddvi` package implemented only a single command: `\AtEndDvi` and that is now available out of the box so the emulation makes the package a no-op.

## 2.4 Emulating everypage

This package patched the original `\@begindvi` hook and replaced it with its own version. Its functionality is now covered by the hooks offered by the kernel so that there is no need for such patching any longer.

<hr/> <hr/>	<code>\AddEverypageHook</code>	<code>\AddEverypageHook{&lt;code&gt;} ≡</code> <code>\AddToHook{shipout/background}{\put(1in,-1in){&lt;code&gt;}}</code> <code>\AddEverypageHook</code> is adding something into the background of every page at a position of 1in to the right and 1in down from the top left corner of the page. By using the kernel hook directly you can put your material directly to the right place, i.e., use other coordinates in the <code>\put</code> statement above.
<hr/> <hr/>	<code>\AddThispageHook</code>	<code>\AddThispageHook{&lt;code&gt;} ≡</code> <code>\AddToHookNext{shipout/background}{\put(1in,-1in){&lt;code&gt;}}</code> The <code>\AddThispageHook</code> wrapper is similar but uses <code>\AddToHookNext</code> .

### 3 The Implementation

1 `<@@=shipout>`

At the moment the whole module rolls back in one go, but if we make any modifications in later releases this will then need splitting.

```
2 <*2ekernel | latexrelease>
3 <latexrelease>\IncludeInRelease{2020/10/01}%
4 <latexrelease>          {\shipout}{Hook management (shipout)}}%
5 \ExplSyntaxOn
```

#### 3.1 Debugging

`\g__shipout_debug_bool` Holds the current debugging state.

```
6 \bool_new:N \g__shipout_debug_bool
```

*(End of definition for `\g__shipout_debug_bool`.)*

`\shipout_debug_on:` Turns debugging on and off by redefining `\__shipout_debug:n`.

```
\shipout_debug_off:
\__shipout_debug:n
\__shipout_debug_gset:
7 \cs_new_eq:NN \__shipout_debug:n \use_none:n
8 \cs_new_protected:Npn \shipout_debug_on:
9   {
10     \bool_gset_true:N \g__shipout_debug_bool
11     \__shipout_debug_gset:
12   }
13 \cs_new_protected:Npn \shipout_debug_off:
14   {
15     \bool_gset_false:N \g__shipout_debug_bool
16     \__shipout_debug_gset:
17   }
18 \cs_new_protected:Npn \__shipout_debug_gset:
19   {
20     \cs_gset_protected:Npx \__shipout_debug:n ##1
21     { \bool_if:NT \g__shipout_debug_bool {##1} }
22   }
```

*(End of definition for `\shipout_debug_on:` and others. These functions are documented on page 1144.)*

`\ShipoutBox` The box filled with the page to be shipped out (both L3 and L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> name).

```
\l_shipout_box
23 \box_new:N \l_shipout_box
24 \cs_set_eq:NN \ShipoutBox \l_shipout_box
```

*(End of definition for `\ShipoutBox` and `\l_shipout_box`. These functions are documented on page 1140.)*

`\l__shipout_raw_box` The `\RawShipout` gets its own box but it is internal as there is no hook manipulation for it.

```
25 \box_new:N \l__shipout_raw_box
```

*(End of definition for `\l__shipout_raw_box`.)*

`\__shipout_finalize_box:` For LuaTeX invoke the `pre_shipout_filter` callback.

```
26 \sys_if_engine luatex:TF
27 {
28   \newprotectedluacmd \__shipout_finalize_box:
29   \exp_args:Nx \everyjob {
30     \exp_not:V \everyjob
31     \exp_not:N \lua_now:n {
32       luatexbase.create_callback('pre_shipout_filter', 'list')
33       local~call, getbox, setbox = luatexbase.call_callback, tex.getbox, tex.setbox~
34       lua.get_functions_table()[\the \allocationnumber] = function()
35         local~head = getbox(\the \l_shipout_box)
36         local~result = call('pre_shipout_filter', head)
37         if~not (result == head) then~
38           setbox(\the \l_shipout_box, result~or~nil)
39         end~
40       end
41     }
42   }
43 } {
44   \cs_set_eq:NN \__shipout_finalize_box: \scan_stop:
45 }
```

*(End of definition for \\_\_shipout\_finalize\_box:.)*

`\__shipout_execute:` This is going to be the code run by `\shipout`. The code follows closely the ideas from `atbegshi`, so not documenting that here for now.

```
46 \cs_set_protected:Npn \__shipout_execute: {
47   \tl_set:Nx \l__shipout_group_level_tl
48   { \int_value:w \tex_currentgrouplevel:D }
49   \tex_afterassignment:D \__shipout_execute_test_level:
50   \tex_setbox:D \l_shipout_box
51 }
```

*(End of definition for \\_\_shipout\_execute:.)*

**\shipout** Overloading the `\shipout` primitive:

```
52 \cs_gset_eq:NN \shipout \__shipout_execute:
```

*(End of definition for \shipout. This function is documented on page 1139.)*

`\l__shipout_group_level_tl` Helper token list to record the group level at which `\__shipout_execute:` is encountered.

```
53 \tl_new:N \l__shipout_group_level_tl
```

*(End of definition for \l\_\_shipout\_group\_level\_tl.)*

`\__shipout_execute_test_level:` If the group level has changed then we are still constructing `\l_shipout_box` and to continue we need to wait until the current group has finished, hence the `\tex_aftergroup:D`.

```
54 \cs_new:Npn \__shipout_execute_test_level: {
55   \int_compare:nNnT
56   \l__shipout_group_level_tl < \tex_currentgrouplevel:D
57   \tex_aftergroup:D \__shipout_execute_cont:
58 }
```

*(End of definition for \\_\_shipout\_execute\_test\_level:.)*

`\__shipout_execute_cont:` This does the actual shipout running several hooks as part of it. The code for them is passed as argument #2 to #4 to `\__shipout_execute_main_cont:Nnnn`; the first argument is the box to be shipped out.

```

59 \cs_new:Npn \__shipout_execute_cont: {
60   \__shipout_execute_main_cont:Nnnn
61   \l_shipout_box
62   { \hook_use:n {shipout/before} }
63   { \hook_if_empty:nF {shipout/foreground}
64     { \__shipout_add_foreground_picture:n
65       { \hook_use:n {shipout/foreground} } } }

```

If the user hook for the background (`shipout/background`) has no code, there might still code in the kernel hook so we need to test for this too. We only test for the `\@kernel@before@shipout@background` though. If the `\@kernel@after@shipout@background` needs executing even if the user hook is empty then we can add another test (or the kernel could put something into the before hook).

```

66   \bool_lazy_and:nnF
67   { \hook_if_empty_p:n {shipout/background} }
68   { \tl_if_empty_p:N \@kernel@before@shipout@background }
69   { \__shipout_add_background_picture:n
70     { \@kernel@before@shipout@background
71       \hook_use:n {shipout/background}
72       \@kernel@after@shipout@background }
73   }
74 }
75 { \hook_use:n {shipout/after} }
76 }

```

(End of definition for `\__shipout_execute_cont:`)

`\_shipout_execute_main_cont:Nnnn` When we have reached this point the shipout box has been processed and is available in `\l_shipout_box` and ready for real ship out (unless it gets discarded during the process).

The three arguments hold hook code that is executed just before the actual shipout (#1), within the shipout adding background and foreground material (#2) and after the shipout has happened (#3). These are passed as arguments because the same code without those hooks is also used when doing a “raw” shipout implemented by `\RawShipout`. The only hook that is always executed is that for the very last page, i.e., `shipout/lastpage`.

First we quickly check if it is void (can’t happen in the standard L<sup>A</sup>T<sub>E</sub>X output routine but `\shipout` might be called from a package that has some special processing logic). If it is void we aren’t shipping anything out and processing ends.<sup>60</sup>

```

77 \cs_new:Npn \__shipout_execute_main_cont:Nnnn #1#2#3#4 {
78   \box_if_empty:NTF #1
79   { \@latex@warning@no@line{ Ignoring~ void~ shipout~ box } }
80   {

```

Otherwise we assume that we will ship something and prepare for final adjustments (in particular setting the state of `\protect` while we are running the hook code). We also save the current `\protect` state to restore it later.

```

81 %       \bool_gset_false:N \g__shipout_discard_bool % setting this would disable
82                                     % \DiscardShipoutBox on doc-level

```

<sup>60</sup>In that case we don’t reset the deadcycles, that would be up to the OR processing logic to do.

```

83      \cs_set_eq:NN \__shipout_saved_protect: \protect
84      \set@typeset@protect

```

We also store the current shipout box dimension in registers, so that they can be used in the hook code.<sup>61</sup>

```

85      \__shipout_get_box_size:N #1

```

Then we execute the `shipout/before` hook (or nothing in case of `\RawShipout`).

```

86      #2

```

In `\g_shipout_totalpages_int` we count all shipout attempts so we increment that counter already here (the other one is incremented later when we know for sure that we do a `\shipout`).

We increment it after running the above hook so that the values for `\g_shipout_totalpages_int` and `\g_shipout_readonly_int` are in sync while the hook is executed (in the case that `totalpages` isn't manually altered or through discarding pages that is).

```

87      \int_gincr:N \g_shipout_totalpages_int

```

The above hook might contain code that requests the page to be discarded so we now test for it.

```

88      \bool_if:NTF \g__shipout_discard_bool
89      { \@latex@info@no@line{Completed~ page~ discarded}
90      \bool_gset_false:N \g__shipout_discard_bool

```

As we are discarding the page box and not shipping anything out, we need to do some house cleaning and reset T<sub>E</sub>X's deadcycles so that it doesn't complain about too many calls to the OR without any shipout.

```

91      \tex_deadcycles:D \c_zero_int

```

*Todo: In atbegshi the box was dropped but is that actually needed? Or the resetting of \protect to its kernel value?*

```

92 %      \group_begin:
93 %      \box_set_eq_drop:NN #1 #1
94 %      \group_end:
95 %      \cs_set_eq:NN \protect \exp_not:N
96      }

```

Even if there was no explicit request to discard the box it is possible that the code for the hook `shipout/before` has voided the box (by mistake or deliberately). We therefore test once more but this time make it a warning, because the best practice way is to use the request mechanism.

```

97      { \box_if_empty:NTF #1
98      { \@latex@warning@no@line { Ignoring~ void~ shipout~ box.
99      \MessageBreak The~ shipout~ box~ was~ voided~ by~ hook~ code }
100      }

```

Finally, if the box is still non-empty we are nearly ready to ship it out. First we increment the total page counter so that we can later test if we have reached the final page according to our available information.<sup>62</sup>

```

101      {

```

---

<sup>61</sup>This is not really necessary as the code could access them via `\box_ht:N`, etc., but it is perhaps convenient.

<sup>62</sup>Doing that earlier would be wrong because we might end up with the last page counted but discard and then we have no place to add the final objects into the output file.

```

102         \int_gincr:N \g_shipout_readonly_int
103         \__shipout_debug:n {
104             \typeout{Absolute~ page~ =~ \int_use:N \g_shipout_readonly_int
105                 \space (target:~ \@abspage@last)}
106         }

```

Then we store the box sizes again (as they may have changed) and then look at the hooks `shipout/foreground` and `shipout/background`. If either or both are non-empty we add a `picture` environment to the box (in the foreground and/or in the background) and execute the hook code inside that environment.

```

107         \__shipout_get_box_size:N #1

```

The first hook we run is the `shipout/firstpage` hook. This is only done once, then the `\__shipout_run_firstpage_hook:` command redefines itself to do nothing. If the hook contains `\specials` for integration at the top of the page they will be temporarily stored in a safe place and added later with `\__shipout_add_firstpage_specials:`.

```

108         \__shipout_run_firstpage_hook:

```

Run the hooks for background and foreground or, if this is called by `\RawShipout`, copy the box `\l__shipout_raw_box` to `\l_shipout_box` so that firstpage and lastpage material gets added if necessary (that is always done to `\l_shipout_box`).

```

109         #3

```

We then run `\__shipout_add_firstpage_specials:` that adds the content of the hook `shipout/firstpage` to the start of the first page (if non-empty). It is then redefined to do nothing on later pages.

```

110         \__shipout_add_firstpage_specials:

```

Then we check if we have to add the `shipout/lastpage` hook or the corresponding kernel hook because we have reached the last page. This test will be false for all but one (and hopefully the correct) page.

```

111         \int_compare:nNnT \@abspage@last = \g_shipout_readonly_int
112         { \bool_lazy_and:nnF
113             { \hook_if_empty_p:n {shipout/lastpage} }
114             { \tl_if_empty_p:N \@kernel@after@shipout@lastpage }
115             { \__shipout_debug:n { \typeout{Executing~ lastpage~ hook~
116                 on~ page~ \int_use:N \g_shipout_readonly_int } }
117                 \__shipout_add_foreground_box:n
118                 { \UseHook{shipout/lastpage}
119                     \@kernel@after@shipout@lastpage }

```

We record that we have handled the `shipout/lastpage` hook but only if we really did.

```

120         \bool_gset_true:N \g__shipout_lastpage_handled_bool
121     }
122 }

```

```

123         \hook_use:n {shipout}
124         \__shipout_finalize_box:

```

Finally we run the actual `TeX` primitive for `shipout`. As that will expand delayed `\write` statements inside the page in which protected commands should not expand we first change `\protect` to the appropriate definition for that case.

```

125         \cs_set_eq:NN \protect \exp_not:N
126         \tex_shipout:D \box_use:N \l_shipout_box

```

The `\l_shipout_box` may contain the firstpage material if this was the very first shipout. That makes it unsuitable for reuse in another shipout, so as a safety measure the next command resets `\l_shipout_box` to its earlier state if that is necessary. On later pages this is then a no-op.

```
127             \__shipout_drop_firstpage_specials:
```

The `shipout/after` hook (if in #4) needs to run with `\protected` commands again being executed, because that hook will “typeset” material added at the top of the next page.

```
128             \set@typeset@protect
129             #4
130         }
131     }
```

Restore the value of `\protect` in case `\shipout` is called outside of the output routine (where it is automatically restored because of the implicit group).

```
132     \cs_set_eq:NN \protect \__shipout_saved_protect:
133 }
134 }
```

*(End of definition for \\_\_shipout\_execute\_main\_cont:Nnnn.)*

`\__shipout_execute_raw:` This implements the “raw” shipout which bypasses the before, foreground, background and after hooks. It follows the same pattern than `\__shipout_execute_raw:` except that it finally calls `\__shipout_execute_main_cont:Nnnn` with three empty arguments. instead of the hook code.

```
135 \cs_set_protected:Npn \__shipout_execute_raw: {
136     \tl_set:Nx \l__shipout_group_level_tl
137     { \int_value:w \tex_currentgrouplevel:D }
138     \tex_afterassignment:D \__shipout_execute_test_level_raw:
139     \tex_setbox:D \l__shipout_raw_box
140 }

141 \cs_new:Npn \__shipout_execute_test_level_raw: {
142     \int_compare:nNnT
143     \l__shipout_group_level_tl < \tex_currentgrouplevel:D
144     \tex_aftergroup:D \__shipout_execute_nohooks_cont:
145 }
```

Well, not totally empty arguments, we add some debugging if we are actually doing a shipout.

```
146 \cs_new:Npn \__shipout_execute_nohooks_cont: {
147     \__shipout_execute_main_cont:Nnnn \l__shipout_raw_box
148     {} { \__shipout_debug:n{ \typeout{Doing~ raw~ shipout~ ...} } }
149     \box_set_eq:NN \l_shipout_box \l__shipout_raw_box } {}
150 }
```

*(End of definition for \\_\_shipout\_execute\_raw: and \\_\_shipout\_execute\_test\_level\_raw:.)*

**\RawShipout** The interface name for raw shipout.

```
151 \cs_gset_eq:NN \RawShipout \__shipout_execute_raw:
```

*(End of definition for \RawShipout. This function is documented on page 1139.)*

`\__shipout_saved_protect:` Remember the current `\protect` state.

```
152 \cs_new_eq:NN \__shipout_saved_protect: \protect
```

(End of definition for `\_shipout_saved_protect:`.)

```

shipout/before Declaring all hooks for the shipout code.
      shipout
shipout/after 153 \hook_new:n{shipout/before}
      shipout 154 \hook_new:n{shipout}
shipout/foreground 155 \hook_new:n{shipout/after}
shipout/background 156 \hook_new:n{shipout/foreground}
shipout/firstpage 157 \hook_new:n{shipout/background}
shipout/lastpage 158 \hook_new:n{shipout/firstpage}
               159 \hook_new:n{shipout/lastpage}

```

(End of definition for `shipout/before` and others. These functions are documented on page 1140.)

```

\@kernel@after@shipout@lastpage And here are the internal kernel hooks going before or after the public ones where needed.
\@kernel@before@shipout@background
\@kernel@after@shipout@background 160 \let\@kernel@after@shipout@lastpage\@empty
                                   161 \let\@kernel@before@shipout@background\@empty
                                   162 \let\@kernel@after@shipout@background\@empty

```

(End of definition for `\@kernel@after@shipout@lastpage`, `\@kernel@before@shipout@background`, and `\@kernel@after@shipout@background`.)

```

\_shipout_run_firstpage_hook: There are three commands to handle the shipout/firstpage hook: \_shipout_run_
firstpage_hook:, \_shipout_add_firstpage_specials: and \_shipout_drop_
firstpage_specials:.

```

That hook is supposed to contain `\specials` and similar material to be placed at the very beginning of the output page and so it needs careful placing to avoid that anything else gets in front of it. And this means we have to wait with this until other hooks such as `shipout/background` have added their bits. It is also important that such `\specials` show up only on the very first page, so if this page gets saved before `\shipout` for later reuse, we have to make sure that they aren't in the saved version.

In addition the hook may also contain code to be executed “first”, e.g., visible from code in `shipout/background` and this conflicts with adding the `\specials` late.

Therefore the processing is split into different parts: `\_shipout_run_firstpage_hook:` is done early and checks if there is any material in the hook.

```

163 \cs_new:Npn \_shipout_run_firstpage_hook: {
164   \hook_if_empty:nTF {shipout/firstpage}

```

If not then we define the other two commands to do nothing.

```

165   {
166     \cs_gset_eq:NN \_shipout_add_firstpage_specials: \prg_do_nothing:
167     \cs_gset_eq:NN \_shipout_drop_firstpage_specials: \prg_do_nothing:
168   }

```

If there is material we execute inside a box, which means any `\special` will end up in that box and any other code is executed and can have side effects (as long as they are global).

```

169   {
170     \hbox_set:Nn \l__shipout_firstpage_box { \UseHook{shipout/firstpage} }
171   }

```

Once we are here we change the definition to do nothing next time and we also change the command used to implement `\AtBeginDvi` to become a warning and not add further material to a hook that is never used again.

```

172 \cs_gset_eq:NN \__shipout_run_firstpage_hook: \prg_do_nothing:
173 \cs_gset:Npn \__shipout_add_firstpage_material:Nn ##1 ##2 {
174   \@latex@warning{ First~ page~ is~ already~ shipped~ out,~ ignoring
175                 \MessageBreak \string##1 }
176 }
177 }

```

*(End of definition for \\_\_shipout\_run\_firstpage\_hook:.)*

`\__shipout_add_firstpage_specials:` The `\__shipout_add_firstpage_specials:` then adds the `\specials` stored in `\l__shipout_firstpage_box` to the page to be shipped out when the time is ready. Note that if there was no material in the `shipout/firstpage` hook then this command gets redefined to do nothing. But for most documents there is something, e.g., some PostScript header, or some metadata declaration, etc. so by default we assume there is something to do.

```

178 \cs_new:Npn \__shipout_add_firstpage_specials: {

```

First we make a copy of the `\l_shipout_box` that we can restore it later on.

```

179 \box_set_eq:NN \l__shipout_raw_box \l_shipout_box

```

Adding something to the beginning means adding it to the background as that layer is done first in the output.

```

180 \__shipout_add_background_box:n { \hbox_unpack_drop:N \l__shipout_firstpage_box }

```

After the actual shipout `\__shipout_drop_firstpage_specials:` is run to restore the earlier content of `\l_shipout_box` and then redefines itself again to do nothing.

As a final act we change the definition to do nothing next time.

```

181 \cs_gset_eq:NN \__shipout_add_firstpage_specials: \prg_do_nothing:
182 }

```

The `\__shipout_drop_firstpage_specials:` is run after the shipout has occurred but before the `shipout/afterpage` hook is executed. That is the point where we have to restore the `\ShipoutBox` to its state without the `shipout/firstpage` material.

```

183 \cs_new:Npn \__shipout_drop_firstpage_specials: {
184   \box_set_eq:NN \l_shipout_box \l__shipout_raw_box

```

If there was no such material then `\__shipout_run_firstpage_hook:` will have changed the definition to a no-op already. Otherwise this is what we do here.

```

185 \cs_gset_eq:NN \__shipout_drop_firstpage_specials: \prg_do_nothing:
186 }

```

*(End of definition for \\_\_shipout\_add\_firstpage\_specials: and  
\\_\_shipout\_drop\_firstpage\_specials:.)*

`\l__shipout_firstpage_box` The box to hold any firstpage `\specials`.

```

187 \box_new:N \l__shipout_firstpage_box

```

*(End of definition for \l\_\_shipout\_firstpage\_box.)*

`\g__shipout_lastpage_handled_bool` A boolean to signal if we have already handled the `shipout/lastpage` hook.

```

188 \bool_new:N \g__shipout_lastpage_handled_bool

```

*(End of definition for \g\_\_shipout\_lastpage\_handled\_bool.)*

`\_shipout_add_firstpage_material:Nn` This command adds material to the `shipout/firstpage` hook. It is used in `\AtBeginDvi`, etc. The first argument is the command through which it is called. Initially this is ignored but once we are passed the first page it can be used to generate a warning message mentioning the right user command.

```

189 \cs_new:Npn \_shipout_add_firstpage_material:Nn #1#2 {
190   \AddToHook{shipout/firstpage}{#2}
191 }

```

(End of definition for `\_shipout_add_firstpage_material:Nn`.)

`\_shipout_get_box_size:N` Store the box dimensions in dimen registers.

*Todo: This could/should perhaps be generalized to set height depth and width given an arbitrary box.*

```

192 \cs_new:Npn \_shipout_get_box_size:N #1 {
193   \dim_set:Nn \l_shipout_box_ht_dim { \box_ht:N #1 }
194   \dim_set:Nn \l_shipout_box_dp_dim { \box_dp:N #1 }
195   \dim_set:Nn \l_shipout_box_wd_dim { \box_wd:N #1 }
196   \dim_set:Nn \l_shipout_box_ht_plus_dp_dim
197     { \l_shipout_box_ht_dim + \l_shipout_box_dp_dim }
198 }

```

(End of definition for `\_shipout_get_box_size:N`.)

`\l_shipout_box_ht_dim` And here are the variables set by `\_shipout_get_box_size:N`.

`\l_shipout_box_dp_dim` 199 `\dim_new:N \l_shipout_box_ht_dim`

`\l_shipout_box_wd_dim` 200 `\dim_new:N \l_shipout_box_dp_dim`

`\l_shipout_box_ht_plus_dp_dim` 201 `\dim_new:N \l_shipout_box_wd_dim`

202 `\dim_new:N \l_shipout_box_ht_plus_dp_dim`

(End of definition for `\l_shipout_box_ht_dim` and others. These functions are documented on page 1140.)

`\g_shipout_discard_bool` Indicate whether or not the current page box should be discarded

```

203 \bool_new:N \g_shipout_discard_bool

```

(End of definition for `\g_shipout_discard_bool`.)

`\l_shipout_tmp_box` We need a box for the background and foreground material and a token register to  
`\l_shipout_saved_badness_tl` remember badness settings as we disable them during the buildup below.

```

204 \box_new:N \l_shipout_tmp_box
205 \tl_new:N \l_shipout_saved_badness_tl

```

(End of definition for `\l_shipout_tmp_box` and `\l_shipout_saved_badness_tl`.)

`\_shipout_add_background_box:n` In standard L<sup>A</sup>T<sub>E</sub>X the shipout box is always a `\vbox` but here we allow for other usage as well, in case some package has its own output routine.

```

206 \cs_new:Npn \_shipout_add_background_box:n #1
207 { \_shipout_get_box_size:N \l_shipout_box

```

But we start testing for a vertical box as that should be the normal case.

```

208   \box_if_vertical:NTF \l_shipout_box
209   {

```

Save current values of `\vfuzz` and `\vbadness` then change them to allow box manipulations without warnings.

```

210      \tl_set:Nx \l__shipout_saved_badness_tl
211      { \vfuzz=\the\vfuzz\relax
212        \vbadness=\the\vbadness\relax }
213      \vfuzz=\c_max_dim
214      \vbadness=\c_max_int

```

Then we reconstruct `\l_shipout_box` ...

```

215      \vbox_set_to_ht:Nnn \l_shipout_box \l_shipout_box_ht_plus_dp_dim
216      {

```

... the material in `#1` is placed into a horizontal box with zero dimensions.

```

217          \hbox_set:Nn \l__shipout_tmp_box
218          { \l__shipout_saved_badness_tl #1 }
219          \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
220          \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
221          \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim

```

The we typeset that box followed by whatever was in `\l_shipout_box` before (unpacked).

```

222          \skip_zero:N \baselineskip
223          \skip_zero:N \lineskip
224          \skip_zero:N \lineskiplimit
225          \box_use:N \l__shipout_tmp_box
226          \vbox_unpack:N \l_shipout_box

```

The `\kern` ensures that the box has no depth which is afterwards explicitly corrected.

```

227          \kern \c_zero_dim
228      }
229      \box_set_ht:Nn \l_shipout_box \l_shipout_box_ht_dim
230      \box_set_dp:Nn \l_shipout_box \l_shipout_box_dp_dim

```

*Todo: The whole boxing maneuver looks a bit like overkill to me, but for the moment I leave.*

```

231      \l__shipout_saved_badness_tl
232    }
233    {

```

A horizontal box is handled in a similar way. The last case would be a void box in which case we do nothing hence the missing F branch.

```

234      \box_if_horizontal:NT \l_shipout_box
235      {
236          \tl_set:Nx \l__shipout_saved_badness_tl
237          { \hfuzz=\the\hfuzz\relax
238            \hbadness=\the\hbadness\relax }
239          \hfuzz=\c_max_dim
240          \hbadness=\c_max_int
241          \hbox_set_to_wd:Nnn \l_shipout_box \l_shipout_box_wd_dim
242          {
243              \hbox_set:Nn \l__shipout_tmp_box
244              { \l__shipout_saved_badness_tl #1 }
245              \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
246              \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
247              \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim

```

```

248             \box_move_up:nn
249             \l_shipout_box_ht_dim
250             { \box_use:N \l__shipout_tmp_box }
251             \hbox_unpack:N \l_shipout_box
252         }
253         \l__shipout_saved_badness_tl
254     }
255 }
256 }

```

(End of definition for \\_\_shipout\_add\_background\_box:n.)

\\_\_shipout\_add\_foreground\_box:n Foreground boxes are done in the same way, only the order and placement of boxes has to be done differently.

```

257 \cs_new:Npn \__shipout_add_foreground_box:n #1
258 {
259     \box_if_vertical:NTF \l_shipout_box
260     {
261         \tl_set:Nx \l__shipout_saved_badness_tl
262         { \vfuzz=\the\vfuzz\relax
263           \vbadness=\the\vbadness\relax }
264         \vfuzz=\c_max_dim
265         \vbadness=\c_max_int
266         \vbox_set_to_ht:Nnn \l_shipout_box \l_shipout_box_ht_plus_dp_dim
267         {
268             \hbox_set:Nn \l__shipout_tmp_box
269             { \l__shipout_saved_badness_tl #1 }
270             \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
271             \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
272             \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
273             \skip_zero:N \baselineskip
274             \skip_zero:N \lineskip
275             \skip_zero:N \lineskiplimit
276             \vbox_unpack:N \l_shipout_box
277             \kern -\l_shipout_box_ht_plus_dp_dim
278             \box_use:N \l__shipout_tmp_box
279             \kern \l_shipout_box_ht_plus_dp_dim
280         }
281         \l__shipout_saved_badness_tl
282         \box_set_ht:Nn \l_shipout_box \l_shipout_box_ht_dim
283         \box_set_dp:Nn \l_shipout_box \l_shipout_box_dp_dim
284     }
285     {
286         \box_if_horizontal:NT \l_shipout_box
287         {
288             \tl_set:Nx \l__shipout_saved_badness_tl
289             { \hfuzz=\the\hfuzz\relax
290               \hbadness=\the\hbadness\relax }
291             \hfuzz=\c_max_dim
292             \hbadness=\c_max_int
293             \hbox_set_to_wd:Nnn \l_shipout_box \l_shipout_box_wd_dim
294             {
295                 \hbox_unpack:N \l_shipout_box
296                 \kern -\box_wd:N \l_shipout_box

```

```

297         \hbox_set:Nn \l__shipout_tmp_box
298         { \l__shipout_saved_badness_tl #1 }
299         \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
300         \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
301         \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
302         \box_move_up:nn { \box_ht:N \l__shipout_box }
303         { \box_use:N \l__shipout_tmp_box }
304         \kern \box_wd:N \l__shipout_box
305     }%
306     \l__shipout_saved_badness_tl
307 }
308 }
309 }

```

(End of definition for `\__shipout_add_foreground_box:n`.)

`\__shipout_init_page_origins:` Two constants holding the offset of the top-left with respect to the media box.  
`\c__shipout_horigin_tl` Setting the constants this way is courtesy of Bruno.  
`\c__shipout_vorigin_tl` We delay setting the constants to the last possible place as there might be updates in the preamble or even in the `begindocument` hook that affects their setup.

```

310 \cs_new:Npn \__shipout_init_page_origins: {
311   \tl_const:Nx \c__shipout_horigin_tl
312   {
313     \cs_if_exist_use:NTF \pdfvariable { horigin }
314     { \cs_if_exist_use:NF \pdfhorigin { 1in } }
315   }
316   \tl_const:Nx \c__shipout_vorigin_tl
317   {
318     \cs_if_exist_use:NTF \pdfvariable { vorigin }
319     { \cs_if_exist_use:NF \pdfvorigin { 1in } }
320   }

```

After the constants have been set there is no need to execute this command again, in fact it would raise an error, so we redefine it to do nothing.

```

321   \cs_gset_eq:NN \__shipout_init_page_origins: \prg_do_nothing:
322 }

```

(End of definition for `\__shipout_init_page_origins:`, `\c__shipout_horigin_tl`, and `\c__shipout_vorigin_tl`.)

`\__shipout_picture_overlay:n` Put the argument into a `picture` environment that doesn't take up any size and uses `1pt` for `\unitlength`.

*Todo: Could perhaps be generalized as it might be useful elsewhere. For now it is not.*

```

323 \cs_new:Npn \__shipout_picture_overlay:n #1 {

```

The very first time this is executed we have to initialize (and freeze) the origins.

```

324   \__shipout_init_page_origins:
325   \kern -\c__shipout_horigin_tl \scan_stop:
326   \vbox_to_zero:n {
327     \kern -\c__shipout_vorigin_tl \scan_stop:
328     \unitlength 1pt \scan_stop:

```

This mimics a simple zero-sized picture environment. The `\hss` is need in case there is horizontal material (without using `\put` with a positive width).

```

329     \hbox_set_to_wd:Nnn \l__shipout_tmp_box \c_zero_dim
330                     { \ignorespaces #1 \hss }
331     \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
332     \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
333     \box_use:N \l__shipout_tmp_box
334     \tex_vss:D
335   }
336 }

```

(End of definition for `\__shipout_picture_overlay:n`.)

`\__shipout_add_background_picture:n` Put a `picture` env in the background of the shipout box with its reference point in the top-left corner.

```

337 \cs_new:Npn \__shipout_add_background_picture:n #1 {
338   \__shipout_add_background_box:n { \__shipout_picture_overlay:n {#1} }
339 }

```

(End of definition for `\__shipout_add_background_picture:n`.)

`\__shipout_add_foreground_picture:n` Put a `picture` env in the foreground of the shipout box with its reference point in the top-left corner.

```

340 \cs_new:Npn \__shipout_add_foreground_picture:n #1 {
341   \__shipout_add_foreground_box:n { \__shipout_picture_overlay:n {#1} }
342 }

```

(End of definition for `\__shipout_add_foreground_picture:n`.)

**`\shipout_discard:`** Request that the next shipout box should be discarded. At the moment this is just setting a boolean, but we may want to augment this behavior that the position of the call is taken into account (in case  $\text{\LaTeX}$  looks ahead and is not using the position for on the next page).

```

343 \cs_new_protected:Npn \shipout_discard: {
344   \bool_gset_true:N \g__shipout_discard_bool
345 }

```

(End of definition for `\shipout_discard:`. This function is documented on page 1143.)

## 3.2 Handling the end of job hook

At the moment this is partly solved by using the existing hooks. But rather than putting the code into these hooks it should be moved to the right place directly as we shouldn't prefill hooks with material unless it needs to interact with other code.

**`\g_shipout_readonly_int`** **`\ReadonlyShipoutCounter`** We count every shipout activity that makes a page (but not those that are discarded) in order to know how many pages got produced.

```

346 \int_new:N \g_shipout_readonly_int

```

For  $\text{\LaTeX} 2_\epsilon$  it is available as a command (i.e., a  $\text{\TeX}$  counter only).

```

347 \cs_new_eq:NN \ReadonlyShipoutCounter \g_shipout_readonly_int

```

(End of definition for `\g_shipout_readonly_int` and `\ReadonlyShipoutCounter`. These functions are documented on page 1144.)

`\g_shipout_totalpages_int` We count every shipout attempt (even those that are discarded) in this counter. It is not used in the code but may get used in user code.

```
348 \int_new:N \g_shipout_totalpages_int
```

For L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> this is offered as a L<sup>A</sup>T<sub>E</sub>X counter so can be easily typeset inside the output routine to display things like “\thepage/\thetotalpages”, etc.

```
349 \cs_new_eq:NN \c@totalpages \g_shipout_totalpages_int
```

```
350 \cs_new:Npn \thetotalpages { \arabic{totalpages} }
```

*(End of definition for \g\_shipout\_totalpages\_int and \c@totalpages. These functions are documented on page 1144.)*

`\@abspage@last` In `\@abspage@last` record the number of pages from the last run. This is written to the .aux and this way made available to the next run. In case there is no .aux file or the statement is missing from it we initialize it with the largest possible number in T<sub>E</sub>X. We use this as the default because then we are inserting the `shipout/lastpage` on the last page (or after the last page) but not on page 1 for a multipage document.

```
351 \xdef\@abspage@last{\number\maxdimen}
```

*(End of definition for \@abspage@last.)*

`\enddocument` Instead of using the hooks `enddocument` and `enddocument/afterlastpage` we add this code to private kernel hooks to be 100% sure when it is executed and to avoid cluttering the hooks with data that is always there.

Inside `\enddocument` there is a `\clearpage`. Just before that we execute this code here. There is a good chance that we are on the last page. Therefore, if we don’t know the value from the last run, we assume that the current page is the right one. So we set `\@abspage@last` and as a result the next shipout will run the `shipout/lastpage` code. Of course, if there are floats that still need a placement this guess will be wrong but then rerunning the document will give us the correct value next time around.

```
\@kernel@after@enddocument 352 \g@addto@macro \@kernel@after@enddocument {
353   \int_compare:nNtT \@abspage@last = \maxdimen
354   {
```

We use L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> coding as `\@abspage@last` is not an L<sub>3</sub> name.

```
355   \xdef\@abspage@last{ \int_eval:n {\g_shipout_readonly_int + 1} }
356   }
357 }
```

After the last page has been shipped out, we force further `\write` calls to be always `\immediate` because we aren’t going to ship out any more pages. This goes before the `enddocument/afterlastpage` hook because that may contain such `\write` commands.

```
358 \g@addto@macro \@kernel@before@enddocument@afterlastpage {
359   \__shipout_force_immediate_writes:
360   % This is also the point where \__tag_lastpage_label: could be executed
361   % instead of going into enddocument/afterlastpage
362 }
```

Once the `\clearpage` has done its work inside `\enddocument` we know for sure how many pages this document has, so we record that in the .aux file for the next run.

```
363 \g@addto@macro \@kernel@after@enddocument@afterlastpage {
```

There is one special case: If no output is produced then there is no point in a) recording the number as 0 will never match the page number of a real page and b) adding an extra page to ran the `shipout/lastpage` is pointless as well (as it would remain forever). So we test for this and run the code only if there have been pages.

```
364 \int_compare:nNnF \g_shipout_readonly_int = 0
365 {
```

This ends up in the `.aux` so we use L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> names here.

*Todo: This needs an interface for `\nofiles` in `expl3`, doesn't at the moment!*

```
366 \if@files
367 \iow_now:Nx \@auxout {
368 \gdef\string\@abspage@last {\int_use:N \g_shipout_readonly_int}}
369 \fi
```

But we may have guessed wrongly earlier and have run it too early or we still have to run the `shipout/lastpage` even though there is no page to place it into. If that is the case we make a trivial extra page and put it there. This temporary page will then vanish again on the next run but helps to keep pdf viewers happy. In either case we should put out an appropriate “rerun” warning.

```
370 \bool_if:NTF \g__shipout_lastpage_handled_bool
371 {
```

If the hook was already executed, we have to test if that total shipouts match the shipouts from last run (because that corresponds to the page it was executed). If not we output a warning.

```
372 \int_compare:nNnF \@abspage@last = \g_shipout_readonly_int
373 {
374 \@latex@warning@no@line{Hook~ 'shipout/lastpage'~ executed~
375 on~ wrong~ page~ (\@abspage@last\space not~
376 \int_use:N \g_shipout_readonly_int).\MessageBreak
377 Rerun~ to~ correct~ this}%
378 }
379 }
380 {
```

If the hook was not run, we need to add an extra page and place it there. However, making this extra page in case the hook is actually empty would be forcing a rerun without any reason, so we check that condition and also check if `\@kernel@after@shipout@lastpage` contains any code. If both are empty we omit the page generation.

```
381 \bool_lazy_and:nnF
382 { \hook_if_empty_p:n {shipout/lastpage} }
383 { \tl_if_empty_p:N \@kernel@after@shipout@lastpage }
384 {
385 \global\advance\c@page\@ne
386 \tex_shipout:D\vbox to\textheight
387 {
388 \hbox:n { \UseHook{shipout/lastpage}
389 \@kernel@after@shipout@lastpage }
390 }
```

This extra page could be totally empty except for the hook content, but to help the user understanding why it is there we put some text into it.

```
390 \__shipout_excuse_extra_page:
391 \null
392 }
```

At this point we also signal to L<sup>A</sup>T<sub>E</sub>X's endgame that a rerun is necessary so that an appropriate message can be shown on the terminal. We do this by simply defining a command used as a flag and tested in `\enddocument`.

```

393             \cs_gset_eq:NN \@extra@page@added \relax
394         }
395     }
396 }
397 }

```

*(End of definition for \enddocument and others.)*

```

\__shipout_excuse_extra_page: Say mea culpa ...
398 \cs_new:Npn \__shipout_excuse_extra_page: {
399     \vfil
400     \begin{center}
401         \bfseries Temporary~ page!
402     \end{center}
403     \LaTeX{}~ was~ unable~ to~ guess~ the~ total~ number~ of~ pages~
404     correctly.~ ~ As~ there~ was~ some~ unprocessed~ data~ that~
405     should~ have~ been~ added~ to~ the~ final~ page~ this~ extra~
406     page~ has~ been~ added~ to~ receive~ it.
407     \par
408     If~ you~ rerun~ the~ document~ (without~ altering~ it)~ this~
409     surplus~ page~ will~ go~ away,~ because~ \LaTeX{}~ now~ knows~
410     how~ many~ pages~ to~ expect~ for~ this~ document.
411     \vfil
412 }

```

*(End of definition for \\_\_shipout\_excuse\_extra\_page:.)*

**\PreviousTotalPages** In the preamble before the aux file was read `\PreviousTotalPages` is always zero.

```

\@kernel@before@begindocument 413 \def\PreviousTotalPages{0}

```

In the aux file there should be an update for `\@abspage@last` recording the number of pages from the previous run. If not that macro holds the value of `\maxdimen`. So we test for it and update `\PreviousTotalPages` if there was a real value. This should happen just before the `begindocument` hook is executed so that the value can be used inside that hook.

```

414 \g@addto@macro\@kernel@before@begindocument
415     {\ifnum\@abspage@last<\maxdimen
416         \xdef\PreviousTotalPages{\@abspage@last}\fi}

```

*(End of definition for \PreviousTotalPages and \@kernel@before@begindocument. These functions are documented on page 1144.)*

## 4 Legacy L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> interfaces

**\DiscardShipoutBox** Request that the next shipout box is to be discarded.

```

417 \cs_new_eq:NN \DiscardShipoutBox \shipout_discard:

```

*(End of definition for \DiscardShipoutBox. This function is documented on page 1143.)*

`\AtBeginDvi` If we roll forward from an earlier kernel `\AtBeginDvi` is defined so we better not use `\cs_new_protected:Npn` here.

```
418 \cs_set_protected:Npn \AtBeginDvi
419 { \__shipout_add_firstpage_material:Nn \AtBeginDvi }
```

(End of definition for `\AtBeginDvi`. This function is documented on page 1142.)

`\DebugShipoutsOn`  
`\DebugShipoutsOff`

```
420 \cs_new_eq:NN \DebugShipoutsOn \shipout_debug_on:
421 \cs_new_eq:NN \DebugShipoutsOff \shipout_debug_off:
```

(End of definition for `\DebugShipoutsOn` and `\DebugShipoutsOff`. These functions are documented on page 1144.)

## 5 Internal commands needed elsewhere

These internal commands use double and triple @ signs so we need to stop getting them translated to the module name.

```
422 <@@=>
```

```
\expl@@@shipout@add@firstpage@material@@Nn
\expl@@@shipout@add@background@box@@n
\expl@@@shipout@add@foreground@box@@n
\expl@@@shipout@add@background@picture@@n
\expl@@@shipout@add@foreground@picture@@n
```

Some internals needed elsewhere.

```
423 \cs_set_eq:NN \expl@@@shipout@add@firstpage@material@@Nn
424 \__shipout_add_firstpage_material:Nn
425 \cs_set_eq:NN \expl@@@shipout@add@background@box@@n
426 \__shipout_add_background_box:n
427 \cs_set_eq:NN \expl@@@shipout@add@foreground@box@@n
428 \__shipout_add_foreground_box:n
429 \cs_set_eq:NN \expl@@@shipout@add@background@picture@@n
430 \__shipout_add_background_picture:n
431 \cs_set_eq:NN \expl@@@shipout@add@foreground@picture@@n
432 \__shipout_add_foreground_picture:n
```

(End of definition for `\expl@@@shipout@add@firstpage@material@@Nn` and others.)

```
433 \ExplSyntaxOff
434 </2ekernel | latexrelease>
435 <latexrelease>\EndIncludeInRelease
```

Rolling back here doesn't undefine the interface commands as they may be used in packages without rollback functionality. So we just make them do nothing which may or may not work depending on the code usage.

```
436 <latexrelease>\IncludeInRelease{0000/00/00}%
437 <latexrelease> { \shipout } { Hook management (shipout) } %
438 <latexrelease>
```

If we roll forward then `\tex_shipout:D` may not be defined in which case `\shipout` does have it original definition and so we must not `\let` it to something else which is `\relax`!

```
439 <latexrelease>\ifcsname tex_shipout:D\endcsname
440 <latexrelease>\expandafter\let\expandafter\shipout
441 <latexrelease> \csname tex_shipout:D\endcsname
442 <latexrelease>\fi
```

```

443 <latexrelease>
444 <latexrelease>\let \RawShipout\@undefined
445 <latexrelease>\let \ShipoutBox\@undefined
446 <latexrelease>\let \ReadonlyShipoutCounter \@undefined
447 <latexrelease>\let \c@totalpages \@undefined
448 <latexrelease>\let \thetotalpages \@undefined
449 <latexrelease>
450 <latexrelease>\let \DiscardShipoutBox \@undefined
451 <latexrelease>\let \DebugShipoutsOn \@undefined
452 <latexrelease>\let \DebugShipoutsOff \@undefined
453 <latexrelease>
454 <latexrelease>\DeclareRobustCommand \AtBeginDvi [1]{%
455 <latexrelease> \global \setbox \@begindvibox
456 <latexrelease> \vbox{\unvbox \@begindvibox #1}%
457 <latexrelease>}
458 <latexrelease>
459 <latexrelease>\let \AtBeginShipout \@undefined
460 <latexrelease>\let \AtBeginShipoutNext \@undefined
461 <latexrelease>
462 <latexrelease>\let \AtBeginShipoutFirst \@undefined
463 <latexrelease>
464 <latexrelease>\let \ShipoutBoxHeight \@undefined
465 <latexrelease>\let \ShipoutBoxDepth \@undefined
466 <latexrelease>\let \ShipoutBoxWidth \@undefined
467 <latexrelease>

```

We do not undo a substitution when rolling back. As the file support gets undone the underlying data is no longer used (and sufficiently obscure that it should not interfere with existing commands) and properly removing it would mean we need to make the `\undeclare@...` and its support macros available in all earlier kernel releases which is pointless (and actually worse).

```

468 <latexrelease>
469 <latexrelease>\let \AtEndDvi \@undefined

```

We do not reenale a disabled package load when rolling back. As the file support gets undone the underlying data is no longer checked (and sufficiently obscure that it should not interfere with existing commands) and properly removing it would mean we need to make the `\reenable@package@load` command available in all earlier kernel releases which is pointless (and actually worse).

```

470 %\reenable@package@load{atenddvii}
471 <latexrelease>
472 <latexrelease>\EndIncludeInRelease
473 <*2ekernel>

```

`\_shipout_force_immediate_writes:` Change all writes to be immediate. To be used after the final page has been shipped out.

```

474 </2ekernel>
475 <*2ekernel | latexrelease>
476 <latexrelease>\IncludeInRelease{2025/06/01}%
477 <latexrelease> {\\_shipout_force_immediate_writes:}{Force immediate writes}%
478 \ExplSyntaxOn
479 \cs_new:Npn \\_shipout_force_immediate_writes: {

```

Need to check if any variants are manually defined and if so adjust them too — not done!

```
480 \cs_gset_eq:NN \iow_shipout:Nn \iow_now:Nn
481 \cs_gset_eq:NN \lua_shipout:n \lua_now:n
482 \cs_gset:Npn \write {\tex_immediate:D \tex_write:D}
```

As the writes will happen without a page break, reset the page number so they reference the last page.

```
483 \global\advance\c@page\m@ne
484 }
485 \ExplSyntaxOff
486 </2ekernel | latexrelease>
487 <latexrelease>\EndIncludeInRelease
488 <latexrelease>\IncludeInRelease{0000/00/00}%
489 <latexrelease> {\_shipout_force_immediate_writes:}{Force immediate writes}%
```

We want a definition for this even when doing rollback so that it can stay in the kernel hook without forcing a rollback there as well.

```
490 <latexrelease>\ExplSyntaxOn
491 <latexrelease> \cs_new_eq:NN \_shipout_force_immediate_writes: \prg_do_nothing:
492 <latexrelease>\ExplSyntaxOff
493 <latexrelease>\EndIncludeInRelease
494 <*2ekernel>
```

*(End of definition for \\_shipout\_force\_immediate\_writes:.)*

## 6 Package emulation for compatibility

### 6.1 Package atenddvi emulation

**\AtEndDvi** This package has only one public command, so simulating it is easy and actually sensible to provide as part of the kernel.

```
495 </2ekernel>
496 <*2ekernel | latexrelease>
497 <latexrelease>\IncludeInRelease{2020/10/01}%
498 <latexrelease> {\AtEndDvi}{atenddvi emulation}%
499 \ExplSyntaxOn
500 \cs_new_protected:Npn \AtEndDvi #1 {\AddToHook{shipout/lastpage}{#1}}
501 \ExplSyntaxOff
```

As the package is integrate we prevent loading (no need to roll that back):

```
502 \disable@package@load{atenddvi}
503 {\PackageWarning{atenddvi}
504 {Functionality of this package is already\MessageBreak
505 provided by LaTeX.\MessageBreak\MessageBreak
506 It is there no longer necessary to load it\MessageBreak
507 and you can safely remove it.\MessageBreak
508 Found on}}
509 </2ekernel | latexrelease>
```

```

510 <latexrelease>\EndIncludeInRelease
511 <latexrelease>\IncludeInRelease{0000/00/00}%
512 <latexrelease>{\AtEndDvi}{atendddvi emulation}%
513 <latexrelease>\let \AtEndDvi \@undefined
514 <latexrelease>\EndIncludeInRelease
515 <*2ekernel>

(End of definition for \AtEndDvi. This function is documented on page 1142.)

516 </2ekernel>

```

## 6.2 Package atbegshi emulation

```

517 <*atbegshi-ltx>
518 \ProvidesPackage{atbegshi-ltx}
519 [2021/01/10 v1.0c
520 Emulation of the original atbegshi^^Jpackage with kernel methods]

```

**\AtBeginShipoutBox**

```
521 \let \AtBeginShipoutBox \ShipoutBox
```

(End of definition for \AtBeginShipoutBox. This function is documented on page 1145.)

**\AtBeginShipoutInit**

Compatibility only, we aren't delaying ...

```
522 \let \AtBeginShipoutInit \@empty
```

(End of definition for \AtBeginShipoutInit. This function is documented on page 1146.)

**\AtBeginShipout**  
**\AtBeginShipoutNext**

Filling hooks

```

523 \protected\long\def\AtBeginShipout #1{\AddToHook{shipout/before}{#1}}
524 \protected\long\def\AtBeginShipoutNext #1{\AddToHookNext{shipout/before}{#1}}

```

(End of definition for \AtBeginShipout and \AtBeginShipoutNext. These functions are documented on page 1146.)

**\AtBeginShipoutFirst**

Slightly more complex as we need to know the name of the command under which the shipout/firstpage hook is filled.

```

525 \protected \def \AtBeginShipoutFirst
526 {\@expl@@@shipout@add@firstpage@material@@Nn \AtBeginShipoutFirst}

```

(End of definition for \AtBeginShipoutFirst. This function is documented on page 1146.)

**\AtBeginShipoutDiscard**

Just a different name.

```
527 \let \AtBeginShipoutDiscard \DiscardShipoutBox
```

(End of definition for \AtBeginShipoutDiscard. This function is documented on page 1146.)

**\AtBeginShipoutAddToBox**  
**\AtBeginShipoutAddToBoxForeground**  
**\AtBeginShipoutUpperLeft**  
**\AtBeginShipoutUpperLeftForeground**

We don't expose them.

```

528 \let \AtBeginShipoutAddToBox
529 \@expl@@@shipout@add@background@box@@n
530 \let \AtBeginShipoutAddToBoxForeground
531 \@expl@@@shipout@add@foreground@box@@n

532 \let \AtBeginShipoutUpperLeft
533 \@expl@@@shipout@add@background@picture@@n
534 \let \AtBeginShipoutUpperLeftForeground
535 \@expl@@@shipout@add@foreground@picture@@n

```

(End of definition for `\AtBeginShipoutAddToBox` and others. These functions are documented on page 1145.)

`\AtBeginShipoutOriginalShipout` This offers the raw `\shipout` primitive of the engine. A page shipped out with this is not counted by `\ReadonlyShipoutCounter` counter and thus the mechanism to place `\specials` at the very end of the output might fail, etc. It should therefore not be used in new applications but is only provided to allow running legacy code. For new code use the commands provided by the kernel instead.

```
536 \ExplSyntaxOn
537 \cs_new_eq:NN \AtBeginShipoutOriginalShipout \tex_shipout:D
```

(End of definition for `\AtBeginShipoutOriginalShipout`. This function is documented on page 1145.)

`\ShipoutBoxHeight` `\ShipoutBoxWidth` `\ShipoutBoxDepth` This is somewhat different from the original in `atbegshi` where `\ShipoutBoxHeight` etc. only holds the `\the\ht<box>` value. This may have some implications in some use cases and if that is a problem then it might need changing.

```
538 \cs_new:Npn \ShipoutBoxHeight { \dim_use:N \l_shipout_box_ht_dim }
539 \cs_new:Npn \ShipoutBoxDepth { \dim_use:N \l_shipout_box_dp_dim }
540 \cs_new:Npn \ShipoutBoxWidth { \dim_use:N \l_shipout_box_wd_dim }
541 \ExplSyntaxOff
```

(End of definition for `\ShipoutBoxHeight`, `\ShipoutBoxWidth`, and `\ShipoutBoxDepth`.)

```
542 </atbegshi-ltx>
```

If the package is requested we substitute the one above:

```
543 <*2ekernel>
544 \declare@file@substitution{atbegshi.sty}{atbegshi-ltx.sty}
545 </2ekernel>
```

### 6.3 Package **everyshi** emulation

This is now directly handled in that package so emulation is not necessary any more.

Rather important :-)

```
546 <@@=>
```

## File 54

# ltoutput.dtx

## 1 Output Routine and float handling

```
1 <*2ekernel>
2 \message{output,}
```

### 1.1 Historical notes on the algorithm and commands

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

```
*****
*                               *
*                               *
*****
```

#### PAGE LAYOUT PARAMETERS

`\topmargin` : Extra space added to top of page.  
`@twoside` : boolean. T if two-sided printing  
`\oddsidemargin` : IF `@twoside = T`  
THEN extra space added to left of odd-numbered  
pages.  
ELSE extra space added to left of all pages.  
`\evensidemargin` : IF `@twoside = T`  
THEN extra space added to left of even-numbered  
pages.  
`\headheight` : height of head  
`\headsep` : separation between head and text  
`\footskip` : distance separation between baseline of last  
line of text and baseline of foot.  
Note difference between `\footSKIP` and `\headSEP`.  
`\textheight` : height of text on page, excluding head and foot  
`\textwidth` : width of printing on page  
`\columnsep` : IF `@twocolumn = T`  
THEN width of space between columns  
`\columnseprule` : IF `@twocolumn = T`  
THEN width of rule between columns (0 if none).  
`\columnwidth` : IF `@twocolumn = T`  
THEN  $(\text{\textwidth} - \text{\columnsep})/2$   
ELSE `\textwidth`  
It is set by the `\twocolumn` and  
`\onecolumn` commands.  
`\@textbottom` : Command executed at bottom of vbox holding text of  
page (including figures). The `\raggedbottom`  
command almost \let's this to `\vfil` (actually sets  
it to `\vskip \z@ plus.0001fil`).  
Should have depth 0pt.

`\@texttop` : Command executed at top of vbox holding text of page (including figures). Used by letter style; can also be used to produce centered pages. Let to `\relax` by `\raggedbottom` and `\flushbottom`.

Page layout must initialize `\@colht` and `\@colroom` to `\textheight`.

#### PAGE STYLE PARAMETERS:

`\floatsep` : Space left between floats.  
`\textfloatsep` : Space between last top float or first bottom float and the text.  
`\topfigrule` : Command to place rule (or whatever) between floats at top of page and text. Executed in inner vertical mode right before the `\textfloatsep` skip separating the floats from the text. Must occupy zero vertical space. (See `\footnoterule`.)  
`\botfigrule` : Same as `\topfigrule`, but put after the `\textfloatsep` skip separating text from the floats at bottom of page.  
`\intextsep` : Space left on top and bottom of an in-text float.  
`\dblfloatsep` : Space between double-column floats.  
`\dbltextfloatsep` : Space between top double-column floats and text.  
`\dblfigrule` : Similar to `\topfigrule`, but for double-column floats.  
`\@fptop` : Glue to go at top of float column – must be 0pt + stretch  
`\@fpsep` : Glue to go between floats in a float column.  
`\@fpbot` : Glue to go at bottom of float column – must be 0pt + stretch  
`\@dblfpsep`, `\@dblfpbot` : Analogous for double-column float page in two-column format.

FOOTNOTES: As in PLAIN, footnotes use `\insert\footins`.

#### PAGE LAYOUT SWITCHES AND MACROS

`@twocolumn` : Boolean. T if two columns per page globally.

#### PAGE STYLE MACROS AND SWITCHES

`\@oddhead` : IF `@twoside = T`  
                   THEN macro to generate head of odd-numbered pages.  
                   ELSE macro to generate head of all pages.  
`\@evenhead` : IF `@twoside = T`  
                   THEN macro to generate head of even-numbered

pages.

`\@oddfoot` : IF `@twoside = T`  
THEN macro to generate foot of odd-numbered  
pages.  
ELSE macro to generate foot of all pages.

`\@evenfoot` : IF `@twoside = T`  
THEN macro to generate foot of even-numbered  
pages.

`@specialpage` : boolean. T if current page is to have a special  
format.

`\@specialstyle` : If its value is foo then  
IF `@specialpage = T`  
THEN the command `\ps@foo` is executed to  
temporarily reset the page style parameters  
before composing the current page.  
This command should execute only `\def`'s and  
`\edef`'s, making only local definitions.

## FLOAT PLACEMENT PARAMETERS

The following parameters are set by the macro `\@floatplacement`.  
When `\@floatplacement` is called,

`\@colht` is the height of the page or column being built. I.e.:

- \* For single-column page it equals `\textheight`.
- \* For double-column page it equals `\textheight - height`  
of double-column floats on page.

Note that some are set globally and some locally:

`\@topnum` :=G Maximum number of floats allowed on the top of a  
column.

`\@toproom` :=G Maximum amount of top of column devoted to floats—  
excluding `\textfloatsep` separation below the floats  
and `\floatsep` separation between them. For  
two-column output, should be computed as a function  
of `\@colht`.

`\@botnum`, `\@botroom`  
: Analogous to above.

`\@colnum` :=G Maximum number of floats allowed in a column,  
including in-text floats.

`\@textmin` :=L Minimum amount of text (excluding footnotes) that  
must appear on a text page.  
%% 27 Sep 85 : made local to  
%% `\@addtocurcol` and `\@addtonextcol`  
It is now also used locally in processing double  
floats.

`\@fpmin` :=L Minimum height of floats in a float column.

The macro `\dblfloatplacement` sets the following parameters.

`\dbltopnum` :=G Maximum number of double-column floats allowed at  
the top of a two-column page.

`\dbltoproom` :=G Maximum height of double-column floats allowed at

top of two-column page.

`\@fpm` :=L Minimum height of floats in a float column.

It should also perform the following local assignments where necessary – i.e., where the new value differs from the old one:

`\@fptop` :=L `\@dblftop`

`\@fpsep` :=L `\@dblfpsep`

`\@fpbot` :=L `\@dblfpbot`

## OUTPUT ROUTINE VARIABLES

`\@colht` : The total height of the current column. In single column style, it equals `\textheight`. In two-column style, it is `\textheight` minus the height of the double-column floats on the current page. MUST BE INITIALIZED TO `\textheight`.

`\@colroom` : The height available in the current column for text and footnotes. It equals `\@colht` minus the height of all floats committed to the top and bottom of the current column.

`\@textfloatsheight` : The total height of in-text floats on the current page.

`\footins` : Footnote insertion number.

`\@maxdepth` : Saved value of TeX's `\maxdepth`. Must be set when any routine sets `\maxdepth`.

## CALLING THE OUTPUT ROUTINE

The output routine is called either by TeX's normal page-breaking mechanism, or by a macro putting a penalty  $<$  or  $= -10000$  in the output list. In the latter case, the penalty indicates why the output routine was called, using the following code.

penalty	reason
-10000	<code>\pagebreak</code> <code>\newpage</code>
-10001	<code>\clearpage</code> ( <code>\penalty -10000 \vbox{}</code> <code>\penalty -10001</code> )
-10002	float insertion, called from horizontal mode
-10003	float insertion, called from vertical mode.
-10004	float insertion.

Note: A float or marginpar puts the following sequence in the output list:

- (i) a penalty of -10004,
- (ii) a null `\vbox`
- (iii) a penalty of -10002 or -10003.

This solves two special problems:

1. If the float comes right after a `\newpage` or `\clearpage`, then the first penalty is ignored, but the second one invokes the output routine.
2. If there is a split footnote on the page, the second 'page' puts out the rest of the footnote.

## THE OUTPUT ROUTINE

---

### FUNCTIONS USED IN THE OUTPUT ROUTINE:

`\@outputpage` : Produces an output page with the contents of box `\@outputbox` as the text part.  
 Also sets `\@colht :=G \textheight`.  
 The page style is determined as follows.  
     IF `@thispagestyle = true`  
         THEN use `\thispagestyle` style  
     ELSE use ordinary page style.

`\@tryfcolumn\FLIST` : Tries to form a float column composed of floats from `\FLIST` (if nonempty) with the following parameters:  
     `\@colht` : height of box  
     `\@fpmin` : minimum height of floats in the box  
     `\@fpsep` : interfloat space  
     `\@fptop` : glue at top of box  
     `\@fpbot` : glue at bottom of box.  
 If it succeeds, then it does the following:  
     \* `\@outputbox :=L` the composed float box.  
     \* `@fcolmade :=G true`  
     \* `\FLIST :=G \FLIST` - floats put in box  
     \* `\@freelist :=G \@freelist +` floats put in box  
 If it fails, then:  
     \* `@fcolmade :=G false`

NOTE: BIT MUST BE A SINGLE TOKEN!

`\@makefcolumn \FLIST` : Same as `\@tryfcolumn` except that it fails to make a float column only if `\FLIST` is empty. Otherwise, it makes a float column containing at least the first box in `\FLIST`, disregarding `\@fpmin`.

`\@startcolumn` :  
 Calls `\@tryfcolumn\@deferlist`. If `\@tryfcolumn` returns with (globally set) `@fcolmade = false`, then:  
     \* Globally sets `\@toplist` and `\@botlist` to floats from `\@deferlist` to go at top and bottom of column, deleting them from `\@deferlist`. It does this using `\@colht` as the total height, the page style parameters `\@floatsep` and `\@textfloatsep`, and the float placement parameters `\@topnum`, `\@toproom`, `\@botnum`, `\@botroom`, `\@colnum` and `\textfraction`.

\* Globally sets `\@colroom` to `\@colht` minus the height of the added floats.

`\@startdblcolumn` :

Calls `\@tryfcolumn\@dbldeferlist{8}`. If `\@tryfcolumn` returns with (globally set) `@fcolmade = false`, then:

- \* Globally sets `\@dbltoplist` to floats from `\@dbldeferlist` to go at top and bottom of column, deleting them from `\@dbldeferlist`. It does this using `\textheight` as the total height, and the parameters `\@dblfloatsep`, etc.
- \* Globally sets `\@colht` to `\textheight` minus the height of the added floats.

`\@combinefloats` : Combines the text from box

`\@outputbox` with the floats from `\@toplist` and `\@botlist`, putting the new box in `\@outputbox`. It uses `\floatsep` and `\textfloatsep` for the appropriate separations. It puts the elements of `\TOPLIST` and `\BOTLIST` onto `\freelist`, and makes those lists null.

`\@makecol` : Makes the contents of `\box255` plus the accumulated footnotes, plus the floats in `\@toplist` and `\@botlist`, into a single column of height `\@colht` (unless the page height has been locally changed), which it puts into box `\@outputbox`. It puts boxes in `\@midlist` back onto `\freelist` and restores `\maxdepth`.

`\@opcol` : Outputs a column whose text is in box `\@outputbox`

If `@twocolumn = false`, then it calls `\@outputpage`, sets `\@colht :=G \textheight`, and calls `\@floatplacement`.

If `@twocolumn = true`, then:

If `@firstcolumn = true`, then it puts box `\@outputbox` into `\@leftcolumn` and sets `@firstcolumn :=G false`.

If `@firstcolumn = false`, then it puts out the current two-column page, any possible two-column float pages, and determines `\@dbltoplist` for the next page.

## USER COMMANDS THAT CALL OR AFFECT THE OUTPUT

### ROUTINE

---

`\newpage == BEGIN \par\vfil\penalty -10000 END`

`\clearpage == BEGIN \newpage  
                   \write -1{}     % Part of hack to make sure no`

```

\hbox{} % \write's get lost.
\penalty -10001
END

\cleardoublepage == BEGIN \clearpage
                    if @twoside = true and c@page is even
                    then \hbox{} \newpage fi
END

\twocolumn[BOX] : starts a new page, changing to twocolumn setting
and puts BOX in a parbox of width \textwidth across the top.
Useful for full-width titles for double-column pages.
SURPRISE: The stretch from \@dbltextfloatsep will be inserted
between the BOX and the top of the two columns.

```

## FLOAT-HANDLING MECHANISMS

---

The float environment obtains an insertion number B from the `\@freelist` (see below for a description of list manipulation), puts the float into box B and sets `\count B` to a FLOAT SPECIFIER. For a normal (not double-column) float, it then causes a page break in one of the following two ways:

- In outer hmode: `\vadjust{\penalty -10002}`
- In vmode : `\penalty -10003`.

For a double-column float, it puts B onto the `\@dbldeferlist`. The float specifier has two components:

- \* A PLACEMENT SPECIFICATION, describing where the float may be placed.
- \* A TYPE, which is a power of two—e.g., figures might be type 1 floats, tables type 2 floats, programs type 4 floats, etc.

The float specifier is encoded as follows, where bit 0 is the least significant bit.

Bit	Meaning
0	1 iff the float may go where it appears in the text.
1	1 iff the float may go on the top of a page.
2	1 iff the float may go on the bottom of a page.
3	1 iff the float may go on a float page.
4	1 unless the PLACEMENT includes a !
5	1 iff a type 1 float
6	1 iff a type 2 float
etc.	

A negative float specifier is used to indicate a marginal note.

## MACROS AND DATA STRUCTURES FOR PROCESSING FLOATS

---

A FLOAT LIST consisting of the floats in boxes `\boxa ... \boxN` has the form:

`\@elt \boxa ... \@elt \boxN`

where `\boxI` is defined by

`\newinsert\boxI`

Normally, `\@elt` is `\let` to `\relax`. A test can be performed on the entire float list by locally `\def`'ing `\@elt` appropriately and executing the list.

This is a lot more efficient than looping through the list.

The following macros are used for manipulating float lists.

```
\@next \CS \LIST {NONEMPTY}{EMPTY} == %% NOTE: ASSUME \@elt
= \relax
  BEGIN  assume that \LIST == \@elt \B1 ... \@elt \Bn
        if n = 0
        then  EMPTY
        else  \CS      :=L \B1
              \LIST :=G \@elt \B2 ... \@elt \Bn
              NONEMPTY
        fi
  END
```

`\@bitor\NUM\LIST` : Globally sets switch `@test` to the disjunction for all `I` of bit `log2 \NUM` of the float specifiers of all the floats in `\LIST`.  
 I.e., `@test` is set to true iff there is at least one float in `\LIST` having bit `log2 \NUM` of its float specifier equal to 1.

Note: `log2 [(\count I)/32]` is the bit number corresponding to the type of float `I`. To see if there is any float in `\LIST` having the same type as float `I`, you run `\@bitor` with  
`\NUM = [(\count I)/32] * 32`.

```
\@bitor\NUM\LIST ==
  BEGIN
    @test :=G false
    { \@elt \CTR == if \NUM <> 0 then
                      if \count\CTR / \NUM is odd
                      then @test := true      fi fi
    \LIST
  }
  END
```

`\@cons\LIST\NUM` : Globally sets `\LIST := \LIST * \@elt \NUM`

```

\@cons\LIST\NUM ==
  BEGIN { \@elt == \relax
    \LIST :=G \LIST \@elt \NUM
  }

```

## BOX LISTS FOR FLOAT-PLACEMENT ALGORITHMS

```

\@freelist      : List of empty boxes for placing new floats.
\@toplist       : List of floats to go at top of current column.
\@midlist       : List of floats in middle of current column.
\@botlist       : List of floats to go at bottom of current column.
\@deferlist     : List of floats to go after current column.
\@dbltoplist    : List of double-col. floats to go at top of current
                  page.
\@dbldeferlist  : List of double-column floats to go on subsequent
                  pages.

```

## FLOAT-PLACEMENT ALGORITHMS

```

\@addtobot : Tries to put insert \@currbox on \@botlist.
             Called only when:
               * \ht BOX < \@colroom
               * type of \@currbox not on \@deferlist
               * \@colnum > 0
               * @insert = false
             If it succeeds, then:
               * sets @insert true
               * decrements \@botroom by \ht BOX
               * decrements \@botnum and \@colnum by 1
               * decrements \@colroom by \ht BOX + either \floatsep
                 or \textfloatsep, as appropriate.
               * sets \maxdepth to 0pt      % <- as of 2025/06/01
                                           %      no longer the case

\@addtotoporbot : Tries to put insert \@currbox on \@toplist or
                  \@botlist.
                  Called only under same conditions as \@addtobot.
                  If it succeeds, then:
                    * sets @insert true
                    * decrements \@toproom or \@botroom by \ht BOX
                    * decrements \@colnum and either \@topnum or
                      \@botnum by 1
                    * decrements \@colroom by \ht BOX + \floatsep
                      or \textfloatsep, as appropriate.

\@addtocurcol : Tries to add \@currbox to current column, setting
                @insert true if it succeeds, false otherwise.
                It will add \@currbox to top only if bit 0 of

```

```

\count \@currbox is 0, and to the bottom only if
bit 0 = 0 or an earlier float of the same type is
put on the bottom.
If the float is put in the text, then
\penalty\interlinepenalty is put
right after the float, before the following \vskip,
and \outputpenalty :=L 0.

\@addtonextcol : Tries to add \@currbox to the next column, setting
                 @insert true if it succeeds, false otherwise.

\@addtodblcol : Tries to add \@currbox to the next double-column page,
                 adding it to \@dbltoplist if it succeeds and
                 \@dbldeferlist if it fails.

\@addmarginpar ==
BEGIN
  if \@currlist nonempty
    then remove \@marbox from \@currlist
    add \@marbox and \@currbox to \@freelist
    %% NOTE: \@currbox = left box
  else LaTeX error: ? %% shouldn't happen
  fi
  \@tempcnta := 1      %% 1 = right, -1 = left
  if @twocolumn = true
    then if @firstcolumn = true
      then \@tempcnta := -1
      fi
    else if @mparswitch = true
      then if count0 odd
        else \@tempcnta := -1
        fi
      fi
    if @reversemargin = true
      then \@tempcnta := -\@tempcnta
      fi
  fi
  if \@tempcnta < 0 then \box\@marbox :=G \box\@currbox
  fi
  \@tempdima :=L maximum(\@mparbottom - \@pageht
                        + ht of \@marbox, 0)
  if \@tempdima > 0 then LaTeX warning: 'marginpar moved' fi
  \@mparbottom :=G \@pageht + \@tempdima + depth of \@marbox
                + \marginparpush
  \@tempdima :=L \@tempdima - ht of \@marbox
  \box\@marbox :=G \box\@currbox
                  \vbox { \vskip \@tempdima
                          \box\@marbox
                          }

```

```

height of \@marbox :=G depth of \@marbox :=G 0
\kern -\@pagedp
\nointerlineskip
\hbox{ if @tempcnta > 0 then \hskip \columnwidth
                                \hskip \marginparsep
                                else \hskip -\marginparsep
                                \hskip -\marginparwidth
                                fi
      \box\@marbox \hss
    }
\nobreak
\nointerlineskip
\hbox{\vrule height 0 width 0 depth \@pagedp}
END

```

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

## 1.2 Core definitions

Floats and marginpars add a lot of dead cycles.

```

3 \maxdeadcycles = 100
4 \let\@elt\relax
5 \def\@next#1#2#3#4{\ifx#2\@empty #4\else
6   \expandafter\@xnext #2\@#1#2#3\fi}
7 \def\@xnext \@elt #1#2\@#3#4{\def#3{#1}\gdef#4{#2}}
8 \def\@testfalse{\global\let@if@test\iffalse}
9 \def\@testtrue {\global\let@if@test\iftrue}
10 \@testfalse
11 \def\@bitor#1#2{\@testfalse {\let\@elt\@xbitor
12   \@tempcnta #1\relax #2}}

```

RmS 91/11/22: Added test for \count#1 = 0. Suggested by Chris Rowley.

```

13 \def\@xbitor #1{\@tempcntb \count#1
14   \ifnum \@tempcnta =\z@
15   \else
16     \divide\@tempcntb\@tempcnta
17     \ifodd\@tempcntb \@testtrue\fi
18   \fi}

```

### 1.2.1 Definition of float boxes

```

19 \let\@elt\newinsert
20 \def\@freelist{%
21   \@elt\bx@A\@elt\bx@B\@elt\bx@C\@elt\bx@D\@elt\bx@E
22   \@elt\bx@F\@elt\bx@G\@elt\bx@H\@elt\bx@I\@elt\bx@J
23   \@elt\bx@K\@elt\bx@L\@elt\bx@M\@elt\bx@N
24   \@elt\bx@O\@elt\bx@P\@elt\bx@Q\@elt\bx@R}
25 \@freelist
26 \def\reserved@a{%
27   \@elt\bx@S\@elt\bx@T\@elt\bx@U\@elt\bx@V

```

```

28 \elt\bx@W\elt\bx@X\elt\bx@Y\elt\bx@Z
29 \elt\bx@AA\elt\bx@BB\elt\bx@CC\elt\bx@DD\elt\bx@EE
30 \elt\bx@FF\elt\bx@GG\elt\bx@HH\elt\bx@II\elt\bx@JJ
31 \elt\bx@KK\elt\bx@LL\elt\bx@MM\elt\bx@NN
32 \elt\bx@OO\elt\bx@PP\elt\bx@QQ\elt\bx@RR
33 \elt\bx@SS\elt\bx@TT\elt\bx@UU\elt\bx@VV
34 \elt\bx@WW\elt\bx@XX\elt\bx@YY\elt\bx@ZZ}
35 \reserved@a
36 \def\elt{\noexpand\elt\noexpand}
37 \edef\freelist{\freelist\reserved@a}
38 \let\reserved@a\relax
39 \let\elt\relax
40 \gdef\@toplist{}
41 \gdef\@botlist{}
42 \gdef\@midlist{}
43 \gdef\@currlist{}
44 \gdef\@deferlist{}
45 \gdef\@dbltoplist{}

```

The new algorithm stores page wide floats together with column floats in a single `\@deferlist` list. We keep `\@dbldeferlist` initialised as empty so that packages that are testing for deferred floats can use the same code for old or new float handling.

```
46 \gdef\@dbldeferlist{}
```

### 1.2.2 Page layout parameters

```

47 \newdimen\topmargin
48 \newdimen\oddsidemargin
49 \newdimen\evensidemargin
50 \let\themargin=\oddsidemargin
51 \newdimen\headheight
52 \newdimen\headsep
53 \newdimen\footskip
54 \newdimen\textheight
55 \newdimen\textwidth
56 \newdimen\columnwidth
57 \newdimen\columnsep
58 \newdimen\columnseprule
59 \newdimen\marginparwidth
60 \newdimen\marginparsep
61 \newdimen\marginparpush

```

**`\AtBeginDvi`** We use a box register in which to put stuff that must appear before anything else in the `.dvi` file.

The stuff in the box should not add any typeset material to the page when it is unboxed.

This interface is no longer used. Instead a new one is inside `ltshipout.dtx`. We only keep the box in case some old code refers to it directly (or we do some rollback).

```

62 \newbox\@begindvibox
63 %\DeclareRobustCommand \AtBeginDvi [1]{%
64 % \global \setbox \@begindvibox
65 % \vbox{\unvbox \@begindvibox #1}%
66 %}

```

*(End of definition for `\AtBeginDvi` and `\@begindvibox`. These functions are documented on page 1142.)*

`\@maxdepth` This is not the right place to set this; it needs to be set in a class/style file when `\maxdepth` is set.

Also, many settings to `\maxdepth` should be to `\@maxdepth`, probably?

```
67 \newdimen\@maxdepth
68 \@maxdepth = \maxdepth
```

*(End of definition for \@maxdepth.)*

`\paperheight` New `\paper...` registers.

```
\paperwidth 69 \newdimen\paperheight
70 \newdimen\paperwidth
```

*(End of definition for \paperheight and \paperwidth.)*

`\stockheight` New `\stock...` registers.

```
\stockwidth 71 \newdimen\stockheight
72 \newdimen\stockwidth
```

*(End of definition for \stockheight and \stockwidth.)*

`\if@insert` Local switches first:

```
\if@fcolmade 73 \newif \if@insert
```

`\if@specialpage` These should definitely be global:

```
\if@firstcolumn 74 \newif \if@fcolmade
\if@twocolumn 75 \newif \if@specialpage \@specialpagefalse
\if@twoside
```

`\if@reversemargin` These should be global but are not always set globally in other files.

```
\if@mparswitch 76 \newif \if@firstcolumn \@firstcolumntrue
\col@number 77 \newif \if@twocolumn \@twocolumnfalse
```

Not sure about these: two questions. Should things which must apply to a whole document be local or global (they probably should be ‘preamble only’ commands)? Are these three such things?

```
78 \newif \if@twoside \@twosidefalse
79 \newif \if@reversemargin \@reversemarginfalse
80 \newif \if@mparswitch \@mparswitchfalse
```

This counter has been imported from ‘multicol’.

```
81 \newcount \col@number
82 \col@number \@ne
```

*(End of definition for \if@insert and others.)*

### 1.2.3 Internal registers

```
83 \newcount\@topnum
84 \newdimen\@toproom
85 \newcount\@dbltopnum
86 \newdimen\@dbltoproom
87 \newcount\@botnum
88 \newdimen\@botroom
89 \newcount\@colnum
90 \newdimen\@textmin
91 \newdimen\@fpmin
92 \newdimen\@colht
93 \newdimen\@colroom
94 \newdimen\@pageht
95 \newdimen\@pagedp
96 \newdimen\@mparbottom \@mparbottom\z@
97 \newcount\@currtype
98 \newbox\@outputbox
99 \newbox\@leftcolumn
100 \newbox\@holdpg
101 \def\@thehead{\@oddhead} % initialization
102 \def\@thefoot{\@oddfoot}
```

### 1.2.4 Page break commands

**\clearpage** The tests at the beginning are an experimental attempt to avoid a completely empty page after a `\twocolumn[...]`. This prevents the text from the argument vanishing into a float box, never to be seen again. We hope that it does not produce wrong formatting in other cases.

```
103 \def\clearpage{%
104   \ifvmode
105     \ifnum \@dbltopnum =\m@ne
106       \ifdim \pagetotal <\topskip
107         \hbox{}%
108       \fi
109     \fi
110   \fi
111   \newpage
```

After the above `\newpage` there may be some still unwritten `\write`'s issued in the output routine and we need to make sure that they are not lost when `\@docclearpage` produces float pages. Therefore the following trick is applied: We add a harmless `\write` followed by an empty `\vbox` and then call the output routine again through a special penalty. That triggers `\@docclearpage` in the OR which splits off a zero-sized chunk from box 255 (which should go up to, but not including, the `\vbox`), then `\unvbox` that (which should contain any `\write`'s, and then throw away the rest of 255 (which should just contain the `\vbox`). That explains the strange `\write-1{}`: that statement introduces a necessary breakpoint so that the split is done before the `\vbox`. If it would not be there and *there are no real \write's*, then the split would grab the whole of 255 and so would put the `\vbox` back on the page and we would end with an extra page only containing that empty `\vbox`.

Deep breath—the above is my (Frank's) attempt of a slightly longer version of Leslie's cryptic comment earlier in the file that this `\write` is “part of a hack to make sure that no `\write`'s are lost”.

This `\write` needs to be non-immediate even if we are supposedly already past the last page because it has to end up on the page sent to the output routine if for some reason that happens.

```

112 \@@write\m@ne{}%
113 \vbox{}%
114 \penalty -\@Mi
115 }

116 \let\@@write\write

```

*(End of definition for \clearpage.)*

`\cleardoublepage`

```

117 \def\cleardoublepage{\clearpage\if@twoside \ifodd\c@page\else
118 \hbox{}\newpage\if@twocolumn\hbox{}\newpage\fi\fi\fi}
119 </2ekernel>

```

*(End of definition for \cleardoublepage.)*

`\onecolumn`

```

120 <*2ekernel | fltrace>
121 \def\onecolumn{%
122 \clearpage
123 \global\columnwidth\textwidth
124 \global\hsize\columnwidth
125 \global\linewidth\columnwidth
126 \global\@twocolumnfalse
127 \col@number \@ne
128 \@floatplacement}

```

*(End of definition for \onecolumn.)*

`\newpage` The two checks at the beginning ensure that an item label or run-in section title immediately before a `\newpage` get printed on the correct page, the one before the page break.

All three tests are largely to make error processing more robust; that is why they all reset the flags explicitly, even when it would appear that this would be done by a `\leavevmode`.

```

129 </2ekernel | fltrace>
130 <latexrelease>\IncludeInRelease{2025/06/01}%
131 <latexrelease> \{\newpage\}{Check depth of page}%
132 <*2ekernel | latexrelease | fltrace>
133 \def \newpage {%
134 \if@noskipsec
135 \ifx \@nodocument\relax
136 \leavevmode
137 \global \@noskipsecfalse
138 \fi
139 \fi
140 \if@inlabel
141 \leavevmode
142 \global \@inlabelfalse
143 \fi
144 \if@nobreak \@nobreakfalse \everypar{}\fi

```

The `\vfil` at the end of the macro before the break penalty will normally result in the page being run short, even with `\flushbottom` in effect (in contrast to the behavior of `\pagebreak`). However, if there is some explicit stretch on the page, say, a `\vfill`, it has the undesired side-effect, that the last line will not align at its baseline if it contains characters going below the baseline, as the value of `\prevdepth` is no longer taken into account by T<sub>E</sub>X. So we have to back up by that amount (or by `\maxdepth` if it is really huge), to mimic the normal behavior without the `\newpage`.

In 2017 this was fixed by doing the backing-up here. However, the problem with that is that if the page contains footnotes the `\skip\ý` is measured from the baseline of the last line and not (as on all other pages) from the bottom of the last line. One can argue that measuring from the baseline is better, but if that is done it should be done everywhere not just on some pages.

Thus this backing up should only happen when there are no footnotes. The problem is that, at the point when `\newpage` is called, it is not known whether or not there are footnotes; that is only determined in the output routine. We have therefore moved this code to the newly introduced output routine sockets.

An explicit `\par` token is required so that after environments like lists `\par` is reset to its standard meaning and does not suppress indentation on the next page.

```

145 \par
146 % \ifdim\prevdepth>\z@
147 % \vskip -%
148 % \ifdim\prevdepth>\maxdepth
149 % \maxdepth
150 % \else
151 % \prevdepth
152 % \fi
153 % \fi
154 \vfil
155 \penalty -\@M}
156 </2ekernel | latexrelease | fltrace>
157 <latexrelease>\EndIncludeInRelease

158 <latexrelease>\IncludeInRelease{2017/04/15}%
159 <latexrelease> \newpage{Check depth of page}%
160 <latexrelease>\def \newpage {%
161 <latexrelease> \if@noskipsec
162 <latexrelease> \ifx \@nodocument\relax
163 <latexrelease> \leavevmode
164 <latexrelease> \global \@noskipsecfalse
165 <latexrelease> \fi
166 <latexrelease> \fi
167 <latexrelease> \if@inlabel
168 <latexrelease> \leavevmode
169 <latexrelease> \global \@inlabelfalse
170 <latexrelease> \fi
171 <latexrelease> \if@nobreak \@nobreakfalse \everypar{}\fi
172 <latexrelease> \par
173 <latexrelease> \ifdim\prevdepth>\z@
174 <latexrelease> \vskip -%
175 <latexrelease> \ifdim\prevdepth>\maxdepth
176 <latexrelease> \maxdepth
177 <latexrelease> \else
178 <latexrelease> \prevdepth

```

```

179 <latexrelease> \fi
180 <latexrelease> \fi
181 <latexrelease> \vfil
182 <latexrelease> \penalty -\@M}

183 <latexrelease>\EndIncludeInRelease
184 <latexrelease>\IncludeInRelease{0000/00/00}%
185 <latexrelease> \newpage}{Check depth of page}%
186 <latexrelease>\def \newpage {%
187 <latexrelease> \if@noskipsec
188 <latexrelease> \ifx \@nodocument\relax
189 <latexrelease> \leavevmode
190 <latexrelease> \global \@noskipsecfalse
191 <latexrelease> \fi
192 <latexrelease> \fi
193 <latexrelease> \if@inlabel
194 <latexrelease> \leavevmode
195 <latexrelease> \global \@inlabelfalse
196 <latexrelease> \fi
197 <latexrelease> \if@nobreak \@nobreakfalse \everypar{}\fi
198 <latexrelease> \par
199 <latexrelease> \vfil
200 <latexrelease> \penalty -\@M}
201 <latexrelease>\EndIncludeInRelease
202 <*2ekernel|fltrace>

```

*(End of definition for \newpage.)*

`\@emptycol` It may be better to use an invisible rule rather than an empty box here.

```
203 \def \@emptycol {\vbox{}\penalty -\@M}
```

*(End of definition for \@emptycol.)*

`\twocolumn` There are several bug fixes to the two-column stuff here.  
`\@topnewpage`

```

204 \def \twocolumn {%
205   \clearpage
206   \global\columnwidth\textwidth
207   \global\advance\columnwidth-\columnsep
208   \global\divide\columnwidth\tw@
209   \global\hsize\columnwidth
210   \global\linewidth\columnwidth
211   \global\@twocolumntrue
212   \global\@firstcolumntrue
213   \col@number \tw@

```

There is no reason to put a `\@dblfloatplacement` here since `\@topnewpage` ignores these settings. The `\@floatplacement` is needed in case this comes after some changes.

```

214   \ifnextchar [\@topnewpage\@floatplacement
215 }

```

Note that here, getting a box from the freelist can assume success since this comes just after a `\clearpage`.

```

216 \long\def \@topnewpage [#1]{%
217   \@nodocument
218   \@next\@currbox\@freelist{}\}%

```

```

219 \global \setbox\@currbox
220 \color@vbox
221 \normalcolor
222 \vbox {%
223 \hsize\textwidth
224 \@parboxrestore
225 \col@number \@ne
226 #1%
227 \vskip -\dbltextfloatsep
228 }%
229 \color@endbox

```

Added size test and warning message; perhaps we should use an error message.

```

230 \ifdim \ht\@currbox>\textheight
231 \ht\@currbox \textheight
232 \fi

```

This next line is not essential but it is more robust to make this value non-zero, in case of weird errors.

This next bit is what is needed from `\@addtodblcol`, plus some extra checks for error trapping.

```

233 \global \count\@currbox \tw@
234 \@tempdima -\ht\@currbox
235 \advance \@tempdima -\dbltextfloatsep
236 \global \advance \@colht \@tempdima
237 \ifx \@dbltoplist \@empty
238 \else
239 \latexerror{Float(s) lost}\@ehb
240 \let \@dbltoplist \@empty
241 \fi
242 \@cons \@dbltoplist \@currbox

```

This setting of `\@dbltopnum` is used only to change the typesetting in `\@combinedblfloats`.

```

243 \global \@dbltopnum \m@ne
244 (*trace)
245 \fl@trace{dbltopnum set to -1 (= \the \@dbltopnum) (topnewpage)}%
246 (/trace)

```

At points such as this we need to check that there is still a minimal amount of room left on the page; this uses an arbitrary small value at present; but note that this value is larger than that used when checking that page is too full of normal floats.

If there is little room left we just force a page-break, OK? This involves producing two empty columns. The second empty column may be produced by `\output`, in which case an extra, misleading, warning will be generated, OK? (This happens only when there is too little room left on the page for any float.) Otherwise (i.e. if the size is such that it is allowed as a normal float) the extra `\@emptycol` will be invoked in the second column by the conditional code guarded by the `\if@firstcolumn` test.

I now think that the cut-off point here should be `3\baselineskip`, but we make it a bit less so that 3 lines of text will be allowed, OK?

Since this happens only when there is nothing on the page but the ‘top-box’, the empty box should not cause any problem other than some overfull box messages, which is not entirely misleading.

Here we need two page-ends since both columns need to be empty.

```

247 \ifdim \@colht<2.5\baselineskip
248 \latex@warning@no@line {Optional argument of \noexpand\twocolumn
249 too tall on page \thepage}%
250 \emptycol
251 \if@firstcolumn
252 \else
253 \emptycol
254 \fi
255 \else
256 \global \vsize \@colht
257 \global \@colroom \@colht
258 \@floatplacement
259 \fi
260 }

```

*(End of definition for \twocolumn and \topnewpage.)*

## 2 The L<sup>A</sup>T<sub>E</sub>X output routine

### 2.1 Hooks and replaceable code blocks

To support packages that want to augment aspects of the output routine we offer a number of hooks (where several packages can add code) as well as some sockets (that can only be changed by one package or through options like those of the `footmisc` package).

#### 2.1.1 Output routine hooks

**build/page/before, build/page/after** These two hooks enable packages to prepend or append code to the page processing in the output routine. They are implemented as mirrored hooks.

Technically, they are executed at the start and the end of the internal L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> `\@outputpage` command, respectively.

**build/page/reset** Packages that set up special conventions for text in the main galley (such as catcode changes, etc.) can use this hook to undo these changes within the output routine, so that they aren't applied to unrelated material, e.g., the text for running header or footers.

**build/column/before, build/column/after** These two hooks enable packages to prepend or append code to the column processing in the output routine. They are implemented as mirrored hooks.

Technically, they are executed at the start and the end of the internal L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> `\@makecol` command, respectively.

#### 2.1.2 Replaceable code blocks (sockets)

To cater for different layouts with respect to text, footnotes, and bottom-floats placements there are sockets for now. They are sockets not hooks, because the overall layout can only be controlled by one package, i.e., the last setting wins.

**build/column/outputbox (0 arguments)** In code for this socket the `\@outputbox` (holding the galley text for the current column or page) is augmented by attaching floats and footnote areas together with appropriate spacing.

Prior to calling the socket the output routine has already decided which floats go into which area and which get deferred. Therefore, the assumption is that the code in the socket attaches all areas that contain floats. If this is not done, then the order of floats is likely to be screwed up unless unused floats are moved to the defer list in an appropriate way (for now we don't offer any interface for that scenario).

Before the code in the socket is run, any existing glue at the bottom of the `\@outputbox` is removed and stored in a safe place. If needed, it can be reinserted with one of the helper commands.

To support setting this up the following helper commands are available:

**`\@outputbox@append (1 argument)`**

This general purpose command alters the `\@outputbox` box by appending material to it.

**`\@outputbox@appendfil (0 arguments)`** Append a `\vfil` to the `\@outputbox`.

Based on the plug in `build/column/baselineattach` either measured from the bottom or from the baseline of the last line in the box.

**`\@outputbox@appendfootnotes (0 arguments)`**

This command appends the footnotes to the `\@outputbox` (if there are any). If not, then it does nothing.

**`\@outputbox@attachfloats (0 arguments)`**

**`\@outputbox@attachtopfloats (0 arguments)`**

**`\@outputbox@attachbottomfloats (0 arguments)`**

Attaching top and bottom floats can usually be done in one go, but for special layouts we might want more control so we provide also separate commands.

**`\@outputbox@reinsertbskip (0 arguments)`**

Reinsert the bottom skip of the `\@outputbox` that was saved before in `\@makecol`.

### Testing for existence of material

There are a number of helpers to run conditional code depending on whether or not there are footnotes or bottom floats. They are `\@if@footnotes@TF` and `\@if@bottomfloats@TF` (names are likely to change).

This socket cannot be empty but needs appropriate code; a set of suitable plugs for it are already given in the kernel. These are

**space-footnotes-floats** After the galley text there is a vertical `\vfil` followed by any footnotes followed by the bottom floats, if any.

**footnotes-space-floats** As before but the `\vfil` is between footnotes and floats.

**floats-space-footnotes** Floats are directly after the text, then a space and then footnotes at the bottom.

**space-floats-footnotes** Both floats and footnotes are pushed to the bottom with footnotes last.<sup>63</sup>

---

<sup>63</sup>There are two more permutations, but neither of them has ever been requested so they aren't set up by default — doing that in a class would be trivial though.

**floats-footnotes** All excess space is distributed across the existing glue on the page, e.g., within the text galley, the separation between blocks, etc. The order is text, floats, footnotes.

**footnotes-floats** As the previous one but floats and footnotes are swapped. This is the L<sup>A</sup>T<sub>E</sub>X default for newer document, i.e., this plug is assigned to the socket when `\DocumentMetadata` is used.

**footnotes-floats-legacy** As the previous one but L<sup>A</sup>T<sub>E</sub>X's bottom skip bug is not corrected, i.e., in ragged bottom designs where footnotes are supposed to be directly attached to the text, they suddenly appear at the bottom of the page when the page is ended with `\newpage` or `\clearpage`. While this is clearly a bug, it was the case since the days of L<sup>A</sup>T<sub>E</sub>X 2.09; thus for compatibility we continue to support this behavior.

**build/column/footnotes (0 arguments)** This socket is used to manipulate the footnote material inside `\box\footins`. If it contains code, it is supposed to do some processing of that box and then write the result back into it (and nothing else!). By default it does nothing, i.e., has the `noop` assigned.

If (short) footnotes are run as a paragraph this socket gets the plug `para` assigned which is defined elsewhere.

**build/column/baselineattach (0 arguments)** By default, footnotes are attached after the last line of text by adding a `\vskip\skip\footins`, i.e., the space is measured from the bottom of `\@outputbox` (plug `off`). Bottom floats are attached in a similar way by using `\vskip\textfloatsep`.

The socket can get the plug `on` assigned, in which case the skip starts at the baseline of the last line in `\@outputbox`, if there is one; otherwise it starts still from the bottom of the box.

### 2.1.3 Tagging sockets

The following sockets are used to implement tagging. They are used via `\UseTaggingSocket` which turns them off when tagging is disabled. For each of them a `default` plug is implemented that holds the tagging code.

**build/column/outputbox (0 arguments)** This socket is used to add any missing tagging structures to the `\@outputbox` box, if necessary.

**build/column/footins (0 arguments)** This socket is used to add any missing tagging structures to `\footins` box, if necessary.

**build/page/header (2 arguments)** This socket receives the content of the formatted page header as its second argument and adds the necessary tagging around it. The first argument is empty as no special setup is necessary.

**build/page/footer (2 arguments)** This socket receives the content of the formatted page footer as its second argument and adds the necessary tagging around it. The first argument is empty as no special setup is necessary.

### 2.1.4 Output routine commands

`\output` This needs some small adjustments. We cannot guarantee that the float mechanism will interact correctly with this stuff, but that mechanism does not always work properly with footnotes already.

RmS 91/09/29:

added reset of `\par` to the output routine. This avoids problems when the output routine is called within a list where `\par` may be a no-op.

```

261 \output {%
262   \let \par \@par
263   \ifnum \outputpenalty<-\@M
264     \@specialoutput
265   \else
266     \@makecol
267     \@opcol

```

Moved to `\@opcol: \@floatplacement`.

```

268   \@startcolumn

```

This loop could be replaced by an `\expandafter` tail recursion in `\@startcolumn`.

```

269   \@whilesw \if@fcolmade \fi
270   {%
271   (*trace)
272     \fl@trace{PAGE: float \if@twocolumn column \else page \fi
273               completed}%
274   (/trace)
275     \@opcol\@startcolumn}%
276   \fi
277   \ifnum \outputpenalty>-\@Miv

```

At points such as this we need to check that there is still a minimal amount of room left on the page; this uses an arbitrary small value at present. If there is little room left we just force a page-break, OK?

This bit is essential only if a float has just been processed so maybe it should be moved; but this is the natural place at which to set the `vsize` and a test would need to be done anyway. A check has been added to ensure that there really has been a change in the value of `\@colroom`.

Since this happens only when there is nothing on the page but floats, the empty box should not cause any problem other than some overfull box messages, which is not entirely misleading.

The `twocolumn` case does not need any extra code here since this is the `\output` itself; in the second column there will still not be enough room left so `\@emptycol` will be executed again when the OR is called by the page builder when it gets to the penalty inserted by the first execution. (The page-builder is never invoked whilst the OR is being executed since it builds a inner `vlist`; thus any conditional code for the two-column case within `\output` may not get executed with the correct value of `\if@firstcolumn`.

```

278   \ifdim \@colroom<1.5\baselineskip
279     \ifdim \@colroom<\textheight
280       \@latex@warning@no@line {Text page \thepage\space
281                               contains only floats}%
282     \@emptycol
283   %     \if@twocolumn
284   %     \if@firstcolumn

```

```

285 %           \else
286 %           \@emptycol
287 %           \fi
288 %           \fi
289     \else
290       \global \vsize \@colroom
291     \fi
292   \else
293     \global \vsize \@colroom
294   \fi
295 \else
296   \global \vsize \maxdimen
297 \fi
298 }

```

*Historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments (not necessarily accurate any more):*

CHANGES TO \@specialoutput:

\* \penalty\z@ changed to \penalty\interlinepenalty so \samepage works properly with figure and table environments.  
(Changed 23 Oct 86)

\* Definition of \@specialoutput changed 26 Feb 88 so \@pageht and \@pagedp aren't changed for a marginal note.  
(Change suggested by Chris Rowley.)

*End of historical L<sup>A</sup>T<sub>E</sub>X 2.09 comments.*

```

299 \gdef\@specialoutput{%
300   \ifnum \outputpenalty>-\@Mii
301     \doclearpage
302   \else
303     \ifnum \outputpenalty<-\@Miii
304       \ifnum \outputpenalty<-\@MM \deadcycles \z@ \fi
305       \global \setbox\@holdpg \vbox {\unvbox\@cclv}%
306     \else

```

Note that \boxmaxdepth should not be set here since we wish to record the natural depth of the holdpg box.

This is changed so as to not lose anything, such as writes and marks, which may get into box 255 and should be returned to the list. This should only happen when the first penalty in the mechanism is discarded and therefore \@holdpg should always be void in this case. This can happen because a penalty is discarded whenever there is no box on the list.

It was just: \setbox\@tempboxa \box \@cclv.

The last box which is removed is the box put there by the double-penalty mechanism. The \unskip then removes the \topskip which is put there since the box is the first on the page.

```

307   \global \setbox\@holdpg \vbox{%
308     \unvbox\@holdpg
309     \unvbox\@cclv

```

We must now remove the box added by the float mechanism and the \topskip glue therefore added above it by T<sub>E</sub>X.

```

310     \setbox\@tempboxa \lastbox
311   \unskip

```

312 }%

These two are needed as separate dimensions only by `\@addmarginpar`; for other purposes we put the whole size into `\@pageht` (see below).

```
313 \pagedp \dp\@holdpg
314 \pageht \ht\@holdpg
315 \unvbox \@holdpg
316 \@next\@currbox\@currlist{%
317 \ifnum \count\@currbox>\z@
```

Putting the whole size into `\@pageht` (see above).

```
318 \advance \@pageht \@pagedp
319 \ifvoid\footins \else
320 \advance \@pageht \ht\footins
321 \advance \@pageht \skip\footins
322 \advance \@pageht \dp\footins
323 \fi
324 \ifvbox \@kludgeins
```

We want to make the adjustment due to this insert only if the non-star form is used. The \*-form will probably not work with floats, but maybe it still could make some adjustment here even so?

```
325 \ifdim \wd\@kludgeins=\z@
326 \advance \@pageht \ht\@kludgeins
327 <{*trace}
328 \fl@trace {Extra size added: \the \ht\@kludgeins}%
329 </trace>
330 \fi
331 \fi
```

This version puts the inserts back just before the additional material; it could be moved earlier, before unboxing the page-so-far. Neither is guaranteed not to put things on the wrong page. This version is similar to the original version.

```
332 \@reinserts
333 \@addtocurcol
334 \else
335 \@reinserts
336 \@addmarginpar
337 \fi
338 }\@latexbug
```

A 2e change: use `\addpenalty` instead of `\penalty` here. Some penalty is needed to create a potential break-point immediately after the reinserts (or the marginal). Otherwise there can be no possibility to break here and this can cause the reinserts or the marginal to appear on the next page (which is often incorrect). However, if the nobreak flag is true, a `\nobreak` must be correct.

```
339 \ifnum \outputpenalty<\z@
340 \if@nobreak
341 \nobreak
342 \else
343 \addpenalty \interlinepenalty
344 \fi
345 \fi
346 \fi
347 \fi
```

```

348 }
349 </2ekernel | fltrace>

(End of definition for \output and \specialoutput.)

```

**\@testwrongwidth** **\f@depth** Test if the float box has the wrong width when trying to place it into some area. (Actually the test is for a conventional depth setting rather than for the width of the float. For that reason the box depth was explicitly tailored when the float was created).

```

350 <latexrelease>\IncludeInRelease{2015/01/01}%
351 <latexrelease>          {\@testwrongwidth}{float order in 2-column}%
352 <*2ekernel | latexrelease | fltrace>

353 \def\@testwrongwidth #1{%
354   \ifdim\dp#1=\f@depth
355   <*trace>
356     \fl@trace{\string#1
357               \ifdim\f@depth=\z@ single \else double \fi
358               column float -- ok}%
359   </trace>
360   \else
361     \global\@testtrue
362   <*trace>
363     \fl@trace{\string#1
364               \ifdim\f@depth=\z@ double \else single \fi
365               column float -- wrong}%
366   </trace>
367   \fi}%

```

Normally looking for single column floats, which have zero depth.

```

368 \let\f@depth\z@

369 </2ekernel | latexrelease | fltrace>
370 <latexrelease>\EndIncludeInRelease
371 <latexrelease>\IncludeInRelease{0000/00/00}%
372 <latexrelease>          {\@testwrongwidth}{float order in 2-column}%
373 <latexrelease>\let\@testwrongwidth\@undefined
374 <latexrelease>\let\f@depth\@undefined
375 <latexrelease>\EndIncludeInRelease

```

(End of definition for \@testwrongwidth and \f@depth.)

**\@docclearpage** This is a very much an emergency action, just dumping everything: footnotes first then floats. A more sophisticated version is needed; but even more urgent is a bug-free version (see, for example, pr/3528).

Also, it puts any left-over non-boxes (writes, specials, etc.) back after any float pages created: this is a very bad bug since, for example, a kludge insert will be in quite the wrong place and, worse, be irremovable and uncancelable.

All the remaining changes are replacing the double column defer list or inserting the extra test \@testwrongwidth{<box>} at suitable places. That is at places where a box is taken off the deferlist.

```

376 <latexrelease>\IncludeInRelease{2015/01/01}{\@docclearpage}%
377 <latexrelease>          {float order in 2-column}%
378 <*2ekernel | latexrelease>
379 \def \@docclearpage {%
380   \ifvoid\footins

```

```

381     \ifvbox\@kludgeins
382     {\setbox \@tempboxa \box \@kludgeins}%
383 < *trace>
384     \fl@trace {kludgeins box made void}%
385 < /trace>
386     \fi
387     \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
388     \setbox\@tempboxa\box\@cclv
389     \xdef\@deferlist{\@toplist\@botlist\@deferlist}%
390     \global \let \@toplist \@empty
391     \global \let \@botlist \@empty
392     \global \@colroom \@colht
393     \ifx \@currlist\@empty
394     \else
395         \@latexerror{Float(s) lost}\@ehb
396         \global \let \@currlist \@empty
397     \fi
398     \@makefcolumn\@deferlist
399     \@whiles\if@fcolmade \fi{\@opcol\@makefcolumn\@deferlist}%
400     \if@twocolumn
401         \if@firstcolumn
402             \xdef\@deferlist{\@dbltoplist\@deferlist}%
403             \global \let \@dbltoplist \@empty
404             \global \@colht \textheight
405             \begingroup
406                 \@dblfloatplacement
407                 \@makefcolumn\@deferlist
408                 \@whiles\if@fcolmade \fi{\@outputpage
409                     \@makefcolumn\@deferlist}%
410             \endgroup
411         \else
412             \vbox{}\clearpage
413         \fi
414     \fi

```

the next line is needed to avoid losing floats in certain circumstances a single call to the original `\doclearpage` will now no longer output all floats.

```

415     \ifx\@deferlist\@empty \else\clearpage \fi
416     \else
417         \setbox\@cclv\vbox{\box\@cclv\vfil}%
418         \@makecol\@opcol
419         \clearpage
420     \fi
421 }%
422 < /2kernel | latexrelease>
423 < latexrelease>\EndIncludeInRelease
424 < latexrelease>\IncludeInRelease{0000/00/00}{\@doclearpage}%
425 < latexrelease>                                     {float order in 2-column}%
426 < latexrelease>\def \@doclearpage {%
427 < latexrelease>     \ifvoid\footins

```

We empty any left over kludge insert box here; this is a temporary fix. It should perhaps be applied to one page of cleared floats, but who cares? The whole of this stuff needs

completely redoing for many such reasons.

```

428 <latexrelease>      \ifvbox\@kludgeins
429 <latexrelease>      {\setbox \@tempboxa \box \@kludgeins}%
430 <*trace>
431 <latexrelease>      \fl@trace {kludgeins box made void}%
432 </trace>
433 <latexrelease>      \fi
434 <latexrelease>      \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
435 <latexrelease>      \setbox\@tempboxa\box\@cclv
436 <latexrelease>      \xdef\@deferlist{\@toplist\@botlist\@deferlist}%

437 <latexrelease>      \global \let \@toplist \@empty
438 <latexrelease>      \global \let \@botlist \@empty
439 <latexrelease>      \global \@colroom \@colht
440 <latexrelease>      \ifx \@currlist\@empty
441 <latexrelease>      \else
442 <latexrelease>      \latexerr{Float(s) lost}\@ehb

443 <latexrelease>      \global \let \@currlist \@empty
444 <latexrelease>      \fi
445 <latexrelease>      \@makefcolumn\@deferlist
446 <latexrelease>      \@whilesw\if@fcolmade \fi
447 <latexrelease>      {\@opcol\@makefcolumn\@deferlist}%
448 <latexrelease>      \if@twocolumn
449 <latexrelease>      \if@firstcolumn
450 <latexrelease>      \xdef\@dbldeferlist{\@dbltoplist\@dbldeferlist}%

451 <latexrelease>      \global \let \@dbltoplist \@empty
452 <latexrelease>      \global \@colht \textheight
453 <latexrelease>      \begingroup
454 <latexrelease>      \dblfloatplacement
455 <latexrelease>      \@makefcolumn\@dbldeferlist
456 <latexrelease>      \@whilesw\if@fcolmade \fi
457 <latexrelease>      {\@outputpage\@makefcolumn\@dbldeferlist}%
458 <latexrelease>      \endgroup
459 <latexrelease>      \else
460 <latexrelease>      \vbox{}\clearpage
461 <latexrelease>      \fi
462 <latexrelease>      \fi
463 <latexrelease>      \else
464 <latexrelease>      \setbox\@cclv\vbox{\box\@cclv\vfil}%
465 <latexrelease>      \@makecol\@opcol
466 <latexrelease>      \clearpage
467 <latexrelease>      \fi
468 <latexrelease>      }%
469 <latexrelease>\EndIncludeInRelease

```

*(End of definition for \@doclearpage.)*

\@opcol Several changes in detail here.

```

470 <*2ekernel | fltrace>
471 \def \@opcol {%
472   \if@twocolumn

```

The funny-looking internal commands are interfacing with the new marks mechanism. We make sure (elsewhere) that those are always defined, even when we roll back, so here we add them unconditionally. This still need turning into a hook or config point eventually:

```

473 \expl@@@mark@update@dblcol@structures@@
474 \outputdblcol
475 \else
476 \expl@@@mark@update@singlecol@structures@@
477 \outputpage
478 <*trace>
479 \fl@trace{PAGE: one column (float? see above) page completed}%
480 </trace>

```

Not needed since it comes after `\@outputpage`:

```

481 % \global\@colht\textheight
482 \fi

```

These do not need to be done every time `\@opcol` is used: they should be grouped together since they all need to be done at the end of the non-special output routine, or at the end of a clearpage one.

```

483 \global \@mparbottom \z@ \global \@textfloatsheight \z@
484 \@floatplacement
485 }
486 </2ekernel | fltrace>

```

*(End of definition for \@opcol.)*

```

487 <*2ekernel | latexrelease>
488 <latexrelease>\IncludeInRelease{2025/06/01}%
489 <latexrelease> {\@makecol}{\@makecol adding hooks/sockets}%

```

`\@makecol` `\@makecol` is shortened a lot, basically all the hardwired code in the middle has moved into a socket.

```

490 \def \@makecol {%

```

A number of packages want to prepend code to `\@makecol`; this is the hook for that:

```

491 \UseHook {build/column/before}%

```

Save away box 255 as `\@outputbox` to make it available for further adjustments.

```

492 \setbox\@outputbox \box\@cclv

```

The only real addition is the next command which either does nothing or removes an infinite glue from the bottom of the `\@outputbox`.

```

493 \@outputbox@removebskip

```

Now a kernel hook for tagging that adjusts the content of `\@outputbox`, if necessary. At this point it just contains the material from the galley.

```

494 \UseTaggingSocket{build/column/outputbox}%

```

When this code is run any “here” floats in the `\@outputbox` are already handled, so we recycle their registers and put them back to the `\@freelist`.

```

495 \let\@elt\relax
496 \xdef\@freelist{\@freelist\@midlist}%
497 \global \let \@midlist \@empty

```

Here we have the configurable part. This socket is supposed to add floats, footnotes and stretchable vertical space as appropriate to the `\@outputbox`. It is used by packages such as `footmisc` to implement different layout, e.g., footnotes above or below bottom floats, etc.

```
498 \UseSocket {build/column/outputbox}%
```

Then we deal with any `\enlargethispage` or run the normal code to build a column.

```
499 \ifvbox\@kludgeins
500   \@make@specialcolbox
501 \else
502   \@make@normalcolbox
503 \fi
504 \global \maxdepth \@maxdepth
```

Finally, another hook for external packages or classes that want to augment or alter the output routine by appending to `\@makecol`.

```
505 \UseHook {build/column/after}%
506 }
```

*(End of definition for \@makecol.)*

`\@outputbox@depth` We need to know the depth of `\@outputbox` once in a while. Rather than using a temp dimen (as it was done in the past), we give it a proper register.

The value of this register is only correct inside of `\outputbox@append`, elsewhere you can't rely on it!

```
507 \newdimen\@outputbox@depth
```

*(End of definition for \@outputbox@depth.)*

`\@make@normalcolbox` Taken out of `\@makecol` for readability.

```
508 \def \@make@normalcolbox {%
509   \setbox\@outputbox \vbox to\@colht {%
510     \@texttop
511     \@outputbox@depth \dp\@outputbox
512     \unvbox \@outputbox
```

The `\vskip -\@outputbox@depth` ensures that the visible depth of the box does not affect the placement of anything on the page. Thus very deep pages will overprint the footer; but these should have been prevented by suitable settings of the maxdepths at appropriate times.

If `\@textbottom` ends with a box or rule of non-zero depth then this skip adjustment should be done again after it.

```
513   \vskip -\@outputbox@depth
514   \@textbottom
515 }%
516 }
```

*(End of definition for \@make@normalcolbox.)*

`\@make@specialcolbox` Make the colbox when `\enlargethispage` was used.

```
517 </2kernel | latexrelease>
518 <*2kernel | latexrelease | fltrace>
519 \def \@make@specialcolbox {%
520 <*trace>
```

```

521 \fl@trace{Kludgeins ht \the\ht\@kludgeins\space
522         dp \the\dp\@kludgeins\space
523         wd \the\wd\@kludgeins}%
524 
```

Note that in this case (the \*-version), the height of the `\@kludgeins` box is not used since its value is somewhat arbitrary: it need only be big enough to ensure that the page-break is not taken prematurely.

Here we calculate how much vertical space needs to be added in order to enable the column to fit into a box of size `\@colht` using the best information we have about the amount of shrink available (another thing which is known internally about a box, but cannot be accessed at the  $\TeX$  level!).

This needs  $\TeX$ 3 otherwise `\pageshrink` is zero anyway; it may not be exactly the figure we wish as it is the total available from the all the material collected before the page-break decision is made. It will, we think, always be an overestimate of the actual shrink in the box; therefore this should always force the shortest possible column with the possibility of an overfull box.

This should work for both flush- and ragged-bottom setting since it makes the contents no smaller than the size (`\@colht`) of the box into which they are put.

Their should perhaps be an upper limit, of 0pt?, on the extra space added to force shrinking.

```

528 \advance \@tempdima -\ht\@outputbox
529 \advance \@tempdima \pageshrink
530 (*trace)
531 \fl@trace {Natural ht of col: \the \ht\@outputbox}%
532 \fl@trace {\string \@colht: \the \@colht}%
533 \fl@trace {Pageshrink added: \the \pageshrink}%
534 \fl@trace {Hence, space added: \the \@tempdima}%
535 
```

For the unstarred version, the final size of the page is precisely specified. Therefore, at least for the flush-bottom case, we need to ensure that, visually, it has this size exactly.

Thus we calculate this size and set the material in a box of this size, which is then put into a box of size `\@colht` with `\vss` at the bottom.

```

541 \else
542 \advance \@tempdima -\ht\@kludgeins
543 (*trace)
544 \fl@trace {Natural ht of col: \the \ht\@outputbox}%
545 \fl@trace {\string \@colht: \the \@colht}%
546 \fl@trace {Extra size added: -\the \ht \@kludgeins}%
547 \fl@trace {Hence, height of inner box: \the \@tempdima}%
548 \fl@trace {Max? pageshrink available: \the \pageshrink}%
549 
```

This type of final packaging could be done always; this may simplify all of this page-makeup.

It is not necessary to set `\boxmaxdepth` here since the `\@outputbox` ends with glue.

```

550     \setbox \@outputbox \vbox to \@colht {%
551         \vbox to \@tempdima {%
552             \unvbox\@outputbox
553             \@textbottom}%
554         \vss}%
555     \fi
556     {\setbox \@tempboxa \box \@kludgeins}%
557     <*trace>
558     \fl@trace {kludgeins box made void}%
559     </trace>
560 }
561 </2ekernel | latexrelease | fltrace>
562 <*2ekernel | latexrelease>

```

*(End of definition for \@make@specialcolbox.)*

**\@outputbox@removebskip** This is really a bug fix for the kernel (from the 2.09 days) but one we only make by default in new documents that are using `\DocumentMetadata`. If `\raggedbottom` is in force, footnotes get attached to the main galley at a distance of `\footskip` on all pages except on those that are ended by `\newpage` or `\clearpage` where the `\vfil` from `\newpage` pushes the footnotes to the very bottom.

This is kind of a weird difference to a page ending with `\pagebreak`—in that case the page is also run short, but the footnotes are not pushed to the bottom.

In `footmisc` `\@outputbox@removebskip` is only applied when `footmisc` is called with an option specifying the footnote placement, i.e., not in the default case. In new documents we apply it always.

```

563 \def\@outputbox@removebskip{%

```

In some special circumstances the `\@outputbox` might be void. As `\@outputbox@append` below would change this, we handle this case by leaving it unchanged, because otherwise we can no longer detect that situation (needed, for example, in `ftnright`).

```

564     \ifvoid \@outputbox
565         \global\let\@outputbox@reinsertbskip\relax
566     \else

```

If it is not void then we drop the final skip at the end of `\@outputbox` provided there is one and it has a glue stretch order of 1 or more (i.e., contains a `fil` or `fill` part).

```

567     \@outputbox@append{%
568         \@tempskipa\lastskip
569         \ifnum \gluestretchorder\@tempskipa>\z@
570             \unskip

```

We also prepare for reinserting the skip we removed elsewhere on the page. As we have to do this globally, we also need to explicitly reset `\@outputbox@reinsertbskip` if we don't find any such glue.

**\@outputbox@reinsertbskip**

```

571         \xdef\@outputbox@reinsertbskip
572             {%

```

Everything is done inside `\@outputbox@append` so that a call to `\@outputbox@reinsertbskip` will update the box. If there are no footnotes and no bottom floats that still needs to be attached we first backup by the depth of the `\@outputbox` so that the skip we add starts from the baseline of the last line inside (if there is one). As it is a `fil`, `fill`, or `filll` glue this normally makes no differences, but if the box itself contains a fill skip of higher order our fill is ignored and text is pushed to the bottom of the page. In that case and without backing up first, the last line would not be with its baseline on the bottom, but slightly too high if it has characters with descenders.

```

573         \noexpand\@outputbox@append{%
574         \noexpand\@if@footnotes@TF
575         {}%
576         {%
577         \noexpand\@if@bottomfloats@TF
578         {}%
579         {\noexpand\@backup@outputbox@depth}%
580         }%
581         \vskip\the\@tempskipa}}%
582     \else
583         \global\let\@outputbox@reinsertbskip\relax
584     \fi
585 }%
586 \fi
587 }

```

We need a trivial top-level definition for `\@outputbox@reinsertbskip` in case the first page has no bottom glue and the command gets called.

```

588 \let \@outputbox@reinsertbskip \relax

```

*(End of definition for \@outputbox@removebskip and \@outputbox@reinsertbskip.)*

`\@backup@outputbox@depth`

In some places we have to make the depth of the `\@outputbox` zero by backing up by its current depth. This is done by `\@backup@outputbox@depth`. The macro can only be used inside of `\@outputbox@append` (or after you have manually set the `\@outputbox@depth` to the right value).

If the depth is zero, there is no point in doing anything, and if the depth is negative it must have been deliberately set to this value, so in this case we also do not back up and change it.

If it is positive we back up by the minimum of `\@outputbox@depth` and `\maxdepth`, i.e., if the depth is unusually large we do not perform a full backup.

```

589 \def\@backup@outputbox@depth{%
590 % \typeout{--> \@backup@outputbox@depth : \the \@outputbox@depth}%
591 \ifdim\@outputbox@depth>\z@
592     \vskip -%
593     \ifdim\@outputbox@depth>\maxdepth
594         \maxdepth
595     \else
596         \@outputbox@depth
597     \fi

```

After the skip was added the depth of the box will become zero but this is not immediately reflected in `\@outputbox@depth`. Thus, if there is further code in the same `\@outputbox@append` testing the register it would make a wrong conclusion. We therefore set it locally to zero.

```

598     \@outputbox@depth\z@
599     \fi
600 }

```

*(End of definition for \@backup@outputbox@depth.)*

## 2.2 The output routine configuration components

Here we provide the commands that are used to define code for the socket `build/column/outputbox`. The all manipulate the `\@outputbox` box in one way or another.

**\@outputbox@append** This general purpose command alters the `\@outputbox` box by appending material to it. As this is a box typesetting operation we make sure that the last line of the box reflects the true depth of the last line (in case that is needed later). We also expose the current depth of `\@outputbox` as `\@outputbox@depth` before unboxing so that its value can be used by `#1` if wanted.

```

601 \def\@outputbox@append #1{%
602     \setbox\@outputbox \vbox {%

```

This `\boxmaxdepth` setting is to ensure that deep footnotes do not overwrite the footer (on account of the negative skip added later): it should use `\@maxdepth` otherwise the change is pointless when there are footnotes.

But see also its use when combining floats.

```

603     \boxmaxdepth \@maxdepth
604     \@outputbox@depth\dp\@outputbox      % if needed in #1
605     \unvbox \@outputbox
606     #1%
607 }%
608 }

```

*(End of definition for \@outputbox@append.)*

**\@outputbox@appendfil** Append a `\vfil` to the `\@outputbox`. Depending on the plug in the `build/column/baselineattach` either from the bottom of the box or the baseline of the last line.

```

609 \def\@outputbox@appendfil{\@outputbox@append
610     {\UseSocket{build/column/baselineattach}\vfil}}

```

*(End of definition for \@outputbox@appendfil.)*

**\@outputbox@appendfootnotes** This command appends the footnotes to the `\@outputbox` (if there are any). If not, then it does nothing.

```

611 \def\@outputbox@appendfootnotes {%
612     \ifvoid\footins \else

```

Handling split footnotes need further work so this is for the moment just a dummy that does nothing. It might vanish and get replaced by a socket eventually.

```

613     \@makecol@handlesplitfootnotes

```

The following socket can be used to manipulate the material in `\footins` box, for example, if the footnotes are to be presented all together in a single paragraph. By default it does nothing.

```

614     \UseSocket{build/column/footnotes}%

```

Then the footnotes are appended:

```

615     \@outputbox@append{%

```

First we call a socket which controls whether or not we back up by the depth of the `\@outputbox` so that the skip that separates the footnotes from the text starts at the baseline of the last text line.

```
616      \UseSocket{build/column/baselineattach}%
617      \vskip \skip\footins
```

The next socket adjusts the tagging of the `\footins` box, if necessary.

```
618      \UseTaggingSocket{build/column/footins}%
619      \color@begingroup
620      \normalcolor
621      \footnoterule
```

Support for `pdfcolfoot`; eventually this can go once color is properly supported. The `csname` is constructed in case the command is not defined, i.e., the package not loaded.

```
622      \csname pdfcolfoot@current\endcsname
623      \unvbox \footins
624      \color@endgroup
625  }%
626 \fi
627 }
```

*(End of definition for \@outputbox@appendfootnotes.)*

`\@makecol@handlesplitfootnotes` For future extensions ...

```
628 \let \@makecol@handlesplitfootnotes \@empty
```

*(End of definition for \@makecol@handlesplitfootnotes.)*

`\@outputbox@attachfloats`  
`\@outputbox@attachtopfloats`  
`\@outputbox@attachbottomfloats`

Attaching top and bottom floats can usually be done in one go, but for special layouts we might want more control so we provide also separate commands.

The next command was called `\@combinefloats` in the past.

```
629 \def \@outputbox@attachfloats {%
630     \@outputbox@attachtopfloats
631     \@outputbox@attachbottomfloats
632 }
633 \def \@outputbox@attachtopfloats {%
634     \ifx \@toplist\@empty \else \@cflt \fi
635 }
```

Before we append the bottom floats we run the `build/column/baselineattach` so that the `\textfloatsep` is measured from the baseline if that is desired.

```
636 \def \@outputbox@attachbottomfloats {%
637     \ifx \@botlist\@empty \else
638         \@outputbox@append{\UseSocket{build/column/baselineattach}}%
639         \@cflb
640     \fi
641 }
```

*(End of definition for \@outputbox@attachfloats, \@outputbox@attachtopfloats, and \@outputbox@attachbottomfloats.)*

The next three conditionals might be useful when setting up running headers and footers so perhaps they should be change to CamelCase names. For now they are internal.

`\@if@flushbottom@TF` Test for `\flushbottom` (currently not used).

```
642 \def\@if@flushbottom@TF{%
643   \ifx\@textbottom\relax
644     \expandafter\@firstoftwo
645   \else
646     \expandafter\@secondoftwo
647   \fi
648 }
```

*(End of definition for \@if@flushbottom@TF.)*

`\@if@footnotes@TF` Test if footnotes are present on the current page or column and not yet added to the `\@outputbox`.

```
649 \def\@if@footnotes@TF{%
650   \ifvoid\footins
651     \expandafter\@secondoftwo
652   \else
653     \expandafter\@firstoftwo
654   \fi
655 }
```

*(End of definition for \@if@footnotes@TF.)*

`\@if@bottomfloats@TF` Test if bottom floats are around and not yet added to the `\@outputbox`.

```
656 \def\@if@bottomfloats@TF{%
657   \ifx \@botlist\@empty
658     \expandafter\@secondoftwo
659   \else
660     \expandafter\@firstoftwo
661   \fi
662 }
```

*(End of definition for \@if@bottomfloats@TF.)*

`build/column/outputbox (socket)` We have one socket that is supposed to augment the `\@outputbox` by attaching floats and footnotes with appropriate spacing.

```
663 \NewSocket{build/column/outputbox}{0}
```

The following plugs are available for this socket:

`space-footnotes-floats (plug)` After the galley text there is a vertical `\vfil` followed by any footnotes followed by the bottom floats, if any.

```
664 \NewSocketPlug {build/column/outputbox}{space-footnotes-floats} {%
665   \@if@footnotes@TF
666     {\@outputbox@appendfil}%
667   {\@if@bottomfloats@TF
668     {\@outputbox@appendfil}%
669     {\@outputbox@reinsertbskip}%
670   }%
671   \@outputbox@appendfootnotes
672   \@outputbox@attachfloats
673 }
```

`footnotes-space-floats` (*plug*) As before but the `\vfil` is between footnotes and floats.

```

674 \NewSocketPlug {build/column/outputbox}{footnotes-space-floats} {%
675   \@outputbox@appendfootnotes
676   \@if@bottomfloats@TF
677     {\@outputbox@appendfil}%
678     {\@outputbox@reinsertbskip}%
679   \@outputbox@attachfloats
680 }

```

`floats-space-footnotes` (*plug*) Floats immediately after the galley text and footnotes at the bottom.

```

681 \NewSocketPlug {build/column/outputbox}{floats-space-footnotes} {%
682   \@outputbox@attachfloats
683   \@if@footnotes@TF
684     {\@outputbox@appendfil}%
685     {\@outputbox@reinsertbskip}%
686   \@outputbox@appendfootnotes
687 }

```

`space-floats-footnotes` (*plug*) Both floats and footnotes are pushed to the bottom with footnotes last.<sup>64</sup>

```

688 \NewSocketPlug {build/column/outputbox}{space-floats-footnotes} {%
689   \@if@bottomfloats@TF
690     {\@outputbox@appendfil}%
691     {\@if@footnotes@TF
692       {\@outputbox@appendfil}%
693       {\@outputbox@reinsertbskip}}%
694   \@outputbox@attachfloats
695   \@outputbox@appendfootnotes
696 }

```

`floats-footnotes` (*plug*) All excess space has to be distributed across the existing glue on the page, e.g., within the text galley, the separation between blocks, etc. The order is text, floats, footnotes.

```

697 \NewSocketPlug {build/column/outputbox}{floats-footnotes} {%
698   \@outputbox@attachfloats
699   \@outputbox@appendfootnotes

```

We do reinsert the bottom skip from `\newpage` if it was taken out earlier. This is, strictly speaking, not necessary in most cases, but it is a `\vfil` while `\raggedbottom` is only generating `\vspace{0pt plus .0001fil}`, so if you have several `\vfil` on the page before the `\newpage` you would alter the space distribution if one is taken out.

```

700   \@outputbox@reinsertbskip
701 }

```

`footnotes-floats` (*plug*)

```

702 \NewSocketPlug {build/column/outputbox}{footnotes-floats} {%
703   \@outputbox@appendfootnotes
704   \@outputbox@attachfloats
705   \@outputbox@reinsertbskip
706 }

```

---

<sup>64</sup>There are two more permutations, but neither of them has ever been requested so they aren't set up by default — doing that in a class would be trivial though.

The `footnote-floats` plug implements the layout used by L<sup>A</sup>T<sub>E</sub>X but with the bottom skip bug corrected. This will be the default when `\DocumentMetadata` is used; it can be overwritten either through `footmisc` or by assigning any of the other plugs (or by coding yet another plug for the socket).

`footnotes-floats-legacy` (*plug*) This implements the 2.09 layout (including its bottom skip bug).

```
707 \NewSocketPlug {build/column/outputbox}{footnotes-floats-legacy} {%
```

In the legacy case we don't really want to take out the bottom skip, but rather than altering `\@outputbox@removebskip` in `\makecol` to do nothing, which we would then have to undo in every other layout, we immediately reinsert the dropped skip again.

In the legacy case there is, however, one other thing that needs doing: if there was a `\vfil` at the bottom of the page (e.g., from `\newpage`) and there are no footnotes, then we need to back up by the depth of the last line in the page box. Otherwise you might end up with incorrect alignment if there is a higher-order fill on the page (e.g., `\vfill`) that pushes the text material to the bottom, since in such cases the depth will not be taken into account by T<sub>E</sub>X.

This is done automatically by `\@outputbox@reinsertbskip` as long as there are no footnotes waiting to be placed. If there are footnotes, the operation is not done because by default the `\skip\footins` separation is measured from the bottom of the line not from the baseline. But if the user has asked to change this behavior we should honor it and that is done by putting the experimental socket `build/column/baselineattach` in which performs the backing up if desired. This should happen only if footnotes are actually present, so we test for this. Otherwise, there may be bottom floats and the `\textfloatsep` should be measured from the bottom of the last line and if not then any necessary back up is done by `\@outputbox@reinsertbskip`.

Note that after this code has backed up, the depth of `\@outputbox` will be zero as there is a skip at its bottom. So even if the same code is executed a second time (in `\@outputbox@reinsertbskip` or in `\@outputbox@appendfootnotes`) it will not alter the box further.

```
708 \if@footnotes@TF
709   {\@outputbox@append{%
710     \UseSocket{build/column/baselineattach}}}%
711   }{%
```

If there are no footnotes but there are bottom floats we execute the socket `build/column/baselineattach` so that `\textfloatsep` is measured from the baseline if that is being asked for.

```
712 \if@bottomfloats@TF
713   {\@outputbox@append{%
714     \UseSocket{build/column/baselineattach}}}%
715   }{%
716   }%
717 \@outputbox@reinsertbskip
718 \@outputbox@appendfootnotes
719 \@outputbox@attachfloats
720 }
```

The `footnote-floats-legacy` plug is the default used by L<sup>A</sup>T<sub>E</sub>X when `\DocumentMetadata` is not used; it can be overwritten either through `footmisc` or by assigning any of the other plugs (or by coding yet another plug for the socket).

```
721 \AssignSocketPlug {build/column/outputbox}{footnotes-floats-legacy}
```

**build/column/footnotes** (*socket*) The socket allowing the manipulation of `\footins` box (result needs to be moved back in there). Used when footnotes are reformatted into a single paragraph by the `para` option of `footmisc`. By default it does nothing.

```
722 \NewSocket{build/column/footnotes}{0}
```

**build/column/baselineattach** (*socket*) Socket that allows backing up by the depth of the outputbox (but not more than `\maxdepth` before attaching any footnotes or floats.

```
723 \NewSocket{build/column/baselineattach}{0}
```

**on** (*plug*)

```
724 \NewSocketPlug {build/column/baselineattach}{on} {%
```

We do nothing if the depth is not positive, and we never back up by more than `\maxdepth`.

```
725   \@backup@outputbox@depth
726 }
```

**off** (*plug*) The `off` plug is actually identical to the `noop` plug which is automatically made available; but offering that it under the name `off` makes the interface a bit nicer.

```
727 \NewSocketPlug {build/column/baselineattach}{off}{}

This feature is not turned on by default to preserve the behavior of old documents. With
new documents using \DocumentMetadata it may become the default.
```

```
728 \AssignSocketPlug {build/column/baselineattach}{off}
```

**build/page/before** (*hook*) Hooks at the start and end of `\@outputpage` for use by packages.

**build/page/after** (*hook*)

```
729 \NewMirroredHookPair{build/page/before}{build/page/after}
```

**build/page/reset** (*hook*) Hook in `\@outputpage` to reset special galley conventions within the output routine. L<sup>A</sup>T<sub>E</sub>X does a lot of resetting in front of this hook, so by default it is empty. They are not made part of the hook (which would have been possible) to ensure that the kernel resets always come first and can be overwritten without the need to apply hook rules unnecessarily.

```
730 \NewHook {build/page/reset}
```

**build/column/before** (*hook*) Hooks at the start and end of `\@makecol` for use by packages.

**build/column/after** (*hook*)

```
731 \NewMirroredHookPair{build/column/before}{build/column/after}

732 </2ekernel | latexrelease>
733 <latexrelease>\EndIncludeInRelease
734 <latexrelease>\IncludeInRelease{0000/00/00}%
735 <latexrelease>   {\@makecol}{\@makecol adding hooks/sockets}%
736 <latexrelease>
737 <latexrelease>\gdef \@makecol {%
738 <latexrelease>   \ifvoid\footins
739 <latexrelease>     \setbox\@outputbox \box\@cc1v
740 <latexrelease>   \else
741 <latexrelease>     \setbox\@outputbox \vbox {%
742 <latexrelease>       \boxmaxdepth \@maxdepth
743 <latexrelease>       \unvbox \@cc1v
744 <latexrelease>       \vskip \skip\footins
745 <latexrelease>       \color@begingroup
746 <latexrelease>       \normalcolor
```

```

747 <latexrelease> \footnoterule
748 <latexrelease> \unvbox \footins
749 <latexrelease> \color@endgroup
750 <latexrelease> }%
751 <latexrelease> \fi
752 <latexrelease> \let\@elt\relax
753 <latexrelease> \xdef\@freelist{\@freelist\@midlist}%
754 <latexrelease> \global \let \@midlist \@empty
755 <latexrelease> \@combinefloats
756 <latexrelease> \ifvbox\@kludgeins
757 <latexrelease> \@makespecialcolbox
758 <latexrelease> \else
759 <latexrelease> \setbox\@outputbox \vbox to\@colht {%
760 <latexrelease> \@texttop
761 <latexrelease> \dimen@ \dp\@outputbox
762 <latexrelease> \unvbox \@outputbox
763 <latexrelease> \vskip -\dimen@
764 <latexrelease> \@textbottom
765 <latexrelease> }%
766 <latexrelease> \fi
767 <latexrelease> \global \maxdepth \@maxdepth
768 <latexrelease> }
769 <latexrelease>
770 <latexrelease> \gdef \@makespecialcolbox {%
771 <latexrelease> \setbox\@outputbox \vbox {%
772 <latexrelease> \@texttop
773 <latexrelease> \dimen@ \dp\@outputbox
774 <latexrelease> \unvbox\@outputbox
775 <latexrelease> \vskip-\dimen@
776 <latexrelease> }%
777 <latexrelease> \@tempdima \@colht
778 <latexrelease> \ifdim \wd\@kludgeins>\z@
779 <latexrelease> \advance \@tempdima -\ht\@outputbox
780 <latexrelease> \advance \@tempdima \pageshrink
781 <latexrelease> \setbox\@outputbox \vbox to \@colht {%
782 <latexrelease> \unvbox\@outputbox
783 <latexrelease> \vskip \@tempdima
784 <latexrelease> \@textbottom
785 <latexrelease> }%
786 <latexrelease> \else
787 <latexrelease> \advance \@tempdima -\ht\@kludgeins
788 <latexrelease> \setbox \@outputbox \vbox to \@colht {%
789 <latexrelease> \vbox to \@tempdima {%
790 <latexrelease> \unvbox\@outputbox
791 <latexrelease> \@textbottom}%
792 <latexrelease> \vss}%
793 <latexrelease> \fi
794 <latexrelease> {\setbox \@tempboxa \box \@kludgeins}%
795 <latexrelease> }
796 <latexrelease>
797 <latexrelease> \let \@make@normalcolbox \@undefined
798 <latexrelease> \let \@make@specialcolbox \@undefined
799 <latexrelease> \let \@outputbox@removebskip \@undefined
800 <latexrelease> \let \@outputbox@reinsertbskip \@undefined

```

```

801 <latexrelease>
802 <latexrelease> \let \@outputbox@append \@undefined
803 <latexrelease> \let \@outputbox@appendfootnotes \@undefined
804 <latexrelease> \let \@outputbox@attachfloats \@undefined
805 <latexrelease> \let \@outputbox@attachtopfloats \@undefined
806 <latexrelease> \let \@outputbox@attachbottomfloats \@undefined
807 <latexrelease>

```

If we roll back we also need to restore this definition.

```

808 <latexrelease> \def \@combinefloats {%
809 <latexrelease> \ifx \@toplist\@empty \else \@cflt \fi
810 <latexrelease> \ifx \@botlist\@empty \else \@cflb \fi
811 <latexrelease> }
812 <latexrelease>
813 <latexrelease> \let \@ifflushbottom@TF \@undefined
814 <latexrelease> \let \@iffootnotes@TF \@undefined
815 <latexrelease> \let \@ifbottomfloats@TF \@undefined
816 <latexrelease>
817 <latexrelease>\EndIncludeInRelease
818 <*2ekernel>

```

**\@reinserts** This is the code which reinserts the inserts. It puts them all in one place; this can make some of them come out on the wrong page. It has been put into a separate macro to expedite experimentation.

```

819 \gdef \@reinserts{%
820 \ifvoid\footins\else\insert\footins{\unvbox\footins}\fi
821 \ifvbox\@kludgeins\insert\@kludgeins
822 {\unvbox\@kludgeins}\fi
823 }

```

*(End of definition for \@reinserts.)*

**\@texttop** These do nothing as a default.  
**\@textbottom**

```

824 \let \@texttop \relax
825 \let \@textbottom \relax

```

*(End of definition for \@texttop and \@textbottom.)*

**\@resetactivechars** RmS 93/09/06: added hook to protect against certain active characters in the output routine. Default checks are for active space and end-of-line.  
**\@activechar@info**

```

826 \def\@activechar@info #1{%
827 \@latex@info@no@line {Active #1 character found while
828 output routine is active
829 \MessageBreak
830 This may be a bug in a package file
831 you are using}%
832 }

```

Do not put any spaces in this next bit!

```

833 \begingroup
834 \obeylines\obeyspaces%
835 \catcode'\'\active%
836 \gdef\@resetactivechars{%
837 \def~M{\@activechar@info{EOL}\space}%
838 \def {\@activechar@info{space}\space}%

```

```

839 \let'\active@math@prime}%
840 \endgroup

```

(End of definition for \@resetactivechars and \@activechar@info.)

\@outputpage The \@color@hbox hooks here are used to avoid putting just a colour special into an otherwise empty box (in a header or footer). These boxes are often set to be completely empty and so adding a special produces a very underfull box message.

There has been extensive tidying up of the old code here; including the removal of a level of grouping.

The setting of \@protect immediately before the \@shipout is needed so that protected commands within \@writes are handled correctly.

Within shipout's vbox it is reset to its default value, \@relax.

Resetting it to its default value after the shipout has been completed (and the contents of the writes have been expanded) must be done by use of \@aftergroup. This is because it must have the value \@relax before macros coming from other uses of \@aftergroup within this box are expanded.

Putting this into the \@aftergroup token list does not affect the definition used in expanding the \@writes because the aftergroup token list is only constructed when popping the save-stack, it is not expanded until after the shipout is completed.

Question: should things from an \@aftergroup within the shipped out box be executed in the environment set up for the writes, or after it finishes?

A lot of this code has been in-lined to prevent mis-use of internal commands as hooks.

```

841 </2ekernel>
842 <latexrelease>\IncludeInRelease{2025/06/01}%
843 <latexrelease> {\@outputpage}{Use new mark mechanism}%
844 <*2ekernel|latexrelease>

```

Temp definition to vanish again when something is offered by the backend:

```

845 \protected \def \pdfannot@link@on@@ { \csname pdfannot_link_on:\endcsname }
846 \protected \def \pdfannot@link@off@@ { \csname pdfannot_link_off:\endcsname }
847 \def \@outputpage {%

```

We start with a hook available to packages that want to prepend code to \@outputpage.

```

848 \UseHook {build/page/before}%

```

The \@endgroup is put in by \@aftergroup.

```

849 \begingroup

```

Now all the set-up stuff has been in-lined for Frank.

First the stuff for the writes.

From here on was orginially in the command \@writesetup.

RmS 93/08/19: Redefined accents to allow changes in font encoding; but exactly why was this needed?

Reset \@language to the value current at \@begin{document}. In particular this ensures that a pagebreak in verbatim does not prevent hyphenation in the page head.

```

850 \language\document@default@language

```

Now a few more resets for things that may have changed during galley processing. We start with resetting some active character definitions.

```

851 \@resetactivechars

```

Then we deal with catcodes that might got altered by `verbatim` or similar environments and reset them to standard values.

```

852 \catcode'\z@
853 \catcode'\@ne
854 \catcode'\tw@
855 \catcode'\$thr@@
856 \catcode'\&4\relax
857 \catcode'\^M5\relax
858 \catcode'\#6\relax
859 \catcode'\^7\relax
860 \catcode'\_8\relax
861 \catcode'\ 10\relax
862 \catcode'\^^I10\relax
863 \@makeother\<%
864 \@makeother\>%
865 \@makeother\*%
866 \@makeother\.%
867 \@makeother\-%
868 \@makeother\/%
869 \@makeother\[%
870 \@makeother\]%
871 \@makeother\'%
872 \@makeother\'%
873 \@makeother\"%
874 \catcode'\~13\relax
875 \catcode'\%14\relax

```

If a page break happens between the start of a list and its first item then `@newlist` will be true and this will mess up any list that is used in the header or footer of the page. So we have to reset that flag.

```

876 \global\let\@@if@newlist\if@newlist
877 \global\@newlistfalse

```

This next hook replaces the following:

```

\let\-\@dischyph
\let\'\'@acci\let\'\'@accii\let\=\@acciii
\let\\\@normalcr
\let\par\@par %% 15 Sep 87 (this was once inside the box)

```

and it does more than they did; in particular it sets:

```

\parindent\z@
\parskip\z@skip
\everypar{}%
\leftskip\z@skip
\rightskip\z@skip
\parfillskip\@flushglue
\lineskip\normallineskip
\baselineskip\normalbaselineskip
\sloppy
878 \@parboxrestore

```

... to here was in the command `\@writsetup`.

Hook to allow adding resets local to the output routine processing, e.g., in `\write` or running headers/footers, for packages that set up special conventions in the main galley that should not leak into the page production just because a page break happens in the middle of such an environment.

```
879 \UseHook {build/page/reset}%
```

The following definition of `\protect` is the one active during the `\write` statement that migrate out of the `\shipout` box, so even though it is immediately changed below (inside `\shipout` it still has to be here!

```
880 \let \protect \noexpand
```

```
881 \shipout \vbox{%
```

Inside the `\shipout` box we have a different setting for `\protect`.

```
882 \set@typeset@protect
```

```
883 \aftergroup \endgroup
```

Once the `\shipout` boxes ends `\protect` is again `\noexpand` which is correct for any `\write` statements, but once they are processed we want to get back to the following setting:

```
884 \aftergroup \set@typeset@protect
```

Now the setup inside the shipped out box; this should contain all the stuff that could only affect typesetting; other stuff may need to be reset for the writes also.

From here ... was in the command `\@shipoutsetup`.

```
885 \if@specialpage
886 \global \@specialpagefalse
887 \@nameuse {ps@\@specialstyle}%
888 \fi
889 \if@twoside
890 \ifodd\count\z@
891 \let \@thehead \@oddhead
892 \let \@thefoot \@oddfoot
893 \let \@themargin \oddsidemargin
894 \else
895 \let \@thehead \@evenhead
896 \let \@thefoot \@evenfoot
897 \let \@themargin \evensidemargin
898 \fi
899 \fi
```

The rest was always inside the box.

RmS 91/08/15: added this line:

```
900 \reset@font
```

RmS 93/08/06 Added `\lineskiplimit=0pt` to guard against it being nonzero: e.g. by `\offinterlineskip` being in effect.

There are probably lots of other things that may need resetting.

```
901 \normalsize
```

Reset the space factors.

```
902 \normalsfcodes
```

Reset these here (previously reset separately for head and foot)

```

903 \let \label \@gobble@with@sphack@om
904 \let \index \@gobble@with@sphack@som
905 \let \glossary \@gobble@with@sphack@om

906 \baselineskip \z@skip
907 \lineskip \z@skip
908 \lineskiplimit \z@

```

... to here was in the command \@shipoutsetup.

```

909 \@beginndvi
910 \vskip \topmargin
911 \moveright\@themargin \vbox {%
912   \setbox\@tempboxa \vbox to\headheight {%
913     \vfil

```

Tagging socket that receives the header in its second argument to surround the header with appropriate tagging structures (first argument is unused). If tagging is disabled it returns the content of the second argument.

```

914   \pdfannot@link@off@@
915   \UseTaggingSocket{build/page/header}{}%
916   {
917     \color@hbox
918     \normalcolor
919     \hb@xt@ \textwidth {\@thehead }%
920     \color@endbox
921   }
922   \pdfannot@link@on@@
923 }
924 \dp \@tempboxa \z@
925 \box \@tempboxa
926 \vskip \headsep
927 \box \@outputbox
928 \baselineskip \footskip

```

Tagging socket that receives the footer in its second argument to surround the footer with appropriate tagging structures (first argument is unused). If tagging is disabled it returns the content of the second argument.

```

929   \pdfannot@link@off@@
930   \UseTaggingSocket{build/page/footer}{}%
931   {
932     \color@hbox
933     \normalcolor
934     \hb@xt@ \textwidth {\@thefoot }%
935     \color@endbox
936   }
937   \pdfannot@link@on@@
938 }
939 }

```

\endgroup now inserted by \aftergroup

Restore \if@newlist

```

940 \global \let \if@newlist \@if@newlist

941 \global \@colht \textheight
942 \stepcounter{page}%

```

Another hook for packages that want to append material to \@outputpage.

```

943 \UseHook {build/page/after}%
944 }
945 <latexrelease>\EndIncludeInRelease

946 <latexrelease>\IncludeInRelease{2017/04/15}%
947 <latexrelease> {\@outputpage}{Reset language for hyphenation}%
948 <latexrelease>\def\@outputpage{%
949 <latexrelease>\begingroup
950 <latexrelease> \let \protect \noexpand
951 <latexrelease> \language\document@default@language
952 <latexrelease> \@resetactivechars
953 <latexrelease> \global\let\@if@newlist\if@newlist
954 <latexrelease> \global\@newlistfalse
955 <latexrelease> \@parboxrestore
956 <latexrelease> \shipout \vbox{%
957 <latexrelease> \set@typeset@protect
958 <latexrelease> \aftergroup \endgroup
959 <latexrelease> \aftergroup \set@typeset@protect
960 <latexrelease> \if@specialpage
961 <latexrelease> \global\@specialpagefalse\@nameuse{ps@\@specialstyle}%
962 <latexrelease> \fi
963 <latexrelease> \if@twoside
964 <latexrelease> \ifodd\count\z@ \let\@thehead\@oddhead \let\@thefoot\@oddfoot
965 <latexrelease> \let\@themargin\oddsidemargin
966 <latexrelease> \else \let\@thehead\@evenhead
967 <latexrelease> \let\@thefoot\@evenfoot \let\@themargin\evensidemargin
968 <latexrelease> \fi
969 <latexrelease> \fi
970 <latexrelease> \reset@font
971 <latexrelease> \normalsize
972 <latexrelease> \normalsfcodes
973 <latexrelease> \let\label\@gobble
974 <latexrelease> \let\index\@gobble
975 <latexrelease> \let\glossary\@gobble
976 <latexrelease> \baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
977 <latexrelease> \@begindvi
978 <latexrelease> \vskip \topmargin
979 <latexrelease> \moveright\@themargin \vbox {%
980 <latexrelease> \setbox\@tempboxa \vbox to\headheight{%
981 <latexrelease> \vfil
982 <latexrelease> \color@hbox
983 <latexrelease> \normalcolor
984 <latexrelease> \hb@xt@\textwidth{\@thehead}%
985 <latexrelease> \color@endbox
986 <latexrelease> }%
987 <latexrelease> \dp\@tempboxa \z@
988 <latexrelease> \box\@tempboxa
989 <latexrelease> \vskip \headsep
990 <latexrelease> \box\@outputbox
991 <latexrelease> \baselineskip \footskip
992 <latexrelease> \color@hbox
993 <latexrelease> \normalcolor
994 <latexrelease> \hb@xt@\textwidth{\@thefoot}%

```

```

995 <latexrelease>      \color@endbox
996 <latexrelease>      }%
997 <latexrelease>      }%
998 <latexrelease>      \global\let\if@newlist\@if@newlist
999 <latexrelease>      \global \colht \textheight
1000 <latexrelease>      \stepcounter{page}%

```

It is now clear that this does something useful (in the old mark mechanism), thanks to Pieter van Oostrum pointing this out. It is needed because a float page is made without using TeX's page-builder; thus the output routine is never called so the marks are not updated.

```

1001 <latexrelease>      \let\firstmark\botmark
1002 <latexrelease>      }
1003 </2ekernel | latexrelease>
1004 <latexrelease>\EndIncludeInRelease

1005 <latexrelease>\IncludeInRelease{0000/00/00}%
1006 <latexrelease>      {\@outputpage}{Reset language for hyphenation}%
1007 <latexrelease>\def\@outputpage{%
1008 <latexrelease>\begingroup
1009 <latexrelease>      \let \protect \noexpand
1010 <latexrelease>      \resetactivechars
1011 <latexrelease>      \global\let\@if@newlist\if@newlist
1012 <latexrelease>      \global\@newlistfalse
1013 <latexrelease>      \@parboxrestore
1014 <latexrelease>      \shipout \vbox{%
1015 <latexrelease>          \set@typeset@protect
1016 <latexrelease>          \aftergroup \endgroup
1017 <latexrelease>          \aftergroup \set@typeset@protect
1018 <latexrelease>      \if@specialpage
1019 <latexrelease>          \global\@specialpagefalse\@nameuse{ps@\@specialstyle}%
1020 <latexrelease>      \fi
1021 <latexrelease>      \if@twoside
1022 <latexrelease>          \ifodd\count\z@
1023 <latexrelease>              \let\@thehead\@oddhead \let\@thefoot\@oddfoot
1024 <latexrelease>              \let\@themargin\oddsidemargin
1025 <latexrelease>          \else \let\@thehead\@evenhead
1026 <latexrelease>              \let\@thefoot\@evenfoot \let\@themargin\evensidemargin
1027 <latexrelease>      \fi
1028 <latexrelease>      \fi
1029 <latexrelease>      \reset@font
1030 <latexrelease>      \normalsize
1031 <latexrelease>      \normalsfcodes
1032 <latexrelease>      \let\label\@gobble
1033 <latexrelease>      \let\index\@gobble
1034 <latexrelease>      \let\glossary\@gobble
1035 <latexrelease>      \baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
1036 <latexrelease>      \@begindvi
1037 <latexrelease>      \vskip \topmargin
1038 <latexrelease>      \moveright\@themargin \vbox {%
1039 <latexrelease>          \setbox\@tempboxa \vbox to\headheight{%
1040 <latexrelease>              \vfil
1041 <latexrelease>              \color@hbox
1042 <latexrelease>              \normalcolor
1043 <latexrelease>              \hb@xt@\textwidth{\@thehead}%

```

```

1044 <latexrelease>      \color@endbox
1045 <latexrelease>      }%
1046 <latexrelease>      \dp\@tempboxa \z@
1047 <latexrelease>      \box\@tempboxa
1048 <latexrelease>      \vskip \headsep
1049 <latexrelease>      \box\@outputbox
1050 <latexrelease>      \baselineskip \footskip
1051 <latexrelease>      \color@hbox
1052 <latexrelease>      \normalcolor
1053 <latexrelease>      \hb@xt@\textwidth{\@thefoot}%
1054 <latexrelease>      \color@endbox
1055 <latexrelease>      }%
1056 <latexrelease>      }%
1057 <latexrelease>      \global\let\if@newlist\@if@newlist
1058 <latexrelease>      \global \@colht \textheight
1059 <latexrelease>      \stepcounter{page}%
1060 <latexrelease>      \let\firstmark\botmark
1061 <latexrelease>      }
1062 <latexrelease>\EndIncludeInRelease
1063 <*2ekernel>

```

*(End of definition for \@outputpage, \@shipoutsetup, and \@writesetup.)*

**\@beginndvi** This unboxes stuff that must appear before anything else in the .dvi file, then returns that box register to the free list and cancels itself.

The stuff in the box should not add any typeset material to the page.

```

1064 \def \@beginndvi{%
1065   \unvbox \@beginndvibox
1066   \global\let \@beginndvi \@empty
1067 }

```

*(End of definition for \@beginndvi.)*

## 2.2.1 Dealing with floats

**\@combinefloats** Old name for what is now called \@outputbox@attachfloats; kept to support legacy packages.

```

1068 \let \@combinefloats \@outputbox@attachfloats

```

*(End of definition for \@combinefloats.)*

**\@cflt** The \boxmaxdepth setting here was not made local to a box so was dangerous. It is needed only within the box made by \@cflt (and not normally even there), so it has been moved there; this also agrees with the original pseudocode.

**\@cflb**

```

1069 \def \@cflt{%
1070   \let \@elt \@comflelt
1071   \setbox\@tempboxa \vbox{}%
1072   \@toplist
1073   \setbox\@outputbox \vbox{%
1074     \boxmaxdepth \maxdepth
1075     \unvbox\@tempboxa
1076     \vskip -\floatsep
1077     \topfigrule
1078     \vskip \textfloatsep

```

```

1079             \unvbox\@outputbox
1080         }%
1081     \let\@elt\relax
1082     \xdef\@freelist{\@freelist\@toplist}%
1083     \global\let\@toplist\@empty
1084 }
1085 \def \@cflb {%
1086     \let\@elt\@comflelt
1087     \setbox\@tempboxa \vbox{}%
1088     \@botlist
1089     \setbox\@outputbox \vbox{%
1090         \unvbox\@outputbox
1091         \vskip \textfloatsep
1092         \botfigrule
1093         \unvbox\@tempboxa
1094         \vskip -\floatsep
1095     }%
1096     \let\@elt\relax
1097     \xdef\@freelist{\@freelist\@botlist}%
1098     \global \let \@botlist\@empty
1099 }

```

(End of definition for \@cflt and \@cflb.)

```

\@comflelt
\@comdblfelet
\@combinedblfloats
1100 \def\@comflelt#1{\setbox\@tempboxa
1101     \vbox{\unvbox\@tempboxa\box #1\vskip\floatsep}}
1102 \def\@comdblfelet#1{\setbox\@tempboxa
1103     \vbox{\unvbox\@tempboxa\box #1\vskip\dblfloatsep}}
1104 \def \@combinedblfloats{%
1105     \ifx \@dbltoplist \@empty
1106     \else
1107         \setbox\@tempboxa \vbox{}%
1108         \let \@elt \@comdblfelet
1109         \@dbltoplist
1110         \let \@elt \relax
1111         \xdef \@freelist {\@freelist\@dbltoplist}%
1112         \global\let \@dbltoplist \@empty
1113         \setbox\@outputbox \vbox to\textheight

```

The setting of \boxmaxdepth here has no effect since the \@outputbox should already have depth zero. Even so, it would have no effect on the layout of the page.

```

1114     {%
1115         \unvbox\@tempboxa\vskip-\dblfloatsep

```

Here we need different typesetting if the top float comes from \@topnewpage.

```

1116         \ifnum \@dbltopnum>\m@ne
1117         \dblfigrule
1118         \fi
1119         \vskip \dbltextfloatsep

```

If pdf links are present in the galley and those links get broken across pages they have to end up being on the same level of boxing (even if not actually in the same structure) due to some engine restrictions in pdfTeX and LuaTeX. We therefore unbox \@outputbox

here (which only contains a single `\hbox`) so that this case has the same boxing level as a normal twocolumn page without top floats.

```

1120     \unvbox\@outputbox
1121   }%
1122   \fi
1123 }
1124 \endkernel

```

(End of definition for `\@comflelt`, `\@comdbflelt`, and `\@combinedblfloats`.)

`\@startcolumn` We could combine (most of) these two into `\@startcol <list>`. Note that `\@xstartcol` was only used once (i.e. in `\@startcolumn`); it has therefore been removed. This is not quite as efficient but it now has the same structure as `\@startdblcolumn`.

The empty-list test has been moved to `\@tryfcolumn`.

```

1125 \endkernel | fltrace)
1126 \def \@startcolumn {%
1127   \global \@colroom \@colht
1128   \@tryfcolumn \@deferlist
1129   \if@fcolmade
1130 \trace)
1131   \fl@trace{PAGE: float \if@twocolumn column \else page \fi
1132             completed}%
1133 \endtrace)
1134 \else
1135   \begingroup
1136     \let \reserved@b \@deferlist
1137     \global \let \@deferlist \@empty
1138     \let \@elt \@scolelt
1139     \reserved@b
1140   \endgroup
1141   \fi
1142 }

```

This one does not need to set `\@colht`.

```

1143 \endkernel | fltrace)
1144 \latexrelease | fltrace)\IncludeInRelease{2015/01/01}%
1145 \latexrelease | fltrace) {\@startdblcolumn}{float order in 2-column}%
1146 \endkernel | latexrelease | fltrace)
1147 \def \@startdblcolumn {%
1148   \@tryfcolumn \@deferlist
1149   \if@fcolmade
1150 \fltrace) \fl@trace{PAGE: double float page completed}%
1151 \else
1152   \begingroup
1153     \let \reserved@b \@deferlist
1154     \global \let \@deferlist \@empty
1155     \let \@elt \@sdblcolelt
1156     \reserved@b
1157   \endgroup
1158   \fi
1159 }%
1160 \endkernel | latexrelease | fltrace)
1161 \latexrelease | fltrace)\EndIncludeInRelease

```

```

1162 <latexrelease | fltrace>\IncludeInRelease{0000/00/00}%
1163 <latexrelease | fltrace> {\@startdblcolumn}{float order in 2-column}%
1164 <latexrelease | fltrace>\def \@startdblcolumn {%

Not needed since this always comes after \@outputpage:

1165 <latexrelease | fltrace>% \global \@colht \textheight
1166 <latexrelease | fltrace> \@tryfcolumn \@dbldeferlist
1167 <latexrelease | fltrace> \if@fcolmade
1168 <*trace>
1169 <latexrelease | fltrace> \fl@trace{PAGE: double float page completed}%
1170 </trace>
1171 <latexrelease | fltrace> \else

1172 <latexrelease | fltrace> \begingroup
1173 <latexrelease | fltrace> \let \reserved@b \@dbldeferlist
1174 <latexrelease | fltrace> \global \let \@dbldeferlist \@empty
1175 <latexrelease | fltrace> \let \@elt \@sdblcolelt
1176 <latexrelease | fltrace> \reserved@b
1177 <latexrelease | fltrace> \endgroup
1178 <latexrelease | fltrace> \fi
1179 <latexrelease | fltrace>}%
1180 <latexrelease | fltrace>\EndIncludeInRelease
1181 <*2ekernel | fltrace>

```

*(End of definition for \@startcolumn and \@startdblcolumn.)*

**\@tryfcolumn** Now tests if its list is empty before any further exertion.

```

1182 \def \@tryfcolumn #1{%
1183   \global \@fcolmadefalse
1184   \ifx #1\@empty
1185   \else
1186   <*trace>
1187     \fl@trace{PAGE: try float \if@twocolumn column/page\else page\fi
1188               ---\string #1}%
1189     \fl@trace{----- \string #1: #1}%
1190   </trace>

1191   \xdef\@trylist{#1}%
1192   \global \let \@failedlist \@empty
1193   \begingroup
1194     \let \@elt \@xtryfc \@trylist
1195   \endgroup
1196   \if@fcolmade
1197     \@vtryfc #1%
1198   \fi
1199   \fi
1200 }
1201 </2ekernel | fltrace>

```

*(End of definition for \@tryfcolumn.)*

```

1202 <*2ekernel>

```

**\@scolelt**

```

1203 \def\@scolelt#1{\def\@currbox{#1}\@addtonextcol}

```

(End of definition for \@scolelt.)

\@sdblcolelt

1204 \def\@sdblcolelt#1{\def\@currbox{#1}\@addtodblcol}

(End of definition for \@sdblcolelt.)

\@vtryfc

1205 \def\@vtryfc #1{%  
1206 \global\setbox\@outputbox\vbox{%  
1207 \let\@elt\@wtryfc  
1208 \@flsucceed  
1209 \global\setbox\@outputbox \vbox to\@colht{%  
1210 \vskip \@fptop  
1211 \vskip -\@fpsep  
1212 \unvbox \@outputbox  
1213 \vskip \@fpbot}%  
1214 \let\@elt\relax  
1215 \xdef #1{\@failedlist\@flfail}%  
1216 \xdef\@freelist{\@freelist\@flsucceed}}

(End of definition for \@vtryfc.)

\@wtryfc

1217 \def\@wtryfc #1{%  
1218 \global\setbox\@outputbox\vbox{%  
1219 \unvbox\@outputbox  
1220 \vskip\@fpsep  
1221 \box #1}}

(End of definition for \@wtryfc.)

\@xtryfc

1222 </2ekernel>  
1223 <latexrelease>\IncludeInRelease{2015/01/01}{\@xtryfc}%  
1224 <latexrelease> {float order in 2-column}%  
1225 <\*2ekernel | latexrelease>  
1226 \def\@xtryfc #1{%  
1227 \@next\reserved@a\@trylist{}{}%  
1228 \@currtype \count #1%  
1229 \divide\@currtype\@xxxii  
1230 \multiply\@currtype\@xxxii  
1231 \@bitor \@currtype \@failedlist  
1232 \@testfp #1%  
1233 \@testwrongwidth #1%  
1234 \ifdim \ht #1>\@colht  
1235 \@testtrue  
1236 \fi  
1237 \if@test  
1238 \@cons\@failedlist #1%  
1239 \else  
1240 \@ytryfc #1%  
1241 \fi}%  
1242 </2ekernel | latexrelease>

```

1243 <latexrelease>\EndIncludeInRelease
1244 <latexrelease>\IncludeInRelease{0000/00/00}{\@xtryfc}%
1245 <latexrelease>                                     {float order in 2-column}%
1246 <latexrelease>\def\@xtryfc #1{%
1247 <latexrelease>  \@next\reserved@a\@trylist{}{}%
1248 <latexrelease>  \@currtype \count #1%
1249 <latexrelease>  \divide\@currtype\@xxxii
1250 <latexrelease>  \multiply\@currtype\@xxxii
1251 <latexrelease>  \@bitor \@currtype \@failedlist
1252 <latexrelease>  \@testfp #1%
1253 <latexrelease>  \ifdim \ht #1>\@colht
1254 <latexrelease>    \@testtrue
1255 <latexrelease>  \fi
1256 <latexrelease>  \if@test
1257 <latexrelease>    \@cons\@failedlist #1%
1258 <latexrelease>  \else
1259 <latexrelease>    \@ytryfc #1%
1260 <latexrelease>  \fi}%
1261 <latexrelease>\EndIncludeInRelease
1262 <*2ekernel>

```

(End of definition for \@xtryfc.)

\@ytryfc

```

1263 \def\@ytryfc #1{%
1264   \begingroup
1265   \gdef\@flsucceed{\@elt #1}%
1266   \global\let\@flfail\@empty
1267   \@tempdima\ht #1%
1268   \let\@elt\@ztryfc
1269   \@trylist
1270   \ifdim \@tempdima >\@fpmin
1271     \global\@fcolmadetrue
1272   \else
1273     \@cons\@failedlist #1%
1274   \fi
1275   \endgroup
1276   \if@fcolmade
1277     \let\@elt\@gobble
1278   \fi}

```

(End of definition for \@ytryfc.)

\@ztryfc

```

1279 </2ekernel>
1280 <latexrelease>\IncludeInRelease{2015/01/01}{\@ztryfc}%
1281 <latexrelease>                                     {float order in 2-column}%
1282 <*2ekernel | latexrelease>
1283 \def\@ztryfc #1{%
1284   \@tempcnta\count #1%
1285   \divide\@tempcnta\@xxxii
1286   \multiply\@tempcnta\@xxxii
1287   \@bitor \@tempcnta {\@failedlist \@flfail}%
1288   \@testfp #1%

```

```

not in fixfloats?
1289 \testwrongwidth #1%
1290 \@tempdimb\@tempdima
1291 \advance\@tempdimb\ht #1%
1292 \advance\@tempdimb\@fpsep
1293 \ifdim \@tempdimb >\@colht
1294 \testtrue
1295 \fi
1296 \if@test
1297 \@cons\@flfail #1%
1298 \else
1299 \@cons\@flsucceed #1%
1300 \@tempdima\@tempdimb
1301 \fi}%
1302 </2ekernel | latexrelease>
1303 <latexrelease>\EndIncludeInRelease
1304 <latexrelease>\IncludeInRelease{0000/00/00}{\ztryfc}%
1305 <latexrelease> {float order in 2-column}%
1306 <latexrelease>\def\@ztryfc #1{%
1307 <latexrelease> \@tempcnta \count#1%
1308 <latexrelease> \divide\@tempcnta\@xxxii
1309 <latexrelease> \multiply\@tempcnta\@xxxii
1310 <latexrelease> \@bitor \@tempcnta {\@failedlist \@flfail}%
1311 <latexrelease> \testfp #1%
1312 <latexrelease> \@tempdimb\@tempdima
1313 <latexrelease> \advance\@tempdimb \ht#1%
1314 <latexrelease> \advance\@tempdimb\@fpsep
1315 <latexrelease> \ifdim \@tempdimb >\@colht
1316 <latexrelease> \testtrue
1317 <latexrelease> \fi
1318 <latexrelease> \if@test
1319 <latexrelease> \@cons\@flfail #1%
1320 <latexrelease> \else
1321 <latexrelease> \@cons\@flsucceed #1%
1322 <latexrelease> \@tempdima\@tempdimb
1323 <latexrelease> \fi}%
1324 <latexrelease>\EndIncludeInRelease

```

*(End of definition for \@ztryfc.)*

The major changes for float suppression and the changes to the float mechanism to make it conform to the documentation are in these next macros.

\@addtobot Lots of changes.

```

1325 <*2ekernel | fltrace>
1326 \def \@addtobot {%
1327 <*trace>
1328 \fl@trace{***Start addtobot}%
1329 </trace>
1330 \@getfpsbit 4\relax
1331 <*trace>
1332 \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi bot:
1333 \the \@fpstype}%
1334 </trace>

```

```

1335 \ifodd \@tempcnta
1336 \@flsetnum \@botnum
1337 \ifnum \@botnum>\z@
1338 \@tempswafalse
1339 \@flcheckspace \@botroom \@botlist
1340 \if@tempswa

1341 % \global \maxdepth \z@
1342 \@flupdates \@botnum \@botroom \@botlist
1343 < *trace >
1344 \fl@trace{colroom (after-bot) = \the \@colroom}%
1345 \fl@trace{colnum (after-bot) = \the \@colnum}%
1346 \fl@trace{botnum (after-bot) = \the \@botnum}%
1347 \fl@trace{***Success: bot}%
1348 < /trace >
1349 \inserttrue
1350 \fi
1351 < *trace >
1352 \else
1353 \fl@trace{Fail: botnum = \the \@botnum:
1354 fpstype \the \@fpstype=ORD?}%
1355 \ifnum \@fpstype<\sixt@n
1356 \fl@trace{ERROR: !b float not successful (addtobot)}%
1357 \fi
1358 < /trace >
1359 \fi
1360 \fi
1361 }

```

(End of definition for \@addtobot.)

\@addtotoporbot Lots of changes.

```

1362 \def \@addtotoporbot {%
1363 < *trace >
1364 \fl@trace{***Start addtotoporbot}%
1365 < /trace >
1366 \@getfpsbit \tw@
1367 < *trace >
1368 \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi top:
1369 \the \@fpstype}%
1370 < /trace >
1371 \ifodd \@tempcnta
1372 \@flsetnum \@topnum
1373 \ifnum \@topnum>\z@
1374 \@tempswafalse
1375 \@flcheckspace \@toproom \@toplist
1376 \if@tempswa
1377 \@bitor\@currtype{\@midlist\@botlist}%
1378 < *trace >
1379 \fl@trace{(mid+bot)list: \@midlist, \@botlist:
1380 (addtotoporbot-before)}%
1381 < /trace >
1382 \if@test
1383 < *trace >

```

```

1384         \fl@trace{type already on list: mid or bot---sent to addtobot}}%
1385     \end{trace}
1386     \else
1387         \@flupdates \@topnum \@toproom \@toplist
1388     \end{trace}
1389         \fl@trace{colroom (after-top) = \the \@colroom}%
1390         \fl@trace{colnum (after-top) = \the \@colnum}%
1391         \fl@trace{topnum (after-top) = \the \@topnum}%
1392         \fl@trace{***Success: top}%
1393     \end{trace}
1394     \@inserttrue
1395     \fi
1396 \fi
1397 \end{trace}
1398     \else
1399         \fl@trace{Fail: topnum = \the \@topnum: fpstype
1400                                     \the \@fpstype=ORD?}%
1401         \ifnum \@fpstype<\sixt@@n
1402             \fl@trace{ERROR: !t float not successful (addtotoporbot)}%
1403         \fi
1404     \end{trace}
1405     \fi
1406 \fi
1407 \if@insert
1408     \else
1409     \end{trace}
1410         \fl@trace{sent to addtobot (addtotoporbot)}%
1411     \end{trace}
1412     \@addtobot
1413 \fi
1414 }
1415 \end{2ekernel} \end{fltrace}

```

(End of definition for \@addtotoporbot.)

\@addtocurcol Lots of changes.

```

1416 \<latexrelease | fltrace | flafter>\IncludeInRelease{2025/06/01}%
1417 \<latexrelease | fltrace | flafter> {\@addtocurcol}{float order in 2-column}%
1418 \<*2ekernel | latexrelease | fltrace | flafter>
1419 \def \@addtocurcol {%
1420 \end{trace}
1421     \fl@trace{***Start addtocurcol}%
1422 \end{trace}
1423     \@insertfalse
1424     \@setfloattypecounts
1425     \ifnum \@fpstype=8
1426     \end{trace}
1427         \fl@trace{fpstype !p only (addtocurcol): \the \@fpstype = 8?}%
1428     \end{trace}
1429     \else
1430         \ifnum \@fpstype=24
1431     \end{trace}
1432         \fl@trace{fpstype p only (addtocurcol): \the \@fpstype = 24?}%
1433     \end{trace}

```

```

1434     \else
1435     \@flsettextmin

```

This is a new adjustment which is quite a major change in functionality; but it implements the documentation. Note that `\@reqcolroom` will include the whole of the page-so-far, and hence includes `\@textfloatsheight` of floats, so before comparing it with `\@textmin`, we add this to `\@textmin` also.

```

1436 \<trace>
1437     \fl@trace{textfloatsheight (before) = \the \@textfloatsheight}%
1438 \</trace>
1439     \advance \@textmin \@textfloatsheight
1440     \@reqcolroom \@pageht

```

This line must be removed since `\@specialoutput` changed.

```

1441 %     \advance \@reqcolroom \@pagedp
1442 \<trace>
1443     \fl@trace{textmin + textfloatsheight: \the \@textmin}%
1444     \fl@trace{page-so-far: \the \@reqcolroom}%
1445 \</trace>
1446     \ifdim \@textmin>\@reqcolroom
1447     \@reqcolroom \@textmin
1448 \<trace>
1449     \fl@trace{ORD? textmin being used}%
1450 \</trace>
1451 \fi
1452     \advance \@reqcolroom \ht\@currbox

```

We save the current value of `\@reqcolroom` so that we can return to this value later, in case a test fails that may have added something to it.

```

1453     \saved@reqcolroom \@reqcolroom
1454 \<trace>
1455     \fl@trace{float size = \the \ht \@currbox (addtocurcol)}%
1456     \fl@trace{colroom = \the \@colroom (addtocurcol)}%
1457     \fl@trace{reqcolroom = \the \@reqcolroom (addtocurcol)}%
1458 \</trace>
1459     \ifdim \@colroom>\@reqcolroom
1460     \@flsetnum \@colnum
1461     \ifnum \@colnum>\z@
1462     \@bitor\@currtype\@deferlist

```

We need to defer the float also if its width doesn't fit.

```

1463     \@testwrongwidth\@currbox
1464 \<trace>
1465     \fl@trace{deferlist: \@deferlist: (addtocurcol-before)}%
1466 \</trace>
1467     \if@test
1468 \<trace>
1469     \fl@trace{type already on list: defer (addtocurcol)}%
1470 \</trace>
1471     \else
1472     \@bitor\@currtype\@botlist
1473 \<trace>
1474     \fl@trace{botlist: \@botlist: (addtocurcol-before)}%
1475 \</trace>
1476     \if@test

```

```

1477 <*trace>
1478         \fl@trace{type already on list: bot---sent to addtobot}%
1479 </trace>
1480         \@addtobot
1481     \else
1482 <*trace>
1483         \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi
1484             here: \the \@fpstype}%
1485 </trace>
1486         \ifodd \count\@currbox
1487             \advance \@reqcolroom \intextsep
1488             \ifdim \@colroom>\@reqcolroom
1489                 \global \advance \@colnum \m@ne
1490                 \global \advance \@textfloatsheight \ht\@currbox

```

This may sometimes give an overestimate.

```

1491         \global \advance \@textfloatsheight 2\intextsep
1492         \@cons \@midlist \@currbox
1493 <*trace>
1494         \fl@trace{***Success: here}%
1495         \fl@trace{textfloatsheight (after-here) =
1496             \the \@textfloatsheight}%
1497         \fl@trace{colnum (after-here) = \the \@colnum}%
1498 </trace>

```

CHANGE TO \@addtocurcol:

\penalty\z@ changed to \penalty\interlinepenalty so \samepage works properly with figure and table environments. (Changed 23 Oct 86)

There is also an \addpenalty\interlinepenalty above.

Although it is best to use \addvspace in case two h floats come together, this makes other spacing more difficult to adjust; whereas if a user specifies two h floats together then they can more easily get the spacing correct by ad hoc commands.

It is necessary to adjust for the addition of \parskip here in case the float is added between paragraphs (i.e. when in vertical mode).

If the nobreak switch is true we need to reset it and clear \everypar since the float may not reset the flag and cannot reset the \everypar globally.

Typesetting starts here (we are in vertical mode).

```

1499         \if@nobreak
1500             \nobreak
1501             \@nobreakfalse
1502             \everypar{}%
1503         \else
1504             \addpenalty \interlinepenalty
1505             \fi
1506             \vskip \intextsep
1507             \box\@currbox
1508             \penalty\interlinepenalty
1509             \vskip\intextsep
1510             \ifnum\outputpenalty <-\@Mii \vskip -\parskip\fi

```

Typesetting ends here.

```

1511         \outputpenalty \z@
1512         \@inserttrue
1513 <*trace>

```

```

1514             \else
1515                 \fl@trace{Fail---no room at 2nd test of colroom
1516                     (addtocurcol \string\intextsep)}%
1517             </trace>
1518             \fi
1519         \fi
1520         \if@insert
1521         \else
Next set of docstrip guards are a bit weird, essentially \@addtotoporbot ends up inside
the kernel and the fltrace package and \@addtobot shows up in the flafter package.
Guess that could have been done a bit more obvious :-)
1522 <*2ekernel | fltrace | latexrelease>
1523 <*trace>
1524             \fl@trace{not here: sent to addtotoporbot}%
1525 </trace>
1526             \@addtotoporbot
1527 </2ekernel | fltrace | latexrelease>
1528 <!*2ekernel&!fltrace&!latexrelease>
1529 <*trace>
1530             \fl@trace{not here: sent to addtobot}%
1531 </trace>
1532             \@addtobot
1533 </!2ekernel&!fltrace&!latexrelease>
1534             \fi
1535         \fi
1536     \fi
1537 <*trace>
1538     \else
1539         \fl@trace{Fail: colnum = \the \@colnum:
1540             fpstype \the \@fpstype=ORD?}%
1541         \ifnum \@fpstype<\sist@n
1542             \fl@trace{ERROR: BANG float not successful (addtocurcol)}%
1543         \fi
1544     </trace>
1545     \fi
1546 <*trace>
1547     \else
1548         \fl@trace{Fail---no room: fl box ht: \the \ht \@currbox
1549             (addtocurcol)}%
1550 </trace>
1551     \fi
1552     \fi
1553     \fi
1554     \if@insert
1555     \else
1556         \@resetfyps
1557 <*trace>
1558         \fl@trace{put on deferlist (addtocurcol)}%
1559 </trace>
1560         \@cons\@deferlist\@currbox
1561 <*trace>
1562         \fl@trace{deferlist: \@deferlist: (addtocurcol-after)}%
1563 </trace>

```

```

1564 \fi
1565 }%
1566 </2ekernel | latexrelease | fltrace | flafter>
1567 <latexrelease | fltrace | flafter>\EndIncludeInRelease

The rollback code is rather complicated as it has to account for the fact that we roll back
not just the kernel but also the packages flafter and fltrace.

1568 <latexrelease | fltrace | flafter>\IncludeInRelease{2015/01/01}%
1569 <latexrelease | fltrace | flafter> {\@addtocurcol}{float order in 2-column}%
1570 <latexrelease | fltrace | flafter>\def \@addtocurcol {%
1571 *trace>
1572 <latexrelease | fltrace | flafter> \fl@trace{***Start addtocurcol}%
1573 </trace>
1574 <latexrelease | fltrace | flafter> \@insertfalse
1575 <latexrelease | fltrace | flafter> \@setfloattyperecounts
1576 <latexrelease | fltrace | flafter> \ifnum \@fpstype=8
1577 *trace>
1578 <latexrelease | fltrace | flafter> \fl@trace{fpstype !p only (addtocurcol): \the \@fpstype = 8?}%
1579 </trace>
1580 <latexrelease | fltrace | flafter> \else
1581 <latexrelease | fltrace | flafter> \ifnum \@fpstype=24
1582 *trace>
1583 <latexrelease | fltrace | flafter> \fl@trace{fpstype p only (addtocurcol): \the \@fpstype = 24?}%
1584 </trace>
1585 <latexrelease | fltrace | flafter> \else
1586 <latexrelease | fltrace | flafter> \@flsettextmin
1587 *trace>
1588 <latexrelease | fltrace | flafter> \fl@trace{textfloatsheight (before) = \the \@textfloatsheight}%
1589 </trace>
1590 <latexrelease | fltrace | flafter> \advance \@textmin \@textfloatsheight
1591 <latexrelease | fltrace | flafter> \@reqcolroom \@pageht
1592 *trace>
1593 <latexrelease | fltrace | flafter> \fl@trace{textmin + textfloatsheight: \the \@textmin}%
1594 <latexrelease | fltrace | flafter> \fl@trace{page-so-far: \the \@reqcolroom}%
1595 </trace>
1596 <latexrelease | fltrace | flafter> \ifdim \@textmin>\@reqcolroom
1597 <latexrelease | fltrace | flafter> \@reqcolroom \@textmin
1598 *trace>
1599 <latexrelease | fltrace | flafter> \fl@trace{ORD? textmin being used}%
1600 </trace>
1601 <latexrelease | fltrace | flafter> \fi
1602 <latexrelease | fltrace | flafter> \advance \@reqcolroom \ht\@currbox
1603 *trace>
1604 <latexrelease | fltrace | flafter> \fl@trace{float size = \the \ht \@currbox (addtocurcol)}%
1605 <latexrelease | fltrace | flafter> \fl@trace{colroom = \the \@colroom (addtocurcol)}%
1606 <latexrelease | fltrace | flafter> \fl@trace{reqcolroom = \the \@reqcolroom (addtocurcol)}%
1607 </trace>
1608 <latexrelease | fltrace | flafter> \ifdim \@colroom>\@reqcolroom
1609 <latexrelease | fltrace | flafter> \@flsetnum \@colnum
1610 <latexrelease | fltrace | flafter> \ifnum \@colnum>z@
1611 <latexrelease | fltrace | flafter> \@bitor\@currtype\@deferlist
1612 <latexrelease | fltrace | flafter> \@testwrongwidth\@currbox
1613 *trace>
1614 <latexrelease | fltrace | flafter> \fl@trace{deferlist: \@deferlist: (addtocurcol-before)}%

```

```

1615 </trace>
1616 <latexrelease | fltrace | flafter>
1617 <*trace>
1618 <latexrelease | fltrace | flafter>
1619 </trace>
1620 <latexrelease | fltrace | flafter>
1621 <latexrelease | fltrace | flafter>
1622 <*trace>
1623 <latexrelease | fltrace | flafter>
1624 </trace>
1625 <latexrelease | fltrace | flafter>
1626 <*trace>
1627 <latexrelease | fltrace | flafter>
1628 </trace>
1629 <latexrelease | fltrace | flafter>
1630 <latexrelease | fltrace | flafter>
1631 <*trace>
1632 <latexrelease | fltrace | flafter>
1633 <latexrelease | fltrace | flafter>
1634 </trace>
1635 <latexrelease | fltrace | flafter>
1636 <latexrelease | fltrace | flafter>
1637 <latexrelease | fltrace | flafter>
1638 <latexrelease | fltrace | flafter>
1639 <latexrelease | fltrace | flafter>
1640 <latexrelease | fltrace | flafter>
1641 <latexrelease | fltrace | flafter>
1642 <*trace>
1643 <latexrelease | fltrace | flafter>
1644 <latexrelease | fltrace | flafter>
1645 <latexrelease | fltrace | flafter>
1646 <latexrelease | fltrace | flafter>
1647 </trace>
1648 <latexrelease | fltrace | flafter>
1649 <latexrelease | fltrace | flafter>
1650 <latexrelease | fltrace | flafter>
1651 <latexrelease | fltrace | flafter>
1652 <latexrelease | fltrace | flafter>
1653 <latexrelease | fltrace | flafter>
1654 <latexrelease | fltrace | flafter>
1655 <latexrelease | fltrace | flafter>
1656 <latexrelease | fltrace | flafter>
1657 <latexrelease | fltrace | flafter>
1658 <latexrelease | fltrace | flafter>
1659 <latexrelease | fltrace | flafter>
1660 <latexrelease | fltrace | flafter>
1661 <latexrelease | fltrace | flafter>
1662 <*trace>
1663 <latexrelease | fltrace | flafter>
1664 <latexrelease | fltrace | flafter>
1665 <latexrelease | fltrace | flafter>
1666 </trace>
1667 <latexrelease | fltrace | flafter>
1668 <latexrelease | fltrace | flafter>

```

```

\if@test
    \fl@trace{type already on list: defer (addtocurcol)}%
\else
    \@bitor\@currtype\@botlist
\fl@trace{botlist: \@botlist: (addtocurcol-before)}%

\if@test
    \fl@trace{type already on list: bot---sent to addtobot}

    \@addtobot
\else
    \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi
        here: \the \@fpstype}%

    \ifodd \count\@currbox
        \advance \@reqcolroom \intextsep
        \ifdim \@colroom>\@reqcolroom
            \global \advance \@colnum \m@ne
            \global \advance \@textfloatsheight \ht\@currbox
            \global \advance \@textfloatsheight 2\intextsep
            \@cons \@midlist \@currbox

        \fl@trace{***Success: here}%
        \fl@trace{textfloatsheight (after-here) =
            \the \@textfloatsheight}%
        \fl@trace{colnum (after-here) = \the \@colnum}%

        \if@nobreak
            \nobreak
            \@nobreakfalse
            \everypar{}%
        \else
            \addpenalty \interlinepenalty
        \fi
        \vskip \intextsep
        \box\@currbox
        \penalty\interlinepenalty
        \vskip\intextsep
        \ifnum\outputpenalty <-\@Mii \vskip -\parskip\fi
        \outputpenalty \z@
        \@inserttrue

    \else
        \fl@trace{Fail---no room at 2nd test of colroom
            (addtocorcol \string\intextsep)}%

    \fi
\fi

```

```

1669 <latexrelease | fltrace | flafter>          \if@insert
1670 <latexrelease | fltrace | flafter>          \else
1671 <*trace>
1672 <fltrace | latexrelease>                    \fl@trace{not here: sent to addtotoporbot}%
1673 </trace>
1674 <fltrace | latexrelease>                    \@addtotoporbot
1675 <*trace>
1676 <flafter>          \fl@trace{not here: sent to addtobot}%
1677 </trace>
1678 <flafter>          \@addtobot
1679 <latexrelease | fltrace | flafter>          \fi
1680 <latexrelease | fltrace | flafter>          \fi
1681 <latexrelease | fltrace | flafter>          \fi
1682 <*trace>
1683 <latexrelease | fltrace | flafter>          \else
1684 <latexrelease | fltrace | flafter>          \fl@trace{Fail: colnum = \the \@colnum:
1685 <latexrelease | fltrace | flafter>          fpstype \the \@fpstype=ORD?}%
1686 <latexrelease | fltrace | flafter>          \ifnum \@fpstype<\sist@n
1687 <latexrelease | fltrace | flafter>          \fl@trace{ERROR: BANG float not successful (addtocurcol)}
1688 <latexrelease | fltrace | flafter>          \fi
1689 </trace>
1690 <latexrelease | fltrace | flafter>          \fi
1691 <*trace>
1692 <latexrelease | fltrace | flafter>          \else
1693 <latexrelease | fltrace | flafter>          \fl@trace{Fail---no room: fl box ht: \the \ht \@currbox
1694 <latexrelease | fltrace | flafter>          (addtocurcol)}}%
1695 </trace>
1696 <latexrelease | fltrace | flafter>          \fi
1697 <latexrelease | fltrace | flafter>          \fi
1698 <latexrelease | fltrace | flafter>          \fi
1699 <latexrelease | fltrace | flafter>          \if@insert
1700 <latexrelease | fltrace | flafter>          \else
1701 <latexrelease | fltrace | flafter>          \@resetfps
1702 <*trace>
1703 <latexrelease | fltrace | flafter>          \fl@trace{put on deferlist (addtocurcol)}}%
1704 </trace>
1705 <latexrelease | fltrace | flafter>          \@cons\@deferlist\@currbox
1706 <*trace>
1707 <latexrelease | fltrace | flafter>          \fl@trace{deferlist: \@deferlist: (addtocurcol-after)}}%
1708 </trace>
1709 <latexrelease | fltrace | flafter>          \fi
1710 <latexrelease | fltrace | flafter>}}%
1711 <latexrelease | fltrace | flafter>\EndIncludeInRelease
1712 <latexrelease | fltrace | flafter>\IncludeInRelease{0000/00/00}%
1713 <latexrelease | fltrace | flafter> {\@addtocurcol}{float order in 2-column}%
1714 <latexrelease | fltrace | flafter>\def \@addtocurcol {%
1715 <*trace>
1716 <latexrelease | fltrace | flafter> \fl@trace{***Start addtocurcol}%
1717 </trace>
1718 <latexrelease | fltrace | flafter> \@insertfalse
1719 <latexrelease | fltrace | flafter> \@setfloattyperecounts
1720 <latexrelease | fltrace | flafter> \ifnum \@fpstype=8
1721 <*trace>
1722 <latexrelease | fltrace | flafter> \fl@trace{fpstype !p only (addtocurcol):

```

```

1723 <latexrelease | fltrace | flafter> \the \@fpstype = 8?}%
1724 </trace>
1725 <latexrelease | fltrace | flafter> \else
1726 <latexrelease | fltrace | flafter> \ifnum \@fpstype=24
1727 <*trace>
1728 <latexrelease | fltrace | flafter> \fl@trace{fpstype p only (addtocurcol):
1729 <latexrelease | fltrace | flafter> \the \@fpstype = 24?}%
1730 </trace>
1731 <latexrelease | fltrace | flafter> \else
1732 <latexrelease | fltrace | flafter> \@flsettextmin

```

This is a new adjustment which is quite a major change in functionality; but it implements the documentation. Note that \@reqcolroom will include the whole of the page-so-far, and hence includes \@textfloatsheight of floats, so before comparing it with \@textmin, we add this to \@textmin also.

```

1733 <*trace>
1734 <latexrelease | fltrace | flafter> \fl@trace{textfloatsheight (before) =
1735 <latexrelease | fltrace | flafter> \the \@textfloatsheight}%
1736 </trace>
1737 <latexrelease | fltrace | flafter> \advance \@textmin \@textfloatsheight
1738 <latexrelease | fltrace | flafter> \@reqcolroom \@pageht

```

This line must be removed since \@specialoutput changed.

```

1739 % \advance \@reqcolroom \@pagedp
1740 <*trace>
1741 <latexrelease | fltrace | flafter> \fl@trace{textmin + textfloatsheight:
1742 <latexrelease | fltrace | flafter> \the \@textmin}%
1743 <latexrelease | fltrace | flafter> \fl@trace{page-so-far: \the \@reqcolroom}%
1744 <latexrelease | fltrace | flafter>
1745 </trace>
1746 <latexrelease | fltrace | flafter> \ifdim \@textmin>\@reqcolroom
1747 <latexrelease | fltrace | flafter> \@reqcolroom \@textmin
1748 <*trace>
1749 <latexrelease | fltrace | flafter> \fl@trace{ORD? textmin being used}%
1750 </trace>
1751 <latexrelease | fltrace | flafter> \fi
1752 <latexrelease | fltrace | flafter> \advance \@reqcolroom \ht\@currbox
1753 <*trace>
1754 <latexrelease | fltrace | flafter> \fl@trace{float size =
1755 <latexrelease | fltrace | flafter> \the \ht \@currbox (addtocurcol)}%
1756 <latexrelease | fltrace | flafter> \fl@trace{colroom =
1757 <latexrelease | fltrace | flafter> \the \@colroom (addtocurcol)}%
1758 <latexrelease | fltrace | flafter> \fl@trace{reqcolroom =
1759 <latexrelease | fltrace | flafter> \the \@reqcolroom (addtocurcol)}%
1760 </trace>
1761 <latexrelease | fltrace | flafter> \ifdim \@colroom>\@reqcolroom
1762 <latexrelease | fltrace | flafter> \@flsetnum \@colnum
1763 <latexrelease | fltrace | flafter> \ifnum \@colnum>\z@
1764 <latexrelease | fltrace | flafter> \@bitor\@currtype\@deferlist
1765 <*trace>
1766 <latexrelease | fltrace | flafter> \fl@trace{deferlist:
1767 <latexrelease | fltrace | flafter> \@deferlist: (addtocurcol-before)}%
1768 </trace>
1769 <latexrelease | fltrace | flafter> \if@test

```

```

1770 <*trace>
1771 <latexrelease | fltrace | flafter>          \fl@trace{type already on list:
1772 <latexrelease | fltrace | flafter>              defer (addtocurcol)}%
1773 </trace>
1774 <latexrelease | fltrace | flafter>          \else
1775 <latexrelease | fltrace | flafter>              \@bitor\@currtype\@botlist
1776 <*trace>
1777 <latexrelease | fltrace | flafter>          \fl@trace{botlist: \@botlist:
1778 <latexrelease | fltrace | flafter>              (addtocurcol-before)}%
1779 </trace>
1780 <latexrelease | fltrace | flafter>          \if@test
1781 <*trace>
1782 <latexrelease | fltrace | flafter>              \fl@trace{type already on list:
1783 <latexrelease | fltrace | flafter>              bot---sent to addtobot}%
1784 </trace>
1785 <latexrelease | fltrace | flafter>          \@addtobot
1786 <latexrelease | fltrace | flafter>          \else
1787 <*trace>
1788 <latexrelease | fltrace | flafter>              \fl@trace{fpstype
1789 <latexrelease | fltrace | flafter>              \ifodd \@tempcnta OK \else not \fi
1790 <latexrelease | fltrace | flafter>              here: \the \@fpstype}%
1791 </trace>
1792 <latexrelease | fltrace | flafter>          \ifodd \count\@currbox
1793 <latexrelease | fltrace | flafter>              \advance \@reqcolroom \intextsep
1794 <latexrelease | fltrace | flafter>              \ifdim \@colroom>\@reqcolroom
1795 <latexrelease | fltrace | flafter>              \global \advance \@colnum \m@ne
1796 <latexrelease | fltrace | flafter>              \global \advance
1797 <latexrelease | fltrace | flafter>              \@textfloatsheight\ht\@currbox

```

This may sometimes give an overestimate.

```

1798 <latexrelease | fltrace | flafter>          \global \advance
1799 <latexrelease | fltrace | flafter>              \@textfloatsheight 2\intextsep
1800 <latexrelease | fltrace | flafter>          \@cons \@midlist \@currbox
1801 <*trace>
1802 <latexrelease | fltrace | flafter>          \fl@trace{***Success: here}%
1803 <latexrelease | fltrace | flafter>          \fl@trace{textfloatsheight
1804 <latexrelease | fltrace | flafter>              (after-here) =
1805 <latexrelease | fltrace | flafter>              \the \@textfloatsheight}%
1806 <latexrelease | fltrace | flafter>          \fl@trace{colnum (after-here) =
1807 <latexrelease | fltrace | flafter>              \the \@colnum}%
1808 </trace>

```

CHANGE TO \@addtocurcol:

\penalty\z@ changed to \penalty\interlinepenalty so \samepage works properly with figure and table environments. (Changed 23 Oct 86)

There is also an \addpenalty\interlinepenalty above.

Although it is best to use \addvspace in case two h floats come together, this makes other spacing more difficult to adjust; whereas if a user specifies two h floats together then they can more easily get the spacing correct by ad hoc commands.

It is necessary to adjust for the addition of \parskip here in case the float is added between paragraphs (i.e. when in vertical mode).

If the nobreak switch is true we need to reset it and clear \everypar since the float may not reset the flag and cannot reset the \everypar globally.

Typesetting starts here (we are in vertical mode).

```

1809 <latexrelease | fltrace | flafter> \if@nobreak
1810 <latexrelease | fltrace | flafter> \nobreak
1811 <latexrelease | fltrace | flafter> \@nobreakfalse
1812 <latexrelease | fltrace | flafter> \everypar{}%
1813 <latexrelease | fltrace | flafter> \else
1814 <latexrelease | fltrace | flafter> \addpenalty\interlinepenalty
1815 <latexrelease | fltrace | flafter> \fi
1816 <latexrelease | fltrace | flafter> \vskip \intextsep
1817 <latexrelease | fltrace | flafter> \box\@currbox
1818 <latexrelease | fltrace | flafter> \penalty\interlinepenalty
1819 <latexrelease | fltrace | flafter> \vskip\intextsep
1820 <latexrelease | fltrace | flafter> \ifnum\outputpenalty
1821 <latexrelease | fltrace | flafter> <-\@Mii \vskip
1822 <latexrelease | fltrace | flafter> -\parskip\fi

```

Typesetting ends here.

```

1823 <latexrelease | fltrace | flafter> \outputpenalty \z@
1824 <latexrelease | fltrace | flafter> \@inserttrue
1825 <*trace>
1826 <latexrelease | fltrace | flafter> \else
1827 <latexrelease | fltrace | flafter> \fl@trace{Fail---no room at 2nd test of colroom
1828 <latexrelease | fltrace | flafter> (addtocorcol \string\intextsep)}%
1829 </trace>
1830 <latexrelease | fltrace | flafter> \fi
1831 <latexrelease | fltrace | flafter> \fi
1832 <latexrelease | fltrace | flafter> \if@insert
1833 <latexrelease | fltrace | flafter> \else

```

Next set of docstrip guards are a bit weird, essentially \@addtotoporbot ends up inside the kernel and the fltrace package and \@addtotoporbot shows up in the flafter package. Guess that could have been done a bit more obvious :-)

```

1834 <*2kernel | fltrace>
1835 <*trace>
1836 <latexrelease | fltrace | flafter> \fl@trace{not here: sent to addtotoporbot}%
1837 </trace>
1838 <latexrelease | fltrace | flafter> \@addtotoporbot
1839 </2kernel | fltrace>
1840 <!*2kernel&!autoload&!fltrace>
1841 <*trace>
1842 <latexrelease | fltrace | flafter> \fl@trace{not here: sent to addtobot}%
1843 </trace>
1844 <latexrelease | fltrace | flafter> \@addtobot
1845 </*!2kernel&!autoload&!fltrace>
1846 <latexrelease | fltrace | flafter> \fi
1847 <latexrelease | fltrace | flafter> \fi
1848 <latexrelease | fltrace | flafter> \fi
1849 <*trace>
1850 <latexrelease | fltrace | flafter> \else
1851 <latexrelease | fltrace | flafter> \fl@trace{Fail: colnum = \the \@colnum:
1852 <latexrelease | fltrace | flafter> fpstype \the \@fpstype=ORD?}%
1853 <latexrelease | fltrace | flafter> \ifnum \@fpstype<\sist@@n
1854 <latexrelease | fltrace | flafter> \fl@trace{ERROR: BANG float not successful
1855 <latexrelease | fltrace | flafter> (addtocurcol)}%
1856 <latexrelease | fltrace | flafter> \fi
1857 </trace>

```

```

1858 <latexrelease | fltrace | flafter>          \fi
1859 <*trace>
1860 <latexrelease | fltrace | flafter>          \else
1861 <latexrelease | fltrace | flafter>          \fl@trace{Fail---no room: fl box ht:
1862 <latexrelease | fltrace | flafter>          \the \ht \@currbox (addtocurcol)}%
1863 </trace>
1864 <latexrelease | fltrace | flafter>          \fi
1865 <latexrelease | fltrace | flafter>          \fi
1866 <latexrelease | fltrace | flafter>          \fi
1867 <latexrelease | fltrace | flafter>          \if@insert
1868 <latexrelease | fltrace | flafter>          \else
1869 <latexrelease | fltrace | flafter>          \@resetfps
1870 <*trace>
1871 <latexrelease | fltrace | flafter>          \fl@trace{put on deferlist (addtocurcol)}%
1872 </trace>
1873 <latexrelease | fltrace | flafter>          \@cons\@deferlist\@currbox
1874 <*trace>
1875 <latexrelease | fltrace | flafter>          \fl@trace{deferlist: \@deferlist:
1876 <latexrelease | fltrace | flafter>          (addtocurcol-after)}%
1877 </trace>
1878 <latexrelease | fltrace | flafter>          \fi
1879 <latexrelease | fltrace | flafter>          }%
1880 <latexrelease | fltrace | flafter>\EndIncludeInRelease

```

(End of definition for \@addtocurcol.)

\@addtonextcol Lots of changes.

```

1881 <latexrelease | fltrace>\IncludeInRelease{2025/06/01}
1882 <latexrelease | fltrace>  {\@addtonextcol}{float order in 2-column}%
1883 <*2ekernel | latexrelease | fltrace>
1884 \def\@addtonextcol{%
1885   \begingroup
1886   <*trace>
1887   \fl@trace{***Start addtonextcol}%
1888   </trace>
1889   \@insertfalse
1890   \@setfloattypescounts
1891   \ifnum \@fpstype=8
1892   <*trace>
1893   \fl@trace{fpstype not curcol: \the \@fpstype = 8?}%
1894   </trace>
1895   \else
1896   \ifnum \@fpstype=24
1897   <*trace>
1898   \fl@trace{fpstype not curcol: \the \@fpstype = 24?}%
1899   </trace>
1900   \else
1901   \@flsettextmin
1902   <*trace>
1903   \fl@trace{text-so-far: 0pt (top of col)}%
1904   </trace>
1905   \@reqcolroom \ht\@currbox
1906   <*trace>
1907   \fl@trace{float size: \the \@reqcolroom (addtonextcol)}%

```

```

1908 </trace>
1909     \advance \@reqcolroom \@textmin
1910
1911     \saved@reqcolroom \@reqcolroom
1912 <*trace>
1913     \fl@trace{colroom = \the \@colroom (addtonextcol)}%
1914     \fl@trace{reqcolroom = \the \@reqcolroom (addtonextcol)}%
1915 </trace>
1916     \ifdim \@colroom>\@reqcolroom
1917         \@flsetnum \@colnum
1918         \ifnum \@colnum>\z@
1919             \@bitor \@currtype \@deferlist
1920 <*trace>
1921             \fl@trace{deferlist: \@deferlist: (addtonextcol-before)}%
1922 </trace>
1923             \@testwrongwidth \@currbox
1924             \if@test
1925 <*trace>
1926                 \fl@trace{type already on list: defer (addtonextcol)}%
1927 </trace>
1928                 \else
1929 <*trace>
1930                 \fl@trace{sent to addtotoporbot (addtonextcol)}%
1931 </trace>
1932                 \@addtotoporbot
1933             \fi
1934 <*trace>
1935             \else
1936                 \fl@trace{Fail---no room: fl box ht: \the \@currbox
1937                     (addtonextcol)}%
1938 </trace>
1939             \fi
1940         \fi
1941     \fi
1942     \if@insert
1943     \else
1944 <*trace>
1945         \fl@trace{put back on deferlist (addtonextcol)}%
1946 </trace>
1947         \@cons \@deferlist \@currbox
1948 <*trace>
1949         \fl@trace{deferlist: \@deferlist: (addtonextcol-after)}%
1950 </trace>
1951     \fi
1952 <*trace>
1953     \fl@trace{End of addtonextcol -- locally counts:}%
1954     \fl@trace{col: \the \@colnum. top: \the \@topnum. bot: \the \@botnum.}%
1955 </trace>
1956     \endgroup
1957 <*trace>
1958     \fl@trace{End of addtonextcol -- globally counts:}%
1959     \fl@trace{col: \the \@colnum. top: \the \@topnum. bot: \the \@botnum.}%
1960 </trace>

```

```

1961 }%
1962 </2ekernel | latexrelease | fltrace>
1963 <latexrelease | fltrace>\EndIncludeInRelease
1964 <latexrelease | fltrace>\IncludeInRelease{2015/01/01}
1965 <latexrelease | fltrace> {\@addtonextcol}{float order in 2-column}%
1966 <latexrelease | fltrace>\def\@addtonextcol{%
1967 <latexrelease | fltrace> \begingroup
1968 <*trace>
1969 <latexrelease | fltrace> \fl@trace{***Start addtonextcol}%
1970 </trace>
1971 <latexrelease | fltrace> \@insertfalse
1972 <latexrelease | fltrace> \@setfloattyperecounts
1973 <latexrelease | fltrace> \ifnum \@fpstype=8
1974 <*trace>
1975 <latexrelease | fltrace> \fl@trace{fpstype not curcol: \the \@fpstype = 8?}%
1976 </trace>
1977 <latexrelease | fltrace> \else
1978 <latexrelease | fltrace> \ifnum \@fpstype=24
1979 <*trace>
1980 <latexrelease | fltrace> \fl@trace{fpstype not curcol: \the \@fpstype = 24?}%
1981 </trace>
1982 <latexrelease | fltrace> \else
1983 <latexrelease | fltrace> \@flsettextmin
1984 <*trace>
1985 <latexrelease | fltrace> \fl@trace{text-so-far: Opt (top of col)}%
1986 </trace>
1987 <latexrelease | fltrace> \@reqcolroom \ht\@currbox
1988 <*trace>
1989 <latexrelease | fltrace> \fl@trace{float size: \the \@reqcolroom (addtonextcol)}%
1990 </trace>
1991 <latexrelease | fltrace> \advance \@reqcolroom \@textmin
1992 <*trace>
1993 <latexrelease | fltrace> \fl@trace{colroom = \the \@colroom (addtonextcol)}%
1994 <latexrelease | fltrace> \fl@trace{reqcolroom = \the \@reqcolroom (addtonextcol)}%
1995 </trace>
1996 <latexrelease | fltrace> \ifdim \@colroom>\@reqcolroom
1997 <latexrelease | fltrace> \@flsetnum \@colnum
1998 <latexrelease | fltrace> \ifnum \@colnum>\z@
1999 <latexrelease | fltrace> \@bitor\@currtype\@deferlist
2000 <*trace>
2001 <latexrelease | fltrace> \fl@trace{deferlist: \@deferlist: (addtonextcol-before)}%
2002 </trace>
2003 <latexrelease | fltrace> \@testwrongwidth\@currbox
2004 <latexrelease | fltrace> \if@test
2005 <*trace>
2006 <latexrelease | fltrace> \fl@trace{type already on list: defer (addtonextcol)}%
2007 </trace>
2008 <latexrelease | fltrace> \else
2009 <*trace>
2010 <latexrelease | fltrace> \fl@trace{sent to addtotoporbot (addtonextcol)}%
2011 </trace>
2012 <latexrelease | fltrace> \@addtotoporbot
2013 <latexrelease | fltrace> \fi
2014 <latexrelease | fltrace> \fi

```

```

2015 <*trace>
2016 <latexrelease | fltrace>          \else
2017 <latexrelease | fltrace>          \fl@trace{Fail---no room: fl box ht: \the \ht \@currbox
2018 <latexrelease | fltrace>                                     (addtonextcol)}%
2019 </trace>
2020 <latexrelease | fltrace>          \fi
2021 <latexrelease | fltrace>          \fi
2022 <latexrelease | fltrace>          \fi
2023 <latexrelease | fltrace>          \if@insert
2024 <latexrelease | fltrace>          \else
2025 <*trace>
2026 <latexrelease | fltrace>          \fl@trace{put back on deferlist (addtonextcol)}%
2027 </trace>
2028 <latexrelease | fltrace>          \@cons\@deferlist\@currbox
2029 <*trace>
2030 <latexrelease | fltrace>          \fl@trace{deferlist: \@deferlist: (addtonextcol-after)}%
2031 </trace>
2032 <latexrelease | fltrace>          \fi
2033 <*trace>
2034 <latexrelease | fltrace>          \fl@trace{End of addtonextcol -- locally counts:}%
2035 <latexrelease | fltrace>          \fl@trace{col: \the\@colnum. top: \the \@topnum. bot: \the \@botnum.}%
2036 </trace>
2037 <latexrelease | fltrace>          \endgroup
2038 <*trace>
2039 <latexrelease | fltrace>          \fl@trace{End of addtonextcol -- globally counts:}%
2040 <latexrelease | fltrace>          \fl@trace{col: \the\@colnum. top: \the \@topnum. bot: \the \@botnum.}%
2041 </trace>
2042 <latexrelease | fltrace>}%
2043 <latexrelease | fltrace>\EndIncludeInRelease

2044 <latexrelease | fltrace>\IncludeInRelease{0000/00/00}%
2045 <latexrelease | fltrace>  {\@addtonextcol}{float order in 2-column}%
2046 <latexrelease | fltrace>\def\@addtonextcol{%
2047 <latexrelease | fltrace>  \begingroup
2048 <*trace>
2049 <latexrelease | fltrace>    \fl@trace{***Start addtonextcol}%
2050 </trace>
2051 <latexrelease | fltrace>    \@insertfalse
2052 <latexrelease | fltrace>    \@setfloattypecounts
2053 <latexrelease | fltrace>    \ifnum \@fpstype=8
2054 <*trace>
2055 <latexrelease | fltrace>        \fl@trace{fpstype not curcol:
2056 <latexrelease | fltrace>                                \the \@fpstype = 8?}%
2057 </trace>
2058 <latexrelease | fltrace>    \else
2059 <latexrelease | fltrace>        \ifnum \@fpstype=24
2060 <*trace>
2061 <latexrelease | fltrace>        \fl@trace{fpstype not curcol:
2062 <latexrelease | fltrace>                                \the \@fpstype = 24?}%
2063 </trace>
2064 <latexrelease | fltrace>    \else
2065 <latexrelease | fltrace>        \@flsettextmin
2066 <*trace>
2067 <latexrelease | fltrace>        \fl@trace{text-so-far: 0pt (top of col)}%
2068 </trace>

```

```

2069 <latexrelease | fltrace> \@reqcolroom \ht\@currbox
2070 <*trace>
2071 <latexrelease | fltrace> \fl@trace{float size:
2072 <latexrelease | fltrace> \the \@reqcolroom (addtonextcol)}%
2073 <latexrelease | fltrace>
2074 </trace>
2075 <latexrelease | fltrace> \advance \@reqcolroom \@textmin
2076 <*trace>
2077 <latexrelease | fltrace> \fl@trace{colroom =
2078 <latexrelease | fltrace> \the \@colroom (addtonextcol)}%
2079 <latexrelease | fltrace> \fl@trace{reqcolroom =
2080 <latexrelease | fltrace> \the \@reqcolroom (addtonextcol)}%
2081 </trace>
2082 <latexrelease | fltrace> \ifdim \@colroom>\@reqcolroom
2083 <latexrelease | fltrace> \@flsetnum \@colnum
2084 <latexrelease | fltrace> \ifnum\@colnum>\z@
2085 <latexrelease | fltrace> \@bitor\@currtype\@deferlist
2086 <*trace>
2087 <latexrelease | fltrace> \fl@trace{deferlist: \@deferlist:
2088 <latexrelease | fltrace> (addtonextcol-before)}%
2089 </trace>
2090 <latexrelease | fltrace> \if@test
2091 <*trace>
2092 <latexrelease | fltrace> \fl@trace{type already on list:
2093 <latexrelease | fltrace> defer (addtonextcol)}%
2094 </trace>
2095 <latexrelease | fltrace> \else
2096 <*trace>
2097 <latexrelease | fltrace> \fl@trace{sent to addtotoporbot
2098 <latexrelease | fltrace> (addtonextcol)}%
2099 </trace>
2100 <latexrelease | fltrace> \@addtotoporbot
2101 <latexrelease | fltrace> \fi
2102 <latexrelease | fltrace> \fi
2103 <*trace>
2104 <latexrelease | fltrace> \else
2105 <latexrelease | fltrace> \fl@trace{Fail---no room: fl box ht:
2106 <latexrelease | fltrace> \the \ht \@currbox (addtonextcol)}%
2107 </trace>
2108 <latexrelease | fltrace> \fi
2109 <latexrelease | fltrace> \fi
2110 <latexrelease | fltrace> \fi
2111 <latexrelease | fltrace> \if@insert
2112 <latexrelease | fltrace> \else
2113 <*trace>
2114 <latexrelease | fltrace> \fl@trace{put back on deferlist
2115 <latexrelease | fltrace> (addtonextcol)}%
2116 </trace>
2117 <latexrelease | fltrace> \@cons\@deferlist\@currbox
2118 <*trace>
2119 <latexrelease | fltrace> \fl@trace{deferlist: \@deferlist:
2120 <latexrelease | fltrace> (addtonextcol-after)}%
2121 </trace>
2122 <latexrelease | fltrace> \fi

```

```

2123 <*trace>
2124 <latexrelease | fltrace> \fl@trace{End of addtonextcol --
2125 <latexrelease | fltrace> locally counts:}%
2126 <latexrelease | fltrace> \fl@trace{col: \the \@colnum.
2127 <latexrelease | fltrace> top: \the \@topnum. bot: \the \@botnum.}%
2128 </trace>
2129 <latexrelease | fltrace> \endgroup
2130 <*trace>
2131 <latexrelease | fltrace> \fl@trace{End of addtonextcol --
2132 <latexrelease | fltrace> globally counts:}%
2133 <latexrelease | fltrace> \fl@trace{col: \the \@colnum.
2134 <latexrelease | fltrace> top: \the \@topnum. bot: \the \@botnum.}%
2135 </trace>
2136 <latexrelease | fltrace>}%
2137 <latexrelease | fltrace>\EndIncludeInRelease

(End of definition for \@addtonextcol.)

```

\@addtodblcol Lots of changes.

```

2138 <latexrelease | fltrace>\IncludeInRelease{2015/01/01}%
2139 <latexrelease | fltrace> {\@addtodblcol}{float order in 2-column}%
2140 <*2ekernel | latexrelease | fltrace>
2141 \def\@addtodblcol{%
2142 \begingroup
2143 <*trace>
2144 \fl@trace{***Start addtodblcol}%
2145 </trace>
2146 \@insertfalse
2147 \@setfloatypecounts
2148 \@getfpsbit \tw@
2149 <*trace>
2150 \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi dbltop:
2151 \the \@fpstype}%
2152 </trace>
2153 \ifodd \@tempcnta
2154 \@flsetnum \@dbltopnum
2155 \ifnum \@dbltopnum>\z@
2156 \@tempswafalse
2157 \ifdim \@dbltoproom>\ht\@currbox
2158 \@tempswatrue
2159 <*trace>
2160 \fl@trace{Space OK: \@dbltoproom =
2161 \the \@dbltoproom > \the \ht \@currbox
2162 (dbltoproom)}%
2163 </trace>
2164 \else
2165 <*trace>
2166 \fl@trace{fpstype: \the \@fpstype (addtodblcol)}%
2167 </trace>
2168 \ifnum \@fpstype<\sist@@n
2169 <*trace>
2170 \fl@trace{BANG float ignoring \@dbltoproom}%
2171 \fl@trace{\@spaces \@dbltoproom = \the \@dbltoproom.
2172 Ht float: \the \ht \@currbox-BANG}%

```

```

2173 </trace>

Need to check that there is room on the page, using the local value of \@textmin to make
the necessary adjustment to \@dbltoproom.

2174 \advance \@dbltoproom \@textmin
2175 <*trace>
2176 \fl@trace{Local value of texmin: \the\@textmin}%
2177 \fl@trace{\@spaces space on page = \the \@dbltoproom.
2178 Ht float: \the \ht \@currbox-BANG}%
2179 </trace>
2180 \ifdim \@dbltoproom>\ht\@currbox
2181 \@tempwattrue
2182 <*trace>
2183 \fl@trace{Space OK BANG: space on page =
2184 \the \@dbltoproom > \the \ht \@currbox}%
2185 \else
2186 \fl@trace{fpstype: \the \@fpstype}%
2187 \fl@trace{Fail---no room dbltoproom-BANG?:}%
2188 \fl@trace{\@spaces space on page = \the \@dbltoproom.
2189 Ht float: \the \ht \@currbox}%
2190 </trace>
2191 \fi
2192 \advance \@dbltoproom -\@textmin
2193 <*trace>
2194 \else
2195 \fl@trace{fpstype: \the \@fpstype}%
2196 \fl@trace{Fail---no room dbltoproom-ORD?:}%
2197 \fl@trace{\@spaces \@dbltoproom = \the \@dbltoproom.
2198 Ht float: \the \ht \@currbox}%
2199 </trace>
2200 \fi
2201 \fi
2202 \if@tempswa
2203 \@bitor \@currtype \@deferlist
2204 <*trace>
2205 \fl@trace{(dbl)deferlist: \@deferlist: (before)}%
2206 </trace>
not in fixfloats?
2207 \@testwrongwidth\@currbox
2208 \if@test
2209 <*trace>
2210 \fl@trace{type already on list: (dbl)defer}%
2211 </trace>
2212 \else
2213 \@tempdima -\ht\@currbox
2214 \advance\@tempdima
2215 -\ifx \@dbltoplist\@empty \dbltextfloatsep \else
2216 \dblfloatsep \fi
2217 \global \advance \@dbltoproom \@tempdima
2218 \global \advance \@colht \@tempdima
2219 \global \advance \@dbltopnum \m@ne
2220 \@cons \@dbltoplist \@currbox
2221 <*trace>

```

```

2222             \fl@trace{dbltopnum (after) = \the \@dbltopnum}%
2223             \fl@trace{***Success: dbltop}%
2224     </trace>
2225             \@inserttrue
2226     \fi
2227 \fi
2228 <*trace>
2229     \else
2230         \fl@trace{Fail: dbltopnum = \the \@dbltopnum: fpstype
2231                 \the \@fpstype=ORD?}%
2232         \ifnum \@fpstype<\sist@n
2233             \fl@trace{ERROR: !t float not successful (addtodblcol)}%
2234         \fi
2235 </trace>
2236     \fi
2237 \fi
2238     \if@insert
2239     \else
2240 <*trace>
2241         \fl@trace{put on deferlist}%
2242 </trace>
2243         \@cons\@deferlist\@currbox
2244 <*trace>
2245         \fl@trace{(dbl)deferlist: \@deferlist: (after)}%
2246 </trace>
2247     \fi
2248 <*trace>
2249     \fl@trace{End of addtodblcol -- locally count:}%
2250     \fl@trace{dbltop: \the \@dbltopnum.}%
2251 </trace>
2252 \endgroup
2253 <*trace>
2254     \fl@trace{End of addtodblcol -- globally count:}%
2255     \fl@trace{dbltop: \the \@dbltopnum.}%
2256 </trace>
2257 }%
2258 </2ekernel | latexrelease | fltrace>
2259 <latexrelease | fltrace>\EndIncludeInRelease
2260 <latexrelease | fltrace>\IncludeInRelease{0000/00/00}%
2261 <latexrelease | fltrace> {\@addtodblcol}{float order in 2-column}%
2262 <latexrelease | fltrace>\def\@addtodblcol{%
2263 <latexrelease | fltrace> \begingroup
2264 <*trace>
2265 <latexrelease | fltrace> \fl@trace{***Start addtodblcol}%
2266 </trace>
2267 <latexrelease | fltrace> \@insertfalse
2268 <latexrelease | fltrace> \@setfloattyperecounts
2269 <latexrelease | fltrace> \@getfpsbit \tw@
2270 <*trace>
2271 <latexrelease | fltrace> \fl@trace{fpstype \ifodd \@tempcnta OK
2272 <latexrelease | fltrace> \else not \fi dbltop: \the \@fpstype}%
2273 </trace>
2274 <latexrelease | fltrace> \ifodd\@tempcnta
2275 <latexrelease | fltrace> \@flsetnum \@dbltopnum

```

```

2276 <latexrelease | fltrace> \ifnum \@dbltopnum>\z@
2277 <latexrelease | fltrace> \@tempswafalse
2278 <latexrelease | fltrace> \ifdim \@dbltoproom>\ht\@currbox
2279 <latexrelease | fltrace> \@tempwattrue
2280 <*trace>
2281 <latexrelease | fltrace> \fl@trace{Space OK: \@dbltoproom =
2282 <latexrelease | fltrace> \the \@dbltoproom > \the \ht \@currbox
2283 <latexrelease | fltrace> (dbltoproom)}%
2284 </trace>
2285 <latexrelease | fltrace> \else
2286 <*trace>
2287 <latexrelease | fltrace> \fl@trace{fpstype: \the \@fpstype (addtodblcol)}%
2288 </trace>
2289 <latexrelease | fltrace> \ifnum \@fpstype<\sist@n
2290 <*trace>
2291 <latexrelease | fltrace> \fl@trace{BANG float ignoring \@dbltoproom}%
2292 <latexrelease | fltrace> \fl@trace{\@spaces \@dbltoproom =
2293 <latexrelease | fltrace> \the \@dbltoproom.
2294 <latexrelease | fltrace> Ht float: \the \ht \@currbox-BANG}%
2295 </trace>

```

Need to check that there is room on the page, using the local value of \@textmin to make the necessary adjustment to \@dbltoproom.

```

2296 <latexrelease | fltrace> \advance \@dbltoproom \@textmin
2297 <*trace>
2298 <latexrelease | fltrace> \fl@trace{Local value of texmin: \the \@textmin}%
2299 <latexrelease | fltrace> \fl@trace{\@spaces space on page =
2300 <latexrelease | fltrace> \the \@dbltoproom.
2301 <latexrelease | fltrace> Ht float: \the \ht \@currbox-BANG}%
2302 </trace>
2303 <latexrelease | fltrace> \ifdim \@dbltoproom>\ht\@currbox
2304 <latexrelease | fltrace> \@tempwattrue
2305 <*trace>
2306 <latexrelease | fltrace> \fl@trace{Space OK BANG: space on page =
2307 <latexrelease | fltrace> \the \@dbltoproom > \the \ht \@currbox}%
2308 <latexrelease | fltrace> \else
2309 <latexrelease | fltrace> \fl@trace{fpstype: \the \@fpstype}%
2310 <latexrelease | fltrace> \fl@trace{Fail---no room dbltoproom-BANG?:}%
2311 <latexrelease | fltrace> \fl@trace{\@spaces space on page =
2312 <latexrelease | fltrace> \the \@dbltoproom.
2313 <latexrelease | fltrace> Ht float: \the \ht \@currbox}%
2314 </trace>
2315 <latexrelease | fltrace> \fi
2316 <latexrelease | fltrace> \advance \@dbltoproom -\@textmin
2317 <*trace>
2318 <latexrelease | fltrace> \else
2319 <latexrelease | fltrace> \fl@trace{fpstype: \the \@fpstype}%
2320 <latexrelease | fltrace> \fl@trace{Fail---no room dbltoproom-ORD?:}%
2321 <latexrelease | fltrace> \fl@trace{\@spaces \@dbltoproom =
2322 <latexrelease | fltrace> \the \@dbltoproom.
2323 <latexrelease | fltrace> Ht float: \the \ht \@currbox}%
2324 </trace>
2325 <latexrelease | fltrace> \fi
2326 <latexrelease | fltrace> \fi

```

```

2327 <latexrelease | fltrace> \if@tempswa
2328 <latexrelease | fltrace> \@bitor \@currtype \@dbldeferlist
2329 <*trace>
2330 <latexrelease | fltrace> \fl@trace{dbldeferlist:
2331 <latexrelease | fltrace> \@dbldeferlist: (before)}%
2332 </trace>
2333 <latexrelease | fltrace> \if@test
2334 <*trace>
2335 <latexrelease | fltrace> \fl@trace{type already on list: dbldefer}%
2336 </trace>
2337 <latexrelease | fltrace> \else
2338 <latexrelease | fltrace> \@tempdima -\ht\@currbox
2339 <latexrelease | fltrace> \advance\@tempdima
2340 <latexrelease | fltrace> -\ifx \@dbltoplist\@empty
2341 <latexrelease | fltrace> \dbltextfloatsep
2342 <latexrelease | fltrace> \else \dblfloatsep \fi
2343 <latexrelease | fltrace> \global \advance \@dbltoproom \@tempdima
2344 <latexrelease | fltrace> \global \advance \@colht \@tempdima
2345 <latexrelease | fltrace> \global \advance \@dbltopnum \m@ne
2346 <latexrelease | fltrace> \@cons \@dbltoplist \@currbox
2347 <*trace>
2348 <latexrelease | fltrace> \fl@trace{dbltopnum (after) =
2349 <latexrelease | fltrace> \the \@dbltopnum}%
2350 <latexrelease | fltrace> \fl@trace{***Success: dbltop}%
2351 </trace>
2352 <latexrelease | fltrace> \@inserttrue
2353 <latexrelease | fltrace> \fi
2354 <latexrelease | fltrace> \fi
2355 <*trace>
2356 <latexrelease | fltrace> \else
2357 <latexrelease | fltrace> \fl@trace{Fail: dbltopnum = \the \@dbltopnum:
2358 <latexrelease | fltrace> fpstype \the \@fpstype=ORD?}%
2359 <latexrelease | fltrace> \ifnum \@fpstype<\sist@n
2360 <latexrelease | fltrace> \fl@trace{ERROR: !t float not successful
2361 <latexrelease | fltrace> (addtodblcol)}%
2362 <latexrelease | fltrace> \fi
2363 </trace>
2364 <latexrelease | fltrace> \fi
2365 <latexrelease | fltrace> \fi
2366 <latexrelease | fltrace> \if@insert
2367 <latexrelease | fltrace> \else
2368 <*trace>
2369 <latexrelease | fltrace> \fl@trace{put on dbldeferlist}%
2370 </trace>
2371 <latexrelease | fltrace> \@cons\@dbldeferlist\@currbox
2372 <*trace>
2373 <latexrelease | fltrace> \fl@trace{dbldeferlist: \@dbldeferlist: (after)}%
2374 </trace>
2375 <latexrelease | fltrace> \fi
2376 <*trace>
2377 <latexrelease | fltrace> \fl@trace{End of addtodblcol -- locally count:}%
2378 <latexrelease | fltrace> \fl@trace{ dbltop: \the \@dbltopnum.}%
2379 </trace>
2380 <latexrelease | fltrace> \endgroup

```

```

2381 <*trace>
2382 <latexrelease|fltrace> \fl@trace{End of addtodblcol -- globally count:}%
2383 <latexrelease|fltrace> \fl@trace{dbltop: \the \@dbltopnum.}%
2384 </trace>
2385 <latexrelease|fltrace>}%
2386 <latexrelease|fltrace>\EndIncludeInRelease

```

(End of definition for \@addtodblcol.)

\@addmarginpar

```

2387 <*2ekernel>
2388 \def\@addmarginpar{\@next\@marbox\@currlist{\@cons\@freelist\@marbox
2389 \@cons\@freelist\@currbox}\@latexbug\@tempcnta\@one
2390 \if@twocolumn
2391 \if@firstcolumn \@tempcnta\m@ne \fi
2392 \else
2393 \if@mparswitch
2394 \ifodd\c@page \else\@tempcnta\m@ne \fi
2395 \fi
2396 \if@reversemargin \@tempcnta -\@tempcnta \fi
2397 \fi
2398 \ifnum\@tempcnta <\z@ \global\setbox\@marbox\box\@currbox \fi
2399 \@tempdima\@mparbottom
2400 \advance\@tempdima -\@pageht
2401 \advance\@tempdima\ht\@marbox
2402 \ifdim\@tempdima >\z@
2403 \latex@warning@no@line {Marginpar on page \thepage\space moved}%
2404 \else
2405 \@tempdima\z@
2406 \fi
2407 \global\@mparbottom\@pageht
2408 \global\advance\@mparbottom\@tempdima
2409 \global\advance\@mparbottom\dp\@marbox
2410 \global\advance\@mparbottom\marginparpush
2411 \advance\@tempdima -\ht\@marbox

```

Putting box movement inside the ‘marbox’:

```

2412 \global\setbox \@marbox
2413 \vbox {\vskip \@tempdima
2414 \box \@marbox}%
2415 \global \ht\@marbox \z@
2416 \global \dp\@marbox \z@

```

Sticking (rather than gluing:-) the ‘marbox’ to the line above, changed vskip to kern:

```

2417 \kern -\@pagedp
2418 \nointerlineskip
2419 \hb@xt@\columnwidth
2420 {\ifnum \@tempcnta >\z@
2421 \hskip\columnwidth \hskip\marginparsep
2422 \else
2423 \hskip -\marginparsep \hskip -\marginparwidth
2424 \fi
2425 \box\@marbox \hss}%

```

For this reason the following code can vanish:

```

\nobreak          %% No longer needed.  CAR92/12
\vskip -\@tempdima  %% No longer needed.  CAR92/12

```

```

2426 \nointerlineskip
2427 \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}}

```

(End of definition for \addmarginpar.)

### 2.2.2 Kludgeins

This part of the file is part of the implementation of the following two new commands for L<sup>A</sup>T<sub>E</sub>X2<sub>ε</sub>.

`\enlargethispage{<dim>}`

Adds <dim> to the height of the current column only. On the printed page the bottom of this column is extended downwards by exactly <dim> without having any effect on the placement of the footer; this may result in an overprinting.

`\enlargethispage*{<dim>}`

Similar to `\enlargethispage` but it tries to squeeze the column to be printed in as small a space as possible, ie it uses any shrinkability in the column. If the column was not explicitly broken (e.g. with `\pagebreak`) this may result in an overfull box message but except for this it will come out as expected (if you know what to expect).

The star form of this command is dedicated to Leslie Lamport, the other we need for ourselves (FMi, CAR).

These commands may well have unwanted effects if used soon before a `\clearpage`: please give keep them clear of such places.

`\@kludgeins` The insert which makes T<sub>E</sub>X do a lot of the necessary work. All we need to put into it is the amount by which the pagegoal should be changed.

```

2428 \newinsert \@kludgeins
2429 \global\dimen\@kludgeins \maxdimen
2430 \global\count\@kludgeins 1000

```

(End of definition for \@kludgeins.)

`\enlargethispage` The user command.  
`\enlargethispage*`

```

2431 \gdef \enlargethispage {%
2432   \@ifstar
2433   {%
2434     <*trace>
2435     \fl@trace{Enlarging page height * }%
2436   </trace>
2437     \@enlargepage{\hbox{\kern\p@}}}%
2438   {%
2439     <*trace>
2440     \fl@trace{Enlarging page height exactly---}%
2441   </trace>
2442     \@enlargepage\@empty}%
2443 }

```

(End of definition for \enlargethispage and \enlargethispage\*.)

`\@enlargepage` This actually inserts the insert, after checking for extreme values of the change.

```

2444 \gdef\@enlargepage#1#2{%
2445   \ifdim \f@l@trace\@spaces\@spaces by #2}%
2446 \fi
2447 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2448 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2449 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2450 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2451 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2452 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2453 \else
2454   \ifdim \f@l@trace\@spaces\@spaces by #2}%
2455 \fi
2456 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2457 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2458 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2459 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2460 \ifdim \f@l@trace\@spaces\@spaces by #2}%

```

This next bit is for tracing only:

```

2461 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2462 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2463 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2464 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2465 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2466 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2467 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2468 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2469 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2470 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2471 \ifdim \f@l@trace\@spaces\@spaces by #2}%

```

*(End of definition for \@enlargepage.)*

`\ShowFloat` This command provides some information about the contents of a float register. Float registers have internal names of the form `\bx@<Uppercase-letter(s)-or numbers>` and you specify just this letter or letters as the argument, e.g., `\ShowFloat{A}`. (There is not much error recovery if you specify something that isn't a float.)

```

2472 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2473 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2474 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2475 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2476 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2477 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2478 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2479 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2480 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2481 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2482 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2483 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2484 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2485 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2486 \ifdim \f@l@trace\@spaces\@spaces by #2}%
2487 \ifdim \f@l@trace\@spaces\@spaces by #2}%

```

```

2488 \fl@traceval{\ht#1}%
2489 \fl@traceval{\dp#1}%
2490 \fl@traceval{\wd#1}%
2491 {\tracingonline1\showboxbreadth10\showboxdepth3\showbox#1}%
2492 }

```

Here are two definitions from `fltrace` that make the above code work:

```

2493 \def \fl@traceval #1{\fl@trace{\string #1 = \the #1}}
2494 \def \fl@tracemessage #1{{\let\@elt\@empty\typeout{LaTeX2e: #1}}}
2495 </2ekernel|latexrelease>
2496 <latexrelease>\EndIncludeInRelease
2497 <latexrelease>\IncludeInRelease{0000/00/00}%
2498 <latexrelease> \ShowFloat{Show float register contents}%
2499 <latexrelease>
2500 <latexrelease>\let\ShowFloat\@undefined
2501 <latexrelease>\let\fl@ShowFloat\@undefined
2502 <latexrelease>\let\fl@traceval\@undefined
2503 <latexrelease>\let\fl@tracemessage\@undefined
2504 <latexrelease>\EndIncludeInRelease

```

*(End of definition for \ShowFloat.)*

### 2.2.3 Float control

This part implements controllable floats and other changes to the float mechanism.

It provides, at the document level, the following command for inclusion in `LATEX2e`.

`\suppressfloats`

This suppresses all further floats on the current page.

With an optional argument it suppresses only floats only in certain positions on the current page.

[t] suppresses only floats at the top of the page [b] suppresses only floats at the bottom of the page

It also enables the use of an extra specifier, `!`, in the location optional argument of a float. If this is present then, just for this particular float, whenever it is processed by the float mechanism the following are ignored:

- all restrictions on the number of floats which can appear;
- all explicit restrictions on the amount of space which should (not) be occupied by floats and/or text.

The mechanism will still attempt to ensure that pages are not overfull.

These specifiers override, for the single float, the suppression commands described above.

In its current form, it also supplies a reasonably exhaustive, and somewhat baroque, means of tracing some aspects of the float mechanism.

More tracing.

```

\fl@trace Set-up tracing for floats independent of other tracing as it produces mega-output. Default
\tracefloatsoff is no tracing.
\tracefloats
\fl@traceval
\tracefloatvals
\fl@tracemessage
2505 <*\fltrace>
2506 \def \fl@tracemessage #1{{\let\@elt\@empty\typeout{LaTeX2e: #1}}}
2507 \def \tracefloats{\let \fl@trace \fl@tracemessage}
2508 \def \tracefloatsoff {\let \fl@trace \@gobble}
2509 \tracefloatsoff
2510 \def \fl@traceval #1{\fl@trace{\string #1 = \the #1}}
2511 \IncludeInRelease{2015/01/01}{\tracefloatvals}%
2512 {trace float vals}%
2513 \def \tracefloatvals{%

As \@dblfloatplacement sets \f@depth it needs to be run inside a group, otherwise the
float placement will test for the wrong value.65
2514 \begingroup

When the user requests \tracefloatvals then they should show regardless of the tracing
state, so locally we make sure that it is activated.
2515 \tracefloats
2516 \@dblfloatplacement
2517 \@floatplacement
2518 \fl@trace{***Float placement parameters:}%
2519 \fl@traceval\@colnum
2520 \fl@traceval\@colroom
2521 \fl@traceval\@topnum
2522 \fl@traceval\@toproom
2523 \fl@traceval\@botnum
2524 \fl@traceval\@botroom
2525 \fl@traceval\@fpmin
2526 \fl@trace{\string\textfraction = \textfraction}%
2527 \fl@traceval\@dbltopnum
2528 \fl@traceval\@dbltoproom
2529 \fl@trace{\string\textfraction = \textfraction}%
2530 \fl@trace{toplist: \@toplist}%
2531 \fl@trace{botlist: \@botlist}%
2532 \fl@trace{midlist: \@midlist}%
2533 \fl@trace{deferlist: \@deferlist}%
2534 \fl@trace{dbltoplist: \@dbltoplist}%
2535 %Fmi \fl@trace{dbldeferlist: \@dbldeferlist}%
2536 \endgroup
2537 }
2538 \EndIncludeInRelease
2539 \IncludeInRelease{0000/00/00}{\tracefloatvals}%
2540 {trace float vals}%
2541 \def \tracefloatvals{%
2542 \begingroup
2543 \tracefloats
2544 \@dblfloatplacement
2545 \@floatplacement
2546 \fl@trace{***Float placement parameters:}%
2547 \fl@traceval\@colnum
2548 \fl@traceval\@colroom

```

---

<sup>65</sup>This is a somewhat questionable design.

```

2549 \fl@traceval\@topnum
2550 \fl@traceval\@toproom
2551 \fl@traceval\@botnum
2552 \fl@traceval\@botroom
2553 \fl@traceval\@fpmin
2554 \fl@trace{\string\textfraction = \textfraction}%
2555 \fl@traceval\@dbltopnum
2556 \fl@traceval\@dbltoproom
2557 \fl@trace{\string\textfraction = \textfraction}%
2558 \fl@trace{toplist: \@toplist}%
2559 \fl@trace{botlist: \@botlist}%
2560 \fl@trace{midlist: \@midlist}%
2561 \fl@trace{deferlist: \@deferlist}%
2562 \fl@trace{dbltoplist: \@dbltoplist}%
2563 % next line only in old releases
2564 \fl@trace{dbldeferlist: \@dbldeferlist}%
2565 \endgroup
2566 }
2567 \EndIncludeInRelease

```

We need to make sure that `fltrace` comes before `flafter` to make the tracing work.

```

2568 \@ifpackageloaded{flafter}
2569 {
2570   \PackageWarningNoLine
2571     {fltrace}{Load 'fltrace' before 'flafter'\MessageBreak
                Attempting to recover by reloading 'flafter'}%
2572   \expandafter\let\csname ver@flafter.sty\endcsname\relax
2573   \def\reserved@a#1{%
2574     \expandafter\let\csname string#1+flafter+IIR\endcsname\relax}%
2575   \reserved@a\@addtocurcol
2576   \reserved@a\@addtonextcol
2577   \RequirePackage{flafter}}{}
2578 </fltrace>

```

As the code for `flafter` will contain tracing calls so that it works in conjunction with `fltrace` we need to provide a dummy definition for `\fl@trace` in that package.

```

2579 <flafter>
2580 \providecommand\fl@trace[1]{}
2581 </flafter>

```

*(End of definition for \fl@trace and others.)*

`\suppressfloats` Float suppression commands: these set the relevant counter globally to zero. Thus they are overridden for a particular float by an `!` specifier.

```

2582 <*2ekernel>
2583 \def \suppressfloats {%
2584   \@ifnextchar [%
2585     \@flstop
2586     {\global \@colnum \z@}%
2587   }

```

Maybe this should be a loop over `#1`?

```

2588 \def \@flstop [#1]{%
2589   \if t#1%

```

```

2590     \global \@topnum \z@
2591   \fi
2592   \if b#1%
2593     \global \@botnum \z@
2594   \fi
2595 }

```

*(End of definition for \suppressfloats and \flstop.)*

Manipulation of float placement and type; both their strings and the corresponding count registers.

**\@fpstype** First a new count register to go with **\@currtype**.  
**\@reqcolroom** Then a new skip register, for information needed to remove the **\@maxsep** conservatism: it is possible that this could use a temporary register.  
**\@textfloatsheight** Finally a dimension register to hold the total height of in-text floats on the current page. This is needed to implement a major change in the functionality of **\@addtocurcol** which is, nevertheless, a bug fix. It is not local and therefore cannot be a temporary register.

```

2596 \newcount \@fpstype
2597 \newdimen \@reqcolroom
2598 \newdimen \@textfloatsheight

```

*(End of definition for \@fpstype, \@reqcolroom, and \@textfloatsheight.)*

**\saved@reqcolroom** Saved value of **\@reqcolroom**; this is needed when making several tests.

```

2599 \</2ekernel>
2600 \<*2ekernel | latexrelease>
2601 \<latexrelease>\IncludeInRelease{2025/06/01}%
2602 \<latexrelease>          {\saved@reqcolroom}{float placement calculation}%
2603 \newdimen \saved@reqcolroom
2604 \</2ekernel | latexrelease>
2605 \<latexrelease>\EndIncludeInRelease
2606 \<latexrelease>\IncludeInRelease{0000/00/00}%
2607 \<latexrelease>          {\saved@reqcolroom}{float placement calculation}%
2608 \<latexrelease>\let \saved@reqcolroom \@undefined
2609 \<latexrelease>\EndIncludeInRelease

```

*(End of definition for \saved@reqcolroom.)*

**\@fpsadddefault** Adds the default placement to what is already there.

Should not need to change this, but could do it as follows:

```

def \@fpsadddefault {%
  \@temptokena \expandafter\expandafter\expandafter
    {\csname fps@\@capttype \endcsname}%
  \edef \reserved@a {\the\@temptokena}%
  \@onelevel@sanitize \reserved@a
  \edef \@fps {\@fps\reserved@a}%
}

```

```

2610 <*2ekernel| fltrace>
2611 \def \@fpsadddefault {%
2612 <*trace>
2613   \fl@trace{fps changed from: \@fps}%
2614 </trace>
2615   \edef \@fps {\@fps\csname fps@\@capytype \endcsname}%
2616   \@latex@warning {%
2617     No positions in optional float specifier.\MessageBreak
2618     Default added (so using ‘\@fps’)}%
2619 }

```

*(End of definition for \@fpsadddefault.)*

**\@setfloattypecounts** Sets counters \@fpstype and \@currtype.

BANG == bit4 of \count\@currbox = 0.

```

2620 \def \@setfloattypecounts {%
2621   \@currtype \count\@currbox
2622   \@fpstype \count\@currbox
2623   \divide\@currtype\@xxxii \multiply\@currtype\@xxxii
2624   \advance \@fpstype -\@currtype
2625 <*trace>
2626   \fl@trace{(mod 32) fpstype: \the \@fpstype}%
2627   \fl@trace{(mult of 32) currtype: \the \@currtype}%
2628 % Tracing only: but some should be changed into real errors/warnings?
2629   \ifnum \@fpstype<\sist@n
2630     \ifnum \@fpstype=\z@
2631       \fl@trace{ERROR: no PLACEMENT, fpstype = \the \@fpstype = 0?}%
2632     \fi
2633     \ifnum \@fpstype=\@ne
2634       \fl@trace{WARNING: only h, fpstype = \the \@fpstype = 1?}%
2635     \fi
2636     \fl@trace{BANG float}%
2637   \else
2638     \ifnum \@fpstype=\sist@n
2639       \fl@trace{ERROR: no PLACEMENT, fpstype = \the \@fpstype = 16?}%
2640     \fi
2641     \ifnum \@fpstype=17
2642       \fl@trace{WARNING: only h, fpstype = \the \@fpstype = 17?}%
2643     \fi
2644     \fl@trace{ORD float}%
2645   \fi
2646 </trace>
2647 }
2648 </2ekernel| fltrace>

```

*(End of definition for \@setfloattypecounts.)*

Macros for getting, testing and setting bits of the fps.

**\@getfpsbit** Sets \@tempcnta to required bit of \count\@currbox.

```

2649 <*2ekernel>
2650 \def \@getfpsbit {%
2651   \@boxfpsbit \@currbox
2652 }

```

*(End of definition for \@getfpsbit.)*

`\@boxfpsbit` Used above.

```
2653 \def \@boxfpsbit #1#2{%  
2654     \@tempcnta \count#1%  
2655     \divide \@tempcnta #2\relax  
2656 }
```

*(End of definition for \@boxfpsbit.)*

`\@testfp` New definition of the float page test.

```
2657 \def \@testfp #1{%  
2658     \@boxfpsbit #18\relax % Really ‘#1 8’ for human readers!  
2659     \ifodd \@tempcnta  
2660     \else  
2661     \@testtrue  
2662     \fi  
2663 }
```

*(End of definition for \@testfp.)*

`\@setfpsbit` Sets required bit of `\@tempcnta` (to 1).

```
2664 \def \@setfpsbit #1{%  
2665     \@tempcntb \@tempcnta  
2666     \divide \@tempcntb #1\relax  
2667     \ifodd \@tempcntb  
2668     \else  
2669     \advance \@tempcnta #1\relax  
2670     \fi  
2671 }  
2672 </2ekernel>
```

*(End of definition for \@setfpsbit.)*

`\@resethfps` Globally adds `t` as a possible location for an `h` or `!h` only placement: this must be done using the count.

Although it will leave `\@fpstype` set to 17 even if it was originally 1, this does not matter since it is the last thing in `\@addtocurcol`.

```
2673 <*2ekernel | fltrace>  
2674 \def \@resethfps {%  
2675     \let\reserved@a\@empty  
2676     \ifnum \@fpstype=\@ne  
2677     \def \reserved@a {!}%  
2678     \@fpstype 17  
2679     \fi  
2680     \ifnum \@fpstype=17  
2681     \global \advance \count\@currbox \tw@  
2682     \@latex@warning@no@line {%  
2683         ‘\reserved@a h’ float specifier changed to ‘\reserved@a ht’}%  
2684 <*trace>  
2685     \fl@trace{%  
2686         ‘t’ added to ‘\reserved@a h’- new Count: \the \count\@currbox}%  
2687 </trace>  
2688     \fi  
2689 }
```

(End of definition for \@resetfps.)  
Special stuff for BANG floats.

\@flsetnum Ignores any zero float counter value in case BANG.

It uses a local assignment to the normally global counter: a bit naughty, perhaps?

These assignments are safe so long as the counter involved is only consulted once (i.e. only for the ‘bang float’) with the changed value. This is the case within \@addtocurcol because it is used only once within a call of the output routine (which forms a group).

For \@addtonextcol this is achieved by putting a group around its code; this is needed because it is called (by \@startcolumn) for each float which was on the deferlist. Almost identical considerations pertain to \@addtodblcol. There may be more efficient ways to handle this, but the group seems to be the simplest.

```

2690 \def \@flsetnum #1{%
2691   \*trace
2692   \fl@trace{fpstype: \the \@fpstype (flsetnum \string#1)}%
2693   \*trace
2694   \ifnum \@fpstype<\sist@n
2695     \ifnum #1=\z@
2696     \*trace
2697     \fl@trace{BANG float resetting \string#1 to 1}%
2698     \*trace
2699     #1\@ne
2700   \fi
2701   \fi
2702   \*trace
2703   \fl@trace{#1 (before) = \the #1}%
2704   \*trace
2705 }

```

(End of definition for \@flsetnum.)

\@flsettextmin This ignores \textfraction space restriction in case BANG.

```

2706 \def \@flsettextmin {%
2707   \*trace
2708   \fl@trace{fpstype: \the \@fpstype (flsettextmin)}%
2709   \*trace
2710   \ifnum \@fpstype<\sist@n
2711   \*trace
2712   \fl@trace{BANG ignoring textmin}%
2713   \*trace
2714   \@textmin \z@
2715   \else
2716   \@textmin \textfraction\@colht
2717   \*trace
2718   \fl@trace{ORD textmin = \the \@textmin}%
2719   \*trace
2720   \fi
2721 }

```

(End of definition for \@flsettextmin.)

`\@flcheckspace` This ignores space restriction in case BANG; this is still slightly conservative since it does not allow for the fact that, if there is no text in the column then `\textfloatsep` is not needed. Sets `@tempswa` true if there is room for `\@currbox`.

```

2722 </2ekernel | fltrace>
2723 <*2ekernel | fltrace | latexrelease>
2724 <latexrelease | fltrace>\IncludeInRelease{2025/06/01}%
2725 <latexrelease | fltrace>                {\@flcheckspace}{float placement calculation}%
2726 \def \@flcheckspace #1#2{%

```

When this test is executed, the value of `\@reqcolroom` may no longer be correct due to a previous test that altered it. We therefore reset it to a value saved earlier.

```

2727     \@reqcolroom \saved@reqcolroom
2728     \advance \@reqcolroom
2729     \ifx #2\@empty \textfloatsep \else \floatsep \fi
2730 <*trace>
2731     \fl@trace{colroom = \the \@colroom
2732                                     (flcheckspace \string#1 \string#2)}%
2733     \fl@trace{reqcolroom = \the \@reqcolroom
2734                                     (flcheckspace \string#1 \string#2)}%
2735 </trace>
2736     \ifdim \@colroom>\@reqcolroom
2737     \ifdim #1>\ht\@currbox
2738     \@tempswatrue
2739 <*trace>
2740     \fl@trace{Space OK: #1 = \the #1 > \the \ht \@currbox
2741                                     (flcheckspace \string#1 \string#2)}%
2742 </trace>
2743     \else
2744 <*trace>
2745     \fl@trace{fpstype: \the \@fpstype
2746                                     (flcheckspace \string#1 \string#2)}%
2747 </trace>
2748     \ifnum \@fpstype<\sixt@n
2749 <*trace>
2750     \fl@trace{BANG float ignoring #1
2751                                     (flcheckspace \string#1 \string#2):}%
2752     \fl@trace{\@spaces #1 = \the #1. Ht float: \the \ht \@currbox
2753                                     \space BANG}%
2754 </trace>
2755     \@tempswatrue
2756 <*trace>
2757     \else
2758     \fl@trace{Fail---no room (flcheckspace \string#1 \string#2)
2759                                     (fpstype \the \@fpstype=ORD?):}%
2760     \fl@trace{\@spaces #1 = \the #1. Ht float: \the \ht \@currbox
2761                                     \space ORD?}%
2762 </trace>
2763     \fi
2764     \fi
2765 <*trace>
2766     \else
2767     \fl@trace{Fail---no room at 2nd test of colroom
2768                                     (flcheckspace \string#1 \string#2)}%
2769 </trace>

```

```

2770 \fi
2771 }
2772 \if2ekernel|fltrace|latexrelease>
2773 <latexrelease|fltrace>\EndIncludeInRelease
2774 <latexrelease|fltrace>\IncludeInRelease{0000/00/00}%
2775 <latexrelease|fltrace>{\@flcheckspace}{float placement calculation}%
2776 <latexrelease|fltrace>
2777 <latexrelease|fltrace>\def \@flcheckspace #1#2{%
2778 <latexrelease|fltrace> \advance \@reqcolroom
2779 <latexrelease|fltrace> \ifx #2\@empty \textfloatsep \else \floatsep \fi
2780 <*trace>
2781 <latexrelease|fltrace> \fl@trace{colroom = \the \@colroom
2782 <latexrelease|fltrace> (flcheckspace \string#1 \string#2)}%
2783 <latexrelease|fltrace> \fl@trace{reqcolroom = \the \@reqcolroom
2784 <latexrelease|fltrace> (flcheckspace \string#1 \string#2)}%
2785 </trace>
2786 <latexrelease|fltrace> \ifdim \@colroom>\@reqcolroom
2787 <latexrelease|fltrace> \ifdim #1>\ht\@currbox
2788 <latexrelease|fltrace> \@tempwattrue
2789 <*trace>
2790 <latexrelease|fltrace> \fl@trace{Space OK: #1 = \the #1 > \the \ht \@currbox
2791 <latexrelease|fltrace> (flcheckspace \string#1 \string#2)}%
2792 </trace>
2793 <latexrelease|fltrace> \else
2794 <*trace>
2795 <latexrelease|fltrace> \fl@trace{fpstype: \the \@fpstype
2796 <latexrelease|fltrace> (flcheckspace \string#1 \string#2)}%
2797 </trace>
2798 <latexrelease|fltrace> \ifnum \@fpstype<\sist@n
2799 <*trace>
2800 <latexrelease|fltrace> \fl@trace{BANG float ignoring #1
2801 <latexrelease|fltrace> (flcheckspace \string#1 \string#2):}%
2802 <latexrelease|fltrace> \fl@trace{\@spaces #1 = \the #1. Ht float: \the \ht \@currbox
2803 <latexrelease|fltrace> \space BANG}%
2804 </trace>
2805 <latexrelease|fltrace> \@tempwattrue
2806 <*trace>
2807 <latexrelease|fltrace> \else
2808 <latexrelease|fltrace> \fl@trace{Fail---no room (flcheckspace \string#1 \string#2)
2809 <latexrelease|fltrace> (fpstype \the \@fpstype=ORD?):}%
2810 <latexrelease|fltrace> \fl@trace{\@spaces #1 = \the #1. Ht float: \the \ht \@currbox
2811 <latexrelease|fltrace> \space ORD?}%
2812 </trace>
2813 <latexrelease|fltrace> \fi
2814 <latexrelease|fltrace> \fi
2815 <*trace>
2816 <latexrelease|fltrace> \else
2817 <latexrelease|fltrace> \fl@trace{Fail---no room at 2nd test of colroom
2818 <latexrelease|fltrace> (flcheckspace \string#1 \string#2)}%
2819 </trace>
2820 <latexrelease|fltrace> \fi
2821 <latexrelease|fltrace>}
2822 <latexrelease|fltrace>\EndIncludeInRelease

```

(End of definition for \@flcheckspace.)

**\@flupdates** This updates everything when a float is placed.

```
2823 <*2ekernel>
2824 \def \@flupdates #1#2#3{%
2825     \global \advance #1\m@ne
2826     \global \advance \@colnum \m@ne
2827     \@tempdima -\ht\@currbox
2828     \advance \@tempdima
2829     -\ifx #3\@empty \textfloatsep \else \floatsep \fi
2830     \global \advance #2\@tempdima
2831     \global \advance \@colroom \@tempdima
2832     \@cons #3\@currbox
2833 }
2834 </2ekernel>
```

(End of definition for \@flupdates.)

Interesting facts about float mechanisms past and present, together with a summary of various features, some unresolved:

1. The value `\textfraction` does not affect the processing of doublecol floats: this seems sensible, but should be documented.
2. `\twocolumn` floatplacement was wrong: dbl not needed, ord needed.
3. `\@floatplacement` was not called after `\@startdblcol` or `\@topnewpage`. This has been changed; it is clearly a bug fix.
4. The use `\@topnewpage` when `\dblfigrule` is non-trivial produced a rule in the wrong place. This has been fixed by not using `\dblfigrule` when processing the ‘float’ from `\@topnewpage`.
5. If the specifier was just h and the float could not be put here, it went on the deferlist and stayed there until a clearpage. It now gets changed to a ‘th’: this is only an error-recovery action, putting just h or !h should be deprecated.
6. `\@dblmaxsep` was ‘the maximum of `\dblfloatsep` and `\dbltextfloatsep`’. But it was never used! Now gone completely, like `\@maxsep`.
7. After an h float is put on a page, it was counted as text when applying the `\textfraction` test; this is possibly too big a change although it is a bug fix?
8. Two consecutive h floats are separated by twice `\intextsep`: this could be changed to one by use of `\addvspace`, OK? Note that it would also mean that less space is put in if an h float immediately follows other spaces. This is also possibly too big a change, at least for compatibility mode? Or it may be simply wrong! It has not been changed.
9. Now `\@addtocurcol` checks first for just p fps. I think that this is an increase in efficiency, but maybe the coding should be made even more efficient.
10. `\@tryfcolumn` now tests if the list is empty first, otherwise lots of wasted time! Thus this test has been removed from `\@startcolumn`. As Frank pointed out, this makes `\@startcolumn` less efficient. But it is now the same as `\@startdblcolumn`: I can see no reason why they should be different, but which is best?

11. Why is `\@colroom` set in `\@docclearpage`?
12. Footnotes. Check what `\clearpage` does when footnotes are left over. Footnotes are not put on float pages and, also, `\@addtonextcol` ignores the existence of held-over footnotes in deciding what floats can go on the page. Not changed.
13. `\clearpage` can still lose non-boxes, at least when floats are involved. It also moves some to the ‘wrong page’, but this may be a coding problem.
14. The `!` option makes it necessary to check in `\output` that there is enough room left on the page after adding a float. (This would have been necessary anyway if anyone set `\@textmin` too close to zero! A similar danger existed also if the text in a `\twocolumn[text]` entity gets too large.) The current implementation of this also makes the normal case a little less efficient, OK? Not enough room means, at present, less than `\baselineskip`, with a warning: is this OK? Should it be made generic (another parameter)?
15. There are four possibilities for supporting this:  
`\twocolumn[\maketitle more text]`  
 One is to change `\maketitle` slightly to allow this. Another is to change `\@topnewpage` so that more than one `\twocolumn[]` command is allowed; in this case `\maketitle\twocolumn[more text]` will work. The former is more robust from the user’s viewpoint, but makes the code for `\maketitle` rather ad hoc (maybe it is already?). Another is to misuse the global `twocolumn` flag locally within `\@topnewpage`. Yet another is to move the column count register from the `multicol` package into the kernel. This has been done.
16. Where should the reinserts be put to maximise the probability that footnotes come out on the correct page? Or should we go for as much compatibility as possible (but see next item)?
17. Should we continue to support (as much as possible) `\samepage`? Some of its intended functionality is now advertised as being provided by `\enlargethispage`. Use of either is likely to result in wrongly placed footnotes, marginals, etc. Which should have priority: obeying the pagination instructions, or correct placement of notes/marginalia?
18. Is the adjustment of space to cause shrinking in the kludge-\* case correct? Should it be limited to 0pt?
19. Is the setting of `\boxmaxdepth` in `makecol` and friends needed? It only has any effect if `\@textbottom` ends with a box or rule, in which case the `vskip` to allow for its depth should also be added. If it is kept, it should probably be the last thing in the box. It has now been removed.  
  
 It would perhaps be better to document that `\@textbottom` and `\@texttop` must have natural height 0pt.
20. I cannot see why the `vskip` adjustment for the depth is needed if `boxmaxdepth` is used to ensure that there is never a too deep box.
21. The value of `\boxmaxdepth` should be explicitly set whenever necessary: it is too risky to assume that it has any particular value. Care is needed in deciding what to set it to.

It is interesting to note that the value of `\boxmaxdepth` is unique in being read before the local settings for the box group are reset; all other parameter settings which affect the box construction use their values outside the box group.

22. Should `\@maxdepth` store the setting of `\maxdepth` from `lplain`? Or should we provide a proper interface to class files for setting these?

An analysis of various other macros.

`\@opcol` should do `\@floatplacement`, but where? Right at the end, since it always occurs at the start of a column.

```
\def\@opcol{%
  % Why is this done first?
  \global \@mparbottom \z@
  \if@twocolumn
    \@outputdblcol
  \else
    \@outputpage
    % This is not needed since it is done at the end of
    %   |\@outputpage|:
    \global \@colht \textheight
  \fi}
```

Only tracing has been added to these.

```
2835 <latexrelease|fltrace>\IncludeInRelease{2017/01/01}%
2836 <latexrelease|fltrace> {\@makefcolumn}{negative height floats}%
2837 <*2ekernel|fltrace|latexrelease>
2838 \def\@makefcolumn #1{%
2839   \begingroup

2840   \@fpmin -\maxdimen

2841   \let \@testfp \@gobble
2842   \@tryfcolumn #1%
2843   \endgroup
2844   <*trace>
2845   \if@fcolmade
2846     \fl@trace{PAGE: in \string\clearpage
2847               \if@twocolumn ---twocolumn\fi---}%
2848     \fl@trace{----- float column/page completed from \string#1}%
2849     \fi
2850   </trace>
2851 }

2852 <latexrelease|fltrace>\EndIncludeInRelease
2853 <latexrelease|fltrace>\IncludeInRelease{0000/00/00}%
2854 <latexrelease|fltrace> {\@makefcolumn}{negative height floats}%
2855 <latexrelease|fltrace>\def\@makefcolumn #1{%
2856 <latexrelease|fltrace> \begingroup
2857 <latexrelease|fltrace>   \@fpmin \z@
2858 <latexrelease|fltrace>   \let \@testfp \@gobble
2859 <latexrelease|fltrace>   \@tryfcolumn #1%
2860 <latexrelease|fltrace> \endgroup
2861 <*trace>
```

```

2862 <latexrelease | fltrace> \if@fcolmade
2863 <latexrelease | fltrace> \fl@trace{PAGE: in \string\clearpage
2864 <latexrelease | fltrace> \if@twocolumn ---twocolumn\fi---}%
2865 <latexrelease | fltrace> \fl@trace{----- float column/page completed
2866 <latexrelease | fltrace> from \string#1}%
2867 <latexrelease | fltrace> \fi
2868 </trace>
2869 <latexrelease | fltrace>}
2870 <latexrelease | fltrace>\EndIncludeInRelease
2871 </2ekernel | fltrace | latexrelease>

```

This will line up the last baselines in the two columns provided they are constructed in the normal way: i.e. ending in a skip of minus the original depth, with `\@textbottom` adding nothing.

Thus again it is essential for `\@textbottom` to have depth 0pt.

```

2872 <latexrelease | fltrace>\IncludeInRelease{2025/06/01}%
2873 <latexrelease | fltrace> {\@outputdblcol}{Use new mark mechanism}%
2874 <*2ekernel | fltrace | latexrelease>

2875 \def\@outputdblcol{%
2876   \if@firstcolumn
2877     \global\@firstcolumnfalse

```

Save the left column

```

2878   \global\setbox\@leftcolumn\copy\@outputbox
2879 <fltrace> \fl@trace{PAGE: first column boxed}%

2880   \else
2881     \global\@firstcolumntrue
2882     \setbox\@outputbox\vbox{%
2883       \hb@xt@\textwidth{%
2884         \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
2885         \hfil

```

The color of the `\vrule` should be `\normalcolor` as to not inherit the color from the column.

```

2886       {\normalcolor\vrule \@width\columnseprule}%
2887       \hfil
2888       \hb@xt@\columnwidth{\box\@outputbox \hss}}}%
2889 <fltrace> \fl@trace{PAGE: second column also boxed}%
2890   \@combinedblfloats
2891   \@outputpage
2892 <fltrace> \fl@trace{PAGE: two column page completed}%
2893   \begingroup
2894     \@dblfloatplacement
2895     \@startdblcolumn
2896     \@whiles\if@fcolmade \fi{\@outputpage
2897 <fltrace> \fl@trace{PAGE: double float page completed}%
2898     \@startdblcolumn}%
2899   \endgroup
2900   \fi}%

2901 <latexrelease | fltrace>\EndIncludeInRelease
2902 <latexrelease | fltrace>\IncludeInRelease{2015/01/01}%
2903 <latexrelease | fltrace> {\@outputdblcol}{2 column marks}%
2904 <latexrelease | fltrace>\def\@outputdblcol{%

```

```

2905 <latexrelease|fltrace> \if@firstcolumn
2906 <latexrelease|fltrace> \global\@firstcolumnfalse
2907 <latexrelease|fltrace> \global\setbox\@leftcolumn\copy\@outputbox
2908 <latexrelease|fltrace> \splitmaxdepth\maxdimen
2909 <latexrelease|fltrace> \vbadness\maxdimen
2910 <latexrelease|fltrace> \setbox\@outputbox\vbox{\unvbox\@outputbox\unskip}%
2911 <latexrelease|fltrace> \setbox\@outputbox\vsplit\@outputbox to\maxdimen
2912 <latexrelease|fltrace> \toks@\expandafter{\topmark}%
2913 <latexrelease|fltrace> \xdef\@firstcoltopmark{\the\toks@}%
2914 <latexrelease|fltrace> \toks@\expandafter{\splitfirstmark}%
2915 <latexrelease|fltrace> \xdef\@firstcolfirstmark{\the\toks@}%
2916 <latexrelease|fltrace> \ifx\@firstcolfirstmark\@empty
2917 <latexrelease|fltrace> \global\let\@setmarks\relax
2918 <latexrelease|fltrace> \else
2919 <latexrelease|fltrace> \gdef\@setmarks{%
2920 <latexrelease|fltrace> \let\firstmark\@firstcolfirstmark
2921 <latexrelease|fltrace> \let\topmark\@firstcoltopmark}%
2922 <latexrelease|fltrace> \fi
2923 <latexrelease|fltrace> \else
2924 <latexrelease|fltrace> \global\@firstcolumntrue
2925 <latexrelease|fltrace> \setbox\@outputbox\vbox{%
2926 <latexrelease|fltrace> \hb@xt@\textwidth{%
2927 <latexrelease|fltrace> \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
2928 <latexrelease|fltrace> \hfil
2929 <latexrelease|fltrace> {\normalcolor\vrule \@width\columnseprule}%
2930 <latexrelease|fltrace> \hfil
2931 <latexrelease|fltrace> \hb@xt@\columnwidth{\box\@outputbox \hss}}}%
2932 <latexrelease|fltrace> \@combinedblfloats
2933 <latexrelease|fltrace> \@setmarks
2934 <latexrelease|fltrace> \@outputpage
2935 <latexrelease|fltrace> \begingroup
2936 <latexrelease|fltrace> \@dblfloatplacement
2937 <latexrelease|fltrace> \@startdblcolumn
2938 <latexrelease|fltrace> \@whilesw\if@fcolmade \fi{\@outputpage
2939 <latexrelease|fltrace> \@startdblcolumn}%
2940 <latexrelease|fltrace> \endgroup
2941 <latexrelease|fltrace> \fi}
2942 <latexrelease|fltrace> \EndIncludeInRelease

2943 <latexrelease|fltrace> \IncludeInRelease{0000/00/00}%
2944 <latexrelease|fltrace> {\@outputdblcol}{2 column marks}%
2945 <latexrelease|fltrace> \def\@outputdblcol{%
2946 <latexrelease|fltrace> \if@firstcolumn
2947 <latexrelease|fltrace> \global \@firstcolumnfalse
2948 <latexrelease|fltrace> \global \setbox\@leftcolumn \box\@outputbox
2949 <*trace>
2950 <latexrelease|fltrace> \fl@trace{PAGE: first column boxed}%
2951 </trace>
2952 <latexrelease|fltrace> \else
2953 <latexrelease|fltrace> \global \@firstcolumntrue
2954 <latexrelease|fltrace> \setbox\@outputbox \vbox {%
2955 <latexrelease|fltrace> \hb@xt@\textwidth {%
2956 <latexrelease|fltrace> \hb@xt@\columnwidth {%
2957 <latexrelease|fltrace> \box\@leftcolumn \hss}%
2958 <latexrelease|fltrace> \hfil

```

```

2959 <latexrelease | fltrace>                {\normalcolor\vrule
2960 <latexrelease | fltrace>                \@width\columnseprule}%
2961 <latexrelease | fltrace>                \hfil
2962 <latexrelease | fltrace>                \hb@xt@\columnwidth {%
2963 <latexrelease | fltrace>                \box\@outputbox \hss}%
2964 <latexrelease | fltrace>                }%
2965 <latexrelease | fltrace>                }%
2966 <*trace>
2967 <latexrelease | fltrace>                \fl@trace{PAGE: second column also boxed}%
2968 </trace>
2969 <latexrelease | fltrace>                \@combinedblfloats
2970 <latexrelease | fltrace>                \@outputpage
2971 <*trace>
2972 <latexrelease | fltrace>                \fl@trace{PAGE: two column page completed}%
2973 </trace>
2974 <latexrelease | fltrace>                \begingroup
2975 <latexrelease | fltrace>                \@dblfloatplacement
2976 <latexrelease | fltrace>                \@startdblcolumn

```

This loop could be replaced by an `\expandafter` tail recursion in `\@startdblcolumn`.

```

2977 <latexrelease | fltrace>                \@whiles\if@fcolmade \fi
2978 <latexrelease | fltrace>                {\@outputpage
2979 <*trace>
2980 <latexrelease | fltrace>                \fl@trace{PAGE: double float page completed}%
2981 </trace>
2982 <latexrelease | fltrace>                \@startdblcolumn}%
2983 <latexrelease | fltrace>                \endgroup
2984 <latexrelease | fltrace> \fi
2985 <latexrelease | fltrace>}%
2986 <latexrelease | fltrace>\EndIncludeInRelease
2987 </2ekernel | fltrace | latexrelease>

```

## 2.2.4 Float placement parameters

The main purpose of this section is to ensure that all the float-placement parameters which need to be set in a class file or package have been declared. It also describes their use and sets values for them which are reasonable for typical documents using US letter or A4 sized paper.

### Limits for the placement of floating objects

**\c@topnumber** This counter holds the maximum number of floats that can appear at the top of a text page or column.

```

2988 <*2ekernel>
2989 \newcount\c@topnumber
2990 \setcounter{topnumber}{2}

```

(End of definition for `\c@topnumber`.)

**\topfraction** This macro holds the maximum proportion (as a decimal number) of a text page or column that can be occupied by floats at the top.

```

2991 \newcommand\topfraction{.7}

```

*(End of definition for \topfraction.)*

**\c@bottomnumber** This counter holds the maximum number of floats that can appear at the bottom of a text page or column.

2992 `\newcount\c@bottomnumber`

2993 `\setcounter{bottomnumber}{1}`

*(End of definition for \c@bottomnumber.)*

**\bottomfraction** This macro holds the maximum proportion (as a decimal number) of a text page or column that can be occupied by floats at the bottom.

2994 `\newcommand\bottomfraction{.3}`

*(End of definition for \bottomfraction.)*

**\c@totalnumber** This counter holds the maximum number of floats that can appear on any text page or column.

2995 `\newcount\c@totalnumber`

2996 `\setcounter{totalnumber}{3}`

*(End of definition for \c@totalnumber.)*

**\textfraction** This macro holds the minimum proportion (as a decimal number) of a text page or column that must be occupied by text.

2997 `\newcommand\textfraction{.2}`

*(End of definition for \textfraction.)*

**\floatpagefraction** This macro holds the minimum proportion (as a decimal number) of a page or column that must be occupied by floating objects before a ‘float page’ is produced.

2998 `\newcommand\floatpagefraction{.5}`

*(End of definition for \floatpagefraction.)*

**\c@dbltopnumber** This counter holds the maximum number of double-column floats that can appear on the top of a two-column text page.

2999 `\newcount\c@dbltopnumber`

3000 `\setcounter{dbltopnumber}{2}`

*(End of definition for \c@dbltopnumber.)*

**\dbltopfraction** This macro holds the maximum proportion (as a decimal number) of a two-column text page that can be occupied by double-column floats at the top.

3001 `\newcommand\dbltopfraction{.7}`

*(End of definition for \dbltopfraction.)*

**\dblfloatpagefraction** This macro holds the minimum proportion (as a decimal number) of a page that must be occupied by double-column floating objects before a ‘double-column float page’ is produced.

3002 `\newcommand\dblfloatpagefraction{.5}`

*(End of definition for \dblfloatpagefraction.)*

## Floats on a text page

`\floatsep`  
`\textfloatsep`  
`\intextsep` When a floating object is placed on a page with text, these parameters control the separation between the float and the other objects on the page. These parameters are used for both one-column mode and single-column floats in two-column mode. They are all rubber lengths.

`\floatsep` is the space between adjacent floats that are placed at the top or bottom of the text page or column.

`\textfloatsep` is the space between the main text and floats at the top or bottom of the page or column.

`\intextsep` is the space between in-text floats and the text.

```
3003 \newskip\floatsep
3004 \newskip\textfloatsep
3005 \newskip\intextsep
3006 \setlength\floatsep {12\p@ \@plus 2\p@ \@minus 2\p@}
3007 \setlength\textfloatsep{20\p@ \@plus 2\p@ \@minus 4\p@}
3008 \setlength\intextsep {12\p@ \@plus 2\p@ \@minus 2\p@}
```

*(End of definition for `\floatsep`, `\textfloatsep`, and `\intextsep`.)*

`\dblfloatsep`  
`\dbltextfloatsep` When double-column floats (floating objects that span the whole `\textwidth`) are placed at the top of a text page in two-column mode, the separation between the float and the text is controlled by `\dblfloatsep` and `\dbltextfloatsep`. They are rubber lengths.

`\dblfloatsep` is the space between adjacent double-column floats placed at the top of the text page.

`\dbltextfloatsep` is the space between the main text and double-column floats at the top of the page.

```
3009 \newskip\dblfloatsep
3010 \newskip\dbltextfloatsep
3011 \setlength\dblfloatsep {12\p@ \@plus 2\p@ \@minus 2\p@}
3012 \setlength\dbltextfloatsep{20\p@ \@plus 2\p@ \@minus 4\p@}
```

*(End of definition for `\dblfloatsep` and `\dbltextfloatsep`.)*

## Floats on their own page or column

`\@fptop`  
`\@fpsep`  
`\@fpbot` When floating objects are placed on a separate page or column, called a ‘float page’, the layout of the page is controlled by these parameters, which are rubber lengths.

At the top of the page `\@fptop` is inserted; typically this supplies some stretchable whitespace. At the bottom of the page `\@fpbot` is inserted. Between adjacent floats `\@fpsep` is inserted.

These parameters are used for all floating objects on a ‘float page’ in one-column mode, and for single-column floats in two-column mode.

Note that at least one of the two parameters `\@fptop` and `\@fpbot` should contain a `plus ...fil` so as to fill the remaining empty space.

```
3013 \newskip\@fptop
3014 \newskip\@fpsep
3015 \newskip\@fpbot
3016 \setlength\@fptop{0\p@ \@plus 1fil}
3017 \setlength\@fpsep{8\p@ \@plus 2fil}
3018 \setlength\@fpbot{0\p@ \@plus 1fil}
```

*(End of definition for `\@fptop`, `\@fpsep`, and `\@fpbot`.)*

`\@dblftop` Double-column ‘float pages’ in two-column mode use similar parameters.

`\@dblpsep` 3019 `\newskip\@dblftop`

`\@dblpbot` 3020 `\newskip\@dblpsep`

3021 `\newskip\@dblpbot`

3022 `\setlength\@dblftop{0\p@ \@plus 1fil}`

3023 `\setlength\@dblpsep{8\p@ \@plus 2fil}`

3024 `\setlength\@dblpbot{0\p@ \@plus 1fil}`

*(End of definition for \@dblftop, \@dblpsep, and \@dblpbot.)*

`\topfigrule` The macros can be used to put in rules between floats and text; whatever they insert

`\botfigrule` should be vertical mode material which takes up zero space.

`\dblfigrule` 3025 `\let\topfigrule=\relax`

3026 `\let\botfigrule=\relax`

3027 `\let\dblfigrule=\relax`

3028 `\</2ekernel>`

*(End of definition for \topfigrule, \botfigrule, and \dblfigrule.)*

## File 55

# ltagging.dtx

1  $\langle *2\text{kernel} \mid \text{latexrelease} \rangle$

2  $\backslash \text{ExplSyntaxOn}$

## 1 General support for tagged output

$\backslash \text{SuspendTagging}$

$\backslash \text{ResumeTagging}$

$\backslash \text{tag\_suspend:n}$

$\backslash \text{tag\_resume:n}$

There are places in code where it is important to stop any tagging activities, e.g., when we are doing trial typesetting that it is done several times. In such a case one must tag only the final version that is actually used, otherwise tagging structures are generated which then do not end up in the PDF and confuse the mechanism. For this we have two commands that can be used in packages:  $\backslash \text{SuspendTagging}$  and  $\backslash \text{ResumeTagging}$  (with corresponding L3 programming layer commands). They are available as part of the L<sup>A</sup>T<sub>E</sub>X kernel, so that they can be safely used in packages whether or not tagging is requested. They all take a string argument that is used for debugging to easily identify why tagging was suspended or restarted, for example, in *tabularx* you find  $\backslash \text{SuspendTagging}\{\text{tabularx}\}$ . By default these four commands do nothing.

The argument is used literally (in  $\backslash \text{typeout}$  messages) without any expansion when debugging is turned on and otherwise it is not used at all. This means it is safe to write something like  $\backslash \text{SuspendTagging}\{\backslash \text{foo}\}$  or even  $\backslash \text{SuspendTagging}\backslash \text{foo}$  which means L<sup>A</sup>T<sub>E</sub>X has to parse only a single token instead of putting a string of characters into the argument. This means a tiny speed improvement but with many such debugging strings...

$\backslash \text{NewTaggingSocket}$

$\backslash \text{NewTaggingSocketPlug}$

$\backslash \text{AssignTaggingSocketPlug}$

Tagging sockets are implemented as normal sockets but with a name that starts with *tagsupport/* and some special conventions how their arguments (if any) are to be interpreted. This means in principle one can use the standard socket commands, which is what we started out with.

However, providing dedicated declaration commands is more convenient and helps in keeping the interfaces clearer and simpler, e.g.,  $\backslash \text{NewTaggingSocket}$  not only declares the socket but also automatically sets up necessary plugs and assigns a suitable default plug when tagging is not enabled.

$\backslash \text{NewTaggingSocketPlug}$  and  $\backslash \text{AssignTaggingSocketPlug}$  on the other hand are mainly syntactic sugar and do nothing more than adding the *tagsupport/* to the socket name behind the scenes.

$\backslash \text{UseTaggingSocket}$

$\backslash \text{tag\_socket\_use:n}$

$\backslash \text{tag\_socket\_use:nn}$

$\backslash \text{tag\_socket\_use:nnn}$

Given that we sometimes have to suspend tagging, it would be fairly inefficient to put different plugs into these sockets whenever that happens. We therefore offer  $\backslash \text{UseTaggingSocket}$  which is like  $\backslash \text{UseSocket}$  except that it expects a socket starting with *tagsupport/* but the socket name is specified without this prefix, i.e.,

$\backslash \text{UseTaggingSocket}\{\text{foo}\} \rightarrow \backslash \text{UseSocket}\{\text{tagsupport}/\text{foo}\}$

Beside being slightly shorter, the big advantage is that this way we can change  $\backslash \text{UseTaggingSocket}$  to do nothing by switching a boolean instead of changing the plugs of the tagging support sockets back and forth.

Usually, these sockets have (beside the default plug defined for every socket) one additional plug defined and directly assigned. This plug is used when tagging is active. There may be more plugs, e.g., tagging with special debugging or special behavior depending on the class or PDF version etc., but right now it is usually just on or off.

When tagging is suspended they all have the same predefined behavior: The sockets with zero arguments do nothing. The sockets with one argument gobble their argument. The sockets with two arguments will drop their first argument and pass the second unchanged.

It is possible to use the tagging support sockets with `\UseSocket` directly, but in this case the socket remains active if `\SuspendTagging` is in force. There may be reasons for doing that but in general we expect to always use `\UseTaggingSocket`.

`\UseExpandableTaggingSocket` For special cases like in some `\halign` contexts we need a fully expandable version of the command. For these cases, `\UseExpandableTaggingSocket` can be used. To allow being expandable, it does not output any debugging information if `\DebugSocketsOn` is in effect and therefore should be avoided whenever possible.

The L3 programming layer versions `\tag_socket_use_expandable:n`, `\tag_socket_use:n`, `\tag_socket_use:nn`, and `\tag_socket_use:nnn` are slightly more efficient than `\UseTaggingSocket` because they do not have to determine how many arguments the socket takes when disabling it.

`\MathCollectTrue` The tagging of math has to collect/grab the math first. This is not wanted for all uses of `$`. These command allow to control the behavior of the math shift token. Without `\MathCollectFalse` the math tagging code they do nothing. Their behavior with the math tagging code is documented in `latex-lab-math.pdf`

`\MathMLintent` These two commands take two arguments. The first argument is the value of the `\MathMLarg` `intent` or `arg` attribute to be added to the MathML generated by the term in the second argument. By default the commands are no-op and discard the first argument and expand to the second. If `luamml` is loaded via the math tagging code, then these commands are redefined. They could also potentially be used by other `TeX` to MathML convertors to control the generated MathML.

`\NewStructureName` Structure elements in a document can use as tag a name from the standard PDF namespaces like `Sect`, `H1` or `Figure` but they can also use new names (which then must be rolemapped to a standard name). The second option is useful for three reasons:

- It looks nicer, if, e.g., a bible uses tag names like `Testament` or `Chapter` or `Book` instead of `Sect`.
- It is possible to formulate additional constraint on such structures in a Schema and thus ensure that there is no `Testament` inside a `Book`, something that can not be done if `Sect` is used everywhere.
- We can provide a uniform LaTeX set of names for tags.

To make it possible to adapt the tag names of a structure in document, the tag name should be stored in a command. These three commands offer an interface to declare, use and reassign such symbolic structure names. `\NewStructureName` takes one argument and declares the internal command, initially its value is `NonStruct`. The expandable command `\UseStructureName` takes one argument and allows to use the stored value. `\AssignStructureRole` takes two arguments. The first is a symbolic structure names, the second a role which should be a simply string allowed as a tag name. When the tagging code is loaded `\AssignStructureRole` is redefined to setup the rolemapping, see the description in `latex-lab-namespace.dtx`. There is also a description of the naming scheme and a list of the already predeclared names.

## 2 Implementation

`\tag_suspend:n` In the kernel, these commands get dummy definitions so that they can be used without harm in packages. The real definition is used when tagging gets enabled.

`\tag_resume:n`

`\SuspendTagging`     3 `\cs_new_eq:NN \tag_suspend:n \use_none:n`

`\ResumeTagging`     4 `\cs_new_eq:NN \tag_resume:n \use_none:n`

5 `\cs_new_protected:Npn \SuspendTagging #1 { \tag_suspend:n {#1} }`

6 `\cs_new_protected:Npn \ResumeTagging #1 { \tag_resume:n {#1} }`

*(End of definition for \tag\_suspend:n and others.)*

`\NewTaggingSocket` Initialize a new tagging socket and assign it a suitable plug.

```
7 \cs_new_protected:Npn \NewTaggingSocket #1 #2 {
8   \socket_new:nn { tagsupport / #1 } { #2 }
9   \int_case:nnF
10     { #2 }
11     {
12       0 \prg_do_nothing:
13       1 { \socket_assign_plug:nn { tagsupport / #1 } { noop } }
```

Tagging sockets with two arguments use a special **transparent** plug that just passes the second argument. Its already assigned so we only have to alter it.

```
14       2 { \socket_new_plug:nnn { tagsupport / #1 } { transparent }
15           { ##2 }
16           \socket_assign_plug:nn { tagsupport / #1 } { transparent } }
17     }
18     \ERRORnewtaggingsocket % that should get a proper error message
19 }
```

*(End of definition for \NewTaggingSocket.)*

`\NewTaggingSocketPlug`

`\AssignTaggingSocketPlug`

```
20 \cs_new_protected:Npn \NewTaggingSocketPlug #1 {
21   \NewSocketPlug { tagsupport/ #1 }
22 }
23 \cs_new_protected:Npn \AssignTaggingSocketPlug #1 {
24   \AssignSocketPlug { tagsupport/ #1 }
25 }
```

*(End of definition for \NewTaggingSocketPlug and \AssignTaggingSocketPlug.)*

`\tag_socket_use:n` Again this is not the final definition for the kernel; it is just a version to get going while some parts of the kernel support are still missing.

`\tag_socket_use:nn`

`\tag_socket_use:nnn`     26 `\prg_new_conditional:Npnn \tag_if_active: { p , T , TF , F }`

`\tag_socket_use_expandable:n`     27 `{ \prg_return_false: }`

`\UseTaggingSocket`

`\UseExpandableTaggingSocket`

Dummy definitions in the kernel. These definitions will get updated in `tagpdf`. The default in the kernel is simply to get rid of the first argument, while the second argument is preserved if present:

```
28 \cs_new:Npn \tag_socket_use_expandable:n #1 { }
29 \cs_new_protected:Npn \tag_socket_use:n #1 { }
30 \cs_new_protected:Npn \tag_socket_use:nn #1#2 { }
31 \cs_new_protected:Npn \tag_socket_use:nnn #1#2#3 { #3 }
32 \cs_new_protected:Npn \UseTaggingSocket #1 { }
```

```

33 \int_case:nnF
34 { \int_use:c { c__socket_taggsupport/#1_args_int } }
35 {
36 0 \prg_do_nothing:
37 1 \use_none:n
38 2 \use_ii:nn

```

We do not expect tagging sockets with more than one or two arguments, so for now we only provide those.

```

39 }
40 \ERRORusetaggingsocket % that should get a proper error message
41 }

```

The same as an expandable command:

```

42 \cs_new:Npn \UseExpandableTaggingSocket #1 {
43 \int_case:nnF
44 { \int_use:c { c__socket_taggsupport/#1_args_int } }
45 {
46 0 \prg_do_nothing:
47 1 \use_none:n
48 2 \use_ii:nn
49 }
50 \ERRORusetaggingsocket % that should get a proper error message
51 }

```

*(End of definition for \tag\_socket\_use:n and others.)*

## 2.1 Math collection

The documentation is in latex-lab-math.

```

\MathCollectTrue
\MathCollectFalse
52 \cs_new_protected:Npn \MathCollectTrue{}
53 \cs_new_protected:Npn \MathCollectFalse{}

```

*(End of definition for \MathCollectTrue and \MathCollectFalse.)*

## 2.2 Tagging sockets

This collects tagging sockets that should be generally available so that they can also be used even if the tagging code is not loaded.

## 2.3 Generic sockets

These sockets are used in various places and should not be reassigned globally.

**mc** (*tag socket*) At first a generic socket to surround content with the mc-commands. The first argument can be used to pass options like **artifact**

```

54 \NewTaggingSocket{mc}{2}
55 \NewTaggingSocketPlug{mc}{kernel}
56 {
57 \tag_mc_begin:n {#1}
58 #2
59 \tag_mc_end:
60 }
61 \AssignTaggingSocketPlug{mc}{kernel}

```

**struct-mc** (*tag socket*) A socket to surround content with a structure and an mc-command. With the first argument the tag and other options can be set.

```

62 \NewTaggingSocket{struct-mc}{2}
63 \NewTaggingSocketPlug{struct-mc}{kernel}
64 {
65   \tag_struct_begin:n{#1}
66   \tag_mc_begin:n {}
67   #2
68   \tag_mc_end:
69   \tag_struct_end:
70 }
71 \AssignTaggingSocketPlug{struct-mc}{kernel}

```

### 2.3.1 Tagging support for paragraph setup

Paragraphs are tagged through the code in the para/hooks. This code is sometimes adjusted, e.g. to produce a “flattened” paragraph or to use a different tag. Sockets related to such code parts are collected here.

**\l\_\_tag\_block\_flattened\_level\_int** The block code needs to know if they are nested blockenvs inside a flattened environment. For this it uses a counter. Inside some contexts, e.g. at the begin of a minipage or a footnote this counter must be reset. We therefore define the counter here so that we can use it in the following socket.

```

72 \int_new:N \l__tag_block_flattened_level_int
(End of definition for \l__tag_block_flattened_level_int.)

```

**para/on** (*tag socket*) These sockets allow paragraph tagging to be enabled/disabled.

**para/off** (*tag socket*)

```

73 \NewTaggingSocket{para/on}{0}
74 \NewTaggingSocketPlug{para/on}{kernel}{\bool_set_true:N \l__tag_para_bool}
75 \NewTaggingSocket{para/off}{0}
76 \NewTaggingSocketPlug{para/off}{kernel}{\bool_set_false:N \l__tag_para_bool}
77 \AssignTaggingSocketPlug{para/on}{kernel}
78 \AssignTaggingSocketPlug{para/off}{kernel}

```

**para/restore** (*tag socket*) This socket restores the para related settings to their default. It should be used in places where “normal” paragraph tagging must be ensured, for example at the begin of a footnote.

```

79 \NewTaggingSocket{para/restore}{0}

```

**default** (*tag plug*)

```

80 \NewTaggingSocketPlug{para/restore}{default}
81 {
82   \tl_set:Nn \l__tag_para_main_tag_tl {\UseStructureName{para/semantic}}
83   \tl_set_eq:NN \l__tag_para_tag_tl \l__tag_para_tag_default_tl
84   \bool_set_false:N \l__tag_para_flattened_bool
85   \int_zero:N \l__tag_block_flattened_level_int
86   \bool_set_true:N \l__tag_para_bool
87 }
88 \AssignTaggingSocketPlug{para/restore}{default}

```

`para/begin` (*tag socket*) These sockets were previously defined in tagpdf. There are the main sockets to handle  
`para/end` (*tag socket*) the paragraph tagging when it is active (i.e., when `para/on` or `para/restore` was executed earlier).

```
89 \NewTaggingSocket{para/begin}{0}
90 \NewTaggingSocket{para/end}{0}
```

Until tagpdf is updated we need to provide the plain and block plugs

```
91 \NewTaggingSocketPlug{para/begin}{plain}{}
92 \NewTaggingSocketPlug{para/end}{plain}{}
93 \NewTaggingSocketPlug{para/begin}{block}{}
94 \NewTaggingSocketPlug{para/end}{block}{}
95
```

`para/semantic/begin` (*tag socket*) These sockets handle the `begin` and `end` structure. These are stored in sockets of their  
`para/semantic/end` (*tag socket*) own to be able to disable them globally.

```
96 \NewTaggingSocket{para/semantic/begin}{1}
97 \NewTaggingSocket{para/semantic/end}{1}
```

`(para/semantic/begin)` (*tag plug*) This tagging socket adds a `structure`. The argument allows to add additional commands like the command that puts the structure number of this command on a stack.

```
98 \tl_new:N \l__tag_para_attr_class_tl
99 \NewTaggingSocketPlug{para/semantic/begin}{kernel}
100 {
101   \__tag_gincr_para_main_begin_int:
102   \tag_struct_begin:n
103     {
104       tag=\l__tag_para_main_tag_tl,
105       attribute-class=\l__tag_para_main_attr_class_tl,
106     }
107   #1
108 }
```

`(para/semantic/end)` (*tag plug*) This socket should be used if a `-structure` is closed. The argument allows e.g. to add debug info.

```
109 \NewTaggingSocketPlug{para/semantic/end}{kernel}
110 {
111   #1
112   \__tag_gincr_para_main_end_int:
113   \tag_struct_end:
114 }
```

And now we assign these plugs:

```
115 \AssignTaggingSocketPlug{para/semantic/begin}{kernel}
116 \AssignTaggingSocketPlug{para/semantic/end}{kernel}
```

`kernel (para/begin)` (*tag plug*) This plug is similar to the block socket currently defined in tagpdf and should overwrite it.

```
117 \NewTaggingSocketPlug{para/begin}{kernel}
118 {
119   \bool_if:NT \l__tag_para_bool
120     {
121       \legacy_if:nF { @inlabel }
122     }
```

```

123     \__tag_check_typeout_v:n
124     {==>~ @endpe = \legacy_if:nTF { @endpe }{true}{false} \on@line }
125     \legacy_if:nF { @endpe }
126     {
127         \bool_if:NF \l__tag_para_flattened_bool
128         {
129             \UseTaggingSocket{para/semantic/begin}
130             { \__tag_para_main_store_struct: }
131         }
132     }
133     \__tag_gincr_para_begin_int:
134     \__tag_check_typeout_v:n {==>~increment~ P \on@line }
135     \tag_struct_begin:n
136     {
137         tag=\l__tag_para_tag_tl
138         ,attribute-class=\l__tag_para_attr_class_tl
139     }
140     \__tag_check_para_begin_show:nn {green}{\PARALABEL}
141     \tag_mc_begin:n {}
142 }
143 }
144 }

```

`kernel (para/end) (tag plug)` This socket is used at the end of paragraphs.

```

145 \NewTaggingSocketPlug{para/end}{kernel}
146 {
147     \bool_if:NT \l__tag_para_bool
148     {
149         \__tag_gincr_para_end_int:
150         \__tag_check_typeout_v:n {==>~increment~ /P \on@line }
151         \tag_mc_end:
152         \__tag_check_para_end_show:nn {red}{ }
153         \tag_struct_end:
154         \bool_if:NF \l__tag_para_flattened_bool
155         {
156             \UseTaggingSocket{para/semantic/end}{ }
157         }
158     }
159 }

```

As tagpdf is currently assigning the sockets after the block code we assign if even later (for now):

```

160 \AddToHook{package/latex-lab-testphase-sec/after}
161 {
162     \AssignTaggingSocketPlug{para/begin}{kernel}
163     \AssignTaggingSocketPlug{para/end}{kernel}
164 }

```

### 2.3.2 Tagging socket for targets

`refstepcounter (tag socket)` When tagging is active we want to track the current structure number when targets are set. This will be mostly used in `\refstepcounter` but also if targets are set manually.

```

165 \NewTaggingSocket{recordtarget}{0}

```

kernel (recordtarget) (tag plug)

```
166 %
167 \NewTaggingSocketPlug{recordtarget}{kernel}
168 {
169   \tl_if_blank:VF \@currentHref
170   {
171     \prop_gput:Nee
172       \g__tag_struct_dest_num_prop
173       {\@currentHref}
174       {\tag_get:n{struct_num}}
175   }
176 }
177 \AssignTaggingSocketPlug{recordtarget}{kernel}
178 \ExplSyntaxOff
```

### 2.3.3 Tagging Sockets for lists and blocks

block/list/label (tag socket) A tagging socket around the label in a list.

```
179 \NewTaggingSocket{block/list/label}{2}
```

block/recipe (tag socket) A tagging socket to set the tagging recipe.

```
180 \NewTaggingSocket{block/recipe}{1}
```

### 2.3.4 Tagging sockets for headings

Tagging headings is quite tricky. The sockets (and plugs) used by the kernel definitions often expect specially formatted arguments. For this reason some of them may not be suitable in other classes or packages. In that case additional sockets (or plugs) might be required.

sec/begin (tag socket) These two sockets should surround the whole section by a **Sect** structure. They should be suited also for classes and packages. The begin socket takes two brace groups as argument: the level and key for the structure (typically **tag=somename**), the end socket takes as argument a level.

```
181 \NewTaggingSocket{sec/begin}{1}
182 \NewTaggingSocket{sec/end}{1}
```

sec/title/begin (tag socket) These two sockets are used around display heading where the number is on a line of its own. The argument of the begin socket consists of two brace groups containing the level and the title.

```
183 \NewTaggingSocket{sec/title/begin}{1}
184 \NewTaggingSocket{sec/title/end}{0}
```

sec/title/hang (tag socket) This socket is used in headings with hanging number.

```
185 \NewTaggingSocket{sec/title/hang}{2}
```

sec/title/init (tag socket) These sockets are used by run-in heading to initialize tagging and to split heading and following text and tag the title.

/title/runin/number (tag socket)

```
186 \NewTaggingSocket{sec/title/init}{1}
187 \NewTaggingSocket{sec/title/split}{0}
188 \NewTaggingSocket{sec/title/runin/number}{2}
```

sec/title/number (tag socket) This is a socket to tag the number. It takes two arguments: the level and the content.

```
189 \NewTaggingSocket{sec/title/number}{2}
```

### 2.3.5 Tagging sockets for toc

`contentsline/before` (*tag socket*) Tagging sockets at the begin and end of contentsline. They receive *all* contentsline arguments as one argument in four brace groups. The socket code should then use the parts it needs.

```
190 \NewTaggingSocket{toc/contentsline/before}{1}
191 \NewTaggingSocket{toc/contentsline/after}{1}
```

`toc/starttoc/before` (*tag socket*) Tagging sockets for the begin and end of start of `\@starttoc`. They take one argument, `toc/starttoc/after` (*tag socket*) the extension.

```
192 \NewTaggingSocket{toc/starttoc/before}{1}
193 \NewTaggingSocket{toc/starttoc/after}{1}
```

`toc/leaders/before` (*tag socket*) Tagging sockets to make the dot leaders an artifact. They do not take an argument.

`toc/leaders/after` (*tag socket*)

```
194 \NewTaggingSocket{toc/leaders/before}{0}
195 \NewTaggingSocket{toc/leaders/after}{0}
```

### 2.3.6 Tagging support for marginpar

`marginpar/begin` (*tag socket*)

`marginpar/end` (*tag socket*)

```
196 \NewTaggingSocket{marginpar/begin}{0}
197 \NewTaggingSocket{marginpar/end}{0}
```

### 2.3.7 Tagging support for table/tabular packages

The code uses a number of sockets to inject the tagging commands. These can be easily set to a noop-plug in case the automated tagging is not wanted.

`tbl/cell/begin` (*tag socket*) At first sockets for the begin and end of cells and table rows:

```
tbl/cell/end (tag socket) 198 \NewTaggingSocket{tbl/cell/begin}{0}
tbl/pcell/end (tag socket) 199 \NewTaggingSocket{tbl/cell/end}{0}
tbl/pcell/end (tag socket) 200 \NewTaggingSocket{tbl/row/begin}{0}
tbl/row/begin (tag socket) 201 \NewTaggingSocket{tbl/row/end}{0}
tbl/row/end (tag socket)
```

Multi-line cells have their own sockets (as they start out in vertical mode and need different treatment).

```
202 \NewTaggingSocket{tbl/pcell/begin}{0}
203 \NewTaggingSocket{tbl/pcell/end}{0}
```

`tbl/init` (*tag socket*) This socket should be at the begin of the table, inside a group. It is used for settings such as disabling para-tagging inside the table. This socket can perhaps be merged later into the begin-sockets.

```
204 \NewTaggingSocket{tbl/init}{0}
```

`tbl/init/celldata` (*tag socket*) This socket is used in `\tbl_init_cell_data_for_table`, the command that stores and initialize cell data to handle nested tables. It can be used to restore similar tagging related values

```
205 \NewTaggingSocket{tbl/init/celldata}{0}
```

`tbl/finalize` (*tag socket*) To fine tune the structure (change cells to header cells, remove unwanted structures, move a foot to the end, etc.). We also need a socket that is executed at the end of the table but *before* all the variables are restored to the outer or default values. The code in the socket can make assignments, but probably shouldn't do typesetting and not write whatsits.

206 `\NewTaggingSocket{tbl/finalize}{0}`

`tbl/restore/celldata` (*tag socket*) This socket is used in `\tbl_restore_outer_cell_data:`, the command that restores cell data when quitting a nested table. It can be used to restore similar tagging related values

207 `\NewTaggingSocket{tbl/restore/celldata}{0}`

`tbl/colspan` (*tag socket*) This socket is used to manage spanning cells, e.g., a `\multicolumn`. It expects one argument (the number of cells spanned) and if tagging is enabled set appropriate tag attributes in the background. We probably need a similar socket for row spans eventually.

208 `\NewTaggingSocket{tbl/colspan}{1}`

`tbl/hmode/begin` (*tag socket*) These sockets are used in the begin and end code of environments, to allow a fast enabling  
`tbl/hmode/end` (*tag socket*) and disabling of the tagging. We distinguish between tables that can be used inside  
`tbl/vmode/begin` (*tag socket*) paragraphs and standalone tables such as `longtable` that are always in vertical mode.  
`tbl/vmode/end` (*tag socket*)

209 `\NewTaggingSocket{tbl/hmode/begin}{0}`

210 `\NewTaggingSocket{tbl/hmode/end}{0}`

211 `\NewTaggingSocket{tbl/vmode/begin}{0}`

212 `\NewTaggingSocket{tbl/vmode/end}{0}`

`tbl/longtable/init` (*tag socket*) `longtable` needs its own sockets to fine tune the structure. Simply switching the plug  
`/longtable/finalize` (*tag socket*) in the previous socket interferes with enabling/disabling the tagging.

213 `\NewTaggingSocket{tbl/longtable/init}{0}`

214 `\NewTaggingSocket{tbl/longtable/finalize}{0}`

`tbl/longtable/head` (*tag socket*) Header and footer boxes need special handling because they are repeatedly used.

`tbl/longtable/foot` (*tag socket*) 215 `\NewTaggingSocket{tbl/longtable/head}{0}`

216 `\NewTaggingSocket{tbl/longtable/foot}{0}`

`tbl/leaders/begin` (*tag socket*) Sockets around leaders such as rules or dotted lines, that should be tagged as artifacts,  
`tbl/leaders/end` (*tag socket*) used, for example, in `\cline`.

217 `\NewTaggingSocket{tbl/leaders/begin}{0}`

218 `\NewTaggingSocket{tbl/leaders/end}{0}`

### 2.3.8 Tagging Support for floats

`float/hmode/begin` (*tag socket*) These sockets are used if the float is called in hmode.

`float/hmode/end` (*tag socket*) 219 `\NewTaggingSocket{float/hmode/begin}{0}`

220 `\NewTaggingSocket{float/hmode/end}{0}`

`float/begin` (*tag socket*) These sockets start and stop the float structure.

`float/end` (*tag socket*) 221 `\NewTaggingSocket{float/begin}{0}`

222 `\NewTaggingSocket{float/end}{0}`

`caption/begin` (*tag socket*) These sockets are used in `\@makecaption`. They open and close the `Caption` structure.  
`caption/end` (*tag socket*) Their default plugs assume that they are used in vmode. The argument of the begin socket is the structure number of the parent float. If it is empty the current structure number is used.

```
223 \NewTaggingSocket{caption/begin}{1}
224 \NewTaggingSocket{caption/end}{0}
```

`caption/label/begin` (*tag socket*) These sockets are used in `\@makecaption` around the label. Their default plugs ensure that the label is outside the paragraph and that the rest of the caption uses flattened para mode. If the caption is not in a hbox, the `para/begin` socket should follow to properly start the paragraph.

```
225 \NewTaggingSocket{caption/label/begin}{0}
226 \NewTaggingSocket{caption/label/end}{0}
```

## 2.4 Tagging support for output routines

`build/page/header` (*tag socket*) These sockets receive the formatted running header/footer in its second argument (the first is not used) following the convention of tagging sockets, i.e., only the second argument is processed if tagging is not active.

```
227 \NewTaggingSocket{build/page/header}{2}
228 \NewTaggingSocket{build/page/footer}{2}
```

`ld/column/outputbox` (*tag socket*) This socket is used to add any missing tagging structures to the `\@outputbox` box, if necessary.

```
229 \NewTaggingSocket{build/column/outputbox}{0}
```

`uild/column/footins` (*tag socket*) This socket is used to add any missing tagging structures to the `\footins` box, if necessary.

```
230 \NewTaggingSocket{build/column/footins}{0}
```

`page@sofar` (*tag socket*) This socket is declared and used in the multicolumn output routines. Only listed for reference.

```
231 %\NewTaggingSocket{page@sofar}{0}
```

## 2.5 Tagging support for math

### 2.5.1 General sockets

The following sockets are the main math sockets.

```
232 \NewTaggingSocket{math/inline/begin}{0}
233 \NewTaggingSocket{math/inline/end}{0}
234 \NewTaggingSocket{math/inline/formula/begin}{2}
235 \NewTaggingSocket{math/inline/formula/end}{0}
236 \NewTaggingSocket{math/display/begin}{0}
237 \NewTaggingSocket{math/display/end}{0}
238 \NewTaggingSocket{math/display/formula/begin}{2}
239 \NewTaggingSocket{math/display/formula/end}{0}
240 \NewTaggingSocket{math/display/tag/begin}{0}
241 \NewTaggingSocket{math/display/tag/end}{0}
```

## 2.5.2 Sockets specific for luamml

**Save sockets** These sockets are wrappers around the `\luamml_save:...` commands. They take an argument which should contain the argument of the save command.

`math/luamml/save/nn` (*tag socket*) The argument should contain the two arguments of the command.

242 `\NewTaggingSocket{math/luamml/save/nn}{1}`

`math/luamml/save/nNn` (*tag socket*) The argument should contain the three arguments of the command.

243 `\NewTaggingSocket{math/luamml/save/nNn}{1}`

### Socket to annotate

`luamml/annotate/false` (*tag socket*) This socket can be used for content that should be annotated with `core=false`

244 `\NewTaggingSocket{math/luamml/annotate/false}{2}`

**Array sockets** These sockets will be used in `array` to add luamml support to the array environment.

`math/luamml/array/save` (*tag socket*) This socket will be used in `\endarray`. The plug is set by luamml.

245 `\NewTaggingSocket{math/luamml/array/save}{0}`

`luamml/array/finalize` (*tag socket*) This socket will be used in `\endarray`. The plug is set by luamml.

246 `\NewTaggingSocket{math/luamml/array/finalize}{0}`

`luamml/array/initcol` (*tag socket*) This socket will be used in `\@classz`. The plug is set by luamml.

247 `\NewTaggingSocket{math/luamml/array/initcol}{0}`

`math/luamml/array/finalizecol` (*tag socket*) This socket will be used in `\@classz`. The plug is set by luamml. The argument sets the type of the column.

248 `\NewTaggingSocket{math/luamml/array/finalizecol}{1}`

**Alignment environments** Multiline environments like `align`, `multline` or `gather` are tagged as `mtable`.

`math/luamml/mtable/finalizecol` (*tag socket*) This socket is used at the end of alignment cells and adds them to the row. The argument passes a type like `last` or `box`.

249 `\NewTaggingSocket{math/luamml/mtable/finalizecol}{1}`

`luamml/mtable/finalize` (*tag socket*) This socket is used at the end of alignment environment to finalize the `mtable` code. It should be used normally with `\UseExpandableTaggingSocket`.

250 `\NewTaggingSocket{math/luamml/mtable/finalize}{1}`

`luamml/mtable/aligncol` (*tag socket*) This socket is used in `multline` to add attributes describing the alignment to the left and right. It takes an argument, the alignment.

251 `\NewTaggingSocket{math/luamml/mtable/aligncol}{1}`

`luamml/mtable/innertable/save` (*tag socket*) This socket is used in `\endaligned` to save the table. It takes no argument.

252 `\NewTaggingSocket{math/luamml/mtable/innertable/save}{0}`

`\smallmatrix/save` (*tag socket*) This socket is used in `\endsmallmatrix` to save the table. It takes no argument. TODO: Check if this socket and the innertable socket can/should be merged into a more generic version.

253 `\NewTaggingSocket{math/luamml/mtable/smallmatrix/save}{0}`

`\innertable/finalize` (*tag socket*) This socket is used e.g. in `\endsmallmatrix` and `\gathered` to finalize the table. It takes no argument.

254 `\NewTaggingSocket{math/luamml/mtable/innertable/finalize}{0}`

`\mml/mtable/tag/save` (*tag socket*) This socket is used to save a tag for later use. has been save before.

255 `\NewTaggingSocket{math/luamml/mtable/tag/save}{0}`

`\mml/mtable/tag/set` (*tag socket*) This socket should be used when a tag is placed. It inserts a tag that has been save before.

256 `\NewTaggingSocket{math/luamml/mtable/tag/set}{0}`

### mbox socket

`math/luamml/hbox` (*tag socket*) This socket is used around `\hbox` inside an `\mbox`, `\makebox` and `\text` and annotates the content if the `\hbox` is used inside math. The real plug is set by luamml but a default plug is defined here so that the socket can also be used if luamml is not used.

257 `\NewTaggingSocket{math/luamml/hbox}{2}`

### math phantom sockets

`math/luamml/finph@nt` (*tag socket*) This socket handles the annotation of `\finph@nt`

258 `\NewTaggingSocket{math/luamml/finph@nt}{2}`

`math/luamml/finph@nt` (*tag socket*) This socket handles the annotation of `\finsm@sh`

259 `\NewTaggingSocket{math/luamml/finsm@sh}{2}`

### Artifact root sign

`math/luamml/artifact` (*tag socket*) Unicode characters like a root sign should be marked as artifacts to avoid duplication, e.g., in derivation if mathml structure elements are used that imply the meaning.

260 `\NewTaggingSocket{math/luamml/artifact}{0}`

## 2.6 MathML intent attributes

`\MathMLintent` Stub definitions here to allow these commands to be used in packages whether or not tagging is enabled.

`\MathMLarg`

261 `\ExplSyntaxOn`

262 `\cs_new_protected:Npn\MathMLintent#1#2{#2}`

263 `\cs_new_protected:Npn\MathMLarg#1#2{#2}`

264 `\ExplSyntaxOff`

(End of definition for `\MathMLintent` and `\MathMLarg`.)

## 2.7 Symbolic structure names

`\NewStructureName` Stub definitions here to allow these commands to be used in packages whether or not the  
`\UseStructureName` tagging support code is loaded.  
`\AssignStructureRole`

```

265 <@@=tag>
266 \ExplSyntaxOn
267 \cs_new_protected:Npn\NewStructureName#1
268 {
269   \tl_new:c {l__tag_name_#1_tl}
270   \tl_set:cn {l__tag_name_#1_tl}{NonStruct}
271 }
272 \cs_new:Npn\UseStructureName#1
273 {
274   \cs:w l__tag_name_#1_tl\cs_end:
275 }
276 \cs_new_protected:Npn\AssignStructureRole#1#2
277 {
278   \tl_set:cn { l__tag_name_#1_tl }{#2}
279 }
280 \ExplSyntaxOff

```

*(End of definition for \NewStructureName, \UseStructureName, and \AssignStructureRole.)*

## 3 For lttab.dtx parked here for now

```

281 <@@=tbl>
282 \ExplSyntaxOn

```

### 3.1 Variables for row, column and span counting

This part needs a decision on names for various integer registers as well as a decision if those should be also made available for L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>-style packages in form of 2e names and or as non-internals for the L3 programming layer.

At the moment they are all internal but this probably has to change.

`\g__tbl_col_int` `\g__tbl_row_int` holds the current row number in the table. The value 0 means we haven't yet processed the table preamble (or in case of longtable are just in front of the next chunk to be processed). It is incremented by every `\cr` including the one ending the table preamble.

TODO: due to the gymnastics needed inside the longtable code the row counter is directly exposed there rather than hidden by interfaces. This needs changing when it is decided how to manage these counters.

`\g__tbl_col_int` holds the current column number. The value 0 means we have not yet started the table or just finished a table row (with `\` typically); any other positive value means we are currently typesetting a cell in that column in some row (denoted by the `\g__tbl_row_int`).

In a `\multicolumn` it holds the column number of the first spanned column and `\g__tbl_span_tl` the info how many cells are spanned.

`\g__tbl_span_tl` is normally 1 except in a `\multicolumn` cell.

```

283 \int_new:N \g__tbl_col_int
284 \int_new:N \g__tbl_row_int
285 \tl_new:N \g__tbl_span_tl

```

```

286 \tl_new:N \g__tbl_table_cols_tl
287
288 \tl_gset:Nn \g__tbl_span_tl {1}
289 \tl_gset:Nn \g__tbl_table_cols_tl {0} % indicates outer level

```

*(End of definition for \g\_\_tbl\_col\_int and others.)*

\l\_\_tbl\_saved\_col\_tl Saving the outer values if we are nesting tables is necessary (as the above variables are globally altered). For this we always use token lists because they don't change and we do not need to blow additional integer registers.

```

290 \tl_new:N \l__tbl_saved_col_tl
291 \tl_new:N \l__tbl_saved_row_tl
292 \tl_new:N \l__tbl_saved_span_tl
293 \tl_new:N \l__tbl_saved_table_cols_tl
294
295 \tl_set:Nn \l__tbl_saved_col_tl{0}
296 \tl_set:Nn \l__tbl_saved_row_tl{0}
297 \tl_set:Nn \l__tbl_saved_span_tl{1}
298 \tl_set:Nn \l__tbl_saved_table_cols_tl{0} % indicates outer level

```

*(End of definition for \l\_\_tbl\_saved\_col\_tl and others.)*

\g\_\_tbl\_missingcells\_int This will contain the number of missing cells in a row:

```

299 \int_new:N \g__tbl_missing_cells_int

```

*(End of definition for \g\_\_tbl\_missingcells\_int.)*

## 3.2 Tracing/debugging

```

\DebugTablesOn
\DebugTablesOff
300 \def\DebugTablesOn{
301   \cs_set_eq:NN \__tbl_trace:n \typeout
302 }
303 \def\DebugTablesOff{
304   \cs_set_eq:NN \__tbl_trace:n \use_none:n
305 }
306 \cs_new_eq:NN \__tbl_trace:n \use_none:n

```

*(End of definition for \DebugTablesOn and \DebugTablesOff.)*

## 3.3 Interface commands

All interface commands for the cell number determination have to be public on some level because they are needed in other packages as well, e.g., longtable. We may or may not also want to provide 2e style names for them.

\tbl\_update\_cell\_data: Updating cell data in columns after the first means we have to increment the \g\_\_tbl\_col\_int by the span count of the previous cell (in case it was a \multicolumn) and then reset the \g\_\_tbl\_span\_tl to one (as the default).

```

307 \cs_new_protected:Npn \tbl_update_cell_data: {
308   \int_gadd:Nn \g__tbl_col_int { \g__tbl_span_tl }
309   \tl_gset:Nn \g__tbl_span_tl {1}
310 }

```

(End of definition for \tbl\_update\_cell\_data:.)

\tbl\_count\_table\_cols: Current implementation of \@mkpream uses the scratch counter \count@ to keep track of the number of toks registers it needs (2 per column), but this can't be used as it counts also insertions made with !{} and @{}. So similar as does longtable for \LT@cols we count the numbers of ampersands instead.

```

311 \cs_new:Npn \tbl_count_table_cols: {
312   \seq_set_split:NnV\l__tbl_tmpa_seq {&}\@preamble
313   \tl_gset:Ne \g__tbl_table_cols_tl { \seq_count:N \l__tbl_tmpa_seq }
314   \__tbl_trace:n { ==>~ Table~ has~ \g__tbl_table_cols_tl \space columns }
315 }

```

(End of definition for \tbl\_count\_table\_cols:.)

\l\_\_tbl\_tmpa\_seq

```

316 \seq_new:N \l__tbl_tmpa_seq

```

(End of definition for \l\_\_tbl\_tmpa\_seq.)

\tbl\_count\_missing\_cells:n We might have the situation that some table package has not implemented the \tbl\_count\_table\_cols: in which case \g\_\_tbl\_table\_cols\_tl would always be zero and we would get an error below when we try to determine the missing cells, so bypass that calculation if we aren't doing tagging (there the packages should have the proper code added). Recall that this is code, that is called by \ and an old table package might rely on whatever the L<sup>A</sup>T<sub>E</sub>X kernel offers here.

```

317 \cs_new:Npn \tbl_count_missing_cells:n #1 {
318   \tag_if_active:T {
319     \int_compare:nNnT \g__tbl_col_int > 0
320     {
321       \int_gset:Nn \g__tbl_missing_cells_int
322       {
323         \g__tbl_table_cols_tl
324         - \g__tbl_col_int
325         - \g__tbl_span_tl
326         + 1
327       }
328       \int_compare:nNnT \g__tbl_missing_cells_int < 0 \ERRORmissingcells % should not happen
329       \__tbl_trace:n{==>~
330         (#1)~
331         This~ row~ needs~
332         \int_use:N \g__tbl_missing_cells_int \space
333         additional~ cell(s)
334       }
335     }
336   }
337 }

```

(End of definition for \tbl\_count\_missing\_cells:n.)

\tbl\_init\_cell\_data\_for\_table:

```

338 \cs_new_protected:Npn \tbl_init_cell_data_for_table: {
339   \tl_set:No \l__tbl_saved_col_tl {\int_use:N \g__tbl_col_int }
340   \tl_set:No \l__tbl_saved_row_tl {\int_use:N \g__tbl_row_int }
341   \tl_set_eq:NN \l__tbl_saved_table_cols_tl \g__tbl_table_cols_tl

```

```

342 \tbl_set_eq:NN \l__tbl_saved_span_tl \g__tbl_span_tl
343 %
344 \__tbl_trace:n { ==>~ saved~cell~data:~
345             \l__tbl_saved_row_tl,
346             \l__tbl_saved_col_tl,
347             \l__tbl_saved_span_tl \space
348             (
349             \int_compare:nNnTF \l__tbl_saved_table_cols_tl = 0
350             { outer~ level }
351             { max:~ \l__tbl_saved_table_cols_tl }
352             )
353     }

```

Tagging has to initialize cell data too.

```

354 \UseTaggingSocket{tbl/init/celldata}

```

These are the initial values when starting a table:

```

355 \int_gzero:N \g__tbl_row_int
356 \int_gzero:N \g__tbl_col_int
357 \tl_gset:Nn \g__tbl_span_tl {1}
358 }

```

*(End of definition for \tbl\_init\_cell\_data\_for\_table:.)*

\tbl\_update\_cell\_data\_for\_next\_row:

```

359 \cs_new_protected:Npn \tbl_update_cell_data_for_next_row: {
360     \int_gincr:N \g__tbl_row_int           % this row about to start
361     \int_gzero:N \g__tbl_col_int           % we are before first col
362 }

```

*(End of definition for \tbl\_update\_cell\_data\_for\_next\_row:.)*

\tbl\_init\_cell\_data\_for\_row: If we start processing a cell in the first column we set \g\_\_tbl\_col\_int to 1 as we are no longer "at" but "in" the first column. We also set \g\_\_tbl\_span\_tl to its default value (not spanning cells).

```

363 \cs_new_protected:Npn \tbl_init_cell_data_for_row: {
364     \tl_gset:Nn \g__tbl_col_int {1}
365     \tl_gset:Nn \g__tbl_span_tl {1}
366 }

```

*(End of definition for \tbl\_init\_cell\_data\_for\_row:.)*

\tbl\_if\_row\_was\_started:T We use \g\_\_tbl\_col\_int equal zero to indicate that we are just after a TR (i.e. between rows or at the very beginning of the table). Using the row count is not so good as longtable may split the table in chunks.

These conditionals have to be expandable (i.e., unprotected) as they are sometimes executed when T<sub>E</sub>X is scanning inside a table.

```

367 \cs_new:Npn \tbl_if_row_was_started:T {
368     \int_compare:nNnT \g__tbl_col_int > 0
369 }
370 \cs_new:Npn \tbl_if_row_was_started:TF {
371     \int_compare:nNnTF \g__tbl_col_int > 0
372 }

```

*(End of definition for \tbl\_if\_row\_was\_started:T and \tbl\_if\_row\_was\_started:TF.)*

`\tbl_gzero_row_count:` This here is basically a temporary interface. What it will be in the end depends on what we decide concerning exposing row and column counters, if they stay internal we need something like this here (perhaps using `gincr` etc, or perhaps some other names in the first place).

```

373 \cs_new_protected:Npn \tbl_gzero_row_count: {
374   \int_gzero:N \g__tbl_row_int
375 }
376 \cs_new_protected:Npn \tbl_gincr_row_count: {
377   \int_gincr:N \g__tbl_row_int
378 }
379 \cs_new_protected:Npn \tbl_gdecr_row_count: {
380   \int_gdecr:N \g__tbl_row_int
381 }

```

*(End of definition for `\tbl_gzero_row_count:`, `\tbl_gincr_row_count:`, and `\tbl_gdecr_row_count:`.)*

`\tbl_inbetween_rows:` Again name is not really brilliant so far.

```

382 \cs_new_protected:Npn \tbl_inbetween_rows: {
383   \int_gzero:N \g__tbl_col_int
384 }

```

*(End of definition for `\tbl_inbetween_rows:`.)*

`\tbl_restore_outer_cell_data:`

```

385 \cs_new_protected:Npn \tbl_restore_outer_cell_data: {
386   \int_gset:Nn \g__tbl_col_int { \l__tbl_saved_col_tl }
387   \int_gset:Nn \g__tbl_row_int { \l__tbl_saved_row_tl }
388   \tl_gset_eq:NN \g__tbl_span_tl \l__tbl_saved_span_tl
389   \tl_gset_eq:NN \g__tbl_table_cols_tl \l__tbl_saved_table_cols_tl
390   \UseTaggingSocket{tbl/restore/celldata}
391   \__tbl_trace:n { ==>~ restored~cell~data:~
392     \int_use:N \g__tbl_row_int,
393     \int_use:N \g__tbl_col_int,
394     \l__tbl_saved_span_tl \space
395     (
396       \int_compare:nNnTF \g__tbl_table_cols_tl = 0
397         { outer~ level }
398         { max:~ \g__tbl_table_cols_tl }
399     )
400   }
401 }

```

*(End of definition for `\tbl_restore_outer_cell_data:`.)*

`\tbl_update_multicolumn_cell_data:n` This macro updates `\g__tbl_col_int` and `\g__tbl_span_tl` inside a `\multicolumn` and possibly calls the tagging socket `tbl/row/begin`.

```

402 \cs_new_protected:Npn \tbl_update_multicolumn_cell_data:n #1 {

```

We execute socket for tagging only if this `\multicolumn` replaces the preamble of the first column. In that case we also have to set `\g__tbl_col_int` to 1 because this is no longer done in the preamble for the cell either.

```

403   \int_compare:nNnTF \g__tbl_col_int = 0
404   {
405     \UseTaggingSocket{tbl/row/begin}
406     \int_gset:Nn \g__tbl_col_int {1}
407   }

```

If we are in a later column we use `\g__tbl_span_tl` from the previous column to update.

```

408     {
409       \int_gadd:Nn \g__tbl_col_int { \g__tbl_span_tl }
410     }

```

Then we set the span value so that it can be use in the next column.

```

411     \tl_gset:Nn \g__tbl_span_tl {#1}
412   }

```

*(End of definition for \tbl\_update\_multicolumn\_cell\_data:n.)*

`\tbl_crcr:n` This macro is used instead of the usual `\crcr` at the end of a table. It is deliberately defined without protection because it may get expanded by the scanning mechanism of low-level  $\TeX$  after a final `\cr` (aka `\`) in the table. In that case it shouldn't stop the expansion and the conditional inside will be false, thus it just vanishes without doing anything. If there are missing cells (in which case we also haven't see `\cr` yet) the macro `\tbl_count_missing_cells:n` is executed and then the row is finished with a final `\cr`.

```

413 \cs_new:Npn \tbl_crcr:n #1 {
414   \int_compare:nNnT \g__tbl_col_int > 0
415     {
416       \tbl_count_missing_cells:n {#1}
417     }

```

Even if we are at the start of a row we may have to do a `\cr`, so we do a `\crcr` always at the end.

```

418     \crcr
419   }

```

*(End of definition for \tbl\_crcr:n.)*

```

420 \ExplSyntaxOff
421 \@@=

```

This is needed for `longtable` because `\refstepcounter` is setting up a target when `hyperref` is loaded and we don't want that in `longtable`. Prevent `longtable` patching by `hyperref` until `hyperref` does so automatically:

```

422 \def\hyper@nopatch@longtable{}
423   Should there be a module?
424   \<latexrelease>\NewModuleRelease{2024/06/01}{ltagging}
425   \<latexrelease>{Tagging support}
426   \<latexrelease>\IncludeInRelease{0000/00/00}{ltagging}%
427   \<latexrelease>{Undo tagging support}
428   \<latexrelease>
429   \<latexrelease>
430   \<latexrelease>\EndModuleRelease
431 \</2ekernel | latexrelease>

```

## File 56

# lthyphen.dtx

This file contains the code for loading hyphenation patterns into L<sup>A</sup>T<sub>E</sub>X. Most of this will end up in a file called `hyphen.ltx`. If you wish to customize your L<sup>A</sup>T<sub>E</sub>X system in respect of hyphenation patterns, write a file `hyphen.cfg`. If this file exists, it will be loaded instead of `hyphen.ltx`. See the comments below for additional information.

To produce the printed version of this file the following code is used. It can be extracted with the DOCSTRIP program, or one can run this file directly through L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

```
1 <*driver>
2 \documentclass{ltxdoc}
3 \begin{document}
4 \DocInput{lthyphen.dtx}
5 \end{document}
6 </driver>
```

The default file `hyphen.ltx` loads hyphenation patterns for US english. If you want to load additional or other hyphenation patterns, you should create a file `hyphen.cfg`. This is best done by starting from `hyphen.ltx`.

For backward compatibility, the default file, `hyphen.ltx`, first tries to load the file `hyphen.tex`. If this file exists, an information message is issued and the appropriate defaults for T<sub>E</sub>X's internal parameters are set: `\language` is initialized to 0, and `\lefthyphenmin` and `\righthyphenmin` to 2 and 3, respectively, to disallow x- or -xx breaks.

```
7 <*default>
8 \InputIfFileExists{hyphen.tex}%
9   {\message{Loading hyphenation patterns for US english.}}%
10   \language=0
11   \lefthyphenmin=2 \righthyphenmin=3 }%
```

Otherwise, since we cannot do anything without any hyphenation patterns, an error message is printed and the IniT<sub>E</sub>X run is terminated by invoking `\@@end` (which is the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> name for T<sub>E</sub>X's `\end` primitive).

```
12   {\errhelp{The configuration for hyphenation is incorrectly
13             installed.^^J%
14             If you don't understand this error message you need
15             to seek^^Jexpert advice.}%
16   \errmessage{OOPS! I can't find any hyphenation patterns for
17             US english.^^J \space Think of getting some or the
18             latex2e setup will never succeed}\@@end}
19 </default>
```

The following example describes the possible contents of a file `hyphen.cfg` that will load both US English and German hyphenation patterns, making the former the default. It sets `\language` to 0 for the US patterns and to 1 for the German patterns. Then `\language` is set to 0 to make this the default and the default values of `\lefthyphenmin` and `\righthyphenmin` are set.

```
language=0
input hyphen % (or \input ushyphen1 if the file has been renamed)
language=1
input ghyph31
```

```
language=0
lefthyphenmin=2
righthyphenmin=3
endinput
```

Another possibility is to use the package `babel`, by Johannes Braams. That package is distributed with a suitable `hyphen.cfg` file.

## File 57

# ltxfinal.dtx

## 1 Final settings

This section contains the final settings for L<sup>A</sup>T<sub>E</sub>X. It initializes some debugging and typesetting parameters, sets the default `\catcodes` and `uc/lc` codes, and inputs the hyphenation file.

### 1.1 Debugging

By default, L<sup>A</sup>T<sub>E</sub>X shows statistics:

```
1 <*2ekernel>
2 \tracingstats1
```

### 1.2 Typesetting parameters

```
\@lowpenalty These are penalties used internally.
\@medpenalty 3 \newcount\@lowpenalty
\@highpenalty 4 \newcount\@medpenalty
5 \newcount\@highpenalty
```

*(End of definition for \@lowpenalty, \@medpenalty, and \@highpenalty.)*

```
\newmarks Allocate extended marks types if etex is active. Placed here at the end of the format to
increase compatibility with count allocations in earlier releases.
```

```
6 </2ekernel>
7 <*2ekernel | latexrelease>
8 <latexrelease>\IncludeInRelease{2015/01/01}%
9 <latexrelease>          {\newmarks}{Extended Allocation}%
10 \ifx\marks\@undefined\else
11 \def\newmarks{%
12   \e@alloc\marks \e@alloc@chardef{\count256}\m@ne\e@alloc@top}
13 \fi
14 </2ekernel | latexrelease>
15 <latexrelease>\EndIncludeInRelease
16 <latexrelease>\IncludeInRelease{0000/00/00}%
17 <latexrelease>          {\newmarks}{Extended Allocation}%
18 <latexrelease>\let\newmarks\@undefined
19 <latexrelease>\EndIncludeInRelease
20 <*2ekernel>
```

*(End of definition for \newmarks.)*

Allocate 3 mark classes to be used in `\markboth` and `\markright`. Should be done earlier but for that definition of `\newmarks` needs moving (which it should I guess).

```
21 </2ekernel>
22 <*2ekernel | latexrelease>
23 <latexrelease>\IncludeInRelease{2022/06/01}%
24 <latexrelease>          {2e-left}{Delayed legacy marks}%
25 \NewMarkClass {2e-left}
```

```

26 \NewMarkClass {2e-right}
27 \NewMarkClass {2e-right-nonempty}

```

No rollback really, the marks will remain.

```

28 </2ekernel | latexrelease>
29 <latexrelease>\EndIncludeInRelease
30 <latexrelease>\IncludeInRelease{0000/00/00}%
31 <latexrelease> {2e-left}{Delayed legacy marks}%
32 <latexrelease>
33 <latexrelease>\EndIncludeInRelease
34 <*2ekernel>

```

```

\newXeTeXintercharclass Allocate \XeTeXintercharclass types if xetex is active. previously defined in xetex.ini.
\XeTeXalloc@intercharclass
\XeTeXalloc@intercharclass@top

```

```

35 </2ekernel>
36 <*2ekernel | latexrelease>
37 <latexrelease>\IncludeInRelease{2015/01/01}%
38 <latexrelease> {\newXeTeXintercharclass}{Extended Allocation}%

```

Classes allocated 1 to 4094 (or 254 on older xetex) (In earlier XeLaTeX versions 1, 2 and 3 were pre-set for CJK).

```

39 \ifx\XeTeXcharclass\@undefined
40 \else
41 \ifdim\the\XeTeXversion\XeTeXrevision\p>0.99993\p@
42 \chardef\XeTeXalloc@intercharclass@top=4095
43 \else
44 \chardef\XeTeXalloc@intercharclass@top=255
45 \fi
46 \def\newXeTeXintercharclass{%
47 \XeTeXalloc\XeTeXcharclass
48 \chardef\XeTeXalloc@intercharclass\m@ne\XeTeXalloc@intercharclass@top}
49 \fi
50 </2ekernel | latexrelease>
51 <latexrelease>\EndIncludeInRelease
52 <latexrelease>\IncludeInRelease{0000/00/00}%
53 <latexrelease> {\newXeTeXintercharclass}{Extended Allocation}%
54 <latexrelease> \ifx\XeTeXcharclass\@undefined
55 <latexrelease> \else
56 <latexrelease> \def\XeTeXalloc@#1#2#3#4#5{\global\advance#1\@ne
57 <latexrelease> \XeTeXch@ck#1#4#2%
58 <latexrelease> \allocationnumber#1%
59 <latexrelease> \global#3#5\allocationnumber
60 <latexrelease> \wlog{\string#5=\string#2\the\allocationnumber}}
61 <latexrelease> \def\XeTeXch@ck#1#2#3{%
62 <latexrelease> \ifnum#1<#2\else
63 <latexrelease> \errmessage{No room for a new #3}%
64 <latexrelease> \fi}
65 <latexrelease> \def\newXeTeXintercharclass{%
66 <latexrelease> \XeTeXalloc\XeTeXalloc@intercharclass
67 <latexrelease> \XeTeXcharclass\chardef\@cclv}
68 <latexrelease> \fi
69 <latexrelease>\EndIncludeInRelease
70 <*2ekernel | latexrelease>
71 <latexrelease>\IncludeInRelease{2016/02/01}%

```

```

72 <latexrelease> {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
73 \ifx\XeTeXcharclass\@undefined
74 \else
75   \countdef\xe@alloc@intercharclass=257
76   \xe@alloc@intercharclass=\z@
77 \fi
78 </2ekernel | latexrelease>
79 <latexrelease>\EndIncludeInRelease
80 <latexrelease>\IncludeInRelease{2015/01/01}%
81 <latexrelease> {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
82 <latexrelease> \ifx\XeTeXcharclass\@undefined
83 <latexrelease> \else
84 <latexrelease>   \xe@alloc@intercharclass=\thr@@
85 <latexrelease> \fi
86 <latexrelease>\EndIncludeInRelease
87 <latexrelease>\IncludeInRelease{0000/00/00}%
88 <latexrelease> {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
89 <latexrelease> \ifx\XeTeXcharclass\@undefined
90 <latexrelease> \else
91 <latexrelease>   \newcount\xe@alloc@intercharclass
92 <latexrelease>   \xe@alloc@intercharclass=\thr@@
93 <latexrelease> \fi
94 <latexrelease>\EndIncludeInRelease
95 <*2ekernel>

```

*(End of definition for \newXeTeXintercharclass, \xe@alloc@intercharclass, and \e@alloc@intercharclass@top.)*

**trace\_stack\_levels** Now define the Lua function to emulate \tracingstacklevels and install it in the input\_level\_string callback.

```

96 </2ekernel>
97 <*2ekernel | latexrelease>

```

In latexrelease mode we always remove the function from the callback, then add the correct version later.

```

98 <latexrelease>\ifx\directlua\@undefined
99 <latexrelease>\else
100 <latexrelease> \directlua{%
101 <latexrelease>   if luatexbase.callbacktypes['input_level_string'] and %
102 <latexrelease>     luatexbase.in_callback('input_level_string','tracingstacklevels') then
103 <latexrelease>     luatexbase.remove_from_callback('input_level_string','tracingstacklevels')
104 <latexrelease>   end}%
105 <latexrelease>\fi
106 <latexrelease>\IncludeInRelease{2021/06/01}{trace_stack_levels}%
107 <latexrelease>           {Lua trace_stack_levels function}%
108 \ifx\directlua\@undefined
109 \else
110 <*2ekernel>
111   \expanded{%
112     \everyjob{\the\everyjob
113       \noexpand%\directlua
114 </2ekernel>
115     \directlua{%
116       local function trace_stack_levels (input_ptr)
117         local tracingstacklevels = tex.count.tracingstacklevels

```

```

118     if tex.tracingmacros > 0 or input_ptr < tracingstacklevels then
119       if tracingstacklevels > 0 then
120         if input_ptr < tracingstacklevels then
121           return "\string\n\string~" .. string.rep(".",input_ptr)
122         else
123           return "\string~\string~"
124         end
125       else
126         return "\string\n"
127       end
128     else
129       return ""
130     end
131   end
132   <latexrelease>   if luatexbase.callbacktypes['input_level_string'] then
133     luatexbase.add_to_callback('input_level_string',
134       trace_stack_levels,'tracingstacklevels')
135   <latexrelease>   end
136   }%
137   <*2ekernel>
138   }}%
139   </2ekernel>
140   \fi
141   <latexrelease>\EndIncludeInRelease
142   <latexrelease>

```

Then for the full rollback, just do nothing, since the function was already taken out of the rollback above.

```

143   <latexrelease>\IncludeInRelease{0000/00/00}{trace_stack_levels}%
144   <latexrelease>           {Lua trace_stack_levels function}%
145   <latexrelease>% Nothing here
146   <latexrelease>\EndIncludeInRelease
147   </2ekernel | latexrelease>
148   <*2ekernel>

```

*(End of definition for trace\_stack\_levels.)*

The default values of the picture and \fbox parameters:

```

149   \unitlength = 1pt
150   \fboxsep = 3pt
151   \fboxrule = .4pt

```

The saved value of T<sub>E</sub>X's \maxdepth:

```

152   \@maxdepth      = \maxdepth

```

\vsize initialized because a \clearpage with \vsize < \topskip causes trouble. \@colroom and \@colht also initialized because \vsize may be set to them if a \clearpage is done before the \begin{document}

```

153   \vsize = 1000pt
154   \@colroom = \vsize
155   \@colht = \vsize

```

Initialise \textheight \textwidth and page style, to avoid internal errors if they are not set by the class.

```

156   \textheight=.5\maxdimen
157   \textwidth=\textheight
158   \ps@empty

```

### 1.3 Lccodes for hyphenation

For 7- and 8-bit engines the assumption of T1 encodings is the basis for the hyphenation patterns. That's not the case for the Unicode engines, where the assumption is engine-native working. The common loader system provides access to data from the Unicode Consortium covering not only `\lccode` but also other related data. The `\lccode` part of that at least needs to be loaded before hyphenation is tackled: XeTeX follows the standard TeX route of building patterns into the format. LuaTeX doesn't require this data be loaded *here* but it does need to be loaded somewhere. Rather than test for the Unicode engines by name, the approach here is to look for the extended math mode handling both provide: any other engine developed in this area will presumably also provide `\Umathcode`.

```
159 \ifnum 0%
160   \ifx\Umathcode\@undefined\else 1\fi
161   \ifx\XeTeXmathcode\@undefined\else 1\fi
162   >\z@
163   \message{ Unicode character data,}
164   \input{load-unicode-data}
165 \endkernel)
166 \latexrelease\IncludeInRelease{2016/02/01}%
167 \latexrelease { \XeTeXintercharclasses}{XeTeX character classes}%
168 \latexrelease \ifx\XeTeXinterchartoks\undefined
169 \latexrelease \else
170 \latexrelease \begingroup
171 \latexrelease \chardef\XeTeXcharclassID = 0 %
172 \latexrelease \chardef\XeTeXcharclassOP = 0 %
173 \latexrelease \chardef\XeTeXcharclassCL = 0 %
174 \latexrelease \chardef\XeTeXcharclassEX = 0 %
175 \latexrelease \chardef\XeTeXcharclassIS = 0 %
176 \latexrelease \chardef\XeTeXcharclassNS = 0 %
177 \latexrelease \chardef\XeTeXcharclassCM = 0 %
178 \latexrelease \input{load-unicode-xetex-classes}
179 \latexrelease \endgroup
180 \latexrelease \global\let\xtxHanGlue\undefined
181 \latexrelease \global\let\xtxHanSpace\undefined
182 \latexrelease \global\XeTeXinterchartoks 0 1 = {}
183 \latexrelease \global\XeTeXinterchartoks 0 2 = {}
184 \latexrelease \global\XeTeXinterchartoks 0 3 = {}
185 \latexrelease \global\XeTeXinterchartoks 1 0 = {}
186 \latexrelease \global\XeTeXinterchartoks 2 0 = {}
187 \latexrelease \global\XeTeXinterchartoks 3 0 = {}
188 \latexrelease \global\XeTeXinterchartoks 1 1 = {}
189 \latexrelease \global\XeTeXinterchartoks 1 2 = {}
190 \latexrelease \global\XeTeXinterchartoks 1 3 = {}
191 \latexrelease \global\XeTeXinterchartoks 2 1 = {}
192 \latexrelease \global\XeTeXinterchartoks 2 2 = {}
193 \latexrelease \global\XeTeXinterchartoks 2 3 = {}
194 \latexrelease \global\XeTeXinterchartoks 3 1 = {}
195 \latexrelease \global\XeTeXinterchartoks 3 2 = {}
196 \latexrelease \global\XeTeXinterchartoks 3 3 = {}
197 \latexrelease \fi
198 \latexrelease\EndIncludeInRelease
199 \latexrelease\IncludeInRelease{0000/00/00}%
```

```

200 <latexrelease> {\XeTeXintercharclasses}{XeTeX character classes}%
201 <latexrelease> \ifx\XeTeXinterchartoks\undefined
202 <latexrelease> \else
203 <latexrelease> \input{load-unicode-xetex-classes}
204 <latexrelease> \gdef\xtxHanGlue{\hskip0pt plus 0.1em\relax}
205 <latexrelease> \gdef\xtxHanSpace{\hskip0.2em plus 0.2em minus 0.1em\relax}
206 <latexrelease> \global\XeTeXinterchartoks 0 1 = {\xtxHanSpace}
207 <latexrelease> \global\XeTeXinterchartoks 0 2 = {\xtxHanSpace}
208 <latexrelease> \global\XeTeXinterchartoks 0 3 = {\nobreak\xtxHanSpace}
209 <latexrelease> \global\XeTeXinterchartoks 1 0 = {\xtxHanSpace}
210 <latexrelease> \global\XeTeXinterchartoks 2 0 = {\nobreak\xtxHanSpace}
211 <latexrelease> \global\XeTeXinterchartoks 3 0 = {\xtxHanSpace}
212 <latexrelease> \global\XeTeXinterchartoks 1 1 = {\xtxHanGlue}
213 <latexrelease> \global\XeTeXinterchartoks 1 2 = {\xtxHanGlue}
214 <latexrelease> \global\XeTeXinterchartoks 1 3 = {\nobreak\xtxHanGlue}
215 <latexrelease> \global\XeTeXinterchartoks 2 1 = {\nobreak\xtxHanGlue}
216 <latexrelease> \global\XeTeXinterchartoks 2 2 = {\nobreak\xtxHanGlue}
217 <latexrelease> \global\XeTeXinterchartoks 2 3 = {\xtxHanGlue}
218 <latexrelease> \global\XeTeXinterchartoks 3 1 = {\xtxHanGlue}
219 <latexrelease> \global\XeTeXinterchartoks 3 2 = {\xtxHanGlue}
220 <latexrelease> \global\XeTeXinterchartoks 3 3 = {\nobreak\xtxHanGlue}
221 <latexrelease> \fi
222 <latexrelease> \EndIncludeInRelease
223 <*2ekernel>

```

There is one over-ride that makes sense here (see below for the same for 8-bit engines): setting the lccode for - to itself.

```

224 \lccode'\- ='\- % default hyphen char

```

The alternative is that a “traditional” engine is in use.

```

225 \else

```

We set things up so that hyphenation files can assume that the default (T1) lccodes are in use (at present this also sets up the uccodes). We temporarily define `\reserved@a` to apply `\reserved@c` to all the numbers in the range of its arguments.

```

226 \def\reserved@a#1#2{%
227   \@tempcnta#1\relax
228   \@tempcntb#2\relax
229   \reserved@b
230 }
231 \def\reserved@b{%
232   \ifnum\@tempcnta>\@tempcntb\else
233     \reserved@c\@tempcnta
234     \advance\@tempcnta\@ne
235     \expandafter\reserved@b
236   \fi
237 }

```

Depending on the T<sub>E</sub>X version, we might not be allowed to do this for non-ASCII characters.

```

238 \def\reserved@c#1{%
239   \count@=#1\advance\count@ by -"20
240   \uccode#1=\count@
241   \lccode#1=#1
242 }

```

```

243 \reserved@a{'\a}{'\z}
244 \reserved@a{"A0}{\BC}
245 \reserved@a{"E0}{\FF}

```

The upper case characters need their `\uccode` and `\lccode` values set, and their `\sfcode` set to 999.

```

246 \def\reserved@c#1{%
247   \count@=#1\advance\count@ by "20
248   \uccode#1=#1
249   \lccode#1=\count@
250   \sfcode#1=999
251 }
252 \reserved@a{'\A}{'\Z}
253 \reserved@a{"80}{\9C}
254 \reserved@a{"C0}{\DF}

```

Well, it would be nice if that were correct, but unfortunately, the Cork encoding contains some odd slots whose `uccode` or `lccode` isn't quite what you'd expect.

```

255 \uccode'\^^Y='I      % dotless i
256 \lccode'\^^Y='^^Y    % dotless i
257 \uccode'\^^Z='J      % dotless j, ae in OT1
258 \lccode'\^^Z='^^Z    % dotless j, ae in OT1
259 \lccode'\^^9d='i     % dotted I
260 \uccode'\^^9d='^^9d  % dotted I
261 \lccode'\^^9e='^^9e  % d-bar
262 \uccode'\^^9e='^^d0 % d-bar

```

Finally here is one that helps hyphenation in the OT1 encoding.

```

263 \lccode'\^^[='^^[    % oe in OT1

```

And we also set the `\lccode` of `\-` and `\textcompwordmark` so that they do not prevent hyphenation in the remainder of the word (as suggested by Lars Helström).

```

264 \lccode'\- ='\'      % default hyphen char
265 \lccode 127=127      % alternate hyphen char
266 \lccode 23 =23       % textcompwordmark in T1

```

End of the conditional to select either Unicode or T1 encoding defaults.

```

267 \fi

```

At this stage, we can install any last-minute `expl3` set-up.

```

268 \@expl@finalise@setup@@
269 \def\@expl@finalise@setup@@{}

```

This is as good a place as any to active a few XeTeX-specific settings

```

270 \ifx\XeTeXuseglyphmetrics\@undefined
271 \else
272   \XeTeXuseglyphmetrics=1 %
273   \XeTeXdashbreakstate=1 %
274 \fi

```

## 1.4 Hyphenation

The following code will be compiled into the format file. It checks for the existence of `hyphen.cfg` in inputs that file if found. Otherwise it inputs `hyphen.ltx`. Note that these are loaded in *before* the `\catcodes` are set, so local hyphenation files can use 8-bit input.

We try to load the customized hyphenation description file.

```

275 \InputIfFileExists{hyphen.cfg}
276     {\typeout{=====^J%
277             Local configuration file hyphen.cfg used^J%
278             =====}%
279     \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
280     }
281     {\input{hyphen.ltx}}
282 \let\@addtofilelist\@gobble

```

`\l@nohyphenation`

```

283 \ifx\l@nohyphenation \@undefined
284 \newlanguage\l@nohyphenation
285 \fi

```

*(End of definition for \l@nohyphenation.)*

`\document@default@language` Default document language. -1 acts as language 0, but used as a flag in `\document` to see if it has been set in the preamble.

```

286 </2ekernel>
287 <*2ekernel | latexrelease>
288 <latexrelease>\IncludeInRelease{2017/04/15}%
289 <latexrelease>    {\document@default@language}{Save language for hyphenation}%
290 \let\document@default@language\m@ne
291 </2ekernel | latexrelease>
292 <latexrelease>\EndIncludeInRelease
293 <latexrelease>\IncludeInRelease{0000/00/00}%
294 <latexrelease>    {\document@default@language}{Save language for hyphenation}%
295 %
296 <latexrelease>\let\document@default@language\@undefined
297 <latexrelease>\EndIncludeInRelease
298 <*2ekernel>

```

*(End of definition for \document@default@language.)*

## 1.5 Font loading

Fonts loaded during the formatting process might already have changed the `\font@submax` from `0pt` to something higher. If so, we put out a bold warning.

```

299 \ifdim \font@submax >\z@
300     \@font@warning{Size substitutions with differences\MessageBreak
301                   up to \font@submax\space have occurred.\MessageBreak
302                   \MessageBreak
303                   Please check the transcript file
304                   carefully\MessageBreak
305                   and redo the format generation if necessary!
306                   \@gobbletwo}%
307     \errhelp{Only stopped, to give you time to
308             read the above message.}
309     \errmessage{}

```

We reset the macro. Otherwise every user will get a warning on every job.

```

310 \def\font@submax{0pt}
311 \fi

```

For pdfT<sub>E</sub>X preload and enable automatic glyph to Unicode mapping for more reliable copy and paste support.

```

312 </2ekernel>
313 <*2ekernel | latexrelease>
314 <latexrelease>\IncludeInRelease{2021/06/01}%
315 <latexrelease>          {\pdfgentounicode}{Preload glyphtounicode}%
316 \ifx \pdfgentounicode \@undefined \else
317 <*2ekernel>
318   \ifnum 0=0%
319     \ifdefined\pdftexversion
320 % \pdftexversion<140 does not have \pdfgentounicode, so we only check higher values
321     \ifnum \pdftexversion=140 \ifnum\pdftexrevision<22 1\fi\fi
322     \fi
323     \relax
324 </2ekernel>
325     \input glyphtounicode
326 <*2ekernel>
327   \else
328     \begingroup
329     \everyeof{\noexpand}\endlinechar-1
330     \edef\x{\endgroup
331       \everyjob{\the\everyjob\@@input glyphtounicode }%
332     }\x
333     \fi
334 </2ekernel>
335     \pdfgentounicode=1
336     \fi
337 </2ekernel | latexrelease>
338 <latexrelease>\EndIncludeInRelease

```

When rolling back we can't unload the glyphtounicode mappings, but we can reset `\pdfgentounicode` to ensure that they aren't used.

```

339 <latexrelease>\IncludeInRelease{0000/00/00}%
340 <latexrelease>          {\pdfgentounicode}{Preload glyphtounicode}%
341 <latexrelease>\ifx \pdfgentounicode \@undefined \else
342 <latexrelease> \pdfgentounicode=0
343 <latexrelease>\fi
344 <latexrelease>\EndIncludeInRelease
345 <*2ekernel>

```

## 1.6 Input encoding

Starting with the 2018 L<sup>A</sup>T<sub>E</sub>X release default the inputencoding to UTF-8. Unless the format is being used with luatex, xetex, enc<sub>te</sub>x or ml<sub>te</sub>x.

This is done in a way largely compatible with older releases: `utf8.def` is input just as if

```
\usepackage[utf8]{inputenc}
```

had been used, however rather than input the whole package a minimal core part just enough to support loading the UTF-8 encoding files is defined here.

If a document re-specifies UTF-8 this is silently ignored.

```

346 </2ekernel>
347 <*2ekernel | latexrelease>

```

Check that a classic 8-bit tex engine is being used (LaTeX or PDFLaTeX).

```
348 \latexrelease\IncludeInRelease{2018/04/01}%
349 \latexrelease\UTFviii@invalid\UTF-8 default}%
```

Skip this section in Unicode TeX, or if MLTeX and EncTeX are enabled.

```
350 \ifnum0%
351   \ifx\Umathcode\@undefined\else 1\fi
352   \ifx\mubyte\@undefined\else 1\fi
353   \ifx\charsubdef\@undefined\else 1\fi
354   =\z@

355 \def\saved@space@catcode{10}
356 \let\@inpenc@test\relax
357 \def\IeC{%
358   \ifx\protect\@typeset@protect
359     \expandafter\@firstofone
360   \else
361     \noexpand\IeC
362   \fi
363 }
```

Make characters active for UTF-8 input formats

```
364 \@tempcnta=1
365 \loop
366   \catcode\@tempcnta=13 %
367   \advance\@tempcnta\@ne %
368   \ifnum\@tempcnta<32 %
369   \repeat %
370 \catcode0=15 % null
371 \catcode9=10 % tab
372 \catcode10=12 % ctrl J
373 \catcode12=13 % ctrl L
374 \catcode13=5 % newline
375 \@tempcnta=128
376 \loop
377   \catcode\@tempcnta=13
378   \advance\@tempcnta\@ne
379   \ifnum\@tempcnta<256
380   \repeat
```

**\UseRawInputEncoding** Reset 8 bit characters to catcode 12 so the input encoding matches the “Raw” font encoding. Useful for special behaviours, or for compatibility with older L<sup>A</sup>T<sub>E</sub>X formats.

```
381 \def\UseRawInputEncoding{%
382   \let\inputencodingname\@undefined % revert
383   \let\DeclareFontEncoding\DeclareFontEncoding@saved % revert
384   \let\DeclareUnicodeCharacter\@undefined % revert
385   \@tempcnta=1
386   \loop
387     \catcode\@tempcnta=15 %
388     \advance\@tempcnta\@ne %
389     \ifnum\@tempcnta<32 %
390     \repeat %
391   \catcode0=15 % null
392   \catcode9=10 % tab
```

```

393 \catcode10=12 % ctrl J
394 \catcode12=13 % ctrl L
395 \catcode13=5 % newline
396 \@tempcnta=128
397 \loop
398   \catcode\@tempcnta=12
399   \advance\@tempcnta\@ne
400 \ifnum\@tempcnta<256
401 \repeat
402 }

```

(End of definition for \UseRawInputEncoding.)

\DeclareFontEncoding@saved Saved version of \DeclareFontEncoding@ before utf8.def modifies it for use in \UseRawInputEncoding above.

```

403 \let\DeclareFontEncoding@saved\DeclareFontEncoding@

```

(End of definition for \DeclareFontEncoding@saved.)

```

404 \edef\inputencodingname{utf8}%
405 \input{utf8.def}
406 \let\UTFviii@undefined@err@@\UTFviii@undefined@err
407 \let\UTFviii@invalid@err@@\UTFviii@invalid@err
408 \let\UTFviii@two@octets@@\UTFviii@two@octets
409 \let\UTFviii@three@octets@@\UTFviii@three@octets
410 \let\UTFviii@four@octets@@\UTFviii@four@octets
411 <2kernel>\def\UTFviii@undefined@err#1{\@gobble#1}%
412 <2kernel>\let\UTFviii@invalid@err\string
413 <2kernel>\let\UTFviii@two@octets\string
414 <2kernel>\let\UTFviii@three@octets\string
415 <2kernel>\let\UTFviii@four@octets\string
416 <2kernel>\everyjob\expandafter{\the\everyjob
417 <2kernel>\let\UTFviii@undefined@err\UTFviii@undefined@err@@
418 <2kernel>\let\UTFviii@invalid@err\UTFviii@invalid@err@@
419 <2kernel>\let\UTFviii@two@octets\UTFviii@two@octets@@
420 <2kernel>\let\UTFviii@three@octets\UTFviii@three@octets@@
421 <2kernel>\let\UTFviii@four@octets\UTFviii@four@octets@@
422 <2kernel>}}
423 \let\@inpenc@test\@undefined
424 \let\saved@space@catcode\@undefined

```

For formats not set up for UTF-8 default, set the C0 controls to catcode 15.

```

425 \else
426 \@tempcnta=0
427 \loop
428   \catcode\@tempcnta=15 %
429   \advance\@tempcnta\@ne %
430 \ifnum\@tempcnta<32 %
431 \repeat %
432 \catcode0=15 % null
433 \catcode9=10 % tab
434 \catcode10=12 % ctrl J
435 \catcode12=13 % ctrl L
436 \catcode13=5 % newline
437 \let\UseRawInputEncoding\relax

```

This ends the skipped code in Unicode engines:

```

438 \fi
439 \if2ekernel|latexrelease)
440 \latexrelease\EndIncludeInRelease
441 \latexrelease\IncludeInRelease{0000/00/00}%
442 \latexrelease{\UTFviii@invalid}{UTF-8 default}%

The first block of commands got only introduced in 2019 but we revert all of Unicode
support in one go not jump to the intermediate version.

443 \latexrelease\let\UTFviii@two@octets@combine\@undefined
444 \latexrelease\let\UTFviii@three@octets@combine\@undefined
445 \latexrelease\let\UTFviii@four@octets@combine\@undefined
446 \latexrelease\let\UTFviii@two@octets@string\@undefined
447 \latexrelease\let\UTFviii@three@octets@string\@undefined
448 \latexrelease\let\UTFviii@four@octets@string\@undefined
449 \latexrelease\let\UTFviii@two@octets@noexpand\@undefined
450 \latexrelease\let\UTFviii@three@octets@noexpand\@undefined
451 \latexrelease\let\UTFviii@four@octets@noexpand\@undefined

452 \latexrelease\@tempcnta=0
453 \latexrelease\loop
454 \latexrelease\catcode\@tempcnta=15
455 \latexrelease\advance\@tempcnta\@ne
456 \latexrelease\ifnum\@tempcnta<32
457 \latexrelease\repeat %
458 \latexrelease\catcode9=10 % tab
459 \latexrelease\catcode10=12 % ctrl J
460 \latexrelease\catcode12=13 % ctrl L
461 \latexrelease\catcode13=5 % newline
462 \latexrelease\@tempcnta=128
463 \latexrelease\loop
464 \latexrelease\catcode\@tempcnta=12
465 \latexrelease\advance\@tempcnta\@ne
466 \latexrelease\ifnum\@tempcnta<256
467 \latexrelease\repeat
468 \latexrelease\let\IeC\@undefined
469 \latexrelease\def\DeclareFontEncoding@#1#2#3{%
470 \latexrelease\expandafter
471 \latexrelease\ifx\csname T@#1\endcsname\relax
472 \latexrelease\def\cdp@elt{\noexpand\cdp@elt}%
473 \latexrelease\xdef\cdp@list{\cdp@list\cdp@elt{#1}%
474 \latexrelease{\default@family}{\default@series}%
475 \latexrelease{\default@shape}}%
476 \latexrelease\expandafter\let\csname#1-cmd\endcsname\@changed@cmd
477 \latexrelease\else
478 \latexrelease\@font@info{Redeclaring font encoding #1}%
479 \latexrelease\fi
480 \latexrelease\global\@namedef{T@#1}{#2}%
481 \latexrelease\global\@namedef{M@#1}{\default@M#3}%
482 \latexrelease\xdef\LastDeclaredEncoding{#1}%
483 \latexrelease}
484 \latexrelease\let\UseRawInputEncoding\@undefined
485 \latexrelease\let\DeclareFontEncoding@saved\@undefined
486 \latexrelease\let\inputencodingname\@undefined
487 \latexrelease\EndIncludeInRelease

```

488 <\*2ekernel>

We temporarily define `\reserved@a` to apply `\reserved@c` to all the numbers in the range of its arguments.

```

489 \def\reserved@a#1#2{%
490   \@tempcnta#1\relax
491   \@tempcntb#2\relax
492   \reserved@b
493 }
494 \def\reserved@b{%
495   \ifnum\@tempcnta>\@tempcntb\else
496     \reserved@c\@tempcnta
497     \advance\@tempcnta\@ne
498     \expandafter\reserved@b
499   \fi
500 }
```

Set the special catcodes (although some of these are useless, since an error will have occurred if the catcodes have changed). Note that `^^J` has catcode ‘other’ for use in warning messages.

```

501 \catcode'\ =10
502 \catcode'\#=6
503 \catcode'\$=3
504 \catcode'\%=14
505 \catcode'\&=4
506 \catcode'\'=0
507 \catcode'\^=7
508 \catcode'\_ =8
509 \catcode'\{=1
510 \catcode'\}=2
511 \catcode'\-=13
512 \catcode'\@=11
513 \catcode'\^^I=10
514 \catcode'\^^J=12
515 \catcode'\^^L=13
516 \catcode'\^^M=5
```

Set the ‘other’ catcodes.

```

517 \def\reserved@c#1{\catcode#1=12\relax}
518 \reserved@c{'\!}
519 \reserved@c{'\"}
520 \reserved@a{'\' }{'\?}
521 \reserved@c{'\[}
522 \reserved@c{'\]}
523 \reserved@c{'\' }
524 \reserved@c{'\|}
```

Set the ‘letter’ catcodes.

```

525 \def\reserved@c#1{\catcode#1=11\relax}
526 \reserved@a{'\A }{'\Z}
527 \reserved@a{'\a }{'\z}
```

All the characters in the range 0–31 and 127–255 are illegal, *except* `tab` (`^^I`), `nl` (`^^J`), `ff` (`^^L`) and `cr` (`^^M`).

## 1.7 Lccodes and uccodes

We now again set up the default (T1) uc/lccodes. The lower case characters need their `\uccode` and `\lccode` values set. Some of this is a repeat of the set-up before loading hyphenation files. Depending on the  $\TeX$  version, we might not be allowed to do this for non-ASCII characters. For the Unicode engines (Xe $\TeX$  and Lua $\TeX$ ) there is no need to do any of this: they use hyphenation data which does not alter any of the set up and so this entire block is skipped.

```

528 \ifnum 0%
529   \ifx\Umathcode\@undefined\else 1\fi
530   \ifx\XeTeXmathcode\@undefined\else 1\fi
531   >\z@
532 \else
533 \def\reserved@c#1{%
534   \count@=#1\advance\count@ by -"20
535   \uccode#1=\count@
536   \lccode#1=#1
537 }
538 \reserved@a{'\a}{'\z}
539 \reserved@a{"A0}{'BC}
540 \reserved@a{"E0}{'FF}

```

The upper case characters need their `\uccode` and `\lccode` values set, and their `\sfcode` set to 999.

```

541 \def\reserved@c#1{%
542   \count@=#1\advance\count@ by "20
543   \uccode#1=#1
544   \lccode#1=\count@
545   \sfcode#1=999
546 }
547 \reserved@a{'\A}{'\Z}
548 \reserved@a{"80}{'9C}
549 \reserved@a{"C0}{'DF}

```

Well, it would be nice if that were correct, but unfortunately, the Cork encoding contains some odd slots whose uccode or lccode isn't quite what you'd expect.

```

550 \uccode'\^^Y=' \I      % dotless i
551 \lccode'\^^Y=' \^^Y    % dotless i
552 \uccode'\^^Z=' \J      % dotless j, ae in OT1
553 \lccode'\^^Z=' \^^Z    % dotless j, ae in OT1
554 \lccode'\^^9d=' \i     % dotted I
555 \uccode'\^^9d=' \^^9d  % dotted I
556 \lccode'\^^9e=' \^^9e  % d-bar
557 \uccode'\^^9e=' \^^d0  % d-bar

```

Finally here is one that helps hyphenation in the OT1 encoding.

```

558 \lccode'\^^[=' \^^[    % oe in OT1
559 \fi % End of reset block for 8-bit engines

```

`\BCPdata` A stub for use by babel, polyglossia, etc.

```

560 \ExplSyntaxOn
561 \newcommand*\BCPdata[1]{
562   \str_case:nn {#1}
563   {
564     { language } { en }

```

```

565     { region }    { US }
566     { script }   { Latn }
567     { tag }      { en-US }
568   }
569 }
570 \ExplSyntaxOff

```

(End of definition for \BCPdata.)

## 1.8 Case changing

\MakeUppercase And whilst we're doing things with uc/lc tables, here are two commands to upper- and lower-case a string.

\MakeLowercase Wrappers around the L3 case changing functions. \protected to make them mostly safe as replacements for uppercase and \lowercase.

\MakeTitlecase In

\NoCaseChange

\AddToNoCaseChangeList

\CaseSwitch

\markboth{\MakeUppercase\contentsname}

{\MakeUppercase\contentsname}

then the uppercasing is only done to the first letter of the contents name, since the mark expands out to:

\mark{\MakeUppercase Table of Contents}

{\MakeUppercase Table of Contents}

\@uclclist

In order to get round this, we redefine \MakeUppercase and \MakeLowercase to grab their argument and brace it.

Earlier versions needed to process \@uclclist in an \edef to handle legacy input encodings, but recent (2022) expl3 versions handle non-UTF8 text natively so we simply call the \text\_...case:n functions.

```

571 \ExplSyntaxOn
572 \keys_define:nn { __kernel }
573 {
574   lang .str_set:N = \reserved@a ,
575   locale .str_set:N = \reserved@a ,
576   words .choices:nn =
577     { all , first }
578     { \str_set:Nn \reserved@b {#1} }
579 }
580 \cs_new_protected:Npn @@text@case@aux #1#2#3
581 {
582   \cs_set_nopar:Npn \reserved@a { }
583   \cs_set_nopar:Npn \reserved@b { first }
584   \tl_if_blank:nTF {#2}
585   {
586     \str_set:Nx \reserved@a
587       { \BCPdata { casing } }
588     \str_if_empty:NT \reserved@a
589     {
590       \str_set:Nx \reserved@a
591         { \BCPdata { language } }
592     }
593   }

```

```

594     { \keys_set:nn { __kernel } {#2} }
595     \use:c { text_ #1 :Vn } \reserved@a {#3}
596 }

```

The odd use of *three* spaces here is needed as `ltcmd` uses the name with one and two spaces to give a ‘friendly’ error message for a runaway argument: that means we can’t use it here.

```

597 \exp_args_generate:n { cnx }
598 \cs_set_protected:Npn \reserved@a #1
599 {
600     \cs_generate_variant:cn { text_ \str_lowercase:n {#1} case:nn } { V }
601     \ExpandArgs { cnx } \NewExpandableDocumentCommand
602     { Make#1case }
603     { O{ } +m }
604     { \exp_not:c { Make#1case \c_space_tl \c_space_tl \c_space_tl } [###1] {####2} }
605 }
606 \reserved@a { Upper }
607 \reserved@a { Lower }
608 \reserved@a { Title }

```

These don’t get covered above so we do them manually.

```

609 \cs_generate_variant:Nn \text_titlecase_all:nn { V }
610 \cs_generate_variant:Nn \text_titlecase_first:nn { V }

```

Currently, `babel` uses the equivalence of `\oe` and `\OE` to force casing of some material, most notably in `\today`. To enable that to work, we have to set those commands equal even though the current case changing code does not work using this approach.

```

611 \cs_new_protected:cpn { MakeLowercase \c_space_tl \c_space_tl \c_space_tl } [1] #2
612 {{
613     \let \OE \oe
614     \@@text@case@aux { lowercase } {#1} {#2}
615 }}
616 \cs_new_protected:cpn { MakeUppercase \c_space_tl \c_space_tl \c_space_tl } [1] #2
617 {{
618     \let \oe \OE
619     \@@text@case@aux { uppercase } {#1} {#2}
620 }}
621 \cs_new_protected:cpn { MakeTitlecase \c_space_tl \c_space_tl \c_space_tl } [1] #2
622 {{
623     \let \oe \OE
624     \@@text@case@aux { titlecase_ \reserved@b } {#1} {#2}
625 }}

```

`\NoCaseChange` protects its argument from the case change functions.

`\AddToNoCaseChangeList` Allows new commands to protect their arguments, eg `AddToNoCaseChangeList{\eqref}` would protect the argument of `\eqref` in the same way as the argument of `\ref`.

```

626 \cs_new_protected_nopar:Npn \AddToNoCaseChangeList
627     {\tl_put_right:Nn \l_text_case_exclude_arg_tl}
628 \AddToNoCaseChangeList{ \NoCaseChange }
629 \cs_new_protected:Npn \NoCaseChange #1 {#1}
630 \cs_new_eq:NN \CaseSwitch \text_case_switch:nnnn
631 \cs_new_eq:NN \DeclareCaseChangeEquivalent
632     \text_declare_case_equivalent:Nn
633 \NewDocumentCommand \DeclareLowercaseMapping { o m m }

```

```

634 {
635   \IfNoValueTF {#1}
636     { \text_declare_lowercase_mapping:nn }
637     { \text_declare_lowercase_mapping:nnn {#1} }
638     {#2} {#3}
639 }
640 \NewDocumentCommand \DeclareTitlecaseMapping { o m m }
641 {
642   \IfNoValueTF {#1}
643     { \text_declare_titlecase_mapping:nn }
644     { \text_declare_titlecase_mapping:nnn {#1} }
645     {#2} {#3}
646 }
647 \NewDocumentCommand \DeclareUppercaseMapping { o m m }
648 {
649   \IfNoValueTF {#1}
650     { \text_declare_uppercase_mapping:nn }
651     { \text_declare_uppercase_mapping:nnn {#1} }
652     {#2} {#3}
653 }
654 \cs_new_protected:Npn \DeclareLowercaseExclusions #1
655 {
656   \clist_map_inline:nn {#1}
657     { \text_declare_lowercase_exclusion:n {##1} }
658 }
659 \cs_new_protected:Npn \DeclareTitlecaseExclusions #1
660 {
661   \clist_map_inline:nn {#1}
662     { \text_declare_titlecase_exclusion:n {##1} }
663 }
664 \cs_new_protected:Npn \DeclareUppercaseExclusions #1
665 {
666   \clist_map_inline:nn {#1}
667     { \text_declare_uppercase_exclusion:n {##1} }
668 }
669 \ExplSyntaxOff
670 \def\@uclclist{\oe\OE\o\O\ae\AE
671   \dh\DH\dj\DJ\l\L\ng\NG\ss\SS\ij\IJ\th\TH}

```

(End of definition for \MakeUppercase and others.)

## 1.9 Automatic insertion of \par tokens

Since 2022 the major T<sub>E</sub>X engines have a parameter, `\partokencontext`, that controls whether a `\par` token is added if T<sub>E</sub>X is in horizontal mode at the end of `\vbox` and similar contexts. This gives more control than the classical behaviour where the internal *end paragraph* routine is invoked with no explicit token being added.

Setting `\partokencontext` to 2 ensures a literal `\par` is used in all contexts, setting to 0 reverts to the classic T<sub>E</sub>X behavior.

```

672 </2ekernel>
673 <*2ekernel|latexrelease>
674 <latexrelease>\IncludeInRelease{2025/11/01}%

```

```

675 <latexrelease>                {\partokencontext}{automatic par insertion}%
676 \ifdefined\partokencontext\partokencontext=\tw@fi
677 </2ekernel|latexrelease>
678 <latexrelease>\EndIncludeInRelease
679 <latexrelease>\IncludeInRelease{0000/00/00}%
680 <latexrelease>                {\partokencontext}{automatic par insertion}%
681 <latexrelease>\ifdefined\partokencontext\partokencontext=\z@fi
682 <latexrelease>\EndIncludeInRelease
683 <*2ekernel>

```

## 1.10 Applying Patch files

Between major releases, small patches will be distributed in files `ltpatch.ltx` which must be added at this point.

Patch file code removed.

```

684 %\IfFileExists{ltpatch.ltx}
685 % {\typeout{=====^^J%
686 %           Applying patch file ltpatch.ltx^^J%
687 %           =====}}
688 % \def\fmtversion@topatch{unknown}
689 % \input{ltpatch.ltx}
690 % \ifx\fmtversion\fmtversion@topatch
691 % \ifx\patch@level\@undefined
692 % \typeout{^^J^^J^^J%
693 %          !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!^^J%
694 %          !! Patch file 'ltpatch.ltx' not suitable for this^^J%
695 %          !! version of LaTeX.^^J^^J%
696 %          !! Please check if initex found an old patch file:^^J%
697 %          !! --- if so, rename it or delete it, and redo the^^J%
698 %          !! initex run.^^J%
699 %          !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!^^J}%
700 % \batchmode \@end
701 % \else

```

The code below adds the 'patch level' string to the first `\typeout` in the startup banner.

```

702 % \def\fmtversion@topatch{0}%
703 % \ifx\fmtversion@topatch\patch@level\else
704 % \def\reserved@a\typeout##1##2\reserved@a{%
705 % \typeout{##1 patch level \patch@level}##2}
706 % \everyjob\expandafter\expandafter\expandafter{%
707 % \expandafter\reserved@a\the\everyjob\reserved@a}
708 % \let\reserved@a\relax
709 % \the\everyjob
710 % \fi
711 % \fi
712 % \else
713 % \typeout{^^J^^J^^J%
714 %          !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!^^J%
715 %          !! Patch file 'ltpatch.ltx' (for version <\fmtversion@topatch>)^^J%
716 %          !! is not suitable for version <\fmtversion> of LaTeX.^^J^^J%
717 %          !! Please check if initex found an old patch file:^^J%
718 %          !! --- if so, rename it or delete it, and redo the^^J%
719 %          !! initex run.^^J%
720 %          !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!^^J}%

```

```

721 %      \batchmode \@@end
722 %      \fi
723 %      \let\fmtversion@topatch\relax
724 %    }{}

```

## 1.11 Freeing Memory

`\reserved@a` And just to make sure nobody relies on those definitions of `\reserved@b` and friends.  
`\reserved@b` These macros are reserved for use in the kernel. *Do not use them as general scratch macros.*

```

725 \let\reserved@a\@filelist
726 \let\reserved@b=\@undefined
727 \let\reserved@c=\@undefined
728 \let\reserved@d=\@undefined
729 \let\reserved@e=\@undefined
730 \let\reserved@f=\@undefined

```

(End of definition for `\reserved@a` and `\reserved@b`.)

`\toks`

```

731 \toks0{}
732 \toks2{}
733 \toks4{}
734 \toks6{}
735 \toks8{}

```

(End of definition for `\toks`.)

`\errhelp` Empty the error help message, which may have some rubbish:

```

736 \errhelp{}

```

(End of definition for `\errhelp`.)

## 1.12 Initialise file list

`\@providesfile` Initialise for use in the document. During initex a modified version has been used which leaves debugging information for `latexbug.tex`.

```

737 \def\@providesfile#1[#2]{%
738   \wlog{File: #1 #2}%
739   \expandafter\xdef\csname ver@#1\endcsname{#2}%
740   \endgroup}

```

(End of definition for `\@providesfile`.)

`\@filelist` Reset `\@filelist` so files input while making the format are not listed. The list built up so far may take up a lot of memory and so it is moved to `\reserved@a` where it will be overwritten as soon as almost any `LATEX` command is issued in a class file. However the `latexbug.tex` program will be able to access this information and insert it into a bug report.

`\@addtofilelist`

```

741 \let\@filelist\@gobble
742 \def\@addtofilelist#1{\xdef\@filelist{\@filelist,#1}}%

```

(End of definition for `\@filelist` and `\@addtofilelist`.)

### 1.13 Preparation for supporting PDF in backends

At the current point in time, basic support for PDF in backends is not part of L<sup>A</sup>T<sub>E</sub>X core; it is provided by external packages. At some time in the future that work will be placed into the kernel but for now it is separate and has to be explicitly loaded in the document.

In that code there is a command `\IfPDFManagementActiveTF` which can be used by packages in order to execute different code depending on the whether this basic backend support is loaded.

To make this also work properly when this external package is not loaded at all, we here add this command already in the kernel (with a trivial definition); thus any package can query this loading state in all circumstances. Once this basic PDF backend support gets moved to the kernel, this definition will vanish again from here or, rather, it will be replaced by a real test.

`\IfPDFManagementActiveTF` So long as the code for the basic backend support for PDF is not loaded, the test that is implicit here will always return the false branch. Once this code is loaded, this definition will get replaced by a real test (as it is then possible that the management code is either activated or not activated).

```
743 \let \IfPDFManagementActiveTF \@secondoftwo
```

The T/F variants are defined in a way that they continue to work when the main definition changes.

```
744 \long\def\IfPDFManagementActiveT#1{\IfPDFManagementActiveTF{#1}{}}
```

```
745 \def\IfPDFManagementActiveF{\IfPDFManagementActiveTF{}}
```

*(End of definition for \IfPDFManagementActiveTF.)*

### 1.14 Do some temporary work for pre-release

This is a good place to load code that hasn't yet been integrated into the other files ...

### 1.15 Some last minute initializations ...

Load the first aid set of definitions for external packages that await updates.

```
746 \@input{latex2e-first-aid-for-external-files.ltx}
```

### 1.16 Dumping the format

Finally we make @ into a letter, ensure the format will be in the 'normal' error mode, and dump everything into the format file.

```
747 \makeatother
```

```
748 \errorstopmode
```

```
749 \dump
```

```
750 </2ekernel>
```

# Change History

1985-11-04 ltmath.dtx LaTeX2.09		<code>\mathversion</code> : Test if version defined added. . . . .	551
General: produce warning message if line extends into margin. Doesn't warn about formula overprinting equation number. . . . .	864		
1989-04-10 ltfssbas.dtx v1.0a		1989-04-29 ltfssbas.dtx v1.0i	
General: Starting with version numbers! <code>\ifmmode</code> added in <code>\math@group</code> . . . . .	538	General: Removed the <code>\halign</code> <code>\noalign</code> correction (wasn't bugfree) . . . . .	538
1989-04-10 ltfssbas.dtx v1.0b		1989-04-29 ltfssini.dtx v1.0f	
General: <code>\preload@sizes</code> added. . . . .	538	General: Corrections to L <sup>A</sup> T <sub>E</sub> X tabular env. added. . . . .	702
<code>\wrong@fontshape</code> changed to define substitution font/shape macro. . . . .	538	1989-05-01 ltfssbas.dtx v1.0j	
1989-04-10 ltfssini.dtx v1.0a		General: Default for <code>\baselinestretch</code> added. . . . .	538
General: Starting with version numbers <code>\newif</code> for <code>\@tempswa</code> added since this switch is unknown at the time when this file is read in. (latex.tex is loaded later.) <code>\math@famname</code> changed to <code>\math@version</code> . . . . .	702	1989-05-22 ltfssbas.dtx v1.0k	
1989-04-14 ltfssbas.dtx v1.0c		General: Lines longer than 72 characters folded. . . . .	538
General: More documentation added. . . . .	538	1989-05-22 ltfssini.dtx v1.0g	
1989-04-15 ltfssini.dtx v1.0b		General: Lines shortened to 72 characters . . . . .	702
General: <code>\mathfontset</code> renamed to <code>\mathversion</code> . . . . .	702	1989-09-14 ltfssbas.dtx v1.0m	
1989-04-19 ltfssbas.dtx v1.0d		General: Global replacement: <code>\group</code> to <code>\mathgroup</code> . . . . .	538
General: Even more doc. . . . .	538	<code>\mathversion</code> : Corrected typo: <code>\endscname</code> to <code>\endcsname</code> . . . . .	551
1989-04-21 ltfssbas.dtx v1.0e		1989-11-07 ltfssini.dtx v1.0i	
General: Documentation is fun! Parameters of <code>\define@mathalphabet</code> changed. . . . .	538	General: All family, series, and shape names abbreviated. . . . .	702
1989-04-21 ltfssini.dtx v1.0c		1989-11-08 ltfssbas.dtx v1.0o	
General: Changed to conform to fam.tex. . . . .	702	General: First parameter of <code>\define@mathalphabet</code> and <code>\define@mathgroup</code> changed from string to control sequence. . . . .	538
1989-04-23 ltfssbas.dtx v1.0f		1989-11-14 ltfssbas.dtx v1.0p	
General: % in <code>\getanddefinefonts</code> added. . . . .	538	<code>\math@version</code> : Math version prefix 'mv@' added. . . . .	551
1989-04-26 ltfssini.dtx v1.0d		1989-11-19 ltfssbas.dtx v1.0q	
General: <code>\xpt</code> added. . . . .	702	<code>\define@newfont</code> : Group added. . . . .	554
1989-04-27 ltfssbas.dtx v1.0g		<code>\wrong@fontshape</code> : Instead of calling <code>\family\default@family</code> , etc. we directly set <code>\f@family</code> , etc. . . . .	559
General: Documentation revised. . . . .	538	1989-11-22 ltfssbas.dtx v1.0r	
1989-04-27 ltfssini.dtx v1.0e		<code>\math@version</code> : <code>\def</code> → <code>\edef</code> for <code>\math@version</code> . . . . .	551
General: Definitions of L <sup>A</sup> T <sub>E</sub> X symbols corrected. . . . .	702	1989-11-25 ltfssbas.dtx v1.0s	
1989-04-29 ltfssbas.dtx v1.0h		General: All <code>\edef\font@name</code> changed to <code>\xdef\font@name</code> . Necessary after introduction of <code>\begingroup/\endgroup</code> in v1.0q. . . . .	538
General: Documented problem with <code>\halign</code> , and <code>\noalign</code> . . . . .	538	extra// → + in <code>\extra@def</code> . . . . .	538

1989-11-26 ltfssbas.dtx v1.0t	1990-01-25 ltfssini.dtx v1.1e
<code>\select@group</code> : <code>\bgroup</code> / <code>\egroup</code>	<code>\nfss@text</code> : Macro added. . . . . 726
changed to	1990-01-27 ltfssbas.dtx v1.2d
<code>\begingroup</code> / <code>\endgroup</code> to avoid	<code>\DeclarePreloadSizes</code> : Font identifier
empty Ord atom on math list. . . 562	set to <code>\relax</code> . . . . . 546
1989-12-02 ltfssini.dtx v1.1b	1990-01-28 ltfssbas.dtx v1.2e
General: <code>\rmmath</code> renamed to	<code>\mathgroup</code> : <code>\newfam</code> let to
<code>\mathrm</code> . . . . . 702	<code>\new@mathgroup</code> . . . . . 538
1989-12-03 ltfssini.dtx v1.1c	1990-01-28 ltfssbas.dtx v1.2f
General: Some internal macros	<code>\define@newfont</code> : Added call to
renamed to make them	<code>\curr@fontshape</code> macro to allow
inaccessible. . . . . 702	substitution. . . . . 555
1989-12-05 ltfssbas.dtx v1.0u	<code>\wrong@fontshape</code> : Warning message
<code>\addto@hook</code> : <code>\addto@hook</code> added. . 566	slightly changed. . . . . 559
1989-12-05 ltfssstrc.dtx v1.0u fam.dtx	1990-01-28 ltfssini.dtx v1.2b
<code>\every@math@size</code> : Hook <code>\every@size</code>	<code>\em</code> : Call to <code>\@nomath</code> added. . . . . 724
added. . . . . 647	1990-02-08 ltfssini.dtx v1.1g
1989-12-13 ltfssstrc.dtx v1.0f	General: Protected the commands
<code>\use@mathgroup</code> : <code>\expandafter</code> added	<code>\family</code> , <code>\series</code> , <code>\shape</code> , <code>\size</code> ,
before final <code>\fi</code> . . . . . 650	<code>\selectfont</code> , and <code>\mathversion</code> . 702
1989-12-16 ltfssbas.dtx v1.1a	1990-02-16 ltfssbas.dtx v1.2g
<code>\select@group</code> : <code>\relax</code> in front	General: Support for changes of
added. . . . . 562	<code>\baselineskip</code> without changing
Now four arguments. . . . . 562	the size. . . . . 538
Redefinition of alphabet now	<code>\math@version</code> : <code>\@nomath</code> added. . . 551
simpler. . . . . 562	1990-02-18 ltfssstrc.dtx v1.0j
Usage of ‘=’ macro added. . . . . 562	<code>\selectfont</code> : Redefine unprotected
1989-12-16 ltfssstrc.dtx v1.1a	version <code>\p@selectfont</code> instead of
<code>\selectfont</code> : Changed order of calls. 642	<code>\selectfont</code> . . . . . 642
<code>\use@mathgroup</code> : Redefinition of	1990-03-14 ltfssstrc.dtx v1.0k
alphabet now simpler. . . . . 649	General: Added code for TeX3. . . . . 638
Usage of ‘=’ macro added. . . . . 649	<code>\extract@font</code> : Added code for
1990-01-18 ltfssstrc.dtx v1.0h	TeX3. . . . . 641
General: <code>\tracingfonts</code> meaning	1990-03-30 ltfssbas.dtx v1.2h
changed. . . . . 638	<code>\math@egroup</code> : Changed to have one
1990-01-20 ltfssbas.dtx v1.2a	arg. . . . . 564
<code>\math@bgroup</code> : Def. placed in this	1990-03-30 ltfssstrc.dtx v1.2h
file. . . . . 564	<code>\use@mathgroup</code> : Third argument
<code>\math@egroup</code> : Def. placed in this	removed (see <code>\math@egroup</code> ). . . . 649
file. . . . . 564	1990-04-01 ltfssbas.dtx v1.2i
<code>\select@group</code> : Def for alph id	General: Code added from
changed. . . . . 562	tracefnt.dtx. . . . . 538
1990-01-21 ltfssbas.dtx v1.2b	Support for TeX3. . . . . 538
<code>\select@group</code> : Code moved to	1990-04-01 ltfssstrc.dtx v1.0l
<code>\use@mathgroup</code> . . . . . 562	General: Part of code moved to
1990-01-21 ltfssstrc.dtx v1.2b	fam.dtx. . . . . 638
<code>\use@mathgroup</code> : Macro added to	<code>\tracingfonts</code> : Check if
allow cleaner interface. . . . . 649	<code>\tracingfonts</code> already defined. . 639
1990-01-23 ltfssbas.dtx v1.2c	1990-04-01 ltfssstrc.dtx v1.0o
General: <code>\no@version@warning</code>	<code>\tracingfonts</code> : Check if
renamed to <code>\no@alphabet@error</code> . 538	<code>\tracingfonts</code> defined removed
Macro <code>\no@alphabet@help</code> added 538	again. . . . . 639
<code>\no@alphabet@error</code> : Changed to	
error call . . . . . 538	

1990-04-02 ltfsini.dtx v1.1i	1991-08-14 ltpictur.dtx LaTeX2.09
General: <code>\input</code> of files now handled by docstrip. . . . .	General: (RmS) inserted extra braces around entry for NFSS . . . . .
702	938
1990-04-05 ltfsstrc.dtx v1.0m	1991-08-14 ltthm.dtx LaTeX2.09
<code>\selectfont</code> : Call <code>\tracingon</code> only if <code>\tracingfonts</code> greater than 3. . .	<code>\endtheorem</code> : Moved <code>\itshape</code> after <code>\item</code> to make it work with NFSS . . .
642	968
1990-05-05 ltfsstrc.dtx v1.0n	1991-08-26 ltfsini.dtx v1.1n
<code>\selectfont</code> : <code>\tracingon</code> with new syntax. . . . .	<code>\reset@font</code> : Macro introduced . . .
642	727
1990-06-23 ltfsini.dtx v1.1k	1991-08-26 ltmiscen.dtx LaTeX2.09
<code>\nfss@text</code> : Changed to <code>\mbox</code> . . .	<code>\verbatim</code> : <code>\@par</code> added . . . . .
727	846
1990-06-24 ltfsbas.dtx v1.2j	1991-08-26 ltpictur.dtx LaTeX2.09
<code>\DeclarePreloadSizes</code> : Missing percent added. . . . .	<code>\endpicture</code> : (RmS & FMI) extra boxing level around <code>\@picbox</code> to guard against unboxing in math mode (proposed by John Hobby) . . .
546	936
1990-06-24 ltfsstrc.dtx v1.0o	1991-08-26 ltplain.dtx LaTeX2.09
<code>\baselinestretch</code> : Moved to tracefnt.dtx. . . . .	<code>\tracingall</code> : Added <code>\errorcontextlines=\maxdimen</code> , suggested by J. Schrod . . . . .
647	31
<code>\getanddefine@fonts</code> : <code>\Adding</code> tracing code. . . . .	1991-09-29 ltboxes.dtx LaTeX2.09
651	<code>\mpfootnotetext</code> : (RmS) added <code>\reset@font</code> . . . . .
<code>\Macro</code> moved from fam.dtx. . . .	903
650	1991-09-29 ltfloat.dtx LaTeX2.09
Adding debug code. . . . .	<code>\@footnotetext</code> : (RmS) added <code>\reset@font</code> . . . . .
651	1002
<code>\use@mathgroup</code> : Tracing code added. 650	1991-09-29 ltmath.dtx LaTeX2.09
1990-06-30 ltfsbas.dtx v1.2l	<code>\eqnnum</code> : RmS: <code>\reset@font</code> added. . .
<code>\showhyphens</code> : Macro added. . . . .	864
565	1991-09-29 ltsect.dtx LaTeX2.09
1990-06-30 ltfsstrc.dtx v1.0p	<code>\dottedtocline</code> : (RmS) added <code>\reset@font</code> for page number . . .
<code>\use@mathgroup</code> : Added <code>\relax</code> after math group number. . . . .	981
650	1991-10-17 ltctrl.dtx LaTeX2.09
1990-07-07 ltfsstrc.dtx v1.0q	<code>\@tfor</code> : (RmS) <code>\xdef</code> replaced by <code>\def</code> (See FMI's array.doc) . . . . .
<code>\getanddefine@fonts</code> : Group number added to tracing. . . . .	399
651	1991-10-25 ltbibl.dtx LaTeX2.09
<code>\math@egroup</code> : Tracing code added. . 650	<code>\citex</code> : added <code>\reset@font</code> , suggested by Bernd Raichle. . . . .
<code>\use@mathgroup</code> : Group number added to tracing. . . . .	1011
650	1991-11-01 ltfloat.dtx LaTeX2.09
1990-08-27 ltfsstrc.dtx 1.0r	<code>\footnote</code> : (RmS) Added <code>\let\protect\noexpand</code> in <code>\footnote</code> , <code>\footnotemark</code> , and <code>\footnotetext</code> , since <code>\xdef</code> is used . . . . .
<code>\type@restoreinfo</code> : Some extra tracing info. . . . .	1002
646	1991-11-04 ltlists.dtx LaTeX2.09
1990-08-27 ltfsstrc.dtx v1.0r	<code>\makelabel</code> : (RmS) added default definition for <code>\makelabel</code> , to produce an error message. . . . .
<code>\getanddefine@fonts</code> : Correcting missing name after <code>\tracingon</code> . . .	885
651	1991-11-04 ltplain.dtx RmS
1991-03-28 ltfsini.dtx v1.1m	General: Removed <code>\itemitem</code> since never needed/useful with L <sup>A</sup> T <sub>E</sub> X. . .
<code>\copyright</code> : Extra braces added. . .	29
727	1991-11-06 ltbibl.dtx LaTeX2.09
1991-03-30 ltfsini.dtx v1.2g	<code>\citex</code> : added code to remove a leading blank . . . . .
<code>\newfont</code> : Definition added. . . . .	1011
725	
<code>\symbol</code> : Definition added. . . . .	
726	
1991-07-24 ltmiscen.dtx LaTeX2.09	
<code>\@verbatim</code> : Added <code>\penalty\interlinepenalty</code> to definition of <code>\par</code> so that <code>\samepage</code> works . . . . .	
846	
1991-08-14 ltmath.dtx LaTeX2.09	
<code>\cases</code> : (RmS) inserted extra braces around entry for NFSS . . . . .	
857	

1991-11-13 ltbibl.dtx LaTeX2.09	avoid conflicts with other channels allocated by <code>\newread</code> . . . . .	80
<code>\@bibitem</code> : Changed counter <code>enumi</code> to <code>enumiv</code> , as it says in the comment above . . . . .		1010
1991-11-21 ltfssini.dtx v1.1o	<code>\xympar</code> : (RmS) added <code>\global\@ignorefalse</code> . . . . .	997
<code>\reset@font</code> : Added extra braces for robustness. . . . .	<code>\end@float</code> : (RmS) changed <code>\@esphack</code> to <code>\@Esphack</code> . . . . .	727
Changed to protected version of macro. . . . .		727
1991-11-22 ltfloat.dtx LaTeX2.09	1992-03-18 ltfloat.dtx LaTeX2.09	
<code>\footnote</code> : (RmS) Added <code>\let\protect\noexpand</code> in <code>\@xfootnote</code> , <code>\@xfootnotemark</code> , and <code>\@xfootnotetext</code> . . . . .	<code>\trivlist</code> : RmS: added <code>\@nmbrlistfalse</code> . . . . .	880
1991-11-22 ltlists.dtx LaTeX2.09	1992-03-18 ltmiscen.dtx LaTeX2.09	
<code>\@item</code> : (RmS) Changed second call to <code>\makelabel</code> to <code>\unhbox\@tempboxa</code> . Avoids problems with side effects in <code>\makelabel</code> and is more efficient. . . . .	<code>\begin</code> : Changed <code>\@ignoretrue</code> to <code>\@ignorefalse</code> (as documented) . . . . .	837
1991-11-27 ltfssbas.dtx v1.3a	1992-03-21 ltfssini.dtx v1.2d	
General: All <code>\family</code> , <code>\shape</code> etc. renamed to <code>\fontfamily</code> etc. . . . .	General: Renamed <code>\text</code> to <code>\nfss@text</code> to make it internal. . . . .	702
1991-11-27 ltfssini.dtx v1.2a	1992-05-12 ltfssbas.dtx v1.3c	
General: All <code>\family</code> , <code>\shape</code> etc. renamed to <code>\fontfamily</code> etc. . . . .	<code>\extract@alph@from@version</code> : Macro added. . . . .	563
1992-01-06 ltfssini.dtx v1.2c	<code>\select@group</code> : Added call to <code>\extract@alph@from@version</code> . . . . .	562
General: added <code>slitex</code> code . . . . .	1992-07-26 ltfssbas.dtx v1.9a	
1992-01-10 ltbibl.dtx LaTeX2.09	<code>\curr@fontshape</code> : . . . . .	554
<code>\@bibitem</code> : Changed <code>\c@enumiv</code> to <code>\value of \@listctr</code> . . . . .	<code>\DeclareFontShape</code> : Introduced <code>\DeclareFontShape</code> . . . . .	539
1992-01-10 ltmath.dtx LaTeX2.09	<code>\define@newfont</code> : . . . . .	554
<code>equation</code> : RmS: put <code>\hbox</code> around <code>\@eqnnum</code> to typeset the equation number in text mode (as in the <code>eqnarray</code> env.) . . . . .	<code>\math@fonts</code> : . . . . .	561
1992-01-10 ltthm.dtx LaTeX2.09	<code>\select@group</code> : . . . . .	562
<code>\@othm</code> : (RmS) Check for existence of theorem environment . . . . .	<code>\split@name</code> : Added splitting into <code>\f@encoding</code> . . . . .	554
1992-01-14 ltbibl.dtx LaTeX2.09	<code>\wrong@fontshape</code> : . . . . .	559
<code>\@biblabel</code> : removed <code>\hfill</code> . . . . .	1992-07-26 ltfssstrc.dtx v2.0b	
1992-01-14 ltsect.dtx 0.0	<code>\s@fct@</code> : . . . . .	660
<code>\@starttoc</code> : (RmS) added <code>\immediate</code> to <code>\openout</code> as all <code>\write</code> commands are also executed <code>\immediate</code> . . . . .	<code>\s@fct@sub</code> : documentation fixes . . . . .	661
1992-02-26 ltbibl.dtx LaTeX2.09	<code>\selectfont</code> : . . . . .	643
<code>\@lbibitem</code> : Added <code>\hfill</code> to restore left-alignment of bibliography labels in alpha style . . . . .	<code>\try@simple@size</code> : . . . . .	654
1992-03-18 ltdefns.dtx LaTeX2.09	<code>\try@size@range</code> : . . . . .	657
General: (RmS) changed input channel from 0 to <code>\@inputcheck</code> to	<code>\use@mathgroup</code> : . . . . .	650
	1992-08-14 ltbibl.dtx LaTeX2.09	
	<code>\@citex</code> : added missing argument braces around <code>\hbox</code> , found by Ed Sznyter . . . . .	1011
	1992-08-14 ltboxes.dtx LaTeX2.09	
	<code>\endminipage</code> : (RmS) replaced <code>\vskip</code> - <code>\lastskip</code> by <code>\unskip</code> (proposed by FMI) . . . . .	903
	1992-08-17 ltbibl.dtx LaTeX2.09	
	<code>\@citex</code> : simplified code for removing leading blanks in citation key (proposed by Frank Jensen and Kresten Krab Thorup) . . . . .	1011
	1992-08-19 ltsect.dtx 0.0	
	<code>\@xsect</code> : (RmS) corrected bug: stretch and shrink in argument to <code>\hskip</code>	

previously not negated . . . . .	974	<code>\footnote:</code> (RmS) Changed all to 'def'protect'noexpand'protect'noexpand . . . . .	1002
1992-08-19 ltthm.dtx LaTeX2.09		1992-12-03 ltffsini.dtx v?	
<code>\@othm:</code> (RmS) Changed error message to complain about undefined counter . . . . .	967	<code>\hexnumber@:</code> Make it accept counters. . . . .	726
1992-08-20 ltffsini.dtx v1.4b		1993-03-08 preload.dtx v2.0b	
<code>\@setsize:</code> Added <code>\@currsize.</code> . . .	726	General: Added 12pt preloads . . . .	753
1992-08-24 ltdefs.dtx LaTeX2.09		1993-03-18 ltffsbas.dtx v2.0c	
<code>\@ifnextchar:</code> (Rms) <code>\@ifnextchar</code> didn't work if its first argument was an equal sign. . . . .	108	General: Changed all <code>\@tempdima</code> in <code>\@tempdimb</code> to avoid killing <code>\numberline</code> . . . . .	538
1992-08-24 ltmiscen.dtx LaTeX2.09		1993-03-18 ltfsstrc.dtx v2.1b	
<code>\begin:</code> Added code to <code>\begin</code> to remember line number. Used by <code>\@badend</code> to display position of non-matching <code>\begin.</code> . . . . .	837	General: Changed all <code>\@tempdima</code> in <code>\@tempdimb</code> to avoid killing <code>\numberline</code> . . . . .	638
<code>\verb:</code> Changed <code>\verb</code> and <code>\@sverb</code> to work correctly in math mode . . .	851	Changed all <code>\@tempdimb</code> in <code>\@tempdimx</code> to avoid killing <code>\numberline</code> . . . . .	638
1992-08-25 ltsect.dtx LaTeX2.09		1993-03-18 ltfsstrc.dtx v2.1c	
<code>\@sect:</code> (FMi) replaced explicit setting of <code>\@svsec</code> by call to <code>\@seccntformat</code> . . . . .	973	<code>\DeclareSizeFunction:</code> Added all args to avoid blanks problems . .	657
1992-09-18 ltlists.dtx LaTeX2.09		1993-04-09 lterror.dtx v1.0e	
<code>\item:</code> (RmS) Added warning if <code>\item</code> is used in math mode . . . . .	883	<code>\@latexerr:</code> Mention The Companion . . . . .	406
1992-09-18 lttab.dtx LaTeX2.09		1993-04-11 lterror.dtx v1.0f	
<code>\@array:</code> Changed <code>\par</code> to <code>\@empty</code> to avoid starting new row e.g. after <code>\hline</code> . . . . .	921	<code>\@latexerr:</code> Remove setting of errorcontextlines . . . . .	406
1992-09-19 ltfsstrc.dtx v2.0c		1993-05-05 ltftncmd.dtx v2.0b	
<code>\try@simple@size:</code> . . . . .	654	General: Removed all LaTeX related cmds . . . . .	756
1992-09-21 ltffsini.dtx v1.4d		1993-05-16 ltffsbas.dtx v2.0e	
<code>\not@math@alphabet:</code> Macro defined. .	725	<code>\showhyphens:</code> Use <code>\reset@font</code> . .	565
1992-09-22 ltffsbas.dtx v1.91a		1993-07-16 ltfsstrc.dtx v2.1h	
General: Introduced <code>\tf@size</code> for math size. . . . .	538	General: Changed layout of info messages . . . . .	638
1992-09-22 ltfsstrc.dtx v2.1a		1993-07-17 ltoutenc.dtx 1.0d	
<code>\getanddefine@fonts:</code> Introduced <code>\tf@size</code> for math size. . . . .	651	General: changed <code>\catcoding @</code> . . .	481
1992-11-13 ltffsini.dtx v?		1993-08-03 ltmiscen.dtx LaTeX2.09	
<code>\hexnumber@:</code> Made expandable. . . .	726	<code>\enddocument:</code> Changed redefinition of <code>\global</code> to redefinition of <code>\@setckpt.</code> . . . . .	829
1992-11-23 ltcounts.dtx LaTeX2.09		1993-08-05 ltpictur.dtx LaTeX2.09	
<code>\stepcounter:</code> Replaced <code>{}</code> in <code>\stepcounter</code> by <code>\begingroup</code> <code>\endgroup</code> to avoid adding an empty ord in math mode . . . . .	527	<code>\circle:</code> (RMS) Added error message if <code>\circle</code> is used in math mode. .	958
1992-11-26 ltboxes.dtx LaTeX2.09		1993-08-05 ltsect.dtx LaTeX2.09	
<code>\@mpfootnotetext:</code> (RmS) added protection for <code>\edef</code> . . . . .	903	<code>\@sect:</code> (RmS) Made sure that <code>\protect</code> works correctly in expansion of <code>\the</code> counter . . . .	973
1992-11-26 ltfloat.dtx LaTeX2.09		1993-08-05 ltspc.dtx LaTeX2e	
<code>\@footnotetext:</code> (RmS) added protection for <code>\edef</code> . . . . .	1002	<code>\@hspace:</code> (RmS) Removed superfluous <code>\leavevmode</code> in <code>\@hspace</code> and <code>\@hspace</code> , as suggested by CAR. . . . .	451

1993-08-05 lttab.dtx latex2e			
\tabular*: Replaced			
\expandafter\def by \@namedef.	920		
1993-08-06 ltbibl.dtx LaTeX2.09			
\@citex: Moved writing to .aux file in			
loop over citation keys so that			
leading blanks are removed there			
as well.	1011		
1993-08-13 ltoutenc.dtx 1.0f			
General: Protected against active @			
sign.	481		
1993-08-13 preload.dtx v2.0c			
General: Added \relax at end of font			
names.	754		
1993-08-16 ltoutenc.dtx 1.0g			
General: Needs space after \string	481		
1993-08-18 ltfsdcl.dtx v2.0e			
\new@mathversion: Exchanged names			
of encodings in warning message of			
\SetSymbolFont.	683		
1993-09-02 ltfsstrc.dtx v2.1i			
General: Corrected name of sgen size			
function.	638		
1993-09-03 ltmiscen.dtx LaTeX2.09			
\verbatim@nolig@list: Replaced			
\@noligs by extensible list	851		
1993-09-07 ltmiscen.dtx LaTeX2.09			
\verb@balance@group: (RmS)			
Changed definition of \verb so			
that it detects a missing second			
delimiter.	851		
1993-09-08 ltmiscen.dtx LaTeX2.09			
\enddocument: Added warning in case			
of undefined references.	829		
1993-09-15 ltfsbas.dtx v2.0g			
\DeclareFontEncoding: Corrected:			
\default@T to \default@M.	542		
1993-09-15 ltfsstrc.dtx v2.1j			
General: Corrected spelling of			
\noxpand.	638		
1993-09-19 lterror.dtx LaTeX2.09			
\@invalidchar: (RmS) Error message			
for invalid input characters.	410		
1993-11-02 ltmath.dtx LaTeX2.09			
General: RmS: Corrected description			
of \@eqnset, moved \@eqnset			
accordingly and removed extra			
\tabskip assignment.	864		
1993-11-03 ltmath.dtx LaTeX2e			
General: RmS: Initialized \everycr to			
empty	864		
1993-11-03 ltpictur.dtx LaTeX2.09			
General: (RmS) changed \halign to			
\ialign to initialize \tabskip and			
\everycr	938		
1993-11-11 ltfsini.dtx v2.1a			
\normalfont: Macro added	727		
1993-11-11 ltfsstrc.dtx v2.2a			
General: Option concept added for			
LaTeX2e	638		
1993-11-14 ltclass.dtx v0.2a			
\@current: Name changed from			
\@currentextension	1056		
\@reset@ptions: macro added	1083		
\AtEndDocument: Included extension			
in the generated macro name for			
package and class hooks.	1084		
\documentstyle: Added			
\RequirePackage			
\@unusedoptionlist stuff.	1072		
\load@onefilewithoptions: Moved			
resetting of \default@ds, \ds@ and			
\@declaredoptions here, from the			
end of \ProcessOptions.	1077		
\NeedsTeXFormat: made more robust			
for alternative syntax for other			
formats.	1074		
\ProcessOptions*: Optimize 'empty			
option' code.	1068		
Stop adding the global option list			
inside class files.	1068		
1993-11-14 ltdefs.dtx v0.2a			
\g@addto@macro: Made global	112		
1993-11-15 ltclass.dtx v0.2b			
\documentstyle: Modified to match			
\ProcessOption*	1072		
\ProcessOptions*: Star form			
added.	1068		
1993-11-17 ltclass.dtx v0.2c			
\@fileswith@ptions: Macro added	1083		
\@badrequireerror: Macro added	1086		
\@twoloadclasserror: Macro added	1086		
\CurrentOption: Name changed from			
\@curroption	1055		
\DeclareOption*: Error checking			
added	1067		
\load@onefilewithoptions: Added			
trap for two \LoadClass			
commands.	1080		
\NeedsTeXFormat: Name changed from			
\NeedsFormat	1074		
\ProcessOptions*: restoring			
\@fileswith@ptions added.	1068		
1993-11-18 ltclass.dtx v0.2d			
\documentstyle: Modified			
\RequirePackage stuff.	1072		

\ExecuteOptions: Use		\newcommand: Macro added . . . . .	82
\CurrentOption not		\newenv: Macro interface changed . .	86
\reserved@a . . . . .	1071	\xargdef: Macro interface changed .	82
\NeedsTeXFormat: \fmtname		\yargdf: Avoid \@? token . . . . .	83
\fmtversion not \@ . . . . .	1074	Macro interface changed . . . . .	83
1993-11-21 ltfiles.dtx LaTeX2e		\newcommand: Macro reimplemented	
\@missingfileerror: Stop infinite		and extended . . . . .	82
looping on \@er@ext . . . . .	474	\renewcommand: Macro reimplemented	
1993-11-21 ltmiscen.dtx v0.9a		and extended . . . . .	85
\@verbatim: use \@verbatim@font		\renewenvironment: Macro	
instead of \tt . . . . .	846	reimplemented and extended . . . .	86
\verb: Use \@verbatim@font instead of		\two@digits: Macro added . . . . .	78
\tt. . . . .	851	1993-11-23 ltoutput.dtx v0.1a	
\@verbatim@font: Macro added . . . .	847	\paperheight: Register added . . .	1180
1993-11-22 ltclass.dtx v0.2f		\paperwidth: Register added . . .	1180
\@fileswithoptions: Made the		1993-11-23 ltoutput.dtx v0.1c	
default [] not		\@enlargepage: Command added .	1244
[\@unknownversion] . . . . .	1075	\@kludgeins: Insert added . . . . .	1243
\@ifl@ter: Added //00 so parsing		\@makecol: Command changed . . .	1195
never produces a runaway		\@specialoutput: Command	
argument. . . . .	1060	changed . . . . .	1189
General: \@unknownversion		\enlargethispage*: Commands	
removed . . . . .	1050	added . . . . .	1243
\load@onefilewithoptions: Made the		1993-11-24 ltfntcmd.dtx v2.1a	
initial version [] not		\maybe@ic: Use \t@st@ic . . . . .	761
[\@unknownversion] . . . . .	1077	\t@st@ic: Macro added . . . . .	762
1993-11-22 ltdefs.dtx LaTeX2e		1993-11-24 ltssini.dtx v2.1a	
\@minus: Macro added . . . . .	79	General: Removed \xpt stuff . . . .	727
\@plus: Macro added . . . . .	79	1993-11-24 ltlogos.dtx LaTeX2e	
\@checkcommand: Macro added . . . . .	87	\LaTeX: Macro changed . . . . .	453
\@providecommand: Macro added . . . .	87	1993-11-28 ltclass.dtx v0.2h	
1993-11-22 lterror.dtx LaTeX2e		\@twoclasseserror: Macro added	1086
\@c@errorcontextlines: Macro added	406	General: Assorted commands now in	
1993-11-22 ltfiles.dtx LaTeX2e		the kernel removed. . . . .	1054
\@listfiles: Removed checking for		Directory syntax checking moved to	
\@unknownversion . . . . .	476	dircheck.dtx . . . . .	1054
1993-11-22 ltlength.dtx LaTeX2e		Primitive filenames now terminated	
\@settodim: Macro added . . . . .	536	by space not \relax. . . . .	1054
\@settopoint: Macro added . . . . .	537	\@endfilecontents: Don't globally	
\@settodepth: Macro added . . . . .	536	allocate a write stream (always use	
\@settoheight: Macro added . . . . .	536	15) . . . . .	1086
1993-11-22 ltlogos.dtx LaTeX2e		1993-11-28 ltfiles.dtx LaTeX2e	
\LaTeXe: Macro added . . . . .	453	\@missingfileerror: Use filename	
1993-11-23 ltclass.dtx v0.2g		parser from dircheck . . . . .	474
\@use@option: Name changed from		1993-11-29 ltoutput.dtx v1.0b	
\@executeoption . . . . .	1070	\@makecol: \@makespecialcolbox	
General: Various macros now moved		added . . . . .	1195
to latex.tex. . . . .	1054	1993-11-29 ltplain.dtx LaTeX2e	
Warnings and errors now directly		General: All accents in decimals;	
coded. . . . .	1054	suggested by Paul Taylor . . . . .	30
1993-11-23 ltdefs.dtx LaTeX2e		1993-11-30 ltoutput.dtx v1.0c	
\@argdef: Macro added . . . . .	82	\@fl@tracemessage: Commands	
\@ifundefined: Redefined to remove a		added . . . . .	1246
trailing \fi . . . . .	106		

1993-12-01 fontdef.dtx v2.1a		1993-12-04 ltfiles.dtx v0.9b	
General: Update for LaTeX2e . . . . .	732	\@iinput: Macro reimplemented . . .	473
1993-12-01 ltoutput.dtx v1.0e		\@input: Macro reimplemented . . .	473
\@reinserts: Command added . . .	1207	\IfFileExists@: Macro added . . . .	469
1993-12-03 ltboxes.dtx v0.1a		\input: Macro reimplemented . . . .	472
\@argrsbox: macro removed . . . . .	906	1993-12-05 ltfloat.dtx LaTeX2e	
\@begin@tempboxa: macro added . .	891	\@dblfloatplacement: Command	
\@end@tempboxa: macro added . . . .	891	changed . . . . .	993
\@iirsbox: redefined to support		\@xfloat: Command changed . . . .	987
\height . . . . .	906	1993-12-05 ltoutput.dtx v1.0f	
\@imakebox: macro modified . . . . .	892	\@addtobot: Command changed . .	1220
\@irsbox: redefined to support		\@addtocurcol: Command changed	1222
\height . . . . .	906	\@addtodblcol: Command changed	1237
\@isavebox: color support . . . . .	895	\@addtonextcol: Command changed	1232
extra group . . . . .	895	\@addtotoporbot: Command	
\@isavepicbox: extra group . . . . .	895	changed . . . . .	1221
\@makebox: default changed from x to		\@boxfpsbit: Command added . .	1250
c . . . . .	891	\@flcheckspace: Command added	1252
\@makepicbox: macro modified . . . .	892	\@flsetnum: Command added . . .	1251
\@savebox: default c not x . . . . .	895	\@flsettextmin: Command added	1251
\bm@b: macros added . . . . .	891	\@flstop: Commands added . . . .	1247
\endlrbox: macro added . . . . .	896	\@flupdates: Command added . .	1254
\fbbox: extra group . . . . .	896	\@fpsadddefault: Command added	1248
\lrbox: color support . . . . .	895	\@getfpsbit: Command added . .	1249
macro added . . . . .	895	\@opcol: Command changed . . . .	1194
\makebox: modified . . . . .	890	Hook added . . . . .	1194
\mbox: extra group . . . . .	891	\@outputpage: Command changed	1208
\minipage: Redefined to support extra		\@resetfps: Command added . .	1250
optional arguments . . . . .	902	\@setfloattypecounts: Command	
\newsavebox: Pass the whole of arg 1		added . . . . .	1249
to \@ifdefinable . . . . .	894	\@setfpsbit: Command added . .	1250
\parbox: Redefined to support extra		\@shipoutsetup: Command added	1208
optional arguments . . . . .	899	\@startcolumn: Command changed	1216
\raisebox: redefined to support		\@startdblcolumn: Command	
\height . . . . .	905	changed . . . . .	1216
\sbox: color support . . . . .	895	\@testfp: Command added . . . .	1250
extra group . . . . .	895	\@textfloatsheight: Commands	
\set@color: color support . . . . .	893	added . . . . .	1248
macro added . . . . .	893	\@topnewpage: Commands changed	1184
1993-12-03 ltclass.dtx v0.2i		\@tryfcolumn: Command changed	1217
\@cls@pkg: Name changed to avoid		\@writesetup: \@startpagehook	
clash with output routine. . . . .	1085	added . . . . .	1208
General: \@onlypreamble: Many		\output: Command changed . . . .	1189
commands declared. . . . .	1054	1993-12-06 ltclass.dtx v0.2k	
Removed obsolete		\ExecuteOptions: Preserve	
\@documentclass . . . . .	1054	\CurrentOption. . . . .	1071
1993-12-03 lterror.dtx v1.0b		1993-12-06 ltoutput.dtx v1.0f	
\@latexerr: Set		\@specialoutput: Unboxing of 255	
\@errorcontextlines to -1 . . .	406	added to rescue writes . . . . .	1189
1993-12-03 ltffsini.dtx v2.1a		1993-12-06 ltoutput.dtx v1.0g	
General: update for LaTeX2e . . . . .	702	\@topnewpage: \@floatplacement	
1993-12-04 ltfilehook.dtx v0.9b		placement bug fixed . . . . .	1184
\unqu@tefilef@und: Macro added	1125	1993-12-07 ltclass.dtx v0.2l	
		\ProvidesFile: Macro added . . . .	1066

1993-12-07 ltclass.dtx v0.2m		<code>\fix@penalty</code> : Macro added . . . . .	762
<code>\load@onefilewithoptions</code> : Reset		<code>\maybe@ic</code> : Macro name changed . .	761
<code>\CurrentOption</code> . . . . .	1077	<code>\maybe@ic@</code> : Macro and name	
1993-12-07 ltoutenc.dtx 1.1		changed . . . . .	761
General: Protected all special		<code>\sw@slant</code> : Macro changed . . . . .	762
characters with <code>\string</code> . . . . .	481	<code>\textup</code> : Macros changed . . . . .	759
1993-12-07 ltoutenc.dtx v1.1		1993-12-11 ltmath.dtx v0.9g	
General: Made all character numbers		General: Added a group around the	
decimal. . . . .	478	first argument of <code>\frac</code> to prevent	
Removed a lot of equal signs and		changes (for example font changes)	
the like. . . . .	478	from modifying the contents of the	
1993-12-08 ltboxes.dtx v0.1b		second argument. . . . .	864
<code>\@begin@tempboxa</code> : Extra braces for		1993-12-11 ltoutenc.dtx v1.2a	
color support (braces removed		General: Corrected for <code>tlenc</code> , <code>math</code> . .	478
from other macros) . . . . .	891	1993-12-11 ltsect.dtx LaTeX2e	
<code>\@irsbox</code> : fix typo . . . . .	906	<code>\author</code> : Added default . . . . .	969
<code>\@parboxto</code> : <code>\endgraf</code> added due to		<code>\title</code> : Added default . . . . .	969
extra group in <code>\@begin@tempboxa</code>	899	1993-12-11 ltxref.dtx LaTeX2e	
<code>\lrbox</code> : move <code>\@endpfalse</code> out of the		<code>\setref</code> : Macro added . . . . .	808
inner group . . . . .	895	<code>\pageref</code> : Macro reimplemented . . .	808
1993-12-08 ltfntcmd.dtx v2.1b		<code>\ref</code> : Macro reimplemented . . . . .	808
General: Macros <code>\rm</code> , <code>\bf</code> and <code>\sf</code>		1993-12-12 ltoutput.dtx v1.0h	
moved to <code>classes.dtx</code> . . . . .	764	<code>\cflb</code> : <code>boxmaxdepth</code> setting moved	1214
1993-12-08 ltlists.dtx LaTeX2e		defs changed to <code>lets</code> . . . . .	1214
<code>\@item</code> : use <code>\sbox</code> to support colour	885	<code>\cflt</code> : name changed . . . . .	1214
1993-12-08 ltspace.dtx LaTeX2e		<code>\doclearpage</code> : defs changed to <code>lets</code>	1194
<code>\@bsphack</code> : Command reimplemented	440	<code>\@makecol</code> : defs changed to <code>lets</code> . .	1195
Command reimplemented; late		<code>\@resetfps</code> : Warnings added:	
birthday present for Chris . . . .	440	minimal . . . . .	1250
<code>\@vbsphack</code> : Command added . . . .	443	<code>\@startdblcolumn</code> : defs changed to	
1993-12-09 ltboxes.dtx v0.1c		<code>lets</code> . . . . .	1216, 1217
<code>\@irsbox</code> : fix another typo . . . . .	906	<code>\@topnewpage</code> : braces removed . . .	1184
1993-12-09 ltclass.dtx v0.2n		<code>\@tryfcolumn</code> : defs changed to <code>lets</code>	1217
<code>\documentstyle</code> : input 209		<code>\fl@tracemessage</code> : Commands	
compatibility file. . . . .	1072	changed . . . . .	1246
1993-12-09 ltfiles.dtx v0.9e		1993-12-13 ltclass.dtx v0.2o	
<code>\document</code> : Hook added . . . . .	456	General: Removed setting	
1993-12-09 ltmiscen.dtx v0.9e		<code>\errorcontextlines</code> (now in	
<code>\enddocument</code> : Hook added . . . . .	829	<code>latex.tex</code> ) . . . . .	1054
1993-12-10 ltoutenc.dtx v1.2		<code>\documentstyle</code> : compatibility file	
General: Added source code for		now <code>latex209.sty</code> . . . . .	1072
<code>tlenc.sty</code> . . . . .	478	<code>\usepackage</code> : Fixed error handling	1073
1993-12-11 ltfntcmd.dtx v3.0a		1993-12-13 ltdirchk.dtx v0.2a	
General: Complete reworking of all		General: on the ‘docstrip’ pass, do not	
text commands, using just one		check <code>openin</code> path . . . . .	10
creator function . . . . .	756	<code>\IfFileExists</code> : Removed interactive	
italic correction now put in front of		prompting for current directory	
penalty before glue . . . . .	756	syntax . . . . .	10
newcommands replaced by defs . .	756	<code>\strip@prefix</code> : modified, name	
newfontswitch command corrected		changed from <code>\stripmeaning</code> . . .	5
and changed . . . . .	756	1993-12-13 ltlists.dtx latex2e	
<code>\DeclareTextFontCommand</code> : Macro		<code>\trivlist</code> : Initialised <code>\@itemlabel</code>	880
changed . . . . .	758	1993-12-13 ltmiscen.dtx v0.9h	
<code>\emph</code> : Macro changed . . . . .	759	<code>\@noligs</code> : Readded <code>\@noligs</code> . . . .	852

- `\@verbatim`: Readded `\@noligs` ... 846
- Removed optional argument of `\item` ... 846
- `center`: Removed optional argument of `\item` ... 843
- `flushleft`: Removed optional argument of `\item` ... 844
- `flushright`: Removed optional argument of `\item` ... 845
- 1993-12-13 ltoutenc.dtx v1.2b
  - General: Corrected file name in driver code. ... 478
- 1993-12-13 lttab.dtx latex2e
  - `\tabbing`: Removed optional argument of `\item` ... 915
- 1993-12-14 ltoutput.dtx v1.0i
  - General: Section added to declare all parameters ... 1259
- 1993-12-15 ltboxes.dtx v0.1d
  - `\@iminipage`: Changed default from ‘c’ to ‘s’ ... 902
  - `\@iparbox`: Changed default from ‘c’ to ‘s’ ... 899
  - `\minipage`: Changed default from ‘c’ to ‘s’ ... 902
  - extra space removed. ... 902
  - `\parbox`: Changed default from ‘c’ to ‘s’ ... 899
- 1993-12-15 ltclass.dtx v0.2p
  - General: Removed extra ‘s’ from `\@warnings` ... 1054
- 1993-12-16 ltlogos.dtx LaTeX2e
  - `\LaTeXe`: Extended logo by DPC ... 453
- 1993-12-16 ltmath.dtx v0.9i
  - `\@eqnocr`: use `\refstepcounter` instead of shortcut ... 866
  - General: use `\refstepcounter` instead of shortcut ... 864
- 1993-12-16 ltmiscen.dtx v0.9i
  - General: `\literal` added ... 852
- 1993-12-16 ltpage.dtx LaTeX2e
  - `\mark`: Init `\mark` at begin document ... 1048
- 1993-12-16 ltspace.dtx LaTeX2e
  - `\@bsphack`: Corrected optimisation ... 440
- 1993-12-16 lttab.dtx latex2e
  - `\@xhline`: Measure from middle of vertical rules ... 930
- 1993-12-17 ltclass.dtx v0.2q
  - `\@documentclasshook`: Macro added ... 1055
  - `\@fileswithoptions`: Add `\@compatibility` hook ... 1075
  - `\documentstyle`: Match Alan’s new code. ... 1072
- 1993-12-17 ltoutenc.dtx 1.3
  - General: Added this section ... 482
  - Removed all the hackery for use in `\DeclareFontEncoding`, and redid everything using `\DeclareTextFoo`. ... 494, 497
  - Removed the catcode hackery, since the file is only read as a package in the preamble, and removed all the messages on the screen, which just confuse users. Replaced them by the appropriate `\ProvidesPackage` commands. Added XXXenc. ... 481
- 1993-12-17 ltoutenc.dtx v1.3
  - General: Added `\EncodingSpecificAccent`, `\EncodingSpecificAccentedLetter` and `\EncodingSpecificCommand`. ... 478
  - Made Rokicki’s encoding a proper encoding scheme rather than a variant of OT1. ... 478
- 1993-12-17 ltoutput.dtx v1.0j
  - `\@opcol`: Hook removed ... 1194
  - `\@specialoutput`: Page room test added ... 1189
  - `\@topnewpage`: check for vsize too small added ... 1184
  - Page room test added ... 1185
  - `\@writesetup`: —and then removed ... 1208
  - `\fl@tracemessage`: tracefloatvals made a document command ... 1246
- 1993-12-17 ltpage.dtx LaTeX2e
  - `\mark`: Removed init `\mark` at begin document, since it doesn’t work. ... 1048
  - `\rightmark`: Stopgap solution to mark `\leftmark` and `\rightmark` work without initializing mark until the problem is solved. ... 1048
- 1993-12-18 ltoutenc.dtx 1.3b
  - General: Fixed typos with `\ProvidesPackage` lines. Added the `\NeedsTeXFormat` line. Added the last argument to `\DeclareEncoding`. Moved the use of the encodings to after their declaration. ... 481
  - Replaced the missing last argument to `\DeclareFontEncoding`. ... 494, 497
- 1993-12-18 ltoutenc.dtx 1.3c
  - General: Rewrote for the new syntax of `\EncodingSpecific`. ... 494, 497
  - Split `\EncodingSpecificAccent` up into `\EncodingSpecific` and `\DeclareAccent`. ... 482

1993-12-18 ltoutenc.dtx v1.3a	1994-01-14 ltdirchk.dtx v0.2d
General: Replaced OT3 by XXX . . . 478	\IfFileExists: Close the texsys.aux
1993-12-18 ltoutenc.dtx v1.3b	output stream . . . . . 10
General: Corrected typos. . . . . 478	1994-01-15 ltfiles.dtx v0.9o
Replaced the missing last argument	\document: move \@preamblecmds
to \DeclareFontEncoding. . . . . 478	after document hook . . . . . 458
1993-12-18 ltoutenc.dtx v1.3c	1994-01-17 ltclass.dtx v0.2s
General: A new syntax, separating	\@fileswithoptions: Modify to
accent-definitions from	reduce parameter stack usage . . 1075
encoding-specific definitions, and	General: Added many more
allowing encoding-specific	\@onlypreamble commands . . . 1054
\chardef, \let, etc. . . . . 478	Wrapped long lines to column 72 1054
Rewrote for the new syntax of	\load@onefile@withoptions: Modify
\EncodingSpecific. . . . . 478	to reduce parameter stack usage 1081
1993-12-18 ltoutenc.dtx v1.3d	1994-01-17 ltfiles.dtx LaTeX2e
General: Some T1 stuff had drifted	\listfiles: New Version, adds 'tex'
into the OT1 file. . . . . 478	if needed, and lines up columns . 476
1993-12-18 ltpage.dtx LaTeX2e	1994-01-17 ltfsbas.dtx v2.1a
\sloppy: Added \emergencystretch 1049	General: New math font setup . . . . 538
1993-12-19 ltclass.dtx v0.2r	\curr@math@size: New math font
\endfilecontents: Different message	setup . . . . . 553
when ignoring a file . . . . . 1086	\everydisplay: New math font setup 552
1993-12-19 ltfntcmd.dtx v3.0b	\everymath: New math font setup . . 552
General: \@pdef command added . . 756	\frozen@everydisplay: New math
Added by ASAJ. . . . . 764	font setup . . . . . 553
Made \@newfontswitch produce an	\frozen@everymath: New math font
error if command already exists,	setup . . . . . 552, 553
and added \@renewfontswitch,	\math@version: New math font setup 551
ASAJ . . . . . 756	1994-01-17 ltfsini.dtx v2.1e
Other tidying . . . . . 756	\not@math@alphabet: Message
Some more tidying done . . . . . 756	changed . . . . . 725
Untidying added, so this is now a	1994-01-17 ltfsstrc.dtx v2.3a
TEMPORARY version. . . . . 756	General: New math font setup . . . . 638
Wording changes by CAR. . . . . 764	\check@mathfonts: New math font
\DeclareOldFontCommand: Corrected	setup . . . . . 648
and tidied . . . . . 763	\glb@currsize: New math font setup 646
\DeclareTextFontCommand: Corrected	\restglb@settings: New math font
and tidied . . . . . 758	setup . . . . . 649
1993-12-19 ltspace.dtx LaTeX2e	1994-01-18 ltbibl.dtx LaTeX2e
\@bsphack: There seem to be problems	\bibliography: Use \@input@ so
with selfmade birthday presents . 441	include files are listed. . . . . 1011
1993-12-20 ltdefs.dtx LaTeX2e	1994-01-18 ltclass.dtx v0.2t
\@reargdef: Kept old version of	\@ifclassloaded: Fix typo
\@reargdef, for array.sty . . . . . 85	\@pkgetension . . . . . 1059
1993-12-20 ltfiles.dtx v0.9m	1994-01-18 ltfilehook.dtx v0.9p
\@obsoletefile: Added this	\unqu@tefilef@und: New Definition 1125
command, removed	1994-01-18 ltfiles.dtx v0.9p
\@oldfilewarning . . . . . 475	\@iffileonpath: Macro added . . . . 471
1994-01-05 fontdef.dtx v2.1d	\@input: do not use a different
General: Removed nf prefix from file	definition for \input@path . . . . 473
names. . . . . 734	\@input@: Macro added . . . . . 474
1994-01-13 ltmath.dtx v0.9o	\IfFileExists@: New Definition . . 469
\@eqnocr: correcting 0.9i . . . . . 866	\includeonly: Use \@input@ so
General: correcting 0.9i . . . . . 864	include files are listed. . . . . 462

1994-01-18 ltffssini.dtx v2.1f	1994-01-25 ltffssbas.dtx v2.1b
<code>\not@math@alphabet</code> : Message corrected . . . . . 725	<code>\math@version</code> : Corrections for math setup . . . . . 552
1994-01-18 ltmiscen.dtx v0.9p	1994-01-25 ltmath.dtx LaTeX2e
<code>\@verbatim</code> : Add	<code>\bordermatrix</code> : Removed <code>\p@renwd</code> . 858
<code>\global\@inlabeledfalse</code> . . . . . 846	1994-01-26 ltfsstrc.dtx v2.3c
Only add <code>\penalty</code> if in hmode . . . . . 846	<code>\check@mathfonts</code> : Correct trace info placement . . . . . 648
1994-01-19 fontdef.dtx v2.1e	<code>\restglb@settings</code> : Correct trace info placement . . . . . 649
General: Added missing setting for symbols in bold version. . . . . 739	1994-01-27 ltfntcmd.dtx v3.1a
1994-01-19 ltdirchk.dtx v0.2e	<code>\nocorrlist</code> : Only <code>.</code> , used as default for cm fonts . . . . . 763
<code>\IfFileExists</code> : name changed from <code>\test</code> . . . . . 9	1994-01-29 ltclass.dtx v0.2v
<code>\input@path</code> : No longer check that an empty group is in the path . . . . . 10	<code>\@unprocessedoptions</code> : Macro added. . . . . 1085
<code>\strip@prefix</code> : name changed from <code>\strip@meaning</code> , to match NFSS. 5	<code>\load@onefile@withoptions</code> : All options raise error if no <code>\ProcessOptions</code> appears . . . . 1081
1994-01-19 ltmath.dtx v1.0n classes	1994-01-31 ltdefns.dtx v0.2w
<code>\mathindent</code> : Deferred setting of <code>\mathindent</code> . . . . . 868	<code>\g@addto@macro</code> : Use toks register to avoid ‘hash’ problems . . . . . 112
1994-01-20 ltdirchk.dtx v0.2f	1994-01-31 ltfiles.dtx v0.9t
General: <code>\@copytexsys</code> and the <code>texsys.new</code> file removed . . . . . 8	<code>\document</code> : set <code>\@normalsize</code> or <code>\normalsize</code> if necessary . . . . . 457
Modify all of <code>ltxcheck</code> . . . . . 13	1994-01-31 ltfntcmd.dtx v3.1b
<code>\IfFileExists</code> : <code>\@copytexsys</code> removed . . . . . 10	General: <code>\@normalsize</code> no longer defined . . . . . 756
1994-01-21 ltclass.dtx v0.2u	1994-02-01 ltpage.dtx LaTeX2e
<code>\documentstyle</code> : compatibility file now <code>latex209.def</code> . . . . . 1072	<code>\pagestyle</code> : (DPC) Modify to get nicer error message . . . . . 1045
1994-01-21 ltdirchk.dtx v0.2g	<code>\thispagestyle</code> : (DPC) Modify to get nicer error message . . . . . 1046
General: Improve documentation, reorganize <code>docstrip</code> module . . . . . 1	1994-02-02 ltclass.dtx v0.2x
<code>\filename@parse</code> : Minor changes, and add Mac version ( <code>:</code> ) . . . . . 11	<code>\load@onefile@withoptions</code> : Only run the hook and options check if the file was loaded. . . . . 1081
<code>\today</code> : Name changed from <code>\stamp</code> , to save memory . . . . . 9	1994-02-03 ltoutput.dtx v1.0k
1994-01-21 ltfloat.dtx LaTeX2e	<code>\@make@specialcolbox</code> : correct mistakes in the documentation . . 1198
<code>\xfloat</code> : Added missing percent characters. . . . . 987	1994-02-07 ltclass.dtx v0.2y
1994-01-21 ltmiscen.dtx v0.9s	<code>\@fileswithoptions</code> : Run <code>\@compatibility</code> on the first class to start (not the first to finish) 1075
<code>\verbatim@font</code> : Removed unnecessary category code hackery. . . . . 847	<code>\@ifclasswith</code> : Add extra <code>,s</code> so ‘two’ is not matched with ‘twocolumn’ 1061
1994-01-24 ltdirchk.dtx v0.2h	<code>\ProcessOptions*</code> : Add extra <code>,s</code> so ‘two’ is not matched with ‘twocolumn’ . . . . . 1069
<code>\IfFileExists</code> : Stop testing once <code>texsys.aux</code> has been found . . . . . 9	1994-02-07 ltffssbas.dtx v2.1c
1994-01-24 ltpage.dtx LaTeX2e	<code>\DeclareFontEncoding</code> : revert catcode settings earlier . . . . . 542
<code>\pagestyle</code> : (DPC) Complain if <code>pagestyle</code> is undefined. . . . . 1045	<code>\DeclareFontShape@</code> : revert catcode settings earlier . . . . . 539
1994-01-25 ltdirchk.dtx v0.2i	
General: Protect against looping on <code>\@input</code> and <code>\@end</code> . . . . . 3	

1994-02-08 ltoutput.dtx v1.0k		1994-03-04 ltvers.dtx v1.0a	
General: Documentation and tasks		General: Initial version, split from	
tidied. . . . .	1168	latex.dtx . . . . .	35
1994-02-10 ltclass.dtx v0.2z		1994-03-07 ltboxes.dtx v0.1a	
\@documentclasshook: Changed the		\@mpfootnotetext: Extra group for	
name from \@compatibility to		color . . . . .	903
\@documentclasshook, and added		1994-03-07 ltboxes.dtx v1.0a	
the check for whether		General: Unify format with other	
\@normalsize has been defined.		Kernel files . . . . .	890
ASAJ. . . . .	1055	1994-03-07 ltdefs.dtx v1.0a	
\@fileswithoptions: Renamed		\@italiccorr: Macro added . . . . .	79
\@compatibility to		1994-03-07 ltfiles.dtx v1.0a	
\@documentclasshook. ASAJ. .	1075	General: Initial version, split from	
1994-02-10 ltffsbas.dtx v2.1d		latex.dtx . . . . .	454
\addto@hook: Made \addto@hook		Long lines wrapped to 72 columns	454
long. . . . .	566	1994-03-07 ltfinal.dtx v0.1a	
1994-02-10 ltffscmp.dtx v2.1d		General: Add code from the old	
\scan@fontshape: scan away stuff		dump.dtx . . . . .	1300
after pt . . . . .	665	Initial version, split from latex.dtx	1284
1994-02-22 ltffsini.dtx v2.1g		move code here from lhyphen.dtx	1290
General: Correct error message . . . .	730	Remove oldcomments	
1994-02-24 ltffsbas.dtx v2.1e		environment . . . . .	1284
\DeclareFontShape: Separate		use \InputIfFileExists not	
restoration of catcodes for fd		\IfFileExists . . . . .	1290
cmds . . . . .	539	1994-03-07 ltfloat.dtx v1.0a	
\define@newfont: Separate		\@endfloatbox: (DPC) Extra group	
restoration of catcodes for fd		for colour . . . . .	992
cmds . . . . .	555	\@footnotetext: (DPC) Extra group	
\nffs@catcodes: Separate restoration		for colour . . . . .	1002
of catcodes for fd cmds . . . . .	555	\@xfloat: (DPC) Extra group for	
1994-02-25 ltdirchk.dtx v0.2j		colour . . . . .	988
General: Remove need for drv file . . . .	1	1994-03-07 lthyphen.dtx v0.1c	
1994-03-01 ltdirchk.dtx v0.2k		General: move the 2kernel code to	
General: Add unstripped module, so		ltfinal.dtx . . . . .	1282
that dircheck.dtx may be used		1994-03-07 ltlength.dtx v1.0a	
with initex . . . . .	1	\@settodim: (DPC) Extra group for	
1994-03-02 ltboxes.dtx v0.1e		colour . . . . .	536
General: Add 2kernel module . . . .	890	1994-03-07 ltlists.dtx v1.0a	
Remove need for drv file . . . . .	890	General: Initial version, split from	
1994-03-02 ltclass.dtx v0.3a		latex.dtx . . . . .	872
General: Remove need for driver file	1054	Long lines wrapped to 72 columns	872
1994-03-03 ltboxes.dtx v0.1f		1994-03-07 ltpage.dtx v1.0a	
\@irsbox: Replaced a missing \else	906	General: Initial version, split from	
1994-03-04 ltfloat.dtx v1.0a		ltherest.dtx . . . . .	1045
General: Initial version, split from		1994-03-07 ltpictur.dtx v0.1a	
latex.dtx . . . . .	983	General: Initial version, split from	
1994-03-04 ltsect.dtx v1.0a		latex.dtx . . . . .	933
General: Initial version, split from		Long lines wrapped to 72 columns	933
latex.dtx . . . . .	969	1994-03-07 ltsect.dtx v1.0a	
1994-03-04 lttab.dtx v1.0a		\@hangfrom: (DPC)Extra groups for	
General: Initial version, split from		colour . . . . .	976
latex.dtx . . . . .	908	1994-03-07 lttab.dtx v1.0a	
		General: Long lines wrapped to 72	
		columns . . . . .	908

1994-03-08 ltclass.dtx v0.3b	1994-03-13 ltfiles.dtx LaTeX2e
General: Modify driver code into ‘new style’ . . . . .	<code>\@addtofilelist</code> : Macro added . . . 475
1994-03-08 ltdirchk.dtx v1.0a	<code>\listfiles</code> : Reset <code>\@addtofilelist</code> at begin document . . . . . 477
General: Reorganize driver module into ‘new style’ . . . . .	1994-03-13 ltfssbas.dtx v2.1g
1994-03-08 ltplain.dtx v1.0a	General: add 2kernel module to omit repeated code . . . . . 538
General: Remove need for a driver file. 14	1994-03-13 ltfssdcl.dtx v2.1c
1994-03-10 ltfssbas.dtx v2.2f	General: add 2kernel module to omit repeated code . . . . . 669
<code>\math@egroup</code> : Changed	1994-03-14 ltboxes.dtx v1.0b
<code>\begin@group/\endgroup</code> to <code>\bgroup/\egroup</code> . . . . .	<code>\@isavebox</code> : Use <code>\color@setgroup</code> . . . . . 895
1994-03-11 ltfssdcl.dtx v2.1b	<code>\@isavepicbox</code> : Use <code>\color@setgroup</code> . . . . . 895
<code>\DeclareSymbolFontAlphabet@</code> : Added check against use of alphabet switch outside of math mode. . . . . 701	<code>\color@begin@group</code> : macro added for color support . . . . . 893
<code>\SetMathAlphabet@</code> : Changed parameter template in temporary macro to catch check add below. 689	<code>\color@end@group</code> : macro added for color support . . . . . 894
1994-03-12 ltclass.dtx v0.3c	<code>\lrbox</code> : Use <code>\color@setgroup</code> . . . . . 895
General: Change name from docclass to ltclass . . . . . 1054	<code>\sbox</code> : Use <code>\color@setgroup</code> . . . . . 895
<code>\ProvidesFile</code> : Add <code>\wlog</code> . . . . . 1066	1994-03-14 ltfloat.dtx v1.0c
<code>\ProvidesPackage</code> : Add <code>\wlog</code> . . . . . 1064	<code>\@xympar</code> : (DPC) Use <code>\color@begin@group</code> . . . . . 997
use <code>\@gtempa</code> . . . . . 1064	1994-03-14 ltfloat.dtx v1.0c
1994-03-12 ltdefs.dtx v1.0b	<code>\@endfloatbox</code> : (DPC) Use <code>\color@end@group</code> . . . . . 992
<code>\@reargdef</code> : New defn, in terms of <code>\@yargdef</code> . . . . . 85	<code>\@footnotetext</code> : (DPC) Use <code>\color@begin@group</code> , add <code>\endgraf</code> . . . . . 1002
<code>\@yargd@f</code> : Name changed from <code>\XXX@argdef</code> . . . . . 83	<code>\@savemarbox</code> : (DPC) Use <code>\color@begin@group</code> . . . . . 996
1994-03-12 ltdirchk.dtx v1.0b	<code>\@xfloat</code> : (DPC) Use <code>\color@begin@group</code> . . . . . 988
General: Change name from dircheck.dtx . . . . . 1	1994-03-15 ltfiles.dtx LaTeX2e
Minor edits to the typeouts in ltxcheck . . . . . 1	<code>\@missingfileerror</code> : Quit on x or X just like a real error . . . . . 474
1994-03-12 ltfloat.dtx v1.0b	1994-03-15 ltfntcmd.dtx v3.2a
<code>\@savemarbox</code> : (DPC) Extra group for colour . . . . . 996	General: Adapted to mass formatting 756
<code>\@xympar</code> : (DPC) Extra bgroup for colour . . . . . 997	Changed <code>\/</code> to <code>\@@italiccorr</code> . . . 756
1994-03-12 ltplain.dtx v1.0b	Removed <code>\@renewfontswitch</code> . . . 756
General: Name changed from lplain. The end of an era . . . . . 14	Removed defs of short-forms and all sizes except <code>\normalize</code> . . . . . 756
1994-03-12 ltplain.dtx v1.0e	1994-03-15 ltoutput.dtx v1.0l
General: Replaced remaining width, height, depth by L <sup>A</sup> T <sub>E</sub> X macro names to save tokens. . . . . 14	<code>\@addtocurcol</code> : Changed <code>\advspace</code> to <code>\vskip</code> . . . . . 1224, 1230
1994-03-13 ltcntrl.dtx v1.0c	<code>\@combinedblfloats</code> : Removed boxmaxdepth setting. . . . . 1215
<code>\@tfor</code> : (DPC) Add <code>\@tf@r</code> so a single group is correctly treated. . . . . 399	<code>\@make@normalcolbox</code> : Removed boxmaxdepth setting. . . . . 1196
1994-03-13 ltfilehook.dtx v0.3b	<code>\@outputbox@append</code> : <code>\maxdepth</code> changed to <code>\@maxdepth</code> . . . . . 1200
<code>\unqu@tefile@und</code> : Use new cmd <code>\@addtofilelist</code> . . . . . 1125	<code>\@topnewpage</code> : Corrected and amended warning message . . . . . 1185

Warning added: it should be improved . . . . .	1185	1994-03-28 ltthm.dtx v1.0a	General: Initial version, split from latex.dtx . . . . .	965
General: Added some warnings when page gets full of top floats. . . .	1168	1994-03-29 ltcounts.dtx v1.0c	General: Create file from parts of ltmiscen and ltherest. . . . .	525
Driver added and further tidying. . . . .	1168	1994-03-29 ltlength.dtx v1.0c	General: Create file ltcntlen from parts of ltmiscen and ltherest. . . . .	536
Removed duplicated code and corrected docstrip options. . . . .	1168	1994-03-29 ltmiscen.dtx v1.0d	General: Remove counter macros to ltcntlen . . . . .	828
Some boxmaxdepth settings removed. . . . .	1168	1994-03-29 ltpageno.dtx v1.0c	General: Create file ltcntlen from parts of ltmiscen and ltherest. . . . .	805
1994-03-16 ltclass.dtx v0.3f		1994-03-29 ltxref.dtx v1.0c	General: Create file ltcntlen from parts of ltmiscen and ltherest. . . . .	806
General: Add pkgindoc package . . . .	1103	1994-03-31 ltbibl.dtx v1.0a	General: Initial version of ltidxbib.dtx, split from ltherest.dtx . . . . .	1009
1994-03-16 ltfiles.dtx LaTeX2e		1994-03-31 ltidxglo.dtx v1.0a	General: Initial version of ltidxbib.dtx, split from ltherest.dtx . . . . .	1006
\listfiles: Move this code directly into \document . . . . .	477	1994-04-09 ltcounts.dtx v1.0d	\@newctr: \@nocnterr now has counter name argument . . . . .	527
1994-03-16 ltfiles.dtx v1.0c			\addtocounter: \@nocnterr now has counter name argument . . . . .	526
\document: (DPC) directly add file list settings . . . . .	458		\setcounter: \@nocnterr now has counter name argument . . . . .	526
1994-03-16 ltmiscen.dtx v1.0b			\stepcounter: Use \addtocounter to have name checked . . . . .	527
\@verbatim: Remove			1994-04-09 ltthm.dtx v1.0b	
\global\@inlabelfalse again. . . . .	846		\@othm: Use standard counter error message (FMi) . . . . .	967
1994-03-28 ltalloc.dtx v1.0d			1994-04-11 ltclass.dtx v0.3g	
General: Redefinition of ‘new’ allocations removed. . . . .	394		\endfilecontents: Add star form, don’t write \endinput at the end of the file. . . . .	1086
1994-03-28 ltdirchk.dtx v1.0d			\ProvidesFile: Protect against weird catcodes. . . . .	1066
General: Improve documentation . . . .	1		1994-04-11 ltfssbas.dtx v2.1h	
1994-03-28 lterror.dtx v1.0d			General: Added \defaultscriptratio and \defaultscriptscriptratio. ASAJ. . . . .	538
\@invalidchar: (DPC) Comment out (use catcode15 instead) . . . . .	410		\defaultscriptratio: Macro added . . . . .	564
General: Remove test for			\defaultscriptscriptratio: Macro added . . . . .	564
\inputlineno undefined. . . . .	406		1994-04-12 ltboxes.dtx v1.0c	
1994-03-28 ltfiles.dtx v1.0d			General: Remove \@acci, now defined in ltplain.dtx . . . . .	900
\document: (DPC) Use \normalsize not \@normalsize . . . . .	457		Remove \@dischyph, now defined in ltinit.dtx . . . . .	900
(DPC) remove				
\@normalsize check . . . . .	457			
1994-03-28 ltfloat.dtx v1.0b				
\@caption: Use \normalsize not \@normalsize . . . . .	986			
General: Split further from ltherest.dtx . . . . .	983			
1994-03-28 ltlists.dtx v1.0b				
General: Improve documentation . . . .	871			
1994-03-28 ltmiscen.dtx v1.0c				
General: Improve Documentation . . . .	828			
1994-03-28 ltplain.dtx v1.0c				
\newlanguage: Remove some \outer declarations. . . . .	17			
1994-03-28 ltsect.dtx v1.0b				
General: Split further from ltherest.dtx . . . . .	969			
1994-03-28 lttab.dtx v1.0b				
General: Improve documentation . . . .	908			

1994-04-12 ltdefs.dtx v1.0g	1994-04-18 ltfsstrc.dtx v2.3d
\@dischyph: Define \@dischyph, was previously in ltboxes.dtx . . . . .	General: Changed to new error/warning scheme . . . . .
1994-04-12 ltplain.dtx v1.0d	\font@submax: Changed dimen to macro . . . . .
General: Define \@acci . . . . .	\fontsubfuzz: Changed dimen to macro . . . . .
1994-04-12 ltvers.dtx v1.0b	\subst@size: \font@submax and \fontsubfuzz now macros . . . . .
General: Have version info generated automatically. . . . .	1994-04-19 ltpage.dtx v1.0b
1994-04-14 ltftcmd.dtx v3.2b	General: Improve documentation . . . . .
General: Macros renamed to non-private forms, JB . . . . .	1994-04-20 ltftcmd.dtx v3.3a
\DeclareOldFontCommand: Renamed from \@newfontswitch . . . . .	General: Documentation up-dated . . . . .
1994-04-15 ltboxes.dtx v1.0d	New implementation of \nocorr . . . . .
\@isavebox: Added missing percent character. . . . .	\check@nocorr@: Macros added . . . . .
1994-04-17 ltcounts.dtx v1.0e	\maybe@ic@: \nocorr etc removed from list of tokens to check, leaving only punctuation characters . . . . .
\@newctr: Use \@nocounterr instead of \@nocnterr . . . . .	1994-04-20 ltmiscen.dtx v1.0e
\addtocounter: Use \@nocounterr instead of \@nocnterr . . . . .	\@enddocument@kernel@warnings: Changed logic for producing warning messages . . . . .
\setcounter: Use \@nocounterr instead of \@nocnterr . . . . .	1994-04-21 ltboxes.dtx v1.0e
1994-04-17 lterror.dtx v1.0h	\@iiminipage: Extra \bgroup for color . . . . .
\@nocounterr: New name for error message, old error message (without arg) kept . . . . .	\@mpfootnotetext: Extra \endgraf for color . . . . .
1994-04-17 ltthm.dtx v1.0c	\endminipage: Extra \egroup for color . . . . .
\@othm: Use new std counter error message (FMi) . . . . .	1994-04-21 ltfinal.dtx v0.1c
\@thm: Use new std counter error message (FMi) . . . . .	General: Added comments, set the catcodes of 128–255. . . . .
1994-04-18 ltfinal.dtx v0.1b	1994-04-22 ltssini.dtx v2.1g
General: Initialise \textheight, \textwidth and page style . . . . .	\not@math@alphabet: Message changed again . . . . .
1994-04-18 ltfloat.dtx v1.0d	1994-04-23 ltfinal.dtx v0.1d
\@footnotetext: (DPC) Remove Colour support . . . . .	General: Check that \font@submax is still zero . . . . .
\@savemarbox: (DPC) Remove Colour support . . . . .	1994-04-24 ltoutput.dtx v1.0m
1994-04-18 ltssbas.dtx v2.1i	\@resetfhps: Number 2 changed to \tw@ . . . . .
General: Macro \no@alphabet@help removed again . . . . .	Warning changed . . . . .
\calculate@math@sizes: Changed message to log only . . . . .	\@specialoutput: Message changed to give more info and ‘top’ removed . . . . .
\no@alphabet@error: Use std LaTeX error macro . . . . .	\@topnewpage: Message changed to give more info . . . . .
1994-04-18 ltssdcl.dtx ???	Warning message removed as it will be generated later . . . . .
\DeclareMathAlphabet: Pass correct arg (2 not 3) . . . . .	General: Changed \@normalsize to \normalsize. . . . .
1994-04-18 ltssdcl.dtx v2.1d	Corrected unverbbed commands in documentation. . . . .
General: Removed surplus \no@alphabet@error (see fam.dtx) . . . . .	Removed some long lines and other aesthetic changes. . . . .

Warning messages changed/corrected. . . . .	1168	1994-04-30 ltfontcmd.dtx v3.3b General: Documentation up-dated and tidied . . . . .	756
1994-04-24 ltpictur.dtx v0.1b General: Removed surplus spaces after <code>\hbox to</code> in several cases . . . . .	933	Prefix frag@ changed to frag in <code>\@protecteddef</code> . . . . .	756
1994-04-25 ltclass.dtx v0.3h General: Removed spurious extra 's at the end of error messages . . . . .	1054	Title changed . . . . .	756
1994-04-25 ltfloat.dtx v1.0e <code>\@largefloatcheck</code> : Changed warning message to give more info . . . . .	992	Warning changed to info message in <code>\@protecteddef</code> . . . . .	756
Command added . . . . .	992	1994-04-30 ltoutput.dtx v1.0n <code>\@activechar@info</code> : <code>\@activechar@warning</code> changed to <code>\@activechar@info</code> . . . . .	1207
General: Changed warning messages . . . . .	983	<code>\@combinedblfloats</code> : Removed rule in topnewpage case . . . . .	1215
Removed obsolete tracing code . . . . .	983	<code>\@emptycol</code> : Empty column action added: <code>\@emptycol</code> . . . . .	1184
1994-04-27 ltfssstrc.dtx v2.3e General: Corrected item that was forgotten in last change. . . . .	638	<code>\@flsetnum</code> : Rogue space removed . . . . .	1251
1994-04-28 lterror.dtx v1.0j <code>\@inmatherr</code> : Macro added . . . . .	410	<code>\@specialoutput</code> : Cut-off point changed to <code>2\baselineskip</code> . . . . .	1189
1994-04-28 lterror.dtx v1.1c <code>\@inmatherr</code> : Replaced <code>\noexpand</code> with <code>\protect</code> . . . . .	410	Empty column action added: <code>\@emptycol</code> . . . . .	1189
1994-04-28 ltssdcl.dtx v2.1e General: Removed all <code>\uppercase</code> in hex num parsing macros . . . . .	669	Extra empty column added for twocolumn case . . . . .	1189
1994-04-28 ltlists.dtx v1.0c <code>\item</code> : Replaced <code>\@ltxnomath</code> by <code>\@inmatherr</code> . . . . .	883	Extra empty column added for twocolumn case (wrong, see below) . . . . .	1189
1994-04-28 ltpictur.dtx v0.1c <code>\@multiput</code> : (DPC) Macro added . . . . .	937	<code>\@topnewpage</code> : Added setting of <code>\col@number</code> . . . . .	1184
General: bezier curves added . . . . .	960	Cut-off point changed to <code>3\baselineskip</code> . . . . .	1185
<code>\multiput</code> : (DPC) Ignore spaces between )( . . . . .	936	Empty column action added: <code>\@emptycol</code> . . . . .	1185
<code>\picture</code> : (DPC) Ignore spaces before ( . . . . .	935	Message changed for Frank . . . . .	1185
1994-04-28 ltplain.dtx v1.0g General: Turn off overfull box tracing in log . . . . .	23	General: <code>\@activechar@warning</code> changed to an info message. . . . .	1168
1994-04-29 ltclass.dtx v1.0a General: Change version number to 1 (no other change) . . . . .	1054	Added <code>\col@number</code> . . . . .	1168
1994-04-29 ltmiscen.dtx v1.0f <code>\@verbatim</code> : <code>\leavevmode</code> added . . . . .	846	Documentation tidied. . . . .	1168
Change to <code>\everypar</code> added . . . . .	846	Empty column action added. . . . .	1168
1994-04-29 ltoutenc.dtx 1.4a General: Removed <code>\EncodingSpecific</code> . Renamed all the commands. Added <code>\DeclareTextGlyph</code> and <code>\UndeclareTextCommand</code> . . . . .	482	Fixed bug from <code>\dblfigrule</code> with <code>\@topnewpage</code> . . . . .	1168
Removed Rokicki's OT1 variant encoding. Moved the driver to the top. . . . .	481	Full of floats action improved. . . . .	1168
		<code>\col@number</code> : Added <code>\col@number</code> . . . . .	1180
		<code>\onecolumn</code> : Added setting of <code>\col@number</code> . . . . .	1182
		1994-05-01 lterror.dtx v1.0k <code>\@latexerr</code> : (CAR) Added draft <code>\@latexinfo</code> . . . . .	406
		1994-05-01 ltoutenc.dtx 1.4a General: Added the <code>\a</code> command. . . . .	491
		Added the <code>\SaveAtCatcode</code> and <code>\RestoreAtCatcode</code> commands. . . . .	494
		Removed the uc/lc table settings, since the T1 uc/lc table is now the default. . . . .	502

Rewrote for the new syntax. . . . .	494, 497	<code>\end@float</code> : (CAR) Added	
1994-05-01 ltoutenc.dtx v1.4a		<code>\@largefloatcheck</code> . . . . .	990
General: Removed Rokicki's		1994-05-03 ltfsdcl.dtx v2.1f	
encoding. . . . .	478	General: Renamed	
Renamed the commands, removed		<code>\@@DeclareMathDelimiter</code> to	
the <code>\EncodingSpecific</code> command.		<code>\@DeclareMathDelimiter</code> . . . . .	669
Turned all slots into decimal.		1994-05-03 ltlists.dtx v1.0d	
Added <code>\a</code> . . . . .	478	<code>\@item</code> : <code>\hskip</code> changed to <code>\kern</code> . .	884
1994-05-02 ltcntrl.dtx v1.0l		<code>\item</code> : Removed superfluous braces	883
<code>\@break@tfor</code> : Macro added (from		1994-05-03 ltmiscen.dtx v1.0h	
ltfiles.dtx) . . . . .	399	<code>\@centercr</code> : <code>\@badcrerr</code> replaced by	
1994-05-02 ltdefns.dtx v1.1f		<code>\@nolnerr</code> . . . . .	842
<code>\renewcommand</code> : Removed surplus		1994-05-03 lttab.dtx v1.0d	
<code>\space</code> in error . . . . .	85	<code>\@endpbox</code> : Use <code>\@finalstrut</code> based	
<code>\renewenvironment</code> : Removed surplus		on depth of <code>\@arstrutbox</code> . . . . .	931
<code>\space</code> in error . . . . .	86	1994-05-04 ltclass.dtx v1.0b	
1994-05-02 ltfiles.dtx v1.0f		<code>\NeedsTeXFormat</code> : Changed wording of	
<code>\@iffilenamepath</code> : <code>\@break@loop</code>		the warning . . . . .	1074
renamed to <code>\@break@tfor</code> . . . . .	471	1994-05-04 lterror.dtx v1.0m	
<code>\@obsoletefile</code> : Make		<code>\@badcrerr</code> : Error message removed	409
<code>\@onlypreamble</code> . . . . .	475	1994-05-05 ltbibl.dtx v1.0c	
1994-05-02 ltfinal.dtx v0.1e		<code>\@citex</code> : Set switch for warning and	
General: Added setting the 'letter'		end of run. . . . .	1011
catcodes. . . . .	1296	<code>\nocite</code> : Do not write page number in	
Added setting the 'other'		<code>\nocite</code> warning message. . . . .	1012
catcodes. . . . .	1296	Set switch for warning and end of	
Added setting the special		run. . . . .	1012
catcodes. . . . .	1296	1994-05-05 ltfinal.dtx v0.1g	
Made slot 127 illegal . . . . .	1296	General: Added empty errhelp. . . .	1284
Set all the catcodes . . . . .	1284	<code>\errhelp</code> : Set error help empty. . .	1302
1994-05-02 ltfinal.dtx v0.1f		1994-05-05 ltfntcmd.dtx v3.3c	
General: Set the catcode of		<code>\@math@egroup</code> : Corrected	
control-J. . . . .	1296	<code>\@fontswitch</code> and added saved	
1994-05-02 ltmiscen.dtx v1.0g		versions . . . . .	763
General: Changed 91 to 1991 and		General: Corrected <code>\@fontswitch</code> . .	756
moved some bits . . . . .	828	1994-05-05 ltmiscen.dtx v1.0i	
1994-05-02 ltoutput.dtx v1.0o		General: Removed braces from	
<code>\@resethfps</code> : Code shortened . . . .	1250	<code>\ifnextchar</code> and <code>\ifstar</code> arguments .	828
General: Code of <code>\@resethfps</code>		1994-05-07 lttab.dtx v1.0c	
shortened. . . . .	1168	<code>\@maxtab</code> : Changed <code>\@firsttab</code> to	
1994-05-03 ltbibl.dtx v1.0b		<code>\chardef</code> . . . . .	912
<code>\nocite</code> : Make <code>\nocite</code> issue a		Changed <code>\@maxtab</code> to <code>\chardef</code> . .	912
warning for an undefined citation		General: Removed definition of <code>\+</code> .	908
key. . . . .	1012	Removed surplus braces from	
1994-05-03 ltfinal.dtx v0.1f		<code>\@ifnextchar</code> constructs . . . . .	908
General: Set the catcode of control-J		1994-05-08 ltfntcmd.dtx v3.3d	
to be 'other', for use in messages.	1284	General: Removed	
1994-05-03 ltfloat.dtx v1.0f		<code>\@undefinedfonterror</code> . . . . .	756
General: (CAR) Added		<code>\normalsize</code> : Removed	
<code>\@largefloatcheck</code> . . . . .	983	<code>\@undefinedfonterror</code> . . . . .	764
Removed unnecessary braces from		1994-05-09 ltfntcmd.dtx v3.3f	
arguments of <code>\@ifnextchar</code> . . . .	983	General: Replaced all <code>\next</code> by	
<code>\end@dblfloat</code> : <code>\@largefloatcheck</code>		<code>\@let@token</code> and undo change	
added . . . . .	991	3.3e, whatever that was. . . . .	756

1994-05-10 ltdefs.dtx v1.0n			
General: (ASAJ) Added		<code>\@changed@cmd</code> and	
<code>\DeclareProtectedCommand</code> . . . . .	78	<code>\DeclareProtectedCommand</code> . . . . .	482
Added <code>\DeclareProtectedCommand</code>	89	Renamed the commands again.	
Removed braces around		Made the encoding part of the	
<code>\@ifundefined</code> argument. ASAJ.	85	command syntax. Added the	
<code>\makeatother</code> : Added <code>\makeatletter</code>		<code>\DeclareTextCommand</code> interface.	
and <code>\makeatother</code> ASAJ. . . . .	110	Used	
1994-05-10 lterror.dtx v1.0n		<code>\DeclareProtectedCommand</code> . . . . .	478
<code>\@latexerr</code> : (ASAJ) Added extra		<code>\DeclareTextAccent</code> : Reimplemented	
blank lines to <code>\@latexerr</code> . . . . .	406	using <code>\DeclareTextCommand</code> . . . . .	485
1994-05-10 ltmiscen.dtx v1.0j		1994-05-11 ltspc.dtx v1.0o	
<code>\@sverb</code> : Slight change in error		<code>\hspace</code> : Use	
message text. . . . .	849	<code>\DeclareRobustCommand</code> . ASAJ.	451
1994-05-11 ltboxes.dtx v1.0f		1994-05-12 ltboxes.dtx v1.0g	
<code>\@begin@tempboxa</code> : Use new		<code>\@finalstrut</code> : macro added . . . . .	906
<code>\color@setgroup</code> concept. . . . .	891	<code>\fbox</code> : New definition, merged with	
<code>\@iiiminipage</code> : Use new		<code>\framebox</code> . . . . .	896
<code>\color@setgroup</code> concept. . . . .	902	<code>\framebox</code> : Merged <code>\fbox</code> and	
<code>\@mpfootnotetext</code> : Use new		<code>\framebox</code> . . . . .	897
<code>\color@setgroup</code> concept. . . . .	903	<code>\normalcolor</code> : macro added for color	
Use new <code>\normalcolor</code> and		support . . . . .	893
<code>\@finalstrut</code> . . . . .	903	1994-05-12 ltdefs.dtx v1.0p	
General: Superfluous braces removed		General: (ASAJ) Fixed a bug with	
from several commands . . . . .	890	<code>\relax</code> which was using <code>\@gobble</code>	
<code>\color@setgroup</code> : macro added for		before defining it. . . . .	78
color support . . . . .	893	Fixed a bug with <code>\relax</code> which	
<code>\endminipage</code> : Use new		was using <code>\@gobble</code> before defining	
<code>\color@setgroup</code> concept. . . . .	903	it. . . . .	89
1994-05-11 ltclass.dtx v1.0c		1994-05-12 ltfssbas.dtx v2.1j	
<code>\endfilecontents</code> : Add checks for		General: New <code>baselinestretch</code> concept	538
form feed and tab . . . . .	1086	Replaced hand-protected commands	
1994-05-11 ltdirchk.dtx v1.0e		by <code>\DeclareRobustCommand</code> defs	538
General: Add <code>\ProvidesFile</code> as used		<code>\f@linespread</code> : New macro . . . . .	550
in fd files. . . . .	4	<code>\fontencoding</code> : Use	
1994-05-11 lterror.dtx v1.0o		<code>\DeclareRobustCommand</code> . . . . .	548
<code>\@latexerr</code> : (ASAJ) Removed one of		<code>\fontfamily</code> : Use	
the extra blank lines to		<code>\DeclareRobustCommand</code> . . . . .	549
<code>\@latexerr</code> . . . . .	406	<code>\fontseries</code> : Use	
1994-05-11 ltlogos.dtx v1.0o		<code>\DeclareRobustCommand</code> . . . . .	549
<code>\LaTeX</code> : Use		<code>\fontshape</code> : Use	
<code>\DeclareProtectedCommand</code> .		<code>\DeclareRobustCommand</code> . . . . .	549
ASAJ. . . . .	453	<code>\fontsize</code> : Redefined to use	
<code>\LaTeXe</code> : Use		<code>\set@fontsize</code> . . . . .	550
<code>\DeclareProtectedCommand</code> .		<code>\linespread</code> : New macro . . . . .	550
ASAJ. . . . .	453	<code>\mathversion</code> : Use	
1994-05-11 ltoutenc.dtx 1.5a		<code>\DeclareRobustCommand</code> . . . . .	551
General: Made T1 and OT1 generate		1994-05-12 ltfssdcl.dtx v2.1g	
packages rather than def files.		General: Allow <code>\relax</code> as undefined	
Renamed the ‘package’ module to		command . . . . .	669
‘teststy’. . . . .	481	Allow <code>\relax</code> ’ed cmds to be	
1994-05-11 ltoutenc.dtx v1.5a		declared . . . . .	669
General: Reimplemented		1994-05-12 ltfssini.dtx v2.1i	
<code>\DeclareTextCommand</code> using		General: Moved <code>\fontencoding</code> to	
		fam.dtx . . . . .	702

Moved <code>\fontfamily</code> to fam.dtx .	702	1994-05-13 ltfiles.dtx v1.0g	
Moved <code>\fontseries</code> to fam.dtx .	702	<code>\document</code> : Added execution of	
Moved <code>\fontshape</code> to fam.dtx .	702	<code>\every@size</code> . . . . .	457
Moved <code>\fontsize</code> to fam.dtx .	702	1994-05-13 ltfinal.dtx v0.1h	
Moved <code>\mathversion</code> to fam.dtx .	702	General: Added package <code>otlenc</code> , and	
Moved <code>\selectfont</code> to tracefnt.dtx	702	defined <code>\@acci</code> , <code>\@accii</code> and	
1994-05-12 ltfsstrc.dtx v2.3f		<code>\@acciii</code> . . . . .	1284
<code>\selectfont</code> : Use		1994-05-13 ltfinal.dtx v1.0h	
<code>\DeclareRobustCommand</code> . . . . .	642	General: Added output enc stuff .	1300
1994-05-12 ltoutenc.dtx 1.5a		1994-05-13 ltfloat.dtx v1.0g	
General: Removed the		<code>\@footnotetext</code> : (DPC) Add new	
<code>\SaveAtCatcode</code> and		style colour support:	
<code>\RestoreAtCatcode</code> commands. .	494	<code>\normalcolor</code> . . . . .	1002
Rewrote for the new syntax. .	494, 497	(DPC) Use <code>\@finalstrut</code> . . . .	1002
1994-05-12 ltoutput.dtx v1.0p		<code>\xfloat</code> : (DPC) Use <code>\normalcolor</code>	988
<code>\@writetsetup</code> : <code>\normalcoloradded</code>	1208	1994-05-13 ltfontcmd.dtx v3.3g	
General: <code>\normalcoloradded</code> in		General: Replaced <code>\@protecteddef</code> by	
various places (DPC). . . . .	1168	<code>\DeclareRobustCommand</code> . . . . .	756
1994-05-13 ltboxes.dtx v1.0h		1994-05-13 ltfsbas.dtx v2.1k	
<code>\@arrayparboxrestore</code> : New accent		General: Remove File identification	
system, use <code>\let</code> not <code>\def</code> . . . .	901	‘typeout’ . . . . .	538
1994-05-13 ltcounts.dtx v1.0f		1994-05-13 ltfsbas.dtx v2.1l	
General: Removed <code>\@lalph</code> . . . . .	532	<code>\DeclareFontEncoding</code> : Init encoding	
Removed <code>\@ialph</code> . . . . .	532	change command . . . . .	542
1994-05-13 ltdefns.dtx v1.0q		<code>\define@newfont</code> : Use <code>\@input@</code> for fd	
General: (ASAJ) Renamed		files . . . . .	555
<code>\DeclareProtectedCommand</code> to		1994-05-13 ltssdcl.dtx v2.1h	
<code>\DeclareRobustCommand</code> .		General: Removed file identification	
Removed <code>\@if@short@command</code> . . .	78	typeout . . . . .	669
(ASAJ) Replaces <code>\space</code> by ‘ ’ in		1994-05-13 ltssini.dtx v2.1j	
<code>\csname</code> . . . . .	78	General: Removed file identification	
Renamed		typeout . . . . .	702
<code>\DeclareProtectedCommand</code> to		1994-05-13 ltfsstrc.dtx v2.3g	
<code>\DeclareRobustCommand</code> .		General: Removed typeouts as	
Removed <code>\@if@short@command</code> .		<code>\ProvidesPackage</code> writes to log. .	638
Moved to after the definition of		1994-05-13 ltoutenc.dtx v1.5b	
<code>\@gobble</code> . . . . .	89	General: Added <code>\{</code> , <code>\}</code> and <code>\\$</code> . . . .	478
1994-05-13 ltdefns.dtx v1.0r		Renamed	
General: (ASAJ) Added logging		<code>\DeclareProtectedCommand</code> to	
message to		<code>\DeclareRobustCommand</code> . . . . .	478
<code>\DeclareProtectedCommand</code> . . . . .	78	Replaces <code>\space</code> by ‘ ’ in <code>\csname</code> . .	478
Added logging message to		1994-05-13 ltpictur.dtx v0.1d	
<code>\DeclareProtectedCommand</code> . . . . .	89	General: Removed surplus braces from	
1994-05-13 ltdefns.dtx v1.0s		<code>\@if..</code> constructions . . . . .	933
General: (ASAJ) Added		1994-05-13 lttab.dtx v1.0d	
<code>\@backslashchar</code> . . . . .	78	<code>\@contfield</code> : Colour support . . . . .	914
(ASAJ) Coded <code>\@ifdefinable</code> more		<code>\@startfield</code> : Colour support . . . .	914
efficiently. . . . .	78	<code>\@stopfield</code> : Colour support . . . . .	914
Coded more efficiently, thanks to		<code>\a</code> : moved to ltoutenc . . . . .	912
FMi. . . . .	85	1994-05-14 fontdef.dtx v2.1f	
1994-05-13 ltfiles.dtx LaTeX2e		General: Removed .def files. . . . .	734
<code>\listfiles</code> : Stop <code>\listfiles</code> being		1994-05-14 ltfsbas.dtx v2.1lm	
run twice . . . . .	476	<code>\enc@update</code> : Macro added . . . . .	549

1994-05-14 ltssbas.dtx v2.1n	1994-05-16 ltssbas.dtx v2.1p
General: Set defaults for all <code>\f@...</code> . . . . . 550	<code>\fontsize</code> : Pass <code>\baselinestretch</code> not
<code>\DeclareErrorFont</code> : Don't set	<code>\f@linespread</code> . . . . . 550
<code>\f@encoding</code> . . . . . 558	<code>\linespread</code> : Remove surplus braces 550
<code>\DeclareFontEncoding</code> : Log if	1994-05-16 ltssini.dtx v2.1m
encoding is redeclared . . . . . 542	<code>\@acciii</code> : Define saved versions of
Only init enc change cmd when new	accents . . . . . 731
encoding . . . . . 542	1994-05-16 ltlogos.dtx v1.1a
1994-05-14 ltssini.dtx v2.1k	General: (ASAJ) Split from ltinit.dtx. 453
General: Init error font just before	1994-05-16 ltmath.dtx v1.0k
checking for fontdef.cfg . . . . . 730	<code>\ensuremath</code> : Use
<code>\reset@font</code> : Remove surplus braces 727	<code>\DeclareRobustCommand</code> and add
1994-05-14 ltssstrc.dtx v2.3h	extra braces in math mode . . . . 867
<code>\selectfont</code> : Added <code>\enc@update</code> . . 644	1994-05-16 ltoutenc.dtx 1.5h
1994-05-14 ltoutenc.dtx 1.5d	General: <code>\pounds</code> was still using u
General: Moved the driver to the top. 481	rather than ui shape. . . . . 494
1994-05-14 ltoutenc.dtx v1.5c	1994-05-16 ltoutenc.dtx v1.5f
General: Added the fontenc package 521	General: enc files now have uc
Added the fontenc package. . . . . 478	encoding name parts (FMi) . . . . 478
Fixed a bug which caused an	Revert code so that the encoding
infinite loop if <code>\f@encoding</code> was	given is used in
incorrectly set. . . . . 478, 482	<code>\DeclareTextCommand</code> (FMi) . . . 478
Moved fontsmpl to its own dtx file. 478	1994-05-16 ltoutenc.dtx v1.5g
1994-05-14 ltoutenc.dtx v1.5d	General: Made fontenc.sty use the new
General: Rewrote	mixed-case encoding files. . . . . 478
<code>\DeclareTextCommand</code> to define its	Removed the lowercasing of the
argument to use the current	filename. . . . . 521
encoding by default, rather than	1994-05-16 ltoutenc.dtx v1.5h
the encoding provided to	General: Added <code>\NG</code> , <code>\ng</code> , <code>\TH</code> , <code>\th</code> ,
<code>\DeclareTextCommand</code> . . . . 478, 482	<code>\DH</code> , <code>\dh</code> , <code>\DJ</code> and <code>\dj</code> . . . . . 478
Tidied up the documentation. . . . 478	Added <code>\r</code> (ring accent) and <code>\k</code>
1994-05-14 ltoutenc.dtx v1.5e	(ogonek) accents. . . . . 478
General: Replaced <code>\ENC@cmd</code> by	Fixed a bug with <code>\pounds</code> . . . . . 478
<code>\ENC-cmd</code> . . . . . 478	Removed <code>\P</code> from the OT1
1994-05-15 ltssbas.dtx v2.1o	definitions file. . . . . 478
General: encoding cmds changed to	1994-05-16 ltoutenc.dtx v1.5i
enc-cmd . . . . . 538	General: Fixed a bug with <code>\d</code> . . . . 478
1994-05-16 fontdef.dtx v2.1g	1994-05-16 ltoutput.dtx v1.0q
General: Removed	<code>\@writsetup</code> : Changed setting of
<code>\DeclareFontEncoding</code> for ot1 and	accents (FMi): with the new
t1 and input .def files instead . . 734	encoding setup they can use <code>\let</code> .
1994-05-16 ltalloc.dtx v1.1a	It could also use the new internal
General: (ASAJ) Split from ltinit.dtx. 394	commands? . . . . . 1209
1994-05-16 ltctrl.dtx v1.0a	General: Changed setting of accents
General: (ASAJ) Split from ltinit.dtx. 396	(FMi). . . . . 1168
1994-05-16 ltdefns.dtx v1.1a	1994-05-16 ltpar.dtx v1.1a
General: (ASAJ) Split from ltinit.dtx. 78	General: (ASAJ) Split from ltinit.dtx. 411
1994-05-16 lterror.dtx v1.1a	1994-05-16 ltplain.dtx v1.0h
General: (ASAJ) Completely new	General: Comment out encoding
error interface. . . . . 400	specific commands . . . . . 29
(ASAJ) Split from ltinit.dtx. . . . 400	Remove <code>\@acci</code> and friends again . 30
1994-05-16 ltfinal.dtx v1.0i	Remove unnecessary def for <code>\item</code> 29
General: moved output enc stuff to	<code>\loop</code> : Use Kabelschacht method . . . 27
lfonts . . . . . 1300	<code>\m@th</code> : Remove unnecessary space . . . 28

1994-05-16 ltspace.dtx v1.1a	Replaced <code>\defaultencoding</code> with	
General: (ASAJ) Split from ltinit.dtx. 433	<code>\encodingdefault</code> . . . . .	478
1994-05-17 ltclass.dtx v1.0e	1994-05-19 ltbibl.dtx v1.1a	
<code>\@use@option</code> : Execute option after	General: Initial version of ltbibl.dtx,	
removing from list, not before . 1070	split from ltidxbib.dtx . . . . .	1009
1994-05-17 ltdefns.dtx 1.1b	1994-05-19 ltcounts.dtx v1.1a	
General: (ASAJ) Added the	General: Extracted file from ltcntlen. 525	
<code>\@protect@...</code> commands. . . . .	1994-05-19 ltdefns.dtx v1.1d	
90	General: (RmS) Added definitions for	
1994-05-17 ltdefns.dtx v1.1b	<code>\@namedef</code> and <code>\@nameuse</code> again. . 78	
General: (ASAJ) Added definitions for	1994-05-19 ltfinal.dtx v0.1k	
<code>protect</code> . . . . .	General: Removed <code>\makeat...</code> . . . .	1284
(ASAJ) Removed warnings and	1994-05-19 ltidxglo.dtx v1.1a	
logging to lterror.dtx. . . . .	General: Initial version of ltidxglo.dtx,	
78	split from ltidxbib.dtx . . . . .	1006
Added the discussion of protected	1994-05-19 ltlength.dtx v1.1a	
commands, defined the values that	General: Extract file ltlength from	
<code>\protect</code> should have. . . . .	ltcntlen. . . . .	536
89	1994-05-19 ltpageno.dtx v1.1a	
1994-05-17 ltdefns.dtx v1.1c	General: Extract file ltpageno from	
General: (ASAJ) Redid definitions for	ltcntlen. . . . .	805
<code>protect</code> . . . . .	1994-05-19 ltplain.dtx v0.1k ltfinal	
78	<code>\showoutput</code> : used <code>\maxdimen</code> not	
1994-05-17 lterror.dtx v1.1b	99999 . . . . .	31
General: (ASAJ) Moved error stuff	<code>\showoverfull</code> : used <code>\@ne</code> not 1 . . . .	30
from ltdefns.dtx. . . . .	1994-05-19 ltxref.dtx v1.1a	
400	General: Extract file ltxref from	
1994-05-17 ltfssini.dtx v2.1n	ltcntlen. . . . .	806
<code>\copyright</code> : Really add extra braces 727	1994-05-20 ltdefns.dtx v1.1e	
<code>\nfss@text</code> : Added braces to allow	General: Changed command name	
use in subscripts . . . . .	from <code>\@checkcommand</code> to	
727	<code>\CheckCommand</code> . . . . .	78
1994-05-17 ltmath.dtx v1.0i	<code>\CheckCommand</code> : Changed name from	
General: Replaced <code>\let</code> by <code>\gdef</code> , for	<code>\@checkcommand</code> to	
indirect definition. . . . .	<code>\CheckCommand</code> . . . . .	87
860	1994-05-20 lterror.dtx v1.1c	
1994-05-17 ltoutenc.dtx v1.5j	General: (ASAJ) Added	
General: Added braces to <code>\pounds</code> so	<code>\@latex@info@no@line</code> . . . . .	400
it works as a subscript. . . . .	(ASAJ) Added missing full stops. 400	
478	(ASAJ) Fixed a bug with	
1994-05-18 ltdefns.dtx 1.1c	<code>\@inmatherr</code> . . . . .	400
General: (ASAJ) Renamed the	1994-05-20 ltfinal.dtx v0.1l	
commands, and removed one	General: Use new font warning	
which is no longer needed. . . . .	commands . . . . .	1291
90	1994-05-20 ltfloat.dtx v1.0h	
1994-05-18 ltdefns.dtx v1.1c	<code>\@endfloatbox</code> : Restore outer value of	
General: Redid the discussion and	<code>@nobreak</code> switch. . . . .	992
definitions, in line with the	<code>\outer@nobreak</code> : Macro added:	
proposed new setting of <code>\protect</code>	default is to do nothing. . . . .	992
in the output routine. . . . .	1994-05-20 ltfntcmd.dtx v3.3h	
89	General: Use new error commands . 756	
1994-05-18 ltfinal.dtx v0.1j	1994-05-20 ltfssbas.dtx v2.1q	
General: Corrected the lccode for	General: Use new error commands . 538	
d-bar. . . . .		
1284		
1994-05-18 ltlogos.dtx v1.1b		
General: (ASAJ) Added the $\TeX$		
logo. . . . .		
453		
(ASAJ) Made the $\LaTeX 2\epsilon$ logo use		
the text font ‘2’ rather than the		
math font ‘2’. . . . .		
453		
1994-05-18 ltoutenc.dtx v1.5k		
General: Made dotted-i produce ‘i’. . 478		
Removed braces from <code>\pounds</code> and		
<code>\dollar</code> . . . . .		
478		

1994-05-20 ltfssstrc.dtx v2.3i	1994-05-22 lterror.dtx v1.2a
General: Use new error command	General: (ASAJ) Made
names . . . . . 638	\GenericError, \GenericWarning
1994-05-20 ltmiscen.dtx v1.0l	and \GenericInfo robust. . . . . 400
\@writefile: Added correct setting of	(ASAJ) Replaced \ and tilde by
\protect. . . . . 835	\MessageBreak and \space. . . . . 400
1994-05-20 ltmiscen.dtx v1.0m	(ASAJ) Replaced
General: Use new warning commands 828	\@generic@message and
1994-05-20 ltoutput.dtx v1.0s	\@generic@error by
\@writsetup: Added setting of	\GenericError, \GenericWarning
\protect during \shipout. . . . 1208	and \GenericInfo. . . . . 400
General: Added setting of \protect	(ASAJ) Replaces \string by
during \shipout. . . . . 1168	\protect in some messages. . . . 400
1994-05-20 ltpage.dtx v1.0d	1994-05-22 lterror.dtx v1.2d
\markright: Changed setting for	\GenericError: (DPC) Alternative
\protect. . . . . 1046	version added for old TeXs . . . . 401
1994-05-20 ltsect.dtx v1.0c	(DPC) New version using long
\addcontentsline: Correct setting of	command name. . . . . 401
\protect. . . . . 978	1994-05-22 ltfloat.dtx v1.0i
\addtocontents: Correct setting of	General: Use new warning commands 983
\protect. . . . . 979	1994-05-22 ltoutput.dtx v1.0t
1994-05-21 ltbibl.dtx v1.1b	General: Changed warnings and infos
General: Use new warning	to new commands. . . . . 1168
commands . . . . . 1009	1994-05-22 ltpictur.dtx v0.1e
1994-05-21 lterror.dtx v1.1d	General: Use new warning cmds . . . 933
General: (ASAJ) Made the error	1994-05-23 ltclass.dtx v1.0h
commands robust. . . . . 400	\NeedsTeXFormat: Don't stop
1994-05-21 ltfiles.dtx v1.0h	completely when format is wrong 1074
General: Use new error commands . 454	\usepackage: Remove argument if
1994-05-21 ltlists.dtx v1.0f	possible . . . . . 1073
General: Use new error commands . 871	1994-05-23 ltdirchk.dtx v1.0f
1994-05-21 ltmiscen.dtx v1.0n	General: Document \@TeXversion . . . 1
General: Use new error commands . 828	1994-05-23 ltfssstrc.dtx v2.3j
1994-05-21 ltsect.dtx v1.0d	General: Removed def of
General: Use new error commands . 969	\@warn@break . . . . . 657
1994-05-21 lttab.dtx v1.0f	1994-05-23 ltoutput.dtx v1.0u
General: Use new error commands . 908	\@activechar@info: Added
1994-05-21 ltxref.dtx v1.1b	\MessageBreak . . . . . 1207
General: Use new warning commands 806	\@writsetup: Changed resetting of
\newlabel: Use new warning	\protect after shipout to use
commands . . . . . 809	\aftergroup . . . . . 1208
1994-05-22 ltclass.dtx v1.0f	General: Added \MessageBreak. . . 1168
General: Use new warning and error	Changed resetting of \protect after
commands . . . . . 1050	shipout. . . . . 1168
1994-05-22 ltdefs.dtx v1.1f	1994-05-24 lterror.dtx v1.2e
General: Use new warning and error	\@latex@info@no@line: Macro added 404
cmds . . . . . 78	1994-05-24 lterror.dtx v1.2f
1994-05-22 lterror.dtx v1.1e	General: (DPC) wrap long lines . . . 400
General: (ASAJ) Replaced bgroup by	1994-05-24 ltfntcmd.dtx v3.3i
begingroup in error messages, to	General: Tidying and typos fixed . . 756
stop extra mathords creeping into	1994-05-24 ltmiscen.dtx v1.0q
math mode. . . . . 400	\@currentvline: Use \@empty as outer
	default . . . . . 841

1994-05-25 ltdirchk.dtx v1.0g		<code>\framebox</code> : New version, so <code>\width</code> is correct in <code>\framebox</code> . . . . .	897
<code>\filename@parse</code> : Mac parser had " typo for : . . . . .	12	1994-06-01 ltlogos.dtx v1.1d	
1994-05-25 ltfntcmd.dtx v3.3j		<code>\LaTeX</code> : Add <code>\m@th</code> to force math size calculations . . . . .	453
General: Insertion of <code>\aftergroups</code> to implement <code>\nocorr</code> moved to the end of the group . . . . .	756	1994-06-01 ltoutput.dtx v1.0w	
<code>\check@icr</code> : Macros added . . . . .	760	General: Tidied up typesetting. . .	1168
<code>\check@nocorr@</code> : Insertion of <code>\aftergroups</code> moved and defaults set up for efficiency . . . . .	760	1994-06-08 ltfinal.dtx v1.0m	
<code>\DeclareTextFontCommand</code> : <code>\expandafter</code> inserted . . . . .	758	General: Add patch file system . . .	1301
Insertion of <code>\aftergroups</code> moved . . . . .	758	1994-06-09 ltfinal.dtx v1.0n	
1994-05-25 ltoutput.dtx v1.0v		General: For $\TeX$ 2, do not set codes for higher half of character table. . . . .	1289, 1297
General: Extra documentation. . . .	1168	1994-06-09 ltfntcmd.dtx v3.3k	
1994-05-25 ltsect.dtx v1.0e		General: Tidying and typos fixed in documentation . . . . .	756
<code>\@dottedtocline</code> : Put braces around argument 4 (the actual toc entry) to avoid font (and possibly other) changes leaking out to the leaders. . . . .	981	1994-06-18 ltfntcmd.dtx v3.3l	
1994-05-25 lthm.dtx v1.0c		General: Added check for empty text . . . . .	756
General: Modify documentation . . .	965	<code>\check@nocorr@</code> : Added check for empty text . . . . .	760
1994-05-25 ltvers.dtx v1.0d		1994-06-22 ltfntcmd.dtx v3.3m	
General: Remove PRELIMINARY TEST RELEASE from startup banner (spring is here) . . . . .	35	General: Removed space from <code>\nfss@text</code> . . . . .	756
1994-05-25 ltxref.dtx v1.1c		Renamed <code>\check@nocorr</code> . . . . .	756
General: Modify documentation . . .	806	<code>\check@nocorr@</code> : Renamed <code>\check@nocorr</code> to <code>\text@command</code> to improve <code>\long</code> error message . . . . .	760
1994-05-26 ltfiles.dtx LaTeX2e		<code>\DeclareTextFontCommand</code> : Removed space from <code>\nfss@text</code> . . . . .	758
<code>\@missingfileerror</code> : Modify message format . . . . .	474	1994-06-22 ltmath.dtx v1.2t classes	
1994-05-26 ltlogos.dtx v1.1c		<code>\mathindent</code> : Set <code>\mathindent</code> at the end of the class instead of at begin document . . . . .	868
General: Remove <code>\SLiTeX</code> logo . . . .	453	1994-07-20 ltlogos.dtx v1.1e	
1994-05-26 ltmiscen.dtx v1.0r		<code>\LaTeX</code> : Save a few tokens . . . . .	453
General: <code>\literal</code> removed . . . . .	852	<code>\LaTeXe</code> : Save a few tokens . . . . .	453
1994-05-26 ltplain.dtx v1.1m		1994-07-20 ltpage.dtx v1.0h	
<code>\iterate</code> : (CAR) added <code>\long</code> . . . .	27	<code>\sloppy</code> : Save a few tokens . . . . .	1049
<code>\underbar</code> : (CAR/FMi) changed to use box <code>\tw@</code> . . . . .	29	1994-09-16 ltfssbas.dtx v2.1s	
1994-05-26 ltplain.dtx v1.1p		<code>\nfss@catcodes</code> : Reset [ and ] as well, just in case . . . . .	556
<code>\underbar</code> : (DPC) changed to use <code>\sbox</code> . . . . .	29	1994-10-07 ltoutenc.dtx v1.5l	
1994-05-29 ltfssdcl.dtx v2.1j		General: Moved the ogonek accent. . .	478
General: Use new error commands . .	669	1994-10-11 ltdirchk.dtx v1.0h	
1994-05-31 ltfinal.dtx v1.0n		<code>\@TeXversion</code> : Check for TeX3.14 . .	13
General: Renamed <code>lthyphen.*</code> to <code>lthyphen.*</code> . . . . .	1284	General: Modify all of <code>ltxcheck</code> again . . . . .	13
1994-06-01 ltboxes.dtx v1.0i		1994-10-12 ltsect.dtx v1.0f	
<code>\@frameb@x</code> : Macro added. . . . .	898	General: Doc. typos . . . . .	969
<code>\@ifframebox</code> : New version, so <code>\width</code> is correct in <code>\framebox</code> . . . . .	897	1994-10-14 fontdef.dtx v2.2a	
<code>\fbox</code> : New version, using <code>\@frameb@x</code> . . . . .	896	General: New coding . . . . .	732
		1994-10-14 ltfssini.dtx v2.2a	
		General: New coding for <code>cfg</code> files . . .	702
		1994-10-14 ltmiscen.dtx v1.0s	
		General: Move math to other file . . .	828

1994-10-14 ltplain.dtx v1.1a	1994-10-25 fontdef.dtx v2.2c
General: Moved code to other files. . . 14	General: Added OMSenc.def . . . . . 734
1994-10-15 ltffsbas.dtx v2.1t	1994-10-25 ltboxes.dtx v1.0l
\extract@alph@from@version: Warn	\@isavepicbox: missing percent
if math alpha is used outside	(moved from ltpatch) . . . . . 895
math . . . . . 564	1994-10-25 ltdefns.dtx v1.2b
1994-10-18 ltboxes.dtx v1.0j	General: Documentation
\@frameb@x: \leavevmode added . . 898	improvements . . . . . 78
\@ifframebox: \leavevmode moved to	1994-10-25 ltoutenc.dtx 1.6a
\@frameb@x . . . . . 897	General: Added \textdollar,
\@parboxto: Macro added to remove	\textlbrace, \textrbrace,
misuse of \@empty . . . . . 899	\textsterling, \textunderline. 497
General: stuff from ltpatch done . . . 890	Removed \textlbrace,
\fbox: \long added . . . . . 896	\textrbrace, \textunderline to
\mbox: \long added . . . . . 891	give them their proper names. . . 497
\sbox: \long added . . . . . 895	1994-10-25 ltoutenc.dtx v1.6a
1994-10-18 ltclass.dtx v1.0j	General: Added
General: Move \listfiles to	\ProvideTextCommand,
ltfiles.dtx . . . . . 1050	\UseTextSymbol, \UseTextAccent,
1994-10-18 ltdefns.dtx v1.2a	\DeclareTextSymbolDefault,
\@star@or@long: macro added . . . . 81	\DeclareTextAccentDefault,
General: Add extra test for \endgraf 78	\DeclareTextCommandDefault,
Add star-forms for all commands . 78	and
\renew@environment: reset end	\ProvideTextCommandDefault. . 478
command . . . . . 86	Added the \Provide commands,
1994-10-18 ltfiles.dtx v1.0i	and the default definitions. . . . 482
\listfiles: code moved here from	Added the defaults. . . . . 491
ltclass . . . . . 476	Added the files OTlenc.def,
1994-10-18 ltoutenc.dtx v1.5l	Tlenc.def and OMSenc.def. . . . 491
General: Added new definitions of	Added the OMS encoding. . . . . 503
\patterns and \hyphenation. . . 490	1994-10-27 ltoutenc.dtx 1.6b
1994-10-18 ltoutenc.dtx v1.5m	General: Added \textasciicircum
General: Added new definitions of	\textasciitilde \textbackslash
\patterns and \hyphenation. . . 478	\textbar \textbraceleft
1994-10-18 ltsect.dtx v1.0g	\textbraceright
\@dottedtocline: Added	\textcompwordmark \textemdash
\normalcolor for page number . 981	\textendash \textexclamdown
General: Added \normalcolor . . . . 969	\textgreater \texthyphenchar
1994-10-19 ltffsbas.dtx v2.1t	\textthyphen \textless
\DeclareFontEncoding: Add missing	\textquestiondown
\relax. . . . . 542	\textquotedblleft
1994-10-23 ltfsstrc.dtx v23.k	\textquotedblright
\every@math@size: Renamed to	\textquotedbl \textquoteleft
\every@math@size . . . . . 647	\textquoteright
1994-10-23 ltmath.dtx v1.0l	\textunderscore
\@eqnnum: Added \normalcolor since	\textvisiblespace . . . . . 497
\eqno introduces a subgroup of the	Added: \textemdash \textendash
displayed math group . . . . . 864	\textexclamdown
\ensuremath: Remove extra braces:	\texthyphenchar \textthyphen
but see p 168 of Leslie's book . . 867	\textquestiondown
1994-10-24 ltboxes.dtx v1.0k	\textquotedblleft
\fbox: Inner braces added (to fix	\textquotedblright
latex/1061) . . . . . 896	\textquoteleft
	\textquoteright . . . . . 494

- 1994-10-27 ltoutenc.dtx v1.5d  
 General: Rewrote  
   `\DeclareTextSymbol` to define its  
   argument to use the current  
   encoding by default, to fit with  
   `\DeclareTextCommand`. . . . . 482
- 1994-10-27 ltoutenc.dtx v1.6b  
 General: Added `\textbackslash`. . . 503  
 Added more defaults for OT1. . . 491  
 Removed the enc.def files . . . . . 478  
 Removed the files OT1enc.def,  
 T1enc.def and OMSenc.def. . . . 491  
 Renamed `\textlbrace` to  
   `\textbraceleft` and `\textrbrace`  
   to `\textbraceright`. . . . . 503
- 1994-10-29 ltmath.dtx 1.0m  
 General: ASAJ: Added  
   `\DeclareMathOperator`. . . . . 853  
 ASAJ: Tidied up documentation. 861
- 1994-10-29 ltmath.dtx v1.0m  
 General: ASAJ: Added  
   `\mathellipsis`, `\mathdollar` and  
   `\mathsterling`. . . . . 860  
 ASAJ: Removed `\dag`, `\ddag`. . . 860  
 ASAJ: Renamed `\S` and `\P` to  
   `\mathsection` and  
   `\mathparagraph` and made them  
   `\mathchardefs`. . . . . 860
- 1994-10-29 ltoutenc.dtx v1.6c  
 General: Added commands like `\dots`  
   for use in text and math. . . . . 491  
 Renamed `\P`, `\S`, `\dag` and `\ddag` to  
   `\textparagraph`, `\textsection`,  
   `\textdagger` and  
   `\textdaggerdbl`. . . . . 478
- 1994-10-30 ltdefs.dtx v1.2c  
   `\@onelevel@sanitize`: Macro added 109  
 General: (CAR)`\@onelevel@sanitize`  
   added . . . . . 78
- 1994-10-30 ltdefs.dtx v1.2f  
 General: (DPC)`\newwrite`'s moved to  
   ltfiles . . . . . 78
- 1994-10-30 ltmath.dtx v1.0n  
 General: ASAJ: Moved the new  
   commands to ltoutenc. . . . . 860
- 1994-10-30 ltoutenc.dtx v1.6d  
 General: Added  
   `\DeclareTextCompositeCommand`. 478  
 Added `\textcircled`. . . 478, 492, 503  
 Added `\t`. . . . . 492  
 Added math commands. . . . . 478  
 Added OML encoding. . . . . 478, 492  
 Added the OML encoding. . . . . 503
- Made `\textless` and `\textgreater`  
 come from OML. . . . . 492  
 Moved math commands here from  
 ltmath. . . . . 494  
 Removed `\textregistered`. . . . 492  
 Rewrote `\copyright` to use  
   `\textcircled`. . . . . 492
- 1994-10-31 fontdef.dtx v2.2d  
 General: Added OMLenc.def ... . . 734
- 1994-10-31 fontdef.dtx v2.2e  
 General: ... and moved further down 734
- 1994-10-31 ltfloat.dtx v1.1a  
   `\@dblfloat`: Major changes since  
   two-column and one-column cases  
   merged . . . . . 986  
   `\@dblflset`: Macro added . . . . . 986  
 Major changes to parameter  
 parsing, setting of local variables,  
 etc; two-column and one-column  
 cases merged; space hacks moved 986  
   `\@endfloatbox`: (DPC/CAR) Extra  
   box added to remove colour  
   resetting from vmode . . . . . 992  
   `\@floatboxreset`: Macro added . . . 990  
   `\@footnotetext`: (DPC/CAR) Move  
   colour setting to output routine 1002  
   `\@savemarbox`: (DPC/CAR) Extra  
   box added for colour . . . . . 996  
   `\@setfps`: Macro added . . . . . 987  
   `\@xdblfloat`: Macros removed:  
   `\@dbflt`, `\@xdblfloat` . . . . . 992  
   `\@xfloat`: (DPC/CAR) Extra box  
   added to remove colour resetting  
   from vmode . . . . . 988  
 Major changes, removing setting of  
 local variables, space hacks etc;  
 two-column and one-column cases  
 merged . . . . . 987  
 Reset hook added . . . . . 988  
   `\@xympar`: (DPC/CAR) Extra box  
   added since needed for floats . . . 997  
   `\fps@dbl`: Macro added . . . . . 987
- 1994-10-31 ltoutput.dtx v1.1a  
   `\@topnewpage`: (DPC/CAR) Extra  
   box added to remove colour  
   resetting from vmode . . . . . 1184  
 (DPC/CAR) Use  
   `\color@begingroup` for colour . 1184  
 (DPC/CAR) Use `\normalcolor` 1184
- 1994-11-02 ltoutenc.dtx v1.6d  
 General: Wrapped lines longer than 70  
   characters. . . . . 478

1994-11-03 ltclass.dtx v1.0k	1994-11-04 ltpage.dtx v1.0e
General: Move <code>\@missingfileerror</code>	<code>\markright</code> : Added
to ltfiles . . . . . 1054	<code>\@unexpandable@protect</code> .
1994-11-03 ltdirchk.dtx v1.0i	ASAJ. . . . . 1046
General: Generate an error if latex.ltx	1994-11-04 ltsect.dtx 1.0h
not used with clean initex . . . . . 1	<code>\@sect</code> : (ASAJ) Added
1994-11-03 ltfiles.dtx v1.0j	<code>\protected@edef</code> . . . . . 973
<code>\@missingfileerror</code> : Move here from	General: (ASAJ) Added
ltclass . . . . . 474	<code>\protected@xdef</code> to <code>\thanks</code> . . . 969
1994-11-04 ltboxes.dtx v1.0m	1994-11-04 ltsect.dtx v1.0h
<code>\@mpfootnotetext</code> : Added	<code>\addcontentsline</code> : Added
<code>\protected@edef</code> . ASAJ. . . . . 903	<code>\protected@write</code> to
1994-11-04 ltdefns.dtx v1.2e	<code>\addcontentsline</code> . ASAJ. . . . . 978
General: Added	<code>\addtocontents</code> : Added
<code>\set@display@protect</code> to	<code>\protected@write</code> to
<code>\typeout</code> . ASAJ. . . . . 78	<code>\addtocontents</code> . ASAJ. . . . . 979
Added commands for setting and	1994-11-04 lttab.dtx v1.0h
restoring <code>\protect</code> . ASAJ. . . . . 92	<code>\@mkpream</code> : (ASAJ) Added
Rewrote protected short commands	<code>\@unexpandable@protect</code> to
using <code>\x@protect</code> . ASAJ. . . . . 90	<code>\@mkpream</code> . . . . . 927
1994-11-04 lterror.dtx v1.2g	<code>\multicolumn</code> : (ASAJ) added
General: Added	<code>\set@typeset@protect</code> . . . . . 923
<code>\set@display@protect</code> to	1994-11-04 ltxref.dtx v1.1d
<code>\Generic*</code> commands. ASAJ. . . 400	<code>\label</code> : (ASAJ)Added
1994-11-04 ltfiles.dtx v1.0k	<code>\protected@edef</code> . . . . . 810
<code>\nofiles</code> : Added setting of	(ASAJ)Added <code>\protected@write</code> 810
<code>\protected@write</code> , <code>\makeindex</code>	1994-11-05 ltboxes.dtx v1.0n
and <code>\makeglossary</code> to <code>\nofiles</code> .	<code>\@mpfootnotetext</code> : Color resetting for
ASAJ. . . . . 461	footnotes moved to endminipage:
<code>\protected@write</code> : Macro added	as for main page. . . . . 903
ASAJ. . . . . 461	<code>\color@endbox</code> : macro added for color
1994-11-04 ltfloat.dtx v1.1b	support . . . . . 893
<code>\@footnotetext</code> : (ASAJ) Added	<code>\color@hbox</code> : macro added for color
<code>\protected@edef</code> . . . . . 1002	support . . . . . 893
<code>\footnotemark</code> : Added	<code>\endminipage</code> : Color resetting for
<code>\protected@xdef</code> to	footnotes moved to here: as for
<code>\footnotemark</code> . . . . . 1003	main page. . . . . 903
1994-11-04 ltidxglo.dtx v1.1b	1994-11-05 ltboxes.dtx v1.0o
<code>\@wrglossary</code> : Added	<code>\@mpfootnotetext</code> : Color groups
<code>\protected@write</code> to	restored here. . . . . 903
<code>\@wrglossary</code> . . . . . 1008	1994-11-05 ltfloat.dtx v1.1c
<code>\@wrindex</code> : Added <code>\protected@write</code>	<code>\@dblflset</code> : Add compatibility with
to <code>\@wrindex</code> . . . . . 1007	old version of <code>\@xfloat</code> . . . . . 986
General: Removed <code>\if@files</code> from	<code>\@endfloatbox</code> : Use new <code>\color@hbox</code>
<code>\makeindex</code> . . . . . 1006	concept. . . . . 992
<code>\makeglossary</code> : Removed <code>\if@files</code>	<code>\@footnotetext</code> : Removed
from <code>\makeglossary</code> . . . . . 1007	<code>\normalcolor</code> (again) . . . . . 1002
1994-11-04 ltmiscen.dtx v1.0t	<code>\@savemarbox</code> : Use new <code>\color@hbox</code>
<code>\@writefile</code> : Removed setting of	concept. . . . . 996
<code>\protect</code> . ASAJ. . . . . 835	<code>\@setfps</code> : Add compatibility with old
1994-11-04 ltoutenc.dtx v1.6f	version of <code>\@xfloat</code> . . . . . 987
General: Added <code>\_</code> . . . . . 493	<code>\@xfloat</code> : Add compatibility with old
Added <code>\mathunderscore</code> . . . . . 494	version of <code>\@xfloat</code> : but the

arguments, provided at exorbitant cost, are now completely ignored	987	1994-11-09 ltfsbas.dtx v2.1v	
Use new <code>\color@hbox</code> concept. . .	988	<code>\@vpt</code> : (DPC) macros added, from	
<code>\@xympar</code> : Use new <code>\color@hbox</code> concept. . . . .	997	setsize.dtx . . . . .	566
1994-11-05 ltoutenc.dtx v1.6g		(DPC) reduce save stack usage	
General: Added setting of		latex/1742 . . . . .	566
<code>\@typeset@protect</code> to <code>\patterns</code>		1994-11-10 ltbibl.dtx v1.1c	
and <code>\hyphenation</code> . . . . .	490	General: Fix <code>\nocite{*}</code> . . . . .	1009
1994-11-05 ltoutput.dtx v1.1b		<code>\nocite</code> : Fix <code>\nocite{*}</code> . . . . .	1012
<code>\@topnewpage</code> : Use new <code>\color@hbox</code> concept. . . . .	1184	1994-11-10 ltmath.dtx v1.2v classes	
<code>\@writsetup</code> : Change protect		<code>eqnarray</code> : Added value of <code>\parskip</code> to	
settings for new-style, protect-free		<code>\abovedisplayskip</code> to compensate	
aux-files. . . . .	1208	for negative <code>\topsep</code> . . . . .	870
Use new <code>\color@hbox</code> concept. . .	1208	1994-11-10 ltoutput.dtx v1.1e	
1994-11-05 ltoutput.dtx v1.1c		<code>\@writsetup</code> : Modify <code>\protect</code>	
<code>\@begindivi</code> : Added macro . . . . .	1214	setting . . . . .	1208
<code>\@begindivibox</code> : Added macro . . .	1179	1994-11-10 ltplain.dtx v1.1b	
<code>\@writsetup</code> : Add new <code>\AtBeginDvi</code>		General: (CAR) added patch to <code>\loop</code> . .	14
concept . . . . .	1208	<code>\iterate</code> : (CAR) added extra <code>\relax</code> .	27
<code>\AtBeginDvi</code> : Added macro . . . . .	1179	1994-11-11 ltspace.dtx v1.2a	
1994-11-06 ltfsbas.dtx v2.1u		<code>\:</code> (DPC) Make robust . . . . .	437
<code>\cf@encoding</code> : New macro . . . . .	550	1994-11-12 ltfntcmd.dtx v3.3o	
<code>\DeclareFixedFont</code> : Renamed		<code>\normalsize</code> : Added <code>\MessageBreak</code> .	764
<code>\every@size</code> to		1994-11-12 ltlists.dtx v1.2b ltspace	
<code>\every@math@size</code> . . . . .	540	<code>\endtrivlist</code> : Changed order of tests	
1994-11-06 ltfsini.dtx v2.2b		to make <code>\noitemerror</code> correct:	
<code>\@setsize</code> : Use <code>\typeset@protect</code> .	726	end of an era. . . . .	880
1994-11-06 ltfsstrc.dtx v2.3k		1994-11-12 ltmiscen.dtx v1.0u	
<code>\glb@currsize</code> : New implementation	646	<code>center</code> : Changed end macro to <code>\def</code> :	
<code>\try@simples</code> : New implementation	658	safer and consistent . . . . .	843
<code>\try@size@substitution</code> : New		<code>flushleft</code> : Changed end macro to	
implementation . . . . .	657	<code>\def</code> : safer and consistent . . . . .	844
<code>\tryis@simple</code> : New implementation	658	<code>flushright</code> : Changed end macro to	
1994-11-07 fontdef.dtx v2.2f		<code>\def</code> : safer and consistent . . . . .	845
General: (DPC) Add		1994-11-12 ltplain.dtx v1.1c	
<code>\DeclareMathSizes</code> declarations	739	General: Comment out more encoding	
(DPC) Updated to use		specific commands . . . . .	29
<code>\ProvidesFile</code> . . . . .	734	1994-11-12 ltspace.dtx v1.2b	
1994-11-07 ltfiles.dtx v1.0m		<code>\addpenalty</code> : Corrected error	
<code>\document</code> : Renamed <code>\every@size</code> to		message . . . . .	445
<code>\every@math@size</code> . . . . .	457	<code>\addvspace</code> : Corrected error message	444
1994-11-07 ltplain.dtx v1.0l		1994-11-13 ltspace.dtx v1.2c	
<code>\@unused</code> : move here from ltdefs,		<code>\addpenalty</code> : Recorrected error	
remove duplicate <code>\@mainaux</code> . . . .	21	message . . . . .	445
1994-11-07 preload.dtx v2.1e		<code>\addvspace</code> : Recorrected error	
General: (DPC) Updated to use		message . . . . .	444
<code>\ProvidesFile</code> . . . . .	753	1994-11-14 ltoutput.dtx v1.1f	
1994-11-09 ltboxes.dtx v1.0p		<code>\@begindivi</code> : Use normal box register:	
<code>\@finalstrut</code> : Revert <code>\finalstrut</code> to		why a box? . . . . .	1214
2.09 equivalent (from ltpatch) . .	906	<code>\@begindivibox</code> : Use normal box	
General: more color changes. . . .	890	register: why a box? . . . . .	1179
		<code>\@writsetup</code> : Modify new	
		<code>\AtBeginDvi</code> concept . . . . .	1208
		General: Removed old definition of	
		<code>\@testfp</code> . . . . .	1168

1994-11-14 ltspace.dtx v1.2d		1994-11-18 ltfsbas.dtx v2.1x	
\\: (DPC) Macro modified . . . . .	437	General: (DPC) use \reserved@f not	
1994-11-14 lttab.dtx v1.0i		\next . . . . .	538
\tabularnewline: (DPC) Macro		1994-11-18 ltfsdcl.dtx v2.1m	
added . . . . .	922	\DeclareMathDelimiter: (DPC)	
1994-11-16 fontdef.dtx v2.2h		\expandafter instead of \next . .	694
General: (DPC) Removed \{ and \}	734	1994-11-18 ltfsstrc.dtx v2.3m	
1994-11-17 ltboxes.dtx v1.0q		General: \next to \reserved@f . . .	638
General: \@tempa to \reserved@a . .	890	1994-11-18 ltmath.dtx v1.0p	
1994-11-17 ltclass.dtx v1.0l		\phantom: (DPC) colour support . .	855
General: \@tempa to \reserved@a . .	1050	(DPC) use \expandafter instead of	
1994-11-17 ltcntrl.dtx v1.0b		\next . . . . .	855
General: \@tempa to \reserved@a . .	396	\prime@s: (DPC) use \@let@token	
1994-11-17 ltdefs.dtx v1.0g		instead of \next and	
General: \@tempa to \reserved@a . . .	78	\expandafter instead of \nxt . .	860
1994-11-17 ltdirchk.dtx v1.0j		\smash: (DPC) colour support . . .	856
General: \@tempa to \reserved@a . . . .	1	(DPC) use \expandafter instead of	
1994-11-17 lterror.dtx v1.2h		\next . . . . .	856
General: \@tempa to \reserved@a . .	400	1994-11-21 ltfloat.dtx v1.1f	
1994-11-17 ltfiles.dtx v1.0n		\@endfloatbox: Added reset of	
General: \@tempa to \reserved@a . .	454	minipage flag . . . . .	992
1994-11-17 ltfinal.dtx v1.0o		Corrected position of	
General: \@tempa to \reserved@a . .	1284	\outer@nobreak . . . . .	992
1994-11-17 ltfloat.dtx v1.1e		\@marginparreset: Macro added . .	996
General: \@tempa to \reserved@a . .	983	\@savemarbox: Added \@setminipage	
1994-11-17 ltfntcmd.dtx v3.3p		etc . . . . .	996
General: \@tempa to \reserved@a . .	756	Added resetting of size and font . .	996
1994-11-17 ltfsbas.dtx v2.1w		Changed to \color@vbox . . . . .	996
General: \@tempa to \reserved@a . .	538	Use \@setnobreak etc . . . . .	996
1994-11-17 ltfsdcl.dtx v2.1m		\@setminipage: Macro added . . . .	990
General: \@tempa to \reserved@a . .	669	\@setnobreak: Macro added . . . .	990
1994-11-17 ltfsstrc.dtx v2.3l		\@xfloat: Added \@setminipage . .	988
General: \@tempa to \reserved@a . .	638	Added resetting of size and font . .	988
1994-11-17 ltmath.dtx v1.0o		Changed to \color@vbox so that	
General: \@tempa to \reserved@a . .	853	large floats overflow at the	
1994-11-17 ltmiscen.dtx v1.0v		bottom . . . . .	988
General: \@tempa to \reserved@a . .	828	Missing percents reinserted after 4,	
1994-11-17 ltoutenc.dtx v1.6h		8: these are not numbers. . . . .	987
General: (DPC) \@tempa to		Use \@setnobreak . . . . .	988
\reserved@a . . . . .	478	\@xympar: Changed to \color@vbox	997
1994-11-17 ltoutput.dtx v1.1h		1994-11-21 ltoutput.dtx v1.1i	
General: \@tempa to \reserved@a. . .	1168	\@addtocurcol: Added \if@nobreak	
1994-11-17 ltpictur.dtx v1.0f		test before float box . . . .	1224, 1230
General: \@tempa to \reserved@a . .	933	\@specialoutput: Added \if@nobreak	
1994-11-17 ltsect.dtx v1.0i		test . . . . .	1191
General: \@tempa to \reserved@a . .	969	\@topnewpage: Changed to	
1994-11-17 lttab.dtx v1.0j		\color@vbox . . . . .	1184
General: \@tempa to \reserved@a . .	908	1994-11-22 ltfsdcl.dtx v2.1o	
1994-11-18 ltboxes.dtx v1.0r		General: wrap long lines . . . . .	669
\color@vbox: macro added for color		1994-11-22 ltoutenc.dtx v1.6i	
support . . . . .	893	General: Corrected \dots so that	
1994-11-18 ltfinal.dtx v1.0n		there's no kerning in monowidth	
General: re-allow slots 127–255 . . .	1296	fonts. . . . .	478

Corrected typo with <code>\mathunderscore</code> . . . . .	478	Rewrote <code>\@text@composite</code> so it allows an empty argument, or an argument containing lots of commands. . . . .	485
Fixed empty accents. Again. . . .	478		
1994-11-24 <code>ltdefs.dtx</code> v1.2h <code>\@newenv</code> : Added test for <code>\endgraf</code> . .	86	1994-12-01 <code>ltfinal.dtx</code> v1.0p General: Renamed <code>lthyphen.*</code> to <code>hyphen.*</code> . . . . .	1284
1994-11-25 <code>ltplain.dtx</code> v1.1f General: (DPC) Comment out lots of obsolete code . . . . .	14	1994-12-01 <code>lthyphen.dtx</code> v1.0g General: Rename <code>lthyphen.ltx/cfg</code> to <code>hyphen.ltx/cfg</code> . . . . .	1282
1994-11-26 <code>ltfloat.dtx</code> v1.1b <code>\footnote</code> : (ASAJ) Added <code>\protected@xdef</code> . . . . .	1002	1994-12-01 <code>ltplain.dtx</code> v1.1g General: (DPC) More doc changes . .	14
1994-11-28 <code>ltcntrl.dtx</code> v1.0c General: Documentation improvements . . . . .	396	1994-12-02 <code>fontdef.dtx</code> v2.2i General: Commented out <code>\ldots</code> . ASAJ. . . . .	732
1994-11-30 <code>ltfiles.dtx</code> v1.0o <code>\@dofilelist</code> : Macro added . . . . .	477	1994-12-02 <code>ltfssini.dtx</code> v2.2c <code>\copyright</code> : <code>\copyright</code> is now in <code>ltoutenc</code> . ASAJ . . . . .	727
<code>\listfiles</code> : Use <code>\@dofilelist</code> . . .	476	1994-12-02 <code>ltlists.dtx</code> v1.0e <code>\@trivlist</code> : RmS: Added check for looping . . . . .	879
<code>\nofiles</code> : There is no <code>\@gobblethree</code> . . . . .	461	1994-12-02 <code>ltoutenc.dtx</code> 1.7b General: Redefined <code>\a</code> properly. . . .	491
1994-11-30 <code>ltfssbas.dtx</code> v2.1y <code>\fontshape</code> : Use <code>\@current@cmd</code> in <code>\@enc@update</code> . ASAJ. . . . .	549	1994-12-02 <code>ltoutenc.dtx</code> v1.7b General: Fixed a bug with <code>\a</code> . . . . .	478
1994-11-30 <code>ltmath.dtx</code> 1.0q General: ASAJ: <code>\DeclareMathOperator</code> moved to <code>AMSLaTeX</code> . . . . .	853	1994-12-04 <code>lthyphen.dtx</code> v1.0h General: Documentation edits for /1989 . . . . .	1282
1994-11-30 <code>ltmiscn.dtx</code> v1.0w <code>\@enddocument@kernel@warnings</code> : (DPC) Do warnings even for <code>\nofiles</code> . . . . .	831	1994-12-05 <code>ltoutenc.dtx</code> v1.7c General: Added braces to <code>\textcircled</code> . . . . .	478
<code>\enddocument</code> : (DPC) Use <code>\@dofilelist</code> . . . . .	830	1994-12-06 <code>ltfssbas.dtx</code> v2.1z <code>\DeclareFontEncoding</code> : use <code>\nfss@catcodes</code> . . . . .	542
1994-11-30 <code>ltoutenc.dtx</code> 1.7a General: Redefined <code>\a</code> for the new scheme. . . . .	491	<code>\nfss@catcodes</code> : Added tab char as well . . . . .	556
1994-11-30 <code>ltoutenc.dtx</code> v1.6g General: Removed new definitions of <code>\patterns</code> and <code>\hyphenation</code> , since encoding-specific commands now expand in the mouth. . . . .	490	1994-12-08 <code>ltoutenc.dtx</code> v1.7d General: Added <code>\null</code> and <code>\sh@ft</code> to <code>\b</code> and <code>\d</code> . . . . .	478
1994-11-30 <code>ltoutenc.dtx</code> v1.7a General: Added new code for encoding-specific commands. These now expand in the mouth, which means that ligaturing and kerning can happen. . . . .	478	1994-12-08 <code>lttab.dtx</code> v1.0k <code>\@array</code> : Add <code>\tabularnewline</code> . . .	921
Always load the <code>enc.def</code> file, so that the default encoding for the commands will change. . . . .	521	<code>\tabularnewline</code> : (DPC) Made it <code>\relax</code> . . . . .	922
Redefined <code>\@changed@cmd</code> to expand in the mouth. . . . .	482	1994-12-09 <code>ltbibl.dtx</code> v1.1d <code>\bibliographystyle</code> : (DPC) Allow use in preamble. . . . .	1012
Removed <code>\@changed@x@mouth</code> since <code>\@changed@x</code> now expands in the mouth. . . . .	482	1994-12-10 <code>ltfloat.dtx</code> v1.1g <code>\@dblfloat</code> : Old version reinstated temporarily . . . . .	986
		<code>\@dblflset</code> : Macro removed temporarily . . . . .	986
		Old version reinstated temporarily	986
		<code>\@setfps</code> : Macro removed temporarily . . . . .	987

<code>\xdblfloat</code> : Macros reinserted temporarily . . . . .	992	1995-04-02 <code>ltfssini.dtx</code> v2.2d <code>\not@math@alphabet</code> : add <code>\noexpand</code> to second part of message . . . . .	725
<code>\xfloat</code> : Old version reinstated temporarily . . . . .	987	1995-04-21 <code>ltclass.dtx</code> v1.0m <code>\DeclareOption*</code> : Made long /1498	1067
Sanitization added temporarily . .	987	<code>\endfilecontents</code> : Close input check stream: latex/1487 . . . . .	1086
General: Some temps reinserted temporarily . . . . .	983	1995-04-21 <code>ltfinal.dtx</code> v1.0q General: Allow initial patch level 0	1301
<code>\fps@dbl</code> : Macro removed temporarily . . . . .	987	1995-04-21 <code>ltoutenc.dtx</code> v1.7h General: Added <code>\null \k</code> latex/1274	478
1994-12-10 <code>ltfntcmd.dtx</code> v3.3q <code>\@math@egroup</code> : Don't read arguments . . . . .	763	1995-04-22 <code>ltfiles.dtx</code> v1.0p <code>\includeonly</code> : Allow blanks in argument . . . . .	462
<code>\check@nocorr@</code> : Use <code>\space</code> command for comparison . . . . .	760	1995-04-22 <code>ltmiscen.dtx</code> v1.0x General: Removed extra def of <code>\gobble</code> . . . . .	828
1994-12-10 <code>ltfssdcl.dtx</code> v2.1p <code>\document@select@group</code> : Surround with braces (add fourth arg) . . .	675	1995-04-23 <code>ltsect.dtx</code> v1.0j <code>\addcontentsline</code> : Use <code>\contentsline</code> internally. . . . .	978
<code>\select@group</code> : Surround with braces (add fourth arg) . . . . .	672	1995-04-24 <code>ltbibl.dtx</code> v1.1e <code>\@citex</code> : Add <code>\mbox</code> to undefined case: latex/1239. . . . .	1011
1994-12-10 <code>ltoutenc.dtx</code> v1.7e General: Added documentation for the OML encoding. . . . .	478	1995-04-24 <code>ltbibl.dtx</code> v1.1f <code>\bibcite</code> : Make <code>\@onlypreamble</code> /1388. . . . .	1010
Replaced width with <code>\@width</code> and ditto height in vrules. . . . .	478	1995-04-24 <code>ltcntrl.dtx</code> v1.0d <code>\@for</code> : Don't expand second argument with <code>\edef</code> : /1317 (DPC) . . . . .	399
1994-12-14 <code>ltoutenc.dtx</code> v1.7f General: Added braces to <code>\copyright</code> so it works unbraced in subscripts. . . . .	478	1995-04-24 <code>ltoutput.dtx</code> v1.1j <code>\fl@tracemessage</code> : Do not add to kernel unless 'trace' specified . .	1246
Added check for math mode in <code>\@changed@cmd</code> . . . . .	478	1995-04-24 <code>ltoutput.dtx</code> v1.1l <code>\@begindivbox</code> : Add <code>\vbox</code> latex/1392 . . . . .	1179
Commented out <code>\textasciicircum</code> , <code>\textasciitilde</code> , <code>\textbackslash</code> , <code>\textbar</code> , <code>\textgreater</code> , <code>\texthyphenchar</code> , <code>\texthyphen</code> and <code>\textless</code> to save memory. . . . .	478	<code>\@writeseup</code> : Reset <code>\</code> latex/1451 (DPC) . . . . .	1209
1995-01-12 <code>ltmath.dtx</code> v1.2y classes <code>\@eqnnum</code> : Added <code>\normalcolor</code> . . .	868	1995-04-24 <code>ltpage.dtx</code> v1.0f <code>\fussy</code> : reset <code>\emergencystretch</code> latex/1344 . . . . .	1049
1995-03-03 <code>ltoutenc.dtx</code> 1.7g General: Corrected an error in documentation referring to the tabular rather than the tabbing environment. . . . .	491	1995-04-24 <code>ltplain.dtx</code> v1.1h <code>\newlanguage</code> : Remove remaining <code>\outer</code> declarations. . . . .	17
1995-04-02 <code>ltfntcmd.dtx</code> v3.3r <code>\@math@egroup</code> : Read them again to be able to add <code>\relax</code> . . . . .	763	1995-04-24 <code>ltxref.dtx</code> v1.1e <code>\newlabel</code> : Make <code>\@onlypreamble</code> for /1388. . . . .	809
1995-04-02 <code>ltfssdcl.dtx</code> v2.1q <code>\document@select@group</code> : fix problem for pr/1275 . . . . .	675	1995-04-25 <code>ltdefns.dtx</code> v1.2i <code>\@check@c</code> : Make <code>\long</code> for latex/1346	88
<code>\select@group</code> : fix problem for pr/1275 . . . . .	672	<code>\new@environment</code> : Parse arguments slowly but safely /1507 . . . . .	86
<code>\set@mathdelimiter</code> : fix pr/1329 . .	697	1995-04-25 <code>ltfiles.dtx</code> v1.0q <code>\document</code> : Removed execution of <code>\every@size</code> latex/1407 . . . . .	457

1995-04-25 ltsect.dtx v1.0k	1995-05-07 ltoutput.dtx v1.1m
\@dottedtocline: Added \hbox	General: Use \hb@xt@. . . . . 1168
around dots. . . . . 981	1995-05-07 ltpictur.dtx v1.0g
1995-04-27 ltboxes.dtx v1.0s	General: Use \hb@xt@. . . . . 933
\@frameb@x: Move \leavevmode for	1995-05-07 ltplain.dtx v1.1j
graphics/1512 . . . . . 898	General: Use \hb@xt@. . . . . 14
\@ifframebox: Move \leavevmode for	1995-05-07 ltsect.dtx v1.0o
graphics/1512 . . . . . 897	General: Use \hb@xt@. . . . . 969
\@iirsbox: Move \leavevmode for	1995-05-07 lttab.dtx v1.0l
graphics/1512 . . . . . 906	General: Use \hb@xt@. . . . . 908
\@irsbox: Move \leavevmode for	1995-05-08 ltbibl.dtx v1.1g
graphics/1512 . . . . . 906	\@citex: Use \@firstofone . . . . 1011
\fbbox: Move \leavevmode for	\bibitem: Removed unnecessary
graphics/1512 . . . . . 896	braces . . . . . 1010
\raisebox: Move \leavevmode for	\nocite: Use \@firstofone . . . . 1012
graphics/1512 . . . . . 905	1995-05-08 ltdefs.dtx v1.2k
1995-04-27 ltfiles.dtx v1.0r	\typein: Use \@firstofone . . . . . 80
\document: Added \global to support	1995-05-08 ltdefs.dtx v1.2l
groups in hook . . . . . 458	\typein: Remove unnecessary braces 80
1995-04-27 ltmiscen.dtx v1.0y	Replace \def by \let . . . . . 80
\enddocument: \@checkend moved	1995-05-08 ltfstrc.dtx v2.3n
after hook . . . . . 829	\ifnot@nil: Use \@firstofone . . . 652
1995-04-27 ltplain.dtx v1.1i	1995-05-11 fontdef.dtx v2.2j
General: Move \hang and	General: Updates to some plain
\textindent to latex209.def . . . . 29	macros . . . . . 732
1995-04-29 ltcntrl.dtx v1.0e	1995-05-12 ltclass.dtx v1.0n
General: Moved init of \protect to	\DeclareOption*: Use \toks@ to
ltdefs.dtx . . . . . 399	remove need to double hash
Removed unused defs for	/1557 . . . . . 1067
\@setprotect and	1995-05-12 ltfloat.dtx v1.1h
\@resetprotect . . . . . 399	\@footnotemark: Add \nobreak to
1995-04-29 ltdefs.dtx v1.2j	allow hyphenation. latex/1605 . 1004
\protect: Init \protect here . . . . 93	1995-05-12 ltpictur.dtx v1.0h
1995-04-29 ltpar.dtx v1.1b	\pictur@: Macro added for
General: (TO) Comments clean-up. 411	latex/1355 . . . . . 935
1995-05-02 ltsect.dtx v1.0l	1995-05-12 ltvers.dtx v1.0e
\@dottedtocline: Don't reset to	General: Add autoload docstrip guards 35
\rmfamily . . . . . 981	Check for format older than 1 year 35
1995-05-03 ltsect.dtx v1.0m	1995-05-13 ltfstrc.dtx v2.3o
General: TO: Promoted	General: Use single hash mark in
documentation to doc.sty	\DeclareOption . . . . . 639
standard . . . . . 969	1995-05-16 ltfloat.dtx v1.1i
1995-05-06 ltsect.dtx 1.0n	\@makefnmark: Now use
\@secCNTformat: Use \quad instead of	\textsuperscript. . . . . 1001
\hskip . . . . . 975	\textsuperscript: Command
\@sect: Added \relax after	added./pr1503 . . . . . 1001
\@secCNTformat just in case . . . 973	\thefootnote: Streamlined parts of
1995-05-07 ltboxes.dtx v1.0t	code. . . . . 1000
General: Use \hb@xt@. . . . . 890	1995-05-17 ltboxes.dtx v1.0u
1995-05-07 ltdefs.dtx v1.2k	\@irsbox: Removed surplus braces . 906
\hb@xt@: Macro added . . . . . 79	1995-05-17 ltdefs.dtx v1.0o
1995-05-07 ltmath.dtx v1.0r	\g@addto@macro: Make long for
General: Use \hb@xt@. . . . . 853	latex/1522 . . . . . 112

1995-05-17 ltlists.dtx v1.0g	1995-05-23 ltssini.dtx v2.2e
\@item: Removed surplus braces . . . 885	\newfont: Font assignment made local again. . . . . 725
\@nbitem: Removed surplus braces . 886	1995-05-24 ltdefs.dtx v1.1l
enumerate: Use \thr@@ and remove surplus braces . . . . . 887	\newif: (DPC) New implementation . 87
itemize: Use \thr@@ . . . . . 887	1995-05-24 ltdefs.dtx v1.2m
1995-05-18 ltfloat.dtx v1.1j	\typein: (DPC) New implementation 80
\@makefnmark: Added \normalfont. 1001	1995-05-24 ltfloat.dtx v1.1l
\thempfootnote: Added \itshape. 1000	\@textsuperscript: Command added. . . . . 1001
1995-05-19 ltpictur.dtx v1.1a	General: Moved definition of \footins and \footnoterule from ltplain. 1000
General: Support autoloading feature 933	\textsuperscript: Use \@textsuperscript . . . . . 1001
1995-05-20 ltcounts.dtx v1.1b	1995-05-24 ltssbas.dtx v3.0a
\@definecounter: Streamlined code 528	General: (DPC) Make file from previous file, fam.dtx 1995/05/20 v2.2d . . . . . 538
\@fnsymbol: Allowing both text and math . . . . . 533	\mathgroup: (DPC) No need to redefine \newfam as not outer . . 538
\fnsymbol: Streamlined code . . . . 532	1995-05-24 ltsscmp.dtx v3.0a
1995-05-20 ltcounts.dtx v1.1c	General: (DPC) Make file from previous file, fam.dtx 1995/05/20 v2.2d . . . . . 664
\@definecounter: And do it right . 528	1995-05-24 ltssdcl.dtx v3.0a
1995-05-20 ltfloat.dtx v1.1k	General: (DPC) Make file from previous file, latint.dtx 1995/05/21 v2.1t . . . . . 669
\@makefnmark: Moved \normalfont back and use	1995-05-24 ltssini.dtx v3.0a
\@textsuperscript . . . . . 1001	General: (DPC) Make file from previous file, lfonts.dtx 1995/05/23 v2.2e . . . . . 702
Moved \normalfont to \textsuperscript . . . . . 1001	\cal: (DPC) Remove definition . . . 731
\textsuperscript: Use \normalfont. . . . . 1001	\mit: (DPC) Remove definition . . . 731
1995-05-21 ltssdcl.dtx v2.1t	1995-05-24 ltssstrc.dtx v3.0a
\DeclareMathRadical: Allow for undefined cs names . . . . . 698	General: (DPC) Make file from previous file, tracefnt 1995/05/16 v2.3o . . . . . 638
1995-05-21 ltlists.dtx v1.0f	1995-05-24 ltssstrc.dtx v3.0b
General: Moved to doc.sty standard 871	General: (DPC) Fix \ProvidesFile usage . . . . . 638
1995-05-21 ltmath.dtx v1.0r	1995-05-25 ltclass.dtx v1.0p
\@sqrt: Use \sqrtsign . . . . . 864	\endfilecontents: Delete \filecontents after preamble . 1086
General: Remove \mathhexbox from this file . . . . . 858	1995-05-25 ltfilehook.dtx v1.0t
Update some plain macros . . . . . 853	\unqu@tefilef@und: (CAR) added \long . . . . . 1125
\lefteqn: Use \rlap . . . . . 867	1995-05-25 ltfiles.dtx v1.0s
\@@t: Use \sqrtsign instead of \sqrt . . . . . 855	\document: Added check for \topskip zero . . . . . 458
1995-05-21 ltoutenc.dtx v1.7h	1995-05-25 ltfiles.dtx v1.0t
\@inmathwarn: Added several \@onlypreamble . . . . . 483	\@iffileonpath: (CAR) added \long 471
1995-05-21 ltoutenc.dtx v1.7j	\document: Corrected typo . . . . . 458
General: Updated some plain macros 495	\IfFileExists@: (CAR) added \long 469
1995-05-21 ltplain.dtx v1.1j	
General: Moved some code to other files . . . . . 14	
1995-05-22 ltplain.dtx v1.1k	
General: Definitions of \footins and \footnoterule moved to ltfloat. . 30	
1995-05-22 lttab.dtx v1.1a	
General: Support autoloading feature 908	

<code>\nofiles:</code> (CAR) added <code>\long</code> . . . . .	461	Save some tokens in	
<code>\protected@write:</code> (CAR) added		<code>\textvisiblespace</code> and	
<code>\long</code> . . . . .	461	<code>\textunderscore.</code> . . . . .	492
1995-05-25 <code>ltfloat.dtx</code> v1.1m		1995-06-06 <code>ltfinal.dtx</code> v1.0s	
<code>\@savemarbox:</code> (CAR) Resettings		General: Made <code>\MakeUppercase</code> and	
moved to hook . . . . .	996	<code>\MakeLowercase</code> brace their	
<code>\@xfloat:</code> (CAR) Resettings moved to		argument. . . . .	1284
hook . . . . .	988	1995-06-09 <code>ltoutenc.dtx</code> v1.7l	
1995-05-25 <code>ltlists.dtx</code> v1.0i		<code>\DeclareTextComposite:</code> Rewrote	
<code>\endtrivlist:</code> Macros moved from		<code>\DeclareTextComposite</code> to define	
<code>ltspace.dtx</code> . . . . .	880	the composite as a no-argument	
1995-05-25 <code>ltmath.dtx</code> v1.3c classes		command rather than a	
<code>\@eqnnum:</code> replace		two-argument command. . . . .	486
<code>\reset@font\rmfamily</code> with		1995-06-11 <code>ltspace.dtx</code> v1.2g	
<code>\normalfont</code> (PR 1578) . . . . .	868	<code>\restorecr:</code> (CAR) <code>\relax</code> added to	
1995-05-25 <code>ltspace.dtx</code> v1.2f		stop silent eating of *. . . . .	452
<code>\@vbsphack:</code> (CAR) not used so		1995-06-13 <code>ltfinal.dtx</code> v1.0t	
‘removed’. . . . .	443	General: Add patch level string more	
<code>\@vspacer:</code> (CAR) <code>\@restorepar</code>		carefully . . . . .	1301
added to avoid possible infinite tail		Call <code>\errorstopmode</code> . . . . .	1303
recursion caused by a typo in the		1995-06-13 <code>ltpictur.dtx</code> v1.1b	
argument. . . . .	447	General: Use <code>\ProvidesFile</code> in	
(CAR) macros modified to be more		autoload . . . . .	933
efficient . . . . .	447	1995-06-14 <code>lftab.dtx</code> v1.1b	
General: Macros moved to <code>ltlists.dtx</code>	433	General: Use <code>\ProvidesFile</code> in	
1995-05-26 <code>ltdefns.dtx</code> v1.2n		autoload . . . . .	908
<code>\@gobblefour:</code> (CAR) Added <code>\longs</code>	88	1995-06-15 <code>ltfssbas.dtx</code> v3.0c	
1995-05-26 <code>ltmath.dtx</code> v1.0s		General: (DPC) minor documentation	
<code>\@eqnnum:</code> Removed <code>\rmfamily</code> (PR		changes . . . . .	538
1578), replaced <code>\reset@font</code> with		1995-06-15 <code>ltfsscmp.dtx</code> v3.0b	
<code>\normalfont</code> . . . . .	864	General: (DPC) minor documentation	
1995-05-26 <code>ltpage.dtx</code> v1.0g		edits . . . . .	664
<code>\ps@plain:</code> removed <code>\rmfamily</code> (PR		1995-06-15 <code>ltfssdcl.dtx</code> v3.0b	
1578) . . . . .	1046	General: (DPC) minor documentation	
1995-05-27 <code>ltfssbas.dtx</code> v3.0b		changes . . . . .	669
<code>\mathgroup:</code> (FMi) But a need to		1995-06-19 <code>ltbibl.dtx</code> v1.1h	
define <code>\new@mathgroup</code> . . . . .	538	<code>\biblecite:</code> Call <code>\@newl@bel</code> so	
1995-06-05 <code>fontdef.dtx</code> v2.2k		repeated keys produce better	
General: Moved math commands from		warning. . . . .	1010
<code>ltoutenc.dtx.</code> . . . . .	750	1995-06-19 <code>ltclass.dtx</code> v1.0q	
1995-06-05 <code>ltfinal.dtx</code> v1.0r		<code>\documentclass:</code> Don’t redefine	
General: Added <code>\MakeUppercase</code> and		<code>\usepackage</code> in compat mode for	
<code>\MakeLowercase.</code> . . . . .	1284	/1634 . . . . .	1072
1995-06-05 <code>ltoutenc.dtx</code> v1.7k		1995-06-19 <code>ltxref.dtx</code> v1.1e	
<code>\@inmathwarn:</code> Removed		<code>\newlabel:</code> Use <code>\@newl@bel</code> to share	
<code>\protected@cmd</code> and replaced with		code with <code>\biblecite</code> . . . . .	809
explicit <code>\noexpand.</code> . . . . .	483	1995-06-28 <code>ltfssini.dtx</code> v3.0b	
General: Allowed		General: (DPC) Fix documentation	
<code>\ProvideTextCommandDefault</code>		typos . . . . .	702
after the preamble. . . . .	484	1995-06-28 <code>ltmath.dtx</code> v1.0t	
Commented out <code>\textless</code> and		General: minor doc edits . . . . .	853
<code>\textgreater.</code> . . . . .	492	1995-07-02 <code>ltplain.dtx</code> v1.1n	
Moved math commands to		General: Removed surplus ‘by’ and ‘=’	
<code>fontdef.dtx.</code> . . . . .	494	in various places . . . . .	14

<code>\offinterlineskip</code> : Replaced 1000 by <code>\@m</code> . . . . .	27	<code>\@writefile</code> : Added missing percent and use <code>\relax</code> in the THEN case	835
<code>\showoutput</code> : Use <code>\showoverfull</code> to save space . . . . .	31	<code>\@xobeysp</code> : Use <code>\nobreak</code> . . . . .	845
<code>\tracingall</code> : Use <code>\showoutput</code> to save space . . . . .	31	General: Improve Documentation . .	828
1995-07-03 <code>ltdefns.dtx</code> v1.2o <code>\set@typeset@protect</code> : Use <code>\@typeset@protect</code> for init . . . . .	92	<code>\enddocument</code> : Set <code>\@setckpt</code> to <code>\@gobbletwo</code> instead of defining it by hand . . . . .	829
1995-07-03 <code>lftntcmd.dtx</code> v3.3s <code>\tst@ic</code> : Use clean interface for jump . . . . .	762	Shorten redefinition of <code>\bibcite</code> and <code>\newlabel</code> . . . . .	830
1995-07-05 <code>lftntcmd.dtx</code> v3.3s <code>\tst@ic</code> : Renamed from <code>\test@next</code>	762	1995-07-14 <code>ltbibl.dtx</code> v1.1i <code>\bibcite</code> : Remove <code>\@onlypreamble</code> so still defined in new <code>\enddocument</code> . . . . .	1010
1995-07-05 <code>ltspace.dtx</code> v1.2h <code>\@gnewline</code> : Use <code>\break</code> . . . . .	439	1995-07-14 <code>ltxref.dtx</code> v1.1g <code>\newlabel</code> : Remove <code>\@onlypreamble</code> so still defined in new <code>\enddocument</code> . . . . .	809
<code>\@no@pgbk</code> : Macro replaces <code>\@pgbk</code> and <code>\@nopgbk</code> . . . . .	437	1995-07-19 <code>ltfssini.dtx</code> v3.0d General: (DPC) TeX2 support . . . .	730
<code>\nopagebreak</code> : Reimplemented both using <code>\@no@pgbk</code> . . . . .	436	1995-07-20 <code>ltboxes.dtx</code> v1.0v <code>\@isavebox</code> : Use <code>\sbox</code> . . . . .	895
1995-07-09 <code>ltcntrl.dtx</code> v1.0f <code>\@iforloop</code> : Reimplemented using Kabelschacht method . . . . .	399	<code>\@isavepicbox</code> : Use <code>\sbox</code> . . . . .	895
<code>\@iwhiledim</code> : Reimplemented using Kabelschacht method . . . . .	397	1995-07-21 <code>ltoutput.dtx</code> v1.1o <code>\@writesetup</code> : Command added . .	1208
<code>\@iwhilenum</code> : Reimplemented using Kabelschacht method . . . . .	397	New, experimental, versions: need in-lining . . . . .	1208
<code>\@iwhilesw</code> : Reimplemented using Kabelschacht method . . . . .	397	1995-08-09 <code>ltmath.dtx</code> v1.0u General: Added code for class options <code>leqno</code> and <code>fleqn</code> . . . . .	868
<code>\@tfor</code> : Reimplemented using Kabelschacht method . . . . .	399	1995-08-11 <code>ltlength.dtx</code> v1.1b General: Doc typos fixed for <code>latex/753</code> . . . . .	536
1995-07-09 <code>ltlists.dtx</code> v1.0j <code>enumerate</code> : Use <code>\expandafter</code> . . . .	887	1995-08-16 <code>ltcntrl.dtx</code> v1.0g <code>\@break@tfor</code> : Made long . . . . .	399
<code>itemize</code> : Use <code>\expandafter</code> . . . . .	888	<code>\@forloop</code> : Made defs long . . . . .	399
1995-07-12 <code>ltpictur.dtx</code> v1.1d General: allow 2e commands in 209 mode. <code>latex/1737</code> . . . . .	933	<code>\@fornoop</code> : Made defs long . . . . .	399
1995-07-13 <code>ltdefns.dtx</code> v1.0p General: Updates to documentation . .	78	<code>\@iforloop</code> : Made defs long . . . . .	399
1995-07-13 <code>ltfiles.dtx</code> v1.0u General: Updates to docu . . . . .	454	<code>\@iwhiledim</code> : Made defs long . . . .	397
1995-07-13 <code>ltfssbas.dtx</code> v3.0d <code>\@defaultsubs</code> : macro added . . . .	561	Removed <code>\@whilenoop</code> . . . . .	397
<code>\@defaultsubs</code> : macro added . . . . .	561	<code>\@iwhilenum</code> : Made defs long . . . .	397
General: minor documentation changes . . . . .	538	Removed <code>\@whilenoop</code> . . . . .	397
<code>\wrong@fontshape</code> : Change a macro not a switch to flag default font substitutions . . . . .	560	<code>\@iwhilesw</code> : Removed <code>\@whileswnoop</code> . . . . .	397
1995-07-13 <code>ltmiscen.dtx</code> v1.0z <code>\@centercr</code> : Use <code>\nobreak</code> . . . . .	842	<code>\@tfor</code> : Made defs long . . . . .	399
<code>\@enddocument@kernel@warnings</code> : Use <code>\@defaultsubs</code> instead of switch	831	1995-08-16 <code>ltfiles.dtx</code> v1.0v <code>\document</code> : set <code>\@maxdepth</code> . . . .	458
		set <code>\do</code> globally . . . . .	458
		set <code>\topskip</code> globally . . . . .	458
		1995-08-24 <code>ltfssbas.dtx</code> v3.0f General: Added autoload code . . . .	538
		1995-08-24 <code>ltfstrc.dtx</code> v3.0c General: Macro <code>\gobble@font@spec</code> removed . . . . .	652
		<code>\tryis@simple</code> : . . . . .	659

1995-08-25 ltoutput.dtx v1.1p	1995-10-10 ltssdcl.dtx v3.0c
General: Support autoloading feature (FMi). . . . .	<code>\non@alpherr:</code> (DPC) autoload error message . . . . .
1995-09-01 lterror.dtx v1.2i	1995-10-10 ltplain.dtx v1.1r
General: Add autoload support . . .	General: Autoload tracing code . . . .
1995-09-01 ltplain.dtx v1.1m	1995-10-10 ltthm.dtx v1.0f
<code>\empty:</code> Use <code>\let</code> to save space . . . .	General: Make <code>\newtheorem</code> ‘only preamble’ . . . . .
<code>\I:</code> Use <code>\let</code> to save space . . . . .	1995-10-11 ltoutput.dtx v1.1r
1995-09-14 ltplain.dtx v1.1o	<code>\clearpage:</code> Added a check so that it does not lose the argument of <code>\twocolumn[...]</code> . . . . .
General: Moved <code>\multispan</code> to lttab.dtx . . . . .	1995-10-16 ltbibl.dtx v1.1j
1995-09-14 lttab.dtx v1.1c	<code>\cite:</code> (DPC) Make robust . . . . .
<code>\cline:</code> (DPC) New implementation	1995-10-16 ltboxes.dtx v1.0w
1995-09-15 ltssini.dtx v3.0e	General: Clarify makebox description
General: (DPC) Modify TeX2 message . . . . .	1995-10-16 ltdefs.dtx v1.2u
1995-09-19 ltmiscen.dtx v1.1a	<code>\@ifstar:</code> (DPC) New implementation, for /1910 . . . . .
<code>\verb:</code> Put <code>\@noligs</code> after <code>\verbatim@font</code> where it belongs.	<code>\new@command:</code> (DPC) Use <code>\@testopt</code> /1911 . . . . .
1995-10-01 ltfiles.dtx LaTeX2e	<code>\new@environment:</code> (DPC) Use <code>\@testopt</code> /1911 . . . . .
<code>\addtofilelist:</code> Macro added . . .	<code>\typein:</code> (DPC) Use <code>\@testopt</code> /1911
1995-10-02 ltdefs.dtx v1.2q	1995-10-16 ltssini.dtx v3.0f
<code>\@ifnch:</code> Use <code>\@let@token</code> for internal/924, save <code>\reserved@e</code> .	<code>\reset@font:</code> Added <code>\relax</code> after <code>\usefont</code> , as the latter eats up spaces. . . . .
<code>\@ifnextchar:</code> Use <code>\@let@token</code> . .	1995-10-16 ltmath.dtx v1.0y
<code>\@protected@testopt:</code> Macro added .	<code>\@yeqncr:</code> (DPC) Use <code>\@testopt</code> /1911 . . . . .
<code>\@testopt:</code> Macro added . . . . .	<code>\sqrt:</code> (DPC) Make robust /1808 . .
<code>\@xargdef:</code> New implementation, using <code>\@test@opt</code> . . . . .	1995-10-16 ltspc.dtx v1.2j
1995-10-03 fontdef.dtx v2.2l	<code>\nolinebreak:</code> (DPC) Use <code>\@testopt</code> /1911 . . . . .
General: <code>\@@sqrt</code> from patch file for /1701 . . . . .	<code>\nopagebreak:</code> (DPC) Use <code>\@testopt</code> /1911 . . . . .
1995-10-03 ltdefs.dtx v1.2r	1995-10-16 ltthm.dtx v1.0g
<code>\typein:</code> Add missing <code>\@typein</code> for /1710 (from patch file) . . . . .	General: Revert to previous <code>\newtheorem</code> behaviour . . . . .
1995-10-03 ltpictur.dtx v1.1e	1995-10-17 ltclass.dtx v1.0r
General: New autoload code . . . . .	<code>\@providesfile:</code> Delay definition of <code>\ProvidesFile</code> till ltfinal . . . .
1995-10-04 ltssbas.dtx v3.0g	<code>\ProcessOptions*</code> : Reset <code>\CurrentOption</code> for graphics/1873 . . . . .
General: Modify autoload code . . . .	1995-10-17 ltdirchk.dtx v1.0l
1995-10-04 ltssstrc.dtx v3.0d	General: Modify initex version of <code>\ProvidesFile</code> . . . . .
General: (DPC) Modify autoload code . . . . .	1995-10-17 ltfinal.dtx v1.0v
1995-10-04 lttab.dtx v1.1d	<code>\@providesfile:</code> reset macro . . . .
General: Modify autoload support . .	<code>\reserved@b:</code> reset here after the <code>\input</code> above . . . . .
1995-10-06 ltfiles.dtx v1.0w	
<code>\@missingfileerror:</code> Autoload error	
1995-10-09 lterror.dtx v1.2j	
General: Modify autoload support . .	
1995-10-09 ltoutenc.dtx v1.7m	
<code>\@inmathwarn:</code> Autoload error . . . .	
1995-10-10 ltssbas.dtx v3.0h	
<code>\showhyphens:</code> Use <code>\normalfont</code> and make colour safe, and autoloadable . . . . .	

1995-10-17 ltplain.dtx v1.1s	Use <code>\@refundefined</code> instead of switch	831
<code>\eject</code> : Move <code>\supereject</code> to compat file		28
1995-10-17 lttab.dtx v1.1e	<code>\@cline</code> : (DPC) Use <code>\@multicnt</code>	931
<code>\@multispan</code> : (DPC) Macro added.		931
1995-10-19 ltfinal.dtx v1.0w	<code>\@filelist</code> : Move after <code>\reserved@a</code> setting	1302
1995-10-20 ltbibl.dtx v1.1k	<code>\@citex</code> : Removed <code>refundefined</code> flag	1011
<code>\nocite</code> : Removed <code>refundefined</code> flag		1012
1995-10-20 ltclass.dtx v1.0s	<code>\@begindocumenthook</code> : Make setting conditional, for autoload version	1084
1995-10-20 ltfsbas.dtx v3.0i	General: (DPC) Modify autoload code, change <code>\undefined</code>	538
1995-10-20 ltfsstrc.dtx v3.0e	General: (DPC) Modify autoload code	638
1995-10-22 ltfsbas.dtx v3.0j	General: (RmS) New size function macro <code>\genb@sfcnt</code> needs to be disabled at <code>\document.</code>	538
1995-10-22 ltfsstrc.dtx v3.0f	General: Added ‘genb’ and ‘sgenb’ size functions to support new DC font naming scheme.	638
1995-10-23 lttab.dtx v1.1f	<code>\@settab</code> : (CAR)Ensure that <code>\@hightab</code> increases by at most one	915
<code>\@startline</code> : (CAR)Ensure that <code>\@nxttabmar</code> is never larger than <code>\@hightab</code>		913
<code>\poptabs</code> : (CAR)Ensure that <code>\@curtab</code> is never larger than <code>\@hightab</code>		916
<code>\tabbing</code> : (CAR)Make <code>\@hightab</code> consistently a local variable		915
1995-10-24 ltfiles.dtx v1.1a	<code>\document</code> : Removed <code>multiplelabels</code> switch	457
Removed <code>refundefined</code> switch		457
1995-10-24 ltfsbas.dtx v3.0k	<code>\@@defaultsubs</code> : macro removed	561
<code>\wrong@fontshape</code> : Make this code inline since it happens only here		560
1995-10-24 ltmiscen.dtx v1.1b	<code>\@enddocument@kernel@warnings</code> : Changed logic for producing warning messages and removed switch	831
1995-10-24 ltxref.dtx v1.1h	<code>\@multiplelabels</code> : Switch for <code>multiplelabels</code> removed	810
<code>\@newl@bel</code> : Switch for <code>multiplelabels</code> replaced by inline code		809
<code>\@refundefined</code> : Switch for <code>refundefined</code> replaced		807
<code>\@setref</code> : Switch for <code>refundefined</code> renamed		808
<code>\if@multiplelabels</code> : Macro removed		810
1995-10-25 ltalloc.dtx v1.1b	General: General doc improvements	394
1995-10-25 ltfloat.dtx v1.1n	<code>\@endfloatbox</code> : (CAR) macro added: to unify code for double and single versions	992
<code>\end@dblfloat</code> : (CAR) unify code for double and single versions		991
<code>\end@float</code> : (CAR) unify code for double and single versions		990
1995-10-25 ltidxglo.dtx v1.1d	General: Doc cleanup	1006
1995-10-25 ltsect.dtx v1.0q	<code>\subparagraphmark</code> : Use <code>\let</code> not <code>\def</code> to save space.	977
1995-10-27 ltpictur.dtx v1.1f	General: Move initialization to kernel from autoload file	960
1995-10-31 ltboxes.dtx v1.0x	<code>\@finalstrut</code> : Add <code>\nobreak</code> in horis mode to allow hyphenation. internal/1931	906
1995-11-01 fontdef.dtx v2.2m	General: add <code>\nfss@catcodes</code> for internal/1932	735
1995-11-01 ltdirchk.dtx v1.0n	General: Initialise <code>\@addtofilelist</code> to <code>\@gobble</code>	4
1995-11-01 ltfinal.dtx v1.0x	General: (DPC) Switch meaning of <code>\@addtofilelist</code> for cfg files	1290
1995-11-01 ltfsbas.dtx v3.0m	<code>\DeclareFontShape@</code> : (DPC) Test for <code>\relax</code> not <code>\undefined</code> , internal/1933	539
1995-11-01 ltfsini.dtx v3.0g	General: (DPC) Switch meaning of <code>\@addtofilelist</code> for cfg files	730
1995-11-02 ltfsbas.dtx v3.0n	<code>\wrong@fontshape</code> : (DPC) Remove extra space with <code>\string</code> for latex/1676	560

- 1995-11-02 ltoutenc.dtx v1.7n  
 General: Changed internal name `\a` to `\@tabacckludge` to protect against redefinition by malicious users. . 491
- 1995-11-07 ltlists.dtx v1.0k  
`\@doendpe`: Enclosed `\setbox0` assignment by a group so that it leaves the contents of box 0 intact. . . . . 882
- 1995-11-07 ltoutenc.dtx v1.7o  
 General: Added `\leavevmode` at start of `\c`, otherwise the output routine might be invoked within the macro. . . . . 495  
 Changed `\char32` to `\@xxxii` (two tokens less). . . . . 496  
 Replaced octal number 27 by decimal number 23 to protect against the quote character being active. . . . . 496  
 Replaced some 0's by `\z@` (faster). 496
- 1995-11-10 ltoutput.dtx v1.1s  
`\@shipoutsetup`: Command removed . . . . . 1208  
`\@writesetup`: Command removed 1208  
 In-lined . . . . . 1208
- 1995-11-14 ltclass.dtx v1.0t  
`\@unprocessedoptions`: Allow empty option . . . . . 1085  
`\@loadwithoptions`: macro added 1072  
`\LoadClassWithOptions`: macro added . . . . . 1073  
`\RequirePackageWithOptions`: macro added . . . . . 1073
- 1995-11-17 ltfssbas.dtx v3.0m  
`\@wrong@font@char`: (DPC) Macro added. latex/1676 . . . . . 561  
`\define@newfont`: Redefine `\typeout` latex/1676 . . . . . 554  
`\wrong@fontshape`: Support `\@wrong@font@char` latex/1676 . 560
- 1995-11-17 ltoutenc.dtx v1.7p  
`\UseTextSymbol`: Support `\@wrong@font@char` latex/1676 . 488
- 1995-11-18 ltoutenc.dtx v1.7q  
`\UseTextSymbol`: Modify message slightly . . . . . 488
- 1995-11-21 fontdef.dtx v2.2n  
 General: Incorporate changed figures, as in plain.tex . . . . . 749
- 1995-11-27 ltfssbas.dtx v3.0n  
`\nfss@catcodes`: Reset hash, for definitions in fd files . . . . . 556
- 1995-11-28 ltfloat.dtx v1.1n  
 General: documentation fixes . . . . . 983
- 1995-11-28 ltfssstrc.dtx v3.0g  
 General: documentation fixes . . . . . 638
- 1995-11-28 ltoutenc.dtx v1.7r  
 General: Added math mode checks to text commands. . . . . 482  
 doc fixes . . . . . 478  
 Renamed `\@changed@x@err` to `\TextSymbolUnavailable`. . . . . 482
- 1995-11-29 ltoutenc.dtx v1.7t  
 General: Added `\textasciicircum`, `\textasciitilde`, `\textbackslash`, `\textbar`, `\textgreater` and `\textless`. . . 498  
 Added `\textasciicircum`, `\textasciitilde`, `\textregistered` and `\texttrademark`. . . . . 492  
 Added `\textbackslash` and `\textbar`. . . . . 492, 503  
 Added `\textless` and `\textgreater`. . . . . 492, 503
- 1995-12-01 ltoutenc.dtx v1.7u  
 General: Made `\SS` a Default, rather than having the default point to the OT1 definition. . . . . 492
- 1995-12-04 ltspace.dtx v1.2k  
`\nobreakspace`: Macro added . . . . . 449
- 1995-12-04 ltspace.dtx v1.2l  
`\@xobeysp`: braces added to definition of tilde . . . . . 450
- 1995-12-04 preload.dtx v2.4e  
 General: Ulrik Vieth. added 12pt OMS and OML preloads /1989 . 755
- 1995-12-05 ltdefs.dtx 1.2w  
`\@unexpandable@protect`: Removed `\unexpandable@noexpand` as never used. internal/1733 . . . . . 90
- 1995-12-05 ltfiles.dtx v1.1c  
`\document`: `\ignorespaces` added for latex/1933 . . . . . 458
- 1995-12-05 ltfloat.dtx v1.1n  
`\@textsuperscript`: Use `\ensuremath` for latex/1984. . . . . 1001
- 1995-12-05 ltoutenc.dtx v1.7v  
`\@inmathwarn`: Changed `\TextSymbolUnavailable` text . . 484
- 1995-12-06 ltfssbas.dtx v3.00  
`\nfss@catcodes`: Reset hat, for typeouts etc in fd files . . . . . 556
- 1995-12-07 ltbibl.dtx v1.1l  
`\@citex`: Restored name of `\G@refundefinedtrue` . . . . . 1011

1995-12-07 lfloat.dtx v1.1m	1996-05-17 fontdef.dtx v2.2o
\@textsuperscript: Move \m@th out	General: \@@sqrt removed, at
of the \ensuremath for	last ..... 732, 748
latex/1984. .... 1001	1996-05-17 ltfiles.dtx v1.1f
1995-12-07 ltxref.dtx v1.1i	\nofiles: added \write to
\@setref: Switch for reundefined	\protected@write for latex/2146 461
restored ..... 808	1996-05-18 ltoutenc.dtx v1.7x
\G@refundefinedtrue: Renamed	General: Produce error if encoding not
(back) from \G@refundefined .. 807	found. pr/2054 ..... 521
1995-12-11 ltoutenc.dtx v1.7w	1996-05-21 ltoutenc.dtx v1.7y
General: Modified \copyright .... 492	General: Corrected error message
1995-12-13 ltdefs.dtx 1.2x	(CAR) ..... 521
\:- Documentation changed. .... 110	1996-05-21 ltsect.dtx v1.0s
1996-01-10 ltfiles.dtx v1.1d	\@sect: (DPC) Added extra braces for
\@iffileonpath: Change argument	internal/2148 ..... 973
handling to not require doubled	(DPC) Moved brace to allow
hash. latex/2024 ..... 471	commands like \MakeUppercase in
1996-01-20 ltidxglo.dtx v1.1e	6th argument. Changed \par to
\makeglossary: Make no-op after use	\endgraf to allow non-long
pr/2048 ..... 1007	commands. internal/2148 ..... 973
\makeindex: Make no-op after use	\@ssect: (DPC) Added extra braces
pr/2048 ..... 1007	for internal/2148 ..... 976
1996-01-20 ltspace.dtx v1.2m	(DPC) Moved brace to allow
\vspacer: Made robust ..... 447	commands like \MakeUppercase in
1996-03-25 ltmath.dtx v1.1a	4th argument. Changed \par to
\@ensuredmath: Macro added for	\endgraf to allow non-long
amslatex/2104 ..... 867	commands. internal/2148 ..... 976
\ensuremath: Reimplement for	1996-05-23 ltoutenc.dtx v1.7z
amslatex/2104 ..... 867	\@strip@args: \expandafter added to
1996-04-18 ltpage.dtx v1.0i	match other changes for
General: Improve documentation . 1045	latex/2133 ..... 487
1996-04-22 ltmiscen.dtx v1.1c	\add@accent: macro added.
General: Improve Documentation .. 828	latex/2133 ..... 485
1996-04-22 ltspace.dtx v1.2n	\DeclareTextAccent: Reimplemented
General: Documentation	using \add@accent to save space
Improvements ..... 433	latex/2133 ..... 485
1996-04-22 lttab.dtx v1.1g	\DeclareTextCompositeCommand:
\@tabclassz: (DPC) Extra \hskip	Modified to cope with new
keeps tabcolsep in empty columns	\add@accent command: required
internal/2122 ..... 928	removal of check for one
1996-04-23 ltcounts.dtx v1.1d	argument-command ..... 486
General: Documentation	1996-05-24 ltoutput.dtx v1.1t
improvements ..... 525	\@specialoutput: Check that
1996-04-24 ltfiles.dtx v1.1e	\@colroom is less than \vsize,
\document: (DPC) Reset	indicating that a float has been
\AtBeginDocument eg for	added ..... 1189
latex/1297 ..... 457	Cut-off point changed to
1996-05-08 ltfssstrc.dtx v3.0h	1.5\baselineskip ..... 1189
\math@egroup: Use \bgroup instead of	\@topnewpage: Cut-off point changed
\begingroup to match a kernel	to 2.5\baselineskip ..... 1185
change made in 1994!! ..... 650	1996-05-25 ltoutput.dtx v1.1u
1996-05-09 ltfntcmd.dtx v3.3t	\@specialoutput: Correct the above
\check@icr: Default definitions	check ..... 1189
added ..... 760	

1996-06-03 ltmiscen.dtx v1.1d	1996-07-26 ltfloat.dtx v1.1n
\@verbatim: Exchanged the following two code lines so that \dospecials cannot reset the category code of characters handled by \@noligs. 846	\@endfloatbox: remove unnecessary \global before \@minipage... 992
General: Move setting of verbatim font and \@noligs. 828	\@savemarbox: remove unnecessary \global before \@minipage... 996
\verb: Put setting of verbatim font after \dospecials so that \dospecials cannot reset the category code of characters handled by \@noligs. 851	\@setminipage: remove unnecessary \global before \@minipage... 990
1996-06-10 ltboxes.dtx v1.0y	\@setnobreak: remove unnecessary \global before \@nobreak... 990
\@parboxto: (DPC) Changed \endgraf to \@@par 899	1996-07-26 ltfsbas.dtx v3.0p
1996-06-10 ltsect.dtx v1.0t	\@DeclareMathSizes: use faster \if test 547
\@sect: (DPC) Changed \endgraf to \@@par 973	\nfss@catcodes: omit \relax as not needed 556
\@ssect: (DPC) Changed \endgraf to \@@par 976	1996-07-26 ltfsdcl.dtx v3.0e
1996-06-13 ltdirchk.dtx v1.0r	\init@restore@version: Removed \ifrestore@version switch and replaced by \init@restore@version 673
General: documentation improvements mainly from internal/2174 1	1996-07-26 ltfsstrc.dtx v3.0i
1996-06-14 lttab.dtx v1.1h	\init@restore@glb@settings: macro added replacing \if@inmath switch 649
\@tabclassz: (DPC) Change both\z@skip to 1sp for latex/2160 928	1996-07-26 ltlists.dtx v1.0l
1996-06-22 ltspace.dtx v1.2o	\@item: Remove unnecessary \global before \@minipage... 884
General: Documentation of problems added 433	Remove unnecessary \global before \@nobreak... 885
1996-07-10 ltfinal.dtx v1.0y	1996-07-26 ltmath.dtx v1.1b
\toks: Free up memory from scratch registers /2213 1302	General: Removed \global before \@ignoretrue in various places. 853
1996-07-19 ltoutenc.dtx v1.8a	1996-07-26 ltmiscen.dtx v1.1e
\@strip@args: Use char 0 not @ as carrier for \lowercase /2197 488	\@ignorefalse: put \global into definition 829
1996-07-26 ltboxes.dtx v1.0z	\begin: remove \global before \@ignore... 837
\if@minipage: put \global into definition 901	\end: remove \global before \@ignore... 839
1996-07-26 ltclass.dtx v1.0u	\ignorespacesafterend: user level macro added 829
\@classoptionslist: made only preamble 1055	1996-07-26 ltoutput.dtx v1.1v
\@unusedoptionlist: made only preamble 1055	\@testfp: remove \global before \@test... 1250
1996-07-26 ltdefs.dtx v1.2y	\@xtryfc: remove \global before \@test... 1218
\@reargdef: third arg picked up by \@yargdef 85	\@ztryfc: remove \global before \@test... 1219
\renew@command: use \noexpand instead of \string 85	General: put \global into definition remove \global before \@test... 1178
use \relax in place of empty arg 85	\clearpage: add number of missing percents 1181
\renew@environment: use \relax in place of empty arg 86	1996-07-26 ltplain.dtx v1.1t
	\sh@ft: replace \dimen\z@ by \dimen@ 30

1996-07-26 ltsect.dtx v1.0u	tests . . . . .	1182
\@starttoc: removed \global before	1996-10-04 ltclass.dtx v1.0v	
\@nobreak . . . . .	\RequirePackageWithOptions: Reset	
\@xsect: Removed \global before	\@unprocessedoptions for	
\@nobreak . . . . .	/2269 . . . . .	1073
1996-07-26 ltspace.dtx v1.2p	1996-10-05 ltfiles.dtx v1.1h	
\if@nobreak: put \global inside	\clubpenalty: Added setting its	
definition . . . . .	value . . . . .	456
1996-07-27 ltfssbas.dtx v3.0q	1996-10-08 ltfntcmd.dtx v3.3u	
General: \if@inmath switch removed	\DeclareTextFontCommand: Removed	
1996-07-27 ltspace.dtx v1.2q	\check@icr when in vmode since	
General: Further documentation of	it causes various errors (see	
problems . . . . .	pr/2157) . . . . .	758
1996-07-27 ltspace.dtx v1.2r	1996-10-21 lttab.dtx v1.1i	
General: Correct documentation of	\@array: Use \set@typeset@protect	921
problems . . . . .	General: Moved the code associated	
1996-08-02 ltfloat.dtx v1.1o	with \mkpream into the group	
\@xympar: Remove \global before	provided by the box, for	
\@ignore . . . . .	robustness (latex/2183) . . . . .	920
1996-08-02 ltsect.dtx v1.0v	\multicolumn: Make \multicolumn	
\@afterheading: Removed \global	long (latex/2180) . . . . .	923
before \@nobreak . . . . .	\tabbing: Moved the \indent so that	
1996-08-02 ltspace.dtx v1.2s	the \everypar can remove it when	
\@Esphack: Remove \global before	necessary; this is needed because	
\@ignore . . . . .	the code for items in lists has	
1996-08-25 ltfssbas.dtx v3.0r	changed (see pr/22111) . . . . .	915
\nfss@catcodes: Reset the acute,	1996-10-23 ltlists.dtx v1.0m	
grave and double quote chars as	\@item: \@nobreak . . . moved into the	
well . . . . .	\everypar and not executed	
1996-09-21 ltoutput.dtx v1.1w	unconditionally, see above . . . . .	885
\@writesetup: Added	\kern . . . changed to \setbox . . .	884
\@parboxrestore and made	Added setting of \clubpenalty and	
consequent deletions: wait for the	set \@nobreakfalse only when	
howls of protest . . . . .	necessary . . . . .	885
1996-09-25 ltdirchk.dtx v1.0t	1996-10-23 ltsect.dtx v1.0x	
General: Move ltxcheck to separate file	\@xsect: Replaced \hskip . . . with	
1996-09-28 ltmiscen.dtx v1.1f	\setbox . . . as used in	
\@xobeysp: Moved to ltspace.dtx . .	\@afterheading . . . . .	974
1996-09-28 ltspace.dtx v1.2t	1996-10-24 ltboxes.dtx v1.1a	
\@xobeysp: Moved from ltmiscen.dtx	\@arrayparboxrestore: Added local	
and redefined to use	settings of flags: dangerous! . . . .	900
\nobreakspace . . . . .	\@iiminipage: Use it or lose it	
1996-09-29 ltfiles.dtx v1.1g	(@setminpage): Frank will want to	
\document: Added disabling of	lose it . . . . .	902
\@nodocument . . . . .	1996-10-24 ltfloat.dtx v1.1p	
1996-09-29 ltoutput.dtx v1.1x	\@floatboxreset: Added local	
\newpage: Checks for noskipsec and	settings of flags: dangerous! . . . .	990
inlabel added . . . . .	\@marginparreset: Added local	
1996-09-29 ltsect.dtx 1.0w	settings of flags: dangerous! . . . .	996
\@noskipsectrue: Added	\@xfloat: Added \@nodocument to	
documentation . . . . .	trap floats in the preamble . . . .	987
1996-09-30 ltoutput.dtx v1.1y	1996-10-24 ltoutput.dtx v1.1z	
\newpage: Checks for noskipsec and	\@addtocurcol: Added \@nobreak, etc	
inlabel removed pending further	as appropriate . . . . .	1224, 1230

<code>\@specialoutput</code> : Added <code>\nobreak</code> as appropriate . . . . .	1191	1996-11-04 <code>ltlists.dtx</code> v1.0q	
<code>\@topnewpage</code> : Added <code>\@nodocument</code> to trap <code>\twocolumn</code> in the preamble . . . . .	1184	<code>\@trivlist</code> : Moved check for missing item: only checked when not inlabel flag is false . . . . .	879
<code>\newpage</code> : Better checks for noskipsec and inlabel added, plus nobreak . . . . .	1182	1996-11-05 <code>ltfiles.dtx</code> v1.1i	
1996-10-25 <code>ltlists.dtx</code> v1.0n		<code>\nofiles</code> : Standard <code>\if@nobreak</code> test added . . . . .	461
<code>\endtrivlist</code> : Change <code>\indent</code> to <code>\leavevmode</code> . . . . .	880	1996-11-09 <code>ltmath.dtx</code> v1.1c	
Reset flags explicitly . . . . .	880	<code>\@ensuredmath</code> : Made long, as it was before. /2104 . . . . .	867
1996-10-25 <code>ltoutput.dtx</code> v1.2a		1996-11-18 <code>ltfssbas.dtx</code> v3.0s	
<code>\newpage</code> : Reset all flags explicitly . . . . .	1182	<code>\define@newfont</code> : (DPC) lowercase fd file names. internal/1044 . . . . .	555
1996-10-26 <code>ltlists.dtx</code> v1.0o		1996-11-18 <code>ltoutenc.dtx</code> v1.8d	
<code>\endtrivlist</code> : Correct typo . . . . .	880	General: (DPC) lowercase external file names. internal/1044 . . . . .	521
1996-10-27 <code>ltoutenc.dtx</code> v1.8c		1996-11-20 <code>fontdef.dtx</code> v2.2p	
<code>\@strip@args</code> : Removed macro . . . . .	486	General: lowercase fd and enc.def file names /1044 . . . . .	732
General: Added <code>\r A</code> . . . . .	496	1996-11-20 <code>ltvers.dtx</code> v1.0f	
Added		General: Check for old format modified /2319 . . . . .	35
<code>\textasteriskcentered</code> . . . . .	492, 503	1996-11-23 <code>ltoutenc.dtx</code> v1.8e	
Corrected syntax descriptions . . . . .	479	General: Corrected description . . . . .	479
Removed <code>\aa</code> and <code>\AA</code> . . . . .	491, 496, 498	Extended description . . . . .	480
1996-10-28 <code>ltplain.dtx</code> v1.1u		1996-11-28 <code>ltvers.dtx</code> v1.0g	
General: (CAR) More doc changes . . . . .	14	General: Check for old format modified /2319 . . . . .	35
<code>\dotfill</code> : Removed math mode . . . . .	30	1996-12-06 <code>ltdirchk.dtx</code> v1.0u	
1996-10-29 <code>ltplain.dtx</code> v1.1v		<code>\IfFileExists</code> : *** removed from various messages for GNU Make. internal/2338 . . . . .	10
<code>\dotfill</code> : Got arithmetic correct (CAR) . . . . .	30	1996-12-06 <code>ltfloat.dtx</code> v1.1r	
1996-10-29 <code>ltspace.dtx</code> v1.2u		<code>\@caption</code> : Call <code>\@setminpage</code> if needed. latex/2318 . . . . .	986
<code>\@gnewline</code> : Added macro . . . . .	439	1996-12-06 <code>ltfssini.dtx</code> v3.0h	
<code>\@no@lnbk</code> : Macro replaces <code>\@lnbk</code> and <code>\@nolnkb</code> . . . . .	437	General: (DPC) Remove *** from messages internal/2338 . . . . .	730
<code>\:</code> : Corrected and rationalised code . . . . .	437	1996-12-17 <code>ltdefns.dtx</code> v1.0w	
<code>\nolinebreak</code> : Reimplemented both using <code>\@no@lnbk</code> . . . . .	436	<code>\g@addto@macro</code> : Use <code>\begingroup</code> to save making a mathord . . . . .	112
1996-10-31 <code>ltfinal.dtx</code> v1.0z		1996-12-20 <code>ltsect.dtx</code> v1.0z	
General: Added extra <code>\lcode</code> , hoping it does no harm in T1 (pr/1969) . . . . .	1290, 1297	<code>\@dottedtocline</code> : Added <code>\nobreak</code> for latex/2343 . . . . .	981
1996-10-31 <code>ltlists.dtx</code> v1.0p		1997-01-08 <code>fontdef.dtx</code> v2.2q	
<code>\@trivlist</code> : Added check for missing item in outer list . . . . .	879	General: Use <code>\DeclareMathDelimiter</code> to set delimiter codes . . . . .	742
1996-10-31 <code>ltsect.dtx</code> v1.0y		<code>\mathparagraph</code> : Define using <code>\DeclareMathSymbol</code> . . . . .	750
General: Corrected and tidied documentation; removed long lines . . . . .	969	1997-01-08 <code>ltfiles.dtx</code> v1.1j	
1996-11-03 <code>ltplain.dtx</code> v1.1w		<code>\@include</code> : reset <code>\deadcycles</code> latex/2365 . . . . .	465
<code>\dotfill</code> : Saved tokens by using <code>\hb@xt@</code> . . . . .	30		
1996-11-04 <code>lterror.dtx</code> v1.2m			
<code>\@nodocument</code> : Always define <code>\@nodocument</code> in kernel, so that it can be cleared by <code>\document.</code> . . . . .	407		

1997-01-08 ltmath.dtx v1.1d	1997-05-29 ltlogos.dtx v1.1f
<code>\root</code> : (DPC) Remove spurious space tokens from plain <code>T<sub>E</sub>X</code> definition /2359 ..... 855	<code>\LaTeXe</code> : Added <code>\m@th</code> so that the $\text{\LaTeX 2\epsilon}$ logo works with non-zero values of <code>\mathsurround</code> . .... 453
1997-02-05 ltdefns.dtx v1.0x	1997-06-16 ltdirchk.dtx v1.0v
<code>\g@addto@macro</code> : missing percent /2402 ..... 112	General: documentation improvements mainly from internal/2520 ..... 1
1997-02-21 ltlists.dtx v1.0r	1997-06-16 ltfloat.dtx v1.1s
<code>\@item</code> : <code>\ifvoid</code> check added for <code>\noindent</code> . latex/2414 ..... 884	General: documentation fixes ..... 983
1997-03-21 ltcounts.dtx v1.1e	1997-06-16 ltfntcmd.dtx v3.3v
<code>\fnsymbol</code> : Use <code>\mathsection</code> and <code>\mathparagraph</code> . latex/2445 ... 532	General: Fix typo in documentation. 756
1997-04-14 ltfiles.dtx v1.1k	1997-08-05 ltoutenc.dtx v1.9e
<code>\document</code> : Set the document space factor defaults. latex/2404 ..... 457	General: Corrected order of arguments in <code>\UseTextSymbol</code> example. ... 479
<code>\normalsfcodes</code> : Macro added (from patch file) latex/2404 ..... 461	1997-08-29 ltoutenc.dtx v1.9f
1997-04-14 ltoutput.dtx v1.2b	General: Added OT4 encoding, provided by Marcin Woliński. .. 478
<code>\@writeseup</code> : Call <code>\normalsfcodes</code> (from patch file) latex/2404 ... 1210	1997-09-09 ltdefns.dtx v1.2z
Move <code>\label</code> and <code>\index</code> (from patch file) ..... 1211	<code>\provide@command</code> : Use <code>\begingroup</code> to avoid generating math ords if used in math mode. pr/2573 .... 87
1997-04-24 ltbibl.dtx v1.1m	1997-09-15 ltpictur.dtx v1.1g
<code>\@citex</code> : <code>\@empty</code> to avoid primitive error on empty cite keys. latex/2432 ..... 1011	<code>\@getcirc</code> : Warn if lines become invisible pr/2524 ..... 954
1997-04-30 ltoutenc.dtx v1.9a	<code>\@picture@warn</code> : Macro added pr/2524 ..... 954
General: Changed <code>\textsc</code> to <code>\scshape</code> ..... 493	<code>\@sline</code> : Warn if lines become invisible pr/2524 ..... 943
Introduced <code>\textcopyright</code> and modified <code>\copyright</code> ..... 492	1997-10-06 ltcounts.dtx v1.1f
Introduced <code>\textcopyright</code> and modify <code>\copyright</code> ..... 493	<code>\@Roman</code> : Change <code>\@Roman</code> to be fully expandable, so that the result is written properly to files. .... 533
Modified <code>\textunderscore</code> , removing <code>\mathunderscore</code> .... 492	<code>\@slowromancap</code> : Macro added. ... 533
Modified <code>\underscore</code> , removing <code>\mathunderscore</code> ..... 493	1997-10-08 ltlogos.dtx v1.1h
1997-04-30 ltoutenc.dtx v1.9b	<code>\LaTeX</code> : Simplify macro (force loading of suitable math fonts once). ... 453
General: Added <code>\leavevmode</code> to <code>\textunderscore</code> ..... 492	1997-10-10 ltclass.dtx v1.0y
1997-05-04 ltoutenc.dtx v1.9c	<code>\endfilecontents</code> : <code>\@currenvir</code> in banner ..... 1089
General: Added ‘hex index tabs’ ... 500	<code>\reserved@c</code> not <code>\verbatim@out</code> to save a csname ..... 1088
Added TS1 encoding v2.2.beta .. 506	Check for text before or after <code>\end</code> environment. latex/2636 ..... 1089
1997-05-07 ltoutenc.dtx v1.9d	Use <code>\@gobbletwo</code> ..... 1088
General: Added <code>\leavevmode</code> to <code>\textcompwordmark</code> ..... 492	1997-10-17 ltfntcmd.dtx v3.3w
1997-05-07 ltspc.dtx v1.2v	<code>\check@nocorr@</code> : Check for vertical mode moved here, from <code>\DeclareTextFontCommand</code> (see PR/2646). ..... 760
<code>\newline</code> : Made completely robust. 438	<code>\DeclareTextFontCommand</code> : Reinstalled <code>\check@icr</code> as check is now done in <code>\check@nocorr@</code> (see PR/2646). ..... 758
1997-05-29 ltfstrc.dtx v3.0j	
General: Replaced <code>\</code> by <code>\MessageBreak</code> , as suggested by Donald Arseneau. .... 640	

1997-10-20 ltfinal.dtx v1.1a	Added section. . . . .	521
\@uclclist: Removed \aa and \AA	Added textcomp.sty. . . . .	478
from \@uclclist as these are	As in OT1, Added \leavevmode at	
macros. . . . .	start of \c, otherwise the output	
	routine might be invoked within	
1997-10-21 ltdefns.dtx v1.2z1	the macro. . . . .	497
\renewcommand: Use	Changed to decimal codes in	
\beginngroup/\endgroup rather	\ooalign. . . . .	508
than braces for grouping, to avoid	Changed to decimal codes. . . . .	503
generating empty math atom. . . .	Documentation changes and	
1997-10-21 ltffsbas.dtx v3.0t	additions. . . . .	478
\define@newfont: Move	Example corrected, braces	
\makeatletter to	removed. . . . .	478
\nfss@catcodes. . . . .	Removed default settings, see next	
	section. . . . .	506
\nfss@catcodes: Moved		
\makeatletter from		
\try@load@font@shape. . . . .	1997-12-19 ltoutenc.dtx v1.9i	
1997-11-09 ltoutput.dtx v1.2c	General: Documentation corrections. . .	478
\@specialoutput: Remove incorrect	1997-12-20 fontdef.dtx v2.2s	
code: only one \@emptycol is	General: Added documentation . . .	734
needed here . . . . .	1997-12-31 ltoutenc.dtx v1.9k	
\@topnewpage: Documentation of vsize	General: Further correction . . . . .	479
check enhanced . . . . .	1998-01-12 ltoutenc.dtx v1.9k	
1997-11-13 ltffsdel.dtx v3.0f	General: Added \ProvidesPackage for	
\DeclareSymbolFont: (DPC) Really	textcomp.sty . . . . .	478
update \group@list don't leave	Adding missing braces and	
new version in \toks@. latex/2661	\ushape. . . . .	508
\stepcounter: (DPC) Remove as	1998-01-16 ltoutenc.dtx v1.9m	
never used. (Re)defined in	General: fixed decimal codes.	
ltxcounts . . . . .	latex/2734 . . . . .	503
1997-11-19 ltfloat.dtx v1.1t	1998-03-04 ltdefns.dtx v1.2z2	
\@footnotetext: Missing percent,	\@xargdef: Unnecessary	
again . . . . .	\expandafter removed: pr/2758 . .	83
1997-11-19 ltoutput.dtx v1.2d	1998-03-05 ltoutenc.dtx v1.9n	
\@vtryfc: Reindent code, to be	General: Added masc/fem ords as in	
understandable(DPC). . . . .	pr/2579 . . . . .	493
1997-11-20 ltffsdel.dtx v3.0g	1998-03-20 ltdefns.dtx v1.2z3	
\document@select@group: (DPC)	\@thirdoffthree: Macro added . . . .	88
inline use of \stepcounter (faster,	1998-03-20 ltoutenc.dtx v1.9o	
and saves a csname per math	General: Documentation added about	
version as no reset list) . . . . .	order of decls . . . . .	481
\select@group: (DPC) inline use of	Documentation added for pr/2783	480
\stepcounter (faster, and saves a	\UndeclareTextCommand: Macro added	
csname per math version as no	for pr/2783 . . . . .	489
reset list) . . . . .	1998-03-20 lttextcomp.dtx v1.9o	
1997-11-23 ltoutenc.dtx v1.9g	General: Added various	
General: Use \textperthousand,	\UndeclareTextCommand	
\textpertenthousand and	declarations for pr/2783 . . . . .	793
\textfractionsolidus not	Load decls after defaults for speed.	793
\textpermill, \textpertenmill	1998-03-21 ltclass.dtx v1.0z	
and \textfraction. /2673 . . . .	General: Added to documentation of	
1997-12-17 ltoutenc.dtx v1.9h	filecontents . . . . .	1050
General: Added \textperthousand	1998-03-21 ltclass.dtx v1.1a	
and \textpertenthousand . . . .	\@providesfile: Allow &.	
Added code for textcomp.sty. . . .	Internal/2702 . . . . .	1066

General: Correct to new onlypreamble command list . . . . .	1103	1998-07-06 lttab.dtx v1.1l	General: Small correction to documentation . . . . .	908
1998-03-25 ltffssbas.dtx v3.0u		1998-08-17 ltboxes.dtx v1.1e	General: (RmS) Minor Documentation fixes. . . . .	889
\showhyphens: Suppress unnecessary error when used in preamble . . .	565	1998-08-17 ltclass.dtx v1.1c	General: (RmS) Minor documentation fixes. . . . .	1050
1998-04-11 fontdef.dtx v2.2t		1998-08-17 ltdirchk.dtx v1.0w	General: (RmS) Documentation improvements. . . . .	1
General: Added \mathring accent (pr2785) . . . . .	748	1998-08-17 ltftcmd.dtx v3.3x	General: (RmS) Minor documentation fixes. . . . .	756
1998-04-15 fontdef.dtx v2.2u		1998-08-17 ltffssbas.dtx v3.0v	General: (RmS) Documentation fixes. . . . .	538
General: Use new syntax for \DeclareMathDelimiter . . . . .	742	1998-08-17 ltffssdcl.dtx v3.0i	General: (RmS) Corrected minor glitches in changes entries. . . . .	669
1998-04-15 ltffssdcl.dtx v3.0h		1998-08-17 ltffssini.dtx v3.0i	General: (RmS) Minor documentation fixes. . . . .	702
\@xxDeclareMathDelimiter: Macro added (pr/2662) . . . . .	694	1998-08-17 ltlogos.dtx v1.1i	General: (RmS) Minor documentation fixes. . . . .	453
1998-04-17 fontdef.dtx v2.2v		1998-08-17 ltmath.dtx v1.1c	General: (RmS) Minor documentation fixes. . . . .	853
General: Reinsert symbol defs for < and > chars. . . . .	742	1998-08-17 ltmiscen.dtx v1.1g	General: (RmS) Minor documentation fixes. . . . .	828
1998-04-18 fontdef.dtx v2.2w		1998-08-17 ltspc.dtx v1.2w	General: Documentation fixes. . . . .	433
General: Reinsert symbol def for / char. . . . .	742	1998-08-17 preload.dtx v2.1g	General: (RmS) Minor documentation fixes. . . . .	753
1998-05-07 ltclass.dtx v1.1b		1998-09-19 ltoutenc.dtx v1.9r	\a: Added \string (pr/2878) . . . . .	491
\@onefilewithoptions@clashchk: Modify help message for latex/2805 . . . . .	1080	1998-11-13 lttab.dtx v1.1m	\@array: Check for hmode to see if something went wrong during parsing (pr/2884) . . . . .	921
1998-05-18 lttab.dtx v1.1j		1999-01-05 fontdef.dtx v2.2x	General: Need special protection for character > in \changes entry. . .	732
\@endpbox: Use \setlength to set \hsize, so that the changes in the calc package apply here. . . . .	931	1999-01-06 ltffssbas.dtx v3.0w	\DeclareFontEncoding: Added \LastDeclaredEncoding to support cyrillic integration (pr/2988) . . . . .	542
\tabular*: Use \setlength, so that calc extensions apply. . . . .	920		\LastDeclaredEncoding: Added \LastDeclaredEncoding to	
1998-05-20 ltfinal.dtx v1.1b				
General: Set up lccodes before loading hyphenation files: pr/2639 . . . .	1289			
Set up uc/lccodes after loading hyphenation files: pr/2639 . . . .	1297			
1998-05-28 lterror.dtx v1.2n				
\@notdefinable: Added message re 'end...' pr/1555 . . . . .	407			
1998-06-04 ltboxes.dtx v1.1c				
\@rule: Support calc-expressions . .	905			
1998-06-12 ltoutenc.dtx v1.9p				
General: Corrected 130 and 131, see pr/2834 . . . . .	508			
Renamed \textmacron pr/2840 . .	509			
1998-06-12 ltoutenc.dtx v1.9q				
\add@accent: Explicitly set \spacefactor after \accent (pr/2877) . . . . .	485			
1998-06-12 lttextcomp.dtx v1.9p				
General: Renamed \textmacron pr/2840 . . . . .	789			
1998-06-18 lttab.dtx v1.1k				
General: Small addition to documentation . . . . .	908			

support cyrillic integration (pr/2988) . . . . .	542	1999-04-29 ltdefs.dtx v1.3f <code>\@yargd@f</code> : Full expansion and conversion needed for digit in new version, see pr/3013 . . . . .	83
1999-01-06 ltoutenc.dtx v1.9r <code>\@strip@args</code> : New impl for latex/2930 . . . . .	487	New macro added . . . . .	83
General: Minor documentation fix. . .	508	1999-06-10 ltoutenc.dtx v1.9u General: Ensure that we also forget old options (pr/2888) . . . . .	524
1999-01-07 ltdefs.dtx v1.3a <code>\@ifnextchar</code> : made long . . . . .	108	1999-06-12 ltoutenc.dtx v1.9v General: Extend <code>\@uclclist</code> only once . . . . .	523
<code>\@newenvb</code> : made long and brace optional arg. latex/2896 . . . . .	86	1999-10-09 ltmath.dtx v1.1e <code>\active@math@prime</code> : Macro added, see PR 3104. . . . .	860
<code>\@testopt</code> : made long and brace optional arg. latex/2896 . . . . .	83	<code>\prime@s</code> : Introduce <code>\active@math@prime</code> . . . . .	860
1999-01-07 ltdefs.dtx v1.3b <code>\@ifnextchar</code> : extra <code>\long</code> . latex/2902 . . . . .	108	1999-10-09 ltoutput.dtx 1.2f <code>\@activechar@info</code> : Reset definition of active prime character (used in math mode) . . . . .	1207
1999-01-07 ltoutenc.dtx v1.9r General: Hackery to allow using fontenc several times . . . . .	524	1999-10-28 ltoutenc.dtx v1.9w <code>\add@accent</code> : Give <code>\accent@spacefactor</code> a default definition (pr/3084) . . . . .	485
Hackery to temp support cyrillic uc/lc . . . . .	522	1999-12-08 ltoutenc.dtx v1.9x General: Changed <code>\CYRRHOOK</code> and <code>\cyrrhook</code> to <code>\CYRRHK</code> and <code>\cyrrhk</code> as name changed in the cyrillic bundle for naming consistency with other “hook” glyphs. . . . .	522
1999-01-13 ltoutenc.dtx v1.9s <code>\@strip@args</code> : Simplified solution for latex/2930 . . . . .	487	2000-01-07 ltmiscen.dtx v1.1h <code>\@verbatim</code> : Disable hyphenation even if the font allows it. . . . .	846
1999-01-18 ltdefs.dtx v1.3c <code>\@yargd@f</code> : New implementation DPC /2942 . . . . .	83	2000-01-15 ltpictur.dtx v1.1i <code>\@upvector</code> : Removed space at end-of-line, CAR . . . . .	946
1999-02-09 ltdefs.dtx v1.3d <code>\@yargd@f</code> : catch bad argument forms by re-inserting #3 . . . . .	83	2000-01-30 ltfntcmd.dtx v3.3y <code>\DeclareTextFontCommand</code> : Use <code>\hmode@bgroup</code> now (pr/3160) . .	758
1999-02-12 lttextcomp.dtx v3.0j <code>\legacyoldstylenums</code> : Use <code>\rmdefault</code> instead of <code>cmm</code> (pr/2954) . . . . .	765	2000-01-30 ltoutenc.dtx v1.9y General: Use <code>\hmode@bgroup</code> where applicable (pr/3160) . . . . .	495–497, 503–506, 508
1999-02-24 ltoutenc.dtx v1.9t General: Corrected hackery cyrillic uc/lc list . . . . .	522	<code>\add@accent</code> : Use <code>\hmode@bgroup</code> where applicable (pr/3160) . . . .	485
1999-03-01 ltdefs.dtx v1.3e <code>\@ifnextchar</code> : remove extra <code>\long</code> . internal/2967 . . . . .	108	<code>\hmode@bgroup</code> : Macro added . . . .	485
1999-04-15 ltpictur.dtx v1.1h <code>\@getlarrow</code> : Replaced octal number, CAR . . . . .	945	2000-01-30 ltoutenc.dtx v1.9z <code>\@use@text@encoding</code> : Macro reimplemented (pr/3160) . . . . .	488
<code>\@upvector</code> : Replaced octal number, CAR . . . . .	946	<code>\add@accent</code> : Macro reimplemented (pr/3160) . . . . .	485
General: Replaced octal number, CAR . . . . .	945, 946	<code>\hmode@start@before@group</code> : Macro added (pr/3160) . . . . .	489
Replaced octal numbers, CAR . .	933		
1999-04-19 ltfloat.dtx v1.1u <code>\caption</code> : Made caption an error outside a float: latex/2815 . . . .	986		
1999-04-27 ltboxes.dtx v1.1f <code>\@parboxto</code> : (CAR) Changed <code>\@empty</code> to <code>\relax</code> as flag for natural width: pr/2975 . . . . .	899		

2000-05-19 ltmiscen.dtx v1.1i	2001-02-16 ltxref.dtx v1.1k
\enddocument: Reset \AtEndDocument for latex/3060 . . . . .	\@newl@bel: Added an extra grouplevel (PR3250), jlb . . . . .
2000-05-26 ltpage.dtx v1.0j	2001-05-25 ltclass.dtx v1.1d
\@markright: Reimplementation to fix expansion error (pr/3203). . . . .	\@providesfile: Explicitly set catcode of \endlinechar to 10 (pr/3334) . . . . .
\leftmark: Use \@empty instead of brace group (pr/3203). . . . .	2001-05-25 ltdirchk.dtx v1.0x
\markright: Reimplementation to fix expansion error (pr/3203). . . . .	General: Explicitly set catcode of \endlinechar to 10 (pr/3334) . . . . .
\rightmark: Use \@empty instead of brace group (pr/3203). . . . .	2001-05-28 ltoutenc.dtx v1.93
2000-06-02 ltpage.dtx v1.0k	General: Added composites for compatibility with T1, pr/3295 . . . . .
\@markright: Small adjustment to give slightly less expansion, CAR . . . . .	Changed the effect of \.i, pr/3295 . . . . .
\markright: Small adjustment to give slightly less expansion, CAR . . . . .	2001-06-02 fontdef.dtx v2.2y
Tidied 1.0j reimplementation, CAR . . . . .	General: Provide default cfg files (pr/3264) . . . . .
2000-07-11 ltmiscen.dtx v1.1j	2001-06-04 fontdef.dtx v2.2z
\@enddocument@kernel@warnings: Fix typo in warning . . . . .	General: Guard against math active equal and pipe sign in \models (pr/3333) . . . . .
2000-07-12 ltoutput.dtx 1.2g	Guard against math active equal sign in \Relbar (pr/3333) . . . . .
General: Ensure that rule is in \normalcolor . . . . .	2001-06-04 ltclass.dtx v1.1e
2000-07-19 ltoutput.dtx v1.2h	\@providesfile: But only if it is a char (pr/3334) . . . . .
\@writsetup: Reset and restore \@if@newlist for internal/3231 . . . . .	2001-06-04 ltdirchk.dtx v1.0y
2000-08-23 ltfinal.dtx v1.1c	General: But only if it is a char (pr/3334) . . . . .
General: Fix typo in warning . . . . .	2001-06-04 ltpictur.dtx v1.1j
2000-08-30 ltoutenc.dtx v1.9l	\@sline: Don't warn for exactly zero pr/3318 . . . . .
\@use@text@encoding: Rearranged but no change to final code, CAR (pr/3160) . . . . .	2001-06-04 ltvers.dtx v1.0i
\add@accent: Rearranged but no change to final code, CAR (pr/3160) . . . . .	General: Check for old format disabled . . . . .
2000-09-01 ltfinal.dtx v1.1d	2001-06-05 ltoutenc.dtx v1.94
\errhelp: Set error help empty at very end (pr/449 done correctly). . . . .	General: Text composite Commands need kludges for ‘, – see tlb1903.lvt . . . . .
2000-09-24 ltfloat.dtx v1.2b	2001-08-26 ltclass.dtx v1.1f
\end@dblfloat: FMI: use output routine to defer float . . . . .	\@providesfile: Readded setting of space char (pr/3353) . . . . .
2000-09-24 ltoutput.dtx v1.2b	2002-02-24 ltplain.dtx v1.1x
\@docclearpage: FMI: ensure \docclearpage is called again until all floats are output. . . . .	\loggingall: Macro added . . . . .
2000-09-24 ltoutput.dtx v1.2n	\loggingoutput: Macro added . . . . .
\@addtocurcol: FMI: test for wide float was in wrong place . . . . .	\showoutput: Use newly added \loggingoutput . . . . .
2001-01-07 ltoutput.dtx v1.2j	\tracingall: Use newly added \loggingoutput . . . . .
\@writsetup: And do it in the right macro (pr/3286) . . . . .	2002-06-16 ltoutenc.dtx v1.95
	General: Added \textbardbl (pr/3400) . . . . .
	Added default for \textbardbl (pr/3400) . . . . .

2002-06-17 ltoutenc.dtx v1.95	2004-01-03 ltoutenc.dtx v1.99b
General: Corrected <code>\c</code> for T1	General: Added <code>\textogonekcentered</code>
(pr/3442) . . . . . 497	(pr/3532) . . . . . 497
Definition of <code>\textexclamdown</code>	Added composites for <code>\k</code> (pr/3532) 502
changed (pr/3368) . . . . . 495	Use <code>\ooalign</code> for <code>\k</code> (pr/3532) . . 497
Definition of <code>\textquestiondown</code>	2004-01-04 ltbibl.dtx v1.1p
changed (pr/3368) . . . . . 495	<code>\nocite</code> : Changed error message . 1012
2002-06-18 ltoutenc.dtx v1.95	2004-01-04 ltoutenc.dtx v1.99c
General: Changed def for	General: More adjustments for ogonek
<code>\textregistered</code> to avoid small	(pr/3532) . . . . . 497
caps (pr/3420) . . . . . 493	2004-01-23 ltdefs.dtx v1.1g
2002-10-01 ltfloat.dtx v1.1v	<code>\@newenvva</code> : Use kernel version of
<code>\thempfootnote</code> : Use braces around	<code>\@ifnextchar</code> (pr/3501) . . . . . 86
<code>\itshape</code> to keep font change local	<code>\@testopt</code> : Use kernel version of
(pr/3460). . . . . 1000	<code>\@ifnextchar</code> (pr/3501) . . . . . 83
2002-10-02 ltfssbas.dtx v3.0x	<code>\@xargdef</code> : Use kernel version of
<code>\DeclareFontSubstitution</code> : Adding	<code>\@ifnextchar</code> (pr/3501) . . . . . 82
<code>\LastDeclaredEncoding</code>	<code>\@xdblarg</code> : Use kernel version of
introduced a bug as on some	<code>\@ifnextchar</code> (pr/3501) . . . . . 109
occasions that macro name was	2004-01-23 ltdefs.dtx v1.3g
stored in the internal lists instead	<code>\kernel@ifnextchar</code> : Added macro
of the actual encoding. (pr/3459) 542	(pr/3501) . . . . . 108
2002-10-28 ltlists.dtx v1.0s	2004-01-28 ltclass.dtx v1.1g
<code>\endtrivlist</code> : Check for math mode	<code>\@providesfile</code> : Use kernel version of
(pr/3437) . . . . . 880	<code>\@ifnextchar</code> (pr/3501) . . . . . 1066
2002-10-28 ltoutenc.dtx v1.96	2004-01-28 ltvers.dtx v1.0k
General: coding change, to follow bug	General: Check for old format made 5
fix by DEK in plain.tex	years (pr/3601) . . . . . 35
(pr/3469) . . . . . 496, 505	2004-02-02 fontdef.dtx v2.3
2002-12-13 ltbibl.dtx v1.1n	General: Many things from here on
<code>\@citex</code> : Added <code>\leavevmode</code> in case	made robust . . . . . 746
citation is at start of paragraph	2004-02-02 ltoutenc.dtx v1.99
(pr/3486) . . . . . 1011	General: Added <code>\textbigcircle</code> . . 503
2003-01-01 ltfntcmd.dtx v3.3z	2004-02-04 fontdef.dtx v2.3a
General: Code checked and	General: Added bigtriangle synonyms
documentation extended by Chris 758	for stmaryrd . . . . . 744
2003-05-18 ltbibl.dtx v1.1o	2004-02-04 ltspaced.dtx v1.3
<code>\nocite</code> : Check if we are after	<code>\nobreakdashes</code> : Macro added . . . . 449
<code>\document</code> . . . . . 1012	2004-02-06 ltoutenc.dtx v1.99d
2003-08-27 ltpictur.dtx v1.1k	<code>\@inmathwarn</code> : New command added
<code>\@bezier</code> : added missing displacement	to fix severe bug: pr/3563 . . . . . 483
pr/3566 . . . . . 962	2004-02-07 ltoutput.dtx v1.2l
<code>\@sline</code> : check for <code>\@linechar</code> being	<code>\@doclearpage</code> : Empty kludgeins box
empty pr/3570 . . . . . 943	if necessary, pr/3528 . . . . . 1193
2003-10-13 ltfinal.dtx v1.1e	2004-02-13 ltoutenc.dtx v1.99e
General: Added extra <code>\lccode</code> for <code>\-</code>	General: Documentation fixes: typos 478
and <code>\textcompwordmark</code> . . . . . 1290	2004-02-15 ltbibl.dtx v1.1q
2003-12-16 ltoutput.dtx v1.2k	<code>\@cite@ofmt</code> : Added hook with
<code>\@makecol</code> : Ensure that <code>\@elt</code> has a	default value <code>\hbox</code> . . . . . 1013
defined state (pr/3586) . . . . . 1195	<code>\@citex</code> : Changed to use a hook with
2003-12-30 ltpictur.dtx v1.1j	default value <code>\hbox</code> . . . . . 1011
<code>\@getcirc</code> : issue warning if circle size	2004-02-15 ltspaced.dtx v1.3a
can't be met pr/3473 . . . . . 954	<code>\nobreakdashes</code> : Added spacefactor
	setting . . . . . 449

2005-07-27 ltfssdcl.dtx v3.0j		
\DeclareMathAlphabet: (MH) Make document commands robust ...	687	
\DeclareSymbolFontAlphabet: (MH) Make document commands robust	699	
\new@mathalphabet: (MH) Make document commands robust ...	688	
\non@alpherr: (MH) Change because command is now properly robust	673	
\SetMathAlphabet: (MH) Make document commands robust ...	688	
2005-09-27 ltoutenc.dtx v1.99g		
General: Replace \sh@ft by \ltx@sh@ft	495, 497, 504	
2005-09-27 ltplain.dtx v1.1y		
\ltx@sh@ft: New macro	30	
\sh@ft: Macro no longer used but left for compatibility	30	
2005-11-08 ltoutenc.dtx v1.99h		
General: Added \ij and \IJ from babel. (pr/3771)	492, 496, 498	
2005-11-10 ltmath.dtx v1.1g		
\l: (MH) Fixed potential problem in \l (pr/3399).	861	
General: (MH) Minor documentation fixes.	853	
2006-05-18 ltboxes.dtx v1.1g		
\@parboxto: Ensure \@parboxto holds the value of \@tempdimb not the register itself (pr/3867)	899	
2006-09-13 ltoutput.dtx v1.1m		
General: Ensure that rule is in \normalcolor	1257	
2007-08-05 ltclass.dtx v1.1h		
\@fileswithoptions: Prevent loss of brackets PR/3965	1075	
2007-08-06 ltcntrl.dtx v1.0h		
\@fornoop: Really make defs long	399	
2007-08-31 ltfssdcl.dtx v3.0l		
\SetSymbolFont@: Font warning changed to info for encoding change (pr/3975)	686	
2009-09-24 ltvers.dtx v1.0l		
General: Stop checking for old format	35	
2009-10-20 ltfssdcl.dtx v3.0m		
\in@: More robust thanks to Heiko.	669	
2009-10-28 lttextcomp.dtx v1.99k		
General: Added Latin Modern and TeX Gyre subsets	795	
2009-11-04 lttextcomp.dtx v1.99l		
General: Added more Latin Modern and TeX Gyre subsets	795	
2009-12-14 ltfntcmd.dtx v3.4a		
\ifmaybe@ic: Macro added	761	
\maybe@ic@: Use switch \ifmaybe@ic instead of \if@tempswa	761	
\t@st@ic: Use switch \ifmaybe@ic instead of \if@tempswa	762	
2010-08-17 ltmiscen.dtx v1.1k		
\enddocument: Use braces around \input arg (pr/4124)	830	
2010-08-17 ltmiscen.dtx v1.1l		
\enddocument: Change of plan: use \@@input instead (pr/4124)	830	
2011-05-08 ltfssdcl.dtx v3.0n		
\in@: Simplified thanks to Bruno.	669	
2011-08-19 ltclass.dtx v1.1i		
\@ifclasswith: Re-jig definition after more stringent \in@ test.	1061	
2011-09-03 ltfssdcl.dtx v3.0o		
\new@mathversion: (Will) Remove \global before \newcount (unnecessary and caused etex bug).	682	
2012-01-20 ltplain.dtx v2.0b		
\loggingall: etex tracing if available	31	
2013-07-07 ltclass.dtx v1.1i		
General: Correctly describe how the date in \@ifpackagelater is used	1053	
2014-04-24 ltoutput.dtx v1.2n		
\fl@tracemessage: Renamed internal trace commands; provide as package	1246	
2014-04-27 ltfloat.dtx v1.2b		
\end@dblfloat: Inline the code to allow some coexistence with packages that hook into \end@float and do not know about the algorithm change	991	
2014-06-10 ltfloat.dtx v1.2b		
\end@dblfloat: missing \fi added	991	
2014-12-30 ltfinal.dtx v2.0a		
\newmarks: macro added	1284	
\newXeTeXintercharclass: macro added	1285	
2014-12-30 ltfloat.dtx v1.2a		
\@textsubscript: Command added (latexrelease)	1002	
\textsubscript: Command added (latexrelease)	1001	
2014-12-30 ltssbas.dtx v3.0y		
\mathgroup: move allocation to ltplain.	538	
2014-12-30 ltoutput.dtx v1.2m		
General: Command updated (latexrelease)	1257	

2014-12-30 ltplain.dtx v2.0a		<code>\@stpelt</code> : Reset all within counters in one go (latexrelease) . . . . .	527
<code>\e@alloc</code> : macro added . . . . .	18	2015-01-11 ltcounts.dtx v1.1h	
<code>\e@alloc@chardef</code> : macro added . . .	18	<code>\TextOrMath</code> : Add command to solve robustness issues (pr/3752) (latexrelease) . . . . .	534
<code>\e@alloc@top</code> : macro added . . . . .	18	2015-01-11 ltfloat.dtx v1.2b	
<code>\e@ch@ck</code> : macro added . . . . .	18	<code>\dblfloatplacement</code> : float order in 2-column (latexrelease) . . . . .	993
<code>\extrafloats</code> : macro added . . . . .	18	<code>\@xfloat</code> : Check for valid option (latexrelease) . . . . .	987
<code>\newlanguage</code> : New engine-specific allocation scheme (latexrelease) . .	17	<code>\end@dblfloat</code> : float order in 2-column (latexrelease) . . . . .	991
2014-12-30 ltspace.dtx v1.3b		2015-01-11 ltfsbas.dtx v3.0y	
<code>\@</code> : <code>\@</code> discards spaces when moving (pr3039)(latexrelease) . . . . .	450	<code>\@DeclareMathSizes</code> : Allow arbitrary units (latexrelease) . . . . .	547
2015-01-03 ltdefs.dtx v1.4a		2015-01-11 ltspace.dtx v1.3d	
<code>\typein</code> : use modified definition in luatex . . . . .	80	<code>\@Esphack</code> : Allow hyphenation (Donald Arseneau pr/3498) (latexrelease) . . . . .	442
2015-01-03 ltdirchk.dtx v1.1		<code>\@esphack</code> : Allow hyphenation (Donald Arseneau pr/3498) (latexrelease) . . . . .	441
General: Enable extra primitives when Lua <sub>T</sub> <sub>E</sub> <sub>X</sub> is used . . . . .	3	2015-01-14 ltoutput.dtx v1.2n	
2015-01-03 ltfinal.dtx v2.0a		<code>\@addtocurcol</code> : float order in 2-column (latexrelease) . . . . .	1222
General: Skip resetting codes with Unicode engines . . . . .	1297	<code>\@addtodblcol</code> : float order in 2-column (latexrelease) . . . . .	1237
Unicode data loading added . . .	1288	<code>\@addtonextcol</code> : float order in 2-column (latexrelease) . . . . .	1232
2015-01-07 ltvers.dtx v1.0n		<code>\@doclearpage</code> : Empty kludgeins box if necessary, pr/3528 . . . . .	1193
<code>\@check@IncludeInRelease</code> : macro added . . . . .	37	float order in 2-column (latexrelease) . . . . .	1192
2015-01-08 ltboxes.dtx v1.1h		<code>\@startdblcolumn</code> : float order in 2-column (latexrelease) . . . . .	1216
<code>\framebox</code> : Make Robust (latexrelease) . . . . .	897	<code>\@xtryfc</code> : float order in 2-column (latexrelease) . . . . .	1218
<code>\makebox</code> : Make Robust (latexrelease)	890	<code>\@ztryfc</code> : float order in 2-column (latexrelease) . . . . .	1219
<code>\parbox</code> : Make Robust (latexrelease)	899	2015-01-14 ltspace.dtx v1.3e	
<code>\raisebox</code> : Make Robust (latexrelease) . . . . .	905	<code>\addpenalty</code> : Avoid adding redundant skips (DPC) . . . . .	445
<code>\rule</code> : Make Robust (latexrelease) .	904	2015-01-17 ltvers.dtx v1.0m	
<code>\savebox</code> : Make Robust (latexrelease)	894	<code>\@check@IncludeInRelease</code> : modified with <code>\@currname</code> . . . . .	37
2015-01-08 ltdefs.dtx v1.4a		2015-01-19 ltvers.dtx v1.0o	
<code>\MakeRobust</code> : Added macro . . . . .	93	<code>\@check@IncludeInRelease</code> : Optional argument . . . . .	37
2015-01-08 ltlength.dtx v1.1c		2015-01-20 ltoutput.dtx v1.2m	
<code>\setlength</code> : to ensure first length argument is terminated. (latexrelease) . . . . .	536	<code>\fl@tracemessage</code> : Reset <code>\IncludeInRelease</code> flags . . . . .	1247
2015-01-08 ltmath.dtx v1.1h			
<code>\]</code> : Make Robust (latexrelease) . . . .	861		
<code>\]</code> : Make Robust (latexrelease) . . . .	861		
2015-01-09 ltfsini.dtx v3.1a			
<code>\em</code> : Allow <code>\emph</code> to produce small caps (latexrelease) . . . . .	724		
<code>\eminershape</code> : macro added (latexrelease) . . . . .	724		
2015-01-09 ltspace.dtx v1.1h			
<code>\addpenalty</code> : Donald Arseneau's fix from PR/377703 (latexrelease) . .	445		
2015-01-10 ltcounts.dtx v1.1h			
<code>\@fnsymbol</code> : Unse <code>\TextOrMath</code> (latexrelease) . . . . .	533		

2015-01-22 ltvers.dtx v1.0p	2015-02-21 ltplain.dtx v2.0e
General: Preserve any <code>\everyjob</code>	General: Removed autoload code . . . 14
material inserted by a loader ( <code>.ini</code>	2015-02-21 lttab.dtx v1.1n
file) . . . . . 36	General: Removed autoload code . . . 908
2015-01-23 ltfinal.dtx v2.0b	2015-02-21 ltvers.dtx v1.0r
<code>\newmarks</code> : use reserved count 256 . . . . . 1284	General: Removed autoload code . . . 35
<code>\newXeTeXintercharclass</code> : use	2015-02-21 ltvers.dtx v1.0w
reserved count 257 . . . . . 1285	<code>\@check@IncludeInRelease</code> : set
2015-01-23 ltplain.dtx v2.0c	<code>\@currname</code> empty here (in case
<code>\extrafloats</code> : reserve counts 256–265 . . . . . 18	<code>\IncludeInRelease</code> input early) . . . 37
2015-01-24 ltfinal.dtx v2.0c	2015-02-22 ltfscomp.dtx v3.0e
General: Skip T1-code entirely with	General: Moved all code into
Unicode engines . . . . . 1288	<code>latexrelease</code> - obsolete commands
2015-02-03 ltfinal.dtx v2.0d	are no longer automatically part of
General: Set <code>\lccode</code> for - with	the kernel . . . . . 664
Unicode engines . . . . . 1289	2015-03-02 ltplain.dtx v2.0f
2015-02-16 ltoutenc.dtx v1.99m	<code>\e@mathgroup@top</code> : macro added . . . 18
General: Added <code>\textcommabelow</code>	<code>\newlanguage</code> : allow 255 math groups
<code>latex/4414</code> . . . . . 493	in Unicode engines . . . . . 17
2015-02-16 ltoutenc.dtx v1.99n	2015-03-10 ltplain.dtx v2.0g
General: Added <code>\textcommaabove</code> . . . . . 494	<code>\hideoutput</code> : macro added . . . . . 33
Added composites for <code>ç</code> . . . . . 502	<code>\loggingall</code> : Reorganize to be less
Added composites for <code>\c</code> . . . . . 497	noisy . . . . . 31
2015-02-16 lttextcomp.dtx v1.99m	<code>\tracingnone</code> : macro added . . . . . 32
General: Added <code>lmtt</code> (Heiko Oberdiek)	2015-03-12 ltoutput.dtx v1.2m
<code>latex/4415</code> . . . . . 795	General: initialise <code>\@dbldeferlist</code>
2015-02-19 ltvers.dtx v1.0q	again . . . . . 1179
<code>\@check@IncludeInRelease</code> : Swap	2015-03-18 ltfsdcl.dtx v3.0q
argument order . . . . . 37	<code>\DeclareSymbolFont</code> : Restrict Symbol
2015-02-20 ltplain.dtx v2.0d	fonts to 0–15 . . . . . 684
<code>\loggingall</code> : Spell commands	<code>\document@select@group</code> : Introduce
correctly :-)) . . . . . 31	<code>\e@mathgroup@top</code> . . . . . 674
2015-02-21 ltdefs.dtx v1.4b	<code>\select@group</code> : Introduce
General: Removed autoload support . . . . . 78	<code>\e@mathgroup@top</code> . . . . . 672
2015-02-21 ltterror.dtx v1.2o	2015-03-26 ltfinal.dtx v2.0d
General: Removed autoload support . . . . . 400	General: Use renamed
2015-02-21 ltfiles.dtx v1.1m	<code>unicode-letters.def</code> . . . . . 1288
General: Removed autoload support . . . . . 454	2015-04-07 ltfsbas.dtx v3.1a
2015-02-21 ltfsbas.dtx v3.0z	<code>\wrong@fontshape</code> : Try loading fd file
General: Removed autoload code . . . . . 538	if family has changed . . . . . 559
2015-02-21 ltfscomp.dtx v3.0d	2015-04-28 ltfinal.dtx v2.0f
General: Removed autoload code . . . . . 664	<code>\newXeTeXintercharclass</code> : define
2015-02-21 ltfsdcl.dtx v3.0p	<code>\xe@alloc@intercharclass</code> for
General: Removed autoload code . . . . . 669	compatibility with older xelatex
2015-02-21 ltfsstrc.dtx v3.0k	initialization . . . . . 1285
General: Removed autoload code . . . . . 638	2015-05-10 ltlists.dtx v1.0t
2015-02-21 ltoutenc.dtx v1.99m	<code>\@doendpe</code> : Explicitly reset
General: Removed autoload code . . . . . 478	<code>\clubpenalty</code> before clearing
2015-02-21 ltoutput.dtx v1.2n	<code>\everypar</code> ; see also pr/0462 and
General: Removed autoload code . . . . . 1168	pr/4065 . . . . . 882
<code>\f@depth</code> : macro added( <code>latexrelease</code> ) . . . . . 1192	2015-06-19 ltfinal.dtx v2.0g
2015-02-21 ltpictur.dtx v1.1k	<code>\e@alloc@intercharclass@top</code> : Use
General: Removed autoload code . . . . . 933	–1 for first range to get contiguous
	allocation . . . . . 1285

\newmarks: Use -1 for first range to get contiguous allocation . . . . .	1284	module_warning: Function added . . .	54
2015-06-19 ltplain.dtx v2.0h		modules: Function modified . . . . .	52
General: delete spurious old definition of \newtoks . . . . .	20	create_callback: Function added . .	65
\e@alloc: extra braces in case arguments not single token . . . . .	18	provides_module: Function added . .	52
\newlanguage: Use -1 for first range to get contiguous allocation . . . . .	17	luatexbase: Table added . . . . .	52
2015-06-23 ltfinal.dtx v2.0h		2015-10-02 ltdirchk.dtx v1.2a	
General: set \patch@level in ltvers rather than in ltfinal/ltpatch . .	1301	General: Allow backing out of unprefixed names . . . . .	3
2015-06-23 ltvers.dtx v1.0t		2015-10-02 ltuatex.dtx v1.0b	
General: set \patch@level in ltvers rather than in ltfinal/ltpatch . . . . .	35	General: Fix backing out of T <sub>E</sub> X code	51
2015-08-06 ltplain.dtx v2.0i		2015-10-02 ltuatex.dtx v1.0c	
\extrafloats: Add \string in case argument is not an unexpandable primitive . . . . .	19	General: Allow backing out of Lua code . . . . .	51
2015-08-23 ltdirchk.dtx v1.2		2015-10-02 ltuatex.dtx v1.0e	
General: Do not use luatex prefix . . . .	3	uninstall: Function added . . . . .	70
2015-08-23 ltvers.dtx v1.0v		2015-10-03 ltuatex.dtx v1.0f	
General: Allow negative patchlevel for pre-release . . . . .	36	provides_module: use luatexbase_log	52
2015-08-30 ltplain.dtx v2.1a		2015-10-27 ltplain.dtx v2.1b	
\newinsert: new \newinsert implementation . . . . .	20	\extrafloats: Use global assignment when switching to extended range	19
2015-09-205 ltoutput.dtx v1.3a		2015-11-07 ltspace.dtx v1.3f	
General: extended \@freelist . . . . .	1178	\@esphack: Only space if there is no space at the end of the hlist latex/4443 . . . . .	441
2015-09-24 ltuatex.dtx v1.0a		2015-11-14 ltuatex.dtx v1.0g	
call_callback: Function added . . . . .	65	General: Track LuaT <sub>E</sub> X changes for (new)token.create . . . . .	54
callback.register: Function modified . . . . .	62	2015-11-18 ltplain.dtx v2.2a	
callback_descriptions: Function added . . . . .	69	\newlanguage: Extended stream allocation in luatex (0.85) . . . . .	17
\catcodetable@atletter: Macro added . . . . .	47	2015-11-19 ltplain.dtx v2.2b	
\catcodetable@initex: Macro added	47	\newlanguage: Only extend allocation of write streams (see luatex list) .	17
\catcodetable@latex: Macro added .	47	2015-11-27 ltuatex.dtx v1.0h	
\catcodetable@string: Macro added	47	callback_descriptions: Match test in in-callback latex/4445 . . . . .	69
add_to_callback: Function added . .	66	in_callback: Guard against undefined list latex/4445 . . . . .	69
remove_from_callback: Function added . . . . .	68	2015-11-29 ltuatex.dtx v1.0i	
new_attribute: Function added . . . .	55	General: Declare this as local before used in the module error definitions (PHG) . . . . .	52
disable_callback: Function added .	69	call_callback: Check name is not nil in error message (PHG) . . . . .	65
in_callback: Function added . . . . .	69	create_callback: Check name is not nil in error message (PHG) . . . . .	65
\newattribute: Macro added . . . . .	47	2015-12-02 ltuatex.dtx v1.0j	
\newcatcodetable: Macro added . . .	47	General: Adjust hashtokens to store the result of tex.hashtokens()), not the function (PHG) . . . . .	54
\newluabytecode: Macro added . . . .	50	Assorted typos fixed (PHG) . . . . .	44
\newluachunkname: Macro added . . .	50	Declaration/use of first_head fixed (PHG) . . . . .	53
\newluafunction: Macro added . . . .	49		
\newwhatsit: Macro added . . . . .	49		
module_error: Function added . . . . .	54		
module_info: Function added . . . . .	54		

Remove nonlocal iteration variables (PHG) . . . . .	44	<code>\DeclareMathAccent</code> : Check for <code>mathaccent</code> not <code>\mathaccent</code> . . .	690
Remove unreachable code after calls to <code>error()</code> (PHG) . . . . .	44	<code>\DeclareMathRadical</code> : Check for <code>radical</code> not <code>\radical</code> . . . . .	698
2015-12-02 ltluatex.dtx v1.0k		<code>\DeclareMathSymbol</code> : Check for <code>mathchar</code> not <code>\mathchar</code> . . . . .	693
General: resolve name and <code>i.description</code> (PHG) . . . . .	63	2016-03-13 ltluatex.dtx v1.0n	
<code>call_callback</code> : Give more specific error messages (PHG) . . . . .	65	General: contribute <code>_filter</code> added . . . . .	61
<code>add_to_callback</code> : Give more specific error messages (PHG) . . . . .	66	<code>insert_local_par</code> added . . . . .	61
<code>remove_from_callback</code> : adjust initialization of <code>cb local</code> (PHG) . .	68	2016-03-29 ltpictur.dtx v1.1l	
Give more specific error messages (PHG) . . . . .	68	<code>\@oval</code> : add setting of line tests . . . . .	955, 956
<code>create_callback</code> : Give more specific error messages (PHG) . . . . .	65	initialise tests . . . . .	955
2015-12-10 ltfinal.dtx v2.0i		<code>\@ovhorz</code> : use glue not leaders if horizontal line not required . . . .	958
General: Use new common Unicode data loaders . . . . .	1288	<code>\@ovvert</code> : use glue not leaders if vertical line not required . . . . .	957
2015-12-18 ltluatex.dtx v1.0l		<code>\if@ovhline</code> : macro added (latex/4452) . . . . .	955
General: Load Unicode data from source . . . . .	47	<code>\if@ovvline</code> : macro added (latex/4452) . . . . .	955
2016-01-04 ltfinal.dtx v2.0j		2016-04-22 ltfinal.dtx v2.0q	
General: Do not set up inter character classes for XeTeX . . . . .	1288	<code>\e@alloc@intercharclass@top</code> : XeTeX 0.99996 has 4096 char classes not 256 . . . . .	1285
<code>\e@alloc@intercharclass@top</code> : Start allocation at one not three . . . .	1285	2016-06-19 ltoutenc.dtx v1.99m	
2016-01-05 ltfinal.dtx v2.0k		General: OT1 definition (was duplicate T1 definition) . . . . .	497
<code>\e@alloc@intercharclass@top</code> : Remove duplicated code . . . . .	1285	2016-06-20 ltclass.dtx v1.1j	
2016-01-05 ltfinal.dtx v2.0l		General: don't declare as <code>\@onlypreamble</code> . . . . .	1061
General: Correct <code>latexrelease</code> guards . . . . .	1288	2016-07-29 ltplain.dtx v2.2c	
Ensure old definitions for inter-character class toks are available using <code>latexrelease</code> . . . .	1288	<code>\extrafloats</code> : use <code>\global \chardef</code> . . . . .	19
Missing brace . . . . .	1288	<code>\newinsert</code> : fix for <code>tlb-newinsert-001</code> . . . . .	20
2016-01-05 ltfinal.dtx v2.0m		2016-10-02 ltclass.dtx v1.2a	
General: Undefine XeTeX classes when using patching an older kernel . .	1288	<code>\@ifclasswith</code> : Ignore spaces while checking for option clash . . . . .	1061
2016-01-05 ltfinal.dtx v2.0p		<code>\ExecuteOptions</code> : Ignore spaces in argument . . . . .	1071
General: Only apply XeTeX change if XeTeX is in use . . . . .	1288	2016-10-15 ltdirchk.dtx v1.2b	
2016-02-11 ltluatex.dtx v1.0m		General: Require eTeX . . . . .	3
General: <code>pdf_stream_filter_callback</code> removed . . . . .	62	2016-10-15 lterror.dtx v1.2p	
<code>process_rule</code> , <code>[hv]pack_quality</code> <code>append_to_vlist_filter</code> added . . .	61	General: Require eTeX . . . . .	400
<code>read_cidmap_file</code> added . . . . .	60	2016-10-15 ltfinal.dtx v2.0r	
<code>show_warning_message</code> added . . .	61	General: Require eTeX . . . . .	1284
<code>token_filter</code> removed . . . . .	61	2016-10-15 ltfinal.dtx v2.0s	
2016-02-18 ltffsdcl.dtx v3.0r		General: Tidy up status of char 127 . . . . .	1284
<code>\@DeclareMathDelimiter</code> : Check for <code>delimiter</code> not <code>\delimiter</code> . . . . .	695	2016-10-15 ltffssini.dtx v3.1b	
		General: Require eTeX . . . . .	702
		2016-10-15 ltplain.dtx v2.2d	
		General: Require eTeX . . . . .	14
		2016-10-16 ltplain.dtx v2.3a	
		<code>\newlanguage</code> : Allow languages up to 16383 in luatex . . . . .	17

2016-10-19 ltcounts.dtx v1.1j		declare composites with empty base	
\TextOrMath: Test directly for		for hat and tilde, use same slots for	
\protected	534	\textasciicircum ans	
2016-11-06 ltplain.dtx v2.3b		\textasciitilde	510
General: Drop \outer entirely	14	declare straight quotes using new	
2016-11-09 ltclass.dtx v2.1b		\remove@tlig command	510
\@fileswithoptions: Improve \ifx		2017-02-22 ltoutenc.dtx v2.0g	
tests PR/4497	1075	General: Fix typo introduced at 2.0f	510
2016-11-17 ltluatex.dtx v1.0p		2017-02-24 ltoutenc.dtx v2.0h	
General: call_edit added	61	General: introduce	
2016-12-03 fontdef.dtx v3.0a		\DeclareUnicodeAccent	510
General: (DPC) Default to TU		\DeclareTextCompositeCommand: add	
encoding for Unicode TeX engines	734	check whether the accent command	
\shapedefault: (DPC) Default to TU		is defined for this encoding	486
encoding for Unicode TeX engines	738	2017-03-08 ltclass.dtx v1.2c	
2016-12-04 ltoutenc.dtx v2.0a		General: add \@parse@version@dash	
General: Added TU encoding	510	to support yyyy-mm-dd as well as	
2017-01-01 ltoutput.dtx v1.3b		yyyy/mm/dd	1061
General: make fpmin negative so		2017-03-09 ltfinal.dtx v2.0t	
ignored even if float height is		\l@nohyphenation: ensure	
negative	1256	\l@nohyphenation is defined.	1291
2017-01-10 ltfssbas.dtx v3.2a		2017-03-09 ltmiscen.dtx v1.1m	
\showhyphens: Add version of		\@verbatim: Use \language not	
\showhyphens that works with		\hyphenchar	846
XeTeX.	565	\verb: Use \language to stop	
2017-01-23 ltoutenc.dtx v2.0b		hyphenation	851
General: Added TU specific commands		2017-03-10 ltfiles.dtx v1.1n	
in ASCII range pr/4500	510	\document: Save language default	457
2017-01-24 ltoutenc.dtx v2.0c		2017-03-10 ltoutput.dtx v1.3c	
General: Declare TU composites for i		\@writersetup: Reset \language	1208
and j	510	2017-03-13 ltdefs.dtx v1.5a	
Make \textasteriskcentered		\ -: Define \- in terms of \hyphenchar	110
U+2217 not U+204E	510	2017-03-27 ltdefs.dtx v1.5b	
TeX ligature syntax for xetex and		\@dischyph: Define \@dischyph after	
luatex reversed	510	\ -	110
2017-01-24 ltoutenc.dtx v2.0d		2017-03-28 ltluatex.dtx v1.1e	
General: Declare macron composites		General: glyph_stream_provider	
for YyGg	510	added	61
2017-02-12 ltoutenc.dtx v2.0e		2017-03-29 ltboxes.dtx v1.3a	
General: Declare fallback code for		\@arrayparboxrestore: Reset	
\textasteriskcentered	510	\lineskiplimit	901
2017-02-18 ltluatex.dtx v1.1c		2017-04-05 ltoutenc.dtx v2.0i	
new_attribute: Parameterize count		\DeclareTextCompositeCommand:	
used in tracking	55	Declare accent command if not	
new_bytecode: Parameterize count		already declared when declaring a	
used in tracking	56	composite.	486
new_chunkname: Parameterize count		2017-04-10 ltplain.dtx v2.3c	
used in tracking	56	\newlanguage: Correction to code to	
new_whatst: Parameterize count used		skip write18 in luatex	17
in tracking	56	2017-04-11 ltoutput.dtx v2.4a	
2017-02-19 ltoutenc.dtx v2.0f		\newpage: account for the depth of the	
General: add \@empty to guard against		last row of the page	1182
3rd argument being empty	496	2017-12-17 ltoutput.dtx v1.4b	
		\@addtonextcol: fix doc guards	1232

2018-01-06 ltdefs.dtx 1.5c	2018-05-29 ltclass.dtx v1.2j
\@ifundefined: Avoid defining	\endfilecontents: use \curname not
undefined commands to \relax . . . . . 106	\@undefined . . . . . 1090
2018-02-18 ltclass.dtx v1.2d	2018-08-11 ltoutenc.dtx v2.0j
\@ifl@ter: Added 0 up front to make	General: Provide \guillemetleft and
bad data come out as 0. . . . . 1060	\guillemetright . . . . . 499, 504, 514
General: Introduce rollback concept 1094	2018-08-18 ltluatex.dtx v1.1h
2018-03-08 ltcounts.dtx v1.1k	General: append_to_vlist_filter is
\@ifbothcounters: Interface added 529	exclusive . . . . . 61
\@removefromreset: Interface added 529	2018-08-24 ltfinal.dtx v2.1f
\counterwithin: Interface added . . 530	\document@default@language: Add to
\counterwithout: Interface added . . 531	latexrelease (github/68) . . . . . 1291
2018-03-24 ltclass.dtx v1.2e	2018-09-02 ltsect.dtx v1.1b
\pkgcls@use@this@release: Use full	\@dottedtocline: Prevent protrusion
file name for old release . . . . . 1100	( <a href="https://tex.stackexchange.com/q/172785/10109">https://tex.stackexchange.com/q/172785/10109</a> ) . . . . . 981
2018-03-25 ltfinal.dtx v2.1a	2018-09-24 fontdef.dtx v3.0b
General: default to UTF-8 . . . . . 1292	General: Start LR-mode if necessary
\UseRawInputEncoding: Macro	(gh/49) . . . . . 751
added . . . . . 1293	2018-09-24 ltmath.dtx v1.2b
2018-03-27 ltclass.dtx v1.2f	\smash: Start LR-mode if necessary
\endfilecontents: Use full file name	(gh/49) . . . . . 857
for old release . . . . . 1089	\phantom: Start LR-mode if
2018-04-06 ltfinal.dtx v2.1b	necessary (gh/49) . . . . . 856
\UseRawInputEncoding: Undo changes	2018-09-24 ltspace.dtx v1.3h
to \DeclareFontEncoding@ and	\enspace: Start LR-mode if necessary
definition of	(gh/49) . . . . . 452
\DeclareUnicodeCharacter . . . 1293	\leavevmode@ifvmode: Macro added
2018-04-07 ltfinal.dtx v2.1c	(gh/49) . . . . . 452
\UseRawInputEncoding: Undefine	2018-09-26 ltdefs.dtx v1.5e
\inputencodingname . . . . . 1293	\renew@command: Always explicitly
2018-04-08 ltclass.dtx v1.2g	generate a space after the curname
\@ifl@ter: Strip leading spaces from	and not rely on \noexpand to save
dates. . . . . 1060	tokens (gh/41) . . . . . 85
2018-04-08 ltclass.dtx v1.2h	2018-09-26 ltmiscen.dtx v1.1n
\@onefilewithoptions: Pass	\@writefile: Sometimes mask the
expanded date . . . . . 1096	endline char when writing to files
2018-04-08 ltfinal.dtx v2.1d	(gh/73) . . . . . 835
General: Delay full UTF-8 handling to	\add@percent@to@temptokena:
\everyjob . . . . . 1294	Sometimes mask the endline char
2018-04-11 ltcounts.dtx v1.1l	when writing to files (gh/73) 835
\counterwithin: Correct default	\protected@file@percent: Sometimes
(issue/38) . . . . . 531	mask the endline char when
2018-05-02 ltluatex.dtx v1.1g	writing to files (gh/73) . . . . . 835
General: find_sfd_file removed . . . . 60	2018-09-26 ltsect.dtx v1.1c
finish_synctex_callback added . . . 61	\addcontentsline: Sometimes mask
glyph_not_found added . . . . . 61	the endline char when writing to
read_sfd_file removed . . . . . 60	files (gh/73) . . . . . 978
2018-05-08 ltclass.dtx v1.2i	2018-10-10 ltspace.dtx v1.3i
\pkgcls@parse@date@arg: Make	\@esphack: Don't introduce
suspicious rollback a warning not	breakpoints if @nobreak is true
error: github issue 43 . . . . . 1098	and after sections . . . . . 441
2018-05-11 ltfinal.dtx v2.18	
General: Make invalid UTF-8 also safe,	
for legacy filesystem encodings . . 1294	

2018-10-11 ltmiscen.dtx v1.1o	font_descriptor_objnum_provider added . . . . .	61
\@@sverb: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) . . . . .	make_extensible added . . . . .	61
\@setupverbvisiblespace: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) . . . . .	new_graf added . . . . .	61
\@verbvisiblespacebox: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) . . . . .	page_objnum_provider added . . . . .	61
\asciispace: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) . . . . .	process_pdf_image_content added . . . . .	61
verbatim*: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) . . . . .	wrapup_run added . . . . .	61
\verbvisiblespace: Provide \verbvisiblespace such that it is usable in normal text (github/70) . . . . .	2019-07-01 ltclass.dtx v1.3a	
Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) . . . . .	\endfilecontents: Support UTF8 and spaces in filecontents environment file name . . . . .	1086
2018-10-21 ltuatex.dtx v1.1i	2019-07-01 ltfiles.dtx v1.2a	
new_luafunction: Function added . . . . .	\IfFileExists: Support UTF-8 . . . . .	469
2018-11-09 ltbib1.dtx LaTeX2e	\includeonly: Support UTF-8 . . . . .	462
\bibliography: Zap spaces in the argument as BibTeX doesn't support them (github/88) . . . . .	\setcurrfile: Support UTF-8 . . . . .	468
2018-11-18 ltoutenc.dtx v2.0k	2019-07-09 ltfssbas.dtx v3.2c	
General: Provide \Hwithstroke and \hwithstroke . . . . .	\DeclareErrorFont: Don't set any \f@... macros . . . . .	558
2018-11-19 ltoutenc.dtx v2.0k	2019-07-09 ltfssini.dtx v3.1c	
General: Added \Hwithstroke and \hwithstroke . . . . .	General: Explicitly set some defaults . . . . .	730
2018-11-28 ltoutput.dtx v1.4d	2019-08-22 ltxref.dtx v1.11	
\@combinedblfloats: Unbox \@outputbox to preserve boxing level (github/94) . . . . .	\labelformat: Commanded moved from varioref.sty . . . . .	812
2018-12-30 lttab.dtx v1.1p	\Ref: Commanded moved from varioref.sty . . . . .	812
\@tabclassz: Add extra \hskip to guard against an \unskip at the start of a c-column cell (gh/102) . . . . .	\refstepcounter: Allow \p@... to have an argument . . . . .	811
2019-02-07 ltfilehook.dtx v1.1o	2019-08-27 fontdef.dtx v3.0c	
\unqu@tefilef@und: Expand \@filef@und before executing second argument (github/109) . . . . .	General: Various commands made robust throughout the file . . . . .	744
2019-02-07 ltfiles.dtx v1.1o	2019-08-27 ltboxes.dtx v1.3b	
\@swaptwoargs: Helper macro added . . . . .	General: Various commands made robust . . . . .	889
2019-02-07 ltfssbas.dtx v3.2b	2019-08-27 ltclass.dtx v1.3b	
\define@newfont: Changed wording of warning (github/107) . . . . .	\endfilecontents: Make various commands robust . . . . .	1086
2019-06-18 ltuatex.dtx v1.1j	2019-08-27 ltdefs.dtx v1.5f	
General: finish_synctex_callback renamed finish_synctex . . . . .	General: Make various commands robust . . . . .	111
	\MakeRobust: Make the assignments global as we may need to apply them inside a group . . . . .	93
	2019-08-27 ltfilehook.dtx v1.2b	
	\unqu@tefilef@und: Make command robust . . . . .	1125
	2019-08-27 ltfiles.dtx v1.2b	
	\IfFileExists: Make command robust . . . . .	469
	2019-08-27 ltfssbas.dtx v3.2d	
	General: Make various commands robust . . . . .	538
	2019-08-27 ltfssdcl.dtx v3.0s	
	\DeclareMathAccent: Make math accents robust . . . . .	690

<code>\set@mathdelimenter</code> : Make math delimiters robust . . . . .	697	2019-09-11 <code>ltclass.dtx</code> v1.3c	
2019-08-27 <code>ltfssini.dtx</code> v3.1d		<code>\endfilecontents</code> : Support optional argument for filecontents . . . . .	1086
General: Make various commands robust . . . . .	702	2019-09-14 <code>ltfinal.dtx</code> v2.1h	
2019-08-27 <code>ltidxglo.dtx</code> v1.1f		<code>\@uclclist</code> : Expand UTF8 chars when case changing (github/177)	1298
General: Make <code>\index</code> and <code>\glossary</code> robust . . . . .	1006	2019-09-16 <code>ltxref.dtx</code> v1.1m	
2019-08-27 <code>ltlength.dtx</code> v1.1d		General: Correctly revert the <code>\p@...</code> change . . . . .	812
General: Make various command robust . . . . .	536	2019-09-21 <code>fontdef.dtx</code> v3.0d	
2019-08-27 <code>ltlogos.dtx</code> v1.1j		General: Distangle alias (gh/184)	745, 749
<code>\TeX</code> : Make <code>\TeX</code> command robust . . . . .	453	2019-10-02 <code>ltexpl.dtx</code> v0.0	
2019-08-27 <code>ltmath.dtx</code> v1.2c		General: Initial version . . . . .	71
General: Make various commands robust . . . . .	853	2019-10-02 <code>ltfinal.dtx</code> v2.2	
2019-08-27 <code>ltmiscen.dtx</code> v1.1p		General: Load <code>ltexpl</code> . . . . .	1302
General: Make various commands robust . . . . .	828	2019-10-02 <code>lthuatex.dtx</code> v1.1k	
<code>\begin</code> : Make command robust . . . . .	837	General: <code>linebreak_filter</code> is <b>exclusive</b>	61
<code>\end</code> : Make command robust . . . . .	839	<code>mlist_to_hlist</code> is <b>exclusive</b> . . . . .	61
2019-08-27 <code>ltoutput.dtx</code> v1.4e		<code>process_rule</code> is <b>exclusive</b> . . . . .	61
<code>\@begindvibox</code> : Make <code>\AtBeginDvi</code> robust . . . . .	1179	2019-10-07 <code>lttab.dtx</code> v1.1q	
2019-08-27 <code>ltpage.dtx</code> v1.0l		<code>\extracolsep</code> : This needs to expand	920
General: Make various commands robust . . . . .	1045	2019-10-11 <code>ltfiles.dtx</code> v1.2c	
2019-08-27 <code>ltpictur.dtx</code> v1.1m		<code>\set@curr@file</code> : Remove one brace group . . . . .	468
General: Make various commands robust . . . . .	933	2019-10-11 <code>ltsfstrc.dtx</code> v3.0l	
Remove several unnecessary <code>\gdef</code> definitions . . . . .	933	<code>\@font@aliasinfo</code> : Added 'alias' size function . . . . .	661
2019-08-27 <code>ltsect.dtx</code> v1.1d		2019-10-18 <code>ltclass.dtx</code> v1.3d	
General: Make various commands robust . . . . .	969	<code>\load@onefilewithoptions</code> : Initialize <code>\...-h@ok</code> only when loading the package or class (gh/198) . . . . .	1077
2019-08-27 <code>ltspace.dtx</code> v1.3j		2019-10-22 <code>lthuatex.dtx</code> v1.1j	
General: Make various commands robust . . . . .	433	General: <code>page_objnum_provider</code> and <code>process_pdf_image_content</code> classified data . . . . .	61
2019-08-27 <code>lttab.dtx</code> v1.1q		2019-10-25 <code>ltmiscen.dtx</code> v1.1q	
General: Make various commands robust . . . . .	908	<code>\add@percent@to@temptokena</code> : Allow unbalanced conditionals in #1 (gh/202) . . . . .	835
Remove several unnecessary <code>\gdef</code> definitions . . . . .	908	2019-10-26 <code>ltfiles.dtx</code> v1.2d	
2019-08-30 <code>lterror.dtx</code> v1.2q		<code>\iffileonpath</code> : quote on openin . . . . .	471
<code>\conditionally@traceoff</code> : Macro added . . . . .	410	<code>\IfFileExists</code> : don't quote name . . . . .	469
<code>\conditionally@traceon</code> : Macro added . . . . .	410	<code>\IfFileExists@</code> : quote on openin . . . . .	469
2019-09-09 <code>ltfssdcl.dtx</code> v3.0s		<code>\set@curr@file</code> : remove quotes . . . . .	468
<code>\DeclareMathSymbol</code> : Allow definition if the math symbol was a command already robust . . . . .	693	2019-11-01 <code>ltdirchk.dtx</code> v1.3a	
		<code>\filename@parse</code> : take last . not first	12
		2019-11-02 <code>ltmiscen.dtx</code> v1.1s	
		<code>\@centercr</code> : Make <code>\@centercr</code> robust (gh/203) . . . . .	842
		2019-11-02 <code>ltspace.dtx</code> v1.3k	
		<code>\@normalcr</code> : Make also <code>\@normalcr</code> robust . . . . .	437

2019-11-09 ltfiles.dtx v1.2e	2020-01-22 lttextcomp.dtx v1.0b
\set@curr@file: expand and \string	\tc@subst: The overall default is
before removing quotes ..... 468	\textcompsubstdefault not
2019-11-10 ltmiscen.dtx v1.1r	\substdefault ..... 766
\add@percent@to@temptokena: fix to	2020-01-25 fontdef.dtx v3.0f
special comment catcodes	General: Load tlenc.def last (gh/255) 734
(gh/202) ..... 835	2020-01-25 ltoutenc.dtx v2.0m
2019-11-11 ltfiles.dtx v1.2f	General: Load each encoding file only
\iffileonpath: make \@filef@und	once (gh/255) ..... 522
match quoting used on \openin . 471	2020-01-27 ltclass.dtx v1.3g
2019-11-22 ltoutenc.dtx v2.0l	\endfilecontents: Fix typo in error
General: Avoid spurious if fontenc	message ..... 1088
selects LY1 as default encoding	2020-01-28 ltclass.dtx v1.3h
(gh/199) ..... 523	\endfilecontents: Allow spaces in
2019-11-29 ltclass.dtx v1.3e	option string and display only
\@pr@videpackage: Protect package	unknown options not the whole
info text (gh/52) ..... 1064	option list (gh/256) ..... 1087
2019-12-17 fontdef.dtx v3.0e	2020-01-31 ltvers.dtx v1.1e
\mddefault: Set \bfdefault to “b” 737	General: Allow for upcoming format as
\shapedefault: Set \shapedefault	pre-release 0 ..... 36
explicitly to “n” ..... 738	2020-02-02 ltluatex.dtx v1.1l
\updefault: Set \updefault to “up” 737	General: Add reverselist callback type 64
2019-12-17 ltfntcmd.dtx v3.4c	glyph_info added ..... 61
\textssc: Macro added ..... 759	page_order_index added ..... 61
2019-12-17 ltfssbas.dtx v3.2e	post_linebreak_filter is
\usefont: Don’t call \fontseries or	reverselist ..... 61
\fontshape ..... 549	create_callback: Provide proper
2019-12-17 ltfssini.dtx v3.1e	fallbacks for user-defined callbacks
General: Provide custom series	without user-provided default
settings a la mweights ..... 703	handler ..... 65
\DeclareEmphSequence: Provide \emph	2020-02-05 ltfssini.dtx v3.1g
sequences ..... 723	\DeclareFontSeriesDefault:
2019-12-18 ltoutenc.dtx v2.0m	Clarified error text ..... 704
General: Don’t fake	Corrected misspelled csname
\textcompwordmark; take default	(gh/264) ..... 704
from T1 instead ..... 492	2020-02-05 lttextcomp.dtx v2.0n
\add@accent: Avoid code that breaks	General: Changed the package default
\accent ..... 485	to info (gh/262) ..... 784
2019-12-21 fontdef.dtx v3.0e	Ensure we are on a new format
General: Distangle alias (gh/184) 743–746	(gh/260) ..... 784
2020-01-05 ltclass.dtx v1.3f	2020-02-07 ltfssini.dtx v3.1h
\endfilecontents: Support more	\symbol: XeTeX-specific version to
write streams in LuaTeX gh/238 1086	avoid bug in maths mode. .... 726
2020-01-11 ltfssini.dtx v3.1f	2020-02-10 ltfssaxes.dtx v1.0c
\rmfamily: Streamlined	\fontseries: Switch
implementation with hook ..... 718	\if@forced@series added ..... 623
\ttfamily: Streamlined	\fontseriesforce: Switch
implementation with hook ..... 718	\if@forced@series added ..... 623
2020-01-20 ltfssdcl.dtx v3.0t	\if@forced@series: Switch
\set@mathdelimater: fix for gh/251 697	\if@forced@series added ..... 623
2020-01-20 ltoutenc.dtx v2.0n	2020-02-10 ltfssini.dtx v3.1h
General: fix for gh/251 ..... 493	\@defaultfamilyhook: Add
	\@defaultfamilyhook to
	\normalfont (gh/269) ..... 719

<code>\reset@font</code> : Add	<code>\update@series@target@value</code> : Drop
<code>\@defaultfamilyhook</code> to	surplus “m” from <code>\reserved@</code>
<code>\normalfont</code> (gh/269) . . . . . 727	(gh/291) . . . . . 709
2020-02-10 lttextcomp.dtx v1.0c	2020-02-27 ltdefns.dtx v1.5g
General: Use <code>\@tabacckludge</code> for	<code>\@gobblethree</code> : Macro added . . . . . 88
tabbing where necessary (gh/271) 770	2020-02-27 ltfssaxes.dtx v1.0d
2020-02-11 fontdef.dtx v3.0g	<code>\series@maybe@drop@one@m</code> : Drop
General: Provide value for	“m” in certain values from a fixed
<code>\@fontenc@load@list</code> (gh/273) . 734	list (gh/293) . . . . . 626
2020-02-11 ltfssini.dtx v3.1h	<code>\set@target@series</code> : Drop “m” only
General: Provide default value for	in a specific set of values (gh/293) 626
<code>\@fontenc@load@list</code> (gh/273) . 730	2020-02-27 ltfssbas.dtx v3.2g
2020-02-11 ltoutenc.dtx v2.0o	<code>\DeclareFontShape@</code> : Only “m” if the
General: Update	series value is a member of a fixed
<code>\@fontenc@load@list</code> with option	list and issue warning if doing it
list (gh/273) . . . . . 524	(gh/293) . . . . . 539
2020-02-14 ltpictur.dtx v1.1n	2020-03-02 ltexpl.dtx v1.0a
<code>\linethickness</code> : Suppress spaces	General: Don’t load expl3 if already in
following the declaration (gh/274) 938	the format (gh/295) . . . . . 71
2020-02-18 ltfssini.dtx v3.1i	2020-03-05 ltexpl.dtx v1.1
<code>\bfseries</code> : Make the <code>\ifx</code> selection	General: Load xparse.ltx if
outside of <code>\fontseries</code> argument	<code>\NewDocumentCommand</code> is not
so that it is not done several times 713	defined by expl3.ltx . . . . . 71
<code>\mdseries</code> : Make the <code>\ifx</code> selection	2020-03-06 ltboxes.dtx v1.3c
outside of <code>\fontseries</code> argument	<code>\clap</code> : Macro <code>\clap</code> added . . . . . 907
so that it is not done several times 713	2020-03-07 ltluatex.dtx v1.1m
<code>\prepare@family@series@update</code> : No	<code>remove_from_callback</code> : Do not call
series auto-update when forced	callback.register for user-defined
(gh/277) . . . . . 707	callbacks . . . . . 68
Recognize current family if it is not	2020-03-07 ltmath.dtx v1.2e
a “meta” family and auto-update	<code>\negthickspace</code> : Add <code>amsmath</code>
series using <code>\bfdefault</code> (gh/277) 708	math/text spacing commands to
2020-02-18 ltmath.dtx v1.2d	the kernel (gh/303) . . . . . 859
<code>\mathindent</code> : Make <code>\mathindent</code> a	2020-03-07 ltspace.dtx v1.3l
skip register to match <code>amsmath</code>	General: Moved <code>\thinspace</code> ,
(gh/252) . . . . . 868	<code>\negthinspace</code> and <code>\,</code> to
<code>equation</code> : Separate formula and eqn	ltmath.dtx (gh/303) . . . . . 433
number by at least a space in fleqn	2020-03-19 fontdef.dtx v3.0h
option . . . . . 869	General: Support legacy use of
2020-02-20 ltclass.dtx v1.3j	<code>\bfdefault</code> and <code>\mddefault</code>
<code>\endfilecontents</code> : Fix missing quotes	(gh/306) . . . . . 737
around file name (gh/284) . . . . 1088	2020-03-19 ltfssdcl.dtx v3.0u
2020-02-24 ltfssbas.dtx v3.2f	<code>\document@select@group</code> : fix for
<code>\DeclareFontShape@</code> : Drop surplus	(gnats/3357) . . . . . 675
“m” in series when defining	2020-03-19 ltfssini.dtx v3.1k
fontshape (gh/289) . . . . . 539	<code>\DeclareFontSeriesDefault</code> : Support
2020-02-25 ltfssini.dtx v3.1j	legacy use of <code>\bfdefault</code> and
<code>\bf@def@ult</code> : Drop surplus “m” from	<code>\mddefault</code> (gh/306) . . . . . 704
<code>\bfdef@ult</code> and <code>\mddef@ult</code>	<code>\maybe@update@bfseries@defaults</code> :
(gh/291) . . . . . 716	Support legacy use of <code>\bfdefault</code>
<code>\prepare@family@series@update</code> :	and <code>\mddefault</code> (gh/306) . . . . 713
Drop surplus “m” from	<code>\mdseries</code> : Support legacy use of
<code>\target@series@value</code> (gh/291) 708	<code>\bfdefault</code> and <code>\mddefault</code>
	(gh/306) . . . . . 713

2020-04-06 ltfssini.dtx v3.1m			
\bf@default: Hook added (gh/306)	716	\@yargarraycr: Support calc syntax	
\maybe@update@bfseries@defaults:		(gh/152)	922
Hook added (gh/306)	713	2020-04-22 ltmiscen.dtx v1.1u	
\maybe@update@mdseries@defaults:		\@sverb: Drop spaces before \verb	
Hook added (gh/306)	714	delimiter (gh/327)	849
2020-04-07 ltclass.dtx v1.3k		2020-04-22 ltoutenc.dtx v2.0p	
\IfFormatAtLeastTF: Macro added;		General: y unicode value in tuenc.def	478
also in rollback (gh/168)	1060	2020-04-29 lttextcomp.dtx v1.0d	
\load@onefile@withoptions: Use		General: Make all capital accents text	
different method to ignore		commands for hyperref (gh/332)	770
unprocessed options (gh/22)	1081	2020-05-02 ltfiles.dtx v1.2g	
\ProcessOptions*: Use different		\@include: Support spaces in	
method to ignore unprocessed		filenames by enclosing the names	
options (gh/22)	1070	of .aux-files in quotes (gh/217)	464
\RequirePackageWithOptions: Use		\includeonly: Get rid of leading and	
different method to ignore		trailing spaces from the filename	
unprocessed options (gh/22)	1073	(gh/217)	462
2020-04-09 ltfloat.dtx v1.2d		Improved support for spaces in	
\@textsubscript: Set non-zero		filenames (gh/217)	462
baseline (gh/249)	1002	Pass the filename to \@include by	
\textsubscript: Set non-zero baseline		value instead of by reference	
(gh/249)	1001	(gh/217)	462
2020-04-13 ltfssdcl.dtx v3.0v		2020-05-05 ltxref.dtx v1.1n	
\process@table: Small update for		\refstepcounter: record the counter	
speed.	680	name in \@currentcounter	810
2020-04-13 ltfssini.dtx v3.1n		2020-05-06 ltspace.dtx v1.3n	
\init@series@setup: Handling		General: Made softthyphen active in	
\seriesdefault changes (gh/315)	712	TU engines	452
\seriesdefault@kernel: Handling		2020-05-09 ltdefns.dtx v1.5j	
\seriesdefault changes (gh/315)	731	\@if@DeclareRobustCommand: Added	
2020-04-21 ltmath.dtx v1.2f		\DeclareCommandCopy (gh/239)	101
\@yeqncr: Support calc syntax		\DeclareCommandCopy: Added	
(gh/152)	866	\DeclareCommandCopy (gh/239)	98
2020-04-21 ltmiscen.dtx v1.1t		2020-05-11 ltdefns.dtx v1.5j	
\@icentercr: Support calc syntax		\@dischyph: Do not overwrite \-	
(gh/152)	843	under LuaTeX	110
2020-04-21 ltpictur.dtx v1.1o		2020-05-15 ltdefns.dtx v1.5g	
\@istackcr: Support calc syntax		\typeout: Allow \par in the argument	
(gh/152)	938	(gh/335)	78
2020-04-21 ltspace.dtx v1.3m		2020-05-19 ltfssaxes.dtx v1.0e	
\@hspace: Support calc syntax		\series@maybe@drop@one@m: Need to	
(gh/152)	451	use \edef (gh/336)	627
\@newline: Support calc syntax		2020-05-19 ltfssini.dtx v3.2a	
(gh/152)	438	\IfFontSeriesContextTF: Macros	
\@vspace@calcify: Support calc		added (gh/335)	720
syntax (gh/152)	438	2020-05-31 ltmiscen.dtx v1.1u	
\@vspacer: Support calc syntax		\centering: Added	
(gh/152)	447	\finalhyphendemerits setting	
\addvspace: Support calc syntax		(gh/247)	843
(gh/152)	444	\raggedleft: Added	
2020-04-21 lttab.dtx v1.1r		\finalhyphendemerits setting	
\@itabcr: Support calc syntax		(gh/247)	844
(gh/152)	914		

<p><code>\raggedright</code>: Added</p> <p><code>\finalhyphendemerits</code> setting (gh/247) ..... 844</p> <p>2020-06-04 <code>ltexpl.dtx</code> v1.2c</p> <p>General: Define a local version of some <math>\LaTeX</math> basic macros to support package loading ..... 71</p> <p>2020-06-04 <code>ltfinal.dtx</code> v2.2a</p> <p>General: Load <code>ltexpl</code> in <code>ltdefns</code> .. 1302</p> <p>2020-06-05 <code>ltclass.dtx</code> v1.3l</p> <p><code>\@currnamestack</code>: Added</p> <p><code>\@expl@pop@filename@@</code> ..... 1057</p> <p>Added <code>\@expl@push@filename@@</code> and <code>\@expl@push@filename@aux@@</code> . 1056</p> <p>2020-06-05 <code>ltfiles.dtx</code> v1.2h</p> <p><code>\document</code>: Added hook to load l3backend code ..... 456</p> <p>2020-06-10 <code>ltluatex.dtx</code> v1.1n</p> <p>General: Define</p> <p><code>\@gobble/\@firstofone</code> even for <math>\LaTeX</math> to allow early loading. .... 45</p> <p>2020-07-04 <code>ltoutenc.dtx</code> v2.0q</p> <p>General: Implement <code>\remove@tlig</code> in Lua<math>\TeX</math> without font reloading .. 511</p> <p>2020-07-08 <code>ltexpl.dtx</code> v1.2d</p> <p>General: Add a last-minute hook for <code>expl3</code> ..... 72</p> <p>2020-07-08 <code>ltfinal.dtx</code> v2.2b</p> <p>General: Add a last-minute hook for <code>expl3</code> ..... 1290</p> <p>2020-07-27 <code>ltmath.dtx</code> v1.2g</p> <p><code>\cases</code>: Don't make the command</p> <p><code>\long</code> (gh/354) ..... 857</p> <p><code>\matrix</code>: Don't make the command</p> <p><code>\long</code> (gh/354) ..... 857</p> <p><code>\pmatrix</code>: Don't make the command</p> <p><code>\long</code> (gh/354) ..... 857</p> <p>2020-07-27 <code>ltoutenc.dtx</code> v2.0r</p> <p><code>\@use@text@encoding</code>: Don't make the command <code>\long</code> (gh/354) .. 488</p> <p>2020-07-27 <code>ltpage.dtx</code> v1.0m</p> <p><code>\markright</code>: Don't make the command</p> <p><code>\long</code> (gh/354) ..... 1046</p> <p>2020-07-27 <code>ltpictur.dtx</code> v1.1p</p> <p><code>\linethickness</code>: Don't make the command <code>\long</code> (gh/354) ..... 938</p> <p>2020-07-27 <code>ltsect.dtx</code> v1.1e</p> <p><code>\author</code>: Don't make the command</p> <p><code>\long</code> (gh/354) ..... 969</p> <p><code>\date</code>: Don't make the command</p> <p><code>\long</code> (gh/354) ..... 969</p> <p>2020-08-01 <code>ltluatex.dtx</code> v1.1p</p> <p>General: new <code>_graf</code> is <code>exclusive</code> .... 61</p>	<p>2020-08-02 <code>ltluatex.dtx</code> v1.1q</p> <p><code>\newattribute</code>: Move reset to 0 inside conditional ..... 47</p> <p><code>\newluabytecode</code>: Move reset to 0 inside conditional ..... 50</p> <p><code>\newluachunkname</code>: Move reset to 0 inside conditional ..... 50</p> <p><code>\newluafunction</code>: Move reset to 0 inside conditional ..... 49</p> <p><code>\newwhatsit</code>: Move reset to 0 inside conditional ..... 49</p> <p>2020-08-08 <code>ltclass.dtx</code> v1.3m</p> <p><code>\endfilecontents</code>: define <code>\q@curr@file</code> directly as the quotes have already been removed (gh/220) ..... 1088</p> <p>2020-08-10 <code>ltluatex.dtx</code> v1.1r</p> <p>General: Load <code>ltluatex</code> Lua module during format building ..... 50</p> <p>2020-08-15 <code>ltpictur.dtx</code> v1.2a</p> <p><code>\@defaultunitsset</code>: Macro added . 935</p> <p>2020-08-19 <code>ltdefns.dtx</code> v1.5k</p> <p><code>\@carcube</code>: Made <code>\long</code> for</p> <p><code>\NewCommandCopy</code> ..... 81</p> <p><code>\robust@command@act</code>: Made</p> <p><code>\robust@command@act</code> (was <code>\declare@command@copy</code>) more generic ..... 97</p> <p><code>\ShowCommand</code>: Added <code>\ShowCommand</code> (gh/373) ..... 101</p> <p>2020-08-19 <code>ltexpl.dtx</code> v1.2e</p> <p>General: Add</p> <p><code>\@expl@cs@&lt;thing&gt;@spec@@N</code> for <code>\ShowCommand</code> (gh/373) ..... 75</p> <p>Add <code>\@expl@cs@to@str@@N</code> and <code>\@expl@str@if@eq@@nnTF</code> for <code>\NewCommandCopy</code> (gh/239) ..... 75</p> <p>2020-08-20 <code>ltplain.dtx</code> v2.3d</p> <p><code>\alloc@</code>: Define <code>\alloc@</code> in terms of <code>\e@alloc</code> ..... 20</p> <p>2020-08-21 <code>ltclass.dtx</code> v1.3o</p> <p>General: Integration of new hook management interface ..... 1050</p> <p>2020-08-21 <code>ltdefns.dtx</code> v1.5l</p> <p>General: Integration of new hook management interface ..... 78</p> <p>2020-08-21 <code>ltdefns.dtx</code> v1.5m</p> <p><code>\MakeRobust</code>: Make <code>\MakeRobust</code> produce the same command structure as</p> <p><code>\DeclareRobustCommand</code> ..... 93</p> <p>2020-08-21 <code>ltexpl.dtx</code> v1.2d</p> <p>General: Dropped unused command . 71</p>
--	---

2020-08-21 ltfiles.dtx v1.2i	2020-09-30 ltffssini.dtx v3.2d
General: Integration of new hook	\maybe@update@bfseries@defaults:
management interface . . . . . 454	\bfdefault@previous not
2020-08-21 ltfinal.dtx v2.2i	\bfseries@previous (gh/395) .. 713
General: Integration of new hook	\mdseries: \mddefault@previous not
management interface . . . . . 1284	\mdseries@previous (gh/395) .. 713
2020-08-21 ltffssaxes.dtx v1.0g	2020-10-01 ltclass.dtx v1.3r
General: Integration of new hook	\@pr@videpackage: Allow for package
management interface . . . . . 636	substitution . . . . . 1064
2020-08-21 ltffssini.dtx v3.2b	2020-10-01 ltsect.dtx v1.1e
\bf@def@ult: Integration of new hook	\addcontentsline: add a fourth
management interface . . . . . 716	argument for better hyperref
mdseries/defaults: Integration of	compatibility . . . . . 978
new hook management interface 718	2020-10-04 ltfiles.dtx v1.2j
\maybe@update@bfseries@defaults:	\@include: Quotes around the aux file
Integration of new hook	name removed, they are not
management interface . . . . . 713	needed and upset BibTeX
\maybe@update@mdseries@defaults:	(gh/400) . . . . . 464
Integration of new hook	2020-10-04 lthooks.dtx v1.0d
management interface . . . . . 714	General: Definition \AddToHookNext
\reset@font: Integration of new hook	was supposed to be for \AddToHook
management interface . . . . . 727	vice versa (gh/401) . . . . . 309
\rmfamily: Integration of new hook	2020-10-08 ltclass.dtx v1.3s
management interface . . . . . 718	\@currnamestack: Added missing
\ttfamily: Integration of new hook	2020/02/02 \IncludeInRelease 1056
management interface . . . . . 718	2020-10-11 ltclass.dtx v1.3t
2020-08-21 ltmiscen.dtx v1.1v	\load@onefilewithoptions: Restore
General: Integration of new hook	\@currpkg@reqd after finished
management interface . . . . . 828	loading a package file (gh/408). 1079
2020-08-21 ltoutput.dtx v1.4f	2020-10-18 ltclass.dtx v1.3t
\@begindvibox: Integration of new	\PassOptionsToClass: Drop path
hook management interface . . . 1179	from \input@path (gh/414). . . 1066
2020-08-23 ltxref.dtx v1.1o	2020-10-23 ltmiscen.dtx v1.1w
\refstepcounter: add default	\enddocument: Make
definition of \@currentcounter . 810	enddocument/afteraux one-time 830
2020-09-06 ltclass.dtx v1.3q	2020-10-26 ltmiscen.dtx v1.1x
\load@onefilewithoptions: Save	\@kernel@before@enddocument:
\@currpkg@reqd so that we don't	\enddocument should always start
lose track of package	out in vmode (gh/385) . . . . . 833
substitutions. . . . . 1079	2020-11-09 ltclass.dtx v1.3u
2020-09-06 ltdefs.dtx v1.5n	\pkgcls@rollbackdate@error:
\char@if@alph: Macro added . . . . 109	Change help text because the
2020-09-06 ltexpl.dtx v1.2f	package may have existed then —
General: Add	there is just no rollback data
\@expl@str@map@function@CNN and \@expl@char@generate@CNN	(gh/423). . . . . 1101
for \string@makeletter (gh/386) 75	2020-11-09 ltmath.dtx v1.2h
2020-09-09 ltshipout.dtx v1.0b	\negthickspace: \negmedspace and
\__shipout_picture_overlay:n:	\negthickspace have been only in
Prevent overfull box warnings	amsmath, so we need to undefine
(gh/387) . . . . . 1159	for rollback (gh/423) . . . . . 860
2020-09-26 ltfinal.dtx v2.2j	2020-11-20 ltclass.dtx v1.3u
General: Load first aid file if existing 1303	\@currpath: Macro added . . . . . 1055
	\@kernel@currpathstack: Macro
	added . . . . . 1058

<code>\load@onefile@withoptions</code> : Copy option list to the requested package. . . . .	1081	<code>\fontseries</code> : Distangle series and shape update (gh/444) . . . . .	623
<code>\PassOptionsToClass</code> : Copy option list to the requested package. . .	1066	<code>\fontshape</code> : Distangle series and shape update (gh/444) . . . . .	634
<code>\ProvidesPackage</code> : Use string comparison instead of <code>\ifx</code> . . .	1064	<code>\fontshapeforce</code> : Distangle series and shape update (gh/444) . . . . .	634
2020-11-20 ltcmd.dtx v1.0a		2020-12-04 ltfssini.dtx v3.2f	
General: Initial version derived from <code>xparse.dtx</code> . . . . .	113	General: Adjust start values for series and shape (gh/444) . . . . .	730
2020-11-20 ltfilehook.dtx v1.0d		2020-12-10 ltbibl.dtx v1.1s	
<code>\unqu@tefilef@und</code> : Move loading to <code>\@input@file@exists@with@hooks</code> and expand <code>\@filef@und</code> to avoid getting the wrong file name in the case of a substitution. . . . .	1124	<code>\nocite</code> : Delay any <code>\nocite</code> in the preamble instead of raising an error . . . . .	1012
2020-11-23 ltshipout.dtx v1.0d		2020-12-10 ltfssbas.dtx v3.2h	
<code>\__shipout_execute_cont::</code> Check for both kernel and user hook (gh/431) . . . . .	1149	<code>\usefont</code> : Drop “m” if the series value is a member of a fixed list and issue warning if doing it (gh/453) .	549
<code>\__shipout_execute_main_cont:Nmn</code> : Check for both kernel and user hook (gh/431) . . . . .	1151	2020-12-14 ltclass.dtx v1.3v	
2020-11-24 ltexpl.dtx v1.2g		<code>\@currnamestack</code> : Removed <code>\@expl@@@hook@curr@name@push@@n</code> . . . . .	1056
General: Support for roll forward (gh/434) . . . . .	73, 75	2020-12-18 ltexpl.dtx v1.2h	
2020-11-24 ltfilehook.dtx v1.0d		<code>\@kernel@after@enddocument@afterlastpage</code> : Define kernel <code>\enddocument</code> hooks early . . . . .	71
General: Support for roll forward (gh/434) . . . . .	1122	2020-12-22 ltfssaxes.dtx v1.0h	
2020-11-24 lthooks.dtx v1.0f		<code>\delayed@merge@font@series</code> : Distangle series and shape update (gh/444) . . . . .	625, 626
<code>\__hook_end_document_label_check::</code> Support for roll forward (gh/434) .	244	<code>\delayed@merge@font@shape</code> : Distangle series and shape update (gh/444) . . . . .	635
2020-11-24 ltshipout.dtx v1.0d		2020-12-22 ltfsstrc.dtx v3.0n	
General: Support for roll forward (gh/434) . . . . .	1163	<code>\selectfont</code> : Execute delayed series and shape updates (gh/444) . . .	642
<code>\AtBeginDvi</code> : Support for roll forward (gh/434) . . . . .	1163	2021-01-07 ltfilehook.dtx v1.0e	
2020-11-25 ltdefns.dtx v1.5o		General: Added rollback for this case to avoid spurious errors (part of gh/463) . . . . .	1136
<code>\@carcube</code> : Added missing latexrelease entry . . . . .	81	<code>\unqu@tefilef@und</code> : Restore <code>\CurrentFile(Path)(Used)</code> after the input (gh/464) . . . . .	1125
2020-12-02 ltluatex.dtx v1.1s		2021-01-07 lthooks.dtx v1.0h	
General: Fix return value of list callbacks . . . . .	63	<code>\__hook_strip_double_slash:w</code> : Assume hook name has at least three nonempty parts (gh/464) .	256
2020-12-03 ltfssstrc.dtx v3.0m		<code>\__hook_tl_set:cn</code> : Manually define some <code>l3tl</code> commands to work around <code>expl3</code> changes . . . . .	231
<code>\selectfont</code> : Install a hook in <code>\selectfont</code> (gh/444) . . . . .	643	2021-01-08 ltshipout.dtx v1.0f	
2020-12-04 ltfilehook.dtx v1.0d		<code>\__shipout_execute_cont::</code> Added another kernel hook for more flexibility (cf.	
<code>\undeclare@file@substitution</code> : Don’t drop file substitution commands on rollback . . . . .	1127		
2020-12-04 ltfssaxes.dtx v1.0h			
General: Reorganized the rollback data . . . . .	568		

https://github.com/pgf-tikz/pgf/issues/1960	2019-10-10 ltfloat.dtx v1.2e	
..... 1149	\@footnotetext: Explicitly run \par at the end of footnote text in preparation for paragraph hooks	1002
2021-01-10 ltshipout.dtx v1.0g		
\@kernel@after@shipout@background:		
Internal hook		
\@kernel@after@shipout@background	\document@select@group: fix for (gh/501)	675
added ..... 1153		
\RawShipout: Macro added ..... 1152	2021-02-16 ltfloat.dtx v1.2f	
2021-01-19 ltshipout.dtx v1.0h	\footref: \footref added ..... 1005	
\__shipout_run_firstpage_hook::	2021-02-17 ltoutenc.dtx v2.0t	
Handling of firstpage hook	General: Adjust values for	
altered ..... 1153	\textasteriskcentered To match TS1 definition (gh/502)	516
2021-01-21 ltclass.dtx v1.3w	Special definition for	
\@kernel@currrpathstack: Add empty entry for latexrelease ..... 1058	\textasteriskcentered when missing in TS1 (gh/502)	507
2021-01-21 ltexpl.dtx v1.3a	2021-02-18 ltclass.dtx v1.3x	
General: Move xparse rollback code to ltcmd.dtx ..... 74	\@fileswithoptions: save raw class option list (gh/85)	1075
2021-01-21 ltfinal.dtx v2.2l	\@remove@eq@value: macro added (gh/85)	1067
General: Load glyphtounicode.tex for pdfTeX ..... 1292	\@use@option: value from unused option list (gh/85)	1070
2021-01-22 ltshipout.dtx v1.0i	\OptionNotUsed: value from unused option list (gh/85)	1067
\__shipout_finalize_box:: Add pre_shipout_filter Lua callback ..... 1148	\PassOptionsToClass: save raw option lists (gh/85)	1066
2021-01-24 ltexpl.dtx v1.3a	2021-02-19 ltoutenc.dtx v2.0u	
General: Define expl3 hooks conditionally ..... 71	General: Add	
2021-01-31 ltfilehook.dtx v1.0f	\textnonbreakinghyphen,	
\@curr@file@reqd: set \protect to \string gh/481 ..... 1128	\textfiguredash and	
2021-02-03 ltfloat.dtx v1.2e	\texthorizontalbar	
\@savemarbox: Explicitly end with \par (gh/489)	(gh/404)	495, 499, 515
2021-02-04 ltboxes.dtx v1.4b	2021-02-25 ltfinal.dtx v2.2m	
\color@endbox: Always add the color groups (gh/488)	General: Improve speed of ToUnicode everyjob loading code ..... 1292	
2021-02-08 ltfilehook.dtx v1.0g	2021-03-03 ltclass.dtx v1.3y	
\unqu@tefilef@und: Undo the internal for robust \InputIfFileExists in rollback (gh/494)	\endfilecontents: Fix overwrite check for files with UTF-8 (gh/415)	1088
2021-02-08 ltmiscen.dtx v1.1y	2021-03-05 ltclass.dtx v1.3z	
\begin: Undo the internals for robust \begin and \end in rollback (gh/494)	\ProcessOptions*: modify so braces to not give errors (gh/513)	1069
2021-02-08 ltmiscen.dtx v1.1y	2021-03-12 ltfiles.dtx v1.2k	
\end\verbvisiblespace: Undo the internals for robust \begin and \end in rollback (gh/494)	\IfFileExists@: Allow unbalanced conditionals (gh/530)	469
2021-02-10 ltboxes.dtx v1.4b	2021-03-18 ltcmd.dtx v1.0b	
\@mpfootnotetext: Explicitly run \par in support for paragraph tagging ..... 903	General: Use \NewModuleRelease. . 113	
	2021-03-18 ltfilehook.dtx v1.0h	
	\__filehook_file_pop_assign:nnnn: Define	
	\g__filehook_input_file_seq to avoid losing data when rolling back.	1122

2021-03-18 ltfsaxes.dtx v1.0i		2021-04-20 ltexpl.dtx v1.3c	
General: Fix rollforward definition. . . . .	624	\@kernel@after@enddocument@afterlastpage:	
2021-03-18 ltfsini.dtx v3.2g		Don't empty kernel hooks on	
General: Add legacy hook definitions		rollback . . . . .	71
for rollback. . . . .	719	2021-04-20 ltfilehook.dtx v1.0i	
2021-03-18 lthooks.dtx v1.0i		\@curr@file@reqd: Make expand to	
\_hook_end_document_label_check::		a string (tracks change in	
Only add top-level if not already		l3kernel) . . . . .	1128
there. . . . .	244	2021-04-26 ltfsbas.dtx v3.2i	
Remove the (empty) "top-level"		\usefont: Unconditionally switch to	
from \@currnamestack. . . . .	244	the requested font face (gh/444)	549
General: Use \NewModuleRelease. . . . .	229	2021-04-26 ltfsini.dtx v3.2h	
2021-03-18 ltvers.dtx v1.1f		\reset@font: Unconditionally switch	
\@check@IncludeInRelease: Add		to the requested font face	
support for usage in		(gh/444) . . . . .	727
\NewModuleRelease . . . . .	37	2021-04-26 ltfsstrc.dtx v3.0o	
\new@moduledate: Added		\selectfont: Unset the forced series	
\NewModuleRelease. . . . .	38	boolean when reaching	
2021-03-19 lttextcomp.dtx v1.0e		\selectfont (gh/444) . . . . .	643
General: Use \NewModuleRelease . . . . .	765	2021-04-29 lthooks.dtx v1.0m	
2021-03-26 ltplain.dtx v2.3e		\ActivateGenericHook: Add	
\@unused: Allocate \@inputcheck and		\ProvideHook etc. . . . .	304
\@unused early so that they are		2021-04-29 ltoutenc.dtx v2.0v	
before expl3 allocates more		General: Add composites for	
streams (gh/538) . . . . .	21	\ae/\AE/\ae/\AE (gh/552) . . . . .	520
2021-03-27 ltclass.dtx v1.4a		2021-05-18 ltclass.dtx v1.4b	
\@currnamestack: Do not completely		\@raw@classoptionslist: Initialise to	
roll back if expl3 is loaded. 1057, 1058		\relax to match	
2021-04-16 ltvers.dtx v1.1g		\@classoptionslist . . . . .	1055
\new@moduledate: \NewModuleRelease		2021-05-24 ltcmd.dtx v1.0e	
with the same arguments as		General: Use \msg_... instead of	
\IncludeInRelease. . . . .	38	\_kernel_msg_... . . . . .	113
2021-04-17 ltfiles.dtx v1.2m		2021-05-24 ltcmdhooks.dtx v1.0b	
\@kernel@after@begindocument:		General: Use \msg_... instead of	
Move		\_kernel_msg_... . . . . .	316
\@kernel@before@begindocument		2021-05-24 ltfilehook.dtx v1.0k	
and		General: Use \msg_... instead of	
\@kernel@after@begindocument		\_kernel_msg_... . . . . .	1120
init earlier so that other modules		2021-05-24 lthooks.dtx v1.0n	
can write to the hooks . . . . .	459	General: Use \msg_... instead of	
2021-04-18 ltluatex.dtx v1.1t		\_kernel_msg_... . . . . .	229
General: input_level_string added . . . . .	61	2021-05-24 ltpara.dtx v1.0g	
2021-04-18 ltplain.dtx v2.3f		General: Use \msg_... instead of	
\loggingall: 3 . . . . .	31	\_kernel_msg_... . . . . .	421
Drop pre- $\epsilon$ -TeX support . . . . .	31	2021-05-26 ltdefns.dtx v1.5p	
\tracingnone: 3 . . . . .	32	\MakeRobust: Normalize error message	
Drop pre- $\epsilon$ -TeX support . . . . .	32	in \MakeRobust . . . . .	93
2021-04-19 ltcmd.dtx v1.0d		2021-06-03 ltclass.dtx v1.4c	
\_cmd_cmd_type_cases:NnnnnF:		\@kernel@currpathstack: Take care	
Renamed		of \@kernel@currpathstack when	
\_cmd_cmd_if_xparse:NTF to		rolling back/forward. . . . .	1058
\_kernel_cmd_if_xparse:NTF for		2021-06-04 ltcmd.dtx v1.0f	
cross-module usage . . . . .	187	General: Normalize various error	
		messages . . . . .	190

2021-06-05 ltmiscen.dtx v1.1z	2021-07-20 ltcmdhooks.dtx v1.0c
\@sverb: Normalize error message . 849	\__hook_patch_DeclareRobustCommand:Nnn: Use \robust@command@chk@safe before \@if@newcommand. . . . . 321
2021-06-06 ltclass.dtx v1.4c	2021-07-22 lthooks.dtx v1.0o
\@loadwithoptions: handle raw options for gh/580 . . . . . 1072	\__hook_gremove_code:nn: Do not queue removals (gh/625) . . . . . 258
\load@onefile@withoptions: Copy raw options for gh/580 . . . . . 1081	\__hook_hash_check_aux:w: Do not queue removals (gh/625) . . . . . 246
\PassOptionsToClass: apply \expandafter to raw options for gh/580 . . . . . 1066	2021-07-23 ltclass.dtx v1.4e
2021-06-09 ltclass.dtx v1.4b	\load@onefile@withoptions: Make class/name/after a one-time hook . . . . . 1082
\endfilecontents: Use \@latex@note@no@line to display the information . . . . . 1088	Make class/name/before a one-time hook . . . . . 1081
2021-06-09 lterror.dtx v1.2r	Make package/name/after a one-time hook . . . . . 1082
\@latex@note@no@line: Macros added . . . . . 405	Make package/name/before a one-time hook . . . . . 1081
2021-06-09 ltfssbas.dtx v3.2j	2021-07-23 ltfiles.dtx v1.2n
\DeclareFontShape@: Improve information message . . . . . 539	\@include: Make include/name/after a one-time hook . . . . . 465
2021-07-08 ltcounts.dtx v1.1m	Make include/name/before a one-time hook . . . . . 465
\counterwithin: New implementation for \counterwithin . . . . . 530	Make include/name/end a one-time hook . . . . . 465
\counterwithout: New implementation for \counterwithout . . . . . 531	2021-07-27 lthooks.dtx v1.0o
2021-07-11 lterror.dtx v1.2s	\ClearHookNext: Macro added . . . . 305
\PackageNoteNoLine: Provide \ClassNote and \PackageNote . 404	\hook_gc_clear_next_code:n: Macro made public . . . . . 291
2021-07-12 ltclass.dtx v1.4d	2021-07-28 ltsect.dtx v1.1f
\@fileswithoptions: add \unexpanded . . . . . 1076	\contentsline: Pick up four arguments (gh/633) . . . . . 980
2021-07-16 ltplain.dtx v2.3g	2021-07-30 ltcmd.dtx v1.0d
General: Use 2 as default value for \tracinglostchars . . . . . 22	\__cmd_cmd_type_cases:NnnnnnF: Added \__cmd_cmd_type_cases:NnnnnnF for \NewCommandCopy and \ShowCommand support . . . . . 187
2021-07-19 ltclass.dtx v1.4e	2021-07-31 ltoutput.dtx v1.4e
\@classoptionslist: Drop \@onlypreamble . . . . . 1055	\fl@tracemessage: Enable display when doing \tracefloatvals . 1246
\@ifclasslater: Drop \@onlypreamble . . . . . 1059	2021-07-31 ltoutput.dtx v1.4g
\@ifclassloaded: Drop \@onlypreamble . . . . . 1059	\ShowFloat: Macro added . . . . . 1244
\@ifclasswith: Drop \@onlypreamble . . . . . 1061	2021-08-02 lthooks.dtx v1.0o
\@ifl@ter: Drop \@onlypreamble 1060	\ActivateGenericHook: Change name . . . . . 304
\@pkgextension: Drop \@onlypreamble . . . . . 1056	\DisableGenericHook: Change name 304
\@optionlist: Drop \@onlypreamble 1059	2021-08-07 ltcmd.dtx v1.0g
\@unusedoptionlist: Drop \@onlypreamble . . . . . 1055	\__cmd_add_grabber:N: Replicate argument processors for all embellishments (gh/639) . . . . . 141
\IfFormatAtLeastTF: Drop \@onlypreamble . . . . . 1060	

<code>\__cmd_add_type_E:w</code> : Replicate argument processors for all embellishments (gh/639) . . . . . 138	2021-08-27 lthooks.dtx v1.0q General: Internal message name changes . . . . . 301
2021-08-08 ltfinal.dtx v2.2p <code>\IfPDFManagementActiveTF</code> : Default definition added (gh/640) . . . . . 1303	2021-08-27 ltpara.dtx v1.0i General: Internal message name changes . . . . . 429
2021-08-10 ltvers.dtx v1.1h <code>\@check@IncludeInRelease</code> : Add error to aid debugging . . . . . 37	2021-08-30 ltcmd.dtx v1.0h General: Added support for <code>\NewCommandCopy</code> . . . . . 145 Added support for <code>\ShowCommand</code> . . . . . 151
2021-08-11 ltuatex.dtx v1.1u General: Define missing local function . . . . . 52	2021-09-03 ltoutput.dtx v1.4h <code>\ShowFloat</code> : Renamed, original name never distributed . . . . . 1244
2021-08-20 lterror.dtx v1.2t <code>\@badend</code> : Improve <code>\@badend</code> error message (gh/587) . . . . . 408	2021-09-06 ltfinal.dtx v2.2q <code>\@uclclist</code> : Correctly upper and lowercase <code>\ij</code> and <code>\IJ</code> (gh/658) . . . . . 1300
2021-08-20 lthooks.dtx v1.0p General: Added deprecation warnings for old generic hook commands (gh/638) . . . . . 307 Documentation updates for generic hook commands (gh/638) . . . . . 202 Renames of generic hook commands (gh/638) . . . . . 240 Section on generic hooks added (gh/638) . . . . . 219	2021-09-06 lthooks.dtx v1.0r <code>\__hook_hash_check_aux:w</code> : Use dedicated conditional (gh/606) . . . . . 246 <code>\__hook_if_execute_immediately:n</code> : Macro added (gh/606) . . . . . 296 <code>\__hook_use_once_clear:n</code> : Clean up after <code>\UseOneTimeHook</code> (gh/606) . . . . . 296 <code>\hook_use_once:nnw</code> : Clean up after <code>\UseOneTimeHook</code> (gh/606) . . . . . 295
2021-08-25 ltclass.dtx v1.4f General: Standardise generic hook names (gh/648) . . . . . 1050 <code>\load@onefile@withoptions</code> : Declare non-generic package and class hooks . . . . . 1082	2021-09-10 ltfssini.dtx v3.2i <code>\bfseries</code> : Do delayed changes to <code>\bfdefault</code> in a separate macro for better reuse (gh/663) . . . . . 713 <code>\DeclareFontSeriesDefault</code> : Do delayed changes to <code>\bfdefault</code> or <code>\mddefault</code> first (gh/663) . . . . . 704 <code>\maybe@update@bfseries@defaults</code> : Do delayed changes to <code>\bfdefault</code> in a separate macro for better reuse (gh/663) . . . . . 713 <code>\maybe@update@mdseries@defaults</code> : Do delayed changes to <code>\mddefault</code> in a separate macro for better reuse (gh/663) . . . . . 714 <code>\mdseries</code> : Do delayed changes to <code>\mddefault</code> in a separate macro for better reuse (gh/663) . . . . . 713
2021-08-25 ltcmdhooks.dtx v1.0d <code>\__hook_try_put_cmd_hook:w</code> : Simplify generic hook detection . . . . . 317	2021-09-12 ltfntcmd.dtx v3.5a <code>\check@nocorr@</code> : use <code>\unexpanded</code> to make <code>#</code> safe . . . . . 760
2021-08-25 ltfilehook.dtx v1.0l <code>\unqu@tefilef@und</code> : Declare non-generic file hooks . . . . . 1125	2021-09-12 ltoutenc.dtx v2.0w General: Move zero skip between <code>i</code> and <code>j</code> for hyphenation (gh/658) . . . . . 496
2021-08-25 ltfiles.dtx v1.2o <code>\@include</code> : Declare non-generic include hooks . . . . . 465 Standardise generic hook names (gh/648) . . . . . 465	2021-09-18 ltpara.dtx v1.0i <code>\para_end::</code> Use skip rather than kern as guard. . . . . 427
2021-08-25 lthooks.dtx v1.0p <code>\__hook_try_declaring_generic_next_hook:nn</code> : Standardize generic hook names (gh/648) . . . . . 251	
2021-08-27 ltcmd.dtx v1.0h <code>\NewDocumentEnvironment</code> : Check for end-of-environment command . . . . . 196	
2021-08-27 ltfilehook.dtx v1.0l <code>\__filehook_file_pop_assign:nnnn</code> : Internal message name changes . . . . . 1122 <code>\__filehook_file_subst_cycle_error:cN</code> : Use <code>\msg_...</code> not <code>\__kernel_msg_...</code> . . . . . 1133	

2021-09-26 ltfsdcl.dtx v3.0x	expansion+redefinition when the macro contains a parameter token (gh/697) . . . . .	322
\c@localmathalphabets: Counter added for (gh/676) . . . . .		674
\document@select@group: Test if we should freeze the version (gh/676)	2021-11-17 ltluatex.dtx v1.1w	674
\freeze@math@version: Macro added for (gh/676) . . . . .	General: hpack_quality is <b>exclusive</b> . . . . .	61
2021-09-28 ltcmdhooks.dtx v1.0e	Never pass on <b>true</b> return values for list callbacks . . . . .	63
\__hook_make_prefixes:w: Make patching of commands a global operation (gh/674) . . . . .	vpack_quality is <b>exclusive</b> . . . . .	61
\__hook_patch_retokenize:Nnnn: Make patching of commands a global operation (gh/674) . . . . .	2021-11-30 ltclass.dtx v1.5a	326
2021-09-28 lthooks.dtx v1.0s	\@onefilewithoptions@clashchk: Separated out from \@onefilewithoptions . . . . .	1080
\__hook_if_usable_use:n: Correct usage of older	2021-11-30 ltexpl.dtx v1.3d	
\__hook_if_file_hook:wTF (gh/675) . . . . .	\skipeval: Moved over from xfp package (gh/711) . . . . .	76
\__hook_try_declaring_generic_hook_split:Nnnn: Correct usage of older	2021-12-02 ltcmd.dtx v1.0i	
\__hook_if_file_hook:wTF (gh/675) . . . . .	\__cmd_run_code:: Correct defaults for optional arguments in end-of-environment code (gh/712) . . . . .	123
2021-10-14 ltboxes.dtx v1.4c	\__cmd_start_aux:ccnnnn: Correct defaults for optional arguments in end-of-environment code (gh/712) . . . . .	123
\@mpfootnotetext: Explicitly set	2021-12-07 ltexpl.dtx v1.3d	
\@currentcounter (gh/687) . . . . .	\skipeval: Added \dimeval and \skipeval (gh/711) . . . . .	76
2021-10-14 ltfiles.dtx v1.2p	2021-12-11 ltdirchk.dtx v1.3a	
\@include: Warn about use in preamble . . . . .	General: Add comment lines into latex.ltx to indicate temp definitions that are later overwritten (gh/725) . . . . .	2
2021-10-14 ltfloat.dtx v1.2g	2021-12-12 ltoutenc.dtx v2.0y	
\@footnotetext: Explicitly set	General: \DeclareUnicodeAccent now makes the encoding argument implicit (gh/253) . . . . .	512
\@currentcounter (gh/687) . . . . .	Added \DeclareUnicodeCommand and \DeclareUnicodeSymbol (gh/253) . . . . .	513
2021-10-14 ltmath.dtx v1.2j	2021-12-27 ltluatex.dtx v1.1x	
\@eqnset: Explicitly set	\newprotectedluacmd: Macros added . . . . .	49
\@currentcounter (gh/687) . . . . .	2021-12-28 ltexpl.dtx v1.3d	
eqnarray: Explicitly set	\ExpandArgs: Added document level names for \exp_args:Nc and the like (gh/735) . . . . .	76
\@currentcounter (gh/687) . . . . .	2021-13-31 ltcmd.dtx v1.0j	
2021-10-15 ltfsdcl.dtx v3.0y	\__cmd_show:x: Make \ShowCommand stop for interaction . . . . .	153, 154
\DeclareMathVersion: Initialize variable for freezing math version (gh/676) . . . . .	2022-01-06 ltexpl.dtx v1.3e	
2021-10-15 ltluatex.dtx v1.1v	\ExpandArgs: Adjust document level names for \exp_args:Nc and the like (gh/735) . . . . .	76
General: provide_charproc_data added . . . . .	2022-01-06 ltshipout.dtx v1.0l	
2021-10-16 ltoutenc.dtx v2.0x	\AtBeginShipoutNext: Correctly simulate \AtBeginShipout and	
\add@accent: Dont set		
\spacefactor in math mode gh/643 . . . . .		
2021-10-19 ltpara.dtx v1.0k		
General: Remove content from		
\tex_everypar:D on rollback . . . . .		
2021-10-20 ltcmdhooks.dtx v1.0f		
\__hook_make_prefixes:w: Correct patching by		

<code>\AtBeginShipoutNext</code> without extending the syntax . . . . .	1166	2022-02-28 <code>ltexpl.dtx</code> v1.3f General: Move latexrelease redefinitions from <code>ltxcmd.dtx</code> . . . .	74
<code>\AtEndDvi</code> : Correctly simulate <code>\AtEndDvi</code> without extending the syntax . . . . .	1165	2022-02-28 <code>ltvers.dtx</code> v1.1i <code>\new@moduledate</code> : Detect a missing <code>\IncludeInRelease{0000/00/00}</code> . . . .	38
2022-01-15 <code>ltkeys.dtx</code> v1.0b <code>\_keys_options_aux:n</code> : Clear option list in end-of-package hook . . .	1108	2022-03-10 <code>ltbibl.dtx</code> v1.1t <code>\cite</code> : Ensure that an empty argument generates a warning (gh/790) . . . . .	1010
2022-01-25 <code>ltplain.dtx</code> v2.3h <code>\obeyspaces</code> : Provide redirection to support special use cases (gh/367) . .	25	2022-03-10 <code>ltfilehook.dtx</code> v1.0m <code>\@curr@file@reqd</code> : Add <code>\set@curr@file@nosearch</code> for <code>graphicx</code> . . . . .	1128
2022-02-05 <code>ltkeys.dtx</code> v1.0b .usage: Create properties in <code>ltkeys</code> . .	1106	2022-03-18 <code>ltclass.dtx</code> v1.5b <code>\load@onefilewithoptions</code> : Switch to <code>\ProcessKeyOptions</code> . . . . .	1078
2022-02-07 <code>ltkeys.dtx</code> v1.0c .usage: Correct <code>..code</code> property . .	1106	2022-03-18 <code>ltxcmd.dtx</code> v1.0l <code>\_cmd_cmd_type_cases:NnnnnF</code> : Fix <code>\_cmd_cmd_type_cases:NnnnnF</code> prematurely expanding macros (gh/795) . . . . .	187
2022-02-15 <code>ltkeys.dtx</code> v1.0c <code>\DeclareKeys</code> : Expand module argument . . . . .	1112	2022-03-18 <code>ltkeys.dtx</code> v1.0f <code>\_keys_options:n</code> : Simplify to always cover global options . . .	1108
<code>\DeclareUnknownKeyHandler</code> : Added <code>\DeclareUnknownKeysHandler</code> . .	1112	<code>\_keys_options_global:n</code> : Simplify to always cover global options . .	1109
<code>\ProcessKeyOptions</code> : Expand module argument . . . . .	1112	<code>\ProcessKeyOptions</code> : Remove <code>\ProcessKeyPackageOptions</code> . .	1112
<code>\SetKeys</code> : Expand module argument . .	1114	2022-04-01 <code>ltfiles.dtx</code> v1.2q <code>\@include</code> : Process some hooks is an include file is bypassed . . . . .	465
2022-02-16 <code>ltkeys.dtx</code> v1.0d <code>\DeclareKeys</code> : Allow for active characters in module argument . .	1112	2022-04-01 <code>lthooks.dtx</code> v1.0t <code>\c__hook_generic_include/./end_tl</code> : Support generic <code>include/.../excluded</code> hooks . .	257
<code>\DeclareUnknownKeyHandler</code> : Allow for active characters in module argument . . . . .	1112	2022-04-03 <code>ltfinal.dtx</code> v2.2s General: Integration of new mark management interface . . . . .	1284
Rename <code>\DeclareUnknownKeysHandler</code> to <code>\DeclareUnknownKeyHandler</code> . .	1112	2022-04-03 <code>ltoutput.dtx</code> v1.1h <code>\@opcol</code> : Interface with new mark mechanism . . . . .	1195
<code>\ProcessKeyOptions</code> : Allow for active characters in module argument . .	1112	2022-04-04 <code>ltpage.dtx</code> v1.0n <code>\markright</code> : Interface with new mark mechanism . . . . .	1046
<code>\SetKeys</code> : Allow for active characters in module argument . . . . .	1114	2022-04-08 <code>ltmath.dtx</code> v1.2k <code>\openup</code> : Make <code>\protected</code> (gh/123) . .	858
2022-02-19 <code>ltxcmd.dtx</code> v1.0k <code>\IfBlankTF</code> : Added <code>\IfBlankTF</code> and friends . . . . .	199	2022-04-12 <code>ltxref.dtx</code> LaTeX2e <code>\pageref</code> : Macro reimplemented with a starred version . . . . .	808
2022-02-20 <code>ltfinal.dtx</code> v2.2r <code>\@uclclist</code> : Use <code>\@expl@text@uppercase@n</code> , removing local redefinition of <code>\UTF@two@octets@noexpand</code> . . .	1298	<code>\ref</code> : Macro reimplemented with a starred version . . . . .	808
use <code>\text_lowercase:n</code> . . . . .	1298		
2022-02-21 <code>ltkeys.dtx</code> v1.0e <code>\_keys_options_expand_module:Nn</code> : Faster approach to module expansion . . . . .	1112		
2022-02-28 <code>ltxcmd.dtx</code> v1.0k General: Move latexrelease redefinitions from <code>ltxcmd.dtx</code> . . .	200		

2022-04-12 ltxref.dtx v1.1p		<code>\__keys_options_package:n</code> : Better handling of option removal . . .	1110
General: Add starred variants for the ref commands . . . . .	806	2022-06-19 ltkeys.dtx v1.0h	
<code>\Ref</code> : Macro reimplemented with a starred version . . . . .	812	<code>\__keys_options_class:n</code> : Further work on handling of option removal . . . . .	1109
2022-04-21 ltfinal.dtx v2.2t		<code>\__keys_options_package:n</code> : Further work on handling of option removal . . . . .	1110
<code>\@uclclist</code> : Support <code>\noexpand</code> in argument of		<code>\__keys_options_package:nnn</code> : New function . . . . .	1110
<code>\@expl@text@uppercase@cn</code> . . .	1298	2022-06-20 ltclass.dtx v1.5c	
2022-05-06 ltmarks.dtx v1.0c		<code>\load@onefilewithoptions</code> : Pass raw options to <code>\ProcessKeyOptions</code>	1078
<code>\__mark_new_class:nn</code> : Wrong command made <code>\@onlypreamble</code>	1024	2022-06-20 ltkeys.dtx v1.0h	
2022-05-08 ltmath.dtx v1.2l		<code>\__keys_options_class:n</code> : Use raw options data . . . . .	1109
General: Use consistent math styles under LuaTeX . . . . .	867	<code>\__keys_options_class:nnn</code> : New function . . . . .	1109
2022-05-08 ltshipout.dtx v1.0m		<code>\__keys_options_global:n</code> : Use raw options data . . . . .	1109
<code>\@kernel@after@enddocument@afterlastpage</code> :		<code>\__keys_options_local::</code> : Use raw options data . . . . .	1110
Handle case where shipout/lastpage is run too early (gh/813) . . . . .	1161	<code>\__keys_options_package:n</code> : Use raw options data . . . . .	1110
<code>\__shipout_execute_main_cont:Nnnn</code> :		2022-06-22 ltkeys.dtx v1.0i	
Handle case where shipout/lastpage is run too early (gh/813) . . . . .	1151	<code>.usage</code> : Add <code>.notif</code> property . . . .	1106
2022-05-13 lthooks.dtx v1.0u		2022-06-30 ltfinal.dtx v2.2u	
<code>\__hook_use_once_clear:n</code> : Check if prop exists to avoid l3debug error	296	<code>\@uclclist</code> : Add	
2022-05-17 lthooks.dtx v1.0u		<code>\AddToNoCaseChangeList</code> . . . .	1299
<code>\__hook_initialize_hook_code:n</code> :		2022-06-30 ltfinal.dtx v2.2v	
Refuse sorting one-time hooks (gh/818). . . . .	273	<code>\@uclclist</code> : Just use	
2022-05-17 ltmeta.dtx v1.0b		<code>\text_lowercase:n</code> without	
General: Default definition for targets added . . . . .	431	<code>\protectd@edf</code> gh/881x . . . .	1298
2022-05-27 ltfiles.dtx v1.2r		2022-07-04 ltfinal.dtx v2.2w	
<code>\listfiles</code> : Try saved version string, if ver@.. is <code>\relax</code> (gh/825) . . .	476	<code>\@uclclist</code> : Introduced <code>\CaseSwitch</code> , <code>\DeclareCaseChangeEquivalent</code> and <code>\MakeTitlecase</code> to support hooking into case changing gh/889 . . . . .	1298
2022-05-27 ltoutenc.dtx v2.0z		2022-07-04 ltssbas.dtx v3.2k	
General: Save the version string (gh/825) . . . . .	524	<code>\frozen@everydisplay</code> : Ignore spaces if necessary (gh/886) . . . . .	553
2022-06-01 ltmarks.dtx v1.0d		<code>\frozen@everymath</code> : Ignore spaces if necessary (gh/886) . . . . .	553
<code>\__mark_prepare_and_extract:nn</code> :		2022-07-04 ltssdcl.dtx v3.0z	
Extend the logic for detecting the marks in the box (gh/836) . . . .	1027	<code>\freeze@math@version</code> : Ignore spaces if necessary (gh/886) . . . . .	678
General: Marks are kernel errors . .	1037	2022-07-05 ltkeys.dtx v1.0i	
2022-06-02 ltfinal.dtx v2.2u		<code>\__keys_options_aux:n</code> : Support <code>\CurrentOption</code> . . . . .	1108
<code>\@uclclist</code> : Add <code>\NoCaseChange</code> . .	1299	<code>\__keys_options_class:nnn</code> : Correct naming of raw class options storage . . . . .	1109
2022-06-15 lthooks.dtx v1.0v			
<code>\__hook_activate_generic:n</code> : Ensure that a newly activated generic hook gets its execution code set .	241		
2022-06-16 ltkeys.dtx v1.0g			
<code>\__keys_options_class:n</code> : Better handling of option removal . . .	1109		

2022-07-23 ltkeys.dtx v1.0j	<code>\freeze@math@version</code> : New logic for freezing math versions (gh/921) . 677
<code>\__keys_options_aux:n</code> : Output ‘public’ package name in messages . . . . . 1108	2022-09-20 ltfssdcl.dtx v3.1b
<code>\__keys_options_loaded:nn</code> : Output ‘public’ package name in messages . . . . . 1113	<code>\DeclareSymbolFont</code> : Drop any surplus ‘m’ in series argument (gh/918) . . . . . 683
2022-08-07 ltfssbas.dtx v1.0g	<code>\SetSymbolFont</code> : Drop any surplus ‘m’ in series argument (gh/918) . . . . 685
<code>\DeclareEncodingSubset</code> : Make global declaration (gh/905) . . . . 544	2022-10-03 ltluatex.dtx v1.2a
2022-08-10 ltcmd.dtx v1.1a	General: Add rules for callback ordering . . . . . 58
<code>\__cmd_arg_to_keyvalue:nn</code> : New internal arg-to-keyval processor . 183	<code>add_to_callback</code> : Add rules for callback ordering . . . . . 66
<code>\__cmd_grab_D_long_obey_spaces_no_strip:w:declare_callback_rule</code> : Add support for skipping brace stripping . . . . . 162	<code>remove_from_callback</code> : Add rules for callback ordering . . . . . 68
<code>\__cmd_grab_R_aux:NNnN</code> : Track changes in D-type implementation 169	2022-10-10 ltclass.dtx v1.5d
<code>\__cmd_grab_b_end:Nw</code> : Track changes in D-type implementation . . . . 157	<code>\@@unprocessedoptions</code> : Use <code>\protected@edef</code> . . . . . 1085
General: New switch . . . . . 115	<code>\load@onefilewithoptions</code> : Use <code>\protected@edef</code> . . . . . 1078
2022-08-13 ltluatex.dtx v1.1y	<code>\PassOptionsToClass</code> : Use <code>\protected@xdef</code> . . . . . 1066
General: shared_callbacks added . . 62	<code>\ProcessOptions*</code> : Use <code>\protected@edef</code> . . . . . 1068
<code>add_to_callback</code> : Adapted code for shared_callbacks . . . . . 66	2022-10-20 ltclass.dtx v1.5e
<code>remove_from_callback</code> : Adapted code for shared_callbacks . . . . . 68	<code>\load@onefilewithoptions</code> : Define key option handler in ltkeys . . 1078
<code>mlist_to_hlist</code> : Use shared_callback system for pre/post/mlist_to_hlist . . . . . 70	2022-10-20 ltkeys.dtx v1.0l
2022-08-18 ltfilehook.dtx v1.0n	<code>\__keys_options_aux:n</code> : Define key option handler in ltkeys . . . . . 1108
<code>\@disable@packageload@do</code> : Inhibit checking the loaded version when package is load-disabled, and write to the .log (gh/888) . . . . . 1134	<code>\__keys_options_loaded:nn</code> : Correct an argument for a message . . . 1113
2022-08-20 ltoutput.dtx v1.4j	2022-10-22 ltclass.dtx v1.5e
<code>\stockheight</code> : Register added . . . 1180	<code>\@fileswithoptions</code> : Use <code>\protected@xdef</code> . . . . . 1075
<code>\stockwidth</code> : Register added . . . . 1180	<code>\@use@option</code> : Use <code>\detokenize</code> . . 1070
2022-08-21 ltkeys.dtx v1.0k	<code>\ProcessOptions*</code> : Use <code>\detokenize</code> . . . . . 1069
<code>\__keys_options_loaded:nn</code> : Correct error message . . . . . 1113	2022-10-22 ltdefns.dtx v1.5r
2022-09-03 ltmath.dtx v1.2m	<code>\@expandtwoargs</code> : Use <code>\protected@edef</code> . . . . . 89
<code>\smash</code> : Guard against reboxing in fractions (gh/517) . . . . . 857	2022-10-22 ltkeys.dtx v1.0l
2022-09-07 ltboxes.dtx v1.4d	<code>\__keys_options_class:nnn</code> : Correct handling of unused option list . 1109
<code>\@iiiminipage</code> : Check for nested minipages and warn (gh/168) . . 902	2022-10-26 ltfinal.dtx v2.2x
<code>\if@in@minipage@env</code> : Check for nested minipages and warn (gh/168) . . . . . 902	<code>\@uclclist</code> : Auto-detect babel locale . . . . . 1298
2022-09-17 ltfssdcl.dtx v3.1a	Introduce optional argument for case-changing commands . . . . . 1298
<code>\DeclareMathVersion</code> : New logic for freezing math versions (gh/921) . 682	Make case changing commands language-aware . . . . . 1298

2022-11-06 ltmiscen.dtx v1.2a	
\enddocument: Repeat release info at the end (gh/944) . . . . .	830
2022-11-06 ltvers.dtx v1.1j	
General: Repeat release info at the end (gh/944) . . . . .	36
2022-11-08 ltshipout.dtx v1.0n	
\__shipout_execute_main_cont:Nnnn: Add shipout hook (gh/920) . . .	1151
shipout/lastpage: Add shipout hook (gh/920) . . . . .	1153
2022-11-16 ltclass.dtx v1.5f	
\endfilecontents: Do not show "current dir" in message (gh/917) . . . . .	1088
Introduce key 'nowarn' on filecontents (gh/958) . . . .	1087, 1088
2022-11-24 ltdefs.dtx v1.5s	
\DeclareEnvironmentCopy: Add \NewEnvironmentCopy, \RenewEnvironmentCopy, and \DeclareEnvironmentCopy (gh/963) . . . . .	100
\ShowEnvironment: Added \ShowEnvironment . . . . .	105
2022-11-28 ltspc.dtx v1.3o	
\@hspace: Support calc syntax correctly (gh/967) . . . . .	451
\@vspace@calcify: Support calc syntax without a group (gh/967)	438
2022-11-29 ltcmd.dtx v1.1b	
\__cmd_show:x: Add \@showenvironmentlisthook . . .	154
2022-11-30 ltcmd.dtx v1.1b	
\__cmd_show:x: Don't stop for the \begin part of an environment . . . . .	153, 154
2022-11-30 ltfinal.dtx v2.2y	
\@uclclist: Set \oe/\OE equal to act as a marker for babel . . . . .	1299
2023-01-05 ltfiles.dtx v1.2s	
\document: \do now with default definition in the kernel (gh/975)	458
2023-01-19 ltluatex.dtx v1.2b	
General: Remove unused local variable tex_setattribute . . . . .	52
2023-01-30 ltpara.dtx v1.0l	
\g_para_standard_everypar_tl: Backout \parskip at top of minipage (gh/989) . . . . .	422
2023-03-12 ltcmd.dtx v1.1c	
\__cmd_copy_expandable:NnNNNNnnn: Distinguish (non-expandable) document commands starting with	
\__cmd_start_-expandable:nNNNNn . . . . .	147
\__cmd_show:x: Distinguish (non-expandable) document commands starting with \__cmd_start_expandable:nNNNNn . . . .	152
2023-03-22 ltspc.dtx v1.3p	
\samepage: Add \predisplayspace setting (gh/1022) . . . . .	436
2023-03-28 ltclass.dtx v1.5g	
\IfFormatAtLeastTF: Added \IfFileAtLeastTF (gh/1015) . .	1060
2023-03-28 ltfinal.dtx v2.2z	
\@uclclist: Use groups for gh/1021	1299
2023-04-01 ltfsbas.dtx v3.2l	
\math@version: Reset frozen mathversion gh/1028 . . . . .	551
2023-04-02 ltfilehook.dtx v1.0o	
\@set@curr@file@aux: Make \@set@curr@file@aux \long gh/942 . . . . .	1130
2023-04-06 ltcmdhooks.dtx v1.0g	
\__hook_double_hashes_space:w: Add case for \c__hook_hashes_tl (hook-args) . . . . .	328
\__hook_make_prefixes:w: Rename to \c__hook_hashes_tl (hook-args)	323
\c__hook_hashes_tl: Rename to \c__hook_hashes_tl and add \c__hook_hash_tl (hook-args) .	317
2023-04-06 lthooks.dtx v1.1a	
\__hook_activate_generic:n: Changes to add hook arguments (hook-args). . . . .	241
\__hook_braced_real_loop:w: Macro added (hook-args). . . . .	266
\__hook_chk_args_allowed:nn: Macro added (hook-args). . . . .	250
\__hook_clear_next:n: Changes to add hook arguments (hook-args).	291
\__hook_code_gset_aux:nnn: Macro added (hook-args). . . . .	261
\__hook_code_gset_auxi:eeen: Macro added (hook-args). . . . .	260
\__hook_cs_end:w: Macro added (hook-args). . . . .	265
\__hook_cs_if_empty:c: Macro added (hook-args). . . . .	265
\__hook_gput_next_do:nn: Changes to add hook arguments (hook-args). . . . .	290
\__hook_gremove_code:nn: Changes to add hook arguments (hook-args). . . . .	258

<code>\__hook_hash_check_aux:w</code> : Add	
<code>\hook_gput_code_with_args:nnn</code>	
(hook-args). . . . .	246
Changes to add hook arguments	
(hook-args). . . . .	246, 247
Macro added (hook-args). . . . .	248
<code>\__hook_if_execute_immediately:n</code> :	
Changes to add hook arguments	
(hook-args). . . . .	296
<code>\__hook_init_structure:n</code> : Changes	
to add hook arguments	
(hook-args). . . . .	237
<code>\__hook_initialize_all::</code> Changes	
to add hook arguments	
(hook-args). . . . .	271
<code>\__hook_initialize_hook_code:n</code> :	
Changes to add hook arguments	
(hook-args). . . . .	272
<code>\__hook_initialize_single:ccn</code> :	
Changes to add hook arguments	
(hook-args). . . . .	275
<code>\__hook_log:nN</code> : Changes to add hook	
arguments (hook-args) . . . . .	283
<code>\__hook_log_next_code:n</code> : Changes	
to add hook arguments	
(hook-args). . . . .	287
<code>\__hook_make_usable:nn</code> : Changes to	
add hook arguments (hook-args). . . . .	235
<code>\__hook_new:nn</code> : Add	
<code>\hook_new_with_args:nn</code>	
(hook-args). . . . .	234
Update hook code after declaring. . . . .	235
<code>\__hook_new_reversed:nn</code> : Add	
<code>\hook_new_reversed_with_-</code>	
<code>args:nn</code>	
(hook-args). . . . .	238
<code>\__hook_normalise_cs_args:nn</code> :	
Macro added (hook-args). . . . .	262
<code>\__hook_parameter:n</code> : Macro added	
(hook-args). . . . .	267
<code>\__hook_post_initialization_defs::</code>	
Macro added (hook-args). . . . .	293
<code>\__hook_set_normalise_fn:nn</code> :	
Macro added (hook-args). . . . .	263
<code>\__hook_tl_set:cn</code> : Clean-up unused	
variants (hook-args). . . . .	231
<code>\__hook_try_declaring_generic_hook:wn</code> :	
Changes to add hook arguments	
(hook-args). . . . .	252
<code>\__hook_use_i_delimit_by_s_mark:nw</code> :	
Use standard naming scheme	
(hook-args). . . . .	231
<code>\__hook_use_initialized:nnw</code> : Add	
<code>\hook_use:nw</code> (hook-args). . . . .	293
<code>\__hook_use_once:nn</code> : Changes to	
add hook arguments (hook-args). . . . .	295
<code>\__hook_use_once_clear:n</code> : Changes	
to add hook arguments	
(hook-args). . . . .	296
General: Add dedicated rollback code	
to revert data structures	
(hook-args). . . . .	310
Messages 'too-many-args',	
'without-args' and 'one-time-args'	
added (hook-args). . . . .	301
<code>\AddToHookNextWithArguments</code> : Add	
<code>\AddToHookNextWithArguments</code>	
(hook-args). . . . .	305
<code>\AddToHookWithArguments</code> : Add	
<code>\AddToHookWithArguments</code>	
(hook-args). . . . .	305
<code>\c__hook_??_parameter_tl</code> : Token	
list added (hook-args). . . . .	267
<code>\c__hook_nine_parameters_tl</code> : Add	
auxiliary token lists (hook-args). . . . .	231
<code>\g__hook_replacing_stack_seq</code> :	
Macro added (hook-args). . . . .	300
<code>\hook_gput_next_code:nn</code> : Add	
<code>\hook_gput_next_code_with_-</code>	
<code>args:nn</code>	
(hook-args). . . . .	289
<code>\hook_if_empty:n</code> : Changes to add	
hook arguments (hook-args). . . . .	297
<code>\hook_new_pair_with_args:nnn</code> : Add	
<code>\hook_new_pair_with_args:nnn</code>	
(hook-args). . . . .	238
<code>\hook_use_once:nw</code> : Add	
<code>\hook_use_once:nw</code> (hook-args). . . . .	295
<code>\NewMirroredHookPairWithArguments</code> :	
Add <code>\NewHookWithArguments</code>	
(hook-args). . . . .	304
<code>\UseOneTimeHookWithArguments</code> : Add	
<code>\UseHookWithArguments</code>	
(hook-args). . . . .	306
2023-04-11 ltfinal.dtx v2.3a	
<code>\@uclclist</code> : Use new generic	
mechanism to detect locale . . . . .	1298
2023-04-13 ltcmd.dtx v1.1d	
<code>\__cmd_grab_v_group_end::</code> Set	
<code>\tex_endlinechar:D</code> earlier	
(gh/876). . . . .	169
2023-04-14 ltclass.dtx v1.5h	
<code>\load@onefilewithoptions</code> : Define	
<code>\load@onefilewithoptions</code> when	
in latexrelease (gh/992) . . . . .	1077
2023-04-15 ltplain.dtx v2.3i	
<code>\extrafloats</code> : Protect box 255 in	
lualatex gh/1041 . . . . .	19

unwind numexpr and ifnum nesting	19	<code>\__hook_try_declaring_generic_next_hook:nn:</code>	
2023-04-16 ltfinal.dtx v2.3a		Changes to allow support	
<code>\BCPdata:</code> Command added	1297	arguments in cmd hooks	
2023-04-16 lthooks.dtx v1.1b		(cmd-args).	251
<code>\__hook_include_legacy_code_chunk:n:</code>		<code>\c__hook_parameter_cmd/.after_tl:</code>	
<code>\__hook_replacing_args_false:</code>		Token lists added (cmd-args).	258
in <code>\__hook_include_legacy_code_chunk:n</code>	239	2023-05-26 ltcmd.dtx v1.1e	
2023-04-19 ltfinal.dtx v2.3b		<code>\__cmd_defaults_error:w:</code> Use	
<code>\@uclclist:</code> Add		simpler variant <code>\cs_generate_from_arg_count:NNno</code>	124
<code>\DeclareLowercaseMapping,</code>		2023-05-30 ltfinal.dtx v2.3c	
<code>\DeclareTitlecaseMapping</code> and		<code>\@uclclist:</code> Fix a typo in	
<code>\DeclareUppercaseMapping</code>	1299	implementation of	
2023-04-19 lthooks.dtx v1.1c		<code>\DeclareLowercaseMapping,</code> etc.	1299
<code>\__hook_gput_next_do:nn:</code> Initialize		2023-06-06 lthooks.dtx v1.1e	
hook structure when adding 'next'		<code>\__hook_code_gset_auxi:eeen:</code>	
code (gh/1052).	290	Short-circuit when the hook is	
<code>\hook_if_empty:n:</code> Simpler and faster		declared without args (gh1078).	260
version (gh/1052).	297	2023-06-14 ltmiscen.dtx v1.2b	
2023-05-12 ltxref.dtx v1.1q		<code>\@vobeytabs:</code> Macro added	845
<code>\label:</code> (UFI)added a hook with		<code>\verbatim*</code> : Support visible tabs in	
argument	810	<code>\verb*</code>	847
(UFI)extended to store five		2023-06-14 ltspace.dtx v1.3q	
arguments	810	<code>\@xobeytab:</code> Macro added	450
2023-05-13 ltmath.dtx v1.2n		2023-06-15 ltmiscen.dtx v1.2b	
<code>\leqno:</code> add <code>\ignorespaces</code> gh/1059	867	<code>\@sverb:</code> Support visible tabs	849
2023-05-15 ltfiles.dtx v1.2t		<code>\@setupverbvisibleSPACE:</code> Support	
<code>\IfFileExists@:</code> Use expl3 file		visible tabs	848
existence test	469	<code>\@vobeyspaces:</code> Support tabs	845
<code>\IfFileExists@@:</code> Macro added	469	2023-06-15 ltmiscen.dtx v1.2q	
2023-05-21 ltcmdhooks.dtx v1.0h		<code>\@setupverbvisibletab:</code> Provide	
<code>\__hook_guess_arg_count:nw:</code> Macro		visible tab in <code>\verb*</code>	849
added (cmd-args)	332	2023-06-16 ltfiles.dtx v1.2u	
<code>\__hook_make_prefixes:w:</code> Changes		<code>\IfFileExists@@:</code> Support piped	
to allow support arguments in cmd		input	469
hooks (cmd-args)	324	2023-07-02 ltluatex.dtx v1.2c	
<code>\__hook_patch_retokenize:Nnnn:</code>		<code>new_luafunction:</code> Ensure existing	
Changes to allow support		table entries not overwritten	
arguments in cmd hooks		gh/1100	57
(cmd-args)	333	2023-08-03 ltluatex.dtx v1.2c	
2023-05-21 lthooks.dtx v1.1d		<code>mlist_to_hlist:</code> Fix callback type of	
<code>\__hook_if_cmd_hook:w:</code> Changes to		<code>post_mlist_to_hlist_callback</code>	70
allow support arguments in cmd		2023-08-19 ltcmd.dtx v1.2a	
hooks (cmd-args).	299	General: Removed commands that	
<code>\__hook_make_usable:nn:</code> Changes to		should have remained only in	
allow support arguments in cmd		<code>xparse.dtx</code>	113
hooks (cmd-args).	236	2023-09-01 ltmiscen.dtx v1.2c	
<code>\__hook_new:nn:</code> Changes to allow		<code>\@vobeytabs:</code> Provide global definition	
support arguments in cmd hooks		for active tab	845
(cmd-args).	235	2023-09-06 ltmiscen.dtx v1.2b	
<code>\__hook_try_declaring_generic_hook:wn:</code>		<code>\enddocument:</code> Test changes of values	
Changes to allow support		in <code>\new@label@record</code>	830
arguments in cmd hooks			
(cmd-args).	253		

2023-09-20 ltproperties.dtx v1.0c	2024-01-13 ltkeys.dtx v1.0m
\RecordProperties: use	\__keys_options_class:n: Trim
\protected@edef for safer	spaces off key names . . . . . 1109
handling of active chars. . . . . 821	\__keys_options_package:n: Trim
\SetProperty: use \protected@edef 820	spaces off key names . . . . . 1110
2023-10-13 ltexpl.dtx v1.3g	2024-01-17 ltproperties.dtx v1.0d
\IfExplAtLeastTF: Provide a test for	\__property_record_value_aux:e:
expl3 date (gh/1004) . . . . . 77	Use \protected@write . . . . . 820
2023-10-26 ltboxes.dtx v1.4e	2024-01-24 lthooks.dtx v1.1h
\@iframebox: Guard against unknown	\__hook_if_usable_use:n: Correct
alignment gh/1072 . . . . . 897	usage of older
\@imakebox: Guard against unknown	\__hook_if_file_hook:wTF
alignment gh/1072 . . . . . 892	(gh/1243) . . . . . 294
\@parboxto: Guard against unknown	\__hook_try_declaring_generic_hook_split:nNNnn:
alignment gh/1072 . . . . . 899	Correct usage of older
2023-10-26 ltspace.dtx v1.3r	\__hook_if_file_hook:wTF
\nobreakspace: Protected definition	(gh/1243) . . . . . 252
for tilde . . . . . 449	2024-01-27 lttextcomp.dtx v1.1a
2023-11-07 ltcounts.dtx v1.1n	General: Added check file for encoding
\@definecounter: Do not change	subset . . . . . 796
\the... if already defined	Adjusted/corrected TS1
(gh/823) . . . . . 528	sub-encoding declarations for
2023-11-07 ltoutenc.dtx v2.1a	various families (gh/1257) . . . . . 775
General: Add more explanation to	2024-01-29 ltmmarks.dtx v1.0e
error message (gh/1102) . . . . . 523	\__mark_extract_and_handle_marks:nn:
2023-11-07 ltplain.dtx v2.3j	Macro added . . . . . 1026
\tracingnone: Set	\mark_update_structure_from_material:nn:
\tracinglostchars to 2 in	Macro renamed . . . . . 1029
\tracingnone (gh/549) . . . . . 32	\ShowMarksAt: Macro added . . . . . 1039
2023-11-15 ltfiles.dtx v1.2v	2024-01-30 ltclass.dtx v1.5i
\if@listfiles@hashes: Extend file	\@fileswithoptions: Test group
list information . . . . . 475	level . . . . . 1075
\if@listfiles@sizes: Extend file list	2024-03-18 ltthm.dtx v1.0g
information . . . . . 475	\@endtheorem: Insert link target in the
\listfiles: Extend file list	label (UFI) . . . . . 968
information . . . . . 476	\@thm: Use \@kernel@refstepcounter
2023-11-16 ltpara.dtx v1.0m	to avoid an unwanted target
\g__para_standard_everypar_tl:	(UFI) . . . . . 967
Correct error message: hook left	2024-03-21 ltcmd.dtx v1.2d
horizontal not vertical mode	\__cmd_grab_v_aux_put:N: Collect
(gh/1182) . . . . . 422	\endlinechar as \obeyedline .. 173
2023-12-01 ltcmd.dtx v1.2b	2024-03-22 ltclass.dtx v1.5j
\__cmd_cmd_type_cases:NnnnnnF:	\load@onefilewithoptions: Apply
Extend for optimized commands 187	one-step expansion to raw option
\__cmd_start_optimized::: Optimize	list, to be consistent with change
cmd creation for all-m arguments 118	for gh/580 (gh/1298). . . . . 1078
2023-12-22 ltcmd.dtx v1.2c	2024-04-10 ltclass.dtx v1.5k
General: Generalize message	\IfClassLoadedWithOptionsTF:
invalid-bang (gh/1198) . . . . . 190	Provide T and F conditionals not
2024-01-03 lthooks.dtx v1.1g	just TF (gh/1262) . . . . . 1062
\__hook_log:nN: Fix expansion of	\IfFileLoadedF: Provide
\__hook__print_args:nn	\IfFileLoadedTF and variants
argument (gh/1221) . . . . . 283	(gh/1222) . . . . . 1063

2024-04-17 ltcmd.dtx v1.2e	<code>\__cmd_cmd_type_cases:NnnnnF</code> : Use <code>\__kernel_cs_parameter_spec:N</code> instead of <code>\cs_argument_-</code> <code>spec:N/\cs_parameter_spec:N</code> . . . 187	<code>insertmark</code> : Use sequence marker to make all marks unique on nearby regions (gh/1359) . . . . . 1035
2024-04-17 ltcmdhooks.dtx v1.0j	General: Use <code>\__kernel_cs_parameter_spec:N</code> instead of <code>\cs_argument_-</code> <code>spec:N/\cs_parameter_spec:N</code> . . . 316	2024-05-31 ltmarks.dtx v1.0g <code>\c__mark_empty_tl</code> : Initialize all marks with an id, use 0 when a new class is made (gh/1359) . . . 1026
2024-04-17 ltdefs.dtx v1.5t	General: Rename <code>\@expl@cs@argument@spec@N</code> to <code>\@expl@cs@parameter@spec@N</code> (gh/1014) . . . . . 78	<code>\mark_use_last:nn</code> : Remove the id when returning the mark value (gh/1359) . . . . . 1036
2024-04-17 ltexpl.dtx v1.3h	General: Add a kernel-level copy of <code>\cs_parameter_spec:N</code> . . . . . 75	2024-06-04 ltclass.dtx v1.5l <code>\@cls@pkg</code> : Allow for extensions other than "cls" and "pkg" . . . . . 1085
	Rename <code>\@expl@cs@argument@spec@N</code> to <code>\@expl@cs@parameter@spec@N</code> (gh/1014) . . . . . 75	<code>\@onefilewithoptions</code> : New argument <code>\pkgcls@ext</code> (gh/870) 1096
	Update name of <code>expl3</code> function . . . 75	<code>\pkgcls@parse@date@arg</code> : New argument <code>\pkgcls@ext</code> (gh/870) 1098
2024-04-17 ltproperties.dtx v1.0e		2024-06-04 ltluatex.dtx v1.2d <code>provides_module</code> : Add <code>v</code> to version string if required (gh/1364) . . . . 52
	<code>\IfLabelExistsF</code> : Renamed <code>\IfLabelExistTF</code> to <code>\IfLabelExistsTF</code> (gh/1262) . . . 824	2024-06-10 ltboxes.dtx v1.4g <code>\@finalstrut</code> : Always use a <code>\vrule</code> strut after all, but back up by a baseline if already in vertical mode. Otherwise empty table p-cells will not get the correct width (bug seen first with <code>colortbl</code> ) . . . . . 906
	<code>\IfPropertyExistsF</code> : Renamed <code>\IfPropertyExistTF</code> to <code>\IfPropertyExistsTF</code> (gh/1262) 823	2024-06-10 lttagging.dtx v1.0b <code>\tbl_crcr:n</code> : Always issue a <code>\crcr</code> even if we are at the start of a row to avoid problems with tabulary and similar code . . . . . 1281
2024-04-18 ltboxes.dtx v1.4f	<code>\@finalstrut</code> : Use a <code>\hrule</code> strut not a <code>\vrule</code> if already in vertical mode (bug seen first with <code>footmisc/14</code> ) . . . . . 906	2024-06-17 ltfsbas.dtx v3.2m <code>\showhyphens</code> : set <code>\tracinglostchars</code> to 0 in <code>\showhyphens</code> . . . . . 565
2024-04-22 lttextcomp.dtx v2.1a	General: Drop default option info (gh/1333) . . . . . 785	2024-06-19 ltkeys.dtx v1.0n <code>\__keys_options_class:n</code> : Refactor function . . . . . 1109
2024-04-24 lttextcomp.dtx v2.1b	General: Load the 2018 version when rolling back prior to 2018-08-11 (gh/1333) . . . . . 784	<code>\__keys_options_class:nn</code> : New function . . . . . 1109
2024-05-30 ltmarks.dtx v1.0f	<code>\__mark_update_dblcol_structures::</code> Correct logic for first mark in page region if first column contains no marks (gh/1359) . . . . . 1042	<code>\__keys_options_class:nnn</code> : Refactor function . . . . . 1109
	<code>\__mark_value:nn</code> : Use sequence marker to make all marks unique on nearby regions (gh/1359) . . . 1035	Track options used by classes . . 1109
	<code>\mark_insert:nn</code> : Use sequence marker to make all marks unique on nearby regions (gh/1359) . . . 1034	<code>\__keys_options_package:nn</code> : New functions . . . . . 1110
		<code>\__keys_options_package:nnn</code> : Skip options given to packages . . . . 1110
		<code>\__keys_scope:N</code> : New function . . 1106
		<code>\__keys_scope:n</code> : New function . . 1106
		<code>\l__keys_class_only_clist</code> : New variable . . . . . 1107
		<code>\l__keys_forced_global_clist</code> : New variable . . . . . 1107

.pass-to-packages: New key property . . . . .	1106	and empty hook (gh/1423) . . . .	243
2024-06-20 ltkeys.dtx v1.0o		\_hook_parse_dot_label:nN: Distinguish between empty label and empty hook (gh/1423) . . . .	242
\_keys_scope:N: Ensure only key name is stored . . . . .	1106	\_hook_parse_label_default:nN: Distinguish between empty label and empty hook (gh/1423) . . . .	242
2024-06-23 ltboxes.dtx v1.4h		General: New message “empty-hook” (gh/1423). . . . .	302
\color@endgroup: Adjust for new @endpe handling . . . . .	894	2024-08-16 ltluatex.dtx v1.2e	
2024-06-23 ltlists.dtx v1.0u		provides_module: Support missing version string (gh/1443) . . . . .	52
\@doendpe: Set \if@endpe to false before calling \par (needed for tagging) . . . . .	882	2024-09-03 fontdef.dtx v3.0k	
\propagate@doendpe: Set \if@endpe globally and also set up migration to the outside . . . . .	883	General: Load also t1cmss.fd and t1cmtt.fd . . . . .	735
2024-06-23 ltmiscen.dtx v1.2d		2024-09-04 ltlength.dtx v1.1e	
\begin: Separate \begin and \end definitions for individual rollback	837	\@settodim: (UF) Suspend tagging .	536
\end: Separate \begin and \end definitions for individual rollback	838	2024-09-05 ltproperties.dtx v1.0f	
\end\verbvisiblespace: Adjust for new @endpe handling . . . . .	840	\_property_record_value_aux:e: Remove \if@files test to be in line with \label, tagging-project issue 696 . . . . .	820
2024-06-23 ltpara.dtx v1.0n		2024-09-10 ltspace.dtx v1.3s	
\g__para_standard_everypar_tl: Append \everypar toks to \g__para_standard_everypar_tl, rollback 2023/06/01 (gh/1386) . .	423	\addpenalty: Drop unnecessary \@noitemerr and instead generate \@LRmoderr if we are in restricted hmode (gh/1460) . . . . .	445
2024-06-24 fontdef.dtx v3.0j		\addvspace: Drop unnecessary \@noitemerr and instead generate \@LRmoderr if we are in restricted hmode (gh/1460) . . . . .	444
General: load ts1 cmr fd file in Unicode engines . . . . .	736	2024-09-11 lterror.dtx v1.2u	
2024-07-06 ltcmd.dtx v1.2f		\@LRmoderr: Error message added .	409
\_cmd_declare_env:ennn: Use space-trimmed envname directly (gh/1399) . . . . .	121	2024-09-13 lttagging.dtx v1.0h	
\NewDocumentEnvironment: Trim spaces from envname first (gh/1399) . . . . .	196	float/hmode/end: Sockets for floats added . . . . .	1272
2024-07-10 ltmiscen.dtx v1.2e		2024-09-20 ltcounts.dtx v1.1o	
General: Drop code chunks before adding them to avoid duplication in rollback (gh/1407) . . . . .	832	\@addtoreset: add the parent theHfoo if a counter is reset . . . . .	529
\enddocument: Drop code chunks before adding them to avoid duplication in rollback (gh/1407)	830	\@definecounter: define theHfoo (used for internal links) . . . . .	528
2024-07-13 lttagging.dtx v1.0c		2024-09-20 lttagging.dtx v1.0h	
tbl/leaders/end: Sockets for \cline leaders added (tagging/134) . .	1272	General: moved \@kernel@refstepcounter into ltxref . . . . .	1281
2024-08-03 ltclass.dtx v1.5m		2024-09-20 ltxref.dtx v1.1r	
\pkgcls@use@this@release: Add selected release to the file list (gh/1413) . . . . .	1100	\refstepcounter: add sockets . . . .	810
2024-08-09 lthooks.dtx v1.1i		provide a kernel copy kernel@refstepcounter . . . . .	810
\_hook_normalize_hook_args_aux:Nn: Distinguish between empty label		set also currentHref . . . . .	810
		2024-09-21 ltmeta.dtx v1.0c	
		General: Added tagging support . . .	431

2024-09-25 ltproperties.dtx v1.0g	Support for macron-i for T1 (gh/1453) . . . . .	502
\IfLabelExistsF: Fixed definitions of \IfLabelExistsT and \IfLabelExistsF . . . . .	2024-11-09 ltmrks.dtx v1.1a \__mark_class_status:nnn: Add a third argument . . . . .	824 1038
2024-10-10 ltagging.dtx v1.0i	\__mark_status:nn: Add a second argument . . . . .	1267 1039
default: Restore also paratagging (tagging/723) . . . . .	\mark_clear_structure:n: . . . . .	1033
2024-10-12 ltmiscen.dtx v1.2f	\mark_copy_structure:nn: Macro renamed . . . . .	1033
\begin: Make \begin engine-protected . . . . .	\mark_use_last:nn: . . . . .	1036
2024-10-21 lthooks.dtx v1.1j	2024-11-12 ltfinal.dtx v2.3d \@uclclist: Add option to titlecase first or all words . . . . .	307 1298
\IfHookEmptyF: Define \IfHookEmptyT, \IfHookEmptyF .	Use updated titlecase-first function in expl3 . . . . .	1040 1298
2024-10-21 ltmrks.dtx v1.0h	2024-11-16 ltpage.dtx v1.0o \markright: Drop legacy mark support . . . . .	1046
\IfMarksEqualF: Define \IfMarksEqualT, \IfMarksEqualF . . . . .	2024-11-19 fontdef.dtx v3.0l General: Preload the TS1 .fd file . .	736
2024-10-21 ltproperties.dtx v1.0h	Preload the TS1 ts1cmr.fd file in all engines . . . . .	735
\IfPropertyRecordedF: Define \IfPropertyRecordedT, \IfPropertyRecordedF . . . . .	2024-11-21 ltagging.dtx v1.0l \UseExpandableTaggingSocket: Define \tag_if_active:TF conditionals here (github/1558)	1265
2024-10-21 ltagging.dtx v1.0k	2024-11-26 lthooks.dtx v1.1l \__hook_hash_check_aux:w: Adjust debugging message (gh/1459) . .	247
\UseExpandableTaggingSocket: Added expandable variants . . .	\__hook_initialize_all::: Adjust debugging message (gh/1459) . .	271
Changed behavior of two argument tagging sockets when disabled. .	\__hook_initialize_hook_code:n: Adjust debugging message (gh/1459) . . . . .	272
2024-10-26 ltcounts.dtx v1.1p	\__hook_initialize_single:ccn: Adjust debugging message (gh/1459) . . . . .	276
\@addtoreset: Fully expand counter name in theHfoo commands (gh/1508) . . . . .	\hook_gput_next_code:nn: Add debugging message (gh/1459) . .	289
\@definecounter: Fully expand counter name in theHfoo commands (gh/1508) . . . . .	2024-11-26 ltoutenc.dtx v2.1c \@inmathwarn: Declare command for logging (gh/1242) . . . . .	482
2024-10-27 ltsockets.dtx v0.9b	\@strip@args: Alter error and info message . . . . .	486
\socket_set_plug:nnn: Make plug definition non-protected . . . . .	\UndeclareTextCommand: Log text command change (gh/1242) . . . . .	489, 490
\socket_use_expandable:n: Added \socket_use_expandable:n . . . .	Use \ifcurname to avoid generating a curname . . . . .	489
2024-10-29 lthooks.dtx v1.1k	2024-11-27 ltfsdcl.dtx v3.1d \freeze@math@version: Reset math version if necessary (gh/1101 and gh/1028) . . . . .	677
\__hook_list_if_rule_exists:nnnF: Skip mapping over undeclared \g_hook_{hook}_code_prop (gh/1513) . . . . .		
\__hook_log:nN: Skip mapping over undeclared \g_hook_{hook}_code_prop (gh/1513) . . . . .		
2024-11-02 ltdirchk.dtx v1.3b		
General: Add tab char to \dospecials		4
2024-11-02 ltplain.dtx v1.3k		
General: Add tab char to \dospecials		14
2024-11-06 ltoutenc.dtx v2.1b		
General: Support for macron-i for OT1 . . . . .		496

Reset top-level alphabet definitions only for the current math version (gh/1101 and gh/1028) . . . . .	678	2025-01-02 ltclass.dtx v1.5n	
2024-11-30 ltfssbas.dtx v3.2o		<code>\AtEndDocument</code> : Do not make <code>\AtBeginDocument</code> preamble only (gh/1604) . . . . .	1084
<code>\math@level</code> : New approach to <code>localmathalphabets</code> (gh/1101) . . . . .	552	2025-01-03 lthooks.dtx v1.1l	
<code>\frozen@everydisplay</code> : New approach to <code>localmathalphabets</code> (gh/1101) . . . . .	553	General: Correct example to use <code>env/quote/begin</code> instead of <code>/before</code> (gh/1599) . . . . .	205
<code>\frozen@everymath</code> : New approach to <code>localmathalphabets</code> (gh/1101) . . . . .	553	2025-01-10 ltmarks.dtx v1.1c	
<code>\math@version</code> : New approach to <code>localmathalphabets</code> (gh/1101) . . . . .	551, 552	<code>\__mark_get_from_splitmarks::</code> Do not expand mark content while debugging . . . . .	1032
2024-12-03 ltmarks.dtx v1.1b		2025-01-15 ltkeys.dtx v1.0p	
<code>\c__mark_empty_tl</code> : Fix inconsistent local/global assignment (gh/1574) . . . . .	1025	<code>\__keys_options_aux:n</code> : Only process global options on first pass . . . . .	1108
2024-12-11 ltfssaxes.dtx v1.0k		2025-01-21 ltcmd.dtx v1.2g	
General: Add <code>ssc</code> shape change rules (gh/1581) . . . . .	629	<code>\__cmd_grab_v_aux_catcodes::</code> Store spaces and tabs as active chars . . . . .	172
Rationalize <code>sw</code> shape change rules (gh/1581) . . . . .	629	<code>\__cmd_grab_v_aux_put:N</code> : Simplify catcode handling . . . . .	173
Reorganized the rollback data . . . . .	627	2025-01-21 ltoutput.dtx v1.4l	
2024-12-13 ltfssaxes.dtx 1.0k		<code>\@writsetup</code> : Support extended syntax for <code>\label</code> , <code>\index</code> , and <code>\glossary</code> (gh/311) . . . . .	1211
General: Add numerous <code>\DeclareFontSeriesChangeRule</code> entries to support the full range of weights (from <code>ul</code> to <code>ub</code> ) and widths (from <code>uc</code> to <code>ux</code> ) (gh/1583) . . . . .	570	2025-01-21 ltsect.dtx v1.1g	
Minor modifications to a few <code>\DeclareFontSeriesChangeRule</code> entries (gh/1583) . . . . .	570	<code>\@gobble@with@sphack@som</code> : Support extended syntax for <code>\label</code> , <code>\index</code> and <code>\glossary</code> (gh/311) . . . . .	979
2024-12-21 ltoutenc.dtx v2.1c		<code>\addtocontents</code> : Support extended syntax for <code>\label</code> , <code>\index</code> , and <code>\glossary</code> (gh/311) . . . . .	979
General: Correct base letter (gh/1587) . . . . .	502	2025-01-22 ltcounts.dtx v1.2a	
2024-12-22 ltcmdhooks.dtx v1.0k		<code>\@ifbothcounters</code> : Guard against star alias. . . . .	529
<code>\__hook_try_put_cmd_hook:w</code> : Avoid defining command while adding a cmd hook (gh/1591) . . . . .	318	<code>\c@*:</code> <code>\c@*</code> added (gh/1632) . . . . .	527
2024-12-27 ltsockets.dtx v0.9c		2025-01-22 ltxref.dtx v1.1t	
<code>\IfSocketPlugAssignedF</code> : Conditionals for sockets, plugs, and assignments (gh/1577) . . . . .	351	<code>\refstepcounter</code> : Guard <code>*</code> from causing infinite loop . . . . .	810
<code>\socket_if_exist:n</code> : Conditionals for sockets, plugs, and assignments (gh/1577) . . . . .	347	Macro added . . . . .	810
<code>\socket_if_plug_assigned:nn</code> : Conditionals for sockets, plugs, and assignments (gh/1577) . . . . .	349	2025-01-23 ltcmd.dtx v1.3a	
<code>\socket_if_plug_exist:nn</code> : Conditionals for sockets, plugs, and assignments (gh/1577) . . . . .	348	<code>\__cmd_add_grabber:N</code> : Extend to support c-type grabbing . . . . .	141
		<code>\__cmd_add_type_b:w</code> : Extend to cover c-type grabbing . . . . .	138
		<code>\__cmd_add_type_b_or_c:N</code> : New function . . . . .	138
		<code>\__cmd_add_type_c:w</code> : New function . . . . .	138
		<code>\__cmd_grab_D_aux:NNnNNNN</code> : Extend to support c-type grabbing . . . . .	163
		<code>\__cmd_grab_D_long_obey_spaces_no_strip:w</code> : Auto-generate D-grabbers . . . . .	162
		<code>\__cmd_grab_D_verb_safe:NN</code> : New macro . . . . .	163

<code>\__cmd_grab_c:w</code> : New c-type grabbing function . . . . .	158	<code>\@if@footnotes@TF</code> : Macro added . . . . .	1202
<code>\__cmd_normalize_type_b:w</code> : Extend to cover c-type grabbing . . . . .	132	<code>\@make@normalcolbox</code> : Macro added . . . . .	1196
<code>\__cmd_normalize_type_b_or_c:nn</code> : New function . . . . .	132	<code>\@make@specialcolbox</code> : Macro added . . . . .	1196
<code>\__cmd_normalize_type_c:w</code> : New function . . . . .	132	<code>\@makecol</code> : Use sockets and hooks . . . . .	1195
<code>\__cmd_prepare_signature:n</code> : Extend to cover c-type grabbing . . . . .	136	<code>\@outputbox@append</code> : Macro added . . . . .	1200
General: Generalize message <code>arg-after-body</code> . . . . .	190	<code>\@outputbox@appendfootnotes</code> : Macro added . . . . .	1200
New message <code>chars-dropped-first-line</code> . . . . .	190	<code>\@outputbox@attachbottomfloats</code> : Macro added . . . . .	1201
New message <code>chars-dropped-last-line</code> . . . . .	190	<code>\@outputbox@attachfloats</code> : Macro added . . . . .	1201
New variable . . . . .	114, 116	<code>\@outputbox@attachtopfloats</code> : Macro added . . . . .	1201
2025-01-23 ltoutput.dtx v1.4m		<code>\@outputbox@depth</code> : Macro added . . . . .	1196
<code>\@writsetup</code> : Make <code>\label</code> , <code>\index</code> and <code>\glossary</code> truly invisible when typesetting (gh/1638) . . . . .	1211	<code>\@outputbox@removebskip</code> : Finally fix bottom skip bug (from 2.09) . . . . .	1198
2025-01-23 ltsect.dtx v1.1h		Macro added . . . . .	1198
<code>\@gobble@with@sphack@som</code> : Make <code>\label</code> , <code>\index</code> and <code>\glossary</code> truly invisible when typesetting (gh/1638) . . . . .	979	<code>\@writsetup</code> : Hooks and sockets added . . . . .	1208
2025-01-26 ltlists.dtx v1.0v		General: Use sockets and hooks in OR . . . . .	1202
<code>\@propagate@doendpe</code> : Only migrate <code>\@doendpe</code> out of simple and semi-simple groups (gh1641) . . . . .	883	<code>build/column/after</code> : Hook added . . . . .	1205
2025-01-27 lttagging.dtx 1.0m		<code>build/column/outputbox</code> : Socket added . . . . .	1202
General: add sockets for math phantom commands . . . . .	1275	<code>build/page/after</code> : Hook added . . . . .	1205
2025-01-29 ltoutput.dtx v1.4n		<code>build/page/reset</code> : Hook added . . . . .	1205
<code>\@addtocurcol</code> : Save current value of <code>\@reqcolroom</code> (gh/1645) . . . . .	1223	2025-02-14 lttagging.dtx v1.0m	
<code>\@addtonextcol</code> : Save current value of <code>\@reqcolroom</code> (gh/1645) . . . . .	1233	General: Tagging support for output routines added . . . . .	1273
<code>\@flcheckspace</code> : Reset current value of <code>\@reqcolroom</code> (gh/1645) . . . . .	1252	<code>build/column/footins</code> : Tagging socket added . . . . .	1273
2025-02-01 ltcmd.dtx v1.3b		<code>build/column/outputbox</code> : Tagging socket added . . . . .	1273
<code>\ProcessList</code> : Use <code>\tl_map_tokens:nn</code> instead of <code>\tl_map_function:nN</code> . . . . .	199	<code>build/page/footer</code> : Tagging socket added . . . . .	1273
2025-02-11 ltoutenc.dtx v2.1c		<code>build/page/header</code> : Tagging socket added . . . . .	1273
<code>\@inmathwarn</code> : Log text command/symbol redeclarations (gh/1242) . . . . .	482	2025-02-19 lttagging.dtx v1.0n	
2025-02-14 ltoutput.dtx v1.4m		General: Moved math sockets into lttagging . . . . .	1273
<code>\@combinefloats</code> : Macro got a new name . . . . .	1214	2025-02-20 ltfssbas.dtx v3.2p	
<code>\@if@bottomfloats@TF</code> : Macro added . . . . .	1202	<code>\CheckEncodingSubset</code> : If necessary, load the <code>.fd</code> before checking the encoding subset (gh/1669) . . . . .	545
<code>\@if@flushbottom@TF</code> : Macro added . . . . .	1202	2025-02-21 lttagging.dtx v1.0n	
		<code>marginpar/end</code> : move marginpar sockets . . . . .	1271
		2025-02-22 ltcounts.dtx v1.2b	
		<code>\counterwithin</code> : <code>\counterwithin</code> needs to expand its arguments (gh/1675) . . . . .	530

2025-02-25 ltoutput.dtx v1.4o	(gh/1687) . . . . .	22
\@writesetup: Reset various catcodes to their default values in case a pagebreak occurs while a special catcode scheme is in force (gh/600) . . . . .	1209	
2025-02-26 ltagging.dtx v1.0o		
\AssignTaggingSocketPlug: Macro added . . . . .	1265	
\NewTaggingSocket: Initialize tagging sockets with 1 or 2 arguments . . . . .	1265	
2025-03-01 ltcounts.dtx v1.2b		
\counterwithout: \counterwithout needs to expand its arguments (gh/1675) . . . . .	531	
2025-03-01 ltexpl.dtx v1.3i		
\IfExplAtLeastTF: Also provide T and F variants of \IfExplAtLeastTF (gh/1522) . . . . .	77	
2025-03-01 ltfinal.dtx v2.3e		
\IfPDFManagementActiveTF: Provide T F variants of \IfPDFManagementActiveTF (gh/1522) . . . . .	1303	
2025-03-01 ltffsini.dtx v3.2k		
\IfFontSeriesContextTF: Provide T F variants of \IfFontSeriesContextTF (gh/1522) . . . . .	721	
2025-03-01 ltmeta.dtx v1.0d		
General: Provide T F variants of \IfDocumentMetadataTF (gh/1522) . . . . .	430	
2025-03-05 ltexpl.dtx v1.3j		
\@kernel@after@begindocument: Add \@kernel@before@enddocument@afterlastpage . . . . .	71	
2025-03-05 ltffsbas.dtx v3.2q		
\showhyphens: set \tracinglostchars to 0 in \showhyphens for all engines . . . . .	565	
2025-03-05 ltmiscen.dtx v1.2g		
\enddocument: Added \@kernel@before@enddocument@afterlastpage . . . . .	830	
2025-03-05 ltoutput.dtx v1.4p		
\clearpage: A L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> name for \write in case it gets changed after the last page . . . . .	1182	
Make sure this is a normal write in all circumstances . . . . .	1182	
2025-03-05 ltplain.dtx v2.3l		
General: Use 4 as default value for \tracinglostchars in LuaT <sub>E</sub> X (gh/1687) . . . . .	22	
\loggingall: Remove \tracinglostchars setting (gh/1691) . . . . .	31	
\tracingnone: Remove \tracinglostchars setting (gh/1691) . . . . .	32	
2025-03-05 ltshipout.dtx v1.0o		
\_shipout_force_immediate_writes:: Macro added . . . . .	1164	
2025-03-05 ltshipout.dtx v1.4p		
\@kernel@before@enddocument@afterlastpage: Make all \writes immediate after the last page (gh/1689) . . . . .	1160	
2025-03-08 ltmath.dtx v1.2o		
\@eqnset: \dollar@begin and \dollar@end introduced for tagging . . . . .	864, 865	
\]: \dollar@begin and \dollar@end introduced for tagging . . . . .	861	
\cequation: \dollar@begin and \dollar@end introduced for tagging . . . . .	863	
\dollar@end: \dollar@begin and \dollar@end introduced for tagging . . . . .	861	
eqnarray: \dollar@begin and \dollar@end introduced for tagging . . . . .	870	
2025-03-20 ltoutput.dtx v1.4q		
\@outputbox@appendfootnotes: Add experimental socket for baseline attachment of footnotes – subject to change (footmisc/19) . . . . .	1201	
\@outputbox@removebskip: Remove a ‘fil’ bottom skip even if we are in ragged bottom typesetting (footmisc/19) . . . . .	1198	
\newpage: Remove skip added in 2.4a (footmisc/19) . . . . .	1183	
\build/column/baselineattach: Add experimental socket for baseline attachment of footnotes – subject to change (footmisc/19) . . . . .	1205	
2025-03-25 ltoutput.dtx v1.4r		
\@addtobot: Don’t set \maxdepth to zero any more (footmisc/19) . . . . .	1221	
\@backup@outputbox@depth: Macro added (footmisc/19) . . . . .	1199	
\@outputbox@reinsertbskip: Back out the depth if we have no		

footnotes and no bottom floats (footmisc/19) . . . . .	1199	2025-04-25 ltfiles.dtx v1.2w <code>\protected@write</code> : Move <code>\write</code> outside the group /gh1717 . . . . .	461
on: (footmisc/19) . . . . .	1205	2025-04-27 ltshipout.dtx v1.0p <code>\@kernel@after@enddocument@afterlastpage</code> : Increment page counter gh/1717	1161
footnotes-floats-legacy: Add support for attaching footnotes with a skip starting at the baseline of the last text line (footmisc/19) . . . . .	1204	<code>\__shipout_force_immediate_writes::</code> : Decrement page counter gh/1717	1164
2025-03-29 ltoutput.dtx v1.4s <code>\@outputbox@attachbottomfloats</code> : Add socket (footmisc/19) . . . . .	1201	2025-04-28 ltmiscen.dtx v1.2h <code>\enddocument</code> : Increment page counter gh/1717 . . . . .	830
footnotes-floats-legacy: Add socket (footmisc/19) . . . . .	1204	2025-05-10 ltclass.dtx v1.5m <code>\IfClassLoadedWithOptionsTF</code> : avoid errors for par in code argument of T versions (gh/1733) . . . . .	1062
2025-03-40 ltexpl.dtx v1.3k <code>\expandableinput</code> : Added document level name for <code>\file_input_raw:n</code> (gh/514) . . . . .	77	2025-05-29 ltmath.dtx v1.2p <code>\leqno</code> : Ensure saved version is primitive gh/1747 . . . . .	867
2025-04-12 ltcmd.dtx v1.3c <code>\__cmd_add_arg_spec_mandatory:n</code> : Track total mandatory args . . . . .	135	2025-06-03 ltdefs.dtx v1.5u <code>\provide@command</code> : Strip trailing spaces from arg (gh/1708) . . . . .	87
<code>\__cmd_add_grabber:N</code> : Refine handling of optional arguments for c-type grabbing . . . . .	141	<code>\renew@command</code> : Strip trailing spaces from arg (gh/1708) . . . . .	85
<code>\__cmd_grab_c_loop:w</code> : Correct behavior on dropping tokens . . . . .	158	2025-06-04 ltfinal.dtx v2.3f <code>\@uclclist</code> : Add default for titlecasing . . . . .	1298
<code>\__cmd_normalize_arg_spec:n</code> : Track total mandatory args . . . . .	128	2025-06-05 ltexpl.dtx v1.3l <code>\IfExplAtLeastTF</code> : Provide T and F variants of <code>\IfExplAtLeastTF</code> with a correct implementation (gh/1752) . . . . .	77
General: New variable . . . . .	114	2025-06-07 ltoutput.dtx v1.4y <code>\@writsetup</code> : Reset catcode of CR (gh/1766) . . . . .	1209
2025-04-13 ltoutput.dtx v1.4x <code>\newpage</code> : reinserted par token (github/1712) . . . . .	1183	2025-06-08 ltoutput.dtx v1.4y <code>\@writsetup</code> : Reset catcode of TAB (gh/1766) . . . . .	1209
2025-04-14 ltoutput.dtx v2.3m General: Always use extended free list . . . . .	1178	2025-06-19 ltmarks.dtx v1.1d <code>\__mark_new_class:nn</code> : Also initialize saved-column region (SX chat)	1025
2025-04-14 ltplain.dtx v2.3m <code>\e@alloc</code> : Always use extended allocation . . . . .	18	2025-06-23 ltfsaxes.dtx 1.0l General: Improve the order of the <code>\DeclareFontSeriesChangeRule</code> entries (gh/1727) . . . . .	593
<code>\e@alloc@chardef</code> : Always use extended allocation . . . . .	18	Offer <code>m</code> as alternative result series for some <code>\DeclareFontSeriesChangeRule</code> entries (gh/1727) . . . . .	594
<code>\e@alloc@top</code> : Drop a redundant $\varepsilon$ -TeX test . . . . .	18	2025-06-25 ltkeys.dtx v1.0q <code>\__keys_options_aux:n</code> : Revise for multiple family support . . . . .	1108
<code>\e@mathgroup@top</code> : Always use extended allocation . . . . .	18	<code>\__keys_options_local::</code> : Revise for multiple family support . . . . .	1110
<code>\extrafloats</code> : Always use extended allocation . . . . .	18		
<code>\newinsert</code> : Always use extended allocation . . . . .	20		
Drop redundant $\varepsilon$ -TeX test . . . . .	20		
<code>\newlanguage</code> : Always use extended allocation . . . . .	17		
2025-04-21 ltcmd.dtx v1.3d <code>\__cmd_grab_c_auxviii::</code> : Correct a logic flaw . . . . .	160		

<code>\__keys_options_local:n</code> : New function . . . . .	1111	statements are affected (gh/1845) . . . . .	1210
<code>\__keys_options_local:nnn</code> : New function . . . . .	1111	2025-08-23 lttagging.dtx v1.0r General: MathML intent macros added . . . . .	1264
<code>\l_keys_local_clist</code> : New variable . . . . .	1107	2025-09-15 ltfsdcl.dtx v3.1e <code>\process@table</code> : Run <code>\set@current@meta@family</code> and the <code>normalfont</code> hook . . . . .	680
2025-06-26 ltdefns.dtx v1.5v <code>\declare@robustcommand</code> : Allow for active chars . . . . .	90	2025-09-15 ltfsini.dtx v3.2l <code>\@currentmetafamily</code> : Macro added . . . . .	707
<code>\declare@robustcommand@auxi</code> : New macro . . . . .	90	<code>\prepare@family@series@update</code> : Always set <code>\@currentmetafamily</code> . . . . .	707
<code>\declare@robustcommand@auxii</code> : New macro . . . . .	90	<code>\reset@font</code> : Drop old 2020 hook <code>\@defaultfamilyhook</code> . . . . .	727
<code>\declare@robustcommand@auxiii</code> : New macro . . . . .	90	Set current meta family . . . . .	727
2025-06-27 ltcmd.dtx v1.3e <code>\__cmd_show:x</code> : Support <code>\showstream</code> (gh/1062) . . . . .	154	<code>\set@current@meta@family</code> : Macro added . . . . .	727
2025-06-27 lthooks.dtx v1.1m <code>\hook_log:n</code> : Support <code>\showstream</code> (gh/1062) . . . . .	282	<code>\update@series@target@value</code> : Rename <code>\target@meta@family@value</code> to <code>\@currentmetafamily</code> and set it always . . . . .	708
2025-06-29 ltfsstrc.dtx v3.0q <code>\getanddefine@fonts</code> : Introduced <code>\transform@scriptfont</code> for script fonts. . . . .	651	2025-09-23 ltcmd.dtx v1.3f <code>\__cmd_add_arg_spec_mandatory:n</code> : Correct logic for recording position of mandatory args . . . . .	135
2025-07-01 ltfinal.dtx v2.3g <code>\@uclclist</code> : Add <code>\DeclareLowercaseExclusions</code> , <code>\DeclareTitlecaseExclusions</code> and <code>\DeclareUppercaseExclusions</code> . . . . .	1300	General: Rename variable . . . . .	114
2025-07-18 ltoutenc.dtx v2.1d General: Add forgotten <code>\DeclareFontSubstitution</code> (gh/1709) . . . . .	495, 497	2025-09-23 ltfinal.dtx v2.3h General: Setting <code>\partokencontext</code> . . . . .	1300
2025-08-01 ltproperties.dtx v1.0j <code>\__property_gset:nnnn</code> : correct name of shipout boolean . . . . .	819	2025-09-24 lthooks.dtx v1.1n <code>\__hook_hash_check:nTF</code> : New function . . . . .	246
2025-08-03 lttagging.dtx v1.0s General: Add sockets for block code . . . . .	1270	<code>\__hook_hash_check_aux:w</code> : New function . . . . .	246
2025-08-11 ltmarks.dtx v1.1e <code>\__mark_vbox_set_split_to_maxdimen:NN</code> : Use <code>\ignoreprimitiverror</code> if available (gh/1750) . . . . .	1028	Only double hashes when needed . . . . .	248
2025-08-21 lttagging.dtx v1.0t <code>default</code> : Use symbolic name instead of text-unit . . . . .	1267	2025-09-24 lttab.dtx v1.1t <code>\@array</code> : Check <code>\currentgrouptype</code> in <code>\par</code> (gh1864) . . . . .	921
2025-08-22 ltoutput.dtx v1.4z <code>\@writesetup</code> : Don't use <code>\nfss@catcodes</code> + updates, but spell everything out explicitly . . . . .	1209	2025-10-01 ltdefns.dtx v1.5w <code>\@star@or@long</code> : Handling protection status differently (gh/571) . . . . .	81
Move setting of <code>\protect</code> after all hooks so that only the <code>\write</code>		<code>\@yargd@f</code> : Ensure that commands without arguments are not long (gh/571) . . . . .	84
		Handling protection status differently (gh/571) . . . . .	84
		<code>\declare@robustcommand@auxiii</code> : Handling protection status differently (gh/571) . . . . .	91
		<code>\pr@TECTEDrel@x</code> : Handling protection status differently (gh/571) . . . . .	82

2025-10-02 ltcmd.dtx v1.3g	v1.0d lttemplates.dtx 2024-10-07
<code>\__cmd_arg_spec_opt:N</code> : New function . . . . . 189	<code>\__template_assign_variable::</code> Correct passing of <code>\KeyValue</code> contents . . . . . 384
<code>\__cmd_cmd_type_cases:NnnnnnF</code> : Remove protected status . . . . . 187	v1.0d lttemplates.dtx 2025-01-08
<code>\__kernel_cmd_if_xparse:NTF</code> : Remove protected status . . . . . 187	<code>\SetTemplateKeys</code> : Test for empty key/val list to speed up processing 392
<code>\cmd_arg_spec:c</code> : New function . . . 189	v1.0e lttemplates.dtx 2025-01-20
2025-10-12 ltcmdhooks.dtx v1.0l	<code>\__template_declare_template_code:nnnnn</code> : Speed up test for <code>\AssignTemplateKeys</code> . . . . . 372
<code>\__hook_retokenize_patch:Nnn</code> : Reset the catcode of space when patching . . . . . 329	v1.0f lttemplates.dtx 2025-07-08
2025-10-20 lttagging.dtx v1.0u	<code>\__template_parse_values_elt_aux:n</code> : Allow for value expansion . . . . . 378
General: Tagging sockets for headings added . . . . . 1270	<code>\__template_parse_values_elt_aux:w</code> : New macro . . . . . 378
v1.0b lttemplates.dtx 2024-02-15	<code>\__template_parse_values_exp:c</code> : New macro . . . . . 378
<code>\IfInstanceExistsTF</code> : New macros 392	<code>\__template_parse_values_exp:e</code> : New macro . . . . . 378
v1.0c lttemplates.dtx 2024-04-17	General: New variable . . . . . 363
<code>\IfInstanceExistsTF</code> : Use plural names . . . . . 392	

# Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
$\backslash!$ . . . . .	02:306, 02:308, 57:518
$\backslash!$ . . . . .	<u>38:214</u>
$\backslash"$ . . . . .	04:512, 04:513, 21:246, 21:399, 21:440, 21:478, 21:491, 21:602, 21:634, 21:661, 21:669, 21:675, 21:679, 21:685, 21:689, 21:695, 21:701, 21:708, 21:709, 21:715, 21:719, 21:770, 21:816, 21:1268, 21:1286, 21:1292, 21:1296, 21:1302, 21:1306, 21:1312, 21:1318, 21:1325, 21:1326, 21:1332, 21:1336, 21:1338, 21:1445, 24:513, 33:135, 33:162, 54:873, 57:519
$\backslash\#$ . . . . .	01:46, 01:59, 02:6, 02:14, 02:406, 06:893, 09:464, 24:500, 54:858, 57:502
$\backslash\$$ . . . . .	01:58, 02:4, 02:13, 06:892, 21:327, 21:465, 21:472, 21:588, 21:828, 21:835, 33:595, 33:602, 54:855, 57:503
$\backslash\$$ . . . . .	<u>1323</u>
$\backslash\%$ . . . . .	01:59, 01:89, 01:91, 01:111, 02:14, 02:404, 06:893, 21:514, 21:516, 24:502, 33:604, 33:724, 37:212, 50:1574, 50:1575, 54:875, 57:504
$\backslash\&$ . . . . .	01:58, 02:5, 02:13, 02:405, 06:892, 50:439, 54:856, 57:505
$\backslash'$ . . . . .	02:426, 21:247, 21:400, 21:442, 21:476, 21:488, 21:604, 21:614, 21:620, 21:622, 21:625, 21:627, 21:635, 21:641, 21:647, 21:649, 21:652, 21:654, 21:662, 21:666, 21:673, 21:677, 21:682, 21:687, 21:690, 21:692, 21:699, 21:704, 21:705, 21:712, 21:717, 21:720, 21:771, 21:818, 21:837, 21:839, 21:840, 21:841, 21:844, 21:846, 21:847, 21:848, 21:850, 21:851, 21:1262, 21:1283, 21:1290, 21:1294, 21:1299, 21:1304, 21:1307, 21:1309, 21:1316, 21:1321, 21:1322, 21:1329, 21:1334, 21:1337, 21:1345, 21:1346, 21:1393, 21:1394, 21:1399, 21:1400, 21:1411, 21:1412, 21:1417, 21:1418, 21:1446, 21:1447, 21:1461, 21:1462, 21:1463, 21:1464, 21:1477, 21:1478, 24:512, 29:904, 30:264, 33:125, 37:740, 38:254, 40:387, 40:408, 41:72, 54:835, 54:872, 57:520
$\backslash($ . . . . .	07:2635, 38:389
$\backslash($ . . . . .	<u>38:271</u>
$\backslash)$ . . . . .	02:426, 07:2657, 38:390
$\backslash)$ . . . . .	<u>38:271</u>
$\backslash*$ . . . . .	22:110, 24:505, 50:1255, 50:1386, 50:1500, 50:1576, 54:865
$\backslash*$ . . . . .	<u>38:251</u>
$\backslash+$ . . . . .	41:72
$\backslash+$ . . . . .	<u>1321</u>
$\backslash,$ . . . . .	02:307, 02:309, 30:517, 37:740, 38:7, 38:8, 38:40, 38:167, 38:169, 38:172, 38:197, 38:220, 38:221, 38:237
$\backslash,$ . . . . .	<u>1362</u>
$\backslash-$ . . . . .	02:253, 06:24, 18:463, 18:554, 21:437, 21:438, 21:597, 21:812, 21:813, 24:507, 37:740, 40:386, 40:407, 41:72, 54:867, 57:224, 57:264
$\backslash-$ . . . . .	<u>06:927</u> , <u>110</u>
$\backslash.$ . . . . .	02:306, 02:308, 20:45, 20:115, 20:173, 21:248, 21:401, 21:473, 21:474, 21:497, 21:610, 21:611, 21:637, 21:638, 21:664, 21:772, 21:842, 21:849, 21:1267, 21:1349, 21:1350, 21:1359, 21:1360, 21:1369, 21:1370, 21:1387, 21:1448, 21:1449, 21:1485, 21:1486, 24:506, 33:137, 33:163, 54:866
$\backslash.$ . . . . .	<u>1350</u>
$\backslash.\text{default}$ . . . . .	<u>569</u>
$\backslash.\text{code}$ . . . . .	<u>51:4</u>
$\backslash.\text{if}$ . . . . .	<u>51:4</u>
$\backslash.\text{ifnot}$ . . . . .	<u>51:4</u>
$\backslash.\text{pass-to-packages}$ . . . . .	<u>51:22</u>
$\backslash.\text{store}$ . . . . .	<u>51:4</u>
$\backslash.\text{usage}$ . . . . .	<u>51:4</u>
$\backslash/$ . . . . .	01:81, 06:25, 09:219, 09:294, 24:454, 24:508, 50:438, 54:868
$\backslash/$ . . . . .	<u>1317</u>
$\backslash:$ . . . . .	<u>38:214</u> , 38:224, 38:225, 38:226, 38:242, <u>38:252</u> , 38:252, 06:887, 06:888, 02:307, 02:309
$\backslash;$ . . . . .	02:307, 02:309, 30:511, 38:198
$\backslash;$ . . . . .	<u>38:214</u> , <u>859</u>
$\backslash<$ . . . . .	21:598, 21:763, 24:503, 37:740, 41:71, 41:109, 54:863
$\backslash=$ . . . . .	21:249, 21:402, 21:479, 21:496, 21:737, 21:773, 21:1265, 21:1339, 21:1340, 21:1355, 21:1356, 21:1378, 21:1379, 21:1380, 21:1405, 21:1406, 21:1431, 21:1432,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

21:1465, 21:1466, 21:1467, 21:1468,	\@outputbox@attachtopfloats . . . . .	1187
21:1483, 21:1484, 21:1491, 21:1492,	\@outputbox@reinsertbskip . . . . .	1187
29:904, 33:143, 40:387, 40:408, 41:71	\@restorepar . . . . .	411
\> 21:595, 21:764, 24:504, 37:740, 38:226,	\@setpar . . . . .	411
38:241, 38:242, 38:252, 41:71, 54:864	@topnum commands:	
\? . . . . .	\@topnum: . . . . .	54:1399
02:306, 02:308, 57:520	\[ . . . . .	24:509, 29:44, 29:55,
\@@par . . . . .	29:77, 29:88, 38:391, 54:869, 57:521	
\@TeXversion . . . . .	\[ . . . . .	38:306, 38:555, 1352
6, 1	\@ . . . . .	01:58, 01:231,
@botlist commands:	01:232, 01:233, 01:234, 01:237,	
\@botlist: . . . . .	01:244, 01:245, 01:246, 01:247,	
.. 54:1379, 54:1474, 54:1623, 54:1777	01:250, 01:257, 01:258, 01:259,	
@botnum commands:	01:260, 01:263, 01:270, 01:276,	
\@botnum: . . . . .	01:277, 01:281, 01:283, 01:284,	
54:1353	01:288, 01:293, 01:294, 01:297,	
\@car . . . . .	01:303, 02:13, 02:252, 04:272,	
80	04:424, 06:272, 06:380, 06:541,	
\@cdr . . . . .	06:664, 06:682, 06:892, 07:473,	
80	07:537, 07:568, 07:714, 07:726,	
@citeb commands:	07:757, 07:1155, 07:1161, 07:2848,	
\@citeb: . . . . .	07:2876, 07:2902, 07:2909, 07:2938,	
47:36, 47:65, 47:82	07:3035, 07:3063, 07:3074, 07:3100,	
@colht commands:	07:3106, 07:3113, 08:1794, 08:1805,	
\@colht: . . . . .	08:2623, 08:2637, 08:2638, 08:2639,	
54:532, 54:545	08:2640, 08:2641, 08:2646, 08:2649,	
@colnum commands:	08:2650, 08:2651, 08:2661, 08:2662,	
\@colnum: . . . . .	08:2676, 08:2697, 08:2701, 08:2702,	
54:1539, 54:1684, 54:1851	08:2704, 08:2710, 08:2721, 08:2722,	
\@cons . . . . .	08:2727, 08:2732, 08:2737, 08:2753,	
80	08:2918, 08:2919, 08:2920, 09:461,	
\@currdir . . . . .	09:599, 11:996, 11:1004, 11:1010,	
5, 1	11:1011, 11:1012, 11:1013, 11:1026,	
@currname commands:	11:1032, 11:1033, 11:1039, 11:1045,	
\@currname: . . . . .	11:1046, 11:1052, 11:1053, 11:1060,	
20:780	11:1067, 11:1074, 11:1081, 11:1082,	
\@dblarg . . . . .	11:1091, 11:1109, 11:1110, 11:1146,	
79	11:1147, 11:1148, 11:1149, 11:1150,	
@dbldeferlist commands:	11:1151, 11:1152, 11:1153, 11:1154,	
\@dbldeferlist: . . . . .	11:1155, 11:1156, 14:279, 16:146,	
54:2331, 54:2373	16:153, 16:160, 16:161, 16:162,	
@dbltopnum commands:	16:163, 18:556, 20:773, 20:792,	
\@dbltopnum: . . . . .	21:583, 24:497, 30:262, 36:249,	
54:2230, 54:2357	37:453, 37:458, 37:463, 37:473,	
@deferlist commands:	37:477, 37:481, 37:522, 38:432,	
\@deferlist: . . . . .	38:461, 38:616, 40:419, 40:578,	
54:1465, 54:1562,	40:580, 41:73, 41:170, 41:180,	
54:1614, 54:1707, 54:1767, 54:1875,	41:194, 42:139, 54:852, 57:506, 433	
54:1920, 54:1949, 54:2001, 54:2030,	\@ . . . . .	18:53, 1326
54:2087, 54:2119, 54:2205, 54:2245	\{ . . . . .	01:6, 01:10, 01:58, 02:2, 02:13,
\@if@bottomfloats@TF . . . . .	07:640, 07:2161, 09:462, 14:22,	
1187	21:328, 21:585, 24:498, 30:260,	
\@if@footnotes@TF . . . . .	37:521, 38:59, 38:167, 54:853, 57:509	
1187	\} . . . . .	01:11, 01:58, 02:3, 02:13, 09:463,
\@ifclasslater . . . . .		
1053		
\@ifclassloaded . . . . .		
1053		
\@ifclasswith . . . . .		
1053		
\@ifdefinable . . . . .		
79		
\@ifnextchar . . . . .		
79		
\@ifpackagelater . . . . .		
1053		
\@ifpackageloaded . . . . .		
1053		
\@ifpackagewith . . . . .		
1053		
\@ifstar . . . . .		
79		
\@ifundefined . . . . .		
79		
\@missingfileerror . . . . .		
1054		
\@namedef . . . . .		
79		
\@nameuse . . . . .		
79		
\@outputbox@append . . . . .		
1187		
\@outputbox@appendfootnotes . . . . .		
1187		
\@outputbox@attachbottomfloats . . . . .		
1187		
\@outputbox@attachfloats . . . . .		
1187		

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

14:21, 21:329, 21:586, 24:499, 30:261, 37:521, 38:59, 54:854, 57:510	57:550, 57:551, 57:552, 57:553, 57:554, 57:555, 57:556, 57:557, 57:558
$\backslash \mathfrak{y}$ ..... 1183	$\backslash$ ..... 21:334,
$\backslash \langle \text{addto-cmd} \rangle$ ..... 203	30:265, 38:269, 38:270, 02:8, 02:14,
$\backslash \langle \text{cmd} \rangle_{\square}$ ..... 147	06:893, 54:860, 57:508, 01:59, 1330
$\backslash \langle \text{cmd} \rangle_{\square}(\text{arg}_{\square}(\text{num}))$ ..... 149	$\backslash \_ \text{hook} \backslash \text{textvisiblespace}_{\square} \backslash \text{meta}_{\square} \{ \text{hook} \}$
$\backslash \langle \text{cmd} \rangle_{\square \square}$ ..... 147	..... 232
$\backslash \langle \text{cmd} \rangle_{\square} \text{code}$ ..... 146	$\backslash \_ \text{hook\_next} \backslash \text{textvisiblespace}_{\square} \backslash \text{meta}_{\square} \{ \text{hook} \}$
$\backslash \langle \text{cmd} \rangle_{\square} \text{defaults}$ ..... 146	..... 232
$\backslash \langle \text{filename} \rangle$ ..... 1130	$\backslash \_ \text{hook\_toplevel} \backslash \text{textvisiblespace}_{\square} \backslash \text{meta}_{\square} \{ \text{hook} \}$
$\backslash \langle \text{function} \rangle$ ..... 174	..... 232
$\backslash \_$ .. 01:58, 01:75, 02:13, 02:256, 02:312, 02:341, 02:342, 02:359, 06:892, 07:1834, 07:2199, 08:2702, 11:1033, 11:1046, 11:1053, 11:1061, 11:1082, 11:1110, 14:19, 14:20, 14:21, 14:22, 14:25, 18:468, 24:494, 24:745, 24:782, 24:807, 30:263, 37:505, 37:506, 37:515, 37:516, 37:661, 37:677, 37:691, 43:53, 43:55, 43:60, 43:62, 47:37, 50:432, 54:861, 57:501	$\backslash \prime$ ..... 21:252, 21:404, 21:441, 21:475, 21:487, 21:603, 21:665, 21:672, 21:676, 21:681, 21:686, 21:691, 21:698, 21:702, 21:703, 21:711, 21:716, 21:775, 21:817, 21:1261, 21:1282, 21:1289, 21:1293, 21:1298, 21:1303, 21:1308, 21:1315, 21:1319, 21:1320, 21:1328, 21:1333, 24:511, 29:904, 33:139, 37:740, 40:387, 40:408, 41:72, 54:871, 57:523
$\backslash \]$ ... 02:426, 24:510, 38:392, 54:870, 57:522	$\backslash \mid$ ..... 21:584,
$\backslash \]$ ..... 38:306, 38:579	22:260, 22:271, 30:584, 30:585, 57:524
$\backslash \sim$ .. 01:47, 01:56, 01:59, 01:103, 01:314, 02:7, 02:9, 02:11, 02:14, 02:255, 02:312, 02:313, 02:332, 02:333, 02:354, 02:355, 06:20, 06:893, 07:6, 07:7, 07:1613, 07:1616, 07:1620, 07:1656, 07:1705, 07:1744, 07:1808, 07:1832, 07:2100, 07:2200, 07:2503, 07:2508, 07:3328, 18:556, 18:558, 18:560, 21:251, 21:306, 21:403, 21:477, 21:489, 21:581, 21:667, 21:674, 21:678, 21:683, 21:688, 21:693, 21:700, 21:706, 21:707, 21:713, 21:718, 21:774, 21:1263, 21:1280, 21:1284, 21:1291, 21:1295, 21:1300, 21:1305, 21:1310, 21:1317, 21:1323, 21:1324, 21:1330, 21:1335, 21:1347, 21:1348, 21:1365, 21:1366, 21:1373, 21:1374, 21:1388, 21:1389, 21:1390, 21:1419, 21:1420, 21:1441, 21:1442, 21:1443, 21:1444, 24:495, 24:496, 24:501, 33:133, 33:161, 37:204, 37:213, 37:507, 37:508, 37:662, 50:1256, 50:1257, 50:1258, 50:1339, 50:1342, 50:1345, 50:1387, 50:1388, 50:1389, 50:1471, 50:1474, 50:1477, 50:1501, 50:1502, 50:1503, 50:1561, 50:1564, 50:1567, 54:857, 54:859, 54:862, 57:255, 57:256, 57:257, 57:258, 57:259, 57:260, 57:261, 57:262, 57:263, 57:507, 57:513, 57:514, 57:515, 57:516,	$\backslash \sim$ ..... 01:59, 02:10, 02:14, 06:893, 14:20, 18:469, 21:259, 21:307, 21:405, 21:490, 21:582, 21:668, 21:680, 21:684, 21:694, 21:710, 21:714, 21:776, 21:1264, 21:1281, 21:1285, 21:1297, 21:1301, 21:1311, 21:1327, 21:1331, 21:1375, 21:1376, 21:1377, 21:1429, 21:1430, 33:151, 33:171, 37:655, 37:672, 37:686, 37:701, 37:744, 54:874, 57:511
	<b>A</b>
	$\backslash \text{A}$ ..... 57:525, 57:526, 57:547
	$\backslash \text{a}$ <u>21:243</u> , <u>41:1</u> , 57:243, 57:527, 57:538, 1321
	$\backslash \text{AA}$ ... 21:260, 21:449, 21:549, <u>02:318</u> , 1347
	$\backslash \text{aa}$ ... 21:265, 21:443, 21:559, <u>02:318</u> , 1347
	$\backslash \text{abovedisplayshortskip}$ .. 38:624, 02:288
	$\backslash \text{abovedisplayskip}$ .....
	38:617, 38:619, 38:621,
	38:622, 38:623, 38:624, 02:287, 1331
	$\backslash \text{abspage}$ ..... 818
	$\text{abspage}$ ..... 36:233, 818
	$\backslash \text{accent}$ ..... 21:91,
	21:414, 21:444, 21:502, 21:787, 1348
	$\backslash \text{ActivateGenericHook}$ .....
	08:2777, <u>08:2779</u> , 08:2784, 08:2786, 203
	$\backslash \text{active}$ ..... 01:103, 37:505, 37:506,
	37:507, 37:508, 37:515, 37:516,
	37:654, 37:661, 37:662, 37:671,
	37:677, 37:685, 37:691, 37:700,
	37:742, 38:254, 38:269, 01:314,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- 02:10, 02:11, 50:1256, 50:1257,  
50:1258, 50:1339, 50:1342, 50:1345,  
50:1387, 50:1388, 50:1389, 50:1471,  
50:1474, 50:1477, 50:1501, 50:1502,  
50:1503, 50:1561, 50:1564, 50:1567,  
54:835, 01:48, 02:332, 02:333,  
02:341, 02:342, 02:354, 02:355, 02:359  
\acute ..... 30:527  
add commands:  
  add\_to\_callback ..... 04:817  
\add\_to\_callback ..... 43  
\addcontentsline .....  
  .... 44:70, 44:80, 44:159, 45:16, 1330  
\AddEveryPageHook ..... 1146  
\Adding ..... 1306  
\addpenalty ..... 18:285,  
  39:124, 39:201, 39:206, 44:50,  
  54:343, 54:1504, 54:1653, 54:1814, 445  
\AddThisPageHook ..... 1146  
\addtocontents .....  
  . 44:164, 44:171, 44:177, 44:188, 1330  
\addtocounter ..... 525  
\addtocounter ..... 22:6, 22:20, 1318  
\AddToHook ..... 08:2789, 08:2939,  
  26:153, 37:44, 37:45, 37:46, 37:109,  
  37:110, 37:111, 37:398, 37:399,  
  37:400, 37:401, 47:72, 50:1136,  
  50:1137, 50:1138, 52:561, 52:563,  
  52:573, 52:574, 52:575, 52:576,  
  53:190, 53:500, 53:523, 55:160, 1146  
\AddToHookNext .....  
  08:2800, 08:2937, 52:562, 53:524, 1146  
\AddToHookNextWithArguments 08:2800, 1376  
\AddToHookWithArguments ... 08:2789, 312  
\addtolength ..... 536  
\addtolength ..... 23:16, 38:619, 38:621  
\AddToNoCaseChangeList .... 57:571, 1373  
\addtoversion ..... 27:20, 27:139  
\advspace 18:234, 37:431, 39:124, 39:202,  
  39:203, 39:207, 39:255, 44:50, 1317  
\adjdemerits ..... 02:206  
\AE .... 21:261, 21:419, 21:550, 21:792,  
  21:1151, 21:1461, 21:1465, 57:670  
\ae .... 21:266, 21:422, 21:560, 21:796,  
  21:1157, 21:1463, 21:1467, 57:670  
\afterassignment ..... 21:232,  
  21:240, 24:391, 38:199, 06:360,  
  06:366, 06:409, 02:376, 02:379, 94  
\AfterEndEnvironment ..... 37:394, 225  
\aftergroup ..... 24:92, 24:410,  
  24:428, 24:433, 26:203, 26:269,  
  28:115, 28:122, 28:130, 28:476,  
  32:64, 37:658, 37:675, 37:689,  
  37:704, 38:538, 38:539, 39:149,  
  39:154, 40:187, 54:883, 54:884,  
  54:958, 54:959, 54:1016, 54:1017, 881  
\AfterLastShipout ..... 52:573  
\afterpreamble ..... 458  
\aleph ..... 30:319  
\allocationnumber ..... 04:52,  
  04:53, 04:54, 04:91, 16:81, 04:213,  
  41:4, 41:9, 02:37, 53:34, 02:53,  
  02:65, 02:67, 57:58, 57:59, 57:60,  
  02:97, 02:98, 02:99, 02:118, 02:119,  
  02:157, 02:163, 02:169, 02:170, 424  
\allowbreak ..... 38:40,  
  06:969, 06:970, 06:989, 06:991, 02:383  
\Alph ..... 525  
\Alpha ..... 22:231, 1144  
\alph ..... 525  
\alpha ..... 22:230  
\alpha ..... 30:279  
\amalg ..... 30:390  
\AmSfont ..... 624  
\and ..... 969  
\and ..... 44:14, 44:27  
\angle ..... 30:348  
\approx ..... 30:433  
\arabic ..... 525  
\arabic ..... 22:131, 22:146, 22:184,  
  22:196, 22:227, 43:46, 53:350, 525  
\arccos ..... 38:13  
\arcsin ..... 38:10  
\arctan ..... 38:16  
\arg ..... 38:26  
array (env.) ..... 41:168  
\array ..... 41:168  
\arraycolsep ... 38:435, 38:436, 38:464,  
  38:465, 38:629, 38:630, 41:258, 41:338  
\arrayrulewidth .....  
  ... 41:324, 41:338, 41:346, 41:347,  
  41:359, 41:363, 41:366, 41:376, 41:378  
\arraystretch ..... 41:186, 41:187, 41:342  
\Arrowvert ..... 30:580  
\arrowvert ..... 30:578  
\asciispace .... 37:578, 37:580, 37:583,  
  37:597, 37:608, 37:609, 37:622, 37:623  
\AssignSocketPlug ... 10:182, 10:208,  
  35:122, 54:721, 54:728, 55:24, 343  
\AssignStructureRole ..... 1264  
\AssignStructureRole ..... 55:265  
\AssignTaggingSocketPlug ..... 1263  
\AssignTaggingSocketPlug 55:20, 55:61,  
  55:71, 55:77, 55:78, 55:88, 55:115,  
  55:116, 55:162, 55:163, 55:177, 1263  
\AssignTemplateKeys .....  
  ..... 11:390, 11:395, 11:1230, 356  
\ast ..... 30:243, 30:406

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=ltfigur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=ltthyphen.dtx, 57=ltfinal.dtx

- `\asympt` ..... 30:460  
`\AtBeginDocument` ..... 20:126,  
     20:181, 25:3257, 47:54, 50:1127, 223  
`\atbegindocumenthook` ..... 458  
`\AtBeginDvi` ... 53:418, 53:454, 54:62, 1142  
`\AtBeginEnvironment` ..... 37:394, 225  
`\AtBeginShipout` .... 53:459, 53:523, 1371  
`\AtBeginShipoutAddToBox` ... 53:528, 1145  
`\AtBeginShipoutAddToBoxForeground` ..  
     ..... 53:528, 1145  
`\AtBeginShipoutBox` ..... 53:521, 1145  
`\AtBeginShipoutDiscard` .... 53:527, 1146  
`\AtBeginShipoutFirst` 53:462, 53:525, 1146  
`\AtBeginShipoutInit` ..... 53:522, 1146  
`\AtBeginShipoutNext` . 53:460, 53:523, 1146  
`\AtBeginShipoutOriginalShipout` ....  
     ..... 53:536, 1145  
`\AtBeginShipoutUpperLeft` ... 53:528, 1145  
`\AtBeginShipoutUpperLeftForeground` .  
     ..... 53:528, 1145  
`\AtEndAfterFileList` ..... 52:575  
`\AtEndDocument` 37:146, 50:1127, 52:579, 1350  
`\AtEndDvi` ..... 53:469, 53:495, 1142  
`\AtEndEnvironment` ..... 37:394, 225  
`\AtEndOfClass` ..... 38:554, 50:1127, 1117  
`\AtEndOfPackage` ..... 50:606, 50:625,  
     50:723, 50:734, 50:1127, 51:89, 1117  
`\AtEndPreamble` ..... 226  
`\AtNextShipout` ..... 1146  
`\atopwithdelims` ..... 38:57, 38:58, 38:59  
`\attribute` ..... 04:79, 40  
`\attributedef` ..... 04:79, 04:223  
`\attributezero` ..... 04:223  
`\AtVeryEndDocument` ..... 52:574  
`\AtVeryVeryEnd` ..... 52:576  
`\author` ..... 969  
`\author` ..... 44:8, 44:24, 44:32
- B**
- `\b` ..... 21:253,  
     21:410, 21:498, 21:783, 21:1272, 1333  
`\backslash` ..... 30:262, 30:601  
`\bar` ..... 30:531  
`\baselineskip` .....  
     ... 26:187, 26:188, 26:189, 26:191,  
     26:192, 30:521, 38:171, 38:172,  
     38:191, 38:197, 38:201, 40:396,  
     40:415, 40:601, 41:198, 42:136,  
     42:314, 42:373, 53:222, 53:273,  
     54:247, 54:278, 54:906, 54:928,  
     54:976, 54:991, 54:1035, 54:1050,  
     02:284, 02:311, 02:374, 02:410, 1342  
`\baselinestretch` 24:382, 26:121, 26:122,  
     26:167, 26:168, 26:185, 26:246, 1304
- `\baselinestretch` ..... 1324  
`\batchmode` ..... 20:710,  
     20:741, 20:742, 27:106, 05:93,  
     05:99, 05:109, 57:700, 57:721, 474  
`\BCPdata` ..... 57:560, 57:587, 57:591  
`\BeforeBeginEnvironment` .... 37:394, 225  
`\BeforeClearDocument` ..... 52:577  
`\begin` ..... 09:83,  
     14:246, 14:248, 20:364, 20:416,  
     26:7, 30:4, 31:4, 37:244, 37:245,  
     37:315, 37:337, 37:362, 37:378,  
     37:386, 38:559, 38:571, 44:14, 44:17,  
     50:744, 06:801, 51:285, 53:400,  
     56:3, 07:1463, 07:1580, 07:2890, 1367  
`\begingroup` ..... 1308  
`\belowdisplayshortskip` .. 38:623, 02:290  
`\belowdisplayskip` ..... 38:622, 02:289  
`\beta` ..... 30:280  
`\bezier` ..... 933  
`\bezier` ..... 42:681,  
     42:682, 42:804, 42:805, 42:820, 42:822  
`\bf` ..... 1312  
`\bfdefault` 29:16, 29:340, 29:346, 29:347,  
     29:348, 29:349, 29:389, 29:390,  
     29:391, 29:392, 29:401, 29:437,  
     29:461, 29:480, 29:521, 29:555,  
     30:104, 30:115, 30:117, 30:125, 706  
`\bfseries` ..... 29:14, 29:15, 29:332,  
     29:333, 29:381, 29:386, 29:387,  
     29:428, 29:431, 29:432, 29:457,  
     29:459, 29:460, 29:553, 29:554,  
     32:19, 35:17, 35:34, 35:51, 43:53,  
     43:55, 43:60, 43:62, 47:40, 53:401, 703  
`bfseries` ..... 29:499  
`bfseries/defaults` ..... 29:499  
`\bgroup` ..... 02:325, 1319  
`\bibcite` ..... 47:7, 47:9, 47:10, 1338  
`\bibdata` ..... 47:45, 47:49  
`\bibitem` ..... 47:3  
`\bibliography` ..... 1009  
`\bibliography` ..... 47:47  
`\bibliographystyle` ..... 1009  
`\bibliographystyle` ..... 47:52  
`\bibstyle` ..... 47:45, 47:57  
`\Big` ..... 30:634, 30:637,  
     30:646, 30:648, 38:44, 38:45, 38:46  
`\big` ..... 30:635, 30:647, 38:41  
`\bigbreak` ..... 06:971, 06:992, 02:390  
`\bigcap` ..... 30:356  
`\bigcirc` ..... 30:403  
`\bigcup` ..... 30:357  
`\Bigg` ... 30:641, 30:650, 38:50, 38:51, 38:52  
`\bigg` ... 30:639, 30:649, 38:47, 38:48, 38:49  
`\Biggl` ..... 38:50

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\biggl</code> .....	38:47	<code>\bool_lazy_all:nTF</code> .....	07:963
<code>\Biggm</code> .....	38:51	<code>\bool_lazy_and:nnTF</code> .....	
<code>\biggm</code> .....	38:48	..... 08:1942, 08:2042,	
<code>\Biggr</code> .....	38:52	08:2492, 08:2960, 53:66, 53:112,	
<code>\biggr</code> .....	38:49	53:381, 07:750, 07:767, 07:959, 08:275	
<code>\Bigl</code> .....	38:44	<code>\bool_lazy_and_p:nn</code> ..	08:2495, 07:116
<code>\bigl</code> .....	38:41	<code>\bool_lazy_any:nTF</code> ...	07:112, 07:488
<code>\Bigm</code> .....	38:45	<code>\bool_lazy_or:nnTF</code> .....	
<code>\bigm</code> .....	38:42	. 08:1893, 07:77, 07:1422, 07:1431,	
<code>\bigodot</code> .....	30:364	07:2633, 07:2655, 07:2840, 08:903	
<code>\bigoplus</code> .....	30:363	<code>\bool_new:N</code> .... 10:6, 11:21, 11:22,	
<code>\bigotimes</code> .....	30:362	36:28, 48:339, 51:58, 53:6, 53:188,	
<code>\Bigr</code> .....	38:46	53:203, 07:19, 07:21, 07:23, 07:34,	
<code>\bigr</code> .....	38:43	07:35, 07:37, 07:38, 07:40, 07:43,	
<code>\bigskip</code> .....	18:447, 02:395	07:46, 07:47, 07:48, 07:49, 08:6, 08:24	
<code>\bigskipamount</code> .....		<code>\bool_set_false:N</code> 08:1932, 08:2032,	
..... 18:449, 18:450, 45:391, 02:394		11:278, 11:687, 11:768, 51:73, 07:61,	
<code>\bigsqcup</code> .....	30:367	07:87, 07:236, 07:258, 07:303, 55:76,	
<code>\bigtriangledown</code> .....	30:372, 30:373	55:84, 07:454, 07:455, 07:456,	
<code>\bigtriangleup</code> .....	30:371, 30:374	07:457, 07:458, 07:459, 07:480,	
<code>\biguplus</code> .....	30:355	07:542, 07:572, 07:597, 07:611,	
<code>\bigvee</code> .....	30:353	07:633, 07:634, 07:635, 07:650,	
<code>\bigwedge</code> .....	30:354	07:717, 07:760, 07:774, 07:775,	
<code>\binoppenalty</code> .....	02:193	07:798, 07:799, 07:800, 07:802,	
<code>block/list/label</code> (tag socket) ....	55:179	07:806, 07:816, 07:820, 07:976,	
<code>block/recipe</code> (tag socket) .....	55:180	07:977, 07:978, 07:979, 07:1599, 07:2087	
<code>\bmod</code> .....	38:35	<code>\bool_set_true:N</code> .....	08:1929,
<code>\boldmath</code> .....	19:14, 29:696	08:2029, 11:249, 11:291, 11:623,	
bool commands:		11:777, 51:70, 07:66, 07:237, 07:259,	
<code>\bool_gset_false:N</code> .....	10:16,	07:292, 55:74, 55:86, 07:453, 07:478,	
36:31, 48:348, 53:15, 53:81, 53:90, 08:15		07:549, 07:556, 07:557, 07:571,	
<code>\bool_gset_true:N</code> ... 10:11, 36:33,		07:763, 07:764, 07:815, 07:836,	
48:343, 53:10, 53:120, 53:344, 08:10		07:837, 07:843, 07:844, 07:850,	
<code>\bool_if:NTF</code> .....	08:1940,	07:851, 07:858, 07:859, 07:860,	
08:1949, 08:2040, 08:2049, 09:179,		07:995, 07:1013, 07:1604, 07:2092	
09:183, 09:195, 09:254, 09:258,		<code>\bool_while_do:nn</code> ... 08:1609, 08:1694	
09:270, 09:397, 10:22, 10:24, 11:223,		<code>\c_false_bool</code> .... 09:158, 09:168,	
11:229, 11:689, 11:792, 11:841,		09:387, 07:2479, 07:2782, 07:3115,	
11:858, 11:880, 36:71, 48:354,		07:3283, 08:397, 08:403, 08:411, 198	
51:24, 51:248, 53:21, 53:88, 53:370,		<code>\l_tmpa_bool</code> .....	356
07:125, 07:134, 07:146, 07:147,		<code>\c_true_bool</code> .....	
07:161, 07:173, 07:177, 07:186,		09:163, 07:2480, 07:2784, 07:3116,	
07:188, 07:198, 07:207, 07:208,		07:3281, 08:404, 08:412, 08:414, 198	
07:211, 07:216, 07:218, 07:322,		bool internal commands:	
55:119, 55:127, 55:147, 55:154,		<code>\g_mark_debug_bool</code> .....	
07:468, 07:477, 07:479, 07:534,		..... 48:339, 48:343, 48:348, 48:354	
07:565, 07:580, 07:629, 07:666,		<code>\BooleanFalse</code> .. 07:2080, 07:2472, 07:3115	
07:711, 07:721, 07:754, 07:762,		<code>\BooleanTrue</code> ... 07:2079, 07:2471, 07:3115	
07:771, 07:779, 07:784, 07:810,		<code>\bordermatrix</code> .....	38:185
07:829, 07:911, 07:957, 07:958,		<code>\bot</code> .....	30:332
07:1028, 07:1041, 07:1058, 07:1078,		<code>\botfigrule</code> .....	54:1092, 54:3025
07:1757, 07:2201, 07:2212, 07:2478,		<code>\botmark</code> ... 49:119, 54:1001, 54:1060, 1014	
07:2810, 07:2851, 08:21, 08:340, 198		<code>\bottomfraction</code> .....	45:275, 54:2994
<code>\bool_if_exist:NTF</code> .....	36:27	<code>\bowtie</code> .....	30:493

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

\Box	29:854
\box	1188
box commands:	
\box_dp:N	53:194
\box_gclear:N	16:89
\box_gset_to_last:N	16:16, 16:49, 16:117
\box_ht:N	53:193, 53:302, 1150
\box_if_empty:NTF	48:88, 53:78, 53:97
\box_if_horizontal:NTF	53:234, 53:286
\box_if_vertical:NTF	
.	48:83, 48:418, 48:450, 53:208, 53:259
\box_move_up:n	53:248, 53:302
\box_new:N	16:84, 48:63,
.	48:64, 53:23, 53:25, 53:187, 53:204
\box_set_dp:Nn	53:221, 53:230,
.	53:247, 53:272, 53:283, 53:301, 53:332
\box_set_eq:NN	53:149, 53:179, 53:184
\box_set_eq_drop:NN	53:93
\box_set_ht:Nn	53:220, 53:229,
.	53:246, 53:271, 53:282, 53:300, 53:331
\box_set_to_last:N	48:80
\box_set_wd:Nn	
.	53:219, 53:245, 53:270, 53:299
\box_use:N	53:126,
.	53:225, 53:250, 53:278, 53:303, 53:333
\box_use_drop:N	16:86
\box_wd:N	53:195, 53:296, 53:304
box internal commands:	
\l_mark_box	48:63, 48:76, 48:80,
.	48:83, 48:84, 48:87, 48:88, 48:98, 1028
\l_mark_ii_box	48:63, 48:87, 48:97
\boxmaxdepth	
.	42:474, 42:502, 42:532, 42:610,
.	42:627, 54:603, 54:742, 54:1074, 02:270
\brace	38:59
\bracedl	
.	30:564, 30:568, 30:569, 30:571, 30:573
\bracelu	30:566, 30:570, 30:572
\bracerd	30:565, 30:570, 30:572
\braceru	30:567, 30:569, 30:573
\bracevert	30:619
\brack	38:58
\break	18:116,
.	06:972, 06:993, 02:383, 02:388, 1338
\breve	30:532
\brokenpenalty	24:765, 02:198
build/column/after (hook)	54:731
build/column/baselineattach (socket)	
.	54:723
build/column/before (hook)	54:731
build/column/footer (tag socket)	55:230
build/column/footer (tag socket)	54:722
build/column/outputbox (socket)	54:663
build/column/outputbox (tag socket)	55:229
build/page/after (hook)	54:729
build/page/before (hook)	54:729
build/page/footer (tag socket)	55:227
build/page/header (tag socket)	55:227
build/page/reset (hook)	54:730
\buildrel	30:480, 38:162
\bullet	30:392
C	
\c	11:386, 21:254, 21:355, 21:357,
.	21:359, 21:361, 21:363, 21:365,
.	21:367, 21:369, 21:371, 21:392,
.	21:394, 21:413, 21:481, 21:501,
.	21:629, 21:631, 21:656, 21:658,
.	21:671, 21:697, 21:724, 21:727,
.	21:728, 21:729, 21:730, 21:731,
.	21:732, 21:733, 21:734, 21:735,
.	21:786, 21:1274, 21:1288, 21:1314,
.	21:1371, 21:1372, 21:1391, 21:1392,
.	21:1395, 21:1396, 21:1401, 21:1402,
.	21:1413, 21:1414, 21:1421, 21:1422,
.	21:1425, 21:1426, 33:131, 33:160, 1341
\cal	29:905
call commands:	
call_callback	04:798
\call_callback	44
callback commands:	
callback_descriptions	04:983
callback.register	04:686
\callback_descriptions	44
\cap	30:383
\capitalacute	21:863, 33:124,
.	33:125, 33:157, 33:654, 33:904, 33:1270
\capitalbreve	21:870, 33:126,
.	33:127, 33:158, 33:655, 33:911, 33:1277
\capitalcaron	21:869, 33:128,
.	33:129, 33:159, 33:656, 33:910, 33:1276
\capitalcedilla	21:856, 33:130,
.	33:131, 33:160, 33:657, 33:901, 33:1280
\capitalcircumflex	21:864, 33:132,
.	33:133, 33:161, 33:658, 33:905, 33:1271
\capitaldieresis	21:866, 33:134,
.	33:135, 33:162, 33:659, 33:907, 33:1273
\capitaldotaccent	21:872, 33:136,
.	33:137, 33:163, 33:660, 33:913, 33:1279
\capitalgrave	21:862, 33:138,
.	33:139, 33:164, 33:661, 33:903, 33:1269
\capitalhungarumlaut	21:867, 33:140,
.	33:141, 33:165, 33:662, 33:908, 33:1274
\capitalmacron	21:871, 33:142,
.	33:143, 33:166, 33:663, 33:912, 33:1278
\capitalnewtie	
.	21:876, 33:154, 33:155, 33:167,
.	33:664, 33:978, 33:979, 33:1285, 769

**File Key:** 01=ltdirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefs.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltxyphen.dtx, 57=ltfinal.dtx

- \capitalogonek . . . . . 21:859, 33:144,  
33:145, 33:168, 33:665, 33:902, 33:1281
- \capitalring . . . . . 21:868, 33:146,  
33:147, 33:169, 33:666, 33:909, 33:1275
- \capitaltie . . . . . 21:874, 33:148, 33:149,  
33:170, 33:667, 33:974, 33:975, 33:1283
- \capitaltilde . . . . . 21:865, 33:150,  
33:151, 33:171, 33:668, 33:906, 33:1272
- \caption . . . . . 45:4, 312
- caption/begin (tag socket) . . . . . 55:223
- caption/end (tag socket) . . . . . 55:223
- caption/label/begin (tag socket) . . . . . 55:225
- caption/label/end (tag socket) . . . . . 55:225
- \cases . . . . . 38:166, 38:167, 38:177, 38:179
- \CaseSwitch . . . . . 57:571, 1373
- \catcode . . . . . 835
- \catcodetable . . . . . 04:89, 04:109, 40
- \catcodetable@atletter . . . . . 41
- \catcodetable@initex . . . . . 41
- \catcodetable@latex . . . . . 41
- \catcodetable@string . . . . . 41
- \catcoding . . . . . 1308
- \cdot . . . . . 30:405
- \cdotp . . . . . 30:513, 30:519
- \cdots . . . . . 30:519
- center (env.) . . . . . 37:446
- \center . . . . . 37:446
- \centering . . . . . 37:446, 37:451,  
37:452, 37:470, 37:472, 37:487, 37:489
- \centerline . . . . . 40:614
- \changes . . . . . 29:766, 35:158, 1348
- \chapter . . . . . 526
- \chaptermark . . . . . 1020
- \char . . . . . 21:412, 21:415, 21:451, 21:454,  
21:465, 21:472, 21:500, 21:504,  
21:509, 21:512, 21:514, 21:516,  
21:757, 21:785, 21:788, 21:821,  
21:828, 21:835, 21:858, 21:861,  
21:890, 21:920, 21:1030, 21:1065,  
21:1189, 21:1191, 21:1193, 21:1240,  
29:709, 29:716, 33:595, 33:602,  
33:604, 33:724, 37:578, 37:745,  
38:251, 42:232, 42:282, 42:296,  
42:304, 42:307, 42:448, 42:562,  
42:567, 42:575, 42:579, 42:615,  
42:616, 42:618, 42:631, 42:632,  
42:635, 42:662, 06:934, 06:949, 1341
- char commands:
- \char\_generate:nn . . . . . 05:149, 07:1909, 07:2221
- \char\_set\_catcode\_active:N . . . . . 07:2503
- \char\_set\_catcode\_active:n . . . . . 07:2199, 07:2200, 07:2680
- \char\_set\_catcode\_escape:N . . . . . 09:461
- \char\_set\_catcode\_group\_begin:N . . . . . 09:462
- \char\_set\_catcode\_group\_end:N . . . . . 09:463
- \char\_set\_catcode\_other:N . . . . . 07:1614, 07:1620,  
07:1656, 07:1705, 07:1744, 07:1808,  
07:1830, 07:1832, 07:2197, 07:2210
- \char\_set\_catcode\_other:n . . . . . 07:1616, 07:2202, 07:2213
- \char\_set\_catcode\_parameter:N . . . . . 09:464
- \char\_set\_catcode\_parameter:n . . . . . 07:2203, 07:2214
- \char\_set\_catcode\_space:n . . . . . 09:399, 07:1834
- \char\_set\_lccode:nn . . . . . 07:2508, 07:2690
- \char\_value\_catcode:n . . . . . 09:392
- \chardef . . . . . 04:22, 04:26, 04:38, 04:47,  
04:48, 12:2, 04:89, 04:157, 04:224,  
20:52, 20:122, 21:36, 24:15, 41:4,  
41:9, 02:10, 02:16, 02:17, 02:18,  
02:19, 02:20, 50:1262, 50:1393,  
50:1510, 02:54, 02:60, 02:62, 02:69,  
02:75, 02:78, 02:80, 57:42, 57:44,  
57:48, 57:67, 57:171, 57:172, 57:173,  
57:174, 57:175, 57:176, 57:177,  
02:86, 02:87, 02:90, 02:92, 02:117,  
02:143, 02:145, 02:169, 01:48, 01:54,  
01:55, 02:404, 02:405, 02:406, 1356
- \charsubdef . . . . . 57:353
- \charzero . . . . . 04:224
- \check . . . . . 30:533
- \CheckCommand . . . . . 06:228, 1325
- \CheckEncodingSubset . . . . . 24:204, 33:16, 33:73, 33:74, 33:75,  
33:120, 33:122, 33:316, 33:585,  
33:794, 33:843, 33:899, 33:900,  
33:968, 33:1085, 33:1088, 33:1102, 765
- \chi . . . . . 30:299
- \choose . . . . . 38:57
- \circ . . . . . 30:402
- \circle . . . . . 42:450, 42:604, 42:806, 42:823, 1308
- \citation . . . . . 47:11, 47:39, 47:67, 47:84
- \cite . . . . . 1009
- \cite . . . . . 47:12, 1010
- \clap . . . . . 40:618, 1362
- class/.../after . . . . . 1116
- class/.../before . . . . . 1116
- class/after . . . . . 1116
- class/before . . . . . 1116
- \ClassError . . . . . 14:84
- \ClassInfo . . . . . 14:84
- \ClassNote . . . . . 14:136, 1369
- \ClassNoteNoLine . . . . . 14:136
- \ClassWarning . . . . . 14:84

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

`\ClassWarningNoLine` ..... [14:84](#)  
`\cleaders` ..... [30:559](#), [30:562](#), [02:424](#)  
`\cleardoublepage` ..... [54:117](#)  
`\ClearHookNext` ..... [08:2811](#), [206](#)  
`\ClearHookRule` .... [08:2848](#), [08:2953](#), [210](#)  
`\clearpage` ..... [20:316](#), [20:343](#),  
[20:347](#), [20:378](#), [20:401](#), [20:404](#),  
[20:425](#), [20:443](#), [37:17](#), [37:85](#), [37:149](#),  
[37:242](#), [54:103](#), [54:117](#), [54:122](#),  
[54:205](#), [54:412](#), [54:415](#), [54:419](#),  
[54:460](#), [54:466](#), [54:2846](#), [54:2863](#), [1160](#)  
`\cline` ..... [41:367](#), [1272](#)  
clist commands:  
`\clist_clear:N` .. [51:66](#), [51:167](#), [51:187](#)  
`\clist_gclear:N` .... [08:1608](#), [08:1693](#)  
`\clist_gput_left:Nn` . [08:1512](#), [08:1547](#)  
`\clist_gput_right:Nn` [08:1514](#), [08:1551](#)  
`\clist_if_empty:NTF` .....  
[08:1959](#), [08:2060](#), [11:542](#), [11:571](#), [51:76](#)  
`\clist_if_exist:NTF` ..... [08:121](#)  
`\clist_if_in:NnTF` . [11:267](#), [11:578](#),  
[51:51](#), [51:52](#), [51:129](#), [51:152](#), [51:154](#)  
`\clist_map_function:nN` ..... [36:59](#)  
`\clist_map_inline:Nn` [11:544](#), [51:78](#),  
[51:110](#), [51:141](#), [51:176](#), [51:190](#), [51:236](#)  
`\clist_map_inline:nn` [51:64](#), [51:271](#),  
[57:656](#), [57:661](#), [57:666](#), [08:934](#), [08:943](#)  
`\clist_map_variable:NNn` ..... [51:71](#)  
`\clist_new:N` ..... [11:33](#), [51:54](#),  
[51:55](#), [51:56](#), [51:57](#), [08:123](#), [08:140](#)  
`\clist_put_right:Nn` .....  
[51:33](#), [51:53](#), [51:123](#), [51:130](#),  
[51:137](#), [51:162](#), [51:178](#), [51:186](#), [51:202](#)  
`\clist_remove_all:Nn` .....  
[11:580](#), [51:35](#), [51:136](#), [51:163](#), [51:203](#)  
`\clist_set:Nn` ..... [11:532](#)  
`\clist_set_eq:NN` ..... [51:172](#)  
`\clist_use:Nn` ..... [08:1961](#), [08:2062](#)  
`\l_tmpa_clist` ..... [356](#)  
`\clubpenalty` .....  
[20:8](#), [20:25](#), [20:95](#), [20:152](#), [24:763](#),  
[39:128](#), [39:225](#), [39:227](#), [44:100](#),  
[44:106](#), [44:130](#), [44:135](#), [02:195](#), [423](#)  
`\clubsuit` ..... [30:342](#)  
cmd commands:  
`\cmd_arg_spec:N` .....  
[07:2817](#), [07:2817](#), [07:2835](#)  
cmd internal commands:  
`\__cmd_add_arg:n` ..... [07:1755](#),  
[07:1824](#), [07:1856](#), [07:1861](#), [07:1862](#),  
[07:1896](#), [07:1984](#), [07:1991](#), [07:2066](#),  
[07:2079](#), [07:2080](#), [07:2154](#), [07:2227](#),  
[07:2234](#), [07:2278](#), [07:2278](#), [07:2283](#), [157](#)  
`\__cmd_add_arg_spec:n` ... [07:595](#),  
[07:609](#), [07:673](#), [07:748](#), [07:748](#), [07:792](#)  
`\__cmd_add_arg_spec_mandatory:n` .  
[07:641](#), [07:651](#), [07:657](#), [07:748](#), [07:777](#)  
`\__cmd_add_default:` ..... [07:872](#),  
[07:910](#), [07:927](#), [07:989](#), [07:992](#),  
[07:999](#), [07:1009](#), [07:1076](#), [07:1085](#), [137](#)  
`\__cmd_add_default:n` .....  
[07:879](#), [07:919](#), [07:935](#),  
[07:989](#), [07:989](#), [07:1006](#), [07:1020](#), [137](#)  
`\__cmd_add_default_E:nn` .....  
[07:887](#), [07:989](#), [07:1004](#), [07:1054](#)  
`\__cmd_add_expandable_grabber:nn`  
[07:1033](#), [07:1046](#), [07:1057](#),  
[07:1077](#), [07:1087](#), [07:1094](#), [07:1094](#)  
`\__cmd_add_expandable_type_+ :w` ..  
[07:1011](#)  
`\__cmd_add_expandable_type_D:w` ..  
[07:1016](#), [07:1016](#)  
`\__cmd_add_expandable_type_D_-`  
aux:NN ... [07:1016](#), [07:1022](#), [07:1039](#)  
`\__cmd_add_expandable_type_D_-`  
aux:NNN .. [07:1016](#), [07:1023](#), [07:1026](#)  
`\__cmd_add_expandable_type_D_-`  
aux:NNNn .....  
[07:1016](#), [07:1017](#), [07:1018](#), [07:1082](#)  
`\__cmd_add_expandable_type_E:w` ..  
[07:1052](#), [07:1052](#)  
`\__cmd_add_expandable_type_E_-`  
aux:n .... [07:1052](#), [07:1056](#), [07:1068](#)  
`\__cmd_add_expandable_type_m:w` ..  
[07:1074](#), [07:1074](#)  
`\__cmd_add_expandable_type_R:w` ..  
[07:1081](#), [07:1081](#)  
`\__cmd_add_expandable_type_t:w` ..  
[07:1083](#), [07:1083](#)  
`\__cmd_add_grabber:N` .... [07:873](#),  
[07:880](#), [07:893](#), [07:912](#), [07:920](#),  
[07:928](#), [07:936](#), [07:950](#), [07:950](#), [139](#)  
`\__cmd_add_type_! :w` ..... [07:840](#)  
`\__cmd_add_type_+ :w` ..... [07:833](#)  
`\__cmd_add_type_= :w` ..... [07:855](#)  
`\__cmd_add_type_> :w` ..... [07:847](#)  
`\__cmd_add_type_b:w` .. [07:865](#), [07:865](#)  
`\__cmd_add_type_b_or_c:N` .....  
[07:865](#), [07:866](#), [07:868](#), [07:869](#)  
`\__cmd_add_type_c:w` .. [07:865](#), [07:867](#)  
`\__cmd_add_type_D:w` .. [07:876](#), [07:876](#)  
`\__cmd_add_type_E:w` .. [07:884](#), [07:884](#)  
`\__cmd_add_type_m:w` .. [07:908](#), [07:908](#)  
`\__cmd_add_type_R:w` .. [07:916](#), [07:916](#)  
`\__cmd_add_type_t:w` .. [07:924](#), [07:924](#)  
`\__cmd_add_type_v:w` .. [07:932](#), [07:932](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

`\__cmd_all_m_check:n` ..... 07:100, 07:100, 07:120  
`\__cmd_all_m_check_aux:n` ..... 07:100, 07:101, 07:102  
`\__cmd_allowed_token_check:N` ... 07:593,  
 07:605, 07:626, 07:647, 07:690, 07:690  
`\__cmd_arg_spec_opt:N` ..... 07:2817, 07:2826, 07:2836  
`\l__cmd_arg_spec_tl` ..... 07:12, 07:94, 07:452,  
 07:540, 07:573, 07:627, 07:765, 129  
`\__cmd_arg_to_keyvalue:nn` ..... 07:862, 07:2562, 07:2562  
`\__cmd_arg_to_keyvalue_auxi:nnn` . 07:2562, 07:2577, 07:2579  
`\__cmd_arg_to_keyvalue_auxii:Nnnn` . 07:2562, 07:2582, 07:2585  
`\__cmd_arg_to_keyvalue_auxiii:nnn` . 07:2562, 07:2588, 07:2591  
`\__cmd_arg_to_keyvalue_auxiv:Nnnn` . 07:2562, 07:2594, 07:2597  
`\__cmd_arg_to_keyvalue_auxv:nn` .. 07:2562, 07:2583,  
 07:2589, 07:2595, 07:2601, 07:2603  
`\__cmd_arg_to_keyvalue_braces:nnn` . 07:2562, 07:2564, 07:2567  
`\__cmd_arg_to_keyvalue_loop:w` ... 07:2562, 07:2605, 07:2608,  
 07:2620, 07:2622, 07:2637, 07:2658  
`\__cmd_arg_to_keyvalue_loop-`  
`group:n` .. 07:2562, 07:2614, 07:2619  
`\__cmd_arg_to_keyvalue_loop_N-`  
`type:N` ... 07:2562, 07:2611, 07:2623  
`\__cmd_arg_to_keyvalue_loop-`  
`space:w` .. 07:2562, 07:2615, 07:2621  
`\__cmd_arg_to_keyvalue_math:w` ... 07:2562, 07:2636,  
 07:2640, 07:2659, 07:2662, 07:2664  
`\__cmd_arg_to_keyvalue_math-`  
`group:n` .. 07:2562, 07:2646, 07:2661  
`\__cmd_arg_to_keyvalue_math_N-`  
`type:N` ... 07:2562, 07:2643, 07:2651  
`\__cmd_arg_to_keyvalue_math-`  
`space:w` .. 07:2562, 07:2647, 07:2663  
`\__cmd_arg_to_keyvalue_set-`  
`default:nn` ..... 07:2562, 07:2626, 07:2654, 07:2665, 183  
`\__cmd_arg_to_keyvalue_set-`  
`keyvalue:nn` ..... 07:2562, 07:2630, 07:2667, 183  
`\l__cmd_args_i_tl` .. 07:14, 07:331,  
 07:337, 07:342, 07:343, 07:345, 113  
`\l__cmd_args_ii_tl` ..... 07:15, 07:341, 07:343,  
 07:345, 07:383, 07:388, 07:395, 113  
`\__cmd_args_process:` ..... 07:321, 07:381, 07:381, 137  
`\__cmd_args_process_aux:n` ..... 07:381, 07:394, 07:398  
`\__cmd_args_process_loop:nn` ..... 07:381, 07:387, 07:390  
`\l__cmd_args_tl` ... 07:13, 07:284,  
 07:309, 07:326, 07:331, 07:337,  
 07:356, 07:385, 07:388, 07:401,  
 07:402, 07:1582, 07:1583, 07:1588,  
 07:1591, 07:1962, 07:1996, 07:2280, 157  
`\__cmd_bad_arg_spec:wn` ... 07:510,  
 07:515, 07:524, 07:533, 07:579,  
 07:592, 07:602, 07:603, 07:608,  
 07:619, 07:625, 07:646, 07:742, 07:742  
`\__cmd_bad_def:wn` ..... 07:466, 07:474, 07:503, 07:538,  
 07:569, 07:584, 07:670, 07:679,  
 07:687, 07:706, 07:715, 07:727,  
 07:742, 07:747, 07:758, 07:788, 146  
`\__cmd_bool_reverse:N` ..... 07:2476, 07:2476, 07:3314  
`\__cmd_break_point:n` ..... 07:97, 07:99, 07:99, 07:742,  
 07:747, 07:1144, 07:1151, 07:1362  
`\__cmd_cant_copy:nwn` ..... 07:1141, 07:1151,  
 07:1151, 07:1267, 07:1330, 07:1360  
`\__cmd_check_definable:nNTF` .... 07:2677, 07:2677,  
 07:3119, 07:3132, 07:3145, 07:3150,  
 07:3238, 07:3251, 07:3264, 07:3272  
`\__cmd_check_definable_aux:nN` ... 07:2677, 07:2678, 07:2681, 186  
`\__cmd_check_end:n` ..... 07:1326, 07:1328, 07:1334  
`\__cmd_check_end:Nn` ... 07:1313,  
 07:1314, 07:1326, 07:1326, 07:1479  
`\__cmd_check_end:w` ..... 07:1326, 07:1336, 07:1339  
`\__cmd_chk_if_free_cs:N` ..... 07:3319, 07:3320  
`\__cmd_cmd_if_xparse:NTF` .... 1368  
`\__cmd_cmd_if_xparse_aux:N` . 07:2744  
`\__cmd_cmd_type_cases:NnnnnnTF` .. 07:1135,  
 07:1354, 07:2744, 07:2744, 07:2767, 151  
`\__cmd_cmd_type_cases:NnnnnTF` . 1369  
`\__cmd_copy:NN` ..... 07:1128, 07:1130, 07:1130,  
 07:1165, 07:1180, 07:1226, 07:1344, 146

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

`\__cmd_copy_command:nnNN` .....  
       07:1136, 07:1166, 07:1166, 147  
`\__cmd_copy_command:NnNNnnnn` ...  
       07:1166, 07:1171, 07:1173, 147  
`\__cmd_copy_environment:nnNN` ...  
       07:1139, 07:1300, 07:1300  
`\__cmd_copy_environment:Nnnnnnn` .  
       07:1300, 07:1306, 07:1309  
`\__cmd_copy_environment_end:nnNN`  
       07:1140, 07:1311, 07:1311  
`\__cmd_copy_environment_end_`  
`aux:nnNN` . 07:1311, 07:1315, 07:1318  
`\__cmd_copy_expandable:nnN` .....  
       07:1245, 07:1250, 07:1253,  
       07:1280, 07:1290, 07:1296, 07:1298  
`\__cmd_copy_expandable:nnNN` .....  
       07:1137, 07:1179, 07:1183,  
       07:1185, 07:1198, 07:1200, 07:1211  
`\__cmd_copy_expandable:NnNNNNnnn`  
       07:1179, 07:1195, 07:1208, 07:1228, 147  
`\__cmd_copy_expandable_signature:NnNNNNnnn`  
       07:1191, 07:1206, 07:1245, 07:1245, 147  
`\__cmd_copy_grabber_(type):w` ... 149  
`\__cmd_copy_grabber_D:w` .....  
       07:1270, 07:1270, 07:1283, 07:1284  
`\__cmd_copy_grabber_D_alt:w` ....  
       07:1270, 07:1282, 07:1285  
`\__cmd_copy_grabber_E:w` .....  
       07:1270, 07:1286, 07:1292  
`\__cmd_copy_grabber_E_long:w` ...  
       07:1270, 07:1292  
`\__cmd_copy_grabber_m:w` .....  
       07:1270, 07:1298, 07:1299  
`\__cmd_copy_grabber_m_long:w` ...  
       07:1270, 07:1299  
`\__cmd_copy_grabber_R:w` .....  
       07:1270, 07:1284  
`\__cmd_copy_grabber_R_alt:w` ....  
       07:1270, 07:1285  
`\__cmd_copy_grabber_t:w` .....  
       07:1270, 07:1293  
`\__cmd_copy_optimized:nnNN` .....  
       07:1138, 07:1214, 07:1214  
`\__cmd_copy_parse_grabber:w` ....  
       07:1245, 07:1257, 07:1261, 149  
`\l__cmd_current_arg_int` .....  
       07:16, 07:28, 07:150, 07:158,  
       07:187, 07:194, 07:274, 07:355,  
       07:359, 07:364, 07:365, 07:449,  
       07:462, 07:485, 07:541, 07:587,  
       07:612, 07:791, 07:796, 07:797,  
       07:968, 07:994, 07:1001, 07:1248,  
       07:1256, 07:1274, 07:1278, 07:1279,  
       07:1289, 07:1488, 07:1554, 07:1563, 113  
`\__cmd_declare_cmd:Nnn` .....  
       07:59, 07:59,  
       07:3127, 07:3135, 07:3146, 07:3151  
`\__cmd_declare_cmd_aux:Nnn` .....  
       07:59, 07:62, 07:67, 07:69  
`\__cmd_declare_cmd_code:Nnn` ....  
       07:95, 07:110, 07:110  
`\__cmd_declare_cmd_code_aux:Nnn` .  
       07:110, 07:127, 07:154  
`\__cmd_declare_cmd_code_expandable:Nnn`  
       07:110, 07:126, 07:182  
`\__cmd_declare_cmd_internal:Nnnnn`  
       07:59, 07:88, 07:90, 07:267, 122  
`\__cmd_declare_cmd_optimized:Nnn`  
       07:110, 07:129, 07:132  
`\__cmd_declare_env:nnnn` .....  
       07:228, 07:228,  
       07:230, 07:240, 07:242, 07:244,  
       07:3169, 07:3184, 07:3190, 07:3200,  
       07:3215, 07:3221, 07:3225, 07:3227, 196  
`\__cmd_declare_env_internal:nnnn`  
       07:228, 07:238, 07:260, 07:265  
`\__cmd_declare_expandable_`  
`cmd:Nnn` ..... 07:59, 07:64,  
       07:3246, 07:3254, 07:3267, 07:3273  
`\__cmd_defaults:` 07:320, 07:328, 07:328  
`\__cmd_defaults_aux:` .....  
       07:328, 07:332, 07:333, 07:334, 07:339  
`\l__cmd_defaults_bool` .....  
       07:19, 07:173,  
       07:188, 07:211, 07:802, 07:995, 114  
`\__cmd_defaults_def:` .....  
       07:328, 07:330, 07:352  
`\__cmd_defaults_def:nn` .....  
       07:328, 07:357, 07:362  
`\__cmd_defaults_def:nnn` .....  
       07:328, 07:365, 07:367  
`\__cmd_defaults_error:w` .....  
       07:328, 07:335, 07:347  
`\l__cmd_defaults_tl` ..... 07:20,  
       07:174, 07:195, 07:312, 07:320,  
       07:356, 07:803, 07:996, 07:1002, 114  
`\__cmd_delimiter_check:nnn` .....  
       07:640, 07:649, 07:731, 07:731  
`\__cmd_end_expandable:NNw` .....  
       07:408, 07:410, 07:410  
`\__cmd_end_expandable_aux:nNNNN` .  
       07:410, 07:413, 07:414  
`\__cmd_end_expandable_aux:w` ....  
       07:410, 07:411, 07:412  
`\__cmd_end_expandable_defaults:nnnNNn`  
       07:410, 07:417,  
       07:426, 07:435, 07:445, 07:446, 126

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

```

\__cmd_end_expandable_defaults:nnw
..... 07:410, 07:434, 07:438
\__cmd_end_expandable_defaults:nw
..... 07:410, 07:441, 07:442, 07:444
\l__cmd_environment_bool .....
.... 07:21, 07:87, 07:114, 07:161,
07:237, 07:259, 07:292, 07:303,
07:322, 07:479, 07:666, 07:2851, 114
\__cmd_environment_or_command: ..
... 07:350, 07:465, 07:497, 07:501,
07:583, 07:669, 07:677, 07:686,
07:701, 07:745, 07:782, 07:2064,
07:2224, 07:2231, 07:2849, 07:2849
\l__cmd_environment_str .....
..... 07:22, 07:164, 07:232,
07:246, 07:247, 07:248, 07:249,
07:252, 07:256, 07:261, 07:291,
07:294, 07:295, 07:323, 07:2852, 114
\l__cmd_expandable_aux_name_tl ..
..... 07:24, 07:25,
07:1031, 07:1035, 07:1044, 07:1048, 114
\l__cmd_expandable_bool .....
07:23, 07:61, 07:66, 07:134, 07:146,
07:186, 07:198, 07:236, 07:258,
07:468, 07:477, 07:534, 07:565,
07:711, 07:721, 07:754, 07:810, 114
\__cmd_expandable_grab_D:nnNNwNN
..... 07:2284, 07:2308, 07:2314
\__cmd_expandable_grab_D:NNwNNn
..... 07:2284, 07:2285, 07:2288
\__cmd_expandable_grab_D:NNwNNnnn
..... 07:2284,
07:2299, 07:2306, 07:2332, 07:2427, 176
\__cmd_expandable_grab_D:Nw ....
..... 07:2284, 07:2310, 07:2313
\__cmd_expandable_grab_D:w .....
..... 07:2284, 07:2284
\__cmd_expandable_grab_D_-
alt:NNwn . 07:2351, 07:2358, 07:2454
\__cmd_expandable_grab_D_-
alt:NNwNNn 07:2336, 07:2337, 07:2340
\__cmd_expandable_grab_D_alt:Nwn
..... 07:2336
\__cmd_expandable_grab_D_alt:w ..
..... 07:2336, 07:2336
\__cmd_expandable_grab_E:w .....
..... 07:2371, 07:2371
\__cmd_expandable_grab_E_aux:w ..
..... 07:2371,
07:2372, 07:2374, 07:2375, 07:2403
\__cmd_expandable_grab_E_end:nnw
..... 07:2371, 07:2387, 07:2404
\__cmd_expandable_grab_E_-
find:nnw . 07:2371, 07:2401, 07:2402
\__cmd_expandable_grab_E_find:w .
..... 07:2371, 07:2392, 07:2400
\__cmd_expandable_grab_E_long:w .
..... 07:2371, 07:2373
\__cmd_expandable_grab_E_-
loop:nnnNNw .....
.. 07:2371, 07:2379, 07:2383, 07:2394
\__cmd_expandable_grab_E_-
test:nnw . 07:2371, 07:2376, 07:2377
\__cmd_expandable_grab_m:w .....
..... 07:2406, 07:2406, 150
\__cmd_expandable_grab_m_aux:wNn
.. 07:2406, 07:2407, 07:2409, 07:2410
\__cmd_expandable_grab_m_long:w .
..... 07:2406, 07:2408
\__cmd_expandable_grab_R:w .....
..... 07:2412, 07:2412
\__cmd_expandable_grab_R_alt:w ..
..... 07:2439, 07:2439
\__cmd_expandable_grab_R_alt_-
aux:NNwNNn 07:2439, 07:2440, 07:2443
\__cmd_expandable_grab_R_-
aux:NNwNNn 07:2412, 07:2413, 07:2416
\__cmd_expandable_grab_t:w .....
..... 07:2466, 07:2466
\__cmd_expandable_grab_t_-
aux:NNwn . 07:2466, 07:2467, 07:2468
\l__cmd_final_verb_bool .....
... 07:49, 07:815, 07:816, 07:965, 116
\__cmd_flush_m_args: .... 07:810,
07:835, 07:842, 07:849, 07:857,
07:871, 07:878, 07:886, 07:918,
07:926, 07:934, 07:939, 07:939, 139
\l__cmd_fn_code_tl .....
..... 07:32, 07:311, 07:326, 115
\l__cmd_fn_tl .....
... 07:31, 07:123, 07:310, 07:1584,
07:1850, 07:1874, 07:1880, 07:1890,
07:1900, 07:1909, 07:1914, 07:1918,
07:1949, 07:1975, 07:1983, 07:1985,
07:1990, 07:1992, 07:2003, 07:2004,
07:2009, 07:2010, 07:2015, 07:2016,
07:2021, 07:2022, 07:2027, 07:2028,
07:2033, 07:2034, 07:2039, 07:2040,
07:2045, 07:2046, 07:2076, 07:2082, 157
\l__cmd_function_tl .....
..... 07:27, 07:33, 07:92, 07:124,
07:140, 07:143, 07:157, 07:168,
07:169, 07:185, 07:193, 07:203,
07:206, 07:210, 07:212, 07:220,
07:226, 07:473, 07:537, 07:568,
07:714, 07:726, 07:757, 07:2855, 115
\__cmd_get_grabber:NN .....
07:1070, 07:1086, 07:1099, 07:1099, 143

```

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

```

\__cmd_get_grabber_auxi:NN .....
.. 07:1099, 07:1102, 07:1105, 07:1113
\__cmd_get_grabber_auxii:NN .....
..... 07:1099, 07:1120, 07:1123
\__cmd_grab_b:w ..... 07:1570, 07:1570
\__cmd_grab_b_aux:NNw .....
..... 07:1570, 07:1571,
07:1573, 07:1575, 07:1577, 07:1578
\__cmd_grab_b_end:Nw .....
..... 07:1570, 07:1581, 07:1586
\__cmd_grab_b_long:w 07:1570, 07:1572
\__cmd_grab_b_long_obey_spaces:w
..... 07:1570, 07:1576
\__cmd_grab_b_obey_spaces:w .....
..... 07:1570, 07:1574
\__cmd_grab_c:w ..... 07:1597, 07:1597
\__cmd_grab_c_auxi:w .....
..... 07:1636, 07:1641, 07:1643
\__cmd_grab_c_auxii:w .....
..... 07:1641, 07:1653, 07:1659
\__cmd_grab_c_auxiii:N .....
.. 07:1641, 07:1665, 07:1667, 07:1676
\__cmd_grab_c_auxiv: .....
.. 07:1641, 07:1672, 07:1690, 07:1713
\__cmd_grab_c_auxv: ..... 07:1641,
07:1686, 07:1699, 07:1718, 07:1740
\__cmd_grab_c_auxvi:N .....
.. 07:1641, 07:1681, 07:1706, 07:1728
\__cmd_grab_c_auxvii: .. 07:1641,
07:1712, 07:1717, 07:1732, 07:1739
\__cmd_grab_c_auxviii: .....
..... 07:1641, 07:1723, 07:1734
\__cmd_grab_c_end:n .....
..... 07:1743, 07:1759, 07:1765
\__cmd_grab_c_end:w .....
..... 07:1737, 07:1743, 07:1745
\__cmd_grab_c_end_auxi:w .....
..... 07:1743, 07:1767, 07:1770
\__cmd_grab_c_end_auxii:w .....
..... 07:1743, 07:1771, 07:1772
\__cmd_grab_c_end_auxiii:w .....
..... 07:1743, 07:1773, 07:1774
\__cmd_grab_c_first:w .....
..... 07:1597, 07:1617, 07:1621
\__cmd_grab_c_loop:w .....
..... 07:1597, 07:1625, 07:1631,
07:1634, 07:1651, 07:1697, 07:1702
\__cmd_grab_c_obey_spaces:w .....
..... 07:1597, 07:1602
\__cmd_grab_c_start:n .....
.. 07:1597, 07:1600, 07:1605, 07:1607
\__cmd_grab_D:w ..... 07:1776
\__cmd_grab_D_aux:NNNN . 07:1580,
07:1807, 07:1811, 07:1847, 07:2059
\__cmd_grab_D_aux:NNNNNN .....
..... 07:1788, 07:1807, 07:1809
\__cmd_grab_D_call:Nw .....
07:1820, 07:1904, 07:1904, 07:2061, 162
\__cmd_grab_D_long:w ..... 07:1776
\__cmd_grab_D_long_no_strip:w 07:1776
\__cmd_grab_D_long_obey_spaces:w
..... 07:1776
\__cmd_grab_D_long_obey_spaces_-
no_strip:w ..... 07:1776
\__cmd_grab_D_nested:NNNN .....
..... 07:1853, 07:1867, 07:1870
\__cmd_grab_D_nested:w .....
..... 07:1867, 07:1885, 07:1902
\__cmd_grab_D_no_strip:w ... 07:1776
\__cmd_grab_D_obey_spaces:w 07:1776
\__cmd_grab_D_obey_spaces_no_-
strip:w ..... 07:1776
\__cmd_grab_D_verb_safe:NN .....
..... 07:1807, 07:1815, 07:1828
\__cmd_grab_E:nnNN 07:1923, 07:1925,
07:1931, 07:1937, 07:1943, 07:1947
\__cmd_grab_E:w .... 07:1923, 07:1923
\__cmd_grab_E_finalise: .....
.. 07:1923, 07:1956, 07:1972, 07:1979
\__cmd_grab_E_long:w 07:1923, 07:1929
\__cmd_grab_E_long_obey_spaces:w
..... 07:1923, 07:1941
\__cmd_grab_E_loop:NnN .. 07:1923,
07:1952, 07:1967, 07:1969, 07:1976
\__cmd_grab_E_obey_spaces:w ....
..... 07:1923, 07:1935
\l__cmd_grab_expandably_bool ...
..... 07:34, 07:125,
07:453, 07:478, 07:480, 07:542,
07:572, 07:597, 07:611, 07:633,
07:650, 07:717, 07:760, 07:829, 115
\__cmd_grab_m:w .... 07:1980, 07:1980
\__cmd_grab_m_1:w ..... 07:1994
\__cmd_grab_m_2:w ..... 07:1994
\__cmd_grab_m_3:w ..... 07:1994
\__cmd_grab_m_4:w ..... 07:1994
\__cmd_grab_m_5:w ..... 07:1994
\__cmd_grab_m_6:w ..... 07:1994
\__cmd_grab_m_7:w ..... 07:1994
\__cmd_grab_m_8:w ..... 07:1994
\__cmd_grab_m_9:w ..... 07:1994
\__cmd_grab_m_aux:Nnnnnnnnn .....
..... 07:1994, 07:1994,
07:2003, 07:2009, 07:2015, 07:2021,
07:2027, 07:2033, 07:2039, 07:2045
\__cmd_grab_m_long:w 07:1980, 07:1987
\__cmd_grab_R:w .... 07:2053, 07:2053

```

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

\\_\_cmd\_grab\_R\_aux:NNnN ..... 07:470, 07:596, 07:610, 07:632,  
     .. 07:2053, 07:2054, 07:2056, 07:2057 07:672, 07:723, 07:733, 07:790, 131  
 \\_\_cmd\_grab\_R\_long:w 07:2053, 07:2055  
 \\_\_cmd\_grab\_t:w .... 07:2069, 07:2069  
 \\_\_cmd\_grab\_t\_aux:NNw .....  
     .. 07:2069, 07:2070, 07:2072, 07:2073  
 \\_\_cmd\_grab\_t\_obey\_spaces:w ....  
     ..... 07:2069, 07:2071  
 \\_\_cmd\_grab\_v:w .... 07:2085, 07:2085  
 \\_\_cmd\_grab\_v\_aux:w .....  
     07:2085, 07:2088, 07:2093, 07:2095, 171  
 \\_\_cmd\_grab\_v\_aux\_abort:n .....  
     07:2112, 07:2130, 07:2136, 07:2149,  
     07:2168, 07:2191, 07:2193, 07:2217, 171  
 \\_\_cmd\_grab\_v\_aux\_catcodes: ....  
     ..... 07:2127, 07:2159, 07:2193,  
     07:2193, 07:2195, 07:2206, 07:2208, 170  
 \\_\_cmd\_grab\_v\_aux\_loop:N .....  
     .. 07:2122, 07:2128, 07:2132, 07:2146  
 \\_\_cmd\_grab\_v\_aux\_loop:NN .....  
     ..... 07:2122, 07:2135, 07:2138  
 \\_\_cmd\_grab\_v\_aux\_loop\_end: ....  
     .. 07:2122, 07:2143, 07:2151, 07:2182  
 \\_\_cmd\_grab\_v\_aux\_put:N .....  
     07:2126, 07:2145, 07:2161, 07:2179,  
     07:2187, 07:2237, 07:2237, 07:2239,  
     07:2249, 07:2251, 07:2265, 07:2267  
 \\_\_cmd\_grab\_v\_aux\_test:N .....  
     ..... 07:2111, 07:2122, 07:2122  
 \\_\_cmd\_grab\_v\_bgroup: .....  
     ..... 07:2107, 07:2157, 07:2157  
 \\_\_cmd\_grab\_v\_bgroup\_loop: ....  
     ..... 07:2157,  
     07:2162, 07:2164, 07:2180, 07:2188  
 \\_\_cmd\_grab\_v\_bgroup\_loop:N ....  
     ..... 07:2157, 07:2167, 07:2170  
 \\_\_cmd\_grab\_v\_group\_end: .....  
     07:2085, 07:2116, 07:2153, 07:2219, 170  
 \\_\_cmd\_grab\_v\_long:w 07:2085, 07:2090  
 \\_\_cmd\_grab\_v\_token\_if\_char:NTF .  
     ..... 07:2124,  
     07:2140, 07:2172, 07:2276, 07:2276, 171  
 \g\_\_cmd\_grabber\_int .....  
     ..... 07:30, 07:1112, 07:1116, 114  
 \\_\_cmd\_if\_recursion\_tail\_stop\_  
     do:Nn . 07:50, 07:52, 07:2625, 07:2653  
 \c\_\_cmd\_ignore\_def\_tl .. 07:2847,  
     07:2863, 07:2870, 07:2884, 07:2917,  
     07:2946, 07:2953, 07:2960, 07:2968,  
     07:2976, 07:2985, 07:2992, 07:2999,  
     07:3006, 07:3013, 07:3025, 07:3032, 189  
 \l\_\_cmd\_last\_delimiters\_tl .....  
     ..... 07:36, 07:451,

07:470, 07:596, 07:610, 07:632,  
 07:672, 07:723, 07:733, 07:790, 131  
 \l\_\_cmd\_last\_mandatory\_arg\_int ..  
     ... 07:18, 07:450, 07:791, 07:969, 114  
 \l\_\_cmd\_long\_bool .. 07:37, 07:455,  
     07:548, 07:549, 07:635, 07:751,  
     07:762, 07:768, 07:774, 07:798,  
     07:836, 07:957, 07:976, 07:1013,  
     07:1028, 07:1041, 07:1058, 07:1078,  
     07:2087, 07:2092, 07:2201, 07:2212, 115  
 \l\_\_cmd\_m\_args\_int .....  
     ..... 07:39, 07:801, 07:913,  
     07:941, 07:944, 07:946, 07:948, 115  
 \l\_\_cmd\_nesting\_a\_tl ..... 07:1867  
 \l\_\_cmd\_nesting\_b\_tl ..... 07:1867  
 \\_\_cmd\_new\_env:nnnn .....  
     ..... 07:3153, 07:3157,  
     07:3171, 07:3202, 07:3228, 07:3229  
 \\_\_cmd\_normalize\_arg\_spec:n ....  
     ..... 07:93, 07:447, 07:447  
 \\_\_cmd\_normalize\_arg\_spec\_loop:n  
     ..... 07:447, 07:460,  
     07:482, 07:543, 07:588, 07:598,  
     07:613, 07:636, 07:642, 07:652, 07:658  
 \\_\_cmd\_normalize\_check\_gv:N ....  
     ..... 07:656, 07:709, 07:709  
 \\_\_cmd\_normalize\_check\_lu:N ....  
     ..... 07:709, 07:719  
 \\_\_cmd\_normalize\_E\_unique\_  
     check:w 07:590, 07:606, 07:615, 07:620  
 \\_\_cmd\_normalize\_type\_!:w ... 07:531  
 \\_\_cmd\_normalize\_type\_+:w ... 07:531  
 \\_\_cmd\_normalize\_type\_=:w ... 07:531  
 \\_\_cmd\_normalize\_type\_>:w ... 07:531  
 \\_\_cmd\_normalize\_type\_aux:NnNn ..  
     07:531, 07:547, 07:553, 07:562, 07:577  
 \\_\_cmd\_normalize\_type\_b:w .....  
     ..... 07:660, 07:660  
 \\_\_cmd\_normalize\_type\_b\_or\_c:nn .  
     ..... 07:660, 07:661, 07:663, 07:664  
 \\_\_cmd\_normalize\_type\_c:w .....  
     ..... 07:660, 07:662  
 \\_\_cmd\_normalize\_type\_D:w .....  
     07:511, 07:519, 07:521, 07:590, 07:590  
 \\_\_cmd\_normalize\_type\_d:w .....  
     ..... 07:506, 07:508  
 \\_\_cmd\_normalize\_type\_E:w .....  
     ..... 07:516, 07:590, 07:600  
 \\_\_cmd\_normalize\_type\_e:w .....  
     ..... 07:506, 07:513  
 \\_\_cmd\_normalize\_type\_m:w .....  
     ..... 07:638, 07:638  
 \\_\_cmd\_normalize\_type\_0:w .....  
     ..... 07:506, 07:520

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

\\_\_cmd\_normalize\_type\_o:w ..... 07:506, 07:518  
 \\_\_cmd\_normalize\_type\_R:w ..... 07:525, 07:638, 07:644  
 \\_\_cmd\_normalize\_type\_r:w ..... 07:506, 07:522  
 \\_\_cmd\_normalize\_type\_s:w ..... 07:506, 07:527  
 \\_\_cmd\_normalize\_type\_t:w ..... 07:528, 07:590, 07:623  
 \\_\_cmd\_normalize\_type\_v:w ..... 07:638, 07:654  
 \l\_\_cmd\_obey\_spaces\_bool ..... 07:35, 07:454, 07:554, 07:556,  
 07:629, 07:634, 07:771, 07:775,  
 07:784, 07:799, 07:843, 07:958,  
 07:977, 07:1599, 07:1604, 07:1757, 141  
 \\_\_cmd\_peek\_cs\_check\_equal:NNN .. 07:2781, 07:2795, 07:2801  
 \\_\_cmd\_peek\_meaning:NTF ..... 07:2772, 07:2781, 07:2781  
 \\_\_cmd\_peek\_meaning\_aux:NNTF ... 07:2781, 07:2782, 07:2784, 07:2785  
 \\_\_cmd\_peek\_meaning\_remove:NTF .. 07:1794, 07:1939, 07:1945,  
 07:2072, 07:2774, 07:2781, 07:2783  
 \\_\_cmd\_peek\_nonspace:NTF ..... 07:2771, 07:2771  
 \\_\_cmd\_peek\_nonspace\_aux:nNNTF .. 07:2771,  
 07:2772, 07:2774, 07:2775, 07:2778  
 \\_\_cmd\_peek\_nonspace\_remove:NTF . 07:1795, 07:1833, 07:1927, 07:1933,  
 07:2060, 07:2070, 07:2771, 07:2773  
 \\_\_cmd\_peek\_true\_remove:NNw 07:2781  
 \\_\_cmd\_peek\_true\_remove:Nw ..... 07:2792, 07:2796, 07:2804, 07:2808  
 \l\_\_cmd\_prefixed\_bool ..... 07:40, 07:820, 07:837,  
 07:844, 07:850, 07:858, 07:911, 116  
 \\_\_cmd\_prepare\_signature:N ..... 07:794, 07:809, 07:818,  
 07:874, 07:882, 07:895, 07:914,  
 07:922, 07:930, 07:937, 07:1014,  
 07:1024, 07:1066, 07:1079, 07:1092, 137  
 \\_\_cmd\_prepare\_signature:n ..... 07:94, 07:794, 07:794  
 \\_\_cmd\_prepare\_signature\_-  
 bypass:N 07:794, 07:821, 07:823,  
 07:838, 07:845, 07:853, 07:863, 137  
 \\_\_cmd\_prepare\_signature\_verb\_-  
 chk:n ..... 07:794, 07:808, 07:812  
 \l\_\_cmd\_process\_all\_tl ..... 07:41, 07:178, 07:313, 07:321,  
 07:386, 07:804, 07:945, 07:980, 116  
 \l\_\_cmd\_process\_one\_tl ..... 07:42, 07:805, 07:852, 07:861,  
 07:891, 07:900, 07:984, 07:987, 116  
 \l\_\_cmd\_process\_some\_bool . 07:43,  
 07:177, 07:806, 07:851, 07:860, 116  
 \\_\_cmd\_provide\_env:nnnn ..... 07:3153, 07:3165,  
 07:3196, 07:3204, 07:3232, 07:3233  
 \\_\_cmd\_put\_arg\_expandable:nw ... 07:2320,  
 07:2325, 07:2326, 07:2361, 07:2366,  
 07:2367, 07:2474, 07:2474, 07:2475  
 \\_\_cmd\_renew\_env:nnnn ..... 07:3153, 07:3161,  
 07:3187, 07:3203, 07:3230, 07:3231  
 \\_\_cmd\_replicate\_processor:nn ... 07:890, 07:897, 07:897  
 \\_\_cmd\_run\_code: .. 07:315, 07:318,  
 07:318, 07:1578, 07:1586, 07:1594,  
 07:1597, 07:1602, 07:1786, 07:1923,  
 07:1929, 07:1935, 07:1941, 07:1965,  
 07:1980, 07:1987, 07:1998, 07:2000,  
 07:2006, 07:2012, 07:2018, 07:2024,  
 07:2030, 07:2036, 07:2042, 07:2053,  
 07:2055, 07:2073, 07:2095, 07:2281, 123  
 \l\_\_cmd\_saved\_args\_tl ..... 07:44, 07:1582, 07:1590, 116  
 \\_\_cmd\_set\_environment\_end:n ... 07:228, 07:279, 07:323  
 \\_\_cmd\_set\_eq\_if\_exist:NN ..... 07:1130, 07:1148, 07:1150,  
 07:1169, 07:1188, 07:1189, 07:1190,  
 07:1203, 07:1204, 07:1205, 07:1303  
 \\_\_cmd\_show:N ..... 07:1347, 07:1349, 07:1349, 07:1376,  
 07:1399, 07:1483, 07:1485, 07:1567, 154  
 \\_\_cmd\_show:n ..... 07:1366, 07:1462, 07:1470, 07:1474  
 \\_\_cmd\_show\_command:N ..... 07:1355, 07:1366, 07:1366  
 \\_\_cmd\_show\_command:NnNNwN ..... 07:1366, 07:1367, 07:1368  
 \\_\_cmd\_show\_command\_aux:NnNNn ... 07:1366, 07:1370,  
 07:1383, 07:1392, 07:1401, 07:1462, 154  
 \\_\_cmd\_show\_delim:Nw 07:1515, 07:1515  
 \\_\_cmd\_show\_delims:Nw 07:1515, 07:1517  
 \\_\_cmd\_show\_delims\_opt:Nw ..... 07:1515, 07:1519  
 \\_\_cmd\_show\_E:Nw .... 07:1515, 07:1534  
 \\_\_cmd\_show\_e:Nw .... 07:1515, 07:1523  
 \\_\_cmd\_show\_environment:N ..... 07:1358, 07:1366, 07:1448, 07:1480

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

```

\__cmd_show_environment:Nnnw ...
    07:1450, 07:1458
\__cmd_show_environment_end:N ...
    07:1359, 07:1477
\__cmd_show_expandable:N ...
    07:1356, 07:1366, 07:1373
\__cmd_show_expandable:NnnNNnnN .
    07:1366, 07:1374, 07:1379,
    07:1381, 07:1388, 07:1390, 07:1396
\__cmd_show_opt:Nw .. 07:1515, 07:1521
\__cmd_show_optimized:N ...
    07:1357, 07:1366, 07:1411
\__cmd_show_optimized:NN ...
    07:1413, 07:1417
\__cmd_show_optimized_aux:N ...
    07:1419, 07:1442
\__cmd_show_prefix:Nw 07:1515, 07:1547
\__cmd_show_processor:Nw ...
    07:1515, 07:1549
\c__cmd_show_type_!_tl ... 07:1509
\c__cmd_show_type+_tl ... 07:1509
\c__cmd_show_type>_tl ... 07:1509
\c__cmd_show_type_D_tl ... 07:1509
\c__cmd_show_type_d_tl ... 07:1509
\c__cmd_show_type_E_tl ... 07:1509
\c__cmd_show_type_e_tl ... 07:1509
\c__cmd_show_type_O_tl ... 07:1509
\c__cmd_show_type_R_tl ... 07:1509
\c__cmd_show_type_r_tl ... 07:1509
\c__cmd_show_type_t_tl ... 07:1509
\l__cmd_signature_tl 07:45, 07:171,
    07:214, 07:807, 07:881, 07:894,
    07:921, 07:929, 07:943, 07:952,
    07:1096, 07:1581, 07:1609, 07:1849,
    07:1955, 07:1965, 07:1982, 07:1989,
    07:1998, 07:2002, 07:2008, 07:2014,
    07:2020, 07:2026, 07:2032, 07:2038,
    07:2044, 07:2075, 07:2097, 07:2281, 174
\__cmd_single_token_check:n ...
    07:593, 07:594, 07:604,
    07:626, 07:647, 07:648, 07:681, 07:681
\l__cmd_some_long_bool ...
    07:47, 07:118, 07:147, 07:208,
    07:216, 07:458, 07:752, 07:763, 127
\l__cmd_some_obey_spaces_bool ...
    07:46, 07:457, 07:557, 07:779, 116
\l__cmd_some_short_bool ...
    07:48, 07:117,
    07:207, 07:218, 07:459, 07:764, 127
\__cmd_split_add_item:n ...
    07:1548, 07:1551, 07:1550, 07:1556, 156
\__cmd_split_argument:nnn ...
    07:2517, 07:2517, 07:3315
\__cmd_split_argument_aux:n ...
    07:2517, 07:2533, 07:2552
\__cmd_split_argument_aux:nnnn ...
    07:2517, 07:2520, 07:2524
\__cmd_split_argument_aux:wn ...
    07:2517, 07:2553, 07:2554
\__cmd_split_end_item:n . 07:1507,
    07:1516, 07:1518, 07:1520, 07:1522,
    07:1528, 07:1539, 07:1551, 07:1558, 156
\__cmd_split_list:nn ...
    07:2482, 07:2484, 07:2519, 07:3316
\__cmd_split_list_multi:nn ...
    07:2482, 07:2489,
    07:2492, 07:2494, 07:2501, 07:2514
\l__cmd_split_list_seq ...
    07:2482, 07:2496, 07:2498, 181
\__cmd_split_list_single:Nn ...
    07:2482, 07:2490, 07:2504
\l__cmd_split_list_tl ...
    07:2483, 07:2506, 07:2512, 07:2514, 181
\__cmd_split_N_head_apply:Nn ...
    07:2562, 07:2582, 07:2594, 07:2669
\__cmd_split_N_head_apply_-
    aux:NNw .. 07:2562, 07:2670, 07:2671
\__cmd_split_signature:n ...
    07:1403, 07:1486, 07:1486, 153
\__cmd_split_signature_loop:Nw ..
    07:1491, 07:1493, 07:1493, 07:1507,
    07:1516, 07:1518, 07:1520, 07:1522,
    07:1530, 07:1543, 07:1548, 07:1550
\__cmd_split_start_item: 07:1496,
    07:1527, 07:1538, 07:1551, 07:1551, 155
\__cmd_start:nNNnnn ...
    07:167, 07:287, 07:298, 07:2752, 139
\__cmd_start_aux:NNnnnn ...
    07:293, 07:304, 07:307, 07:307, 07:317
\__cmd_start_env:nnnnn ...
    07:163, 07:287, 07:287, 07:2755, 187
\__cmd_start_expandable:nNNNNn ..
    07:201, 07:405, 07:405, 07:2753, 1375
\__cmd_start_optimized: ...
    07:110, 07:139,
    07:153, 07:1222, 07:2754, 07:2824, 187
\l__cmd_suppress_strip_bool ...
    07:38, 07:456, 07:563, 07:571,
    07:800, 07:859, 07:960, 07:978, 115
\__cmd_tl_mapthread_function:NNN
    07:356, 07:384, 07:2718, 07:2718
\__cmd_tl_mapthread_function:nnN
    07:432, 07:1541, 07:2718, 07:2731, 156
\__cmd_tl_mapthread_loop:w ...
    07:2718,
    07:2721, 07:2733, 07:2737, 07:2742

```

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

\__cmd_tmp:w	07:53,	45:470, 45:489, 45:507, 54:56,
07:56, 07:342, 07:358, 07:400,		54:123, 54:124, 54:125, 54:206,
07:402, 07:506, 07:530, 07:1101,		54:207, 54:208, 54:209, 54:210,
07:1107, 07:1125, 07:1332, 07:1342,		54:2419, 54:2421, 54:2884, 54:2888,
07:1509, 07:1512, 07:1514, 07:1532,		54:2927, 54:2931, 54:2956, 54:2962
07:1536, 07:1542, 07:1546, 07:2286,		
07:2305, 07:2338, 07:2357, 07:2414,		\cong ..... 30:468
07:2438, 07:2441, 07:2465, 07:2813, 129		\contentsline ..... .. 44:164, 44:171, 44:177, 44:209, 978
\l__cmd_tmp_prop		\coprod ..... 30:352
. 07:53, 07:1951, 07:1954, 07:1960, 117		\copyright .. 21:305, 21:336, 29:732, 1346
\l__cmd_tmpa_tl		\coremissesfalse ..... 33:1220
... 07:54, 07:354, 07:359, 07:369,		\coremisestruue ..... 33:1198
07:1070, 07:1072, 07:1086, 07:1089,		\cos ..... 38:12
07:1243, 07:1249, 07:1264, 07:1272,		\cosh ..... 38:14
07:1288, 07:1295, 07:1313, 07:1316,		\cot ..... 38:18
07:1407, 07:1479, 07:1480, 07:1489,		\coth ..... 38:19
07:1560, 07:1663, 07:1675, 07:1685,		\countdef . 04:75, 04:85, 04:174, 04:190,
07:1694, 07:1701, 07:1733, 07:1888,		04:198, 04:206, 04:225, 34:3, 02:37,
07:1891, 07:2787, 07:2812, 07:2815, 117		02:38, 02:39, 02:41, 02:47, 57:75, 01:50
\l__cmd_tmptb_tl		counter ..... 36:243, 819
..... 07:55, 07:1055, 07:1060,		\counterwithin ..... 525
07:1071, 07:1314, 07:1316, 07:1490,		\counterwithin ..... 22:127, 1369
07:1496, 07:1553, 07:1557, 07:1561,		\counterwithout ..... 525
07:1562, 07:1680, 07:1722, 07:1727,		\counterwithout ..... 22:180, 1369
07:1733, 07:1736, 07:1960, 07:1961,		\CountZero ..... 04:225
07:1963, 07:2788, 07:2799, 07:2805, 154		\cr ..... 21:523,
\__cmd_token_if_cs:NTF		21:529, 21:539, 21:545, 33:65, 33:69,
07:1912, 07:2709, 07:2709, 07:2794, 133		33:891, 33:895, 38:188, 38:192,
\l__cmd_total_args_int		38:440, 38:469, 38:517, 38:633,
..... 07:17, 07:796, 114		41:192, 41:203, 41:210, 41:219,
\__cmd_trim_spaces:n		41:224, 41:230, 41:377, 42:141,
..... 07:2560, 07:2560, 07:3317		42:143, 42:148, 42:154, 02:321, 1281
\__cmd_use_i_delimit_by_q-		\crrcr ..... 21:347, 21:382, 21:383,
recursion_stop:nw . 07:50, 07:2629		21:411, 21:415, 21:418, 21:499,
\l__cmd_v_arg_tl		21:503, 21:507, 21:509, 21:512,
07:1611, 07:1647, 07:1650, 07:1692,		21:756, 21:784, 21:788, 21:791,
07:1701, 07:1754, 07:1760, 07:2084,		21:858, 21:861, 21:919, 21:1277,
07:2101, 07:2120, 07:2154, 07:2225,		29:734, 30:348, 30:349, 30:351,
07:2232, 07:2241, 07:2253, 07:2269, 171		30:470, 30:473, 30:477, 30:541,
\l__cmd_v_nesting_int		30:542, 30:543, 30:544, 30:545,
07:2160, 07:2176, 07:2177, 07:2186, 171		30:546, 30:548, 30:549, 30:550,
\l__cmd_verb_safe_bool		30:551, 30:552, 30:554, 33:70,
..... 07:979		33:896, 38:168, 38:170, 38:171,
\cmrFont		38:172, 38:188, 38:190, 38:191,
..... 33:1213, 33:1216		38:192, 38:210, 38:211, 41:171,
\colon		41:172, 42:141, 55:418, 02:411, 1379
..... 30:514		create commands:
\color		create_callback ..... 04:773
..... 422		\create_callback ..... 44
\columnbreak		\CS ..... 80
..... 1026		\cs ..... 35:158
\columnsep 20:27, 20:97, 20:154, 54:57, 54:207		cs commands:
\columnseprule		\cs:w ..... 08:1755,
..... 54:58, 54:2886, 54:2929, 54:2960		08:1756, 08:1757, 08:1764, 08:1771,
\columnwidth		
. 20:24, 20:27, 20:28, 20:30, 20:94,		
20:97, 20:98, 20:100, 20:151, 20:154,		
20:155, 20:158, 40:444, 40:483,		
40:501, 40:518, 45:99, 45:168,		

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

08:2249, 08:2268, 08:2274, 08:2288,  
 08:2298, 08:2320, 08:2374, 08:2461,  
 08:2526, 08:2576, 08:2959, 08:2979,  
 08:2988, 08:2989, 09:34, 28:335,  
 28:338, 51:212, 52:211, 52:225,  
 52:237, 52:238, 55:274, 07:1915,  
 07:2758, 08:381, 08:1083, 08:1140,  
 08:1291, 08:1431, 08:1538, 08:1539,  
 08:1600, 08:1620, 08:1623, 08:1684,  
 08:1709, 08:1712, 08:1730, 08:1731, 243  
 \cs\_argument\_spec:N . . . . 05:145, 1379  
 \cs\_end: . . . . .  
 08:1756, 08:1757, 08:1764, 08:1771,  
 08:2126, 08:2248, 08:2252, 08:2256,  
 08:2268, 08:2273, 08:2274, 08:2288,  
 08:2294, 08:2308, 08:2321, 08:2326,  
 08:2374, 08:2460, 08:2461, 08:2526,  
 08:2576, 08:2959, 08:2979, 08:2989,  
 09:34, 28:335, 28:338, 51:212,  
 52:211, 52:225, 52:237, 52:238,  
 55:274, 07:1915, 07:2760, 08:381,  
 08:784, 08:1083, 08:1140, 08:1294,  
 08:1434, 08:1538, 08:1539, 08:1600,  
 08:1620, 08:1623, 08:1684, 08:1709,  
 08:1712, 08:1730, 08:1731, 08:1746  
 \cs\_generate\_from\_arg\_count:NNnn  
 . . . . . 10:86,  
 10:103, 11:405, 11:467, 11:849,  
 07:142, 07:156, 07:184, 07:192,  
 07:272, 07:358, 07:361, 07:400, 1377  
 \cs\_generate\_variant:Nn . . . . .  
 . . . . . 09:20, 11:65, 11:350,  
 11:510, 11:660, 11:662, 11:734,  
 11:765, 11:838, 20:547, 36:37, 36:52,  
 36:62, 36:79, 36:96, 36:116, 36:117,  
 36:214, 36:231, 48:298, 51:51, 51:52,  
 51:53, 51:209, 52:461, 52:469, 07:11,  
 07:240, 07:317, 07:361, 57:600,  
 57:609, 57:610, 07:1150, 07:1447,  
 07:2283, 07:2475, 07:2501, 07:2835,  
 07:3202, 07:3203, 07:3204, 08:37,  
 08:38, 08:39, 08:40, 08:41, 08:42,  
 08:43, 08:53, 08:54, 08:57, 08:66,  
 08:1097, 08:1120, 08:1650, 08:1733  
 \cs\_gset:Npn . . . . . 08:2087,  
 08:2331, 08:2401, 11:842, 28:286,  
 28:340, 36:24, 52:242, 53:173,  
 53:482, 08:1096, 08:1116, 08:1646  
 \cs\_gset:Npx . . . . . 52:213, 08:1064  
 \cs\_gset\_eq:NN . . 08:2237, 08:2338,  
 08:2339, 08:2340, 08:2341, 08:2605,  
 09:73, 09:557, 09:585, 11:673,  
 24:414, 28:284, 28:294, 28:332,  
 28:346, 05:140, 05:141, 05:142,  
 05:144, 05:145, 05:146, 05:147,  
 05:148, 05:149, 53:52, 53:151,  
 53:166, 53:167, 53:172, 53:181,  
 53:185, 53:321, 53:393, 53:480,  
 53:481, 07:3319, 08:787, 08:1441,  
 08:1467, 08:1482, 08:1483, 08:1486  
 \cs\_gset\_nopar:Npn . . . . . 08:2987  
 \cs\_gset\_nopar:Npx . . . . . 08:50, 08:52  
 \cs\_gset\_protected:Npn . . . . .  
 . . . . . 08:2182, 08:2185,  
 08:2213, 08:2218, 08:2236, 08:2395,  
 08:2425, 08:2821, 08:2964, 09:248,  
 09:441, 09:563, 11:407, 11:859,  
 51:86, 08:88, 08:91, 08:100, 08:133,  
 08:160, 08:188, 08:191, 08:197,  
 08:221, 08:226, 08:251, 08:310,  
 08:328, 08:598, 08:601, 08:619,  
 08:645, 08:694, 08:702, 08:1465, 08:1526  
 \cs\_gset\_protected:Npx . . . . 10:21,  
 10:23, 48:353, 53:20, 08:20, 08:1178  
 \cs\_if\_eq:NNTF . . . . .  
 51:99, 51:101, 51:168, 07:1107, 07:1971  
 \cs\_if\_exist:N . . . . . 1110  
 \cs\_if\_exist:NTF . . . . .  
 . . . . . 08:1840, 08:2507, 08:2536,  
 08:2544, 09:90, 09:98, 10:118, 11:55,  
 11:61, 11:74, 11:87, 11:403, 11:461,  
 11:496, 11:671, 11:694, 11:710,  
 05:143, 36:67, 36:157, 51:67, 51:84,  
 51:170, 52:93, 52:438, 52:442,  
 07:71, 07:233, 07:249, 07:1110,  
 07:1149, 07:1468, 07:2819, 07:3121,  
 07:3134, 07:3146, 07:3173, 07:3179,  
 07:3189, 07:3198, 07:3210, 07:3213,  
 07:3220, 07:3225, 07:3240, 07:3253,  
 07:3266, 08:1068, 08:1133, 1132  
 \cs\_if\_exist\_p:N . . 07:78, 07:79, 08:277  
 \cs\_if\_exist\_use:NTF . . . . 11:651,  
 11:759, 26:351, 05:188, 53:313,  
 53:314, 53:318, 53:319, 07:486,  
 07:1266, 08:1300, 08:1344, 08:1369  
 \cs\_if\_free:NTF . . . . . 36:8, 51:108  
 \cs\_meaning:N . . . . . 10:69  
 \cs\_new:Npn . . . . . 08:2083, 08:2090,  
 08:2246, 08:2271, 08:2279, 08:2292,  
 08:2300, 08:2309, 08:2318, 08:2353,  
 08:2534, 08:2542, 08:2556, 08:2574,  
 08:2583, 08:2588, 08:2829, 08:2830,  
 08:2831, 08:2832, 08:2836, 08:2837,  
 09:320, 09:330, 09:340, 09:342,  
 09:344, 09:355, 09:378, 09:379,  
 09:382, 09:503, 09:611, 10:88,  
 10:154, 11:351, 11:352, 11:462,  
 11:516, 11:939, 11:1223, 11:1225,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

11:1227, 16:85, 16:88, 16:113,  
 16:125, 20:538, 05:186, 36:63,  
 36:65, 36:89, 36:97, 36:104, 36:167,  
 36:168, 36:182, 36:183, 36:197,  
 36:198, 48:279, 48:289, 48:290,  
 48:291, 48:292, 48:297, 49:111,  
 49:112, 51:206, 51:208, 52:30,  
 52:38, 52:44, 52:57, 52:95, 52:100,  
 52:105, 52:112, 52:127, 52:234,  
 52:240, 52:411, 52:413, 52:415,  
 52:418, 52:422, 52:436, 52:452,  
 52:462, 52:582, 53:54, 53:59, 53:77,  
 53:141, 53:146, 53:163, 53:178,  
 53:183, 53:189, 53:192, 53:206,  
 53:257, 53:310, 53:323, 53:337,  
 53:340, 53:350, 53:398, 53:479,  
 53:538, 53:539, 53:540, 07:100,  
 07:102, 07:153, 55:28, 55:42, 55:272,  
 55:311, 55:317, 55:367, 55:370,  
 55:413, 07:405, 07:410, 07:412,  
 07:414, 07:426, 07:438, 07:444,  
 07:1173, 07:1228, 07:1309, 07:1334,  
 07:1339, 07:1765, 07:1770, 07:1772,  
 07:1774, 07:1902, 07:2284, 07:2288,  
 07:2306, 07:2313, 07:2314, 07:2336,  
 07:2340, 07:2358, 07:2371, 07:2373,  
 07:2375, 07:2377, 07:2383, 07:2400,  
 07:2402, 07:2404, 07:2406, 07:2408,  
 07:2410, 07:2412, 07:2416, 07:2439,  
 07:2443, 07:2466, 07:2468, 07:2474,  
 07:2552, 07:2554, 07:2579, 07:2585,  
 07:2591, 07:2597, 07:2669, 07:2671,  
 07:2718, 07:2731, 07:2737, 07:2744,  
 07:2765, 07:2817, 07:2836, 07:2849,  
 07:3275, 07:3292, 07:3293, 07:3297,  
 07:3298, 07:3299, 08:45, 08:46,  
 08:330, 08:336, 08:351, 08:361,  
 08:362, 08:364, 08:378, 08:384,  
 08:568, 08:921, 08:923, 08:925,  
 08:1219, 08:1231, 08:1236, 08:1244,  
 08:1253, 08:1255, 08:1262, 08:1289,  
 08:1296, 08:1298, 08:1413, 08:1429,  
 08:1563, 08:1564, 08:1735, 08:1736  
 \cs\_new:Npx ..... 08:560  
 \cs\_new\_eq:NN .....  
 08:1810, 08:1811, 08:1812, 08:1813,  
 08:1814, 08:1815, 08:2308, 08:2850,  
 08:2851, 08:2852, 08:2853, 08:2923,  
 08:2925, 09:13, 09:14, 09:458,  
 10:7, 10:8, 10:150, 10:151, 10:152,  
 10:153, 10:157, 10:182, 10:183,  
 10:184, 10:185, 10:186, 10:187,  
 10:188, 10:189, 10:190, 10:191,  
 10:192, 10:193, 10:194, 10:195,  
 10:196, 10:197, 10:198, 11:357,  
 11:358, 11:359, 11:374, 11:661,  
 16:135, 20:816, 20:817, 05:166,  
 05:167, 05:168, 05:169, 05:185,  
 05:221, 36:166, 36:181, 36:196,  
 48:340, 48:356, 48:357, 48:399,  
 48:401, 48:513, 48:515, 51:8, 52:252,  
 52:253, 52:509, 52:511, 52:513,  
 52:515, 52:517, 52:519, 52:521,  
 52:523, 52:525, 52:527, 53:7, 53:152,  
 53:347, 53:349, 53:417, 53:420,  
 53:421, 53:491, 53:537, 07:56, 07:99,  
 55:3, 55:4, 55:306, 57:630, 57:631,  
 07:1284, 07:1285, 07:1292, 07:1299,  
 07:3115, 07:3116, 07:3294, 07:3295,  
 07:3296, 07:3302, 07:3303, 07:3304,  
 07:3314, 07:3315, 07:3316, 07:3317,  
 07:3318, 08:7, 08:23, 08:34, 08:63,  
 08:1203, 08:1386, 08:1393, 08:1436  
 \cs\_new\_protected:Npe ... 11:276,  
 07:1634, 07:1659, 07:1706, 07:1784  
 \cs\_new\_protected:Npn .....  
 ..... 08:1753, 08:1760, 08:1767,  
 08:1774, 08:1782, 08:1788, 08:1799,  
 08:1816, 08:1823, 08:1835, 08:1842,  
 08:1849, 08:1855, 08:1857, 08:1861,  
 08:1979, 08:2101, 08:2119, 08:2124,  
 08:2133, 08:2151, 08:2165, 08:2187,  
 08:2200, 08:2227, 08:2231, 08:2241,  
 08:2254, 08:2263, 08:2277, 08:2283,  
 08:2306, 08:2313, 08:2336, 08:2359,  
 08:2369, 08:2380, 08:2386, 08:2406,  
 08:2436, 08:2438, 08:2448, 08:2590,  
 08:2596, 08:2602, 08:2773, 08:2774,  
 08:2775, 08:2798, 08:2809, 08:2839,  
 08:2840, 08:2841, 08:2842, 08:2854,  
 08:2861, 08:2868, 08:2875, 08:2882,  
 08:2884, 08:2886, 08:2893, 08:2900,  
 08:2907, 08:2914, 09:18, 09:23,  
 09:25, 09:40, 09:42, 09:51, 09:53,  
 09:63, 09:71, 09:80, 09:94, 09:114,  
 09:134, 09:147, 09:152, 09:161,  
 09:166, 09:173, 09:313, 09:384,  
 09:422, 09:459, 09:487, 09:516, 10:9,  
 10:14, 10:19, 10:27, 10:58, 10:77,  
 10:78, 10:98, 10:122, 10:144, 11:43,  
 11:53, 11:59, 11:66, 11:72, 11:97,  
 11:105, 11:121, 11:129, 11:137,  
 11:147, 11:163, 11:173, 11:183,  
 11:189, 11:204, 11:220, 11:242,  
 11:254, 11:271, 11:297, 11:321,  
 11:353, 11:355, 11:360, 11:362,  
 11:364, 11:366, 11:368, 11:370,  
 11:372, 11:375, 11:401, 11:409,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

11:420, 11:422, 11:436, 11:440,  
 11:454, 11:511, 11:530, 11:548,  
 11:569, 11:586, 11:593, 11:601,  
 11:606, 11:615, 11:621, 11:626,  
 11:641, 11:648, 11:658, 11:663,  
 11:676, 11:685, 11:704, 11:717,  
 11:729, 11:735, 11:741, 11:746,  
 11:766, 11:774, 11:779, 11:790,  
 11:796, 11:816, 11:833, 11:839,  
 11:845, 11:856, 11:862, 11:874,  
 11:884, 11:903, 11:905, 11:916,  
 11:921, 11:927, 11:933, 11:940,  
 11:942, 11:944, 11:953, 11:962,  
 11:971, 11:979, 11:1193, 11:1195,  
 11:1197, 11:1199, 11:1201, 11:1203,  
 11:1205, 11:1207, 11:1209, 11:1211,  
 11:1213, 11:1215, 11:1217, 11:1219,  
 11:1221, 11:1229, 11:1230, 11:1231,  
 11:1241, 16:93, 24:413, 28:279,  
 36:6, 36:17, 36:22, 36:38, 36:43,  
 36:48, 36:50, 36:53, 36:128, 36:142,  
 36:149, 36:199, 36:206, 36:215, 48:7,  
 48:17, 48:54, 48:67, 48:75, 48:102,  
 48:132, 48:137, 48:162, 48:171,  
 48:213, 48:224, 48:235, 48:243,  
 48:246, 48:277, 48:341, 48:346,  
 48:351, 48:359, 48:372, 48:388,  
 48:417, 48:449, 51:22, 51:28, 51:44,  
 51:59, 51:61, 51:97, 51:106, 51:118,  
 51:134, 51:139, 51:148, 51:160,  
 51:165, 51:182, 51:198, 51:210,  
 51:214, 51:232, 51:246, 52:49, 52:62,  
 52:70, 52:79, 52:208, 52:222, 52:392,  
 52:397, 52:420, 52:547, 53:8, 53:13,  
 53:18, 53:343, 53:500, 07:59, 07:64,  
 07:69, 07:90, 07:110, 07:132, 07:154,  
 07:182, 07:230, 07:244, 07:265,  
 07:279, 07:287, 07:307, 07:318,  
 07:328, 55:5, 55:6, 55:7, 07:339,  
 55:20, 55:23, 55:29, 55:30, 55:31,  
 55:32, 55:52, 55:53, 07:347, 07:352,  
 07:362, 07:367, 55:262, 55:263,  
 55:267, 55:276, 55:307, 55:338,  
 07:381, 55:359, 55:363, 55:373,  
 55:376, 55:379, 55:382, 55:385,  
 55:402, 07:390, 07:398, 57:580,  
 57:611, 57:616, 57:621, 07:447,  
 57:629, 57:654, 57:659, 57:664,  
 07:482, 07:508, 07:513, 07:518,  
 07:520, 07:522, 07:527, 07:531,  
 07:545, 07:551, 07:560, 07:577,  
 07:590, 07:600, 07:615, 07:623,  
 07:638, 07:644, 07:654, 07:660,  
 07:662, 07:664, 07:681, 07:690,  
 07:709, 07:719, 07:731, 07:742,  
 07:747, 07:748, 07:777, 07:794,  
 07:812, 07:818, 07:823, 07:833,  
 07:840, 07:847, 07:855, 07:865,  
 07:867, 07:869, 07:876, 07:884,  
 07:897, 07:908, 07:916, 07:924,  
 07:932, 07:939, 07:950, 07:989,  
 07:999, 07:1004, 07:1011, 07:1016,  
 07:1018, 07:1026, 07:1039, 07:1052,  
 07:1068, 07:1074, 07:1081, 07:1083,  
 07:1094, 07:1099, 07:1105, 07:1123,  
 07:1130, 07:1148, 07:1151, 07:1166,  
 07:1185, 07:1200, 07:1214, 07:1245,  
 07:1253, 07:1261, 07:1270, 07:1282,  
 07:1286, 07:1293, 07:1298, 07:1300,  
 07:1311, 07:1318, 07:1326, 07:1349,  
 07:1366, 07:1368, 07:1373, 07:1381,  
 07:1390, 07:1401, 07:1411, 07:1417,  
 07:1448, 07:1458, 07:1470, 07:1474,  
 07:1477, 07:1486, 07:1493, 07:1515,  
 07:1517, 07:1519, 07:1521, 07:1523,  
 07:1534, 07:1547, 07:1549, 07:1551,  
 07:1556, 07:1558, 07:1570, 07:1572,  
 07:1574, 07:1576, 07:1578, 07:1586,  
 07:1597, 07:1602, 07:1607, 07:1621,  
 07:1643, 07:1667, 07:1690, 07:1699,  
 07:1732, 07:1734, 07:1745, 07:1809,  
 07:1828, 07:1847, 07:1870, 07:1923,  
 07:1929, 07:1935, 07:1941, 07:1947,  
 07:1969, 07:1979, 07:1980, 07:1987,  
 07:2000, 07:2006, 07:2012, 07:2018,  
 07:2024, 07:2030, 07:2036, 07:2042,  
 07:2053, 07:2055, 07:2057, 07:2069,  
 07:2071, 07:2073, 07:2085, 07:2090,  
 07:2095, 07:2116, 07:2122, 07:2132,  
 07:2138, 07:2151, 07:2164, 07:2170,  
 07:2195, 07:2208, 07:2217, 07:2239,  
 07:2251, 07:2267, 07:2276, 07:2278,  
 07:2476, 07:2484, 07:2494, 07:2504,  
 07:2517, 07:2524, 07:2560, 07:2562,  
 07:2567, 07:2603, 07:2608, 07:2619,  
 07:2621, 07:2623, 07:2640, 07:2651,  
 07:2661, 07:2663, 07:2665, 07:2667,  
 07:2677, 07:2681, 07:2709, 07:2771,  
 07:2773, 07:2775, 07:2781, 07:2783,  
 07:2785, 07:2801, 07:2808, 07:3117,  
 07:3130, 07:3143, 07:3148, 07:3155,  
 07:3159, 07:3163, 07:3167, 07:3171,  
 07:3187, 07:3196, 07:3208, 07:3218,  
 07:3224, 07:3226, 07:3236, 07:3249,  
 07:3262, 07:3270, 08:8, 08:13,  
 08:18, 08:47, 08:49, 08:51, 08:55,  
 08:58, 08:64, 08:69, 08:71, 08:73,  
 08:104, 08:148, 08:172, 08:174,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

08:176, 08:201, 08:203, 08:205,	07:275, 07:276, 55:301, 55:304,
08:231, 08:266, 08:268, 08:285,	07:1125, 07:1149, 07:1168, 07:1187,
08:290, 08:292, 08:385, 08:394,	07:1202, 07:1216, 07:1277, 07:1302,
08:399, 08:407, 08:431, 08:433,	07:1307, 07:1322, 07:1324, 07:1614,
08:449, 08:457, 08:467, 08:477,	07:1830, 07:2003, 07:2009, 07:2015,
08:488, 08:494, 08:500, 08:516,	07:2021, 07:2027, 07:2033, 07:2039,
08:529, 08:572, 08:589, 08:649,	07:2045, 07:2197, 07:2210, 07:2813,
08:668, 08:676, 08:683, 08:715,	08:1511, 08:1512, 08:1513, 08:1514,
08:721, 08:727, 08:737, 08:779,	08:1544, 08:1546, 08:1548, 08:1550
08:781, 08:789, 08:791, 08:794,	\cs_set_nopar:Npe . . . . 07:135, 07:1219
08:796, 08:977, 08:979, 08:1014,	\cs_set_nopar:Npn . . 57:582, 57:583, 157
08:1051, 08:1063, 08:1066, 08:1095,	\cs_set_nopar:Npx . . . . .
08:1108, 08:1110, 08:1112, 08:1114,	. . . . . 07:199, 07:220, 07:225,
08:1131, 08:1155, 08:1162, 08:1320,	07:270, 07:281, 07:1030, 07:1043,
08:1327, 08:1358, 08:1380, 08:1387,	07:1193, 07:1207, 07:1320, 08:48
08:1394, 08:1400, 08:1405, 08:1410,	\cs_set_protected:Npe . . . . . 11:696
08:1411, 08:1439, 08:1492, 08:1572,	\cs_set_protected:Npn . . 08:2105,
08:1654, 08:1737, 08:1744, 1163	08:2136, 09:190, 09:265, 11:325,
\cs_new_protected:Npx . . . 09:493,	11:860, 28:327, 28:359, 51:5, 51:220,
48:114, 07:298, 07:2048, 07:2157	53:46, 53:135, 53:418, 07:158,
\cs_new_protected_nopar:Npn . . . .	57:598, 07:506, 07:1332, 07:1509,
. . . . . 57:626, 07:1904, 07:1994	07:1532, 07:1536, 07:1573, 07:1577,
\cs_parameter_spec:N . . . . 05:143,	07:1791, 07:1932, 07:1944, 07:1956,
05:144, 07:1439, 07:2838, 08:1247, 323	07:1990, 07:2056, 07:2076, 07:2286,
\cs_prefix_spec:N 09:224, 09:299, 05:142	07:2338, 07:2414, 07:2441, 08:420
\cs_replacement_spec . . . . . 261	\cs_set_protected_nopar:Npe . . . .
\cs_replacement_spec:N . . . . .	. . . . . 07:136, 07:1218
. . . . . 08:1903, 08:1916, 08:1925,	\cs_set_protected_nopar:Npn . . . .
05:147, 07:1408, 07:1444, 07:1454,	. . . . . 07:1571, 07:1575, 07:1792,
08:37, 08:41, 08:1222, 08:1457, 08:1479	07:1926, 07:1938, 07:1983, 07:2054
\cs_set:Npe . . . . . 07:1419	\cs_set_protected_nopar:Npx . . . .
\cs_set:Npn . . . . .	. . . . . 07:159,
08:1900, 08:2594, 08:2600, 08:2973,	07:199, 07:1170, 07:1193, 07:1305
09:216, 09:291, 09:474, 09:533,	\cs_show:N . . . . . 11:943, 386
09:569, 10:105, 11:329, 11:843,	\cs_to_str:N . . . . . 09:129, 09:150,
16:37, 16:68, 26:344, 26:350, 26:354,	09:164, 09:169, 05:140, 07:78,
26:355, 26:356, 48:374, 07:194,	07:79, 07:92, 07:1142, 07:1144,
07:273, 07:358, 07:400, 07:1101,	07:1362, 07:1414, 07:1453, 07:1455,
08:1164, 08:1175, 08:1182, 08:1191, 157	07:1479, 07:1915, 07:2760, 07:2827, 243
\cs_set:Npx . . . . . 52:211,	\cs_undefine:N . . . . . 08:2346,
52:225, 07:223, 07:1029, 07:1042	08:2432, 08:2570, 09:76, 09:227,
\cs_set_eq:NN . . . . . 08:1837,	09:512, 09:520, 52:227, 07:3228,
08:1844, 08:1851, 09:188, 09:189,	07:3229, 07:3230, 07:3231, 07:3232,
09:209, 09:210, 09:215, 09:263,	07:3233, 07:3308, 07:3309, 07:3310,
09:264, 09:284, 09:285, 09:290,	07:3320, 08:79, 08:80, 08:90, 08:132,
09:470, 09:471, 09:529, 09:530,	08:190, 08:196, 08:271, 08:666,
09:565, 09:566, 09:624, 11:712,	08:1101, 08:1102, 08:1103, 08:1104,
16:91, 16:92, 16:136, 16:137, 16:138,	08:1124, 08:1125, 08:1126, 08:1127,
16:140, 16:141, 16:142, 16:176,	08:1151, 08:1207, 08:1227, 08:1285,
16:177, 16:178, 16:181, 28:299,	08:1306, 08:1307, 08:1318, 08:1412
28:349, 36:232, 48:113, 48:280,	cs\check@icr commands:
48:281, 48:282, 51:89, 53:24, 53:44,	\cs_gset_eq:NN . . . . . 74
53:83, 53:95, 53:125, 53:132, 53:423,	\csc . . . . . 38:21
53:425, 53:427, 53:429, 53:431,	\csname . . . . . 1323

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\csname\endcsname</code> . . . . .	1128	<code>\CYRCHRDSC</code> . . . . .	21:1535
<code>\cup</code> . . . . .	30:384	<code>\cyrchrdsc</code> . . . . .	21:1534
<code>\CurrentFile</code> . . . . .	50:946, 52:3, 52:67, 52:84, 52:166, 52:171, 52:174, 52:377, 52:381, 52:555, 52:556, 1125	<code>\CYRCHVCRS</code> . . . . .	21:1535
<code>\CurrentFilePath</code> . . . . .	52:3, 52:67, 52:83, 52:165, 52:378, 52:381, 1116	<code>\cyrchvcrs</code> . . . . .	21:1535
<code>\CurrentFilePathUsed</code> . . . . .	52:3, 52:66, 52:81, 52:163, 52:375, 52:378, 1116	<code>\CYRD</code> . . . . .	21:1535
<code>\CurrentFileUsed</code> . . . . .	50:946, 52:3, 52:66, 52:82, 52:164, 52:375, 52:377, 52:554, 52:555, 1119	<code>\cyrd</code> . . . . .	21:1535
<code>\currentgrouplevel</code> . . . . .	50:788	<code>\CYRDELTA</code> . . . . .	21:1535
<code>\currentgrouptype</code> . . . . .	39:148, 39:151, 39:153, 41:195, 1386	<code>\cyrdelta</code> . . . . .	21:1535
<code>\CurrentOption</code> . . . . .	21:1560, 21:1563, 21:1568, 21:1584, 50:14, 50:520, 50:531, 50:544, 50:545, 50:550, 50:563, 50:564, 50:566, 50:580, 50:581, 50:584, 50:598, 50:603, 50:604, 50:617, 50:622, 50:623, 50:636, 50:638, 50:644, 50:646, 50:658, 50:659, 50:660, 50:668, 50:669, 50:670, 50:996, 50:1061, 50:1180, 50:1181, 50:1191, 51:71, 51:72, 1339	<code>\CYRDJE</code> . . . . .	21:1536
CurrentOption commands:		<code>\cyrdje</code> . . . . .	21:1536
<code>\CurrentOption:</code> . . . . .	50:543, 50:562, 50:579, 50:597, 50:602, 50:616, 50:621, 50:657, 50:667, 50:1190	<code>\CYRDZE</code> . . . . .	21:1536
<code>\currsubencoding</code> . . . . .	33:1212, 33:1223, 33:1379, 33:1381, 33:1382	<code>\cyrdze</code> . . . . .	21:1536
<code>\CYRA</code> . . . . .	21:1532	<code>\CYRDZHE</code> . . . . .	21:1536
<code>\cyr</code> . . . . .	21:1532, 21:1587	<code>\cyrdzhe</code> . . . . .	21:1536
<code>\CYRABHCH</code> . . . . .	21:1532	<code>\CYRE</code> . . . . .	21:1536
<code>\cyrabhch</code> . . . . .	21:1532	<code>\cyre</code> . . . . .	21:1536
<code>\CYRABHCHDSC</code> . . . . .	21:1532	<code>\CYREPS</code> . . . . .	21:1537
<code>\cyrabhchdsc</code> . . . . .	21:1532	<code>\cyreps</code> . . . . .	21:1536
<code>\CYRABHDZE</code> . . . . .	21:1533	<code>\CYREREV</code> . . . . .	21:1537
<code>\cyrabhdze</code> . . . . .	21:1532	<code>\cyrerev</code> . . . . .	21:1537
<code>\CYRABHHA</code> . . . . .	21:1533	<code>\CYRERY</code> . . . . .	21:1537
<code>\cyrabhha</code> . . . . .	21:1533	<code>\cyrery</code> . . . . .	21:1537
<code>\CYRAE</code> . . . . .	21:1533	<code>\CYRF</code> . . . . .	21:1537
<code>\cyr</code> . . . . .	21:1533	<code>\cyrf</code> . . . . .	21:1537
<code>\CYRB</code> . . . . .	21:1533	<code>\CYRFITA</code> . . . . .	21:1538
<code>\cyrb</code> . . . . .	21:1533	<code>\cyrfita</code> . . . . .	21:1537
<code>\CYREYUS</code> . . . . .	21:1534	<code>\CYRG</code> . . . . .	21:1538
<code>\cyrbyus</code> . . . . .	21:1533	<code>\cyrg</code> . . . . .	21:1538
<code>\CYRC</code> . . . . .	21:1534	<code>\CYRGDSC</code> . . . . .	21:1538
<code>\cyrc</code> . . . . .	21:1534	<code>\cyrgdsc</code> . . . . .	21:1538
<code>\CYRCH</code> . . . . .	21:1534	<code>\CYRGDSCHCRS</code> . . . . .	21:1538
<code>\cyrch</code> . . . . .	21:1534	<code>\cyrgdschcrs</code> . . . . .	21:1538
<code>\CYRCHLDSC</code> . . . . .	21:1534	<code>\CYRGHCRS</code> . . . . .	21:1539
<code>\cyrchldsc</code> . . . . .	21:1534	<code>\cyrghcrs</code> . . . . .	21:1539
		<code>\CYRGHK</code> . . . . .	21:1539
		<code>\cyrghk</code> . . . . .	21:1539
		<code>\CYRGUP</code> . . . . .	21:1539
		<code>\cyrgup</code> . . . . .	21:1539
		<code>\CYRH</code> . . . . .	21:1539
		<code>\cyrh</code> . . . . .	21:1539
		<code>\CYRHDSC</code> . . . . .	21:1540
		<code>\cyrhdsc</code> . . . . .	21:1540
		<code>\CYRHHCRS</code> . . . . .	21:1540
		<code>\cyrhhcrs</code> . . . . .	21:1540
		<code>\CYRHHK</code> . . . . .	21:1540
		<code>\cyrhhk</code> . . . . .	21:1540
		<code>\CYRHRDSN</code> . . . . .	21:1541
		<code>\cyrhrdsn</code> . . . . .	21:1540
		<code>\CYRI</code> . . . . .	21:1541
		<code>\cyri</code> . . . . .	21:1541
		<code>\CYRIE</code> . . . . .	21:1541
		<code>\cyrie</code> . . . . .	21:1541
		<code>\CYRII</code> . . . . .	21:1541
		<code>\cyrii</code> . . . . .	21:1541

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

\CYRISHRT	21:1541	\CYRQ	21:1548
\cyrishrt	21:1541	\cyrq	21:1548
\CYRISHRTDSC	21:1542	\CYRR	21:1548
\cyrishrtdsc	21:1542	\cyrr	21:1548
\CYRIZH	21:1542	\CYRRDSC	21:1548
\cyrizh	21:1542	\cyrrdsc	21:1548
\CYRJE	21:1542	\CYRRHK	21:1549, 1349
\cyrje	21:1542	\cyrrhk	21:1548, 1349
\CYRK	21:1542	\CYRRHOOK	1349
\cyrk	21:1542	\cyrrhook	1349
\CYRKBEAK	21:1543	\CYRRTICK	21:1549
\cyrkbeak	21:1543	\cyrrtick	21:1549
\CYRKDSC	21:1543	\CYRS	21:1549
\cyrkdsc	21:1543	\cyr	21:1549
\CYRKHCERS	21:1543	\CYRSACRS	21:1549
\cyrkhcrs	21:1543	\cyrscrs	21:1549
\CYRKHK	21:1544	\CYRSCHWA	21:1550
\cyrkhk	21:1543	\cyrschwa	21:1550
\CYRKVCERS	21:1544	\CYRSDSC	21:1550
\cyrkvcrs	21:1544	\cyrsdsc	21:1550
\CYRL	21:1544	\CYRSEMISFTSN	21:1550
\cyr	21:1544	\cyrsemisftsn	21:1550
\CYRLDSC	21:1544	\CYRSFTSN	21:1551
\cyrl	21:1544	\cyr	21:1551
\CYRLHK	21:1545	\CYRSH	21:1551
\cyr	21:1544	\cyrsh	21:1551
\CYRLJE	21:1545	\CYRSHCH	21:1551
\cyr	21:1545	\cyrshch	21:1551
\CYRM	21:1545	\CYRSHHA	21:1551
\cyr	21:1545	\cyrsha	21:1551
\CYRMDSC	21:1545	\CYRT	21:1552
\cyr	21:1545	\cyr	21:1552
\CYRMHK	21:1545	\CYRTDSC	21:1552
\cyr	21:1545	\cyrtdsc	21:1552
\CYRN	21:1546	\CYRTETSE	21:1552
\cyr	21:1546	\cyr	21:1552
\CYRNDSC	21:1546	\CYRTSHE	21:1552
\cyr	21:1546	\cyrtshe	21:1552
\CYRNG	21:1546	\CYRU	21:1553
\cyr	21:1546	\cyr	21:1553
\CYRNHK	21:1546	\CYRUSHRT	21:1553
\cyr	21:1546	\cyrushrt	21:1553
\CYRNJE	21:1547	\CYRV	21:1553
\cyr	21:1546	\cyr	21:1553
\CYRNLHK	21:1547	\CYRW	21:1553
\cyr	21:1547	\cyr	21:1553
\CYRO	21:1547	\CYRY	21:1553
\cyr	21:1547	\cyr	21:1553
\CYROTL	21:1547	\CYRYA	21:1554
\cyr	21:1547	\cyr	21:1554
\CYRP	21:1547	\CYRYAT	21:1554
\cyr	21:1547	\cyr	21:1554
\CYRPHK	21:1548	\CYRYHCERS	21:1554
\cyr	21:1548	\cyr	21:1554

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=ltlooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

\CYRYI .....	21:1554	\debug_suspend: .....	
\cyr yi .....	21:1554	... 11:99, 11:107, 11:123, 11:131, 231	
\CYRYO .....	21:1555	\DebugHooksOff ....	08:2841, 08:2949, 213
\cyr yo .....	21:1554	\DebugHooksOn ....	08:2841, 08:2948, 213
\CYRYU .....	21:1555	\DebugMarksOff .....	48:356, 1019
\cyr yu .....	21:1555	\DebugMarksOn .....	48:356, 1019
\CYRZ .....	21:1555	\DebugShipoutsOff ..	53:420, 53:452, 1144
\cyr z .....	21:1555	\DebugShipoutsOn ...	53:420, 53:451, 1144
\CYRZDSC .....	21:1555	\DebugSocketsOff ....	10:182, 10:212, 345
\cyr z d s c .....	21:1555	\DebugSocketsOn ....	10:182, 10:211, 1264
\CYRZH .....	21:1555	\DebugTablesOff .....	55:300
\cyr zh .....	21:1555	\DebugTablesOn .....	55:300
\CYRZHDSC .....	21:1556	declare commands:	
\cyr z h d s c .....	21:1556	declare_callback_rule .....	04:864
		\declare_callback_rule .....	44
		\DeclareAccent .....	1313
		\DeclareCaseChangeEquivalent	57:571, 1373
		\DeclareCommandCopy .....	
		.....	06:564, 06:565, 06:567, 96
		\DeclareCurrentRelease ..	33:777, 50:1771
		\DeclareDefaultHookRule .....	
		.....	08:2845, 08:2952, 211
		\DeclareDocumentCommand .....	
		.....	44:186, 44:187, 07:3117, 88
		\DeclareDocumentEnvironment ...	07:3153
		\DeclareEmphSequence .....	722
		\DeclareEmphSequence .....	
		..	29:624, 29:660, 29:661, 29:673, 723
		\DeclareEncoding .....	1313
		\DeclareEncodingSubset .....	
		.....	24:186, 33:361, 33:362,
		33:363, 33:364, 33:365, 33:366,	
		33:367, 33:368, 33:369, 33:370,	
		33:371, 33:372, 33:373, 33:374,	
		33:375, 33:376, 33:377, 33:378,	
		33:379, 33:380, 33:381, 33:382,	
		33:383, 33:384, 33:385, 33:386,	
		33:387, 33:388, 33:389, 33:390,	
		33:391, 33:392, 33:393, 33:394,	
		33:395, 33:396, 33:397, 33:398,	
		33:399, 33:400, 33:401, 33:402,	
		33:403, 33:404, 33:405, 33:406,	
		33:407, 33:408, 33:409, 33:410,	
		33:411, 33:412, 33:413, 33:414,	
		33:415, 33:416, 33:417, 33:418,	
		33:419, 33:420, 33:421, 33:422,	
		33:423, 33:424, 33:425, 33:426,	
		33:427, 33:428, 33:429, 33:430,	
		33:431, 33:432, 33:433, 33:434,	
		33:435, 33:436, 33:437, 33:438,	
		33:439, 33:440, 33:441, 33:442,	
		33:443, 33:444, 33:445, 33:446,	
		33:447, 33:448, 33:449, 33:450,	
		33:451, 33:452, 33:453, 33:454,	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=lt para.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=lt page.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

33:455, 33:456, 33:457, 33:458,	\DeclareFontFamily 24:94, 27:85, 27:86, 557
33:459, 33:460, 33:461, 33:462,	\DeclareFontFamilySubstitution . 24:534
33:463, 33:464, 33:465, 33:466,	\DeclareFontSeriesChangeRule . . . . .
33:467, 33:468, 33:469, 33:470,	. . . . . 25:4, 25:5,
33:471, 33:472, 33:473, 33:474,	25:7, 25:8, 25:9, 25:10, 25:11, 25:12,
33:475, 33:476, 33:477, 33:478,	25:13, 25:14, 25:15, 25:16, 25:17,
33:479, 33:480, 33:481, 33:482,	25:18, 25:19, 25:20, 25:21, 25:22,
33:483, 33:484, 33:485, 33:486,	25:23, 25:24, 25:25, 25:26, 25:27,
33:487, 33:488, 33:489, 33:490,	25:28, 25:29, 25:30, 25:31, 25:32,
33:491, 33:492, 33:493, 33:494,	25:33, 25:34, 25:35, 25:36, 25:37,
33:495, 33:496, 33:497, 33:498,	25:38, 25:39, 25:40, 25:41, 25:42,
33:499, 33:500, 33:501, 33:502,	25:43, 25:44, 25:45, 25:46, 25:47,
33:503, 33:504, 33:505, 33:506,	25:48, 25:49, 25:50, 25:51, 25:52,
33:507, 33:508, 33:509, 33:510,	25:53, 25:54, 25:55, 25:56, 25:57,
33:511, 33:512, 33:513, 33:514,	25:58, 25:59, 25:60, 25:61, 25:62,
33:515, 33:516, 33:517, 33:518,	25:63, 25:64, 25:65, 25:66, 25:67,
33:519, 33:520, 33:521, 33:522,	25:68, 25:69, 25:70, 25:71, 25:72,
33:523, 33:524, 33:525, 33:526,	25:73, 25:74, 25:75, 25:76, 25:77,
33:527, 33:528, 33:529, 33:530,	25:78, 25:79, 25:80, 25:81, 25:82,
33:531, 33:532, 33:533, 33:534,	25:83, 25:84, 25:85, 25:86, 25:87,
33:535, 33:536, 33:537, 33:538,	25:88, 25:89, 25:90, 25:91, 25:92,
33:539, 33:584, 33:782, 33:783,	25:93, 25:94, 25:95, 25:96, 25:97,
33:784, 33:785, 33:826, 33:833,	25:98, 25:99, 25:100, 25:101, 25:102,
33:834, 33:835, 33:836, 33:1112,	25:103, 25:104, 25:105, 25:106,
33:1113, 33:1114, 33:1115, 33:1116,	25:107, 25:108, 25:109, 25:110,
33:1117, 33:1118, 33:1119, 33:1120,	25:111, 25:112, 25:113, 25:114,
33:1121, 33:1122, 33:1123, 33:1124,	25:115, 25:116, 25:117, 25:118,
33:1125, 33:1126, 33:1127, 33:1128,	25:119, 25:120, 25:121, 25:122,
33:1129, 33:1130, 33:1131, 33:1132,	25:123, 25:124, 25:125, 25:126,
33:1133, 33:1134, 33:1135, 33:1136,	25:127, 25:128, 25:129, 25:130,
33:1137, 33:1138, 33:1139, 33:1140,	25:131, 25:132, 25:133, 25:134,
33:1141, 33:1142, 33:1143, 33:1144,	25:135, 25:136, 25:137, 25:138,
33:1145, 33:1146, 33:1147, 33:1148,	25:139, 25:140, 25:141, 25:142,
33:1149, 33:1150, 33:1151, 33:1152,	25:143, 25:144, 25:145, 25:146,
33:1153, 33:1154, 33:1155, 33:1156,	25:147, 25:148, 25:149, 25:150,
33:1157, 33:1158, 33:1159, 33:1160,	25:151, 25:152, 25:153, 25:154,
33:1161, 33:1162, 33:1163, 33:1164,	25:155, 25:156, 25:157, 25:158,
33:1165, 33:1166, 33:1167, 33:1168,	25:159, 25:160, 25:161, 25:162,
33:1169, 33:1170, 33:1171, 33:1172, 545	25:163, 25:164, 25:165, 25:166,
\DeclareEncodingsubset . . . . . 796	25:167, 25:168, 25:169, 25:170,
\DeclareEnvironmentCopy . . . . .	25:171, 25:172, 25:173, 25:174,
. . . . . 06:605, 06:606, 06:608, 1375	25:175, 25:176, 25:177, 25:178,
\DeclareErrorFont . . . . .	25:179, 25:180, 25:181, 25:182,
. 24:574, 28:403, 28:453, 29:863, 30:61	25:183, 25:184, 25:185, 25:186,
\DeclareExpandableDocumentCommand . .	25:187, 25:188, 25:189, 25:190,
. . . . . 44:184, 44:185, 07:3236	25:191, 25:192, 25:193, 25:194,
\DeclareFixedFont . . . . .	25:195, 25:196, 25:197, 25:198,
. . . . . 24:76, 33:1213, 33:1215, 797	25:199, 25:200, 25:201, 25:202,
\DeclareFontEncoding . . . . .	25:203, 25:204, 25:205, 25:206,
. . . 21:397, 21:485, 21:740, 21:762,	25:207, 25:208, 25:209, 25:210,
21:768, 21:854, 21:1062, 24:119,	25:211, 25:212, 25:213, 25:214,
30:137, 30:138, 30:139, 30:140, 1324	25:215, 25:216, 25:217, 25:218,
\DeclareFontEncodingDefaults . . . . .	25:219, 25:220, 25:221, 25:222,
. . . . . 24:169, 27:90, 27:91, 30:36	25:223, 25:224, 25:225, 25:226,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

25:227, 25:228, 25:229, 25:230, 25:443, 25:444, 25:445, 25:446,  
 25:231, 25:232, 25:233, 25:234, 25:447, 25:448, 25:449, 25:450,  
 25:235, 25:236, 25:237, 25:238, 25:451, 25:452, 25:453, 25:454,  
 25:239, 25:240, 25:241, 25:242, 25:455, 25:456, 25:457, 25:458,  
 25:243, 25:244, 25:245, 25:246, 25:459, 25:460, 25:461, 25:462,  
 25:247, 25:248, 25:249, 25:250, 25:463, 25:464, 25:465, 25:466,  
 25:251, 25:252, 25:253, 25:254, 25:467, 25:468, 25:469, 25:470,  
 25:255, 25:256, 25:257, 25:258, 25:471, 25:472, 25:473, 25:474,  
 25:259, 25:260, 25:261, 25:262, 25:475, 25:476, 25:477, 25:478,  
 25:263, 25:264, 25:265, 25:266, 25:479, 25:480, 25:481, 25:482,  
 25:267, 25:268, 25:269, 25:270, 25:483, 25:484, 25:485, 25:486,  
 25:271, 25:272, 25:273, 25:274, 25:487, 25:488, 25:489, 25:490,  
 25:275, 25:276, 25:277, 25:278, 25:491, 25:492, 25:493, 25:494,  
 25:279, 25:280, 25:281, 25:282, 25:495, 25:496, 25:497, 25:498,  
 25:283, 25:284, 25:285, 25:286, 25:499, 25:500, 25:501, 25:502,  
 25:287, 25:288, 25:289, 25:290, 25:503, 25:504, 25:505, 25:506,  
 25:291, 25:292, 25:293, 25:294, 25:507, 25:508, 25:509, 25:510,  
 25:295, 25:296, 25:297, 25:298, 25:511, 25:512, 25:513, 25:514,  
 25:299, 25:300, 25:301, 25:302, 25:515, 25:516, 25:517, 25:518,  
 25:303, 25:304, 25:305, 25:306, 25:519, 25:520, 25:521, 25:522,  
 25:307, 25:308, 25:309, 25:310, 25:523, 25:524, 25:525, 25:526,  
 25:311, 25:312, 25:313, 25:314, 25:527, 25:528, 25:529, 25:530,  
 25:315, 25:316, 25:317, 25:318, 25:531, 25:532, 25:533, 25:534,  
 25:319, 25:320, 25:321, 25:322, 25:535, 25:536, 25:537, 25:538,  
 25:323, 25:324, 25:325, 25:326, 25:539, 25:540, 25:541, 25:542,  
 25:327, 25:328, 25:329, 25:330, 25:543, 25:544, 25:545, 25:546,  
 25:331, 25:332, 25:333, 25:334, 25:547, 25:548, 25:549, 25:550,  
 25:335, 25:336, 25:337, 25:338, 25:551, 25:552, 25:553, 25:554,  
 25:339, 25:340, 25:341, 25:342, 25:555, 25:556, 25:557, 25:558,  
 25:343, 25:344, 25:345, 25:346, 25:559, 25:560, 25:561, 25:562,  
 25:347, 25:348, 25:349, 25:350, 25:563, 25:564, 25:565, 25:566,  
 25:351, 25:352, 25:353, 25:354, 25:567, 25:568, 25:569, 25:570,  
 25:355, 25:356, 25:357, 25:358, 25:571, 25:572, 25:573, 25:574,  
 25:359, 25:360, 25:361, 25:362, 25:575, 25:576, 25:577, 25:578,  
 25:363, 25:364, 25:365, 25:366, 25:579, 25:580, 25:581, 25:582,  
 25:367, 25:368, 25:369, 25:370, 25:583, 25:584, 25:585, 25:586,  
 25:371, 25:372, 25:373, 25:374, 25:587, 25:588, 25:589, 25:590,  
 25:375, 25:376, 25:377, 25:378, 25:591, 25:592, 25:593, 25:594,  
 25:379, 25:380, 25:381, 25:382, 25:595, 25:596, 25:597, 25:598,  
 25:383, 25:384, 25:385, 25:386, 25:599, 25:600, 25:601, 25:602,  
 25:387, 25:388, 25:389, 25:390, 25:603, 25:604, 25:605, 25:606,  
 25:391, 25:392, 25:393, 25:394, 25:607, 25:608, 25:609, 25:610,  
 25:395, 25:396, 25:397, 25:398, 25:611, 25:612, 25:613, 25:614,  
 25:399, 25:400, 25:401, 25:402, 25:615, 25:616, 25:617, 25:618,  
 25:403, 25:404, 25:405, 25:406, 25:619, 25:620, 25:621, 25:622,  
 25:407, 25:408, 25:409, 25:410, 25:623, 25:624, 25:625, 25:626,  
 25:411, 25:412, 25:413, 25:414, 25:627, 25:628, 25:629, 25:630,  
 25:415, 25:416, 25:417, 25:418, 25:631, 25:632, 25:633, 25:634,  
 25:419, 25:420, 25:421, 25:422, 25:635, 25:636, 25:637, 25:638,  
 25:423, 25:424, 25:425, 25:426, 25:639, 25:640, 25:641, 25:642,  
 25:427, 25:428, 25:429, 25:430, 25:643, 25:644, 25:645, 25:646,  
 25:431, 25:432, 25:433, 25:434, 25:647, 25:648, 25:649, 25:650,  
 25:435, 25:436, 25:437, 25:438, 25:651, 25:652, 25:653, 25:654,  
 25:439, 25:440, 25:441, 25:442, 25:655, 25:656, 25:657, 25:658,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

25:659, 25:660, 25:661, 25:662, 25:875, 25:876, 25:877, 25:878,  
 25:663, 25:664, 25:665, 25:666, 25:879, 25:880, 25:881, 25:882,  
 25:667, 25:668, 25:669, 25:670, 25:883, 25:884, 25:885, 25:886,  
 25:671, 25:672, 25:673, 25:674, 25:887, 25:888, 25:889, 25:890,  
 25:675, 25:676, 25:677, 25:678, 25:891, 25:892, 25:893, 25:894,  
 25:679, 25:680, 25:681, 25:682, 25:895, 25:896, 25:897, 25:898,  
 25:683, 25:684, 25:685, 25:686, 25:899, 25:900, 25:901, 25:902,  
 25:687, 25:688, 25:689, 25:690, 25:903, 25:904, 25:905, 25:906,  
 25:691, 25:692, 25:693, 25:694, 25:907, 25:908, 25:909, 25:910,  
 25:695, 25:696, 25:697, 25:698, 25:911, 25:912, 25:913, 25:914,  
 25:699, 25:700, 25:701, 25:702, 25:915, 25:916, 25:917, 25:918,  
 25:703, 25:704, 25:705, 25:706, 25:919, 25:920, 25:921, 25:922,  
 25:707, 25:708, 25:709, 25:710, 25:923, 25:924, 25:925, 25:926,  
 25:711, 25:712, 25:713, 25:714, 25:927, 25:928, 25:929, 25:930,  
 25:715, 25:716, 25:717, 25:718, 25:931, 25:932, 25:933, 25:934,  
 25:719, 25:720, 25:721, 25:722, 25:935, 25:936, 25:937, 25:938,  
 25:723, 25:724, 25:725, 25:726, 25:939, 25:940, 25:941, 25:942,  
 25:727, 25:728, 25:729, 25:730, 25:943, 25:944, 25:945, 25:946,  
 25:731, 25:732, 25:733, 25:734, 25:947, 25:948, 25:949, 25:950,  
 25:735, 25:736, 25:737, 25:738, 25:951, 25:952, 25:953, 25:954,  
 25:739, 25:740, 25:741, 25:742, 25:955, 25:956, 25:957, 25:958,  
 25:743, 25:744, 25:745, 25:746, 25:959, 25:960, 25:961, 25:962,  
 25:747, 25:748, 25:749, 25:750, 25:963, 25:964, 25:965, 25:966,  
 25:751, 25:752, 25:753, 25:754, 25:967, 25:968, 25:969, 25:970,  
 25:755, 25:756, 25:757, 25:758, 25:971, 25:972, 25:973, 25:974,  
 25:759, 25:760, 25:761, 25:762, 25:975, 25:976, 25:977, 25:978,  
 25:763, 25:764, 25:765, 25:766, 25:979, 25:980, 25:981, 25:982,  
 25:767, 25:768, 25:769, 25:770, 25:983, 25:984, 25:985, 25:986,  
 25:771, 25:772, 25:773, 25:774, 25:987, 25:988, 25:989, 25:990,  
 25:775, 25:776, 25:777, 25:778, 25:991, 25:992, 25:993, 25:994,  
 25:779, 25:780, 25:781, 25:782, 25:995, 25:996, 25:997, 25:998,  
 25:783, 25:784, 25:785, 25:786, 25:999, 25:1000, 25:1001, 25:1002,  
 25:787, 25:788, 25:789, 25:790, 25:1003, 25:1004, 25:1005, 25:1006,  
 25:791, 25:792, 25:793, 25:794, 25:1007, 25:1008, 25:1009, 25:1010,  
 25:795, 25:796, 25:797, 25:798, 25:1011, 25:1012, 25:1013, 25:1014,  
 25:799, 25:800, 25:801, 25:802, 25:1015, 25:1016, 25:1017, 25:1018,  
 25:803, 25:804, 25:805, 25:806, 25:1019, 25:1020, 25:1021, 25:1022,  
 25:807, 25:808, 25:809, 25:810, 25:1023, 25:1024, 25:1025, 25:1026,  
 25:811, 25:812, 25:813, 25:814, 25:1027, 25:1028, 25:1029, 25:1030,  
 25:815, 25:816, 25:817, 25:818, 25:1031, 25:1032, 25:1033, 25:1034,  
 25:819, 25:820, 25:821, 25:822, 25:1035, 25:1036, 25:1037, 25:1038,  
 25:823, 25:824, 25:825, 25:826, 25:1039, 25:1040, 25:1041, 25:1042,  
 25:827, 25:828, 25:829, 25:830, 25:1043, 25:1044, 25:1045, 25:1046,  
 25:831, 25:832, 25:833, 25:834, 25:1047, 25:1048, 25:1049, 25:1050,  
 25:835, 25:836, 25:837, 25:838, 25:1051, 25:1052, 25:1053, 25:1054,  
 25:839, 25:840, 25:841, 25:842, 25:1055, 25:1056, 25:1057, 25:1058,  
 25:843, 25:844, 25:845, 25:846, 25:1059, 25:1060, 25:1061, 25:1062,  
 25:847, 25:848, 25:849, 25:850, 25:1063, 25:1064, 25:1065, 25:1066,  
 25:851, 25:852, 25:853, 25:854, 25:1067, 25:1068, 25:1069, 25:1070,  
 25:855, 25:856, 25:857, 25:858, 25:1071, 25:1072, 25:1073, 25:1074,  
 25:859, 25:860, 25:861, 25:862, 25:1075, 25:1076, 25:1077, 25:1078,  
 25:863, 25:864, 25:865, 25:866, 25:1079, 25:1080, 25:1081, 25:1082,  
 25:867, 25:868, 25:869, 25:870, 25:1083, 25:1084, 25:1085, 25:1086,  
 25:871, 25:872, 25:873, 25:874, 25:1087, 25:1088, 25:1089, 25:1090,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpara.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

25:1091, 25:1092, 25:1093, 25:1094,  
 25:1095, 25:1096, 25:1097, 25:1098,  
 25:1099, 25:1100, 25:1101, 25:1102,  
 25:1103, 25:1104, 25:1105, 25:1106,  
 25:1107, 25:1108, 25:1109, 25:1110,  
 25:1111, 25:1112, 25:1113, 25:1114,  
 25:1115, 25:1116, 25:1117, 25:1118,  
 25:1119, 25:1120, 25:1121, 25:1122,  
 25:1123, 25:1124, 25:1125, 25:1126,  
 25:1127, 25:1128, 25:1129, 25:1130,  
 25:1131, 25:1132, 25:1133, 25:1134,  
 25:1135, 25:1136, 25:1137, 25:1138,  
 25:1139, 25:1140, 25:1141, 25:1142,  
 25:1143, 25:1144, 25:1145, 25:1146,  
 25:1147, 25:1148, 25:1149, 25:1150,  
 25:1151, 25:1152, 25:1153, 25:1154,  
 25:1155, 25:1156, 25:1157, 25:1158,  
 25:1159, 25:1160, 25:1161, 25:1162,  
 25:1163, 25:1164, 25:1165, 25:1166,  
 25:1167, 25:1168, 25:1169, 25:1170,  
 25:1171, 25:1172, 25:1173, 25:1174,  
 25:1175, 25:1176, 25:1177, 25:1178,  
 25:1179, 25:1180, 25:1181, 25:1182,  
 25:1183, 25:1184, 25:1185, 25:1186,  
 25:1187, 25:1188, 25:1189, 25:1190,  
 25:1191, 25:1192, 25:1193, 25:1194,  
 25:1195, 25:1196, 25:1197, 25:1198,  
 25:1199, 25:1200, 25:1201, 25:1202,  
 25:1203, 25:1204, 25:1205, 25:1206,  
 25:1207, 25:1208, 25:1209, 25:1210,  
 25:1211, 25:1212, 25:1213, 25:1214,  
 25:1215, 25:1216, 25:1217, 25:1218,  
 25:1219, 25:1220, 25:1221, 25:1222,  
 25:1223, 25:1224, 25:1225, 25:1226,  
 25:1227, 25:1228, 25:1229, 25:1230,  
 25:1231, 25:1232, 25:1233, 25:1234,  
 25:1235, 25:1236, 25:1237, 25:1238,  
 25:1239, 25:1240, 25:1241, 25:1242,  
 25:1243, 25:1244, 25:1245, 25:1246,  
 25:1247, 25:1248, 25:1249, 25:1250,  
 25:1251, 25:1252, 25:1253, 25:1254,  
 25:1255, 25:1256, 25:1257, 25:1258,  
 25:1259, 25:1260, 25:1261, 25:1262,  
 25:1263, 25:1264, 25:1265, 25:1266,  
 25:1267, 25:1268, 25:1269, 25:1270,  
 25:1271, 25:1272, 25:1273, 25:1274,  
 25:1275, 25:1276, 25:1277, 25:1278,  
 25:1279, 25:1280, 25:1281, 25:1282,  
 25:1283, 25:1284, 25:1285, 25:1286,  
 25:1287, 25:1288, 25:1289, 25:1290,  
 25:1291, 25:1292, 25:1293, 25:1294,  
 25:1295, 25:1296, 25:1297, 25:1298,  
 25:1299, 25:1300, 25:1301, 25:1302,  
 25:1303, 25:1304, 25:1305, 25:1306,  
 25:1307, 25:1308, 25:1309, 25:1310,  
 25:1311, 25:1312, 25:1313, 25:1314,  
 25:1315, 25:1316, 25:1317, 25:1318,  
 25:1319, 25:1320, 25:1321, 25:1322,  
 25:1323, 25:1324, 25:1325, 25:1326,  
 25:1327, 25:1328, 25:1329, 25:1330,  
 25:1331, 25:1332, 25:1333, 25:1334,  
 25:1335, 25:1336, 25:1337, 25:1338,  
 25:1339, 25:1340, 25:1341, 25:1342,  
 25:1343, 25:1344, 25:1345, 25:1346,  
 25:1347, 25:1348, 25:1349, 25:1350,  
 25:1351, 25:1352, 25:1353, 25:1354,  
 25:1355, 25:1356, 25:1357, 25:1358,  
 25:1359, 25:1360, 25:1361, 25:1362,  
 25:1363, 25:1364, 25:1365, 25:1366,  
 25:1367, 25:1368, 25:1369, 25:1370,  
 25:1371, 25:1372, 25:1373, 25:1374,  
 25:1375, 25:1376, 25:1377, 25:1378,  
 25:1379, 25:1380, 25:1381, 25:1382,  
 25:1383, 25:1384, 25:1385, 25:1386,  
 25:1387, 25:1388, 25:1389, 25:1390,  
 25:1391, 25:1392, 25:1393, 25:1394,  
 25:1395, 25:1396, 25:1397, 25:1398,  
 25:1399, 25:1400, 25:1401, 25:1402,  
 25:1403, 25:1404, 25:1405, 25:1406,  
 25:1407, 25:1408, 25:1409, 25:1410,  
 25:1411, 25:1412, 25:1413, 25:1414,  
 25:1415, 25:1416, 25:1417, 25:1418,  
 25:1419, 25:1420, 25:1421, 25:1422,  
 25:1423, 25:1424, 25:1425, 25:1426,  
 25:1427, 25:1428, 25:1429, 25:1433,  
 25:1435, 25:1438, 25:1439, 25:1440,  
 25:1441, 25:1442, 25:1443, 25:1444,  
 25:1445, 25:1446, 25:1447, 25:1448,  
 25:1449, 25:1450, 25:1451, 25:1452,  
 25:1453, 25:1454, 25:1455, 25:1456,  
 25:1457, 25:1458, 25:1459, 25:1460,  
 25:1461, 25:1462, 25:1463, 25:1464,  
 25:1465, 25:1466, 25:1467, 25:1468,  
 25:1469, 25:1470, 25:1471, 25:1472,  
 25:1473, 25:1474, 25:1475, 25:1476,  
 25:1477, 25:1478, 25:1479, 25:1480,  
 25:1481, 25:1482, 25:1483, 25:1484,  
 25:1485, 25:1486, 25:1487, 25:1488,  
 25:1489, 25:1490, 25:1491, 25:1492,  
 25:1493, 25:1494, 25:1495, 25:1496,  
 25:1497, 25:1498, 25:1499, 25:1500,  
 25:1501, 25:1502, 25:1503, 25:1504,  
 25:1505, 25:1506, 25:1507, 25:1508,  
 25:1509, 25:1510, 25:1511, 25:1512,  
 25:1513, 25:1514, 25:1515, 25:1516,  
 25:1517, 25:1518, 25:1519, 25:1520,  
 25:1521, 25:1522, 25:1523, 25:1524,  
 25:1525, 25:1526, 25:1527, 25:1528,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

25:1529, 25:1530, 25:1531, 25:1532,  
 25:1533, 25:1534, 25:1535, 25:1536,  
 25:1537, 25:1538, 25:1539, 25:1540,  
 25:1541, 25:1542, 25:1543, 25:1544,  
 25:1545, 25:1546, 25:1547, 25:1548,  
 25:1549, 25:1550, 25:1551, 25:1552,  
 25:1553, 25:1554, 25:1555, 25:1556,  
 25:1557, 25:1558, 25:1559, 25:1560,  
 25:1561, 25:1562, 25:1563, 25:1564,  
 25:1565, 25:1566, 25:1567, 25:1568,  
 25:1569, 25:1570, 25:1571, 25:1572,  
 25:1573, 25:1574, 25:1575, 25:1576,  
 25:1577, 25:1578, 25:1579, 25:1580,  
 25:1581, 25:1582, 25:1583, 25:1584,  
 25:1585, 25:1586, 25:1587, 25:1588,  
 25:1589, 25:1590, 25:1591, 25:1592,  
 25:1593, 25:1594, 25:1595, 25:1596,  
 25:1597, 25:1598, 25:1599, 25:1600,  
 25:1601, 25:1602, 25:1603, 25:1604,  
 25:1605, 25:1606, 25:1607, 25:1608,  
 25:1609, 25:1610, 25:1611, 25:1612,  
 25:1613, 25:1614, 25:1615, 25:1616,  
 25:1617, 25:1618, 25:1619, 25:1620,  
 25:1621, 25:1622, 25:1623, 25:1624,  
 25:1625, 25:1626, 25:1627, 25:1628,  
 25:1629, 25:1630, 25:1631, 25:1632,  
 25:1633, 25:1634, 25:1635, 25:1636,  
 25:1637, 25:1638, 25:1639, 25:1640,  
 25:1641, 25:1642, 25:1643, 25:1644,  
 25:1645, 25:1646, 25:1647, 25:1648,  
 25:1649, 25:1650, 25:1651, 25:1652,  
 25:1653, 25:1654, 25:1655, 25:1656,  
 25:1657, 25:1658, 25:1659, 25:1660,  
 25:1661, 25:1662, 25:1663, 25:1664,  
 25:1665, 25:1666, 25:1667, 25:1668,  
 25:1669, 25:1670, 25:1671, 25:1672,  
 25:1673, 25:1674, 25:1675, 25:1676,  
 25:1677, 25:1678, 25:1679, 25:1680,  
 25:1681, 25:1682, 25:1683, 25:1684,  
 25:1685, 25:1686, 25:1687, 25:1688,  
 25:1689, 25:1690, 25:1691, 25:1692,  
 25:1693, 25:1694, 25:1695, 25:1696,  
 25:1697, 25:1698, 25:1699, 25:1700,  
 25:1701, 25:1702, 25:1703, 25:1704,  
 25:1705, 25:1706, 25:1707, 25:1708,  
 25:1709, 25:1710, 25:1711, 25:1712,  
 25:1713, 25:1714, 25:1715, 25:1716,  
 25:1717, 25:1718, 25:1719, 25:1720,  
 25:1721, 25:1722, 25:1723, 25:1724,  
 25:1725, 25:1726, 25:1727, 25:1728,  
 25:1729, 25:1730, 25:1731, 25:1732,  
 25:1733, 25:1734, 25:1735, 25:1736,  
 25:1737, 25:1738, 25:1739, 25:1740,  
 25:1741, 25:1742, 25:1743, 25:1744,  
 25:1745, 25:1746, 25:1747, 25:1748,  
 25:1749, 25:1750, 25:1751, 25:1752,  
 25:1753, 25:1754, 25:1755, 25:1756,  
 25:1757, 25:1758, 25:1759, 25:1760,  
 25:1761, 25:1762, 25:1763, 25:1764,  
 25:1765, 25:1766, 25:1767, 25:1768,  
 25:1769, 25:1770, 25:1771, 25:1772,  
 25:1773, 25:1774, 25:1775, 25:1776,  
 25:1777, 25:1778, 25:1779, 25:1780,  
 25:1781, 25:1782, 25:1783, 25:1784,  
 25:1785, 25:1786, 25:1787, 25:1788,  
 25:1789, 25:1790, 25:1791, 25:1792,  
 25:1793, 25:1794, 25:1795, 25:1796,  
 25:1797, 25:1798, 25:1799, 25:1800,  
 25:1801, 25:1802, 25:1803, 25:1804,  
 25:1805, 25:1806, 25:1807, 25:1808,  
 25:1809, 25:1810, 25:1811, 25:1812,  
 25:1813, 25:1814, 25:1815, 25:1816,  
 25:1817, 25:1818, 25:1819, 25:1820,  
 25:1821, 25:1822, 25:1823, 25:1824,  
 25:1825, 25:1826, 25:1827, 25:1828,  
 25:1829, 25:1830, 25:1831, 25:1832,  
 25:1833, 25:1834, 25:1835, 25:1836,  
 25:1837, 25:1838, 25:1839, 25:1840,  
 25:1841, 25:1842, 25:1843, 25:1844,  
 25:1845, 25:1846, 25:1847, 25:1848,  
 25:1849, 25:1850, 25:1851, 25:1852,  
 25:1853, 25:1854, 25:1855, 25:1856,  
 25:1857, 25:1858, 25:1859, 25:1860,  
 25:1861, 25:1862, 25:1863, 25:1864,  
 25:1865, 25:1866, 25:1867, 25:1868,  
 25:1869, 25:1870, 25:1871, 25:1872,  
 25:1873, 25:1874, 25:1875, 25:1876,  
 25:1877, 25:1878, 25:1879, 25:1880,  
 25:1881, 25:1882, 25:1883, 25:1884,  
 25:1885, 25:1886, 25:1887, 25:1888,  
 25:1889, 25:1890, 25:1891, 25:1892,  
 25:1893, 25:1894, 25:1895, 25:1896,  
 25:1897, 25:1898, 25:1899, 25:1900,  
 25:1901, 25:1902, 25:1903, 25:1904,  
 25:1905, 25:1906, 25:1907, 25:1908,  
 25:1909, 25:1910, 25:1911, 25:1912,  
 25:1913, 25:1914, 25:1915, 25:1916,  
 25:1917, 25:1918, 25:1919, 25:1920,  
 25:1921, 25:1922, 25:1923, 25:1924,  
 25:1925, 25:1926, 25:1927, 25:1928,  
 25:1929, 25:1930, 25:1931, 25:1932,  
 25:1933, 25:1934, 25:1935, 25:1936,  
 25:1937, 25:1938, 25:1939, 25:1940,  
 25:1941, 25:1942, 25:1943, 25:1944,  
 25:1945, 25:1946, 25:1947, 25:1948,  
 25:1949, 25:1950, 25:1951, 25:1952,  
 25:1953, 25:1954, 25:1955, 25:1956,  
 25:1957, 25:1958, 25:1959, 25:1960,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

25:1961, 25:1962, 25:1963, 25:1964,  
 25:1965, 25:1966, 25:1967, 25:1968,  
 25:1969, 25:1970, 25:1971, 25:1972,  
 25:1973, 25:1974, 25:1975, 25:1976,  
 25:1977, 25:1978, 25:1979, 25:1980,  
 25:1981, 25:1982, 25:1983, 25:1984,  
 25:1985, 25:1986, 25:1987, 25:1988,  
 25:1989, 25:1990, 25:1991, 25:1992,  
 25:1993, 25:1994, 25:1995, 25:1996,  
 25:1997, 25:1998, 25:1999, 25:2000,  
 25:2001, 25:2002, 25:2003, 25:2004,  
 25:2005, 25:2006, 25:2007, 25:2008,  
 25:2009, 25:2010, 25:2011, 25:2012,  
 25:2013, 25:2014, 25:2015, 25:2016,  
 25:2017, 25:2018, 25:2019, 25:2020,  
 25:2021, 25:2022, 25:2023, 25:2024,  
 25:2025, 25:2026, 25:2027, 25:2028,  
 25:2029, 25:2030, 25:2031, 25:2032,  
 25:2033, 25:2034, 25:2035, 25:2036,  
 25:2037, 25:2038, 25:2039, 25:2040,  
 25:2041, 25:2042, 25:2043, 25:2044,  
 25:2045, 25:2046, 25:2047, 25:2048,  
 25:2049, 25:2050, 25:2051, 25:2052,  
 25:2053, 25:2054, 25:2055, 25:2056,  
 25:2057, 25:2058, 25:2059, 25:2060,  
 25:2061, 25:2062, 25:2063, 25:2064,  
 25:2065, 25:2066, 25:2067, 25:2068,  
 25:2069, 25:2070, 25:2071, 25:2072,  
 25:2073, 25:2074, 25:2075, 25:2076,  
 25:2077, 25:2078, 25:2079, 25:2080,  
 25:2081, 25:2082, 25:2083, 25:2084,  
 25:2085, 25:2086, 25:2087, 25:2088,  
 25:2089, 25:2090, 25:2091, 25:2092,  
 25:2093, 25:2094, 25:2095, 25:2096,  
 25:2097, 25:2098, 25:2099, 25:2100,  
 25:2101, 25:2102, 25:2103, 25:2104,  
 25:2105, 25:2106, 25:2107, 25:2108,  
 25:2109, 25:2110, 25:2111, 25:2112,  
 25:2113, 25:2114, 25:2115, 25:2116,  
 25:2117, 25:2118, 25:2119, 25:2120,  
 25:2121, 25:2122, 25:2123, 25:2124,  
 25:2125, 25:2126, 25:2127, 25:2128,  
 25:2129, 25:2130, 25:2131, 25:2132,  
 25:2133, 25:2134, 25:2135, 25:2136,  
 25:2137, 25:2138, 25:2139, 25:2140,  
 25:2141, 25:2142, 25:2143, 25:2144,  
 25:2145, 25:2146, 25:2147, 25:2148,  
 25:2149, 25:2150, 25:2151, 25:2152,  
 25:2153, 25:2154, 25:2155, 25:2156,  
 25:2157, 25:2158, 25:2159, 25:2160,  
 25:2161, 25:2162, 25:2163, 25:2164,  
 25:2165, 25:2166, 25:2167, 25:2168,  
 25:2169, 25:2170, 25:2171, 25:2172,  
 25:2173, 25:2174, 25:2175, 25:2176,  
 25:2177, 25:2178, 25:2179, 25:2180,  
 25:2181, 25:2182, 25:2183, 25:2184,  
 25:2185, 25:2186, 25:2187, 25:2188,  
 25:2189, 25:2190, 25:2191, 25:2192,  
 25:2193, 25:2194, 25:2195, 25:2196,  
 25:2197, 25:2198, 25:2199, 25:2200,  
 25:2201, 25:2202, 25:2203, 25:2204,  
 25:2205, 25:2206, 25:2207, 25:2208,  
 25:2209, 25:2210, 25:2211, 25:2212,  
 25:2213, 25:2214, 25:2215, 25:2216,  
 25:2217, 25:2218, 25:2219, 25:2220,  
 25:2221, 25:2222, 25:2223, 25:2224,  
 25:2225, 25:2226, 25:2227, 25:2228,  
 25:2229, 25:2230, 25:2231, 25:2232,  
 25:2233, 25:2234, 25:2235, 25:2236,  
 25:2237, 25:2238, 25:2239, 25:2240,  
 25:2241, 25:2242, 25:2243, 25:2244,  
 25:2245, 25:2246, 25:2247, 25:2248,  
 25:2249, 25:2250, 25:2251, 25:2252,  
 25:2253, 25:2254, 25:2255, 25:2256,  
 25:2257, 25:2258, 25:2259, 25:2260,  
 25:2261, 25:2262, 25:2263, 25:2264,  
 25:2265, 25:2266, 25:2267, 25:2268,  
 25:2269, 25:2270, 25:2271, 25:2272,  
 25:2273, 25:2274, 25:2275, 25:2276,  
 25:2277, 25:2278, 25:2279, 25:2280,  
 25:2281, 25:2282, 25:2283, 25:2284,  
 25:2285, 25:2286, 25:2287, 25:2288,  
 25:2289, 25:2290, 25:2291, 25:2292,  
 25:2293, 25:2294, 25:2295, 25:2296,  
 25:2297, 25:2298, 25:2299, 25:2300,  
 25:2301, 25:2302, 25:2303, 25:2304,  
 25:2305, 25:2306, 25:2307, 25:2308,  
 25:2309, 25:2310, 25:2311, 25:2312,  
 25:2313, 25:2314, 25:2315, 25:2316,  
 25:2317, 25:2318, 25:2319, 25:2320,  
 25:2321, 25:2322, 25:2323, 25:2324,  
 25:2325, 25:2326, 25:2327, 25:2328,  
 25:2329, 25:2330, 25:2331, 25:2332,  
 25:2333, 25:2334, 25:2335, 25:2336,  
 25:2337, 25:2338, 25:2339, 25:2340,  
 25:2341, 25:2342, 25:2343, 25:2344,  
 25:2345, 25:2346, 25:2347, 25:2348,  
 25:2349, 25:2350, 25:2351, 25:2352,  
 25:2353, 25:2354, 25:2355, 25:2356,  
 25:2357, 25:2358, 25:2359, 25:2360,  
 25:2361, 25:2362, 25:2363, 25:2364,  
 25:2365, 25:2366, 25:2367, 25:2368,  
 25:2369, 25:2370, 25:2371, 25:2372,  
 25:2373, 25:2374, 25:2375, 25:2376,  
 25:2377, 25:2378, 25:2379, 25:2380,  
 25:2381, 25:2382, 25:2383, 25:2384,  
 25:2385, 25:2386, 25:2387, 25:2388,  
 25:2389, 25:2390, 25:2391, 25:2392,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

25:2393, 25:2394, 25:2395, 25:2396,  
 25:2397, 25:2398, 25:2399, 25:2400,  
 25:2401, 25:2402, 25:2403, 25:2404,  
 25:2405, 25:2406, 25:2407, 25:2408,  
 25:2409, 25:2410, 25:2411, 25:2412,  
 25:2413, 25:2414, 25:2415, 25:2416,  
 25:2417, 25:2418, 25:2419, 25:2420,  
 25:2421, 25:2422, 25:2423, 25:2424,  
 25:2425, 25:2426, 25:2427, 25:2428,  
 25:2429, 25:2430, 25:2431, 25:2432,  
 25:2433, 25:2434, 25:2435, 25:2436,  
 25:2437, 25:2438, 25:2439, 25:2440,  
 25:2441, 25:2442, 25:2443, 25:2444,  
 25:2445, 25:2446, 25:2447, 25:2448,  
 25:2449, 25:2450, 25:2451, 25:2452,  
 25:2453, 25:2454, 25:2455, 25:2456,  
 25:2457, 25:2458, 25:2459, 25:2460,  
 25:2461, 25:2462, 25:2463, 25:2464,  
 25:2465, 25:2466, 25:2467, 25:2468,  
 25:2469, 25:2470, 25:2471, 25:2472,  
 25:2473, 25:2474, 25:2475, 25:2476,  
 25:2477, 25:2478, 25:2479, 25:2480,  
 25:2481, 25:2482, 25:2483, 25:2484,  
 25:2485, 25:2486, 25:2487, 25:2488,  
 25:2489, 25:2490, 25:2491, 25:2492,  
 25:2493, 25:2494, 25:2495, 25:2496,  
 25:2497, 25:2498, 25:2499, 25:2500,  
 25:2501, 25:2502, 25:2503, 25:2504,  
 25:2505, 25:2506, 25:2507, 25:2508,  
 25:2509, 25:2510, 25:2511, 25:2512,  
 25:2513, 25:2514, 25:2515, 25:2516,  
 25:2517, 25:2518, 25:2519, 25:2520,  
 25:2521, 25:2522, 25:2523, 25:2524,  
 25:2525, 25:2526, 25:2527, 25:2528,  
 25:2529, 25:2530, 25:2531, 25:2532,  
 25:2533, 25:2534, 25:2535, 25:2536,  
 25:2537, 25:2538, 25:2539, 25:2540,  
 25:2541, 25:2542, 25:2543, 25:2544,  
 25:2545, 25:2546, 25:2547, 25:2548,  
 25:2549, 25:2550, 25:2551, 25:2552,  
 25:2553, 25:2554, 25:2555, 25:2556,  
 25:2557, 25:2558, 25:2559, 25:2560,  
 25:2561, 25:2562, 25:2563, 25:2564,  
 25:2565, 25:2566, 25:2567, 25:2568,  
 25:2569, 25:2570, 25:2571, 25:2572,  
 25:2573, 25:2574, 25:2575, 25:2576,  
 25:2577, 25:2578, 25:2579, 25:2580,  
 25:2581, 25:2582, 25:2583, 25:2584,  
 25:2585, 25:2586, 25:2587, 25:2588,  
 25:2589, 25:2590, 25:2591, 25:2592,  
 25:2593, 25:2594, 25:2595, 25:2596,  
 25:2597, 25:2598, 25:2599, 25:2600,  
 25:2601, 25:2602, 25:2603, 25:2604,  
 25:2605, 25:2606, 25:2607, 25:2608,  
 25:2609, 25:2610, 25:2611, 25:2612,  
 25:2613, 25:2614, 25:2615, 25:2616,  
 25:2617, 25:2618, 25:2619, 25:2620,  
 25:2621, 25:2622, 25:2623, 25:2624,  
 25:2625, 25:2626, 25:2627, 25:2628,  
 25:2629, 25:2630, 25:2631, 25:2632,  
 25:2633, 25:2634, 25:2635, 25:2636,  
 25:2637, 25:2638, 25:2639, 25:2640,  
 25:2641, 25:2642, 25:2643, 25:2644,  
 25:2645, 25:2646, 25:2647, 25:2648,  
 25:2649, 25:2650, 25:2651, 25:2652,  
 25:2653, 25:2654, 25:2655, 25:2656,  
 25:2657, 25:2658, 25:2659, 25:2660,  
 25:2661, 25:2662, 25:2663, 25:2664,  
 25:2665, 25:2666, 25:2667, 25:2668,  
 25:2669, 25:2670, 25:2671, 25:2672,  
 25:2673, 25:2674, 25:2675, 25:2676,  
 25:2677, 25:2678, 25:2679, 25:2680,  
 25:2681, 25:2682, 25:2683, 25:2684,  
 25:2685, 25:2686, 25:2687, 25:2688,  
 25:2689, 25:2690, 25:2691, 25:2692,  
 25:2693, 25:2694, 25:2695, 25:2696,  
 25:2697, 25:2698, 25:2699, 25:2700,  
 25:2701, 25:2702, 25:2703, 25:2704,  
 25:2705, 25:2706, 25:2707, 25:2708,  
 25:2709, 25:2710, 25:2711, 25:2712,  
 25:2713, 25:2714, 25:2715, 25:2716,  
 25:2717, 25:2718, 25:2719, 25:2720,  
 25:2721, 25:2722, 25:2723, 25:2724,  
 25:2725, 25:2726, 25:2727, 25:2728,  
 25:2729, 25:2730, 25:2731, 25:2732,  
 25:2733, 25:2734, 25:2735, 25:2736,  
 25:2737, 25:2738, 25:2739, 25:2740,  
 25:2741, 25:2742, 25:2743, 25:2744,  
 25:2745, 25:2746, 25:2747, 25:2748,  
 25:2749, 25:2750, 25:2751, 25:2752,  
 25:2753, 25:2754, 25:2755, 25:2756,  
 25:2757, 25:2758, 25:2759, 25:2760,  
 25:2761, 25:2762, 25:2763, 25:2764,  
 25:2765, 25:2766, 25:2767, 25:2768,  
 25:2769, 25:2770, 25:2774, 25:2776, 568  
 \DeclareFontSeriesDefault ..... 703  
 \DeclareFontSeriesDefault .....  
 ..... 29:35, 29:36, 29:70, 29:72,  
 29:73, 29:83, 29:94, 29:103, 29:105, 716  
 \DeclareFontShape ..... 24:19,  
 24:543, 24:544, 24:545, 24:546,  
 24:547, 24:548, 24:549, 24:550,  
 24:551, 24:552, 24:553, 24:554,  
 24:555, 24:556, 24:557, 24:558,  
 24:559, 24:560, 24:561, 24:562,  
 24:563, 27:25, 27:27, 27:81, 27:82, 1307  
 \DeclareFontShapeChangeRule 25:2912,  
 25:2934, 25:2947, 25:2949, 25:2950,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

25:2951, 25:2952, 25:2953, 25:2954,	30:527, 30:528, 30:529, 30:530,
25:2955, 25:2956, 25:2957, 25:2958,	30:531, 30:532, 30:533, 30:534,
25:2959, 25:2960, 25:2961, 25:2962,	30:535, 30:536, 30:537, 30:538, 30:539
25:2963, 25:2964, 25:2965, 25:2966,	<code>\DeclareMathAlphabet</code> . . . . . 27:119,
25:2967, 25:2968, 25:2969, 25:2970,	27:123, 27:125, 27:132, 28:686,
25:2971, 25:2972, 25:2973, 25:2974,	28:849, 30:162, 30:163, 30:164, 30:165
25:2975, 25:2976, 25:2977, 25:2978,	<code>\DeclareMathAlphabetCharacter</code> . 28:1035
25:2979, 25:2980, 25:2981, 25:2982,	<code>\DeclareMathDelimiter</code> . . . . .
25:2983, 25:2984, 25:2985, 25:2986,	. . . . . 28:1037, 30:266, 30:267,
25:2987, 25:2988, 25:2989, 25:2990,	30:268, 30:269, 30:270, 30:271,
25:2991, 25:2992, 25:2993, 25:2994,	30:274, 30:276, 30:277, 30:574,
25:2995, 25:2996, 25:2997, 25:2998,	30:576, 30:578, 30:580, 30:582,
25:2999, 25:3000, 25:3001, 25:3002,	30:585, 30:587, 30:589, 30:591,
25:3003, 25:3004, 25:3005, 25:3006,	30:593, 30:595, 30:597, 30:599,
25:3007, 25:3008, 25:3009, 25:3010,	30:601, 30:603, 30:605, 30:607,
25:3011, 25:3012, 25:3013, 25:3014,	30:609, 30:611, 30:613, 30:615,
25:3015, 25:3016, 25:3017, 25:3018,	30:617, 30:619, 30:621, 30:623, 1345
25:3019, 25:3020, 25:3021, 25:3022,	<code>\DeclareMathOperator</code> . . . . . 1329
25:3023, 25:3024, 25:3025, 25:3026,	<code>\DeclareMathRadical</code> . . . . . 28:1172, 30:540
25:3027, 25:3028, 25:3029, 25:3030,	<code>\DeclareMathScriptfontMapping</code> . . 26:354
25:3031, 25:3032, 25:3033, 25:3034,	<code>\DeclareMathSizes</code> . . . . .
25:3035, 25:3036, 25:3037, 25:3038,	. . . . . 24:268, 24:274, 24:296,
25:3039, 25:3040, 25:3041, 25:3042,	30:168, 30:169, 30:170, 30:171,
25:3043, 25:3044, 25:3045, 25:3049,	30:172, 30:173, 30:174, 30:175,
25:3051, 25:3052, 25:3053, 25:3054,	30:176, 30:177, 30:178, 30:179, 1331
25:3055, 25:3056, 25:3057, 25:3058,	<code>\DeclareMathSizes*</code> . . . . . 24:268
25:3059, 25:3060, 25:3061, 25:3062,	<code>\DeclareMathSymbol</code> . . . . .
25:3063, 25:3064, 25:3065, 25:3066,	. 28:973, 28:1036, 28:1053, 30:180,
25:3067, 25:3068, 25:3069, 25:3070,	30:181, 30:182, 30:183, 30:184,
25:3071, 25:3072, 25:3073, 25:3074,	30:185, 30:186, 30:187, 30:188,
25:3075, 25:3076, 25:3077, 25:3078,	30:189, 30:190, 30:191, 30:192,
25:3079, 25:3080, 25:3081, 25:3082,	30:193, 30:194, 30:195, 30:196,
25:3083, 25:3084, 25:3085, 25:3086,	30:197, 30:198, 30:199, 30:200,
25:3087, 25:3088, 25:3090, 25:3091,	30:201, 30:202, 30:203, 30:204,
25:3092, 25:3093, 25:3095, 25:3096,	30:205, 30:206, 30:207, 30:208,
25:3097, 25:3099, 25:3100, 25:3101,	30:209, 30:210, 30:211, 30:212,
25:3102, 25:3103, 25:3104, 25:3106,	30:213, 30:214, 30:215, 30:216,
25:3107, 25:3108, 25:3109, 25:3110,	30:217, 30:218, 30:219, 30:220,
25:3111, 25:3112, 25:3114, 25:3115,	30:221, 30:222, 30:223, 30:224,
25:3116, 25:3117, 25:3118, 25:3119,	30:225, 30:226, 30:227, 30:228,
25:3121, 25:3122, 25:3123, 25:3124,	30:229, 30:230, 30:231, 30:232,
25:3125, 25:3126, 25:3127, 25:3130	30:233, 30:234, 30:235, 30:236,
<code>\DeclareFontSubstitution</code> . . . . 21:398,	30:237, 30:238, 30:239, 30:240,
21:486, 21:769, 21:855, 24:142,	30:241, 30:242, 30:243, 30:244,
30:26, 30:34, 30:37, 30:38, 30:39,	30:245, 30:246, 30:247, 30:248,
30:141, 30:142, 30:143, 30:144, 1386	30:249, 30:250, 30:251, 30:252,
<code>\DeclareHookRule</code> . . . 08:2843, 08:2951,	30:253, 30:254, 30:255, 30:256,
37:52, 37:53, 37:117, 37:118, 211	30:257, 30:258, 30:259, 30:260,
<code>\DeclareInstance</code> . . . . . 11:1193, 360	30:261, 30:262, 30:272, 30:273,
<code>\DeclareInstanceCopy</code> . . . . . 11:1193, 359	30:275, 30:279, 30:280, 30:281,
<code>\DeclareKeys</code> . . . . . 51:216, 1105	30:282, 30:283, 30:284, 30:285,
<code>\DeclareLowercaseExclusions</code> 57:571, 1386	30:286, 30:287, 30:288, 30:289,
<code>\DeclareLowercaseMapping</code> . . . 57:571, 1377	30:290, 30:291, 30:292, 30:293,
<code>\DeclareMathAccent</code> . . . . . 28:860,	30:294, 30:295, 30:296, 30:297,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

30:298,	30:299,	30:300,	30:301,	31:19,	31:21,	31:22,	31:23,	31:25,
30:302,	30:303,	30:304,	30:305,	31:26,	31:27,	31:28,	31:29,	31:30,
30:306,	30:307,	30:308,	30:309,	31:34,	31:38,	31:43,	31:45,	31:49,
30:310,	30:311,	30:312,	30:313,	31:50,	31:53,	31:54,	31:57,	31:58,
30:314,	30:315,	30:316,	30:317,	31:64				
30:318,	30:319,	30:320,	30:321,	\DeclareProtectedCommand	.....	1323		
30:322,	30:323,	30:324,	30:325,	\DeclareRelease	..	33:775,	33:776,	50:1677
30:326,	30:327,	30:328,	30:329,	DeclareRelease commands:				
30:330,	30:331,	30:332,	30:333,	\DeclareRelease:	.....	50:1680		
30:334,	30:335,	30:336,	30:338,	\DeclareRobustCommand	.....	14:4,		
30:339,	30:340,	30:341,	30:342,	14:11,	14:30,	14:57,	18:7,	18:8,
30:343,	30:344,	30:345,	30:352,	18:10,	18:11,	18:69,	18:93,	18:377,
30:353,	30:354,	30:355,	30:356,	18:453,	18:467,	18:512,	18:537,	19:2,
30:357,	30:358,	30:360,	30:361,	19:3,	19:13,	20:488,	20:635,	21:168,
30:362,	30:363,	30:364,	30:365,	21:176,	21:327,	21:330,	21:331,	
30:367,	30:368,	30:369,	30:370,	21:332,	21:333,	21:334,	21:336,	
30:371,	30:372,	30:375,	30:376,	21:338,	21:340,	22:280,	23:32,	
30:377,	30:378,	30:381,	30:382,	23:33,	23:34,	24:314,	24:342,	24:343,
30:383,	30:384,	30:385,	30:386,	24:344,	24:349,	24:361,	24:371,	
30:387,	30:388,	30:389,	30:390,	24:379,	24:381,	24:399,	24:738,	
30:391,	30:392,	30:393,	30:394,	24:748,	25:2782,	25:2786,	25:2795,	
30:395,	30:396,	30:397,	30:398,	25:2797,	25:2807,	25:2914,	25:2919,	
30:399,	30:400,	30:401,	30:402,	25:2924,	25:3135,	25:3138,	25:3146,	
30:403,	30:404,	30:405,	30:406,	25:3147,	25:3153,	25:3233,	26:116,	
30:407,	30:408,	30:409,	30:410,	26:165,	29:5,	29:8,	29:11,	29:14,
30:411,	30:412,	30:413,	30:414,	29:17,	29:20,	29:23,	29:26,	29:29,
30:415,	30:416,	30:417,	30:418,	29:333,	29:356,	29:386,	29:407,	
30:419,	30:420,	30:421,	30:422,	29:431,	29:442,	29:459,	29:462,	
30:425,	30:426,	30:429,	30:430,	29:484,	29:489,	29:494,	29:527,	
30:431,	30:432,	30:433,	30:434,	29:532,	29:537,	29:553,	29:556,	
30:435,	30:436,	30:437,	30:438,	29:559,	29:562,	29:565,	29:579,	
30:439,	30:440,	30:441,	30:443,	29:632,	29:633,	29:668,	29:674,	
30:444,	30:445,	30:446,	30:447,	29:696,	29:698,	29:707,	29:709,	
30:448,	30:449,	30:452,	30:453,	29:716,	29:732,	29:740,	29:773,	
30:454,	30:456,	30:457,	30:458,	29:789,	29:805,	29:822,	29:838,	
30:459,	30:460,	30:461,	30:462,	29:845,	30:346,	30:347,	30:348,	
30:463,	30:464,	30:465,	30:466,	30:359,	30:366,	30:423,	30:424,	
30:488,	30:490,	30:512,	30:513,	30:455,	30:467,	30:471,	30:474,	
30:514,	30:564,	30:565,	30:566,	30:479,	30:481,	30:483,	30:486,	
30:567,	30:625,	30:626,	30:627,	30:489,	30:491,	30:492,	30:494,	
\DeclareMathVersion	...	28:468,	29:3,	30:496,	30:498,	30:500,	30:502,	
\DeclareOldFontCommand	..	32:125,	32:141	30:504,	30:506,	30:508,	30:510,	
\DeclareOption	.....	1054		30:516,	30:518,	30:520,	30:523,	
\DeclareOption	.....			30:541,	30:544,	30:547,	30:551,	
....	21:1559,	26:30,	26:38,	30:555,	30:558,	30:561,	30:568,	
26:54,	26:57,	26:61,	33:782,	30:571,	30:628,	30:629,	30:630,	
33:784,	33:785,	33:786,	33:788,	30:635,	30:637,	30:639,	30:641,	32:3,
33:790,	33:792,	33:793,	33:833,	32:126,	33:4,	33:11,	33:574,	33:1097,
33:834,	33:835,	33:836,	33:837,	35:186,	35:197,	37:271,	37:452,	
33:839,	33:840,	50:496,	50:1201,	37:457,	37:462,	37:472,	37:476,	
\DeclareOption*	.....	1054		37:480,	37:578,	37:582,	06:274,	38:3,
\DeclareOption*	.....	50:496		38:4,	38:5,	38:6,	38:7,	38:8,
\DeclarePreloadSizes	.....			38:9,	38:10,	38:11,	38:12,	38:13,
.....	24:248,	27:95,	27:96,	38:14,	38:15,	38:16,	38:17,	38:18,
				38:19,	38:20,	38:21,	38:22,	38:23,
				38:24,				

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

38:25, 38:26, 38:27, 38:28, 38:29,	21:253, 21:254, 21:255, 21:256,
38:30, 38:31, 38:32, 38:33, 38:34,	21:257, 21:258, 21:259, 21:299,
38:35, 38:39, 38:41, 38:42, 38:43,	21:302, 33:651, 33:652, 33:901,
38:44, 38:45, 38:46, 38:47, 38:48,	33:902, 33:903, 33:904, 33:905,
38:49, 38:50, 38:51, 38:52, 38:81,	33:906, 33:907, 33:908, 33:909,
38:82, 38:83, 38:84, 38:126, 38:167,	33:910, 33:911, 33:912, 33:913, 1328
38:169, 38:173, 38:218, 38:220,	<code>\DeclareTextCommand</code> 21:3, 21:76, 21:83,
38:222, 38:224, 38:227, 38:228,	21:101, 21:410, 21:413, 21:416,
38:230, 38:237, 38:239, 38:240,	21:430, 21:431, 21:432, 21:435,
38:251, 38:274, 38:276, 38:309,	21:436, 21:443, 21:445, 21:447,
38:322, 38:337, 38:348, 38:411,	21:449, 21:455, 21:457, 21:459,
38:412, 38:413, 38:522, 38:556,	21:466, 21:498, 21:501, 21:505,
38:580, 40:7, 40:24, 40:159, 40:172,	21:508, 21:510, 21:513, 21:515,
40:195, 40:196, 40:212, 40:223,	21:517, 21:533, 21:591, 21:592,
40:302, 40:534, 40:552, 40:560,	21:593, 21:754, 21:781, 21:783,
40:615, 40:616, 40:617, 40:618,	21:786, 21:789, 21:822, 21:829,
40:619, 40:620, 41:139, 41:142,	21:856, 21:859, 21:889, 21:917,
41:154, 42:124, 42:127, 42:130,	21:1077, 21:1104, 33:340, 33:341,
44:7, 44:8, 44:9, 44:10, 44:14,	33:342, 33:343, 33:344, 33:345,
44:247, 45:402, 45:423, 47:16, 47:28,	33:346, 33:347, 33:348, 33:349,
48:520, 48:521, 49:23, 49:28, 49:38,	33:589, 33:596, 33:603, 33:723, 1322
49:49, 49:64, 49:72, 49:126, 49:128,	<code>\DeclareTextCommandDefault</code> . . . 21:75,
49:130, 49:137, 50:1136, 50:1137,	21:204, 21:206, 21:303, 21:306,
50:1138, 50:1144, 50:1145, 50:1801,	21:307, 21:308, 21:310, 21:312,
06:925, 06:926, 06:932, 52:148,	21:316, 21:320, 21:321, 21:323,
52:184, 06:947, 53:454, 54:63, 101	21:324, 21:325, 21:326, 21:346,
<code>\DeclareSizeFunction</code> . . . . . 26:434,	21:375, 33:119, 33:121, 33:124,
26:507, 26:508, 26:519, 26:520,	33:126, 33:128, 33:130, 33:132,
26:524, 26:525, 26:531, 26:532,	33:134, 33:136, 33:138, 33:140,
26:560, 26:574, 26:575, 26:582, 26:583	33:142, 33:144, 33:146, 33:148,
<code>\DeclareSymbolFont</code> . . . . . 27:136,	33:150, 33:152, 33:154, 33:157,
28:527, 30:152, 30:153, 30:154, 30:155	33:158, 33:159, 33:160, 33:161,
<code>\DeclareSymbolFontAlphabet</code> . . . . .	33:162, 33:163, 33:164, 33:165,
. . . . . 28:1246, 30:159, 30:160, 30:161	33:166, 33:167, 33:168, 33:169,
<code>\DeclareTemplateCode</code> . . . . .	33:170, 33:171, 33:172, 33:174,
11:1025, 11:1066, 11:1092, 11:1193, 356	33:176, 33:178, 33:180, 33:182,
<code>\DeclareTemplateCopy</code> . . . . . 11:1193, 357	33:184, 33:186, 33:188, 33:190,
<code>\DeclareTemplateInterface</code> . . 11:1193, 355	33:192, 33:194, 33:196, 33:198,
<code>\DeclareTextAccent</code> . . . . . 21:82,	33:200, 33:202, 33:204, 33:206,
21:399, 21:400, 21:401, 21:402,	33:208, 33:210, 33:212, 33:214,
21:403, 21:404, 21:405, 21:406,	33:216, 33:218, 33:220, 33:222,
21:407, 21:408, 21:409, 21:487,	33:224, 33:226, 33:228, 33:230,
21:488, 21:489, 21:490, 21:491,	33:232, 33:234, 33:236, 33:238,
21:492, 21:493, 21:494, 21:495,	33:240, 33:242, 33:244, 33:246,
21:496, 21:497, 21:765, 21:770,	33:248, 33:250, 33:252, 33:254,
21:771, 21:772, 21:773, 21:774,	33:256, 33:258, 33:260, 33:262,
21:775, 21:776, 21:777, 21:778,	33:264, 33:266, 33:268, 33:270,
21:779, 21:780, 21:862, 21:863,	33:273, 33:275, 33:277, 33:279,
21:864, 21:865, 21:866, 21:867,	33:281, 33:283, 33:285, 33:287,
21:868, 21:869, 21:870, 21:871,	33:289, 33:291, 33:293, 33:295,
21:872, 21:873, 21:874, 21:875, 21:876	33:297, 33:299, 33:301, 33:303,
<code>\DeclareTextAccentDefault</code> . . . . .	33:305, 33:307, 33:309, 33:311,
. . . 21:203, 21:246, 21:247, 21:248,	33:313, 33:315, 33:317, 33:319,
21:249, 21:250, 21:251, 21:252,	33:321, 33:323, 33:325, 33:327,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

33:329, 33:618, 33:626, 33:628, 21:727, 21:728, 21:729, 21:730,  
 33:634, 33:642, 33:967, 33:969, 21:731, 21:732, 21:733, 21:734,  
 33:970, 33:972, 33:974, 33:976, 21:735, 21:737, 21:819, 21:1083, 1329  
 33:978, 33:980, 33:982, 33:984, \DeclareTextFontCommand . . . . . 32:1,  
 33:986, 33:988, 33:990, 33:992, 32:15, 32:16, 32:17, 32:18, 32:19,  
 33:994, 33:996, 33:998, 33:1000, 32:20, 32:21, 32:22, 32:23, 32:24,  
 33:1002, 33:1004, 33:1006, 33:1008, 32:29, 32:30, 32:31, 32:42, 32:140, 1346  
 33:1010, 33:1012, 33:1014, 33:1016, \DeclareTextFoo . . . . . 1313  
 33:1018, 33:1020, 33:1022, 33:1024, \DeclareTextGlyph . . . . . 1320  
 33:1026, 33:1028, 33:1030, 33:1032, \DeclareTextSymbol . . . . . 21:3, 21:419,  
 33:1034, 33:1036, 33:1038, 33:1040, 21:420, 21:421, 21:422, 21:423,  
 33:1042, 33:1044, 33:1046, 33:1048, 21:424, 21:425, 21:426, 21:427,  
 33:1050, 33:1052, 33:1054, 33:1056, 21:428, 21:429, 21:433, 21:434,  
 33:1058, 33:1060, 33:1062, 33:1064, 21:437, 21:438, 21:439, 21:440,  
 33:1066, 33:1068, 33:1070, 33:1072, 21:441, 21:442, 21:549, 21:550,  
 33:1074, 33:1076, 33:1078, 33:1080, 21:551, 21:552, 21:553, 21:554,  
 33:1082, 33:1084, 33:1087, 1328 21:555, 21:556, 21:557, 21:558,  
 \DeclareTextComposite . 21:94, 21:473, 21:559, 21:560, 21:561, 21:562,  
 21:474, 21:610, 21:611, 21:612, 21:563, 21:564, 21:566, 21:567,  
 21:613, 21:614, 21:615, 21:616, 21:568, 21:569, 21:570, 21:571,  
 21:617, 21:618, 21:619, 21:620, 21:572, 21:573, 21:574, 21:575,  
 21:621, 21:622, 21:623, 21:624, 21:576, 21:577, 21:578, 21:579,  
 21:625, 21:626, 21:627, 21:628, 21:580, 21:581, 21:582, 21:583,  
 21:629, 21:630, 21:631, 21:632, 21:584, 21:585, 21:586, 21:587,  
 21:633, 21:634, 21:635, 21:636, 21:588, 21:589, 21:590, 21:594,  
 21:637, 21:638, 21:639, 21:640, 21:595, 21:596, 21:597, 21:598,  
 21:641, 21:642, 21:643, 21:644, 21:599, 21:600, 21:601, 21:602,  
 21:645, 21:646, 21:647, 21:648, 21:603, 21:604, 21:605, 21:606,  
 21:649, 21:650, 21:651, 21:652, 21:607, 21:608, 21:609, 21:741,  
 21:653, 21:654, 21:655, 21:656, 21:742, 21:743, 21:744, 21:745,  
 21:657, 21:658, 21:659, 21:660, 21:746, 21:747, 21:748, 21:749,  
 21:661, 21:662, 21:663, 21:664, 21:750, 21:751, 21:752, 21:753,  
 21:665, 21:666, 21:667, 21:668, 21:763, 21:764, 21:792, 21:793,  
 21:669, 21:670, 21:671, 21:672, 21:794, 21:795, 21:796, 21:797,  
 21:673, 21:674, 21:675, 21:676, 21:798, 21:800, 21:801, 21:802,  
 21:677, 21:678, 21:679, 21:680, 21:803, 21:804, 21:805, 21:806,  
 21:681, 21:682, 21:683, 21:684, 21:807, 21:808, 21:809, 21:810,  
 21:685, 21:686, 21:687, 21:688, 21:811, 21:812, 21:813, 21:814,  
 21:689, 21:690, 21:691, 21:692, 21:815, 21:816, 21:817, 21:818,  
 21:693, 21:694, 21:695, 21:696, 21:877, 21:878, 21:879, 21:880,  
 21:697, 21:698, 21:699, 21:700, 21:881, 21:882, 21:883, 21:884,  
 21:701, 21:702, 21:703, 21:704, 21:885, 21:886, 21:887, 21:888,  
 21:705, 21:706, 21:707, 21:708, 21:900, 21:901, 21:902, 21:903,  
 21:709, 21:710, 21:711, 21:712, 21:904, 21:905, 21:906, 21:907,  
 21:713, 21:714, 21:715, 21:716, 21:908, 21:909, 21:910, 21:911,  
 21:717, 21:718, 21:719, 21:720, 21:912, 21:913, 21:914, 21:915,  
 21:836, 21:837, 21:838, 21:839, 21:916, 21:923, 21:924, 21:925,  
 21:840, 21:841, 21:842, 21:843, 21:926, 21:927, 21:928, 21:929,  
 21:844, 21:845, 21:846, 21:847, 21:930, 21:931, 21:932, 21:933,  
 21:848, 21:849, 21:850, 21:851, 1337 21:934, 21:935, 21:936, 21:937,  
 \DeclareTextCompositeCommand . . . . . 21:938, 21:939, 21:940, 21:941,  
 . . . . . 21:94, 21:452, 21:475, 21:942, 21:943, 21:944, 21:945,  
 21:476, 21:477, 21:478, 21:479, 21:946, 21:947, 21:948, 21:949,  
 21:481, 21:721, 21:722, 21:724, 21:950, 21:951, 21:952, 21:953,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

21:954, 21:955, 21:956, 21:957,	33:947, 33:948, 33:949, 33:950,
21:958, 21:959, 21:960, 21:961,	33:951, 33:952, 33:953, 33:954,
21:962, 21:963, 21:964, 21:965,	33:955, 33:956, 33:957, 33:958,
21:966, 21:967, 21:968, 21:969,	33:959, 33:960, 33:961, 33:962,
21:970, 21:971, 21:972, 21:973,	33:963, 33:964, 33:965, 33:966, 1328
21:974, 21:975, 21:976, 21:977,	\DeclareTitlecaseExclusions 57:571, 1386
21:978, 21:979, 21:980, 21:981,	\DeclareTitlecaseMapping ... 57:571, 1377
21:982, 21:983, 21:984, 21:985,	\DeclareUnicode... 513
21:986, 21:987, 21:988, 21:989,	\DeclareUnicodeAccent ..... 21:1066,
21:990, 21:991, 21:992, 21:993,	21:1261, 21:1262, 21:1263, 21:1264,
21:994, 21:995, 21:996, 21:997,	21:1265, 21:1266, 21:1267, 21:1268,
21:998, 21:999, 21:1000, 21:1001,	21:1269, 21:1270, 21:1271, 21:1272,
21:1002, 21:1103, 33:332, 33:333,	21:1273, 21:1274, 21:1275, 1357
33:334, 33:335, 33:336, 33:337,	\DeclareUnicodeCharacter ... 57:384, 1358
33:338, 33:339, 33:350, 33:351,	\DeclareUnicodeCommand ..... 21:1104, 21:1105,
33:352, 33:353, 33:354, 33:355,	21:1106, 21:1107, 21:1188, 21:1190,
33:356, 33:357, 33:358, 33:359,	21:1192, 21:1239, 21:1276, 1371
33:553, 33:554, 33:555, 33:556,	\DeclareUnicodeComposite ..... 21:1081, 21:1280, 21:1281, 21:1282,
33:557, 33:558, 33:559, 33:560, 1329	21:1283, 21:1284, 21:1285, 21:1286,
\DeclareTextSymbolDefault ..... 21:203, 21:260, 21:261, 21:262,	21:1287, 21:1288, 21:1289, 21:1290,
21:263, 21:264, 21:265, 21:266,	21:1291, 21:1292, 21:1293, 21:1294,
21:267, 21:268, 21:269, 21:270,	21:1295, 21:1296, 21:1297, 21:1298,
21:271, 21:272, 21:273, 21:274,	21:1299, 21:1300, 21:1301, 21:1302,
21:275, 21:276, 21:277, 21:278,	21:1303, 21:1304, 21:1305, 21:1306,
21:279, 21:280, 21:281, 21:282,	21:1307, 21:1308, 21:1309, 21:1310,
21:283, 21:284, 21:285, 21:286,	21:1311, 21:1312, 21:1313, 21:1314,
21:287, 21:288, 21:289, 21:290,	21:1315, 21:1316, 21:1317, 21:1318,
21:291, 21:292, 21:293, 21:294,	21:1319, 21:1320, 21:1321, 21:1322,
21:295, 21:296, 21:297, 21:298,	21:1323, 21:1324, 21:1325, 21:1326,
21:300, 21:301, 21:311, 33:78,	21:1327, 21:1328, 21:1329, 21:1330,
33:80, 33:82, 33:84, 33:85, 33:86,	21:1331, 21:1332, 21:1333, 21:1334,
33:87, 33:88, 33:89, 33:90, 33:91,	21:1335, 21:1336, 21:1337, 21:1338,
33:92, 33:93, 33:94, 33:95, 33:96,	21:1339, 21:1340, 21:1341, 21:1342,
33:97, 33:98, 33:99, 33:100, 33:101,	21:1343, 21:1344, 21:1345, 21:1346,
33:102, 33:103, 33:104, 33:105,	21:1347, 21:1348, 21:1349, 21:1350,
33:106, 33:107, 33:108, 33:109,	21:1351, 21:1352, 21:1353, 21:1354,
33:110, 33:111, 33:112, 33:113,	21:1355, 21:1356, 21:1357, 21:1358,
33:114, 33:115, 33:116, 33:117,	21:1359, 21:1360, 21:1361, 21:1362,
33:118, 33:541, 33:542, 33:543,	21:1363, 21:1364, 21:1365, 21:1366,
33:544, 33:545, 33:546, 33:547,	21:1367, 21:1368, 21:1369, 21:1370,
33:548, 33:561, 33:562, 33:563,	21:1371, 21:1372, 21:1373, 21:1374,
33:564, 33:565, 33:566, 33:567,	21:1375, 21:1376, 21:1377, 21:1378,
33:568, 33:587, 33:588, 33:606,	21:1379, 21:1380, 21:1381, 21:1382,
33:607, 33:608, 33:609, 33:610,	21:1383, 21:1384, 21:1385, 21:1386,
33:611, 33:612, 33:614, 33:914,	21:1387, 21:1388, 21:1389, 21:1390,
33:915, 33:916, 33:917, 33:918,	21:1391, 21:1392, 21:1393, 21:1394,
33:919, 33:920, 33:921, 33:922,	21:1395, 21:1396, 21:1397, 21:1398,
33:923, 33:924, 33:925, 33:926,	21:1399, 21:1400, 21:1401, 21:1402,
33:927, 33:928, 33:929, 33:930,	21:1403, 21:1404, 21:1405, 21:1406,
33:931, 33:932, 33:933, 33:934,	21:1407, 21:1408, 21:1409, 21:1410,
33:935, 33:936, 33:937, 33:938,	21:1411, 21:1412, 21:1413, 21:1414,
33:939, 33:940, 33:941, 33:942,	21:1415, 21:1416, 21:1417, 21:1418,
33:943, 33:944, 33:945, 33:946,	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- 21:1419, 21:1420, 21:1421, 21:1422,  
 21:1423, 21:1424, 21:1425, 21:1426,  
 21:1427, 21:1428, 21:1429, 21:1430,  
 21:1431, 21:1432, 21:1433, 21:1434,  
 21:1435, 21:1436, 21:1437, 21:1438,  
 21:1439, 21:1440, 21:1441, 21:1442,  
 21:1443, 21:1444, 21:1445, 21:1446,  
 21:1447, 21:1448, 21:1449, 21:1450,  
 21:1451, 21:1452, 21:1453, 21:1454,  
 21:1455, 21:1456, 21:1457, 21:1458,  
 21:1459, 21:1460, 21:1461, 21:1462,  
 21:1463, 21:1464, 21:1465, 21:1466,  
 21:1467, 21:1468, 21:1469, 21:1470,  
 21:1471, 21:1472, 21:1473, 21:1474,  
 21:1475, 21:1476, 21:1477, 21:1478,  
 21:1479, 21:1480, 21:1481, 21:1482,  
 21:1483, 21:1484, 21:1485, 21:1486,  
 21:1487, 21:1488, 21:1489, 21:1490,  
 21:1491, 21:1492, 21:1493, 21:1494,  
 21:1495, 21:1496, 21:1497, 21:1498,  
 21:1499, 21:1500, 21:1501, 21:1502,  
 21:1503, 21:1504, 21:1505, 21:1506,  
 21:1507, 21:1508, 21:1509, 21:1510,  
 21:1511, 21:1512, 21:1513, 21:1514,  
 21:1515, 21:1516, 21:1517, 21:1518,  
 21:1519, 21:1520, 21:1521, 21:1522,  
 21:1523, 21:1524, 21:1525, 21:1526, 512
- `\DeclareUnicodeSymbol` .....  
 ..... 21:1103, 21:1108, 21:1109,  
 21:1110, 21:1111, 21:1112, 21:1113,  
 21:1114, 21:1115, 21:1116, 21:1117,  
 21:1118, 21:1119, 21:1120, 21:1121,  
 21:1122, 21:1123, 21:1124, 21:1125,  
 21:1126, 21:1127, 21:1128, 21:1130,  
 21:1131, 21:1132, 21:1133, 21:1134,  
 21:1135, 21:1136, 21:1137, 21:1138,  
 21:1139, 21:1140, 21:1141, 21:1142,  
 21:1143, 21:1144, 21:1146, 21:1147,  
 21:1148, 21:1149, 21:1150, 21:1151,  
 21:1152, 21:1153, 21:1154, 21:1155,  
 21:1156, 21:1157, 21:1158, 21:1159,  
 21:1160, 21:1161, 21:1162, 21:1163,  
 21:1164, 21:1165, 21:1166, 21:1167,  
 21:1168, 21:1169, 21:1170, 21:1171,  
 21:1172, 21:1173, 21:1174, 21:1175,  
 21:1176, 21:1177, 21:1178, 21:1179,  
 21:1180, 21:1181, 21:1182, 21:1183,  
 21:1184, 21:1185, 21:1186, 21:1187,  
 21:1194, 21:1195, 21:1196, 21:1197,  
 21:1198, 21:1199, 21:1200, 21:1201,  
 21:1202, 21:1203, 21:1204, 21:1205,  
 21:1206, 21:1207, 21:1208, 21:1209,  
 21:1210, 21:1211, 21:1212, 21:1213,  
 21:1214, 21:1215, 21:1216, 21:1217,  
 21:1218, 21:1219, 21:1220, 21:1221,  
 21:1222, 21:1223, 21:1224, 21:1225,  
 21:1226, 21:1227, 21:1228, 21:1229,  
 21:1230, 21:1231, 21:1232, 21:1233,  
 21:1234, 21:1235, 21:1237, 21:1238,  
 21:1250, 21:1251, 21:1252, 21:1253,  
 21:1254, 21:1255, 21:1256, 21:1257,  
 21:1258, 21:1259, 21:1260, 1371
- `\DeclareUnknownKeyHandler` .. 51:218, 1372  
`\DeclareUnknownKeysHandler` ..... 1372  
`\DeclareUppercaseExclusions` 57:571, 1386  
`\DeclareUppercaseMapping` ... 57:571, 1377  
`\def` ..... 713  
`default` (tag plug) ..... 55:80  
`\defaultencoding` ..... 1325  
`\defaultshyphenchar` . 06:935, 06:950, 02:253  
`\defaultscriptratio` . 24:721, 24:728, 1318  
`\defaultscriptscriptratio` .....  
 ..... 24:722, 24:728, 1318  
`\defaultskewchar` ..... 02:254  
`\deg` ..... 38:34  
`\delcode` ..... 28:1170  
`\delimiter` 28:1083, 28:1153, 28:1164, 1356  
`\delimiterfactor` ..... 02:257  
`\delimitershortfall` ..... 02:272  
`\Delta` ..... 30:309  
`\delta` ..... 30:282  
`\depth` ..... 40:32, 40:35  
`\det` ..... 38:30  
`\Details` ..... 33:1589, 33:1590  
`\detokenize` ..... 03:96, 03:97,  
 03:182, 14:249, 14:250, 20:273,  
 20:524, 21:1022, 21:1064, 24:190,  
 25:2822, 29:646, 37:207, 06:666,  
 06:684, 06:748, 50:564, 50:598,  
 50:638, 50:910, 50:1277, 50:1281,  
 50:1409, 50:1410, 50:1414, 1374  
`\DH` ..... 21:551, 21:1152, 57:671, 1324  
`\dh` ..... 21:561, 21:1158, 57:671, 1324  
`\Diamond` ..... 29:855  
`\diamond` ..... 30:391  
`\diamondsuit` ..... 30:343  
`\dim` ..... 38:28  
`dim` commands:  
`\dim_eval:n` ..... 11:365, 05:168  
`\dim_new:N` .....  
 . 11:34, 53:199, 53:200, 53:201, 53:202  
`\dim_set:Nn` .....  
 ..... 53:193, 53:194, 53:195, 53:196  
`\dim_set_eq:NN` ..... 48:69, 48:71  
`\dim_use:N` ..... 53:538, 53:539, 53:540  
`\c_max_dim` .....  
 .... 48:69, 48:71, 48:109, 48:113,  
 53:213, 53:239, 53:264, 53:291, 1028

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\l_tmpa_dim</code> .....	356	42:417, 42:422, 42:477, 42:505,
<code>\c_zero_dim</code> .....		42:534, 42:730, 42:786, 45:65,
... 16:102, 53:219, 53:220, 53:221,		45:134, 47:36, 47:65, 47:82, 50:232,
53:227, 53:245, 53:246, 53:247,		50:249, 02:13, 02:14, 50:543, 50:562,
53:270, 53:271, 53:272, 53:299,		50:579, 50:597, 50:602, 50:616,
53:300, 53:301, 53:329, 53:331, 53:332		50:621, 50:657, 50:667, 50:1190,
<code>\dimen</code> .....	1343	50:1227, 50:1309, 50:1362, 50:1442,
<code>\dimendef</code> 04:226, 02:42, 02:43, 02:44, 02:48		50:1531, 50:1816, 07:1614, 07:1830,
<code>\dimenzero</code> .....	04:226	07:2197, 07:2210, 01:58, 01:59, 1338
<code>\dimeval</code> .....	75	<code>\DocInput</code> .....
<code>\dimeval</code> .....	05:162, 05:178, 75	26:8, 30:5, 31:5, 56:4
<code>\dimexpr</code> .....	21:526, 21:542,	<code>\docclearpage</code> .....
21:893, 21:896, 21:1243, 21:1246, 42:13		1350
<code>\directlua</code> .....	04:2, 04:14, 04:29,	<code>\document</code> .....
04:213, 04:231, 04:256, 04:261,		454
04:265, 21:1035, 01:12, 01:15,		<code>document (env.)</code> .....
06:34, 01:20, 01:23, 50:1262, 06:846,		37:8
50:1393, 06:931, 01:28, 02:61, 02:77,		<code>\document</code> .....
57:98, 57:100, 57:108, 57:113,		16:143, 20:9, 37:260, 47:64, 47:81, 1318
57:115, 02:82, 02:142, 02:228, 02:238		<code>\documentclass</code> .....
disable commands:		04:16, 26:2, 30:2,
<code>disable_callback</code> .....	04:975	31:2, 50:674, 50:681, 50:740, 50:743,
<code>\disable_callback</code> .....	44	50:983, 50:1078, 50:1210, 56:2, 207
<code>\DisableGenericHook</code> .....		<code>\DocumentMetadata</code> .....
... 08:2781, 08:2787, 08:2935, 314		17:8, 17:17,
<code>\DisableHook</code> .....	08:2886, 202	17:21, 17:23, 17:66, 50:773, 50:776, 431
<code>\DiscardShipoutBox</code> .....		<code>\documentstyle</code> .....
... 53:82, 53:417, 53:450, 53:527, 1143		50:679, 50:1210
<code>\discretionary</code> .....		<code>\doesglyphexist</code> .....
... 38:251, 06:933, 06:948, 06:958		33:1182,
<code>\displayindent</code> .....	02:278	33:1208, 33:1226, 33:1227, 33:1228,
<code>\displaylines</code> .....	38:203	33:1229, 33:1230, 33:1231, 33:1232,
<code>displaymath (env.)</code> .....	38:389	33:1235, 33:1236, 33:1237, 33:1238,
<code>\displaymath</code> .....	38:391	33:1241, 33:1242, 33:1243, 33:1244,
<code>\displaystyle</code> .. 30:543, 30:546, 30:550,		33:1247, 33:1248, 33:1251, 33:1252,
30:552, 38:62, 38:210, 38:434,		33:1255, 33:1256, 33:1257, 33:1258,
38:437, 38:463, 38:466, 38:521,		33:1259, 33:1260, 33:1261, 33:1262,
38:563, 38:575, 38:603, 38:628, 38:631		33:1265, 33:1266, 33:1269, 33:1270,
<code>\displaywidowpenalty</code> .....	02:197	33:1271, 33:1272, 33:1273, 33:1274,
<code>\displaywidth</code> .....	38:210,	33:1275, 33:1276, 33:1277, 33:1278,
38:433, 38:462, 38:550, 38:606, 02:277		33:1279, 33:1280, 33:1281, 33:1282,
<code>\div</code> .....	30:394	33:1283, 33:1284, 33:1285, 33:1286,
<code>\DJ</code> .....	21:552, 21:1162, 57:671, 1324	33:1287, 33:1288, 33:1289, 33:1290,
<code>\dj</code> .....	21:562, 21:1163, 57:671, 1324	33:1291, 33:1292, 33:1293, 33:1294,
<code>\do</code> .....	01:110, 13:3, 13:7,	33:1295, 33:1296, 33:1297, 33:1298,
13:16, 13:26, 20:66, 20:69, 20:72,		33:1299, 33:1300, 33:1301, 33:1302,
20:135, 20:138, 20:190, 20:193,		33:1303, 33:1304, 33:1305, 33:1306,
20:252, 20:324, 20:386, 20:433,		33:1307, 33:1308, 33:1309, 33:1310,
20:606, 20:623, 20:774, 20:780,		33:1311, 33:1312, 33:1313, 33:1314,
32:90, 06:69, 37:543, 37:564, 37:724,		33:1315, 33:1316, 33:1317, 33:1318,
37:734, 37:740, 37:746, 40:78, 40:97,		33:1319, 33:1320, 33:1321, 33:1322,
41:244, 41:269, 42:104, 42:116,		33:1323, 33:1324, 33:1325, 33:1326,
42:123, 42:203, 42:337, 42:339,		33:1327, 33:1328, 33:1329, 33:1330,
42:362, 42:365, 42:394, 42:396,		33:1331, 33:1332, 33:1333, 33:1334,
		33:1337, 33:1341, 33:1342, 33:1343,
		33:1344, 33:1345, 33:1346, 33:1347,
		33:1348, 33:1349, 33:1350, 33:1351,
		33:1352, 33:1353, 33:1354, 33:1355,
		33:1356, 33:1357, 33:1358, 33:1359,
		33:1360, 33:1361, 33:1362, 33:1363,
		33:1364, 33:1365, 33:1366, 33:1367,
		33:1368, 33:1369, 33:1370, 33:1371, 797

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\dollar</code> .....	1325	<code>\EncodingSpecificCommand</code> .....	1313	
<code>\dospecials</code> .....	01:110, 37:543, 37:564, 37:724, 37:734, 02:13, 50:1309, 50:1442, 50:1531, 07:1615, 07:1831, 07:2198, 07:2211, 01:58, 1343	<code>\end</code> 14:250, 26:9, 30:6, 06:23, 31:6, 37:270, 37:298, 37:312, 37:348, 37:364, 37:378, 37:386, 37:522, 37:523, 38:584, 38:593, 39:112, 44:15, 44:17, 06:811, 50:1324, 50:1328, 50:1335, 50:1457, 50:1461, 50:1467, 06:868, 50:1546, 50:1550, 50:1556, 53:402, 56:5, 07:1453, 07:1580, 07:1595, 07:1762, 01:53, 07:2896, 106	<code>\end\verbvisiblespace</code> .....	37:345
<code>\dot</code> .....	30:536	<code>\endaligned</code> .....	1274	
<code>\doteq</code> .....	30:480	<code>\endarray</code> .....	41:171, 1274	
<code>\dotfill</code> .....	06:973, 06:994, 02:421	<code>\endcenter</code> .....	37:447	
<code>\dots</code> .....	21:340, 21:342, 1329	<code>\endcsname</code> .....	207	
<code>\doublehyphendemerits</code> .....	02:204	<code>\enddisplaymath</code> .....	38:392	
<code>\doublerulesep</code> ....	41:311, 41:338, 41:362	<code>\enddocument</code> .....	37:8, 37:79, 37:80, 37:143, 37:145, 53:352, 1160	
<code>\Downarrow</code> .....	30:597	<code>\endenumerate</code> .....	39:271	
<code>\downarrow</code> .....	30:591	<code>\endeqnarray</code> .....	38:442, 38:471, 38:520	
<code>\downbracefill</code> .....	30:549, 30:568	<code>\endequation</code> .....	38:400, 38:407	
<code>\dump</code> .....	57:749	<code>\endfilecontents</code> .....	50:1214	
<b>E</b>				
<code>\E</code> .....	50:1316, 50:1319, 50:1347, 50:1449, 50:1452, 50:1479, 50:1538, 50:1541, 50:1569	<code>\endflushleft</code> .....	37:497	
<code>\edef</code> .....	627	<code>\endflushright</code> .....	37:499	
<code>\EditInstance</code> .....	11:1193, 360	<code>\endgraf</code> .....	16:140, 16:178, 40:138, 40:144, 02:320, 1328	
<code>\EditTemplateDefaults</code> .....	11:1193, 360	<code>\endgroup</code> .....	1308	
<code>\egroup</code> .....	02:325, 1317	<code>\EndIncludeInRelease</code> .....	02:564, 02:574, 02:579, 08:1975, 08:2079, 08:2084, 08:2089, 08:2179, 08:2186, 08:2210, 08:2226, 08:2233, 08:2238, 08:2260, 08:2280, 08:2310, 08:2328, 08:2333, 08:2343, 08:2347, 08:2350, 08:2377, 08:2392, 08:2403, 08:2421, 08:2433, 08:2445, 08:2455, 08:2485, 08:2504, 08:2567, 08:2571, 08:2653, 08:2656, 03:71, 08:2770, 08:2776, 08:2783, 08:2788, 08:2795, 08:2799, 08:2806, 08:2810, 08:2833, 08:2838, 09:37, 09:48, 09:62, 09:245, 09:312, 09:438, 09:457, 09:509, 09:513, 09:560, 09:587, 09:590, 09:602, 14:157, 14:161, 14:204, 14:210, 16:44, 16:75, 17:48, 17:59, 18:21, 18:31, 18:65, 18:78, 18:86, 18:91, 18:104, 18:110, 18:152, 18:166, 18:178, 18:189, 18:206, 18:218, 18:250, 18:266, 18:283, 18:319, 18:353, 18:375, 18:412, 18:445, 18:481, 18:485, 18:494, 18:498, 18:506, 18:510, 18:520, 18:526, 18:540, 18:547, 04:234, 20:83, 20:140, 04:257, 20:195, 20:221, 20:234, 20:275, 20:296, 20:308,	
<code>\eject</code> .....	02:388			
<code>\ell</code> .....	30:322			
<code>\else</code> .....	1316			
else commands:				
<code>\else:</code> .....	08:2295, 08:2323, 08:2465, 08:2481, 08:2528, 08:2563, 08:2578, 09:364, 16:26, 16:32, 16:64, 48:112, 06:813, 52:241, 07:1340, 07:1838, 07:1839, 07:1840, 07:1841, 08:784, 08:1058, 08:1215, 08:1277, 08:1418, 08:1425, 08:1433, 08:1749			
<code>\em</code> .....	29:633, 29:660, 32:42, 723			
<code>\emergencystretch</code> ..	49:132, 49:138, 1334			
<code>\emforce</code> .....	722			
<code>\emforce</code> .....	29:629, 29:656, 29:665, 723			
<code>\eminnershape</code> ..	29:637, 29:643, 29:660, 723			
<code>\emph</code> .....	32:42, 1353			
<code>\empty</code> .....	02:323			
<code>\emptyset</code> .....	30:329			
<code>\emreset</code> .....	722			
<code>\emreset</code> .....	29:629, 29:632, 29:663, 722			
<code>\emrest</code> .....	29:632			
<code>\ENC-cmd</code> .....	1324			
<code>\encodingdefault</code> ..	04:260, 04:275, 04:283, 21:1014, 21:1560, 21:1597, 21:1598, 28:408, 28:458, 29:741, 29:774, 29:790, 29:806, 29:823, 30:62, 1325			
<code>\EncodingSpecific</code> .....	1313			
<code>\EncodingSpecificAccent</code> .....	1313			
<code>\EncodingSpecificAccentedLetter</code> ..	1313			

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=ltlooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

20:371, 20:375, 04:280, 04:284,  
 20:454, 20:492, 20:515, 20:550,  
 20:571, 20:590, 20:597, 20:616,  
 20:633, 20:646, 20:650, 20:668,  
 20:679, 20:689, 20:728, 20:755,  
 21:121, 21:141, 21:186, 21:193,  
 21:350, 21:372, 21:387, 21:395,  
 22:30, 22:35, 22:58, 22:76, 22:87,  
 22:92, 22:120, 22:125, 22:142,  
 22:156, 22:172, 22:178, 22:193,  
 22:204, 22:218, 22:225, 22:267,  
 22:273, 22:293, 22:296, 23:10, 23:14,  
 23:25, 23:30, 24:53, 24:74, 24:227,  
 24:246, 24:294, 24:311, 24:357,  
 24:367, 24:377, 24:438, 24:447,  
 24:527, 24:532, 24:567, 24:572,  
 24:589, 24:607, 24:646, 24:679,  
 24:797, 24:809, 25:1431, 25:2772,  
 25:2778, 25:2791, 25:2803, 25:2810,  
 25:2893, 25:2908, 25:2930, 25:2942,  
 25:3047, 25:3128, 25:3131, 25:3142,  
 25:3149, 25:3156, 25:3229, 25:3247,  
 25:3254, 25:3258, 25:3261, 26:158,  
 26:161, 26:177, 26:566, 26:572,  
 27:21, 27:143, 28:78, 28:106, 28:180,  
 05:13, 28:210, 28:240, 28:272, 05:22,  
 28:322, 28:365, 05:31, 28:417,  
 28:464, 28:482, 28:488, 28:493,  
 28:576, 28:583, 28:628, 28:635,  
 28:909, 28:951, 28:964, 28:971,  
 28:1159, 28:1167, 05:114, 05:135,  
 29:68, 29:101, 29:123, 29:143,  
 29:156, 05:151, 29:232, 29:285,  
 29:293, 05:160, 29:320, 29:327,  
 29:379, 29:426, 29:455, 29:466,  
 05:172, 29:513, 29:547, 29:573,  
 05:180, 29:611, 29:622, 29:659,  
 29:671, 29:678, 29:712, 29:718,  
 05:195, 29:769, 29:785, 29:800,  
 05:201, 29:817, 29:832, 29:841,  
 29:846, 05:209, 30:92, 30:102,  
 05:216, 30:120, 30:129, 05:224,  
 05:229, 06:12, 06:18, 30:644, 30:651,  
 32:33, 32:40, 06:60, 06:64, 06:82,  
 06:91, 06:148, 06:159, 35:28, 35:45,  
 35:61, 35:75, 35:82, 35:110, 35:115,  
 35:145, 35:154, 35:166, 35:176,  
 35:188, 35:199, 35:210, 37:77,  
 37:141, 37:180, 37:188, 37:194,  
 37:227, 37:240, 37:268, 37:279,  
 37:310, 37:335, 37:343, 37:361,  
 37:376, 37:384, 37:389, 37:403,  
 37:412, 37:422, 37:429, 37:439,  
 37:444, 37:468, 37:484, 37:493,  
 37:512, 37:518, 06:265, 37:548,  
 37:569, 06:270, 37:591, 37:601,  
 37:618, 37:630, 37:634, 37:642,  
 37:646, 37:667, 37:680, 37:695,  
 37:707, 37:729, 37:737, 38:86, 38:95,  
 38:117, 38:124, 38:143, 38:148,  
 38:156, 38:160, 38:175, 38:183,  
 06:306, 38:232, 38:249, 38:279,  
 38:287, 38:296, 38:302, 38:335,  
 38:360, 38:387, 06:327, 38:402,  
 38:408, 38:449, 38:477, 38:500,  
 38:509, 38:541, 38:546, 38:566,  
 38:578, 38:587, 38:596, 39:134,  
 39:139, 39:161, 39:169, 40:13,  
 40:22, 40:57, 40:65, 40:90, 40:107,  
 01:290, 40:121, 40:132, 40:141,  
 40:146, 40:152, 40:163, 40:170,  
 40:227, 40:234, 40:260, 40:271,  
 40:307, 40:315, 40:354, 06:416,  
 40:375, 40:399, 40:417, 40:494,  
 40:510, 40:527, 40:536, 40:541,  
 40:564, 40:571, 40:605, 40:612,  
 06:444, 41:64, 41:69, 41:156, 41:164,  
 41:226, 41:231, 06:472, 06:477,  
 01:300, 42:15, 42:19, 42:38, 42:47,  
 42:68, 06:496, 42:76, 42:88, 42:96,  
 42:111, 42:121, 42:150, 42:155,  
 42:171, 42:182, 06:510, 42:249,  
 42:263, 42:368, 42:425, 42:462,  
 42:468, 42:499, 42:529, 42:554,  
 42:570, 42:581, 42:594, 42:602,  
 42:623, 42:640, 42:650, 42:654,  
 42:744, 06:551, 42:799, 42:818,  
 42:835, 06:561, 43:33, 43:39, 43:56,  
 43:63, 44:19, 44:29, 44:167, 44:173,  
 44:178, 44:195, 44:207, 44:217,  
 44:223, 44:249, 44:271, 06:593,  
 45:104, 45:172, 06:602, 45:231,  
 45:246, 45:293, 45:306, 45:351,  
 45:368, 45:411, 45:417, 45:426,  
 45:430, 06:629, 45:439, 45:445,  
 45:449, 45:481, 06:635, 45:498,  
 45:516, 45:558, 45:564, 47:24, 47:32,  
 47:76, 06:649, 47:92, 06:654, 01:25,  
 49:34, 49:60, 49:81, 49:104, 49:115,  
 49:124, 50:21, 50:26, 50:49, 50:61,  
 50:84, 50:93, 50:99, 50:111, 50:142,  
 50:149, 50:174, 50:181, 50:199,  
 50:210, 50:244, 50:261, 50:272,  
 50:281, 06:755, 50:312, 50:342,  
 50:359, 50:371, 50:392, 50:405,  
 50:418, 50:428, 06:770, 50:464,  
 50:480, 50:489, 50:523, 50:533,  
 50:573, 50:589, 50:611, 50:626,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpara.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

50:640, 50:647, 50:662, 50:671,	08:1562, 08:1651, 08:1734, 02:559, 26
50:705, 50:712, 50:729, 50:736,	<code>\EndIncludeRelease</code> ..... 03:78
50:797, 50:804, 50:842, 50:869,	<code>\endinput</code> ..... 1318
50:897, 06:821, 50:1053, 06:825,	<code>\enditemize</code> ..... 39:282
50:1110, 50:1140, 50:1147, 50:1165,	<code>\endline</code> ..... 38:188, 02:320
50:1175, 50:1350, 06:857, 06:866,	<code>\endlinechar</code> ..... 20:703,
50:1481, 50:1571, 06:916, 06:923,	20:737, 01:188, 06:37, 06:39, 06:44,
52:14, 52:23, 52:88, 52:140, 52:179,	50:433, 50:434, 50:435, 57:329,
52:191, 52:200, 06:945, 52:245,	02:255, 01:76, 01:77, 01:78, 1378
52:256, 52:263, 06:956, 52:298,	<code>\endlist</code> ..... 39:98, 39:271, 39:282
06:959, 52:321, 52:342, 52:356,	<code>\endlrbox</code> ..... 40:194
52:361, 52:384, 52:404, 52:429,	<code>\endmath</code> ..... 38:390
52:474, 52:494, 52:501, 52:531,	<code>\endminipage</code> ..... 40:460
52:536, 06:987, 06:1008, 53:435,	<code>\EndModuleRelease</code> ..... 08:2957,
53:472, 53:487, 53:493, 53:510,	03:111, 03:112, 03:152, 09:626,
53:514, 54:157, 54:183, 54:201,	10:224, 11:1252, 16:183, 17:68,
54:370, 54:375, 54:423, 54:469,	33:773, 36:281, 48:531, 55:430, 07:3325
54:733, 54:817, 54:945, 54:1004,	<code>\endpicture</code> ..... 42:49
54:1062, 54:1161, 54:1180, 54:1243,	<code>\endscname</code> ..... 1304
54:1261, 54:1303, 54:1324, 54:1567,	<code>\endsloppypar</code> ..... 49:136
54:1711, 54:1880, 54:1963, 54:2043,	<code>\endsmallmatrix</code> ..... 1275
07:241, 54:2137, 54:2259, 07:264,	<code>\endtabbing</code> ..... 41:84
54:2386, 54:2496, 54:2504, 54:2538,	<code>\endtabular</code> ..... 41:171
54:2567, 54:2605, 54:2609, 54:2773,	<code>\endtabular*</code> ..... 41:171
54:2822, 54:2852, 54:2870, 54:2901,	<code>\endtrivlist</code> .....
54:2942, 54:2986, 57:15, 57:19,	... 37:447, 37:497, 37:499, 37:572,
57:29, 57:33, 57:51, 57:69, 57:79,	38:608, 39:100, 39:101, 41:85, 43:66
57:86, 57:94, 57:141, 57:146, 57:198,	<code>\endverbatim</code> ..... 37:571, 37:589
57:222, 57:292, 57:297, 57:338,	<code>\enlargethispage</code> ..... 54:2431, 1027
57:344, 57:440, 57:487, 01:34,	<code>\enlargethispage*</code> ..... 54:2431
57:678, 57:682, 07:1179, 07:1182,	<code>\enskip</code> ..... 18:549
07:1197, 07:1210, 07:1213, 07:1343,	<code>\enspace</code> ..... 18:537, 18:545
07:1346, 07:1375, 07:1378, 07:1387,	<code>\ensuremath</code> ..... 22:269, 38:522,
07:1395, 07:1398, 07:1565, 07:1569,	45:409, 45:416, 45:437, 45:444, 1341
02:234, 02:242, 07:2205, 07:2216,	<code>enumerate (env.)</code> ..... 39:262
07:2248, 07:2264, 07:2275, 07:3205,	<code>\enumerate</code> ..... 39:262
07:3235, 07:3305, 07:3312, 02:346,	environments:
02:363, 08:85, 08:101, 08:129,	array ..... 41:168
08:145, 08:157, 08:169, 08:185,	center ..... 37:446
08:198, 08:218, 08:228, 08:248,	displaymath ..... 38:389
08:263, 08:281, 08:287, 08:307,	document ..... 37:8
08:325, 08:329, 08:595, 08:646,	enumerate ..... 39:262
08:663, 08:667, 08:690, 08:711,	eqnarray ..... 38:415, 38:609
08:745, 02:453, 08:803, 08:833,	eqnarray* ..... 38:518
08:865, 08:892, 08:895, 08:915,	equation ..... 38:393, 38:597
08:918, 08:931, 08:949, 08:954,	filecontents ..... 50:1214, 1051
08:957, 08:966, 08:971, 08:974,	flushleft ..... 37:496
08:1011, 08:1048, 02:487, 08:1098,	flushright ..... 37:498
08:1105, 08:1121, 08:1128, 08:1148,	itemize ..... 39:273
08:1152, 02:495, 08:1204, 08:1208,	list ..... 39:34
08:1224, 08:1228, 08:1256, 08:1259,	lrbox ..... 889
08:1282, 08:1286, 08:1303, 08:1308,	math ..... 38:389
08:1315, 08:1319, 08:1355, 08:1379,	minipage ..... 890
02:519, 08:1462, 08:1489, 08:1523,	picture ..... 42:21

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpara.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

sloppypar .....	49:135	\everymath .	24:418, 24:420, 24:436, 24:445
tabbing .....	41:71	\everypar .....	411
tabular .....	41:174	\everypar .....	16:35,
thebibliography .....	1009		16:41, 16:72, 16:77, 16:120, 16:130,
trivlist .....	39:89		16:143, 16:181, 20:43, 20:113,
verbatim .....	37:571		20:171, 24:742, 24:756, 24:803,
verbatim* .....	37:586		37:243, 37:545, 37:567, 39:130,
\epsilon .....	30:283		39:131, 39:133, 39:137, 39:138,
eqnarray (env.) .....	38:415, 38:609		39:211, 39:228, 40:389, 40:410,
\eqnarray .....			41:81, 44:48, 44:96, 44:107, 44:127,
	38:423, 38:424, 38:451, 38:453, 38:519		44:136, 45:187, 54:144, 54:171,
eqnarray* (env.) .....	38:518		54:197, 54:1502, 54:1651, 54:1812, 1320
\eqno .....	38:400, 38:407, 38:532, 1328	\EveryShipout .....	1146
equation (env.) .....	38:393, 38:597	\ExecuteOptions	26:58, 26:71, 33:841, 50:650
\equation ..	38:397, 38:398, 38:404, 38:406	\exhyphenpenalty .....	02:192, 02:382
\equiv .....	30:459	\exists .....	30:335
\errhelp .....	03:31, 14:39,	\exp .....	38:31
	14:66, 01:201, 56:12, 57:307, 57:736	exp commands:	
\errmessage .....		\exp:w ...	07:2670, 08:774, 08:828, 253
	03:32, 10:77, 04:63, 14:47, 14:72,	\exp_after:wN .....	
	01:7, 24:618, 24:653, 01:206, 26:442,		08:1867, 08:1900, 08:1985,
	26:542, 27:65, 05:83, 05:98, 56:16,		08:2129, 08:2274, 08:2458, 08:2461,
	57:63, 57:309, 02:108, 01:42, 02:174		08:2525, 08:2987, 09:30, 09:32,
\ERROR .....	07:1881, 07:1891, 07:1900,		09:187, 09:262, 09:316, 09:317,
	07:2300, 07:2313, 07:2333, 07:2352,		09:370, 09:489, 11:286, 11:771,
	07:2428, 07:2455, 08:1735, 08:1736, 176		11:904, 11:911, 16:41, 16:72, 28:335,
\errorcontextlines .....	14:212,		28:338, 51:46, 52:73, 52:236, 52:237,
	02:264, 02:443, 02:462, 02:478,		07:326, 07:342, 07:396, 07:402,
	02:493, 02:507, 02:530, 02:547, 1306		07:416, 07:1171, 07:1191, 07:1195,
\ERRORmissingcells .....	55:328		07:1206, 07:1208, 07:1257, 07:1306,
\ERRORnewtaggingsocket .....	55:18		07:1336, 07:1367, 07:1374, 07:1450,
\errorstopmode .....	57:748, 02:429, 1337		07:1591, 07:1850, 07:1874, 07:1890,
\ERRORusetaggingsocket .....	55:40, 55:50		07:1908, 07:1914, 07:1918, 07:1949,
\escapchar .....	468		07:1983, 07:1990, 07:2003, 07:2009,
\escapechar ....	04:212, 20:473, 24:464,		07:2015, 07:2021, 07:2027, 07:2033,
	24:688, 26:230, 28:59, 28:87, 28:159,		07:2039, 07:2045, 07:2076, 07:2220,
	28:190, 28:220, 28:251, 28:392,		07:2673, 07:2674, 07:2720, 07:2721,
	28:442, 06:166, 06:210, 06:214,		07:2722, 07:2723, 07:2724, 07:2725,
	06:222, 06:379, 06:380, 06:404,		07:2726, 07:2757, 08:56, 08:61,
	06:541, 06:664, 06:682, 52:280,		08:380, 08:381, 08:426, 08:562,
	52:303, 52:326, 52:347, 02:252, 103		08:773, 08:827, 08:1057, 08:1059,
\eta .....	30:285		08:1200, 08:1365, 08:1538, 08:1748, 253
\etatcatcode .....	04:1026	\exp_args:Nc .....	
\eTeXversion .....	01:41		08:2215, 09:46, 09:59, 09:91,
\evensidemargin .....			09:149, 48:22, 07:267, 07:1102,
	54:49, 54:897, 54:967, 54:1026		07:1113, 07:1413, 07:1454, 07:1480,
\everycr .....	38:205, 38:208,		07:1584, 07:2826, 08:1221, 08:1234
	38:433, 38:462, 38:625, 02:409, 1309	\exp_args:Ncc .....	07:142, 07:184
\everydisplay	24:419, 24:420, 24:431, 24:443	\exp_args:NcV .....	08:586
\everyeof .....	57:329	\exp_args:Ne .....	
\everyjob .....	03:37,		08:2363, 08:2364, 09:523, 10:139,
	04:216, 04:262, 04:263, 28:414,		11:876, 51:112, 51:143, 51:192,
	28:462, 53:29, 53:30, 57:112, 57:331,		52:46, 52:97, 07:2746, 08:731, 08:733
	57:416, 57:706, 57:707, 57:709, 36	\exp_args:Nee .....	52:129

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

\exp_args:Nf . . . . .	09:178,	11:468, 11:469, 11:484, 11:486,
09:253, 52:32, 52:34, 52:394, 07:421,		11:502, 11:632, 11:641, 11:642,
07:2432, 07:2459, 07:2520, 07:2748		11:698, 11:700, 11:803, 11:811,
\exp_args:NNc . . . . .	09:163, 09:168	11:851, 11:866, 11:891, 11:898,
\exp_args:NNe . . . . .	07:1383, 08:1640	16:39, 16:40, 16:70, 16:71, 16:79,
\exp_args:Nne . . . . .	08:1877	16:80, 36:72, 48:115, 48:118, 48:120,
\exp_args:NNNo 07:402, 07:1753, 07:2118		48:125, 48:128, 51:224, 51:225,
\exp_args:Nnnv . . . . .	08:257	51:226, 53:31, 53:95, 53:125, 07:124,
\exp_args:NNo . . . . .	08:2988, 09:186,	07:139, 07:140, 07:168, 07:169,
09:261, 08:1081, 08:1138, 08:1729		07:201, 07:203, 07:204, 07:210,
\exp_args:NNV . . . . .		07:212, 07:271, 07:283, 07:300,
. . . . .	09:205, 09:280, 08:1613, 08:1700	07:301, 07:302, 07:304, 07:372,
\exp_args:NNx 07:1479, 08:1519, 08:1557		57:604, 07:944, 07:954, 07:1035,
\exp_args:No . . . . .		07:1048, 07:1072, 07:1090, 07:1097,
08:2088, 08:2147, 08:2977, 08:2988,		07:1135, 07:1143, 07:1144, 07:1176,
09:186, 09:205, 09:261, 09:280,		07:1222, 07:1223, 07:1230, 07:1231,
36:41, 36:46, 07:94, 07:323, 07:413,		07:1232, 07:1236, 07:1239, 07:1240,
07:432, 07:441, 07:530, 07:935,		07:1242, 07:1261, 07:1264, 07:1265,
07:1342, 07:2305, 07:2316, 07:2357,		07:1266, 07:1274, 07:1321, 07:1340,
07:2438, 07:2465, 07:2688, 07:2714,		07:1354, 07:1361, 07:1362, 07:1463,
07:2823, 08:1081, 08:1138, 08:1199		07:1464, 07:1636, 07:1643, 07:1659,
\exp_args:Nof . . . . .	07:2308	07:1663, 07:1665, 07:1695, 07:1708,
\exp_args:Noo . . . . .	07:1315	07:1712, 07:1713, 07:1717, 07:1718,
\exp_args:NV . . . . .	09:206,	07:1722, 07:1723, 07:1727, 07:1728,
09:281, 51:224, 52:53, 07:260,		07:1788, 07:1794, 07:1795, 07:1797,
07:365, 07:1546, 07:1759, 07:1762		07:1798, 07:1800, 07:1801, 07:2050,
\exp_args:Nv . . . . .		07:2051, 07:2159, 07:2161, 07:2162,
. . . . .	08:2017, 08:2025, 08:2127, 08:1266	07:2244, 07:2245, 07:2256, 07:2259,
\exp_args:Nx 36:10, 53:29, 07:2687,		07:2272, 07:2749, 07:2752, 07:2753,
07:2690, 07:2713, 08:432, 08:474, 08:546		07:2754, 07:2755, 07:2757, 08:391,
\exp_args_generate:n . . . . .	57:597	08:562, 08:563, 08:564, 08:568,
\exp_end: . . . . .	07:2673, 08:774, 08:828	08:569, 08:1168, 08:1172, 08:1191,
\exp_last_unbraced:Ne . . . . .		08:1194, 08:1195, 08:1197, 08:1241,
. . . . .	08:2979, 07:2759,	08:1503, 08:1505, 08:1641, 08:1643, 324
08:1083, 08:1116, 08:1140, 08:1233		\exp_not:n . . . . .
\exp_last_unbraced:Nf . . . . .		08:2977, 09:188,
. . . . .	08:1924, 09:127, 08:1246	09:201, 09:204, 09:206, 09:241,
\exp_last_unbraced:NNf . . . . .	08:1174	09:263, 09:276, 09:279, 09:281,
\exp_last_unbraced:NNNo . . . . .		09:309, 09:373, 09:404, 09:406,
. . . . .	08:2082, 09:133, 09:492, 08:383	09:407, 09:409, 09:410, 11:283,
\exp_last_unbraced:NnNo . . . . .	07:2532	11:471, 11:596, 11:699, 11:804,
\exp_last_unbraced:NNo . . . . .	09:381	11:805, 11:812, 11:850, 11:852,
\exp_last_unbraced:Nno . . . . .	26:345	11:853, 11:866, 11:869, 11:870,
\exp_not:N . . . . .	09:125, 09:127, 09:128,	11:891, 11:892, 11:898, 11:899,
09:129, 09:201, 09:216, 09:223,		36:239, 48:186, 48:193, 48:265,
09:224, 09:231, 09:236, 09:276,		48:266, 48:267, 48:297, 48:374,
09:291, 09:298, 09:299, 09:303,		51:208, 52:211, 52:225, 53:30,
09:307, 09:324, 09:369, 09:375,		07:163, 07:167, 07:171, 07:174,
09:393, 09:403, 09:477, 09:478,		07:178, 07:195, 07:202, 07:214,
09:498, 09:503, 09:526, 09:553,		07:284, 07:303, 07:372, 07:375,
09:554, 09:581, 09:582, 11:278,		07:376, 07:630, 07:772, 07:891,
11:279, 11:280, 11:281, 11:291,		07:902, 07:904, 07:905, 07:984,
11:297, 11:300, 11:302, 11:303,		07:1036, 07:1049, 07:1060, 07:1072,
11:307, 11:309, 11:312, 11:317,		07:1089, 07:1175, 07:1177, 07:1230,
		07:1243, 07:1275, 07:1310, 07:1575,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- 07:1577, 07:1590, 07:1629, 07:1630,  
07:1694, 07:1736, 07:1750, 07:1751,  
07:1758, 07:1775, 07:1859, 07:1860,  
07:1903, 07:1963, 07:2160, 07:2323,  
07:2324, 07:2364, 07:2365, 07:2547,  
07:2556, 07:2573, 07:2587, 07:2599,  
07:2749, 08:114, 08:241, 08:549,  
08:552, 08:1065, 08:1089, 08:1188,  
08:1192, 08:1198, 08:1199, 08:1647, *324*  
  \exp\_stop\_f: ..... 07:1502,  
  07:2310, 08:1267, 08:1415, 08:1423  
expandable commands:  
  \expandable\_grab\_{type}:w ..... *148*  
\expandableinput .. *05:217*, 05:226, 05:228  
\expandafter ..... *1309*  
expandafter commands:  
  \expandafter: ..... *32:88*, 41:269  
\ExpandArgs ..... *76*  
\ExpandArgs ..... *05:181*,  
  05:197, 05:200, 06:626, 06:627, 57:601  
\expanded ..... 50:910, 57:111, *243*  
\ExplLoaderFileDate ..... 05:205, 05:213  
\ExplSyntaxOff ..... 08:2994,  
  09:398, 09:627, 10:225, 11:1253,  
  16:184, 17:47, 17:69, 20:548, 20:768,  
  20:818, 24:417, 26:358, 28:320,  
  28:363, 05:150, 05:170, 05:193,  
  05:222, 36:282, 48:532, 49:32, 49:59,  
  49:113, 50:515, 51:289, 52:12, 52:86,  
  52:138, 52:243, 52:254, 52:402,  
  52:427, 52:472, 52:529, 52:584,  
  53:433, 53:485, 53:492, 53:501,  
  53:541, 55:178, 55:264, 55:280,  
  55:420, 57:570, 57:669, 07:3326, *1057*  
\ExplSyntaxOn .....  
  .... 09:3, 09:399, 10:2, 11:6, 16:3,  
  17:2, 17:27, 20:537, 20:762, 20:815,  
  24:412, 26:343, 28:278, 28:326,  
  05:139, 05:165, 05:184, 05:220, 36:2,  
  48:3, 49:22, 49:37, 49:110, 50:513,  
  51:3, 52:7, 52:29, 52:92, 52:207,  
  52:251, 52:391, 52:410, 52:435,  
  52:508, 52:577, 53:5, 07:8, 53:478,  
  53:490, 53:499, 53:536, 55:2, 55:261,  
  55:266, 55:282, 57:560, 57:571, 08:3, *76*  
\extracolsep ..... *41:167*  
\extrafloats ..... *02:100*, *02:112*, 02:160
- F**
- \fam ..... 04:22, 04:26, 04:38, 24:16, 02:250  
\family ..... *1305*  
\familydefault ..... 21:1598, 28:409,  
  28:459, 29:523, 29:742, 29:775,  
  29:791, 29:807, 29:824, 30:131, *712*
- \fbox ..... *889*  
\fbox ..... *40:212*, 40:225, 40:232, *1322*  
\fbboxrule *40:210*, 40:257, 40:269, 40:274,  
  40:280, 40:282, 40:289, 40:290, 57:151  
\fbboxsep *40:210*, 40:216, 40:249, 40:256,  
  40:268, 40:275, 40:285, 40:287, 57:150  
\fi ..... *1310*  
fi commands:  
  \fi: .....  
  08:2130, 08:2250, 08:2258, 08:2275,  
  08:2297, 08:2325, 08:2462, 08:2467,  
  08:2483, 08:2530, 08:2565, 08:2580,  
  09:359, 09:361, 09:362, 09:366,  
  09:371, 09:378, 16:26, 16:33, 16:65,  
  16:103, 48:130, 52:241, 07:902,  
  07:905, 07:983, 07:1340, 07:1504,  
  07:1842, 07:2670, 07:2674, 08:786,  
  08:1060, 08:1217, 08:1240, 08:1280,  
  08:1419, 08:1427, 08:1433, 08:1751, *328*  
\filbreak ..... *02:386*  
file commands:  
  \g\_file\_curr\_name\_str ..... 08:2824  
  \file\_full\_name:n . 20:544, 52:35, *1124*  
  \file\_input\_raw:n ..... 05:221, *1385*  
  \file\_md5five\_hash:n ..... 20:816  
  \file\_parse\_full\_name\_apply:nN ..  
  .... 52:32, 52:47, 52:90, 52:93, 52:95  
  \l\_file\_search\_path\_seq ..... *1124*  
  \file\_size:n ..... 20:817  
file internal commands:  
  \\_\_file\_parse\_full\_name\_area:nw .  
  ..... 52:102, 52:105, 52:109  
  \\_\_file\_parse\_full\_name\_auxi:nN .  
  ..... 52:97, 52:100  
  \\_\_file\_parse\_full\_name\_base:nw .  
  ..... 52:108, 52:112, 52:124  
  \\_\_file\_parse\_full\_name\_tidy:nnnN  
  ..... 52:119, 52:120, 52:122, 52:127  
file/.../after ..... *1115*  
file/.../before ..... *1115*  
file/after ..... *1115*  
file/before ..... *1115*  
filecontents (env.) ..... *50:1214*, *1051*  
\filecontents ..... *50:1214*  
filehook internal commands:  
  \\_\_filehook\_clear\_replacement\_-  
  flag: ..... 52:417, 52:420, 52:520  
  \\_\_filehook\_drop\_extension:N ..  
  ..... 52:44, 52:49, 52:522  
  \\_\_filehook\_drop\_extension\_-  
  aux:nnn ..... 52:54, 52:57  
  \\_\_filehook\_file\_name\_compose:nnn  
  52:218, *52:406*, 52:414, 52:415, 52:425

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\__filehook_file_parse_full_-</code>	<code>\finalstrut</code> . . . . .	1331
name:nN 52:28, <a href="#">52:30</a> , 52:30, 52:53,	<code>\FirstMark</code> . . . . .	<a href="#">48:402</a> , <a href="#">48:522</a> , <a href="#">1016</a>
52:238, 52:394, 52:412, 52:414, <a href="#">1121</a>	<code>\firstmark</code> . . . . .	
<code>\__filehook_file_pop:</code> . . . . .		<a href="#">49:120</a> , <a href="#">54:1001</a> , <a href="#">54:1060</a> , <a href="#">54:2920</a> , <a href="#">1014</a>
. . . . . <a href="#">52:59</a> , 52:70, 52:526	flag internal commands:	
<code>\__filehook_file_pop_assign:nnnn</code>	<code>\flag__filehook_file_replaced</code>	<a href="#">1132</a>
. . . . . <a href="#">52:59</a> , 52:73, 52:79, 52:528	flag commands:	
<code>\__filehook_file_push:</code> . . . . .	<code>\flag_clear:n</code> . . . . .	<a href="#">52:421</a>
. . . . . <a href="#">52:59</a> , 52:62, 52:524	<code>\flag_if_raised:nTF</code> . . . . .	
<code>\__filehook_file_replaced</code> . . . . <a href="#">52:417</a>	. . . . . <a href="#">36:109</a> , <a href="#">36:201</a> , <a href="#">52:419</a> , <a href="#">52:440</a>	
<code>\__filehook_file_subst_begin:nnn</code>	<code>\flag_new:n</code> . . . . .	<a href="#">36:88</a> , <a href="#">52:417</a>
. . . . . <a href="#">52:412</a> , <a href="#">52:422</a> , 52:422, <a href="#">1131</a>	<code>\flag_raise:n</code> . . . . .	<a href="#">36:110</a> , <a href="#">52:441</a>
<code>\__filehook_file_subst_cycle_-</code>	<code>\flat</code> . . . . .	<a href="#">30:339</a>
error:NN . . . . . <a href="#">52:457</a> ,	<code>float/begin</code> (tag socket) . . . . .	<a href="#">55:221</a>
<a href="#">52:462</a> , <a href="#">52:462</a> , <a href="#">52:467</a> , 52:469, <a href="#">1133</a>	<code>float/end</code> (tag socket) . . . . .	<a href="#">55:221</a>
<code>\__filehook_file_subst_loop:NN</code> . .	<code>float/hmode/begin</code> (tag socket) . . .	<a href="#">55:219</a>
. . . . . <a href="#">52:431</a> , <a href="#">52:444</a> , <a href="#">52:452</a> , <a href="#">52:461</a> , <a href="#">1132</a>	<code>float/hmode/end</code> (tag socket) . . . .	<a href="#">55:219</a>
<code>\__filehook_file_subst_tortoise_-</code>	<code>\floatingpenalty</code> . . . . .	
hare:nn . . . . . <a href="#">52:424</a> ,	. . . . . <a href="#">45:469</a> , <a href="#">45:488</a> , <a href="#">45:506</a> , <a href="#">02:202</a>	
<a href="#">52:431</a> , <a href="#">52:434</a> , <a href="#">52:436</a> , 52:459, <a href="#">1132</a>	<code>\floatpagefraction</code> . . . . .	<a href="#">45:278</a> , <a href="#">54:2998</a>
<code>\__filehook_full_name:nn</code> . . . . .	<code>floats:footnotes</code> (plug) . . . . .	<a href="#">54:697</a>
. . . . . <a href="#">52:30</a> , 52:34, 52:38	<code>floats:space:footnotes</code> (plug) . . .	<a href="#">54:681</a>
<code>\__filehook_if_file_replaced:TF</code> .	<code>\floatsep</code> . . . . . <a href="#">54:1076</a> , <a href="#">54:1094</a> , <a href="#">54:1101</a> ,	
. . . . . <a href="#">52:417</a> , 52:418, 52:518, <a href="#">1132</a>	<a href="#">54:2729</a> , <a href="#">54:2779</a> , <a href="#">54:2829</a> , <a href="#">54:3003</a>	
<code>\__filehook_if_no_extension:nTF</code> .	<code>\flushbottom</code> . . . . .	<a href="#">49:128</a> , <a href="#">1202</a>
. . . . . <a href="#">52:44</a> , 52:44, 52:510	<code>flushleft</code> (env.) . . . . .	<a href="#">37:496</a>
<code>\g__filehook_input_file_seq</code> . . . .	<code>\flushleft</code> . . . . .	<a href="#">37:496</a>
. . . . . <a href="#">52:59</a> , <a href="#">1367</a>	<code>flushright</code> (env.) . . . . .	<a href="#">37:498</a>
<code>\l__filehook_internal_tl</code> . . . . . <a href="#">52:59</a>	<code>\flushright</code> . . . . .	<a href="#">37:498</a>
<code>\__filehook_log_file_record:n</code> . . .	<code>\fmtname</code> <a href="#">03:1</a> , <a href="#">03:41</a> , <a href="#">03:43</a> , <a href="#">03:46</a> , <a href="#">03:48</a> ,	
. . . . . <a href="#">52:547</a> , 52:547, 52:561, 52:563	<a href="#">03:51</a> , <a href="#">03:60</a> , <a href="#">50:749</a> , <a href="#">50:753</a> , <a href="#">1310</a>	
<code>\g__filehook_nesting_level_int</code> . .	<code>\fmtversion</code> . . . . .	
. . . . . <a href="#">52:544</a> , 52:549, 52:552, 52:553, 52:559	. . . . . <a href="#">03:1</a> , <a href="#">03:19</a> , <a href="#">03:41</a> , <a href="#">03:43</a> , <a href="#">03:46</a> ,	
<code>\__filehook_normalize_file_-</code>	<a href="#">03:48</a> , <a href="#">03:51</a> , <a href="#">03:60</a> , <a href="#">03:105</a> , <a href="#">03:118</a> ,	
name:w . . . . . <a href="#">52:406</a> , 52:413, 52:516	<a href="#">03:166</a> , <a href="#">14:2</a> , <a href="#">04:276</a> , <a href="#">21:1562</a> ,	
<code>\__filehook_resolve_file_subst:w</code>	<a href="#">29:318</a> , <a href="#">41:1</a> , <a href="#">42:1</a> , <a href="#">50:169</a> , <a href="#">50:177</a> ,	
. . . . . <a href="#">52:406</a> , 52:409, 52:411, 52:514	<a href="#">50:766</a> , <a href="#">50:769</a> , <a href="#">57:690</a> , <a href="#">57:716</a> , <a href="#">1310</a>	
<code>\__filehook_set_curr_file:nNN</code> . . .	<code>\fnsymbol</code> . . . . .	<a href="#">525</a>
. . . . . <a href="#">52:387</a> , 52:390, 52:392, 52:512	<code>\fnsymbol</code> . . . . .	<a href="#">22:232</a>
<code>\__filehook_set_curr_file_-</code>	<code>\font</code> . . . . .	<a href="#">21:317</a> , <a href="#">21:318</a> ,
assign:nnnNN <a href="#">52:387</a> , 52:395, 52:397	. . . . . <a href="#">21:319</a> , <a href="#">21:460</a> , <a href="#">21:467</a> , <a href="#">21:823</a> ,	
<code>\__filehook_subst_add:nn</code> . . . . .	<a href="#">21:830</a> , <a href="#">21:890</a> , <a href="#">21:1027</a> , <a href="#">21:1028</a> ,	
. . . . . <a href="#">52:206</a> , <a href="#">52:208</a> , 52:208, 52:252, <a href="#">1126</a>	<a href="#">21:1084</a> , <a href="#">21:1189</a> , <a href="#">21:1191</a> , <a href="#">21:1193</a> ,	
<code>\__filehook_subst_empty_name_-</code>	<a href="#">21:1240</a> , <a href="#">24:82</a> , <a href="#">24:88</a> , <a href="#">24:90</a> , <a href="#">26:85</a> ,	
chk:NN . . . . . <a href="#">52:208</a> , 52:236, 52:240	<a href="#">29:636</a> , <a href="#">29:669</a> , <a href="#">29:675</a> , <a href="#">29:701</a> , <a href="#">31:8</a> ,	
<code>\__filehook_subst_file_normalize:Nn</code>	<a href="#">31:9</a> , <a href="#">31:10</a> , <a href="#">32:85</a> , <a href="#">33:6</a> , <a href="#">33:576</a> ,	
. . . . . <a href="#">52:208</a> , 52:216, 52:218, 52:230, 52:234	<a href="#">33:590</a> , <a href="#">33:597</a> , <a href="#">37:566</a> , <a href="#">06:934</a> ,	
<code>\__filehook_subst_remove:n</code> . . . . .	<a href="#">06:937</a> , <a href="#">06:949</a> , <a href="#">06:952</a> , <a href="#">02:414</a> , <a href="#">02:419</a>	
. . . . . <a href="#">52:208</a> , 52:222, 52:253	<code>\fontdimen</code> . . . . .	<a href="#">21:317</a> , <a href="#">21:318</a> ,
<code>\filename@parse</code> . . . . . <a href="#">6</a> , <a href="#">1</a>	. . . . . <a href="#">21:319</a> , <a href="#">21:460</a> , <a href="#">21:467</a> , <a href="#">21:823</a> ,	
<code>\filesize</code> . . . . . <a href="#">05:76</a> , <a href="#">05:122</a>	<a href="#">21:830</a> , <a href="#">29:636</a> , <a href="#">29:669</a> , <a href="#">29:675</a> ,	
<code>\fill</code> . . . . . <a href="#">18:530</a>	<a href="#">32:85</a> , <a href="#">33:6</a> , <a href="#">33:576</a> , <a href="#">33:590</a> , <a href="#">33:597</a> ,	
<code>\finalhyphemerits</code> . . . . .	<a href="#">42:126</a> , <a href="#">42:129</a> , <a href="#">42:678</a> , <a href="#">02:414</a> , <a href="#">02:419</a>	
. . . . . <a href="#">37:455</a> , <a href="#">37:459</a> , <a href="#">37:465</a> , <a href="#">02:205</a> , <a href="#">1363</a>		

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- `\fontencoding` ..... 04:259,  
04:260, 04:282, 04:283, 21:891,  
21:1597, [24:314](#), [24:349](#), [24:361](#),  
[24:371](#), [28:408](#), [28:458](#), [29:741](#),  
[29:774](#), [29:790](#), [29:806](#), [30:16](#), [30:24](#),  
[30:79](#), [30:86](#), [30:95](#), [30:97](#), [33:36](#), [549](#)
  - `\fontfamily` ..... [24:342](#), [29:7](#),  
[29:10](#), [29:13](#), [29:168](#), [29:178](#), [29:239](#),  
[29:249](#), [29:561](#), [29:564](#), [29:567](#),  
[29:834](#), [29:866](#), [30:70](#), [30:81](#), [30:88](#),  
[30:99](#), [33:28](#), [33:30](#), [33:32](#), [33:34](#),  
[33:49](#), [33:51](#), [33:53](#), [33:55](#), [33:877](#), [707](#)
  - `\FontFamilyToCheck` .....  
..... [33:1584](#), [33:1585](#), [33:1598](#)
  - `\fontname` ..... [21:1028](#), [24:90](#)
  - `\fontseries` ..... [24:342](#), [25:2781](#),  
[25:2782](#), [25:2793](#), [25:2795](#), [25:2805](#),  
[25:2807](#), [29:16](#), [29:19](#), [29:337](#),  
[29:338](#), [29:339](#), [29:340](#), [29:360](#),  
[29:361](#), [29:362](#), [29:363](#), [29:398](#),  
[29:399](#), [29:400](#), [29:401](#), [29:418](#),  
[29:419](#), [29:420](#), [29:421](#), [29:434](#),  
[29:435](#), [29:436](#), [29:437](#), [29:445](#),  
[29:446](#), [29:447](#), [29:448](#), [29:461](#),  
[29:464](#), [29:555](#), [29:558](#), [29:868](#), [1323](#)
  - `\fontseriesforce` .....  
..... [25:2786](#), [25:2797](#), [25:2808](#), [623](#)
  - `\fontshape` ..... [21:470](#), [21:833](#),  
[24:342](#), [25:2916](#), [25:2921](#), [25:2926](#),  
[25:3134](#), [25:3135](#), [25:3144](#), [25:3146](#),  
[25:3151](#), [25:3153](#), [25:3204](#), [25:3208](#),  
[25:3211](#), [25:3214](#), [25:3217](#), [25:3220](#),  
[25:3223](#), [25:3226](#), [25:3233](#), [29:22](#),  
[29:25](#), [29:28](#), [29:31](#), [29:869](#), [33:600](#), [642](#)
  - `\fontshapeforce` .....  
.. [25:3138](#), [25:3147](#), [25:3154](#), [25:3234](#)
  - `\fontsize` ..... [19:6](#), [21:322](#),  
[21:348](#), [21:380](#), [21:892](#), [21:1242](#),  
[21:1278](#), [24:80](#), [24:381](#), [29:724](#),  
[29:870](#), [33:68](#), [33:636](#), [33:894](#),  
[45:409](#), [45:416](#), [45:437](#), [45:444](#), [1323](#)
  - `\fontsubfuzz` ..... [26:458](#),  
[26:492](#), [37:55](#), [37:120](#), [37:159](#), [1319](#)
  - `\F00` ..... [79](#)
  - `\foo` ..... [322](#)
  - `\footins` ..... [45:390](#), [45:465](#),  
[45:484](#), [45:502](#), [54:319](#), [54:320](#),  
[54:321](#), [54:322](#), [54:380](#), [54:427](#),  
[54:612](#), [54:617](#), [54:623](#), [54:650](#),  
[54:738](#), [54:744](#), [54:748](#), [54:820](#), [1188](#)
  - `\footnote` ..... [45:452](#), [1005](#)
  - `\footnotemark` ..... [44:10](#), [45:518](#), [1306](#)
  - `\footnoterule` .....  
.. [40:466](#), [45:394](#), [54:621](#), [54:747](#), [1336](#)
  - `footnotes:floats (plug)` ..... [54:702](#)
  - `footnotes:floats:legacy (plug)` .. [54:707](#)
  - `footnotes:space:floats (plug)` ... [54:674](#)
  - `\footnotesep` ..... [40:490](#),  
[40:507](#), [40:524](#), [45:451](#), [45:468](#),  
[45:477](#), [45:487](#), [45:495](#), [45:505](#), [45:513](#)
  - `\footnotesize` ..... [40:482](#),  
[40:500](#), [40:517](#), [45:466](#), [45:485](#), [45:503](#)
  - `\footnotetext` ..... [44:12](#), [45:535](#), [1306](#)
  - `\footref` ..... [45:547](#), [1367](#)
  - `\footskip` .....  
.. [54:53](#), [54:928](#), [54:991](#), [54:1050](#), [1198](#)
  - `\forall` ..... [30:334](#)
  - fp commands:  
  `\fp_eval:n` ..... [11:369](#), [05:166](#)  
  `\l_tmpa_fp` ..... [356](#)
  - `\fpeval` ..... [75](#)
  - `\fpeval` ..... [05:162](#), [05:174](#), [05:176](#), [75](#)
  - `\frac` ..... [38:412](#), [1312](#)
  - `\frame` ..... [40:196](#), [40:297](#)
  - `\framebox` ..... [889](#)
  - `\framebox` ..... [40:219](#), [1327](#)
  - `\frenchspacing` .....  
... [20:46](#), [20:116](#), [20:174](#), [37:571](#),  
[37:588](#), [37:739](#), [06:974](#), [06:995](#), [02:306](#)
  - `\frown` ..... [30:462](#)
  - `\fussy` ..... [49:137](#)
  - `\futurelet` .... [18:457](#), [18:465](#), [05:53](#),  
[32:83](#), [38:256](#), [41:359](#), [06:874](#), [06:888](#)
- ## G
- `\g_hook_\meta_{hook}_code_prop` ... [232](#)
  - `\g_hook_\meta_{hook}_declared_tl` . [232](#)
  - `\g_hook_\meta_{hook}_parameter_tl` [232](#)
  - `\g_hook_\meta_{hook}_reversed_tl` . [232](#)
  - `\Gamma` ..... [30:308](#)
  - `\gamma` ..... [30:281](#)
  - `\gathered` ..... [1275](#)
  - `\gcd` ..... [38:33](#)
  - `\gdef` ..... [1325](#)
  - gdef commands:  
  `\gdef_` ..... [38:269](#)
  - `\ge` ..... [30:428](#), [30:430](#)
  - `\Generic*` ..... [1330](#)
  - `\GenericError` ..... [14:18](#),  
[14:85](#), [14:111](#), [14:164](#), [26:63](#), [1326](#)
  - `\GenericInfo` ... [03:106](#), [03:108](#), [03:119](#),  
[03:122](#), [03:127](#), [03:162](#), [03:163](#),  
[03:168](#), [03:172](#), [03:176](#), [03:197](#), [14:4](#),  
[14:104](#), [14:130](#), [14:182](#), [21:8](#), [26:32](#),  
[26:35](#), [26:40](#), [26:76](#), [05:67](#), [50:66](#),  
[50:74](#), [50:104](#), [50:107](#), [50:1742](#), [1326](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpara.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

- \GenericWarning ..... 14:11, 14:94,  
14:120, 14:141, 14:149, 14:173,  
14:195, 26:43, 26:48, 26:51, 26:79, 1326
  - \geq ..... 30:426, 30:428
  - \getanddefinefonts ..... 1304
  - \GetFileInfo ..... 30:3
  - \gets ..... 30:450, 30:452
  - \gg ..... 30:444
  - \global ..... 1343
  - \globaldefs 24:690, 26:232, 28:61, 28:90,  
28:161, 28:192, 28:222, 28:254, 02:247
  - \glossary ..... 1006
  - \glossary ..... 44:192,  
44:200, 46:23, 46:35, 48:282,  
49:40, 49:51, 49:66, 49:74, 49:89,  
49:97, 54:905, 54:975, 54:1034, 1382
  - \glossaryentry ..... 46:32
  - \gluestretchorder ..... 54:569
  - \glyphmissingdetails 33:1183, 33:1208, 797
  - \goodbreak ..... 06:975, 06:996, 02:386
  - \grave ..... 30:528
  - \group ..... 1304
  - group commands:
    - \group\_align\_safe\_begin/end: .. 170
    - \group\_align\_safe\_begin: .....  
..... 07:290, 07:302, 07:407, 119
    - \group\_align\_safe\_end: .....  
..... 07:324, 07:430, 07:2106, 123
    - \group\_begin: ..... 09:29,  
09:218, 09:293, 16:17, 16:23, 16:50,  
16:56, 28:298, 28:348, 48:68, 48:250,  
48:373, 51:4, 52:210, 52:224, 53:92,  
07:1610, 07:1619, 07:1655, 07:1704,  
07:1743, 07:1807, 07:1814, 07:2098,  
07:2502, 07:2507, 07:2679, 07:2683,  
07:2711, 08:387, 08:1167, 08:1180
    - \c\_group\_begin\_token 07:692, 07:703,  
07:1678, 07:2104, 07:2185, 07:2791
    - \group\_end: . 09:31, 09:222, 09:297,  
16:19, 16:28, 16:52, 16:60, 28:301,  
28:351, 48:73, 48:269, 48:386, 51:21,  
52:220, 52:232, 53:94, 07:1640,  
07:1689, 07:1731, 07:1753, 07:1764,  
07:1819, 07:1823, 07:1827, 07:2119,  
07:2511, 07:2516, 07:2693, 07:2694,  
07:2696, 07:2698, 07:2708, 07:2715,  
07:2716, 08:390, 08:1171, 08:1190, 318
    - \c\_group\_end\_token .....  
..... 07:695, 07:1720, 07:2174
    - \group\_insert\_after:N .....  
28:334, 28:335, 28:338, 28:360, 28:361
  - \guillemotleft 21:563, 21:797, 21:1128, 1358
  - \guillemotright .....  
..... 21:564, 21:798, 21:1144, 1358
  - \guillemotleft ... 21:566, 21:800, 21:1130
  - \guillemotright .. 21:567, 21:801, 21:1146
  - \guilsinglleft ..... 21:568, 21:1207
  - \guilsinglright ..... 21:569, 21:1208
- ## H
- \H ..... 14:24, 21:250, 21:406, 21:492,  
21:624, 21:632, 21:651, 21:659,  
21:777, 21:1270, 21:1409, 21:1410,  
21:1437, 21:1438, 33:141, 33:165
  - \halign ..... 38:127, 38:210,  
38:433, 38:462, 38:625, 02:409, 1304
  - \hang ..... 1335
  - \hangafter ..... 02:249
  - \hangindent ..... 44:139, 02:280
  - \hat ..... 30:534
  - \hbadness 24:745, 24:752, 24:788, 24:807,  
53:238, 53:240, 53:290, 53:292, 02:188
  - \hbar ..... 30:346
  - \hbox ..... 1145
  - hbox commands:
    - \hbox:n ..... 53:388
    - \hbox\_set:Nn .....  
53:170, 53:217, 53:243, 53:268, 53:297
    - \hbox\_set\_to\_wd:Nnn .....  
..... 53:241, 53:293, 53:329
    - \hbox\_unpack:N .....  
..... 48:425, 48:457, 53:251, 53:295
    - \hbox\_unpack\_drop:N ..... 53:180
  - \hbox\_u to\_u ..... 1320
  - \headheight . 54:51, 54:912, 54:980, 54:1039
  - \headsep ... 54:52, 54:926, 54:989, 54:1048
  - \heartsuit ..... 30:344
  - \height . 21:896, 21:1246, 40:31, 40:34, 1311
  - \hfil ..... 873
  - \hfill ..... 1307
  - \hfuzz ..... 24:753,  
49:133, 49:134, 49:140, 49:141,  
53:237, 53:239, 53:289, 53:291, 02:265
  - \hglue ..... 02:376
  - \hideoutput ..... 02:565
  - \hideskip ..... 02:179, 02:400
  - \hidewidth ..... 21:347,  
21:349, 21:378, 21:382, 21:411,  
21:412, 21:415, 21:418, 21:499,  
21:500, 21:504, 21:507, 21:509,  
21:512, 21:524, 21:529, 21:545,  
21:784, 21:785, 21:788, 21:791,  
21:858, 21:861, 21:1277, 21:1279, 02:400
  - \hline ..... 41:358, 41:361, 1308
  - \hoffset ..... 02:281
  - \holdinginserts ..... 02:209
  - \hom ..... 38:29

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

## hook commands:

`\hook_activate_generic:n` ..... 08:2780, 08:2866,  
 08:2885, 08:2898, 08:288, 08:288,  
 08:290, 08:308, 08:326, 08:328, 241  
`\hook_debug_off:` .....  
 ..... 08:2842, 08:7, 08:13, 216  
`\hook_debug_on:` 08:2841, 08:7, 08:8, 216  
`\hook_disable:n` .... 08:2854, 08:2854  
`\hook_disable_generic:n` .....  
 08:2782, 08:2859, 08:2891, 08:264,  
 08:264, 08:266, 08:282, 08:285, 214  
`\hook_gclear_next_code:n` .....  
 ..... 08:2227, 08:2227, 08:2812, 215  
`\hook_gput_code:nnn` .....  
 .. 08:2792, 08:486, 08:486, 08:488,  
 08:596, 08:598, 08:698, 08:719, 246  
`\hook_gput_code_with_args:nnn` ...  
 . 08:2794, 08:486, 08:494, 08:645, 215  
`\hook_gput_next_code:nn` .....  
 08:2149, 08:2149, 08:2151, 08:2180,  
 08:2182, 08:2803, 08:707, 08:725, 215  
`\hook_gput_next_code_with_`  
`args:nn` 08:2165, 08:2185, 08:2805, 215  
`\hook_gremove_code:nn` .. 08:2814,  
 08:975, 08:975, 08:977, 08:1012, 215  
`\hook_gset_rule:nnnn` ... 08:2844,  
 08:2846, 08:2849, 08:1320, 08:1320, 268  
`\hook_if_empty:n` .....  
 .. 08:2469, 08:2471, 08:2486, 08:2488  
`\hook_if_empty:nTF` .....  
 08:1889, 08:1995, 08:2469, 08:2850,  
 08:2851, 08:2852, 53:63, 53:164, 208  
`\hook_if_empty_p:n` 08:1944, 08:2044,  
 08:2469, 53:67, 53:113, 53:382, 216  
`\hook_log:n` .....  
 ..... 08:1835, 08:1835, 08:2840, 216  
`\hook_new:n` ..... 08:2757,  
 48:288, 53:153, 53:154, 53:155,  
 53:156, 53:157, 53:158, 53:159,  
 08:67, 08:69, 08:88, 08:223, 08:878, 298  
`\hook_new_pair:nn` ..... 08:2761,  
 16:6, 16:7, 08:199, 08:201, 08:221, 213  
`\hook_new_pair_with_args:nn` ... 214  
`\hook_new_pair_with_args:nnn` ...  
 ..... 08:2769, 08:199,  
 08:199, 08:203, 08:219, 08:226, 214  
`\hook_new_reversed:n` ... 08:2759,  
 08:170, 08:172, 08:188, 08:224, 213  
`\hook_new_reversed_with_args:nn` .  
 ..... 08:2767, 08:170,  
 08:170, 08:174, 08:186, 08:197, 214  
`\hook_new_with_args:nn` .. 08:2765,  
 08:67, 08:67, 08:71, 08:86, 08:100, 214  
`\g_hook_patch_action_list_tl` ...  
 ..... 09:6, 09:108, 09:141  
`\hook_provide:n` .... 08:2854, 08:2861  
`\hook_provide_pair:nn` 08:2854, 08:2875  
`\hook_provide_reversed:n` .....  
 ..... 08:2854, 08:2868  
`\hook_show:n` .....  
 08:1835, 08:1842, 08:1849, 08:2839, 282  
`\hook_use:n` .....  
 08:2239, 08:2239, 08:2241, 08:2261,  
 08:2263, 08:2281, 08:2283, 08:2338,  
 08:2829, 16:22, 16:31, 16:55, 16:63,  
 16:98, 16:105, 48:252, 53:62, 53:65,  
 53:71, 53:75, 53:123, 08:1482, 291  
`\hook_use:nnw` ..... 08:2279,  
 08:2309, 08:2311, 08:2311, 08:2313,  
 08:2329, 08:2331, 08:2339, 08:2831, 215  
`\hook_use_once:n` .....  
 08:2378, 08:2380, 08:2395, 08:2830, 219  
`\hook_use_once:nnw` 08:2378, 08:2378,  
 08:2386, 08:2393, 08:2401, 08:2832, 215  
hook internal commands:  
`\c_hook` ..... 08:1312, 08:1316  
`\g_hook_??_code_prop` ..... 08:1309  
`\c_hook_??_parameter_tl` ... 08:1309  
`\g_hook_??_reversed_tl` .... 08:1309  
`\g_hook_{hook}_code_prop` .... 1381  
`\g_hook_{hook}_labels_clist` ... 236  
`\g_hook_{hook}_reversed_tl` ... 232  
`\_hook_print_args:nn` ..... 1378  
`\_hook_activate_generic:n` .. 08:288  
`\_hook_activate_generic:nn` ....  
 ..... 08:2883, 08:291, 08:292, 08:310  
`\_hook_activate_generic_pair:nn`  
 .. 08:2854, 08:2880, 08:2884, 08:2912  
`\_hook_activate_generic_`  
`reversed:n` ..... 08:2854,  
 08:2873, 08:2882, 08:2885, 08:2905  
`\g_hook_all_seq` ..... 08:2985,  
 08:28, 08:108, 08:137, 08:1443, 08:1470  
`\_hook_apply_rule->:nnn` . 08:1810  
`\_hook_apply_rule<-:nnn` . 08:1810  
`\_hook_apply_rule<:nnn` .. 08:1810  
`\_hook_apply_rule>:nnn` .. 08:1810  
`\_hook_apply_rule_xE:nnn` . 08:1810  
`\_hook_apply_rule_xW:nnn` . 08:1810  
`\_hook_apply_label_pair:nnn` ...  
 ..... 08:1590, 08:1591,  
 08:1672, 08:1673, 08:1737, 08:1737, 279  
`\_hook_apply_rule:nnn` .....  
 ..... 08:1753, 08:1753, 08:1747, 279  
`\_hook_apply_rule:nnnN` ..... 280  
`\_hook_apply_rule->:nnn` .. 08:1788  
`\_hook_apply_rule<-:nnn` .. 08:1788

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

`\__hook_apply_rule_<:nnn` ... [08:1760](#)  
`\__hook_apply_rule_>:nnn` ... [08:1760](#)  
`\__hook_apply_rule_xE:nnn` .. [08:1774](#)  
`\__hook_apply_rule_xW:nnn` .. [08:1774](#)  
`\__hook_braced_cs_parameter:n` ...  
     ..... [08:2980](#),  
     [08:1084](#), [08:1141](#), [08:1166](#), [08:1177](#),  
     [08:1229](#), [08:1229](#), [08:1231](#), [08:1257](#)  
`\__hook_braced_hidden_loop:w` ...  
     .. [08:1229](#), [08:1233](#), [08:1236](#), [08:1242](#)  
`\__hook_braced_parameter:n` .....  
     ..... [09:238](#), [09:523](#), [08:1260](#),  
     [08:1260](#), [08:1262](#), [08:1283](#), [08:1285](#),  
     [08:1504](#), [08:1506](#), [08:1641](#), [08:1643](#)  
`\__hook_braced_real_loop:w` . [08:1260](#)  
`\__hook_chk_args_allowed:nn` ....  
     ..... [08:2203](#), [08:502](#), [08:647](#),  
     [08:647](#), [08:649](#), [08:664](#), [08:666](#), [290](#)  
`\__hook_clear_next:n` .....  
     [08:2207](#), [08:2223](#), [08:2228](#), [08:2229](#),  
     [08:2229](#), [08:2231](#), [08:2234](#), [08:2236](#), [287](#)  
`\__hook_clist_gput:Nn` .....  
     [08:1512](#), [08:1514](#), [08:1546](#), [08:1550](#),  
     [08:1614](#), [08:1701](#), [08:1735](#), [08:1736](#)  
`\__hook_cmd_begindocument_code:` .  
     [09:63](#), [09:71](#), [09:76](#), [09:79](#), [09:624](#), [335](#)  
`\__hook_cmd_if_scanable:Nn` .. [09:468](#)  
`\__hook_cmd_if_scanable:NnTF` ...  
     ..... [09:426](#), [09:445](#), [09:468](#), [330](#)  
`\__hook_cmd_patch_xparse:Nnn` ...  
     ..... [09:145](#), [09:166](#), [09:166](#)  
`\__hook_cmd_try_patch:nn` .....  
     ..... [09:69](#), [09:80](#), [09:80](#)  
`\__hook_code_gset:nn` ... [08:2440](#),  
     [08:118](#), [08:1106](#), [08:1106](#), [08:1108](#),  
     [08:1120](#), [08:1122](#), [08:1124](#), [08:1501](#)  
`\__hook_code_gset_aux:nnn` .....  
     ..... [08:1069](#), [08:1106](#), [08:1109](#),  
     [08:1111](#), [08:1113](#), [08:1114](#), [08:1127](#)  
`\__hook_code_gset_auxi:nnnn` ....  
     ..... [08:1049](#), [08:1070](#),  
     [08:1095](#), [08:1097](#), [08:1104](#), [08:1135](#), [260](#)  
`\__hook_cs_end:w` ..... [08:1229](#),  
     [08:1248](#), [08:1249](#), [08:1250](#), [08:1255](#)  
`\__hook_cs_gput_right:nnn` .....  
     [08:2208](#), [08:2411](#), [08:541](#), [08:1049](#),  
     [08:1049](#), [08:1051](#), [08:1099](#), [08:1101](#)  
`\__hook_cs_gput_right_fast:nnn` ..  
     .. [08:1049](#), [08:1057](#), [08:1063](#), [08:1102](#)  
`\__hook_cs_gput_right_slow:nnn` ..  
     .. [08:1049](#), [08:1059](#), [08:1066](#), [08:1103](#)  
`\__hook_cs_if_empty:N` .....  
     .. [08:1209](#), [08:1211](#), [08:1225](#), [08:1227](#)  
`\__hook_cs_if_empty:NnTF` .....  
     ..... [08:1914](#), [08:1921](#), [08:2204](#),  
     [08:2206](#), [08:2477](#), [08:2478](#), [08:1209](#)  
`\__hook_cs_if_empty_p:N` .... [08:1209](#)  
`\__hook_cs_parameter_count:N` ...  
     ..... [08:1229](#), [08:1234](#), [08:1244](#)  
`\__hook_cs_parameter_count:w` ...  
     .. [08:1229](#), [08:1246](#), [08:1253](#), [08:1254](#)  
`\l__hook_cur_hook_tl` ... [08:1794](#),  
     [08:1805](#), [08:29](#), [08:1576](#), [08:1658](#), [281](#)  
`\__hook_curr_name_pop:` .....  
     . [08:2820](#), [08:2926](#), [08:417](#), [08:449](#), [245](#)  
`\__hook_curr_name_push:n` .....  
     . [08:2818](#), [08:2823](#), [08:417](#), [08:431](#), [245](#)  
`\__hook_curr_name_push_aux:n` ...  
     ..... [08:417](#), [08:432](#), [08:433](#)  
`\__hook_currname_or_default:` ...  
     ..... [08:2668](#), [08:2716](#),  
     [08:333](#), [08:343](#), [08:347](#), [08:363](#),  
     [08:364](#), [08:364](#), [08:538](#), [08:628](#), [242](#)  
`\__hook_debug:n` .....  
     ..... [08:1762](#), [08:1769](#), [08:1776](#),  
     [08:1784](#), [08:1790](#), [08:1801](#), [08:2155](#),  
     [08:2169](#), [09:19](#), [09:28](#), [09:45](#),  
     [09:56](#), [09:65](#), [09:66](#), [09:82](#), [09:86](#),  
     [08:7](#), [08:7](#), [08:20](#), [08:531](#), [08:621](#),  
     [08:1442](#), [08:1451](#), [08:1469](#), [08:1472](#),  
     [08:1494](#), [08:1518](#), [08:1528](#), [08:1556](#),  
     [08:1595](#), [08:1615](#), [08:1677](#), [08:1702](#), [229](#)  
`\g__hook_debug_bool` .....  
     ..... [08:6](#), [08:10](#), [08:15](#), [08:21](#)  
`\__hook_debug_gset:` .....  
     ..... [08:7](#), [08:11](#), [08:16](#), [08:18](#)  
`\__hook_debug_label_data:N` .....  
     ..... [08:1823](#), [08:1823](#),  
     [08:1595](#), [08:1637](#), [08:1678](#), [08:1726](#)  
`\__hook_debug_print_rules:n` ....  
     ..... [08:2133](#), [08:2133](#)  
`\__hook_declare_deprecated_`  
     generic:NNn . [08:773](#), [08:794](#), [08:827](#)  
`\__hook_declare_deprecated_`  
     generic:NNw . [08:789](#), [08:795](#), [08:796](#)  
`\__hook_def_cmd:w` .....  
     ..... [09:13](#), [09:14](#), [09:209](#),  
     [09:215](#), [09:284](#), [09:290](#), [09:316](#), [326](#)  
`\g__hook_delayed_patches_prop` ...  
     ..... [09:17](#), [09:68](#), [09:74](#), [09:75](#)  
`\__hook_deprecated_generic_`  
     warn:n ..... [08:1865](#),  
     [08:1983](#), [08:772](#), [08:779](#), [08:826](#),  
     [08:1004](#), [08:1040](#), [08:1331](#), [08:1362](#), [253](#)  
`\__hook_deprecated_generic_`  
     warn:Nn ..... [08:779](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\__hook_deprecated_generic_-</code>		
<code>warn:Nw</code> .....	<a href="#">08:779</a>	
<code>\__hook_deprecated_generic_-</code>		
<code>warn:w</code> .....	<a href="#">08:780</a> , <a href="#">08:781</a>	
<code>\__hook_deprecated_warn:nn</code> .....		
.....	<a href="#">08:2856</a> , <a href="#">08:2863</a> ,	
.....	<a href="#">08:2870</a> , <a href="#">08:2877</a> , <a href="#">08:2888</a> , <a href="#">08:2895</a> ,	
.....	<a href="#">08:2902</a> , <a href="#">08:2909</a> , <a href="#">08:2914</a> , <a href="#">08:2914</a>	
<code>\__hook_disable:n</code> .....		
.....	<a href="#">09:226</a> , <a href="#">09:519</a> , <a href="#">08:264</a> , <a href="#">08:267</a> , <a href="#">08:268</a>	
<code>\__hook_do_deprecated_generic:Nn</code>		
.....	<a href="#">08:1866</a> , <a href="#">08:1984</a> , <a href="#">08:789</a> , <a href="#">08:789</a> ,	
.....	<a href="#">08:1005</a> , <a href="#">08:1041</a> , <a href="#">08:1332</a> , <a href="#">08:1363</a>	
<code>\__hook_do_deprecated_generic:Nw</code>		
.....	<a href="#">08:789</a> , <a href="#">08:790</a> , <a href="#">08:791</a>	
<code>\__hook_double_hashes:n</code> .....		
.....	<a href="#">09:205</a> , <a href="#">09:280</a> ,	
.....	<a href="#">09:342</a> , <a href="#">09:342</a> , <a href="#">09:380</a> , <a href="#">08:553</a> ,	
.....	<a href="#">08:1081</a> , <a href="#">08:1090</a> , <a href="#">08:1138</a> , <a href="#">08:1195</a> , <a href="#">264</a>	
<code>\__hook_double_hashes:w</code> .....		
.....	<a href="#">09:342</a> , <a href="#">09:343</a> ,	
.....	<a href="#">09:344</a> , <a href="#">09:376</a> , <a href="#">09:380</a> , <a href="#">09:383</a> , <a href="#">327</a>	
<code>\__hook_double_hashes_group:n</code> ...		
.....	<a href="#">09:342</a> , <a href="#">09:350</a> , <a href="#">09:379</a>	
<code>\__hook_double_hashes_output:N</code> ..		
.....	<a href="#">09:342</a> , <a href="#">09:347</a> , <a href="#">09:355</a> , <a href="#">328</a>	
<code>\__hook_double_hashes_space:w</code> ...		
.....	<a href="#">09:342</a> , <a href="#">09:351</a> , <a href="#">09:382</a>	
<code>\__hook_double_hashes_stop:w</code> ...		
.....	<a href="#">09:342</a> , <a href="#">09:358</a> , <a href="#">09:378</a>	
<code>\c__hook_empty_tl</code> ....	<a href="#">08:35</a> , <a href="#">08:1301</a>	
<code>\__hook_end_document_label_-</code>		
<code>check:</code> .....	<a href="#">08:417</a> , <a href="#">08:456</a> , <a href="#">08:457</a> , <a href="#">08:464</a>	
<code>\__hook_exp_not:n</code> .....		
.....	<a href="#">09:188</a> , <a href="#">09:189</a> , <a href="#">09:193</a> , <a href="#">09:204</a> ,	
.....	<a href="#">09:263</a> , <a href="#">09:264</a> , <a href="#">09:268</a> , <a href="#">09:279</a> , <a href="#">323</a>	
<code>\__hook_exp_not:NN</code> .....	<a href="#">09:13</a> ,	
.....	<a href="#">09:13</a> , <a href="#">09:210</a> , <a href="#">09:216</a> , <a href="#">09:236</a> ,	
.....	<a href="#">09:241</a> , <a href="#">09:285</a> , <a href="#">09:291</a> , <a href="#">09:307</a> , <a href="#">09:309</a>	
<code>\__hook_file_hook_normalize:n</code> ...		
.....	<a href="#">08:2364</a> , <a href="#">08:733</a> ,	
.....	<a href="#">08:916</a> , <a href="#">08:916</a> , <a href="#">08:919</a> , <a href="#">08:921</a> , <a href="#">256</a>	
<code>\l__hook_front_tl</code> .....	<a href="#">08:1565</a> ,	
.....	<a href="#">08:1606</a> , <a href="#">08:1609</a> , <a href="#">08:1612</a> , <a href="#">08:1614</a> ,	
.....	<a href="#">08:1615</a> , <a href="#">08:1616</a> , <a href="#">08:1630</a> , <a href="#">08:1631</a> ,	
.....	<a href="#">08:1691</a> , <a href="#">08:1695</a> , <a href="#">08:1699</a> , <a href="#">08:1701</a> ,	
.....	<a href="#">08:1703</a> , <a href="#">08:1705</a> , <a href="#">08:1719</a> , <a href="#">08:1720</a>	
<code>\c__hook_generic_{type}/./{place}_tl</code>		
.....	<a href="#">253</a>	
<code>\c__hook_generic_class/./after_-</code>		
<code>tl</code> .....	<a href="#">08:932</a>	
<code>\c__hook_generic_class/./before_-</code>		
<code>tl</code> .....	<a href="#">08:932</a>	
<code>\c__hook_generic_cmd/./after_tl</code> .		<a href="#">08:932</a>
.....		
<code>\c__hook_generic_cmd/./before_tl</code>		<a href="#">08:932</a>
.....		
<code>\c__hook_generic_env/./after_tl</code> .		<a href="#">08:932</a>
.....		
<code>\c__hook_generic_env/./before_tl</code>		<a href="#">08:932</a>
.....		
<code>\c__hook_generic_env/./begin_tl</code> .		<a href="#">08:932</a>
.....		
<code>\c__hook_generic_env/./end_tl</code>	<a href="#">08:932</a>	
<code>\c__hook_generic_file/./after_tl</code>		<a href="#">08:932</a>
.....		
<code>\c__hook_generic_file/./before_-</code>		<a href="#">08:932</a>
<code>tl</code> .....		
<code>\c__hook_generic_include/./after_-</code>		<a href="#">08:932</a>
<code>tl</code> .....		
<code>\c__hook_generic_include/./before_-</code>		<a href="#">08:932</a>
<code>tl</code> .....		
<code>\c__hook_generic_include/./end_-</code>		<a href="#">08:932</a>
<code>tl</code> .....		
<code>\c__hook_generic_package/./after_-</code>		<a href="#">08:932</a>
<code>tl</code> .....		
<code>\c__hook_generic_package/./before_-</code>		<a href="#">08:932</a>
<code>tl</code> .....		
<code>\__hook_generic_parameter:n</code> ....		
.....	<a href="#">08:1076</a> , <a href="#">08:1296</a> , <a href="#">08:1307</a>	
<code>\__hook_generic_parameter:w</code> ....		
.....	<a href="#">08:1297</a> , <a href="#">08:1298</a>	
<code>\c__hook_generics_file_prop</code> ....		
.....	<a href="#">08:908</a> , <a href="#">08:955</a>	
<code>\c__hook_generics_prop</code> .....		
.....	<a href="#">08:844</a> , <a href="#">08:876</a> , <a href="#">08:932</a> , <a href="#">08:950</a> , <a href="#">08:952</a>	
<code>\c__hook_generics_reversed_ii_-</code>		
<code>prop</code> .....	<a href="#">08:853</a> , <a href="#">08:880</a> , <a href="#">08:955</a>	
<code>\c__hook_generics_reversed_iii_-</code>		
<code>prop</code> .....	<a href="#">08:857</a> , <a href="#">08:884</a> , <a href="#">08:955</a>	
<code>\__hook_gput_code:nnn</code> .....		
.....	<a href="#">08:486</a> , <a href="#">08:491</a> ,	
.....	<a href="#">08:497</a> , <a href="#">08:500</a> , <a href="#">08:600</a> , <a href="#">08:601</a> , <a href="#">08:679</a>	
<code>\__hook_gput_code_store:nnn</code> ....		
.....	<a href="#">08:486</a> , <a href="#">08:513</a> , <a href="#">08:516</a>	
<code>\__hook_gput_next_code:nn</code> .....		
.....	<a href="#">08:2154</a> , <a href="#">08:2168</a> ,	
.....	<a href="#">08:2184</a> , <a href="#">08:2187</a> , <a href="#">08:2187</a> , <a href="#">08:686</a>	
<code>\__hook_gput_next_do:nn</code> .	<a href="#">08:2193</a> ,	
.....	<a href="#">08:2198</a> , <a href="#">08:2198</a> , <a href="#">08:2200</a> , <a href="#">08:2211</a> ,	
.....	<a href="#">08:2213</a> , <a href="#">08:687</a> , <a href="#">08:708</a> , <a href="#">08:725</a> , <a href="#">251</a>	
<code>\__hook_gput_next_do:Nnn</code> .....		
.....	<a href="#">08:2215</a> , <a href="#">08:2218</a>	
<code>\__hook_gput_undeclared_hook:nnn</code>		
.....	<a href="#">08:668</a> ,	
.....	<a href="#">08:668</a> , <a href="#">08:680</a> , <a href="#">08:699</a> , <a href="#">08:719</a> , <a href="#">251</a>	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

\\_\_hook\_gremove\_code:nn ..... 08:1993, 08:2073, 08:2189, 08:264,  
 ..... 08:975, 08:978,  
 08:979, 08:1006, 08:1014, 08:1042  
 \\_\_hook\_gset\_rule:nnnn .....  
 08:1320, 08:1322, 08:1325, 08:1327,  
 08:1332, 08:1356, 08:1358, 08:1363  
 \\_\_hook\_guess\_arg\_count:NN 09:485,  
 09:485, 09:487, 09:510, 09:512, 09:518  
 \\_\_hook\_guess\_arg\_count:nw .....  
 ..... 09:485, 09:498, 09:503, 09:506  
 \\_\_hook\_guess\_arg\_count:wN .....  
 ..... 09:485, 09:489, 09:493  
 \\_\_hook\_hash\_check:nTF .....  
 ..... 08:486, 08:551, 08:560  
 \\_\_hook\_hash\_check\_aux:w .....  
 ..... 08:486, 08:562, 08:568  
 \c\_\_hook\_hash\_tl ... 09:11, 09:271,  
 09:272, 09:274, 09:361, 08:1241, 265  
 \c\_\_hook\_hashes\_tl . 09:11, 09:196,  
 09:197, 09:199, 09:362, 08:1168, 323  
 \g\_\_hook\_hook\_curr\_name\_tl .....  
 ..... 08:32, 08:366, 08:376,  
 08:417, 08:429, 08:444, 08:445,  
 08:452, 08:462, 08:463, 08:484, 305  
 \\_\_hook\_hook\_gput\_code\_do:nnn ...  
 ..... 08:240, 08:257, 08:486,  
 08:520, 08:529, 08:608, 08:619, 08:671  
 \\_\_hook\_if\_cmd\_hook:n .....  
 ..... 08:2552, 08:2554, 08:2568  
 \\_\_hook\_if\_cmd\_hook:nTF .....  
 ..... 08:2095, 08:2552, 08:2570  
 \\_\_hook\_if\_cmd\_hook:w 08:2555, 08:2556  
 \\_\_hook\_if\_cmd\_hook:wTF .... 08:2552  
 \\_\_hook\_if\_cmd\_hook\_p:n .... 08:2552  
 \\_\_hook\_if\_cmd\_hook\_p:w .... 08:2552  
 \\_\_hook\_if\_declared:n ..... 08:2517  
 \\_\_hook\_if\_declared:nTF . 08:2094,  
 08:2517, 09:84, 08:75, 08:93, 08:178,  
 08:207, 08:210, 08:297, 08:315,  
 08:653, 08:878, 08:1054, 08:1072, 233  
 \\_\_hook\_if\_declared\_p:n .... 08:2517  
 \\_\_hook\_if\_deprecated\_generic:n .  
 ..... 08:2540  
 \\_\_hook\_if\_deprecated\_generic:nTF  
 ..... 08:1863,  
 08:1981, 08:2532, 08:770, 08:824,  
 08:1002, 08:1038, 08:1329, 08:1360  
 \\_\_hook\_if\_deprecated\_generic:w .  
 ..... 08:2541, 08:2542  
 \\_\_hook\_if\_deprecated\_generic\_-  
 p:n ..... 08:2532  
 \\_\_hook\_if\_disabled:n ..... 08:273  
 \\_\_hook\_if\_disabled:nTF .....  
 ..... 08:1875, 08:1887, 08:1970,  
 08:1993, 08:2073, 08:2189, 08:264,  
 08:294, 08:312, 08:524, 08:612, 234  
 \\_\_hook\_if\_disabled\_p:n ..... 08:264  
 \\_\_hook\_if\_execute\_immediately:n  
 ..... 08:2456  
 \\_\_hook\_if\_execute\_immediately:nTF  
 ..... 08:2382, 08:2388, 08:2397,  
 08:2456, 08:503, 08:603, 08:1336  
 \\_\_hook\_if\_execute\_immediately\_-  
 p:n ..... 08:2456  
 \\_\_hook\_if\_file\_hook:w .....  
 ..... 08:893, 08:896, 08:898  
 \\_\_hook\_if\_file\_hook:wTF .....  
 ..... 08:2361, 08:729, 08:893, 256  
 \\_\_hook\_if\_file\_hook\_p:w .... 08:893  
 \\_\_hook\_if\_generic:n ..... 08:2532  
 \\_\_hook\_if\_generic:nTF .....  
 ..... 08:1873, 08:1989,  
 08:2532, 08:753, 08:811, 08:1075  
 \\_\_hook\_if\_generic:w 08:2533, 08:2534  
 \\_\_hook\_if\_generic\_p:n ..... 08:2532  
 \\_\_hook\_if\_generic\_reversed:n 08:2572  
 \\_\_hook\_if\_generic\_reversed:nTF .  
 08:2572, 08:302, 08:320, 08:765, 08:819  
 \\_\_hook\_if\_generic\_reversed:w ...  
 ..... 08:2573, 08:2574  
 \\_\_hook\_if\_generic\_reversed\_p:n .  
 ..... 08:2572  
 \\_\_hook\_if\_has\_hash:n ..... 09:328  
 \\_\_hook\_if\_has\_hash:nTF .....  
 ..... 09:186, 09:261, 09:328, 327  
 \\_\_hook\_if\_has\_hash:w .....  
 09:328, 09:329, 09:330, 09:336, 09:338  
 \\_\_hook\_if\_has\_hash\_check:w ....  
 ..... 09:328, 09:335, 09:340  
 \\_\_hook\_if\_has\_hash\_p:n ..... 09:328  
 \\_\_hook\_if\_label\_case:nnnnn ....  
 ..... 08:2110,  
 08:1429, 08:1429, 08:1588, 08:1670  
 \\_\_hook\_if\_public\_command:N . 09:125  
 \\_\_hook\_if\_public\_command:NTF ...  
 ..... 09:94, 09:104, 320  
 \\_\_hook\_if\_public\_command:w ....  
 ..... 09:94, 09:128, 09:134  
 \\_\_hook\_if\_replacing\_args: . 08:2586  
 \\_\_hook\_if\_replacing\_args:TF ...  
 ..... 08:2582, 08:2588, 08:2593,  
 08:2594, 08:2599, 08:2600, 08:2605,  
 08:505, 08:548, 08:575, 08:651, 08:1088  
 \\_\_hook\_if\_reversed:n ..... 08:2523  
 \\_\_hook\_if\_reversed:nTF . 08:1910,  
 08:1950, 08:1952, 08:2011, 08:2050,  
 08:2053, 08:2523, 08:1510, 08:1543  
 \\_\_hook\_if\_reversed\_p:n .... 08:2523

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

```

\__hook_if_structure_exist:n 08:2511
\__hook_if_structure_exist:nTF ..
    08:2192, 08:2490, 08:2511, 08:2747,
    08:150, 08:162, 08:981, 08:1016, 234
\__hook_if_structure_exist_p:n ..
    ..... 08:2511
\__hook_if_usable:n ..... 08:2505
\__hook_if_usable:nTF .....
    08:1885, 08:1909, 08:1968, 08:1991,
    08:2009, 08:2071, 08:2156, 08:2170,
    08:2414, 08:2505, 08:2853, 08:106,
    08:518, 08:532, 08:577, 08:606,
    08:622, 08:755, 08:813, 08:846,
    08:998, 08:1034, 08:1497, 08:1532, 233
\__hook_if_usable_p:n .....
    ..... 08:1943, 08:2043, 08:2505
\__hook_if_usable_use:n .....
    08:2348, 08:2363, 08:2366, 08:2369, 294
\__hook_include_legacy_code_-
    chunk:n ..... 08:126,
    08:142, 08:229, 08:229, 08:231,
    08:249, 08:251, 08:1496, 08:1531, 1377
\__hook_init_structure:n 08:2202,
    08:119, 08:139, 08:146, 08:146,
    08:148, 08:158, 08:160, 08:540,
    08:630, 08:670, 08:1342, 08:1367, 298
\__hook_initialize_all: .....
    ..... 08:2924, 08:1437, 08:1437,
    08:1439, 08:1463, 08:1465, 08:1487
\__hook_initialize_hook_code:n ..
    ..... 08:2257, 08:2278,
    08:2307, 08:1441, 08:1468, 08:1490,
    08:1490, 08:1492, 08:1524, 08:1526, 279
\__hook_initialize_single:NNn ...
    08:1516, 08:1554, 08:1570, 08:1570,
    08:1572, 08:1650, 08:1652, 08:1654, 272
\l__hook_label_0_tl ..... 08:1565
\__hook_label_if_exist_apply:nnnTF
    08:1737, 08:1739, 08:1741, 08:1744, 288
\__hook_label_ordered:nn 08:1421, 271
\__hook_label_ordered:nnTF .....
    08:1384, 08:1391, 08:1398, 08:1421, 269
\__hook_label_ordered_p:nn . 08:1421
\__hook_label_pair:nn .....
    ..... 08:1819, 08:1820,
    08:1383, 08:1390, 08:1397, 08:1402,
    08:1407, 08:1412, 08:1413, 08:1413, 269
\l__hook_labels_int .... 08:1565,
    08:1575, 08:1579, 08:1611, 08:1633,
    08:1657, 08:1661, 08:1697, 08:1722, 277
\l__hook_labels_seq .....
    08:1825, 08:1565, 08:1574, 08:1580,
    08:1598, 08:1656, 08:1662, 08:1681
\__hook_list_if_rule_exists:nnnTF
    .. 08:2101, 08:2121, 08:2122, 08:2124
\__hook_list_one_rule:nnn .....
    .. 08:2101, 08:2112, 08:2113, 08:2119
\__hook_list_rules:nn .. 08:1930,
    08:2030, 08:2101, 08:2101, 08:2138, 288
\__hook_log:nN .. 08:1835, 08:1838,
    08:1845, 08:1852, 08:1859, 08:1861,
    08:1866, 08:1977, 08:1979, 08:1984
\__hook_log_cmd:n .....
    ..... 08:1837, 08:1844, 08:1851,
    08:1856, 08:1858, 08:1870, 08:1988
\__hook_log_line:n 08:1835, 08:1855,
    08:1886, 08:1888, 08:1892, 08:1906,
    08:1918, 08:1928, 08:1946, 08:1965,
    08:1992, 08:1994, 08:1998, 08:2006,
    08:2020, 08:2028, 08:2046, 08:2067
\__hook_log_line_indent:n .....
    ..... 08:1835, 08:1857,
    08:1896, 08:1902, 08:1912, 08:1919,
    08:1933, 08:1941, 08:2000, 08:2003,
    08:2013, 08:2021, 08:2033, 08:2041
\__hook_log_next_code:n . 08:2025,
    08:2080, 08:2080, 08:2085, 08:2087
\__hook_log_next_code:w .....
    ..... 08:1924, 08:2083
\__hook_make_name:n .....
    ..... 08:357, 08:363, 08:372,
    08:378, 08:378, 08:432, 08:475, 243
\__hook_make_name:w .....
    ..... 08:378, 08:380, 08:384
\__hook_make_prefixes:w .....
    09:171, 09:224, 09:299, 09:320, 09:325
\__hook_make_usable:n .....
    . 08:97, 08:133, 08:318, 08:817, 08:850
\__hook_make_usable:nn .....
    ..... 09:228, 09:521, 08:81,
    08:102, 08:102, 08:104, 08:130,
    08:132, 08:300, 08:760, 08:763, 236
\__hook_misused_if_replacing_-
    args:nn .. 08:2582, 08:2583, 08:2589
\__hook_msg_pair_found:nnn .....
    08:1762, 08:1769, 08:1776, 08:1784,
    08:1792, 08:1803, 08:1816, 08:1816
\g__hook_name_stack_seq .....
    .. 08:32, 08:418, 08:419, 08:423,
    08:430, 08:444, 08:451, 08:459, 08:469
\__hook_new:n ... 08:89, 08:91, 08:193
\__hook_new:nn ..... 08:67, 08:70,
    08:72, 08:73, 08:90, 08:181, 08:213
\__hook_new_pair:nnn .....
    ..... 08:202, 08:204, 08:205
\__hook_new_reversed:n 08:189, 08:191

```

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

```

\__hook_new_reversed:nn .....
..... 08:170, 08:173,
08:175, 08:176, 08:190, 08:196, 08:214
\__hook_next_⟨hook⟩ ..... 258
\__hook_next_gset:nn .....
08:2207, 08:2232, 08:2441, 08:154,
08:987, 08:1106, 08:1112, 08:1126
\c__hook_nine_parameters_tl ....
..... 08:1901,
08:35, 08:114, 08:1077, 08:1192
\__hook_normalise_code_pool:n ...
..... 08:120, 08:1153,
08:1153, 08:1155, 08:1205, 08:1207, 236
\__hook_normalise_cs_args:nn ...
..... 08:116, 08:117, 08:1129,
08:1129, 08:1131, 08:1149, 08:1151, 236
\__hook_normalise_fn:nn .....
08:581, 08:1159, 08:1178, 08:1203, 263
\__hook_normalize_hook_args:Nn ..
..... 08:1838, 08:1845, 08:1852,
08:2154, 08:2168, 08:2183, 08:2228,
08:2383, 08:2389, 08:2398, 08:2883,
08:70, 08:72, 08:89, 08:173, 08:175,
08:189, 08:267, 08:291, 08:385, 08:394
\__hook_normalize_hook_args:Nnn .
..... 08:202, 08:204, 08:385,
08:399, 08:491, 08:497, 08:599, 08:978
\__hook_normalize_hook_args_-
aux:Nn .....
08:385, 08:385, 08:396, 08:401, 08:409
\__hook_normalize_hook_rule_-
args:Nnnnn . 08:385, 08:407, 08:1322
\l__hook_param_text_tl .....
..... 09:8, 09:192,
09:213, 09:267, 09:288, 09:317, 323
\__hook_parameter:n .....
08:1880, 08:1117, 08:1175, 08:1287,
08:1287, 08:1289, 08:1304, 08:1306
\c__hook_parameter_cmd 08:967, 08:972
\c__hook_parameter_cmd/.after_-
tl ..... 08:967
\c__hook_parameter_cmd/.before_-
tl ..... 08:967
\__hook_parse_dot_label:nN .....
..... 08:334, 08:336, 08:336
\__hook_parse_dot_label:w .....
..... 08:336, 08:348, 08:351
\__hook_parse_dot_label_aux:w ...
..... 08:336, 08:354, 08:362
\__hook_parse_dot_label_cleanup:w
..... 08:336, 08:358, 08:361
\__hook_parse_label_default:nN ..
..... 08:330, 08:330, 08:397,
08:403, 08:404, 08:411, 08:412, 08:414
\__hook_patch_check:NNnn .....
.. 09:94, 09:98, 09:101, 09:104, 09:114
\__hook_patch_cmd_or_delay:Nnn ..
..... 09:33,
09:46, 09:59, 09:63, 09:63, 09:73, 318
\__hook_patch_command:Nnn .....
..... 09:73, 09:91, 09:94, 09:94, 319
\__hook_patch_debug:n .....
09:18, 09:18, 09:96, 09:97, 09:100,
09:103, 09:106, 09:175, 09:250,
09:389, 09:425, 09:428, 09:429,
09:434, 09:444, 09:447, 09:448, 09:453
\__hook_patch_DeclareRobustCommand:Nnn
..... 09:143, 09:147, 09:147, 321
\__hook_patch_DeclareRobustCommand_-
aux:Nnn ..... 09:149, 09:152
\__hook_patch_expand_redefine:NNnn
..... 09:158,
09:163, 09:168, 09:171, 09:171,
09:173, 09:246, 09:248, 09:387, 329
\__hook_patch_newcommand:Nnn ...
.. 09:144, 09:157, 09:161, 09:161, 321
\l__hook_patch_num_args_int ....
..... 09:7, 09:176,
09:181, 09:184, 09:198, 09:228,
09:237, 09:251, 09:256, 09:259,
09:273, 09:518, 09:521, 09:541, 09:548
\l__hook_patch_prefixes_tl .....
.... 09:8, 09:223, 09:298, 09:315, 326
\__hook_patch_required_catcodes:
..... 09:459,
09:459, 09:480, 09:556, 09:584, 334
\__hook_patch_retokenize:Nnnn ...
..... 09:430, 09:449, 09:514,
09:514, 09:516, 09:561, 09:563, 330
\__hook_post_initialization_-
defs: . 08:2334, 08:2334, 08:2336,
08:2341, 08:2344, 08:2346, 08:1460
\__hook_preamble_hook:n .....
..... 08:1869, 08:1987, 08:2239,
08:2243, 08:2254, 08:2267, 08:2277,
08:2287, 08:2306, 08:2315, 08:2340,
08:2373, 08:2408, 08:2427, 08:1483, 291
\__hook_print_args:n ..... 08:2090
\__hook_print_args:nn 08:1877, 08:2090
\__hook_prop_gput_labeled_-
cleanup:nnn . 08:486, 08:546, 08:572
\__hook_prop_gput_labeled_do:Nnn
..... 08:586, 08:589
\__hook_prop_gput_labeled_-
do:Nnnn ..... 08:486
\l__hook_rear_tl .....
..... 08:1565, 08:1596, 08:1602,

```

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

08:1603, 08:1626, 08:1627, 08:1679,  
 08:1687, 08:1688, 08:1715, 08:1716  
 \\_\_hook\_redefine\_with\_hooks:Nnnn  
 .. 09:171, 09:231, 09:303, 09:313, 324  
 \l\_\_hook\_replace\_text\_tl .....  
 ..... 09:8, 09:193, 09:200,  
 09:201, 09:202, 09:207, 09:214,  
 09:241, 09:268, 09:275, 09:276,  
 09:277, 09:282, 09:289, 09:309, 323  
 \\_\_hook\_replacement\_spec:N .....  
 ..... 08:1213, 08:1219  
 \\_\_hook\_replacing\_args\_false: ...  
 08:2153, 08:2410, 08:2582, 08:2596,  
 08:237, 08:490, 08:658, 08:1446, 250  
 \\_\_hook\_replacing\_args\_reset: ...  
 08:2163, 08:2177, 08:2413, 08:2582,  
 08:2602, 08:243, 08:492, 08:498, 08:1449  
 \\_\_hook\_replacing\_args\_true: ...  
 ..... 08:2167,  
 08:2582, 08:2590, 08:496, 08:1447  
 \g\_\_hook\_replacing\_stack\_seq 08:2582  
 \\_\_hook\_retokenize\_patch:Nnn ...  
 ..... 09:109, 09:384, 09:384  
 \l\_\_hook\_return\_tl .....  
 .. 08:2604, 08:2605, 08:25, 08:451,  
 08:452, 08:459, 08:463, 08:574,  
 08:582, 08:587, 08:591, 08:592,  
 08:637, 08:640, 08:994, 08:1029,  
 08:1612, 08:1613, 08:1699, 08:1700  
 \\_\_hook\_rollback\_tiding: .. 08:2964  
 \\_\_hook\_rule<\_gset:nnn .... 08:1380  
 \\_\_hook\_rule>\_gset:nnn .... 08:1380  
 \\_\_hook\_rule\_after\_gset:nnn ....  
 ..... 08:1380, 08:1387, 08:1393  
 \\_\_hook\_rule\_before\_gset:nnn ...  
 ..... 08:1380, 08:1380, 08:1386, 276  
 \\_\_hook\_rule\_gclear:nnn .....  
 08:1343, 08:1368, 08:1410, 08:1411, 270  
 \\_\_hook\_rule\_incompatible-error\_-  
 gset:nnn ..... 08:1400  
 \\_\_hook\_rule\_incompatible-warning\_-  
 gset:nnn ..... 08:1400  
 \\_\_hook\_rule\_unrelated\_gset:nnn .  
 ..... 08:1410, 08:1410, 270  
 \\_\_hook\_rule\_voids\_gset:nnn ....  
 ..... 08:1394, 08:1394  
 \\_\_hook\_seq\_csname:n ... 08:1765,  
 08:1772, 08:1830, 08:1563, 08:1564,  
 08:1582, 08:1616, 08:1664, 08:1705  
 \\_\_hook\_set\_default\_hook\_label:n  
 ..... 08:2816, 08:467, 08:467  
 \\_\_hook\_set\_default\_label:n .....  
 ..... 08:467, 08:475, 08:477  
 \\_\_hook\_set\_normalise\_fn:nn ....  
 08:579, 08:1153, 08:1157, 08:1162, 263  
 \\_\_hook\_str\_compare:nn .....  
 08:23, 08:23, 08:1415, 08:1423, 08:1432  
 \\_\_hook\_strip\_double\_slash:n ...  
 ..... 08:916, 08:922, 08:923  
 \\_\_hook\_strip\_double\_slash:w ...  
 ..... 08:916, 08:924, 08:925, 08:929  
 \\_\_hook\_tl\_csname:n .....  
 08:1763, 08:1764, 08:1770, 08:1771,  
 08:1829, 08:1563, 08:1563, 08:1569,  
 08:1581, 08:1597, 08:1600, 08:1602,  
 08:1606, 08:1618, 08:1620, 08:1623,  
 08:1626, 08:1631, 08:1663, 08:1680,  
 08:1684, 08:1686, 08:1691, 08:1707,  
 08:1709, 08:1712, 08:1714, 08:1720  
 \\_\_hook\_tl\_gclear:N .... 08:2450,  
 08:2451, 08:2452, 08:64, 08:64,  
 08:66, 08:244, 08:259, 08:1021,  
 08:1022, 08:1026, 08:1607, 08:1692  
 \\_\_hook\_tl\_gput:Nn 08:1511, 08:1513,  
 08:1544, 08:1548, 08:1613, 08:1640,  
 08:1700, 08:1729, 08:1735, 08:1735, 277  
 \\_\_hook\_tl\_gput\_left:Nn .....  
 ..... 08:58, 08:58, 08:1511, 08:1545  
 \\_\_hook\_tl\_gput\_right:Nn 08:2224,  
 08:55, 08:55, 08:57, 08:631, 08:1513,  
 08:1549, 08:1642, 08:1731, 08:1733  
 \\_\_hook\_tl\_gset:Nn .....  
 ..... 08:2223, 08:2437, 08:2975,  
 08:49, 08:49, 08:51, 08:53, 08:54,  
 08:56, 08:60, 08:1382, 08:1389,  
 08:1396, 08:1401, 08:1406, 08:1536  
 \\_\_hook\_tl\_gset\_eq:NN .....  
 ..... 08:63, 08:63, 08:65  
 \\_\_hook\_tl\_set:Nn ..... 08:47,  
 08:47, 08:1168, 08:1581, 08:1663, 231  
 \\_\_hook\_tmp:w .....  
 ..... 08:1900, 08:1903, 08:2105,  
 08:2127, 08:2136, 08:2147, 08:2973,  
 08:2990, 08:2991, 09:190, 09:196,  
 09:197, 09:199, 09:265, 09:271,  
 09:272, 09:274, 09:471, 09:474,  
 09:478, 09:530, 09:533, 09:554,  
 09:566, 09:569, 09:582, 08:34, 08:34,  
 08:420, 08:424, 08:426, 08:1164,  
 08:1175, 08:1191, 08:1197, 08:1200, 333  
 \l\_\_hook\_tmpa\_bool ..... 08:1929,  
 08:1932, 08:1940, 08:1949, 08:2029,  
 08:2032, 08:2040, 08:2049, 08:24, 284  
 \l\_\_hook\_tmpa\_tl .. 09:183, 09:185,  
 09:187, 09:258, 09:260, 09:262,  
 09:390, 09:406, 09:409, 09:477,  
 09:480, 09:522, 09:526, 09:542,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

09:549, 09:553, 09:556, 09:581, 09:584, 08:25, 08:430, 08:1176, 08:1198	\_hook_use_initialized:nnw . . . . .
\_hook_tmptb_tl . . . . . 09:395, 09:407, 09:410, 08:25, 08:1165, 08:1172, 08:1200	.. 08:2311, 08:2316, 08:2318, 08:2339
\_hook_toplevel_\hook . . . . . 247	\_hook_use_none_delimit_by_s_- mark:w . . . . . 08:2458, 08:2525, 09:507, 08:45, 08:45, 08:1334, 08:1340
\_hook_toplevel_gset:nn . . . . .	\_hook_use_once:n . . . . . 08:2398, 08:2425
.. . . . . 08:2442, 08:153, 08:986, 08:991, 08:1106, 08:1110, 08:1125	\_hook_use_once:nn . . . . .
\_hook_try_declaring_generic_- hook:nnn . . . . . 08:526, 08:614, 08:673, 08:674, 08:676, 08:692, 08:694, 08:713, 08:716, 251	.. . . . . 08:2383, 08:2389, 08:2404, 08:2404, 08:2406, 08:2423, 08:2432
\_hook_try_declaring_generic_- hook:nnNnn . . . . .	\_hook_use_once_clear:n . . . . .
.. 08:718, 08:724, 08:727, 08:727, 250	.. . . . . 08:2412, 08:2430, 08:2434, 08:2434, 08:2438, 08:2446, 08:2448, 296
\_hook_try_declaring_generic_- hook:wn . . . . . 08:747, 08:750, 08:805, 08:808, 08:835, 08:838, 08:867, 08:870	\_hook_use_once_set:n . . . . .
\_hook_try_declaring_generic_- hook:wnTF 08:678, 08:685, 08:696, 08:705, 08:740, 08:746, 08:799, 253	08:2409, 08:2428, 08:2434, 08:2436, 296
\_hook_try_declaring_generic_- hook_split:nnNnn . . . . .	\_hook_use_undefined:w . . . . .
.. . . . . 08:727, 08:732, 08:735, 08:738	.. . . . . 08:2296, 08:2300
\_hook_try_declaring_generic_- next_hook:nn . . . . . 08:2194, 08:673, 08:683, 08:703, 08:722, 251	\_hook_used_prop . . . . .
\_hook_try_file_hook:n . . . . .	.. . . . . 08:31, 08:1442, 08:1454, 08:1469, 08:1475, 08:1519, 08:1557
.. . . . . 08:2348, 08:2356, 08:2359, 294	\_hook_work_prop . . . . . 08:1797, 08:1808, 08:30, 08:582, 08:1158, 08:1160, 08:1194, 08:1515, 08:1552, 08:1577, 08:1584, 08:1586, 08:1595, 08:1612, 08:1637, 08:1659, 08:1666, 08:1668, 08:1678, 08:1698, 08:1726, 276
\_hook_try_patch_with_catcodes:Nnnnw .. . . . . 09:403, 09:420, 09:420, 09:422, 09:435, 09:439, 09:441, 09:454, 329	hook_?? internal commands: \_hook_?? . . . . . 267
\_hook_try_put_cmd_hook:n . . . . .	hook_\hook internal commands: \_hook_\hook . . . . . 232
. 09:21, 09:21, 09:23, 09:38, 09:40, 09:49, 09:51, 08:759, 08:816, 08:849	\hookleftarrow . . . . . 30:491
\_hook_try_put_cmd_hook:w 09:21, 09:24, 09:25, 09:41, 09:42, 09:52, 09:53	\hookrightarrow . . . . . 30:489
\_hook_unpatchable_cases:n . . . . .	Hooks: build/column/after . . . . . 54:731 build/column/before . . . . . 54:731 build/page/after . . . . . 54:729 build/page/before . . . . . 54:729 build/page/reset . . . . . 54:730
.. . . . . 09:609, 09:611	hook ?? internal commands: \_hook-?? . . . . . 08:1309
\_hook_update_hook_code:n . . . . .	\hphantom . . . . . 38:75
.. . . . . 08:2205, 08:2221, 09:243, 09:558, 08:82, 08:303, 08:321, 08:521, 08:609, 08:999, 08:1035, 08:1347, 08:1372, 08:1436, 08:1436, 08:1441, 08:1448, 08:1467, 08:1471, 247	\hrule . . . . . 18:397, 18:405, 18:431, 18:439, 21:309, 21:314, 30:351, 30:629, 40:202, 40:207, 40:280, 40:290, 41:359, 41:376, 42:589, 42:599, 45:395, 02:377, 02:421, 906
\_hook_use:wn . . . . . 08:2290, 08:2304, 08:2348, 08:2348, 08:2351, 08:2353, 294	\hrulefill . . . . . 06:976, 06:997, 02:421
\_hook_use_end: . . . . .	\hsize . . . . . 1348
.. . . . . 08:2298, 08:2301, 08:2308	\hskip . . . . . 1321
\_hook_use_i_delimit_by_s_- mark:nw . . . . . 08:45, 08:46, 08:1239	\hskip... . . . . . 1344
\_hook_use_initialized:n 08:2239, 08:2244, 08:2246, 08:2271, 08:2292, 08:2338, 08:2415, 08:2429, 08:1482, 291	\hspace . . . . . 18:512, 18:516, 18:522, 451
	\hss . . . . . 1159
	\Hwithstroke . . . . . 21:517, 21:1237, 1359
	\hwithstroke . . . . . 21:533, 21:1238, 1359
	\hyphenation . . . . . 21:225, 1328

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- \hyphenchar . . . . . 37:566, 06:934, 06:937,  
06:946, 06:949, 06:952, 06:957, 110
- \hyphenpenalty . . . . . 24:760, 24:792, 02:191
- I**
- \I . . . . . 50:1343, 50:1475,  
50:1565, 50:1585, 57:255, 57:550, 02:312
- \i . . . . . 21:267, 21:423,  
21:473, 21:474, 21:475, 21:476,  
21:477, 21:478, 21:479, 21:570,  
21:610, 21:611, 21:703, 21:705,  
21:707, 21:709, 21:737, 21:802,  
21:1164, 21:1319, 21:1321, 21:1323,  
21:1325, 21:1376, 21:1379, 21:1382,  
21:1385, 21:1455, 57:259, 57:554, 1350
- \ialign . . . . . 30:348,  
30:470, 30:541, 30:544, 30:548,  
30:551, 38:168, 38:170, 38:189,  
41:191, 42:141, 02:409, 02:411, 1309
- \IeC . . . . . 57:357, 57:361, 57:468
- \if . . . . . 1343
- if commands:
- \if:w . . . . . 08:2459, 08:2473, 08:2526, 08:2558,  
09:360, 08:1053, 08:1213, 08:1238, 296
- \if\_case:w . . . . . 07:1502, 08:1264, 08:1415, 08:1432
- \if\_catcode:w . . . . . 09:369,  
07:1838, 07:1839, 07:1840, 07:1841, 328
- \if\_charcode:w . . . . . 08:2576, 07:983
- \if\_cs\_exist:N . . . . . 48:101
- \if\_cs\_exist:w . . . . . 08:2126,  
08:2248, 08:2256, 08:2273, 08:2294,  
08:2321, 08:2460, 08:784, 08:1746
- \if\_false: . . . . . 07:902, 07:905, 07:2670, 07:2674
- \if\_int\_compare:w . . . . . 16:101, 08:1423
- \if\_meaning:w . . . . . 09:357, 09:361, 09:362, 52:241, 07:1340
- \if\_mode... . . . . . 425
- \if\_mode\_horizontal: . . . . . 16:32, 16:64
- \if... . . . . . 1105
- \IfBlankF . . . . . 07:3300
- \IfBlankT . . . . . 07:3300
- \IfBlankTF . . . . . 47:19, 07:3300, 1372
- \IfBold . . . . . 720
- \IfBooleanF . . . . . 22:134, 22:149, 22:187, 22:199, 07:3275
- \IfBooleanT . . . . . 07:3275
- \IfBooleanTF . . . . . 17:37,  
35:67, 35:69, 35:164, 07:3275, 198
- \IfClassAtLeastF . . . . . 50:283
- \IfClassAtLeastT . . . . . 50:283
- \IfClassAtLeastTF . . . . . 1053
- \IfClassAtLeastTF . . . . . 50:165, 50:293, 50:294, 50:322, 50:323
- \IfClassLoadedF . . . . . 50:283
- \IfClassLoadedT . . . . . 50:283
- \IfClassLoadedTF . . . . . 1053
- \IfClassLoadedTF . . . . . 50:263, 50:289, 50:290, 50:318, 50:319
- \IfClassLoadedWithOptionsF . . . . . 50:283
- \IfClassLoadedWithOptionsT . . . . . 50:301, 50:330
- \IfClassLoadedWithOptionsTF . . . . . 1053
- \IfClassLoadedWithOptionsTF . . . . . 50:263, 50:283
- \ifcoremisses . . . . . 33:1186, 33:1377
- \ifcsname . . . . . 21:11, 21:210, 24:403,  
25:2828, 25:2831, 25:3173, 25:3176,  
26:129, 28:154, 29:43, 29:54, 29:76,  
29:87, 33:1212, 06:832, 50:1228,  
06:849, 50:1363, 53:439, 54:2479, 1381
- \ifdefined . . . . . 05:26,  
05:75, 05:76, 05:77, 05:78, 05:121,  
05:122, 05:123, 29:706, 57:319,  
57:676, 57:681, 02:217, 02:444, 02:508
- \IfDocumentMetadataF . . . . . 17:7, 17:13, 50:772, 50:778
- \IfDocumentMetadataT . . . . . 17:6, 17:12
- \IfDocumentMetadataTF . . . . . 17:5, 17:11, 1384
- \IfExplAtLeastF . . . . . 77
- \IfExplAtLeastF . . . . . 05:207, 05:215
- \IfExplAtLeastT . . . . . 77
- \IfExplAtLeastT . . . . . 05:206, 05:214
- \IfExplAtLeastTF . . . . . 77
- \IfExplAtLeastTF . . . . . 05:202,  
05:211, 05:213, 05:214, 05:215, 77
- \iff . . . . . 30:511
- \IfFileAtLeastF . . . . . 50:283
- \IfFileAtLeastT . . . . . 50:283
- \IfFileAtLeastTF . . . . . 1053
- \IfFileAtLeastTF . . . . . 50:165,  
50:295, 50:296, 50:324, 50:325, 1375
- \IfFileExists . . . . . 454, 1054
- \IfFileExists . . . . . 20:488,  
20:500, 20:636, 20:692, 20:717,  
01:162, 05:41, 05:72, 05:118, 50:933,  
52:149, 52:185, 52:195, 57:684, 1316
- \IfFileLoadedF . . . . . 50:303
- \IfFileLoadedT . . . . . 50:303
- \IfFileLoadedTF . . . . . 50:303, 1378
- \iffontchar . . . . . 21:890, 21:1084, 21:1189, 21:1191,  
21:1193, 21:1240, 33:1182, 33:1183
- \IfFontSeriesContextF . . . . . 29:595, 29:617
- \IfFontSeriesContextT . . . . . 29:594, 29:616
- \IfFontSeriesContextTF . . . . . 29:575, 29:613, 29:615, 720

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- \IfFormatAtLeastF ..... 50:283
- \IfFormatAtLeastT ..... 50:283
- \IfFormatAtLeastTF ..... 1053
- \IfFormatAtLeastTF ..... 50:165,  
50:297, 50:298, 50:326, 50:327, 1126
- \IfHookEmptyF ..... 08:2850, 212
- \IfHookEmptyT ..... 08:2850, 212
- \IfHookEmptyTF .....  
. 08:2850, 08:2955, 37:351, 37:368, 307
- \IfHookExistsTF ... 08:2853, 08:2954, 307
- \ifincsn ..... 18:475, 06:297, 06:318, 91
- \ifinner ..... 18:239,  
18:290, 38:277, 38:285, 38:324,  
38:350, 38:376, 45:57, 45:126, 45:315
- \IfInstanceExistsF ..... 11:1223, 359
- \IfInstanceExistsT ..... 11:1223, 359
- \IfInstanceExistsTF ..... 11:1223, 359
- \IfLabelExistsF ..... 36:181, 818
- \IfLabelExistsT ..... 36:181, 818
- \IfLabelExistsTF .... 36:181, 36:276, 818
- \IfLabelExistTF ..... 1379
- \IfMarksEqualF ..... 48:408, 1016
- \IfMarksEqualT ..... 48:408, 1016
- \IfMarksEqualTF .... 48:408, 48:525, 1016
- \ifmmode ..... 1304
- \IfNoValueF ..... 07:3294
- \IfNoValueT ..... 07:3294
- \IfNoValueTF .....  
36:120, 57:635, 57:642, 57:649, 07:3294
- \ifnum ..... 1144
- \ifodd . 28:1228, 42:320, 42:344, 42:378,  
42:400, 45:68, 45:137, 54:17, 54:117,  
54:890, 54:964, 54:1022, 54:1332,  
54:1335, 54:1368, 54:1371, 54:1483,  
54:1486, 54:1632, 54:1635, 54:1789,  
54:1792, 54:2150, 54:2153, 54:2271,  
54:2274, 54:2394, 54:2659, 54:2667
- \IfPackageAtLeastF ..... 50:283
- \IfPackageAtLeastT ..... 50:283
- \IfPackageAtLeastTF ..... 1053
- \IfPackageAtLeastTF .....  
50:165, 50:291, 50:292, 50:320, 50:321
- \IfPackageLoadedF ..... 50:283
- \IfPackageLoadedT ..... 50:283
- \IfPackageLoadedTF ..... 1053
- \IfPackageLoadedTF .....  
50:263, 50:287, 50:288, 50:316, 50:317
- \IfPackageLoadedWithOptionsF ... 50:283
- \IfPackageLoadedWithOptionsT ... 50:283
- \IfPackageLoadedWithOptionsTF ... 1053
- \IfPackageLoadedWithOptionsTF .....  
50:263, 50:299, 50:300, 50:328, 50:329
- \IfPDFManagementActiveF ..... 57:745
- \IfPDFManagementActiveT ..... 57:744
- \IfPDFManagementActiveTF ... 57:743, 1384
- \IfPropertyExistsF ..... 36:166, 818
- \IfPropertyExistsT ..... 36:166, 818
- \IfPropertyExistsTF . 36:166, 36:275, 1379
- \IfPropertyExistTF ..... 1379
- \IfPropertyRecordedF ..... 36:196, 1381
- \IfPropertyRecordedT ..... 36:196, 1381
- \IfPropertyRecordedTF 36:196, 36:277, 818
- \ifsafesubencodingfound .....  
.. 33:1185, 33:1199, 33:1204, 33:1373
- \IfSocketExistsF ..... 10:190, 10:216
- \IfSocketExistsT ..... 10:190, 10:215
- \IfSocketExistsTF ... 10:190, 10:214, 344
- \IfSocketPlugAssignedF .. 10:190, 10:222
- \IfSocketPlugAssignedT .. 10:190, 10:221
- \IfSocketPlugAssignedTF .....  
10:190, 10:220, 344
- \IfSocketPlugExistsF .... 10:190, 10:219
- \IfSocketPlugExistsT .... 10:190, 10:218
- \IfSocketPlugExistsTF 10:190, 10:217, 344
- \IfTargetDateBefore ..... 50:1801
- \ifthenelse ..... 809
- \IfValueF ..... 07:3297
- \IfValueT ..... 07:3297
- \IfValueTF ..... 07:3297
- \ifvbox ..... 54:324,  
54:381, 54:428, 54:499, 54:756, 54:821
- \ifvoid ..... 1346
- \ifx ..... 1362
- \ignoreprimitiverror ..... 1028
- \ignorespaces .....  
... 18:50, 18:144, 18:163, 18:175,  
18:186, 18:202, 18:215, 18:559,  
20:71, 20:139, 20:194, 21:90, 24:355,  
24:365, 24:375, 24:428, 28:317,  
28:356, 37:341, 37:358, 37:374,  
37:383, 37:432, 37:437, 37:443,  
38:332, 38:358, 38:384, 38:538,  
38:539, 39:55, 39:248, 40:193,  
40:490, 40:507, 40:524, 41:57,  
41:62, 41:68, 41:83, 41:92, 41:105,  
41:109, 41:116, 41:123, 41:125,  
41:134, 41:154, 41:237, 41:301,  
41:303, 41:305, 41:332, 42:36, 42:46,  
42:66, 42:75, 42:109, 42:120, 42:131,  
42:143, 42:148, 42:154, 43:43, 43:45,  
44:110, 45:17, 45:24, 45:477, 45:495,  
45:513, 47:7, 47:9, 53:330, 1341
- \ignorespacesafterend ..... 37:7
- \IJ ..... 21:270,  
21:457, 21:573, 21:1165, 57:671, 1370
- \ij ..... 21:269,  
21:455, 21:572, 21:1166, 57:671, 1370
- \Im ..... 30:325

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\imath</code> .....	30:320	22:220, 22:252, 22:268, 22:276,
<code>\immediate</code> .....	1160	22:294, 23:5, 23:11, 23:19, 23:26,
<code>\in</code> .....	30:440, 30:472	24:25, 24:54, 24:206, 24:228, 24:273,
in commands:		24:295, 24:347, 24:358, 24:368,
<code>in_callback</code> .....	04:959	24:424, 24:439, 24:517, 24:528,
<code>\in_callback</code> .....	44	24:536, 24:568, 24:576, 24:590,
<code>\include</code> .....	454	24:611, 24:647, 24:734, 24:798,
<code>\include</code> .....	20:237, 20:285, 20:287,	25:3, 25:1432, 25:2773, 25:2780,
	20:303, 20:305, 20:364, 20:416, 224	25:2792, 25:2804, 25:2812, 25:2894,
<code>include/.../after</code> .....	1118	25:2910, 25:2931, 25:2946, 25:3048,
<code>include/.../before</code> .....	1118	25:3129, 25:3133, 25:3143, 25:3150,
<code>include/.../end</code> .....	1118	25:3158, 25:3230, 25:3249, 25:3255,
<code>include/after</code> .....	1118	25:3259, 26:114, 26:159, 26:162,
<code>include/before</code> .....	1118	26:558, 26:567, 27:2, 27:22, 28:50,
<code>include/end</code> .....	1118	28:79, 05:2, 28:139, 28:181, 28:211,
<code>\IncludeInRelease</code> ...	02:561, 02:566,	05:14, 28:242, 28:276, 05:24, 28:323,
	08:1859, 02:576, 08:1977, 08:2080,	28:369, 28:418, 28:470, 28:483,
	08:2085, 08:2149, 08:2180, 08:2198,	28:489, 28:529, 28:577, 28:604,
	08:2211, 08:2229, 08:2234, 08:2239,	28:629, 05:62, 28:862, 28:910,
	08:2261, 08:2281, 08:2311, 08:2329,	28:956, 28:965, 28:1149, 28:1160,
	08:2334, 08:2344, 08:2348, 08:2351,	05:116, 29:34, 29:69, 05:137, 29:102,
	08:2378, 08:2393, 08:2404, 08:2423,	29:127, 29:144, 29:160, 05:152,
	08:2434, 08:2446, 08:2469, 08:2486,	29:233, 29:286, 29:297, 29:321,
	08:2552, 08:2568, 08:2625, 08:2654,	29:331, 29:380, 29:427, 05:163,
	03:71, 08:2762, 08:2771, 08:2777,	29:456, 29:474, 05:173, 29:514,
	08:2784, 08:2789, 08:2796, 08:2800,	29:548, 29:577, 29:612, 29:626,
	08:2807, 08:2827, 08:2834, 08:2928,	05:182, 29:660, 29:673, 29:704,
	09:21, 09:38, 09:49, 09:171, 09:246,	29:713, 29:738, 05:196, 29:770,
	09:420, 09:439, 09:485, 09:510,	29:786, 29:802, 29:819, 29:836,
	09:514, 03:180, 09:561, 09:588,	29:842, 05:203, 05:210, 30:75, 30:93,
	09:591, 03:184, 09:621, 03:188,	30:112, 30:121, 05:218, 05:225, 06:5,
	03:192, 10:200, 04:3, 11:1249,	06:13, 30:633, 30:645, 32:27, 32:34,
	14:138, 14:158, 14:192, 14:205,	06:56, 06:62, 33:571, 06:74, 06:83,
	16:12, 16:45, 16:167, 17:25, 17:49,	06:136, 06:149, 35:12, 35:29, 35:46,
	17:63, 18:5, 18:22, 18:55, 18:66,	35:62, 35:76, 35:96, 35:112, 35:116,
	18:82, 18:87, 18:99, 18:105, 18:133,	35:146, 35:155, 35:167, 35:177,
	18:153, 18:167, 18:179, 18:192,	35:189, 35:200, 36:265, 37:10, 37:78,
	18:207, 18:236, 18:251, 18:267,	37:142, 37:184, 37:189, 37:201,
	18:286, 18:320, 18:354, 18:380,	37:228, 37:247, 37:269, 37:297,
	18:413, 18:471, 18:482, 18:489,	37:314, 37:336, 37:347, 37:363,
	18:495, 18:501, 18:507, 18:515,	37:377, 37:385, 37:396, 37:404,
	18:521, 18:535, 18:541, 04:235,	37:417, 37:423, 37:435, 37:440,
	20:10, 20:84, 20:142, 04:258, 20:209,	01:274, 37:450, 37:469, 06:259,
	20:222, 20:239, 20:276, 20:297,	37:486, 37:502, 37:513, 37:527,
	20:312, 20:373, 04:281, 20:422,	06:266, 37:549, 37:576, 37:592,
	20:483, 20:493, 20:519, 20:551,	37:605, 37:619, 37:631, 37:637,
	20:573, 20:591, 20:601, 20:617,	37:643, 37:650, 37:668, 37:681,
	20:642, 20:647, 20:655, 20:669,	37:697, 37:720, 37:730, 06:291,
	20:680, 20:696, 20:729, 21:95,	38:79, 38:87, 38:109, 38:118, 38:137,
	21:122, 21:166, 21:187, 21:344,	38:144, 38:152, 38:157, 38:165,
	21:352, 21:373, 21:389, 22:26, 22:32,	38:176, 06:307, 38:216, 38:233,
	22:39, 22:60, 22:79, 22:89, 22:95,	38:272, 38:280, 38:291, 38:297,
	22:121, 22:129, 22:143, 22:157,	38:307, 38:336, 38:361, 38:396,
	22:173, 22:182, 22:194, 22:205,	38:403, 38:422, 38:450, 38:492,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

38:501,	38:534,	38:542,	38:555,	52:357,	52:365,	06:968,	52:389,
38:567,	38:579,	38:588,	01:21,	52:408,	52:433,	52:479,	52:495,
39:125,	39:135,	39:143,	39:162,	52:506,	52:533,	06:988,	53:3,
06:376,	40:4,	40:14,	40:42,	53:476,	53:488,	53:497,	53:511,
40:71,	40:91,	40:112,	40:122,	54:130,	54:158,	54:184,	54:350,
40:142,	40:147,	40:156,	40:164,	54:371,	54:376,	54:424,	54:488,
01:291,	40:220,	40:228,	40:241,	54:734,	54:842,	54:946,	54:1005,
40:261,	40:299,	40:308,	40:327,	54:1144,	54:1162,	54:1223,	54:1244,
40:355,	40:378,	06:418,	40:400,	54:1280,	54:1304,	54:1416,	54:1568,
40:477,	40:495,	40:511,	40:531,	54:1712,	54:1881,	07:228,	54:1964,
40:537,	40:557,	40:565,	40:595,	54:2044,	07:242,	54:2138,	54:2260,
40:606,	06:446,	41:60,	41:65,	54:2474,	54:2497,	54:2511,	54:2539,
41:157,	41:222,	41:227,	06:474,	54:2601,	54:2606,	54:2724,	54:2774,
06:481,	42:10,	42:16,	42:26,	54:2835,	54:2853,	54:2872,	54:2902,
42:55,	42:69,	42:80,	42:89,	54:2943,	55:425,	57:8,	57:16,
42:100,	42:112,	42:146,	42:151,	57:30,	57:37,	57:52,	57:71,
42:160,	42:172,	42:235,	06:514,	57:87,	57:106,	57:143,	57:166,
42:250,	42:311,	42:369,	42:455,	57:199,	57:288,	57:293,	57:314,
42:463,	42:472,	42:500,	42:530,	57:339,	57:348,	57:441,	57:674,
42:557,	42:571,	42:584,	42:595,	57:679,	07:1128,	07:1180,	07:1183,
42:607,	42:624,	42:644,	42:651,	07:1198,	07:1211,	07:1226,	07:1344,
42:685,	42:745,	06:552,	42:803,	07:1347,	07:1376,	07:1379,	07:1388,
42:819,	43:28,	43:34,	43:50,	07:1396,	07:1399,	07:1567,	02:226,
06:564,	44:5,	44:20,	44:161,	02:236,	07:2193,	07:2206,	07:2237,
44:174,	44:182,	44:196,	44:211,	07:2249,	07:2265,	02:329,	07:3153,
44:218,	44:227,	44:250,	45:35,	07:3206,	07:3300,	07:3306,	07:3322,
06:594,	45:105,	06:605,	45:206,	02:347,	08:67,	08:86,	08:102,
45:232,	45:280,	45:294,	45:335,	08:146,	08:158,	08:170,	08:186,
45:352,	45:406,	45:412,	45:420,	08:199,	08:219,	08:229,	08:249,
45:427,	45:434,	45:440,	06:630,	08:264,	08:282,	08:288,	08:308,
45:446,	45:463,	45:482,	45:499,	08:326,	08:486,	02:432,	08:596,
45:549,	45:559,	06:638,	47:14,	08:647,	08:664,	08:673,	08:691,
47:61,	47:77,	06:650,	06:657,	08:712,	08:746,	02:455,	08:804,
49:20,	49:35,	49:61,	49:82,	08:834,	08:866,	08:893,	08:896,
49:116,	50:18,	50:23,	50:36,	08:916,	08:919,	08:932,	08:950,
50:63,	50:87,	50:95,	50:101,	08:955,	08:958,	08:967,	08:972,
50:144,	50:167,	50:175,	50:187,	08:975,	08:1012,	08:1049,	08:1099,
50:200,	50:226,	50:245,	50:265,	08:1106,	02:489,	08:1122,	08:1129,
50:273,	50:285,	06:756,	50:313,	08:1149,	08:1153,	02:496,	08:1205,
50:345,	50:361,	50:375,	50:393,	08:1209,	08:1225,	08:1229,	08:1257,
50:406,	50:422,	50:442,	01:26,	08:1260,	08:1283,	08:1287,	08:1304,
50:465,	50:481,	06:773,	50:510,	08:1312,	08:1316,	08:1325,	08:1356,
50:524,	50:556,	50:574,	50:594,	02:521,	08:1437,	08:1463,	08:1490,
50:612,	50:631,	50:641,	50:651,	08:1524,	08:1570,	08:1652,	1354
50:663,	50:695,	50:706,	50:720,	\includeonly .....	454		
50:730,	50:784,	50:798,	50:813,	\includeonly .....	20:237,		
50:843,	50:870,	50:902,	06:822,	20:277,	20:279,	20:298,	20:299,
50:1054,	06:828,	50:1134,	50:1141,				463
50:1152,	50:1166,	50:1216,	50:1351,	\indent .....	18:538,	39:192,	41:81,
06:858,	50:1482,	06:899,	06:918,	\IndentBox .....	16:91,	16:171,	416
52:5,	52:15,	52:27,	06:929,	\index .....	1006		
52:144,	52:181,	52:192,	52:205,	\index 44:191,	44:200,	46:6,	46:18,
06:946,	52:249,	52:257,	52:268,	49:40,	49:51,	49:66,	49:74,
06:957,	52:299,	52:322,	52:343,	49:89,	49:97,	54:904,	54:974,
						54:1033,	1382
				\indexentry .....	46:15		

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- \inf ..... 38:25
- \infty ..... 30:327
- \initcatcodetable ..... 04:91
- \input ..... 454, 1054
- \input ..... 04:18, 20:652,
  - 01:158, 01:161, 26:16, 27:106,
  - 01:218, 05:112, 05:134, 29:880,
  - 29:890, 29:900, 30:10, 30:11, 30:12,
  - 30:13, 30:14, 30:23, 30:42, 30:43,
  - 30:44, 30:48, 30:49, 30:50, 30:51,
  - 30:52, 30:53, 30:58, 30:147, 30:148,
  - 30:149, 30:150, 06:22, 30:665,
  - 30:666, 30:667, 33:1090, 50:680,
  - 57:164, 57:178, 57:203, 57:281,
  - 57:325, 57:405, 57:689, 01:52, 1116
- \input@path ..... 6, 1
- input@path commands:
  - \input@path: ..... 01:223
- \inputencodingname .....
  - ..... 57:382, 57:404, 57:486, 1358
- \InputIfFileExists ..... 454, 1054
- \InputIfFileExists 17:9, 20:635, 20:658,
  - 20:673, 20:683, 20:693, 20:747,
  - 21:1570, 24:488, 29:872, 29:882,
  - 29:892, 33:806, 33:1173, 50:1019,
  - 50:1085, 52:143, 56:8, 57:275, 1081
- \inputlineno ..... 14:214, 01:311, 1318
- \insert ..... 45:465, 45:484, 45:502,
  - 54:820, 54:821, 54:2459, 02:129,
  - 02:165, 02:167, 02:170, 02:202, 414
- \InsertMark ..... 48:399, 48:521, 1015
- insertmark ..... 48:278, 1015
- \int ..... 30:359
- int commands:
  - \int\_add:Nn ..... 07:612, 07:1289
  - \int\_case:nnTF .... 55:9, 55:33, 55:43
  - \int\_compare:nNnTF 08:2092, 08:2098,
    - 08:2417, 08:2614, 09:181, 09:256,
    - 09:392, 09:505, 10:39, 11:46, 28:288,
    - 28:290, 28:342, 48:81, 48:283, 53:55,
    - 53:111, 53:142, 53:353, 53:364,
    - 53:372, 55:319, 55:328, 55:349,
    - 55:368, 55:371, 55:396, 55:403,
    - 55:414, 07:462, 07:607, 07:899,
    - 07:941, 07:2177, 07:2243, 07:2258,
    - 07:2526, 07:2528, 08:1600, 08:1622,
    - 08:1633, 08:1683, 08:1711, 08:1722
  - \int\_compare:nTF ..... 11:192
  - \int\_compare\_p:nNn .....
    - ..... 08:2961, 08:2962, 07:968
  - \int\_const:Nn ..... 10:37
  - \int\_decr:N ..... 07:541,
    - 07:587, 07:2176, 08:1611, 08:1697
  - \int\_div\_truncate:nn ..... 07:1438
- \int\_eval:n ..... 08:1764, 08:1771,
  - 08:1879, 11:363, 05:167, 53:355,
  - 07:2540, 08:1265, 08:1619, 08:1708
- \int\_gadd:Nn ..... 55:308, 55:409
- \int\_gdecr:N ..... 52:559, 55:380
- \int\_gincr:N 17:42, 48:284, 52:549,
  - 53:87, 53:102, 55:360, 55:377, 07:1112
- \int\_gset:Nn .....
  - ... 24:415, 28:295, 28:347, 52:545,
  - 55:321, 55:364, 55:386, 55:387, 55:406
- \int\_gzero:N ..... 48:285,
  - 55:355, 55:356, 55:361, 55:374, 55:383
- \int\_if\_odd:nTF ..... 48:439, 48:499
- \int\_if\_zero:nTF ..... 10:33
- \int\_incr:N ..... 07:364, 07:485,
  - 07:913, 07:994, 07:1001, 07:1256,
  - 07:1563, 07:2186, 08:1579, 08:1661, 150
- \int\_new:N ..... 09:7, 11:35, 17:28,
  - 48:278, 52:544, 07:16, 07:17, 07:18,
  - 53:346, 53:348, 07:30, 07:39, 55:72,
  - 55:283, 55:284, 55:299, 07:2156, 08:1566
- \int\_set:Nn . 09:176, 09:219, 09:251,
  - 09:294, 09:465, 09:466, 09:496,
  - 11:191, 52:212, 52:226, 07:1134,
  - 07:1145, 07:1353, 07:1363, 07:1488,
  - 07:2160, 07:2686, 07:2712, 08:1181
- \int\_set\_eq:NN .. 48:70, 07:791, 07:796
- \int\_step\_function:nN ..... 07:1436
- \int\_step\_inline:nn ..... 48:367
- \int\_step\_inline:nnn .....
  - ..... 09:184, 09:198, 09:259, 09:273
- \int\_use:N ..... 09:237, 09:541,
  - 09:548, 10:63, 10:89, 10:106, 17:43,
  - 28:282, 28:283, 28:285, 28:290,
  - 28:330, 28:331, 28:333, 28:342,
  - 36:234, 36:244, 36:245, 48:105,
  - 48:118, 48:120, 48:255, 52:553,
  - 53:104, 53:116, 53:368, 53:376,
  - 07:28, 55:34, 55:44, 55:332, 55:339,
  - 55:340, 55:392, 55:393, 07:944,
  - 07:1116, 07:1145, 07:1274, 07:1278,
  - 07:1279, 07:1363, 07:1554, 1144
- \int\_value:w ..... 53:48, 53:137
- \int\_zero:N ..... 55:85, 07:355,
  - 07:449, 07:450, 07:797, 07:801,
  - 07:948, 07:1248, 08:1575, 08:1657
- \c\_max\_int .....
  - . 48:70, 53:214, 53:240, 53:265, 53:292
- \l\_tmpa\_int ..... 356
- \c\_zero\_int ..... 09:181, 09:256, 53:91
- int internal commands:
  - \g\_mark\_int .....
    - 48:255, 48:278, 48:283, 48:284, 48:285

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=lt page.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- `\interdisplaylinepenalty` .....  
         18:14, [38:55](#), 38:207, 38:486  
`\interfootlinepenalty` ..... [02:302](#)  
`\interfootnotelinepenalty` .....  
         18:19, 45:467, 45:486, 45:504, 02:302  
`\interlinepenalty` ..... 18:11,  
         24:762, 37:538, 37:541, 37:559,  
         37:562, 44:67, 44:118, 44:234,  
         44:257, 45:467, 45:486, 45:504,  
         54:343, 54:1504, 54:1508, 54:1653,  
         54:1657, 54:1814, 54:1818, 02:201, [1306](#)  
`\interval` ..... [75](#)  
`\interval` ..... [05:162](#), 05:177, [75](#)  
`\intertextsep` .....  
         54:1487, 54:1491, 54:1506, 54:1509,  
         54:1516, 54:1636, 54:1640, 54:1655,  
         54:1658, 54:1665, 54:1793, 54:1799,  
         54:1816, 54:1819, 54:1828, [54:3003](#)  
`\intop` ..... 30:358, 30:359  
`\iota` ..... 30:287  
iow commands:  
    `\iow_char:N` .....  
         08:1794, 08:1805, 08:2637,  
         08:2639, 08:2641, 08:2646, 08:2649,  
         08:2651, 08:2661, 08:2662, 08:2702,  
         08:2710, 08:2722, 08:2727, 08:2732,  
         08:2918, 08:2920, 09:599, 16:153,  
         16:160, 16:161, 16:162, 16:163,  
         07:473, 07:537, 07:568, 07:640,  
         07:714, 07:726, 07:757, 07:1155,  
         07:1161, 07:2161, 07:3035, 07:3113  
    `\iow_log:n` ..... 08:1837  
    `\iow_newline:` .....  
         52:557, 07:1406, 07:1426, 07:1435,  
         07:1453, 07:1471, 07:1475, 07:1561  
    `\iow_now:Nn` ..... 53:367, 53:480  
    `\iow_shipout:Nn` ..... 53:480  
    `\iow_show:n` .....  
         08:1840, 08:1844, 07:1468, 07:1471  
    `\iow_term:n` .....  
         08:1793, 08:1804, 08:1818, 08:1824,  
         08:1825, 08:1826, 08:1829, 08:1833,  
         08:1851, 08:2135, 08:2140, 08:2155,  
         08:2169, 09:19, 09:28, 09:45, 09:56,  
         09:65, 09:67, 09:83, 09:87, 10:25,  
         48:20, 48:92, 48:179, 48:185, 48:191,  
         48:258, 52:550, 52:583, 07:1475,  
         08:531, 08:621, 08:1453, 08:1456,  
         08:1474, 08:1477, 08:1495, 08:1529,  
         08:1615, 08:1635, 08:1636, 08:1638,  
         08:1702, 08:1724, 08:1725, 08:1727  
`\ishortstack` ..... [42:132](#)  
`\itdefault` ..... 25:3217, 29:31, [30:106](#)
- `\item` ... 14:282, 37:446, 37:496, 37:498,  
         37:529, 37:551, 38:562, 38:574,  
         38:601, [39:172](#), 39:250, 41:78, 43:53,  
         43:55, 43:60, 43:62, 47:4, 47:8, [1313](#)  
`\itemindent` .....  
         [39:9](#), 39:42, 39:95, 39:218, 39:239, [873](#)  
`\itemitem` ..... [1306](#)  
`itemize (env.)` ..... [39:273](#)  
`\itemize` ..... 39:273  
`\itemsep` ..... [39:1](#), 39:207, [873](#)  
`\iterate` ..... 01:65, 01:66, [02:365](#)  
`\itshape` ..... 21:468, 21:831, 25:3215,  
         25:3216, 29:29, 29:30, 29:637,  
         29:670, 29:676, 32:21, 33:598, 43:53,  
         43:55, 43:60, 43:62, 45:399, [1351](#)
- ### J
- `\J` ..... 57:257, 57:552  
`\j` ..... 21:268, 21:424, 21:571,  
         21:803, 21:1174, 21:1389, 21:1475  
`\jmath` ..... 30:321  
`\jobname` ..... [1088](#)  
`\Join` ..... 29:853  
`\joinrel` ..... 30:482, 30:489,  
         30:491, 30:493, 30:495, 30:497,  
         30:499, 30:501, 30:503, 30:507, 30:509  
`\jot` ..... [38:53](#), 38:204, 38:497, 38:507
- ### K
- `\k` ..... 21:508, 21:613, 21:618,  
         21:640, 21:645, 21:721, 21:722,  
         21:781, 21:782, 21:836, 21:838,  
         21:843, 21:845, 21:1275, 21:1343,  
         21:1344, 21:1361, 21:1362, 21:1384,  
         21:1385, 21:1386, 21:1439, 21:1440,  
         21:1473, 21:1474, 33:145, 33:168, [504](#)  
`\kanjiskip` ..... 05:78  
`\kappa` ..... 30:288  
`\ker` ..... 38:27  
`\kern` ..... [1321](#)  
`\kern...` ..... [1344](#)  
`kernel (para/begin) (tag plug)` ... [55:117](#)  
`kernel (para/end) (tag plug)` ..... [55:145](#)  
`kernel (para/semantic/begin) (tag plug)` ..... [55:98](#)  
`kernel (para/semantic/end) (tag plug)` ..... [55:109](#)  
`kernel (recordtarget) (tag plug)` . [55:166](#)  
`kernel (refstepcounter/target) (plug)` ..... [35:120](#)  
kernel internal commands:  
    `\__kernel_chk_if_free_cs:N` .....  
         07:3319, [200](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

- \\_kernel\_cmd\_if\_xparse:NTF . . . . . 09:145, 07:1165, 07:1483,  
07:1485, 07:2744, 07:2765, 07:2821, 154
  - \\_kernel\_cs\_parameter\_spec:N . . . . . 09:178,  
09:253, 09:386, 05:146, 07:2748, 1379
  - \\_kernel\_cs\_parm\_from\_arg\_-  
count:nnTF . . . . . 08:109
  - \\_kernel\_exp\_not:w . . . . . 08:48, 08:50, 08:56, 08:61
  - \l\\_kernel\_expl\_bool . . . . . 09:397
  - \\_kernel\_file\_name\_sanitiz:n 52:98
  - \\_kernel\_msg... 1368
  - \\_kernel\_msg... 1370
  - \\_kernel\_quark\_new\_conditional:Nn  
. . . . . 11:42
  - \\_kernel\_quark\_new\_test:N . . . 07:52
  - \g\\_kernel\_target\_int . . . . . 17:28, 17:42, 17:43
  - \kerneltmpDoNotUse . . . 09:458, 09:470,  
09:476, 09:481, 09:529, 09:536,  
09:557, 09:565, 09:572, 09:585, 332
  - keys commands:
    - \keys\_define:nn . . . . . 11:513,  
11:534, 11:595, 20:763, 51:209,  
51:217, 51:221, 51:238, 51:273, 57:572
    - \keys\_if\_exist:nnTF . . . . . 51:120, 51:126, 51:150, 51:184, 51:200
    - \l\\_keys\_key\_str . . . . . 51:48, 51:49, 51:226
    - \l\\_keys\_key\_tl . . . . . 51:48
    - \l\\_keys\_path\_str . . . . . 51:47
    - \keys\_set:nn . . . . . 11:1245, 51:72, 51:288, 57:594
    - \keys\_set\_known:nnN . . . . . 11:1238
    - \l\\_keys\_usage\_load\_prop . . . . 51:234
    - \l\\_keys\_usage\_preamble\_prop . 51:269
  - keys internal commands:
    - \l\\_keys\_class\_only\_clist . . . . . 51:54, 51:123, 51:152
    - \\_keys\_find\_key\_module:wNn . . 51:46
    - \l\\_keys\_forced\_global\_clist . . . . . 51:49, 51:55, 51:154
    - \l\\_keys\_local\_clist . . . . . 51:57,  
51:167, 51:172, 51:176, 51:186, 51:190
    - \l\\_keys\_no\_value\_bool . . . . . 51:24
    - \\_keys\_options:n 51:59, 51:59, 51:230
    - \\_keys\_options\_aux:n . . . . . 51:59, 51:60, 51:61
    - \\_keys\_options\_class:n . . . . . 51:102, 51:106, 51:106
    - \\_keys\_options\_class:nn . . . . . 51:106, 51:122, 51:127, 51:134
    - \\_keys\_options\_class:nnn . . . . . 51:106, 51:112, 51:118
    - \l\\_keys\_options\_clist . . . . . 51:56, 51:66, 51:71,  
51:137, 51:162, 51:186, 51:202, 1108
    - \\_keys\_options\_expand\_module:Nn  
. . . . . 51:60,  
51:210, 51:210, 51:217, 51:221, 51:288
    - \\_keys\_options\_expand\_module:nN  
. . . . . 51:210, 51:214
    - \\_keys\_options\_global:n . . . . . 51:68, 51:97, 51:97
    - \\_keys\_options\_loaded:n . . . . . 51:74, 51:232, 51:232
    - \\_keys\_options\_loaded:nn . . . . . 51:232, 51:241, 51:246
    - \l\\_keys\_options\_loading\_bool . . . . . 51:58, 51:70, 51:73, 51:248, 1108
    - \\_keys\_options\_local: . . . . . 51:63, 51:165, 51:165
    - \\_keys\_options\_local:n . . . . . 51:69, 51:182, 51:182
    - \\_keys\_options\_local:nnn . . . . . 51:182, 51:192, 51:198
    - \\_keys\_options\_package:n . . . . . 51:103, 51:139, 51:139
    - \\_keys\_options\_package:nn . . . . . 51:139, 51:155, 51:157, 51:160
    - \\_keys\_options\_package:nnn . . . . . 51:139, 51:143, 51:148
    - \c\\_keys\_props\_root\_str . . . . . 51:9, 51:10, 51:22
    - \\_keys\_remove\_equals:n . . 51:113,  
51:144, 51:179, 51:193, 51:206, 51:206
    - \\_keys\_remove\_equals:w . . . . . 51:206, 51:207, 51:208
    - \\_keys\_scope:N . . . . . 51:22, 51:33, 51:35, 51:44
    - \\_keys\_scope:n . . . . . 51:22, 51:25, 51:26, 51:28
    - \\_keys\_tmp:nn . . . . . 51:5, 51:11, 51:13
    - \l\\_keys\_tmpa\_tl . . . . . 51:234, 51:236
    - \l\\_keys\_unused\_clist . . . . . 51:76, 51:78, 51:178, 51:187, 51:203
  - keyval commands:
    - \keyval\_parse:NNn . . . . . 11:213, 11:618
    - \keyval\_parse:nnn . . . . . 11:414, 11:535
    - \KeyValue . . . . . 11:80, 11:905, 11:1110, 11:1229, 355
    - \kill . . . . . 41:154, 41:162
- L**
- \L . . . . . 21:262, 21:445,  
21:553, 21:795, 21:1167, 50:1340,  
50:1472, 50:1562, 50:1584, 57:671

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- `\l` ..... 21:271,  
21:447, 21:574, 21:804, 21:1168, 57:671
- `\label` ..... 35:94, 35:168,  
35:172, 44:190, 44:200, 48:280,  
49:40, 49:51, 49:66, 49:74, 49:89,  
49:97, 54:903, 54:973, 54:1032, 817
- `label` ..... 36:237, 818
- `\labelenumi` ..... 886
- `\labelenumiv` ..... 886
- `\labelformat` ..... 807
- `\labelformat` ..... 35:157,  
35:185, 35:190, 35:196, 35:201, 35:207
- `\labelitemi` ..... 886
- `\labelitemii` ..... 886
- `\labelitemiii` ..... 886
- `\labelitemiv` ..... 886
- `\labelsep` ..... 39:9, 39:241,  
39:247, 43:53, 43:55, 43:60, 43:62, 886
- `\labelwidth` .....  
39:9, 39:93, 39:240, 39:242, 39:245, 873
- `\Lambda` ..... 30:311
- `\lambda` ..... 30:289
- `\land` ..... 30:379, 30:381
- `\langle` ..... 30:605
- `\language` ..... 20:52, 20:122,  
37:534, 37:726, 02:35, 54:850,  
54:951, 02:78, 02:80, 56:10, 1357
- `\lastbox` ..... 24:780,  
38:193, 38:194, 39:132, 39:138,  
39:216, 44:99, 44:132, 54:310, 421
- `\LastDeclaredEncoding` .....  
..... 24:138, 24:141, 57:482, 1348
- `\LastMark` ..... 48:402, 48:523, 1016
- `\lastnamedcs` ..... 06:850
- `\lastnodetype` 24:773, 24:774, 24:775, 24:779
- `\lastpenalty` ..... 24:776, 32:112, 32:115
- `\lastskip` ..... 18:45, 18:129, 18:141,  
18:160, 18:221, 18:222, 18:226,  
18:228, 18:229, 18:241, 18:256,  
18:273, 18:295, 18:298, 18:328,  
18:331, 18:362, 18:365, 18:366,  
32:102, 32:105, 39:115, 39:116,  
39:181, 39:182, 42:123, 54:568,  
02:389, 02:390, 02:392, 02:394, 1307
- `\LaTeX` ... 19:3, 19:15, 50:1302, 50:1435,  
50:1524, 06:929, 53:403, 53:409, 02:256
- `\LaTeXe` ..... 19:13
- `\latexrelease` ..... 1136
- `\LaTeXReleaseInfo` ..... 03:36, 03:37,  
03:40, 03:45, 03:50, 37:49, 37:114, 36
- `\latexreleaseversion` ..... 03:1
- `\lbrace` ..... 21:328, 30:609
- `\lbrack` ..... 02:316
- `\lccode` ..... 14:19, 14:20,  
14:21, 14:22, 14:23, 14:24, 21:158,  
21:1089, 37:655, 37:672, 37:686,  
37:701, 37:744, 57:224, 57:241,  
57:249, 57:256, 57:258, 57:259,  
57:261, 57:263, 57:264, 57:265,  
57:266, 57:536, 57:544, 57:551,  
57:553, 57:554, 57:556, 57:558, 1354
- `\lceil` ..... 30:613
- `\lcode` ..... 1345
- `\ldotp` ..... 30:512, 30:515, 30:630
- `\ldots` ..... 21:342, 30:516, 1333
- `\le` ..... 30:427, 30:429
- `\leaders` 30:351, 30:569, 30:570, 30:572,  
30:573, 41:376, 42:564, 42:577,  
42:589, 42:599, 44:239, 44:262, 02:421
- `\leadsto` ..... 29:856
- `\leavevmode` 18:454, 18:468, 21:93, 21:202,  
21:309, 21:310, 21:414, 21:446,  
21:450, 21:453, 21:502, 21:787,  
21:820, 32:123, 33:62, 33:888,  
37:538, 37:559, 37:572, 37:583,  
37:613, 37:627, 37:722, 37:732,  
37:745, 38:562, 38:574, 38:601,  
39:58, 39:103, 40:8, 40:17, 40:24,  
40:195, 40:197, 40:213, 40:245,  
40:264, 40:331, 40:358, 40:437,  
40:544, 40:561, 40:568, 41:178,  
42:134, 42:314, 42:373, 44:40,  
44:235, 44:247, 44:258, 45:530,  
47:34, 54:136, 54:141, 54:163,  
54:168, 54:189, 54:194, 02:380,  
02:407, 02:410, 02:421, 02:423, 1308
- `\left` ..... 30:636, 30:638,  
30:640, 30:642, 30:647, 30:648,  
30:649, 30:650, 38:167, 38:173, 38:195
- `\Leftarrow` ..... 30:421, 30:503, 30:509
- `\leftarrow` ..... 30:448,  
30:450, 30:491, 30:501, 30:507, 30:561
- `\leftarrowfill` ..... 30:545, 30:561
- `\lefteqn` ..... 38:521
- `\leftharpoondown` ..... 30:464, 30:478
- `\leftharpoonup` ..... 30:463
- `\lefthyphenmin` ..... 56:11, 02:246
- `\leftline` ..... 40:614
- `\leftmargin` ..... 39:9,  
39:52, 39:53, 39:94, 39:177, 39:179, 873
- `\leftmargini` ..... 38:554, 39:17, 873
- `\leftmarginii` ..... 39:17
- `\leftmarginiii` ..... 39:17
- `\leftmarginiv` ..... 39:17
- `\leftmarginv` ..... 39:17
- `\leftmarginvi` ..... 39:17, 873
- `\leftmark` ..... 49:106, 1313

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\Leftrightarrow</code> .....	30:420	<code>\llap</code> .....	39:269, 39:280, <a href="#">40:618</a>
<code>\leftrightharpoonarrow</code> .....	30:447	<code>\lmoustache</code> .....	30:574
<code>\leftskip</code> .....	24:757,	<code>\ln</code> .....	38:5
37:454, 37:460, 37:464, 37:474,		<code>\lnot</code> .....	30:337, 30:338
37:478, 37:482, 37:531, 37:553,		<code>\LoadClass</code> .....	<a href="#">1052</a>
39:74, 40:392, 40:413, 44:232,		<code>\LoadClass</code> .....	
44:237, 44:255, 44:260, 02:291, 02:402		.. <a href="#">50:686</a> , <a href="#">50:716</a> , <a href="#">50:967</a> , <a href="#">50:1102</a> ,	
legacy commands:		<a href="#">50:1197</a> , <a href="#">50:1205</a> , <a href="#">50:1206</a> , <a href="#">1309</a>	
<code>\legacy_if:nTF</code> ...	48:437, 48:459,	<code>\LoadClassWithOptions</code> .....	<a href="#">1052</a>
48:497, 48:504, 55:121, 55:124, 55:125		<code>\LoadClassWithOptions</code> .....	<a href="#">50:715</a>
<code>\legacyoldstylenums</code> .....	<a href="#">33:4</a> , <a href="#">33:581</a>	<code>\LoadFontDefinitionFile</code> .....	
<code>\leq</code> .....	30:425, 30:427	..... <a href="#">24:210</a> , <a href="#">24:515</a> , <a href="#">24:541</a> ,	
<code>\leqno</code> .....	<a href="#">38:532</a>	<a href="#">24:542</a> , 30:21, 30:27, 30:28, 30:29, 30:33	
<code>\let</code> .....	<a href="#">1324</a>	<code>\LoadPackageWithOptions</code> .....	<a href="#">1116</a>
<code>\LetLtxMacro</code> .....	<a href="#">101</a>	<code>\loccount</code> .....	04:17
<code>\lfloor</code> .....	30:617	<code>\log</code> .....	<a href="#">38:3</a>
<code>\lg</code> .....	38:4	<code>\loggingall</code> .....	<a href="#">02:432</a>
<code>\lggroup</code> .....	30:619	<code>\loggingoutput</code> .....	<a href="#">02:428</a> ,
<code>\lhd</code> .....	29:859	<a href="#">02:445</a> , <a href="#">02:463</a> , <a href="#">02:479</a> , <a href="#">02:493</a> , <a href="#">1350</a>	
<code>\lhook</code> .....	30:488, 30:489	<code>\LogHook</code> .....	<a href="#">08:2839</a> , <a href="#">212</a>
<code>\lim</code> .....	38:6	<code>\LogSocket</code> .....	<a href="#">10:182</a> , <a href="#">10:205</a> , <a href="#">341</a>
<code>\liminf</code> .....	38:8	<code>\long</code> .....	<a href="#">1364</a>
<code>\limits</code> ....	30:550, 30:554, 38:162, 38:411	<code>\Longleftarrow</code> .....	30:503
<code>\limsup</code> .....	38:7	<code>\longleftarrow</code> .....	30:500
<code>\line</code> .	<a href="#">14:269</a> , <a href="#">42:158</a> , <a href="#">42:450</a> , <a href="#">42:808</a> , <a href="#">42:825</a>	<code>\Longleftrightarrow</code> ....	30:509, 30:511
<code>\linebreak</code> .....	<a href="#">433</a>	<code>\longleftrightarrow</code> .....	30:507
<code>\linebreak</code> .....	<a href="#">18:9</a> , <a href="#">18:27</a>	<code>\longmapsto</code> .....	30:505
<code>\linepenalty</code> .....	02:190	<code>\Longrightarrow</code> .....	30:497
<code>\lineskip</code> .....	30:469,	<code>\longrightarrow</code> .....	30:498, 30:505
38:200, 40:394, 40:414, 41:71,		<code>\loop</code> .....	04:150, 04:159, 24:771,
41:198, 42:136, 42:315, 42:374,		<a href="#">41:382</a> , <a href="#">50:1250</a> , <a href="#">50:1311</a> , <a href="#">50:1381</a> ,	
53:223, 53:274, 54:907, 54:976,		<a href="#">50:1444</a> , <a href="#">50:1495</a> , <a href="#">50:1533</a> , <a href="#">57:365</a> ,	
54:1035, 02:285, 02:310, 02:375, 02:410		<a href="#">57:376</a> , <a href="#">57:386</a> , <a href="#">57:397</a> , <a href="#">57:427</a> ,	
<code>\lineskiplimit</code> .....	30:469,	<a href="#">57:453</a> , <a href="#">57:463</a> , <a href="#">01:65</a> , <a href="#">02:365</a> , <a href="#">1331</a>	
30:521, 38:202, 38:206, 40:380,		<code>\looseness</code> .....	02:207
40:395, 40:402, 53:224, 53:275,		<code>\lor</code> .....	30:380, 30:382
54:908, 54:976, 54:1035, 02:271,		<code>\lower</code> .....	19:2, 30:469,
02:311, 02:375, 02:412, 02:413, <a href="#">1357</a>		<a href="#">40:278</a> , <a href="#">42:35</a> , <a href="#">42:45</a> , <a href="#">42:196</a> , <a href="#">42:305</a> ,	
<code>\linespread</code> .....	<a href="#">24:379</a>	<a href="#">42:306</a> , <a href="#">42:353</a> , <a href="#">42:354</a> , <a href="#">42:409</a> , <a href="#">42:410</a>	
<code>\linethickness</code> ....	<a href="#">42:130</a> , <a href="#">42:809</a> , <a href="#">42:826</a>	<code>\lowercase</code> .....	
<code>\linewidth</code> ....	20:30, 20:100, 20:158,	.. <a href="#">14:26</a> , <a href="#">21:159</a> , <a href="#">21:1090</a> , <a href="#">21:1568</a> ,	
38:315, 38:343, 38:368, 38:563,		<a href="#">22:110</a> , <a href="#">24:395</a> , <a href="#">24:487</a> , <a href="#">37:659</a> ,	
38:575, 38:602, 38:606, 38:625, 39:9,		<a href="#">37:676</a> , <a href="#">37:690</a> , <a href="#">37:705</a> , <a href="#">37:745</a> , <a href="#">1343</a>	
39:51, 39:52, 39:54, 40:390, 40:411,		<code>\lq</code> .....	<a href="#">02:314</a>
41:36, 45:266, 54:125, 54:210, <a href="#">872</a>		<code>lrbox (env.)</code> .....	<a href="#">889</a>
<code>\LinkTargetOff</code> .....	<a href="#">17:25</a>	<code>\lrbox</code> .....	<a href="#">40:183</a>
<code>\LinkTargetOn</code> .....	<a href="#">17:25</a>	<code>\ltfilehookdate</code> .....	52:542
<code>list (env.)</code> .....	<a href="#">39:34</a>	<code>\ltfilehookversion</code> .....	52:542
<code>\list</code> .....	<a href="#">39:34</a> , 39:267, 39:278	lua commands:	
<code>\listfiles</code> .....	<a href="#">1054</a>	<code>\lua_now:n</code> .....	53:31, 53:481
<code>\listfiles</code> .....	<a href="#">20:769</a> , <a href="#">1323</a>	<code>\lua_shipout:n</code> .....	53:481
<code>\listparindent</code> ....	<a href="#">39:9</a> , 39:41, 39:50, <a href="#">873</a>	<code>\luabytecode</code> .....	04:202
<code>\literal</code> .....	<a href="#">1327</a>	<code>\luachunk</code> .....	04:210
<code>\ll</code> .....	30:445	<code>\luadef</code> .....	<a href="#">04:182</a> , <a href="#">04:186</a> , <a href="#">40</a>

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- \luafunction ... 04:178, 04:182, 04:186, 40  
 luamml commands:  
   \luamml\_save:... 1274  
 luatexbase ..... 04:288  
 \luatexluafunction ..... 01:21, 01:26  
 \luatexversion ..... 04:5, 21:1018,  
   01:14, 05:77, 05:123, 02:217, 02:218
- M**
- \M ..... 02:312  
 \Macro ..... 1306  
 \mag ..... 02:251  
 \magstep ..... 02:303  
 \magstephalf ..... 02:303  
 \makeat... 1325  
 \makeatletter .....  
   ... 09:393, 20:32, 20:102, 20:160,  
   24:493, 37:29, 37:94, 37:156, 44:151,  
   50:680, 50:931, 50:1063, 06:925, 1347  
 \makeatother .....  
   . 09:393, 50:680, 06:925, 57:747, 1322  
 \makebox ..... 889  
 \makebox 38:315, 38:343, 38:368, 40:3, 1275  
 \makecol ..... 1204  
 \makeglossary ..... 1006  
 \makeglossary ..... 20:205, 46:20, 1330  
 \makeindex ..... 1006  
 \makeindex ..... 20:204, 46:3, 1330  
 \makelabel ..... 39:45, 39:97,  
   39:236, 39:249, 39:269, 39:280, 1307  
 \MakeLinkTarget .. 17:25, 43:53, 43:55, 432  
 \MakeLowercase ..... 57:571, 1337  
 \MakeRobust ... 28:960, 28:1155, 06:375,  
   42:805, 42:806, 42:807, 42:808,  
   42:809, 42:810, 42:811, 42:812,  
   42:813, 42:814, 42:815, 42:816,  
   06:970, 06:971, 06:972, 06:973,  
   06:974, 06:975, 06:976, 06:977,  
   06:978, 06:979, 06:980, 06:981,  
   06:982, 06:983, 06:984, 06:985, 1368  
 \maketitle ..... 969  
 \MakeTitlecase ..... 57:571, 1373  
 \MakeUppercase ..... 35:160,  
   35:162, 35:187, 35:198, 57:571, 1337  
 \mapsto ..... 30:455  
 \mapstochar ..... 30:454, 30:455, 30:505  
 \marginpar ..... 45:308, 416  
 marginpar/begin (tag socket) ..... 55:196  
 marginpar/end (tag socket) ..... 55:196  
 \marginparpush ..... 54:61, 54:2410  
 \marginparsep .... 54:60, 54:2421, 54:2423  
 \marginparwidth .....  
   ..... 45:341, 45:359, 54:59, 54:2423
- \mark ..... 49:46, 49:56,  
   49:69, 49:77, 49:92, 49:100, 49:121, 26  
 mark commands:  
   \mark\_clear\_structure:n .....  
     ..... 48:224, 48:224, 1023  
   \mark\_copy\_structure:nn .....  
     ..... 48:138, 48:213,  
     48:213, 48:427, 48:428, 48:429,  
     48:430, 48:461, 48:465, 48:466, 1022  
   \mark\_debug\_off: .....  
     ..... 48:340, 48:346, 48:357, 1019  
   \mark\_debug\_on: .....  
     ..... 48:340, 48:341, 48:356, 1019  
   \mark\_get\_marks\_for\_reinsertion:nnN  
     ..... 48:162, 48:162, 1026  
   \mark\_if\_eq:nnnn ..... 48:299  
   \mark\_if\_eq:nnnnnn ..... 48:306  
   \mark\_if\_eq:nnnnnnTF ... 48:299, 1016  
   \mark\_if\_eq:nnnnTF .....  
     . 48:299, 48:409, 48:412, 48:415, 1016  
   \mark\_insert:nn ..... 48:189,  
     48:200, 48:246, 48:246, 48:401,  
     49:24, 49:25, 49:26, 49:29, 49:30,  
     49:43, 49:44, 49:45, 49:54, 49:55, 1023  
   \mark\_new\_class:n .....  
     ..... 48:7, 48:7, 48:16, 48:399, 1015  
   \mark\_set\_structure\_to\_err:n ...  
     ..... 48:235, 48:235, 48:462, 1022  
   \mark\_update\_structure\_from\_-  
     material:nn .... 48:132, 48:132,  
     48:420, 48:424, 48:452, 48:456, 1022  
   \mark\_use\_first:nn .....  
     . 48:289, 48:289, 48:403, 49:112, 1016  
   \mark\_use\_last:nn .....  
     . 48:289, 48:290, 48:405, 49:111, 1016  
   \mark\_use\_top:nn .....  
     ..... 48:289, 48:291, 48:407, 1016  
 mark internal commands:  
   \\_mark\_update\_dblcol\_structures:  
     ..... 1022  
   \\_mark\_class\_status:nnn .....  
     ..... 48:358, 48:359, 48:391  
   \\_mark\_debug:n .....  
     .... 48:20, 48:92, 48:179, 48:185,  
     48:191, 48:258, 48:340, 48:340,  
     48:353, 48:396, 48:433, 48:493, 1038  
   \\_mark\_debug\_gset: .....  
     ..... 48:340, 48:344, 48:349, 48:351  
   \\_mark\_drop\_id:n .....  
     48:189, 48:202, 48:295, 48:297, 48:298  
   \\_mark\_error:n ..... 48:235  
   \\_mark\_error:nn .....  
     48:238, 48:239, 48:240, 48:243, 48:294

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\__mark_extract_and_handle_-</code>	<code>math/luamml/finph@nt</code> (tag socket) . . . .
<code>marks:nn</code> . . . . .	. . . . . <a href="#">55:258</a> , <a href="#">55:259</a>
. . . <a href="#">48:67</a> , <a href="#">48:67</a> , <a href="#">48:133</a> , <a href="#">48:165</a> , <a href="#">1027</a>	<code>math/luamml/hbox</code> (tag socket) . . . . <a href="#">55:257</a>
<code>\__mark_get_from_splitmarks:</code> . . .	<code>math/luamml/mtable/aligncol</code> (tag
. . . . . <a href="#">48:166</a> , <a href="#">48:171</a> , <a href="#">48:171</a>	socket) . . . . . <a href="#">55:251</a>
<code>\__mark_init_region:nn</code> . . . . .	<code>math/luamml/mtable/finalize</code> (tag
. <a href="#">48:24</a> , <a href="#">48:25</a> , <a href="#">48:26</a> , <a href="#">48:27</a> , <a href="#">48:28</a> ,	socket) . . . . . <a href="#">55:250</a>
<a href="#">48:29</a> , <a href="#">48:30</a> , <a href="#">48:31</a> , <a href="#">48:32</a> , <a href="#">48:33</a> ,	<code>math/luamml/mtable/finalizecol</code> (tag
<a href="#">48:34</a> , <a href="#">48:35</a> , <a href="#">48:36</a> , <a href="#">48:37</a> , <a href="#">48:38</a> ,	socket) . . . . . <a href="#">55:249</a>
<a href="#">48:39</a> , <a href="#">48:40</a> , <a href="#">48:41</a> , <a href="#">48:42</a> , <a href="#">48:43</a> ,	<code>math/luamml/mtable/innertable/finalize</code>
<a href="#">48:44</a> , <a href="#">48:45</a> , <a href="#">48:46</a> , <a href="#">48:47</a> , <a href="#">48:48</a> ,	(tag socket) . . . . . <a href="#">55:254</a>
<a href="#">48:49</a> , <a href="#">48:50</a> , <a href="#">48:51</a> , <a href="#">48:52</a> , <a href="#">48:54</a> , <a href="#">48:54</a>	<code>math/luamml/mtable/innertable/save</code>
<code>\__mark_new_class:nn</code> <a href="#">48:7</a> , <a href="#">48:14</a> , <a href="#">48:17</a>	(tag socket) . . . . . <a href="#">55:252</a>
<code>\__mark_prepare_and_extract:nn</code> . .	<code>math/luamml/mtable/smallmatrix/save</code>
. . . . . <a href="#">48:72</a> , <a href="#">48:75</a> , <a href="#">48:75</a> , <a href="#">48:96</a> , <a href="#">1027</a>	(tag socket) . . . . . <a href="#">55:253</a>
<code>\__mark_region_status:nnn</code> . . . . .	<code>math/luamml/mtable/tag/save</code> (tag
. . . <a href="#">48:361</a> , <a href="#">48:362</a> , <a href="#">48:363</a> , <a href="#">48:364</a> ,	socket) . . . . . <a href="#">55:255</a>
<a href="#">48:365</a> , <a href="#">48:366</a> , <a href="#">48:369</a> , <a href="#">48:372</a> , <a href="#">48:372</a>	<code>math/luamml/mtable/tag/set</code> (tag
<code>\__mark_status:nn</code> . . . . .	socket) . . . . . <a href="#">55:256</a>
<a href="#">48:388</a> , <a href="#">48:388</a> , <a href="#">48:396</a> , <a href="#">48:435</a> , <a href="#">48:495</a>	<code>math/luamml/save/nn</code> (tag socket) . . <a href="#">55:242</a>
<code>\__mark_update_dblcol_structures:</code>	<code>math/luamml/save/nNn</code> (tag socket) . <a href="#">55:243</a>
. . . . . <a href="#">48:449</a> , <a href="#">48:449</a> , <a href="#">48:516</a> , <a href="#">1023</a>	<code>\mathaccent</code> . . . . . <a href="#">1356</a>
<code>\__mark_update_singlecol_-</code>	<code>\mathaccent</code> . <a href="#">28:877</a> , <a href="#">28:925</a> , <a href="#">28:959</a> , <a href="#">28:969</a>
<code>structures:</code> . . . . .	<code>\mathalpha</code> . . . . .
. . . . . <a href="#">48:417</a> , <a href="#">48:417</a> , <a href="#">48:514</a> , <a href="#">1022</a>	. <a href="#">28:1047</a> , <a href="#">28:1226</a> , <a href="#">30:180</a> , <a href="#">30:181</a> ,
<code>\__mark_update_structure_from_-</code>	<a href="#">30:182</a> , <a href="#">30:183</a> , <a href="#">30:184</a> , <a href="#">30:185</a> ,
<code>splitmarks:n</code> . . . . .	<a href="#">30:186</a> , <a href="#">30:187</a> , <a href="#">30:188</a> , <a href="#">30:189</a> ,
. . . . . <a href="#">48:134</a> , <a href="#">48:137</a> , <a href="#">48:137</a> , <a href="#">1030</a>	<a href="#">30:190</a> , <a href="#">30:191</a> , <a href="#">30:192</a> , <a href="#">30:193</a> ,
<code>\__mark_use_check:nnn</code> . . . . .	<a href="#">30:194</a> , <a href="#">30:195</a> , <a href="#">30:196</a> , <a href="#">30:197</a> ,
. . . . . <a href="#">48:289</a> , <a href="#">48:290</a> , <a href="#">48:291</a> , <a href="#">48:292</a>	<a href="#">30:198</a> , <a href="#">30:199</a> , <a href="#">30:200</a> , <a href="#">30:201</a> ,
<code>\__mark_value:nn</code> . . . . .	<a href="#">30:202</a> , <a href="#">30:203</a> , <a href="#">30:204</a> , <a href="#">30:205</a> ,
. . . . . <a href="#">48:62</a> , <a href="#">48:238</a> , <a href="#">48:239</a> ,	<a href="#">30:206</a> , <a href="#">30:207</a> , <a href="#">30:208</a> , <a href="#">30:209</a> ,
<a href="#">48:240</a> , <a href="#">48:255</a> , <a href="#">48:277</a> , <a href="#">48:277</a> , <a href="#">48:374</a>	<a href="#">30:210</a> , <a href="#">30:211</a> , <a href="#">30:212</a> , <a href="#">30:213</a> ,
<code>\__mark_vbox_set_split_to_-</code>	<a href="#">30:214</a> , <a href="#">30:215</a> , <a href="#">30:216</a> , <a href="#">30:217</a> ,
<code>maxdimen:NN</code> . . . . .	<a href="#">30:218</a> , <a href="#">30:219</a> , <a href="#">30:220</a> , <a href="#">30:221</a> ,
. . <a href="#">48:87</a> , <a href="#">48:101</a> , <a href="#">48:102</a> , <a href="#">48:114</a> , <a href="#">1027</a>	<a href="#">30:222</a> , <a href="#">30:223</a> , <a href="#">30:224</a> , <a href="#">30:225</a> ,
<code>\markboth</code> . . <a href="#">49:21</a> , <a href="#">49:22</a> , <a href="#">49:36</a> , <a href="#">49:38</a> ,	<a href="#">30:226</a> , <a href="#">30:227</a> , <a href="#">30:228</a> , <a href="#">30:229</a> ,
<a href="#">49:62</a> , <a href="#">49:64</a> , <a href="#">49:83</a> , <a href="#">49:85</a> , <a href="#">49:87</a> , <a href="#">1020</a>	<a href="#">30:230</a> , <a href="#">30:231</a> , <a href="#">30:232</a> , <a href="#">30:233</a> ,
<code>\markright</code> . . . . .	<a href="#">30:234</a> , <a href="#">30:235</a> , <a href="#">30:236</a> , <a href="#">30:237</a> ,
<a href="#">49:22</a> , <a href="#">49:49</a> , <a href="#">49:72</a> , <a href="#">49:86</a> , <a href="#">49:95</a> , <a href="#">1020</a>	<a href="#">30:238</a> , <a href="#">30:239</a> , <a href="#">30:240</a> , <a href="#">30:241</a> ,
<code>\marks</code> . . . . . <a href="#">04:37</a> , <a href="#">57:10</a> , <a href="#">57:12</a>	<a href="#">30:308</a> , <a href="#">30:309</a> , <a href="#">30:310</a> , <a href="#">30:311</a> ,
<code>math</code> (env.) . . . . . <a href="#">38:389</a>	<a href="#">30:312</a> , <a href="#">30:313</a> , <a href="#">30:314</a> , <a href="#">30:315</a> ,
<code>\math</code> . . . . . <a href="#">38:389</a>	<a href="#">30:316</a> , <a href="#">30:317</a> , <a href="#">30:318</a> , <a href="#">30:527</a> ,
<code>math/luamml/annotate/false</code> (tag	<a href="#">30:528</a> , <a href="#">30:529</a> , <a href="#">30:530</a> , <a href="#">30:531</a> ,
socket) . . . . . <a href="#">55:244</a>	<a href="#">30:532</a> , <a href="#">30:533</a> , <a href="#">30:534</a> , <a href="#">30:536</a> , <a href="#">30:539</a>
<code>math/luamml/array/finalize</code> (tag	<code>\mathbf</code> . . . . . <a href="#">29:15</a> , <a href="#">29:334</a> ,
socket) . . . . . <a href="#">55:246</a>	<a href="#">29:387</a> , <a href="#">29:432</a> , <a href="#">29:460</a> , <a href="#">29:554</a> , <a href="#">30:162</a>
<code>math/luamml/array/finalizecol</code> (tag	<code>\mathbin</code> <a href="#">28:1231</a> , <a href="#">30:243</a> , <a href="#">30:244</a> , <a href="#">30:246</a> ,
socket) . . . . . <a href="#">55:248</a>	<a href="#">30:369</a> , <a href="#">30:370</a> , <a href="#">30:371</a> , <a href="#">30:372</a> ,
<code>math/luamml/array/initcol</code> (tag socket)	<a href="#">30:375</a> , <a href="#">30:376</a> , <a href="#">30:377</a> , <a href="#">30:378</a> ,
. . . . . <a href="#">55:247</a>	<a href="#">30:381</a> , <a href="#">30:382</a> , <a href="#">30:383</a> , <a href="#">30:384</a> ,
<code>math/luamml/array/save</code> (tag socket) <a href="#">55:245</a>	<a href="#">30:385</a> , <a href="#">30:386</a> , <a href="#">30:387</a> , <a href="#">30:388</a> ,
<code>math/luamml/artifact</code> (tag socket) . <a href="#">55:260</a>	<a href="#">30:389</a> , <a href="#">30:390</a> , <a href="#">30:391</a> , <a href="#">30:392</a> ,
	<a href="#">30:393</a> , <a href="#">30:394</a> , <a href="#">30:395</a> , <a href="#">30:396</a> ,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- 30:397, 30:398, 30:399, 30:400,  
 30:401, 30:402, 30:403, 30:404,  
 30:405, 30:406, 30:407, 30:408, 38:37  
 $\backslash$ mathcal ..... 30:161  
 $\backslash$ mathchar ..... 28:988, 28:1032,  
 30:346, 30:347, 30:628, 02:408, 1356  
 $\backslash$ mathchardef ..... 12:3, 12:4, 12:5,  
 12:6, 04:227, 21:88, 28:1023, 02:21,  
 02:22, 02:23, 02:24, 02:83, 02:84, 1329  
 $\backslash$ mathcharzero ..... 04:227  
 $\backslash$ mathchoice ..... 38:61  
 $\backslash$ mathclose ..... 28:1234, 30:242,  
 30:251, 30:253, 30:256, 30:261,  
 30:267, 30:269, 30:271, 30:577,  
 30:604, 30:608, 30:612, 30:616,  
 30:622, 38:43, 38:46, 38:49, 38:52  
 $\backslash$ mathcode . 28:1020, 30:263, 30:264, 30:265  
 $\backslash$ MathCollectFalse ..... 1264  
 $\backslash$ MathCollectFalse ..... 55:52  
 $\backslash$ MathCollectTrue ..... 1264  
 $\backslash$ MathCollectTrue ..... 55:52  
 $\backslash$ mathdefaultsmode ..... 38:529, 38:530  
 $\backslash$ mathdollar ..... 21:327, 30:625, 1329  
 $\backslash$ mathellipsis ..... 21:341, 30:630, 1329  
 $\backslash$ mathfontset ..... 1304  
 $\backslash$ mathgroup .... 24:15, 26:304, 26:310,  
 26:316, 26:317, 26:328, 30:654, 33:8,  
 33:14, 33:578, 33:1100, 02:75, 1304  
 $\backslash$ mathhexbox ..... 29:735, 02:408, 1336  
 $\backslash$ mathindent ..... 38:552,  
 38:564, 38:576, 38:604, 38:615, 1362  
 $\backslash$ mathinner . 30:515, 30:519, 30:524, 30:630  
 $\backslash$ mathit 25:3216, 29:30, 30:164, 30:167, 30:628  
 $\backslash$ MathMLarg ..... 1264  
 $\backslash$ MathMLarg ..... 55:261  
 $\backslash$ MathMLintent ..... 1264  
 $\backslash$ MathMLintent ..... 55:261  
 $\backslash$ mathnormal ..... 30:160  
 $\backslash$ mathop 28:1230, 30:352, 30:353, 30:354,  
 30:355, 30:356, 30:357, 30:358,  
 30:360, 30:361, 30:362, 30:363,  
 30:364, 30:365, 30:367, 30:368,  
 30:548, 30:551, 38:3, 38:4, 38:5,  
 38:6, 38:7, 38:8, 38:9, 38:10, 38:11,  
 38:12, 38:13, 38:14, 38:15, 38:16,  
 38:17, 38:18, 38:19, 38:20, 38:21,  
 38:22, 38:23, 38:24, 38:25, 38:26,  
 38:27, 38:28, 38:29, 38:30, 38:31,  
 38:32, 38:33, 38:34, 38:162, 38:411  
 $\backslash$ mathopen 28:1233, 30:252, 30:255, 30:260,  
 30:266, 30:268, 30:270, 30:575,  
 30:606, 30:610, 30:614, 30:618,  
 30:620, 38:41, 38:44, 38:47, 38:50  
 $\backslash$ mathord .... 28:1047, 28:1229, 30:247,  
 30:254, 30:257, 30:262, 30:274,  
 30:275, 30:276, 30:278, 30:279,  
 30:280, 30:281, 30:282, 30:283,  
 30:284, 30:285, 30:286, 30:287,  
 30:288, 30:289, 30:290, 30:291,  
 30:292, 30:293, 30:294, 30:295,  
 30:296, 30:297, 30:298, 30:299,  
 30:300, 30:301, 30:302, 30:303,  
 30:304, 30:305, 30:306, 30:307,  
 30:319, 30:320, 30:321, 30:322,  
 30:323, 30:324, 30:325, 30:326,  
 30:327, 30:328, 30:329, 30:330,  
 30:331, 30:332, 30:333, 30:334,  
 30:335, 30:336, 30:338, 30:339,  
 30:340, 30:341, 30:342, 30:343,  
 30:344, 30:345, 30:535, 30:537,  
 30:538, 30:560, 30:561, 30:564,  
 30:565, 30:566, 30:567, 30:579,  
 30:581, 30:583, 30:586, 30:588,  
 30:602, 30:624, 30:625, 30:626, 30:627  
 $\backslash$ mathpalette ..... 30:468, 30:472,  
 30:475, 38:60, 38:69, 38:99, 38:129  
 $\backslash$ mathparagraph .....  
 . 21:330, 22:259, 22:271, 30:625, 1329  
 $\backslash$ mathpunct ..... 28:1235,  
 30:245, 30:249, 30:512, 30:513, 30:514  
 $\backslash$ mathrel ..... 28:1232, 30:248, 30:250,  
 30:258, 30:259, 30:272, 30:273,  
 30:349, 30:409, 30:410, 30:411,  
 30:412, 30:413, 30:414, 30:415,  
 30:416, 30:417, 30:418, 30:419,  
 30:420, 30:421, 30:422, 30:425,  
 30:426, 30:429, 30:430, 30:431,  
 30:432, 30:433, 30:434, 30:435,  
 30:436, 30:437, 30:438, 30:439,  
 30:440, 30:441, 30:443, 30:444,  
 30:445, 30:446, 30:447, 30:448,  
 30:449, 30:452, 30:453, 30:454,  
 30:456, 30:457, 30:458, 30:459,  
 30:460, 30:461, 30:462, 30:463,  
 30:464, 30:465, 30:466, 30:468,  
 30:472, 30:475, 30:482, 30:484,  
 30:487, 30:488, 30:490, 30:493,  
 30:495, 30:590, 30:592, 30:594,  
 30:596, 30:598, 30:600, 38:42,  
 38:45, 38:48, 38:51, 38:162, 38:411  
 $\backslash$ mathring ..... 30:539, 1348  
 $\backslash$ mathrm ..... 29:6,  
 29:485, 29:528, 29:560, 30:159, 1305  
 $\backslash$ mathsection .....  
 . 21:331, 22:258, 22:270, 30:625, 1329  
 $\backslash$ mathsf ..... 29:9,  
 29:490, 29:533, 29:563, 30:163, 30:166

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\mathsterling</code> . . . . .	21:339, 30:625, 1329	<code>\medspace</code> . . . . .	38:214
<code>\mathstrut</code> . . .	38:84, 38:93, 38:171, 38:172	<code>\MessageBreak</code> . . . . .	03:101, 14:3, 14:6, 14:13, 14:33, 14:46, 14:60, 14:73, 14:220, 14:222, 14:228, 14:235, 17:19, 21:179, 21:1012, 21:1573, 21:1575, 21:1577, 21:1580, 24:35, 24:36, 24:633, 24:667, 25:2844, 26:21, 26:22, 26:68, 26:89, 26:328, 26:495, 26:515, 26:547, 26:563, 26:578, 26:591, 27:31, 27:33, 28:281, 28:329, 28:654, 28:663, 28:801, 05:82, 05:85, 05:86, 05:87, 05:88, 05:89, 05:90, 05:103, 05:104, 05:105, 05:106, 05:107, 29:62, 29:95, 32:144, 33:23, 33:43, 33:45, 33:64, 33:812, 33:814, 33:815, 33:816, 33:818, 33:820, 33:821, 33:822, 33:823, 33:824, 33:874, 33:876, 33:883, 33:890, 33:1105, 37:56, 37:121, 37:160, 06:245, 06:383, 06:422, 06:450, 50:353, 50:367, 50:742, 50:753, 50:755, 50:757, 50:768, 50:775, 50:777, 50:962, 50:963, 50:964, 50:965, 50:975, 50:976, 50:978, 50:979, 50:980, 50:982, 50:984, 50:1070, 50:1071, 50:1073, 50:1074, 50:1075, 50:1077, 50:1079, 50:1097, 50:1098, 50:1099, 50:1100, 50:1182, 50:1199, 50:1200, 50:1272, 50:1289, 50:1328, 50:1403, 50:1422, 50:1461, 50:1516, 50:1550, 50:1666, 50:1668, 50:1751, 50:1754, 50:1767, 50:1769, 52:488, 53:99, 53:175, 53:376, 53:504, 53:505, 53:506, 53:507, 54:829, 54:2570, 54:2617, 57:300, 57:301, 57:302, 57:304, 1326
<code>\mathsurround</code> . . . . .	02:275, 02:396, 1346	<code>\mho</code> . . . . .	29:852
<code>\mathsymbol</code> . . . . .	28:1025	<code>\mid</code> . . . . .	30:413
<code>\mathhtt</code> 29:12, 29:495, 29:538, 29:566, 30:165		<code>\min</code> . . . . .	38:23
<code>\mathunderscore</code> . . . . .	30:625, 1330	<code>minipage (env.)</code> . . . . .	890
<code>\mathversion</code> .	24:399, 29:697, 29:699, 1305	<code>\minipage</code> . . . . .	40:424
<code>\mathversion.</code> . . . . .	1304	<code>\mit</code> . . . . .	29:905
<code>\matrix</code> . . . . .	38:169, 38:173, 38:180	<code>\mkern</code> . . . . .	30:346, 30:349, 30:351, 30:473, 30:482, 30:524, 30:525, 30:526, 30:556, 30:557, 30:558, 30:559, 30:560, 30:561, 30:562, 30:563, 38:36, 38:37, 38:40, 38:73, 38:74, 44:240, 44:263
<code>\max</code> . . . . .	38:22	<code>mlist commands:</code>	
<code>\maxdeadcycles</code> . . . . .	54:3, 02:248	<code>mlist_to_hlist</code> . . . . .	04:1008
<code>\maxdepth</code> . . . . .	18:302, 18:335, 20:60, 20:129, 20:184, 54:68, 54:148, 54:149, 54:175, 54:176, 54:504, 54:593, 54:594, 54:767, 54:1074, 54:1341, 57:152, 02:268, 1384	<code>mode commands:</code>	
<code>\maxdimen</code> . . . . .	24:743, 24:753, 24:789, 24:804, 26:401, 26:454, 30:469, 42:474, 42:502, 42:532, 42:610, 42:627, 50:1605, 50:1653, 50:1662, 53:351, 53:353, 53:415, 54:296, 54:2429, 54:2449, 54:2454, 54:2840, 54:2908, 54:2909, 54:2911, 57:156, 02:179, 02:269, 02:270, 02:375, 02:413, 02:429, 02:443, 02:444, 02:462, 02:478, 02:493, 1162	<code>\mode_if_horizontal:TF</code> .	16:95, 16:100
<code>\mbox</code> . . . . .	889	<code>\mode_if_inner:TF</code> . . . . .	16:96
<code>\mbox</code> . . . . .	19:13, 21:313, 21:430, 21:591, 21:1189, 29:731, 30:517, 40:11, 40:20, 40:24, 42:52, 45:409, 45:416, 45:437, 45:444, 02:408, 1334	<code>\mode_if_math:TF</code> . . . . .	28:360
<code>mc (tag socket)</code> . . . . .	55:54		
<code>\mddefault</code> . . . . .	29:19, 29:363, 29:369, 29:370, 29:371, 29:410, 29:411, 29:412, 29:421, 29:448, 29:464, 29:481, 29:522, 29:558, 30:104, 30:116, 30:118, 30:132, 703		
<code>\mdseries</code> . . . . .	29:17, 29:18, 29:314, 29:356, 29:407, 29:408, 29:442, 29:443, 29:462, 29:463, 29:556, 29:557, 29:734, 32:20, 712		
<code>mdseries</code> . . . . .	29:499		
<code>mdseries/defaults</code> . . . . .	29:499		
<code>\meaning</code> . . . . .	01:203, 01:212, 28:699, 28:712, 28:813, 28:878, 28:925, 28:989, 28:1083, 28:1179, 28:1283, 06:332, 06:394, 06:432, 06:460, 01:307, 06:543, 06:896		
<code>\medbreak</code> . . . . .	06:977, 06:998, 02:390		
<code>\mediumseries</code> . . . . .	712		
<code>\medmuskip</code> . . . . .	30:656, 38:36, 38:38, 38:224, 38:227, 38:241		
<code>\medskip</code> . . . . .	18:447, 02:393		
<code>\medskipamount</code> . . . .	18:448, 18:450, 02:392		

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpara.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

`\mode_if_vertical:TF` . 16:114, 16:126  
`\models` . . . . . 30:495, 1350  
module commands:  
  `module_error` . . . . . 04:344  
  `module_info` . . . . . 04:344  
  `module_warning` . . . . . 04:344  
`\module_error` . . . . . 43  
`\module_info` . . . . . 43  
`\module_warning` . . . . . 43  
`modules` . . . . . 04:297  
`\month` . . . . . 03:11, 03:17, 01:169,  
  50:1306, 50:1439, 50:1528, 02:260  
`\moveright` . . . . . 54:911, 54:979, 54:1038  
`\mp` . . . . . 30:400  
`\mscount` . . . . . 41:379  
msg commands:  
  `\msg_...` . . . . . 1368  
  `\msg_error:nn` . . . . . 10:49, 11:268,  
  16:122, 16:132, 36:14, 08:436, 08:453  
  `\msg_error:nnn` . . . . .  
  . . . 08:2190, 10:30, 10:96, 10:115,  
  10:136, 11:63, 11:70, 11:186, 11:234,  
  11:248, 11:292, 11:314, 11:421,  
  11:434, 11:451, 11:507, 11:545,  
  11:624, 11:637, 11:653, 11:762,  
  11:914, 48:11, 48:273, 51:276, 52:75,  
  07:349, 07:756, 07:3175, 07:3181,  
  07:3192, 07:3211, 07:3214, 07:3222,  
  08:76, 08:94, 08:179, 08:208, 08:211,  
  08:461, 08:525, 08:543, 08:613, 08:633  
  `\msg_error:nnnn` . . . . .  
  . . . . . 09:60, 09:118, 09:415,  
  10:83, 10:112, 10:133, 11:57, 11:76,  
  11:200, 11:563, 11:591, 11:603,  
  11:715, 11:727, 11:827, 11:931,  
  11:937, 16:20, 16:33, 16:53, 16:65,  
  16:108, 36:35, 48:244, 51:38, 51:80,  
  51:250, 07:464, 07:472, 07:496,  
  07:500, 07:536, 07:567, 07:582,  
  07:668, 07:685, 07:713, 07:725,  
  07:744, 07:781, 07:1152, 07:2063,  
  07:2700, 07:2704, 07:3123, 07:3137,  
  07:3242, 07:3256, 08:112, 08:507, 08:657  
  `\msg_error:nnnnn` . . . . . 11:49,  
  11:418, 07:675, 07:700, 07:2223,  
  07:2230, 07:2539, 08:440, 08:471, 08:481  
  `\msg_error:nnnnnn` . . . . .  
  . . . 08:1777, 08:1338, 08:1350, 08:1375  
  `\msg_expandable_error:nn` . . . . .  
  . . . . . 08:341, 08:342  
  `\msg_expandable_error:nnn` . . . . .  
  . . . . . 08:2585, 05:189, 36:77,  
  36:113, 07:420, 07:3288, 08:370, 08:1278  
  `\msg_expandable_error:nnnn` . . . . .  
  . . . . . 52:464, 07:2431, 07:2458  
  `\msg_info:nnnn` . . . . .  
  . . . . . 11:110, 11:194, 11:404,  
  11:672, 11:695, 11:711, 07:73,  
  07:84, 07:234, 07:235, 07:251, 07:255  
  `\msg_line_context:` . . . . .  
  . . . . . 08:2667, 08:2672, 08:2676, 08:2723,  
  11:1037, 11:1043, 11:1050, 11:1057,  
  11:1064, 11:1071, 11:1079, 11:1172,  
  11:1174, 11:1178, 11:1181, 48:20,  
  48:94, 48:180, 48:259, 07:3080,  
  07:3085, 07:3090, 07:3095, 08:580  
  `\msg_module_name:n` . . . . .  
  . . . . . 51:95, 51:255, 51:261, 51:265  
  `\g_msg_module_name_prop` . . . . . 08:2609  
  `\g_msg_module_type_prop` . . . . . 08:2607,  
  08:2608, 10:181, 11:1192, 48:313, 07:58  
  `\msg_new:nnn` . . . . .  
  . . . . . 08:2665, 08:2670, 08:2674, 08:2719,  
  08:2725, 08:2730, 08:2735, 08:2740,  
  08:2744, 08:2751, 08:2916, 11:1171,  
  11:1173, 11:1175, 11:1180, 11:1182,  
  11:1187, 05:191, 51:253, 52:470,  
  07:1153, 07:3034, 07:3077, 07:3082,  
  07:3087, 07:3092, 07:3097, 07:3109  
  `\msg_new:nnnn` . . . . . 08:2610, 08:2620,  
  08:2627, 08:2634, 08:2643, 08:2657,  
  08:2679, 08:2695, 08:2708, 09:593,  
  09:603, 10:158, 10:163, 10:167,  
  10:171, 10:177, 11:993, 11:1001,  
  11:1007, 11:1016, 11:1022, 11:1029,  
  11:1036, 11:1042, 11:1049, 11:1056,  
  11:1063, 11:1070, 11:1078, 11:1085,  
  11:1094, 11:1100, 11:1106, 11:1113,  
  11:1119, 11:1125, 11:1131, 11:1137,  
  11:1143, 11:1159, 11:1165, 16:144,  
  16:155, 36:246, 36:252, 36:258,  
  48:314, 48:322, 48:329, 51:91,  
  51:258, 51:281, 07:2858, 07:2865,  
  07:2872, 07:2879, 07:2886, 07:2892,  
  07:2898, 07:2905, 07:2912, 07:2919,  
  07:2926, 07:2933, 07:2941, 07:2948,  
  07:2955, 07:2962, 07:2970, 07:2978,  
  07:2987, 07:2994, 07:3001, 07:3008,  
  07:3015, 07:3021, 07:3027, 07:3036,  
  07:3042, 07:3049, 07:3056, 07:3067  
  `\msg_redirect_module:nnn` . . . . . 07:57  
  `\msg_show:nnnnn` . . . . . 11:984  
  `\msg_show:nnnnnn` . . . . . 11:973  
  `\msg_show_item_unbraced:nn` . . . . .  
  . . . . . 11:977, 11:989  
  `\msg_warning:nnn` . . . . . 07:81, 08:295, 08:313  
  `\msg_warning:nnnn` . . . . . 08:2915,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=ltthyphen.dtx, 57=ltfinal.dtx

- 51:249, 07:737, 07:1628, 07:1749,  
08:995, 08:1008, 08:1030, 08:1044  
\msg\_warning:nnnnn ..... 08:785  
\msg\_warning:nnnnnn ..... 08:1785  
msg internal commands:  
  \c\_\_msg\_coding\_error\_text\_tl ...  
    ..... 48:317, 48:325, 48:332  
  \c\_\_msg\_return\_text\_tl 48:320, 48:337  
\mskip ..... 38:36, 38:38,  
    38:219, 38:238, 38:241, 38:243, 38:244  
\mu ..... 30:290  
\mubyte ..... 57:352  
\multicolumn ..... 41:233, 1280  
\multipt ..... 42:78, 42:810, 42:827  
\multispan ..... 41:233, 41:379, 1339  
\muskip . 04:34, 30:556, 30:557, 02:29, 02:51  
muskip commands:  
  \muskip\_eval:n ..... 11:367  
  \muskip\_new:N ..... 11:36  
  \l\_tmpa\_muskip ..... 356  
\muskipdef ..... 04:228, 02:51  
\muskipzero ..... 04:228
- N
- \n 04:331, 04:333, 04:340, 04:342, 04:469,  
  04:688, 04:713, 04:737, 04:778,  
  04:800, 04:819, 04:827, 04:828,  
  04:853, 04:870, 04:909, 04:916,  
  04:917, 04:924, 04:936, 57:121, 57:126  
\nabla ..... 30:330  
\NAME ..... 79  
\narrower ..... 02:401  
\natural ..... 30:340  
\ncallback ..... 04:783  
\ndefault ..... 04:788, 04:792  
\ne ..... 30:424, 745  
\narrow ..... 30:416  
\NeedsDocumentMetadata ..... 1053  
\NeedsDocumentMetadata ..... 50:771  
\NeedsFormat ..... 1309  
\NeedsTeXFormat .....  
  . 26:12, 33:781, 50:747, 50:1813, 1313  
\neg ..... 30:336, 30:337  
\negmedspace ..... 38:214, 1365  
\negthickspace ..... 38:214, 1365  
\negthinspace ..... 18:544, 38:214, 1362  
\neq ..... 30:423, 745  
new commands:  
  new\_attribute ..... 04:410  
  new\_bytecode ..... 04:444  
  new\_chunkname ..... 04:457  
  new\_luafunction ..... 04:473  
  new\_whatsit ..... 04:432  
\new\_attribute ..... 41  
  \new\_bytecode ..... 41  
  \new\_chunkname ..... 41  
  \new\_luafunction ..... 41  
  \new\_whatsit ..... 41  
  \newattribute ..... 40  
  \newattribute ..... 04:74, 04:238  
  \newbox ... 12:13, 37:585, 38:66, 39:27,  
    40:154, 41:16, 41:17, 41:18, 41:343,  
    42:6, 42:669, 42:674, 54:62, 54:98,  
    54:99, 54:100, 02:47, 02:184, 02:398  
  \newcatcodetable ..... 40  
  \newcatcodetable ..... 04:84,  
    04:93, 04:94, 04:120, 04:121, 04:242  
  \newcommand ..... 79  
  \newcommand .....  
    .. 21:4, 25:2918, 25:2923, 25:2928,  
    29:37, 29:73, 30:63, 30:64, 30:65,  
    30:66, 30:68, 30:69, 30:71, 30:72,  
    30:104, 30:105, 30:106, 30:107,  
    30:108, 30:109, 30:131, 30:132,  
    30:133, 06:95, 36:241, 37:398,  
    37:399, 37:400, 37:401, 42:681,  
    52:573, 52:574, 52:575, 52:576,  
    52:578, 54:2991, 54:2994, 54:2997,  
    54:2998, 54:3001, 54:3002, 57:561, 81  
  \NewCommandCopy .....  
    . 06:565, 06:567, 07:1129, 07:1181,  
    07:1199, 07:1212, 07:1227, 07:1345, 101  
  \newcount ..... 12:7, 12:8,  
    18:125, 20:7, 22:42, 22:62, 24:422,  
    26:26, 28:28, 28:143, 28:501, 38:55,  
    38:415, 38:416, 39:23, 39:24, 39:25,  
    39:26, 39:56, 39:257, 39:272, 40:473,  
    41:11, 41:12, 41:13, 41:14, 41:15,  
    41:335, 41:336, 41:337, 42:663,  
    42:664, 42:665, 42:666, 42:675,  
    44:36, 44:140, 44:141, 45:3, 45:267,  
    45:268, 45:269, 45:270, 50:1602,  
    54:81, 54:83, 54:85, 54:87, 54:89,  
    54:97, 02:47, 54:2596, 54:2989,  
    54:2992, 54:2995, 54:2999, 57:3,  
    57:4, 57:5, 57:91, 02:231, 02:302, 1352  
  \newcounter ..... 525  
  \newcounter ..... 22:10  
  \newdimen ..... 12:10,  
    12:11, 12:12, 18:124, 26:415, 26:416,  
    38:53, 39:9, 39:10, 39:11, 39:12,  
    39:13, 39:14, 39:15, 39:16, 39:17,  
    39:18, 39:19, 39:20, 39:21, 39:22,  
    40:210, 40:211, 41:3, 41:5, 41:6,  
    41:7, 41:8, 41:166, 41:338, 41:339,  
    41:340, 41:341, 42:3, 42:4, 42:5,  
    42:7, 42:431, 42:432, 42:433, 42:434,  
    42:435, 42:436, 42:667, 42:668,

File Key: 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

- 42:670, 42:671, 42:672, 42:673,  
45:451, 54:47, 54:48, 54:49, 54:51,  
54:52, 54:53, 54:54, 54:55, 54:56,  
54:57, 54:58, 54:59, 54:60, 54:61,  
54:67, 54:69, 54:70, 54:71, 54:72,  
54:84, 54:86, 54:88, 54:90, 54:91,  
54:92, 54:93, 54:94, 54:95, 54:96,  
02:47, 54:507, 54:2597, 54:2598,  
54:2603, 02:179, 02:181, 02:182, 02:301
- \NewDocumentCommand ..... 08:2756,  
08:2758, 08:2760, 08:2764, 08:2766,  
08:2768, 08:2779, 08:2781, 08:2791,  
08:2793, 08:2802, 08:2804, 08:2811,  
08:2813, 08:2815, 08:2817, 08:2819,  
08:2843, 08:2845, 08:2848, 17:29,  
17:51, 17:60, 17:61, 17:62, 20:769,  
22:131, 22:146, 22:184, 22:196,  
35:66, 35:68, 35:163, 36:80, 48:394,  
51:216, 51:218, 51:229, 51:287,  
57:633, 57:640, 57:647, 07:3117, 200
- \NewDocumentEnvironment .....  
..... 07:2901, 07:2908, 07:3153, 224
- \newenvironment ..... 80
- \newenvironment .....  
..... 06:187, 50:1304, 50:1437, 50:1526, 224
- \NewEnvironmentCopy . 06:606, 06:608, 1375
- \NewExpandableDocumentCommand .....  
... 36:118, 48:402, 48:404, 48:406,  
48:408, 48:411, 48:414, 57:601, 07:3236
- \newfam ..... 04:38, 24:17, 02:47, 1305
- \newfont ..... 29:701
- \newgroup ..... 28:48
- \newhelp ..... 02:176
- \NewHook ..... 08:2756, 08:2931,  
20:73, 20:74, 20:75, 20:367, 20:370,  
20:419, 26:151, 29:499, 29:500,  
29:501, 29:502, 29:503, 29:504,  
29:505, 29:506, 29:507, 37:36,  
37:37, 37:38, 37:39, 37:40, 37:101,  
37:102, 37:103, 37:104, 37:105,  
50:1048, 50:1049, 52:177, 54:730, 223
- \NewHookPair ..... 313
- \NewHookWithArguments 08:2762, 35:101, 220
- \newif ..... 03:73, 12:9, 20:5, 20:6,  
24:267, 25:2789, 25:2801, 28:16,  
29:609, 32:82, 33:832, 33:1185,  
33:1186, 35:3, 06:209, 38:75, 38:76,  
38:203, 38:417, 39:28, 39:29, 39:30,  
39:31, 39:32, 39:33, 39:140, 40:423,  
40:529, 41:19, 41:251, 42:157,  
42:427, 42:428, 42:429, 42:430,  
42:459, 42:460, 44:38, 44:124, 50:2,  
06:964, 54:73, 54:74, 54:75, 54:76,  
54:77, 54:78, 54:79, 54:80, 1304
- \newinsert ..... 40:474, 45:390,  
54:19, 54:2428, 02:116, 02:142, 1355
- \newlabel .... 35:84, 35:106, 35:174, 1338
- \newlanguage ..... 02:47, 57:284
- \newlength ..... 536
- \newlength ..... 23:3
- \newline ..... 18:93, 18:100, 18:106
- \newlinechar ..... 06:20, 02:256, 01:56
- \newluabytecode ..... 41
- \newluabytecode ..... 04:197, 04:252
- \newluachunkname ..... 41
- \newluachunkname ..... 04:205, 04:254
- \newluacmd ..... 40
- \newluacmd ..... 04:181, 41
- \newluafunction ..... 40
- \newluafunction .....  
..... 04:4, 04:173, 04:236, 04:248, 40
- \NewMarkClass ..... 48:399,  
48:520, 57:25, 57:26, 57:27, 1015
- \NewMarkRegion ..... 1025
- \newmarks ..... 48:22, 57:6, 1021
- \newmathalphabet ..... 27:13, 27:109
- \NewMirroredHookPair .....  
..... 08:2756, 08:2933, 54:729, 54:731, 202
- \NewMirroredHookPairWithArguments ..  
..... 08:2762, 202
- \NewModuleRelease .....  
09:4, 03:152, 10:4, 11:7, 16:4, 17:3,  
33:2, 36:4, 48:4, 07:9, 55:423, 08:4, 1367
- \newmuskip ..... 02:47
- \newpage .... 54:111, 54:118, 54:129, 1183
- \NewProperty ..... 36:38, 36:268, 817
- \newprotectedluacmd ..... 41
- \newprotectedluacmd 04:181, 21:1034, 53:28
- \newread ..... 02:47, 02:177, 1307
- \NewReversedHook ..... 08:2756,  
08:2932, 20:368, 20:369, 20:420,  
20:421, 50:1050, 50:1051, 52:178, 202
- \NewReversedHookWithArguments .....  
..... 08:2762, 202
- \newrobustcmd ..... 96
- \newsavebox ..... 889
- \newsavebox ..... 40:154
- \newskip ..... 12:14,  
12:15, 12:17, 18:450, 18:451, 18:452,  
18:517, 18:530, 23:3, 37:495, 38:418,  
38:553, 39:2, 39:3, 39:4, 39:5, 39:6,  
39:7, 39:8, 02:47, 54:3003, 54:3004,  
54:3005, 54:3009, 54:3010, 54:3013,  
54:3014, 54:3015, 54:3019, 54:3020,  
54:3021, 02:180, 02:183, 02:299, 02:300
- \NewSocket .... 10:182, 10:203, 35:118,  
35:119, 54:663, 54:722, 54:723, 343

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=ltthyphen.dtx, 57=ltfinal.dtx

- \NewSocketPlug . . . . . 10:173, [10:182](#),  
10:207, 35:120, 54:664, 54:674,  
54:681, 54:688, 54:697, 54:702,  
54:707, 54:724, 54:727, 55:21, [339](#)
- \NewStructureName . . . . . [1264](#)
- \NewStructureName . . . . . [55:265](#)
- \NewTaggingSocket . . . . . [1263](#)
- \NewTaggingSocket . 55:7, 55:54, 55:62,  
55:73, 55:75, 55:79, 55:89, 55:90,  
55:96, 55:97, 55:165, 55:179, 55:180,  
55:181, 55:182, 55:183, 55:184,  
55:185, 55:186, 55:187, 55:188,  
55:189, 55:190, 55:191, 55:192,  
55:193, 55:194, 55:195, 55:196,  
55:197, 55:198, 55:199, 55:200,  
55:201, 55:202, 55:203, 55:204,  
55:205, 55:206, 55:207, 55:208,  
55:209, 55:210, 55:211, 55:212,  
55:213, 55:214, 55:215, 55:216,  
55:217, 55:218, 55:219, 55:220,  
55:221, 55:222, 55:223, 55:224,  
55:225, 55:226, 55:227, 55:228,  
55:229, 55:230, 55:231, 55:232,  
55:233, 55:234, 55:235, 55:236,  
55:237, 55:238, 55:239, 55:240,  
55:241, 55:242, 55:243, 55:244,  
55:245, 55:246, 55:247, 55:248,  
55:249, 55:250, 55:251, 55:252,  
55:253, 55:254, 55:255, 55:256,  
55:257, 55:258, 55:259, 55:260, [1263](#)
- \NewTaggingSocketPlug . . . . . [1263](#)
- \NewTaggingSocketPlug . . . . . 55:20,  
55:55, 55:63, 55:74, 55:76, 55:80,  
55:91, 55:92, 55:93, 55:94, 55:99,  
55:109, 55:117, 55:145, 55:167, [1263](#)
- \NewTemplateType . . . . .  
. . . . . 11:1097, 11:1162, [11:1193](#), [353](#)
- \newtheorem . . . . . [43:1](#), [1339](#)
- \newtie . 21:875, 33:152, 33:153, 33:172,  
33:669, 33:976, 33:977, 33:1284, [769](#)
- \newtoks . . . . .  
03:36, 12:16, 16:77, 24:420, 24:421,  
25:2887, 26:248, [02:47](#), 02:176, [1355](#)
- \newwhatsit . . . . . [41](#)
- \newwhatsit . . . . . [04:189](#), [04:250](#)
- \newwrite . . . . . 20:3, 20:4,  
[44:154](#), [46:4](#), [46:21](#), [02:47](#), 02:178, [1329](#)
- \newXeTeXintercharclass . . . . . [57:35](#)
- \next . . . . . [1332](#)
- \NextLinkTarget . . . . . [17:25](#)
- nfss internal commands:  
  \\_nfss\_init\_mv\_freeze:N . . . . .  
  . . . . . [28:334](#), [28:359](#), [28:360](#)
- \\_nfss\_transform\_scriptfont:nw .  
  . . . . . [26:346](#), [26:350](#)
- \NG . . . . . 21:554, 21:1169, 57:671, [1324](#)
- \ng . . . . . 21:575, 21:1170, 57:671, [1324](#)
- \ni . . . . . 30:441, 30:442
- \noalign 30:350, 30:542, 30:545, 30:548,  
30:549, 30:553, 30:554, 38:171,  
38:172, 38:188, 38:191, 38:205,  
38:497, 38:507, 41:224, 41:230,  
41:359, 41:378, 42:148, 42:154, [838](#)
- \nobreak . . 18:60, 18:72, 18:116, 18:142,  
18:148, 18:161, 18:174, 18:200,  
18:398, 18:406, 18:432, 18:440,  
18:461, 18:468, 18:528, 20:203,  
20:218, 20:232, 21:430, 21:456,  
21:458, 21:591, 21:1189, 37:420,  
37:427, 40:599, 40:609, 44:90,  
44:237, 44:238, 44:242, 44:260,  
44:261, 44:265, 45:531, 48:270,  
49:48, 49:58, 49:71, 49:79, 49:94,  
49:102, 06:978, 06:999, 54:341,  
54:1500, 54:1649, 54:1810, 57:208,  
57:210, 57:214, 57:215, 57:216,  
57:220, 02:378, 02:381, [02:383](#), [426](#)
- \nobreakdashes . . . . . [18:453](#)
- \nobreakspace . . . . . [18:467](#), [450](#)
- \nobreakspace\_ . . . . . [1344](#)
- \NoCaseChange . . . . . [57:571](#), [1373](#)
- \nocite . . . . . [1009](#)
- \nocite . . . . . [47:59](#), [1331](#)
- \nocorr . . . [32:43](#), [32:58](#), [32:62](#), [32:65](#), [1327](#)
- \nocorrlist . . . . . [32:89](#), [32:121](#)
- \noexpand . . . . . [1210](#)
- \nofiles . . . . . [454](#)
- \nofiles . . . . . [20:199](#), [831](#)
- \noindent . . . . 24:767, 24:793, 44:139, [418](#)
- \nointerlineskip . . . . 30:350, 30:542,  
30:545, 30:549, 30:553, 38:314,  
38:342, 38:367, 42:562, 42:565,  
42:575, 42:577, 54:2418, 54:2426, [02:373](#)
- \nolimits . . . . . 30:359, 30:366,  
38:3, 38:4, 38:5, 38:9, 38:10, 38:11,  
38:12, 38:13, 38:14, 38:15, 38:16,  
38:17, 38:18, 38:19, 38:20, 38:21,  
38:26, 38:27, 38:28, 38:29, 38:31, 38:34
- \nolinebreak . . . . . [433](#)
- \nolinebreak . . . . . [18:9](#), [18:28](#)
- \nonfrenchspacing . . . . 02:582, 20:48,  
20:118, 20:176, 06:979, 06:1000, [02:306](#)
- \nonscript . . . . . 38:36, 38:38
- \nonstopmode . . . . . [1029](#)
- \nonumber . . . . . [38:480](#), [38:519](#), [38:520](#)
- \nopagebreak . . . . . [433](#)
- \nopagebreak . . . . . [18:7](#), [18:26](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

<code>\noprotusion</code> .....	<a href="#">44:247</a> , <a href="#">44:270</a>	<code>\nunknown</code> .....	<a href="#">04:805</a>
<code>\normalbaselines</code> .....	<a href="#">38:167</a> , <a href="#">38:169</a> , <a href="#">02:271</a> , <a href="#">02:284</a> , <a href="#">02:285</a> , <a href="#">02:310</a>	<code>\narrow</code> .....	<a href="#">30:418</a>
<code>\normalbaselineskip</code> .....	<a href="#">26:189</a> , <a href="#">40:396</a> , <a href="#">40:415</a> , <a href="#">02:299</a> , <a href="#">02:311</a>	<code>\nxt</code> .....	<a href="#">1332</a>
<code>\normalcolor</code> .....	<a href="#">38:410</a> , <a href="#">38:549</a> , <a href="#">40:110</a> , <a href="#">40:465</a> , <a href="#">44:243</a> , <a href="#">44:266</a> , <a href="#">45:97</a> , <a href="#">45:166</a> , <a href="#">54:221</a> , <a href="#">54:620</a> , <a href="#">54:746</a> , <a href="#">54:918</a> , <a href="#">54:933</a> , <a href="#">54:983</a> , <a href="#">54:993</a> , <a href="#">54:1042</a> , <a href="#">54:1052</a> , <a href="#">54:2886</a> , <a href="#">54:2929</a> , <a href="#">54:2959</a> , <a href="#">1323</a>	<b>O</b>	
<code>\normalfont</code> .....	<a href="#">24:744</a> , <a href="#">24:805</a> , <a href="#">29:736</a> , <a href="#">29:771</a> , <a href="#">29:773</a> , <a href="#">29:782</a> , <a href="#">29:787</a> , <a href="#">29:789</a> , <a href="#">29:798</a> , <a href="#">29:803</a> , <a href="#">29:805</a> , <a href="#">29:813</a> , <a href="#">29:820</a> , <a href="#">29:822</a> , <a href="#">29:828</a> , <a href="#">32:18</a> , <a href="#">37:573</a> , <a href="#">38:410</a> , <a href="#">38:549</a> , <a href="#">44:243</a> , <a href="#">44:266</a> , <a href="#">45:401</a> , <a href="#">1337</a>	<code>\O</code> .....	<a href="#">21:264</a> , <a href="#">21:421</a> , <a href="#">21:556</a> , <a href="#">21:794</a> , <a href="#">21:1154</a> , <a href="#">57:670</a>
<code>normalfont</code> .....	<a href="#">29:499</a>	<code>\o</code> .....	<a href="#">21:273</a> , <a href="#">21:426</a> , <a href="#">21:577</a> , <a href="#">21:805</a> , <a href="#">21:1160</a> , <a href="#">57:670</a>
<code>\normalize</code> .....	<a href="#">1317</a>	<code>\oalign</code> .....	<a href="#">02:410</a>
<code>\normallineskip</code> .....	<a href="#">40:394</a> , <a href="#">40:414</a> , <a href="#">02:299</a> , <a href="#">02:310</a>	<code>\obeycr</code> .....	<a href="#">18:556</a>
<code>\normallineskiplimit</code> .....	<a href="#">38:206</a> , <a href="#">40:379</a> , <a href="#">40:395</a> , <a href="#">40:401</a> , <a href="#">02:299</a> , <a href="#">02:311</a>	<code>\obeyedline</code> .....	<a href="#">07:1650</a> , <a href="#">07:1695</a> , <a href="#">07:1768</a> , <a href="#">07:1770</a> , <a href="#">07:1772</a> , <a href="#">07:2244</a> , <a href="#">07:2250</a> , <a href="#">07:2259</a> , <a href="#">07:2266</a> , <a href="#">07:2334</a> , <a href="#">02:338</a> , <a href="#">02:361</a> , <a href="#">1378</a>
<code>\normalmarginpar</code> .....	<a href="#">45:387</a>	<code>\obeyedspace</code> ...	<a href="#">02:339</a> , <a href="#">02:342</a> , <a href="#">02:362</a> , <a href="#">26</a>
<code>\normalsfcodes</code> .....	<a href="#">20:44</a> , <a href="#">20:46</a> , <a href="#">20:48</a> , <a href="#">20:114</a> , <a href="#">20:116</a> , <a href="#">20:118</a> , <a href="#">20:172</a> , <a href="#">20:174</a> , <a href="#">20:176</a> , <a href="#">20:198</a> , <a href="#">54:902</a> , <a href="#">54:972</a> , <a href="#">54:1031</a> , <a href="#">1346</a>	<code>\obeylines</code>	<a href="#">37:544</a> , <a href="#">37:565</a> , <a href="#">37:713</a> , <a href="#">37:714</a> , <a href="#">06:980</a> , <a href="#">06:1001</a> , <a href="#">54:834</a> , <a href="#">02:327</a> , <a href="#">26</a>
<code>\normalshape</code> .....	<a href="#">25:3202</a> , <a href="#">25:3243</a> , <a href="#">635</a>	<code>\obeyspaces</code> .....	<a href="#">06:981</a> , <a href="#">06:1002</a> , <a href="#">54:834</a> , <a href="#">02:327</a> , <a href="#">26</a>
<code>\normalsize</code> ....	<a href="#">20:42</a> , <a href="#">20:112</a> , <a href="#">20:170</a> , <a href="#">32:142</a> , <a href="#">45:23</a> , <a href="#">45:176</a> , <a href="#">45:372</a> , <a href="#">50:5</a> , <a href="#">54:901</a> , <a href="#">54:971</a> , <a href="#">54:1030</a> , <a href="#">206</a>	<code>\oddsidemargin</code> .....	<a href="#">54:48</a> , <a href="#">54:50</a> , <a href="#">54:893</a> , <a href="#">54:965</a> , <a href="#">54:1024</a>
<code>\not</code> .....	<a href="#">30:349</a> , <a href="#">30:423</a> , <a href="#">30:424</a> , <a href="#">30:446</a>	<code>\odot</code> .....	<a href="#">30:395</a>
<code>\notexpanded</code> .....	<a href="#">327</a>	<code>\OE</code> .....	<a href="#">21:263</a> , <a href="#">21:420</a> , <a href="#">21:555</a> , <a href="#">21:793</a> , <a href="#">21:1171</a> , <a href="#">57:613</a> , <a href="#">57:618</a> , <a href="#">57:623</a> , <a href="#">57:670</a> , <a href="#">1375</a>
<code>\notin</code> .....	<a href="#">30:472</a>	<code>\oe</code> .....	<a href="#">21:272</a> , <a href="#">21:425</a> , <a href="#">21:576</a> , <a href="#">21:806</a> , <a href="#">21:1172</a> , <a href="#">57:613</a> , <a href="#">57:618</a> , <a href="#">57:623</a> , <a href="#">57:670</a> , <a href="#">1299</a>
<code>\noexpand</code> .....	<a href="#">1309</a>	<code>\of</code> .....	<a href="#">38:67</a> , <a href="#">38:414</a>
<code>\nu</code> .....	<a href="#">30:291</a>	<code>off (plug)</code> .....	<a href="#">54:727</a>
<code>\null</code> .....	<a href="#">21:347</a> , <a href="#">21:383</a> , <a href="#">21:509</a> , <a href="#">21:512</a> , <a href="#">21:858</a> , <a href="#">21:861</a> , <a href="#">21:1277</a> , <a href="#">35:21</a> , <a href="#">35:38</a> , <a href="#">35:55</a> , <a href="#">37:538</a> , <a href="#">37:559</a> , <a href="#">37:722</a> , <a href="#">37:732</a> , <a href="#">38:112</a> , <a href="#">38:121</a> , <a href="#">38:169</a> , <a href="#">38:198</a> , <a href="#">44:237</a> , <a href="#">44:260</a> , <a href="#">53:391</a> , <a href="#">02:324</a> , <a href="#">1334</a>	<code>\offinterlineskip</code> .....	<a href="#">02:373</a>
<code>\nulldelimiterspace</code> ....	<a href="#">30:653</a> , <a href="#">02:273</a>	<code>\oint</code> .....	<a href="#">30:366</a>
<code>\nullfont</code> .....	<a href="#">37:244</a>	<code>\ointop</code> .....	<a href="#">30:365</a> , <a href="#">30:366</a>
<code>\number</code> .....	<a href="#">03:52</a> , <a href="#">03:61</a> , <a href="#">04:105</a> , <a href="#">22:233</a> , <a href="#">24:693</a> , <a href="#">24:696</a> , <a href="#">26:456</a> , <a href="#">28:65</a> , <a href="#">28:94</a> , <a href="#">28:114</a> , <a href="#">28:129</a> , <a href="#">28:165</a> , <a href="#">28:196</a> , <a href="#">28:226</a> , <a href="#">28:258</a> , <a href="#">29:728</a> , <a href="#">06:2</a> , <a href="#">06:132</a> , <a href="#">50:1213</a> , <a href="#">50:1306</a> , <a href="#">50:1439</a> , <a href="#">50:1528</a> , <a href="#">53:351</a> , <a href="#">01:70</a>	<code>\oldstylenums</code> .....	<a href="#">33:4</a> , <a href="#">33:340</a> , <a href="#">33:341</a> , <a href="#">33:342</a> , <a href="#">33:343</a> , <a href="#">33:344</a> , <a href="#">33:345</a> , <a href="#">33:346</a> , <a href="#">33:347</a> , <a href="#">33:348</a> , <a href="#">33:349</a> , <a href="#">33:574</a> , <a href="#">33:1097</a> , <a href="#">774</a>
<code>\numberline</code>	<a href="#">44:72</a> , <a href="#">44:82</a> , <a href="#">44:273</a> , <a href="#">45:17</a> , <a href="#">1308</a>	<code>\Omega</code> .....	<a href="#">30:318</a>
<code>\numexpr</code>	<a href="#">04:82</a> , <a href="#">04:105</a> , <a href="#">04:157</a> , <a href="#">21:1058</a> , <a href="#">28:151</a> , <a href="#">06:839</a> , <a href="#">02:112</a> , <a href="#">02:128</a> , <a href="#">02:138</a>	<code>\omega</code> .....	<a href="#">30:301</a>
		<code>\ominus</code> .....	<a href="#">30:398</a>
		<code>\omit</code> .....	<a href="#">38:191</a> , <a href="#">38:192</a> , <a href="#">41:369</a> , <a href="#">41:372</a> , <a href="#">41:379</a> , <a href="#">41:383</a>
		<code>\OmitIndent</code> .....	<a href="#">16:91</a> , <a href="#">16:170</a> , <a href="#">416</a>
		<code>on (plug)</code> .....	<a href="#">54:724</a>
		<code>\onecolumn</code> .....	<a href="#">54:120</a>
		<code>\OnlyDescription</code> .....	<a href="#">26:5</a> , <a href="#">31:3</a>
		<code>\oalign</code> .....	<a href="#">21:347</a> , <a href="#">21:377</a> , <a href="#">21:415</a> , <a href="#">21:503</a> , <a href="#">21:509</a> , <a href="#">21:511</a> , <a href="#">21:522</a> , <a href="#">21:538</a> , <a href="#">21:755</a> , <a href="#">21:788</a> , <a href="#">21:858</a> , <a href="#">21:861</a> , <a href="#">21:918</a> , <a href="#">21:1277</a> , <a href="#">29:733</a> , <a href="#">30:473</a> , <a href="#">30:476</a> , <a href="#">02:410</a> , <a href="#">1351</a>
		<code>\openin</code> .....	<a href="#">1361</a>
		<code>\openout</code> .....	<a href="#">1307</a>

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=lt para.dtx, 16=lt para.dtx, 17=lt meta.dtx, 18=lt space.dtx, 19=lt logos.dtx, 20=lt files.dtx, 21=lt outenc.dtx, 22=lt counts.dtx, 23=lt length.dtx, 24=lt fssbas.dtx, 25=lt fssaxes.dtx, 26=lt fssstrc.dtx, 27=lt fsscmp.dtx, 28=lt fssdcl.dtx, 29=lt fssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=lt fntcmd.dtx, 33=lt textcomp.dtx, 34=lt pageno.dtx, 35=lt xref.dtx, 36=lt properties.dtx, 37=lt miscen.dtx, 38=lt math.dtx, 39=lt lists.dtx, 40=lt boxes.dtx, 41=lt tab.dtx, 42=lt pictur.dtx, 43=lt thm.dtx, 44=lt sect.dtx, 45=lt float.dtx, 46=lt idxglo.dtx, 47=lt bibl.dtx, 48=lt marks.dtx, 49=lt page.dtx, 50=lt class.dtx, 51=lt keys.dtx, 52=lt filehook.dtx, 53=lt shipout.dtx, 54=lt output.dtx, 55=lt tagging.dtx, 56=lt thyphen.dtx, 57=lt final.dtx

- `\openup` ..... [38:199](#), [38:204](#)  
`\oplus` ..... [30:399](#)  
`\OptionNotUsed` ... [50:509](#), [50:536](#), [50:1116](#)  
 or commands:  
     `\or:` ..... [07:1503](#),  
         [07:1504](#), [08:1268](#), [08:1269](#), [08:1270](#),  
         [08:1271](#), [08:1272](#), [08:1273](#), [08:1274](#),  
         [08:1275](#), [08:1276](#), [08:1417](#), [08:1433](#)  
`\oslash` ..... [30:396](#)  
`\OT` ..... [21:392](#)  
`\otimes` ..... [30:397](#)  
`\outer` ..... [04:21](#), [04:38](#), [1357](#)  
`\output` ..... [54:261](#), [02:203](#)  
`\outputpenalty` ..... [54:263](#),  
         [54:277](#), [54:300](#), [54:303](#), [54:304](#),  
         [54:339](#), [54:1510](#), [54:1511](#), [54:1659](#),  
         [54:1660](#), [54:1820](#), [54:1823](#), [02:203](#)  
`\oval` ..... [42:450](#), [42:453](#), [42:811](#), [42:828](#)  
`\over` ..... [30:480](#), [38:162](#), [38:412](#)  
`\overbrace` ..... [30:547](#)  
`\overfullrule` ..... [49:142](#), [02:267](#)  
`\overleftarrow` ..... [30:544](#)  
`\overrightarrow` ..... [30:541](#)  
`\owns` ..... [30:442](#), [30:443](#)
- P**
- `\P` ..... [21:330](#), [1324](#)  
`package/.../after` ..... [1116](#)  
`package/.../before` ..... [1116](#)  
`package/after` ..... [1116](#)  
`package/before` ..... [1116](#)  
`\PackageError` .. [03:77](#), [03:135](#), [03:147](#),  
         [14:84](#), [21:1571](#), [33:787](#), [33:838](#), [33:882](#)  
`\PackageInfo` ... [14:84](#), [33:791](#), [33:807](#),  
         [33:812](#), [33:828](#), [33:829](#), [33:889](#), [33:1174](#)  
`\PackageNote` ..... [14:136](#), [1369](#)  
`\PackageNoteNoLine` ..... [14:136](#)  
`\PackageWarning` .....  
         [14:84](#), [33:789](#), [33:839](#), [33:1103](#), [53:503](#)  
`\PackageWarningNoLine` .....  
         [14:84](#), [21:1010](#), [54:2569](#)  
`page` ..... [36:235](#), [818](#)  
`page@sofar` (tag socket) ..... [55:231](#)  
`\pagebreak` ..... [433](#)  
`\pagebreak` .. [18:6](#), [18:7](#), [18:23](#), [18:25](#), [1198](#)  
`\pagegoal` ..... [54:2456](#), [54:2463](#)  
`pagenum` ..... [36:236](#), [818](#)  
`\pagenumbering` ..... [805](#)  
`\pagenumbering` ..... [34:5](#)  
`\pageref` ..... [35:10](#), [814](#)  
`\pageshrink` . [54:529](#), [54:533](#), [54:548](#), [54:780](#)  
`\pagestyle` ..... [49:2](#)  
`pagetarget` ..... [36:241](#), [819](#)  
`\pagetotal` ..... [54:106](#)
- `\paperheight` ..... [54:69](#)  
`\paperwidth` ..... [54:69](#)  
`\par` ..... [01:104](#), [15:3](#), [15:4](#),  
         [15:5](#), [04:156](#), [16:140](#), [16:176](#), [18:239](#),  
         [18:290](#), [24:770](#), [06:9](#), [06:21](#), [37:186](#),  
         [37:242](#), [37:420](#), [37:427](#), [37:536](#),  
         [37:557](#), [39:63](#), [39:110](#), [39:127](#),  
         [39:130](#), [39:137](#), [39:192](#), [39:195](#),  
         [40:385](#), [40:406](#), [40:461](#), [40:491](#),  
         [40:508](#), [41:195](#), [41:385](#), [44:41](#),  
         [44:90](#), [44:245](#), [44:267](#), [45:15](#), [45:24](#),  
         [45:249](#), [45:344](#), [45:478](#), [45:496](#),  
         [49:135](#), [49:136](#), [02:11](#), [53:407](#),  
         [54:145](#), [54:172](#), [54:198](#), [54:262](#),  
         [54:2462](#), [02:320](#), [02:336](#), [02:338](#),  
         [02:355](#), [02:377](#), [02:386](#), [02:387](#),  
         [02:388](#), [02:390](#), [02:392](#), [02:394](#), [1367](#)  
 para commands:  
     `\para_end:` ..... [16:93](#),  
         [16:93](#), [16:140](#), [16:141](#), [16:142](#), [425](#)  
     `\g_para_indent_box` .. [16:16](#), [16:49](#),  
         [16:84](#), [16:86](#), [16:89](#), [16:91](#), [16:117](#), [418](#)  
     `\para_omit_indent:` .. [16:88](#), [16:92](#), [418](#)  
     `\para_raw_end:` .....  
         [16:113](#), [16:135](#), [16:138](#), [427](#)  
     `\para_raw_indent:` .....  
         [16:113](#), [16:113](#), [16:136](#), [418](#)  
     `\para_raw_noindent:` .....  
         [16:113](#), [16:125](#), [16:137](#), [418](#)  
 para internal commands:  
     `\__para_handle_indent:` .....  
         [16:34](#), [16:66](#), [16:85](#), [16:85](#), [16:119](#)  
     `\g__para_standard_everypar_tl` ...  
         [16:12](#), [16:76](#), [16:78](#), [16:118](#), [16:129](#), [424](#)  
     `\__para_tmp:w` [16:37](#), [16:41](#), [16:68](#), [16:72](#)  
`para/after` ..... [16:6](#), [416](#)  
`para/before` ..... [16:6](#), [416](#)  
`para/begin` (tag socket) ..... [55:89](#)  
`para/begin` ..... [16:6](#), [416](#)  
`para/end` (tag socket) ..... [55:89](#)  
`para/end` ..... [16:6](#), [416](#)  
`para/off` (tag socket) ..... [55:73](#)  
`para/on` (tag socket) ..... [55:73](#)  
`para/restore` (tag socket) ..... [55:79](#)  
`para/semantic/begin` (tag socket) ... [55:96](#)  
`para/semantic/end` (tag socket) .... [55:96](#)  
`\paracntvalue` ..... [419](#)  
`\paragraphmark` ..... [44:143](#)  
`\PARALABEL` ..... [55:140](#)  
`\parallel` ..... [30:412](#)  
`\parbox` ..... [889](#)  
`\parbox` ..... [40:298](#), [414](#)  
`\parfillskip` ... [24:743](#), [24:759](#), [24:804](#),  
         [37:456](#), [37:466](#), [37:475](#), [37:483](#),

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

- 37:532, 37:554, 39:76, 40:393,  
40:414, 44:232, 44:255, 02:298, 427
- \parindent 37:456, 37:461, 37:466, 37:475,  
37:479, 37:483, 37:532, 37:554,  
39:50, 40:388, 40:409, 44:233,  
44:256, 02:279, 02:402, 02:403, 413
- \parsep ..... 39:1, 39:49, 39:90, 873
- \parseunicodedataI ..... 04:123, 04:162
- \parseunicodedataII ..... 04:124, 04:126
- \parseunicodedataIII ..... 04:128, 04:134
- \parseunicodedataIV ..... 04:130, 04:142
- \parseunicodedataV ..... 04:146, 04:149
- \parshape ..... 39:54, 421
- \parskip ..... 37:431, 37:530, 37:532,  
37:552, 37:554, 38:621, 39:49, 39:73,  
39:88, 39:90, 39:117, 39:184, 39:203,  
39:254, 40:388, 40:409, 41:79,  
54:1510, 54:1659, 54:1822, 02:286, 420
- \partial ..... 30:326
- \partokencontext .....  
57:675, 57:676, 57:680, 57:681, 1300
- \partopsep ..... 38:619, 39:1, 39:61, 873
- \PassOptionsToClass ..... 1052
- \PassOptionsToClass ..... 50:441
- \PassOptionsToPackage ..... 1052
- \PassOptionsToPackage ..... 50:441
- \patterns ..... 21:225, 1331
- \pausing ..... 02:208
- \pdffilesize ..... 05:75, 05:121
- \pdfgentounicode ..... 57:315, 57:316,  
57:320, 57:335, 57:340, 57:341, 57:342
- \pdfhorigin ..... 53:314
- \pdfsavepos ..... 819
- \pdftexrevision ..... 57:321
- \pdftexversion ..... 57:319, 57:320, 57:321
- \pdfvariable ..... 53:313, 53:318
- \pdfvorigin ..... 53:319
- peek commands:
- \peek\_meaning:NTF ..... 07:2789, 188
- \peek\_meaning\_remove:NTF .....  
07:2104, 07:2221, 07:2777, 188
- \peek\_N\_type:TF .....  
07:2110, 07:2134, 07:2166
- \peek\_remove\_spaces:n ..... 07:2102
- \penalty .. 18:35, 18:38, 18:47, 18:296,  
18:306, 18:329, 18:339, 18:363,  
18:367, 32:118, 37:538, 37:541,  
37:559, 37:562, 38:37, 38:207,  
38:497, 38:507, 39:221, 41:56,  
45:195, 45:199, 45:201, 45:217,  
45:221, 45:223, 47:37, 54:114,  
54:155, 54:182, 54:200, 54:203,  
54:1508, 54:1657, 54:1818, 02:382,
- 02:383, 02:384, 02:385, 02:386,  
02:387, 02:391, 02:393, 02:395, 1306
- \perp ..... 30:458
- \phantom ..... 38:75
- \Phi ..... 30:316
- \phi ..... 30:298
- \Pi ..... 30:313
- \pi ..... 30:293
- picture (env.) ..... 42:21
- \picture ..... 42:21
- Plugs:
- floats:footnotes ..... 54:697
- floats:space:footnotes ..... 54:681
- footnotes:floats ..... 54:702
- footnotes:floats:legacy ..... 54:707
- footnotes:space:floats ..... 54:674
- kernel (refstepcounter/target) 35:120
- off ..... 54:727
- on ..... 54:724
- space:floats:footnotes ..... 54:688
- space:footnotes:floats ..... 54:664
- \pm ..... 30:401
- \pmatrix ..... 38:173, 38:181
- \pmod ..... 38:39
- \PopDefaultHookLabel ..... 08:2815, 209
- \poptabs ..... 14:256, 41:142, 41:161
- \poptracing ..... 26:149, 26:341
- \postdisplaypenalty .....  
18:13, 38:561, 38:573, 38:599, 02:200
- \pounds ..... 21:338, 1325
- \Pr ..... 38:32
- pre commands:
- pre\_shipout\_filter ..... 1143
- \prec ..... 30:432
- \preceq ..... 30:435
- \predisdisplaypenalty ..... 18:12,  
38:560, 38:572, 38:598, 02:199, 1375
- \predisplaysize ..... 02:276
- \pretolerance 24:745, 24:761, 24:806, 02:186
- \prevdepth ..... 18:302, 18:303,  
18:335, 18:336, 18:396, 18:401,  
18:430, 18:435, 38:205, 45:196,  
45:198, 45:218, 45:220, 54:146,  
54:148, 54:151, 54:173, 54:175,  
54:178, 02:373, 02:377, 02:378, 445
- \PreviousTotalPages ..... 53:413, 1162
- prg commands:
- \prg\_break:n ..... 07:3278,  
07:3280, 07:3282, 07:3284, 07:3285
- \prg\_break\_point: ..... 07:3286
- \prg\_do\_nothing: .....  
08:2341, 09:210, 09:285, 09:405,  
09:624, 48:265, 52:132, 52:134,  
53:166, 53:167, 53:172, 53:181,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

- 53:185, 53:321, 53:491, 55:12, 55:36,  
55:46, 07:411, 07:996, 07:2046, 142
- `\prg_generate_conditional_-`  
variant:Nnn .....  
..... 11:84, 36:165, 36:180, 36:195
- `\prg_new_conditional:Npnn` .....  
..... 08:2456, 08:2471,  
08:2488, 08:2505, 08:2511, 08:2517,  
08:2523, 08:2532, 08:2540, 08:2554,  
08:2572, 09:328, 10:53, 10:117,  
10:138, 11:78, 11:85, 11:91, 36:154,  
36:169, 36:184, 48:299, 48:306,  
55:26, 08:273, 08:898, 08:1211, 08:1421
- `\prg_new_protected_conditional:Npnn`  
..... 09:124,  
09:468, 08:749, 08:807, 08:837, 08:869
- `\prg_replicate:nn` ..... 08:2324,  
08:2332, 08:2402, 08:2418, 52:552,  
07:903, 07:946, 07:1007, 07:1062,  
07:2546, 07:2553, 07:2838, 08:1185
- `\prg_return_false:` 08:2466, 08:2482,  
08:2500, 08:2509, 08:2515, 08:2521,  
08:2529, 08:2538, 08:2547, 08:2550,  
08:2564, 08:2579, 09:139, 09:341,  
09:483, 10:56, 10:120, 10:142,  
11:82, 11:89, 11:95, 36:162, 36:177,  
36:192, 48:304, 48:311, 55:27,  
08:279, 08:776, 08:830, 08:842,  
08:862, 08:874, 08:889, 08:906,  
08:910, 08:913, 08:1216, 08:1426, 253
- `\prg_return_true:` .....  
08:2464, 08:2480, 08:2499, 08:2502,  
08:2508, 08:2514, 08:2520, 08:2527,  
08:2537, 08:2548, 08:2562, 08:2577,  
09:138, 09:341, 09:482, 10:55,  
10:119, 10:141, 11:81, 11:88, 11:94,  
36:159, 36:174, 36:189, 48:303,  
48:310, 08:278, 08:767, 08:821,  
08:860, 08:887, 08:909, 08:1214, 08:1424
- `\prime` ..... 30:264, 30:328, 38:256
- `\ProcessedArgument` ..... 07:392,  
07:396, 07:403, 07:2479, 07:2480,  
07:2497, 07:2499, 07:2521, 07:2530,  
07:2536, 07:2544, 07:2561, 07:2573,  
07:2600, 07:2666, 07:2668, 07:3313, 182
- `\ProcessKeyOptions` ... 51:87, 51:229, 1106
- `\ProcessKeyPackageOptions` ..... 1372
- `\ProcessList` ..... 07:3318
- `\ProcessOption*` ..... 1309
- `\ProcessOptions` 21:1596, 26:72, 33:805,  
33:842, 50:537, 50:628, 50:1201, 1315
- `\ProcessOptions*` ..... 50:537
- `\prod` ..... 30:360
- prop commands:
- `\prop_clear:N` .....  
... 11:145, 11:155, 11:171, 11:181,  
11:210, 11:211, 11:413, 07:1954, 08:1158
- `\prop_clear_new:N` ..... 11:124
- `\prop_const_from_keyval:Nn` .....  
..... 08:952, 08:960, 08:962, 08:964
- `\prop_gclear:N` .... 09:75, 11:111,  
08:985, 08:1020, 08:1442, 08:1469
- `\prop_gclear_new:N` .....  
.... 08:2443, 08:2453, 11:100, 11:132
- `\prop_get:NnN` ..... 11:45,  
11:558, 11:561, 11:588, 11:722,  
11:743, 11:824, 08:582, 08:1612, 08:1698
- `\prop_get:NnNTF` .. 11:426, 11:539,  
11:634, 11:748, 11:750, 11:835,  
11:908, 51:234, 07:1960, 08:591, 08:636
- `\prop_gprop:NnNTF` ..... 08:993, 08:1028
- `\prop_gput:Nnn` .....  
..... 08:2607, 08:2608, 08:2609,  
09:68, 10:181, 11:196, 11:192,  
48:313, 07:58, 55:171, 08:592,  
08:593, 08:639, 08:642, 08:1519, 08:1557
- `\prop_gset_eq:NN` .....  
..... 11:101, 11:114, 11:133, 08:1160
- `\prop_if_empty:NTF` .....  
.. 08:1999, 08:2476, 08:1499, 08:1534
- `\prop_if_empty_p:N` .. 08:1895, 08:2493
- `\prop_if_exist:NTF` .....  
..... 08:2103, 08:2475, 08:2513,  
11:108, 11:139, 11:149, 11:165, 11:175
- `\prop_if_exist_p:N` ..... 08:1894
- `\prop_if_in:NnTF` ... 11:68, 11:185,  
11:552, 11:556, 08:844, 08:852,  
08:856, 08:876, 08:879, 08:883, 08:908
- `\prop_map_break:` .....  
..... 08:2111, 08:1589, 08:1671
- `\prop_map_function:NN` .....  
.. 09:74, 11:977, 11:988, 08:1159, 263
- `\prop_map_inline:Nn` .....  
..... 08:1827, 08:1898, 08:2002,  
08:2106, 08:2108, 11:417, 51:269,  
08:1454, 08:1475, 08:1577, 08:1584,  
08:1586, 08:1659, 08:1666, 08:1668
- `\prop_new:N` ... 09:17, 11:18, 11:29,  
11:31, 11:32, 11:113, 07:53, 08:30,  
08:31, 08:152, 08:164, 08:1309, 08:1310
- `\prop_put:Nnn` .....  
..... 08:1797, 08:1808, 11:262,  
11:354, 11:356, 11:361, 11:475,  
11:489, 11:504, 11:533, 11:599,  
11:691, 07:1951, 08:37, 08:42, 08:1194
- `\prop_remove:Nn` ..... 11:432

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

- \prop\_set\_eq:NN .. 11:125, 11:142, 11:152, 11:168, 11:178, 08:1515, 08:1552
- \prop\_show:N ..... 288
- property commands:
  - \property\_gset:nnnn ..... 36:6, 36:17, 36:46, 815
  - \property\_if\_exist:n . 36:154, 36:165
  - \property\_if\_exist:nTF ..... 36:154, 36:166, 36:167, 36:168, 817
  - \property\_if\_exist\_p:n ... 36:154, 817
  - \property\_if\_recorded:n 36:169, 36:180
  - \property\_if\_recorded:nn ..... 36:184, 36:195
  - \property\_if\_recorded:nnTF 36:184, 36:196, 36:197, 36:198, 36:219, 817
  - \property\_if\_recorded:nTF ..... 36:169, 36:181, 36:182, 36:183, 36:208, 36:217, 817
  - \property\_if\_recorded\_p:n 36:169, 817
  - \property\_if\_recorded\_p:nn 36:184, 817
  - \property\_new:nnnn ..... 36:6, 36:6, 36:41, 36:233, 36:235, 36:236, 36:237, 36:238, 36:240, 36:242, 36:243, 36:244, 36:245, 815
  - \property\_record:nN . 36:48, 36:48, 816
  - \property\_record:nn ..... 36:48, 36:49, 36:50, 36:52, 36:85, 816
  - \property\_ref:nn ..... 36:89, 36:89, 36:96, 36:122, 816
  - \property\_ref:nnn ..... 36:97, 36:97, 36:117, 36:125, 816
  - \property\_ref\_undefined\_warn: ... 36:199, 36:199, 816
  - \property\_ref\_undefined\_warn:n .. 36:206, 36:206, 36:214, 816
  - \property\_ref\_undefined\_warn:nn . 36:215, 36:215, 36:231, 36:232, 815
- property internal commands:
  - \\_\_property\_data:nnn ..... 36:128, 36:140, 36:142, 36:147
  - \\_\_property\_gset:nnnn ..... 36:6, 36:10, 36:19, 36:22, 36:37
  - \\_\_property\_record:nn ..... 36:48, 36:51, 36:53, 36:62
  - \\_\_property\_record\_value:n ..... 36:48, 36:59, 36:63
  - \\_\_property\_record\_value\_aux:n .. 36:48, 36:64, 36:65, 36:79
  - \\_\_property\_ref:nnn ..... 36:91, 36:97, 36:99, 36:104, 36:116
  - l\_\_property\_ref\_flag ..... 36:88
- \propto ..... 30:409
- \protect 14:246, 14:248, 14:250, 14:256, 14:262, 14:269, 14:279, 14:282, 14:288, 20:215, 20:228, 21:44, 21:50, 21:69, 21:73, 21:229, 21:237, 28:762, 28:1310, 29:721, 32:143, 06:120, 35:16, 35:33, 35:50, 37:282, 37:285, 37:319, 37:329, 06:273, 06:338, 06:347, 06:352, 06:355, 06:356, 06:358, 06:359, 06:364, 06:365, 06:370, 06:373, 06:374, 06:399, 06:437, 06:465, 41:264, 44:12, 44:72, 44:82, 44:164, 44:171, 44:177, 45:17, 47:5, 06:672, 06:692, 52:281, 52:304, 53:83, 53:95, 53:125, 53:132, 53:152, 54:880, 54:950, 54:1009, 57:358, 1326
- \protected 17:8, 18:57, 04:186, 18:238, 18:289, 18:474, 18:538, 21:328, 21:329, 22:15, 22:285, 25:3202, 25:3206, 25:3209, 25:3212, 25:3215, 25:3218, 25:3221, 25:3224, 28:1152, 29:656, 06:7, 37:203, 37:249, 37:419, 06:286, 06:293, 06:294, 38:199, 06:310, 06:312, 06:314, 06:329, 38:481, 38:519, 38:538, 38:539, 41:56, 41:201, 41:208, 42:142, 06:547, 50:771, 53:523, 53:524, 53:525, 54:845, 54:846, 02:338, 697
- \Provide ..... 1328
- \providecommand ..... 08:2940, 08:2943, 21:6, 21:13, 21:1005, 35:98, 35:99, 35:100, 06:219, 54:2580
- \ProvideCommandCopy ..... 98
- \ProvideDocumentCommand ..... 07:3117
- \ProvideDocumentEnvironment ... 07:3153
- \ProvideExpandableDocumentCommand .. 07:3236
- \ProvideHook ..... 08:2886, 1368
- \ProvideMirroredHookPair ..... 08:2886
- \ProvideReversedHook ..... 08:2886
- provides commands:
  - provides\_module ..... 04:298
  - \provides\_module ..... 43
  - \ProvidesClass ..... 1052
  - \ProvidesClass ..... 50:421
  - \ProvidesExplPackage ..... 52:541
  - \ProvidesFile .. 30:676, 30:678, 30:679, 30:680, 33:1178, 50:430, 01:73, 1337
  - \ProvidesPackage ..... 1052
  - \ProvidesPackage ..... 26:13, 33:779, 33:810, 50:344, 50:423, 50:425, 50:1814, 52:570, 53:518, 1065
  - \ProvideTextCommand .... 21:3, 21:78, 1328
  - \ProvideTextCommandDefault .. 21:75, 1328
  - \Psi ..... 30:317
  - \psi ..... 30:300
  - \PushDefaultHookLabel ..... 08:2815, 208

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- `\pushtabs` ..... 07:1967, 07:1971, 07:2725, 07:2728,  
 14:256, 41:139, 41:138, 41:158, 41:160  
 07:2734, 07:2735, 08:427, 08:428, 129  
`\pushtracing` ..... 26:118, 26:322  
`\put` ..... 42:56, 42:58, 42:70, 42:72,  
 42:325, 42:326, 42:327, 42:328,  
 42:336, 42:338, 42:351, 42:352,  
 42:353, 42:354, 42:361, 42:364,  
 42:384, 42:385, 42:386, 42:387,  
 42:393, 42:395, 42:407, 42:408,  
 42:409, 42:410, 42:415, 42:420,  
 42:728, 42:784, 42:812, 42:829, 1145
- ### Q
- `\qbezier` ..... 933  
`\qbezier` ..... 42:681, 42:813, 42:830  
`\qbeziermax` . 42:680, 42:706, 42:707, 42:767  
`\qqquad` ..... 18:549  
`\quad` ..... 18:549,  
 38:168, 38:170, 38:190, 44:111, 1335  
 quark commands:  
`\q_mark` ..... 07:1337,  
 07:1340, 07:2380, 07:2384, 07:2396,  
 07:2726, 07:2734, 07:2737, 07:2742  
`\q_nil` 11:80, 11:93, 07:606, 07:1329,  
 07:1340, 07:1514, 07:1767, 07:1768,  
 07:1770, 07:1771, 07:1772, 07:1773,  
 07:1774, 07:1860, 07:1881, 07:1885,  
 07:1891, 07:1900, 07:1902, 07:2300,  
 07:2324, 07:2333, 07:2365, 07:2380,  
 07:2384, 07:2396, 07:2402, 07:2428, 175  
`\quark_if_nil:N`TF 07:617, 07:2386, 177  
`\quark_if_nil:n`TF ..... 07:1511  
`\quark_if_recursion_tail_stop:N` .  
 ..... 07:825, 07:1495  
`\quark_if_recursion_tail_stop:n` .  
 .... 36:144, 51:7, 07:484, 07:674,  
 07:1255, 07:2739, 07:2740, 08:422  
`\quark_if_recursion_tail_stop-`  
`do:Nn` ..... 07:625  
`\quark_if_recursion_tail_stop-`  
`do:nn` ..... 09:424,  
 09:443, 07:510, 07:515, 07:524,  
 07:533, 07:579, 07:592, 07:602, 07:646  
`\quark_new:N` ..... 09:15,  
 09:16, 11:41, 07:50, 07:51, 07:1869  
`\q_recursion_stop` .....  
 ... 09:413, 36:140, 51:20, 07:336,  
 07:347, 07:461, 07:809, 07:1251,  
 07:1491, 07:1952, 07:1967, 07:1969,  
 07:1976, 07:2729, 07:2735, 08:428  
`\q_recursion_tail` .....  
 ..... 09:413, 36:140, 51:19,  
 07:461, 07:809, 07:1251, 07:1491,
- `\q_stop` ..... 11:80,  
 11:93, 11:632, 11:642, 07:424,  
 07:606, 07:615, 07:620, 07:1337,  
 07:1339, 07:1768, 07:1774, 07:1885,  
 07:1902, 07:2537, 08:564, 08:569  
 quark internal commands:  
`\q__cmd` ... 07:408, 07:412, 07:1031,  
 07:1367, 07:1368, 07:1450, 07:1458,  
07:1867, 07:2284, 07:2285, 07:2288,  
 07:2293, 07:2299, 07:2300, 07:2302,  
 07:2306, 07:2311, 07:2314, 07:2317,  
 07:2328, 07:2332, 07:2333, 07:2336,  
 07:2337, 07:2340, 07:2351, 07:2354,  
 07:2358, 07:2369, 07:2371, 07:2372,  
 07:2373, 07:2374, 07:2375, 07:2376,  
 07:2377, 07:2381, 07:2400, 07:2401,  
 07:2402, 07:2403, 07:2404, 07:2405,  
 07:2406, 07:2407, 07:2408, 07:2409,  
 07:2410, 07:2411, 07:2412, 07:2413,  
 07:2416, 07:2421, 07:2427, 07:2428,  
 07:2434, 07:2439, 07:2440, 07:2443,  
 07:2454, 07:2461, 07:2466, 07:2467,  
 07:2468, 07:2471, 07:2472, 07:2474, 177  
`\q__cmd_recursion_stop` .....  
 ..... 07:51, 07:2606,  
 07:2608, 07:2617, 07:2640, 07:2649, 117  
`\q__cmd_recursion_tail` .....  
 ..... 07:50, 07:2606, 117  
`\q_hook_recursion_stop` .....  
 . 09:15, 09:343, 09:344, 09:353, 09:378  
`\q_hook_recursion_tail` .....  
 ..... 09:15, 09:343, 09:357  
`\q_template_nil` ... 11:41, 11:912, 363  
`\quotedblbase` .... 21:578, 21:807, 21:1200  
`\quotesinglbase` ..... 21:579, 21:1197
- ### R
- `\r` ..... 21:256, 21:409, 21:452,  
 21:493, 21:633, 21:660, 21:670,  
 21:696, 21:780, 21:819, 21:1269,  
 21:1287, 21:1313, 21:1435, 21:1436,  
 33:147, 33:169, 02:318, 02:319, 1345  
`\radical` .. 28:1176, 28:1179, 28:1209, 1356  
`\raggedbottom` ..... 49:126, 1198  
`\raggedleft` . 37:462, 37:480, 37:491, 37:498  
`\raggedright` 37:457, 37:476, 37:490, 37:496  
`\raise` .. 21:347, 21:379, 21:451, 21:454,  
 21:756, 21:821, 21:919, 21:1277,  
 29:734, 30:476, 30:524, 30:526,  
 38:73, 40:579, 40:588, 42:61, 42:73,  
 42:105, 42:117, 42:195, 42:305,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

- 42:452, 42:494, 42:525, 42:550,  
42:618, 42:635, 42:636, 42:739, 42:795
- \raisebox ..... 890
- \raisebox ..... 21:896, 21:1246, 40:556
- \rangle ..... 30:603
- \RawIndent ..... 16:136, 16:172, 418
- \RawNoIndent ..... 16:136
- \RawNoindent ..... 16:137, 16:173, 418
- \RawParEnd ... 16:136, 16:174, 02:357, 418
- \RawShipout ..... 53:151, 53:444, 1140
- \rbrace ..... 21:329, 30:607
- \rbrack ..... 02:316
- \rceil ..... 30:611
- \Re ..... 30:324
- \read ..... 474
- \ReadOnlyShipoutCounter .....  
..... 53:346, 53:446, 1145
- \RecordProperties .... 36:80, 36:271, 817
- \Ref ..... 807
- \Ref .... 35:113, 35:156, 35:158, 35:178,  
35:186, 35:190, 35:197, 45:553, 815
- \ref .... 35:10, 35:186, 35:197, 45:553, 815
- \RefProperty ..... 36:118, 36:272, 818
- \refstepcounter ..... 525
- refstepcounter (socket) ..... 35:118
- refstepcounter (tag socket) ..... 55:165
- \refstepcounter ..... 35:111,  
35:112, 35:180, 35:190, 35:192,  
35:201, 35:203, 38:399, 38:406,  
38:600, 39:233, 43:37, 44:59, 45:9, 315
- refstepcounter/target (socket) ... 35:119
- \RefUndefinedWarn ... 36:215, 36:273, 816
- regex commands:
- \regex\_match:nnTF ..... 11:386
- \registernumber ..... 42
- registernumber ..... 04:389
- \relax ..... 414
- \relax\_ ..... 1322
- \Relbar 30:487, 30:495, 30:497, 30:503, 1350
- \relbar ..... 30:484, 30:499, 30:501
- \relpenalty ..... 02:194
- remove commands:
- remove\_from\_callback ..... 04:907
- \remove\_from\_callback ..... 44
- \RemoveFromHook .....  
... 08:2813, 08:2942, 37:41, 37:42,  
37:43, 37:106, 37:107, 37:108, 205
- \removelastskip .....  
..... 02:389, 02:391, 02:393, 02:395
- \renewcommand ..... 79
- \renewcommand .... 30:78, 30:80, 30:82,  
30:83, 30:85, 30:87, 30:89, 30:90,  
30:96, 30:98, 30:100, 30:101, 30:114,  
30:115, 30:116, 30:124, 30:125,  
06:163, 38:548, 38:568, 38:589, 704
- \RenewCommandCopy .... 06:565, 06:567, 98
- \RenewDocumentCommand ..... 07:3117
- \RenewDocumentEnvironment .....  
..... 07:2915, 07:3153
- \renewenvironment ..... 80
- \renewenvironment . 06:193, 38:597, 38:609
- \RenewEnvironmentCopy 06:606, 06:608, 1375
- \RenewExpandableDocumentCommand ....  
..... 48:522,  
48:523, 48:524, 48:525, 07:3236, 197
- \repeat ..... 04:154, 04:164, 24:787,  
41:382, 50:1254, 50:1315, 50:1385,  
50:1448, 50:1499, 50:1537, 57:369,  
57:380, 57:390, 57:401, 57:431,  
57:457, 57:467, 01:65, 01:67, 02:365
- \requestedLaTeXdate ..... 08:2962,  
50:1600, 50:1640, 50:1660, 50:1747
- \requestedpatchdate .... 50:1670, 50:1748
- \RequirePackage ..... 1052
- \RequirePackage 04:24, 50:676, 50:683,  
50:726, 50:735, 50:1197, 54:2577, 208
- \RequirePackageWithOptions ..... 1052
- \RequirePackageWithOptions ..... 50:718
- reserved@a commands:
- \reserved@a: ..... 20:252,  
20:324, 20:386, 20:433, 50:1227, 50:1362
- reserved@b commands:
- \reserved@b: ..... 50:232, 50:249
- reserved@c commands:
- \reserved@c: ..... 20:774
- \RestoreAtCatcode ..... 1320
- \restorecr ..... 18:556
- \ResumeTagging ..... 1263
- \ResumeTagging ..... 23:22, 55:3, 1263
- \ReverseBoolean ..... 07:3314
- \reversemarginpar ..... 45:387
- \rfloor ..... 30:615
- \rgroup ..... 30:619
- \rhd ..... 29:861
- \rho ..... 30:294
- \rhook ..... 30:490, 30:491
- \right ..... 30:636, 30:638,  
30:640, 30:642, 30:647, 30:648,  
30:649, 30:650, 38:168, 38:173, 38:197
- \Rightarrow ..... 30:422, 30:497, 30:509
- \rightarrow ..... 30:449, 30:451,  
30:455, 30:489, 30:499, 30:507, 30:560
- \rightarrowfill ..... 30:542, 30:558
- \rightharpoondown ..... 30:466
- \rightharpoonup ..... 30:465, 30:477
- \righthyphenmin ..... 56:11, 02:246
- \rightleftharpoons ..... 30:475

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpara.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=lt page.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

- `\rightline` ..... 40:614  
`\rightmargin` ..... 39:9, 39:40, 39:51, 873  
`\rightmark` ..... 49:106, 1020  
`\rightskip` .... 24:758, 37:454, 37:458,  
37:464, 37:474, 37:477, 37:482,  
37:531, 37:553, 39:75, 40:392,  
40:413, 44:232, 44:255, 02:292, 02:403  
`\rlap` ..... 21:451, 21:454, 21:821,  
38:521, 38:549, 40:618, 41:81, 1336  
`\rm` ..... 1312  
`\rmdefault` ..... 29:7, 29:301, 29:477,  
29:486, 29:518, 29:529, 29:561,  
29:751, 30:62, 30:131, 33:7, 33:577, 523  
`\rmfamily` .. 29:5, 29:6, 29:484, 29:527,  
29:528, 29:559, 29:560, 32:15, 707  
`rmfamily` ..... 29:499  
`\rmmath` ..... 1305  
`\rmoustache` ..... 30:576  
`\rmsubstdefault` .....  
.... 30:18, 30:30, 33:28, 33:39, 33:49  
`\Roman` ..... 525  
`\Roman` ..... 22:229, 1144  
`\roman` ..... 525  
`\roman` ..... 22:228  
`\romannumeral` .....  
... 22:234, 22:235, 37:318, 37:350,  
37:367, 39:43, 39:265, 39:276, 839  
`\root` ..... 38:66, 38:414  
`\rootbox` ..... 38:66  
`\rq` ..... 02:314  
`\rule` ..... 890  
`\rule` ..... 40:490, 40:507,  
40:524, 40:530, 45:477, 45:495, 45:513
- S**
- `\S` ..... 21:331, 1329  
`\safesubencodingfoundfalse` .... 33:1219  
`\safesubencodingfoundtrue` .... 33:1209  
`\samepage` ..... 433  
`\samepage` ..... 18:11, 18:29, 1306  
`\SaveAtCatcode` ..... 1320  
`\savebox` ..... 889  
`\savebox` ..... 40:155  
`\savecatcodetable` . 04:117, 04:168, 04:170  
`\savepos` ..... 819  
`\sb` ..... 38:212  
`\sbox` ..... 889  
`\sbox` ..... 19:4, 21:521,  
21:537, 39:236, 40:161, 40:168,  
40:172, 40:177, 40:182, 02:397, 1312  
scan commands:  
`\scan_new:N` ..... 11:39, 11:40, 08:44  
`\scan_stop:` 08:2573, 08:2574, 09:470,  
09:471, 09:529, 09:530, 09:565,
- 09:566, 16:94, 48:106, 48:108,  
48:118, 48:120, 48:122, 48:123,  
48:280, 48:281, 48:282, 51:89,  
51:99, 53:44, 53:325, 53:327, 53:328,  
07:1612, 07:1613, 07:1638, 07:1644,  
07:1653, 07:1660, 07:2099, 07:2100,  
08:678, 08:685, 08:696, 08:705,  
08:740, 08:751, 08:787, 08:799,  
08:809, 08:839, 08:871, 08:1213, 123  
scan internal commands:  
`\s__file_stop` ..... 52:103,  
52:105, 52:108, 52:110, 52:112, 52:125  
`\s__hook_mark` ..... 08:2290,  
08:2304, 08:2353, 08:2361, 08:2464,  
08:2466, 08:2527, 08:2529, 08:2533,  
08:2534, 08:2541, 08:2542, 08:2555,  
08:2556, 09:24, 09:26, 09:41, 09:43,  
09:52, 09:54, 09:130, 09:135, 09:329,  
09:340, 09:475, 09:478, 09:490,  
09:494, 09:499, 09:534, 09:554,  
09:570, 09:582, 08:44, 08:45,  
08:46, 08:348, 08:351, 08:354,  
08:358, 08:361, 08:362, 08:729,  
08:780, 08:782, 08:790, 08:792,  
08:795, 08:797, 08:899, 08:924,  
08:925, 08:929, 08:1234, 08:1251,  
08:1255, 08:1297, 08:1298, 08:1353, 231  
`\s__keys_stop` ... 51:47, 51:207, 51:208  
`\s__template_mark` .. 11:39, 11:912, 363  
`\s__template_stop` ..... 11:40,  
11:287, 11:298, 11:309, 11:330,  
11:344, 11:352, 11:438, 11:441,  
11:771, 11:774, 11:912, 11:916, 363  
`\scdefault` ..... 25:3214, 29:28, 30:106  
`\scriptfont` ..... 26:339  
`\scriptscriptfont` ..... 26:340  
`\scriptscriptstyle` ..... 38:65, 38:68  
`\scriptspace` ..... 02:274  
`\scriptstyle` ..... 30:348, 38:64  
`\scshape` ..... 21:320, 25:3212,  
25:3213, 29:26, 29:27, 32:23, 1346  
`\searrow` ..... 30:417  
`\sec` ..... 38:20  
`sec/begin` (tag socket) ..... 55:181  
`sec/end` (tag socket) ..... 55:181  
`sec/title/begin` (tag socket) ..... 55:183  
`sec/title/end` (tag socket) ..... 55:183  
`sec/title/hang` (tag socket) ..... 55:185  
`sec/title/init` (tag socket) ..... 55:186  
`sec/title/number` (tag socket) .... 55:189  
`sec/title/runin/number` (tag socket) 55:186  
`sec/title/split` (tag socket) ..... 55:186  
`\secdef` ..... 44:142  
`\secondoftwo` ..... 469

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\section</code> .....	1036	<code>\seq_set_split:Nnn</code> ...	55:312, 07:2496
<code>\sectionmark</code> .....	44:143, 1020	<code>\seq_use:Nnnn</code> .	08:1825, 08:1830, 10:65
<code>\selectfont</code> .....	19:7,	seq internal commands:	
	21:322, 21:349, 21:380, 21:470,	<code>\g__mark_classes_seq</code> .....	
	21:833, 21:895, 21:1245, 21:1279,		48:6, 48:9, 48:23,
	21:1597, 24:354, 24:364, 24:374,		48:139, 48:172, 48:214, 48:225,
	25:2916, 25:2921, 25:2926, 25:3204,		48:236, 48:248, 48:390, 48:467, 1024
	25:3208, 25:3211, 25:3214, 25:3217,	<code>\series</code> .....	1305
	25:3220, 25:3223, 25:3226, 26:115,	<code>\seriesdefault</code> .....	
	26:116, 26:160, 26:163, 26:165,		.. 21:1598, 28:410, 28:460, 29:313,
	29:7, 29:10, 29:13, 29:16, 29:19,		29:315, 29:743, 29:776, 29:792,
	29:22, 29:25, 29:28, 29:31, 29:343,		29:808, 29:825, 29:902, 30:131, 1363
	29:366, 29:404, 29:424, 29:439,	<code>\setattribute</code> .....	41
	29:450, 29:461, 29:464, 29:488,	<code>\setattribute</code> .....	04:82, 04:239
	29:493, 29:498, 29:531, 29:536,	<code>\setbox</code> .....	882
	29:541, 29:555, 29:558, 29:561,	<code>\setbox...</code> .....	1344
	29:564, 29:567, 29:647, 29:724,	<code>\setbox0</code> .....	1341
	29:748, 29:781, 29:796, 29:811,	<code>\setcounter</code> .....	525
	33:36, 33:58, 33:68, 33:600, 33:637,	<code>\setcounter</code> .....	20:464,
	33:877, 33:894, 45:403, 45:424, 623		22:2, 22:43, 22:63, 28:144, 39:256,
<code>selectfont</code> .....	26:151		54:2990, 54:2993, 54:2996, 54:3000, 674
seq commands:		<code>\SetDefaultHookLabel</code> .....	08:2815, 209
<code>\seq_clear:N</code> .....		<code>\SetKeys</code> .....	20:770, 51:287, 1106
	.... 11:161, 11:212, 08:1574, 08:1656	<code>\SetKnownTemplateKeys</code> .....	11:1231, 356
<code>\seq_clear_new:N</code> ....	08:1582, 08:1664	<code>\setlength</code> .....	536
<code>\seq_const_from_clist:Nn</code> .....	11:16	<code>\setlength</code> .....	18:84,
<code>\seq_count:N</code> .....	55:313		18:244, 18:259, 18:518, 23:4, 38:617,
<code>\seq_gclear_new:N</code> .....	11:116		38:622, 38:623, 38:624, 40:47, 40:62,
<code>\seq_gpop:NN</code> .....	08:2604		40:247, 40:266, 40:333, 40:336,
<code>\seq_gpop:NNTF</code> ..	52:72, 08:451, 08:459		40:360, 40:363, 40:439, 40:546,
<code>\seq_gpop_right:NN</code> .....	08:430		40:547, 40:548, 40:577, 40:578,
<code>\seq_gpush:Nn</code> .....			40:585, 40:586, 40:587, 41:176,
	.... 08:2592, 08:2598, 52:64, 08:444		41:384, 54:3006, 54:3007, 54:3008,
<code>\seq_gput_right:Nn</code> .....			54:3011, 54:3012, 54:3016, 54:3017,
	. 48:23, 08:108, 08:137, 08:419, 08:423		54:3018, 54:3022, 54:3023, 54:3024, 447
<code>\seq_gset_eq:NN</code> .....	11:117	<code>\SetMathAlphabet</code> .....	24:12,
<code>\seq_if_empty:NTF</code> ....	08:418, 08:469		27:140, 27:141, 28:767, 30:166, 30:167
<code>\seq_if_exist:NTF</code> ....	11:156, 52:60	<code>\setminusminus</code> .....	30:404
<code>\seq_if_in:NnTF</code> .	11:231, 48:9, 48:248	<code>\SetProperty</code> .....	36:38, 36:269, 817
<code>\seq_map_break:</code> .....	11:250, 11:341	<code>\setrangeatcode</code> .....	
<code>\seq_map_function:NN</code> .....			.... 04:96, 04:104, 04:113, 04:114
	.... 11:227, 11:347, 11:738	<code>\SetSymbolFont</code> .....	
<code>\seq_map_inline:Nn</code> .....			. 28:602, 30:156, 30:157, 30:158, 1309
	.... 08:2985, 48:139, 48:172,	<code>\SetTemplateKeys</code> .....	11:1231, 357
	48:214, 48:225, 48:236, 48:390,	<code>\settodepth</code> .....	536
	48:467, 07:2498, 08:1443, 08:1470,	<code>\settodepth</code> .....	23:17
	08:1598, 08:1616, 08:1681, 08:1704	<code>\settoheight</code> .....	536
<code>\seq_mapthread_function:NNN</code> ...	186	<code>\settoheight</code> .....	23:17
<code>\seq_new:N</code> .....		<code>\settowidth</code> .....	536
	08:2582, 10:36, 11:30, 48:6, 52:61,	<code>\settowidth</code> .....	23:17
	55:316, 07:2482, 08:28, 08:33, 08:1565	<code>\sf</code> .....	1312
<code>\seq_put_right:Nn</code> .....	08:1765,	<code>\sfcode</code> .....	18:463, 20:45,
	08:1772, 10:91, 11:264, 08:1580, 08:1662		20:115, 20:173, 57:250, 57:545,
<code>\seq_set_eq:NN</code> .....	11:158		02:306, 02:307, 02:308, 02:309, 02:426

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

- \sfdefault 29:10, 29:305, 29:478, 29:491,  
29:519, 29:534, 29:564, 30:62, 707
- \sffamily . . . 29:8, 29:9, 29:489, 29:532,  
29:533, 29:562, 29:563, 32:16, 721
- sffamily . . . . . 29:499
- \sfsubstdefault 30:19, 30:31, 33:30, 33:51
- \shape . . . . . 1307
- \shapedefault . . . . . 21:1598, 25:3204,  
28:411, 28:461, 29:744, 29:777,  
29:793, 29:809, 29:826, 30:131, 628
- \sharp . . . . . 30:341
- \shipout . . . . . 53:4, 53:52, 53:437,  
53:440, 54:881, 54:956, 54:1014, 1210
- shipout . . . . . 53:153
- shipout commands:
  - \l\_shipout\_box . . . . . 53:23, 53:35, 53:38, 53:50, 53:61,  
53:126, 53:149, 53:179, 53:184,  
53:207, 53:208, 53:215, 53:226,  
53:229, 53:230, 53:234, 53:241,  
53:251, 53:259, 53:266, 53:276,  
53:282, 53:283, 53:286, 53:293,  
53:295, 53:296, 53:302, 53:304, 1149
  - \l\_shipout\_box\_dp\_dim . . . . . 53:194, 53:197,  
53:199, 53:230, 53:283, 53:539, 1140
  - \l\_shipout\_box\_ht\_dim . . . . . 53:193, 53:197, 53:199,  
53:229, 53:249, 53:282, 53:538, 1140
  - \l\_shipout\_box\_ht\_plus\_dp\_dim . . . . . 53:196, 53:199,  
53:215, 53:266, 53:277, 53:279, 1140
  - \l\_shipout\_box\_wd\_dim . . . 53:195,  
53:199, 53:241, 53:293, 53:540, 1140
  - \shipout\_debug\_off: . . . . . 53:7, 53:13, 53:421, 1144
  - \shipout\_debug\_on: . . . . . 53:7, 53:8, 53:420, 1144
  - \shipout\_discard: . . . . . 53:343, 53:343, 53:417, 1143
  - \g\_shipout\_readonly\_int . . . . . 36:234, 53:102, 53:104,  
53:111, 53:116, 53:346, 53:355,  
53:364, 53:368, 53:372, 53:376, 1144
  - \g\_shipout\_totalpage\_int . . . . 1144
  - \g\_shipout\_totalpages\_int . . . . . 53:87, 53:348, 1150
- shipout internal commands:
  - \\_\_shipout\_add\_background\_box:n . . . . . 53:180, 53:206, 53:206, 53:338, 53:426
  - \\_\_shipout\_add\_background\_-  
picture:n . . . . . 53:69, 53:337, 53:337, 53:430
  - \\_\_shipout\_add\_firstpage\_-  
material:Nn . . . . . 53:173, 53:189, 53:189, 53:419, 53:424
  - \\_\_shipout\_add\_firstpage\_-  
specials: . . . . . 53:110,  
53:166, 53:178, 53:178, 53:181, 1154
  - \\_\_shipout\_add\_foreground\_box:n . . . . . 53:117, 53:257, 53:257, 53:341, 53:428
  - \\_\_shipout\_add\_foreground\_-  
picture:n . . . . . 53:64, 53:340, 53:340, 53:432
  - \\_\_shipout\_debug:n . . . . 53:7, 53:7,  
53:20, 53:103, 53:115, 53:148, 1147
  - \g\_\_shipout\_debug\_bool . . . . . 53:6, 53:10, 53:15, 53:21
  - \\_\_shipout\_debug\_gset: . . . . . 53:7, 53:11, 53:16, 53:18
  - \g\_\_shipout\_discard\_bool . . . . . 53:81, 53:88, 53:90, 53:203, 53:344
  - \\_\_shipout\_drop\_firstpage\_-  
specials: . . . . . 53:127,  
53:167, 53:178, 53:183, 53:185, 1153
  - \\_\_shipout\_excuse\_extra\_page: . . . . . 53:390, 53:398, 53:398
  - \\_\_shipout\_execute: . . . . . 53:46, 53:46, 53:52, 1148
  - \\_\_shipout\_execute\_cont: . . . . . 53:57, 53:59, 53:59
  - \\_\_shipout\_execute\_main\_cont:Nnnn . . . . . 53:60, 53:77, 53:77, 53:147, 1152
  - \\_\_shipout\_execute\_nohooks\_cont: . . . . . 53:144, 53:146
  - \\_\_shipout\_execute\_raw: . . . . . 53:135, 53:135, 53:151, 1152
  - \\_\_shipout\_execute\_test\_level: . . . . . 53:49, 53:54, 53:54
  - \\_\_shipout\_execute\_test\_level\_-  
raw: . . . . . 53:135, 53:138, 53:141
  - \\_\_shipout\_finalize\_box: . . . . . 53:26, 53:28, 53:44, 53:124
  - \l\_\_shipout\_firstpage\_box . . . . . 53:170, 53:180, 53:187, 1154
  - \\_\_shipout\_force\_immediate\_-  
writes: . . . . . 53:359,  
53:474, 53:477, 53:479, 53:489, 53:491
  - \\_\_shipout\_get\_box\_size:N . . . 53:85,  
53:107, 53:192, 53:192, 53:207, 1155
  - \l\_\_shipout\_group\_level\_tl . . . . . 53:47, 53:53, 53:56, 53:136, 53:143
  - \c\_\_shipout\_horigin\_tl 53:310, 53:325
  - \\_\_shipout\_init\_page\_origins: . . . . . 53:310, 53:310, 53:321, 53:324
  - \g\_\_shipout\_lastpage\_handled\_-  
bool . . . . . 53:120, 53:188, 53:370

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

- `\_shipout_picture_overlay:n` ...  
     ... [53:323](#), [53:323](#), [53:338](#), [53:341](#)
- `\l_shipout_raw_box` [53:25](#), [53:139](#),  
     [53:147](#), [53:149](#), [53:179](#), [53:184](#), [1151](#)
- `\_shipout_run_firstpage_hook:` ..  
     . [53:108](#), [53:163](#), [53:163](#), [53:172](#), [1153](#)
- `\l_shipout_saved_badness_tl` ...  
     ... [53:204](#), [53:210](#), [53:218](#), [53:231](#),  
     [53:236](#), [53:244](#), [53:253](#), [53:261](#),  
     [53:269](#), [53:281](#), [53:288](#), [53:298](#), [53:306](#)
- `\_shipout_saved_protect:` .....  
     ..... [53:83](#), [53:132](#), [53:152](#), [53:152](#)
- `\l_shipout_tmp_box` .....  
     ... [53:204](#), [53:217](#), [53:219](#), [53:220](#),  
     [53:221](#), [53:225](#), [53:243](#), [53:245](#),  
     [53:246](#), [53:247](#), [53:250](#), [53:268](#),  
     [53:270](#), [53:271](#), [53:272](#), [53:278](#),  
     [53:297](#), [53:299](#), [53:300](#), [53:301](#),  
     [53:303](#), [53:329](#), [53:331](#), [53:332](#), [53:333](#)
- `\c_shipout_vorigin_tl` [53:310](#), [53:327](#)
- `shipout/after` ..... [53:153](#), [1140](#)
- `shipout/background` ..... [53:153](#), [1140](#)
- `shipout/before` ..... [53:153](#), [1140](#)
- `shipout/firstpage` ..... [53:153](#), [1140](#)
- `shipout/foreground` ..... [53:153](#), [1140](#)
- `shipout/lastpage` ..... [53:153](#), [1140](#)
- `\ShipoutBox` ... [53:23](#), [53:445](#), [53:521](#), [1141](#)
- `\ShipoutBoxDepth` ..... [53:465](#), [53:538](#)
- `\ShipoutBoxHeight` .. [53:464](#), [53:538](#), [1167](#)
- `\ShipoutBoxWidth` ..... [53:466](#), [53:538](#)
- `\shortstack` .....  
     [42:132](#), [42:147](#), [42:152](#), [42:814](#), [42:831](#)
- `\show` ..... [06:644](#), [06:717](#), [102](#)
- show commands:  
     `\show_hook:n` ..... [282](#)
- `\showbox` ..... [54:2491](#)
- `\showboxbreadth` .... [02:570](#), [54:2491](#),  
     [02:262](#), [02:429](#), [02:505](#), [02:528](#), [02:545](#)
- `\showboxdepth` ..... [02:571](#),  
     [24:745](#), [24:790](#), [24:807](#), [54:2491](#),  
     [02:263](#), [02:429](#), [02:504](#), [02:527](#), [02:544](#)
- `\ShowCommand` .....  
     [06:637](#), [07:1348](#), [07:1377](#), [07:1389](#),  
     [07:1397](#), [07:1400](#), [07:1568](#), [1364](#)
- `\ShowEnvironment` ..... [06:772](#), [1375](#)
- `\ShowFloat` ..... [54:2472](#)
- `\ShowHook` ..... [08:2839](#), [08:2947](#), [212](#)
- `\showhyphens` ..... [24:733](#), [1384](#)
- `\ShowInstanceValues` ..... [11:1213](#), [361](#)
- `\ShowMarksAt` ..... [48:394](#)
- `\showoutput` ..... [02:428](#), [1338](#)
- `\showoverfull` ..... [02:427](#),  
     [02:430](#), [02:451](#), [02:486](#), [02:494](#), [1338](#)
- `\ShowSocket` ... [10:161](#), [10:182](#), [10:204](#), [341](#)
- `\showstream` ..... [1386](#)
- `\ShowTemplateCode` ..... [11:1213](#), [361](#)
- `\ShowTemplateDefaults` ..... [11:1213](#), [361](#)
- `\ShowTemplateInterface` .... [11:1213](#), [361](#)
- `\ShowTemplateVariables` .... [11:1213](#), [361](#)
- `\showtokens` ..... [06:752](#), [104](#)
- `\Sigma` ..... [30:314](#)
- `\sigma` ..... [30:295](#)
- `\sim` ..... [30:456](#), [30:468](#)
- `\simeq` ..... [30:457](#)
- `\sin` ..... [38:9](#)
- `\sinh` ..... [38:11](#)
- `\size` ..... [1305](#)
- `\skew` ..... [30:555](#)
- `\skip` [04:33](#), [40:464](#), [45:391](#), [02:28](#), [54:321](#),  
     [54:617](#), [02:49](#), [54:744](#), [02:132](#), [1188](#)
- skip commands:  
     `\skip_eval:n` ..... [11:371](#), [05:169](#)
- `\skip_new:N` ..... [11:37](#)
- `\skip_set:Nn` ..... [16:25](#)
- `\skip_zero:N` ..... [16:58](#), [53:222](#),  
     [53:223](#), [53:224](#), [53:273](#), [53:274](#), [53:275](#)
- `\l_tmpa_skip` ..... [356](#)
- `\c_zero_skip` ..... [16:26](#)
- `\skipdef` ..... [04:229](#), [02:45](#), [02:49](#)
- `\skipeval` ..... [75](#)
- `\skipeval` ..... [05:162](#), [05:179](#), [1371](#)
- `\skipzero` ..... [04:229](#)
- `\slash` ..... [06:982](#), [06:1003](#), [02:382](#)
- `\sldefault` ..... [25:3211](#), [29:25](#), [30:106](#)
- `\SLiTeX` ..... [1327](#)
- `\sloppy` .... [40:397](#), [40:416](#), [49:130](#), [49:135](#)
- `sloppypar (env.)` ..... [49:135](#)
- `\sloppypar` ..... [49:135](#)
- `\slshape` .... [21:461](#), [21:824](#), [25:3209](#),  
     [25:3210](#), [29:23](#), [29:24](#), [32:22](#), [33:591](#)
- `\small` ..... [206](#)
- `\smallbreak` ..... [06:983](#), [06:1004](#), [02:390](#)
- `\smallint` ..... [30:368](#)
- `\smallskip` ..... [18:447](#), [02:391](#)
- `\smallskipamount` .. [18:447](#), [18:450](#), [02:390](#)
- `\smash` .... [17:34](#), [17:56](#), [30:484](#), [30:558](#),  
     [30:559](#), [30:562](#), [30:563](#), [38:126](#), [856](#)
- `\smile` ..... [30:461](#)
- socket commands:  
     `\socket_assign_plug:nn` .....  
         ..... [10:42](#), [10:44](#), [10:122](#),  
         [10:122](#), [10:186](#), [55:13](#), [55:16](#), [343](#)
- `\socket_debug_off:` .....  
         ..... [10:7](#), [10:14](#), [10:189](#), [345](#)
- `\socket_debug_on:` [10:7](#), [10:9](#), [10:188](#), [345](#)
- `\socket_if_exist:n` ..... [10:53](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=ltlooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

- \socket\_if\_exist:nTF .....
  - . 10:28, [10:53](#), 10:60, 10:79, 10:99,
  - 10:123, 10:190, 10:191, 10:192, [344](#)
- \socket\_if\_exist\_p:n ..... [10:53](#)
- \socket\_if\_plug\_assigned:nn . 10:138
- \socket\_if\_plug\_assigned:nnTF ...
  - .. [10:138](#), 10:196, 10:197, 10:198, [344](#)
- \socket\_if\_plug\_assigned\_p:nn [10:138](#)
- \socket\_if\_plug\_exist:nn .... [10:117](#)
- \socket\_if\_plug\_exist:nnTF .....
  - ..... 10:81, 10:101, [10:117](#),
  - 10:125, 10:193, 10:194, 10:195, [344](#)
- \socket\_if\_plug\_exist\_p:nn .. [10:117](#)
- \socket\_log:n .....
  - ..... [10:58](#), 10:58, 10:77, 10:184, [344](#)
- \socket\_new:nn .....
  - ..... [10:27](#), 10:27, 10:182, 55:8, [343](#)
- \socket\_new\_plug:nnn .... 10:38,
  - 10:41, [10:78](#), 10:78, 10:185, 55:14, [343](#)
- \socket\_set\_plug:nnn .....
  - ..... [10:78](#), 10:98, 10:175, [343](#)
- \socket\_show:n [10:58](#), 10:77, 10:183, [344](#)
- \socket\_use:n .... [10:144](#), 10:150, [344](#)
- \socket\_use:nn ... [10:144](#), 10:151, [344](#)
- \socket\_use:nnn .. [10:144](#), 10:152, [344](#)
- \socket\_use:nnnn .. [10:144](#), 10:153, [344](#)
- \socket\_use:nw .....
  - ..... [10:144](#), 10:144, 10:150,
  - 10:151, 10:152, 10:153, 10:187, [344](#)
- \socket\_use\_expandable:n .....
  - ..... [10:154](#), 10:157, [344](#)
- \socket\_use\_expandable:nw .....
  - ..... [10:154](#), 10:154, 10:157, [344](#)
- socket internal commands:
  - \\_\_socket\_debug:n [10:7](#), 10:7, 10:21, [345](#)
  - \g\_\_socket\_debug\_bool .....
    - ..... [10:6](#), 10:11, 10:16, 10:22, 10:24
  - \\_\_socket\_debug\_gset: .....
    - ..... [10:7](#), 10:12, 10:17, 10:19
  - \\_\_socket\_debug\_term:n .....
    - ..... [10:7](#), 10:8, 10:23, 10:45,
    - 10:92, 10:108, 10:127, 10:145, [345](#)
- Sockets:
  - build/column/baselineattach . [54:723](#)
  - build/column/footnotes ..... [54:722](#)
  - build/column/outputbox ..... [54:663](#)
  - refstepcounter ..... [35:118](#)
  - refstepcounter/target ..... [35:119](#)
- \sourceLaTeXdate .....
  - ..... 08:2961, 03:164, 50:65, 50:103
- \sp ..... [38:212](#)
- \space ..... [02:322](#), [1323](#)
- space:floats:footnotes (plug) ... [54:688](#)
- space:footnotes:floats (plug) ... [54:664](#)
- \spacefactor ..... 17:33, 17:35,
  - 17:55, 17:57, 18:130, 18:139, 18:158,
  - 18:172, 18:184, 18:198, 18:212,
  - 18:463, 18:504, 18:509, 21:88, 21:91,
  - 45:531, 45:533, 02:380, 02:381, [1348](#)
- \spacefactor\_in\_math\_mode\_ugh/643 . [1371](#)
- \spaceskip ..... 33:6, 33:576, 02:296
- \spadesuit ..... 30:345
- \span ..... 41:383
- \special ..... 17:31, 17:53, [1154](#)
- \SplitArgument ..... [07:3314](#)
- \splitfirstmark ..... 54:2914
- \SplitList ..... [07:3314](#), [199](#)
- \splitmaxdepth .....
  - 45:469, 45:488, 45:506, 54:2908, 02:269
- \splittopskip 45:468, 45:487, 45:505, 02:294
- \sqcap ..... 30:387
- \sqcup ..... 30:388
- \sqrt ..... [38:413](#), [1336](#)
- \sqrtsign .... 30:540, 38:71, 38:413, [1336](#)
- \sqsubset ..... 29:857
- \sqsubseteq ..... 30:410
- \sqsupset ..... 29:858
- \sqsupseteq ..... 30:411
- \SS .. 21:324, 21:557, 21:1181, 57:671, [1341](#)
- \ss ..... 21:274,
  - 21:427, 21:580, 21:808, 21:1156, 57:671
- \sscdefault .... [25:2924](#), 25:2940, 25:3226
- \sscshape ..... [25:2924](#),
  - 25:2939, 25:3224, 25:3225, 32:31, [631](#)
- \stackrel ..... [38:411](#)
- \stamp ..... [1315](#)
- \star ..... 30:408
- \stepcounter ..... [525](#)
- \stepcounter .... [22:19](#), 22:29, 24:698,
  - [28:49](#), 35:125, 35:138, 35:148,
  - 35:180, 35:192, 35:203, 38:425,
  - 38:454, 38:516, 38:610, 45:452,
  - 45:520, 54:942, 54:1000, 54:1059, [1347](#)
- \stockheight ..... [54:71](#)
- \stockwidth ..... [54:71](#)
- \stop ..... 33:1600, [37:242](#)
- \storedpar ..... 04:156, 04:161
- str commands:
  - \c\_backslash\_str .....
    - . 09:164, 09:416, 07:1637, 07:1644,
    - 07:1660, 07:1664, 07:1715, 07:2855
  - \c\_hash\_str ..... 09:499, 09:503,
    - 09:527, 07:1421, 07:1554, 08:563, 08:569
  - \c\_right\_brace\_str ..... 08:2083
  - \str\_case:nn .....
    - ..... 09:613, 11:518, 57:562, 07:1156
  - \str\_case:nnTF .....
    - .. 09:57, 11:456, 36:29, 51:30, 07:3102

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- `\str_case_e:nnTF` ..... 07:2746
- `\str_count:n` .... 08:1880, 09:178, 09:253, 07:2838, 08:37, 08:43, 08:1266
- `\str_gset:Nn` ..... 08:2824
- `\str_head:n` ..... 07:2691
- `\str_if_empty:NTF` ..... 57:588
- `\str_if_eq:nn` ..... 271
- `\str_if_eq:NNTF` ..... 52:555
- `\str_if_eq:nnTF` . 08:1818, 08:1936, 08:2036, 08:2143, 08:2355, 08:2559, 08:2613, 08:2683, 09:232, 09:304, 09:386, 09:538, 09:545, 09:574, 09:577, 10:140, 11:80, 11:93, 11:244, 11:265, 11:470, 11:485, 11:501, 11:573, 11:753, 11:755, 11:929, 05:141, 52:131, 52:549, 52:559, 07:104, 07:106, 07:429, 07:814, 07:1235, 07:1240, 07:1736, 07:1790, 07:1793, 07:1796, 07:1799, 07:1858, 07:2277, 07:2290, 07:2292, 07:2322, 07:2342, 07:2344, 07:2363, 07:2390, 07:2418, 07:2420, 07:2445, 07:2447, 07:2470, 07:2587, 07:2599, 07:2627, 07:2803, 08:346, 08:438, 08:479, 08:536, 08:538, 08:625, 08:627, 08:757, 08:815, 08:848, 08:901, 08:983, 08:990, 08:1018, 08:1025, 177
- `\str_if_eq_p:nn` ..... 07:490, 07:491, 07:492, 07:493, 07:769, 07:961, 07:966, 07:2635, 07:2657, 08:905, 08:1609, 08:1695
- `\str_if_exist:NTF` ..... 10:54
- `\str_if_in:nnTF` ..... 11:384
- `\str_lowercase:n` ..... 57:600
- `\str_map_function:NN` ..... 05:148
- `\str_new:N` ..... 10:35, 11:28, 07:22
- `\str_replace_all:Nnn` ..... 09:526
- `\str_set:Nn` ..... 10:130, 11:646, 52:399, 52:400, 07:232, 07:246, 07:247, 07:291, 57:578, 57:586, 57:590
- `\str_tail:n` ..... 07:2277, 07:2688, 07:2714, 174
- `\str_use:N` ..... 10:67, 10:70, 10:128, 10:147, 10:148, 10:155
- str internal commands:
  - `\__str_if_eq:nn` ..... 08:23, 230
  - `\strcmp` ..... 50:346, 50:362
  - `\stretch` ..... 18:532
  - `\string` ..... 1309
  - `\stripmeaning` ..... 1312
  - `struct:mc (tag socket)` ..... 55:62
  - `\strut` ..... 38:191, 38:192, 41:29, 06:984, 06:1005, 02:398, 229
  - `\strutbox` 26:190, 40:490, 40:507, 40:524, 41:186, 41:187, 45:469, 45:477, 45:488, 45:495, 45:506, 45:513, 02:398
  - `\subencodingresult` .. 33:1200, 33:1205, 33:1374, 33:1378, 33:1380, 33:1381
  - `\subparagraphmark` ..... 44:143
  - `\subsectionmark` ..... 44:143, 1020
  - `\subset` ..... 30:437
  - `\subseteq` ..... 30:439
  - `\substdefault` ..... 1361
  - `\subsubsectionmark` ..... 44:143
  - `\succ` ..... 30:431
  - `\succeq` ..... 30:434
  - `\sum` ..... 30:361
  - `\sup` ..... 38:24
  - `\supereject` ..... 1340
  - `\suppressfloats` ..... 54:2582
  - `\supset` ..... 30:436
  - `\supseteq` ..... 30:438
  - `\surd` ..... 30:347
  - `\SuspendTagging` ..... 1263
  - `\SuspendTagging` ..... 23:22, 55:3, 1264
  - `\swarrow` ..... 30:419
  - `\swdefault` .... 25:2919, 25:2938, 25:3223
  - `\swshape` ..... 25:2919, 25:2937, 25:3221, 25:3222, 32:30
  - `\symbol` ..... 21:180, 29:702
  - `\symletters` ... 33:8, 33:14, 33:578, 33:1100
  - `\symoperators` ..... 30:654
  - sys commands:
    - `\sys_if_engine luatex:TF` ..... 53:26
- T
  - `\T` ..... 14:23, 21:355, 21:357, 21:359, 21:361, 21:363, 21:365, 21:367, 21:369, 21:371, 21:394, 50:1580, 50:1584, 50:1585
  - `\t` ..... 21:302, 21:765, 21:873, 33:121, 33:122, 33:149, 33:153, 33:155, 33:167, 33:170, 33:172, 33:652, 33:820, 33:1087, 33:1089, 33:1282, 1329
  - tabbing (env.) ..... 41:71
  - `\tabbing` ..... 41:71
  - `\tabbingsep` ..... 41:130, 41:132, 41:166
  - `\tabcolsep` ..... 41:259, 41:338
  - `\tableofcontents` ..... 834
  - `\tabskip` ..... 38:208, 38:209, 38:431, 38:434, 38:437, 38:439, 38:460, 38:463, 38:466, 38:468, 38:615, 38:628, 38:631, 38:633, 41:167, 41:192, 02:295, 02:409, 1309
  - tabular (env.) ..... 41:174
  - `\tabular` ..... 41:174
  - `\tabular*` ..... 41:175

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\tabularnewline</code> . . . . .	<a href="#">41:194</a> , <a href="#">41:207</a> , <a href="#">1333</a>	<code>kernel (para/end)</code> . . . . .	<a href="#">55:145</a>
tag commands:		<code>kernel (para/semantic/begin)</code> .	<a href="#">55:98</a>
<code>\tag_get:n</code> . . . . .	<a href="#">55:174</a>	<code>kernel (para/semantic/end)</code> . .	<a href="#">55:109</a>
<code>\tag_if_active:</code> . . . . .	<a href="#">55:26</a>	<code>kernel (recordtarget)</code> . . . . .	<a href="#">55:166</a>
<code>\tag_if_active:TF</code> . . . . .	<a href="#">55:318</a> , <a href="#">1381</a>	Tagging sockets:	
<code>\tag_mc_begin:n</code> . . . . .	<a href="#">55:57</a> , <a href="#">55:66</a> , <a href="#">55:141</a>	<code>block/list/label</code> . . . . .	<a href="#">55:179</a>
<code>\tag_mc_end:</code> . . . . .	<a href="#">55:59</a> , <a href="#">55:68</a> , <a href="#">55:151</a>	<code>block/recipe</code> . . . . .	<a href="#">55:180</a>
<code>\tag_resume:n</code> . . . . .	<a href="#">55:3</a> , <a href="#">55:4</a> , <a href="#">55:6</a>	<code>build/column/footins</code> . . . . .	<a href="#">55:230</a>
<code>\tag_socket_use:n</code> . . . . .	<a href="#">55:26</a> , <a href="#">55:29</a> , <a href="#">1264</a>	<code>build/column/outputbox</code> . . . . .	<a href="#">55:229</a>
<code>\tag_socket_use:nn</code> . . . . .	<a href="#">55:26</a> , <a href="#">55:30</a> , <a href="#">1264</a>	<code>build/page/footer</code> . . . . .	<a href="#">55:227</a>
<code>\tag_socket_use:nnn</code> . . . . .	<a href="#">55:26</a> , <a href="#">55:31</a> , <a href="#">1264</a>	<code>build/page/header</code> . . . . .	<a href="#">55:227</a>
<code>\tag_socket_use_expandable:n</code> . . . . .	<a href="#">55:26</a> , <a href="#">55:28</a> , <a href="#">1264</a>	<code>caption/begin</code> . . . . .	<a href="#">55:223</a>
<code>\tag_struct_begin:n</code> . . . . .	<a href="#">55:65</a> , <a href="#">55:102</a> , <a href="#">55:135</a>	<code>caption/end</code> . . . . .	<a href="#">55:223</a>
<code>\tag_struct_end:</code> . . . . .	<a href="#">55:69</a> , <a href="#">55:113</a> , <a href="#">55:153</a>	<code>caption/label/begin</code> . . . . .	<a href="#">55:225</a>
<code>\tag_suspend:n</code> . . . . .	<a href="#">55:3</a> , <a href="#">55:3</a> , <a href="#">55:5</a>	<code>caption/label/end</code> . . . . .	<a href="#">55:225</a>
tag internal commands:		<code>float/begin</code> . . . . .	<a href="#">55:221</a>
<code>\l__tag_block_flattened_level_-int</code> . . . . .	<a href="#">55:72</a> , <a href="#">55:85</a>	<code>float/end</code> . . . . .	<a href="#">55:221</a>
<code>\__tag_check_para_begin_show:nn</code> . . . . .	<a href="#">55:140</a>	<code>float/hmode/begin</code> . . . . .	<a href="#">55:219</a>
<code>\__tag_check_para_end_show:nn</code> . . . . .	<a href="#">55:152</a>	<code>float/hmode/end</code> . . . . .	<a href="#">55:219</a>
<code>\__tag_check_typeout_v:n</code> . . . . .	<a href="#">55:123</a> , <a href="#">55:134</a> , <a href="#">55:150</a>	<code>marginpar/begin</code> . . . . .	<a href="#">55:196</a>
<code>\__tag_gincr_para_begin_int:</code> . . . . .	<a href="#">55:133</a>	<code>marginpar/end</code> . . . . .	<a href="#">55:196</a>
<code>\__tag_gincr_para_end_int:</code> . . . . .	<a href="#">55:149</a>	<code>math/luamml/annotate/false</code> . .	<a href="#">55:244</a>
<code>\__tag_gincr_para_main_begin_-int:</code> . . . . .	<a href="#">55:101</a>	<code>math/luamml/array/finalize</code> . .	<a href="#">55:246</a>
<code>\__tag_gincr_para_main_end_int:</code> . . . . .	<a href="#">55:112</a>	<code>math/luamml/array/finalizecol</code> .	<a href="#">55:248</a>
<code>\__tag_lastpage_label:</code> . . . . .	<a href="#">53:360</a>	<code>math/luamml/array/initcol</code> . . .	<a href="#">55:247</a>
<code>\l__tag_para_attr_class_tl</code> . . . . .	<a href="#">55:98</a> , <a href="#">55:138</a>	<code>math/luamml/array/save</code> . . . . .	<a href="#">55:245</a>
<code>\l__tag_para_bool</code> . . . . .	<a href="#">55:74</a> , <a href="#">55:76</a> , <a href="#">55:86</a> , <a href="#">55:119</a> , <a href="#">55:147</a>	<code>math/luamml/artifact</code> . . . . .	<a href="#">55:260</a>
<code>\l__tag_para_flattened_bool</code> . . . . .	<a href="#">55:84</a> , <a href="#">55:127</a> , <a href="#">55:154</a>	<code>math/luamml/finph@nt</code> . . . . .	<a href="#">55:258</a> , <a href="#">55:259</a>
<code>\l__tag_para_main_attr_class_tl</code> . . . . .	<a href="#">55:105</a>	<code>math/luamml/hbox</code> . . . . .	<a href="#">55:257</a>
<code>\__tag_para_main_store_struct:</code> . . . . .	<a href="#">55:130</a>	<code>math/luamml/mtable/aligncol</code> .	<a href="#">55:251</a>
<code>\l__tag_para_main_tag_tl</code> . . . . .	<a href="#">55:82</a> , <a href="#">55:104</a>	<code>math/luamml/mtable/finalize</code> .	<a href="#">55:250</a>
<code>\l__tag_para_tag_default_tl</code> . . . . .	<a href="#">55:83</a>	<code>math/luamml/mtable/finalizecol</code> .	<a href="#">55:249</a>
<code>\l__tag_para_tag_tl</code> . . . . .	<a href="#">55:83</a> , <a href="#">55:137</a>	<code>math/luamml/mtable/innertable/finalize</code> . . . . .	<a href="#">55:254</a>
<code>\g__tag_struct_dest_num_prop</code> . . . . .	<a href="#">55:172</a>	<code>math/luamml/mtable/innertable/save</code> . . . . .	<a href="#">55:252</a>
<code>\tag_resume:n</code> . . . . .	<a href="#">1263</a>	<code>math/luamml/mtable/smallmatrix/save</code> . . . . .	<a href="#">55:253</a>
<code>\tag_socket_use:n</code> . . . . .	<a href="#">1263</a>	<code>math/luamml/mtable/tag/save</code> . .	<a href="#">55:255</a>
<code>\tag_socket_use:nn</code> . . . . .	<a href="#">1263</a>	<code>math/luamml/mtable/tag/set</code> . . .	<a href="#">55:256</a>
<code>\tag_socket_use:nnn</code> . . . . .	<a href="#">1263</a>	<code>math/luamml/save/nn</code> . . . . .	<a href="#">55:242</a>
<code>\tag_socket_use_expandable:n</code> . . . . .	<a href="#">1264</a>	<code>math/luamml/save/nNn</code> . . . . .	<a href="#">55:243</a>
<code>\tag_suspend:n</code> . . . . .	<a href="#">1263</a>	<code>mc</code> . . . . .	<a href="#">55:54</a>
Tagging Plugs:		<code>page@sofar</code> . . . . .	<a href="#">55:231</a>
<code>default</code> . . . . .	<a href="#">55:80</a>	<code>para/begin</code> . . . . .	<a href="#">55:89</a>
<code>kernel (para/begin)</code> . . . . .	<a href="#">55:117</a>	<code>para/end</code> . . . . .	<a href="#">55:89</a>
		<code>para/off</code> . . . . .	<a href="#">55:73</a>
		<code>para/on</code> . . . . .	<a href="#">55:73</a>
		<code>para/restore</code> . . . . .	<a href="#">55:79</a>
		<code>para/semantic/begin</code> . . . . .	<a href="#">55:96</a>
		<code>para/semantic/end</code> . . . . .	<a href="#">55:96</a>
		<code>refstepcounter</code> . . . . .	<a href="#">55:165</a>
		<code>sec/begin</code> . . . . .	<a href="#">55:181</a>
		<code>sec/end</code> . . . . .	<a href="#">55:181</a>

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

sec/title/begin	55:183	\tbl_init_cell_data_for_table: ..	55:338, 55:338
sec/title/end	55:183	\tbl_restore_outer_cell_data: ...	55:385, 55:385, 1272
sec/title/hang	55:185	\tbl_update_cell_data: 55:307, 55:307	
sec/title/init	55:186	\tbl_update_cell_data_for_next-	
sec/title/number	55:189	row: 55:359, 55:359	
sec/title/runin/number	55:186	\tbl_update_multicolumn_cell-	
sec/title/split	55:186	data:n 55:402, 55:402	
struct:mc	55:62	tbl internal commands:	
tbl/cell/begin	55:198	\g__tbl_col_int 55:283,	
tbl/cell/end	55:198	55:308, 55:319, 55:324, 55:339,	
tbl/colspan	55:208	55:356, 55:361, 55:364, 55:368,	
tbl/finalize	55:206	55:371, 55:383, 55:386, 55:393,	
tbl/hmode/begin	55:209	55:403, 55:406, 55:409, 55:414, 1276	
tbl/hmode/end	55:209	\g__tbl_missing_cells_int .....	
tbl/init	55:204	55:299, 55:321, 55:328, 55:332	
tbl/init/celldata	55:205	\g__tbl_missingcells_int .... 55:299	
tbl/leaders/begin	55:217	\g__tbl_row_int 55:283,	
tbl/leaders/end	55:217	55:340, 55:355, 55:360, 55:374,	
tbl/longtable/finalize	55:213	55:377, 55:380, 55:387, 55:392, 1276	
tbl/longtable/foot	55:215	\l__tbl_saved_col_tl .....	
tbl/longtable/head	55:215	55:290, 55:339, 55:346, 55:386	
tbl/longtable/init	55:213	\l__tbl_saved_row_tl .....	
tbl/pcell/end	55:198, 55:198	55:290, 55:340, 55:345, 55:387	
tbl/restore/celldata	55:207	\l__tbl_saved_span_tl .....	
tbl/row/begin	55:198	55:290, 55:342, 55:347, 55:388, 55:394	
tbl/row/end	55:198	\l__tbl_saved_table_cols_tl ...	
tbl/vmode/begin	55:209	55:290, 55:341, 55:349, 55:351, 55:389	
tbl/vmode/end	55:209	\g__tbl_span_tl .. 55:283, 55:308,	
toc/contentsline/after	55:190	55:309, 55:325, 55:342, 55:357,	
toc/contentsline/before	55:190	55:365, 55:388, 55:409, 55:411, 1276	
toc/leaders/after	55:194	\g__tbl_table_cols_tl .....	
toc/leaders/before	55:194	... 55:283, 55:313, 55:314, 55:323,	
toc/starttoc/after	55:192	55:341, 55:389, 55:396, 55:398, 1278	
toc/starttoc/before	55:192	\l__tbl_tmpa_seq 55:312, 55:313, 55:316	
\tan	38:15	\__tbl_trace:n ... 55:301, 55:304,	
\tanh	38:17	55:306, 55:314, 55:329, 55:344, 55:391	
target	36:240, 819	tbl/cell/begin (tag socket) .....	55:198
\tau	30:296	tbl/cell/end (tag socket) .....	55:198
tbl commands:		tbl/colspan (tag socket) .....	55:208
\tbl_count_missing_cells:n	55:317, 55:317, 55:416, 1281	tbl/finalize (tag socket) .....	55:206
\tbl_count_table_cols:	55:311, 55:311, 1278	tbl/hmode/begin (tag socket) .....	55:209
\tbl_crcr:n	55:413, 55:413	tbl/hmode/end (tag socket) .....	55:209
\tbl_gdecr_row_count:	55:373, 55:379	tbl/init (tag socket) .....	55:204
\tbl_gincr_row_count:	55:373, 55:376	tbl/init/celldata (tag socket) ...	55:205
\tbl_gzero_row_count:	55:373, 55:373	tbl/leaders/begin (tag socket) ...	55:217
\tbl_if_row_was_started:TF	55:367, 55:367, 55:370	tbl/leaders/end (tag socket) .....	55:217
\tbl_inbetween_rows:	55:382, 55:382	tbl/longtable/finalize (tag socket)	55:213
\tbl_init_cell_data_for_row:	55:363, 55:363	tbl/longtable/foot (tag socket) ..	55:215
\tbl_init_cell_data_for_table	1271	tbl/longtable/head (tag socket) ..	55:215
		tbl/longtable/init (tag socket) ..	55:213
		tbl/pcell/end (tag socket) .	55:198, 55:198
		tbl/restore/celldata (tag socket) .	55:207

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- tbl/row/begin (tag socket) . . . . . [55:198](#)
- tbl/row/end (tag socket) . . . . . [55:198](#)
- tbl/vmode/begin (tag socket) . . . . . [55:209](#)
- tbl/vmode/end (tag socket) . . . . . [55:209](#)
- template internal commands:
  - \\_\_template\_assign\_boolean: . . . . . [11:790](#), [11:790](#)
  - \\_\_template\_assign\_boolean\_aux:n . . . . . [11:790](#), [11:793](#), [11:794](#), [11:796](#)
  - \\_\_template\_assign\_choice: . . . . . [11:816](#), [11:816](#)
  - \\_\_template\_assign\_choice\_-aux:nTF . . . . . [11:816](#), [11:818](#), [11:821](#), [11:833](#), [11:838](#)
  - \\_\_template\_assign\_function: . . . . . [11:839](#), [11:839](#)
  - \\_\_template\_assign\_function\_-aux:N . . . . . [11:839](#), [11:842](#), [11:843](#), [11:845](#)
  - \\_\_template\_assign\_instance: . . . . . [11:856](#), [11:856](#)
  - \\_\_template\_assign\_instance\_-aux:N . . . . . [11:856](#), [11:859](#), [11:860](#), [11:862](#)
  - \\_\_template\_assign\_variable: . . . . . [11:760](#), [11:874](#), [11:874](#)
  - \\_\_template\_assign\_variable:n . . . . . [11:874](#), [11:876](#), [11:884](#)
  - \\_\_template\_assignments\_pop: . . . . . [11:939](#), [11:939](#), [11:1230](#)
  - \\_\_template\_assignments\_push:n . . . . . [11:698](#), [11:940](#), [11:940](#)
  - \l\_\_template\_assignments\_tl . . . . . [11:19](#), [11:699](#), [11:737](#), [11:801](#), [11:809](#), [11:836](#), [11:847](#), [11:864](#), [11:889](#), [11:896](#), [11:939](#), [11:941](#), [362](#)
  - \c\_\_template\_code\_root\_tl . . . . . [11:9](#), [11:55](#), [11:403](#), [11:406](#), [11:671](#), [11:673](#), [11:674](#), [11:700](#), [11:787](#), [11:943](#), [362](#)
  - \\_\_template\_convert\_to\_assignments: . . . . . [11:693](#), [11:735](#), [11:735](#), [11:786](#)
  - \\_\_template\_convert\_to\_assignments\_-aux:n . . . . . [11:735](#), [11:739](#), [11:741](#)
  - \\_\_template\_convert\_to\_assignments\_-aux:nn . . . . . [11:735](#), [11:744](#), [11:746](#), [11:765](#)
  - \\_\_template\_declare\_instance:nnnn . . . . . [11:676](#), [11:676](#), [11:1206](#)
  - \\_\_template\_declare\_instance\_-aux:nnnn . . . . . [11:676](#), [11:682](#), [11:685](#), [11:732](#)
  - \\_\_template\_declare\_template\_-code:nnnn . . . . . [11:375](#), [11:387](#), [11:389](#), [11:394](#), [11:401](#)
  - \\_\_template\_declare\_template\_-code:nnnnn . . . . . [11:375](#), [11:375](#), [11:1198](#)
  - \\_\_template\_declare\_template\_-keys:nnnn . . . . . [11:204](#), [11:204](#), [11:1196](#)
  - \\_\_template\_declare\_type:nn . . . . . [11:183](#), [11:187](#), [11:189](#)
  - \l\_\_template\_default\_tl . . . . . [11:20](#), [362](#)
  - \c\_\_template\_defaults\_root\_tl . . . . . [11:10](#), [11:100](#), [11:101](#), [11:140](#), [11:143](#), [362](#)
  - \\_\_template\_define\_type:nn . . . . . [11:183](#), [11:183](#), [11:1194](#)
  - \\_\_template\_edit\_defaults:nnn . . . . . [11:606](#), [11:606](#), [11:1202](#)
  - \\_\_template\_edit\_instance:nnn . . . . . [11:717](#), [11:717](#), [11:1210](#)
  - \\_\_template\_edit\_instance\_-aux:nnnn . . . . . [11:724](#), [11:729](#), [11:734](#)
  - \\_\_template\_edit\_instance\_-aux:nnnnn . . . . . [11:717](#)
  - \l\_\_template\_error\_bool . . . . . [11:21](#), [11:223](#), [11:229](#), [11:249](#), [11:278](#), [11:291](#), [11:623](#), [11:687](#), [11:689](#), [362](#)
  - \\_\_template\_execute\_if\_arg\_-agree:nnTF . . . . . [11:43](#), [11:43](#), [11:208](#), [11:379](#)
  - \\_\_template\_execute\_if\_code\_-exist:nnTF . . . . . [11:53](#), [11:53](#), [11:678](#), [11:781](#), [11:964](#)
  - \\_\_template\_execute\_if\_keys\_-exist:nnTF . . . . . [11:72](#)
  - \\_\_template\_execute\_if\_keytype\_-exist:nTF . . . . . [11:59](#), [11:59](#), [11:65](#), [11:225](#)
  - \\_\_template\_execute\_if\_type\_-exist:nTF . . . . . [11:66](#), [11:66](#), [11:206](#), [11:377](#)
  - \\_\_template\_find\_global: . . . . . [11:756](#), [11:766](#), [11:766](#)
  - \\_\_template\_find\_global\_aux:w . . . . . [11:766](#), [11:771](#), [11:774](#)
  - \l\_\_template\_global\_bool . . . . . [11:22](#), [11:768](#), [11:777](#), [11:792](#), [11:841](#), [11:858](#), [11:880](#), [362](#)
  - \\_\_template\_if\_instance\_exist:nn . . . . . [11:85](#)
  - \\_\_template\_if\_instance\_exist:nnTF . . . . . [11:85](#), [11:706](#), [11:719](#), [11:935](#), [11:981](#), [11:1224](#), [11:1226](#), [11:1228](#)
  - \\_\_template\_if\_key\_value:n . . . . . [11:78](#), [11:84](#)
  - \\_\_template\_if\_key\_value:nTF . . . . . [11:78](#), [11:798](#), [11:886](#)
  - \\_\_template\_if\_keys\_exist:nnTF . . . . . [11:72](#), [11:381](#), [11:608](#), [11:946](#), [11:955](#)
  - \\_\_template\_if\_use\_template:n . . . . . [11:91](#)
  - \\_\_template\_if\_use\_template:nTF . . . . . [11:91](#), [11:923](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

```

\__template_implement_choice_-
  elt:n ..... 11:536, 11:569, 11:601
\__template_implement_choice_-
  elt:nnn .... 11:537, 11:569, 11:569
\__template_implement_choice_-
  elt_aux:n ..... 11:569, 11:575, 11:583, 11:586
\__template_implement_choice_-
  elt_aux:nnn ..... 11:569, 11:574, 11:581, 11:593
\__template_implement_choices:nn
  ..... 11:458, 11:530, 11:530
\__template_implement_choices_-
  default: ... 11:530, 11:541, 11:548
\__template_instance_set_eq:nnn .
  ..... 11:704, 11:704, 11:1208
\c__template_instances_root_tl ..
  .... 11:11, 11:87, 11:694, 11:696,
  11:710, 11:712, 11:713, 11:936, 362
\l__template_key_name_tl .. 11:23,
  11:232, 11:235, 11:262, 11:264,
  11:285, 11:300, 11:307, 11:312,
  11:354, 11:356, 11:361, 11:424,
  11:427, 11:432, 11:476, 11:490,
  11:505, 11:514, 11:533, 11:534,
  11:539, 11:551, 11:555, 11:558,
  11:561, 11:564, 11:565, 11:588,
  11:591, 11:596, 11:598, 11:604,
  11:634, 11:637, 11:645, 11:758,
  11:819, 11:822, 11:824, 11:828, 378
\c__template_key_order_root_tl ..
  ..... 11:13,
  11:116, 11:117, 11:156, 11:159, 362
\l__template_key_order_seq .....
  ... 11:30, 11:118, 11:158, 11:161,
  11:212, 11:231, 11:264, 11:738, 363
\__template_key_to_value: .....
  ..... 11:800, 11:888, 11:903, 11:903
\__template_key_to_value_auxi:w .
  ..... 11:903, 11:904, 11:905
\__template_key_to_value_auxii:w
  ..... 11:903, 11:911, 11:916
\l__template_keytype_arg_tl ....
  ..... 11:25, 11:246, 11:259,
  11:260, 11:267, 11:324, 11:338,
  11:471, 11:532, 11:852, 11:869, 363
\l__template_keytype_tl .....
  ... 11:24, 11:225, 11:244, 11:258,
  11:265, 11:274, 11:323, 11:334,
  11:428, 11:430, 11:456, 11:518,
  11:659, 11:753, 11:755, 11:759, 363
\c__template_keytypes_arg_seq ...
  ..... 11:16, 11:227, 11:347, 362

\l__template_keytypes_prop .....
  ..... 11:29, 11:115, 11:152,
  11:155, 11:211, 11:262, 11:417,
  11:426, 11:432, 11:558, 11:588,
  11:634, 11:743, 11:824, 11:958, 363
\c__template_keytypes_root_tl ...
  .... 11:12, 11:74, 11:108, 11:111,
  11:113, 11:114, 11:150, 11:153, 362
\__template_map_var_type: .....
  11:497, 11:500, 11:516, 11:516, 11:878
\__template_parse_keys_elt:n ...
  .. 11:214, 11:220, 11:220, 11:273, 369
\__template_parse_keys_elt:nn ...
  ..... 11:214, 11:271, 11:271
\__template_parse_keys_elt_aux: .
  ..... 11:220, 11:237, 11:254
\__template_parse_keys_elt_aux:n
  ..... 11:220, 11:228, 11:242
\__template_parse_values:nnn ...
  11:611, 11:615, 11:615, 11:688, 11:785
\__template_parse_values_elt:n ..
  ..... 11:619, 11:621, 11:621
\__template_parse_values_elt:nn .
  ..... 11:619, 11:626, 11:626
\__template_parse_values_elt_-
  aux:n ..... 11:626, 11:636, 11:648
\__template_parse_values_elt_-
  aux:w ..... 11:626, 11:630, 11:641
\__template_parse_values_exp:N ..
  ..... 11:626, 11:661, 11:662
\__template_parse_values_exp:n ..
  ..... 11:626, 11:658, 11:660, 11:661
\__template_parse_vars_elt:n ...
  ..... 11:415, 11:420, 11:420
\__template_parse_vars_elt:nnn ..
  ..... 11:415, 11:422, 11:422
\__template_parse_vars_elt_-
  aux:nn ..... 11:422, 11:431, 11:436
\__template_parse_vars_elt_-
  aux:nnn ..... 11:422, 11:444, 11:448, 11:454, 11:510
\__template_parse_vars_elt_-
  aux:nw ..... 11:422, 11:438, 11:440
\__template_parse_vars_elt_-
  key:nn ..... 11:422, 11:463, 11:480, 11:498, 11:511
\__template_quark_if_nil:N ... 11:42
\__template_quark_if_nil:NTF 11:918
\__template_quark_if_nil:nTF . 11:42
\__template_quark_if_nil_p:n . 11:42
\__template_recover_defaults:nn .
  ..... 11:137, 11:137, 11:411,
  11:610, 11:665, 11:680, 11:783, 11:948

```

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=ltlooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

```

__template_recover_keytypes:nn .
    . . . . . 11:137,
    11:147, 11:412, 11:617, 11:667, 11:957
__template_recover_values:nn . . .
    11:137, 11:163, 11:708, 11:721, 11:983
__template_recover_vars:nn . . . .
    . . . . . 11:137, 11:173,
    11:669, 11:681, 11:731, 11:784, 11:966
\c__template_restrict_root_tl . . 362
__template_show:Nnnn . . . . .
    11:944, 11:949, 11:958, 11:967, 11:971
__template_show_code:nn . . . . .
    . . . . . 11:942, 11:942, 11:1214
__template_show_defaults:nn . . .
    . . . . . 11:944, 11:944, 11:1216
__template_show_keytypes:nn . . .
    . . . . . 11:944, 11:953, 11:1218
__template_show_values:nn . . . .
    . . . . . 11:979, 11:979, 11:1222
__template_show_vars:nn . . . . .
    . . . . . 11:944, 11:962, 11:1220
__template_split_keytype:n . . . .
    . . . . . 11:222, 11:276, 11:276
__template_split_keytype_arg:n .
    . . . . . 11:317,
    11:321, 11:321, 11:350, 11:430,
    11:560, 11:590, 11:650, 11:752, 11:826
__template_split_keytype_arg_-
    aux:n . 11:321, 11:325, 11:348, 11:351
__template_split_keytype_arg_-
    aux:w . 11:321, 11:329, 11:344, 11:352
__template_split_keytype_aux:w .
    . . . . . 11:276, 11:286, 11:297, 11:309
__template_store_defaults:nn . . .
    . . 11:97, 11:97, 11:215, 11:612, 11:666
__template_store_key_implementation:nnn
    . . . . . 11:383, 11:409, 11:409
__template_store_keytypes:nn . . .
    . . . . . 11:97, 11:105, 11:216, 11:668
__template_store_value:n . . . . .
    11:355, 11:355, 11:357, 11:358, 11:359
__template_store_value_aux:Nn . .
    . . . . . 11:360, 11:360, 11:363,
    11:365, 11:367, 11:369, 11:371, 11:373
__template_store_value_boolean:n
    . . . . . 11:353, 11:353
__template_store_value_choice:n
    . . . . . 11:355, 11:357
__template_store_value_commalist:n
    . . . . . 11:360, 11:374
__template_store_value_function:n
    . . . . . 11:355, 11:358
__template_store_value_instance:n
    . . . . . 11:355, 11:359
__template_store_value_integer:n
    . . . . . 11:360, 11:362
__template_store_value_length:n
    . . . . . 11:360, 11:364
__template_store_value_muskip:n
    . . . . . 11:360, 11:366
__template_store_value_real:n . .
    . . . . . 11:360, 11:368
__template_store_value_skip:n . .
    . . . . . 11:360, 11:370
__template_store_value_tokenlist:n
    . . . . . 11:360, 11:372, 11:374
__template_store_values:nn . . . .
    . . . . . 11:97, 11:121, 11:692, 11:709
__template_store_vars:nn . . . . .
    . . . . . 11:97, 11:129, 11:416, 11:670
__template_template_set_eq:nnn .
    . . . . . 11:663, 11:663, 11:1200
\l__template_tmp_clist . . . . .
    . . . . . 11:33, 11:532, 11:542,
    11:544, 11:571, 11:578, 11:580, 363
\l__template_tmp_dim . . . . 11:34, 363
\l__template_tmp_int . 11:35, 11:191,
    11:192, 11:195, 11:197, 11:201, 363
\l__template_tmp_muskip . . 11:36, 363
\l__template_tmp_skip . . . 11:37, 363
\l__template_tmp_tl . . . . .
    11:38, 11:45, 11:46, 11:50, 11:256,
    11:263, 11:279, 11:280, 11:281,
    11:287, 11:540, 11:550, 11:551,
    11:552, 11:554, 11:555, 11:556,
    11:559, 11:560, 11:562, 11:589,
    11:590, 11:597, 11:599, 11:635,
    11:650, 11:723, 11:725, 11:743,
    11:744, 11:825, 11:826, 11:835,
    11:836, 11:907, 11:908, 11:914, 363
\g__template_type_prop . . . . .
    11:18, 11:45, 11:68, 11:185, 11:196, 362
__template_use_instance:nn . . . .
    . . . . . 11:868, 11:921, 11:921, 11:1212
__template_use_instance_aux:nn .
    . . . . . 11:921, 11:925, 11:933
__template_use_instance_-
    aux:nNnnn . . 11:921, 11:924, 11:927
__template_use_template:nnn . . .
    . . . . 11:779, 11:779, 11:930, 11:1204
\l__template_value_exp_str . . . .
    . . . 11:28, 11:646, 11:651, 11:653, 363
\l__template_value_tl . . . . .
    . . . 11:26, 11:748, 11:798, 11:805,
    11:811, 11:819, 11:829, 11:853,
    11:870, 11:886, 11:892, 11:899,
    11:904, 11:909, 11:911, 11:919, 363

```

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\l__template_values_prop</code> .....	33:1517, 33:1518, 33:1519, 33:1520,
..... 11:31, 11:102,	33:1521, 33:1522, 33:1523, 33:1524,
11:126, 11:142, 11:145, 11:168,	33:1525, 33:1526, 33:1527, 33:1528,
11:171, 11:210, 11:354, 11:356,	33:1529, 33:1530, 33:1531, 33:1532,
11:361, 11:539, 11:561, 11:691,	33:1533, 33:1534, 33:1535, 33:1536,
11:722, 11:748, 11:949, 11:988, 363	33:1537, 33:1538, 33:1539, 33:1540,
<code>\c__template_values_root_tl</code> 11:14,	33:1541, 33:1542, 33:1543, 33:1544,
11:124, 11:125, 11:166, 11:169, 362	33:1545, 33:1546, 33:1547, 33:1548,
<code>\l__template_var_tl</code> .....	33:1549, 33:1550, 33:1551, 33:1552,
..... 11:27, 11:750, 11:769,	33:1553, 33:1554, 33:1555, 33:1556,
11:771, 11:776, 11:804, 11:812,	33:1557, 33:1558, 33:1559, 33:1560,
11:850, 11:866, 11:891, 11:898, 363	33:1561, 33:1562, 33:1563, 33:1564,
<code>\l__template_vars_prop</code> .....	33:1565, 33:1566, 33:1567, 33:1568,
... 11:32, 11:134, 11:178, 11:181,	33:1569, 33:1570, 33:1571, 33:1572,
11:413, 11:475, 11:489, 11:504,	33:1573, 33:1574, 33:1575, 33:1576,
11:533, 11:552, 11:556, 11:599,	33:1577, 33:1578, 33:1579, 33:1598
11:750, 11:835, 11:908, 11:967, 363	<code>\testallkerneldefinedfamilies</code> .....
<code>\c__template_vars_root_tl</code> . 11:15,	..... 33:1386, 33:1595
11:132, 11:133, 11:176, 11:179, 362	<code>\testFont</code> 33:1182, 33:1183, 33:1215, 33:1216
<code>\tencirc</code> ..... 31:10, 42:125, 42:677	<code>\testgroup</code> . 33:1187, 33:1225, 33:1234,
<code>\tencircw</code> ..... 31:10, 42:128	33:1240, 33:1246, 33:1250, 33:1254,
<code>\tenln</code> . 31:9, 42:124, 42:126, 42:676, 42:678	33:1264, 33:1268, 33:1336, 33:1340
<code>\tenlnw</code> ..... 31:9, 42:127, 42:129	<code>\TeX</code> ..... 19:1, 19:12, 1360
<code>\test</code> ..... 1315	TeX and L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> commands:
<code>\testallgroups</code> .....	<code>\...-hook</code> ..... 1360
33:1214, 33:1387, 33:1388, 33:1389,	<code>\...@without@substitution</code> ..... 643
33:1391, 33:1392, 33:1393, 33:1394,	<code>\@</code> ..... 09:392,
33:1395, 33:1396, 33:1397, 33:1398,	04:20, 14:19, 18:500, 19:2, 04:1026,
33:1399, 33:1400, 33:1401, 33:1402,	50:43, 50:58, 50:71, 50:80, 50:118,
33:1403, 33:1404, 33:1405, 33:1406,	06:925, 06:926, 57:512, 01:49, 1310
33:1407, 33:1408, 33:1409, 33:1413,	<code>\@...hook</code> ..... 239
33:1414, 33:1415, 33:1416, 33:1417,	<code>\@?@?</code> ..... 1310
33:1418, 33:1422, 33:1423, 33:1424,	<code>\@@</code> . 13:15, 13:19, 13:20, 13:21, 13:22,
33:1428, 33:1429, 33:1430, 33:1431,	13:24, 13:27, 13:28, 13:30, 13:31,
33:1432, 33:1433, 33:1434, 33:1435,	20:772, 20:792, 26:527, 26:529,
33:1436, 33:1437, 33:1438, 33:1439,	26:530, 41:238, 41:239, 41:240,
33:1440, 33:1441, 33:1442, 33:1443,	41:250, 01:315, 01:316, 54:6, 54:7
33:1444, 33:1445, 33:1446, 33:1447,	<code>\@@DeclareMathDelimiter</code> ..... 1321
33:1448, 33:1450, 33:1454, 33:1455,	<code>\@@defaultsubs</code> ..... 24:682
33:1456, 33:1457, 33:1458, 33:1459,	<code>\@enc@update</code> .....
33:1460, 33:1461, 33:1462, 33:1464,	..... 21:201, 24:322, 24:326, 1333
33:1465, 33:1466, 33:1467, 33:1468,	<code>\@end</code> ..... 20:741, 20:742, 01:206,
33:1469, 33:1470, 33:1471, 33:1472,	06:23, 37:35, 37:100, 37:176, 37:242,
33:1473, 33:1474, 33:1475, 33:1476,	56:18, 57:700, 57:721, 01:53, 474
33:1477, 33:1478, 33:1479, 33:1480,	<code>\@@endpbox</code> ..... 41:193, 41:236, 41:386
33:1481, 33:1482, 33:1483, 33:1484,	<code>\@eqnocr</code> ..... 38:443,
33:1485, 33:1486, 33:1487, 33:1488,	38:472, 38:496, 38:506, 38:511, 38:634
33:1489, 33:1490, 33:1491, 33:1492,	<code>\@fileswith@pti@ns</code> .....
33:1493, 33:1494, 33:1495, 33:1496,	..... 50:605, 50:624, 50:1112
33:1497, 33:1498, 33:1499, 33:1500,	<code>\@hyph</code> ..... 06:24, 06:942
33:1501, 33:1502, 33:1503, 33:1504,	<code>\@hyphenation</code> ..... 21:225
33:1505, 33:1506, 33:1507, 33:1508,	<code>\@if@newlist</code> ..... 54:876,
33:1509, 33:1510, 33:1511, 33:1512,	54:940, 54:953, 54:998, 54:1011, 54:1057
33:1513, 33:1514, 33:1515, 33:1516,	<code>\@ifdefinable</code> ..... 21:35, 06:173

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

$\backslash$ @input ..... 20:639,  
 20:652, 20:692, 06:22, 37:29,  
 37:94, 37:156, 50:1735, 52:172,  
 52:188, 52:196, 57:331, 01:52, *1315*  
 $\backslash$ @italiccorr *06:25*, 32:113, 32:117, *1317*  
 $\backslash$ @line ..... 40:614  
 $\backslash$ @math@bgroup ..... 32:131, 32:138  
 $\backslash$ @math@egroup ..... *32:128*  
 $\backslash$ @par .....  
 15:4, *16:140*, 16:177, *06:21*, 37:242,  
 37:533, 37:538, 37:541, 37:555,  
 37:559, 37:562, 39:82, 39:85, 40:334,  
 40:361, 40:385, 40:406, 41:195,  
 41:199, 44:67, 44:118, 54:262, *425*  
 $\backslash$ @patterns ..... *21:225*  
 $\backslash$ @protect ..... 06:358, 06:364, 06:373  
 $\backslash$ @sqrt ..... *1339*  
 $\backslash$ @startpbox ... 41:193, 41:236, *41:386*  
 $\backslash$ @sverb ..... *37:648*, *849*  
 $\backslash$ @text@case@aux .....  
 ..... 57:580, 57:614, 57:619, 57:624  
 $\backslash$ @underline ... *40:551*, 40:554, 40:555  
 $\backslash$ @unprocessedoptions .....  
 ..... 50:1024, 50:1089, *50:1187*  
 $\backslash$ @warning ..... *14:215*, *1313*  
 $\backslash$ @write ..... 54:112, 54:116  
 $\backslash$ @Alph ..... 22:231, *22:247*, *109*  
 $\backslash$ DeclareEncodingSubset .. 24:191,  
 24:193, 24:194, 24:195, 24:196, 24:199  
 $\backslash$ DeclareMathDelimiter .....  
 ..... 28:1039, *28:1058*, *1321*  
 $\backslash$ DeclareMathSizes .....  
 ..... 24:269, 24:270, *24:272*  
 $\backslash$ Esphack .....  
 . *18:191*, 45:201, 45:223, 45:241, *1307*  
 $\backslash$ Ialph ..... *1323*  
 $\backslash$ IncludeInRele@se ..... *03:71*  
 $\backslash$ IncludeInRelease ..... *03:71*  
 $\backslash$ LRmoderr *14:271*, 18:239, 18:290, *1380*  
 $\backslash$ M ..... 18:11,  
 18:12, 18:13, 18:14, 18:15, 18:16,  
 18:17, 18:18, 18:19, 18:120, 24:752,  
 24:760, 26:456, 26:469, 06:37,  
 06:39, 38:484, 39:225, 41:56, 44:67,  
 44:100, 44:118, 44:130, 44:234,  
 44:257, *02:21*, 54:155, 54:182,  
 54:200, 54:203, 54:263, 02:383, 02:384  
 $\backslash$ MM ..... 45:469,  
 45:488, 45:506, *02:21*, 54:304, *394*  
 $\backslash$ Mi ..... *12:3*, 54:114  
 $\backslash$ Mii ..... *12:3*, 45:53, 45:122,  
 45:194, 45:216, 45:241, 45:311,  
 54:300, 54:1510, 54:1659, 54:1821  
 $\backslash$ Miii *12:3*, 45:55, 45:124, 45:313, 54:303  
 $\backslash$ Miv ..... *12:3*,  
 45:195, 45:201, 45:217, 45:223, 54:277  
 $\backslash$ Roman ..... 22:229, *22:235*, *1346*  
 $\backslash$ TeXversion ..... 14:28, *01:310*, *2*  
 $\backslash$ abspage@last ... 53:105, 53:111,  
 53:351, 53:353, 53:355, 53:368,  
 53:372, 53:375, 53:415, 53:416, *1160*  
 $\backslash$ acci ... *29:904*, 40:387, 40:408, *1318*  
 $\backslash$ accii .. *29:904*, 40:387, 40:408, *1323*  
 $\backslash$ acciii . *29:904*, 40:387, 40:408, *1323*  
 $\backslash$ acol ..... 41:168, 41:178,  
 41:260, 41:261, 41:273, 41:274,  
 41:277, 41:294, 41:309, 41:317, 41:327  
 $\backslash$ acolampacol .... *41:258*, 41:275,  
 41:277, 41:284, 41:292, 41:326, 41:329  
 $\backslash$ activechar@info ..... *54:826*, *1320*  
 $\backslash$ activechar@warning ..... *1320*  
 $\backslash$ addamp ..... *41:251*, 41:260,  
 41:261, 41:276, 41:290, 41:327, 41:328  
 $\backslash$ addfield ..... 41:43, *41:53*,  
 41:86, 41:93, 41:125, 41:140, 41:142  
 $\backslash$ addmarginpar ..... 54:336, *54:2387*  
 $\backslash$ addtobot .....  
 54:1325, 54:1412, 54:1480, 54:1532,  
 54:1629, 54:1678, 54:1785, 54:1844  
 $\backslash$ addtocurcol 54:333, *54:1416*, 54:2575  
 $\backslash$ addtodblcol ..... 54:1204, *54:2138*  
 $\backslash$ addtofilelist .....  
 ... 20:64, 20:133, 20:188, 20:639,  
 20:761, 29:878, 29:881, 29:888,  
 29:891, 29:898, 29:901, 50:1734,  
 52:169, 52:188, 52:196, 57:279,  
 57:282, *57:741*, 01:85, 01:87, *1340*  
 $\backslash$ addtonextcol 54:1203, *54:1881*, 54:2576  
 $\backslash$ addtopreamble .. 41:311, 41:324,  
 41:330, 41:331, 41:332, *41:334*, 41:346  
 $\backslash$ addtoreset .. 22:18, 22:45, 22:65,  
 22:78, 22:133, 22:148, 22:162, 22:165  
 $\backslash$ addtotoporbot .....  
 ..... *54:1362*, 54:1526, 54:1674,  
 54:1838, 54:1931, 54:2012, 54:2100  
 $\backslash$ afterheading ... 44:92, *44:125*, *1344*  
 $\backslash$ afterindentfalse ..... 44:45  
 $\backslash$ afterindenttrue .....  
 ..... 44:43, *44:124*, 44:233, 44:256  
 $\backslash$ alph .... 22:230, *22:243*, 45:399, *109*  
 $\backslash$ ampacol *41:258*, 41:275, 41:286, 41:329  
 $\backslash$ arabic ..... 22:53, 22:71,  
 22:170, 22:217, 22:227, *22:233*, 45:397  
 $\backslash$ argarraycr ..... 41:203, *41:204*  
 $\backslash$ argdef ..... *06:98*  
 $\backslash$ argsrbox ..... *40:575*  
 $\backslash$ argtabularcr ..... 41:210, *41:211*  
 $\backslash$ array ..... 41:181, *41:182*

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\@arrayacol</code> .....	<a href="#">41:168</a> , <a href="#">41:258</a>	<code>\@bitor</code> .....	<a href="#">54:11</a> ,
<code>\@arrayclassiv</code> .....	<a href="#">41:169</a> , <a href="#">41:331</a>		<a href="#">54:1231</a> , <a href="#">54:1251</a> , <a href="#">54:1287</a> , <a href="#">54:1310</a> ,
<code>\@arrayclassz</code> .....	<a href="#">41:168</a> , <a href="#">41:275</a>		<a href="#">54:1377</a> , <a href="#">54:1462</a> , <a href="#">54:1472</a> , <a href="#">54:1611</a> ,
<code>\@arraycr</code> .....	<a href="#">41:170</a> , <a href="#">41:201</a> , <a href="#">41:203</a>		<a href="#">54:1621</a> , <a href="#">54:1764</a> , <a href="#">54:1775</a> , <a href="#">54:1918</a> ,
<code>\@arrayparboxrestore</code> .....			<a href="#">54:1999</a> , <a href="#">54:2085</a> , <a href="#">54:2203</a> , <a href="#">54:2328</a>
	<a href="#">40:377</a> , <a href="#">40:419</a> , <a href="#">41:384</a>	<code>\@botlist</code> ...	<a href="#">54:41</a> , <a href="#">54:389</a> , <a href="#">54:391</a> ,
<code>\@arrayrule</code> .....	<a href="#">41:309</a> ,		<a href="#">54:436</a> , <a href="#">54:438</a> , <a href="#">54:637</a> , <a href="#">54:657</a> ,
	<a href="#">41:311</a> , <a href="#">41:315</a> , <a href="#">41:317</a> , <a href="#">41:319</a> , <a href="#">41:346</a>		<a href="#">54:810</a> , <a href="#">54:1088</a> , <a href="#">54:1097</a> , <a href="#">54:1098</a> ,
<code>\@arstrut</code> .....	<a href="#">41:192</a> , <a href="#">41:237</a> , <a href="#">41:343</a>		<a href="#">54:1339</a> , <a href="#">54:1342</a> , <a href="#">54:1377</a> , <a href="#">54:1472</a> ,
<code>\@arstrutbox</code> .....			<a href="#">54:1621</a> , <a href="#">54:1775</a> , <a href="#">54:2531</a> , <a href="#">54:2559</a>
	<a href="#">41:185</a> , <a href="#">41:218</a> , <a href="#">41:343</a> , <a href="#">41:385</a> , <a href="#">1321</a>	<code>\@botnum</code> ...	<a href="#">45:274</a> , <a href="#">54:87</a> , <a href="#">54:1336</a> ,
<code>\@author</code> .....	<a href="#">44:8</a> , <a href="#">44:32</a>		<a href="#">54:1337</a> , <a href="#">54:1342</a> , <a href="#">54:1346</a> , <a href="#">54:1954</a> ,
<code>\@auxout</code> .....			<a href="#">54:1959</a> , <a href="#">54:2035</a> , <a href="#">54:2040</a> , <a href="#">54:2127</a> ,
	... <a href="#">20:236</a> , <a href="#">20:242</a> , <a href="#">20:286</a> , <a href="#">20:304</a> ,		<a href="#">54:2134</a> , <a href="#">54:2523</a> , <a href="#">54:2551</a> , <a href="#">54:2593</a>
	<a href="#">20:328</a> , <a href="#">20:361</a> , <a href="#">20:390</a> , <a href="#">20:413</a> ,	<code>\@botroom</code> .....	<a href="#">45:275</a> , <a href="#">54:88</a> ,
	<a href="#">20:437</a> , <a href="#">20:452</a> , <a href="#">35:105</a> , <a href="#">35:173</a> ,		<a href="#">54:1339</a> , <a href="#">54:1342</a> , <a href="#">54:2524</a> , <a href="#">54:2552</a>
	<a href="#">36:55</a> , <a href="#">44:189</a> , <a href="#">44:199</a> , <a href="#">47:7</a> , <a href="#">47:8</a> ,	<code>\@boxfpsbit</code> .	<a href="#">54:2651</a> , <a href="#">54:2653</a> , <a href="#">54:2658</a>
	<a href="#">47:39</a> , <a href="#">47:49</a> , <a href="#">47:57</a> , <a href="#">47:67</a> , <a href="#">47:84</a> , <a href="#">53:367</a>	<code>\@break@loop</code> .....	<a href="#">1321</a>
<code>\@backslashchar</code> ..	<a href="#">14:234</a> , <a href="#">14:236</a> ,	<code>\@break@tfor</code> .....	
	<a href="#">30:277</a> , <a href="#">06:272</a> , <a href="#">06:573</a> , <a href="#">06:722</a> ,		... <a href="#">13:31</a> , <a href="#">20:612</a> , <a href="#">20:629</a> , <a href="#">32:98</a> , <a href="#">1321</a>
	<a href="#">06:734</a> , <a href="#">06:738</a> , <a href="#">06:739</a> , <a href="#">06:744</a> ,	<code>\@bsphack</code> ...	<a href="#">18:37</a> , <a href="#">18:126</a> , <a href="#">18:387</a> ,
	<a href="#">06:788</a> , <a href="#">50:1316</a> , <a href="#">50:1449</a> , <a href="#">50:1538</a> , <a href="#">1323</a>		<a href="#">18:403</a> , <a href="#">18:421</a> , <a href="#">18:437</a> , <a href="#">35:102</a> ,
<code>\@backup@outputbox@depth</code> .....			<a href="#">35:172</a> , <a href="#">36:82</a> , <a href="#">44:186</a> , <a href="#">44:187</a> , <a href="#">45:52</a> ,
	... <a href="#">54:579</a> , <a href="#">54:589</a> , <a href="#">54:725</a> , <a href="#">1199</a>		<a href="#">45:121</a> , <a href="#">45:310</a> , <a href="#">46:6</a> , <a href="#">46:18</a> , <a href="#">46:23</a> ,
<code>\@badcrrr</code> .....	<a href="#">14:279</a> , <a href="#">1321</a>		<a href="#">46:35</a> , <a href="#">47:63</a> , <a href="#">47:80</a> , <a href="#">54:2458</a> , <a href="#">814</a>
<code>\@badend</code> .....	<a href="#">14:247</a> , <a href="#">37:392</a> , <a href="#">1308</a>	<code>\@caption</code> .....	<a href="#">45:12</a> , <a href="#">45:14</a>
<code>\@badlinearg</code> .....	<a href="#">14:267</a> , <a href="#">42:165</a> ,	<code>\@capttype</code> .....	<a href="#">45:5</a> , <a href="#">45:9</a> , <a href="#">45:12</a> ,
	<a href="#">42:177</a> , <a href="#">42:188</a> , <a href="#">42:189</a> , <a href="#">42:193</a> ,		<a href="#">45:40</a> , <a href="#">45:88</a> , <a href="#">45:109</a> , <a href="#">45:157</a> , <a href="#">54:2615</a>
	<a href="#">42:242</a> , <a href="#">42:247</a> , <a href="#">42:257</a> , <a href="#">42:262</a> , <a href="#">42:275</a>	<code>\@car</code> .....	<a href="#">19:14</a> ,
<code>\@badmath</code> .....	<a href="#">14:251</a> ,		<a href="#">21:107</a> , <a href="#">21:128</a> , <a href="#">06:53</a> , <a href="#">06:166</a> , <a href="#">06:222</a>
	<a href="#">38:275</a> , <a href="#">38:277</a> , <a href="#">38:282</a> , <a href="#">38:285</a> ,	<code>\@carcube</code> .....	<a href="#">06:55</a> , <a href="#">06:176</a> , <a href="#">06:725</a>
	<a href="#">38:311</a> , <a href="#">38:325</a> , <a href="#">38:330</a> , <a href="#">38:339</a> ,	<code>\@cclv</code> .....	<a href="#">02:16</a> ,
	<a href="#">38:351</a> , <a href="#">38:356</a> , <a href="#">38:364</a> , <a href="#">38:377</a> ,		<a href="#">54:305</a> , <a href="#">54:309</a> , <a href="#">54:387</a> , <a href="#">54:388</a> ,
	<a href="#">38:382</a> , <a href="#">38:557</a> , <a href="#">38:569</a> , <a href="#">38:585</a> , <a href="#">38:594</a>		<a href="#">54:417</a> , <a href="#">54:434</a> , <a href="#">54:435</a> , <a href="#">54:464</a> ,
<code>\@badpoptabs</code> ....	<a href="#">14:255</a> , <a href="#">41:85</a> , <a href="#">41:151</a>		<a href="#">54:492</a> , <a href="#">54:739</a> , <a href="#">54:743</a> , <a href="#">57:67</a> , <a href="#">1146</a>
<code>\@badrequireerror</code> ....	<a href="#">50:497</a> , <a href="#">50:1195</a>	<code>\@ccarvi</code> ..	<a href="#">04:30</a> , <a href="#">04:58</a> , <a href="#">02:21</a> , <a href="#">50:1314</a> ,
<code>\@badtab</code> .....	<a href="#">14:258</a> , <a href="#">41:22</a> ,		<a href="#">50:1447</a> , <a href="#">50:1536</a> , <a href="#">02:53</a> , <a href="#">02:78</a> , <a href="#">02:103</a>
	<a href="#">41:87</a> , <a href="#">41:108</a> , <a href="#">41:114</a> , <a href="#">41:121</a> , <a href="#">41:148</a>	<code>\@cdr</code> ....	<a href="#">20:270</a> , <a href="#">06:53</a> , <a href="#">06:868</a> , <a href="#">06:869</a>
<code>\@begin@tempboxa</code> .....		<code>\@centercr</code> ..	<a href="#">37:415</a> , <a href="#">37:453</a> , <a href="#">37:458</a> ,
	<a href="#">40:27</a> , <a href="#">40:46</a> , <a href="#">40:61</a> , <a href="#">40:246</a> , <a href="#">40:265</a> ,		<a href="#">37:463</a> , <a href="#">37:473</a> , <a href="#">37:477</a> , <a href="#">37:481</a> , <a href="#">1360</a>
	<a href="#">40:334</a> , <a href="#">40:361</a> , <a href="#">40:576</a> , <a href="#">40:584</a> , <a href="#">1312</a>	<code>\@centering</code> .....	<a href="#">38:418</a> ,
<code>\@begindocumenthook</code> .....			<a href="#">38:419</a> , <a href="#">38:431</a> , <a href="#">38:434</a> , <a href="#">38:437</a> ,
	... <a href="#">20:61</a> , <a href="#">20:127</a> , <a href="#">20:130</a> , <a href="#">20:182</a> ,		<a href="#">38:460</a> , <a href="#">38:463</a> , <a href="#">38:466</a> , <a href="#">38:627</a> , <a href="#">38:631</a>
	<a href="#">20:185</a> , <a href="#">47:53</a> , <a href="#">50:1123</a> , <a href="#">50:1144</a> , <a href="#">223</a>	<code>\@cflb</code> .....	<a href="#">54:639</a> , <a href="#">54:810</a> , <a href="#">54:1069</a>
<code>\@begindvi</code> .....		<code>\@cflt</code> .....	<a href="#">54:634</a> , <a href="#">54:809</a> , <a href="#">54:1069</a>
	<a href="#">54:909</a> , <a href="#">54:977</a> , <a href="#">54:1036</a> , <a href="#">54:1064</a> , <a href="#">1146</a>	<code>\@changed@cmd</code> .....	<a href="#">21:3</a> , <a href="#">21:81</a> ,
<code>\@begindvibox</code> .....			<a href="#">21:243</a> , <a href="#">24:132</a> , <a href="#">24:330</a> , <a href="#">57:476</a> , <a href="#">1334</a>
	<a href="#">53:455</a> , <a href="#">53:456</a> , <a href="#">54:62</a> , <a href="#">54:1065</a> , <a href="#">1141</a>	<code>\@changed@x</code> .	<a href="#">21:3</a> , <a href="#">21:231</a> , <a href="#">21:239</a> , <a href="#">1333</a>
<code>\@beginparpenalty</code> ..	<a href="#">18:15</a> , <a href="#">38:560</a> ,	<code>\@changed@x@err</code> .....	<a href="#">1341</a>
	<a href="#">38:572</a> , <a href="#">38:598</a> , <a href="#">39:23</a> , <a href="#">39:201</a> , <a href="#">873</a>	<code>\@changed@x@mouth</code> ..	<a href="#">21:231</a> , <a href="#">21:239</a> , <a href="#">1333</a>
<code>\@begintheorem</code> .....	<a href="#">43:43</a> , <a href="#">43:48</a>	<code>\@charlb</code> .....	<a href="#">20:458</a> , <a href="#">20:466</a>
<code>\@bezier</code> .....	<a href="#">42:683</a> , <a href="#">42:682</a>	<code>\@charrb</code> .....	<a href="#">20:460</a> , <a href="#">20:466</a>
<code>\@bibitem</code> .....	<a href="#">47:3</a> , <a href="#">47:8</a>	<code>\@chclass</code> .....	
<code>\@biblabel</code> .....	<a href="#">47:4</a> , <a href="#">47:97</a>		<a href="#">41:271</a> , <a href="#">41:272</a> , <a href="#">41:335</a> , <a href="#">41:348</a> , <a href="#">41:353</a>

File Key: 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\@check@IncludeInRelease</code> . . . . .	<a href="#">03:71</a>	<code>\@colht</code> 20:22, 20:92, 20:149, 45:273,	
<code>\@check@c</code> . . . . .	<a href="#">06:230</a> , <a href="#">06:232</a>	45:275, 45:278, 45:284, 45:285,	
<code>\@check@eq</code> . . . . .	<a href="#">06:236</a> , <a href="#">06:237</a> , <a href="#">06:241</a>	45:298, 45:299, 54:92, 54:236,	
<code>\@checkcommand</code> . . . . .	<a href="#">1325</a>	54:247, 54:256, 54:257, 54:392,	
<code>\@checkend</code> . . . . .		54:404, 54:439, 54:452, 54:481,	
. . . . .	<a href="#">37:16</a> , <a href="#">37:84</a> , <a href="#">37:148</a> , <a href="#">37:339</a> ,	54:509, 54:526, 54:532, 54:536,	
. . . . .	<a href="#">37:354</a> , <a href="#">37:371</a> , <a href="#">37:381</a> , <a href="#">37:391</a> , <a href="#">1335</a>	54:545, 54:550, 54:759, 54:777,	
<code>\@chnum</code> . . . . .	<a href="#">41:279</a> ,	54:781, 54:788, 54:941, 54:999,	
. . . . .	<a href="#">41:298</a> , <a href="#">41:335</a> , <a href="#">41:350</a> , <a href="#">41:351</a> , <a href="#">41:352</a>	54:1058, 54:1127, 54:1165, 54:1209,	
<code>\@circ</code> . . . . .		54:1234, 54:1253, 54:1293, 54:1315,	
. . . . .	<a href="#">42:621</a> , <a href="#">42:639</a> , <a href="#">42:648</a> , <a href="#">42:653</a> , <a href="#">42:656</a>	54:2218, 54:2344, 54:2716, 57:155	
<code>\@circle</code> . . . . .	<a href="#">42:604</a> , <a href="#">42:605</a>	<code>\@colnum</code> . . . . .	
<code>\@circlefnt</code> . . . . .	<a href="#">42:125</a> ,	. . . . .	
. . . . .	<a href="#">42:128</a> , <a href="#">42:447</a> , <a href="#">42:490</a> , <a href="#">42:519</a> ,	. . . . .	
. . . . .	<a href="#">42:544</a> , <a href="#">42:614</a> , <a href="#">42:630</a> , <a href="#">42:662</a> , <a href="#">42:677</a>	. . . . .	
<code>\@cite</code> . . . . .	<a href="#">47:36</a> , <a href="#">47:95</a>	. . . . .	
<code>\@cite@ofmt</code> . . . . .	<a href="#">47:44</a> , <a href="#">47:96</a>	. . . . .	
<code>\@citea</code> . . . . .	<a href="#">47:35</a> , <a href="#">47:37</a>	. . . . .	
<code>\@citeb</code> . . . . .	<a href="#">47:38</a> , <a href="#">47:39</a> ,	. . . . .	
. . . . .	<a href="#">47:40</a> , <a href="#">47:43</a> , <a href="#">47:44</a> , <a href="#">47:66</a> , <a href="#">47:67</a> ,	. . . . .	
. . . . .	<a href="#">47:68</a> , <a href="#">47:69</a> , <a href="#">47:83</a> , <a href="#">47:84</a> , <a href="#">47:85</a> , <a href="#">47:86</a>	. . . . .	
<code>\@citex</code> 47:20, 47:21, 47:29, <a href="#">47:34</a> , <a href="#">1010</a>		. . . . .	
<code>\@citex@checkblank</code> 47:17, 47:18, 47:30		. . . . .	
<code>\@classi</code> . . . . .	<a href="#">41:271</a> , <a href="#">41:307</a>	. . . . .	
<code>\@classii</code> . . . . .	<a href="#">41:271</a> , <a href="#">41:321</a>	. . . . .	
<code>\@classiii</code> . . . . .	<a href="#">41:271</a> , <a href="#">41:326</a>	. . . . .	
<code>\@classiv</code> . . . . .	<a href="#">41:169</a> , <a href="#">41:180</a> , <a href="#">41:272</a>	. . . . .	
<code>\@classoptionslist</code> . . . . .		. . . . .	
. . . . .	<a href="#">50:9</a> , <a href="#">50:546</a> , <a href="#">50:561</a> , <a href="#">50:562</a> ,	. . . . .	
. . . . .	<a href="#">50:579</a> , <a href="#">50:818</a> , <a href="#">50:819</a> , <a href="#">50:847</a> ,	. . . . .	
. . . . .	<a href="#">50:848</a> , <a href="#">50:874</a> , <a href="#">50:875</a> , <a href="#">50:1816</a> , <a href="#">1368</a>	. . . . .	
<code>\@classv</code> . . . . .	<a href="#">41:272</a> , <a href="#">41:332</a>	. . . . .	
<code>\@classz</code> . . . . .	<a href="#">41:168</a> , <a href="#">41:179</a> , <a href="#">41:271</a> , <a href="#">1274</a>	. . . . .	
<code>\@cline</code> . . . . .	<a href="#">41:367</a>	. . . . .	
<code>\@clnht</code> 42:195, 42:196, 42:204, 42:206,		. . . . .	
. . . . .	<a href="#">42:208</a> , <a href="#">42:218</a> , <a href="#">42:225</a> , <a href="#">42:273</a> , <a href="#">42:671</a>	. . . . .	
<code>\@clnwd</code> . . . . .	<a href="#">42:197</a> ,	. . . . .	
. . . . .	<a href="#">42:203</a> , <a href="#">42:207</a> , <a href="#">42:209</a> , <a href="#">42:210</a> , <a href="#">42:671</a>	. . . . .	
<code>\@cls@pkg</code> . . . . .	<a href="#">08:2716</a> ,	. . . . .	
. . . . .	<a href="#">50:353</a> , <a href="#">50:354</a> , <a href="#">50:367</a> , <a href="#">50:368</a> ,	. . . . .	
. . . . .	<a href="#">50:963</a> , <a href="#">50:973</a> , <a href="#">50:1021</a> , <a href="#">50:1068</a> ,	. . . . .	
. . . . .	<a href="#">50:1098</a> , <a href="#">50:1150</a> , <a href="#">50:1180</a> , <a href="#">50:1182</a> ,	. . . . .	
. . . . .	<a href="#">50:1199</a> , <a href="#">50:1744</a> , <a href="#">50:1766</a> , <a href="#">50:1796</a>	. . . . .	
<code>\@clsextension</code> . . . . .	<a href="#">50:31</a> ,	. . . . .	
. . . . .	<a href="#">50:156</a> , <a href="#">50:164</a> , <a href="#">50:222</a> , <a href="#">50:383</a> ,	. . . . .	
. . . . .	<a href="#">50:399</a> , <a href="#">50:411</a> , <a href="#">50:493</a> , <a href="#">50:517</a> ,	. . . . .	
. . . . .	<a href="#">50:528</a> , <a href="#">50:546</a> , <a href="#">50:560</a> , <a href="#">50:578</a> ,	. . . . .	
. . . . .	<a href="#">50:677</a> , <a href="#">50:692</a> , <a href="#">50:716</a> , <a href="#">50:817</a> ,	. . . . .	
. . . . .	<a href="#">50:846</a> , <a href="#">50:873</a> , <a href="#">50:967</a> , <a href="#">50:1014</a> ,	. . . . .	
. . . . .	<a href="#">50:1041</a> , <a href="#">50:1102</a> , <a href="#">50:1115</a> , <a href="#">50:1155</a> ,	. . . . .	
. . . . .	<a href="#">50:1170</a> , <a href="#">50:1621</a> , <a href="#">51:101</a> , <a href="#">51:168</a> , <a href="#">1081</a>	. . . . .	
<code>\@clubpenalty</code> . . . . .	<a href="#">20:7</a> , <a href="#">20:25</a> , <a href="#">20:95</a> ,	. . . . .	
. . . . .	<a href="#">20:152</a> , <a href="#">39:128</a> , <a href="#">39:227</a> , <a href="#">44:106</a> , <a href="#">44:135</a>	. . . . .	
<code>\@colht</code> 20:22, 20:92, 20:149, 45:273,		. . . . .	
45:275, 45:278, 45:284, 45:285,		. . . . .	
45:298, 45:299, 54:92, 54:236,		. . . . .	
54:247, 54:256, 54:257, 54:392,		. . . . .	
54:404, 54:439, 54:452, 54:481,		. . . . .	
54:509, 54:526, 54:532, 54:536,		. . . . .	
54:545, 54:550, 54:759, 54:777,		. . . . .	
54:781, 54:788, 54:941, 54:999,		. . . . .	
54:1058, 54:1127, 54:1165, 54:1209,		. . . . .	
54:1234, 54:1253, 54:1293, 54:1315,		. . . . .	
54:2218, 54:2344, 54:2716, 57:155		. . . . .	
<code>\@colnum</code> . . . . .		. . . . .	
. . . . .	<a href="#">45:276</a> , <a href="#">54:89</a> , <a href="#">54:1345</a> , <a href="#">54:1390</a> ,	. . . . .	
. . . . .	<a href="#">54:1460</a> , <a href="#">54:1461</a> , <a href="#">54:1489</a> , <a href="#">54:1497</a> ,	. . . . .	
. . . . .	<a href="#">54:1609</a> , <a href="#">54:1610</a> , <a href="#">54:1638</a> , <a href="#">54:1646</a> ,	. . . . .	
. . . . .	<a href="#">54:1762</a> , <a href="#">54:1763</a> , <a href="#">54:1795</a> , <a href="#">54:1807</a> ,	. . . . .	
. . . . .	<a href="#">54:1916</a> , <a href="#">54:1917</a> , <a href="#">54:1954</a> , <a href="#">54:1959</a> ,	. . . . .	
. . . . .	<a href="#">54:1997</a> , <a href="#">54:1998</a> , <a href="#">54:2035</a> , <a href="#">54:2040</a> ,	. . . . .	
. . . . .	<a href="#">54:2083</a> , <a href="#">54:2084</a> , <a href="#">54:2126</a> , <a href="#">54:2133</a> ,	. . . . .	
. . . . .	<a href="#">54:2519</a> , <a href="#">54:2547</a> , <a href="#">54:2586</a> , <a href="#">54:2826</a>	. . . . .	
<code>\@colroom</code> . . . . .		. . . . .	
. . . . .	<a href="#">20:23</a> , <a href="#">20:93</a> , <a href="#">20:150</a> , <a href="#">54:93</a> , <a href="#">54:257</a> ,	. . . . .	
. . . . .	<a href="#">54:278</a> , <a href="#">54:279</a> , <a href="#">54:290</a> , <a href="#">54:293</a> ,	. . . . .	
. . . . .	<a href="#">54:392</a> , <a href="#">54:439</a> , <a href="#">54:1127</a> , <a href="#">54:1344</a> ,	. . . . .	
. . . . .	<a href="#">54:1389</a> , <a href="#">54:1456</a> , <a href="#">54:1459</a> , <a href="#">54:1488</a> ,	. . . . .	
. . . . .	<a href="#">54:1605</a> , <a href="#">54:1608</a> , <a href="#">54:1637</a> , <a href="#">54:1757</a> ,	. . . . .	
. . . . .	<a href="#">54:1761</a> , <a href="#">54:1794</a> , <a href="#">54:1912</a> , <a href="#">54:1915</a> ,	. . . . .	
. . . . .	<a href="#">54:1993</a> , <a href="#">54:1996</a> , <a href="#">54:2078</a> , <a href="#">54:2082</a> ,	. . . . .	
. . . . .	<a href="#">54:2520</a> , <a href="#">54:2548</a> , <a href="#">54:2731</a> , <a href="#">54:2736</a> ,	. . . . .	
. . . . .	<a href="#">54:2781</a> , <a href="#">54:2786</a> , <a href="#">54:2831</a> , <a href="#">57:154</a> , <a href="#">1342</a>	. . . . .	
<code>\@combinedblfloats</code> . . . . .		. . . . .	
. . . . .	<a href="#">54:1100</a> , <a href="#">54:2890</a> , <a href="#">54:2932</a> , <a href="#">54:2969</a>	. . . . .	
<code>\@combinefloats</code> . . . . .		. . . . .	
. . . . .	<a href="#">54:755</a> , <a href="#">54:808</a> , <a href="#">54:1068</a> , <a href="#">1201</a>	. . . . .	
<code>\@comdblflleft</code> . . . . .	<a href="#">54:1100</a>	. . . . .	
<code>\@comflelt</code> . . . . .	<a href="#">54:1070</a> , <a href="#">54:1086</a> , <a href="#">54:1100</a>	. . . . .	
<code>\@compatibility</code> . . . . .	<a href="#">1313</a>	. . . . .	
<code>\@cons</code> . . . . .		. . . . .	
. . . . .	<a href="#">22:82</a> , <a href="#">22:91</a> , <a href="#">06:52</a> , <a href="#">45:193</a> , <a href="#">45:215</a> ,	. . . . .	
. . . . .	<a href="#">45:239</a> , <a href="#">45:379</a> , <a href="#">54:242</a> , <a href="#">54:1238</a> ,	. . . . .	
. . . . .	<a href="#">54:1257</a> , <a href="#">54:1273</a> , <a href="#">54:1297</a> , <a href="#">54:1299</a> ,	. . . . .	
. . . . .	<a href="#">54:1319</a> , <a href="#">54:1321</a> , <a href="#">54:1492</a> , <a href="#">54:1560</a> ,	. . . . .	
. . . . .	<a href="#">54:1641</a> , <a href="#">54:1705</a> , <a href="#">54:1800</a> , <a href="#">54:1873</a> ,	. . . . .	
. . . . .	<a href="#">54:1947</a> , <a href="#">54:2028</a> , <a href="#">54:2117</a> , <a href="#">54:2220</a> ,	. . . . .	
. . . . .	<a href="#">54:2243</a> , <a href="#">54:2346</a> , <a href="#">54:2371</a> , <a href="#">54:2388</a> ,	. . . . .	
. . . . .	<a href="#">54:2389</a> , <a href="#">54:2832</a> , <a href="#">02:119</a> , <a href="#">02:137</a>	. . . . .	
<code>\@contentsline@destination</code> . . . . .		. . . . .	
. . . . .	<a href="#">44:213</a> , <a href="#">44:215</a> , <a href="#">44:222</a> , <a href="#">980</a>	. . . . .	
<code>\@contfield</code> . . . . .	<a href="#">41:50</a> , <a href="#">41:141</a> , <a href="#">41:153</a>	. . . . .	
<code>\@copy@...</code> . . . . .	<a href="#">101</a>	. . . . .	
<code>\@copy@DeclareRobustCommand</code> . . . . .		. . . . .	
. . . . .	<a href="#">06:589</a> , <a href="#">06:659</a> , <a href="#">06:680</a> , <a href="#">06:758</a> , <a href="#">06:761</a>	. . . . .	
<code>\@copy@newcommand</code> . . . . .		. . . . .	
. . . . .	<a href="#">06:410</a> , <a href="#">06:590</a> , <a href="#">06:659</a> ,	. . . . .	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

06:701, 06:731, 06:758, 06:764, 94	\@currentHpage . . . 36:241, 36:242, 819
\@copytexsys . . . . . 1315	\@currentHref . . . . . 17:39,
\@ctrerr . . . . .	17:43, 35:99, 35:107, 35:117, 35:121,
14:243, 22:246, 22:250, 22:264, 22:272	35:147, 36:240, 55:169, 55:173, 819
\@curfield . . . . . 41:16, 41:41, 41:47,	\@currentcounter . . . . .
41:51, 41:52, 41:54, 41:130, 41:131	. . . 22:16, 35:114, 35:128, 35:141,
\@curline . . . . . 41:16, 41:27,	35:149, 35:179, 35:181, 35:191,
41:39, 41:44, 41:53, 41:54, 41:55,	36:243, 38:427, 38:456, 38:612,
41:90, 41:91, 41:103, 41:128, 41:129	40:485, 43:53, 43:55, 45:471, 1365
\@curr@enc . . . . . 21:172, 21:174	\@currentlabel . . . . .
\@curr@file . . . . .	. . . . . 35:106, 35:130, 35:143,
. . . 20:246, 20:247, 20:256, 20:258,	35:150, 35:174, 35:182, 35:193,
20:282, 20:290, 20:471, 20:490,	35:204, 35:212, 36:237, 38:426,
20:659, 20:674, 50:948, 50:1261,	38:455, 38:611, 40:486, 40:503,
50:1266, 50:1272, 50:1278, 50:1282,	40:520, 45:472, 45:490, 45:508, 818
50:1293, 50:1302, 50:1329, 50:1392,	\@currentlabelname . . . . .
50:1397, 50:1403, 50:1426, 50:1435,	. . . . . 35:98, 35:107, 36:239, 819
50:1461, 52:266, 52:374, 52:376, 1130	\@currentmetafamily 29:163, 29:165,
\@curr@file@reqd . . . . .	29:197, 29:204, 29:206, 29:229,
. . . . . 52:266, 52:376, 52:380, 1130	29:753, 29:756, 29:759, 29:761, 1386
\@currbox . . . . . 45:60, 45:91, 45:95,	\@currenttarget . . . . . 35:170
45:129, 45:160, 45:164, 45:193,	\@currenttitle . . . . . 35:169
45:214, 45:215, 45:239, 45:257,	\@currenvir . . . . .
45:259, 45:261, 45:319, 45:322,	. . . . 14:249, 37:3, 37:253, 37:274,
45:327, 45:331, 54:218, 54:219,	37:292, 37:302, 37:392, 39:112,
54:230, 54:231, 54:233, 54:234,	40:188, 50:1304, 50:1316, 50:1324,
54:242, 54:316, 54:317, 54:1203,	50:1328, 50:1335, 50:1437, 50:1449,
54:1204, 54:1452, 54:1455, 54:1463,	50:1457, 50:1461, 50:1467, 50:1526,
54:1486, 54:1490, 54:1492, 54:1507,	50:1538, 50:1546, 50:1550, 50:1556,
54:1548, 54:1560, 54:1602, 54:1604,	07:1630, 07:1736, 07:1751, 07:1762, 408
54:1612, 54:1635, 54:1639, 54:1641,	\@currenvline . . . . 14:249, 37:254,
54:1656, 54:1693, 54:1705, 54:1752,	37:275, 37:293, 37:303, 37:393, 40:189
54:1755, 54:1792, 54:1797, 54:1800,	\@currentxt . . . . .
54:1817, 54:1862, 54:1873, 54:1905,	. 50:30, 50:42, 50:57, 50:70, 50:79,
54:1922, 54:1936, 54:1947, 54:1987,	50:117, 50:379, 50:382, 50:383,
54:2003, 54:2017, 54:2028, 54:2069,	50:398, 50:399, 50:410, 50:411,
54:2106, 54:2117, 54:2157, 54:2161,	50:517, 50:528, 50:539, 50:546,
54:2172, 54:2178, 54:2180, 54:2184,	50:560, 50:578, 50:607, 50:687,
54:2189, 54:2198, 54:2207, 54:2213,	50:700, 50:702, 50:710, 50:724,
54:2220, 54:2243, 54:2278, 54:2282,	50:916, 50:917, 50:919, 50:923,
54:2294, 54:2301, 54:2303, 54:2307,	50:926, 50:928, 50:933, 50:938,
54:2313, 54:2323, 54:2338, 54:2346,	50:940, 50:945, 50:951, 50:959,
54:2371, 54:2389, 54:2398, 54:2621,	50:965, 50:967, 50:971, 50:976,
54:2622, 54:2651, 54:2681, 54:2686,	50:982, 50:991, 50:994, 50:999,
54:2737, 54:2740, 54:2752, 54:2760,	50:1002, 50:1005, 50:1007, 50:1008,
54:2787, 54:2790, 54:2802, 54:2810,	50:1010, 50:1014, 50:1023, 50:1025,
54:2827, 54:2832, 02:161, 02:162, 02:163	50:1026, 50:1031, 50:1034, 50:1037,
\@currdir . . . . .	50:1041, 50:1047, 50:1060, 50:1065,
. . . 01:92, 01:114, 01:116, 01:122,	50:1066, 50:1071, 50:1077, 50:1081,
01:124, 01:130, 01:132, 01:137,	50:1083, 50:1084, 50:1086, 50:1088,
01:139, 01:149, 01:162, 01:227,	50:1090, 50:1091, 50:1094, 50:1100,
01:240, 01:253, 50:1240, 50:1266,	50:1102, 50:1115, 50:1128, 50:1155,
50:1375, 50:1397, 50:1426, 50:1509, 9	50:1158, 50:1170, 50:1188, 50:1189,
\@current@cmd . . . . 21:43, 24:334, 1333	51:67, 51:84, 51:86, 51:101, 51:108,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

51:110, 51:168, 51:170, 51:173, 1079	\@dashbox . . . . .
\@currextension . . . . . 1309	. . . 42:324, 42:325, 42:326, 42:327,
\@currlist . . . . . 45:193,	42:328, 42:331, 42:337, 42:339,
45:215, 45:379, 54:43, 54:316,	42:349, 42:351, 42:352, 42:353,
54:393, 54:396, 54:440, 54:443, 54:2388	42:354, 42:358, 42:362, 42:365,
\@currname . . 03:71, 03:116, 03:124,	42:382, 42:384, 42:385, 42:386,
20:781, 20:803, 20:809, 50:29,	42:387, 42:390, 42:394, 42:396,
50:41, 50:56, 50:69, 50:78, 50:116,	42:405, 42:407, 42:408, 42:409,
50:351, 50:353, 50:365, 50:367,	42:410, 42:413, 42:417, 42:422, 42:673
50:379, 50:382, 50:398, 50:410,	\@dashcnt . . . . .
50:539, 50:607, 50:700, 50:702,	. . . 42:317, 42:319, 42:320, 42:321,
50:710, 50:724, 50:914, 50:917,	42:322, 42:323, 42:336, 42:338,
50:919, 50:923, 50:926, 50:928,	42:341, 42:343, 42:344, 42:345,
50:933, 50:935, 50:938, 50:940,	42:347, 42:348, 42:361, 42:364,
50:945, 50:950, 50:959, 50:963,	42:376, 42:377, 42:378, 42:379,
50:965, 50:971, 50:973, 50:974,	42:380, 42:381, 42:393, 42:395,
50:976, 50:982, 50:991, 50:993,	42:398, 42:399, 42:400, 42:401,
50:999, 50:1002, 50:1005, 50:1007,	42:403, 42:404, 42:416, 42:421, 42:673
50:1008, 50:1012, 50:1016, 50:1023,	\@dashdim . . . . . 42:316, 42:317,
50:1025, 50:1026, 50:1031, 50:1034,	42:318, 42:319, 42:320, 42:322,
50:1038, 50:1042, 50:1047, 50:1059,	42:325, 42:327, 42:328, 42:329,
50:1083, 50:1084, 50:1086, 50:1088,	42:336, 42:338, 42:340, 42:341,
50:1090, 50:1091, 50:1128, 50:1180,	42:342, 42:343, 42:344, 42:347,
50:1182, 50:1189, 50:1199, 50:1744,	42:351, 42:353, 42:354, 42:355,
50:1766, 50:1796, 51:67, 51:81,	42:363, 42:366, 42:375, 42:376,
51:84, 51:86, 51:108, 51:110, 51:170,	42:377, 42:378, 42:380, 42:384,
51:173, 51:216, 51:218, 51:229,	42:386, 42:387, 42:388, 42:393,
51:287, 08:368, 08:374, 08:429, 1353	42:395, 42:397, 42:398, 42:399,
\@currnamestack . . . . .	42:400, 42:403, 42:407, 42:409,
. . 50:33, 50:136, 52:546, 08:426, 1368	42:410, 42:411, 42:419, 42:424, 42:673
\@curroption . . . . . 1309	\@date . . . . . 44:9, 44:33
\@curroptions . . . . . 50:539,	\@dbflt . . . . . 45:32, 45:264, 1329
50:547, 50:597, 50:616, 50:1189, 50:1190	\@dblarg . . 44:54, 44:142, 45:12, 06:890
\@currpath . . . . .	\@dbldeferlist . . . . . 45:239,
. . . . 50:15, 50:46, 50:139, 50:351,	54:46, 54:450, 54:455, 54:457,
50:353, 50:915, 50:933, 50:940,	54:1166, 54:1173, 54:1174, 54:2328,
50:949, 50:991, 50:992, 50:1019, 1081	54:2371, 54:2535, 54:2564, 1354
\@currpkg@reqd . . . 50:381, 50:943,	\@dblfloat . . . . . 45:31
50:945, 50:954, 50:987, 50:1001,	\@dblfloatplacement . . . . .
50:1004, 50:1019, 50:1021, 1079	. . . . . 20:31, 20:101, 20:159,
\@currsize . . . . . 29:722, 1308	45:280, 54:406, 54:454, 54:2516,
\@currtype . . . . . 54:97,	54:2544, 54:2894, 54:2936, 54:2975
54:1228, 54:1229, 54:1230, 54:1231,	\@dblflset . . . . . 45:26
54:1248, 54:1249, 54:1250, 54:1251,	\@dblfpbot . . . . 45:290, 45:304, 54:3019
54:1377, 54:1462, 54:1472, 54:1611,	\@dblfpsep . . . . 45:289, 45:303, 54:3019
54:1621, 54:1764, 54:1775, 54:1918,	\@dblfpstop . . . . 45:288, 45:302, 54:3019
54:1999, 54:2085, 54:2203, 54:2328,	\@dbltoplist . . . . . 54:45, 54:237,
54:2621, 54:2623, 54:2624, 54:2627	54:240, 54:242, 54:402, 54:403,
\@curtab 41:11, 41:26, 41:86, 41:87,	54:450, 54:451, 54:1105, 54:1109,
41:88, 41:94, 41:95, 41:98, 41:102,	54:1111, 54:1112, 54:2215, 54:2220,
41:103, 41:107, 41:146, 41:147, 1340	54:2340, 54:2346, 54:2534, 54:2562
\@curtabmar 41:11, 41:25, 41:26, 41:38,	\@dbltopnum . . . . . 45:283,
41:44, 41:89, 41:102, 41:106, 41:107	45:297, 54:85, 54:105, 54:243,
\@d@r . . . . . 01:145, 01:146	54:245, 54:1116, 54:2154, 54:2155,

File Key: 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- 54:2219, 54:2222, 54:2250, 54:2255,  
54:2275, 54:2276, 54:2345, 54:2349,  
54:2378, 54:2383, 54:2527, 54:2555
- \@dbltoproom 45:284, 45:286, 45:298,  
45:300, 54:86, 54:2157, 54:2160,  
54:2161, 54:2170, 54:2171, 54:2174,  
54:2177, 54:2180, 54:2184, 54:2188,  
54:2192, 54:2197, 54:2217, 54:2278,  
54:2281, 54:2282, 54:2291, 54:2292,  
54:2293, 54:2296, 54:2300, 54:2303,  
54:2307, 54:2312, 54:2316, 54:2321,  
54:2322, 54:2343, 54:2528, 54:2556
- \@dec@text@cmd ..... [21:3](#)
- \@declarecommandcopylisthook ...  
... 06:586, [06:588](#), 06:600, 07:1164, [151](#)
- \@declareoptions .....  
..... [50:8](#), 50:500, 50:543,  
50:581, 50:602, 50:621, 50:1121, [1309](#)
- \@declareoption 50:498, 50:499, 50:507
- \@defaultfamilyhook [29:508](#), 29:780,  
29:795, 29:810, 29:815, 29:830, [1386](#)
- \@defaultsubs .... 24:636, 24:670,  
[24:682](#), 37:59, 37:124, 37:163, [1338](#)
- \@defaultunits .....  
... 24:277, 24:281, 24:282, 24:283,  
24:298, [24:391](#), 26:180, 26:182, 42:13
- \@defaultunitsset ... 40:74, 40:85,  
[42:8](#), 42:29, 42:30, 42:32, 42:34,  
42:60, 42:63, 42:84, 42:85, 42:107,  
42:108, 42:164, 42:241, 42:316,  
42:318, 42:332, 42:340, 42:342,  
42:357, 42:479, 42:480, 42:611,  
42:647, 42:689, 42:690, 42:692,  
42:693, 42:696, 42:697, 42:699,  
42:700, 42:711, 42:712, 42:714,  
42:715, 42:717, 42:718, 42:720, 42:721
- \@defdefault@ds 50:498, 50:503, 50:508
- \@deferlist ..... 54:44,  
54:389, 54:398, 54:399, 54:402,  
54:407, 54:409, 54:415, 54:436,  
54:445, 54:447, 54:1128, 54:1136,  
54:1137, 54:1148, 54:1153, 54:1154,  
54:1462, 54:1560, 54:1611, 54:1705,  
54:1764, 54:1873, 54:1918, 54:1947,  
54:1999, 54:2028, 54:2085, 54:2117,  
54:2203, 54:2243, 54:2533, 54:2561
- \@definecounter .... 22:12, [22:38](#),  
38:393, 39:258, 39:259, 39:260,  
39:261, 43:8, 43:16, 45:396, 45:398
- \@depth 26:192, 30:569, 30:570, [06:26](#),  
30:572, 30:573, 40:550, 40:603,  
40:610, 41:187, 41:219, 42:227,  
42:300, 42:303, 42:324, 42:333,  
42:383, 42:391, 42:726, 42:782, 54:2427
- \@dir .....  
01:144, 01:147, 01:149, 01:151, 01:152
- \@disable@packageload@do .....  
..... 50:938, [52:477](#)
- \@dischyp .....  
... 40:386, 40:407, [06:927](#), [06:961](#), [1357](#)
- \@docclearpage ... 54:301, [54:376](#), [1181](#)
- \@documentclass ..... [1311](#)
- \@documentclasshook .....  
... [50:3](#), 50:823, 50:851, 50:878, [1316](#)
- \@doendpe ..... 37:340, 37:355,  
37:372, 37:382, [39:123](#), 39:159, [881](#)
- \@dofilelist ..... 20:778,  
[20:820](#), 37:44, 37:109, 37:158, [1333](#)
- \@dofilelist@hash .... 20:809, [20:815](#)
- \@dofilelist@size .... 20:803, [20:815](#)
- \@donoparitem ..... [39:175](#), 39:189
- \@dot ..... 42:604, [42:642](#)
- \@dotsep ..... 44:240, 44:263
- \@dottedtocline [44:225](#), 44:251, 44:252
- \@downline ..... 42:297, [42:301](#), 42:306
- \@downvector ..... 42:268, [42:306](#)
- \@eha ..... 03:195, [14:219](#),  
14:237, 14:239, 14:241, 14:250,  
14:252, 14:284, 20:243, 20:287,  
20:305, 21:70, 21:102, 24:29, 24:59,  
24:103, 24:145, 24:250, 24:316,  
24:402, 26:107, 28:26, 28:71, 28:100,  
28:173, 28:204, 28:234, 28:266,  
28:550, 28:571, 28:623, 28:674,  
28:719, 28:724, 28:779, 28:897,  
28:901, 28:905, 28:940, 28:944,  
28:948, 28:1005, 28:1015, 28:1100,  
28:1105, 28:1108, 28:1140, 28:1143,  
28:1216, 28:1219, 28:1222, 28:1289,  
28:1295, 32:146, 33:24, 33:45,  
33:876, 33:885, 37:252, 37:273,  
37:291, 37:301, 06:384, 06:423,  
06:451, 47:71, 47:88, 54:2452, 54:2468
- \@ehb [14:219](#), 14:244, 14:270, 14:272,  
14:274, 14:276, 54:239, 54:395, 54:442
- \@ehc ..... 03:184, [14:219](#),  
14:279, 14:282, 14:288, 14:290,  
06:169, 06:196, 37:657, 37:674,  
37:688, 37:703, 37:716, 38:515,  
39:251, 44:31, 06:573, 06:614, 50:1796
- \@ehd ..... 03:102, 03:159, [14:219](#),  
14:246, 14:254, 14:257, 14:259,  
14:265, 28:119, 05:92, 41:100,  
41:109, 45:6, 50:757, 50:777, 50:1021
- \@elt .... 20:459, 21:1600, 21:1602,  
22:22, 22:37, 22:102, 22:105,  
29:162, 29:174, 29:176, 29:177,  
29:202, 29:236, 29:245, 29:247,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

- 29:248, 29:265, 29:584, 29:586,  
 29:587, 29:599, 29:871, 30:17,  
 30:25, 06:52, 54:4, 54:7, 54:11,  
 54:19, 54:21, 54:22, 54:23, 54:24,  
 54:27, 54:28, 54:29, 54:30, 54:31,  
 54:32, 54:33, 54:34, 54:36, 54:39,  
 54:495, 54:752, 54:1070, 54:1081,  
 54:1086, 54:1096, 54:1108, 54:1110,  
 54:1138, 54:1155, 54:1175, 54:1194,  
 54:1207, 54:1214, 54:1265, 54:1268,  
 54:1277, 54:2494, 54:2506, 1351  
 \@empty ..... 13:14, 1308  
 \@emptycol ..... 54:203,  
 54:250, 54:253, 54:282, 54:286, 1320  
 \@enc@info .....  
 ... 21:7, 21:12, 21:103, 21:211, 21:221  
 \@end@check@IncludeInRelease ...  
 ..... 03:143, 03:145  
 \@end@tempboxa .....  
 ..... 40:36, 40:55, 40:64, 40:258,  
 40:270, 40:352, 40:374, 40:582, 40:592  
 \@enddocument@kernel@warnings ...  
 .. 37:45, 37:54, 37:110, 37:119, 37:178  
 \@enddocumenthook .....  
 ..... 37:147, 50:1123, 50:1145  
 \@endfloatbox .....  
 ..... 45:190, 45:211, 45:236, 45:248  
 \@endpary ..... 39:120, 39:123, 881  
 \@endparpenalty ... 18:16, 38:561,  
 38:573, 38:599, 39:23, 39:124, 873  
 \@endpbox ..... 41:193,  
 41:236, 41:266, 41:333, 41:384, 41:387  
 \@endpfalse 37:258, 37:278, 37:296,  
 37:306, 39:129, 39:133, 39:137,  
 39:138, 39:140, 40:138, 40:191, 881  
 \@endptrue .....  
 .. 39:124, 39:126, 39:136, 39:140, 881  
 \@endpreamblehook ..... 458  
 \@endtheorem 43:13, 43:19, 43:25, 43:48  
 \@enlargepage 54:2437, 54:2442, 54:2444  
 \@ensuredmath ..... 38:526, 38:528  
 \@enumctr ..... 39:265, 39:268, 39:269  
 \@enumdepth .....  
 .. 39:257, 39:263, 39:264, 39:265, 886  
 \@enumsparing ..... 886  
 \@eqcnt ..... 38:415, 38:512,  
 38:517, 38:614, 38:629, 38:630, 38:632  
 \@eqncr ..... 38:432,  
 38:461, 38:481, 38:518, 38:519, 38:616  
 \@eqnnum ..... 38:400, 38:407,  
 38:410, 38:516, 38:547, 38:606, 1307  
 \@eqnset ..... 38:415, 38:628, 1309  
 \@eqnswfalse ..... 38:480  
 \@eqnswtrue .....  
 38:417, 38:428, 38:457, 38:517, 38:613  
 \@eqpen .....  
 38:415, 38:484, 38:486, 38:497, 38:507  
 \@er@ext ..... 1310  
 \@err@ ..... 14:37, 14:41,  
 14:44, 14:52, 14:64, 14:68, 14:71, 14:79  
 \@esphack .....  
 ... 18:39, 18:132, 18:392, 18:409,  
 18:426, 18:443, 35:109, 35:175,  
 36:86, 44:186, 44:187, 45:385, 46:17,  
 46:19, 46:34, 47:74, 47:90, 54:2460, 817  
 \@evenfoot .....  
 . 49:12, 49:15, 54:896, 54:967, 54:1026  
 \@evenhead .....  
 . 49:12, 49:15, 54:895, 54:966, 54:1025  
 \@execute@begin@hook .....  
 ..... 37:255, 37:259, 37:262, 837  
 \@executeoption ..... 1310  
 \@expandtwoargs .....  
 ..... 03:188, 06:258, 50:224,  
 50:350, 50:545, 50:581, 50:635, 50:644  
 \@expast ..... 41:239, 41:267  
 \@expl@@@filehook@clear@replacement@flag@@  
 ..... 50:449,  
 50:472, 52:295, 52:318, 52:339, 52:519  
 \@expl@@@filehook@drop@extension@@N  
 ..... 52:292, 52:293, 52:315,  
 52:316, 52:336, 52:337, 52:521, 1129  
 \@expl@@@filehook@file@pop@@ ...  
 ..... 50:956, 52:157, 52:525, 52:535  
 \@expl@@@filehook@file@pop@assign@@nnnn  
 ..... 52:162, 52:527, 1125  
 \@expl@@@filehook@file@push@@ ...  
 ..... 50:939, 52:151, 52:523  
 \@expl@@@filehook@if@file@replaced@@TF  
 . 52:289, 52:312, 52:333, 52:517, 1130  
 \@expl@@@filehook@if@no@extension@@nTF  
 ..... 52:285,  
 52:308, 52:329, 52:507, 52:509, 52:534  
 \@expl@@@filehook@normalize@file@name@@w  
 ..... 52:291, 52:314, 52:335, 52:515  
 \@expl@@@filehook@resolve@file@subst@@w  
 ..... 50:447,  
 50:470, 52:288, 52:311, 52:332, 52:513  
 \@expl@@@filehook@set@curr@file@@nNN  
 ..... 50:446, 50:469,  
 50:908, 52:374, 52:380, 52:511, 1130  
 \@expl@@@hook@curr@name@pop@@ ...  
 ..... 08:2923, 50:89  
 \@expl@@@hook@curr@name@push@@n 1366  
 \@expl@@@initialize@call@@ .....  
 ..... 08:2923, 37:263, 08:1486

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

\@expl@@mark@update@dblcol@structures@@	54:1257, 54:1273, 54:1287, 54:1310
..... 48:515, 48:528, 54:473	\@fcolmadefalse ..... 54:1183
\@expl@@mark@update@singlecol@structures@@	\@fcolmadetrue ..... 54:1271
..... 48:513, 48:527, 54:476	\@file-subst@{file} ..... 1126
\@expl@@@shipout@add@background@box@@@n	\@filef@und . 20:510, 20:522, 20:523,
..... 53:423, 53:529	20:526, 20:532, 20:564, 20:586,
\@expl@@@shipout@add@background@picture@@@n	20:609, 20:626, 20:639, 20:692,
..... 53:423, 53:533	52:155, 52:172, 52:188, 52:196, 1361
\@expl@@@shipout@add@firstpage@material@@@n	\@filehook@file@push ..... 1079
..... 53:423, 53:526	\@filehook@set@CurrentFile .....
\@expl@@@shipout@add@foreground@box@@@n	20:334, 20:395, 50:941, 52:152, 52:363
..... 53:423, 53:531	\@filelist .. 20:63, 20:132, 20:187,
\@expl@@@shipout@add@foreground@picture@@@n	20:760, 20:761, 20:780, 29:878,
..... 53:423, 53:535	29:888, 29:898, 57:279, 57:725, 57:741
\@expl@char@generate@@@nn ..... 05:149, 06:906, 1365	\@fileswf@false ..... 20:200,
\@expl@cs@{thing}@spec@@@N .... 1364	50:1236, 50:1237, 50:1371, 50:1372
\@expl@cs@argument@spec@@@N .... 1379	\@fileswith@ptions ..... 50:497,
\@expl@cs@parameter@spec@@@N ....	50:605, 50:624, 50:809, 50:810,
... 05:144, 05:145, 05:146, 05:157,	50:814, 50:816, 50:844, 50:845,
06:749, 06:802, 06:813, 06:818, 1379	50:871, 50:872, 50:899, 50:1112, 1309
\@expl@cs@prefix@spec@@@N ..... 05:142, 05:156, 06:747, 06:817	\@fileswith@ptions ..... 50:794,
\@expl@cs@replacement@spec@@@N ...	50:795, 50:802, 50:803, 50:807, 50:811
..... 05:147, 05:158, 06:707,	\@fileswith@ptions ..... 50:677, 50:684, 50:692, 50:783
06:742, 06:749, 06:803, 06:814, 06:818	\@filesw@true ..... 20:5,
\@expl@cs@to@str@@@N ..... 05:137, 05:140, 05:152, 05:154,	50:1219, 50:1222, 50:1279, 50:1283,
06:581, 06:673, 06:693, 06:695,	50:1354, 50:1357, 50:1412, 50:1416
06:696, 06:709, 06:722, 06:734,	\@final@strut ..... 40:490, 40:507, 40:524, 40:593,
06:738, 06:739, 06:744, 06:788,	41:385, 45:477, 45:495, 45:513, 1321
06:797, 06:801, 06:809, 06:811, 1364	\@first@stamp@false 41:254, 41:277, 41:294
\@expl@finalise@setup@@ ..... 05:34, 57:268, 57:269	\@first@stamp@true ..... 41:262
\@expl@pop@filename@@ ..... 05:30, 50:88, 50:92, 50:98, 50:109, 1364	\@first@col@first@mark ..... 54:2915, 54:2916, 54:2920
\@expl@push@filename@@ ..... 05:28, 50:37, 50:39, 50:52,	\@first@col@top@mark ... 54:2913, 54:2921
50:54, 50:64, 50:76, 50:96, 50:102, 1056	\@first@column@false ..... 54:2877, 54:2906, 54:2947
\@expl@push@filename@aux@@ ..... 08:2821, 05:29, 50:37,	\@first@column@true ..... 20:28, 20:98, 20:156,
50:48, 50:60, 50:64, 50:82, 50:102, 306	54:76, 54:212, 54:2881, 54:2924, 54:2953
\@expl@str@if@eq@@@nnTF ... 05:141,	\@first@off@five 35:23, 35:25, 35:40, 35:57
05:155, 06:545, 06:547, 50:350, 1364	\@first@of@one ..... 04:12, 04:100, 04:108, 04:166,
\@expl@str@map@function@@@NN .... 05:148, 05:159, 06:903, 109	17:7, 17:12, 20:126, 20:181, 20:478,
\@expl@str@map@function@@@NN and	21:86, 21:171, 26:363, 28:54, 28:82,
\@expl@char@generate@@@nn ... 1365	28:147, 28:185, 28:215, 28:246,
\@expl@sys@load@backend@@ ..... 20:17, 05:25, 05:27	05:38, 05:65, 05:80, 28:1050, 05:206,
\@expl@text@uppercase@@@n ..... 1372	05:214, 37:146, 06:253, 38:524,
\@extra@page@added 37:70, 37:135, 53:393	41:372, 06:569, 06:574, 06:575,
\@failed@list ..... 54:1192,	06:578, 06:579, 45:10, 06:610,
54:1215, 54:1231, 54:1238, 54:1251,	06:615, 06:616, 06:619, 06:620,
	47:38, 47:66, 47:83, 50:287, 50:289,
	50:291, 50:293, 50:295, 50:297,

**File Key:** 01=lt@dirchk.dtx, 02=lt@plain.dtx, 03=lt@vers.dtx, 04=lt@luatex.dtx, 05=lt@expl.dtx, 06=lt@defns.dtx, 07=lt@cmd.dtx, 08=lt@hooks.dtx, 09=lt@cmdhooks.dtx, 10=lt@sockets.dtx, 11=lt@templates.dtx, 12=lt@alloc.dtx, 13=lt@cntrl.dtx, 14=lt@error.dtx, 15=lt@par.dtx, 16=lt@para.dtx, 17=lt@meta.dtx, 18=lt@space.dtx, 19=lt@logos.dtx, 20=lt@files.dtx, 21=lt@outenc.dtx, 22=lt@counts.dtx, 23=lt@length.dtx, 24=lt@fssbas.dtx, 25=lt@fssaxes.dtx, 26=lt@fssstrc.dtx, 27=lt@fssc@mp.dtx, 28=lt@fssdcl.dtx, 29=lt@fssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=lt@fntcmd.dtx, 33=lt@textcomp.dtx, 34=lt@pageno.dtx, 35=lt@xref.dtx, 36=lt@properties.dtx, 37=lt@miscen.dtx, 38=lt@math.dtx, 39=lt@lists.dtx, 40=lt@boxes.dtx, 41=lt@tab.dtx, 42=lt@pictur.dtx, 43=lt@thm.dtx, 44=lt@sect.dtx, 45=lt@float.dtx, 46=lt@idxglo.dtx, 47=lt@bibl.dtx, 48=lt@marks.dtx, 49=lt@page.dtx, 50=lt@class.dtx, 51=lt@keys.dtx, 52=lt@filehook.dtx, 53=lt@shipout.dtx, 54=lt@out@put.dtx, 55=lt@tagging.dtx, 56=lt@thyphen.dtx, 57=lt@final.dtx

50:299, 50:301, 50:309, 50:957,  
 50:986, 52:352, 52:369, 57:359, *1335*  
 \@firstoftwo . 03:85, 17:11, 20:525,  
 20:531, 20:565, 20:610, 20:627,  
 21:151, 22:282, 22:287, 24:219,  
 24:239, 05:39, 05:47, 28:1054,  
 29:589, 33:798, 33:848, 33:864,  
 35:42, 35:78, 06:253, 06:298, 06:319,  
 06:546, 06:548, 06:570, 06:611,  
 06:676, 49:16, 06:727, 50:161,  
 50:195, 50:207, 50:230, 50:248,  
 50:307, 50:337, 06:842, 06:852,  
 06:862, 06:889, 50:1805, 06:913,  
 54:644, 54:653, 54:660, 01:71, *472*  
 \@firsttab . . . . . 41:2, 41:74,  
 41:75, 41:76, 41:106, 41:118, *1321*  
 \@flcheckspace 54:1339, 54:1375, 54:2722  
 \@flfail . . . . . 54:1215, 54:1266,  
 54:1287, 54:1297, 54:1310, 54:1319  
 \@float . . . . . 45:26, 45:32  
 \@floatboxreset 45:101, 45:170, 45:174  
 \@floatpenalty . . . . .  
 . 45:3, 45:53, 45:55, 45:58, 45:122,  
 45:124, 45:127, 45:191, 45:194,  
 45:199, 45:201, 45:212, 45:216,  
 45:221, 45:223, 45:237, 45:241,  
 45:311, 45:313, 45:317, 45:321, 45:379  
 \@floatplacement . . . 20:31, 20:101,  
 20:159, 45:271, 54:128, 54:214,  
 54:258, 54:484, 54:2517, 54:2545, *1311*  
 \@flsetnum 54:1336, 54:1372, 54:1460,  
 54:1609, 54:1762, 54:1916, 54:1997,  
 54:2083, 54:2154, 54:2275, 54:2690  
 \@flsettextmin . . . . .  
 . . . . . 54:1435, 54:1586, 54:1732,  
 54:1901, 54:1983, 54:2065, 54:2706  
 \@flstop . . . . . 54:2582  
 \@flsucceed . . . . . 54:1208,  
 54:1216, 54:1265, 54:1299, 54:1321  
 \@fltovf . 14:275, 45:93, 45:162, 45:322  
 \@flupdates . 54:1342, 54:1387, 54:2823  
 \@flushglue . 12:17, 37:454, 37:458,  
 37:464, 37:474, 37:477, 37:482,  
 37:532, 37:554, 39:76, 40:393, 40:414  
 \@fnsymbol . . . . . 22:232, 22:251  
 \@font@aliasinfo . . . . . 26:556  
 \@font@info . 24:134, 24:172, 24:178,  
 24:201, 24:202, 24:463, 24:480,  
 24:718, 25:2866, 26:31, 26:39, 26:47,  
 26:75, 26:88, 26:155, 26:201, 26:215,  
 26:226, 26:240, 26:256, 26:262,  
 26:275, 26:282, 26:289, 26:294,  
 26:304, 26:316, 26:328, 26:508,  
 26:520, 26:525, 26:532, 26:562,  
 26:575, 26:583, 28:280, 28:293,  
 28:304, 28:309, 28:314, 28:328,  
 28:345, 28:354, 28:373, 28:388,  
 28:423, 28:438, 28:498, 28:554,  
 28:653, 28:659, 28:703, 28:716,  
 28:799, 28:888, 28:931, 28:996,  
 28:1090, 28:1257, 28:1286, 33:63, 57:478  
 \@font@series@contextfalse . . . . .  
 . . . . . 29:581, 29:621  
 \@font@series@contexttrue . . . . .  
 . . . . . 29:602, 29:606, 29:620  
 \@font@shape@subst@warning . . . . .  
 . . . . . 25:2833, 25:2836,  
 25:2841, 25:2899, 25:3178, 25:3181, *635*  
 \@font@warning . . . . . 24:4,  
 24:632, 24:637, 24:664, 24:671,  
 25:2844, 26:20, 26:34, 26:42, 26:50,  
 26:62, 26:78, 26:493, 26:507, 26:519,  
 26:524, 26:531, 26:574, 26:582,  
 27:30, 37:56, 37:121, 37:160, 57:300  
 \@fontenc@load@list . . . . .  
 . . 21:1601, 29:871, 30:17, 30:25, *1362*  
 \@fontswitch . . . . 32:126, 32:128, *1321*  
 \@footnotemark . . . . . 45:454,  
 45:460, 45:522, 45:528, 45:529, 45:555  
 \@footnotetext . . . . . 40:455,  
 45:454, 45:460, 45:461, 45:538, 45:544  
 \@for . . . . . 13:16, 20:252,  
 20:324, 20:386, 20:433, 20:780,  
 47:36, 47:65, 47:82, 50:232, 50:249,  
 50:543, 50:562, 50:579, 50:597,  
 50:602, 50:616, 50:621, 50:657,  
 50:667, 50:1190, 50:1227, 50:1362, *1010*  
 \@forced@seriesfalse . . . . .  
 . . . . . 25:2782, 25:2795, 26:141  
 \@forced@seriestrue . 25:2786, 25:2797  
 \@forloop . . . . . 13:19, 13:20  
 \@fornoop . . . . . 13:15, 13:23, 13:29  
 \@fortmp . . . . .  
 13:17, 13:18, 13:26, 50:655, 50:657,  
 50:1226, 50:1227, 50:1361, 50:1362  
 \@fpbot 45:290, 45:304, 54:1213, 54:3013  
 \@fpmin . . . . . 45:278,  
 45:287, 45:301, 54:91, 54:1270,  
 54:2525, 54:2553, 54:2840, 54:2857  
 \@fps 45:41, 45:42, 45:44, 45:47, 45:64,  
 45:110, 45:111, 45:113, 45:116,  
 45:133, 54:2613, 54:2615, 54:2618  
 \@fpsadddefault . . . . .  
 . 45:45, 45:48, 45:114, 45:117, 54:2610  
 \@fpsep . . . 45:289, 45:303, 54:1211,  
 54:1220, 54:1292, 54:1314, 54:3013  
 \@fpstype 54:1333, 54:1354, 54:1355,  
 54:1369, 54:1400, 54:1401, 54:1425,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

54:1427, 54:1430, 54:1432, 54:1484,  
 54:1540, 54:1541, 54:1576, 54:1578,  
 54:1581, 54:1583, 54:1633, 54:1685,  
 54:1686, 54:1720, 54:1723, 54:1726,  
 54:1729, 54:1790, 54:1852, 54:1853,  
 54:1891, 54:1893, 54:1896, 54:1898,  
 54:1973, 54:1975, 54:1978, 54:1980,  
 54:2053, 54:2056, 54:2059, 54:2062,  
 54:2151, 54:2166, 54:2168, 54:2186,  
 54:2195, 54:2231, 54:2232, 54:2272,  
 54:2287, 54:2289, 54:2309, 54:2319,  
 54:2358, 54:2359, 54:2596, 54:2622,  
 54:2624, 54:2626, 54:2629, 54:2630,  
 54:2631, 54:2633, 54:2634, 54:2638,  
 54:2639, 54:2641, 54:2642, 54:2676,  
 54:2678, 54:2680, 54:2692, 54:2694,  
 54:2708, 54:2710, 54:2745, 54:2748,  
 54:2759, 54:2795, 54:2798, 54:2809  
 \@fptop 45:288, 45:302, 54:1210, 54:3013  
 \@frameb@x .....  
 . 40:218, 40:257, 40:269, 40:273, 1327  
 \@framebox ..... 40:225, 40:232, 40:236  
 \@framepicbox .. 40:225, 40:232, 40:294  
 \@freelist ..... 45:60, 45:129,  
 45:319, 45:320, 54:20, 54:25, 54:37,  
 54:218, 54:496, 54:753, 54:1082,  
 54:1097, 54:1111, 54:1216, 54:2388,  
 54:2389, 02:119, 02:137, 02:161, 1195  
 \@generic@error ..... 1326  
 \@generic@message ..... 1326  
 \@getcirc ..... 42:437,  
 42:484, 42:513, 42:540, 42:612, 42:628  
 \@getfpsbit ..... 54:1330,  
 54:1366, 54:2148, 54:2269, 54:2649  
 \@getlarrow .... 42:266, 42:274, 42:276  
 \@getlinechar ..... 42:190, 42:229  
 \@getpen ... 18:35, 18:38, 18:47, 18:118  
 \@getrarrow .... 42:267, 42:274, 42:283  
 \@glossaryfile ... 46:21, 46:22, 46:31  
 \@gnewline 18:96, 18:102, 18:109, 18:112  
 \@gobble ..... 03:163,  
 03:187, 04:11, 13:6, 13:9, 04:98,  
 14:101, 14:127, 14:147, 14:155,  
 14:180, 14:189, 14:202, 17:6, 17:13,  
 17:21, 18:76, 18:559, 20:64, 20:133,  
 20:188, 20:485, 20:487, 20:760,  
 21:47, 24:633, 24:666, 26:362, 27:26,  
 28:29, 28:31, 05:37, 28:502, 28:513,  
 28:597, 28:664, 28:665, 28:694,  
 28:700, 28:708, 28:713, 28:731,  
 05:69, 28:745, 28:755, 28:764,  
 28:777, 28:794, 28:803, 28:877,  
 28:879, 28:883, 28:891, 28:925,  
 28:934, 05:92, 28:986, 28:988,  
 28:999, 28:1083, 28:1093, 28:1174,  
 28:1179, 28:1248, 28:1279, 29:140,  
 29:202, 29:265, 29:599, 29:881,  
 29:891, 29:901, 05:206, 05:214,  
 33:825, 06:129, 06:174, 37:283,  
 06:249, 06:272, 06:340, 06:344,  
 06:381, 06:387, 06:390, 06:400,  
 06:420, 06:426, 06:429, 06:438,  
 06:448, 06:454, 06:457, 06:466,  
 06:484, 06:488, 06:490, 06:491,  
 06:493, 06:501, 06:505, 06:507,  
 44:143, 44:144, 44:145, 44:146,  
 44:147, 44:200, 45:7, 47:11, 47:45,  
 47:46, 50:287, 50:289, 50:291,  
 50:293, 50:295, 50:297, 50:299,  
 50:301, 50:309, 50:745, 50:936,  
 50:1211, 50:1275, 50:1302, 50:1406,  
 50:1435, 50:1519, 50:1524, 50:1598,  
 50:1750, 50:1762, 52:261, 54:973,  
 54:974, 54:975, 54:1032, 54:1033,  
 54:1034, 54:1277, 54:2508, 54:2841,  
 54:2858, 57:282, 57:411, 57:741, 1079  
 \@gobble@AddToHook@args .....  
 ..... 08:2939, 08:2940  
 \@gobble@IncludeInRelease .... 03:71  
 \@gobble@RemoveFromHook@arg ....  
 ..... 08:2942, 08:2943  
 \@gobble@om .....  
 ... 44:180, 44:190, 44:192, 44:203, 88  
 \@gobble@som .....  
 ... 44:180, 44:191, 44:197, 44:204, 88  
 \@gobble@with@sphack@om .....  
 ... 44:180, 44:205, 54:903, 54:905, 88  
 \@gobble@with@sphack@som .....  
 ..... 44:180, 44:206, 54:904, 88  
 \@gobblecr ..... 18:557, 18:558  
 \@gobblefour ..... 28:25, 28:499,  
 28:655, 28:657, 28:661, 28:663,  
 28:673, 28:677, 28:801, 28:853,  
 06:249, 50:1304, 50:1437, 50:1526  
 \@gobblethree .....  
 . 06:249, 06:736, 50:128, 06:748, 1333  
 \@gobbletwo ..... 13:12,  
 20:32, 20:102, 20:160, 24:638,  
 24:672, 28:133, 05:127, 05:132,  
 06:216, 06:217, 37:24, 37:57, 37:91,  
 37:122, 37:153, 37:161, 06:249,  
 49:11, 49:13, 50:1274, 50:1405,  
 50:1518, 52:260, 52:489, 57:306, 1338  
 \@gtempa ..... 20:704,  
 20:705, 20:711, 20:712, 20:713,  
 20:738, 20:739, 20:741, 20:742,  
 20:743, 06:166, 06:168, 06:222,  
 06:224, 41:3, 41:5, 41:6, 41:7,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=lt page.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

- 41:8, 06:667, 06:675, 50:349, 50:351,  
50:364, 50:365, 50:384, 50:386,  
50:400, 50:402, 50:412, 50:414, 1317
- \@halfwidth ..... 42:2,  
42:126, 42:129, 42:131, 42:227,  
42:299, 42:302, 42:324, 42:333,  
42:349, 42:361, 42:364, 42:383,  
42:391, 42:405, 42:416, 42:421,  
42:679, 42:705, 42:724, 42:725,  
42:726, 42:765, 42:780, 42:781, 42:782
- \@halignto 41:170, 41:174, 41:177, 41:191
- \@hangfrom ..... 44:66, 44:117, 44:138
- \@height .....  
... 18:397, 18:405, 18:431, 18:439,  
21:313, 21:315, 26:191, 30:351,  
30:569, 30:570, 06:26, 30:572,  
30:573, 40:202, 40:207, 40:280,  
40:290, 40:550, 40:603, 40:610,  
41:186, 41:219, 41:359, 41:376,  
42:227, 42:300, 42:303, 42:324,  
42:333, 42:351, 42:359, 42:383,  
42:391, 42:407, 42:414, 42:589,  
42:599, 42:725, 42:781, 54:2427, 02:377
- \@highpenalty ..... 18:119, 57:3
- \@hightab ..... 41:11,  
41:21, 41:23, 41:74, 41:86, 41:95,  
41:96, 41:111, 41:146, 41:147, 1340
- \@hline . 42:167, 42:179, 42:226, 42:265
- \@holdpg ..... 54:100, 54:305,  
54:307, 54:308, 54:313, 54:314, 54:315
- \@hspace . 18:512, 18:513, 18:529, 1308
- \@hspacer ..... 18:512, 18:528, 1308
- \@hvector ..... 42:244, 42:259, 42:265
- \@ialph ..... 1323
- \@icentercr ..... 37:432, 37:433
- \@iden ..... 06:256
- \@if ..... 06:212, 06:213, 06:215
- \@if.. ..... 1323
- \@if@DeclareRobustCommand .....  
..... 09:143, 06:589,  
06:646, 06:657, 06:658, 06:662,  
06:756, 06:757, 06:760, 06:783, 101
- \@if@bottomfloats@TF .....  
..... 54:577, 54:656, 54:667,  
54:676, 54:689, 54:712, 54:815, 1187
- \@if@flushbottom@TF .. 54:642, 54:813
- \@if@footnotes@TF .....  
..... 54:574, 54:649, 54:665,  
54:683, 54:691, 54:708, 54:814, 1187
- \@if@newcommand .. 09:144, 09:155,  
06:408, 06:590, 06:647, 06:658,  
06:700, 06:712, 06:718, 06:784, 102
- \@if@newlist ..... 1350
- \@if@pti@ns .....  
50:224, 50:227, 50:229, 50:246, 50:247
- \@if@ptions .....  
50:221, 50:222, 50:223, 50:971, 50:1066
- \@if@short@command ..... 1323
- \@ifatmargin ..... 41:55, 41:106
- \@ifbothcounters ..... 22:110,  
22:124, 22:132, 22:147, 22:162,  
22:164, 22:185, 22:197, 22:210, 22:212
- \@ifclasslater . 50:163, 50:171, 50:179
- \@ifclassloaded 50:155, 50:268, 50:277
- \@ifclasswith .. 50:221, 50:270, 50:279
- \@ifdefinable ..... 21:32, 21:35,  
22:11, 23:3, 29:701, 06:102, 06:104,  
06:171, 06:173, 06:295, 06:316,  
06:342, 40:154, 43:7, 43:15, 43:22, 1323
- \@iffileonpath .....  
20:506, 20:560, 20:582, 20:599, 20:620
- \@ifl@aded ..... 50:155, 50:156,  
50:157, 50:917, 50:1047, 50:1065, 1078
- \@ifl@t@r .....  
.. 21:1562, 05:205, 05:213, 50:169,  
50:172, 50:177, 50:180, 50:184,  
50:188, 50:190, 50:201, 50:202, 50:766
- \@ifl@ter ..... 21:1607, 21:1608,  
50:163, 50:164, 50:183, 50:959, 50:1094
- \@ifl@ter@@ ..... 21:1607, 21:1608
- \@ifnch .....  
.. 05:53, 05:54, 06:874, 06:876, 06:888
- \@ifnextchar ..... 18:94, 18:558,  
20:652, 22:13, 26:428, 05:49, 37:431,  
38:413, 39:174, 40:9, 40:11, 40:18,  
40:20, 40:26, 40:68, 40:160, 40:161,  
40:167, 40:168, 40:175, 40:179,  
40:224, 40:225, 40:231, 40:232,  
40:237, 40:295, 40:303, 40:311,  
40:318, 40:322, 40:425, 40:429,  
40:433, 40:534, 40:539, 40:562,  
40:569, 40:574, 41:57, 41:181,  
41:203, 41:210, 42:23, 42:132,  
42:143, 42:453, 43:3, 43:5, 43:32,  
43:38, 45:27, 45:264, 45:324, 45:452,  
45:519, 45:536, 47:3, 47:17, 47:29,  
50:356, 50:370, 50:761, 50:793,  
50:801, 50:808, 50:1220, 50:1223,  
50:1355, 50:1358, 06:870, 06:875,  
06:889, 54:214, 54:2584, 01:82, 1351
- \@iforloop ..... 13:21, 13:22
- \@ifpackagelater .....  
..... 50:163, 50:170, 50:178, 1053
- \@ifpackageloaded .....  
50:155, 50:267, 50:276, 54:2568, 1053
- \@ifpackagewith .....  
..... 50:221, 50:269, 50:278, 1053

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

\@ifframebox . . . . . 40:238, 40:239, 40:240  
 \@ifframepicbox . . . . . 40:295, 40:296  
 \@ifstar 18:60, 18:72, 18:377, 18:512,  
     22:160, 22:208, 24:269, 27:121,  
     06:78, 06:87, 37:420, 37:427, 37:727,  
     37:736, 38:483, 41:56, 41:202,  
     41:209, 42:142, 42:604, 44:52,  
     44:142, 50:498, 50:540, 06:889, 54:2432  
 \@ifundefin@d@i . . . . .  
     . . . . . 06:832, 06:833, 06:850, 06:853  
 \@ifundefin@d@ii 06:832, 06:835, 06:838  
 \@ifundefined . . . . . 22:3,  
     22:7, 22:18, 22:99, 22:113, 22:115,  
     24:101, 24:200, 24:249, 26:441,  
     28:544, 05:136, 33:827, 06:168,  
     35:85, 06:175, 06:195, 06:202,  
     06:224, 06:235, 37:218, 37:235,  
     37:251, 37:272, 37:290, 37:300,  
     06:381, 06:387, 06:420, 06:426,  
     06:448, 06:454, 06:484, 06:501,  
     43:21, 06:582, 06:622, 06:623, 47:40,  
     47:68, 47:85, 49:3, 49:7, 50:128,  
     50:153, 50:451, 50:457, 50:474,  
     50:486, 50:564, 50:598, 50:617,  
     50:919, 06:827, 52:484, 07:3327, 1322  
 \@ignore... . . . . . 1344  
 \@ignorefalse 24:433, 37:4, 37:257,  
     37:277, 37:295, 37:305, 37:341,  
     37:358, 37:374, 37:383, 45:384, 1307  
 \@ignoretrue . . . . . 18:201, 18:214,  
     24:428, 37:4, 37:7, 38:392, 38:400,  
     38:407, 38:446, 38:475, 38:637, 1343  
 \@iiminipage . . . . .  
     40:427, 40:431, 40:434, 40:435, 40:436  
 \@iiparbox . . . . . 40:305, 40:313,  
     40:320, 40:323, 40:324, 40:325, 40:472  
 \@iiminipage . . . . . 40:430, 40:432  
 \@iinput . . . . . 20:652, 20:653, 473  
 \@iiparbox . . . . . 40:319, 40:321  
 \@iirsbox . . . . . 40:574, 40:583  
 \@imakebox . . . . . 40:26, 40:41, 40:177  
 \@imakepicbox . . . . .  
     . . . . . 40:68, 40:69, 40:182, 40:297  
 \@iminipage . . . . . 40:426, 40:428  
 \@in@minipage@envtrue . . . . . 40:451  
 \@include . . . . .  
     . . . . . 20:247, 20:290, 20:306, 20:310, 462  
 \@includeinreleasefalse . . . . .  
     . . . . . 03:74, 03:79, 03:133, 03:141, 06:965  
 \@includeinreleasetrue . . . . . 03:123  
 \@index . . . . . 46:18, 46:19, 46:35  
 \@indexfile . . . . . 46:4, 46:5, 46:14  
 \@inlabelfalse . . . . . 39:28, 39:104,  
     39:215, 54:142, 54:169, 54:195, 1315  
 \@inlabeltrue . . . . . 39:28, 39:209  
 \@inmatherr . . . . .  
     . . . . . 14:285, 39:112, 39:173, 42:604, 1325  
 \@inmathwarn . . . . . 21:3  
 \@inpenc@test . . . . . 57:356, 57:423  
 \@input . . . . . 20:34,  
     20:104, 20:162, 20:318, 20:380,  
     20:427, 20:691, 44:152, 57:746, 1115  
 \@input@ . . . . .  
     . . . . . 20:338, 20:365, 20:398, 20:417,  
     20:442, 20:693, 24:490, 47:51, 1314  
 \@input@file@exists@with@hooks . . . . .  
     . . . . . 52:143, 1366  
 \@inputcheck . . . . . 20:501, 20:502,  
     20:509, 20:555, 20:556, 20:563,  
     20:577, 20:578, 20:585, 20:607,  
     20:608, 20:611, 20:624, 20:625,  
     20:628, 01:175, 01:176, 01:179,  
     01:187, 05:42, 05:43, 05:46, 06:38,  
     06:45, 50:1263, 50:1264, 50:1298,  
     50:1394, 50:1395, 50:1431, 50:1506,  
     50:1507, 50:1514, 02:177, 01:54, 1307  
 \@insertfalse . . . . .  
     54:1423, 54:1574, 54:1718, 54:1889,  
     54:1971, 54:2051, 54:2146, 54:2267  
 \@inserttrue . . . . .  
     . . . . . 54:1349, 54:1394, 54:1512,  
     54:1661, 54:1824, 54:2225, 54:2352  
 \@invalidchar . . . . . 14:290  
 \@iparbox . . . . . 40:304, 40:312, 40:317  
 \@irsbox 40:562, 40:569, 40:574, 40:575  
 \@isavebox . . . . . 40:175, 40:176  
 \@isavepicbox . . . . . 40:180, 40:181  
 \@ishortstack . . . . . 42:133, 42:141  
 \@istackcr . . . . . 42:143, 42:144  
 \@itabcr . . . . . 41:57, 41:58  
 \@item . . . . . 39:174, 39:187  
 \@itemdepth . . . . .  
     . . . . . 39:272, 39:274, 39:275, 39:276, 886  
 \@itemfudge . . . . . 41:38, 41:44, 41:82  
 \@itemitem . . . . . 39:276, 39:279  
 \@itemlabel . . . . . 39:44, 39:96, 39:174, 1312  
 \@itempenalty 18:17, 39:23, 39:206, 873  
 \@itemspacing . . . . . 886  
 \@iwhiledim . . . . . 13:7  
 \@iwhilenum . . . . . 13:3  
 \@iwhilesw . . . . . 13:10  
 \@ixpt . . . . . 24:816  
 \@ixstackcr . . . . . 42:142  
 \@kernel@... . . . . 1056  
 \@kernel@Ref . . . . . 35:159, 35:164  
 \@kernel@after@hook . . . . . 222  
 \@kernel@after@begindocument . . . . .  
     09:78, 20:58, 20:76, 05:7, 51:267, 1368

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

\@kernel@after@begindocument@before	\@kernel@sref . 35:13, 35:25, 35:30,
..... 20:16, 20:76, 25:3251, 458	35:42, 35:47, 35:59, 35:64, 35:67, 35:161
\@kernel@after@enddocument	\@killglue .. 42:59, 42:73, 42:103, 42:115, 42:123
..... 05:1, 37:15, 37:83, 53:352	\@kludgeins . 54:324, 54:325, 54:326,
\@kernel@after@enddocument@afterlastpage	54:328, 54:381, 54:382, 54:428,
... 05:1, 37:20, 37:87, 53:363, 08:455	54:429, 54:499, 54:521, 54:522,
\@kernel@after@para@after	54:523, 54:527, 54:542, 54:546,
..... 16:8, 16:106, 417	54:556, 54:756, 54:778, 54:787,
\@kernel@after@para@end	54:794, 54:821, 54:822, 54:2428, 54:2459
..... 16:8, 16:99, 416	\@labels ..... 39:27, 39:177,
\@kernel@after@shipout@background	39:178, 39:220, 39:237, 39:238, 872
..... 53:72, 53:160, 1367	\@largefloatcheck ..... 45:192, 45:213, 45:238, 45:256, 1321
\@kernel@after@shipout@lastpage	\@lastchclass .... 41:262, 41:272,
..... 53:114,	41:273, 41:275, 41:283, 41:308,
53:119, 53:160, 53:383, 53:389, 1161	41:322, 41:326, 41:335, 41:348, 41:349
\@kernel@before@hook) ..... 222	\@latex@error ... 03:100, 08:2966,
\@kernel@before@begindocument	03:159, 03:184, 03:195, 14:163,
..... 20:56, 20:76, 05:7, 53:413, 1368	14:217, 14:233, 14:239, 14:241,
\@kernel@before@enddocument	14:244, 14:246, 14:248, 14:252,
..... 37:13, 37:81, 37:182, 833	14:254, 14:256, 14:259, 14:263,
\@kernel@before@enddocument@afterlastpage	14:268, 14:272, 14:274, 14:276,
..... 05:1, 37:18, 53:358, 1384	14:278, 14:279, 14:281, 14:284,
\@kernel@before@insertmark	14:288, 14:290, 17:16, 20:243,
..... 48:251, 48:278, 1034	20:287, 20:305, 21:68, 21:102, 24:6,
\@kernel@before@para@before	24:29, 24:59, 24:103, 24:145, 24:250,
..... 16:8, 16:21, 16:54, 416	24:316, 24:402, 26:106, 27:100,
\@kernel@before@para@begin	27:111, 28:24, 28:69, 28:98, 28:118,
..... 16:8, 16:30, 16:62, 416	28:171, 28:202, 28:232, 28:264,
\@kernel@before@shipout@background	28:384, 28:400, 28:434, 28:450,
..... 53:68, 53:70, 53:160, 1149	28:550, 28:571, 28:623, 28:673,
\@kernel@currentdata ..... 35:171	28:677, 28:719, 28:724, 28:779,
\@kernel@currpathstack	28:847, 28:853, 05:84, 28:897,
..... 50:45, 50:47, 50:91, 50:123, 1368	28:901, 28:905, 28:940, 28:944,
\@kernel@eqno .. 38:536, 38:538, 38:544	28:948, 28:1005, 28:1015, 28:1100,
\@kernel@leqno . 38:537, 38:539, 38:545	28:1105, 28:1108, 28:1140, 28:1143,
\@kernel@make@file@csname	28:1216, 28:1219, 28:1222, 28:1289,
..... 52:287, 52:290,	28:1295, 29:50, 29:61, 29:83, 29:94,
52:310, 52:313, 52:331, 52:334, 52:363	29:683, 29:848, 32:143, 06:169,
\@kernel@new@label@record@testdef	06:196, 37:252, 37:273, 37:291,
..... 36:149, 36:280, 37:26	37:301, 37:657, 37:674, 37:688,
\@kernel@pageref ..... 35:65, 35:69	37:703, 37:715, 38:515, 39:250,
\@kernel@pageref@exp ..... 35:70	06:382, 06:421, 06:449, 41:100,
\@kernel@ref .... 35:64, 35:67, 35:159	41:109, 44:31, 06:573, 45:6, 45:83,
\@kernel@ref@exp ..... 35:72	06:614, 47:71, 47:88, 50:688, 50:739,
\@kernel@refstepcounter	50:752, 50:773, 50:789, 50:972,
..... 35:136, 35:153, 43:31, 1378	50:1020, 50:1067, 50:1179, 50:1196,
\@kernel@rename@newcommand	50:1204, 50:1209, 50:1231, 50:1288,
..... 06:389, 06:406,	50:1366, 50:1421, 50:1765, 50:1795,
06:443, 06:471, 06:476, 06:489, 94	54:239, 54:395, 54:2450, 54:2467
\@kernel@reserved@label@data	\@latex@info ..... 14:163,
..... 35:100, 35:107	14:208, 33:40, 06:277, 06:402,
\@kernel@sRef ..... 35:161, 35:164	06:440, 06:468, 06:927, 52:487, 406
\@kernel@spageref	
..... 35:26, 35:43, 35:60, 35:65, 35:69	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\@latex@info@no@line</code> .. <a href="#">14:163</a> , <a href="#">14:209</a> , <a href="#">53:89</a> , <a href="#">54:827</a> , <a href="#">1325</a>	<code>\@listfiles</code> .. <a href="#">20:62</a> , <a href="#">20:131</a> , <a href="#">20:186</a> , <a href="#">20:772</a> , <a href="#">20:791</a>
<code>\@latex@note</code> .. <a href="#">14:190</a> , <a href="#">24:34</a>	<code>\@listi</code> .. <a href="#">873</a>
<code>\@latex@note@no@line</code> .. <a href="#">14:190</a> , <a href="#">50:1245</a> , <a href="#">50:1265</a> , <a href="#">50:1271</a> , <a href="#">1369</a>	<code>\@listii</code> .. <a href="#">873</a>
<code>\@latex@warning</code> .. <a href="#">14:163</a> , <a href="#">14:215</a> , <a href="#">20:363</a> , <a href="#">20:415</a> , <a href="#">21:73</a> , <a href="#">22:55</a> , <a href="#">22:73</a> , <a href="#">35:18</a> , <a href="#">35:35</a> , <a href="#">35:52</a> , <a href="#">36:211</a> , <a href="#">36:222</a> , <a href="#">36:228</a> , <a href="#">40:51</a> , <a href="#">40:252</a> , <a href="#">40:347</a> , <a href="#">40:447</a> , <a href="#">42:449</a> , <a href="#">45:260</a> , <a href="#">47:42</a> , <a href="#">47:69</a> , <a href="#">47:86</a> , <a href="#">50:1327</a> , <a href="#">50:1334</a> , <a href="#">50:1460</a> , <a href="#">50:1466</a> , <a href="#">50:1549</a> , <a href="#">50:1555</a> , <a href="#">53:174</a> , <a href="#">54:2616</a>	<code>\@listvi</code> .. <a href="#">873</a>
<code>\@latex@warning@no@line</code> .. <a href="#">14:163</a> , <a href="#">14:216</a> , <a href="#">20:19</a> , <a href="#">20:89</a> , <a href="#">20:146</a> , <a href="#">20:758</a> , <a href="#">05:102</a> , <a href="#">35:8</a> , <a href="#">35:88</a> , <a href="#">35:89</a> , <a href="#">36:133</a> , <a href="#">36:134</a> , <a href="#">37:64</a> , <a href="#">37:71</a> , <a href="#">37:129</a> , <a href="#">37:136</a> , <a href="#">37:168</a> , <a href="#">06:243</a> , <a href="#">44:32</a> , <a href="#">50:352</a> , <a href="#">50:366</a> , <a href="#">50:767</a> , <a href="#">50:960</a> , <a href="#">50:1095</a> , <a href="#">50:1247</a> , <a href="#">50:1396</a> , <a href="#">50:1402</a> , <a href="#">50:1425</a> , <a href="#">50:1508</a> , <a href="#">50:1515</a> , <a href="#">50:1582</a> , <a href="#">50:1666</a> , <a href="#">53:79</a> , <a href="#">53:98</a> , <a href="#">53:374</a> , <a href="#">54:248</a> , <a href="#">54:280</a> , <a href="#">54:2403</a> , <a href="#">54:2682</a>	<code>\@lmbk</code> .. <a href="#">1345</a>
<code>\@latexbug</code> .... <a href="#">14:277</a> , <a href="#">54:338</a> , <a href="#">54:2389</a>	<code>\@loadwithoptions</code> .. <a href="#">50:694</a> , <a href="#">50:716</a> , <a href="#">50:726</a> , <a href="#">50:735</a>
<code>\@latexerr</code> .. <a href="#">14:215</a> , <a href="#">54:442</a> , <a href="#">1322</a>	<code>\@lowpenalty</code> .. <a href="#">18:118</a> , <a href="#">57:3</a>
<code>\@latexinfo</code> .. <a href="#">1320</a>	<code>\@ltab</code> .. <a href="#">41:71</a> , <a href="#">41:106</a>
<code>\@latexrelease@catcode@null</code> .. <a href="#">07:6</a> , <a href="#">07:3328</a>	<code>\@ltxnmath</code> .. <a href="#">1320</a>
<code>\@lbbitem</code> .. <a href="#">47:3</a> , <a href="#">47:4</a>	<code>\@m</code> .. <a href="#">18:303</a> , <a href="#">18:336</a> , <a href="#">18:504</a> , <a href="#">18:509</a> , <a href="#">20:45</a> , <a href="#">20:115</a> , <a href="#">20:173</a> , <a href="#">39:80</a> , <a href="#">42:213</a> , <a href="#">42:217</a> , <a href="#">47:37</a> , <a href="#">02:21</a> , <a href="#">02:304</a> , <a href="#">02:306</a> , <a href="#">02:307</a> , <a href="#">02:373</a> , <a href="#">02:374</a> , <a href="#">394</a>
<code>\@ldots</code> .. <a href="#">30:515</a> , <a href="#">30:517</a>	<code>\@mainaux</code> .. <a href="#">20:3</a> , <a href="#">20:37</a> , <a href="#">20:38</a> , <a href="#">20:107</a> , <a href="#">20:108</a> , <a href="#">20:165</a> , <a href="#">20:166</a> , <a href="#">20:236</a> , <a href="#">20:318</a> , <a href="#">20:361</a> , <a href="#">20:380</a> , <a href="#">20:413</a> , <a href="#">20:427</a> , <a href="#">20:452</a> , <a href="#">37:23</a> , <a href="#">37:90</a> , <a href="#">37:152</a> , <a href="#">1331</a>
<code>\@leftcolumn</code> .. <a href="#">54:99</a> , <a href="#">54:2878</a> , <a href="#">54:2884</a> , <a href="#">54:2907</a> , <a href="#">54:2927</a> , <a href="#">54:2948</a> , <a href="#">54:2957</a>	<code>\@make@normalcolbox</code> .. <a href="#">54:502</a> , <a href="#">54:508</a> , <a href="#">54:797</a>
<code>\@leftmark</code> .. <a href="#">49:16</a> , <a href="#">49:119</a>	<code>\@make@specialcolbox</code> .. <a href="#">54:500</a> , <a href="#">54:517</a> , <a href="#">54:798</a>
<code>\@let@token</code> .. <a href="#">18:457</a> , <a href="#">18:458</a> , <a href="#">18:465</a> , <a href="#">05:53</a> , <a href="#">05:55</a> , <a href="#">32:83</a> , <a href="#">32:96</a> , <a href="#">38:256</a> , <a href="#">38:258</a> , <a href="#">38:261</a> , <a href="#">06:874</a> , <a href="#">06:877</a> , <a href="#">06:880</a> , <a href="#">06:888</a> , <a href="#">1321</a>	<code>\@makebox</code> .. <a href="#">40:11</a> , <a href="#">40:20</a> , <a href="#">40:25</a>
<code>\@lign</code> .. <a href="#">38:208</a> , <a href="#">38:210</a>	<code>\@makecaption</code> .. <a href="#">45:24</a> , <a href="#">1273</a>
<code>\@linechar</code> .. <a href="#">42:190</a> , <a href="#">42:191</a> , <a href="#">42:192</a> , <a href="#">42:196</a> , <a href="#">42:197</a> , <a href="#">42:199</a> , <a href="#">42:204</a> , <a href="#">42:206</a> , <a href="#">42:207</a> , <a href="#">42:208</a> , <a href="#">42:209</a> , <a href="#">42:211</a> , <a href="#">42:215</a> , <a href="#">42:216</a> , <a href="#">42:219</a> , <a href="#">42:220</a> , <a href="#">42:225</a> , <a href="#">42:272</a> , <a href="#">42:669</a> , <a href="#">1351</a>	<code>\@makecol</code> ... <a href="#">54:266</a> , <a href="#">54:418</a> , <a href="#">54:465</a> , <a href="#">54:489</a> , <a href="#">54:490</a> , <a href="#">54:735</a> , <a href="#">54:737</a> , <a href="#">1187</a>
<code>\@linefnt</code> ... <a href="#">42:124</a> , <a href="#">42:127</a> , <a href="#">42:190</a> , <a href="#">42:265</a> , <a href="#">42:273</a> , <a href="#">42:304</a> , <a href="#">42:307</a> , <a href="#">42:676</a>	<code>\@makecol@handlesplitfootnotes</code> .. <a href="#">54:613</a> , <a href="#">54:628</a>
<code>\@linelen</code> ... <a href="#">42:164</a> , <a href="#">42:165</a> , <a href="#">42:176</a> , <a href="#">42:177</a> , <a href="#">42:203</a> , <a href="#">42:210</a> , <a href="#">42:219</a> , <a href="#">42:221</a> , <a href="#">42:226</a> , <a href="#">42:227</a> , <a href="#">42:228</a> , <a href="#">42:241</a> , <a href="#">42:242</a> , <a href="#">42:256</a> , <a href="#">42:257</a> , <a href="#">42:300</a> , <a href="#">42:303</a> , <a href="#">42:305</a> , <a href="#">42:306</a> , <a href="#">42:670</a>	<code>\@makefcolumn</code> .. <a href="#">54:398</a> , <a href="#">54:399</a> , <a href="#">54:407</a> , <a href="#">54:409</a> , <a href="#">54:445</a> , <a href="#">54:447</a> , <a href="#">54:455</a> , <a href="#">54:457</a> , <a href="#">54:2836</a> , <a href="#">54:2838</a> , <a href="#">54:2854</a> , <a href="#">54:2855</a>
<code>\@list</code> .. <a href="#">873</a>	<code>\@makefmark</code> .. <a href="#">45:400</a> , <a href="#">45:532</a>
<code>\@listctr</code> .. <a href="#">39:233</a> , <a href="#">39:256</a> , <a href="#">47:9</a> , <a href="#">872</a>	<code>\@makefntext</code> .. <a href="#">40:489</a> , <a href="#">40:506</a> , <a href="#">40:523</a> , <a href="#">45:476</a> , <a href="#">45:494</a> , <a href="#">45:512</a>
<code>\@listdepth</code> .. <a href="#">39:23</a> , <a href="#">39:35</a> , <a href="#">39:38</a> , <a href="#">39:43</a> , <a href="#">39:99</a> , <a href="#">40:456</a> , <a href="#">872</a>	<code>\@makeother</code> .. <a href="#">01:110</a> , <a href="#">24:503</a> , <a href="#">24:504</a> , <a href="#">24:505</a> , <a href="#">24:506</a> , <a href="#">24:507</a> , <a href="#">24:508</a> , <a href="#">24:509</a> , <a href="#">24:510</a> , <a href="#">24:511</a> , <a href="#">24:512</a> , <a href="#">24:513</a> , <a href="#">37:543</a> , <a href="#">37:564</a> , <a href="#">37:709</a> , <a href="#">37:724</a> , <a href="#">37:734</a> , <a href="#">50:438</a> , <a href="#">50:439</a> , <a href="#">50:1309</a> , <a href="#">50:1442</a> , <a href="#">50:1531</a> , <a href="#">06:892</a> , <a href="#">06:893</a> , <a href="#">54:863</a> , <a href="#">54:864</a> , <a href="#">54:865</a> , <a href="#">54:866</a> , <a href="#">54:867</a> , <a href="#">54:868</a> , <a href="#">54:869</a> , <a href="#">54:870</a> , <a href="#">54:871</a> , <a href="#">54:872</a> , <a href="#">54:873</a> , <a href="#">01:60</a> , <a href="#">01:81</a>

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- 54:2401, 54:2409, 54:2411, 54:2412,  
54:2414, 54:2415, 54:2416, 54:2425  
`\marginparreset` 45:343, 45:361, [45:370](#)  
`\markright` . 49:52, 49:75, 49:98, [49:121](#)  
`\math@level` . . . . . 24:404,  
24:422, 24:429, 24:434, 28:288, 551  
`\maxdepth` . . . . . 20:60,  
20:129, 20:184, 54:67, 54:504,  
54:603, 54:742, 54:767, 57:152, 1317  
`\maxtab` . . . . . [41:2](#), 41:94, [1321](#)  
`\medpenalty` . . . . . 18:119, [57:3](#)  
`\meta@family@list` . . . . .  
. . . . . 29:117, 29:162, 29:175,  
29:236, 29:246, 29:289, 29:585, 708  
`\midlist` . . . . .  
. . . . . 54:42, 54:496, 54:497, 54:753,  
54:754, 54:1377, 54:1379, 54:1492,  
54:1641, 54:1800, 54:2532, 54:2560  
`\minipage...` . . . . . 1343  
`\minipagefalse` . . . . .  
. . . . . 39:212, 40:420, 40:422,  
40:469, 45:187, 45:250, 45:345, 45:363  
`\minipagerestore` . . . . 40:457, [40:459](#)  
`\minipagetrue` . . . . . 40:421, 45:186  
`\minus` . . . . . [06:26](#), 54:3006,  
54:3007, 54:3008, 54:3011, 54:3012  
`\missing@onefilewithoptions` . . .  
. . . . . 50:934, [50:990](#), 50:1108  
`\missingfile@area` . . . . .  
. . . . . 20:665, 20:706, 20:719, 50:992  
`\missingfile@base` . . . . .  
. . . . . 20:665, 20:707, 20:720, 50:993  
`\missingfile@ext` . . . . .  
. . . . . 20:665, 20:708, 20:721, 50:994  
`\missingfileerror` 20:660, 20:675,  
20:685, [20:694](#), 50:991, 50:1088, 1330  
`\mkboth` . . . . . 49:11, 49:13  
`\mklab` . . . . . 39:45, [39:171](#)  
`\mkpream` . 41:189, 41:234, [41:262](#), 1344  
`\mparbottom` . . . . . 45:387,  
45:388, 54:96, 54:483, 54:2399,  
54:2407, 54:2408, 54:2409, 54:2410  
`\mpargs` . . . . . 40:440, 40:472  
`\mparswitchfalse` . . . . . 54:80  
`\mpfn` . . . . .  
. . . . . 40:454, 45:452, 45:457, 45:541, [45:545](#)  
`\mpfootins` . . . . . 40:446, 40:463,  
40:464, 40:467, [40:473](#), 40:480,  
40:481, 40:498, 40:499, 40:515, 40:516  
`\mpfootnotetext` . . . . 40:455, [40:475](#)  
`\mplistdepth` . . . . . 40:456, [40:473](#)  
`\multicnt` . . . . . 41:370,  
41:372, 41:373, 41:374, 41:381,  
41:382, 41:383, 42:103, 42:104,  
42:106, 42:115, 42:116, 42:118,  
[42:666](#), 42:703, 42:705, 42:706,  
42:707, 42:709, 42:710, 42:716,  
42:722, 42:733, 42:737, 42:763,  
42:765, 42:767, 42:769, 42:770,  
42:774, 42:778, 42:789, 42:793, 1340  
`\multiplelabels` . . . 20:33, 20:103,  
20:161, 35:87, [35:93](#), 36:132, 37:62,  
37:68, 37:127, 37:133, 37:166, 37:172  
`\multiput` . . . . . 42:86, 42:95, [42:98](#)  
`\multispan` . . . . 41:371, 41:375, [41:379](#)  
`\mypkg@name` . . . . . 1105  
`\mypkg@other@name` . . . . . 1105  
`\namedef` . . . . . 20:465,  
24:136, 24:137, 24:161, 24:203, 25:6,  
25:1436, 25:2913, 26:435, 28:473,  
28:477, 28:486, 33:57, [06:50](#), 33:830,  
35:90, 37:289, 37:349, 37:366,  
37:380, 37:586, 37:595, 38:519,  
38:520, 41:175, 43:12, 43:13, 43:18,  
43:19, 43:23, 43:24, 43:25, 50:1222,  
50:1357, 52:482, 57:480, 57:481, 1309  
`\nameuse` . . . 20:355, 20:411, 20:450,  
20:464, [06:51](#), 43:23, 49:5, 50:928,  
52:486, 54:887, 54:961, 54:1019, 1325  
`\nbitem` . . . . . 39:199, [39:252](#)  
`\one` . . . . . [02:16](#), 394  
`\needsf@rmat` . . 50:762, 50:765, 50:770  
`\needsformat` . . 50:750, 50:760, 50:764  
`\negargfalse` . . . . . 42:186  
`\negargtrue` . . . . . 42:185  
`\newcommand` . . . . . [06:97](#), [06:98](#)  
`\newctr` . . . . . 22:13, [22:17](#), 43:8  
`\newenv` . . . . . [06:191](#), [06:192](#), [06:201](#)  
`\newenva` . . . . . [06:190](#), 06:189  
`\newenvb` . . . . . [06:192](#), 06:191  
`\newfontswitch` . . . . . 1319  
`\newl@bel` . . . . .  
. . . . . 35:84, 37:25, 37:92, 37:154, 47:10, 1337  
`\newline` . . . . . 18:95, [18:97](#)  
`\newlistfalse` . . . . 39:29, [39:33](#),  
39:108, 39:213, 54:877, 54:954, 54:1012  
`\newlisttrue` . . . . 39:29, [39:33](#), 39:87  
`\next` . . . . . 45:60, 45:129,  
45:319, 45:320, 54:5, 54:218, 54:316,  
54:1227, 54:1247, 54:2388, 02:161  
`\nextchar` . . . . .  
. . . . . 41:269, 41:270, 41:330, 41:331, 41:332  
`\nil` . . . . .  
. . . . . 03:13, 03:19, 03:83, 03:104, 03:105,  
03:117, 03:118, 03:165, 03:166,  
03:167, 13:13, 13:19, 13:27, 19:14,  
20:266, 20:267, 20:268, 01:145,  
01:146, 21:107, 21:128, 21:1020,

File Key: 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

- 21:1024, 21:1087, 21:1099, 21:1101,  
24:455, 24:466, 24:582, 24:597,  
24:701, 24:704, 24:705, 24:713,  
25:2819, 25:2821, 25:2853, 25:2855,  
25:3165, 25:3167, 25:3191, 25:3193,  
26:367, 26:368, 26:370, 26:383,  
26:389, 26:393, 26:394, 26:430,  
26:451, 26:456, 26:536, 26:550,  
27:26, 27:44, 27:53, 27:57, 28:41,  
28:643, 28:651, 28:684, 28:1300,  
28:1302, 32:58, 32:62, 06:53, 06:54,  
06:58, 06:63, 06:166, 06:176, 06:222,  
41:367, 41:368, 06:543, 06:544,  
06:725, 50:90, 50:91, 50:97, 50:105,  
50:108, 50:115, 50:140, 50:191,  
50:192, 50:203, 50:204, 50:214,  
50:215, 50:217, 50:447, 50:470,  
50:514, 50:520, 50:636, 50:656,  
50:660, 50:666, 50:670, 50:885,  
50:894, 50:911, 50:912, 06:868,  
06:869, 50:1639, 50:1644, 50:1647,  
50:1649, 50:1650, 50:1665, 50:1685,  
50:1702, 50:1757, 50:1779, 50:1803,  
52:168, 52:176, 52:369, 52:411, 52:413  
`\@nmbrlistfalse` 39:33, 39:46, 39:91, 1307  
`\@nmbrlisttrue` ..... 39:256  
`\@nnil` ..... 13:13, 13:20,  
13:21, 13:22, 13:28, 20:267, 20:268,  
24:277, 24:281, 24:282, 24:283,  
24:298, 26:180, 26:182, 26:362,  
26:364, 26:376, 26:378, 26:383,  
26:397, 26:399, 26:406, 26:417,  
26:418, 26:420, 26:451, 26:456,  
42:13, 06:521, 06:527, 50:830,  
50:831, 50:838, 50:858, 50:859, 50:866  
`\@no@font@optfalse` .... 27:17, 27:129  
`\@no@lnbk` ..... 18:9, 18:10, 18:41, 1345  
`\@no@pgbk` ..... 18:7, 18:8, 18:33, 1338  
`\@nobreak...` ..... 1344  
`\@nobreakfalse` ..... 18:121,  
18:123, 39:224, 44:94, 44:129,  
44:157, 45:182, 54:144, 54:171,  
54:197, 54:1501, 54:1650, 54:1811, 1344  
`\@nobreaktrue` .. 18:122, 44:126, 45:181  
`\@nocnterr` ..... 14:240, 1318  
`\@nocounterr` ..... 14:240, 22:4,  
22:8, 22:18, 22:113, 22:115, 43:21, 1319  
`\@nodocument` ..... 14:245, 16:143,  
20:68, 20:137, 20:192, 20:315,  
20:377, 37:243, 45:39, 45:108,  
54:135, 54:162, 54:188, 54:217, 1345  
`\@noitemargfalse` ..... 39:32, 39:231  
`\@noitemargtrue` ..... 39:32, 39:174  
`\@noitemerr` .....  
... 14:280, 18:264, 18:281, 18:351,  
18:373, 39:69, 39:81, 39:107, 1380  
`\@noitemerror` ..... 1331  
`\@noligs` ..... 37:544,  
37:565, 37:725, 37:735, 37:746, 1343  
`\@nolnbnk` ..... 1345  
`\@nolnerr` ..... 14:238,  
18:43, 18:114, 37:419, 37:426, 1321  
`\@nomath` 24:3, 24:400, 29:634, 29:669,  
29:675, 29:696, 29:698, 29:720, 1305  
`\@noparitemfalse` ..... 39:30, 39:176  
`\@noparitemtrue` ..... 39:30, 39:66  
`\@noparlistfalse` ..... 39:31, 39:70  
`\@noparlisttrue` ..... 39:31, 39:67  
`\@nopgbk` ..... 1338  
`\@normalcr` .. 18:53, 18:93, 40:419, 1360  
`\@normalsize` ..... 50:4, 50:5, 1318  
`\@normalsizeucheck` ..... 1318  
`\@noskipsecfalse` ... 20:54, 20:124,  
20:179, 44:98, 54:137, 54:164, 54:190  
`\@noskipsectrue` ..... 44:38, 44:95  
`\@notdefinable` ..... 14:232,  
06:177, 06:178, 06:182, 06:570, 06:611  
`\@notprerr` 14:283, 20:66, 20:135, 20:190  
`\@nthm` ..... 43:3, 43:4  
`\@nxxtabmar` .....  
.. 41:11, 41:21, 41:23, 41:25, 41:75,  
41:111, 41:112, 41:118, 41:119, 1340  
`\@obsoletefile` ..... 20:757  
`\@oddfoot` ..... 49:11, 49:14,  
49:15, 54:102, 54:892, 54:964, 54:1023  
`\@oddhead` ..... 49:11,  
49:14, 54:101, 54:891, 54:964, 54:1023  
`\@onefilewithoptions` 50:822, 50:826,  
50:832, 50:850, 50:854, 50:860,  
50:877, 50:881, 50:887, 50:903,  
50:905, 50:988, 50:1055, 50:1608, 1077  
`\@onefilewithoptions@clashchk` ...  
..... 50:920, 50:970  
`\@onelevel@sanitize` .....  
..... 45:42, 45:111, 06:894, 1329  
`\@onfilewithoptions` ..... 1082  
`\@onlypreamble` .....  
.. 08:2847, 20:197, 20:206, 20:262,  
20:759, 20:819, 21:41, 21:42, 21:79,  
21:80, 21:84, 21:143, 21:163, 21:207,  
21:208, 21:224, 24:18, 24:116,  
24:118, 24:124, 24:140, 24:168,  
24:183, 24:266, 24:271, 24:313,  
24:609, 26:436, 27:28, 27:36, 27:42,  
27:79, 27:83, 27:88, 27:93, 27:98,  
27:108, 27:126, 27:127, 27:128,  
27:134, 27:138, 27:142, 28:18,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=ltthyphen.dtx, 57=ltfinal.dtx

- 28:20, 28:45, 28:47, 28:108, 28:117,  
28:137, 28:466, 28:467, 28:480,  
28:526, 28:574, 28:586, 28:588,  
28:601, 28:626, 28:683, 28:685,  
28:727, 28:766, 28:782, 28:859,  
28:953, 28:962, 28:1018, 28:1021,  
28:1024, 28:1044, 28:1057, 28:1111,  
28:1146, 28:1157, 28:1171, 28:1225,  
28:1245, 28:1249, 28:1313, 32:140,  
32:141, 06:66, 33:831, 35:92, 06:229,  
06:231, 06:240, 06:248, 46:12,  
46:29, 47:64, 47:81, 48:16, 48:400,  
50:10, 50:13, 50:85, 50:112, 50:120,  
50:122, 50:154, 50:357, 50:420,  
50:426, 50:491, 50:494, 50:495,  
50:506, 50:507, 50:508, 50:535,  
50:541, 50:554, 50:591, 50:609,  
50:629, 50:649, 50:673, 50:678,  
50:682, 50:685, 50:693, 50:714,  
50:717, 50:727, 50:746, 50:759,  
50:764, 50:770, 50:806, 50:811,  
50:899, 50:988, 50:1113, 50:1122,  
50:1130, 50:1131, 50:1149, 50:1177,  
50:1186, 50:1193, 50:1194, 50:1202,  
50:1207, 50:1212, 50:1588, 50:1589,  
50:1590, 50:1591, 50:1593, 51:231, 1369  
\@opargbegintheorem . . . . 43:45, 43:48  
\@opcol . . . . 54:267, 54:275, 54:399,  
54:418, 54:447, 54:465, 54:470, 1041  
\@options . . . . . 50:628  
\@othm . . . . . 43:3, 43:20  
\@outerparskip . . . . .  
. . . 39:1, 39:88, 39:117, 39:183, 39:253  
\@outputbox . . . . . 48:418,  
48:421, 48:425, 48:450, 48:453,  
48:457, 54:98, 54:492, 54:509,  
54:511, 54:512, 54:528, 54:531,  
54:536, 54:537, 54:544, 54:550,  
54:552, 54:564, 54:602, 54:604,  
54:605, 54:739, 54:741, 54:759,  
54:761, 54:762, 54:771, 54:773,  
54:774, 54:779, 54:781, 54:782,  
54:788, 54:790, 54:927, 54:990,  
54:1049, 54:1073, 54:1079, 54:1089,  
54:1090, 54:1113, 54:1120, 54:1206,  
54:1209, 54:1212, 54:1218, 54:1219,  
54:2878, 54:2882, 54:2888, 54:2907,  
54:2910, 54:2911, 54:2925, 54:2931,  
54:2948, 54:2954, 54:2963, 1200  
\@outputbox@append 54:525, 54:567,  
54:573, 54:601, 54:609, 54:615,  
54:638, 54:709, 54:713, 54:802, 1199  
\@outputbox@appendfil . . . . .  
. . . . . 54:609, 54:666, 54:668,  
54:677, 54:684, 54:690, 54:692, 1187  
\@outputbox@appendfootnotes . . . .  
. . . . . 54:611,  
54:671, 54:675, 54:686, 54:695,  
54:699, 54:703, 54:718, 54:803, 1187  
\@outputbox@attachbottomfloats . .  
. . . . . 54:629, 54:806, 1187  
\@outputbox@attachfloats . . . . .  
. . . . . 54:629, 54:672,  
54:679, 54:682, 54:694, 54:698,  
54:704, 54:719, 54:804, 54:1068, 1187  
\@outputbox@attachtopfloats . . . .  
. . . . . 54:629, 54:805, 1187  
\@outputbox@depth . 54:507, 54:511,  
54:513, 54:525, 54:590, 54:591,  
54:593, 54:596, 54:598, 54:604, 1199  
\@outputbox@reinsertbskip . . . . .  
. . . . . 54:565, 54:571,  
54:669, 54:678, 54:685, 54:693,  
54:700, 54:705, 54:717, 54:800, 1187  
\@outputbox@removebskip . . . . .  
. . . . . 54:493, 54:563, 54:799, 1204  
\@outputdblcol . . . . .  
. . . . . 54:474, 54:2873, 54:2875,  
54:2903, 54:2904, 54:2944, 54:2945  
\@outputpage 54:408, 54:457, 54:477,  
54:841, 54:2891, 54:2896, 54:2934,  
54:2938, 54:2970, 54:2978, 1212  
\@oval . . . . . 42:453, 42:470  
\@ovbtrue . . . . . 42:475, 42:503, 42:533  
\@ovdx 42:431, 42:486, 42:488, 42:494,  
42:496, 42:515, 42:517, 42:525,  
42:527, 42:542, 42:550, 42:552,  
42:588, 42:591, 42:598, 42:600,  
42:692, 42:693, 42:694, 42:695,  
42:711, 42:712, 42:713, 42:716,  
42:732, 42:752, 42:753, 42:754,  
42:755, 42:771, 42:772, 42:774, 42:788  
\@ovdy 42:431, 42:487, 42:489, 42:495,  
42:496, 42:516, 42:518, 42:526,  
42:527, 42:543, 42:551, 42:552,  
42:563, 42:568, 42:576, 42:580,  
42:699, 42:700, 42:701, 42:702,  
42:717, 42:718, 42:719, 42:722,  
42:736, 42:759, 42:760, 42:761,  
42:762, 42:775, 42:776, 42:778, 42:792  
\@ovhlinefalse . . . . . 42:476, 42:504  
\@ovhlinetrue . . . . 42:456, 42:460,  
42:464, 42:482, 42:488, 42:510, 42:517  
\@ovhorz . . . . . 42:493, 42:494,  
42:524, 42:525, 42:549, 42:550, 42:583  
\@ovltrue . . . . . 42:475, 42:503, 42:533  
\@ovvri 40:33, 42:431, 42:485, 42:514,  
42:541, 42:563, 42:576, 42:592, 42:601

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

`\@ovro` ..... [42:431](#), [42:485](#), [42:494](#),  
[42:495](#), [42:514](#), [42:525](#), [42:526](#),  
[42:541](#), [42:550](#), [42:551](#), [42:562](#),  
[42:568](#), [42:575](#), [42:580](#), [42:587](#),  
[42:597](#), [42:613](#), [42:620](#), [42:629](#), [42:638](#)  
`\@ovrtrue` ..... [42:475](#), [42:503](#), [42:533](#)  
`\@ovttrue` ..... [42:475](#), [42:503](#), [42:533](#)  
`\@ovvert` ..... [42:491](#), [42:492](#),  
[42:520](#), [42:522](#), [42:545](#), [42:547](#), [42:556](#)  
`\@ovvlinefalse` ..... [42:476](#), [42:504](#)  
`\@ovvlinetrue` .....  
[42:459](#), [42:481](#), [42:489](#), [42:509](#), [42:518](#)  
`\@ovxx` ..... [42:431](#), [42:479](#),  
[42:481](#), [42:482](#), [42:486](#), [42:492](#),  
[42:493](#), [42:507](#), [42:509](#), [42:510](#),  
[42:515](#), [42:522](#), [42:524](#), [42:536](#),  
[42:538](#), [42:542](#), [42:547](#), [42:549](#),  
[42:587](#), [42:597](#), [42:689](#), [42:690](#),  
[42:691](#), [42:695](#), [42:704](#), [42:705](#),  
[42:714](#), [42:715](#), [42:716](#), [42:731](#),  
[42:749](#), [42:750](#), [42:751](#), [42:755](#),  
[42:764](#), [42:765](#), [42:773](#), [42:774](#), [42:787](#)  
`\@ovyy` ..... [42:431](#),  
[42:480](#), [42:481](#), [42:482](#), [42:487](#),  
[42:494](#), [42:508](#), [42:509](#), [42:510](#),  
[42:516](#), [42:525](#), [42:537](#), [42:538](#),  
[42:543](#), [42:550](#), [42:560](#), [42:573](#),  
[42:696](#), [42:697](#), [42:698](#), [42:702](#),  
[42:704](#), [42:720](#), [42:721](#), [42:722](#),  
[42:735](#), [42:756](#), [42:757](#), [42:758](#),  
[42:762](#), [42:764](#), [42:777](#), [42:778](#), [42:791](#)  
`\@p@pfilename` ..... [50:90](#),  
[50:97](#), [50:105](#), [50:108](#), [50:115](#), [50:120](#)  
`\@p@pfilepath` ... [50:91](#), [50:138](#), [50:147](#)  
`\@p@pfilepath@aux` [50:139](#), [50:140](#), [50:148](#)  
`\@pagedp` ... [54:95](#), [54:313](#), [54:318](#),  
[54:1441](#), [54:1739](#), [54:2417](#), [54:2427](#)  
`\@pageht` [54:94](#), [54:314](#), [54:318](#), [54:320](#),  
[54:321](#), [54:322](#), [54:326](#), [54:1440](#),  
[54:1591](#), [54:1738](#), [54:2400](#), [54:2407](#)  
`\@par` ..... [15:3](#), [15:5](#)  
`\@parboxrestore` .....  
..... [40:334](#), [40:361](#), [40:419](#),  
[40:453](#), [40:484](#), [40:502](#), [40:519](#),  
[45:19](#), [45:100](#), [45:169](#), [45:342](#),  
[45:360](#), [45:470](#), [45:489](#), [45:507](#),  
[54:224](#), [54:878](#), [54:955](#), [54:1013](#), [1344](#)  
`\@parboxto` ..... [40:325](#), [1352](#)  
`\@parmoderr` [14:273](#), [45:58](#), [45:127](#), [45:316](#)  
`\@parse@version` ..... [03:83](#),  
[03:104](#), [03:105](#), [03:117](#), [03:118](#),  
[03:165](#), [03:166](#), [03:167](#), [50:197](#),  
[50:203](#), [50:204](#), [50:214](#), [50:1650](#),  
[50:1665](#), [50:1702](#), [50:1779](#), [50:1803](#)  
`\@parse@version@` .....  
..... [50:191](#), [50:192](#), [50:197](#), [50:209](#)  
`\@parse@version@dash` .....  
..... [50:215](#), [50:217](#), [1357](#)  
`\@partaux` ..... [20:3](#), [20:242](#),  
[20:286](#), [20:304](#), [20:328](#), [20:330](#),  
[20:331](#), [20:351](#), [20:390](#), [20:392](#),  
[20:393](#), [20:407](#), [20:437](#), [20:439](#),  
[20:440](#), [20:446](#), [20:458](#), [20:460](#), [20:463](#)  
`\@partlist` .....  
... [20:251](#), [20:255](#), [20:256](#), [20:258](#),  
[20:282](#), [20:301](#), [20:324](#), [20:386](#), [20:433](#)  
`\@partswfalse` ..... [20:6](#)  
`\@partswtrue` ... [20:250](#), [20:280](#), [20:300](#)  
`\@pass@options` .....  
... [50:443](#), [50:445](#), [50:465](#), [50:466](#),  
[50:468](#), [50:481](#), [50:482](#), [50:484](#),  
[50:491](#), [50:492](#), [50:493](#), [50:999](#), [50:1081](#)  
`\@pboxswfalse` .. [40:332](#), [40:359](#), [40:438](#)  
`\@pboxswtrue` ..... [40:342](#), [40:369](#)  
`\@pdef` ..... [1314](#)  
`\@penup` ..... [38:199](#), [38:200](#)  
`\@percentchar` ... [50:1301](#), [50:1303](#),  
[50:1305](#), [50:1307](#), [50:1434](#), [50:1436](#),  
[50:1438](#), [50:1440](#), [50:1523](#), [50:1525](#),  
[50:1527](#), [50:1529](#), [50:1577](#), [01:90](#)  
`\@pgbk` ..... [1338](#)  
`\@picbox` .....  
. [42:6](#), [42:31](#), [42:43](#), [42:51](#), [42:52](#), [1306](#)  
`\@picht` ..... [42:6](#), [42:29](#), [42:42](#), [42:51](#)  
`\@picture` ..... [42:23](#), [42:24](#)  
`\@picture@warn` .....  
..... [42:223](#), [42:441](#), [42:445](#), [42:449](#)  
`\@pkgetension` ..... [1314](#)  
`\@pkgextension` [50:31](#), [50:155](#), [50:163](#),  
[50:221](#), [50:492](#), [50:684](#), [50:687](#),  
[50:726](#), [50:735](#), [50:833](#), [50:861](#),  
[50:888](#), [50:1010](#), [50:1037](#), [50:1158](#),  
[50:1188](#), [50:1622](#), [52:482](#), [52:492](#), [1081](#)  
`\@plus` ..... [18:532](#),  
[06:26](#), [44:16](#), [44:231](#), [44:254](#),  
[49:127](#), [54:3006](#), [54:3007](#), [54:3008](#),  
[54:3011](#), [54:3012](#), [54:3016](#), [54:3017](#),  
[54:3018](#), [54:3022](#), [54:3023](#), [54:3024](#)  
`\@pnumwidth` ..... [44:243](#), [44:266](#)  
`\@popfilename` .....  
..... [50:33](#), [50:968](#), [50:1103](#), [1056](#)  
`\@pr@videpackage` .....  
..... [50:356](#), [50:370](#), [50:373](#),  
[50:394](#), [50:396](#), [50:407](#), [50:409](#), [50:420](#)  
`\@preamble` .....  
... [41:190](#), [41:192](#), [41:200](#), [41:237](#),  
[41:256](#), [41:258](#), [41:259](#), [41:263](#),  
[41:278](#), [41:296](#), [41:297](#), [41:334](#), [55:312](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=ltthyphen.dtx, 57=ltfinal.dtx

- \@preamblecmds . . . . . 20:67, 20:136,  
20:191, [06:66](#), 50:1817, 50:1818, [1314](#)
- \@preamerr [14:260](#), 41:199, 41:274, 41:355
- \@process@pti@ns . . . . .  
50:553, 50:571, 50:588,  
50:595, 50:596, 50:609, 50:613, 50:615
- \@process@ptions 50:540, 50:542, 50:554
- \@protect@... . . . . . [1325](#)
- \@protected@testopt . . . . .  
60:107, [06:119](#), 06:720, 06:732
- \@protecteddef . . . . . [1320](#)
- \@providesfile . . . . .  
50:430, [57:737](#), 01:82, 01:83
- \@optionlist . . . . .  
50:152, 50:224, 50:539, 50:976,  
50:982, 50:1071, 50:1077, 50:1189
- \@pushfilename . . . . .  
50:33, 50:913, 50:1058, [1057](#)
- \@put . . . . . [42:452](#),  
42:496, 42:527, 42:552, 42:620, 42:638
- \@qend . . . . . [14:236](#), 06:177, [06:868](#)
- \@qrelax . . . . . 06:178, [06:868](#)
- \@raw@classoptionslist . . . . .  
50:11, 50:820, 51:99, 51:141
- \@rc@ifdefinable . . . . . 21:32,  
06:171, [06:173](#), 06:295, 06:316, 06:342
- \@reargdef . . . . . [06:161](#), [1314](#)
- \@refundefined 20:55, 20:125, 20:180,  
[35:3](#), 37:60, 37:125, 37:164, [1340](#)
- \@reinserts . . . . . 54:332, 54:335, [54:819](#)
- \@remove@eq@value [50:509](#), 50:576, 50:636
- \@remove@tlig . . . . . 21:1020, 21:1028
- \@remove@tlig@ . . . . . 21:1020, 21:1021
- \@remove@tlig@@ . . . . . 21:1021, 21:1024
- \@remove@tlig@@@ . . . . . 21:1034, 21:1053
- \@remove@element . [13:32](#), 50:635, 50:644
- \@remove@fromreset . . 22:95, 22:122,  
22:123, 22:186, 22:198, 22:210, 22:213
- \@renewfontswitch . . . . . [1317](#)
- \@reqcolroom . . . . .  
54:1440, 54:1441, 54:1444,  
54:1446, 54:1447, 54:1452, 54:1453,  
54:1457, 54:1459, 54:1487, 54:1488,  
54:1591, 54:1594, 54:1596, 54:1597,  
54:1602, 54:1606, 54:1608, 54:1636,  
54:1637, 54:1738, 54:1739, 54:1743,  
54:1746, 54:1747, 54:1752, 54:1759,  
54:1761, 54:1793, 54:1794, 54:1905,  
54:1907, 54:1909, 54:1910, 54:1913,  
54:1915, 54:1987, 54:1989, 54:1991,  
54:1994, 54:1996, 54:2069, 54:2072,  
54:2075, 54:2080, 54:2082, [54:2596](#),  
54:2727, 54:2728, 54:2733, 54:2736,  
54:2778, 54:2783, 54:2786, [1248](#)
- \@reserveda . . . . . [625](#)
- \@reset@ptions . . . . . 50:932, 50:969,  
50:997, 50:1062, 50:1104, [50:1114](#)
- \@reset@activechars . . . . .  
54:826, 54:851, 54:952, 54:1010
- \@reset@hfps . . . . . 54:1556,  
54:1701, 54:1869, [54:2673](#), [1321](#)
- \@reset@protect . . . . . [1335](#)
- \@restore@metafamily . . . . . [29:228](#), [709](#)
- \@restore@par . [15:5](#), 18:388, 18:404,  
18:422, 18:438, 39:127, 39:137, [1337](#)
- \@reverse@margin@false . . 45:388, 54:79
- \@reverse@margin@true . . . . . 45:387
- \@right@mark . . . . . [49:16](#), 49:120
- \@right@skip . . . . . 37:458,  
37:477, [37:495](#), 39:75, 40:392, 40:413
- \@rjfield@false . . . . . 41:34, 41:77
- \@rjfield@true . . . . . 41:125
- \@rmfamilyhook . . . . .  
29:508, 29:530, 29:542, 29:569
- \@roman . . . . . 22:228, [22:234](#)
- \@rsbox . . . . . 40:562, 40:569, [40:573](#)
- \@rtab . . . . . 41:71, [41:86](#)
- \@rule . . . . . 40:534, 40:539, [40:543](#)
- \@sanitize . . . . .  
46:7, 46:18, 46:24, 46:35, [06:892](#)
- \@save@box . . . . . 40:161, 40:168, [40:174](#)
- \@save@marbox . . . . .  
45:326, 45:327, 45:330, [45:333](#)
- \@save@picbox . . . . . 40:161, 40:168, [40:178](#)
- \@sav@sf . . . . . 17:33, 17:35,  
17:55, 17:57, [18:124](#), 18:130, 18:139,  
18:158, 18:172, 18:184, 18:198, 18:212
- \@sav@sk . . . . . [18:124](#), 18:129, 18:140,  
18:159, 18:173, 18:185, 18:199, 18:213
- \@scolelt . . . . . 54:1138, [54:1203](#)
- \@sdblcolelt 54:1155, 54:1175, [54:1204](#)
- \@seccnt@format . . . . . 44:60, [44:111](#), [1335](#)
- \@second@offive 35:24, 35:27, 35:41, 35:58
- \@second@oftwo . . . . .  
03:87, 03:185, 17:5, 20:528, 20:558,  
20:604, 20:621, 21:149, 22:281,  
22:286, 24:221, 24:241, 05:40, 05:44,  
29:591, 33:800, 33:850, 33:866,  
35:44, 35:80, [06:253](#), 06:300, 06:321,  
06:549, 06:678, 49:17, 06:729,  
50:159, 50:193, 50:205, 50:238,  
50:256, 50:305, 50:335, 06:837,  
06:844, 06:864, 50:1808, 06:911,  
54:646, 54:651, 54:658, 57:743, 01:72
- \@secp@enalty . . . . . 18:18, [44:36](#), 44:50
- \@sect . . . . . [44:54](#), [44:55](#)
- \@seq@ncr . . . . . [38:518](#)
- \@set@curr@file@aux . . . . . [52:363](#), [1375](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=lt page.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- \@setckpt ..... 20:458,  
20:465, 37:24, 37:91, 37:153, 1308
- \@setfloattypecounts ... 54:1424,  
54:1575, 54:1719, 54:1890, 54:1972,  
54:2052, 54:2147, 54:2268, 54:2620
- \@setfontsize ..... 29:720
- \@setfps ..... 45:34
- \@setfpsbit ... 45:73, 45:75, 45:77,  
45:85, 45:143, 45:146, 45:149, 54:2664
- \@setmarks .. 54:2917, 54:2919, 54:2933
- \@setminipage ..... 40:458,  
45:21, 45:177, 45:185, 45:376, 1332
- \@setminpage ..... 1345
- \@setnobreak .... 45:179, 45:375, 1332
- \@setpar ..... 15:3, 39:78
- \@setprotect ..... 1335
- \@setref ..... 35:10
- \@setsize ..... 29:720
- \@settab ..... 41:71, 41:93
- \@settodim ..... 23:17
- \@settopoint ..... 23:35
- \@setupverbvisiblespace .. 37:587,  
37:599, 37:603, 37:664, 37:678, 37:692
- \@setupverbvisibletab 37:615, 37:636
- \@sffamilyhook .....  
..... 29:508, 29:535, 29:543, 29:570
- \@sharp 41:196, 41:235, 41:265, 41:280,  
41:281, 41:301, 41:303, 41:305, 41:333
- \@shipoutsetup ..... 54:841
- \@shortstack ..... 42:132, 42:133
- \@show@... ..... 101
- \@show@DeclareRobustCommand ....  
06:646, 06:660, 06:705, 06:759, 06:762
- \@show@DeclareRobustCommand@env .  
..... 06:783, 06:785
- \@show@Environment ... 06:777, 06:778
- \@show@Environment@begin .....  
..... 06:786, 06:792, 06:800, 06:805
- \@show@Environment@end .....  
..... 06:790, 06:799, 06:804, 105
- \@show@Environment@end@aux .....  
..... 06:808, 06:810
- \@show@macro ..... 06:705, 06:795
- \@show@newcommand . 06:647, 06:660,  
06:713, 06:740, 06:759, 06:765, 103
- \@show@newcommand@aux .....  
..... 06:740, 06:769, 06:787, 104
- \@show@newcommand@env 06:785, 06:784
- \@show@nonstop ... 06:795, 06:816, 106
- \@show@normalenv ..... 06:781, 06:804
- \@show@tokens .....  
..... 06:745, 06:750, 06:794, 06:811
- \@show@typeout .....  
..... 06:789, 06:794, 06:816, 106
- \@showcommandlisthook .....  
..... 06:643, 06:645, 06:653, 07:1482, 105
- \@showenvironmentlisthook .....  
..... 06:780, 06:782, 07:1484, 1375
- \@skipping@modulefalse .....  
..... 03:154, 03:173, 03:200
- \@skipping@moduletrue 03:153, 03:177
- \@sline . 42:167, 42:179, 42:184, 42:269
- \@slowromancap ..... 22:235, 22:236
- \@spaces ..... 14:218
- \@specialoutput ..... 54:261
- \@specialpagefalse .....  
..... 54:75, 54:886, 54:961, 54:1019
- \@specialpagetrue ..... 49:9
- \@specialstyle .....  
..... 49:9, 54:887, 54:961, 54:1019
- \@sptoken ..... 06:877, 06:887
- \@sqrt ..... 38:413
- \@ssect ..... 44:53, 44:112
- \@stackcr ..... 42:139, 42:142
- \@star@or@long 06:72, 06:95, 06:163,  
06:187, 06:193, 06:219, 06:228, 06:274
- \@startcolumn . 54:268, 54:275, 54:1125
- \@startdblcolumn .....  
..... 54:1125, 54:2895, 54:2898,  
54:2937, 54:2939, 54:2976, 54:2982
- \@startfield ..... 41:28,  
41:46, 41:92, 41:104, 41:125, 41:133
- \@startline .....  
41:20, 41:57, 41:62, 41:68, 41:83, 41:154
- \@startpagehook ..... 1311
- \@startpbox ..... 41:193,  
41:236, 41:266, 41:332, 41:384, 41:386
- \@startsection ..... 44:39
- \@starttoc ..... 44:149, 1271
- \@stopfield 41:32, 41:48, 41:86, 41:93,  
41:125, 41:127, 41:140, 41:142, 41:154
- \@stopline ..... 41:30, 41:56, 41:85
- \@stpelt ..... 22:22, 22:25
- \@string@makeletter ..... 06:898, 109
- \@strip@args ..... 21:94
- \@strip@tex@ext ..... 20:246,  
20:256, 20:258, 20:263, 20:293, 462
- \@strip@tex@ext@aux .. 20:263, 20:294
- \@svector ..... 42:244, 42:259, 42:269
- \@sverb .....  
.. 37:648, 37:727, 37:736, 37:739, 849
- \@svsec 44:57, 44:60, 44:66, 44:78, 1308
- \@svsechd ..... 44:76, 44:101, 44:121
- \@swaptwoargs ..... 20:638,  
20:640, 50:942, 52:153, 52:167, 52:187
- \@sxverbatim ... 37:520, 37:588, 37:595

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\@tabacckludge</code> .....	42:362, 42:363, 42:364, 42:365,
..... 21:243, 21:245, 21:475,	42:392, 42:393, 42:394, 42:395,
21:476, 33:157, 33:164, 33:166, 1362	42:396, 42:414, 42:416, 42:418,
<code>\@tabacol</code> .....	42:419, 42:421, 42:423, 42:438,
41:178, 41:258	42:439, 42:440, 42:442, 42:444,
<code>\@tabarray</code> .....	42:446, 42:448, 42:561, 42:566,
41:170, 41:180, 41:181	42:574, 42:578, 42:615, 42:616,
<code>\@tabclassiv</code> .....	42:617, 42:618, 42:631, 42:632,
41:180, 41:330	42:634, 42:635, 42:657, 42:658,
<code>\@tabclassz</code> .....	42:659, 42:660, 42:661, 42:662,
41:179, 41:282	42:710, 42:730, 42:770, 42:786,
<code>\@tabcr</code> .....	45:62, 45:68, 45:70, 45:79, 45:80,
41:56, 41:73	45:90, 45:91, 45:131, 45:137, 45:139,
<code>\@tabfbox</code> .....	45:152, 45:153, 45:159, 45:160,
41:16, 41:80, 41:82	50:1249, 50:1251, 50:1252, 50:1253,
<code>\@tablab</code> .....	50:1380, 50:1382, 50:1383, 50:1384,
41:72, 41:126	50:1494, 50:1496, 50:1497, 50:1498,
<code>\@tabminus</code> .....	54:12, 54:14, 54:16, 54:1284,
41:72, 41:117	54:1285, 54:1286, 54:1287, 54:1307,
<code>\@tabplus</code> .....	54:1308, 54:1309, 54:1310, 54:1332,
41:72, 41:110	54:1335, 54:1368, 54:1371, 54:1483,
<code>\@tabpush</code> .....	54:1632, 54:1789, 54:2150, 54:2153,
41:11,	54:2271, 54:2274, 54:2389, 54:2391,
41:77, 41:85, 41:140, 41:143, 41:145	54:2394, 54:2396, 54:2398, 54:2420,
<code>\@tabrj</code> .....	54:2654, 54:2655, 54:2659, 54:2665,
41:72, 41:124	54:2669, 57:227, 57:232, 57:233,
<code>\@tabular</code> .....	57:234, 57:364, 57:366, 57:367,
41:174, 41:177, 41:178	57:368, 57:375, 57:377, 57:378,
<code>\@tabularcr</code> .....	57:379, 57:385, 57:387, 57:388,
41:180, 41:208	57:389, 57:396, 57:398, 57:399,
<code>\@tempa</code> .....	57:400, 57:426, 57:428, 57:429,
1332	57:430, 57:452, 57:454, 57:455,
<code>\@tempboxa</code> .....	57:456, 57:462, 57:464, 57:465,
12:13, 21:87, 23:21,	57:466, 57:490, 57:495, 57:496, 57:497
23:22, 23:23, 23:28, 23:29, 39:236,	<code>\@tempcntb</code> .. 12:7, 28:1027, 28:1031,
39:242, 39:243, 39:245, 40:29, 40:30,	28:1033, 42:279, 42:280, 42:281,
40:31, 40:32, 40:37, 40:38, 40:39,	42:283, 42:284, 42:285, 42:561,
40:40, 40:214, 40:248, 40:267,	42:562, 42:566, 42:567, 42:574,
40:276, 40:286, 40:441, 40:472,	42:575, 42:578, 42:579, 45:88, 45:89,
40:579, 40:580, 40:581, 40:588,	45:90, 45:157, 45:158, 45:159, 54:13,
40:589, 40:590, 40:591, 42:304,	54:16, 54:17, 54:2665, 54:2666,
42:305, 42:447, 42:448, 42:485,	54:2667, 57:228, 57:232, 57:491, 57:495
42:490, 42:495, 42:496, 42:514,	<code>\@tempdima</code> .....
42:519, 42:526, 42:527, 42:541,	12:10,
42:544, 42:551, 42:552, 42:613,	24:282, 24:287, 38:186, 38:189,
42:614, 42:619, 42:620, 42:629,	38:195, 40:47, 40:48, 40:62, 40:63,
42:630, 42:637, 42:638, 42:723,	40:247, 40:248, 40:266, 40:267,
42:741, 42:779, 42:797, 44:138,	40:274, 40:275, 40:276, 40:278,
44:139, 45:322, 45:380, 54:310,	40:333, 40:334, 40:360, 40:361,
54:382, 54:387, 54:388, 54:429,	40:439, 40:443, 40:546, 40:549,
54:434, 54:435, 54:556, 54:794,	40:550, 40:577, 40:579, 40:585,
54:912, 54:924, 54:925, 54:980,	40:588, 41:35, 41:36, 41:37, 41:88,
54:987, 54:988, 54:1039, 54:1046,	41:89, 41:90, 41:91, 41:218, 41:219,
54:1047, 54:1071, 54:1075, 54:1087,	42:210, 42:211, 42:213, 42:214,
54:1093, 54:1100, 54:1101, 54:1102,	42:215, 42:216, 42:217, 42:218,
54:1103, 54:1107, 54:1115, 1307	
<code>\@tempcnta</code> .....	
12:7,	
28:1026, 28:1027, 28:1028, 28:1029,	
28:1033, 41:242, 41:243, 41:244,	
41:245, 42:187, 42:188, 42:214,	
42:215, 42:216, 42:229, 42:230,	
42:231, 42:232, 42:239, 42:240,	
42:254, 42:255, 42:270, 42:271,	
42:276, 42:278, 42:279, 42:280,	
42:281, 42:282, 42:285, 42:287,	
42:288, 42:289, 42:290, 42:291,	
42:292, 42:293, 42:294, 42:295,	
42:296, 42:335, 42:336, 42:337,	
42:338, 42:339, 42:360, 42:361,	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

42:437, 42:438, 42:439, 42:448,	<code>\@tempskipb</code> . . . . . <a href="#">12:14</a> ,
42:486, 42:487, 42:491, 42:492,	18:221, 18:223, 18:225, 18:228,
42:515, 42:516, 42:520, 42:522,	18:230, 18:244, 18:259, 18:276,
42:542, 42:543, 42:545, 42:547,	18:298, 18:300, 18:301, 18:305,
42:616, 42:618, 42:633, 42:635,	18:307, 18:309, 18:310, 18:331,
42:636, 42:656, 42:657, 42:658,	18:333, 18:334, 18:338, 18:340,
44:236, 44:237, 44:259, 44:260,	18:342, 18:343, 18:365, 18:368, <a href="#">445</a>
44:273, 45:196, 45:198, 45:218,	<code>\@tempswa</code> . . . . . <a href="#">1304</a>
45:220, 45:258, 45:259, 45:260,	<code>\@tempswafalse</code> . . . . <a href="#">20:322</a> , <a href="#">20:384</a> ,
54:234, 54:235, 54:236, 54:256,	<a href="#">20:431</a> , <a href="#">21:1561</a> , <a href="#">24:95</a> , <a href="#">24:772</a> ,
54:528, 54:529, 54:534, 54:538,	<a href="#">28:538</a> , <a href="#">28:613</a> , <a href="#">28:687</a> , <a href="#">28:768</a> ,
54:542, 54:547, 54:551, 54:777,	<a href="#">28:1288</a> , <a href="#">28:1294</a> , <a href="#">37:27</a> , <a href="#">37:93</a> ,
54:779, 54:780, 54:783, 54:787,	<a href="#">37:155</a> , <a href="#">37:535</a> , <a href="#">37:556</a> , <a href="#">47:17</a> , <a href="#">47:29</a> ,
54:789, 54:1267, 54:1270, 54:1290,	<a href="#">50:1222</a> , <a href="#">50:1238</a> , <a href="#">50:1357</a> , <a href="#">50:1373</a> ,
54:1300, 54:1312, 54:1322, 54:2213,	<a href="#">52:286</a> , <a href="#">52:309</a> , <a href="#">52:330</a> , <a href="#">54:1338</a> ,
54:2214, 54:2217, 54:2218, 54:2338,	<a href="#">54:1374</a> , <a href="#">54:2156</a> , <a href="#">54:2277</a> , <a href="#">02:148</a> , <a href="#">01:62</a>
54:2339, 54:2343, 54:2344, 54:2399,	<code>\@tempwatrue</code> . . . . <a href="#">20:320</a> , <a href="#">20:325</a> ,
54:2400, 54:2401, 54:2402, 54:2405,	<a href="#">20:382</a> , <a href="#">20:387</a> , <a href="#">20:429</a> , <a href="#">20:434</a> ,
54:2408, 54:2411, 54:2413, 54:2827,	<a href="#">21:1564</a> , <a href="#">21:1565</a> , <a href="#">24:98</a> , <a href="#">24:773</a> ,
54:2828, 54:2830, 54:2831, <a href="#">1308</a>	<a href="#">24:774</a> , <a href="#">24:777</a> , <a href="#">24:780</a> , <a href="#">28:541</a> ,
<code>\@tempdimb</code> . . . . . <a href="#">12:10</a> , <a href="#">24:283</a> ,	<a href="#">28:616</a> , <a href="#">28:690</a> , <a href="#">28:771</a> , <a href="#">28:1251</a> ,
<a href="#">24:288</a> , <a href="#">24:721</a> , <a href="#">24:725</a> , <a href="#">26:180</a> ,	<a href="#">36:152</a> , <a href="#">37:198</a> , <a href="#">37:540</a> , <a href="#">37:561</a> ,
<a href="#">26:181</a> , <a href="#">26:454</a> , <a href="#">26:477</a> , <a href="#">26:478</a> ,	<a href="#">47:17</a> , <a href="#">47:29</a> , <a href="#">50:1219</a> , <a href="#">50:1354</a> ,
<a href="#">26:487</a> , <a href="#">26:488</a> , <a href="#">26:492</a> , <a href="#">26:510</a> ,	<a href="#">52:286</a> , <a href="#">52:309</a> , <a href="#">52:330</a> , <a href="#">54:2158</a> ,
<a href="#">26:513</a> , <a href="#">26:516</a> , <a href="#">26:518</a> , <a href="#">40:336</a> ,	<a href="#">54:2181</a> , <a href="#">54:2279</a> , <a href="#">54:2304</a> , <a href="#">54:2738</a> ,
<a href="#">40:337</a> , <a href="#">40:363</a> , <a href="#">40:364</a> , <a href="#">40:547</a> ,	<a href="#">54:2755</a> , <a href="#">54:2788</a> , <a href="#">54:2805</a> , <a href="#">02:154</a> , <a href="#">01:63</a>
<a href="#">40:550</a> , <a href="#">40:578</a> , <a href="#">40:580</a> , <a href="#">40:586</a> ,	<code>\@temptokena</code> . . . . . <a href="#">12:16</a> , <a href="#">37:210</a> ,
<a href="#">40:589</a> , <a href="#">42:211</a> , <a href="#">42:212</a> , <a href="#">42:357</a> ,	<a href="#">37:214</a> , <a href="#">37:223</a> , <a href="#">37:236</a> , <a href="#">37:237</a> ,
<a href="#">42:359</a> , <a href="#">42:362</a> , <a href="#">42:365</a> , <a href="#">42:481</a> ,	<a href="#">49:42</a> , <a href="#">49:46</a> , <a href="#">49:53</a> , <a href="#">49:56</a> , <a href="#">49:68</a> ,
<a href="#">42:483</a> , <a href="#">42:484</a> , <a href="#">42:509</a> , <a href="#">42:512</a> ,	<a href="#">49:69</a> , <a href="#">49:76</a> , <a href="#">49:77</a> , <a href="#">49:91</a> , <a href="#">49:92</a> ,
<a href="#">42:513</a> , <a href="#">42:538</a> , <a href="#">42:539</a> , <a href="#">42:540</a> ,	<a href="#">49:99</a> , <a href="#">49:100</a> , <a href="#">49:122</a> , <a href="#">49:123</a> , <a href="#">835</a>
<a href="#">42:611</a> , <a href="#">42:612</a> , <a href="#">42:621</a> , <a href="#">42:627</a> ,	<code>\@test</code> . . . . . <a href="#">1343</a>
<a href="#">42:628</a> , <a href="#">42:639</a> , <a href="#">42:647</a> , <a href="#">42:648</a> ,	<code>\@test@opt</code> . . . . . <a href="#">1339</a>
<a href="#">42:653</a> , <a href="#">54:1290</a> , <a href="#">54:1291</a> , <a href="#">54:1292</a> ,	<code>\@testdef</code> . . . . <a href="#">37:25</a> , <a href="#">37:92</a> , <a href="#">37:154</a> , <a href="#">37:196</a>
<a href="#">54:1293</a> , <a href="#">54:1300</a> , <a href="#">54:1312</a> , <a href="#">54:1313</a> ,	<code>\@testfalse</code> . . . . . <a href="#">54:8</a> , <a href="#">54:10</a> , <a href="#">54:11</a>
<a href="#">54:1314</a> , <a href="#">54:1315</a> , <a href="#">54:1322</a> , <a href="#">1308</a>	<code>\@testfp</code> . . . . .
<code>\@tempdimc</code> . . . . <a href="#">12:10</a> , <a href="#">26:471</a> , <a href="#">26:472</a> ,	<a href="#">54:1232</a> , <a href="#">54:1252</a> , <a href="#">54:1288</a> , <a href="#">54:1311</a> ,
<a href="#">26:474</a> , <a href="#">26:475</a> , <a href="#">26:477</a> , <a href="#">26:478</a> ,	<a href="#">54:2657</a> , <a href="#">54:2841</a> , <a href="#">54:2858</a> , <a href="#">1331</a>
<a href="#">40:74</a> , <a href="#">40:75</a> , <a href="#">40:85</a> , <a href="#">40:86</a> , <a href="#">40:548</a> ,	<code>\@testopt</code> . . . . .
<a href="#">40:549</a> , <a href="#">40:550</a> , <a href="#">42:30</a> , <a href="#">42:31</a> , <a href="#">42:32</a> ,	<a href="#">18:7</a> , <a href="#">18:8</a> , <a href="#">18:9</a> , <a href="#">18:10</a> , <a href="#">06:33</a> , <a href="#">06:97</a> ,
<a href="#">42:33</a> , <a href="#">42:34</a> , <a href="#">42:35</a> , <a href="#">42:60</a> , <a href="#">42:61</a> ,	<a href="#">06:117</a> , <a href="#">06:121</a> , <a href="#">06:189</a> , <a href="#">38:489</a> , <a href="#">1339</a>
<a href="#">42:63</a> , <a href="#">42:64</a> , <a href="#">42:332</a> , <a href="#">42:333</a> , <a href="#">42:334</a>	<code>\@testpach</code> . . . . . <a href="#">41:270</a> , <a href="#">41:348</a>
<code>\@tempdimx</code> . . . . . <a href="#">1308</a>	<code>\@testtrue</code> . . . . .
<code>\@tempskipa</code> . . . . .	. . . . . <a href="#">54:9</a> , <a href="#">54:17</a> , <a href="#">54:361</a> , <a href="#">54:1235</a> ,
<a href="#">12:14</a> , <a href="#">18:45</a> , <a href="#">18:48</a> , <a href="#">18:49</a> , <a href="#">18:300</a> ,	<a href="#">54:1254</a> , <a href="#">54:1294</a> , <a href="#">54:1316</a> , <a href="#">54:2661</a>
<a href="#">18:307</a> , <a href="#">18:309</a> , <a href="#">18:312</a> , <a href="#">18:333</a> ,	<code>\@testwrongwidth</code> . . . . .
<a href="#">18:340</a> , <a href="#">18:342</a> , <a href="#">18:345</a> , <a href="#">26:182</a> ,	<a href="#">54:350</a> , <a href="#">54:1233</a> , <a href="#">54:1289</a> , <a href="#">54:1463</a> ,
<a href="#">26:183</a> , <a href="#">39:116</a> , <a href="#">39:117</a> , <a href="#">39:118</a> ,	<a href="#">54:1612</a> , <a href="#">54:1922</a> , <a href="#">54:2003</a> , <a href="#">54:2207</a>
<a href="#">39:181</a> , <a href="#">39:183</a> , <a href="#">39:184</a> , <a href="#">39:185</a> ,	<code>\@text@composite</code> . . . . .
<a href="#">39:253</a> , <a href="#">39:254</a> , <a href="#">39:255</a> , <a href="#">44:42</a> , <a href="#">44:44</a> ,	. . . . . <a href="#">21:94</a> , <a href="#">21:1094</a> , <a href="#">21:1099</a> , <a href="#">1333</a>
<a href="#">44:45</a> , <a href="#">44:50</a> , <a href="#">44:62</a> , <a href="#">44:63</a> , <a href="#">44:88</a> ,	<code>\@text@composite@x</code> . . . . . <a href="#">21:94</a>
<a href="#">44:89</a> , <a href="#">44:91</a> , <a href="#">44:103</a> , <a href="#">44:104</a> , <a href="#">44:113</a> ,	<code>\@textbottom</code> . . . . . <a href="#">49:127</a> ,
<a href="#">44:114</a> , <a href="#">54:568</a> , <a href="#">54:569</a> , <a href="#">54:581</a> ,	<a href="#">49:129</a> , <a href="#">54:514</a> , <a href="#">54:539</a> , <a href="#">54:553</a> ,
<a href="#">54:2448</a> , <a href="#">54:2449</a> , <a href="#">54:2451</a> , <a href="#">54:2459</a>	<a href="#">54:643</a> , <a href="#">54:764</a> , <a href="#">54:784</a> , <a href="#">54:791</a> , <a href="#">54:824</a>

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

`\@textfloatsheight` ..... 54:483,  
     54:1437, 54:1439, 54:1490, 54:1491,  
     54:1496, 54:1588, 54:1590, 54:1639,  
     54:1640, 54:1645, 54:1735, 54:1737,  
     54:1797, 54:1799, 54:1805, 54:2596  
`\@textmin` ..... 45:285,  
     45:286, 45:299, 45:300, 54:90,  
     54:1439, 54:1443, 54:1446, 54:1447,  
     54:1590, 54:1593, 54:1596, 54:1597,  
     54:1737, 54:1742, 54:1746, 54:1747,  
     54:1909, 54:1991, 54:2075, 54:2174,  
     54:2176, 54:2192, 54:2296, 54:2298,  
     54:2316, 54:2714, 54:2716, 54:2718  
`\@textsubscript` ..... 45:424, 45:432  
`\@textsuperscript` .....  
     ..... 45:401, 45:403, 45:404, 1336  
`\@texttop` ..... 49:127,  
     49:129, 54:510, 54:760, 54:772, 54:824  
`\@tf@r` ..... 13:25, 13:26, 1317  
`\@tfor` ..... 13:25, 20:605, 20:622,  
     20:774, 32:88, 40:78, 40:97, 41:268,  
     42:477, 42:505, 42:534, 45:63, 45:132  
`\@tforloop` ..... 13:27, 13:28, 13:30  
`\@thanks` ..... 44:11, 44:34  
`\@thefnmark` ..... 40:487, 40:504,  
     40:521, 45:400, 45:401, 45:453,  
     45:458, 45:473, 45:491, 45:509,  
     45:521, 45:526, 45:537, 45:542, 45:553  
`\@thefoot` ..... 54:102, 54:892,  
     54:896, 54:934, 54:964, 54:967,  
     54:994, 54:1023, 54:1026, 54:1053  
`\@thehead` ..... 54:101, 54:891,  
     54:895, 54:919, 54:964, 54:966,  
     54:984, 54:1023, 54:1025, 54:1043  
`\@themargin` ..... 54:50, 54:893,  
     54:897, 54:911, 54:965, 54:967,  
     54:979, 54:1024, 54:1026, 54:1038  
`\@themark` 49:41, 49:42, 49:52, 49:53,  
     49:67, 49:68, 49:75, 49:76, 49:90,  
     49:91, 49:98, 49:99, 49:121, 49:123  
`\@thirdoffthree` ..... 21:215, 06:257  
`\@thm` ..... 43:12, 43:18, 43:24, 43:26  
`\@thmcounter` ..... 43:11, 43:17, 43:46  
`\@thmcountersep` ..... 43:10, 43:46  
`\@title` ..... 44:7, 44:31  
`\@tocrmarg` ..... 44:232, 44:255  
`\@too deep` . 14:253, 39:36, 39:263, 39:274  
`\@toplist` ..... 54:40, 54:389,  
     54:390, 54:436, 54:437, 54:634,  
     54:809, 54:1072, 54:1082, 54:1083,  
     54:1375, 54:1387, 54:2530, 54:2558  
`\@topnewpage` ..... 54:204, 1320  
`\@topnum` ... 45:271, 54:83, 54:1372,  
     54:1373, 54:1387, 54:1391, 54:1954,  
     54:1959, 54:2035, 54:2040, 54:2127,  
     54:2134, 54:2521, 54:2549, 54:2590  
`\@toproom` ..... 45:273, 54:84,  
     54:1375, 54:1387, 54:2522, 54:2550  
`\@topsep` ... 39:1, 39:71, 39:73, 39:202  
`\@topsepadd` .....  
     .... 39:1, 39:59, 39:61, 39:71, 39:124  
`\@totalleftmargin` .....  
     37:531, 37:553, 39:9, 39:53, 39:54,  
     40:391, 40:412, 41:35, 41:76, 41:81, 872  
`\@trivlist` ..... 39:48, 39:57, 39:92  
`\@tryfcolumn` .... 54:1128, 54:1148,  
     54:1166, 54:1182, 54:2842, 54:2859  
`\@trylist` ..... 54:1191,  
     54:1194, 54:1227, 54:1247, 54:1269  
`\@ttfamilyhook` .....  
     ..... 29:508, 29:540, 29:544, 29:571  
`\@twoclasseserror` .... 50:675, 50:1208  
`\@twocolumnfalse` ..... 54:77, 54:126  
`\@twocolumntrue` ..... 54:211  
`\@twoloadclasserror` .....  
     ..... 50:967, 50:1102, 50:1203  
`\@twosidefalse` ..... 54:78  
`\@typein` 06:32, 06:33, 06:40, 06:48, 1339  
`\@typeset@protect` .....  
     .... 21:44, 21:50, 21:230, 21:238,  
     29:721, 06:120, 37:282, 37:319,  
     06:347, 06:354, 06:356, 57:358, 1338  
`\@uclclist` .....  
     21:1530, 21:1531, 21:1588, 57:571, 1349  
`\@undefind` .....  
     42:57, 42:71, 42:82, 42:91, 42:162,  
     42:174, 42:237, 42:252, 42:313, 42:371  
`\@undefined` .....  
     .... 02:563, 02:578, 01:92, 01:93,  
     01:94, 03:53, 03:62, 10:203, 10:204,  
     10:205, 10:207, 10:208, 10:209,  
     10:211, 10:212, 10:214, 10:215,  
     10:216, 10:217, 10:218, 10:219,  
     10:220, 10:221, 10:222, 04:2, 04:15,  
     04:16, 04:17, 04:29, 04:30, 01:115,  
     04:74, 04:84, 14:28, 01:123, 16:170,  
     16:171, 16:172, 16:173, 16:174,  
     04:173, 17:66, 18:90, 01:131, 04:189,  
     04:197, 04:205, 18:497, 18:546,  
     18:552, 04:237, 04:238, 04:239,  
     04:240, 04:241, 04:242, 04:243,  
     20:61, 20:62, 04:244, 04:245, 04:246,  
     04:247, 04:248, 04:249, 04:250,  
     04:251, 20:130, 20:131, 04:252,  
     04:253, 04:254, 04:255, 01:138,  
     20:185, 20:186, 04:261, 20:293,  
     20:294, 20:496, 20:497, 20:498,  
     20:503, 20:557, 20:570, 20:579,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltaloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

20:594, 20:649, 21:213, 21:215,  
 21:353, 21:355, 21:357, 21:359,  
 21:361, 21:363, 21:365, 21:367,  
 21:369, 21:371, 21:390, 21:392,  
 21:394, 21:480, 21:723, 21:726,  
 22:112, 22:295, 24:531, 24:571,  
 24:633, 24:666, 24:730, 24:737,  
 01:189, 01:193, 25:2776, 25:2799,  
 25:2808, 25:2897, 25:2898, 25:2899,  
 25:2900, 25:2901, 25:2902, 25:2903,  
 25:2904, 25:2905, 25:2906, 25:2917,  
 25:2922, 25:2927, 25:2934, 25:2935,  
 25:2936, 25:2937, 25:2938, 25:2939,  
 25:2940, 25:3154, 25:3234, 25:3236,  
 25:3237, 25:3239, 25:3240, 25:3241,  
 25:3243, 26:569, 26:570, 27:4, 27:5,  
 27:6, 27:7, 27:8, 27:9, 27:10, 27:11,  
 27:12, 27:13, 27:14, 27:15, 27:16,  
 27:17, 27:18, 27:19, 27:20, 05:4,  
 28:142, 05:10, 05:16, 05:17, 05:18,  
 05:19, 05:20, 28:581, 01:219, 28:633,  
 28:884, 28:991, 29:36, 01:226, 29:59,  
 29:72, 29:92, 29:105, 29:106, 29:107,  
 29:108, 29:109, 29:110, 29:111,  
 29:112, 29:113, 29:114, 29:115,  
 29:117, 29:118, 29:119, 29:147,  
 29:148, 29:149, 29:150, 29:151,  
 29:152, 29:153, 29:154, 29:155,  
 05:154, 05:155, 05:156, 05:157,  
 05:158, 05:159, 29:289, 29:290,  
 29:291, 29:325, 29:383, 29:384,  
 05:176, 05:177, 29:551, 05:178,  
 05:179, 29:569, 29:570, 29:571,  
 29:615, 29:616, 29:617, 29:618,  
 29:619, 29:620, 29:621, 29:661,  
 29:662, 29:663, 29:664, 29:665,  
 29:666, 29:677, 05:199, 05:200,  
 29:830, 30:15, 30:55, 30:62, 30:77,  
 05:228, 32:37, 32:38, 32:39, 32:122,  
 33:123, 06:34, 33:331, 33:581,  
 33:584, 33:585, 33:615, 33:616,  
 33:617, 33:620, 33:621, 33:622,  
 33:623, 33:624, 33:625, 33:630,  
 33:631, 33:632, 33:633, 33:638,  
 33:639, 33:640, 33:641, 33:644,  
 33:645, 33:646, 33:648, 33:649,  
 33:654, 33:655, 33:656, 33:657,  
 33:658, 33:659, 33:660, 33:661,  
 33:662, 33:663, 33:664, 33:665,  
 33:666, 33:667, 33:668, 33:669,  
 33:671, 33:672, 33:674, 33:675,  
 33:676, 33:677, 33:678, 33:679,  
 33:680, 33:681, 33:682, 33:683,  
 33:685, 33:686, 33:687, 33:688,  
 33:689, 33:690, 33:691, 33:692,  
 33:693, 33:695, 33:696, 33:697,  
 33:698, 33:699, 33:700, 33:701,  
 33:702, 33:703, 33:704, 33:705,  
 33:706, 33:707, 33:708, 33:709,  
 33:710, 33:711, 33:712, 33:713,  
 33:714, 33:715, 33:716, 33:717,  
 33:718, 33:719, 33:720, 33:721,  
 33:726, 33:727, 33:729, 33:730,  
 33:731, 33:732, 33:733, 33:734,  
 33:735, 33:736, 33:738, 33:739,  
 33:741, 33:742, 33:744, 33:745,  
 33:746, 33:747, 33:749, 33:750,  
 33:751, 33:753, 33:755, 33:756,  
 33:757, 33:758, 33:759, 33:760,  
 33:761, 33:763, 33:764, 33:765,  
 33:766, 33:767, 33:768, 33:769,  
 33:770, 33:771, 35:169, 35:170,  
 35:171, 35:191, 35:207, 35:208,  
 36:268, 36:269, 36:271, 36:272,  
 36:273, 36:275, 36:276, 36:277,  
 36:279, 36:280, 37:178, 37:230,  
 37:231, 37:232, 37:233, 37:308,  
 37:387, 37:407, 37:408, 37:409,  
 37:410, 37:517, 37:579, 37:597,  
 37:598, 37:599, 37:600, 37:633,  
 37:645, 06:276, 37:694, 38:236,  
 38:246, 38:247, 38:283, 38:286,  
 38:373, 38:386, 38:529, 40:21,  
 40:169, 40:233, 40:314, 06:411,  
 06:412, 40:540, 40:570, 06:443,  
 06:471, 06:475, 06:476, 42:18,  
 06:493, 06:507, 42:466, 42:467,  
 06:554, 06:555, 06:556, 06:557,  
 06:558, 06:559, 06:560, 01:310,  
 01:311, 44:203, 44:204, 44:205,  
 44:206, 44:222, 44:270, 45:5, 06:596,  
 06:597, 06:598, 06:599, 06:600,  
 06:601, 45:429, 45:448, 06:632,  
 06:633, 06:634, 45:562, 47:30,  
 47:53, 06:652, 06:653, 50:4, 50:25,  
 50:146, 50:147, 50:148, 50:209,  
 06:760, 06:761, 06:762, 06:763,  
 06:764, 06:765, 50:416, 06:767,  
 06:768, 06:769, 50:526, 50:576,  
 50:989, 50:1027, 50:1029, 50:1035,  
 06:824, 50:1092, 50:1107, 50:1108,  
 50:1123, 06:839, 50:1262, 06:846,  
 50:1340, 50:1343, 50:1393, 50:1472,  
 50:1475, 50:1485, 50:1486, 50:1487,  
 50:1488, 50:1489, 50:1490, 50:1491,  
 50:1562, 50:1565, 50:1581, 50:1601,  
 50:1608, 06:920, 06:921, 06:922,  
 52:18, 52:19, 52:20, 52:21, 06:931,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

- 52:147, 52:189, 52:190, 52:197,  
 52:198, 52:199, 52:320, 52:341,  
 52:355, 52:359, 52:360, 52:492,  
 52:498, 52:499, 52:500, 53:444,  
 53:445, 53:446, 53:447, 53:448,  
 53:450, 53:451, 53:452, 53:459,  
 53:460, 53:462, 53:464, 53:465,  
 53:466, 53:469, 53:513, 54:373,  
 54:374, 54:797, 54:798, 54:799,  
 54:800, 54:802, 54:803, 54:804,  
 54:805, 54:806, 54:813, 54:814,  
 54:815, 02:61, 54:2500, 54:2501,  
 54:2502, 54:2503, 54:2608, 02:77,  
 57:10, 57:18, 57:39, 57:54, 57:73,  
 57:82, 57:89, 57:98, 57:108, 57:160,  
 57:161, 02:82, 57:270, 57:283,  
 57:296, 57:316, 57:341, 57:351,  
 57:352, 57:353, 57:382, 57:384,  
 57:423, 57:424, 57:443, 57:444,  
 57:445, 57:446, 57:447, 57:448,  
 57:449, 57:450, 57:451, 57:468,  
 57:484, 57:485, 57:486, 57:529,  
 57:530, 57:691, 57:726, 57:727,  
 57:728, 57:729, 57:730, 02:89,  
 02:112, 02:142, 02:228, 02:238,  
 02:240, 01:52, 01:53, 02:350, 02:351,  
 02:361, 02:362, 02:456, 02:523, *1136*  
 \undefinedfonterror ..... *1321*  
 \unexpandable@protect .....  
 ..... 20:215, 20:228, *06:273*,  
 06:359, 06:365, 06:370, 41:264, *1330*  
 \unknownoptionerror .....  
 ..... 50:1118, *50:1178*, 50:1191  
 \unknownversion ..... *1310*  
 \unprocessedoptions .... 50:625,  
 50:734, 50:989, 50:1028, 50:1029,  
 50:1089, 50:1093, 50:1193, 51:89, *1344*  
 \unused ..... 14:15, 14:32, 14:59,  
 06:10, 06:17, 50:1586, *02:177*, *1368*  
 \unusedoptionlist .....  
 20:18, 20:20, 20:88, 20:90, 20:145,  
 20:147, *50:12*, 50:518, 50:519,  
 50:529, 50:530, 50:637, 50:645,  
 51:129, 51:130, 51:136, 51:163, *1109*  
 \upline ..... *42:297*, *42:298*, 42:304  
 \upordown .....  
 42:195, 42:196, 42:204, 42:225, 42:273  
 \upvector ..... 42:268, *42:304*  
 \use@option . 50:549, 50:565, 50:583,  
 50:599, 50:601, 50:618, 50:620, *50:630*  
 \use@text@encoding .....  
 ..... *21:168*, 33:16, 33:1102  
 \vbsphack ..... *18:220*  
 \verb ..... *37:727*, *37:736*, *37:739*  
 \verbatim *37:525*, 37:571, 37:586, 37:595  
 \verbvisiblespacebox ... *37:585*,  
 37:600, 37:612, 37:613, 37:626, 37:627  
 \verreq ..... 30:468, 30:469  
 \viipt ..... *24:815*  
 \vipt ..... *24:814*  
 \vline ..... *42:166*, *42:178*, *42:297*  
 \vobeyspaces .... *37:501*, 37:571,  
 37:588, 37:664, 37:678, 37:692, 37:739  
 \vobeytabs ..... *37:501*  
 \vpt ..... *24:812*  
 \vspace ..... *18:377*  
 \vspace@calcify .....  
 ... *18:80*, *18:102*, *18:242*, *18:257*,  
 18:384, 18:389, 18:399, 18:407,  
 37:437, 38:497, 41:62, 41:224, 42:148  
 \vspacer ..... *18:377*  
 \vtryfc ..... 54:1197, *54:1205*  
 \vvector ..... *42:243*, *42:258*, *42:268*  
 \warning ..... *14:215*  
 \wckptelt ..... 20:459, *20:462*  
 \whiledim ..... *13:7*, 42:123, 42:203  
 \whilenoop ..... *13:3*, *1338*  
 \whilenum ..... *13:3*,  
 41:244, 42:104, 42:116, 42:336,  
 42:338, 42:361, 42:364, 42:393,  
 42:395, 42:416, 42:421, 42:730, 42:786  
 \whilesw ..... *13:10*,  
 54:269, 54:399, 54:408, 54:446,  
 54:456, 54:2896, 54:2938, 54:2977  
 \whileswnoop ..... *13:10*, *1338*  
 \wholewidth .....  
 ... 40:199, 40:201, 40:202, 40:204,  
 40:206, 40:207, 40:208, 40:209, *42:2*,  
 42:126, 42:129, 42:131, 42:299,  
 42:302, 42:350, 42:359, 42:406,  
 42:413, 42:564, 42:577, 42:589,  
 42:599, 42:678, 42:679, 42:727, 42:783  
 \@width ..... 18:528, 21:309,  
 21:314, 26:193, *06:26*, 30:629,  
 40:204, 40:206, 40:282, 40:289,  
 40:550, 40:603, 40:610, 41:188,  
 41:219, 41:347, 41:366, 42:227,  
 42:299, 42:302, 42:325, 42:333,  
 42:350, 42:359, 42:384, 42:392,  
 42:406, 42:413, 42:564, 42:577,  
 42:727, 42:783, 45:395, 54:2427,  
 54:2886, 54:2929, 54:2960, 02:380, *1334*  
 \wrglossary ..... 46:25, *46:30*, *1330*  
 \wrindex ..... 46:8, *46:13*, *1330*  
 \writeckpt .....  
 ..... 20:349, 20:405, 20:444, *20:456*

File Key: 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

- \@writefile ..... 20:32, 20:102,  
20:160, [37:217](#), 44:193, 44:201, [978](#)
- \@writsetup ..... [54:841](#)
- \@wrong@font@char .....  
. 21:179, 24:634, 24:668, 24:681, [1341](#)
- \@wtryfc ..... [54:1207](#), [54:1217](#)
- \@x@protect ..... 06:123, [06:346](#)
- \@x@sf ..... [45:531](#), [45:533](#)
- \@xDeclareMathDelimiter .....  
..... [28:1056](#), [28:1112](#)
- \@xaddvskip .....  
..... [18:220](#), 18:245, 18:260, 18:277
- \@xarg ..... 42:163,  
42:166, 42:175, 42:178, 42:185,  
42:189, 42:190, 42:226, 42:228,  
42:238, 42:239, 42:243, 42:253,  
42:254, 42:258, 42:266, 42:274, [42:663](#)
- \@xargarraycr .. 41:205, 41:214, [41:218](#)
- \@xargdef ..... [06:98](#)
- \@xarraycr ..... 41:202, 41:203
- \@xbitor ..... [54:11](#), [54:13](#)
- \@xcentercr .... [37:420](#), [37:427](#), [37:431](#)
- \@xdblarg ..... [06:890](#)
- \@xdblfloat ..... [45:264](#), [1329](#)
- \@xdim . 42:84, 42:93, 42:105, 42:107,  
42:117, 42:119, [42:667](#), 42:731,  
42:732, 42:733, 42:734, 42:740,  
42:787, 42:788, 42:789, 42:790, 42:796
- \@xeqncr ..... [38:481](#)
- \@exnoop ..... [41:238](#), [41:248](#)
- \@expast ..... [41:239](#), [41:240](#)
- \@xfloat [45:28](#), [45:29](#), [45:34](#), 45:266, [1330](#)
- \@xfootnote ..... [45:452](#), [45:455](#), [1307](#)
- \@xfootnotemark . [45:519](#), [45:523](#), [1307](#)
- \@xfootnotenext ..... [45:536](#), [45:539](#)
- \@xfootnotetext ..... [1307](#)
- \@xhline ..... [41:360](#), [41:361](#)
- \@xifnch ..... [06:878](#), [06:888](#)
- \@xipt . [24:819](#), 30:175, 30:177, 30:178
- \@xipt ..... [24:818](#), 30:174
- \@xivpt ..... [24:820](#), 30:176, 30:178
- \@xmpar ..... [45:324](#), [45:325](#)
- \@xnewline .....  
..... [18:61](#), 18:62, 18:73, 18:74, [18:94](#)
- \@xnext ..... [54:6](#), [54:7](#)
- \@xnthm ..... [43:5](#), [43:6](#)
- \@xobeysp ..... [18:467](#), 18:492,  
[37:506](#), [37:516](#), [37:520](#), [37:609](#),  
[37:613](#), [37:623](#), [37:627](#), [37:640](#), [450](#)
- \@xobeytab ..... [18:488](#), 37:508, 37:640
- \@xprocess@ptions ..... [50:540](#),  
[50:557](#), [50:559](#), [50:575](#), [50:577](#), [50:591](#)
- \@xpt ... [24:817](#), 30:173, 30:176, 30:177
- \@xssect ..... [44:86](#), [44:87](#), [44:123](#)
- \@xtabcr ..... [41:56](#), [41:57](#)
- \@xtabularcr ..... [41:209](#), [41:210](#)
- \@xthm ..... [43:32](#), [43:38](#), [43:41](#)
- \@xtryfc ..... [54:1194](#), [54:1222](#)
- \@xtypein ..... 06:33, 06:35, 06:42
- \@xverbatim ..... [37:520](#), [37:571](#)
- \@xvipt ..... [24:821](#), 30:177, 30:179
- \@xxDeclareMathDelimiter .....  
..... [28:1041](#), [28:1045](#)
- \@xxpt ..... [24:822](#), 30:178, 30:179
- \@xxvpt ..... [24:823](#), 30:179
- \@xxxii ..... [12:2](#), 21:446, 21:448,  
[45:89](#), [45:158](#), [54:1229](#), [54:1230](#),  
[54:1249](#), [54:1250](#), [54:1285](#), [54:1286](#),  
[54:1308](#), [54:1309](#), [54:2623](#), [1341](#)
- \@xympar ..... [45:328](#), [45:332](#), [45:378](#)
- \@yarg ..... 42:163, 42:167,  
42:175, 42:179, 42:185, 42:186,  
42:195, 42:238, 42:244, 42:253,  
42:259, 42:268, 42:270, 42:297, [42:663](#)
- \@yargarraycr .. 41:206, 41:216, [41:220](#)
- \@yargd@f ..... [06:125](#)
- \@yargdef .....  
. 06:102, 06:112, 06:125, 06:162, [1317](#)
- \@ydim . 42:85, 42:94, 42:105, 42:108,  
42:117, 42:119, [42:667](#), 42:735,  
42:736, 42:737, 42:738, 42:739,  
42:791, 42:792, 42:793, 42:794, 42:795
- \@yeqncr ..... [38:481](#)
- \@ympar ..... [45:324](#), [45:329](#)
- \@ynthm ..... [43:5](#), [43:14](#)
- \@ythm ..... [43:32](#), [43:38](#), [43:41](#)
- \@ytryfc ... [54:1240](#), [54:1259](#), [54:1263](#)
- \@yyarg ..... 42:185,  
42:186, 42:187, 42:190, 42:274, [42:663](#)
- \@ztryfc ..... [54:1268](#), [54:1279](#)
- \@@end ..... [227](#)
- \@accent@spacefactor .....  
..... [21:88](#), 21:91, 21:92, [1349](#)
- \@active@math@prime .....  
..... [38:253](#), 38:254, 54:839, [1349](#)
- \@add@accent ..... 21:83, [21:85](#), [1342](#)
- \@add@percent@to@temptokena .....  
.. [37:204](#), [37:220](#), [37:222](#), [37:231](#), [835](#)
- \@add@unicode@accent . 21:1063, 21:1077
- \@addto@hook .....  
... [24:153](#), [24:155](#), [24:811](#), 28:510,  
[28:646](#), [28:650](#), [28:667](#), [28:791](#),  
[28:797](#), [28:805](#), [28:821](#), [28:824](#),  
[28:827](#), [28:1260](#), [28:1267](#), [28:1270](#), [1316](#)
- \@addToHook ..... [311](#)
- \@addToHookNext ..... [311](#)
- \@addToHookNextWithArguments ... [311](#)
- \@addToHookWithArguments ..... [311](#)

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\alloc@</code> .....	54:30
04:22, 04:26, 04:38, 24:15, <u>02:141</u> , <u>1364</u>	
<code>\alpha@elt</code> .....	54:22
28:514, 28:741, 28:843, 28:1259, 28:1260	
<code>\alpha@list</code> ..	54:30
28:42, 28:44, 28:523,	
28:729, 28:741, 28:786, 28:841,	
28:842, 28:1255, 28:1261, 28:1262	
<code>\apptocmd</code> .....	54:22
312	
<code>\atveryend@DEPRECATED</code>	54:30
52:580, 52:582	
<code>\best@size</code>	54:22
26:455, 26:479, 26:485, 26:491	
<code>\bf@def@ult</code> .....	54:30
29:476	
<code>\bfdef@ult</code> .....	54:22
29:222, 29:280,	
29:350, 29:351, 29:352, 29:393,	
29:394, 29:395, 29:480, 29:521, <u>713</u>	
<code>\bfdefault@previous</code>	54:22
29:346, 29:349,	
29:389, 29:392, 30:117, 30:127, <u>713</u>	
<code>\bfseries@..</code> .....	54:23
706	
<code>\bfseries@previous</code> .....	54:31
1365	
<code>\bfseries@rm</code> .....	54:23
29:106, 29:129,	
29:147, 29:300, 29:303, 29:337,	
29:350, 29:393, 29:398, 29:434, <u>721</u>	
<code>\bfseries@rm@kernel</code> .....	54:23
.. 29:109, 29:132, 29:150, 29:300, <u>711</u>	
<code>\bfseries@sf</code> .....	54:23
29:107, 29:129,	
29:148, 29:304, 29:307, 29:338,	
29:351, 29:394, 29:399, 29:435, <u>711</u>	
<code>\bfseries@sf@kernel</code> .....	54:23
.. 29:110, 29:133, 29:151, 29:304	
<code>\bfseries@tt</code> .....	54:23
29:108, 29:129,	
29:149, 29:308, 29:311, 29:339,	
29:352, 29:395, 29:400, 29:436, <u>711</u>	
<code>\bfseries@tt@kernel</code> .....	54:23
.. 29:111, 29:134, 29:152, 29:308	
<code>\bm@b</code> .....	54:23
40:37	
<code>\bm@c</code> .....	54:23
40:37, 40:50, 40:251, 40:346	
<code>\bm@l</code> .....	54:23
40:37	
<code>\bm@r</code> .....	54:23
40:37	
<code>\bm@s</code> .....	54:23
40:37	
<code>\bm@t</code> .....	54:23
40:37	
<code>\botmark</code> .....	54:23
1021	
<code>\bx@</code> .....	54:23
1244	
<code>\bx@A</code> .....	54:23
54:21	
<code>\bx@AA</code> .....	54:23
54:29	
<code>\bx@B</code> .....	54:23
54:21	
<code>\bx@BB</code> .....	54:23
54:29	
<code>\bx@C</code> .....	54:23
54:21	
<code>\bx@CC</code> .....	54:23
54:29	
<code>\bx@D</code> .....	54:23
54:21	
<code>\bx@DD</code> .....	54:23
54:29	
<code>\bx@E</code> .....	54:23
54:21	
<code>\bx@EE</code> .....	54:23
54:29	
<code>\bx@F</code> .....	54:23
54:22	
<code>\bx@FF</code> .....	54:23
54:30	
<code>\bx@G</code> .....	54:23
54:22	
<code>\bx@GG</code> .....	54:30
<code>\bx@H</code> .....	54:22
<code>\bx@HH</code> .....	54:30
<code>\bx@I</code> .....	54:22
<code>\bx@II</code> .....	54:30
<code>\bx@J</code> .....	54:22
<code>\bx@JJ</code> .....	54:30
<code>\bx@K</code> .....	54:23
<code>\bx@KK</code> .....	54:31
<code>\bx@L</code> .....	54:23
<code>\bx@LL</code> .....	54:31
<code>\bx@M</code> .....	54:23
<code>\bx@MM</code> .....	54:31
<code>\bx@N</code> .....	54:23
<code>\bx@NN</code> .....	54:31
<code>\bx@O</code> .....	54:24
<code>\bx@OO</code> .....	54:32
<code>\bx@P</code> .....	54:24
<code>\bx@PP</code> .....	54:32
<code>\bx@Q</code> .....	54:24
<code>\bx@QQ</code> .....	54:32
<code>\bx@R</code> .....	54:24
<code>\bx@RR</code> .....	54:32
<code>\bx@S</code> .....	54:27
<code>\bx@SS</code> .....	54:33
<code>\bx@T</code> .....	54:27
<code>\bx@TT</code> .....	54:33
<code>\bx@U</code> .....	54:27
<code>\bx@UU</code> .....	54:33
<code>\bx@V</code> .....	54:27
<code>\bx@VV</code> .....	54:33
<code>\bx@W</code> .....	54:28
<code>\bx@WW</code> .....	54:34
<code>\bx@X</code> .....	54:28
<code>\bx@XX</code> .....	54:34
<code>\bx@Y</code> .....	54:28
<code>\bx@YY</code> .....	54:34
<code>\bx@Z</code> .....	54:28
<code>\bx@ZZ</code> .....	54:34
<code>\c@</code> .....	22:112
<code>\c@*</code> .....	22:15, <u>1382</u>
<code>\c@bottomnumber</code>	45:269, 45:274, <u>54:2992</u>
<code>\c@dbltopnumber</code> .....	
.. 45:268, 45:283, 45:297, <u>54:2999</u>	
<code>\c@enumi</code> .....	<u>39:258</u>
<code>\c@enumii</code> .....	<u>39:258</u>
<code>\c@enumiv</code> .....	<u>39:258</u> , <u>1307</u>
<code>\c@equation</code> .....	
.. 38:393, 38:445, 38:474, 38:636	
<code>\c@errorcontextlines</code> ..	<u>14:212</u> , <u>1311</u>
<code>\c@footnote</code> .....	44:12, 45:397, 45:525
<code>\c@localmathalphabets</code> .....	
.. <u>28:138</u> , 28:151, 28:283, 28:331, <u>674</u>	
<code>\c@mpfootnote</code> .....	40:454, 45:399

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- `\c@ncel` ..... 30:472, 30:473
- `\c@page` 34:3, 34:6, 34:7, 37:28, 48:439,  
48:499, 53:385, 53:483, 54:117, 54:2394
- `\c@secnumdepth` .....  
..... 44:56, 44:71, 44:81, 44:140
- `\c@tocdepth` .... 44:140, 44:230, 44:253
- `\c@topnumber` .. 45:267, 45:271, 54:2988
- `\c@totalnumber` 45:270, 45:276, 54:2995
- `\c@totalpages` ..... 53:348, 53:447
- `\calculate@math@sizes` 24:717, 26:220
- `\catcodetable@atletter` . 04:93, 04:246
- `\catcodetable@initex` .. 04:93, 04:243
- `\catcodetable@latex` ... 04:93, 04:245
- `\catcodetable@string` .. 04:93, 04:244
- `\c@p@elt` ..... 24:97, 24:117,  
24:128, 24:129, 24:150, 24:153,  
24:155, 28:372, 28:422, 28:540,  
28:615, 28:689, 28:770, 57:472, 57:473
- `\c@p@list` ... 24:99, 24:115, 24:129,  
24:157, 24:158, 28:390, 28:440,  
28:542, 28:617, 28:691, 28:772, 57:473
- `\cf@encoding` .....  
..... 21:52, 21:59, 21:62, 21:69,  
21:172, 24:319, 24:329, 24:339, 24:389
- `\ch@ck` .....  
50:1267, 50:1286, 50:1398, 50:1419,  
50:1511, 02:129, 02:130, 02:131,  
02:132, 02:133, 02:165, 02:167, 02:172
- `\char@if@alph` ..... 06:898
- `\chardef@text@cmd` ..... 21:3
- `\check@command` ..... 06:228, 06:230
- `\check@icl` ..... 32:9,  
32:44, 32:49, 32:55, 32:63, 32:70, 32:72
- `\check@icr` ..... 32:9, 32:44,  
32:50, 32:56, 32:64, 32:73, 32:78, 1344
- `\check@mathfonts` ..... 19:5,  
21:322, 21:348, 21:380, 21:1278,  
24:430, 24:435, 24:442, 24:444,  
26:251, 28:336, 28:475, 33:636, 682
- `\check@nocorr` ..... 1327
- `\check@nocorr@` ..... 32:46, 1346
- `\check@orange` ..... 26:396, 26:397
- `\check@single` ..... 26:395, 26:417
- `\cl@ckpt` ..... 20:459, 22:37
- `\cl@page` ..... 34:4
- `\col@number` .....  
.. 54:73, 54:127, 54:213, 54:225, 1320
- `\color@begingroup` ..... 24:740,  
24:802, 38:104, 38:134, 40:29,  
40:110, 40:215, 40:442, 40:488,  
40:505, 40:522, 41:47, 41:51, 45:475,  
45:493, 45:511, 54:619, 54:745, 1317
- `\color@endbox` .... 40:110, 45:253,  
45:348, 45:366, 54:229, 54:920,  
54:935, 54:985, 54:995, 54:1044, 54:1054
- `\color@endgroup` .....  
... 24:746, 24:808, 38:104, 38:134,  
40:29, 40:119, 40:134, 40:173,  
40:194, 40:217, 40:470, 40:492,  
40:509, 40:525, 41:49, 45:479,  
45:497, 45:514, 54:624, 54:749, 882
- `\color@hbox` . 40:110, 54:917, 54:932,  
54:982, 54:992, 54:1041, 54:1051, 1331
- `\color@setgroup` .....  
..... 40:110, 40:173, 40:192, 1317
- `\color@vbox` . 40:110, 45:96, 45:165,  
45:339, 45:357, 45:381, 54:220, 1332
- `\conditionally@traceoff` .....  
..... 14:291, 07:289, 07:301, 410
- `\conditionally@traceon` 14:291, 07:325
- `\contionally@traceon` ..... 410
- `\copy@kernel@robust@command` ....  
..... 06:680, 06:767
- `\count@` ..... 03:14,  
03:15, 03:16, 03:17, 03:18, 03:20,  
01:163, 01:164, 01:165, 01:170,  
24:776, 24:782, 24:784, 26:23,  
26:303, 26:305, 26:327, 26:328,  
28:507, 28:509, 28:513, 28:872,  
28:873, 28:874, 28:920, 28:921,  
28:922, 28:981, 28:982, 28:983,  
28:1029, 28:1030, 28:1031, 28:1069,  
28:1070, 28:1071, 28:1077, 28:1078,  
28:1079, 28:1123, 28:1124, 28:1125,  
28:1131, 28:1132, 28:1133, 28:1192,  
28:1193, 28:1194, 28:1200, 28:1201,  
28:1202, 32:115, 32:118, 06:210,  
06:214, 06:379, 06:404, 42:729,  
42:730, 42:731, 42:734, 42:735,  
42:738, 42:742, 42:785, 42:786,  
42:787, 42:790, 42:791, 42:794,  
42:798, 50:1310, 50:1312, 50:1313,  
50:1314, 50:1443, 50:1445, 50:1446,  
50:1447, 50:1532, 50:1534, 50:1535,  
50:1536, 02:41, 57:239, 57:240,  
57:247, 57:249, 57:534, 57:535,  
57:542, 57:544, 02:114, 02:115,  
02:120, 02:122, 02:128, 02:129,  
02:130, 02:131, 02:132, 02:133,  
02:134, 01:50, 02:380, 02:381, 1278
- `\counterwithin@s` 22:160, 22:161, 22:176
- `\counterwithin@x` 22:160, 22:163, 22:177
- `\counterwithout@s` 22:208, 22:209, 22:223
- `\counterwithout@x` 22:208, 22:211, 22:224
- `\curr@fontshape` ... 21:198, 24:89,  
24:460, 24:468, 24:472, 24:474,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltaloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- 24:616, 24:622, 24:625, 24:634,  
 24:641, 24:643, 24:651, 24:657,  
 24:660, 24:668, 24:675, 24:677,  
 25:2842, 26:93, 26:101, 26:143,  
 26:170, 26:494, 26:514, 26:546,  
 26:562, 26:577, 28:394, 28:399,  
 28:444, 28:449, 29:639, 29:648, 1305  
 \curr@math@size .....  
 24:449, 26:257, 26:263, 26:268, 26:285  
 \declare@command@copy ..... 1364  
 \declare@commandcopy .... 06:568,  
 06:572, 06:577, 06:580, 06:599, 99  
 \declare@commandcopy@do .....  
 ..... 06:580, 06:626, 06:627  
 \declare@commandcopy@let . 06:587,  
 06:591, 06:601, 06:702, 06:703, 99  
 \declare@environmentcopy .....  
 ..... 06:609, 06:613, 06:618, 06:621  
 \declare@file@substitution .....  
 ..... 52:247, 52:567, 53:544, 1119  
 \declare@robustcommand ..... 06:274  
 \declare@robustcommand@auxi . 06:274  
 \declare@robustcommand@auxii 06:274  
 \declare@robustcommand@auxiii 06:274  
 \DeclareEncodingSubset@aux .....  
 ..... 24:187, 24:189  
 \DeclareFontEncoding@ .....  
 ..... 24:123, 24:125,  
 24:140, 57:383, 57:403, 57:469, 1358  
 \DeclareFontEncoding@saved .....  
 ..... 57:383, 57:403, 57:485  
 \DeclareFontShape@ ..... 24:22, 24:23  
 \DeclareRobustCommand ..... 321  
 \DeclareSymbolFont@m@dropped ...  
 ..... 28:532, 28:537, 28:580, 28:581  
 \DeclareSymbolFontAlphabet@ ....  
 ..... 28:1247, 28:1250  
 \DeclareUnicodeAccent@ .....  
 ..... 21:1070, 21:1072, 21:1076  
 \def ..... 331  
 \default@ds ..... 50:505, 50:536,  
 50:600, 50:619, 50:1116, 50:1118, 1309  
 \default@family .....  
 ... 24:130, 24:162, 24:584, 24:598,  
 24:601, 24:626, 24:661, 57:474, 1304  
 \default@M ..... 24:137,  
 24:177, 24:180, 24:184, 57:481, 1309  
 \default@mextra ..... 27:10, 27:89  
 \default@series .....  
 ..... 24:130, 24:163, 24:585,  
 24:599, 24:602, 24:623, 24:658, 57:474  
 \default@shape .....  
 ..... 24:131, 24:164, 24:586,  
 24:600, 24:603, 24:621, 24:656, 57:475  
 \default@T .....  
 . 24:171, 24:174, 24:184, 24:335, 1309  
 \define@mathalphabet .....  
 ..... 27:18, 27:131, 1304  
 \define@mathgroup . 27:19, 27:135, 1304  
 \define@newfont ..... 24:452, 24:461  
 \delayed@f@adjustment ... 24:353,  
 25:2783, 25:2784, 25:2785, 25:2787,  
 25:2788, 25:2799, 25:3136, 25:3137,  
 25:3139, 25:3140, 26:123, 26:127,  
 26:135, 26:139, 29:746, 29:778, 727  
 \delayed@merge@font@series .....  
 ..... 25:2784, 25:2848,  
 25:2863, 25:2902, 26:134, 26:137  
 \delayed@merge@font@shape 25:3137,  
 25:3186, 25:3241, 26:133, 26:136  
 \development@branch@name .....  
 ..... 03:11, 03:39,  
 03:53, 03:54, 03:55, 03:62, 03:63, 03:64  
 \dimen@ ..... 14:28, 14:29,  
 18:396, 18:401, 18:430, 18:435,  
 21:450, 21:451, 21:453, 21:454,  
 21:820, 21:821, 24:277, 24:279,  
 24:285, 24:298, 24:301, 24:305,  
 24:720, 24:721, 24:722, 24:726,  
 26:468, 26:469, 26:470, 26:471,  
 26:475, 33:66, 33:68, 33:892, 33:894,  
 38:72, 38:73, 38:199, 38:200, 38:201,  
 38:202, 40:587, 40:590, 41:176,  
 41:177, 02:41, 54:761, 54:763,  
 54:773, 54:775, 02:377, 02:378,  
 02:414, 02:415, 02:417, 02:419, 1343  
 \dimen@i ..... 02:41  
 \dimen@ii ..... 24:281, 24:286, 02:41  
 \disable@package@load .....  
 ..... 52:477, 53:502, 1119  
 \display ..... 38:204, 38:208, 38:209  
 \do@add@percent@to@temptokena ...  
 ..... 37:208, 37:214, 37:232  
 \do@emfont@update 29:640, 29:644, 29:664  
 \do@noligs ..... 37:741, 37:746  
 \do@subst@correction .....  
 ..... 24:85, 26:499, 26:554  
 \document@default@language .....  
 ..... 20:51, 20:52,  
 20:121, 20:122, 54:850, 54:951, 57:286  
 \document@select@group .....  
 .. 28:140, 28:146, 28:407, 28:457, 674  
 \dollar@dollar@begin ..... 38:289,  
 38:318, 38:398, 38:433, 38:625, 1384  
 \dollar@dollar@end ..... 38:289,  
 38:327, 38:400, 38:446, 38:636, 1384  
 \dont@add@percent@to@temptokena .  
 ..... 37:207, 37:209, 37:233

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltaloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

<code>\dorestore@version</code> . . .	28:115, <a href="#">28:120</a>	<code>\error@fontshape</code> . . . . .	
<code>\ds@</code> . . . . .	50:538, 50:1120, <a href="#">1309</a>	. . . . .	24:579, 24:594, 24:619, 24:654, 26:108, 26:544, 28:393, 28:443
<code>\dt@pfalse</code> . . . . .	38:205	<code>\escapechar</code> . . . . .	<a href="#">324</a>
<code>\dt@ptrue</code> . . . . .	38:204	<code>\et@xmaxfam</code> . . . . .	04:22, 04:26, 04:30, 04:38
<code>\e@alloc</code> . . . . .	04:15, 04:49, 04:79, 04:89, 04:178, 04:182, 04:186, 04:194, 04:202, 04:210, 02:47, 02:48, 02:49, 02:51, 02:52, 02:59, 02:60, 02:62, 02:64, 02:75, 02:78, 02:80, 57:12, 57:47, <a href="#">02:94</a> , 02:141, <a href="#">1364</a>	<code>\et@xmaxregs</code> . . . . .	04:29, 04:31, 04:32, 04:33, 04:34, 04:35, 04:36, 04:37
<code>\e@alloc@attribute@count</code> . . . . .		<code>\every@math@size</code> . . . . .	. . . . .
. . . . .	04:66, 04:74, 04:75, 04:76, 04:80, 04:237	. . . . .	24:79, 26:236, <a href="#">26:248</a> , <a href="#">1331</a>
<code>\e@alloc@bytecode@count</code> . . . . .	04:70, 04:197, 04:198, 04:199, 04:203, 04:253	<code>\every@size</code> . . . . .	<a href="#">1305</a>
<code>\e@alloc@ccodetable@count</code> . . . . .	04:67, 04:84, 04:85, 04:86, 04:90, 04:241	<code>\execute@size@function</code> . . . . .	. . . . .
<code>\e@alloc@chardef</code> . . . . .	04:48, 04:178, 04:194, 04:202, 04:210, 02:56, 57:12, <a href="#">02:82</a> , 02:134, 02:135	. . . . .	26:379, 26:407, 26:421, <a href="#">26:438</a>
<code>\e@alloc@intercharclass@top</code> . . . . .	<a href="#">57:35</a>	<code>\expand@font@defaults</code> . . . . .	. . . . .
<code>\e@alloc@luachunk@count</code> . . . . .	04:71, 04:205, 04:206, 04:207, 04:211, 04:255	. . . . .	29:38, 29:171, 29:241, 29:335, 29:358, 29:388, 29:409, 29:433, 29:444, 29:475, <a href="#">29:476</a> , 29:515, 29:517, 29:549, 29:551, 29:580, 33:26, 33:47, <a href="#">228</a>
<code>\e@alloc@luafunction@count</code> . . . . .	. . . . .	<code>expand@font@defaults</code> . . . . .	<a href="#">29:499</a>
. . . . .	04:68, 04:173, 04:174, 04:175, 04:179, 04:183, 04:187, 04:247, 04:249	<code>\expandafter</code> . . . . .	<a href="#">1134</a>
<code>\e@alloc@top</code> . . . . .	04:47, 04:80, 04:179, 04:183, 04:187, 04:195, 04:203, 04:211, 02:51, 02:59, 57:12, <a href="#">02:82</a> , 02:111, 02:145	<code>\external@font</code> . . . . .	26:85, 26:88, 26:99, 26:103, 26:105, 26:408, 26:422, 26:484, 26:518, 26:586, 26:588, 26:590
<code>\e@alloc@whatsit@count</code> . . . . .	04:69, 04:189, 04:190, 04:191, 04:195, 04:251	<code>\extra@def</code> . . . . .	27:9, <a href="#">27:84</a> , <a href="#">1304</a>
<code>\e@ch@ck</code> . . . . .	04:51, 04:55, 02:96, <a href="#">02:100</a>	<code>\extract@alph@from@version</code> . . . . .	. . . . .
<code>\e@insert@top</code> . . . . .	02:143, 02:145, 02:162	. . . . .	24:694, <a href="#">24:700</a> , 28:163, 28:194, 28:224, 28:256, <a href="#">1307</a>
<code>\e@mathgroup@top</code> . . . . .		<code>\extract@default@composite</code> . . . . .	. . . . .
. . . . .	28:57, 28:150, 28:151, 28:188, 28:218, 02:75, <a href="#">02:89</a> , <a href="#">1354</a>	. . . . .	21:1086, 21:1093
<code>\em@currfont</code> . . . . .	29:639, 29:650, <a href="#">724</a>	<code>\extract@default@composite@a</code> . . . . .	. . . . .
<code>\em@force</code> . . . . .	29:648, 29:653, <a href="#">29:656</a> , 29:666, <a href="#">724</a>	. . . . .	21:1095, 21:1099
<code>\emfontdeclare@clist</code> . . . . .	29:629, 29:631, 29:635, 29:640, 29:645, 29:651, 29:662, <a href="#">723</a>	<code>\extract@default@composite@b</code> . . . . .	. . . . .
<code>\empty@sfcnt</code> . . . . .	26:507, 26:508, 26:509, 26:523, 26:528, 26:580	. . . . .	21:1097, 21:1101
<code>\ENC@cmd</code> . . . . .	<a href="#">1324</a>	<code>\extract@font</code> . . . . .	24:475, <a href="#">26:82</a>
<code>\enc@update</code> . . . . .	24:320, 24:322, 24:338, <a href="#">24:341</a> , 26:148, 26:174, <a href="#">1324</a>	<code>\extract@fontinfo</code> . . . . .	26:375, 26:382
<code>\end@dblfloat</code> . . . . .	<a href="#">45:205</a>	<code>\extract@rangefontinfo</code> . . . . .	. . . . .
<code>\end@float</code> . . . . .	45:189, 45:227, 45:243, 45:383, <a href="#">997</a>	. . . . .	26:392, 26:399, 26:418, 26:451
<code>\endlinechar</code> . . . . .	<a href="#">331</a>	<code>\extract@sizefn</code> . . . . .	<a href="#">26:367</a> , 26:389
<code>\enlargethispage</code> . . . . .	<a href="#">1027</a>	<code>\f@...</code> . . . . .	<a href="#">1324</a>
<code>\err@rel@i</code> . . . . .	27:12, <a href="#">27:99</a> , 27:132, 27:136	<code>\f@baselineskip</code> . . . . .	. . . . .
		. . . . .	21:894, 21:1244, 24:380, 24:387, 24:605, 26:122, 26:168, 26:183, 26:187, 26:202, 26:216, 26:227, 26:241
		<code>\f@depth</code> . . . . .	45:291, <a href="#">54:350</a>
		<code>\f@encoding</code> . . . . .	04:260, 04:275, 04:283, 21:196, <a href="#">24:314</a> , 24:333, 24:336, 24:337, 24:339, 24:389, 24:455, 24:460, 24:479, 24:481, 24:483, 24:488, 24:490, 24:521, 24:583, 24:615, 24:650, 25:2827, 25:2831, 25:3172, 25:3176, 26:92, 26:129, 26:308, 26:534, 28:378, 28:428, <a href="#">1324</a>
		<code>\f@family</code> . . . . .	. . . . .
		. . . . .	24:209, 24:210, 24:213, 24:216,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

24:233,	24:236,	<u>24:342</u> ,	24:350,	26:289,	26:294,	26:376,	26:383,
24:362,	24:372,	24:383,	24:456,	26:402,	26:404,	26:419,	26:470,
24:460,	24:479,	24:481,	24:483,	26:472,	26:474,	26:490,	26:491,
24:488,	24:490,	24:522,	24:601,	26:496,	26:510,	26:522,	26:527,
24:626,	24:661,	25:2827,	25:2831,	26:539,	26:547,	26:552,	26:578,
25:3172,	25:3176,	26:92,	26:129,	26:592,	29:639,	29:648,	33:66,
28:378,	28:409,	28:428,	28:459,	<code>\f@user@size</code>	.....	.....	26:490, 26:495, 26:539, 26:552
29:173,	29:200,	29:201,	29:244,	<code>\f@warn@break</code>	.....	.....	<i>1326</i>
29:264,	29:337,	29:338,	29:339,	<code>\famdef@ult</code>	.....	.....	29:523
29:360,	29:361,	29:362,	29:398,	<code>\filec@ntents</code>	.....	.....	50:1217, 50:1220, 50:1223,
29:399,	29:400,	29:418,	29:419,	.....	.....	.....	50:1234, 50:1259, 50:1352, 50:1355,
29:420,	29:434,	29:435,	29:436,	.....	.....	.....	50:1358, 50:1369, 50:1390, 50:1483,
29:445,	29:446,	29:447,	29:583,	.....	.....	.....	50:1505, 50:1593, 50:1816, <i>1336</i>
29:598,	29:742,	29:752,	29:755,	<code>\filec@ntents@checkdir</code>	.....	.....	50:1240, 50:1242, 50:1260,
29:758,	29:775,	29:791,	29:807,	.....	.....	.....	50:1375, 50:1377, 50:1391, 50:1490
29:839,	29:845,	29:866,	33:23, 33:27,	<code>\filec@ntents@force</code>	.....	.....	50:1236, 50:1371, 50:1486
33:29,	33:31,	33:44,	33:48, 33:50,	<code>\filec@ntents@noheader</code>	.....	.....	50:1238, 50:1373, 50:1488
33:52,	33:57,	33:64,	33:858, 33:861,	<code>\filec@ntents@nosearch</code>	.....	.....	50:1239, 50:1374, 50:1489
33:875,	33:884,	33:890,	33:1105, <i>727</i>	<code>\filec@ntents@nowarn</code>	.....	.....	50:1244
<code>\f@linespread</code>	....	<u>24:383</u> ,	26:121,	<code>\filec@ntents@opt</code>	.....	.....	50:1220, 50:1223, 50:1225,
26:167,	26:184,	26:185,	26:188,	.....	.....	.....	50:1355, 50:1358, 50:1360, 50:1485
26:196,	26:199,	26:210,	26:213, <i>1324</i>	<code>\filec@ntents@OPTION</code>	.....	.....	<i>1087</i>
<code>\f@series</code>	.....	19:14,	<u>24:342</u> ,	24:373,	24:384,	24:457,	<code>\filec@ntents@overwrite</code>
24:460,	24:602,	24:623,	24:658,	25:2788,	25:2798,	25:2807,	25:2817,
25:2851,	25:2870,	25:2871,	25:3172,	25:3176,	26:126,	26:129,	26:132,
28:410,	28:460,	29:167,	29:182,	29:184,	29:188,	29:189,	29:190,
29:211,	29:217,	29:220,	29:222,	29:252,	29:255,	29:272,	29:277,
29:279,	29:280,	29:315,	29:601,	29:605,	29:743,	29:776,	29:792,
29:808,	29:868,	33:7,	33:577, <i>568</i>	<code>\f@series@saved</code>	.....	26:126, 26:132	
<code>\f@series@saved</code>	.....	26:126, 26:132	<code>\f@shape</code>	.....	<u>24:342</u> ,	24:352,	
24:364,	24:374,	24:385,	24:458,	24:460,	24:603,	24:621,	24:656,
25:2827,	25:2831,	25:3140,	25:3147,	25:3153,	25:3163,	25:3170,	25:3174,
25:3177,	25:3180,	25:3189,	25:3196,	25:3198,	25:3233,	26:125,	26:129,
26:131,	28:411,	28:461,	29:744,	29:777,	29:793,	29:809,	29:869, <i>730</i>
<code>\f@shape@saved</code>	.....	26:125, 26:131	<code>\f@size</code>	21:198, 21:893, 21:1243, 24:89,	24:380,	24:386,	24:459, 24:604,
24:643,	24:677,	24:719,	24:720,	24:723,	24:724,	26:122,	26:143,
26:168,	26:170,	26:181,	26:201,	26:216,	26:219,	26:222,	26:227,
26:234,	26:241,	26:253,	26:256,	26:262,	26:268,	26:285,	26:286,
26:289,	26:294,	26:376,	26:383,	26:402,	26:404,	26:419,	26:470,
26:472,	26:474,	26:490,	26:491,	26:496,	26:510,	26:522,	26:527,
26:539,	26:547,	26:552,	26:578,	26:592,	29:639,	29:648,	33:66,
33:66,	33:892			<code>\f@user@size</code>	.....	.....	26:490, 26:495, 26:539, 26:552
<code>\f@warn@break</code>	.....	.....	<i>1326</i>	<code>\famdef@ult</code>	.....	.....	29:523
<code>\filec@ntents</code>	.....	.....	50:1217, 50:1220, 50:1223,	.....	.....	.....	50:1234, 50:1259, 50:1352, 50:1355,
.....	.....	.....	50:1358, 50:1369, 50:1390, 50:1483,	.....	.....	.....	50:1505, 50:1593, 50:1816, <i>1336</i>
<code>\filec@ntents@checkdir</code>	.....	.....	50:1240, 50:1242, 50:1260,	.....	.....	.....	50:1375, 50:1377, 50:1391, 50:1490
<code>\filec@ntents@force</code>	.....	.....	50:1236, 50:1371, 50:1486	<code>\filec@ntents@noheader</code>	.....	.....	50:1238, 50:1373, 50:1488
<code>\filec@ntents@nosearch</code>	.....	.....	50:1239, 50:1374, 50:1489	<code>\filec@ntents@nowarn</code>	.....	.....	50:1244
<code>\filec@ntents@opt</code>	.....	.....	50:1220, 50:1223, 50:1225,	.....	.....	.....	50:1355, 50:1358, 50:1360, 50:1485
<code>\filec@ntents@OPTION</code>	.....	.....	<i>1087</i>	<code>\filec@ntents@overwrite</code>	.....	.....	50:1237, 50:1372, 50:1487
<code>\filec@ntents@warning</code>	.....	.....	50:1245, 50:1247, 50:1292	<code>\filec@ntents@where</code>	.....	.....	50:1241, 50:1243, 50:1272,
.....	.....	.....	50:1376, 50:1378, 50:1403, 50:1491	<code>\filename@area</code>	... 20:661, 20:676,	20:686,	20:718, 20:719, 20:723,
20:748,	20:751,	20:776,	20:792,	20:794,	01:230,	01:236,	01:243,
01:249,	01:256,	01:262,	01:269, 50:949	<code>\filename@base</code>	.....	20:661,	20:676, 20:686, 20:718, 20:720,
20:723,	20:748,	20:751,	20:783,	20:792,	01:279, 01:286, 01:299, 50:950		
<code>\filename@dot</code>	.....	01:297, 01:303	<code>\filename@dots</code>	.....	01:281, 01:283, 01:288		
<code>\filename@ext</code>	....	20:662, 20:677,	20:687,	20:714,	20:715,	20:718,	20:721, 20:723, 20:744, 20:745,
20:748,	20:751,	20:784,	01:278,	01:285,	01:295, 01:297, 50:951, <i>1125</i>		
<code>\filename@parse</code>	.....	.....	01:94, 20:659, 20:674, 20:684,				

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

20:713, 20:743, 20:781, <u>01:226</u> , 50:948	54:2040, 54:2049, 54:2055, 54:2061,
\filename@path .....	54:2067, 54:2071, 54:2077, 54:2079,
... 01:231, 01:232, 01:237, 01:244,	54:2087, 54:2092, 54:2097, 54:2105,
01:245, 01:250, 01:257, 01:258, 01:263	54:2114, 54:2119, 54:2124, 54:2126,
\filename@simple .....	54:2131, 54:2133, 54:2144, 54:2150,
..... 01:234, 01:247, 01:260,	54:2160, 54:2166, 54:2170, 54:2171,
01:270, 01:274, 01:276, 01:291, 01:293	54:2176, 54:2177, 54:2183, 54:2186,
\finish@module@release .. 03:89, 03:93	54:2187, 54:2188, 54:2195, 54:2196,
\finph@nt ..... 38:104, 38:106,	54:2197, 54:2205, 54:2210, 54:2222,
38:110, 38:111, 38:119, 38:120, <i>1275</i>	54:2223, 54:2230, 54:2233, 54:2241,
\finsm@sh ... 38:134, 38:141, 38:147,	54:2245, 54:2249, 54:2250, 54:2254,
38:153, 38:154, 38:158, 38:159, <i>856</i>	54:2255, 54:2265, 54:2271, 54:2281,
\fix@penalty ..... <u>32:101</u>	54:2287, 54:2291, 54:2292, 54:2298,
\fixed@sfcnt ... 26:582, 26:583, 26:584	54:2299, 54:2306, 54:2309, 54:2310,
\fl@ShowFloat 54:2480, 54:2486, 54:2501	54:2311, 54:2319, 54:2320, 54:2321,
\fl@trace ..... 54:245, 54:272,	54:2330, 54:2335, 54:2348, 54:2350,
54:328, 54:356, 54:363, 54:384,	54:2357, 54:2360, 54:2369, 54:2373,
54:431, 54:479, 54:521, 54:531,	54:2377, 54:2378, 54:2382, 54:2383,
54:532, 54:533, 54:534, 54:544,	54:2435, 54:2440, 54:2446, 54:2456,
54:545, 54:546, 54:547, 54:548,	54:2463, 54:2477, 54:2478, 54:2482,
54:558, 54:1131, 54:1150, 54:1169,	54:2493, <u>54:2505</u> , 54:2613, 54:2626,
54:1187, 54:1189, 54:1328, 54:1332,	54:2627, 54:2631, 54:2634, 54:2636,
54:1344, 54:1345, 54:1346, 54:1347,	54:2639, 54:2642, 54:2644, 54:2685,
54:1353, 54:1356, 54:1364, 54:1368,	54:2692, 54:2697, 54:2703, 54:2708,
54:1379, 54:1384, 54:1389, 54:1390,	54:2712, 54:2718, 54:2731, 54:2733,
54:1391, 54:1392, 54:1399, 54:1402,	54:2740, 54:2745, 54:2750, 54:2752,
54:1410, 54:1421, 54:1427, 54:1432,	54:2758, 54:2760, 54:2767, 54:2781,
54:1437, 54:1443, 54:1444, 54:1449,	54:2783, 54:2790, 54:2795, 54:2800,
54:1455, 54:1456, 54:1457, 54:1465,	54:2802, 54:2808, 54:2810, 54:2817,
54:1469, 54:1474, 54:1478, 54:1483,	54:2846, 54:2848, 54:2863, 54:2865,
54:1494, 54:1495, 54:1497, 54:1515,	54:2879, 54:2889, 54:2892, 54:2897,
54:1524, 54:1530, 54:1539, 54:1542,	54:2950, 54:2967, 54:2972, 54:2980
54:1548, 54:1558, 54:1562, 54:1572,	\fl@tracemessage .....
54:1578, 54:1583, 54:1588, 54:1593,	.. 54:2477, 54:2494, 54:2503, <u>54:2505</u>
54:1594, 54:1599, 54:1604, 54:1605,	\fl@traceval .....
54:1606, 54:1614, 54:1618, 54:1623,	..... 54:2487, 54:2488, 54:2489,
54:1627, 54:1632, 54:1643, 54:1644,	54:2490, 54:2493, 54:2502, <u>54:2505</u>
54:1646, 54:1664, 54:1672, 54:1676,	\float@count .....
54:1684, 54:1687, 54:1693, 54:1703,	02:47, 02:48, 02:49, 02:58, 02:111,
54:1707, 54:1716, 54:1722, 54:1728,	02:128, 02:134, 02:136, 02:137, 02:141
54:1734, 54:1741, 54:1743, 54:1749,	\fmtversion@topatch ..... 57:688,
54:1754, 54:1756, 54:1758, 54:1766,	57:690, 57:702, 57:703, 57:715, 57:723
54:1771, 54:1777, 54:1782, 54:1788,	\font@info 26:100, 26:382, 26:451, 26:456
54:1802, 54:1803, 54:1806, 54:1827,	\font@name .. 21:197, 21:200, 24:87,
54:1836, 54:1842, 54:1851, 54:1854,	24:257, 24:259, 24:451, 24:466,
54:1861, 54:1871, 54:1875, 54:1887,	24:642, 24:676, 26:85, 26:89, 26:91,
54:1893, 54:1898, 54:1903, 54:1907,	26:106, 26:142, 26:145, 26:155,
54:1912, 54:1913, 54:1920, 54:1925,	26:169, 26:172, 26:331, 26:332,
54:1929, 54:1936, 54:1945, 54:1949,	26:333, 26:334, 26:335, 26:340, <i>1304</i>
54:1953, 54:1954, 54:1958, 54:1959,	\font@submax <u>26:458</u> , 26:487, 26:488,
54:1969, 54:1975, 54:1980, 54:1985,	37:55, 37:57, 37:120, 37:122, 37:159,
54:1989, 54:1993, 54:1994, 54:2001,	37:161, 57:299, 57:301, 57:310, <i>1319</i>
54:2006, 54:2010, 54:2017, 54:2026,	\fps@dbl ..... <u>45:34</u>
54:2030, 54:2034, 54:2035, 54:2039,	\freeze@math@version . 28:155, <u>28:274</u>

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

`\frozen@everydisplay` ..... 54:2888, 54:2926, 54:2927, 54:2931,  
     .. 24:418, 24:423, 24:440, 24:442, 678  
`\frozen@everymath` ..... 54:2955, 54:2956, 54:2962, 02:424, 1345  
     ..... 24:418, 24:432, 24:444, 678  
`\g@addto@macro` ..... 09:78,  
     25:3251, 28:475, 50:133, 50:460,  
     50:1128, 50:1144, 50:1145, 06:1010,  
     53:352, 53:358, 53:363, 53:414, 236  
`\G@refundefined` ..... 1342  
`\G@refundefinedfalse` ..... 35:5, 807  
`\G@refundefinedtrue` ..... 35:3,  
     35:16, 35:33, 35:50, 36:203, 36:210,  
     36:221, 36:227, 47:41, 47:68, 47:85, 825  
`\gen@sfcnt` ..... 26:519, 26:520, 26:521  
`\genb@sfcnt` 26:524, 26:525, 26:526, 1340  
`\genb@x` ..... 26:527, 26:529  
`\genb@y` ..... 26:529  
`\get@cdp` ..... 28:643, 28:651, 28:684  
`\get@external@font` 26:84, 26:97, 26:553  
`\getanddefine@fonts` 24:689, 24:707,  
     26:321, 28:60, 28:88, 28:133, 28:160,  
     28:191, 28:221, 28:252, 28:299,  
     28:349, 28:510, 28:594, 28:648,  
     28:650, 28:667, 28:790, 28:791,  
     28:823, 28:824, 28:1266, 28:1267, 678  
`\glb@currrsize` .....  
     ... 20:41, 20:111, 20:169, 24:409,  
     26:218, 26:253, 26:257, 26:263, 26:286  
`\glb@settings` .....  
     ..... 24:410, 26:218, 26:265, 26:296  
`\gobble@finish@module@release` ...  
     ..... 03:109, 03:111, 03:170  
`\gobble@font@spec` ..... 1338  
`\group@elt` ..... 28:36, 28:508,  
     28:555, 28:556, 28:587, 28:591, 28:1298  
`\group@list` ..... 28:512, 28:562,  
     28:585, 28:590, 28:591, 28:640,  
     28:866, 28:914, 28:975, 28:1060,  
     28:1063, 28:1114, 28:1117, 28:1183,  
     28:1186, 28:1253, 28:1304, 1347  
`\h@false` ..... 38:81  
`\h@true` ..... 38:82, 38:83  
`\hb@xt@` 21:446, 06:29, 38:210, 38:438,  
     38:467, 38:548, 38:563, 38:575,  
     38:602, 38:633, 40:48, 40:63, 40:86,  
     40:104, 40:248, 40:267, 40:614,  
     40:618, 40:619, 40:620, 41:37, 42:31,  
     42:43, 42:62, 42:74, 42:105, 42:117,  
     42:265, 42:299, 42:302, 42:305,  
     42:307, 42:314, 42:373, 42:452,  
     42:587, 42:597, 42:740, 42:796,  
     44:243, 44:266, 44:273, 54:919,  
     54:934, 54:984, 54:994, 54:1043,  
     54:1053, 54:2419, 54:2883, 54:2884,  
     54:2888, 54:2926, 54:2927, 54:2931,  
     54:2955, 54:2956, 54:2962, 02:424, 1345  
`\hexnumber@` . 28:887, 28:895, 28:930,  
     28:938, 28:959, 28:969, 28:995,  
     28:1003, 28:1011, 28:1020, 28:1023,  
     28:1032, 28:1033, 28:1072, 28:1080,  
     28:1126, 28:1134, 28:1153, 28:1154,  
     28:1164, 28:1165, 28:1170, 28:1196,  
     28:1204, 28:1209, 28:1211, 29:728  
`\hgl@` ..... 02:379, 02:380  
`\hmode@bgroup` 21:85, 21:93, 21:347,  
     21:376, 21:411, 21:417, 21:448,  
     21:459, 21:466, 21:499, 21:506,  
     21:509, 21:511, 21:519, 21:535,  
     21:754, 21:784, 21:790, 21:822,  
     21:829, 21:857, 21:860, 21:917,  
     21:1277, 32:7, 33:589, 33:596, 1349  
`\hmode@start@before@group` .....  
     . 21:86, 21:169, 21:171, 21:177, 21:202  
`\hyper@nopatch@longtable` .... 55:422  
`\if@afterindent` ..... 44:124, 44:131  
`\if@compatibility` ..... 50:2, 50:676  
`\if@endpe` ..... 37:340,  
     37:355, 37:372, 37:382, 39:140, 1380  
`\if@eqnsw` ..... 38:415, 38:516  
`\if@fcolmade` .....  
     ... 54:73, 54:269, 54:399, 54:408,  
     54:446, 54:456, 54:1129, 54:1149,  
     54:1167, 54:1196, 54:1276, 54:2845,  
     54:2862, 54:2896, 54:2938, 54:2977  
`\if@files` ..... 20:5, 20:36,  
     20:106, 20:164, 20:317, 20:329,  
     20:350, 20:379, 20:391, 20:406,  
     20:426, 20:438, 20:445, 20:457,  
     37:22, 37:61, 37:89, 37:126, 37:151,  
     37:165, 44:153, 47:4, 47:8, 47:39,  
     47:48, 47:56, 47:67, 47:84, 50:1270,  
     50:1287, 50:1401, 50:1420, 53:366, 1380  
`\if@firstamp` ..... 41:251  
`\if@firstcolumn` ... 54:73, 54:251,  
     54:284, 54:401, 54:449, 54:2391,  
     54:2876, 54:2905, 54:2946, 1023  
`\if@font@series@context` .....  
     ..... 29:588, 29:609, 29:619, 721  
`\if@forced@series` .....  
     ..... 25:2789, 29:166, 29:238, 1361  
`\if@ignore` ..... 28:317, 28:356,  
     37:4, 37:341, 37:358, 37:374, 37:383  
`\if@in@minipage@env` .. 40:423, 40:445  
`\if@includeinrelease` .....  
     ..... 03:73, 03:76, 03:132, 06:964  
`\if@inlabel` .. 39:28, 39:65, 39:102,  
     39:191, 39:214, 54:140, 54:167, 54:193  
`\if@inmath` ..... 1343

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

- \if@insert ..... 54:73,  
54:1407, 54:1520, 54:1554, 54:1669,  
54:1699, 54:1832, 54:1867, 54:1942,  
54:2023, 54:2111, 54:2238, 54:2366
- \if@listfiles@hashes .....  
..... 20:762, 20:797, 20:804, 20:808
- \if@listfiles@sizes .....  
..... 20:762, 20:798, 20:802
- \if@minipage .....  
... 16:26, 18:240, 18:255, 18:272,  
18:291, 18:324, 18:358, 37:530,  
37:552, 39:180, 40:420, 41:79, 45:20
- \if@mparswitch ..... 54:73, 54:2393
- \if@multiplelabels ..... 35:93
- \if@mypkg@draft ..... 1105
- \if@negarg 42:157, 42:198, 42:212, 42:273
- \if@newlist .. 37:572, 39:29, 39:33,  
39:69, 39:78, 39:106, 39:197, 54:876,  
54:940, 54:953, 54:998, 54:1011, 54:1057
- \if@nmbrlist ..... 39:33, 39:232
- \if@no@font@opt . 27:16, 27:110, 27:129
- \if@nobreak ..... 18:121,  
18:148, 18:293, 18:326, 18:360,  
20:203, 20:218, 20:232, 39:198,  
39:223, 40:383, 40:404, 44:47,  
44:128, 45:180, 45:373, 48:270,  
49:48, 49:58, 49:71, 49:79, 49:94,  
49:102, 54:144, 54:171, 54:197,  
54:340, 54:1499, 54:1648, 54:1809, 1332
- \if@noitemarg ..... 39:32, 39:230
- \if@noparitem ..... 39:30, 39:188
- \if@noparlist ..... 39:31, 39:114
- \if@noskipsec ..... 18:148,  
39:58, 40:384, 40:405, 44:38, 44:40,  
44:97, 45:374, 54:134, 54:161, 54:187
- \if@ovb ..... 42:427,  
42:494, 42:525, 42:550, 42:561, 42:574
- \if@ovhline ..... 42:459, 42:589
- \if@ovl ..... 42:427,  
42:492, 42:521, 42:546, 42:591, 42:600
- \if@ovr ..... 42:427,  
42:491, 42:520, 42:545, 42:588, 42:598
- \if@ovt ..... 42:427,  
42:493, 42:524, 42:549, 42:566, 42:578
- \if@ovvline ..... 42:459, 42:564
- \if@partsw . 20:5, 20:321, 20:383, 20:430
- \if@pboxsw ..... 40:351, 40:373, 40:529
- \if@reversemargin .... 54:73, 54:2396
- \if@rjfield ..... 41:19, 41:33
- \if@skipping@module .....  
..... 03:137, 03:149, 03:152
- \if@specialpage .....  
..... 54:73, 54:885, 54:960, 54:1018
- \if@tempswa .. 12:9, 20:327, 20:389,  
20:436, 21:1566, 24:100, 24:786,  
28:543, 28:618, 28:692, 28:773,  
28:1297, 37:63, 37:128, 37:167,  
37:537, 37:558, 47:95, 50:1299,  
50:1432, 50:1521, 52:292, 52:293,  
52:315, 52:316, 52:336, 52:337,  
54:1340, 54:1376, 54:2202, 54:2327,  
02:156, 01:62, 01:63, 01:64, 1352
- \if@test ..... 54:8, 54:9,  
54:1237, 54:1256, 54:1296, 54:1318,  
54:1382, 54:1467, 54:1476, 54:1616,  
54:1625, 54:1769, 54:1780, 54:1923,  
54:2004, 54:2090, 54:2208, 54:2333
- \if@twocolumn ..... 20:26,  
20:96, 20:153, 45:32, 45:210, 45:235,  
54:73, 54:118, 54:272, 54:283,  
54:400, 54:448, 54:472, 54:1131,  
54:1187, 54:2390, 54:2847, 54:2864
- \if@twoside .....  
54:73, 54:117, 54:889, 54:963, 54:1021
- \ifdt@p ..... 38:203, 38:205
- \ifFileExists@ ..... 20:490, 20:517
- \ifFileExists@@ ..... 20:517
- \ifG@refundefined .... 35:3, 35:4, 35:5
- \ifh@ ..... 38:76, 38:114, 38:123
- \ifin@ 21:1586, 21:1589, 27:50, 27:52,  
28:3, 28:23, 28:497, 28:639, 28:641,  
28:702, 28:715, 28:785, 28:787,  
28:815, 28:867, 28:881, 28:915,  
28:927, 28:976, 28:992, 28:1061,  
28:1064, 28:1085, 28:1115, 28:1118,  
28:1181, 28:1184, 28:1187, 28:1254,  
28:1256, 28:1285, 29:303, 29:307,  
29:311, 50:236, 50:254, 50:548, 50:582
- \ifmath@fonts ..... 24:267, 26:223
- \ifmaybe@ic ..... 32:82, 32:91, 1352
- \ifnot@nil ..... 26:360, 26:377, 26:398
- \ifrestore@version ..... 1343
- \iftc@forced .. 33:832, 33:843, 33:1111
- \ifv@ ..... 38:75, 38:113, 38:122
- \ifx ..... 332
- \in@ ..... 21:1584,  
21:1587, 27:49, 27:51, 28:3, 28:22,  
28:496, 28:638, 28:640, 28:698,  
28:711, 28:784, 28:786, 28:813,  
28:865, 28:876, 28:913, 28:924,  
28:974, 28:988, 28:1059, 28:1062,  
28:1082, 28:1113, 28:1116, 28:1178,  
28:1182, 28:1185, 28:1252, 28:1255,  
28:1283, 29:301, 29:305, 29:309,  
50:235, 50:252, 50:545, 50:581, 1352
- \in@@ ..... 25:2877, 25:2878,  
25:2880, 25:2881, 28:6, 28:7, 28:8, 28:10

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\in@false</code> .....	28:11	<code>\load@onefilewithoptions</code> .....	
<code>\in@true</code> .....	28:13	.....	50:900, 50:1057, 50:1608, 1077
<code>\init@restore@glb@settings</code> .....		<code>\lower@bound</code> ...	26:403, 26:404, 26:415
.....	26:266, 26:269, 26:271	<code>\lst@vskip</code> .....	426
<code>\init@restore@version</code> ....	28:63,	<code>\LT@cols</code> .....	1278
28:92, 28:109, 28:124, 28:125, 1343		<code>\ltx@sh@ft</code> ..	21:411, 21:418, 21:499,
<code>\init@series@setup</code> .....	25:3252,	21:507, 21:784, 21:791, 02:416, 1352	
25:3257, 29:121, 29:295, 29:322, 29:323		<code>\ltx@star@counter</code>	35:111, 35:127, 35:140
<code>\input@path</code> .....	01:93,	<code>\m@ne</code> .....	02:39, 394
01:115, 01:117, 01:123, 01:125,		<code>\m@th</code> .....	19:13, 30:348, 30:470,
01:131, 01:133, 01:138, 01:140,		30:472, 30:473, 30:476, 30:517,	
20:503, 20:557, 20:579, 20:606,		30:541, 30:544, 30:548, 30:551,	
20:623, 01:150, 01:217, 52:275, 10		30:558, 30:561, 30:568, 30:571,	
<code>\in@sc@unt</code> .....	02:37, 02:47,	30:653, 38:68, 38:71, 38:106, 38:140,	
02:48, 02:49, 02:58, 02:149, 02:150,		38:147, 38:167, 38:169, 38:185,	
02:151, 02:152, 02:153, 02:157, 02:159		38:204, 38:429, 38:458, 38:563,	
<code>\install@mathalphabet</code> .....		38:575, 38:602, 38:613, 40:351,	
.....	24:684, 24:701, 24:708,	40:373, 40:555, 41:181, 44:239,	
28:516, 28:519, 28:645, 28:646,		44:262, 45:400, 45:409, 45:416,	
28:743, 28:795, 28:798, 28:805,		45:437, 45:444, 02:396, 02:408, 1346	
28:820, 28:821, 28:828, 28:1268, 28:1270		<code>\makeph@nt</code> .....	38:101, 38:103
<code>\is@range</code> .....	26:393, 26:394	<code>\makesm@sh</code> .....	38:131, 38:133
<code>\kernel@ifnextchar</code> ..	03:90, 06:99,	<code>\mandatory@arg</code> .....	26:431,
06:118, 06:191, 50:440, 06:875, 06:890		26:518, 26:522, 26:527, 26:534,	
<code>\kernel@make@fragile</code> .....	18:25,	26:536, 26:541, 26:543, 26:548,	
18:26, 18:27, 18:28, 18:29, 21:190,		26:550, 26:563, 26:579, 26:586, 26:588	
21:191, 37:489, 37:490, 37:491,		<code>\math@bgroup</code> .....	24:715,
38:90, 38:91, 38:92, 38:93, 38:179,		26:307, 26:313, 28:54, 28:82, 28:147,	
38:180, 38:181, 41:160, 41:161,		28:176, 28:185, 28:207, 28:215,	
41:162, 06:479, 42:822, 42:823,		28:246, 32:130, 32:131, 32:138, 675	
42:824, 42:825, 42:826, 42:827,		<code>\math@egroup</code> .....	24:715, 26:311,
42:828, 42:829, 42:830, 42:831,		26:312, 32:131, 32:132, 32:139, 1305	
42:832, 42:833, 44:23, 44:24, 44:25,		<code>\math@famname</code> .....	1304
44:26, 44:27, 49:85, 49:86, 06:991,		<code>\math@fonts</code> .....	24:685,
06:992, 06:993, 06:994, 06:995,		24:690, 26:233, 26:337, 28:61,	
06:996, 06:997, 06:998, 06:999,		28:90, 28:161, 28:192, 28:222, 28:254	
06:1000, 06:1001, 06:1002, 06:1003,		<code>\math@fontsfalse</code> .....	
06:1004, 06:1005, 06:1006, 1048		.....	19:7, 21:322, 21:349,
<code>\l@ngrel@x</code> .....	06:79, 06:80,	21:380, 21:1279, 24:78, 24:269,	
06:88, 06:89, 06:93, 06:144, 06:156,		24:279, 24:302, 33:67, 33:637, 33:893	
06:208, 06:311, 06:312, 06:314, 84		<code>\math@fontstrue</code> .....	24:267, 24:727
<code>\l@nohyphenation</code> .....		<code>\math@group</code> .....	1304
.....	37:534, 37:726, 57:283, 1357	<code>\math@version</code> .....	
<code>\last@fontshape</code> .....		.....	24:8, 24:399, 24:689, 24:693,
.....	24:617, 24:635, 24:652, 24:669	24:695, 24:696, 24:698, 26:231,	
<code>\latexrelease@postltxcmd</code> ....	07:3327	28:57, 28:60, 28:65, 28:66, 28:70,	
<code>\latexrelease@postltxexpl</code> ....	05:136	28:85, 28:89, 28:94, 28:95, 28:99,	
<code>\leavevmode@ifvmode</code> .....		28:112, 28:113, 28:114, 28:127,	
.....	18:537, 18:538, 18:546,	28:128, 28:129, 28:150, 28:152,	
30:635, 30:637, 30:639, 30:641,		28:154, 28:155, 28:160, 28:164,	
38:115, 38:154, 38:219, 38:239, 38:240		28:166, 28:168, 28:172, 28:188,	
<code>\load@onefile@withoptions</code> .....		28:191, 28:195, 28:197, 28:199,	
.....	50:953, 50:995, 50:1107, 1079	28:203, 28:218, 28:221, 28:225,	
		28:227, 28:229, 28:233, 28:249,	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

- 28:253, 28:257, 28:259, 28:261,  
 28:265, 28:296, 28:300, 29:700, 674  
 \math@version. . . . . 1304  
 \mathchar@type . . . . . 28:959,  
 28:969, 28:1020, 28:1023, 28:1032,  
 28:1048, 28:1153, 28:1164, 28:1227  
 \mathph@nt . . . . . 38:99, 38:105  
 \mathsm@sh . . . . .  
 38:129, 38:138, 38:139, 38:145, 38:146  
 \maybe@ic . . . . . 32:63, 32:64, 32:83  
 \maybe@ic@ . . . . . 32:83  
 \maybe@icfalse . . . . . 32:97  
 \maybe@ictrue . . . . . 32:87  
 \maybe@load@fontshape . . . . .  
 . . . . . 21:89, 25:2864,  
 25:2903, 26:128, 29:186, 29:254, 485  
 \maybe@update@bfseries@defaults .  
 . . . . . 29:39, 29:336, 29:345, 29:383  
 \maybe@update@mdseries@defaults .  
 . . . . . 29:40, 29:359, 29:368, 29:384  
 \mb@b . . . . . 40:76, 40:87, 40:95, 40:105  
 \mb@l . . . . . 40:76, 40:80, 40:86,  
 40:95, 40:99, 40:104, 42:137, 42:141  
 \mb@r . . . . . 40:76, 40:80, 40:86,  
 40:95, 40:99, 40:104, 42:137, 42:141  
 \mb@t . . . . . 40:77, 40:84, 40:96, 40:103  
 \md@def@ult . . . . . 29:476  
 \mddef@ult . . . . . 29:220, 29:279,  
 29:372, 29:373, 29:374, 29:413,  
 29:414, 29:415, 29:481, 29:522, 1362  
 \mddefault@previous 29:369, 29:371,  
 29:410, 29:412, 30:118, 30:128, 1365  
 \mdseries@. . . . . 712  
 \mdseries@previous . . . . . 1365  
 \mdseries@rm . . . . . 29:112,  
 29:128, 29:129, 29:145, 29:153,  
 29:360, 29:372, 29:413, 29:418, 29:445  
 \mdseries@sf 29:113, 29:129, 29:154,  
 29:361, 29:373, 29:414, 29:419, 29:446  
 \mdseries@tt 29:114, 29:129, 29:155,  
 29:362, 29:374, 29:415, 29:420, 29:447  
 \meaning . . . . . 316  
 \merge@font@series 25:2796, 25:2813,  
 25:2814, 25:2895, 25:2897, 26:134, 623  
 \merge@font@series@ . . . . .  
 . . . . . 25:2816, 25:2821, 25:2898  
 \merge@font@series@without@substitution  
 25:2848, 25:2863, 25:2900, 26:137, 625  
 \merge@font@series@without@substitution@  
 . . . . . 25:2848, 25:2901  
 \merge@font@shape 25:3146, 25:3159,  
 25:3160, 25:3231, 25:3236, 26:133  
 \merge@font@shape@ . . . . .  
 . . . . . 25:3162, 25:3167, 25:3237  
 \merge@font@shape@without@substitution  
 . . . . . 25:3186, 25:3239, 26:136  
 \merge@font@shape@without@substitution@  
 . . . . . 25:3186, 25:3240  
 \mv@<version> . . . . . 677  
 \mv@<version>@frozen . . . . . 674  
 \mv@<version>@reset . . . . . 677  
 \n@space . . . . .  
 . . . . . 30:636, 30:638, 30:640, 30:642,  
 30:647, 30:648, 30:649, 30:650, 30:653  
 \new@command . . . . . 06:96, 06:95, 06:172,  
 06:206, 06:225, 06:296, 06:317, 06:343  
 \new@environment 06:188, 06:187, 06:200  
 \new@fontshape 27:2, 27:4, 27:22, 27:24  
 \new@label@record . . . . .  
 . . . . . 36:57, 36:128, 36:279, 37:62, 817  
 \new@mathalphabet 28:696, 28:717, 28:728  
 \new@mathgroup . . . . .  
 04:27, 24:15, 28:546, 02:74, 02:76, 1305  
 \new@mathversion . . . . .  
 . . . . . 28:21, 28:479, 28:487, 28:492, 28:495  
 \new@module@skip 03:138, 03:150, 03:152  
 \new@moduledate . . . . .  
 . . . . . 03:82, 03:101, 03:104, 03:152  
 \new@modulename . . . . . 03:96, 03:152  
 \new@symbolfont . . . . . 28:547, 28:589  
 \newcommand . . . . . 321  
 \NewCommandCopy . . . . . 320  
 \NewDocumentCommand . . . . . 313  
 \newlinechar . . . . . 331  
 \newmathalphabet@ . . . . . 27:14  
 \newmathalphabet@@ . . . . . 27:109  
 \newmathalphabet@@@ . . . . . 27:15, 27:109  
 \nfss@catcodes . . . . . 24:20,  
 24:121, 24:484, 24:485, 24:492,  
 24:539, 30:41, 30:47, 30:57, 30:146, 557  
 \nfss@text . . . . . 21:335, 21:337, 29:731,  
 32:5, 32:122, 35:17, 35:34, 35:51, 1327  
 \no@alphabet@error . . . . . 24:5,  
 28:515, 28:517, 28:733, 28:734,  
 28:748, 28:757, 28:843, 28:844, 1305  
 \no@alphabet@help . . . . . 1305  
 \no@version@warning . . . . . 1305  
 \noaccents@ . . . . . 24:730, 30:140  
 \noexpand . . . . . 333  
 \non@alpherr . . . . . 24:709,  
 24:711, 28:73, 28:102, 28:118,  
 28:175, 28:206, 28:236, 28:268, 28:1305  
 \not@base . . . . . 29:848, 29:852, 29:853,  
 29:854, 29:855, 29:856, 29:857,  
 29:858, 29:859, 29:860, 29:861, 29:862  
 \not@math@alphabet . . . . . 25:2915,  
 25:2920, 25:2925, 25:3203, 25:3207,  
 25:3210, 25:3213, 25:3216, 25:3219,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

25:3222, 25:3225, 29:6, 29:9, 29:12,  
 29:15, 29:18, 29:21, 29:24, 29:27,  
 29:30, 29:334, 29:357, 29:387,  
 29:408, 29:432, 29:443, 29:460,  
 29:463, 29:485, 29:490, 29:495,  
 29:528, 29:533, 29:538, 29:554,  
 29:557, 29:560, 29:563, 29:566, 29:680  
 \now@and@everyjob .....  
 ..... 04:215, 04:221, 21:1035  
 \o@lign ..... 21:411, 21:418,  
 21:499, 21:507, 21:784, 21:791, 02:410  
 \on@line ..... 08:2158,  
 08:2172, 14:8, 14:15, 14:214,  
 29:167, 29:170, 37:254, 37:275,  
 37:293, 37:303, 40:189, 50:961,  
 50:1096, 55:124, 55:134, 55:150,  
 08:533, 08:624, 08:1495, 08:1530, 419  
 \operator@font . 30:654, 38:3, 38:4,  
 38:5, 38:6, 38:7, 38:8, 38:9, 38:10,  
 38:11, 38:12, 38:13, 38:14, 38:15,  
 38:16, 38:17, 38:18, 38:19, 38:20,  
 38:21, 38:22, 38:23, 38:24, 38:25,  
 38:26, 38:27, 38:28, 38:29, 38:30,  
 38:31, 38:32, 38:33, 38:34, 38:37, 38:40  
 \optional@arg .....  
 26:432, 26:511, 26:513, 26:585, 26:588  
 \outer@nobreak ..... 45:181,  
 45:251, 45:255, 45:346, 45:364, 1332  
 \outputbox@append ..... 1196  
 \p@ ..... 02:181  
 \p@... ..... 1359  
 \p@enum ..... 886  
 \p@equation .... 38:426, 38:455, 38:611  
 \p@renwd ..... 1315  
 \p@selectfont ..... 26:120, 1305  
 \par ..... 175  
 \par@deathcycles .....  
 ..... 39:56, 39:77, 39:79, 39:80  
 \patch@level .....  
 .. 03:1, 03:39, 03:44, 03:46, 03:48,  
 03:52, 03:61, 57:691, 57:703, 57:705, 35  
 \patchcmd ..... 313  
 \pdfannot@link@off@@ .....  
 ..... 54:846, 54:914, 54:929  
 \pdfannot@link@on@@ .....  
 ..... 54:845, 54:922, 54:937  
 \ph@nt ..... 38:81, 38:82, 38:83, 38:97  
 \pickup@font ..... 21:199,  
 24:258, 24:450, 24:644, 24:678,  
 26:144, 26:171, 26:332, 26:334, 26:336  
 \pictur@ ..... 42:21  
 \pkgcls@arg ..... 50:1619, 50:1750  
 \pkgcls@candidate .....  
 ..... 50:1606, 50:1628, 50:1704,  
 50:1708, 50:1712, 50:1781, 50:1784  
 \pkgcls@debug ... 50:1596, 50:1612,  
 50:1613, 50:1614, 50:1615, 50:1616,  
 50:1680, 50:1681, 50:1682, 50:1683,  
 50:1692, 50:1697, 50:1715, 50:1724,  
 50:1740, 50:1774, 50:1775, 50:1776  
 \pkgcls@ext ... 50:1620, 50:1668, 1379  
 \pkgcls@innerdate ..... 50:1601,  
 50:1653, 50:1656, 50:1662, 50:1802  
 \pkgcls@mindate ..... 50:1633,  
 50:1642, 50:1658, 50:1663, 1097  
 \pkgcls@name ..... 50:1618, 50:1668  
 \pkgcls@parse@date@arg .....  
 ..... 50:1627, 50:1638  
 \pkgcls@parse@date@arg@ .....  
 ..... 50:1644, 50:1647  
 \pkgcls@parse@date@arg@version ..  
 ..... 50:1654, 50:1675  
 \pkgcls@releasedate .....  
 .. 50:1606, 50:1709, 50:1713, 50:1785  
 \pkgcls@rollbackdate@error .....  
 ..... 50:1705, 50:1764, 50:1782  
 \pkgcls@show@selection .....  
 .. 50:1732, 50:1738, 50:1788, 50:1793  
 \pkgcls@targetdate .....  
 ..... 50:1601, 50:1640, 50:1648,  
 50:1651, 50:1652, 50:1656, 50:1664,  
 50:1665, 50:1678, 50:1686, 50:1701,  
 50:1703, 50:1733, 50:1745, 50:1747,  
 50:1772, 50:1778, 50:1780, 1097  
 \pkgcls@targetlabel .....  
 ..... 50:1601, 50:1641,  
 50:1661, 50:1676, 50:1688, 50:1720,  
 50:1754, 50:1792, 50:1795, 1097  
 \pkgcls@use@this@release .....  
 ..... 50:1689, 50:1706,  
 50:1708, 50:1721, 50:1731, 50:1784  
 \pr@@@s ..... 38:259, 38:267  
 \pr@@@t ..... 38:262, 38:268  
 \pr@m@s ..... 38:256, 38:257  
 \pr@tectedrel@x .....  
 ..... 06:77, 06:94, 06:143, 06:294, 84  
 \preload@sizes .... 27:11, 27:94, 1304  
 \prepare@family@series@update ...  
 ..... 29:118,  
 29:161, 29:162, 29:234, 29:237,  
 29:287, 29:290, 29:486, 29:491,  
 29:496, 29:529, 29:534, 29:539, 718  
 \pretocmd ..... 312  
 \prim@s ..... 38:253, 38:255, 38:267  
 \prime@s ..... 38:254  
 \process@table .....  
 ..... 20:40, 20:110, 20:168, 28:367  
 \propagate@doendpe ..... 39:140, 881

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\protected@edf</code> .....	1373	<code>\reserved@a</code> ...	03:13, 03:19, 03:34,
<code>\protected</code> .....	291		01:105, 01:109, 01:110, 03:181,
<code>\protected@cmd</code> .....	1337		03:182, 13:33, 13:37, 14:234, 18:456,
<code>\protected@edef</code> .....			18:459, 20:216, 20:217, 20:229,
.....	22:283, 29:629, 35:130,		20:230, 20:254, 20:263, 20:272,
	35:143, 35:150, 35:159, 35:161,		20:325, 20:387, 20:434, 20:504,
	35:182, 35:186, 35:193, 35:197,		20:506, 20:511, 20:513, 20:525,
	35:204, 36:40, 36:45, 36:83, 36:84,		20:528, 20:531, 20:534, 20:535,
	06:263, 06:357, 40:486, 40:503,		20:536, 20:558, 20:560, 20:565,
	40:520, 44:60, 45:472, 45:490,		20:567, 20:568, 20:569, 20:580,
	45:508, 50:539, 50:922, 50:1189, 1330		20:582, 20:587, 20:589, 20:604,
<code>\protected@file@percent</code> .....			20:610, 20:614, 20:621, 20:627,
.....	37:199, 37:206, 37:221,		20:631, 20:660, 20:663, 20:664,
	37:229, 37:230, 44:165, 44:172, 834		20:666, 20:675, 20:678, 20:685,
<code>\protected@wlog</code> .....			20:688, 20:710, 20:711, 20:712,
.....	50:386, 50:388, 50:402, 50:416		20:716, 20:724, 20:741, 20:742,
<code>\protected@write</code> .....	20:202,		20:746, 20:752, 20:782, 20:786,
	20:207, 35:105, 35:173, 36:55,		20:789, 20:794, 21:99, 21:100,
	44:189, 44:199, 46:14, 46:31, 1330		21:104, 21:107, 21:115, 21:125,
<code>\protected@xdef</code> .....	06:357,		21:128, 21:137, 21:156, 21:161,
	44:11, 45:453, 45:521, 45:537,		21:1019, 21:1023, 21:1067, 21:1069,
	50:378, 50:397, 50:450, 50:819, 1330		21:1070, 21:1072, 21:1074, 21:1082,
<code>\provide@command</code> .....	06:220, 06:219		21:1091, 24:31, 24:32, 24:33, 24:42,
<code>\ps@empty</code> .....	49:10, 57:158		24:45, 24:48, 24:64, 24:67, 24:70,
<code>\ps@plain</code> .....	49:13		24:106, 24:109, 24:111, 24:148,
<code>\q@curr@file</code> .....	50:1217, 50:1261,		24:152, 24:486, 24:489, 24:616,
	50:1263, 50:1268, 50:1294, 50:1392,		24:617, 24:632, 24:635, 24:640,
	50:1394, 50:1399, 50:1427, 1364		24:651, 24:652, 24:665, 24:669,
<code>\quote@name</code> .....	20:481, 20:497		24:674, 24:701, 24:704, 24:705,
<code>\quote@name</code> .....	20:481, 20:494,		24:713, 01:179, 01:180, 01:183,
	20:496, 20:607, 20:609, 20:618, 50:1392		01:201, 25:2823, 25:2824, 25:2827,
<code>\r@@t</code> .....	38:66		25:2828, 25:2843, 25:2844, 25:2856,
<code>\reenable@package@load</code> .....			25:2857, 01:205, 25:3168, 25:3169,
.....	52:477, 53:470, 1119		25:3172, 25:3173, 25:3194, 25:3195,
<code>\reinstall@nfss@defs</code> .....			26:197, 26:199, 26:201, 26:211,
.....	25:3205, 25:3246, 25:3250,		26:213, 26:216, 26:361, 26:362,
	25:3252, 25:3256, 25:3257, 25:3260		26:375, 26:376, 27:53, 27:57, 05:26,
<code>\relax</code> .....	333		05:27, 05:28, 05:29, 05:30, 28:532,
<code>\rem@pt</code> .....	24:392		28:535, 05:51, 28:607, 28:610,
<code>\remove@angles</code> .....	26:364, 26:387		05:56, 28:643, 28:652, 28:654,
<code>\remove@nil</code> .....	28:37		28:698, 28:701, 28:711, 28:714,
<code>\remove@star</code> .....	26:364, 26:370		28:812, 28:814, 28:876, 28:880,
<code>\remove@tlig</code> .....	21:1025,		28:924, 28:926, 05:93, 28:987,
	21:1027, 21:1029, 21:1053, 21:1058,		28:990, 05:99, 28:1082, 28:1084,
	21:1105, 21:1106, 21:1107, 1364		05:109, 28:1178, 28:1180, 28:1282,
<code>\remove@to@nnil</code> .....			28:1284, 28:1300, 28:1302, 28:1303,
.....	24:391, 26:364, 26:390, 26:503		28:1308, 29:41, 29:42, 29:74, 29:75,
<code>\renew@command</code> .....			01:227, 29:196, 29:197, 29:261,
.....	06:164, 06:163, 06:226, 06:234		29:262, 29:597, 29:598, 01:234,
<code>\renew@environment</code> ...	06:194, 06:193		01:237, 01:239, 01:240, 32:47,
<code>\requested@test@context</code> .....			32:48, 32:53, 32:54, 32:65, 32:68,
.....	29:582, 29:601, 29:605, 721		32:88, 32:95, 01:247, 01:250, 01:252,
<code>\reserved@b</code> .....	693		01:253, 06:140, 01:260, 06:145,
			06:153, 06:156, 01:263, 35:126,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

35:127, 35:128, 06:174, 35:139,  
 35:140, 35:141, 06:175, 06:176,  
 35:159, 35:160, 35:161, 35:162,  
 06:178, 35:186, 35:187, 35:197,  
 35:198, 01:265, 36:40, 36:41, 36:45,  
 36:46, 36:83, 36:85, 06:225, 06:226,  
 06:227, 06:233, 06:234, 06:235,  
 06:236, 37:197, 37:198, 06:239,  
 37:252, 37:253, 37:258, 37:273,  
 37:274, 37:278, 37:291, 37:292,  
 37:296, 37:301, 37:302, 37:306,  
 37:391, 37:392, 06:263, 06:269,  
 06:330, 06:334, 38:511, 38:512,  
 38:513, 38:514, 38:516, 06:392,  
 40:78, 40:79, 40:82, 40:97, 40:98,  
 06:396, 40:101, 40:184, 40:190,  
 06:430, 06:434, 06:458, 06:462,  
 41:241, 41:245, 41:250, 41:269,  
 41:360, 41:361, 42:199, 42:201,  
 42:205, 42:477, 42:478, 42:505,  
 42:506, 42:534, 42:535, 06:573,  
 06:581, 06:582, 45:29, 45:30, 45:32,  
 45:33, 45:63, 45:67, 45:72, 45:74,  
 45:76, 45:78, 45:83, 45:84, 45:132,  
 45:136, 45:142, 45:145, 45:148,  
 45:151, 01:315, 06:614, 01:316,  
 06:622, 06:623, 06:624, 06:625,  
 01:317, 06:665, 06:668, 06:683,  
 06:685, 06:688, 06:697, 06:719,  
 06:726, 50:131, 50:134, 50:136,  
 50:230, 50:238, 50:242, 50:248,  
 50:256, 50:260, 06:751, 06:753,  
 50:448, 50:450, 50:451, 50:452,  
 50:456, 50:471, 50:473, 50:474,  
 50:475, 50:479, 50:656, 50:660,  
 50:666, 50:670, 50:748, 50:749,  
 50:752, 50:821, 50:825, 50:837,  
 50:838, 50:840, 50:849, 50:853,  
 50:865, 50:866, 50:868, 50:876,  
 50:880, 50:892, 50:893, 50:894,  
 50:896, 50:908, 50:911, 50:912,  
 50:914, 50:998, 50:1047, 50:1064,  
 50:1105, 50:1228, 50:1229, 50:1231,  
 50:1363, 50:1364, 50:1366, 50:1408,  
 50:1409, 50:1411, 50:1415, 06:872,  
 50:1630, 50:1635, 06:881, 50:1687,  
 50:1688, 50:1719, 50:1720, 50:1791,  
 50:1792, 50:1816, 50:1818, 52:161,  
 52:167, 52:168, 52:169, 54:26, 54:35,  
 54:37, 54:38, 54:1227, 54:1247,  
 54:2573, 54:2575, 54:2576, 54:2675,  
 54:2677, 54:2683, 54:2686, 57:226,  
 57:243, 57:244, 57:245, 57:252,  
 57:253, 57:254, 57:489, 57:520,  
 57:526, 57:527, 57:538, 57:539,  
 57:540, 57:547, 57:548, 57:549,  
 57:574, 57:575, 57:582, 57:586,  
 57:588, 57:590, 57:595, 57:598,  
 57:606, 57:607, 57:608, 57:704,  
 57:707, 57:708, 57:725, 02:116, 1332  
 \reserved@b . 01:106, 01:107, 13:33,  
 13:34, 13:37, 18:457, 18:458, 18:465,  
 20:323, 20:325, 20:385, 20:387,  
 20:432, 20:434, 20:605, 20:607,  
 20:609, 20:622, 20:624, 20:626,  
 20:710, 20:711, 20:712, 20:785,  
 20:787, 20:788, 20:795, 21:108,  
 21:115, 21:130, 21:137, 21:1022,  
 21:1023, 21:1068, 21:1069, 21:1091,  
 21:1100, 21:1102, 24:32, 24:33,  
 24:39, 24:96, 24:98, 24:151, 24:152,  
 24:702, 24:713, 25:2842, 25:2843,  
 25:2845, 27:47, 27:54, 27:71, 27:73,  
 28:533, 28:534, 28:535, 28:539,  
 28:541, 05:52, 28:608, 28:609,  
 28:610, 28:614, 28:616, 05:58,  
 28:651, 28:652, 28:653, 28:688,  
 28:690, 28:769, 28:771, 28:816,  
 28:817, 28:818, 28:825, 28:985,  
 28:989, 28:991, 29:203, 29:208,  
 29:212, 29:213, 29:220, 29:221,  
 29:266, 29:273, 29:279, 32:52,  
 32:53, 32:66, 32:68, 32:95, 32:96,  
 06:127, 06:129, 06:141, 06:154,  
 06:176, 06:177, 36:84, 36:85, 06:331,  
 06:332, 06:334, 06:393, 06:394,  
 06:396, 06:431, 06:432, 06:434,  
 06:459, 06:460, 06:462, 41:246,  
 41:248, 41:250, 45:43, 45:44, 45:112,  
 45:113, 06:666, 06:668, 06:684,  
 06:688, 06:723, 06:726, 50:231,  
 50:232, 50:233, 50:235, 50:250,  
 50:253, 50:448, 50:471, 50:829,  
 50:835, 50:838, 50:857, 50:863,  
 50:866, 50:884, 50:890, 50:894,  
 50:908, 50:915, 50:1277, 50:1278,  
 50:1281, 50:1282, 50:1317, 50:1318,  
 50:1320, 50:1347, 50:1410, 50:1411,  
 50:1414, 50:1415, 50:1450, 50:1451,  
 50:1453, 50:1479, 50:1539, 50:1540,  
 50:1542, 06:873, 50:1569, 06:883,  
 54:1136, 54:1139, 54:1153, 54:1156,  
 54:1173, 54:1176, 57:229, 57:231,  
 57:235, 57:492, 57:494, 57:498,  
 57:578, 57:583, 57:624, 57:725, 539  
 \reserved@c . 01:107, 01:112, 20:775,  
 24:97, 24:98, 24:703, 24:706, 27:48,  
 27:55, 27:61, 27:68, 28:34, 28:38,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=ltthyphen.dtx, 57=ltfinal.dtx

- 28:540, 28:541, 28:615, 28:616,  
28:689, 28:690, 28:770, 28:771,  
28:793, 28:802, 28:817, 28:831,  
28:1072, 28:1089, 28:1098, 28:1126,  
28:1137, 28:1195, 28:1208, 28:1210,  
29:205, 29:208, 29:218, 29:219,  
29:222, 29:223, 29:268, 29:278,  
29:280, 32:67, 32:69, 32:76, 50:909,  
50:911, 50:912, 50:1262, 50:1267,  
50:1268, 50:1286, 50:1294, 50:1300,  
50:1322, 50:1330, 50:1393, 50:1398,  
50:1399, 50:1419, 50:1427, 50:1433,  
50:1455, 50:1462, 50:1510, 50:1511,  
50:1512, 50:1522, 50:1544, 50:1551,  
50:1579, 06:878, 06:881, 06:883,  
06:886, 57:233, 57:238, 57:246,  
57:496, 57:517, 57:518, 57:519,  
57:521, 57:522, 57:523, 57:524,  
57:525, 57:533, 57:541, 57:727, *1346*
- `\reserved@d` .....  
... 01:110, 01:113, 20:773, 20:775,  
27:61, 27:68, 27:70, 27:74, 05:50,  
05:55, 28:1080, 28:1089, 28:1098,  
28:1134, 28:1137, 28:1203, 28:1208,  
28:1212, 29:210, 29:211, 29:216,  
29:217, 29:271, 29:272, 29:276,  
29:277, 06:871, 06:880, 57:728, *1362*
- `\reserved@e` .....  
18:58, 18:60, 18:70, 18:72, 18:101,  
18:108, 18:116, 27:39, 27:45, 27:70,  
27:73, 27:74, 28:35, 28:40, 57:729, *1339*
- `\reserved@f` .....  
18:59, 18:60, 18:71, 18:72, 18:116,  
21:1567, 21:1568, 21:1569, 21:1570,  
21:1572, 21:1583, 24:253, 24:255,  
24:261, 24:262, 26:399, 26:410,  
26:414, 26:418, 26:424, 26:427,  
26:466, 26:503, 26:506, 27:27, 27:38,  
27:45, 27:71, 27:73, 57:730, *1332*
- `\reset@font` ..... 29:312,  
29:736, 29:782, 29:798, 29:813,  
29:828, 35:17, 35:34, 35:51, 40:482,  
40:500, 40:517, 45:175, 45:371,  
45:466, 45:485, 45:503, 47:40,  
49:14, 54:900, 54:970, 54:1029, *712*
- `\restglb@settings` .... 26:269, *26:279*
- `\restore@mathversion` .....  
..... 28:108, 28:111, 28:126, 28:134
- `\restore@protect` ..... *06:357*
- `\rlh@` ..... 30:475, 30:476
- `\rm@def@ult` ..... *29:476*
- `\rmdef@ult` .....  
... 29:337, 29:360, 29:398, 29:418,  
29:434, 29:445, 29:477, 29:518,  
29:751, 29:752, 33:27, 33:48, *721*
- `\robust@command@act` .....  
..... 09:107, 06:514, 06:515,  
*06:517*, 06:585, 06:642, 06:779, *97*
- `\robust@command@act@chk@args` ...  
..... *06:539*, 06:560, *97*
- `\robust@command@act@do` .....  
..... *06:525*, 06:557, *97*
- `\robust@command@act@end` .. 06:522,  
*06:523*, 06:535, *06:538*, 06:558, *97*
- `\robust@command@act@loop` .....  
..... 06:519, *06:525*, 06:555, *97*
- `\robust@command@act@loop@aux` ...  
..... *06:525*, 06:556
- `\robust@command@chk@safe` .....  
..... 09:154, 06:407, 06:518,  
*06:539*, 06:559, 06:699, 06:711, *103*
- `\s@fct@` ..... 26:443, *26:507*
- `\s@fct@alias` ..... 26:569
- `\s@fct@fixed` ..... *26:582*
- `\s@fct@gen` ..... *26:519*
- `\s@fct@genb` ..... *26:524*
- `\s@fct@sgen` ..... *26:519*
- `\s@fct@sgenb` ..... *26:524*
- `\s@fct@sub` ..... *26:531*
- `\s@fct@subf` ..... *26:574*
- `\saved@reqcolroom` .....  
.. 54:1453, 54:1910, 54:2599, 54:2727
- `\saved@space@catcode` . 57:355, 57:424
- `\scan@fontshape` ... 27:7, 27:40, *27:43*
- `\scan@fontshape` ... 27:6, 27:26, *27:37*
- `\scantokens` ..... *316*
- `\scriptfont@name` ..... 26:334, 26:339
- `\section` ..... *313*
- `\select@group` *24:686*, *24:705*, *28:49*,  
28:407, 28:457, 28:520, 28:698,  
28:751, 28:760, 28:798, 28:830, *674*
- `\series@change@debug` .....  
..... *29:138*, 29:167, 29:170,  
29:180, 29:183, 29:187, 29:199,  
29:207, 29:212, 29:218, 29:221, 29:223
- `\series@check@toks` .....  
..... 25:2878, 25:2880, 25:2887
- `\series@drop@one@m` .....  
..... 25:2884, *25:2888*, 25:2906
- `\series@maybe@drop@one@m` .. 24:32,  
*25:2871*, *25:2873*, 25:2905, 28:534,  
28:609, 29:190, 29:209, 29:215,  
29:255, 29:270, 29:275, 29:480, 29:481
- `\series@maybe@drop@one@m@x` .....  
..... 25:2874, 25:2876
- `\seriesdefault@kernel` .....  
..... 29:313, *29:902*, *731*
- `\set@@mathdelimiter` . 28:1135, *28:1169*

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

<code>\set@color</code> .....	40:109	28:982, 28:1028, 28:1030, 28:1068,
<code>\set@curr@file</code> ...	20:245, 20:254,	28:1070, 28:1076, 28:1078, 28:1122,
	20:281, 20:289, 20:471, 20:489,	28:1124, 28:1130, 28:1132, 28:1191,
	50:940, 50:1260, 50:1391, 52:266, 1128	28:1193, 28:1199, 28:1201, 42:278,
<code>\set@curr@file@aux</code> .....		42:293, 42:295, 45:62, 45:80, 45:131,
	52:272, 52:278, 52:279	45:153, 02:16, 54:1355, 54:1401,
<code>\set@curr@file@nosearch</code> .	52:266, 1372	54:1541, 02:60, 54:1686, 02:62,
<code>\set@current@meta@family</code> .	28:412,	54:1853, 54:2168, 54:2232, 54:2289,
	29:745, 29:750, 29:784, 29:839, 1386	54:2359, 54:2629, 54:2638, 54:2694,
<code>\set@display@protect</code> .....		54:2710, 54:2748, 54:2798, 01:55
	14:7, 14:14, 14:34,	<code>\sixt@on</code> .....
	14:61, 06:8, 06:16, 06:355, 50:389, 1330	394
<code>\set@fontsize</code> .....	24:380,	<code>\size@update</code> .....
	24:382, 26:122, 26:168, 26:178, 1322	26:147, 26:173, 26:186, 26:205, 26:207
<code>\set@mathaccent</code> .....		<code>\sizefn@info</code> .....
	28:885, 28:893, 28:928, 28:936, 28:954	26:369, 26:371, 26:379, 26:407, 26:421
<code>\set@mathchar</code> .....	28:1009, 28:1019	<code>\skip@</code> .....
<code>\set@mathdelimiter</code> .....		32:105, 32:108,
	28:1086, 28:1095, 28:1147	02:41, 02:376, 02:378, 02:379, 02:381
<code>\set@mathradical</code> .....	28:467, 28:1205	<code>\sp@ce@skip</code> .....
<code>\set@mathsymbol</code> .....	28:993, 28:1001, 28:1022	18:84, 18:517, 18:518
<code>\set@simple@size@args</code> .....		<code>\sp@n</code> .....
	26:365, 26:378, 26:385, 26:406, 26:420	41:379
<code>\set@size@funct@args</code> .....		<code>\split@name</code> .....
	26:368, 26:370, 26:428	24:454,
<code>\set@size@funct@args@</code> .....	26:428	24:466, 24:580, 24:595, 26:536, 26:550
<code>\set@target@series</code> .....	24:351, 24:363,	<code>\ssf@size</code> ..
	25:2825, 25:2829, 25:2832, 25:2835,	21:348, 21:380, 21:1278,
	25:2858, 25:2860, 25:2869, 25:2904	24:288, 24:307, 24:726, 26:329, 26:335
<code>\set@typeset@protect</code> .....		<code>\string@makeletter</code> ..
	06:355, 06:374, 41:197, 41:235,	50:914, 50:949,
	53:84, 53:128, 54:882, 54:884,	50:950, 50:951, 06:898, 52:169, 1365
	54:957, 54:959, 54:1015, 54:1017, 1330	<code>\strip@meaning</code> .....
<code>\SetMathAlphabet@</code> .....	28:705, 28:774, 28:783	1315
<code>\SetSymbolFont@</code> .....	28:565, 28:619, 28:637	<code>\strip@prefix</code> .....
<code>\SetSymbolFont@m@dropped</code> .....		01:95, 24:683, 01:212, 06:332,
	28:607, 28:612, 28:632, 28:633	06:394, 06:432, 06:460, 01:307, 06:895
<code>\sf@def@ult</code> .....	29:476	<code>\strip@pt</code> ...
<code>\sf@size</code> .....	19:6, 21:322, 24:287,	24:279, 24:285, 24:286,
	24:306, 24:725, 26:329, 26:333,	24:287, 24:288, 24:301, 24:305,
	33:636, 45:409, 45:416, 45:437, 45:444	24:392, 24:725, 24:726, 26:181, 02:418
<code>\sfdef@ult</code> ..	29:338, 29:361, 29:399,	<code>\sub@sfcnt</code> ..
	29:419, 29:435, 29:446, 29:478,	26:531, 26:532, 26:533, 26:560
	29:519, 29:755, 33:29, 33:50, 713	<code>\subf@sfcnt</code> ....
<code>\sh@ft</code> .....	02:414, 1333	26:574, 26:575, 26:576
<code>\show@kernel@robust@command</code> .....		<code>\subst@correction</code> .....
	06:705, 06:768, 06:796	24:86, 24:92
<code>\show@release@info</code> .....		<code>\subst@fontshape</code> .....
	03:38, 03:41, 03:46, 03:51, 37:47,	27:8, 27:80
	37:48, 37:50, 37:112, 37:113, 37:115, 36	<code>\subst@size</code> .....
<code>\ShowCommand</code> .....	320	26:482
<code>\sixt@on</code> .....		<code>\sw@slant</code> .....
	04:30, 24:15, 28:85, 28:249, 28:871,	32:91, 32:101
	28:873, 28:919, 28:921, 28:980,	<code>\t@st@ic</code> .....
		32:90, 32:94, 1310
		<code>\target@meta@family@value</code> .....
		29:243, 29:262, 29:267, 29:269, 1386
		<code>\target@series@value</code> .....
		29:172, 29:179, 29:182,
		29:184, 29:188, 29:189, 29:190,
		29:213, 29:219, 29:220, 29:222,
		29:242, 29:250, 29:252, 29:255,
		29:273, 29:278, 29:279, 29:280, 716
		<code>\tc@check@accent</code> .....
		33:73, 33:125, 33:127, 33:129,
		33:131, 33:133, 33:135, 33:137,
		33:139, 33:141, 33:143, 33:145,
		33:147, 33:149, 33:151, 33:153,
		33:155, 33:899, 33:975, 33:977, 33:979

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltaloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

`\tc@check@symbol` ... 33:73, 33:175, 26:293, 38:438, 38:467, 38:632,  
 33:177, 33:179, 33:181, 33:183, 39:263, 39:274, 42:287, 42:288,  
 33:185, 33:187, 33:189, 33:191, 42:290, 42:291, 42:329, 42:355,  
 33:193, 33:195, 33:197, 33:199, 42:388, 42:411, 02:16, 54:855,  
 33:201, 33:203, 33:205, 33:207, 57:84, 57:92, 02:447, 02:481, 1336  
 33:209, 33:211, 33:213, 33:215, `\toks@` ..... 03:94, 03:106,  
 33:217, 33:219, 33:221, 33:223, 03:108, 03:115, 03:119, 03:122,  
 33:225, 33:227, 33:229, 33:231, 03:127, 18:455, 18:456, 18:461,  
 33:233, 33:235, 33:237, 33:239, 24:149, 24:153, 24:155, 24:158,  
 33:241, 33:243, 33:245, 33:247, 24:284, 24:289, 28:7, 28:8, 28:506,  
 33:249, 33:251, 33:253, 33:255, 28:510, 28:516, 28:519, 28:524,  
 33:257, 33:259, 33:261, 33:263, 28:590, 28:591, 28:593, 28:594,  
 33:265, 33:267, 33:269, 33:271, 28:644, 28:646, 28:650, 28:667,  
 33:274, 33:276, 33:278, 33:280, 28:670, 28:729, 28:741, 28:742,  
 33:282, 33:284, 33:286, 33:288, 28:743, 28:789, 28:791, 28:797,  
 33:290, 33:292, 33:294, 33:296, 28:805, 28:809, 28:821, 28:824,  
 33:298, 33:300, 33:302, 33:304, 28:827, 28:835, 28:837, 28:1258,  
 33:306, 33:308, 33:310, 33:312, 28:1260, 28:1262, 28:1265, 28:1267,  
 33:314, 33:318, 33:320, 33:322, 28:1270, 28:1273, 28:1305, 28:1306,  
 33:324, 33:326, 33:328, 33:330, 50:501, 50:502, 50:504, 50:505,  
 33:399, 33:969, 33:971, 33:973, 06:1012, 06:1013, 02:41, 54:2912,  
 33:981, 33:983, 33:985, 33:987, 54:2913, 54:2914, 54:2915, 1347  
 33:989, 33:991, 33:993, 33:995, `\topmark` ..... 1021  
 33:997, 33:999, 33:1001, 33:1003, `\topmark(s)` ..... 1021  
 33:1005, 33:1007, 33:1009, 33:1011, `\transform@scriptfont` .....  
 33:1013, 33:1015, 33:1017, 33:1019, ..... 26:333, 26:335, 26:343, 1386  
 33:1021, 33:1023, 33:1025, 33:1027, `\try@load@font@shape` ..... 1347  
 33:1029, 33:1031, 33:1033, 33:1035, `\try@load@fontshape` 24:469, 24:477,  
 33:1037, 33:1039, 33:1041, 33:1043, 24:523, 24:628, 25:2867, 26:537,  
 33:1045, 33:1047, 33:1049, 33:1051, 28:379, 28:396, 28:429, 28:446, 626  
 33:1053, 33:1055, 33:1057, 33:1059, `\try@simple@size` ..... 26:373, 26:498  
 33:1061, 33:1063, 33:1065, 33:1067, `\try@simples` ... 26:456, 26:462, 26:466  
 33:1069, 33:1071, 33:1073, 33:1075, `\try@size@range` 26:102, 26:373, 26:449  
 33:1077, 33:1079, 33:1081, 33:1083, `\try@size@substitution` 26:104, 26:453  
`\tc@error` ..... 33:74, 33:879, 33:900, `\tryif@simple` ..... 26:464, 26:465  
`\tc@errorwarn` ..... 33:21, `\tryis@simple` ..... 26:465  
 33:40, 33:42, 33:787, 33:789, 33:791, `\tt@def@ult` ..... 29:476  
 33:792, 33:838, 33:839, 33:840, 33:873, `\ttdef@ult` .. 29:339, 29:362, 29:400,  
`\tc@fake@euro` ..... 29:420, 29:436, 29:447, 29:479,  
 ..... 33:61, 33:316, 33:887, 33:968, 29:520, 29:758, 33:31, 33:52, 713  
`\tc@forcedfalse` ..... 33:832, `\tw@` ..... 02:16, 1327  
`\tc@forcedtrue` ..... 33:837, `\two@digits` ..... 01:169,  
`\tc@oldstylesubst` ..... 33:16, 33:20, 01:170, 26:529, 06:2, 50:1213,  
`\tc@subst` .. 33:41, 33:73, 33:872, 33:899, 50:1306, 50:1439, 50:1528, 01:70  
`\tc@swap@accent` ..... 33:76, 33:77, `\type@restoreinfo` .... 26:203, 26:208  
`\test@font@series@context` ..... `\unconditionally@reset@math@version`  
 ..... 29:584, 29:596, 29:618, 721, ..... 24:405, 24:413  
`\test@next` ..... 1338, `\undeclare@...` ..... 1164  
`\text@command` ..... 32:8, 32:46, 1327, `\undeclare@file@substitution` ...  
`\textfont@name` ..... 26:332, 26:338, ..... 52:247, 1119  
`\tf@size` ..... 24:286, `\unexpandable@noexpand` ..... 1341  
 24:306, 24:724, 26:329, 26:331, 1308, `\unexpanded` ..... 1016  
`\thr@` ..... 26:59, 26:255, `\unqu@tefilef@und` ..... 52:143  
 26:261, 26:274, 26:281, 26:288,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

- \unquote@name ..... 20:475, 20:481, 20:498, 52:349
- \unrestored@protected@xdef 06:357,  
45:458, 45:526, 45:542, 45:553,  
48:253, 49:41, 49:67, 49:90, 49:123
- \unskip ..... 1027
- \update@series@target@value ....  
..... 29:119,  
29:174, 29:195, 29:245, 29:260, 29:291
- \update@ucllc@with@cyrillic .....  
.. 21:1529, 21:1557, 21:1591, 21:1599
- \upper@bound .....  
..... 26:400, 26:401, 26:402, 26:415
- \use@mathgroup ... 24:692, 24:710,  
24:712, 26:300, 28:64, 28:93, 28:711,  
28:813, 28:816, 28:1283, 28:1307, 1305
- \UTF@two@octets@noexpand ..... 1372
- \UTFviii@four@octets .....  
..... 57:410, 57:415, 57:421
- \UTFviii@four@octets@@ 57:410, 57:421
- \UTFviii@four@octets@combine 57:445
- \UTFviii@four@octets@noexpand 57:451
- \UTFviii@four@octets@string . 57:448
- \UTFviii@invalid ..... 57:349, 57:442
- \UTFviii@invalid@err .....  
..... 57:407, 57:412, 57:418
- \UTFviii@invalid@err@@ 57:407, 57:418
- \UTFviii@three@octets .....  
..... 57:409, 57:414, 57:420
- \UTFviii@three@octets@@ 57:409, 57:420
- \UTFviii@three@octets@combine 57:444
- \UTFviii@three@octets@noexpand 57:450
- \UTFviii@three@octets@string 57:447
- \UTFviii@two@octets .....  
..... 57:408, 57:413, 57:419
- \UTFviii@two@octets@@ 57:408, 57:419
- \UTFviii@two@octets@combine . 57:443
- \UTFviii@two@octets@noexpand 57:449
- \UTFviii@two@octets@string .. 57:446
- \UTFviii@undefined@err .....  
..... 57:406, 57:411, 57:417
- \UTFviii@undefined@err@@ .....  
..... 57:406, 57:417
- \v@false ..... 38:82
- \v@true ..... 38:81, 38:83
- \vbox ..... 1027
- \ver@... ..... 476
- \ver@@... ..... 476
- \ver@{file}.<ext> ..... 1078
- \verb@balance@group ..... 37:656,  
37:658, 37:673, 37:675, 37:687,  
37:689, 37:702, 37:704, 37:710, 37:711
- \verb@egroup ..... 37:656,  
37:659, 37:673, 37:676, 37:687,  
37:690, 37:702, 37:705, 37:711, 37:715
- \verb@eol@error 37:712, 37:724, 37:734
- \verbatim@font ..... 37:544,  
37:565, 37:573, 37:725, 37:735, 1339
- \verbatim@nolig@list . 37:740, 37:746
- \verbatim@out ..... 1346
- \version@elt ..... 28:19,  
28:32, 28:33, 28:503, 28:504, 28:563,  
28:593, 28:704, 28:742, 28:834, 28:1263
- \version@list .....  
..... 28:17, 28:22, 28:33, 28:496,  
28:504, 28:568, 28:599, 28:638,  
28:709, 28:754, 28:784, 28:839, 28:1276
- \vgl@ ..... 02:376, 02:377
- \voidb@x .. 23:23, 23:29, 02:181, 02:407
- \vsplit ..... 1026
- \warn@rel@i 27:5, 27:25, 27:29, 27:81,  
27:85, 27:90, 27:95, 27:119, 27:140
- \wrong@fontshape . 24:473, 24:610, 1304
- \x@protect .. 06:335, 06:346, 06:397,  
06:435, 06:463, 06:669, 06:689, 1330
- \xe@alloc@ ..... 57:56, 57:66
- \xe@alloc@intercharclass . 57:35, 1354
- \xe@ch@ck ..... 57:57, 57:61
- \XXX@argdef ..... 1317
- \z@ ..... 02:181, 394
- \z@skip ..... 02:181, 426
- \zap@space ..... 20:281, 20:301,  
29:629, 47:49, 50:231, 50:453,  
50:476, 50:488, 50:655, 50:779,  
50:819, 50:837, 50:848, 50:865,  
50:875, 50:892, 50:924, 50:1226, 50:1361
- \zref@labelbyprop ..... 819
- tex commands:
- \tex\_afterassignment:D .....  
..... 53:49, 53:138, 07:2812
- \tex\_aftergroup:D . 53:57, 53:144, 1148
- \tex\_currentgrouplevel:D .....  
... 10:33, 53:48, 53:56, 53:137, 53:143
- \tex\_deadcycles:D ..... 53:91
- \tex\_endlinechar:D 09:465, 07:1613,  
07:2100, 07:2202, 07:2203, 07:2213,  
07:2214, 07:2221, 07:2243, 07:2258, 169
- \tex\_escapechar:D .....  
... 09:219, 09:294, 48:119, 48:120,  
48:122, 52:212, 52:226, 07:1134,  
07:1145, 07:1353, 07:1363, 07:1612,  
07:2099, 07:2686, 07:2712, 08:1181, 185
- \tex\_everypar:D .....  
.. 16:20, 16:24, 16:29, 16:53, 16:57,  
16:61, 16:76, 16:76, 16:116, 16:118,  
16:128, 16:129, 16:180, 16:181, 421

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

`\tex_gdef:D` ..... 09:209, 09:284, 326  
`\tex_hskip:D` ..... 16:102  
`\tex_ignoreprimitiverror:D` ....  
    ..... 48:101, 48:104, 48:105, 48:108  
`\tex_immediate:D` ..... 53:482  
`\tex_indent:D` ..... 16:123  
`\tex_interactionmode:D` .....  
    ..... 48:117, 48:118, 48:123  
`\tex_lastnodetype:D` 16:101, 48:81, 427  
`\tex_lastxpos:D` ..... 36:244  
`\tex_lastypos:D` ..... 36:245  
`\tex_lowercase:D` .... 07:2509, 07:2692  
`\tex_marks:D` ..... 48:261  
`\tex_newlinechar:D` ..... 09:466  
`\tex_noindent:D` 16:27, 16:59, 16:133, 422  
`\tex_par:D` .....  
    ..... 16:18, 16:51, 16:104, 16:111,  
    16:135, 16:176, 16:177, 16:178, 425  
`\tex_parskip:D` ... 16:25, 16:26, 16:58  
`\tex_savepos:D` ..... 815  
`\tex_setbox:D` ... 48:124, 53:50, 53:139  
`\tex_shipout:D` . 53:126, 53:386, 53:537  
`\tex_splitbotmarks:D` .....  
    ..... 48:144, 48:175, 1030  
`\tex_splitfirstmarks:D` .....  
    ..... 48:156, 48:194, 48:203, 1030  
`\tex_splitmaxdepth:D` ..... 48:69  
`\tex_unskip:D` ..... 16:97, 48:79, 426  
`\tex_vbadness:D` ..... 48:70  
`\tex_vfuzz:D` ..... 48:71  
`\tex_vsplit:D` ..... 48:124, 1030  
`\tex_vss:D` ..... 53:334  
`\tex_write:D` ..... 53:482  
`\tex_xdef:D` ..... 09:215, 09:290, 326  
`\text` ..... 1307  
text commands:  
    `\l_text_case_exclude_arg_tl` . 57:627  
    `\text_case_switch:nnnn` ..... 57:630  
    `\text_declare_case_equivalent:Nn`  
        ..... 57:632  
    `\text_declare_lowercase_exclusion:n`  
        ..... 57:657  
    `\text_declare_lowercase_mapping:nn`  
        ..... 57:636  
    `\text_declare_lowercase_mapping:nnn`  
        ..... 57:637  
    `\text_declare_titlecase_exclusion:n`  
        ..... 57:662  
    `\text_declare_titlecase_mapping:nn`  
        ..... 57:643  
    `\text_declare_titlecase_mapping:nnn`  
        ..... 57:644  
    `\text_declare_uppercase_exclusion:n`  
        ..... 57:667  
    `\text_declare_uppercase_mapping:nn`  
        ..... 57:650  
    `\text_declare_uppercase_mapping:nnn`  
        ..... 57:651  
    `\text_lowercase:n` ..... 1373  
    `\text_titlecase_all:nn` ..... 57:609  
    `\text_titlecase_first:nn` .... 57:610  
`\textacutedbl` ..... 21:939, 21:1177,  
    33:198, 33:199, 33:685, 33:932, 33:1313  
`\textascendercompwordmark` .....  
    21:878, 33:118, 33:649, 33:915, 33:1344  
`\textasciicute` .... 21:989, 21:1138,  
    33:200, 33:201, 33:686, 33:956, 33:1332  
`\textasciibreve` .... 21:937, 21:1176,  
    33:202, 33:203, 33:687, 33:929, 33:1310  
`\textasciicaron` .... 21:938, 21:1175,  
    33:204, 33:205, 33:688, 33:930, 33:1311  
`\textasciicircum` .....  
    ..... 21:306, 21:581, 21:1112, 1357  
`\textasciidieresis` .. 21:977, 21:1125,  
    33:206, 33:207, 33:689, 33:946, 33:1329  
`\textasciigrave` .... 21:928, 21:1106,  
    33:208, 33:209, 33:690, 33:927, 33:1301  
`\textasciimacron` ... 21:984, 21:1133,  
    33:210, 33:211, 33:691, 33:951, 33:1312  
`\textasciitilde` .....  
    ..... 21:307, 21:582, 21:1117, 1341  
`\textasteriskcentered` .....  
    ... 21:287, 21:741, 21:888, 21:889,  
    21:1239, 22:255, 22:261, 33:84,  
    33:541, 33:606, 33:922, 33:1347, 1357  
`\textbackslash` .....  
    21:288, 21:583, 21:742, 21:1111, 1341  
`\textbaht` 21:963, 21:1180, 33:216, 33:217,  
    33:695, 33:1062, 33:1063, 33:1323  
`\textbar` .....  
    21:289, 21:584, 21:743, 21:1115, 1341  
`\textbardbl` ..... 21:290,  
    21:744, 21:943, 21:1194, 22:260,  
    33:91, 33:329, 33:330, 33:542,  
    33:614, 33:761, 33:935, 33:1228, 1350  
`\textbf` ..... 32:19, 36:239, 706  
`\textbigcircle` ..... 21:753,  
    21:916, 21:1256, 33:218, 33:219,  
    33:696, 33:1014, 33:1015, 33:1298, 1351  
`\textblank` ... 21:885, 21:1253, 33:309,  
    33:310, 33:749, 33:984, 33:985, 33:1235  
`\textborn` 21:929, 33:220, 33:221, 33:351,  
    33:697, 33:1020, 33:1021, 33:1302  
`\textbraceleft` ..... 21:291,  
    21:328, 21:585, 21:745, 21:1114, 1329  
`\textbraceright` ..... 21:292,  
    21:329, 21:586, 21:746, 21:1116, 1328

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=lthyphen.dtx, 57=ltfinal.dtx

- `\textbrokenbar` ..... 21:975, 21:1202, 22:257, 22:263, 33:86, 33:544, 33:608, 33:934, 33:1349, 1329
- `\textbullet` ..... 21:293, 21:747, 21:945, 21:1203, 33:85, 33:543, 33:607, 33:937, 33:1351
- `\textcapitalcompwordmark` ..... 21:877, 33:117, 33:648, 33:914, 33:1343
- `\textcelsius` ..... 21:946, 21:1222, 33:93, 33:317, 33:318, 33:616, 33:755, 33:938, 33:1229
- `\textcent` ..... 21:971, 21:1119, 33:94, 33:617, 33:941, 33:1353
- `\textcentoldstyle` ..... 21:948, 33:222, 33:223, 33:356, 33:359, 33:698, 33:1036, 33:1037, 33:1316, 775
- `\textcircled` ... 21:299, 21:303, 21:320, 21:321, 21:754, 21:917, 33:119, 33:120, 33:619, 33:635, 33:651, 33:819, 33:1084, 33:1086, 33:1337, 799
- `\textcircledP` ..... 21:982, 21:1224, 33:224, 33:225, 33:699, 33:1078, 33:1079, 33:1331
- `\textcolonmonetary` ..... 21:950, 21:1215, 33:277, 33:278, 33:729, 33:1038, 33:1039, 33:1259
- `\textcommaabove` ..... 21:373, 21:375, 21:389, 21:390, 21:480, 21:481, 21:723, 21:724, 1354
- `\textcommabelow` ..... 21:344, 21:346, 21:352, 21:353, 21:726, 21:727, 21:728, 21:729, 21:730, 21:731, 21:732, 21:733, 21:734, 21:735, 21:1276, 21:1479, 21:1480, 21:1481, 21:1482, 1354
- `\textcompsubstdefault` ..... 33:34, 33:39, 33:55, 33:582, 33:877, 1361
- `\textcompwordmark` ..... 21:310, 21:311, 21:587, 21:1182, 1361
- `\textcopyleft` ..... 21:980, 33:226, 33:227, 33:332, 33:700, 33:1076, 33:1077, 33:1330
- `\textcopyright` ..... 21:303, 21:337, 21:978, 21:1126, 33:95, 33:618, 33:947, 33:1358, 1346
- `\textcurrency` ..... 21:973, 21:1121, 33:299, 33:300, 33:742, 33:814, 33:818, 33:972, 33:973, 33:1248
- `\textdagger` ..... 21:295, 21:332, 21:749, 21:941, 21:1201, 22:256, 22:262, 33:87, 33:545, 33:609, 33:933, 33:1348, 1329
- `\textdaggerdbl` ..... 21:294, 21:333, 21:748, 21:942, 21:1202, 22:257, 22:263, 33:86, 33:544, 33:608, 33:934, 33:1349, 1329
- `\textdblhyphen` . 21:900, 33:230, 33:231, 33:333, 33:702, 33:986, 33:987, 33:1286
- `\textdblhyphenchar` ..... 21:936, 33:228, 33:229, 33:334, 33:701, 33:1032, 33:1033, 33:1309
- `\textdegree` ..... 21:985, 21:1134, 33:96, 33:620, 33:952, 33:1362
- `\textdied` 21:931, 33:232, 33:233, 33:352, 33:703, 33:1024, 33:1025, 33:1304
- `\textdiscount` ..... 21:965, 21:1214, 33:234, 33:235, 33:704, 33:1066, 33:1067, 33:1324
- `\textdiv` ..... 21:1002, 21:1159, 33:97, 33:621, 33:966, 33:1371
- `\textdivorced` ..... 21:930, 21:1259, 33:236, 33:237, 33:705, 33:1022, 33:1023, 33:1303
- `\textdollar` .... 21:275, 21:327, 21:459, 21:588, 21:822, 21:886, 21:1108, 33:78, 33:79, 33:587, 33:589, 33:920, 33:1092, 33:1094, 33:1345, 1328
- `\textdollaroldstyle` ..... 21:947, 33:238, 33:239, 33:357, 33:358, 33:706, 33:1034, 33:1035, 33:1315, 775
- `\textdong` 21:959, 21:1219, 33:279, 33:280, 33:730, 33:1056, 33:1057, 33:1262
- `\textdownarrow` ..... 21:927, 21:1234, 33:281, 33:282, 33:731, 33:1018, 33:1019, 33:1258
- `\texteightoldstyle` ..... 21:910, 33:178, 33:179, 33:348, 33:674, 33:1004, 33:1005, 33:1295
- `\textellipsis` .... 21:316, 21:341, 21:1204
- `\textemdash` .... 21:276, 21:428, 21:432, 21:589, 21:593, 21:809, 21:1186, 1328
- `\textendash` .... 21:277, 21:429, 21:431, 21:590, 21:592, 21:810, 21:1185, 1328
- `\textestimated` ..... 21:966, 21:1230, 33:293, 33:294, 33:738, 33:817, 33:970, 33:971, 33:1252
- `\texteuro` ..... 21:1000, 21:1220, 33:315, 33:316, 33:753, 33:815, 33:967, 33:968, 33:1238
- `\textexclamdown` .... 21:278, 21:433, 21:435, 21:594, 21:811, 21:1118, 1351
- `\textfiguredash` ..... 21:431, 21:592, 21:1184, 21:1190, 1367
- `\textfiveoldstyle` ..... 21:907, 33:180, 33:181, 33:345, 33:675, 33:998, 33:999, 33:1292
- `\textfloatsep` 54:1078, 54:1091, 54:2729, 54:2779, 54:2829, 54:3003, 1201

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltaloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\textflorin</code> .....	21:949, 21:1173, 33:297, 33:298, 33:741, 33:939, 33:1247	<code>\textlegacydaggerdbl</code> ....	33:553, 33:767
<code>\textfont</code> .....	26:338, 38:251	<code>\textlegacyparagraph</code> ....	33:553, 33:769
<code>\textfouroldstyle</code> .....	21:906, 33:182, 33:183, 33:344, 33:676, 33:996, 33:997, 33:1291	<code>\textlegacyperiodcentered</code>	33:553, 33:770
<code>\textfraction</code>	54:2526, 54:2529, 54:2554, 54:2557, 54:2716, 54:2997, 1347	<code>\textlegacysection</code> .....	33:553, 33:771
<code>\textfractionsolidus</code> .....	21:901, 21:1211, 33:301, 33:302, 33:744, 33:923, 33:1241, 33:1473, 777	<code>\textless</code> .....	21:300, 21:598, 21:763, 21:1109, 1334
<code>\textgravedbl</code> .....	21:940, 21:1178, 33:212, 33:213, 33:692, 33:931, 33:1314	<code>\textlira</code>	21:955, 21:1216, 33:285, 33:286, 33:733, 33:1048, 33:1049, 33:1261
<code>\textgreater</code> .....	21:301, 21:595, 21:764, 21:1110, 1341	<code>\textlnot</code> .....	21:981, 21:1131, 33:98, 33:622, 33:949, 33:1360
<code>\textguarani</code> .....	21:953, 33:240, 33:241, 33:355, 33:707, 33:1044, 33:1045, 33:1318	<code>\textlquill</code> .....	21:969, 21:1212, 33:244, 33:245, 33:709, 33:1072, 33:1073, 33:1327
<code>\textheight</code> .....	20:22, 20:23, 20:92, 20:93, 20:149, 20:150, 45:257, 45:258, 45:261, 45:287, 45:301, 53:386, 54:54, 54:230, 54:231, 54:279, 54:404, 54:452, 54:481, 54:941, 54:999, 54:1058, 54:1113, 54:1165, 57:156, 57:157, 1319	<code>\textmacron</code> .....	1348
<code>\texthorizontalbar</code> .....	21:432, 21:593, 21:1187, 21:1192, 1367	<code>\textmarried</code> .....	21:933, 21:1258, 33:246, 33:247, 33:710, 33:1028, 33:1029, 33:1306
<code>\texthyphen</code> .....	21:280, 21:438, 21:597, 21:813, 1328	<code>\textmd</code> .....	32:19
<code>\texthyphenchar</code> .....	21:279, 21:437, 21:596, 21:812, 1328	<code>\textmho</code>	21:915, 21:1229, 33:248, 33:249, 33:711, 33:1012, 33:1013, 33:1297
<code>\textindent</code> .....	1335	<code>\textminus</code> ...	21:913, 21:1235, 33:307, 33:308, 33:747, 33:924, 33:1242, 779
<code>\textinterrobang</code> .....	21:957, 21:1210, 33:313, 33:314, 33:751, 33:1052, 33:1053, 33:1236	<code>\textmu</code> .....	21:990, 21:1139, 33:305, 33:306, 33:746, 33:957, 33:1244
<code>\textinterrobangdown</code> .....	21:958, 21:1260, 33:311, 33:312, 33:750, 33:1054, 33:1055, 33:1237	<code>\textmusicalnote</code> .....	21:934, 21:1257, 33:250, 33:251, 33:712, 33:1030, 33:1031, 33:1307
<code>\textit</code> .....	32:21	<code>\textnaira</code> .....	21:952, 21:1217, 33:252, 33:253, 33:713, 33:1042, 33:1043, 33:1317
<code>\textlangle</code> .....	21:912, 21:1251, 33:273, 33:274, 33:726, 33:1008, 33:1009, 33:1265	<code>\textnineoldstyle</code> .....	21:911, 33:184, 33:185, 33:349, 33:677, 33:1006, 33:1007, 33:1296
<code>\textlbrace</code> .....	1328	<code>\textnonbreakinghyphen</code> .....	21:430, 21:591, 21:1183, 21:1188, 1367
<code>\textlbrackdbl</code> .....	21:924, 33:174, 33:175, 33:353, 33:671, 33:925, 33:1299	<code>\textnormal</code> .....	32:15
<code>\textleaf</code>	21:932, 33:242, 33:243, 33:337, 33:708, 33:1026, 33:1027, 33:1305	<code>\textnumero</code> .....	21:964, 21:1223, 33:295, 33:296, 33:739, 33:1064, 33:1065, 33:1251
<code>\textleftarrow</code>	21:883, 21:1231, 33:283, 33:284, 33:732, 33:980, 33:981, 33:1255	<code>\textogonekcentered</code> .....	21:510, 21:721, 21:722, 1351
<code>\textlegacyasteriskcentered</code> .....	33:553, 33:764	<code>\textohm</code> .....	21:923, 21:1228, 33:303, 33:304, 33:745, 33:816, 33:969, 33:1243
<code>\textlegacybardbl</code> .....	33:553, 33:765	<code>\textonehalf</code> .....	21:998, 21:1148, 33:99, 33:623, 33:963, 33:1368
<code>\textlegacybullet</code> .....	33:553, 33:766	<code>\textoneoldstyle</code>	21:903, 33:186, 33:187, 33:341, 33:678, 33:990, 33:991, 33:1288
<code>\textlegacydagger</code> .....	33:553, 33:768	<code>\textonequarter</code> .....	21:997, 21:1147, 33:100, 33:624, 33:962, 33:1367
		<code>\textonesuperior</code> .....	21:994, 21:1142, 33:101, 33:319, 33:320, 33:625, 33:756, 33:960, 33:1232

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltfigur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

- `\textopenbullet` .....  
     .. 21:967, 21:1255, 33:254, 33:255,  
     33:714, 33:1068, 33:1069, 33:1325
- `\textordfeminine` .... 21:325, 21:979,  
     21:1127, 33:102, 33:626, 33:948, 33:1359
- `\textordmasculine` ... 21:326, 21:995,  
     21:1143, 33:103, 33:628, 33:961, 33:1366
- `\TextOrMath` .....  
     ... 22:252, 22:255, 22:256, 22:257,  
     22:258, 22:259, 22:260, 22:261,  
     22:262, 22:263, 22:268, 22:275, 1353
- `\textparagraph` . 21:296, 21:330, 21:750,  
     21:991, 21:1140, 22:259, 33:88,  
     33:546, 33:610, 33:958, 33:1364, 1329
- `\textperiodcentered` .....  
     .. 21:297, 21:751, 21:992, 21:1141,  
     33:89, 33:547, 33:611, 33:959, 33:1365
- `\textpermill` ..... 1347
- `\textpertenmill` ..... 1347
- `\textpertenthousand` .....  
     ..... 21:515, 21:961, 21:1206,  
     33:270, 33:271, 33:272, 33:723,  
     33:1058, 33:1059, 33:1096, 33:1321, 772
- `\textperthousand` ..... 21:513,  
     21:944, 21:1205, 33:82, 33:83,  
     33:603, 33:936, 33:1095, 33:1350, 1347
- `\textpeso` 21:954, 21:1221, 33:256, 33:257,  
     33:715, 33:1046, 33:1047, 33:1319
- `\textpilcrow` .....  
     ... 21:962, 33:258, 33:259, 33:350,  
     33:716, 33:1060, 33:1061, 33:1322
- `\textpm` ..... 21:986,  
     21:1135, 33:104, 33:630, 33:953, 33:1363
- `\textquestiondown` ... 21:281, 21:434,  
     21:436, 21:599, 21:814, 21:1150, 1328
- `\textquotedbl` .... 21:602, 21:1107, 1328
- `\textquotedblleft` ..... 21:282,  
     21:439, 21:600, 21:815, 21:1198, 1328
- `\textquotedblright` ..... 21:283,  
     21:440, 21:601, 21:816, 21:1199, 1328
- `\textquoteleft` ..... 21:284,  
     21:441, 21:603, 21:817, 21:1195, 1328
- `\textquoteright` ..... 21:285,  
     21:442, 21:604, 21:818, 21:1196, 1328
- `\textquotesingle` ..... 21:887,  
     21:1105, 33:105, 33:631, 33:921, 33:1346
- `\textquotestraightbase` .... 21:879,  
     33:106, 33:335, 33:632, 33:916, 33:1341
- `\textquotestraightdblbase` ... 21:880,  
     33:107, 33:336, 33:633, 33:917, 33:1342
- `\textrangle` .....  
     .. 21:914, 21:1252, 33:275, 33:276,  
     33:727, 33:1010, 33:1011, 33:1266
- `\textrbrace` ..... 1328
- `\textrbrackdbl` ..... 21:925, 33:176,  
     33:177, 33:354, 33:672, 33:926, 33:1300
- `\textrecipe` .....  
     .. 21:956, 21:1225, 33:260, 33:261,  
     33:717, 33:1050, 33:1051, 33:1320
- `\textreferencemark` .....  
     .. 21:993, 21:1209, 33:262, 33:263,  
     33:718, 33:1080, 33:1081, 33:1333
- `\textregistered` .....  
     .. 21:320, 21:321, 21:983, 21:1132,  
     33:108, 33:634, 33:950, 33:1361, 1329
- `\textrightarrow` 21:884, 21:1233, 33:287,  
     33:288, 33:734, 33:982, 33:983, 33:1256
- `\textrm` ..... 32:15
- `\textrquill` .....  
     .. 21:970, 21:1213, 33:264, 33:265,  
     33:719, 33:1074, 33:1075, 33:1328
- `\textsc` ..... 32:21, 1346
- `\textsection` ..... 21:298,  
     21:331, 21:605, 21:752, 21:976,  
     21:1124, 22:258, 33:90, 33:548,  
     33:549, 33:612, 33:945, 33:1357, 1329
- `\textservicemark` .....  
     .. 21:968, 21:1226, 33:266, 33:267,  
     33:720, 33:1070, 33:1071, 33:1326
- `\textsevenoldstyle` .....  
     ... 21:909, 33:188, 33:189, 33:347,  
     33:679, 33:1002, 33:1003, 33:1294
- `\textsf` ..... 32:15
- `\textsixoldstyle` .....  
     ... 21:908, 33:190, 33:191, 33:346,  
     33:680, 33:1000, 33:1001, 33:1293
- `\textsl` ..... 32:21
- `\textssc` ..... 25:2924, 32:25
- `\textsterling` .. 21:286, 21:339, 21:466,  
     21:606, 21:829, 21:972, 21:1120,  
     33:80, 33:81, 33:588, 33:596,  
     33:942, 33:1091, 33:1093, 33:1354, 1328
- `\textstyle` ..... 19:15, 30:480, 38:63
- `\textsubscript` ..... 45:419
- `\textsuperscript` 21:323, 21:325, 21:326,  
     33:627, 33:629, 33:643, 45:402, 1336
- `\textsurd` 21:996, 21:1250, 33:268, 33:269,  
     33:721, 33:1082, 33:1083, 33:1334
- `\textsw` ..... 25:2919, 32:25
- `\TextSymbolUnavailable` 21:3, 21:782, 1341
- `\textthreeoldstyle` .....  
     ..... 21:905, 33:192, 33:193,  
     33:343, 33:681, 33:994, 33:995, 33:1290
- `\textthreequarters` ..... 21:999,  
     21:1149, 33:110, 33:639, 33:964, 33:1369
- `\textthreequartersemdash` .....  
     ... 21:882, 33:109, 33:321, 33:322,  
     33:339, 33:638, 33:757, 33:919, 33:1227

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\textthreesuperior</code> .....	<code>\thempfootnote</code> .....
.. 21:988, 21:1137, 33:111, 33:323, 33:324, 33:640, 33:758, 33:955, 33:1231	40:454, <a href="#">45:398</a>
<code>\texttildelow</code> .....	<code>\thepage</code> .. 20:213, 20:226, 34:6, 35:18, 35:35, 35:52, 35:106, 35:174, 36:211, 36:223, 36:228, 36:235, 44:164, 44:171, 44:177, 46:15, 46:32, 47:43, 49:14, 54:249, 54:280, 54:2403, <a href="#">1160</a>
33:214, 33:215, 33:693, 33:928, 33:1308	<code>\Theta</code> .....
<code>\texttimes</code> .....	30:310
21:1153, 33:112, 33:641, 33:965, 33:1370	<code>\theta</code> .....
<code>\texttrademark</code> 21:323, 21:960, 21:1227, 33:113, 33:642, 33:940, 33:1352, <a href="#">1341</a>	30:286
<code>\textttt</code> .....	<code>\thetotalpages</code> .....
<a href="#">32:15</a>	53:350, 53:448, <a href="#">1160</a>
<code>\texttwelveudash</code> .....	<code>\thicklines</code> .....
.. 21:881, 33:114, 33:325, 33:326, 33:338, 33:644, 33:759, 33:918, 33:1226	<a href="#">42:124</a>
<code>\texttwooldstyle</code> 21:904, 33:194, 33:195, 33:342, 33:682, 33:992, 33:993, 33:1289	<code>\thickmuskip</code> 30:657, 38:228, 38:230, 38:243
<code>\texttwosuperior</code> .....	<code>\thickspace</code> .....
.. 21:987, 21:1136, 33:115, 33:327, 33:328, 33:645, 33:760, 33:954, 33:1230	38:214
<code>\textulc</code> .....	<code>\thinlines</code> .....
<a href="#">25:2914</a> , <a href="#">32:25</a>	<a href="#">42:124</a> , <a href="#">42:815</a> , <a href="#">42:832</a>
<code>\textunderline</code> .....	<code>\thinmuskip</code> .....
<a href="#">1328</a>	30:655, 38:220, 38:222, 38:238, 38:244
<code>\textunderscore</code> .....	<code>\thinspace</code> .....
21:308, 21:335, 21:607, 21:1113, <a href="#">1346</a>	18:536, 18:542, 18:543, 38:189, <a href="#">38:214</a> , 38:251, <a href="#">1362</a>
<code>\textup</code> .....	<code>\thispagestyle</code> .....
<a href="#">32:21</a> , <a href="#">630</a>	<a href="#">49:6</a>
<code>\textuparrow</code> .....	<code>\tilde</code> .....
.. 21:926, 21:1232, 33:289, 33:290, 33:735, 33:1016, 33:1017, 33:1257	18:472, 18:483, 30:530
<code>\textvisiblespace</code> .....	<code>\time</code> .....
.. 21:312, 21:608, 21:1254, <a href="#">1337</a>	01:163, 01:167, 02:258
<code>\textwidth</code> .....	<code>\times</code> .....
20:24, 20:94, 20:151, 40:444, 45:266, 54:55, 54:123, 54:206, 54:223, 54:919, 54:934, 54:984, 54:994, 54:1043, 54:1053, 54:2883, 54:2926, 54:2955, 57:157, <a href="#">1319</a>	30:407
<code>\textwon</code> 21:951, 21:1218, 33:291, 33:292, 33:736, 33:1040, 33:1041, 33:1260	<code>\title</code> .....
<code>\textyen</code> .....	969
21:1122, 33:116, 33:646, 33:943, 33:1355	<code>\title</code> .....
<code>\textzerooldstyle</code> .....	44:6, <a href="#">44:7</a> , 44:21, 44:23, 44:31
.. 21:902, 33:196, 33:197, 33:340, 33:683, 33:988, 33:989, 33:1287	<code>title</code> .....
<code>\TH</code> .....	<a href="#">36:238</a> , <a href="#">819</a>
21:558, 21:1155, 57:671, <a href="#">1324</a>	tl commands:
<code>\th</code> .....	<code>\c_empty_tl</code> ... 08:2237, 11:1235, 08:65
21:609, 21:1161, 57:671, <a href="#">1324</a>	<code>\c_novaluel_tl</code> .....
<code>\thanks</code> .....	07:530, 07:935, 07:1002, 07:1063, 07:1546, 07:1824, 07:1961, 07:2066, 07:2227, 07:2234, 07:2305, 07:2357, 07:2438, 07:2465, 07:2547, <a href="#">242</a>
969	<code>\c_space_tl</code> . 09:382, 11:551, 11:555, 11:598, 11:819, 11:822, 16:42, 16:73, 16:82, 52:553, 52:556, 07:27, 07:124, 07:140, 07:143, 07:157, 07:168, 07:169, 07:185, 07:193, 07:203, 07:206, 07:208, 07:210, 07:212, 07:220, 07:226, 07:294, 07:295, 57:604, 57:611, 57:616, 57:621, 07:1189, 07:1204, 07:1236, 07:1237, 07:1414, 07:1421, 07:1554, 07:2827
<code>\thanks</code> .....	<code>\tl_clear:N</code> .....
<a href="#">44:10</a> , <a href="#">44:26</a> , <a href="#">1330</a>	09:213, 09:288, 11:285, 11:324, 11:737, 07:309, 07:354, 07:383, 07:451, 07:452, 07:672, 07:790, 07:803, 07:804, 07:805, 07:807, 07:987, 07:1055, 07:1249, 07:1489, 07:1490, 07:1562, 07:1583, 07:1611, 07:1872, 07:1873, 07:1889, 07:2101, 07:2497
<code>\the</code> .....	<code>\tl_const:Nn</code> .....
424	09:11, 09:12, 11:9, 11:10, 11:11, 11:12, 11:13, 11:14, 11:15, 48:62, 53:311, 53:316, 07:1512, 07:2847, 08:35, 08:36, 08:110,
<code>\the...</code> .....	
<a href="#">1378</a>	
<code>\the#1</code> .....	
528	
<code>thebibliography (env.)</code> .....	
1009	
<code>\theenum</code> .....	
886	
<code>\theequation</code> .....	
38:410, 38:426, 38:455, 38:550, 38:611	
<code>\thefootnote</code> <a href="#">45:396</a> , 45:521, 45:526, 45:546	
<code>\thempfn</code> .....	
40:454, <a href="#">45:453</a> , <a href="#">45:458</a> , <a href="#">45:537</a> , <a href="#">45:542</a> , <a href="#">45:545</a>	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltthyphen.dtx, 57=ltfinal.dtx

08:113, 08:936, 08:937, 08:939,  
 08:940, 08:941, 08:942, 08:945,  
 08:946, 08:948, 08:969, 08:970, 08:1314  
 \tl\_count:N ... 52:546, 07:401, 07:2521  
 \tl\_count:n .....  
 .. 07:607, 07:612, 07:890, 07:1008,  
 07:1062, 07:1289, 07:1439, 07:1447  
 \tl\_gclear:N ..... 48:163, 48:164, 290  
 \tl\_gclear\_new:N . 36:25, 36:145, 08:270  
 \tl\_gput\_left:Nn ..... 51:267  
 \tl\_gput\_right:Nn ..... 16:38,  
 16:69, 16:78, 28:336, 48:188, 48:199,  
 07:1164, 07:1482, 07:1484, 08:455, 273  
 \tl\_gremove\_once:Nn .... 08:37, 08:37  
 \tl\_gset:Nn .....  
 ..... 09:141, 16:15, 16:48, 17:39,  
 17:43, 28:285, 28:333, 36:26, 36:138,  
 36:146, 48:143, 48:154, 48:174,  
 48:238, 48:239, 48:240, 52:51,  
 55:288, 55:289, 55:309, 55:313,  
 55:357, 55:365, 55:411, 08:182,  
 08:194, 08:301, 08:319, 08:417,  
 08:429, 08:445, 08:484, 08:766,  
 08:820, 08:854, 08:858, 08:881, 08:885  
 \tl\_gset\_eq:NN .....  
 48:58, 48:59, 48:60, 48:141, 48:142,  
 48:147, 48:149, 48:153, 48:216,  
 48:218, 48:220, 48:227, 48:229,  
 48:231, 48:469, 48:471, 48:473,  
 48:475, 48:481, 48:485, 48:488,  
 55:388, 55:389, 08:63, 08:452, 08:463  
 \tl\_head:N ..... 07:2749  
 \tl\_head:n ..... 07:11, 07:814  
 \tl\_head:w ..... 11:80, 11:93  
 \tl\_if\_blank:nTF .. 11:332, 11:336,  
 11:443, 11:446, 20:540, 55:169,  
 57:584, 07:603, 07:1623, 07:1747,  
 07:1855, 07:2319, 07:2360, 07:2571,  
 07:3302, 07:3303, 07:3304, 08:435  
 \tl\_if\_blank\_p:n ..... 07:120  
 \tl\_if\_empty:N ..... 297  
 \tl\_if\_empty:NNTF ..... 08:2015,  
 08:2023, 08:2220, 08:2222, 11:246,  
 11:259, 11:312, 48:145, 48:176,  
 48:264, 07:320, 07:321, 07:470,  
 07:723, 07:1496, 08:235, 08:255,  
 08:366, 08:368, 08:654, 08:1055, 08:1445  
 \tl\_if\_empty:nTF .....  
 ..... 08:2546, 09:137, 09:322,  
 09:341, 11:1185, 11:1190, 11:1233,  
 11:1243, 49:26, 49:30, 49:45, 49:55,  
 52:40, 52:46, 52:58, 52:107, 52:114,  
 52:116, 52:118, 52:416, 07:1648,  
 07:2316, 07:2687, 07:2713, 07:2748,  
 07:2982, 07:3072, 08:338, 08:353,  
 08:356, 08:571, 08:841, 08:873, 08:927  
 \tl\_if\_empty\_p:N .....  
 08:2496, 08:2497, 53:68, 53:114, 53:383  
 \tl\_if\_empty\_p:n ..... 08:904  
 \tl\_if\_eq:NNTF ..... 48:293,  
 48:301, 48:308, 48:377, 48:478, 07:343  
 \tl\_if\_eq:NnTF ..... 28:296, 36:151  
 \tl\_if\_eq:nnTF 07:735, 07:1021, 07:2692  
 \tl\_if\_exist:N ..... 291  
 \tl\_if\_exist:NNTF .....  
 ..... 08:2265, 08:2285, 08:2371,  
 08:2519, 08:2560, 36:106, 36:111,  
 36:130, 36:172, 36:187, 48:375,  
 07:1497, 08:135, 08:233, 08:253, 08:1292  
 \tl\_if\_exist\_p:N ..... 08:276  
 \tl\_if\_head\_eq\_charcode:nNTF ...  
 ..... 20:542, 20:547  
 \tl\_if\_head\_eq\_meaning:nNTF 07:2823  
 \tl\_if\_head\_is\_group:nTF .....  
 ... 09:349, 07:2569, 07:2613, 07:2645  
 \tl\_if\_head\_is\_N\_type:nTF 09:346,  
 07:2581, 07:2593, 07:2610, 07:2642  
 \tl\_if\_in:NnTF ..... 07:1886  
 \tl\_if\_in:nnTF .....  
 ..... 11:281, 11:305, 11:327,  
 11:769, 07:619, 07:1852, 07:1878, 176  
 \tl\_if\_noalue:nTF .....  
 ... 07:374, 07:393, 07:440, 07:991,  
 07:2389, 07:3294, 07:3295, 07:3296,  
 07:3297, 07:3298, 07:3299, 08:332  
 \tl\_if\_single:nTF .....  
 ..... 11:494, 07:2486, 07:3277  
 \tl\_if\_single\_token:nTF .....  
 . 09:332, 07:683, 07:2684, 07:3279, 198  
 \tl\_item:Nn ..... 07:2829  
 \tl\_log:n ..... 08:1838, 08:37, 08:39  
 \tl\_map\_function:nN 07:101, 07:394,  
 07:604, 07:605, 07:1006, 07:1056, 1383  
 \tl\_map\_inline:Nn ..... 07:733  
 \tl\_map\_inline:nn 07:1525, 07:1776,  
 07:1778, 07:1780, 07:1782, 07:1958  
 \tl\_map\_tokens:nn ..... 07:3318, 1383  
 \tl\_new:N ..... 09:6, 09:8,  
 09:9, 09:10, 11:19, 11:20, 11:23,  
 11:24, 11:25, 11:26, 11:27, 11:38,  
 11:1248, 16:14, 36:137, 48:55, 48:56,  
 48:57, 48:65, 48:66, 48:131, 48:211,  
 48:212, 52:8, 52:9, 52:10, 52:11,  
 52:59, 53:53, 07:12, 07:13, 53:205,  
 07:14, 07:15, 07:20, 07:24, 07:31,  
 07:32, 07:33, 07:36, 07:41, 07:42,  
 07:44, 07:45, 07:54, 07:55, 55:98,  
 55:269, 55:285, 55:286, 55:290,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=lt space.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

55:291, 55:292, 55:293, 07:1867,  
 07:1868, 07:2084, 07:2483, 07:3313,  
 08:25, 08:26, 08:27, 08:29, 08:32,  
 08:78, 08:96, 08:124, 08:138, 08:141,  
 08:165, 08:166, 08:299, 08:317,  
 08:1311, 08:1567, 08:1568, 08:1569  
 \tl\_put\_left:Nn 07:852, 07:861, 07:1581  
 \tl\_put\_right:Nn .. 09:185, 09:199,  
 09:260, 09:274, 11:300, 11:307,  
 11:801, 11:809, 11:836, 11:847,  
 11:864, 11:889, 11:896, 07:369,  
 07:395, 57:627, 07:540, 07:573,  
 07:596, 07:610, 07:627, 07:632,  
 07:765, 07:881, 07:894, 07:921,  
 07:929, 07:943, 07:945, 07:952,  
 07:980, 07:996, 07:1002, 07:1071,  
 07:1096, 07:1264, 07:1272, 07:1288,  
 07:1295, 07:1557, 07:1560, 07:1647,  
 07:1650, 07:1675, 07:1685, 07:1692,  
 07:1701, 07:1722, 07:1727, 07:1733,  
 07:1876, 07:1877, 07:1884, 07:1894,  
 07:1962, 07:1996, 07:2241, 07:2253,  
 07:2269, 07:2280, 07:2499, 07:2544  
 \tl\_replace\_all:Nnn .. 11:280, 07:2512  
 \tl\_rescan:nn .....  
 .. 09:20, 09:20, 09:480, 09:556, 09:584  
 \tl\_reverse:n ..... 07:814  
 \tl\_set:Nn ..... 08:1763,  
 08:1770, 09:183, 09:196, 09:197,  
 09:200, 09:202, 09:223, 09:258,  
 09:271, 09:272, 09:275, 09:277,  
 09:298, 09:390, 09:395, 09:477,  
 09:522, 09:553, 09:581, 11:256,  
 11:279, 11:323, 11:334, 11:338,  
 11:424, 11:550, 11:554, 11:597,  
 11:645, 11:758, 11:776, 11:907,  
 11:919, 11:941, 48:103, 48:115,  
 52:81, 52:82, 52:83, 52:84, 53:47,  
 53:136, 53:210, 53:236, 53:261,  
 53:288, 07:25, 07:92, 07:123, 07:310,  
 07:311, 07:312, 07:313, 07:341,  
 55:82, 55:270, 55:278, 55:295,  
 55:296, 55:297, 55:298, 55:339,  
 55:340, 07:392, 07:900, 07:1108,  
 07:1126, 07:1328, 07:1553, 07:1588,  
 07:1609, 07:1663, 07:1680, 07:1754,  
 07:1849, 07:1955, 07:1982, 07:1989,  
 07:2002, 07:2008, 07:2014, 07:2020,  
 07:2026, 07:2032, 07:2038, 07:2044,  
 07:2075, 07:2097, 07:2120, 07:2479,  
 07:2480, 07:2506, 07:2530, 07:2561,  
 07:2573, 07:2600, 07:2666, 07:2668,  
 07:2787, 07:2788, 08:37, 08:40,  
 08:574, 08:1165, 08:1172, 08:1176,  
 08:1576, 08:1596, 08:1597, 08:1602,  
 08:1603, 08:1618, 08:1625, 08:1627,  
 08:1658, 08:1679, 08:1680, 08:1686,  
 08:1688, 08:1707, 08:1714, 08:1716  
 \tl\_set\_eq:NN .....  
 ..... 09:214, 09:289, 11:1235,  
 48:168, 48:169, 07:331, 07:337,  
 07:345, 55:83, 55:341, 55:342,  
 07:388, 07:1582, 07:1888, 07:1961,  
 08:1606, 08:1630, 08:1691, 08:1719  
 \tl\_show:n ..... 08:1845, 08:1852,  
 08:1956, 08:2057, 07:1370, 07:1383,  
 07:1392, 07:1428, 07:1451, 08:37, 08:38  
 \tl\_tail:N ..... 07:2154  
 \tl\_to\_str:N 07:2225, 07:2232, 07:2855  
 \tl\_to\_str:n .....  
 08:2004, 08:2017, 08:2088, 08:2160,  
 08:2174, 09:130, 09:135, 09:475,  
 09:494, 09:523, 09:534, 09:570,  
 11:303, 11:425, 11:631, 11:907,  
 11:974, 11:975, 11:976, 11:985,  
 11:986, 36:10, 36:19, 36:51, 36:64,  
 36:92, 36:93, 36:100, 36:101, 36:145,  
 36:146, 36:187, 48:259, 48:274,  
 51:123, 51:152, 51:154, 52:580,  
 07:74, 07:85, 07:252, 07:256, 07:465,  
 07:473, 07:486, 07:497, 07:501,  
 07:537, 07:568, 07:649, 07:678,  
 07:686, 07:701, 07:714, 07:726,  
 07:745, 07:785, 07:786, 07:1262,  
 07:1336, 07:1342, 07:1557, 07:1561,  
 07:2226, 07:2233, 07:2433, 07:2460,  
 07:2540, 07:2541, 07:2701, 07:2705,  
 08:384, 08:535, 08:563, 08:624, 185  
 \tl\_trim\_spaces:n .....  
 ... 09:324, 11:302, 11:323, 11:335,  
 11:425, 11:449, 11:631, 11:907,  
 50:514, 51:113, 51:144, 51:179,  
 51:193, 52:41, 52:42, 07:248, 07:421,  
 07:540, 07:574, 07:1571, 07:1573,  
 07:2432, 07:2459, 07:2561, 07:3157,  
 07:3161, 07:3165, 07:3169, 08:413, 326  
 \tl\_trim\_spaces\_apply:nN . 07:683,  
 07:2564, 07:2588, 07:2678, 08:334  
 \tl\_use:N .....  
 .. 08:1829, 24:415, 28:291, 28:295,  
 28:343, 28:347, 36:94, 36:107,  
 07:1407, 07:1502, 08:1073, 08:1136  
 \l\_tmpa\_tl ..... 356  
 tl internal commands:  
 \c\_mark\_empty\_tl .....  
 . 48:54, 48:228, 48:230, 48:232, 48:377  
 \g\_mark\_first\_marks\_tl .....  
 . 48:163, 48:168, 48:199, 48:211, 1032

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

- \g\_\_mark\_last\_marks\_tl ..... 07:74, 07:82, 07:85, 07:421, 07:830,  
48:164, 48:169, 48:188, 48:211, 1032 07:1103, 07:1257, 07:1406, 07:1430,
- \g\_\_mark\_new\_top\_tl ..... 07:1453, 07:1919, 07:2065, 07:2260,  
48:63, 48:141, 48:142, 48:148, 48:150 07:2272, 07:2432, 07:2459, 07:2688,
- \l\_\_mark\_saved\_parameters\_tl ... 07:2701, 07:2705, 07:2714, 07:3124,  
48:103, 48:110, 48:115, 48:128, 48:131 07:3125, 07:3138, 07:3139, 07:3243,  
07:3244, 07:3257, 07:3258, 08:381, 185
- \g\_\_mark\_tmp\_tl ..... 48:63,  
48:143, 48:145, 48:153, 48:174,  
48:176, 48:186, 48:189, 48:253,  
48:259, 48:264, 48:266, 48:267, 1032 \toks ..... 04:36, 16:40,  
16:71, 16:80, 28:740, 28:741, 28:751,  
28:760, 02:31, 02:59, 57:731, 424
- \tmSPACE ..... 38:214, 859 \toksdef ..... 04:230, 02:46, 02:59
- \to ..... 30:451, 30:453 \tokszero ..... 04:230
- toc/contentsline/after (tag socket) 55:190 \tolerance ..... 24:745,  
24:791, 24:806, 49:131, 49:139, 02:187
- toc/contentsline/before (tag socket) 55:190 \top ..... 30:331
- toc/leaders/after (tag socket) ... 55:194 \topfigrule ..... 54:1077, 54:3025
- toc/leaders/before (tag socket) .. 55:194 \topfraction ..... 45:273, 54:2991
- toc/starttoc/after (tag socket) .. 55:192 \topmargin .. 54:47, 54:910, 54:978, 54:1037
- toc/starttoc/before (tag socket) .. 55:192 \TopMark ..... 48:402, 48:524, 1016
- \today ..... 01:168,  
01:172, 01:180, 01:183, 44:33, 1299 \topmark ..... 54:2912, 54:2921, 1014
- token commands: \topsep ..... 38:617, 39:1, 39:59, 873
- \c\_math\_subscript\_token .... 07:1840 \topskip ..... 20:59,  
20:128, 20:183, 54:106, 02:293, 1338
- \c\_math\_toggle\_token ..... 07:1838 \totalheight ..... 40:33, 40:34, 40:35
- \c\_space\_token ..... 07:1673, 07:2777 totalpages ..... 1144
- \token\_case\_charcode:NnTF ..... trace commands:
- ..... 07:1669, 07:1708 trace\_stack\_levels ..... 57:96
- \token\_if\_active:NnTF 07:2255, 07:2271 \tracefloats ..... 54:2505
- \token\_if\_cs:NnTF ..... 07:2488, 186 \tracefloatsoff ..... 54:2505
- \token\_if\_eq\_catcode:NnTF ..... \tracefloatvals ..... 54:2505, 1246
- ..... 09:334, 07:1906 \tracemath ..... 410
- \token\_if\_eq\_charcode:NnTF ..... \tracemath ..... 410
- ... 07:416, 07:2142, 07:2174, 07:2185 \tracingall ..... 02:432, 410
- \token\_if\_eq\_meaning:NnTF 09:204, \tracingassigns .....  
09:279, 09:481, 52:454, 52:466, 02:449, 02:483, 02:500, 02:540
- 07:692, 07:695, 07:703, 07:1329, \tracingcommands 02:222, 02:447, 02:465,  
07:1833, 07:2791, 07:3281, 07:3283 02:481, 02:490, 02:503, 02:526, 02:543
- \token\_if\_long\_macro\_p:N ..... \tracingfonts ..... 26:17, 26:55,  
07:1423, 07:2841 26:59, 26:87, 26:119, 26:154, 26:195,
- \token\_if\_macro:NnTF ..... 26:225, 26:239, 26:255, 26:261,  
09:101, 08:1221, 08:1247, 320 26:274, 26:281, 26:288, 26:293,  
07:2634, 07:2656 26:302, 26:315, 26:323, 26:326, 1305
- \token\_if\_protected\_long\_macro\_p:N ..... \tracinggroups .....  
07:1424, 07:1433, 07:2842 ..... 02:439, 02:474, 02:512, 02:551
- \token\_if\_protected\_macro:NnTF ... \tracingifs .. 02:440, 02:475, 02:511, 02:550
- ..... 07:1192, 07:1217, 07:1384 \tracinglostchars ... 24:741, 24:755,  
07:1432 02:216, 02:219, 02:433, 02:460,
- \token\_if\_protected\_macro\_p:N 07:1432 02:472, 02:491, 02:534, 02:554, 22
- \token\_to\_meaning:N 09:97, 09:478, \tracingmacros .. 02:211, 02:446, 02:464,  
09:490, 09:554, 09:582, 16:41, 16:72 02:480, 02:492, 02:514, 02:533, 02:553
- \token\_to\_str:N .... 09:96, 09:97, \tracingnesting .....  
09:119, 09:540, 09:547, 09:575, ..... 02:442, 02:477, 02:509, 02:548
- 09:578, 11:280, 11:281, 11:298, \tracingnone ..... 02:496, 1378
- 11:305, 11:308, 11:315, 11:642, \tracingoff ..... 26:119, 26:323
- 11:1110, 26:348, 36:57, 52:241,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
06=ltdefns.dtx, 07=ltcmd.dtx, 08=lt hooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
16=ltpara.dtx, 17=ltmeta.dtx, 18=ltSPACE.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
56=ltthyphen.dtx, 57=ltfinal.dtx

- `\tracingon` ..... 26:120, 26:324, 1306  
`\tracingonline` 02:572, 24:754, 54:2491,  
 02:210, 02:427, 02:502, 02:525, 02:542  
`\tracingoutput` ..... 02:569,  
 02:215, 02:428, 02:506, 02:529, 02:546  
`\tracingpages` .. 02:214, 02:437, 02:459,  
 02:471, 02:491, 02:515, 02:535, 02:555  
`\tracingparagraphs` .....  
 ..... 02:213, 02:438, 02:461,  
 02:473, 02:492, 02:513, 02:532, 02:552  
`\tracingrestores` 02:223, 02:448, 02:466,  
 02:482, 02:492, 02:501, 02:531, 02:541  
`\tracingscantokens` ..... 02:441,  
 02:456, 02:476, 02:510, 02:523, 02:549  
`\tracingstacklevels` .....  
 ... 02:224, 02:433, 02:444, 02:508, 22  
`\tracingstats` .....  
 .... 57:2, 02:212, 02:436, 02:458,  
 02:470, 02:490, 02:516, 02:536, 02:556  
`\triangle` ..... 30:333  
`\triangleleft` ..... 30:369, 30:493  
`\triangleright` ..... 30:370, 30:493  
`\TrimSpaces` ..... 07:3314  
`trivlist (env.)` ..... 39:89  
`\trivlist` ..... 37:446, 37:496, 37:498,  
 37:529, 37:551, 38:601, 39:89,  
 41:78, 43:52, 43:54, 43:59, 43:61, 880  
 TS1 commands:  
`\TS1:?` ..... 797  
`\TS1:<family>` ..... 797  
`\tt` ..... 1310  
`\ttdefault` 29:13, 29:309, 29:479, 29:496,  
 29:520, 29:539, 29:567, 30:62, 707  
`\ttfamily` ..... 29:11,  
 29:12, 29:489, 29:537, 29:538,  
 29:565, 29:566, 32:17, 37:573, 228  
`ttfamily` ..... 29:499  
`\ttsubstdefault` 30:20, 30:32, 33:32, 33:53  
`\twocolumn` ..... 54:204, 1345  
`\twocolumn[...]` ..... 1339  
`\twocolumn[]` ..... 458  
`\typein` ..... 80, 80  
`\typein` ..... 06:31, 33:1584, 33:1589  
`\typeout` ..... 80  
`\typeout` .. 03:21, 03:38, 01:100, 10:59,  
 10:62, 10:64, 10:66, 10:68, 10:71,  
 10:74, 14:74, 20:201, 20:692, 20:693,  
 20:699, 20:733, 20:779, 20:793,  
 20:814, 01:156, 24:463, 01:181,  
 01:183, 01:195, 25:2866, 01:210,  
 01:217, 29:139, 01:228, 29:646,  
 29:873, 29:883, 29:893, 30:9, 30:136,  
 06:3, 01:241, 06:36, 06:43, 01:254,  
 33:1180, 33:1217, 33:1224, 33:1377,  
 33:1380, 33:1383, 33:1581, 33:1582,  
 33:1583, 33:1586, 33:1587, 33:1588,  
 33:1593, 33:1597, 01:267, 01:305,  
 46:8, 46:25, 48:360, 48:379, 06:706,  
 06:707, 06:741, 06:742, 06:747,  
 50:384, 50:400, 50:412, 06:801,  
 06:802, 06:817, 06:819, 50:1597,  
 50:1804, 50:1807, 53:104, 53:115,  
 53:148, 54:590, 54:2494, 54:2506,  
 55:301, 57:276, 57:685, 57:692,  
 57:704, 57:705, 57:713, 01:57, 626  
`\typeoutdetails` .... 33:1180, 33:1181,  
 33:1184, 33:1190, 33:1192, 33:1196,  
 33:1197, 33:1203, 33:1221, 33:1222,  
 33:1376, 33:1591, 33:1593, 33:1597  
 U  
`\u` ..... 21:257, 21:407, 21:495, 21:612,  
 21:619, 21:639, 21:646, 21:778,  
 21:1266, 21:1341, 21:1342, 21:1357,  
 21:1358, 21:1367, 21:1368, 21:1381,  
 21:1382, 21:1383, 21:1407, 21:1408,  
 21:1433, 21:1434, 33:127, 33:158  
`\uccode` ..... 57:240, 57:248, 57:255,  
 57:257, 57:260, 57:262, 57:535,  
 57:543, 57:550, 57:552, 57:555, 57:557  
`\Ucharcat` ..... 29:707  
`\uchyph` ..... 02:245  
`\ulcdefault` ..... 25:2914, 25:2936  
`\ulcshape` .....  
 25:2911, 25:2914, 25:2932, 25:2935,  
 25:3218, 25:3219, 29:632, 32:29, 628  
`\Umathcode` ..... 04:30, 18:552, 30:15,  
 30:55, 30:62, 30:77, 33:123, 33:331,  
 37:579, 57:160, 57:351, 57:529, 02:89  
`\unboldmath` ..... 29:698  
`\UndeclareTextCommand` .....  
 21:209, 33:79, 33:81, 33:83, 33:272,  
 33:549, 33:1091, 33:1092, 33:1093,  
 33:1094, 33:1095, 33:1096, 1347  
`\undefined` ..... 22:123, 22:124,  
 22:175, 22:176, 22:177, 22:222,  
 22:223, 22:224, 01:12, 01:14, 29:784,  
 30:127, 30:128, 35:40, 35:41, 35:57,  
 35:58, 35:59, 35:60, 01:20, 57:168,  
 57:180, 57:181, 57:201, 01:41, 1340  
`\undefinedpagestyle` ..... 49:4, 49:8  
`\underbar` ..... 06:985, 06:1006, 02:397  
`\underbrace` ..... 30:551  
`\underline` ..... 890  
`\underline` ..... 40:551, 40:552, 02:397  
`\underscore` ..... 1346  
`\unexpanded` ..... 22:138, 22:189,  
 32:47, 37:281, 37:317, 06:724,

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx

06:735, 50:832, 50:1632, 50:1634, 322	\upbracefill . . . . . 30:554, 30:571
\unhbox . . . . . 1307	\updefault . . . . . 25:3208, 29:22, 30:106,
\unhcopy . . . . . 41:345, 42:741, 42:797, 02:399	30:113, 30:114, 30:122, 30:124, 1361
\unicodedataline . . . . .	\Updownarrow . . . . . 30:599
04:143, 04:146, 04:160, 04:161, 04:162	\updownarrow . . . . . 30:593
\UnicodeEncodingName . . . . .	\uplus . . . . . 30:389
. . . . . 21:1005, 21:1011, 21:1062,	\uppercase . . . . . 1320
21:1068, 21:1072, 21:1083, 21:1087,	\upshape . . . . . 21:463, 21:756,
21:1103, 21:1104, 33:340, 33:341,	21:826, 21:919, 25:3206, 25:3207,
33:342, 33:343, 33:344, 33:345,	29:20, 29:21, 29:632, 29:643,
33:346, 33:347, 33:348, 33:349,	29:676, 29:734, 32:24, 33:593, 630
33:350, 33:351, 33:352, 33:353,	\Upsilon . . . . . 30:315
33:354, 33:355, 33:356, 33:357, 512	\upsilon . . . . . 30:297
\UnicodeFontFile . . . . . 21:1060	use commands:
\UnicodeFontName . . . . . 21:1061	\use:N . . . . .
\UnicodeFontTeXLigatures 21:1017, 21:1057	08:1779, 08:1780, 08:1820, 08:2332,
\unicoderead . . . . . 04:143,	08:2402, 08:2418, 10:148, 10:155,
04:157, 04:158, 04:159, 04:160, 04:165	11:274, 11:497, 11:659, 11:787,
uninstall . . . . . 04:999	11:936, 28:300, 28:350, 05:185,
\unitlength . . . . . 40:74, 40:85,	36:73, 48:126, 48:144, 48:157,
40:94, 40:104, 42:5, 42:29, 42:30,	48:175, 48:195, 48:204, 48:261,
42:32, 42:34, 42:42, 42:43, 42:44,	48:380, 48:381, 48:382, 52:442,
42:45, 42:60, 42:63, 42:73, 42:74,	52:446, 52:448, 52:465, 57:595,
42:84, 42:85, 42:93, 42:94, 42:107,	07:826, 07:1499, 07:1835, 08:1646, 349
42:108, 42:119, 42:164, 42:176,	\use:n . . . . . 08:2097,
42:241, 42:256, 42:316, 42:318,	08:2131, 08:2384, 08:2390, 08:2399,
42:332, 42:340, 42:342, 42:357,	09:122, 09:189, 09:192, 09:220,
42:375, 42:377, 42:392, 42:397,	09:229, 09:264, 09:267, 09:295,
42:399, 42:414, 42:417, 42:422,	09:301, 09:367, 09:401, 09:424,
42:479, 42:480, 42:507, 42:508,	09:443, 09:472, 09:502, 09:524,
42:536, 42:537, 42:611, 42:627,	09:531, 09:567, 11:295, 11:339,
42:647, 42:653, 42:689, 42:690,	11:373, 11:628, 11:639, 20:542,
42:692, 42:693, 42:696, 42:697,	48:125, 51:212, 07:190, 07:693,
42:699, 42:700, 42:711, 42:712,	07:696, 07:888, 07:1132, 07:1259,
42:714, 42:715, 42:717, 42:718,	07:1351, 07:1460, 07:1641, 07:1657,
42:720, 42:721, 42:749, 42:750,	07:1800, 07:2621, 07:2663, 07:3278,
42:752, 42:753, 42:756, 42:757,	07:3280, 07:3285, 08:238, 08:388,
42:759, 42:760, 42:771, 42:773,	08:511, 08:566, 08:1169, 08:1644, 470
42:775, 42:777, 53:328, 57:149, 1141	\use:nn . . . . . 08:2147,
\unkern . . . . . 24:774	08:2722, 09:234, 09:306, 08:1750
\unless . . . . . 04:151, 04:159, 04:161	\use:nnn . . . . .
\unlhd . . . . . 29:860	07:3124, 07:3138, 07:3243, 07:3257, 197
\unpenalty . . . . . 24:777,	\use_i:nn . . . . . 08:2249, 08:2594,
24:781, 32:116, 37:545, 37:567, 421	07:983, 07:1877, 07:2716, 07:2769, 356
\unrhd . . . . . 29:862	\use_i:nnn . . . . . 08:2096, 07:2694, 271
\unsetattribute . . . . . 41	\use_i:nnnn . . . . . 09:365, 328
\unsetattribute . . . . . 04:82, 04:240	\use_i_delimit_by_q_recursion_-
\unskip . . . . . 421	stop:nw . . . . . 09:431, 09:450
\UnusedTemplateKeys . . . . .	\use_i_delimit_by_q_stop:nw . 07:430
. . . . . 11:1235, 11:1238, 11:1248, 356	\use_ii:nn . . . . . 08:2600,
\unvbox . . . . . 1181	09:74, 09:156, 55:38, 55:48, 07:1580,
\unvcopy . . . . . 38:193, 1022	07:1798, 07:2059, 07:2296, 07:2309,
\Uparrow . . . . . 30:595	07:2348, 07:2366, 07:2391, 07:2424,
\uparrow . . . . . 30:589	07:2451, 07:2715, 07:3289, 08:654, 176

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

<code>\use_ii:nnn</code> .....	50:1011, 50:1015, 50:1039, 50:1043,
.. 07:1860, 07:2365, 07:2698, 07:3282	52:170, 52:171, 52:174, 52:175,
<code>\use_ii:nnnn</code> .....	53:118, 53:170, 53:388, 54:491,
<code>\use_ii_i:nn</code> .....	54:505, 54:848, 54:879, 54:943, 220
<code>\use_ii_iii:nnn</code> .....	<code>\UseHookWithArguments</code> .....
..... 52:216, 52:230, 52:242, 52:242	08:2827,
<code>\use_iii:nn</code> .....	09:236, 09:540, 09:547, 35:104, 315
..... 271	<code>\UseInstance</code> . 11:486, 11:1103, 11:1193, 360
<code>\use_iii:nnn</code> .....	<code>\UseLegacyTextSymbols</code> ... 33:540, 33:763
52:47, 07:2325,	<code>\UseName</code> .....
07:2693, 07:2696, 07:2768, 07:3284	76
<code>\use_iii:nnnn</code> .....	<code>\UseName</code> .....
07:2324	05:181, 05:199
<code>\use_iv:nnnn</code> .....	<code>\UseOneTimeHook</code> 08:2827, 08:2946, 20:15,
07:416, 07:422	20:57, 20:70, 20:336, 20:340, 20:345,
<code>\use_none:n</code> .....	20:358, 20:397, 20:399, 20:402,
08:2251,	37:14, 37:19, 37:31, 37:32, 37:34,
08:2340, 09:372, 09:431, 09:450,	37:82, 37:86, 37:96, 37:97, 37:99,
10:7, 10:8, 11:654, 48:340, 52:131,	50:1012, 50:1016, 50:1038, 50:1042, 219
52:134, 53:7, 07:99, 55:3, 55:4,	<code>\UseOneTimeHookWithArguments</code> 08:2827, 204
55:37, 55:47, 55:304, 55:306, 07:697,	<code>\usepackage</code> .. 50:676, 50:738, 50:1612, 208
07:1797, 07:1801, 07:1855, 07:1856,	<code>\UseRawInputEncoding</code> 57:381, 57:437, 57:484
07:1859, 07:1862, 07:1876, 07:1903,	<code>\UseSocket</code> 10:182, 10:209, 35:124, 35:132,
07:2040, 07:2360, 07:2361, 07:2364,	35:137, 54:498, 54:610, 54:614,
07:2367, 07:2571, 08:7, 08:655,	54:616, 54:638, 54:710, 54:714, 339
08:1365, 08:1436, 08:1483, 08:1748, 291	<code>\UseStructureName</code> .....
<code>\use_none:nn</code> .....	1264
..... 08:2088, 08:2129, 28:299,	<code>\UseStructureName</code> .....
28:349, 07:1149, 07:2034, 07:2319,	55:82, 55:265
07:2320, 07:2323, 07:2326, 07:2600	<code>\UseTaggingSocket</code> .....
<code>\use_none:nnn</code> ... 08:2094, 07:899,	1263
07:2028, 07:2317, 07:2759, 07:3176,	<code>\UseTaggingSocket</code> .....
07:3182, 07:3193, 07:3199, 08:761, 176	... 17:45, 35:133, 54:494, 54:618,
<code>\use_none:nnnn</code> 08:2971, 07:2022, 07:2574	54:915, 54:930, 55:26, 55:129,
<code>\use_none:nnnnn</code> .....	55:156, 55:354, 55:390, 55:405, 1188
..... 08:1867, 08:1985, 07:2016	<code>\UseTemplate</code> .....
<code>\use_none:nnnnnn</code> .....	11:93, 11:1193, 360
07:2010	<code>\UseTextAccent</code> .....
<code>\use_none:nnnnnnn</code> .....	21:167,
07:2004	21:168, 21:206, 33:74, 33:75, 33:77,
<code>\use_none:nnnnnnnnn</code> .....	33:120, 33:122, 33:900, 33:1085,
..... 08:1867, 08:1985, 08:1365	33:1086, 33:1088, 33:1089, 1328
<code>\use_none_delimit_by_q_recursion-</code>	<code>\UseTextSymbol</code> .....
<code>stop:w</code> .....	21:168, 21:204,
07:344	33:73, 33:316, 33:899, 33:968, 1346
<code>\use_none_delimit_by_q_stop:w</code> ...	<code>\usetikzlibrary</code> .....
..... 07:2535, 07:2554, 07:2558	208
<code>\usebox</code> .....	<code>\ushape</code> .....
40:195	1347
<code>\usecounter</code> .....	
39:256, 39:269	
<code>\UseExpandableTaggingSocket</code> .....	
1264	
<code>\UseExpandableTaggingSocket</code> . 55:26, 1274	
<code>\usefont</code> 21:1598, 24:81, 24:345, 24:750,	
29:823, 33:7, 33:577, 37:583, 1339	
<code>\UseHook</code> 08:2827, 08:2945, 09:307, 09:575,	
09:578, 20:335, 20:341, 20:346,	
20:357, 20:396, 20:400, 20:403,	
26:146, 28:413, 29:342, 29:353,	
29:365, 29:375, 29:396, 29:403,	
29:416, 29:423, 29:482, 29:487,	
29:492, 29:497, 29:747, 29:779,	
29:794, 37:250, 37:262, 37:265,	
37:353, 37:357, 37:370, 37:373,	

## V

<code>\v</code> .....	21:258, 21:408,
21:494, 21:615, 21:616, 21:617,	
21:621, 21:623, 21:626, 21:628,	
21:630, 21:636, 21:642, 21:643,	
21:644, 21:648, 21:650, 21:653,	
21:655, 21:657, 21:663, 21:779,	
21:1271, 21:1351, 21:1352, 21:1353,	
21:1354, 21:1363, 21:1364, 21:1397,	
21:1398, 21:1403, 21:1404, 21:1415,	
21:1416, 21:1423, 21:1424, 21:1427,	
21:1428, 21:1450, 21:1451, 21:1452,	
21:1453, 21:1454, 21:1455, 21:1456,	
21:1457, 21:1458, 21:1459, 21:1460,	

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=ltterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfssscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=lt pictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=lthyphen.dtx, 57=ltfinal.dtx

	21:1469, 21:1470, 21:1471, 21:1472,	\vglue	02:376
	21:1475, 21:1476, 33:129, 33:159	\vline	41:366
\vadjust	18:38, 18:60, 18:72,	\voffset	02:282
	18:101, 18:108, 18:388, 18:404,	\vphantom	21:520, 21:536, 38:75
	18:422, 18:438, 45:201, 45:223, 416	\vrule	18:528,
\valign	33:65, 33:891		21:313, 21:315, 21:525, 21:541,
\value	525		26:191, 30:569, 30:570, 30:572,
\value	22:14,		30:573, 40:204, 40:206, 40:282,
	22:16, 22:48, 22:85, 36:236, 47:9, 1307		40:289, 40:550, 40:603, 40:610,
\varbigtriangledown	30:373, 30:376		41:186, 41:219, 41:347, 41:366,
\varbigtriangleup	30:374, 30:375		42:227, 42:299, 42:302, 42:324,
\varepsilon	19:15, 30:302		42:333, 42:350, 42:359, 42:383,
\varphi	30:307		42:391, 42:406, 42:413, 42:564,
\varpi	30:304		42:577, 42:725, 42:781, 54:2427,
\varrho	30:305		54:2886, 54:2929, 54:2959, 02:380, 1379
\varsigma	30:306	\vsize	1342
\vartheta	30:303	\vskip	414
\vbadness	53:212, 53:214,	\vspacer	18:377, 18:447, 18:448, 18:449
	53:263, 53:265, 54:2909, 02:189, 1156	\vsplit	54:387, 54:434, 54:2911, 1031
\vbox	1181		
vbox commands:		W	
\vbox_set:Nn	48:76	\wedge	30:377, 30:379
\vbox_set_split_to_ht:NNn	48:109	\whatsit	04:194, 41
\vbox_set_to_ht:Nnn	53:215, 53:266	\widehat	30:538
\vbox_to_zero:n	53:326	\widetilde	30:537
\vbox_unpack:N	48:84, 48:97,	\widowpenalty	24:764, 02:196
	48:98, 48:421, 48:453, 53:226, 53:276	\width	40:30, 1327
\vdash	30:415	\wlog	04:6, 04:7, 04:8, 04:54,
\vdots	30:521		37:47, 37:112, 50:414, 02:40, 57:60,
\vec	30:535		57:738, 02:99, 02:170, 01:84, 1317
\vector	14:269, 42:233, 42:816, 42:833	\wp	30:323
\vee	30:378, 30:380	\wr	30:393
\verb	37:577, 37:593, 37:606, 37:620,	\write	1384
	37:632, 37:638, 37:644, 37:657,		
	37:669, 37:674, 37:682, 37:688,	X	
	37:698, 37:703, 37:716, 37:718, 1309	\x	03:96, 03:99, 24:396, 24:397, 57:330, 57:332
\verb*	1359	\xdef	1306
\verbatim(env.)	37:571	\XeTeXcharclass	24:737, 57:39,
\verbatim	37:571		57:47, 57:54, 57:67, 57:73, 57:82, 57:89
\verbatim*(env.)	37:586	\XeTeXcharclassCL	57:173
\verbvisiblespace		\XeTeXcharclassCM	57:177
	37:577, 37:579, 37:593, 37:598,	\XeTeXcharclassEX	57:174
	37:608, 37:612, 37:622, 37:626, 1359	\XeTeXcharclassID	57:171
\Vert	30:582, 30:584	\XeTeXcharclassIS	57:175
\vert	30:587	\XeTeXcharclassNS	57:176
\vfil	33:66, 33:69,	\XeTeXcharclassOP	57:172
	33:892, 33:895, 42:565, 42:577,	\XeTeXcharglyph	21:1058
	53:399, 53:411, 54:154, 54:181,	\XeTeXdashbreakstate	57:273
	54:199, 54:417, 54:464, 54:610,	\XeTeXglyph	21:1058
	54:913, 54:981, 54:1040, 02:386, 1203	\XeTeXintercharclasses	57:167, 57:200
\vfll	1204	\XeTeXinterchartoks	
\vfllneg	02:386		57:168, 57:182, 57:183,
\vfuuzz	49:134, 49:141, 53:211,		57:184, 57:185, 57:186, 57:187,
	53:213, 53:262, 53:264, 02:266, 1156		57:188, 57:189, 57:190, 57:191,

**File Key:** 01=ltmdirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx, 06=ltdefs.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx, 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx, 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx, 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx, 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx, 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx, 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx, 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx, 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx, 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx, 56=ltxyphen.dtx, 57=ltfinal.dtx

57:192, 57:193, 57:194, 57:195,  
 57:196, 57:201, 57:206, 57:207,  
 57:208, 57:209, 57:210, 57:211,  
 57:212, 57:213, 57:214, 57:215,  
 57:216, 57:217, 57:218, 57:219, 57:220  
 \XeTeXmathcode ..... 57:161, 57:530  
 \XeTeXrevision ..... 57:41  
 \XeTeXuseglyphmetrics ... 57:270, 57:272  
 \XeTeXversion ..... 29:706, 57:41  
 \Xi ..... 30:312  
 \xi ..... 30:292  
 xpos ..... 36:244, 819  
 \xpt ..... 1304  
 \xspaceskip ..... 02:297  
 \xtxHanGlue ..... 57:180, 57:204,  
 57:212, 57:213, 57:214, 57:215,  
 57:216, 57:217, 57:218, 57:219, 57:220  
 \xtxHanSpace ... 57:181, 57:205, 57:206,  
 57:207, 57:208, 57:209, 57:210, 57:211  
  
**Y**  
 \y ..... 03:97, 03:99  
 \year ..... 03:11, 03:14, 01:169,  
 50:1306, 50:1439, 50:1528, 02:261  
 ypos ..... 36:244, 819  
  
**Z**  
 \Z ..... 57:252, 57:526, 57:547  
 \z ..... 57:243, 57:527, 57:538  
 \zetaeta ..... 30:284

**File Key:** 01=ltldirchk.dtx, 02=ltplain.dtx, 03=ltvers.dtx, 04=ltluatex.dtx, 05=ltexpl.dtx,  
 06=ltdefns.dtx, 07=ltcmd.dtx, 08=lthooks.dtx, 09=ltcmdhooks.dtx, 10=ltsockets.dtx,  
 11=lttemplates.dtx, 12=ltalloc.dtx, 13=ltcntrl.dtx, 14=lterror.dtx, 15=ltpar.dtx,  
 16=ltpara.dtx, 17=ltmeta.dtx, 18=ltspace.dtx, 19=ltlogos.dtx, 20=ltfiles.dtx,  
 21=ltoutenc.dtx, 22=ltcounts.dtx, 23=ltlength.dtx, 24=ltfssbas.dtx, 25=ltfssaxes.dtx,  
 26=ltfssstrc.dtx, 27=ltfsscmp.dtx, 28=ltfssdcl.dtx, 29=ltfssini.dtx, 30=fontdef.dtx,  
 31=preload.dtx, 32=ltfntcmd.dtx, 33=lttextcomp.dtx, 34=ltpageno.dtx, 35=ltxref.dtx,  
 36=ltproperties.dtx, 37=ltmiscen.dtx, 38=ltmath.dtx, 39=ltlists.dtx, 40=ltboxes.dtx,  
 41=lttab.dtx, 42=ltpictur.dtx, 43=ltthm.dtx, 44=ltsect.dtx, 45=ltfloat.dtx,  
 46=ltidxglo.dtx, 47=ltbibl.dtx, 48=ltmarks.dtx, 49=ltpage.dtx, 50=ltclass.dtx,  
 51=ltkeys.dtx, 52=ltfilehook.dtx, 53=ltshipout.dtx, 54=ltoutput.dtx, 55=lttagging.dtx,  
 56=lthyphen.dtx, 57=ltfinal.dtx